

platted

APR 20 1910

4-683.

MINERAL SURVEY No. 2755

LOT No. _____

Arizona Land District.

FIELD NOTES

OF THE SURVEY OF THE MINING CLAIM OF

Leadville Mining Co.

KNOWN AS THE

King Solomon
Tulquoise Mining District,

Cochise County, Arizona

Section Approx., Township 19 S, Range 25 E, undivided

Surveyed under instructions dated April 4, 1910

by John A. Rockfellow
U. S. Mineral Surveyor.

Location

Claim located See Notation, 1910

Survey commenced April 10, 1910

Survey completed April 16, 1910

6-322

Attorneys for Claimants
Pickett, Bowman & Pickett,
Tombstone Ariz.

Feet.

SURVEY NO. 2755.

KING SOLOMON LODE.

Beginning at Cor. No. 1, the N.W. Cor. of location, a pine post 4 ins. square, 3 ft. above ground, in a mound of stone, scribed NWC-KS, 1-2755. Also scribed NEC-M.

Whence:

U.S.L.M. No. 1319, brs. S 43°05'W- 408.2 ft.

The S.W. Cor., Cor. No. 1, Poor Man lode, Survey No. 2689, a post scribed 1/2689 PML, brs. N 60° 06'W - 62.45 ft.

A cross (x) and BR 1-2755 chiseled on limestone bedrock exposing 48x18 ins. brs. N 72°05'E, 13.6 ft.

Center of a shaft 12 ft. deep brs. S 87°W, 19 ft.

Thence N 49°28'E. Va. 13°15'.E

33.0 A stone monument.

54.99 Intersect line 1-4 Poor Man lode, Survey No. 2689, at N 87°15'E, 96.04 ft. from Cor. No. 1.

140.0 Grade of Mexico and Arizona R.R., on curve NNE.

300. N. Center End identical with location, a cross (x) and NOE-KS chiseled on limestone bedrock exposing 24x20 ins., also 2755. This point is witnessed by a monument of stone alongside.

600. To Cor. No. 2, identical with location, a pine post 4 ins. square, 3 ft. above ground, in a mound of stone, scribed NEC-KS, 2-2755.

Whence:

W

A cross (x) and BR 2-2755 chiseled on limestone bedrock, brs. N 28°50'E, 4.3 ft.

A cross (x) and br 2-2755 chiseled on limestone bedrock brs. S 76°52'E, 11.8 ft.

Thence S 40°20'E. Va. 13°15'E.

421.36 Intersect line 1-4 Poor Man lode, Survey No. 2689, at N 87°15'E, 783.74 ft. from Cor. No. 1.

422.8 NW Cor. Moro lode a post in a mound of stone, scribed NWC-M.

- Feet.
1321.9 A post marked in pencil Mountain View.
1500. To Cor. No. 3, identical with location and with Cor. No. 2
and Cor. No. 1 April Fool lode, Sur. No. 2765
Maid of Sunshine lode, Survey No. 2587, a pine
post, 4 ins. square, 3 ft. above ground in a
mound of stone scribed SEC-KS, 3-2755. Also
scribed N Cor. M.S. 2-2587. Also W Cor. A.F. 1-2765.
Also SWC.MV. M
- Whence:
- A cross (x) and BR 3-2755 chiseled on limestone
bedrock brs. N 19°27'E, 42.5 ft.
No other rock bearings available.
The SW Cor. of post at gallows frame April Fool
Mine Shaft brs. N 67°27'E, 88.2 ft.
Thence S 49°28'W. Va. 13°10'E.
- 28.0 Center of grade of a siding Mexico & Colorado R.R.
brs. NW and SE.
The S. Center End monument identical with the N.
Center End of Maid of Sunshine lode, Survey No.
2587 has been entirely covered with earth in making
a fill by the Mexico & Colorado R.R.
Hence at
- 146.8 Establish a witness monument. Set a pine post 4 ins.
square, 4 ft. long, 5 ins. in the ground to bedrock
in a mound of stone, scribed WC to SCE-KS 2755.
- 195.3 Intersect line 2-3 Germahia No. 1 lode, Survey No. 2688
at S 40°06'E, 438.8 ft. from Cor. No. 2.
- 223.8 Center of track of Mexico & Colorado R.R. on curve
Southwesterly.
300. Point for S.C.E. whence W.C., heretofore described brs.
N 49°28'E, 153.2 ft.
600. To Cor. No. 4, identical with location and with Cor. No. 1
Maid of Sunshine lode, Survey No. 2587. A pine
post 4 ins. square, 3 ft. above ground, in a mound
of stone, scribed SWC-KS. 4-2755. Also scribed
WCOR M.S. 1-2587.

Feet.

Whence:

A cross (x) and BR 4-2755 chiseled on a quartzite rock 30x24x18 ins. brs. S 28°37'W, 51.1 ft.

A cross (x) and BR 4-2755 chiseled on a quartzite rock 15x10x4 ins. brs. S 83°00'E, 60.7 ft.

A post scribed 1-2688 G. No. 1 brs. S 49°53'W, 5.8 ft.

Thence N 40°20'W. Va. 13°15'E.

6.2 Intersect line 1-2 Germania No. 1 lode at N 2°47'E, 8.5 ft from Cor. No. 1, and S 24°47'W, 594.6 ft. from Cor. No. 2.

71.4 Center of track Mexico & Colorado R.R. on curve course Southwesterly.

412. Stone monument on line contains notice of location of McKean lode claim.

1500. To Cor. No. 1, the place of beginning.

Acres.

A R E A . King Solomon lode,

20.661

Area in conflict with Poor Man lode,

Survey No. 2689, -----2.635 A.

Area in conflict with Germania No. 1

lode, Survey No. 2688, -----2.067 A.

L O C A T I O N .

This claim is located in Turquoise Mining District, Cochise County, Arizona, in Tp 19 S R 25 E unsurveyed. Probably close to E. B'd'y Coronado Forest Reserve, unsurveyed.

Lode Line

The presumed course of the lode or vein is N 40°20'W, 1500 ft. from S.C. End to N. C. End.

A D J O I N I N G C L A I M S

---, on the North, Poor Man lode, Survey No. 2689,

P. B. Warnekros claimant.

On the East, More lode, unsurveyed,

L.D. Shattuck, claimant.

Mountain View lode, unsurveyed,

Brown & Co. Claimants.

On the South, Maid of Sunshine lode, Survey No. 2587,

Leadville Mining Co. claimants; *and Harmon*

On the West, McKean lode, unsurveyed,

Swattling & Smith claimants.

EXPENDITURE OF FIVE HUNDRED
DOLLARS.

I certify that the value of labor and improvements made on this claim by the claimant or its grantors is not less than five hundred dollars and the said improvements consist of:-

No. 1) Discovery shaft the center of W side of which
brs. from the S. Center End N 40°20'W, 714 ft.
Shaft caved, now 10x8 ft, 5 ft. deep.

Value, ----- \$50.

No. 2.) A shaft the center of which brs. from a point
on lode line N 40°20'W, 679 ft. N 49°40'E, 17ft.
Shaft 8x6 ft. 10 ft. deep ,

Value, ----- \$100.

No. 3.) A tunnel or cross cut driven from the April
Fool shaft, (A bearing which is given in des-
cribing Corner No. 3,) first course S 53°45'W,
58 ft. from West Cor. of shaft, thence S 79°22'W,
515 ft. to face entering the end of King Solomon
lode at S 49°28'W, approximately 15 ft. ^{from Cor No. 3} and ex-
tending within the boundaries of the lode, approx-
imately 450 ft. Said tunnel or cross cut is at a
depth of about 500 ft. below the surface, is
6½x5 ft. NOTE: This measurement was made by
me Jan. 17, 1910, At date of survey for patent.
The tunnel was filled with water.

Value at \$12. per ft., ----- \$5400.

No. 4.) A shaft which bears from WC to SCE N 53°00'W,
282 ft. Shaft partly filled with rubbish now
7x4 ft 10 ft. deep,

Value, ----- \$100.

From a point on line 4-1 at N 40°20'W, 310.2 ft.
 No. 5.) A shaft which bears N 1°30'E, 197 ft. Shaft
 8x5 ft. ⁸/₁ deep.

Value, ----- \$80.

No. 6.) A shaft which bears N 6°00'W, 197 ft.
 Shaft 6x4 ft. 4 ft. deep, formerly deeper,

Value, ----- \$30.

No. 7.) A cut the mouth of ~~which~~ brs. N 23°10'W, 254 ft.
 Cut 18x4 ft. 6 ft. face, course S.Westerly,

Value, ----- \$50.

Total value of improvements, ----- \$5810.

OTHER IMPROVEMENTS.

A shaft which brs. from a point on line 4-1 at
 N 40°20'W, 423 ft.

N 49°40'E, 75 ft.

Shaft 5¹/₂x4 ft., 18 ft. deep.

Claimant unknown.

INSTRUMENT.

This survey was made with a Young & Sons mountain transit,
 No. 6855, provided with Smith Solar Attachment. The
 courses were deflected with true meridian as obtained
 by direct solar observations. The measurements were made
 with 500 and 50 ft. steel tapes.

Any discrepancies between this survey and location
 notice are due to errors in the latter.

The disagreement between these field notes and those
 of other adjoining surveys are due to errors in the latter.

Tombstone, Arizona.
 April 18, 1910.

John A. Rockwell

 U.S. Mineral Surveyor.

FINAL OATHS FOR SURVEYS.

LIST OF NAMES.

A list of the names of the individuals employed by John A. Rockefeller
 United States Mineral Surveyor, to assist in running, measuring, and marking the lines, corners, and
 boundaries described in the foregoing field notes of the survey of the mining claim of _____
Leadville Mining Co
 known as the King Solomon
 and showing the respective capacities in which they acted.

L. D. Mars _____, Chainman.
 _____, Chainman.
 _____, Axman.
 _____, Flagman.

FINAL OATHS OF ASSISTANTS.

We, L. D. Mars
 and John A. Rockefeller, do solemnly swear that we assisted John A. Rockefeller
Rockefeller, United States Mineral Surveyor, in marking the corners and surveying
 the boundaries of the mining claim of Leadville Mining
Company
 known as the King Solomon
 represented in the foregoing field notes as having been surveyed by said mineral surveyor and under his
 direction; and that said survey has been in all respects, to the best of our knowledge and belief, faithfully
 and correctly executed, and the corner and boundary monuments established according to law and the instruc-
 tions furnished by the United States Surveyor-General for Arizona

L. D. Mars _____, Chainman.
 _____, Chainman.
 _____, Axman.
 _____, Flagman.

Subscribed and sworn to by the above-named persons before me this 18

day of April, 1910

Samuel I. Rockefeller
Notary Public

My Commission expires
Oct 15 1912

9
APR 4-1910

Amended Notice of Location.

Notice is hereby given that the King Solomon Lode mining claim was located by William Holmes on the 12th. day of April 1897, said claim is 1500 feet in length and 600 feet wide, that is 300 feet wide on each side of the point of Discovery and the North Center end monument of the claim is distant in a Northwesterly direction 785 feet from the point of Discovery, a shaft at which this notice is posted, and the opposite center end monument a post in a mound of stone is distant 715 feet from said point of Discovery and the general course of the claim is N.40°20' W.

This claim is situate in the Turquoise Mining District, Cochise County, Territory of Arizona.

From S.W. Corner corner No.4 Hard Up lode (patented) Survey No. 1970. bears S. 49°54' W. 194.5 ft. and from the N.W. Corner the S.W. Cor. of Poorman Lode on line 3-4 George Lode Survey No.1319 bears N. 60°45' W. 615 ft.

The boundaries of the claim are as follows: Beginning at a post in a mound of stone in a southeasterly direction 715 feet from the Discovery shaft, thence S. 49°28' W. 300 ft. to a post in a mound of Stone at the S.W. Corner thence N. 40°20' W. 1500 ft. to the N.W. Corner thence N. 49°28' E 300 ft. to the North center end, a cross (x) chiseled on limestone, witnessed by a monument alongside, thence same course 300 ft. to the N.E. corner, thence South 40°20' E 1500 ft. to the S.E. Cor., thence S. 49°28' W. 300 ft. to the place of beginning.

This is an amended notice of location of the King Solomon lode, located April 12th. 1897 by Wm. Holmes and recorded in Book No.14, at page No.245 Records of Mines of Cochise County and is made to better describe said claim.

Posted on the ground this 23rd day of Sept. 1908.

Leadville Mining Co. By Wm Holmes Mgr.


Present owner.

Filed and recorded at request of J.A.Rockfellow, Sep.24, 1908,
at 11:20 A.M. in Book No. 40 Record of Mines at Page 217.

TERRITORY OF ARIZONA, |
 | SS.
COUNTY OF COCHISE. |

I, C.A.McDonald, County Recorder in and for the
County and Territory aforesaid DO HEREBY CERTIFY that I have com-
pared the annexed and foregoing copy with the original Amended
Location Notice of the KING SOLOMON Mining Claim filed for record in
my office on the 24th day of September, A.D. 1908 and recorded in
Book No. 40 Record of Mines at Page 217, and that the same is a full,
true and correct copy of said original and of the whole thereof.

Given under my hand and seal of office this 2nd day of April,
A.D. 1910.



County Recorder.

U. S. SURVEYOR-GENERAL'S FINAL CERTIFICATE ON FIELD NOTES.

Department of the Interior,

OFFICE OF U. S. SURVEYOR-GENERAL,

Phoenix, Arizona

June 7, 1910, 190

I, U. S. Surveyor-General for District of Arizona

do hereby certify that the foregoing transcript of the Field Notes, return and approval of the survey of the mining claim of Leadville Mining Co.

known as the King Solomon

situate in Turquoise

Mining District, Cochise County, Arizona

in Section, Township No. 19 S., Range No. 25 E. Unsur., and

designated as Survey No. 2755, has been correctly copied from the originals on file in

this office; that said Field Notes furnish such an accurate description of said mining claim as will, if incorporated into a patent, serve fully to identify the premises, and that such reference is made therein to natural objects or permanent monuments as will perpetuate and fix the locus thereof.

And I further certify that five hundred dollars' worth of labor has been expended or improvements made upon said mining claim by claimant or its grantors, and that said improvements consist of 5 shafts, 1 cut and 1 tunnel, total value \$5810.00

and that no portion of said labor or improvements has been included in the estimate of expenditures upon any other claim.

I further certify that the plat thereof, filed in the U. S. Land Office at Phoenix Arizona is correct and in conformity with the foregoing Field Notes.

Frank S. Ingalls,

United States Surveyor-General for Arizona.

4-687.

SURVEYOR-GENERAL'S CERTIFICATE OF APPROVAL OF FIELD
NOTES AND SURVEY OF MINING CLAIM.

Department of the Interior,

Office of U. S. Surveyor-General,

Phoenix, Arizona.

June 7, 1910, 190

I, U. S. Surveyor-General for District of Arizona

do hereby certify that the foregoing and hereto attached Field Notes and Return of the Survey of the
Mining Claim of Leadville Mining Co.

....., known as the

King Solomon

situate in Turquoise Mining District,

Cochise County, Arizona

in Section, Township No. 19 S., Range No. 25 E. Unsur.

....., designated as Survey No. 2755

executed by John A. Rockfellow, U. S. Deputy Mineral

Surveyor, April 15-16, 1910, 190, under my instructions dated

April 4, 1910, 190, have been critically examined and the necessary cor-

rections and explanations made, and the said Field Notes and Return, and the Survey they describe,

are hereby approved. A true copy of the copy of the location certificate filed by the applicant for

survey is included in the field notes.

Frank S. Lyman

U. S. Surveyor-General for Arizona.