

MINERAL SURVEY No. 3510

ARIZONA Land District.

FIELD NOTES

OF THE SURVEY OF THE MINING CLAIM OF

Alexander Rossi, William Reid, Julia Baxter, Michael Irish, and the estate of Charles W. Baxter, deceased, Phil C. Brannen, administrator.

KNOWN AS THE

OREGON and THE PRIDE lodes

Pima Mining District,

Pima County, Arizona

Section 31/6, Township 17 S. 18 S., Range 13 E. 13 E.; G. & S. R. B. & M.

Surveyed under instructions dated April 27, 1918.

by Paul E. Fernald U. S. Mineral Surveyor.

Claim located See location notices, 19

Survey commenced July 2, 1918

Survey completed July 6, 1918

Address of claimant's Attorney; Geo. O. Hilzinger, Box 67, Tucson, Arizona.

- DATES OF AMENDED LOCATIONS -

Feet

## U. S. MINERAL SURVEY NO. 3510.

## THE PRIDE lode.

Beginning at Cor. No. 1, a 1 inch iron pipe 4 ft. long with claw base, set  $1\frac{1}{2}$  feet in the ground and surrounded by monument of stones. Brass cap on pipe stamped U. S. Mineral Survey No. 3510 1-Pride. Whence

The N. W. Cor. of Section 6, T. 18 S., R. 13 E., G. & S.R.B. & M., bears N.  $86^{\circ} 47'$  W. 657.20 feet.

Thence N.  $7^{\circ} 06'$  E.

- 37.16 Intersect line between Sec. 31, T. 17 S., R. 13 E., and Sec. 6, T. 18 S., R. 13 E., at East 660.76 ft. from the Cor. of Secs. 1, 6, 31 and 36, and West 1891.46 ft. from the point for  $\frac{1}{4}$  Cor. between Secs. 6 and 31.
- 45.00 West End Center, monument of stones 3 feet high.
- 116.00 Crosses road running East.
- 345.00 Cor. No. 2, on line 1-2 Standard Copper lode, Survey No. 2643, at point N.  $7^{\circ} 04'$  E. 345.06 feet from Cor. No. 1. A 1 inch iron pipe  $3\frac{1}{2}$  feet long with claw base, set  $1\frac{1}{2}$  feet in the ground and surrounded by monument of stones. Brass cap on pipe stamped U. S. Mineral Survey No. 3510, 2-Pride. Whence
- Cor. No. 2, Standard Copper lode, Survey No. 2643, bears N.  $7^{\circ} 04'$  E. 254.46 feet.
- Thence S.  $65^{\circ} 58'$  E.
- 737.50 North Side Center, monument of stones 3 feet high.
- 750.07 Intersect line between Secs. 6 and 31, at East 1383.85 ft. from the Cor. of Secs. 1, 6, 31 and 36, and West 1168.37 ft. from the point for  $\frac{1}{4}$  Cor. between Secs. 6 and 31.
- 1475.13 Cor. No. 3, a 1 inch iron pipe,  $3\frac{1}{2}$  feet long with claw base, set  $1\frac{1}{2}$  feet in the ground and surrounded by monument of stones. Brass cap on pipe stamped U. S. Mineral Survey No. 3510, 3-Pride.

Feet	Thence S. 7° 06' W.
300.00	East End Center, monument of stones 3 feet high.
345.00	Cor. No. 4, identical with the S. E. Cor. Bloomfield lode, unsurveyed, and with Cor. No. 4, Copper Queen lode, Survey No. 2643, identical with Cor. No. 1, Copper Glance lode, Survey No. 2643. A 1 inch iron pipe $3\frac{1}{2}$ feet long, with claw base, set $1\frac{1}{2}$ feet in the ground and surrounded by monument of stones. Brass cap on pipe stamped U.S. Mineral Survey No. 3510,4-Pride.
	Thence N. 65° 58' W.
236.00	Crosses Twin Buttes R.R. Track, running S.-SE.
460.00	Crosses road running S.-SE.
492.00	Crosses road running SE.
737.63	South Side Center, monument of stones 3 feet high.
960.00	Crosses road running East.
1302.00	Crosses Twin Buttes R.R. track, running E.-NE.
1474.92	Cor. No. 1, Standard Copper lode, Survey No. 2643, identical with Cor. No. 1 Copper King lode, and Cor. No. 1 Copper Queen lode, same survey, and S. W. Cor. Bloomfield lode, unsurveyed, whence Cor. No. 2, Copper King lode, Survey No. 2643, identical with Cor. No. 2 Copper Queen lode, same survey, bears S. 7° 04' W. 599.09 feet. Cor. No. 4, Standard Copper lode, identical with Cor. No. 4, Copper King lode, both Survey No. 2643, bears N. 75° 16' W.
1475.13	Cor. No. 1, the point of beginning. ----- OREGON lode. Beginning at Cor. No. 1, identical with Cor. No. 3, The Pride lode, this survey, heretofore described. Brass cap on pipe stamped 1-Oregon, additionally for this lode, whence

Feet	
	The N. W. Cor. of Section 6, T. 18 S., R. 13 E., G. & S. R. B. & M., bears N. 81° 47' W. 2067.28 feet.
	Thence S. 7° 06' W.
300.00	West End Center, monument of stones 3 feet high.
345.00	Cor. No. 2, identical with Cor. No. 4, The Pride lode, this survey, heretofore described, with the S. W. Cor. of Hamilton lode, unsurveyed, and with Cor. No. 1 Copper Glance lode, Survey No. 2643. Brass cap on pipe stamped 2-Oregon, additionally for this lode.
	Thence S. 59° 10' E.
48.00	West side adobe house.
65.00	East side adobe house.
541.00	Crosses spur, Twin Buttes R.R., running W.- SW.
578.00	Crosses track Twin Buttes R.R., running W.- SW.
603.00	Crosses spur Twin Buttes R.R., running W.- SW.
699.83	South Side Center, monument of stones 3 feet high.
1399.66	Cor. No. 3, identical with the S. E. Cor. of Hamilton Lode, unsurveyed, and with Cor. No. 2, Copper Glance lode, and Cor. No. 1, Bullion No. 2 lode, both Survey No. 2643. A 1 inch iron pipe 3½ feet long, with claw base, set 1½ feet in the ground and surrounded by monument of stones. Brass cap on pipe stamped U. S. Mineral Survey No. 3510, 3-Oregon.
	Thence N. 7° 06' E.
227.18	East End Center, monument of stones 3 feet high.
527.18	Cor. No. 4, on line 4-1 Bullion No. 2 lode, Survey No. 2643. A 1 inch iron pipe 3½ feet long with claw base, set 1½ feet in the ground and surrounded by monument of stones. Brass cap on pipe stamped U. S. Mineral Survey No. 3510, 4-Oregon, whence
	Cor. No. 4, Bullion No. 2 lode, Survey No. 2643, bears N. 7° 06' E. 71.93 feet.

Feet	Thence N. 66° 20' W.
196.00	Crosses track Twin Buttes R.R., running E.- NE.
668.39	North Side Center, monument of stones 3 feet high.
1336.78	Cor. No. 1, the point of beginning.

-----

Magnetic variation at all corners 14 degrees East.

No natural bearing objects available from any corner of this survey.

All corners of this survey are identical with the respective corners of location.

-----

LODE LINES.

As near as can be determined from the present state of development, the veins of locations embraced in this survey extend as follows from their respective discovery points;

The Pride lode, N. 65° 58' W. 462 ft., and S. 65° 58' E. 1013.13 ft.

Oregon lode, N. 66° 20' W. 910.78 ft., and S. 60° 20' E. 426 ft.

-----

LOCATION.

This survey is located in the SW $\frac{1}{4}$  of Section 31, T. 17 S., R. 13 E., and the N $\frac{1}{2}$  of Section 6, T. 18 S., R. 13 E., G. & S.R. B. & M., in the Pima Mining District, Pima County, Arizona.

-----

AREAS.

The Pride lode, total area,	11.176 Acres
Conflict with Standard Copper lode, Survey No. 2643,	.001
Oregon lode, total area,	12.827 "

-----

IMPROVEMENTS.

I certify that the value of labor and improvements

made upon or for the benefit of each of the locations embraced in this survey, by the claimants or their grantors, is not less than Five Hundred Dollars, and that such improvements consist of:

The Pride lode.

No. 1, discovery shaft, on center line 462 feet from the West End Center, 4 x 6 - 97 feet deep.

Value, \$970.00

No. 2, shaft 4 x 6 - 8 feet deep, center of which bears S. 64° 38' W. 78 feet from Cor. No. 3.

Value, \$ 40.00

No. 3, shaft 4 x 6 - 8 feet deep, center of which bears S. 37° 30' W. 45 feet from Cor. No. 3.

Value, \$ 40.00

Oregon lode.

No. 1, discovery shaft, on center line 426 feet from the East End Center, 6 x 6 - 8 feet deep present depth. Shows evidence of filling, original depth unknown.

Value, \$ 60.00

No. 2, shaft 5½ x 7½ - 39 feet deep, center of which bears S. 64° 07' E. 242.5 feet from Cor. No. 1.

Value, \$670.00

No. 3, cut running into this location from the north. Center of cut is at point 1227 line 4-1, whence it runs south 20 feet, 4 feet wide, 8 feet deep.

Value, \$130.00

No. 4, shaft 4 x 6 - 7 feet deep, center of which bears S. 49° 15' E. 144 feet from Cor. No. 1.

Value, \$ 35.00

-----  
OTHER IMPROVEMENTS.

Oregon lode.

Adobe house 33 ft. NE by 17 ft. SE. Point at west side of house 14 ft. from N. W. Cor. is at point 48,

line 2-3.

Discovery shaft Hamilton lode, unsurveyed, 4 x 7 - 7 feet deep, the center of which bears N. 9° 07' W. 140 feet from Cor. No. 3. -----

#### INSTRUMENT.

This survey was made with Buff & Buff special transit No. 7905. Courses were deflected from the true meridian as determined by direct solar observations. Distances were measured with 350 and 100 foot steel tapes.

#### ADJOINING AND CONFLICTING CLAIMS.

The Pride lode, this survey, conflicts slightly with the Standard Copper lode, Survey No. 2643, on the west, is joined by the Copper Queen lode, Survey No. 2643, on the south, and approximately its total area is in conflict with the Bloomfield lode, unsurveyed.

Oregon lode, this survey, is joined by the Copper Glance lode, Sur. No. 2643, on the south, and Bullion No. 2 lode, Survey No. 2643, on the east. It is largely in conflict with Hamilton lode, unsurveyed.

The above mentioned Bloomfield and Hamilton lodes, unsurveyed, are claimed by Manuel Smith, of Tucson, Ariz.

#### REPORT.

The N. W. Cor. of T. 18 S., R. 13 E., G. & S.R.B. & M., is a 1½ inch iron pipe, 8 inches above ground, surrounded by a small monument of stones. I retraced the north and west boundary lines of said township respectively for two miles east and south from said N. W. Corner, but was unable to find any trace of other corners of the public survey. Also retraced the east boundary of Section 6, of said township, but found no trace of public survey corners. Intersection with the line between

Secs. 6 & 31, reported in this survey, have been computed from the record of such line.

Corners of Bloomfield and Hamilton lodes, unsurveyed, are monuments of stone with 4 x 4 posts or laths set therein marked with corner description. Approx. location of these lodes as shown on plat.

Corners of Sur. No. 2643.

Copper King lode;

Cor. No. 1, identical with Cor. No. 1, Standard Copper lode, hereinafter described. Cor. No. 2, identical with Cor. No. 2 Copper Queen lode, hereinafter described. Cor. No. 4, identical with Cor. No. 4 Standard Copper lode, hereinafter described.

Standard Copper lode;

Cor. No. 1, stone 5 inches above ground, scribed X, 2643, S.C.1, J.K.1, C.K.1, on sides facing respective lode. Cor. No. 2, stone 4 inches above ground, scribed X, 2643, S.C.2. Cor. No. 4, stone 5 inches above ground, scribed X 2643, S.C.4, J.K.4, on sides facing respective lodes.

Copper Queen lode;

Cor. No. 1, identical with Cor. No. 1, Standard Copper lode, heretofore described. Cor. No. 2, Lime Rock, 12 inches above ground, scribed X 2643, C.Q.2, C.K.2, on sides facing respective lodes. Large monument of stones  $3\frac{1}{2}$  feet south. Cor. No. 4, stone 5 inches above ground, marked X 2643, C.Q.4, C.C.1, on sides facing respective lodes.

Copper Glance lode;

Cor. No. 1, identical with Cor. No. 4, Copper Queen lode, heretofore described. Cor. No. 2, stone 5 inches above ground, marked X 2643, C.G.2, B.No.2 1, C.B.1, on sides facing respective lodes.

Bullion No. 2 lode;

Cor. No. 1, identical with Cor. No. 2, Copper Glance lode, heretofore described. Cor. No. 4, stone 8 inches above ground, marked X 2643, B No. 2-4.

I have to report the following errors in Survey No. 2643; Copper Queen lode;

Line 1-2, S. 7° 04' W. 599.09 ft. vice S. S. 7° 04' W. 600 ft.

Copper Glance lode; Line 1-2, S. 59° 10' E. 1399.66 ft. vice S. 59° 14' 15" E. 1399.8 ft.

Line 4-1, S. 7° 06' W. 599.11 ft. vice S. 7° 04' W. 600 ft.

The difference between locations embraced in this survey as marked upon the ground, and as described in the respective location notices, is due to error of description in the location notices.

The lines of this survey were run direct upon the ground.

Paul E. Fernald,  
U. S. Mineral Surveyor.

# FINAL OATHS FOR SURVEYS.

## LIST OF NAMES.

A list of the names of the individuals employed by Paul E. Fernald  
 United States Mineral Surveyor, to assist in running, measuring, and marking the lines, corners, and  
 boundaries described in the foregoing field notes of the survey of the mining claim of  
Alexander Rossi, William Reid, Julia Baxter, Michael Irish, and the estate  
of Charles W. Baxter, deceased, Phil C. Brannen, Administrator  
 known as the OREGON and THE PRIDE lodes  
 and showing the respective capacities in which they acted.

James Gorman, *Chainman.*  
 \_\_\_\_\_, *Chainman.*  
 \_\_\_\_\_, *Arman.*  
 \_\_\_\_\_, *Flagman.*

## FINAL OATHS OF ASSISTANTS.

-We, I, James Gorman  
 and \_\_\_\_\_, do solemnly swear that we assisted  
Paul E. Fernald, United States Mineral Surveyor, in marking the corners and surveying  
 the boundaries of the mining claim of Alexander Rossi, William Reid, Julia Baxter,  
Michael Irish, and the estate of Charles W. Baxter, deceased, Phil C. Brannen,  
Administrator.  
 known as the OREGON and THE PRIDE lodes  
 represented in the foregoing field notes as having been surveyed by said mineral surveyor and under his  
 direction; and that said survey has been in all respects, to the best of our knowledge and belief, faithfully  
 and correctly executed, and the corner and boundary monuments established according to law and the instruc-  
 tions furnished by the United States Surveyor-General for Arizona

James Gorman, *Chainman.*  
 \_\_\_\_\_, *Chainman.*  
 \_\_\_\_\_, *Arman.*  
 \_\_\_\_\_, *Flagman.*

Subscribed and sworn to by the above-named persons before me this ninth  
 day of July, 1918

J. J. O'Dowd

(Seal)

Notary Public, Pima Co., Ariz.

My commission expires June 6, 1920.

4-686.

## FINAL OATH OF U. S. MINERAL SURVEYOR.

I, Paul E. Fernald, U. S. Mineral Surveyor,  
do solemnly swear that, in pursuance of instructions received from the United States  
Surveyor General for Arizona, dated  
April 27th, 1918, I have, in strict conformity to the laws of the  
United States, the official regulations and instructions thereunder, and the instructions  
of said Surveyor General, faithfully and correctly executed the survey of the Mining  
Claim of Alexander Rossi, William Reid, Julia Baxter, Michael Irish,  
and the estate of Charles W. Baxter, deceased,  
Phil C. Brannen, Administrator., known as the  
OREGON and THE PRIDE lodes,  
situate in Pima Mining District,  
Pima County, Arizona, in Section  
31, Township No. 17 S, Range No. 13 E., G. & S.R.B. & M.,  
6, Township No. 18 S., Range No. 13 E.,  
and designated as Survey No. 3510, as represented  
in the foregoing field notes, which accurately show the boundaries of said mining claim  
as distinctly marked by monuments on the ground, and described in the attached copy  
of the location certificate, which was received by me from the Surveyor General with  
said instructions, and that all the corners of said survey have been established and per-  
petuated in strict accordance with the law, official regulations and instructions there-  
under; and I do further solemnly swear that the foregoing are the true and original  
field notes of said survey and my report therein, and that the labor expended and  
improvements made upon said mining claim by claimant or their grantors  
are as therein fully stated, and that the character, extent, location, and itemized value  
thereof are specified therein with particularity and full detail, and that no portion of  
said labor or improvements so credited to this claim has been included in the estimate  
of expenditures upon any other claim.

Paul E. Fernald

*U. S. Mineral Surveyor.*

Subscribed and sworn to by the said Paul E. Fernald  
U. S. Mineral Surveyor, before me J. J. O'Dowd, Notary Public,  
Pima County, Arizona, this ninth  
day of July, 1918.

J. J. O'Dowd

(Seal)

Notary Public,  
Pima Co., Ariz.

6-1044

My commission expires June 6, 1920.



OREGON MINING CLAIM.  
NOTICE OF MINING LOCATION,  
Quartz Claim.

TO ALL WHOM IT MAY CONCERN:

This mining claim, the name of which is the OREGON Mining Claim, situate on lands belonging to the United States of America, and in which there are valuable mineral mineral deposits, was entered upon and located for the purpose of exploration and purchase by Hugh Canney & Mike Irish, the undersigned, on the 19th day of April, 1899.

The length of the claim is 700 feet in a Westerly direction and 800 feet in a Easterly direction from the center of the discovery shaft, at which this notice is posted, lengthwise of the claim, together with 300 feet in width of the surface grounds, on each side of the center of said claim.

The general course of the lode deposit and premises is from the East to the West.

The claim is situated and located in the Pima Mining District, in Pima County, in the Territory of Arizona, about  $\frac{1}{2}$  Mile in a Southerly direction from Twin Buttes.

The surface boundaries of the claim are marked upon the ground as follows: Beginning at the Westerly Center End at a point in a Westerly direction 700 feet from the discovery shaft (at which this notice is posted), being in the center of the Westerly end line of said claim; thence southerly 300 feet to a monument of stone, being the S. West corner of said claim; thence Easterly 750 feet to a monument at the center of the south side line of said claim; thence Easterly 750 feet to a monument being at the S. East corner of said claim; thence Northerly 300 feet to a monument at the center of the Easterly end of said claim; thence Northerly 300 feet to a monument, being at the N. East corner of said claim; thence Westerly 750 feet to a monument being at the center of the Northerly side line of said claim; thence Westerly 750 feet to a monument at the N. West corner of said claim; thence southerly 300 feet to the place of beginning.

All done under the provisions of Chapter Six, of Title XXXII, of the Revised Statutes of the United States, and of an Act of the General Assembly of Arizona, entitled "An Act Concerning Mines " approved March 20th, 1895.

Dated and posted on the ground this 19th day of April, 1899.

Witness  
J. A. Sheridan

Locators- Hugh Canney  
Mike Irish

Filed and recorded at request of Michael Irish July 15<sup>th</sup> 1899 at 9 A.M.

Book G.G. Page 399

Chas. A. Shibell,  
County Recorder.

STATE OF ARIZONA, )  
County of Pima. ) ss.

I, R. B. Vinson, County Recorder in and for the County of Pima, State of Arizona, do hereby certify that the above and foregoing is a full, true and correct copy of the Oregon Mining Claim, located on the 19th day of April, A.D. 1899 and situated in the Pima Mining District, Pima Co. Arizona, as appears of record now in my office in Book GG Record of Mines Pages 399.

In Witness Whereof, I have hereunto set my hand and affixed my official seal, at my office in Tucson, this 25 day of March, A.D. 1918.

(Seal)

R. B. Vinson, County Recorder  
of Pima County, Arizona.

U. S. SURVEYOR-GENERAL'S FINAL CERTIFICATE ON FIELD NOTES.

Department of the Interior,

OFFICE OF U. S. SURVEYOR-GENERAL,

Phoenix, Arizona,

June 12, 1919.

I, U. S. Surveyor-General for DISTRICT OF ARIZONA

do hereby certify that the foregoing transcript of the Field Notes, return and approval of the survey of the mining claim of Alexander Rossi, William Reid, Julia Baxter, Michael Irish, and the estate of Charles W. Baxter, deceased, Phil C. Brannen, administrator known as the OREGON and THE PRIDE lodes

situate in Pima

Mining District, Pima County, Arizona

in Section 31 6, Township No. 17 S 18 S., Range No. 13 E. & S. R. 13 E. B. & N. R., and

designated as Survey No. 3510, has been correctly copied from the originals on file in

this office; that said Field Notes furnish such an accurate description of said mining claim as will, if incorporated into a patent, serve fully to identify the premises, and that such reference is made therein to natural objects or permanent monuments as will perpetuate and fix the locus thereof.

And I further certify that five hundred dollars' worth of labor has been expended or improvements made upon each of said mining claims by claimants or their grantors, and that said improvements consist of 6 shafts and 1 cut, total value \$1945.00

and that no portion of said labor or improvements has been included in the estimate of expenditures upon any other claim.

I further certify that the plat thereof, filed in the U. S. Land Office at Phoenix, Arizona, is correct and in conformity with the foregoing Field Notes.

Frank P. Trott

United States Surveyor-General for Arizona.

4-687

SURVEYOR GENERAL'S CERTIFICATE OF APPROVAL OF FIELD NOTES  
AND SURVEY OF MINING CLAIM

DEPARTMENT OF THE INTERIOR  
OFFICE OF U. S. SURVEYOR GENERAL

Phoenix, Arizona,

June 12, 1919

I, U. S. Surveyor General for District of Arizona

do hereby certify that the foregoing and hereto attached Field Notes and Return of the Survey of the Mining Claim of Alexander Rossi, William Reid, Julia Baxter, Michael Irish, and the estate of Charles W. Baxter, deceased, Phil C. Brannen, Administrator, known as the

OREGON and THE PRIDE lodes

situate in Pima mining district,

Pima County, Arizona

in Section  $\begin{matrix} 31 \\ 6 \end{matrix}$ , Township No.  $\begin{matrix} 17 S \\ 18 S \end{matrix}$ , Range No.  $\begin{matrix} 13 E. \\ 13 E. \end{matrix}$ ,

G. & S. R. B. & M., designated as Survey No. 3510

executed by Paul E. Fernald, U. S. Mineral

Surveyor, July 2nd - July 6th, 1918, under my instructions dated

April 27, 1918, have been critically examined and the necessary

corrections and explanations made, and the said Field Notes and Return, and the survey they describe,

are hereby approved. The certified copy of the location certificate filed by the applicant for survey is

on file in this office and a true copy of said certified copy of said location certificate is included and

made a part of the transcript of the field notes.

Frank P. Trott

U. S. Surveyor General for Arizona

MINERAL SURVEY NO. 3510

OREGON and THE PRIDE lodes.

Aug. 16, 1918  
17  
Platted

6-7-1919 Copied ARC

(4-683.)

Mineral Survey No. 3510

Lot No. \_\_\_\_\_

Arizona Land District.

### FIELD NOTES

OF THE SURVEY OF THE MINING CLAIM OF

Alexander Rossi, William Reid, Julia Baxter, Michael Irish and  
the estate of Charles W. Baxter, deceased, Phil C. Brannen,  
Administrator.

KNOWN AS THE

OREGON and THE PRIDE Lodes.

Pima Mining District,

Pima County, Arizona

Section 31, Township 17 S., Range 13 E., G. & S. R. B. & M.  
6 18 S. 13 E., G. & S. R. B. & M.

Surveyed under instructions dated April 27, 1918.

by Paul E. Fernald  
U. S. Deputy Mineral Surveyor.

Claim located See location Notices . . . . .

Survey commenced July 2nd., 1918.

Survey completed July 6th., 1918.

P.O. Address of Attorney for Claimant:-  
Geo. O. Hilzinger, Atty.  
Box 67, Tucson, Ariz.

## U.S. MINERAL SURVEY NO. 3510.

Feet.	THE PRIDE LODE.
	Beginning at Cor.No. I, T. 18 S., R. 13 E., G. & S. R. B. & M.
	A 1 inch iron pipe, 4 feet long with claw base, set $1\frac{1}{2}$ feet in the ground and surrounded by monument of stones.
	Brass cap on pipe stamped U.S. Mineral Survey No. 3510, 1 - PRIDE.
	Whence The N.W. Cor. of Section 6, T 18 S., R 13 E., G. & S. R. B. & M. bears N $86^{\circ} 47' W$ , 657.20 feet
	Thence N $7^{\circ} 6' E$ .
37.16	Intersect line between Sec. 31, T. 17 S., R. 13 E. & Sec. 6, T. 18 S., R. 13 E., at East 660.76 ft. from the Cor. of Secs. 1, 6, 31 & 36, & West 1891.46 ft. from the point for $\frac{1}{4}$ Cor. between Secs. 6 & 31.
45.00	West end center - monument of stones 3 feet high.
116.00	Crosses road running East.
345.00	Cor.No. 2, on line 1-2, Standard Copper Lode, Survey No. 2643, at point N $7^{\circ} 4' E$ , 345.06 feet from Cor.No. I.
	A 1 inch iron pipe, $3\frac{1}{2}$ feet long with claw base, set $1\frac{1}{2}$ feet in the ground and surrounded by monument of stones.
	Brass cap on pipe stamped U.S. Mineral Survey No. 3510, 2 - PRIDE.
	Whence Cor.No. 2, Standard Copper Lode, Survey No. 2643, bears N $7^{\circ} 4' E$ , 254.46 feet.
	Thence S $65^{\circ} 58' E$
737.50	North side center - monument of stones 3 feet high.
750.07	Intersect line between Secs. 6 & 31, at East 1383.85 ft. from the Cor. of Secs. 1, 6, 31 & 36, and West 1168.37 ft. from the point for $\frac{1}{4}$ Cor. between Secs. 6 & 31.
1475.13	Cor.No. 3.
	A 1 inch iron pipe, $3\frac{1}{2}$ feet long with claw base, set $1\frac{1}{2}$ feet in the ground and surrounded by monument of stones.
	Brass cap on pipe stamped U.S. Mineral Survey No. 3510, 3 - PRIDE.
	Thence S $7^{\circ} 6' W$
300.00	East end center - monument of stones 3 feet high.
345.00	Cor.No. 4, identical with the S.E. Cor. Bloomfield Lode, Unsurveyed, and with Cor.No. 4, Copper Queen Lode, Survey No. 2643 - identical with Cor.No. I, Copper Glance Lode, Survey No. 2643.
	A 1 inch iron pipe, $3\frac{1}{2}$ feet long with claw base, set $1\frac{1}{2}$ feet in the ground and surrounded by monument of stones.
	Brass cap on pipe stamped U.S. Mineral Survey No. 3510, 4 - PRIDE.

	Thence N 65° 58' W
236.00	Crosses Twin Buttes R.R. Track, running S. - S.E.
460.00	Crosses road running S. - S.E.
492.00	Crosses road running S.E.
737.63	South side center - monument of stones 3 feet high.
960.00	Crosses road running East.
1302.00	Crosses Twin Buttes R.R. Track, running E. - N.E.
1474.92	Cor.No. I, Standard Copper Lode, Survey No. 2643, ident. with Cor.No. I Copper King Lode and Cor.No. I Copper Queen Lode, same survey, and S.W. Cor. Bloomfield Lode, Unsyd. Whence Cor.No. 2, Copper King Lode, Survey No. 2643, ident. with Cor.No. 2 Copper Queen Lode, same survey, bears S 7° 4' W, 599.09 feet.
	Cor.No. 4, Standard Copper Lode, identical with Cor.No. 4, Copper King Lode, both Survey No. 2643, bears N 75° 16' W.
1475.13	Cor.No. I, the point of beginning.
	<u>OREGON LODE.</u>
	Beginning at Cor.No. I, identical with Cor.No. 3, The Pride Lode, this survey, heretofore described.
	Brass cap on pipe stamped 1 - OREGON, additionally for this lode.
	Whence the N.W. Cor. of Section 6, T 18 S, R 13 E, G. & S.R. B. & M. bears N 81° 47' W, 2067.28 feet.
	Thence S 7° 6' W
300.00	West end center - monument of stones 3 feet high.
345.00	Cor.No. 2, identical with Cor.No. 4, The Pride Lode, this survey, heretofore described, with the S.W. Cor. of Hamilton Lode, Unsurveyed, and with Cor.No. I, Copper Glance Lode, Survey No. 2643.
	Brass cap on pipe stamped 2 - OREGON, additionally for this lode.
	Thence S 59° 10' E
48.00	West side adobe house.
65.00	East side adobe house.
541.00	Crosses spur - Twin Buttes R.R. running W. - S.W.

U.S. MINERAL SURVEY NO. 3510.

- 578.00 Crosses track Twin Buttes R.R. running W. - S.W.
- 603.00 Crosses spur Twin Buttes R.R. running W. - S.W.
- 699.83 South side center - monument of stones 3 feet high.
- 1399.66 Cor.No.3. identical with the S.E.Cor.of Hamilton Lode, unsurveyed, and with Cor.No.2, Copper Glance Lode, and Cor.No.1, Bullion No.2 Lode, both Survey No.2643.  
A 1 inch iron pipe,  $3\frac{1}{2}$  feet long with claw base, set  $1\frac{1}{2}$  feet in the ground and surrounded by monument of stones.  
Brass cap on pipe stamped U.S.Mineral Survey No.3510, 3 - OREGON.  
Thence N  $7^{\circ}6'E$
- 227.18 East End Center - monument of stones 3 feet high.
- 527.18 Cor.No.4. on line 4-I, Bullion No.2 Lode, Survey No.2643.  
A 1 inch iron pipe,  $3\frac{1}{2}$  feet long with claw base, set  $1\frac{1}{2}$  feet in the ground and surrounded by monument of stones.  
Brass cap on pipe stamped U.S.Mineral Survey No.3510, 4 - OREGON.

Whence Cor.No.4, Bullion No.2 Lode, Survey No.2643, bears N  $7^{\circ}6'E$ , 71.93 feet.  
Thence N  $66^{\circ}20'W$

- 196.00 Crosses track Twin Buttes R.R. running E.- N.E.
- 668.39 North side center - monument of stones 3 feet high.
- 1336.78 Cor.No.1, the point of beginning.  
Magnetic variation at all corners 14 degrees East.  
No natural bearing objects available from any corner of this survey.  
All corners of this survey are identical with the respective corners of location.

LODE LINES:- As near as can be determined from the present state of development, the veins of locations embraced in this survey extend as follows from their respective discovery points.

- THE PRIDE Lode, N  $65^{\circ}58'W$  - 462.ft. and S  $65^{\circ}58'E$  - 1013.13 ft.
- OREGON Lode, N  $66^{\circ}20'W$  - 910.78 ft.and S  $66^{\circ}20'E$  - 426. ft.

LOCATION:- This survey is located in the S.W. $\frac{1}{4}$  of Section 31, T 17 S. R 13 E, and the N  $\frac{1}{2}$  of Section 6, T 18 S. R 13 E. G.& S.R.

B. & M., in the Pima Mining District, Pima County, Arizona.

AREAS:-

- THE PRIDE Lode - total area II.176 acres
- Conflict with Standard
- Copper Lode, Survey No. 2643. .001 "
- OREGON Lode - total area 12.827 "

IMPROVEMENTS:-

I certify that the value of labor and improvements made upon or for the benefit of each of the locations embraced in this survey, by the claimants or their grantors, is not less than Five Hundred Dollars, and that such improvements consist of:-

THE PRIDE Lode:-

No. 1, Discovery shaft, on center line 462. feet from the West end center, 4x6 - 97 feet deep.

Value \$970.00

No. 2. Shaft 4x6 - 8 feet deep, center of which bears S 64° 38' W, 78. feet from Cor. No. 3.

Value \$40.00

No. 3. Shaft 4x6 - 8 feet deep, center of which bears S 37° 30' W, 45. feet from Cor. No. 3.

Value \$40.00

OREGON Lode:-

No. 1. Discovery shaft, on center line 426. feet from the East end center, 6x6 - 8 feet deep present depth. Shows evidence of filling - original depth unknown.

Value \$60.00

No. 2. Shaft 5½x7½ - 39 feet deep, center of which bears S 64° 7' E, 242.5 feet from Cor. No. 1.

Value \$670.00

No. 3. Cut, running into this location from the north.

Center of cut is at point I227, line 4-I, whence it runs south 20 feet, 4 feet wide, 8 feet deep.

Value \$130.00

No. 4. Shaft 4x6 - 7 feet deep, center of which bears S 49° 15' E, 144. feet from Cor. No. 1.

Value \$35.00

U.S. MINERAL SURVEY NO. 3510.

OTHER IMPROVEMENTS:

OREGON Lode;\*

Adobe house, 33 ft. N.E. by 17 ft. S.E. Point at west side of house 14 ft. from N.W. Cor., is at point 48, line 2-3,

~~Oregon Lode.~~

Discovery Shaft Hamilton Lode, Unsurveyed, 4x6 - 7 feet deep, the center of which bears N 9° 7' W, 140. feet from Cor. No. 3.

INSTRUMENT:- This survey was made with Buff & Buff special transit

No. 7905. Courses were deflected from the true meridian as determined by direct solar observations. Distances were measured with 350 and 100 foot steel tapes.

ADJOINING AND CONFLICTING CLAIMS:-

The Pride Lode, this survey, conflicts slightly with the Standard Copper Lode, Survey No. 2643, on the west, is joined by the Copper Queen Lode, Survey No. 2643, on the south, and approximately its total area is ~~approx~~ in conflict with the Bloomfield Lode, Unsurveyed.

Oregon Lode, this survey, is joined <sup>by</sup> the Copper Glance Lode, Sur. No. 2643, on the south; and Bullion No. 2 Lode, Survey No. 2643, on the east. It is largely in conflict with Hamilton Lode, Unsurveyed.

The above mentioned Bloomfield and Hamilton Lodes, unsurveyed, are claimed by Manuel Smith, of Tucson, Ariz.

REPORT:- The N.W. Cor. of T 18 S., R 13 E. G. & S. R. B. & M., is a 1 1/2 inch

iron pipe, 8 inches above ground, surrounded by a small monument of stones. I retraced the north and west

boundary lines of said township respectively for two miles east and south from said N.W. Corner, but was unable

to find any trace of other corners of the public survey. Also retraced the east boundary of Section 6, of said

Township, but found no trace of public survey corners. Intersection with the line between Secs. 6 & 31, reported in this survey, have been computed

Corners of Bloomfield and Hamilton Lodes, unsurveyed, are monuments of stone with 4x4 posts or laths set therein marked with corner description. Aprox.

location of these lodes as shown on plat.

from the record of such line

Corners of Sur.No.2643:-

Copper King Lode,

Cor.No.1, identical with Cor.No.1, Standard Copper Lode, hereinafter described.

Cor.No.2, identical with Cor.No.2 Copper Queen Lode, hereinafter described.

Cor.No.4, identical with Cor.No.4 Standard Copper Lode, hereinafter described.

Standard Copper Lode.

Cor.No.1, Stone, 5 inches above ground, scribed X, 2643.

S.C. 1, C.K. 1, C.Q. 1, on sides facing respective lodes,

Cor.No.2, stone, 4 inches above ground, scribed X, 2643.

S.C. 2.

Cor.No.4. Stone, 5 inches above ground, scribed X 2643,

S.C. 4., C.K. 4. on sides facing respective lodes.

Copper Queen Lode.

Cor.No.1, identical with Cor.No.1, Standard Copper Lode,

heretofore described.

Cor.No.2, Lime rock, 12 inches above ground, scribed

X 2643, C.Q. 2, C.K. 2, on sides facing respective

lodes. Large monument of stones 3 1/2 feet south.

Cor.No.4, Stone, 5 inches above ground, marked X 2643,

C.Q. 4, C.G. 1, on sides facing respective lodes.

Copper Glance Lode.

Cor.No.1, identical with Cor.No.4, Copper Queen Lode,

heretofore described.

Cor.No.2, stone, 5 inches above ground, marked X 2643,

C.G. 2, B No. 2 1, C.B. 1, on sides facing respective

lodes.

Bullion No.2 Lode.

Cor.No.1, identical with Cor.No.2, Copper Glance Lode,

heretofore described.

Cor.No.4, stone, 8 inches above ground, marked X 2643,

B No. 2 ~ 4.

I have to report the following errors in Survey No.2643:-

## U.S. MINERAL SURVEY NO. 3510.

Copper Queen Lode.

Line I-2, S 7°4'W, 599.09 ft. vice S 7°4'W, 600.00 ft.

Copper Glance Lode.

Line I-2, S 59°10'E, 1399.66 ft. vice S 59°14'15"E, 1399.8 ft.

Bullion No.2 Lode.

Line 4-I, S 7°6'W, 599.11 ft. vice S 7°4'W, 600.00 ft.

The difference between locations embraced in this survey as marked upon the ground, and as described in the respective location notices, is due to error of description in the location notices.

The lines of this survey were run direct upon the ground.

Paul E. Jewald.

U.S. Mineral Surveyor

~~Tucson, Ariz. August 7th. 1918.~~

U.S. MINERAL SURVEY NO. 3510.

Direct Solar Observation for Meridian, Saturday, July 6th. 1918.

Time 10.10 A.M. Lat. N 31 54 1/2'. Decl. = N 22 45' 20.1"  
- 14.51" x 4 1/6.  
= N 22 44' 20".

Station - Cor. No. 3, Queen Lode, Survey No. 2643.

Defl. from line 3 - 4, " " " " .

Direct - R. 81 11', Alt. 44 10', (- Ref. Cor. 1').

Reverse R 81 36', Alt. 44 54', ( " ).

\* \* \* \* \*

Direct: - Cos. Q. =  $\frac{\text{Sin. } 22 \ 44' \ 20''}{\text{Cos. } 31 \ 54 \frac{1}{2}'}$  - tan 31 54 1/2' x tan. 44 9'.  
 $\frac{\text{Cos. } 44 \ 9'}{\text{Cos. } 44 \ 9'}$  equiv.

$\frac{.38653}{.848895}$  - .62265 x .97076  
.71752

.63459 - .60444 = .03015 = Cos. 88 16' 21"  
 81 11'  
 N 7 5' 21"E.

Reverse

$\frac{.38653}{.848895}$  - .62265 x tan. 44 53'  
cos. 44 53' equiv.

$\frac{.45533}{.70855}$  - .62265 x .99594  
 equiv.  
 .64262 - .62012 = .02250 = Cos. 88 42' 39"  
 81 36'  
 N 7 6' 39"E.

Average N 7 6'E.

*do not copy*

Y

# FINAL OATHS FOR SURVEYS.

## LIST OF NAMES.

A list of the names of the individuals employed by Paul E. Fernald  
 United States Mineral Surveyor, to assist in running, measuring, and marking the lines, corners, and  
 boundaries described in the foregoing field notes of the survey of the mining claim of  
~~Alexander Rossi, William Reid, Julia Baxter, Michael Irish and the~~  
~~Estate of Charles W. Baxter, deceased, Phil. C. Brannen, Administrator.~~  
 known as the OREGON and THE PRIDE lodes.  
 and showing the respective capacities in which they acted.

James Gorman, Chainman.  
 \_\_\_\_\_, Chainman.  
 \_\_\_\_\_, Axman.  
 \_\_\_\_\_, Flagman.

## FINAL OATHS OF ASSISTANTS.

~~We~~, I, James Gorman  
 and \_\_\_\_\_, do solemnly swear that ~~we~~ I assisted Paul E.  
Fernald, United States Mineral Surveyor, in marking the corners and surveying  
 the boundaries of the mining claim of Alexander Rossi, William Reid, Julia  
Baxter, Michael Irish and the Estate of Charles W. Baxter, Deceased,  
Phil. C. Brannen, Administrator.  
 known as the OREGON and THE PRIDE lodes  
 represented in the foregoing field notes as having been surveyed by said mineral surveyor and under his  
 direction; and that said survey has been in all respects, to the best of our knowledge and belief, faithfully  
 and correctly executed, and the corner and boundary monuments established according to law and the instruc-  
 tions furnished by the United States Surveyor-General for Arizona.

James Gorman, Chainman.  
 \_\_\_\_\_, Chainman.  
 \_\_\_\_\_, Axman.  
 \_\_\_\_\_, Flagman

Subscribed and sworn to by the above-named persons before me this ninth

day of July, 1918

J. H. Dowd  
 Notary Public  
 Lima Co., Ariz

*My commission expires  
 June 6 - 1920.*

FINAL OATH OF U. S. MINERAL SURVEYOR.

I, Paul E. Fernald, U. S. Mineral Surveyor, do solemnly swear that, in pursuance of instructions received from the United States Surveyor General for Arizona, dated April 27th. 1918, I have, in strict conformity to the laws of the United States, the official regulations and instructions thereunder, and the instructions of said Surveyor General, faithfully and correctly executed the survey of the Mining Claim of Alexander Rossi, William Reid, Julia Baxter, Michael Irish and the Estate of Charles W. Baxter, deceased, known as the Phil. C. Brannen, Administrator. OREGON and THE PRIDE lodes, situate in Pima Mining District, Pima County, Arizona, in Section 31, Township No. 17 S, Range No. 13 E, G. & S. R. B. & M. and designated as Survey No. 3510, as represented in the foregoing field notes, which accurately show the boundaries of said mining claim as distinctly marked by monuments on the ground, and described in the attached copy of the location certificate, which was received by me from the Surveyor General with said instructions, and that all the corners of said survey have been established and perpetuated in strict accordance with the law, official regulations and instructions thereunder; and I do further solemnly swear that the foregoing are the true and original field notes of said survey and my report therein, and that the labor expended and improvements made upon said mining claim by claimants or their grantors are as therein fully stated, and that the character, extent, location, and itemized value thereof are specified therein with particularity and full detail, and that no portion of said labor or improvements so credited to this claim has been included in the estimate of expenditures upon any other claim.

Paul E. Fernald
U. S. Mineral Surveyor.

Subscribed and sworn to by the said Paul E. Fernald
U. S. Mineral Surveyor, before me J. O. Dowd, Notary Public,
Pima County, Arizona, this ninth
day of July, 1918.

My commission expires June 6-1920.

J. O. Dowd
Notary Public
Pima Co., Ariz.

April 19 1899

Oregon Mining Claim.

Notice of Mining Location. Quartz Claim. To all whom it may concern:

This mining claim, the name of which is the Oregon Mining Claim, situate on lands belonging to the United States of America, and in which there are valuable mineral mineral deposits, was entered upon and located for the purpose of exploration and purchase by Hugh Canney & Mike Irish, the undersigned, on the 19th day of April, 1899.

The length of the claim is 700 feet in a Westerly direction and 800 feet in a Easterly direction from the center of the discovery shaft, at which this notice is posted, lengthwise of the claim, together with 300 feet in width of the surface grounds, on each side of the center of said claim.

The general course of the lode deposit and premises is from the East to the West.

The claim is situated and located in the Pima Mining District, in Pima County, in the Territory of Arizona, about 1/2 Mile in a Southerly direction from Twin Buttes.

The surface boundaries of the claim are marked upon the ground as follows: Beginning at the Westerly Center End at a point in a Westerly direction 700 feet from the discovery shaft (at which this notice is posted), being in the center of the Westerly end line of said claim; thence southerly 300 feet to a monument of stone, being the S. West corner of said claim; thence Easterly 750 feet to a monument at the center of the south side line of said claim; thence Easterly 750 feet to a monument being at the S. East corner of said claim; thence Northerly 300 feet to a monument at the center of the Easterly end of said claim; thence Northerly 300 feet to a monument, being at the N. East corner of said claim; thence Westerly 750 feet to a monument being at the center of the Northerly side line of said claim; thence Westerly 750 feet to a monument at the N. West corner of said claim; thence southerly 300 feet to the place of beginning.

All done under the provisions of Chapter Six, of Title XXXII, of the Revised Statutes of the United States, and of an Act of the General Assembly of Arizona, entitled "An Act Concerning Mines" approved March 20th, 1895.

Dated and posted on the ground this 19th day of April, 1899.

Witness

J. A. Sheridan

Filed and recorded at request of Michael Irish July 15' 1899 at 9 A. M.

Locators- Hugh Canney  
Mike Irish

Chas. A. Shibell,  
County Recorder.

Book G.G. Page 399.

STATE OF ARIZONA, }  
COUNTY OF PIMA. } ss.

I, ..... R.B. Vinson ..... County Recorder in and for the  
County of Pima, State of Arizona, do hereby certify that the above and foregoing is a full, true and correct copy  
of the Oregon Mining Claim, located on the 19th day of April A.D. 1899  
and situated in the Pima Mining District, Pima Co. Arizona, .....

as appears of record now in my office in Book GG Record of Mines Pages 399 .....

IN WITNESS WHEREOF, I have hereunto set my hand

and affixed my official seal, at my office in Tucson,

this 25 ..... day of

March ..... A. D. 191 8

*R.B. Vinson*  
County Recorder of Pima County, Arizona.

6007079

The Pride.

Location Notice. The undersigned do hereby locate and claim 1500 feet on this ledge or deposit and 300 feet on each side. And is more generally described, Commencing at the West end center which is 300 feet West from this monument, thence Northerly 300 feet, thence Easterly 750 feet, thence Easterly 750 feet, thence Southerly 300 feet, thence Southerly 300 feet, thence Westerly 750 feet, thence Westerly 750 feet and thence Northerly 300 feet to place of Beginning.

Said claim runs Easterly & westerly and shall be known The Pride, running parallel with Copper Queen, Hoffman Camp Twin Buttes Pima Mining District, Pima Co., Arizona, about one mile south of Twin Buttes.

Dated this 7th April 1898.

Hugh Conney

Michael Irish

Filed and recorded at request of Mike Irish July 5 A. D. 1898.  
at 2-15 P.M.

Chas. A. Shibell,  
County Recorder

Book F.F. Page 770.

STATE OF ARIZONA, }  
COUNTY OF PIMA. } ss.

I, R.B.Vinson, County Recorder in and for the  
County of Pima, State of Arizona, do hereby certify that the above and foregoing is a full, true and correct copy  
of the Pride Mining Claim, located on the 7th day of April, A.D.  
1898 and situated in the Pima Mining District, Pima Co. Arizona,

as appears of record now in my office in Book FF Record of Mines Pages 770

IN WITNESS WHEREOF, I have hereunto set my hand

and affixed my official seal, at my office in Tucson,

this 25 day of

March, A. D. 1918

R.B.Vinson  
County Recorder of Pima County, Arizona.

## U. S. SURVEYOR-GENERAL'S FINAL CERTIFICATE ON FIELD NOTES.

**Department of the Interior,**

OFFICE OF U. S. SURVEYOR-GENERAL,

Phoenix, Arizona.

June 12, 1919

I, U. S. Surveyor-General for DISTRICT OF ARIZONA,

do hereby certify that the foregoing transcript of the Field Notes, return and approval of the survey of the mining claim of ALEXANDER ROSSI, WILLIAM REID, JULIA BAXTER, MICHAEL IRISH and the estate of CHARLES W. BAXTER, deceased, PHIL. C. BRANNEN, Administrator, known as the OREGON and THE PRIDE Lodes,

situate in PIMA

Mining District, PIMA County, ARIZONA,  
 in Section 31, Township No. 17 S., Range No. 13 E., G. & S. R. B. & M. and  
 designated as Survey No. 3510, has been correctly copied from the originals on file in

this office; that said Field Notes furnish such an accurate description of said mining claim as will, if incorporated into a patent, serve fully to identify the premises, and that such reference is made therein to natural objects or permanent monuments as will perpetuate and fix the *locus* thereof.

And I further certify that five hundred dollars' worth of labor has been expended or improvements made upon each of said mining claims by claimants or their grantors, and that said improvements consist of 6 shafts and 1 cut. total value \$1945.00

and that no portion of said labor or improvements has been included in the estimate of expenditures upon any other claim.

I further certify that the plat thereof, filed in the U. S. Land Office at Phoenix, Arizona is correct and in conformity with the foregoing Field Notes.

Frank P. Trott,

United States Surveyor-General for Arizona.

SURVEYOR GENERAL'S CERTIFICATE OF APPROVAL OF FIELD NOTES  
AND SURVEY OF MINING CLAIM

DEPARTMENT OF THE INTERIOR  
OFFICE OF U. S. SURVEYOR GENERAL

.....Phoenix, Arizona,.....

.....June 12....., 191 9

I, U. S. Surveyor General for .....DISTRICT OF ARIZONA,.....

do hereby certify that the foregoing and hereto attached Field Notes and Return of the Survey of the Mining Claim of ALEXANDER ROSSI, WILLIAM REID, JULIA BAXTER, MICHAEL IRISH and the estate of CHARLES W. BAXTER, deceased, PHIL. C. BRANNEN, Administrator,

....., known as the

.....OREGON and THE PRIDE Lodes.....

situate in .....PIMA..... mining district,

PIMA..... County, .....ARIZONA,.....

in Section 31..... Township No. 17 S., 18 S.,..... Range No. 13 E.,

G. & S. R. B. & M. designated as Survey No. 3510.....

executed by .....Paul E. Fernald,....., U. S. Mineral

Surveyor, .....July 2nd- July 6th....., 1918, under my instructions dated

April 27,....., 1918, have been critically examined and the necessary cor-

rections and explanations made, and the said Field Notes and Return, and the Survey they describe,

are hereby approved. The certified copy of the location certificate filed by the applicant for survey is

on file in this office and a true copy of said certified copy of said location certificate is included and made

a part of the transcript of the field notes.



U. S. Surveyor General for .....Arizona......