

MINERAL SURVEY No. 3520

LOT No.

ARIZONA Land District.

FIELD NOTES

OF THE SURVEY OF THE MINING CLAIM OF

Bullion Hill Mines Company

KNOWN AS THE

Bullion South, Peggy and Burlock Lodes

Wallapai Mining District,

Mohave County, Arizona

Section 2 and 3 Township 23 N., Range 18 W., approved, and Secs. 34 and 35, T. 24 N., R. 18 W., G. & S.R.B. & M., unapproved survey.

Surveyed under instructions dated May 20, 1918.

by Louis D. Rasor U. S. Mineral Surveyor.

Claim located See location notices, 19

Survey commenced May 22, 1918.

Survey completed May 25, 1918.

Address of claimant Knight Building, Provo, Utah.

DATES OF AMENDED LOCATIONS.

Bullion South, March 30, 1918.

Peggy, March 30, 1918.

Burlock, March 30, 1918.

MINERAL SURVEY NO. 3520.

BULLION SOUTH LODE.

Beginning at Cor. No. 1.

Identical with Cor. No. 1, Burlock Lode of this survey.

A redwood post, 4 ft. long, 4 ins. square, set 18 ins. in ground, with mound of stone, scribed BS1-B2-3520, whence

The Cor. of Secs. 2, 3, 34 and 35, Ts. 23 and 24 N., R. 18 W., G. & S. R. B. & M., bears S. 28° 40' E., 5.9 ft.

No bearings available.

Feet
5.90
1175.00
1475.00

Thence S. 28° 40' E.
Cor. Secs. 2, 3, 34 and 35, Ts. 23 and 24 N., R. 18 W.
Center of road running N. E. and S. W.

To Cor. No. 2.

Identical with Cor. No. 4, Burlock Lode of this survey.

A redwood post, 4 ft. long, 4 ins. square, set 18 ins. in the ground, with mound of stone, scribed BS2-B4-3520.

No bearings available.

300.00
600.00

Thence S. 59° 25' W.
S. end center.

A redwood post, 4 ft. long, 4 ins. square, set 18 ins. in the ground, with mound of stone, scribed S. END. CEN. BULLION SOUTH 3520.

To Cor. No. 3.

Identical with Cor. No. 2, Peggy Lode of this survey.

A redwood post, 4 ft. long, 4 ins. square, set 18 ins. in the ground, with mound of stone, scribed BS3-P2-3520.

No bearings available.

SURVEY NO. 3520-Continued.

BULLION SOUTH LODE-Continued.

Thence N. $18^{\circ} 02' 10''$ W.

Feet.
140.00 Road running E. and W.
639.23 Intersect line between Secs. 2 and 3, at N. $0^{\circ} 33'$ E.,
1643.31 ft. from the $\frac{1}{4}$ Cor., and S. $0^{\circ} 33'$ W., 986.49
ft. from the Cor. of Secs. 2, 3, 34 and 35.
1510.32 To Cor. No. 4.

Identical with Cor. No. 1, Peggy Lode of this
survey.

A redwood post, 4 ft. long, 4 ins. square, set 18
ins. in the ground, with mound of stones, scribed BS4-
PI-3520.

No bearings available.

Thence N. $59^{\circ} 25'$ E.

902.00 N. end center.

A redwood post, 4 ft. long, 4 ins. square, set 18
ins. in the ground, with mound of stone, scribed N.END
CFN. BULLION SOUTH.

130.00 Road running S.E. and N.W.

321.00 To Cor. No. 1, the place of beginning.

PEGGY LODE.

Beginning at Cor. No. 1.

Identical with Cor. No. 4, Bullion South Lode of
this survey, heretofore described, whence

The Cor. of Secs. 2, 3, 34 and 35, T. 23 N., R. 18
W., G. & S. R. B. & M., bears N. $60^{\circ} 28' 10''$ E.,
320.86 ft.

Thence S. $18^{\circ} 02' 10''$ E.

871.09 Intersect line between Secs. 2 and 3, at N. $0^{\circ} 33'$ E.,
1643.31 ft. from the $\frac{1}{4}$ Cor. and S. $0^{\circ} 33'$ W., 986.49
ft. from the Cor. of Secs. 2, 3, 34 and 35.

SURVEY NO. 3520-Continued.

PEGGY LODGE-Continued.

Feet.
1370.32

Road running E. and W.

1510.32

To Cor. No. 2.

Identical with Cor. No. 3 Bullion South Lode of this survey, heretofore described.

Thence S. 83° 25' W.

205.32

Intersect line between Secs. 2 and 3, at N. 0° 33' E., 1011.92 ft. from the I Cor., and S. 0° 33' W., 1617.88 ft. from the Cor. of Secs. 2, 3, 34 and 35.

300.00

S. end center.

A redwood post, 4 ft. long, 4 ins. square, set 18 ins. in the ground, with mound of stone, scribed S.FND GEN. PEGGY.

600.00

To Cor. No. 3.

Identical with Cor. Nos. 4 and 1, Survey No. 1427 Tennessee and Tennessee South Lodes, respectively. I removed the old post and set a new redwood post, 4 ft. long, 4 ins. square, scribed T4-TS1-1427-P3-3520.

Cor. No. 2, Sur. No. 3353. Tennessee Extension lode bears N. 83° 50' E., 290.3 ft.

A cross (+) and B.R.P3-3520, chiseled on the face of a granite boulder, 3 x 5 ft., 2 ft. high, bears N. 65° 32' E., 20.45 ft.

A cross (+) and BRP3-3520 chiseled on the face of granite boulder, 3 x 4 ft., bears N. 24° 20' E., 6.22 ft.

Thence N. 8° 30' 30" W.

117.00

Road running E. and W.

1481.11

To Cor. No. 4.

On line 4-I Survey No. 1427 Tennessee Lode.

On line 4-I Sur. No. 1221, Schuylkill Mill Site.

A pine post, 4 ft. long, 4 ins. square, set 10

SURVEY NO. 3520-Continued.

PEGGY LODGE-Continued.

ins. in the ground, on bedrock, with mound of stone,
scribed P4-3520.

Cor. No. 1, Survey No. 1427 Tennessee Lode bears
N. $8^{\circ} 30' 30''$ W., 19.26 ft.

A cross (+) and BRP4-3520 chiseled on the face of
a granite outcrop, 24 x 24 ins., 10 ins. high, bears
S. $49^{\circ} 56'$ W., 14.05 ft.

No other bearings available.

Feet

Thence N. $83^{\circ} 25'$ E.

131.28 Cor. No. 1, Sur. No. 1221, Schuylkill Mill Site.

A pine post, 4 ins. square, $3\frac{1}{2}$ ft. above ground,
scribed 1-1221.

180.00 N. end center.

A redwood post, 4 ft. long, 4 ins. square, set 18
ins. in the ground, with mound of stones, scribed
N.END CEN. PEGGY.

350.00 Cor. No. 1, the place of beginning.

BURLOCK LODGE.

Beginning at Cor. No. 1.

Identical with Cor. No. 1, Bullion South Lode of this
survey, heretofore described, whence

The Cor. of Secs. 2, 3, 34 and 35, T. 23 N., R.
18 W., G. & S. R. P. & M., bears S. $28^{\circ} 42'$ E., 5.9 ft.

Thence N. $72^{\circ} 53'$ E.

242.00 N. end center.

A redwood post, 4 ft. long, 4 ins. square, set 18
ins. in the ground, with mound of stones, scribed N.END
CEN. BURLOCK 3520.

542.00 To Cor. No. 2.

A pine post, 4 ft. long, 4 ins. square, set 18 ins.

SURVEY NO. 3520-Continued.

BURLOCK LODE-Continued.

in the ground, with mound of stone, scribed B2-3520.

A cross (+) and BRB2-3520, chiseled on the face of granite outcrop, 2 ft. high, bears S. $36^{\circ} 55' W.$, 63.48 ft.

No other bearings available.

Thence S. $30^{\circ} 51' 30'' E.$

730.00 Road running N.E. and S.W.

1487.70 Point for Cor. No. 3.

Not set, as it falls in road.

I set a witness corner at S. $72^{\circ} 53' W.$, 9.75 ft.

A redwood post, 4 ft. long, 4 ins. square, set 18 ins. in the ground, with mound of stones, scribed WC-B3-3520.

A cross (+) and BR-B3-3520, chiseled on face of granite outcrop 14 x 20 ins. bears from true corner, N. $28^{\circ} 16' W.$, 34.45 ft.

No other bearings available.

Thence from true corner S. $72^{\circ} 53' W.$

9.75 W.C. heretofore described.

300.00 S. end center.

A redwood post, 4 ft. long, 4 ins. square, set 18 ins. in the ground, with mound of stone, scribed S.END CFN.BURLOCK.

600.00 To Cor. No. 4.

Identical with Cor. No. 2 Bullion South Lode, this survey, heretofore described.

Thence N. $28^{\circ} 40' W.$

300.00 Road running N.W. and S.E.
1469.10 Cor. of Secs. 2, 3, 34 & 35. rs. 23 & 24 N., R. 18 W.
1475.00 To the place of beginning.

SURVEY NO. 3520-Continued.

Variation at all corners, 15° 45' E.

Lode Lines.

As near as can be determined from present developments the veins of the several locations embraced in this claim, extend as follows from their respective discovery points.

Bullion South Lode, 225 ft., N. 26° 00' W., and 1253.96 ft., S. 26° 00' E.

Peggy Lode, 621 ft., N. 13° 08' W., and 868.98 ft., S. 13° 08' E.

Burlock Lode, 100 ft., N. 30° 51' 30" W., and 1387.7 ft., S. 30° 51' 30" E.

AREA.

	Acres.
Total Area Bullion South Lode-----	15.585
Total Area Peggy Lode-----	16.141
Total Area Burlock Lode-----	18.943

The survey of each lode of this location is identical with the respective location, as staked upon the ground.

LOCATION.

This survey is located in Secs. 2 and 3, T. 23 N., R. 18 W., and Secs. 34 and 35, T. 24 N., R. 18 W., G. & S. R. B. & M., the latter being an unapproved survey.

EXPENDITURE OF FIVE HUNDRED DOLLARS.

I certify that the value of labor and improvements made upon, or for the benefit of this claim, by the claimant, or its grantors, is not less than five hundred dollars, and that said improvements consist of:

SURVEY NO. 3520-Continued.

BULLION SOUTH LODE.

No. 1. The discovery cut, the mouth of which being the discovery point, is on the lode line, 1253.96 ft. from the center of line 2-3, 4 ft. wide, 10 ft. face, running S. 15 ft.

Value, \$40.00

No. 2. A cut, the mouth of which bears from Cor. No. 4, S. $52^{\circ} 37'$ E., 200 ft., 4 ft. wide, 6 ft. face, running S. 10° W., 10 ft.

Value, \$30.00

No. 3. A shaft, which bears from Cor. No. 4, S. $28^{\circ} 05'$ E., 490 ft., 4 x 6 ft., 10 ft. deep.

Value, \$90.00

No. 4. A shaft, which bears from Cor. No. 4, S. $29^{\circ} 30'$ E., 576 ft., 4 x 6 ft., 20 ft. deep.

Value, \$200.00

No. 5. A shaft, which bears from Cor. No. 4, S. $29^{\circ} 30'$ E., 646 ft., 4 x 6 ft., 8 ft. deep.

Value, \$50.00

No. 6. A shaft, which bears from Cor. No. 4, S. $29^{\circ} 30'$ E., 687 ft., 4 x 6 ft., 25 ft. deep.

Value, \$250.00

No. 7. A cut, the mouth of which bears from Cor. No. 4, S., $29^{\circ} 30'$ E., 687 ft., 4 ft. wide, 10 ft. face, running N. 33° W., 35 ft., thence a tunnel, 4 x 6 ft., runs N. 35° W., 137 ft.

Value, \$1520.00

No. 8. A two compartment shaft, which bears from Cor. No. 4, N. $73^{\circ} 35'$ E., 160 ft., 4 x 8 ft., inside of timbers, 320 ft. deep. From the 300 ft. level a cross cut tunnel, 4 x $6\frac{1}{2}$ ft., runs N. $63^{\circ} 40'$ E., 75.5 ft., to a drift 4 x $6\frac{1}{2}$ ft., running N. $25^{\circ} 45'$ W., 40 ft. And S. $35^{\circ} 20'$ E., 330 ft. From 35 ft. depth in the shaft a tunnel, 4 x 6 ft., runs S. $63^{\circ} 40'$ W., 50

SURVEY NO. 3520-Continued.

ft.

Value of shaft, drift and tunnels, \$13,300.00

No. 9. A shaft, which bears from Cor. No. 4, N. $83^{\circ} 30'$ E., 130 ft., 4 x 6 ft., 50 ft. deep. From the bottom of the shaft a drift 4 x 6 ft., runs S. 35° E., 33 ft., and N. 35° W., 10 ft. At 30 ft. depth in the shaft is a drift 4 x 6 ft., running S. 35° E., 10 ft., and N. 35° W., 26 ft. At a depth of 20 ft. in the shaft is a drift 4 x 6 ft., running N. 35° W., 15 ft.

Value of shaft and drifts, \$1500.00

PEGGY LODE.

No. 1. The discovery shaft is on the lode line 868.98 ft. from the center of line 2-3, 4 x 6 ft., 8 ft. deep.

Value, \$50.00

No. 2. A shaft, which bears from Cor. No. 3, N. $11^{\circ} 30'$ E., 663 ft., 4 x 6 ft., 4 ft. deep.

Value, \$20.00

No. 3. A tunnel, the mouth of which bears from Cor. No. 2, N. $24^{\circ} 02'$ W., 578 ft., 4 x $6\frac{1}{2}$ ft., running N. $34^{\circ} 45'$ W., 50 ft.

Value, \$500.00

BURLOCK LODE.

No. 1. The discovery shaft is on the lode line 1387.7 ft., from the center of line 3-4, 4 x 6 ft., 8 ft. deep.

Value, \$50.00

No. 2. A shaft, which bears from Cor. No. 4, N. $4^{\circ} 40'$ W., 387 ft., 7 x 7 ft., 6 ft. deep.

Value, \$75.00

No. 3. A cut, the mouth of which bears from Cor. No. 4, N. $23^{\circ} 05'$ W., 600 ft., 4 ft. wide, 10 ft. face, running N. 27° W., 13 ft. Thence a tunnel runs N. 27° W., 27 ft., thence N. 17° W., 21 ft. From a point in

SURVEY NO. 3520-Continued.

the tunnel 27 ft, from the mouth a tunnel runs N. 37° W., 14 ft. From a point in the tunnel 18 ft. from the mouth, a tunnel 4 x 6 ft., runs S. 80° W., 10 ft.

Value, \$750.00

OTHER IMPROVEMENTS.

A powder tunnel, the mouth of which bears from Cor. No. 4 Bullion South Lode, S. $66^{\circ} 56'$ E., 131 ft., 6 x 8 ft., running South 10 ft.

INSTRUMENT.

This survey was made with a C. L. Berger & Sons transit, No. 3164. The courses were deflected from the true meridian, as determined by observation on Polaris, as follows:

On May 25, 1918.

I set instrument on Cor. No. 3, Bullion South Lode, and at 3:06 A.M., local time, observed Polaris in eastern elongation, and marked the line thus determined by a stake 300 ft. from the corner.

Latitude of station $35^{\circ} 20'$.

Azimuth of Polaris $1^{\circ} 23'$.

Deflect right $58^{\circ} 02'$ to Cor. No. 2.

Course of line thus determined S. $59^{\circ} 25'$ E.

The distances were measured with a 500 and 100 ft. steel tapes.

The lode line of each location of this claim was run directly upon the ground, and the several corners established by means of offsets from the lode lines. All tie lines were run directly upon the ground.

The Cor. of Secs. 2, 3, 34 and 35, Ts. 23 and 24 N., R. 18 W., G. & S. R. E. & M., is an iron post, properly set and marked.

The $\frac{1}{4}$ Cor. between Secs. 2 and 3, T. 23 N., R. 18 W., G. & S. R. E. & M., is a stone properly set and

SURVEY NO. 3520-Continued.

marked.

I find the north half of the line between Secs. 2 and 3, T. 23 N., R. 18 W., G. & S. R. B. & M., to be S. $0^{\circ} 33'$ W., 2629.8 ft., instead of South 2645.28 ft., as approved.

Sur. No. 1221, Schuylkill Mill Site.

Cor. No. 1 is a pine post properly set and scribed with the number of the corner and survey. Cor. No. 4 could not be found.

Sur. No. 1427, Tennessee and Tennessee South lodes:

All of the corners are pine posts properly set and scribed with the number of the corner and survey.

I find Line 4-I of the Tennessee Lode to be N. $8^{\circ} 30'$ W., 1500.37 ft., instead of N. $9^{\circ} 15'$ W., 1500 ft. as approved.

Sur. No. 3353 Tennessee Extension Lode:

Cor. No. 2 is a stone properly set and marked, with the number of the corner and survey.

FINAL OATHS FOR SURVEYS.

LIST OF NAMES.

A list of the names of the individuals employed by Louis D. Rasor
 United States Mineral Surveyor, to assist in running, measuring, and marking the lines, corners, and
 boundaries described in the foregoing field notes of the survey of the mining claim of
Bullion Hill Mines Company,
 known as the Bullion South, Peggy and Burlock Lodes
 and showing the respective capacities in which they acted.

A. W. Kellogg , Chainman.
 , Chainman.
 , Axman.
 , Flagman.

FINAL OATHS OF ASSISTANTS.

~~xxx~~ I, Wm J. Cooke Jr
 and , do solemnly swear that ^I~~we~~ assisted Louis D. Rasor
 , United States Mineral Surveyor, in marking the corners and surveying
 the boundaries of the mining claim of Bullion Hill Mines Company
 known as the Bullion South, Peggy and Burlock Lodes
 represented in the foregoing field notes as having been surveyed by said mineral surveyor and under his
 direction; and that said survey has been in all respects, to the best of ^{my}~~our~~ knowledge and belief, faithfully
 and correctly executed, and the corner and boundary monuments established according to law and the instruc-
 tions furnished by the United States Surveyor-General for Arizona.

Wm J. Cooke Jr. , Chainman.
 , Chainman.
 , Axman.
 , Flagman

Subscribed and sworn to by the above-named persons before me this 1st

day of June, 1918

C. Bleary
 Notary Public

6-1043

My commission expires Aug 17-1920

4-686.

FINAL OATH OF U. S. MINERAL SURVEYOR.

I, Louis D. Rasor, U. S. Mineral Surveyor,
do solemnly swear that, in pursuance of instructions received from the United States
Surveyor General for Arizona, dated
May 20, 1918, I have, in strict conformity to the laws of the
United States, the official regulations and instructions thereunder, and the instructions
of said Surveyor General, faithfully and correctly executed the survey of the Mining
Claim of Bullion Hill Mines Company
, known as the
Bullion South, Peggy and Burlock Lodes
situate in Wallapai Mining District,
Mohave County, Arizona in Section 2
and 3, T. 23 N.R. 18 W. App. and Secs. 34 and 35, T. 24 N., R. 18 W.,
XXXXXX, XXXXXX,
G. & S. P. P. & M. unapproved survey, 3520. and designated as Survey No. 3520., as represented
in the foregoing field notes, which accurately show the boundaries of said mining claim
as distinctly marked by monuments on the ground, and described in the attached copy
of the location certificate, which was received by me from the Surveyor General with
said instructions, and that all the corners of said survey have been established and per-
petuated in strict accordance with the law, official regulations and instructions there-
under; and I do further solemnly swear that the foregoing are the true and original
field notes of said survey and my report therein, and that the labor expended and
improvements made upon said mining claim by claimant or its grantors
are as therein fully stated, and that the character, extent, location, and itemized value
thereof are specified therein with particularity and full detail, and that no portion of
said labor or improvements so credited to this claim has been included in the estimate
of expenditures upon any other claim.

Louis D. Rasor
U. S. Mineral Surveyor.

Subscribed and sworn to by the said Louis D Rasor
U. S. Mineral Surveyor, before me C B Cravens
Notary Public this 1st
day of June, 19 18

C B Cravens
Notary Public

NOTICE OF AMENDED LOCATION
LODE.

MAR 31 1913

KNOW ALL MEN BY THESE PRESENTS,

That Bullion Hill Mines Company having complied with all the requirements of the Laws of the United States, and the State of Arizona, relating to mining claims, and with the local laws and rules, does hereby make and file this Amended Location of the Bullion South Lode, claiming by right of discovery, location, primal appropriation and possession 1478.96 feet, linear and horizontal measurement on this lead, lode or deposit of mineral or other rock in place, bearing valuable minerals, with all dips, variations and angles, the same running S. 26° 00' E., 1253.96 feet along the lead, lode or deposit from the discovery point, and N. 26°00' W., 225.00 feet along the ledge therefrom, together with 300 feet in width on each side of the middle of said ledge, and all veins, ledges, mineral deposits, mineral and surface ground within the lines of said claim.

Situate in Wallapai Mining District, County of Mohave, State of Arizona, and more particularly described as follows, to-wit:

Beginning at the N. E. Cor. of the claim, whence the Corner of Secs. 2, 3, 34 and 35, Ts. 23 and 24 N., R. 18 W., G. & S. R. B. & M., bears S. 28°42' E., 5.9 ft; and running thence S. 28°40' E., 1475.00 ft. to the S.E. Cor; thence S. 59°25'W. 300 ft. to the South end center, and 600 ft. to the S.W. Cor; thence N. 18°02' W., 1510.32 ft., to the N.W. Cor; thence N.59°25' E., 90 ft. to the North end center, and 321.0 ft. to the place of beginning.

All corners and end centers are marked by redwood posts, 4 ins. square 4 ft. long, firmly set in ground with mound of earth and stones, and plainly marked.

This claim is bounded on the easterly side by the Burlock Lode, and on the westerly side by the Peggy Lode.

This amended location is made in conformity with the original location made January 1, 1910, and recorded March 31, 1910, in Book FF, Page 299 of Mining Records in the office of the Recorder of said County, and it is made for the purpose of appropriating all ground within the boundaries hereinbefore described, and of more definitely

-2-

the situation and boundaries of said lode, correcting any irregularities, informalities or errors, supplying omissions and correcting any defects which may have existed in the original location, or the record thereof, hereby waiving no rights acquired under and by virtue of said original location. And if the original location or the certificate thereof is void, then this location shall be an original location, and this certificate an original certificate.

Date of Original Location January 1, 1910.
Date of Amended Location March 30, 1918.

Bullion Hill Mines Company
H. M. Eakin
Its Agent.

Filed and Recorded at Request of Bullion Hill Mines Co., April 2nd A.D. 1918 at nine o'clock A.M. in Book SS of Mines Pages 513 Records of Mohave County, Arizona.

H. L. Underwood,
County Recorder.
By H. F. Williams,
Deputy.

NOTICE OF AMENDED LOCATION

MAY 30 1918

LODE.

KNOW ALL MEN BY THESE PRESENTS:

That Bullion Hill Mines Company having complied with all the requirements of the Laws of the United States, and the State of Arizona, relating to mining claims, and with the local laws and rules, does hereby make and file this Amended Location of the Peggy Lode, claiming by right of discovery, location, primal appropriation and possession 1489.98 feet, linear and horizontal measurement on this lead, lode or deposit of mineral or other rock in place, bearing valuable minerals, with all dips, variations and angles, the same running S. 13°08' E. 868.98 feet along the lead, lode or deposit from the discovery point, and N. 13° 08' W., 621 feet along the ledge therefrom, together with 300 feet in width on each side of the middle of said ledge, and all veins, ledges, mineral deposits, mineral and surface ground within the lines of said claim.

Situate in Wallapai Mining District, County of Mohave, State of Arizona, and more particularly described as follows, to-wit:

Beginning at the N.E. Cor. of the claim, whence the Corner to Secs. 2, 3, 34 and 35, Ts. 23 and 24 N., R. 18 W., G. & S. R. B. & M., bears S. 60° 28' W. 320.86 ft., and running S. 18° 02' E., 1510.32 ft. to the S.E. Cor. thence S. 83° 25' W., 300 ft. to the South end center, and 600 ft. to the S.W. Cor; thence N. 8° 30' 30" W., 1481.11 ft. to the N.W. Cor; thence N. 83° 25' E., 180 ft. to the North end center, and 350 ft. to the place of beginning.

All corners and end centers are marked by redwood posts, 4 ins. square, 4 ft. long, firmly set in ground with mound of earth and stones, and plainly marked.

This claim is bounded on the easterly side by the Bullion South Lode, and on the west by the Tennessee Lode.

This amended location is made in conformity with the original location made January 1, 1910, and recorded March 31, 1910, in Book FF,

-2-

Page 301 of Mining Records in the office of the Recorder of said County, and it is made for the purpose of appropriating all ground within the boundaries hereinbefore described, and of more definitely describing the situation and boundaries of said lode, correcting any irregularities, informalities or errors, supplying omissions and correcting any defects which may have existed in the original location, or the record thereof, hereby waiving no rights acquired under and by virtue of said original location. And if the original location or the certificate thereof is void, then this location shall be an original location, and this certificate an original certificate.

Date of Original Location January 1, 1910.

Date of Amended Location March 30, 1918.

Bullion Hill Mines Company,
H. M. Eakin,
Its Agent.

Filed and Recorded at Request of Bullion Hill Mines Co., April 2nd A.D. 1918 at nine o'clock A.M. in Book SS of Mines Pages 512 Records of Mohave County, Arizona.

H. L. Underwood,
County Recorder.
By H. F. Williams,
Deputy Recorder.

NOTICE OF AMENDED LOCATION

LODE.

KNOW ALL MEN BY THESE PRESENTS,

That Bullion Hill Mines Company having complied with all the requirements of the Laws of the United States, and the State of Arizona, relating to mining claims, and with the local laws and rules, does hereby make and file this Amended Location of the Burlock Lode, claiming by right of discovery, location, primal appropriation and possession 1487.7 feet, linear and horizontal measurement on this lead, lode or deposit of mineral or other rock in place, bearing valuable minerals, with all dips, variations and angles, the same running S. 30°51'30" E. 1387.7 feet along the lead, lode or deposit from the discovery point, and N. 30°51'30" W., 100 ft. feet along the ledge therefrom, together with 300 feet in width on each side of the middle of said ledge, and all veins, ledges, mineral deposits, mineral and surface ground within the lines of said claim.

Situate in Wallapai Mining District, County of Mohave, State of Arizona, and more particularly described as follows, to-wit:

Beginning at the N.W. Cor. of the claim, whence the Corner of Secs. 2, 3, 34 and 35, Ts. 23 and 24 N., R. 18 W., G. & S. R. B. & M., bears South 28°42' E., 5.9 ft; and running thence N. 72°53' E. 242 ft. to the North center end, and 542 ft. to the N.E. Cor; thence S.30°51'30" E. 1487.7 ft. to the S.E. Cor; thence S. 72°53' W., 300 ft. to the South end center, 600 ft. to the S.W. Cor.; thence N. 28°40' W., 1475.0 ft. to the place of beginning.

All corners and end centers are marked by redwood posts, 4 ins. square and 4 ft. long, firmly set in ground, with mound of earth and stones, and plainly marked.

This claim is bounded on the westerly side by the Bullion South Lode.

This amended location is made in conformity with the original location made December 28, 1905, and recorded March 5, 1906, in Book W, Page 325 of Mining Records in the office of the Recorder of said County, and it is made for the purpose of appropriating all ground within the boundaries hereinbefore described, and of more definitely describing the

-2-

situation and boundaries of said lode, correcting any irregularities, informalities or errors, supplying omissions and correcting any defects which may have existed in the original location, or the record thereof, hereby waiving no rights acquired under and by virtue of said original location. And if the original location or the certificate thereof is void, then this location shall be an original location, and this certificate an original certificate.

Date of Original Location December 28, 1905.
Date of Amended Location March 30, 1918.

Bullion Hill Mines Company,
H. M. Eakin,
Its Agent.

Filed and Recorded at Request of Bullion Hill Mines Co., April 2nd A.D. 1918 at nine o'clock A.M. in Book SS of Mines, pages 514 Records of Mohave County, Arizona.

H. L. Underwood,
County Recorder.
By H. F. Williams,
Deputy Recorder.

STATE OF ARIZONA }
County of Mohave } ss.

I,H. L. Underwood....., Recorder of Mohave County, State of Arizona, do hereby certify that I have compared the foregoing copies of Amended Locations of ... Peggy Lode, Bullion South Lode, and Burlock Lode Mining Claims, and of the endorsement thereon with the original records of the same on file in this office, and that the same are correct transcripts therefrom and of the whole of said original records.

WITNESS my hand and the seal of said office this ..25th... day ofApril....., 1918.



.....H. L. Underwood.....
Recorder of Mohave County, Arizona.

By H. F. Williams
Deputy.

U. S. SURVEYOR-GENERAL'S FINAL CERTIFICATE ON FIELD NOTES.

Department of the Interior,

OFFICE OF U. S. SURVEYOR-GENERAL,

Phoenix, Arizona,

September 23, 1919.

I, U. S. Surveyor-General for District of Arizona

do hereby certify that the foregoing transcript of the Field Notes, return and approval of the survey of the mining claim of

Bullion Hill Mines Company

known as the BULLION SOUTH, PEGGY and BURLOCK Lodes

situate in Wallapai

Mining District, Mohave County, Arizona

in Sections 2 & 3, 34 & 35, Township No. 23 N, 24 N, Range No. 18 W., approved, and 18 W., unapproved

designated as Survey No. 3520, has been correctly copied from the originals on file in this office; that said Field Notes furnish such an accurate description of said mining claim as will, if incorporated into a patent, serve fully to identify the premises, and that such reference is made therein to natural objects or permanent monuments as will perpetuate and fix the locus thereof.

And I further certify that five hundred dollars' worth of labor has been expended or improvements made upon each of said mining claims by claimant or its grantors, and that said improvements consist of 4 cuts, 6 tunnels, 10 shafts, 1 crosscut and 4 drifts, total value \$18,325.

and that no portion of said labor or improvements has been included in the estimate of expenditures upon any other claim.

I further certify that the plat thereof, filed in the U. S. Land Office at Phoenix, Arizona is correct and in conformity with the foregoing Field Notes.

Frank P. Trott

United States Surveyor-General for Arizona

SURVEYOR-GENERAL'S CERTIFICATE OF APPROVAL OF FIELD NOTES AND SURVEY OF MINING CLAIM.

Department of the Interior,

OFFICE OF U. S. SURVEYOR-GENERAL,

Phoenix, Arizona,

September 23, 1919

I, U. S. Surveyor-General for District of Arizona

do hereby certify that the foregoing and hereto attached Field Notes and Return of the Survey of the Mining Claim of

Bullion Hill Mines Company

, known as the

BULLION SOUTH, PEGGY and BURLOCK Lodes

situate in Wallapai mining district,

Mohave County, Arizona

in Section 2 & 3, Township No. 23 N, Range No. 18 W., approved & 34 & 35, Township No. 24 N, Range No. 18 W., unapproved

, designated as Survey No. 3520

executed by Louis D. Rasor, United States Mineral

Surveyor, May 22 - 25, 1918, under my instructions dated

May 20, 1918, have been critically examined and the necessary cor-

rections and explanations made, and the said Field Notes and Return, and the Survey they describe,

are hereby approved. A true copy of the copy of the location certificate filed by the applicant for

survey is included in the field notes.

[Handwritten signature]

U. S. Surveyor-General for Arizona.