

MINERAL SURVEY No. 3575

Arizona

Land District.

FIELD NOTES

OF THE SURVEY OF THE MINING CLAIM OF

O. D. M. Gaddis

KNOWN AS THE

Seneca and Oneida South lodes

Wallapai

Mining District,

Mohave

County,

Arizona

Sections 3 & 10

Township 22 N.

Range

17 West

G & S. R. B. & M.

Surveyed under instructions dated March 11, 1919

by Leon H. Foster.

U. S. Mineral Surveyor.

~~Seneca, Jan. 1st. 1908~~

Claim located ~~Oneida South, Jan. 1st.~~, 1915 See location notices.

Survey commenced March 20, 19 19

Survey completed March 30, 19 19

Address of claimant By Fern S. Hildreth, Phoenix, Ariz.

DATES OF AMENDED LOCATIONS.

~~Seneca, March 7. 1919~~

~~Oneida South, March, 7 1919~~

Mineral Survey No. 3575

Seneca lode.

Beginning Cor. No. 1.

A native pine post, 4 ins. square, 4 ft. long, with a nail at the exact corner, set 12 ins. in the ground, in a mound of earth and stone, scribed S-1-3575.

Identical with the location.

A granite boulder, 5 ft. dia. and 4 ft. high, with a cross cut on the northeast face and marked B.R.-S-1-3575, bears S. 57° 03' W. 5.60 ft.

The northern corner ~~between~~ sections 3 and 4, T. 22 N. R. 17 W. G. & S. R. B. & M. bears N. 24° 03' 30" W. 5305.10.ft.

feet

Thence S. 34° 46' E.

561.67

Intersect line between sections 3 and 10 at S. 89° 52' E. 2490.65 ft., N. 89° 52' W. 165.85 ft. from Corner of sections 3-4-9-10 and the quarter corner between sections 3 and 10, respectively.

1500.00

To Cor. No. 2.

A native pine post, 4 ins. square, 4 ft. long, with a nail at the exact ~~(at the exact)~~ corner, set 15 ins. in the ground, in a mound of earth and stone, scribed S-2-3575.

Identical with the location and with Cor. No. 1 Oneida South lode, this survey.

Thence S. 57° 03' W.

300.00

To the south end center of the location.

A native pine post, 4 ins. square, 4 ft. long, with a nail at the exact point, set 12 ins. in the ground, in a mound of earth and stone, scribed 3575.

A granite boulder, 3 ft. wide, 4 ft. long, and 2 ft. above ground, with a cross cut on the north face and marked B.R.-3575, bears S. 77° 27' E. 27.00 ft.

The discovery shaft bears N. 34° 46' W. 1227 ft.

600.00

To Cor. No. 3.

A native pine post, 4 ins. square, 4 ft. long, with a nail at the exact corner, set 15 ins. in the ground, in a mound of earth and stone, scribed S-3-3575.

Survey No. 3575.

feet

Seneca lode, continued.

Identical with the location and with Cor. No. 4, Oneida South lode, this survey.

Thence N. 34° 46' W.

1337.67 Intersect line between sections 3 and 10 at S. 89° 52' E. 1759.45 and N. 89° 52' W. 897.05 ft. from corner of sections 3-4-9-10 and quarter corner between sections 3 and 10, respectively.

1500.00 To Cor. No. 4.

A pine post, 4 ins. square, 4 ft. long, with a nail at the exact corner, set 12 ins. in the ground, in a mound of earth and stone, scribed S-4-3575.

Identical with the location.

Thence N. 57° 03' E.

300.00 To the north end center of the location.

A native pine post, 4 ins. square, 4 ft. long, with a nail at the exact point, set 12 ins. in the ground, in a mound of earth and stone, scribed 3575.

The discovery shaft bears S. 34° 46' E. 273 ft.

600.00 To Cor. No. 1, the place of beginning.

Variation at all corners = 14° 30' E.

Oneida South lode.

Beginning Cor. No. 1.

A pine post, previously described, scribed O-S-1-3575.

Identical with the location and with Cor. No. 2, Seneca lode, this survey.

The northern corner between sections 3 and 4, T. 22 N. R. 17 W.G. & S. R. B. & M. ^{bears} N. 26° 25' W. 6784.60 ft.

Thence S. 22° 27' E.

1500.00 To Cor. No. 2.

A granite slab, 5x12x30 ins. long, with a cross at the exact corner, set 12 ins. in the ground, in a mound of earth and stone, scribed O-S-2-3575.

Identical with the location.

Survey No. 3575

Oneida South Lode, continued.

Seneca lode: Thence S. 57° 03' W. 300.00

To the south end center of the location.

A pine post, 4 ins. square, 4 ft. long, with a nail at the exact point, set 15 ins. in the ground, in a mound of earth and stone, scribed 3575.

The discovery cut bears N. 22° 27' W. 685 ft.

A granite stone 5 ft. wide, 8 ft. long and 5 ft. above

ground, with a cross cut on the north face, marked B.R.-

3575, bears S. 21° 58' W. 28.40 ft.

To Cor. No. 3. I certify that the value

A native pine post, 4 ins. square, 4 ft. long, with a nail at the exact corner set 15 ins. in the ground, in a mound of earth and stone, scribed 3575.

Identical with the location.

Thence N. 22° 27' W. 1500.00

To Cor. No. 4. which is on the lode line

A pine post, previously described, scribed 3575-4-3575.

Identical with the location and with Cor. No. 3,

Seneca lode, this survey, No. 3, a shaft

Thence N. 57° 03' E. 300.00

To the north end center of the location.

A pine post, previously described, scribed 3575.

Identical with the south end center, Seneca lode, this

survey. is on the lode line 325 ft. from the south

The discovery cut bears S. 22° 27' E. 815 Ft.

To Cor. No. 1, the place of beginning.

Variation at all corners = 14° 30' E. corner of which bears S. 55° 46' E. 146 ft. from Cor. No. 4

and extending S. 54° 46' E. 9 ft. 2 ft. wide and 250 ft.

LODE LINES

As near as can be determined from present developments the course of the lode lines of the claims of this survey

extend as follows; 1/2 of above -- scribed 3575

Seneca lode: N. 34° 46' W. 273 ft. and S. 34° 46' E.

1227 ft. from the discovery shaft.

Oneida South lode: N. 22° 27' W. 815 ft. and S. 22° 27' E. 685 ft. from the discovery cut.

Survey No. 3575

** AREAS **

Seneca lode: -----20.651 Acres

Oneida South lode: -----20.315

at the exact point, the LOCATION, in a mound

This survey is located in the Wallapai mining

District, Mohave County, Arizona, in sections 3 and 10

T. 22 N. R. 17 W. S. 3 & S. R. B. & M. Mining A xxx xxx

** Expenditure of Five Hundred Dollars **

I certify that the value of the improvements and

labor, made upon and for the benefit of this group of lode

claims by the claimant or his grantors, is not less than

Five Hundred Dollars for each claim and is as follows;

Seneca lode, the location with the location

No. 1-, the discovery shaft, the center of

which is on the lode line, 1227 ft. from the south end

center, 6' X 6' X 35' deep, a pine post, previously

Value \$525.00

No. 2, a shaft, 6' X 6' X 6' feet deep, the

center of which is on the lode line, 1108 ft. from the

south end center. Value \$20.00

No. 3, a shaft, 8' X 8' X 15' deep, the center of which

is on the lode line, 332 ft. from the south end center.

Value \$75.00

No. 4, the main working shaft, the northeast

corner of which bears S. 53° E. 746 ft. from Cer. No. 4

and extending S. 34° 46' E. 9 ft, 5 ft. wide and 250 ft.

deep, valued at \$7500.00 which is divided equally between

the two claims of this survey.

1/2 of above -- \$3750.00

Oneida South lode.

No. 1, the discovery cut, 4 ft. wide, 12 ft.

face, the center of which is on the lode line, 815 ft.

from the north end center and extending East 22 ft. to its

Survey No. 3575

Improvements, continued.

mouth. West from the face, a tunnel 4' X 6' , 11' long, thence N. 25° W. 15 ft. to the breast.

Value ----- \$325.00

* Adding Claim *

No. 2, a shaft, 3' X 8' X 6' deep, the center of which bears S. 5° W. 548 ft. from Cor. No. 1.

Value ----- \$25.00

No. 3, a shaft, 4 ft. wide, 8 ft. long and 10 ft.

deep, the east side being on the lode line, the northeast corner at 875 ft. from the north end center.

Value ----- \$50.00

1/2 value of improvement No. 4, Seneca lode, main working shaft. ----- \$3750.00

** Instrument and Meridian **

This survey was made with a Berger & Son's Mining transit and a 500 and 100 ft. steel tape.

The Meridian was determined by direct observation on the sun.

* REPORT *

The side and end lines were measured direct on the ground.

The main working shaft, timbered, two compartments and 250 ft. deep, was sunk on the west side of the vein which extends thru the two claims of this survey and for the benefit of these two claims. I value this at \$7500.00 and credit each claim with one half.

The section corner on the north ^{of Secs.} ~~between~~ 3 and 4, T. 22 N. R. 17 W. G. & S. R. B. & M. is a two and one half inch pipe, with a brass cap marked 4 | 3, properly set and is the nearest corner to this survey that could be identified. Being unable to find the quarter corner between sections 3 & 4, the corner of sections 3-4-9-10, the quarter corner between sections 3 & 10 or the corner of sections 2-3-10-11, I therefore calculated the ~~ties~~

Improvements, ~~with~~ ~~and intersections~~ ~~to~~ the line between sections 3 and 10
 mouth West from the face, a tunnel 4' X 6' 11" long,
 from the record of the Public Land Survey.
 thence N. 25° W. 12 ft. to the present.

Value ----- \$325.00

*** Adjoining Claims ***

No. 2, a shaft, 5' X 8' X 6' deep, the center of
 The Onida North lode, unsurveyed, joins this
 which bears S. 2° W. 248 ft. from Ger. No. 1.
 group on the north, O. D. M. Gaddis and J. E. Perry,
 Value ----- \$25.00
 claimants.

No. 3, a shaft, 4 ft. wide, 8 ft. long and 10 ft.

Leon H. Foster
 U. S. Mineral Surveyor.
 corner at 875 ft. from the north end center.

Value ----- \$50.00

1/2 Value of Improvement No. 4, Seneca lode,
 main working shaft. ----- \$3750.00

**** Instrument and Meridian ****

This survey was made with a Berger & Son's Mining
 transit and a 500 and 100 ft. steel tape.
 The Meridian was determined by direct observation
 on the sun.

*** REPORT ***

The side and end lines were measured direct on the
 Ground.
 The main working shaft, timbered, two compartment
 and 250 ft. deep, was sunk on the west side of the vein
 which extends from the two claims of this survey and for
 the benefit of these two claims. I value this at \$7500.00
 and credit each claim with one half.
 The section corner on the north between 3 and 4, T.
 22 N. R. 17 W. G. & S. R. B. & M. is a two and one half
 inch pipe, with a brass cap marked "T", properly set
 and in the recent corner to this survey that could be
 identified. Being unable to find the quarter corner between
 sections 3 & 4, the corner of sections 3-4-9-10, the
 quarter corner between sections 3 & 10 on the corner of
 sections 2-3-10-11, I therefore calculated the true

FINAL OATHS FOR SURVEYS.

LIST OF NAMES.

A list of the names of the individuals employed by Leon H. Foster
 United States Mineral Surveyor, to assist in running, measuring, and marking the lines, corners, and
 boundaries described in the foregoing field notes of the survey of the mining claim of O. D. M. Gaddis
 known as the Seneca and Oneida South lodes
 and showing the respective capacities in which they acted.

R. B. Blum, Chainman.
XXXXXXXXXXXXXXXXXX, Chainman.
XXXXXXXXXXXXXXXXXXXX, Axman.
XXXXXXXXXXXXXXXXXXXX, Flagman.

FINAL OATHS OF ASSISTANTS.

WXX I, R. B. Blum
 and XXXXXXXXXXXXXXXXXXXX, do solemnly swear that I assisted
Leon H. Foster, United States Mineral Surveyor, in marking the corners and surveying
 the boundaries of the mining claim of O. D. M. Gaddis
 known as the Seneca and Oneida South lodes
 represented in the foregoing field notes as having been surveyed by said mineral surveyor and under his
 direction; and that said survey has been in all respects, to the best of our knowledge and belief, faithfully
 and correctly executed, and the corner and boundary monuments established according to law and the instruc-
 tions furnished by the United States Surveyor-General for Arizona

R. B. Blum, Chainman.
 _____, Chainman.
 _____, Axman.
 _____, Flagman

Subscribed and sworn to by the above-named persons before me this 8th
 day of April, 1919.

J. J. Morgan
 Clerk Superior Court

FINAL OATH OF U. S. MINERAL SURVEYOR.

I, Leon H. Foster, U. S. Mineral Surveyor, do solemnly swear that, in pursuance of instructions received from the United States Surveyor General for Arizona, dated March 8, 1919, I have, in strict conformity to the laws of the United States, the official regulations and instructions thereunder, and the instructions of said Surveyor General, faithfully and correctly executed the survey of the Mining Claim of O. D. M. Gaddis, known as the SENECA and ONEIDA SOUTH lodes, situate in Wallapai Mining District, Mohave County, Arizona, in Sections 3 & 10, Township No. 22 N., Range No. 17 West, G. & S. R. B. & M. and designated as Survey No. 3575, as represented in the foregoing field notes, which accurately show the boundaries of said mining claim as distinctly marked by monuments on the ground, and described in the attached copy of the location certificate, which was received by me from the Surveyor General with said instructions, and that all the corners of said survey have been established and perpetuated in strict accordance with the law, official regulations and instructions thereunder; and I do further solemnly swear that the foregoing are the true and original field notes of said survey and my report therein, and that the labor expended and improvements made upon said mining claim by claimant or His grantors are as therein fully stated, and that the character, extent, location, and itemized value thereof are specified therein with particularity and full detail, and that no portion of said labor or improvements so credited to this claim has been included in the estimate of expenditures upon any other claim.

Leon H. Foster
U. S. Mineral Surveyor.

Subscribed and sworn to by the said Leon H. Foster
U. S. Mineral Surveyor, before me J. T. Morgan, Clerk of the Superior Court this 8th day of April, 1919.

J. T. Morgan
Clerk Superior Court

U. S. SURVEYOR-GENERAL'S FINAL CERTIFICATE ON FIELD NOTES.

Department of the Interior,

OFFICE OF U. S. SURVEYOR-GENERAL,

Phoenix, Arizona.

July 31, 1919

I, U. S. Surveyor-General for District of Arizona

do hereby certify that the foregoing transcript of the Field Notes, return and approval of the survey of the mining claim of O. D. M. Gaddis

known as the SENECA and ONEIDA SOUTH lodes

situate in WALLAPAI

Mining District, MOHAVE County, ARIZONA

in Section 3 & 10, Township No. 22 N., Range No. 17 W., and

designated as Survey No. 3575, has been correctly copied from the originals on file in

this office; that said Field Notes furnish such an accurate description of said mining claim as will, if incorporated into a patent, serve fully to identify the premises, and that such reference is made therein to natural objects or permanent monuments as will perpetuate and fix the locus thereof.

And I further certify that five hundred dollars' worth of labor has been expended or improvements made upon said mining claims by claimant or his grantors, and that said improvements consist of 6 shafts, 1 cut and 1 tunnel, total value \$8520. As improvement No. 4 on the Seneca is a common improvement for the benefit and development of both of the claims of this survey, an undivided one-half interest therein, value \$3750, is properly credited to each of the claims in this group.

and that no portion of said labor or improvements has been included in the estimate of expenditures upon any other claim.

I further certify that the plat thereof, filed in the U. S. Land Office at Phoenix, Arizona is correct and in conformity with the foregoing Field Notes.

Frank P. Trott

United States Surveyor-General for Arizona.

SURVEYOR-GENERAL'S CERTIFICATE OF APPROVAL OF FIELD
NOTES AND SURVEY OF MINING CLAIM.

Department of the Interior,

OFFICE OF U. S. SURVEYOR-GENERAL,

Phoenix, Arizona.

July 31, 1919

I, U. S. Surveyor-General for District of Arizona

do hereby certify that the foregoing and hereto attached Field Notes and Return of the Survey of the
Mining Claim of

O. D. M. Gaddis

, known as the

SENECA and ONEIDA SOUTH lodes

situate in WALLAPAI mining district,

MOHAVE

County,

ARIZONA

in Sections 3 & 10, Township No. 22 N., Range No. 17 W.

, designated as Survey No. 3575

executed by Leon H. Foster, United States Mineral

Surveyor, March 20-30, 1919, under my instructions dated

March 11, 1919, have been critically examined and the necessary cor-

rections and explanations made, and the said Field Notes and Return, and the Survey they describe,

are hereby approved. A true copy of the copy of the location certificate filed by the applicant for

survey is included in the field notes.

Frank O. Foster

U. S. Surveyor-General for Arizona.