

MINERAL SURVEY No. 3956

Arizona Land District.

FIELD NOTES

OF THE SURVEY OF THE MINING CLAIM OF

Granberg Silver Mines Corporation,

Loc. 246, Kingman, Arizona

KNOWN AS THE

Twin Basin, Black Eagle, Black Eagle Annex, Black Warrior,

Sacotash & Fraction lodes, Wallapai Mining District,

Mohave County, Arizona

Section 18 & 13, Township 22 N., Range 17 & 18 W.

Surveyed under instructions dated July 5th., 1924

by L. H. Foster

U. S. Mineral Surveyor.

Claim located see back, 19

Survey commenced Sept. 10th, 19 24

Survey completed October 20th., 19 24

Address of claimant's Atty. Louis L. Wallace
P.O. Box 246, Kingman, Arizona

DATES OF AMENDED LOCATIONS.

see back

MINERAL SURVEY No. 8833

Claim	Located	Amended
Twin Basin	Feb. 10th. 1915	June 27th. 1924
Black Eagle	April 19th 1917	" " "
Black Eagle Annex	Jan. 2nd. 1918	" " "
Black Warrior	April 5th. 1917	" " "
Sacotash	Nov. 18th. 1917	" " "
Fraction	Aug. 12th. 1917	" " "

Grandby Silver Mines Corporation

\*\*\*\*\*

Twin Basin, Black Eagle, Black Eagle Annex, Black Warrior

Sacotash & Fraction lodes, Black Eagle

Mohave County, Grandby

Range 18 & 19, Township 22 N., Range 17 & 18 W.

Survey under instructions dated July 28th, 1924

I. H. Foster

see back

Sept. 10th

October 20th

Atty. Louis L. Wallace

P.O. Box 248, Kingman, Arizona

MAPS OF AMENDED LOCATIONS

see back

feet

TWIN BASIN LODE

Beginning Cor. No. I.

A redwood post, 4 ins. square, 4 ft. long, with a nail at the exact corner, set 15 ins. in the ground, in a mound of earth and stone, scribed TB-1-3956.

The <sup>w.</sup> <sup>of</sup> I/4 corner ~~between~~ sections ~~15-18~~, T. 22 N. R. ~~18~~ & 17 W. G. & S. R. B. & M. bears S. 46° 32' W. 671.91 feet.

Cor. No. 4, Twins-lode, Sur. No. 3612, bears S. 44° 16' 30" E. 519.91 feet.

Thence N. 54° 47' E.

128.64 To Cor. No. I, Fraction lode, This survey.

314.64 To the north end center post of the location.

428.64 To the south end center post, Fraction lode, this survey.

629.28 To Cor. No. 2.

A redwood post, 4 ins. square, 4 ft. long, with a nail at the exact corner, set 15 ins. in the ground, in a mound of earth and stone, scribed TB-2-3612.

Identical with Cor. No. I, Black Eagle Annex lode, this survey.

Thence S. 17° 40' E.

1500.00 To Cor. No. 3.

A redwood post, 4 ins. square, 4 ft. long, with a nail at the exact corner, set 15 ins. in the ground, in a mound of earth and stone, scribed TB-3-3612.

Identical with Cor. No. 4, Black Eagle Annex lode, this survey.

Thence S. 54° 47' W.

314.64 To the south end center post of the location.

629.28 To Cor. No. 4.

Mineral Survey No. 3956

feet

Twin Basin lode, continued.

A redwood post, 4 ins. square, 4 ft. long, with a nail at the exact corner, set 15 ins. in the ground, in a mound of earth and stone, scribed TB-4-3956.

Thence N. 17° 40' W.

801.47 Intersect line 4-1, Twins lode, Sur. No. 3612, at S. 27° 07' W. 330.12 feet and N. 27° 07' E. 269.88 feet from Cors. No. 4 and 1, respectively.

1266.58 Intersect line 3-4, Twins lode, Sur. No. 3612. at S. 62° 53' E. 1172.36 feet and N. 62° 53' W. 327.64 ft. from Cors. No. 3 and 4, respectively.

1500.00 To Cor. No. 1, the place of beginning.

All corners are identical with the location.

Variation at all corners is 15° 30' East.

No. bearing objects available.

\*\*\*\*\*

Fraction lode

Beginning Cor. No. 1.

A redwood post, 4 ins. square, 4 ft. long, with a nail at the exact corner, set 15 ins. in the ground, in a mound of earth and stone, scribed F-1-3956.

The <sup>W</sup>1/4 section corner <sup>of</sup> between sections 13-18, T 22 N. R. 18 & 17 W. G. & S. R. B. & M. bears S. 47° 51' 30" W. 799.46 feet.

On line I-2, Twin Basin lode, this survey, at 128.64 ft. from Cor. No. 1.

Thence N. 54° 57' W.

926.20 To Cor. No. 2.

A redwood post, 4 ins. square, 4 ft. long, with a nail at the exact corner, set 15 ins. in the ground, in a mound of earth and stone, scribed F-2-3956.

Mineral Survey No. 3956

feet

Fraction lode, continued

Thence N. 54° 47' E.

300.00 To the north end center post of the location.

600.00 To Cor. No. 3.

A redwood post, 4 ins. square, 4 ft. long, with a nail at the exact corner, set 15 ins. in the ground, in a mound of earth and stone, scribed F-3-3956.

Thence S. 54° 57' E.

926.20 To Cor. No. 4.

A cross chiseled on the north face of a granite ledge, 3 ft. high, 4 ft. thick and 25 ft. long, marked F-4-3956.

Thence S. 54° 47' W.

99.36 To Cors. No 2 and I, Twin Basin and Black Eagle Annex lodes, this survey, respectively.

300.00 To the south end center post of the location.

414.00 To the north end center post, Twin Basin lode, this survey.

600.00 To Cor. No. I, the place of beginning.

All corners are identical with the location.

Variation, all corners, 15° 30' East.

No bearing objects available.

\*\*\*\*\*

Black Eagle Annex lode

Beginning Cor. No. I.

A redwood post, previously described, scribed BEA-1-3956.

Identical with Cor. No. 2, Twin Basin lode, this survey, previously described.

The <sup>W</sup>I/4 corner, <sup>of</sup> between sections 13 & 18, T. 22 N. R. 18 & 17 W. bears S. 50° 31' 30" W. 1277.85 ft.

Thence N. 54° 47' E.

99.36 To Cor. No. 4, Fraction lode, this survey

Mineral Survey No. 3956

feet

Black Eagle Annex lode, continued

314.64 To the north end center post of the location.

481.20 Intersect line 4-I, Black Warrior lode, this survey, at S. 52° 13' E. 149.54 ft. from Cor. No. 1,

629.28 To Cor. No. 2.

A redwood post, 4 ins. square, 4 ft. long, with a nail at the exact corner, set 15 ins. in the ground, in a mound of earth and stone, scribed BEA-2-3956.

Thence S. 17° 40' E.

249.70 To Cor. No. 2, Black Eagle lode, this survey, and intersect line 4-I, Black Warrior lode, this survey, at S. 52° 13' E. 398.50 ft. from Cor. No. 1.

1302.59 Intersect line 4-I, Black Eagle lode, this survey at S. 52° 13' E. <sup>808.48</sup> ~~808.42~~ ft. from Cor. No. 1.

1500.00 To Cor. No. 3.

A redwood post, 4 ins. square, 4 ft. long, with a nail at the exact corner, set 15 ins. in the ground, in a mound of earth and stone, scribed BEA-3-3956.

Thence S. 54° 47' W.

314.64 To the south end center post of the location.

629.28 To Cor. No. 4.

A redwood post, previously described, scribed BEA-4-3956.

Identical with Cor. No. 3, Twin Basin lode, this survey.

Thence N. 17° 40' W.

1500.00 To Cor. No. 1, the place of beginning.

All corners are identical with the location.

Variation, all corners, 15° 30' East.

No bearing objects available.

\*\*\*\*\*

Mineral Survey No. 3956

feet

Black Warrior lode

Beginning Cor. No. 1.

A redwood post, 4 ins. square, 4 ft. long, with a nail at the exact corner, set 15 ins. in the ground, in a mound of earth and stone, scribed BW-1-3956.

The <sup>W</sup>1/4 corner between sections 13-18, T. 22 N. R. 16 & 17 W. bears S. 46° 55' W. 1748.18 ft.

Thence N. 32° 10' E.

300.00 To the north end center post of the location.

600.00 To Cor. No. 2

A redwood post, 4 ins. square, 4 ft. long, with a nail at the exact corner, set 15 ins. in the ground, in a mound of earth and stone, scribed BW-2-3956.

Thence S. 52° 13' E.

1500.00 To Cor. No. 3.

A redwood post, 4 ins. square, 4 ft. long, with a nail at the exact corner, set 15 ins. in the ground, in a mound of earth and stone, scribed BW-3-3956.

Thence S. 32° 10' W.

300.00 To the south end center post of the location.

600.00 To Cor. No. 4.

A redwood post, 4 ins. square, 4 ft. long, with a nail at the exact corner, set 15 ins. in the ground, in a mound of earth and stone, scribed BW-4-3956.

Identical with Cors. No. 2 and 3, Sacotash and Black Eagle lodes, this survey, respectively.

Thence N. 52° 13' W.

1101.50 To Cor. No. 2, Black Eagle lode, this survey and intersect line 2-3, Black Eagle Annex lode, this survey, at S. 17° 40' E. 249.70 ft. from Cor. No. 2.

Mineral Survey No. 3956

feet

Black Warrior lode, continued

1350.46

Intersect line I-2, Black Eagle Annex lode, this survey at S. 54° 47' W. 148.08 ft. from Cor. No. 2.

1500.00

To Cor. No. 1, the place of beginning.  
All corners are identical with the location.  
Variation, all corners, 15° 30' East  
No bearing objects available.

\*\*\*\*\*

Black Eagle lode

Beginning Cor. No. I.

A redwood post, 4 ins. square, 4 ft. long, with a nail at the exact corner, set 15 ins. in the ground, in a mound of earth and stone, scribed BE-I-3956.

The <sup>W</sup>1/4 corner between sections 18-18, T.22 N. R. 18 & 17 W. bears S. 70° 50' W. 1346.84 feet.

Thence N. 32° 10' E.

300.00

To the north end center post of the location.

600.00

To Cor. No. 2.

A redwood post, 4 ins. square, 4 ft. long, with a nail at the exact corner, set 15 ins in the ground, in a mound of earth and stone, scribed Be-2-3956.

On line 2-3 and I-4, Black Eagle Annex and Black Warrior lodes, this survey, at S. 17° 40' E. 249.70 feet and S. 52° 13' E. 398.50 feet from Cors. No. 2 and I respectively.

Thence S. 52° 13' E.

1101.50

To Cor. No 3.

A redwood post, previously described, scribed BE-3-3956.

Mineral Survey No. 3956

feet

Black Eagle lode, continued

Identical with Cors. No. 4 and 2, Black Warrior and Sacotash lodes, this survey, respectively.

Thence S. 32° 10' W.

300.00 To the south end center of the location.

Identical with the north end center of the

Sacotash lode, this survey.

600.00 To Cor. No. 4.

A redwood post, 4 ins. square, 4 ft. long, with a nail at the exact corner, set 15 ins. in the ground, in a mound of earth and stone, scribed BE-4-3956.

Identical with Cor. No. 1, Sacotash lode, this

survey.

Thence N. 52° 13' W.

293.02 Intersect line 2-3, Black Eagle Annex lode, this survey, at N. 17° 40' W. 197.41 ft. from Cor. No. 3.

1101.50 To Cor. No. 1, the place of beginning.

All corners are identical with the location.

Variation, all corners, 15° 30' East.

No. bearing objects available.

\*\*\*\*\*

Sacotash lode

Beginning Cor. No. 1.

A redwood post previously described, scribed

S-I-3956.

Identical with Cor. No. 4, Black Eagle lode,

this survey.

The <sup>w</sup>I/4 corner between sections 18 & 13, T. 22 N.

R. 17 & 18 W. bears N. 83° 48' W. 2155.39 ft.

Thence N. 32° 10' E.

300.00 To the north end center post of the location.

Identical with the south end center of the

Black Eagle lode, this survey.

Mineral Survey No. 3956

feet

Sacotash lode, continued

600.00 To Cor. No. 2.

A redwood post, previously described, scribed S-2-3956. and Cor. No. 4 Black Warrior

Identical with Cor. No. 3, Black Eagle lode, this survey.

To the south end center of the location. Thence S. 52° 13' E.

1500.00 To Cor. No. 3.

A redwood post, 4 ins. square, 4 ft. long, with a nail at the exact corner, set 15 ins. in the ground, in a mound of earth and stone, scribed S-3-3956.

Thence S. 32° 10' W.

300.00 To the south end center post of the location.

600.00 To Cor. No. 4.

A redwood post, 4 ins. square, 4 ft. long, with a nail at the exact corner, set 15 ins. in the ground, in a mound of earth and stone, scribed S-4-3956.

Thence N. 52° 13' W.

1500.00 To Cor. No. 1, the place of beginning.

All corners are identical with the location.

Variation, all corners, 15° 30' East.

No bearing objects available.

\*\*\*\*\*

Lode Lines

As near as can be determined from present developments, the lode lines of the different claims of this survey, extend from their respective discovery points, as follows;-

Twin Basin lode;- N. 17° 40' W. 172.00 ft. and S. 17° 40' E. 1328.00 ft. from the discovery shaft.

Black Eagle Annex;- N. 17° 40' W. 278.00 ft. and S 17° 40' E. 1222.00 ft. from the discovery cut.

Fraction;- N. 54° 57' W. 640.20 ft. and S. 54° 57' E. 286.00 ft. from the discovery cut.

Mineral Survey No. 3956

Lode Lines, continued

Black Eagle; N. 52° 13' W. 811.50 ft. and S. 52° 13' E. 290.00 ft. from the discovery shaft.

Black Warrior; N. 52° 13' W. 870.00 ft. and S. 52° 13' E. 630.00 ft. from the discovery shaft.

Sacotash; N. 52° 13' W. 320 ft. and S. 52° 13' E. 1180.00 ft. from the discovery cut.

\*\*\*\*\*

LOCATION

This group of lode claims is located in the Wallapai Mining District, Mohave County, Arizona, in sections 18 & 13, T. 22 N. R. 17 & 18 W. G. & S. R. B. & M.

\*\*\*\*\*

AREAS

Claim	Acres
Twin Basin	20.661
Area in conflict with Twins lode,	
Sur. No. 3612	1.242 Ac.
Black Eagle Annex	20.661
Area in conflict with Black	
Eagle lode, this survey	5,541 Ac.
Fraction;	12.008
Black Eagle	15.099
Black Warrior	20.562
Area in conflict with Black	
Eagle Annex, this survey	0.405 Ac.
Sacotash	20.562

\*\*\*\*\*

Expenditure of Five Hundred Dollars

I certify that the value of the improvements and labor, made upon or for the benefit of this group of lode claims, by the claimant or its grantors, is not less

12

Mineral Survey No. 3956

Improvements, continued

than five hundred dollars for each and every lode claim embraced within the group and are as follows:-

Twin basin lode;

No. 1 - The discovery shaft, 5 by 9 ft. by 75 ft. deep with a drift running S. 17° 40' E. 4 by 6 ft. by 30 ft. long, valued at \$2235, one half of which is credited to the Fraction lode, this survey. On the lode line at 172 ft. from the north end center. I/2 of above value to this claim -----\$1117.50

Fraction lode;

No. 1 ; - The discovery cut, 12 ft. face, 5 ft. wide and extending East 9 ft. to its mouth. The face is on the lode line at 286.00 ft. from the south end center.

Value ----- \$50.00

I/2 value of No. 1, Twin Basin lode -----\$1117.50

Black Eagle Annex;

No. 1. ; - The discovery cut, 10 ft. face, 5 ft. wide extending N. 30° E. 17 ft. The face is on the lode line, at 278 ft. from the north end center.

Value ----- \$50.00

No. 2 - A shaft, 4 by 6 ft. by 26 ft. deep. The center bears S. 6° W. 395 ft. from Cor. No. 2.

Value ----- \$500.00

Black Warrior;

No. 1 - The discovery shaft, 5 by 7 by 10 ft. deep on the lode line at 630 ft. from the south end center.

Value ----- \$50.00

No. 2 - A shaft, 4 by 6 ft., by 22 ft. deep. The center bears N. 73° W. 540 ft. from Cor. No. 3.

Value ----- \$475.00

No. 3 - A cut, 7 ft. face, 5 ft. wide, extending North 17 ft. The center of the face bears N. 73° W. 510 ft. from Cor. No. 3.

Value ----- \$35.00

and labor made upon or for the benefit of this group of lode claims by the claimant or its grantors is not less

Mineral Survey No. 3956

Improvements, continued

Black Eagle;

No. 1- The discovery shaft, 5 by 7 ft. by 110 ft. deep, with a drift from the bottom 4 by 6 ft. running S. 50° E. 50 ft. The center is on the lode line at 290 ft. from the south end center. Valued at \$3250, one half of which is credited to the Sacotash lode, this survey.

1/2 of above value to this claim ----\$1625.00

No. 2- An open cut, 10 ft. face, 5 ft. wide, extending S. 10° E. 20 ft. and a shaft 4 by 6 ft. by 10 ft. deep. Center of face bears N. 78° W. 330 ft. from Cor. No.

3. Value ----- \$115.00

No. 3- An open cut, 10 ft. face, 5 ft. wide, extending West 15 ft. and a tunnel running East, 4 by 6 ft. by 30 ft. long. Center of face bears N. 63° W. 455 ft.

from Cor. No. 3. Value ----- \$350.00

No. 4- An open cut, 10 ft. face, 6 ft. wide, extending West 10 ft. Center of face bears N. 63° W. 635 ft. from Cor. No: 3. Value ----- \$50.00

Sacotash lode;

No. 1- The discovery cut, 10 ft. face, 6 ft. wide, extending N. 50° W. 15 ft. with a shaft, 6 by 7 ft. by 7 ft. deep. On the lode line at 320 ft. from the north end center.

Value ----- \$115.00

No. 2- An open cut, 6 ft. face, 4 ft. wide, extending N. 50° W. 10 ft. Center of face bears S. 32° E. 675 ft. from Cor. No. 2.

Value ----- \$35.00

1/2 value of No. 1, Black Eagle lode \$1625.00

Mineral Survey No. 3956

REPORT

All side lines and end lines and all other lines were run directly on the ground.

The corners of the Twins lode, Sur. No. 3612, tied to in this survey are redwood posts, properly set and marked.

After diligent search and being unable identify anything as the 1/4 corners between sections 7 & 10 I tie all claims to the 1/4 corner between sections 18 & 13, T. 22 N. R. 17 & 18 W. G. & S. R. B. & M. which is a one inch iron pipe, with a brass cap, properly set and marked.

Improvement No. I, Twin Basin lode, is a 5 by 9 ft. shaft, 75 ft. deep, with a drift from the bottom, running S. 17° 40' E. 30 ft. and was sunk to develop the vein thru the Twin Basin and Fraction lodes and it is the intent to drift north and south from this shaft into both claims and is therefore a common improvement for the two, valued at \$2235.00, making \$1117.50 for each.

Improvement No. I, Black Eagle lode, is a shaft 5 by 7 ft. by 110 ft. deep, with a drift from the bottom running S. 50° E. 50 ft. and can be extended into the Sacotash lode and is intended as a common improvement for both claims, valued at \$3250, making \$1625.00 for each.

\*\*\*\*\*

Adjoining and Conflicting Claims

This group is joined on the west by the Twins lode, Sur. No. 3612 and on all other sides by Public domain.

\*\*\*\*\*

Instrument and Meridian

This survey was made with a 100 and 500 ft. steel tape and with a Berger & Sons mining transit.

FINAL SURVEYS

Mineral Survey No. 3956

Instrument & Meridian

The meridian was determined by direct observation on the sun.

\*\*\*\*\*

The differences between this survey and the location notices are due to error in the latter.

~~December 15th, 1924~~

*L. H. Foster*

U.S. Mineral Surveyor.

FINAL OATHS OF ASSISTANTS

L. H. Foster

L. H. Foster

*Paul A. Harrison*

*Wm. J. ...*  
*...*

4-686.

# FINAL OATH OF U. S. MINERAL SURVEYOR.

I, L. H. Foster, U. S. Mineral Surveyor, do solemnly swear that, in pursuance of instructions received from the United States Surveyor General for Arizona, dated July 5th. 1924, I have, in strict conformity to the laws of the United States, the official regulations and instructions thereunder, and the instructions of said Surveyor General, faithfully and correctly executed the survey of the Mining Claim of Granberg Silver Mines Corporation, known as the Twin Basin, Black Eagle, Black Eagle Annex, Black Warrior, Sacotash & Fraction lodes, situate in Wallapai Mining District, Mohave County, Arizona, in Section 18 & 13, Township No. 22 N., Range No. 17 & 18 W. G. & S.R.B. & M., and designated as Survey No. 3956, as represented in the foregoing field notes, which accurately show the boundaries of said mining claim as distinctly marked by monuments on the ground, and described in the attached copy of the location certificate, which was received by me from the Surveyor General with said instructions, and that all the corners of said survey have been established and perpetuated in strict accordance with the law, official regulations and instructions thereunder; and I do further solemnly swear that the foregoing are the true and original field notes of said survey and my report therein, and that the labor expended and improvements made upon said mining claim by claimant or its grantors are as therein fully stated, and that the character, extent, location, and itemized value thereof are specified therein with particularity and full detail, and that no portion of said labor or improvements so credited to this claim has been included in the estimate of expenditures upon any other claim.

L. H. Foster  
U. S. Mineral Surveyor.

Subscribed and sworn to by the said L. H. Foster  
U. S. Mineral Surveyor, before me Mary E. Carrow  
Melany Public this 16  
day of December, 19 24

Mary E. Carrow  
Melany Public

5-1044

*Commission Expires*  
*Mar 20/1927*

U. S. SURVEYOR-GENERAL'S FINAL CERTIFICATE ON FIELD NOTES.

Department of the Interior,

OFFICE OF U. S. SURVEYOR-GENERAL,

Phoenix, Arizona.

April 21, 1925

I, U. S. Surveyor-General for Arizona

do hereby certify that the foregoing transcript of the Field Notes, return and approval of the survey of the mining claim of

Granberg Silver Mines Corporation  
TWIN BASIN, BLACK EAGLE, BLACK EAGLE ANNEX, BLACK WARRIOR,  
known as the SACOTASH, and FRACTION lodes

situate in Wallapai

Mining District, Mohave County, Arizona

in Sections 13 & 18, Township No. 22 N., Range No. 17 and 18 W., and

designated as Survey No. 3956, has been correctly copied from the originals on file in

this office; that said Field Notes furnish such an accurate description of said mining claim as will, if incorporated into a patent, serve fully to identify the premises, and that such reference is made therein to natural objects or permanent monuments as will perpetuate and fix the locus thereof.

And I further certify that five hundred dollars' worth of labor has been expended or improvements made upon said mining claims by claimant or its grantors, and that said improvements consist of 7 shafts, 8 cuts, 1 tunnel and 2 drifts, total value \$7310.

and that no portion of said labor or improvements has been included in the estimate of expenditures upon any other claim.

I further certify that the plat thereof, filed in the U. S. Land Office at Phoenix, Arizona is correct and in conformity with the foregoing Field Notes.

Charles H. Donohoe

United States Surveyor-General for Arizona.

4-687

**SURVEYOR GENERAL'S CERTIFICATE OF APPROVAL OF FIELD NOTES  
AND SURVEY OF MINING CLAIM**

**DEPARTMENT OF THE INTERIOR  
OFFICE OF U. S. SURVEYOR GENERAL**

..... Phoenix, Arizona, .....

..... April 21, 1925 .....

I, U. S. Surveyor General for ..... Arizona .....

do hereby certify that the foregoing and hereto attached Field Notes and Return of the Survey of the  
Mining Claim of .....

..... Granberg Silver Mines Corporation .....

....., known as the  
TWIN BASIN, BLACK EAGLE, BLACK EAGLE ANNEX, BLACK WARRIOR,  
..... SACOTASH, and FRACTION lodes .....

situate in ..... Wallapai ..... mining district,

..... Mohave ..... County, ..... Arizona .....

in Section s. 13 & 18 ..... Township No. 22 N. ...., Range No. 17 & 18 W.

....., designated as Survey No. 3956 .....

executed by ..... L. H. Foster ....., U. S. Mineral

Surveyor, ..... September 10 - October 20 ....., 1924, under my instructions dated

..... July 5 ....., 1924, have been critically examined and the necessary

corrections and explanations made, and the said Field Notes and Return, and the survey they describe,

are hereby approved. The certified copy of the location certificate filed by the applicant for survey is

on file in this office and a true copy of said certified copy of said location certificate is included and

made a part of the transcript of the field notes.

*Charles M. Donohoe*

U. S. Surveyor General for ..... Arizona .....