

UNITED STATES
DEPARTMENT OF THE INTERIOR
BUREAU OF LAND MANAGEMENT



MINERAL SURVEY NO. 4384

Arizona Land District.

FIELD NOTES

Of The Survey Of The Mining Claim Of

C.M. d'Autremont and H.W. Hasselgren
trustees

Known As The

(Tombstone Extension, Tombstone Extension *1, Tombstone Extension *2
Tombstone Extension *3, Tombstone Extension *4, Tombstone Extension No.5
Blind Ledge, Blind Ledge No.2, Blind Ledge No.3, Tombstone Mining District,
Chance and Chance No.1 lode mining claims)
Cochise County, Arizona

Sections 12 and 13 Township No. 20 South Range No. 22 East G. & S.R. M
7 and 18 Township No. 20 South Range No. 23 East Arizona

Surveyed under order dated August 31, 1953

by *[Signature]*
Mineral Surveyor.

Claim located See other side, 19

Survey commenced September 15, 1953

Survey completed November 18, 1953

Address of claimant Route 1, Box 134, Hemet, California.

DATES OF AMENDED LOCATIONS

	Claim Located	Amended
Tombstone Extension lode	May 1, 1929 ✓	
Tombstone Extension *1 lode	May 1, 1929 ✓	
Tombstone Extension *2 lode	May 1, 1929 ✓	
Tombstone Extension *3 lode	May 1, 1929 ✓	
Tombstone Extension *4 lode	July 1, 1930 ✓	
Tombstone Extension No.5 lode	May 1, 1929 ✓	June 15, 1953 ✓
Blind Ledge lode	Nov.14, 1929 ✓	June 2, 1930 ✓
Blind Ledge No.2 lode	Nov.14, 1929 ✓	Aug. 15, 1931 ✓
Blind Ledge No.3 lode	June 2, 1930 ✓	June 15, 1953 ✓
Chance lode	June 20, 1930 ✓	June 15, 1953 ✓
Chance No.1 lode	July 1, 1934 ✓	June 15, 1953 ✓

Survey No. 4384

This survey was made with a Buff & Buff transit with horizontal limb 5 ins. diam. having two opposite verniers; the verniers read to one minute of arc. The instrument was in good condition at the time of the survey and all adjustments were in good order.

All azimuths in this record were determined by the method of deflection angles referred to the meridian determined by the following observation:

Wednesday, September 16, 1953 at Corner No. 3, Tombstone Extension # 1, in latitude $31^{\circ}41'23''$ and longitude $110^{\circ}03'08''$ W., I made a series of altitude observations upon the sun for azimuth at approximately equal time intervals, three each with the telescope in direct and reversed positions, bisecting the sun and reading the horizontal angle from the reference point S E to the sun.

Mean time of observation, 105 meridian, standard time - 9h 48m A.M.
Apparent time ----- - 9h 22m 32.8s

Declination of sun at mean time of observation $2^{\circ}34'43.2''$

Mean observed vertical angle to sun's center $-45^{\circ}00'03''$

Mean horizontal angle from reference point- $1^{\circ}24'$

True bearing of reference point ----- S. $58^{\circ}52'00''$ E.

The lines were measured with a Keuffel & Esser steel tape 300 ft. in length, the first foot graduated to tenths and hundredths; and a 100 ft. Lufkin steel tape, graduated to feet, tenths and hundredths; both tapes were compared with a standard and were correct at the time of the survey.

All lines and connections of this survey were run by direct methods, the magnetic declination observed at each corner of the survey gave a uniform value of $14^{\circ}30'$ E.

Feet

Tombstone Extension lode

At Cor. No.1 of the Tombstone Extension lode, identical with Cor. Nos. 1,2 and 2, Tombstone Extension # 1, Tombstone Extension # 4 and Tombstone Extension No.5 lodes respectively of this survey.

Set an iron post, $3\frac{1}{2}$ ft. long, 2 ins. diam. 18 ins. in the ground, surrounded by a mound of stone to top with leaden cap, mkd 1 T Ex, 1 T Ex # 1, 2 T Ex # 4 and 2 T Ex No.5 ; from which

The E. $\frac{1}{4}$ Sec. Cor. Sec. 13, T. 20 S., R. 22E. G. & S. R. M. bears S. $87^{\circ}51'30''$ E. 1148.52 ft. dist. ; a porphyry rock 10×12 ins showing 6 ins above ground firmly set and marked as described in the official record.

No other bearing objects are available.

Thence N. $58^{\circ}52'$ W.

300.0 Lode line; discovery point bears N. $30^{\circ}08'$ E., 1000.0 ft. dist

Set a pine post 4 ins. sq by $3\frac{1}{2}$ ft. long, firmly in the ground, surrounded by a mound of stone, mkd S. Cr. T Ex, N Cr. T. Ex 1

545.0 Wash 3 ft. wide, course northerly.

588.0 Wash 3 ft. wide, course northerly.

600.0 Cor. No.2, identical with Cor. Nos. 2,1 and 3, Tombstone Extension # 1, # 2 and # 3 lodes respectively of this survey.

Set an iron post $3\frac{1}{2}$ ft. long, 2 ins. diam. 18 ins in the ground surrounded by a mound of stone to top with leaden cap mkd 2 T Ex,

Survey No. 4384

Feet	
	<p>2 T. Ex 1, 1-T Ex 2, 3-T Ex 3- 4384</p> <p>No bearing objects are available.</p> <p>Thence N. 30° 08' E.</p>
30.0	Wash 3 ft. wide, course northerly
75.0	Wash 3 ft. wide, course northerly.
500.0	Road brs northwesterly and southeasterly
980.0	Wash 4 ft. wide, course northerly.
1500.0	<p>To Cor. No. 3, identical with Cor. Nos 2, 4 and 4, Tombstone Extension #3, Chance and Chance No.1 lodes respectively of this survey.</p> <p>Set an iron pipe 3 1/2 ft. long, 2 ins. diam. 18 ins in the ground surrounded by a mound of stone to top, with leaden cap mkd 3 TE Ex, 2 T Ex 3, 4 C and 4 C. 1 - 4384</p> <p>No bearing objects are available.</p> <p>Thence S. 58° 52' E.</p>
300.0	<p>Lode line; discovery point bears S. 30° 08' W., 500 ft. dist.</p> <p>Set an iron post 3 ins. diam by 4 ft. long firmly in the ground and surrounded by a mound of stone, mkd N Cr. T Ex, S. Cr. C.</p>
430.0	Wash 3 ft. wide, course northerly
460.0	Road brs northeasterly and southwesterly
549.0	S. right of way fence, U.S. Highway 80 brs S. 39° 13' E. and N. 39° 13' W.
600.0	<p>Cor. No.4, identical with Cors No. 3, Chance and Tombstone Extension #4 lodes of this survey.</p> <p>Set an iron post, 3 1/2 ft. long, 2 ins. diam. 18 ins. in the ground, surrounded by a mound of stone to top with leaden cap mkd 4 T. EX. 3 C, 3 T. Ex 4- 4384</p> <p>No bearing objects are available.</p> <p>Thence S. 30° 08' W.</p>
18.0	S. Right of way fence, U.S. Highway 80 brs S. 39° 13' E. and N. 39° 13' W.
950.0	Road brs northerly and southwesterly.
1200.0	Road brs northwesterly and southeasterly.
1500.0	Cor. No.1 and place of beginning.

	<p>TOMBSTONE EXTENSION #1 lode</p> <p>At Cor. No.1 of the Tombstone Extension #1 lode, identical with Cor. Nos. 1,2 and 2, Tombstone Extension, Tombstone Extension 4 and Tombstone Extension No. 5 lodes respectively of this Sur. heretofore described; from which</p>

Survey No. 4384

Feet.

The E. 1/4 Corner Sec. 13, T. 20 S., R. 22 E. bears S. 67° 51' 30" E
1148.52 ft. dist.

Thence N. 58° 52' W.

300.0 Lode line; discovery point bears S. 30° 49' W., 75 ft. dist.
identical with lode line Tombstone Extension lode of this Sur.
heretofore described.

545.0 Wash, 3 ft. wide, course northerly

588.0 Wash, 3 ft. wide, course northerly

600.0 Cor. No. 2, identical with cor. Nos 1, 2 and 3, Tombstone Ex. * 2,
Tombstone Extension and Tombstone Extension * 3 lodes respectively
of this sur., heretofore described.

Thence S. 30° 49' W.

330.0 Old road bears northerly and southerly.

830.0 Wash 15 ft. wide, course northwesterly.

1030. Center old US Highway 80, abandoned bears northwesterly and
southeasterly.

1500.0 Cor. No. 3, identical with Cor. No. 4, Tombstone Extension * 2 lode
of this survey.

Set an iron post 2 ins. diam., 3 1/2 ft. long, 18 ins in the ground,
surrounded by a mound of stone to top with leaden cap mkd 3 T EX 1,
4 T Ex 2 - 4384

Cor. No. 4 Sur. No. 2613 Mc Kinly lode, claimant unknown bears
S. 14° 45' 30" E., 354.6 ft. dist.

Cor. No. 2 Sur. No. 827 Omega lode bears S. 8° 7' 4" E., 287.16
ft. dist.

Thence S. 58° 52' E.

147.0 Wash 3 ft. wide, course northeasterly.

300.0 Lode line ; discovery point bears N. 30° 49' E., 1425.0 ft. dist.

Set an iron post 3 ins. diam., 4 ft. long, firmly in the ground
surrounded by a mound of stone mkd S. Cr. T. Ex 1

430.54 Intersect line 2-3 Sur. No. 827 Omega lode at N. 79° 21' E., 333.73 ft.
from Cor. No. 2 and S. 79° 21' W., 1466.27 ft. from Cor. No. 3

530.09 Intersect line 4-1 Sur. No. 2613 Mc Kinly lode at N. 79° 16' 30" E.,
369.87 ft. from Cor. No. 4 and S 79° 16' 30" W., 1141.53 ft. from Cor. No. 1

600.0 Cor. No. 4, identical with Cor. No. 3 Tombstone Extension No. 5 lode
of this Sur.

Set an iron post 2 ins. diam., 3 1/2 ft. long, 18 ins. in the ground
surrounded by a mound of stone mkd. 4 T Ex 1, 3 T Ex 5 - 4384.

Survey No. 4384

Feet.	No bearing objects are available. Thence N. 30° 49' E.
40.0	Wash 5 ft. wide, course northerly.
62.23	Intersect line 4-1 Sur. No. 2613 Ke Kinly lode at N.79° 16' 30", E., 463.27 ft. from Cor. No.4
150.69	Intersect line 2-3 Sur. No. 827 Omega lode At. N. 79°21' E., 559.87 ft. from Cor. No. 2
218.0	Wash 10 ft. wide, course northerly.
575.0	Wash 3 ft. wide, course northerly.
660.0	Old U.S. Highway 80 (abandoned) bears northwesterly and southeasterly
1500.0	Cor. No.1 and place of beginning.

TOMBSTONE EXTENSION * 2 Lode	
Beginning at Cor. No. 1 of the Tombstone Extension * 2 lode, identical with Cor. Nos. 2, 2 and 3, Tombstone Extension, Tombstone Extension * 1 and Tombstone Extension * 3 lodes respectively of this survey, heretofore described from which	
The E. 1/4 th Sect. 2 Sec. 15, T. 22 N., R. 22 E., bears S. 72° 59' 58" E. 1698.41 ft. dist. by a mound of stone to top with leaden cap mkd 1 T Ex 2, 2 T Ex 1,	
No other bearing objects are available Thence N. 58° 52' W.	
300.0	Lode line; discovery point bears S. 30° 49' W., 75 ft. dist. Set an iron post 3 ins. diam by 4 ft. long, firmly in the ground and surrounded by a mound of stone, mkd M. Cr. T. Ex 2, S. Cr. T. Ex 3
310.0	Old road brs northerly and southerly.
600.0	Cor. No.2, identical with Cor. Nos. 2, 3 and 4, Blind Ledge No.2, Blind Ledge and Tombstone Extension * 3 lodes respectively of this survey. Set an iron post 3 1/2 ft. long, 2 ins. diam., 18 ins in the ground, surrounded by a mound of stone to top with leaden cap mkd 2 T Ex 2, 2 B L 2, 3 BL, 4 T Ex 3 - 4384
No bearing objects are available. Thence S. 30° 49' W.	
200.0	Wash 5 ft. wide, course northerly.
565.0	Wash 15 ft. wide, course northerly
830.0	Old U.S. highway 80 (abandoned) bears northwesterly and southeasterly

Survey No. 4384

Feet	
930.0	Wash 5 ft. wide, course northwesterly
1500.0	Cor. No.3, identical with Cor. No.3 Blind ledge No.2 lode of this Sur.
	Set an iron post 3 1/2 ft. long, 2 ins diam. 18 ins in the ground surrounded by a mound of stone to top with leaden cap, mkd 3 T.Ex 2, 3 B L 2 - 4384
	No bearing objects are available.
	Thence S. 58° 52' E.
280.0	Wash 5 ft. wide, course northerly.
300.0	Lode line; discovery point bears N. 30° 49' E., 1425 ft. dist.
	Set an iron post 3 1/2 ft. long, 2 ins. diam. firmly in the ground and surrounded by a mound of stone, mkd S. Cr. T. Ex 2
600.0	Cor. No.4, identical with Cor. No.3 Tombstone Extension * 1 lode of this Sur., heretofore described.
	Thence N. 30° 49' E.
470.0	Center of Old U.S. Highway 80 (abandoned) , bears northwesterly and southeasterly.
670.0	Wash 15 ft. wide, course northwesterly.
1170.0	Old road bears northerly and southerly.
1500.0	Cor. No.1 and place of beginning
	TOMBSTONE EXTENSION * 3 lode.
	Beginning at Cor. No.1 of the Tombstone Extension * 3 lode identical with Cor Nos. 2,2 and 3, Blind Ledge, Blind ledge No.3 and Chance No.1 lodes respectively of this Sur., Set an iron post 3 1/2 ft long, 2 ins. diam., 18 ins. in the ground, surrounded by a md of stone to top with leaden cap, mkd.2 BL, 2BL 3, 3 C.1 -4384 ; from which The 1/4 Sec. Cor. bet Secs 12 and 13, T. 20 S. R. 22 E. bears N.60° 38' 17 " W., 1399.75 ft. dist. A sand stone Rock 8 x 12 ins. showing 8 ins above ground, firmly set and marked as described in the official record.
	Thence S. 58° 52' E.
300.0	Lode line; discovery point bears S. 30° 8' W., 500 ft. dist.
	Set an iron post 3 1/2 ft. long, 2 ins diam. firmly in the ground , surrounded by a mound of stone, mkd N. Cr. T.Ex 3 , S. Cr. C.1.
443.0	Wash 4 ft. wide, course northerly.
600.0	Cor. No. 2, identical with Cor. Nos. 3,4 and 4 , Tombstone Extension, Chance and Chance No. 1 lodes respectively of this sur. heretofore described.
	Thence S. 30° 08' W.

Survey No. 4384

Feet.	
520.0	Wash 4 ft. wide, course northerly.
1000.0	Old road bears northwesterly and southeasterly
1425.0	Wash, 3 ft. wide, course northerly.
1470.0	Wash, 3 ft. wide, course northerly.
1500.0	Cor. No.3, identical with Cor. Nos. 2,2 and 1, Tombstone Extension, Tombstone Extension *1 and Tombstone Extension *2 lodes respectively of this survey, heretofore described.
	Thence N. 58° 52' W.
300.0	Lode line; discovery point bears N. 30° 8' E., 1000. ft. dist. identical with lode line Tombstone Extension *2 lode of this Sur. heretofore described.
310.0	Old road bears northerly and southerly.
600.0	Cor. No.4, identical with Cor. Nos. 2,2 and 3, Tombstone Extension *2, Blind Ledge No2 and Blind Ledge lodes respectively of this Sur., heretofore described.
	Thence N. 30° 8' E.
521.0	Old road bears northerly and southerly
660.0	Old road bears northwesterly and southeasterly
801.0	Wash 3 ft. wide, course northwesterly and southeasterly
883.0	Wash 3 ft. wide, course northerly.
1500.0	Cor. No.1 and place of beginning.
	TOMBSTONE EXTENSION *4 Lode
	At Cor. No. 1 of the Tombstone Extension *4 lode, identical with Cor. No 1 Tombstone Extension No.5 lode of this Sur.
	Set an iron post, 3 1/2 ft. long, 2 ins. diam. 18 ins in the ground, surrounded by a mound of stone to top with leaden cap mkd. 1 T EX 4 1 T Ex 5 - 4384 from which
	The E. 1/4 Cor. Sec. 13, T. 20 S., R. 22 E. bears N. 67° 7' 58" E., 688.22 ft. dist.
	Cor. No. 6, Sur. No. 263, San Diego lode, claimant unknown bears S. 55° 41' 48" W., 526.29 ft. dist.
	No other bearing objects are available.
	Thence N. 58° 52' W.

Survey No. 4384

Feet.	
70.0	Road bears southwesterly and northeasterly.
210.0	Road bears northerly and southeasterly.
288.18	Intersect line 5-6 Sur. No. 263 San Diego lode at N. 22° 53' E. 483.67 ft. from Cor. No.6 and S. 22° 53' W., 931.53 ft. from Cor. No. 5.
300.0	Lode line; discovery point bears N. 30° 8' E., 1425.0 ft. dist. Set an iron post 2 ins. diam., 3 1/2 ft. long, firmly in the ground, surrounded by a mound of stone mkd S. Cr. T EX 4, N. Cr. T. Ex 5 - 4384.
315.0	Wash 3 ft. wide, course northeasterly.
540.0	Road bears northeasterly and southwesterly.
600.0	Cor. No. 2, identical with Cor. Nos. 1, 1 and 2 Tombstone Extension, Tombstone Extension No. 1 and Tombstone Extension No.5 lodes respectively of this Sur., heretofore described. Thence N. 30° 8' E.,
300.0	Road bears northwesterly and southeasterly.
550.0	Road bears northerly and southerly.
1482.0	W. right of way fence U.S. Highway 80 bears N. 39° 13' W. and S. 39° 13' E.
1500.0	Cor. No. 3, identical with Cor. Nos 3 and 4, Chance and Tombstone Extension lodes respectively of this Sur. heretofore described. Thence S. 58° 52' E.
300.0	Lode line; discovery point bears S. 30° 8' W., 75 ft. dist. Set an iron post 2 ft. long, 2 ins diam. 18 ins in the ground, surrounded by a mound of stone mkd N. Cr.T. Ex 4
330.0	Wash 10 ft. wide, course northerly.
460.04	Intersect W. line Sec. 18, T. 20 S., R. 23 E. S.S. 079031, Pat. 1128306 State of Ariz. from which point the 1/4 Cor. Secs. 13 & 18 T. 20 S., Rs 22 & 23 E., brs. S. 0° 2' 52" E., 1102.24 ft. dist.
547.0	E. right of way fence U.S. Highway 80 bears N. 39° 13' W. and S. 39° 13' E.
600.0	Cor. No.4 Set an iron post 3 1/2 ft. long, 2 ins. diam. 18 ins. in the ground surrounded by a mound of stone to top with leaden cap, mkd 4 T Ex 4-4384. from which Cor. No.5 Sur. No.263 San Diego lode brs. S. 65° 31' 17" W., 700.49 ft. dist. No bearing objects are available Thence S. 30° 8' W.
19.3	E. right of way fence U.S. Highway 80 bears N. 39° 13' W. and S. 39° 13' E.

Feet.	
233.0	W. right of way fence, U.S. Highway 80 bears N. 39° 13' W. and S. 39° 13' E.
238.18	Intersect W. line Sec. 18, T. 20 S. R. 23 E. at a point from which the 1/4 Cor. Secs. 13 & 18, T. 20 S. Rs. 22 & 23 E. brs. S. 0° 12' 52" E., 823.86 ft. dist.
519.47	Intersect line 3-5, Sur. No. 263, San Diego lode at S. 67° 7' E., 408.93 ft. from Cor. No. 5
1400.0	Road bears southwesterly and northeasterly.
1415.0	Wash 3 ft. wide, course northerly.
1500.0	Cor. No. 1 and place of beginning.
TOMBSTONE EXTENSION No. 5 lode.	
At Cor. No. 1 of the Tombstone Extension No. 5 lode, identical with Cor. No. 1 Tombstone Extension No. 4 lode of this Sur., heretofore described. from which	
	The E. 1/4 Cor. Sec. 13, T. 20 S., R. 22 E. bears N. 67° 7' 58" E., 688.22 ft. dist.
	Cor. No. 6 Sur. No. 263 San Diego Lode bears S. 55° 41' 48" W., 526.29 ft. Dist.
	Thence N. 58° 52' W.
70.0	Road bears southwesterly and northeasterly.
210.0	Road bears northerly and southeasterly.
288.18	Intersect line 5-6 Sur. No. 263 San Diego lode.
300.0	Lode line; discovery point bears S. 30° 49' W., 104. ft. dist. Identical with lode line Tombstone Extension No. 4 lode, of this Sur. heretofore described.
315.0	Wash 3 ft. wide, course northeasterly.
540.0	Road bears northeasterly and southwesterly.
600.0	Cor. No. 2, identical with Cor. Nos. 2, 1 and 1, Tombstone Extension No. 4, Tombstone Extension and Tombstone Extension No. 1 lodes respectively of this survey, heretofore described.
	Thence S. 30° 49' W.
840.0	Old U.S. Highway 80 (abandoned) bears northwesterly and southeasterly
925.0	Wash 3 ft. wide, course northerly.
1282.0	Wash 10 ft. wide, course northerly.
1349.21	Intersect line 2-3, Sur. No. 827 Omega lode at N. 79° 21' E., 559.87 ft. from Cor. No. 2
1437.67	Intersect line 4-1 Sur. No. 2613 Mc Kinly lode at N. 79° 16' 30" E., 463.27 ft. from Cor. No. 4
1460.0	Wash 5 ft. wide, course northerly.

Survey No. 4384

Feet.	
1500.0	Cor. No. 3, identical with Cor. No. 4 Tombstone Extension * 1 lode of this Sur., heretofore described.
	Thence S. 58° 52' E.
304.00	Wash 5 ft. wide, course northerly.
300.0	Lode line; discovery point bears N. 30° 49' E., 1396.0 ft. dist.
	Set an iron post 3 1/2 ft. long, 2 ins. diam. firmly in the ground surrounded by a mound of stone, mkd S. Cr T. Ex 5
450.0	Wash 20 ft. wide, course northerly.
572.68	Intersect line 5-6 Sur. No. 827 Omega lode at S. 79°25' W., 336.17 ft. from Cor. No.5
600.0	Cor. No.4
	Set an iron post 3 1/2 ft. long, 2 ins. diam. 18 ins. in the ground surrounded by a mound of stone to top with leaden cap, mkd 4 T Ex 5-4384.
	Cor. No.5 Sur. No. 827 Omega lode brs. N. 76° 6' 58" E., 316.26 ft. dist. Cor. No.
	Cor. No.1 Sur. No. 2613 Mc Kinly lode brs. N. 44° 7' E., 787.46 ft. dist.
	No other bearing objects are available.
	Thence N. 30° 49' E.
24.28	Intersect line 5-6 Sur. No. 827 Omega lode at S. 79°25' W., 299.68 ft. from Cor. No.5
597.25	Intersect line 4-1 Sur. No. 2613 Mc Kinly lode at S.79°16' 30" W. 246.51 ft. from Cor. No. 1 and N 79°16'30" E., 1264.89 ft. from Cor. No. 4
684.21	Intersect line 2-3, Sur. No. 827 Omega lode at S. 79° 21' W., 139.44 ft. from Cor. No. 3. and N. 79° 21' E., 1360.56 ft. from Cor. No. 2
860.0	Old U.S. Highway 80 (abandoned) bears northwesterly and southeasterly.
1053.41	Intersect line 6-2 Sur. No. 263 San Diego lode at S. 67° 07' E., 223.56 ft. from Cor. No.6 and N. 67°07' W., 376.44 ft. from Cor. No.2
1500.0	Cor. No. 1 and place of beginning.
	BLIND LEDGE Lode.
	Beginning at Cor. No.1 of the Blind Ledge lode, identical with Cor. No.1, Blind Ledge No.3 lode of this survey. from which
	The 1/4 Cor. bet. Secs 12 and 13, T. 20 S., R. 22 E. bears N.61°58' W., 800.25 ft. dist.
	No other bearing objects are available.

Feet.	
	Thence S. 58°52' E.
275.0	Wash 5 ft. wide, course northeasterly and southwesterly.
300.0	Lode line; discovery point bears S. 30° 8' W., 560 ft. dist.
	Set an iron post 3 1/2 ft. long, 2 ins. diam. firmly in the ground surrounded by a mound of stone, mkd N. Cr.BL, S. Cr. BL 3
316.0	Wash 2 ft. wide, course northerly.
600.0	Cor. No.2, identical with Cor. Nos. 1,3 and 2, Tombstone Extension *3, Chance No.1 and Blind Ledge No.3 lodes respectively of this Sur., heretofore described.
	Thence S. 30° 8' W.
617.0	Wash 3 ft. wide, course northerly.
699.0	Wash 3 ft. wide, course northerly.
840.0	Old road bears northwesterly and southeasterly
979.0	Old road bears northerly and southerly.
1500.0	Cor. No.3, identical with Cor. Nos 2,4 and 2, Tombstone Extension *2, Tombstone Extension *3 and Blind Ledge No.2; lodes respectively of this sur., heretofore described.
	Thence N. 58° 52' W.
115.0	Wash 5 ft. wide, course northwesterly.
300.0	Lode line; discovery point bears N. 30° 8' E. 940. ft. dist.
	Set an iron pipe 3 1/2 ft. long, 2 ins. diam. firmly in the ground surrounded by a mound of stone, mkd S. Cr.B L, N. Cr.B L 2
440.0	Wash 15 ft. wide, course northerly
600.0	Cor. No. 4, identical with Cor. No.1 Blind Ledge No.2 lode of this Sur.
	Set an iron post 3 1/2 ft. long, 2 ins. diam. 18 ins. in the ground surrounded by a mound of stone to top with leaden cap mkd 4 B L, 1 BL 2 - 4384
	U.S. M.M. No.1 bears N. 77°22'56" W., 4252.65 ft. dist. Consisting of a mound of stone 7 ft. base, 4 ft. high with a 1/2 in. open pipe extending 2 ft. above the top of monument.
	No other bearing objects are available.
	Thence N. 30° 8'E.
240.0	Wash 20 ft. wide, course northerly.
644.0	Wash 2 ft. wide, course northerly.

Feet.	
910.0	Old road bears northwesterly and southeasterly.
1500.0	Cor. No. 1 and place of beginning.
BLIND LEDGE No.2 lode.	
Beginning at Cor.No.1 of the Blind Ledge No2 lode, identical with Cor. No.4 Blind ledge lode of this Sur., heretofore described from which	
The 1/4 Sec. Cor. bet. Secs 12 and 13 T. 20 S.R.22E. bears N.1°35'50" E., 1674.05 ft. dist.	
U.S. M.M. No. 1 bears N.77°22'56" W., 4252.65 ft. dist.	
Thence S. 58°52' E.	
160.0	Wash 15 ft. wide, course northerly.
300.0	Lode line; discovery point bears S. 30°49' W. 467.0 ft. dist. Identical with lode line Blind ledge of this Sur., heretofore described.
485.0	Wash 5 ft. wide, course northwesterly.
600.00	Cor. No.2, identical with Cor. Nos. 2,4 and 3, Tombstone Extension *2, Tombstone Extension *3 and Blind Ledge lodes respectively of this Sur., heretofore described.
Thence S. 30° 49' W.	
200.0	Wash 5 ft. wide , course northerly.
565.0	Wash 15 ft. wide, course northerly
830.0	Old U.S. highway 80 (abandoned) bears northwesterly and southeasterly
930.0	Wash 5 ft. wide, course northwesterly.
1500.0	Cor. No.3, identical with Cor. No. 3 , Tombstone Extension *2 lode of this Sur., heretofore described .
Thence N. 58°52' W	
15.0	Wash 5 ft. wide, course northerly
300.0	Lode line; discovery point bears N. 30° 8'E., 1033. ft. dist. Set an iron post 3 1/2 ft. long, 2 ins. diam. firmly in the ground surrounded by a mound of stone, mkd S. Cr. BL 2
600.0	Cor. No.4 Set an iron post 3 1/2 ft. long, 2 ins diam. 18 ins in the ground Surrounded by a mound of stone to top with leaden cap mkd 4 BL 2
No bearing objects are available.	
Thence N.30° 49' E.	

Feet.	
950.0	Old U.S. highway 80 (abandoned) bears northwesterly and southeasterly.
1425.0	Wash 5 ft. wide, course northerly.
1500.0	Cor. No.1 and place of beginning.
<p>BLIND LEDGE No.3 Lode.</p> <p>Beginning at Cor. No.1 of the Blind Ledge No.3 lode, identical with Cor. No.1 Blind Ledge lode of this sur. heretofore described from which</p> <p>The 1/4 Cor. bet. Secs 12 and 13^{1/2} T. 20 S. R. 22 E. bears N. 61°58' W., 800.25 ft. dist.</p> <p>Thence S. 58° 52 ' E.</p>	
275.0	Wash 5 ft. wide, course northerly and southwesterly.
300.0	Lode line, discovery point bears N. 30° 8' E., 400.0 ft. dist.
316.0	Identical with lode line, Blind Ledge lode of this Sur. heretofore described.
316.0	Wash 2 ft. wide, course northerly.
600.0	Cor. No.2, identical with Cor. Nos. 2, 1 and 3, Blind Ledge, Tombstone Extension $\frac{2}{3}$ and Chance No.1 lodes respectively of this Sur. heretofore described.
<p>Thence N. 30° 8' E.</p>	
417.0	W. right of way fence U.S. Highway 80 bears N. 39° 13' W. and S. 39° 13 ' E.
640.0	E. right of way fence U.S. Highway 80 bears N. 39° 13' W. and S. 39° 13' E.
1500.0	Cor. No. 3, identical with Cor. No.2, Chance NO. 1 lode of this Sur.
<p>Set an iron post 3 1/2 ft. long, 2 ins. diam., 18 ins in the ground surrounded by mound of stone to top with leaden cap mkd 3 B L 3, 2 C. 1 - 4384.</p> <p>Thence N. 58° 52' W.</p>	
265.0	Wash 5 ft. wide, course northerly.
300.0	Lode line; discovery point bears S. 30° 8' W. 1100 ft. dist.
600.0	Set an iron post 2 ft. long, 2 ins. diam. firmly in ground mkd N. Cr BL 3
600.0	Cor. No.4
<p>Set an iron post 3 1/2 ft. long, 2 ins. diam, 18 ins. in the ground surrounded by a mound of stone to top with leaden cap mkd 4 BL 3 - 4384.</p> <p>No bearing objects are available.</p> <p>Thence S. 30° 8' W.</p>	

Feet.	
655.0	E. right of way fence U.S. Highway 80 bears N. 39° 13' W. and S. 39° 13' E.
873.0	W. right of way fence U.S. Highway 80 bears N. 39° 13' W. and S. 39° 13' E.
1500.0	Cor. No. 1 and place of beginning.
CHANCE LODE	
Beginning at Cor. No. 1 of the Chance Lode, identical with Cor. No. 1 Chance No. 1 lode	
Set an iron post 3 1/2 ft. long, 2 ins. diam. 18 ins. in the ground surrounded by a mound of stone to top with leaden cap, mkd. 1 C, 1 C 1-4384; from which	
The Cor. to Secs. 7, 12, 13 and 18 T. 20 S. Rs 22 and 23 E. bears S. 26° 27' E., 343.58 ft. dist, a limestone rock 10 X 10 ins. showing 10 ins above ground, firmly set and marked as described in the official record.	
No other bearing objects are available.	
Thence S. 58° 52' E.	
178.88	Intersect fence on W. line Sec. 7 T. 20 S. R. 23 E. - S S 039145 State of Arizona. at a point from which the cor. of Secs. 7, 12, 13 & 18, T. 20 S., Rs 22 & 23 E. brs. south 215.17 ft. dist.
300.0	Lode line; discovery point bears S. 30° 8' W., 1490. ft. dist. Set an iron post 2 ins. diam. 3 1/2 ft. long, firmly in the ground surrounded by a mound of stone, mkd N. Cr. C.
538.0	Fence bears east and west.
598.81	Intersect line bet. Secs 7 and 18 T. 20 S. R. 23 E. Enter State land -S S 079031, Pat 1128306. From which point the cor. of Secs. (as above) brs. N. 89° 41' W., 359.52 ft. dist.
600.0	Cor. No. 2 Set an iron post 3 1/2 ft. long, 2 ins. diam. 18 ins. in the ground surrounded by a mound of stone to top with leaden cap mkd 2 C-4384 No bearing objects are available. Thence S. 30° 8' W.
700.0	Wash 10 ft. wide, course northwesterly.
717.1	Intersect Sec. line bet Secs. 13 and 18, T. 20 S. Rs 22 and 23 E. at a pt. from which the Cor. of Secs. (as above) brs. N. 0° 2' 52" W., 622.81 ft. dist.
1300.0	E. right of way fence, U.S. Highway 80 bears S. 39° 13' E. and N. 39° 13' W.
1500.0	Cor. No. 3, identical with Cor. Nos 4 and 3, Tombstone Extension and Tombstone Extension #4 lodes of this Sur.

Feet.	
	Thence N. 58° 52' W
51.0	W. right of way fence U.S. Highway 80 bears N. 39° 13' W. and S. 39° 13' E.
140.0	Road bears northeasterly and southwesterly.
170.0	Wash 3 ft. wide, course northerly
300.0	Lode line; discovery point bears N. 30° 8' E., 10. ft. dist. Identical with Lode line, Tombstone Extension lode of this Sur. heretofore described.
600.0	Cor. No.4, identical with Cor. Nos. 2,3 and 4, Tombstone Extension *3, Tombstone Extension and Chance No.1 lodes respectively of this Sur. heretofore described.
	Thence N. 30° 8' E.
200.0	W. right of way fence U.S. highway 80 bears N. 39° 13' W. and S. 39° 13' E.
412.0	E. right of way fence U.S. highway 80 bears N. 39° 13' W. and S. 39° 13' E.
1080.0	Wash 10 ft. wide, course northwesterly and southeasterly.
1500.0	Cor. No.1 and place of beginning.
CHANCE No 1 Lode.	
	At Cor. No. 1, Chance No.1 identical with Cor. No. 1 Chance lode of this Sur. heretofore described; from which
	The Cor. to Secs. 7,12,13 and 18 T. 20 S. R 22 and 23 E. bears S. 26° 27' E., 343.58 ft. dist.
	Thence N. 58° 52' W.
300.0	Lode line; discovery point bears S. 30° 8' W., 900 ft. dist.
	Set an iron post 3 1/2 ft. long, 2 ins. diam. firmly in the ground surrounded by mound of stone, mkd N. Cr. C. 1
432.0	Wash 10 ft. wide, course northwesterly.
600.0	Cor. No.2, identical with Cor. No.3, Blind Ledge No.3 lode of this Sur., heretofore described.
	Thence S. 30° 8' W.
860.0	E. right of way line fence, U.S. highway 80 bears N. 39° 13' W. and S. 39° 13' E.
1083.0	W. right of way line fence, U.S. highway 80 bears N. 39° 13' W., and S. 39° 13' E.

Feet	
1500.0	Cor. No.3, identical with Cor. Nos. 1, 2 and 2 Tombstone Extension *3, Blind Ledge and Blind Ledge No. 3 lodes respectively of this Sur. heretofore described.
	Thence S. 58° 52' E
300.0	Lode line; discovery point bears N. 30° 8' E. 600.0 ft. dist. identical with Lode line Tombstone Extension *3 lode of this Sur. heretofore described.
443.0	Wash 4 ft. wide, course northerly.
600.0	Cor. No.4, identical with Cor. Nos. 2,3 and 4, Tombstone Extension *3, Tombstone Extension and Chance loded respectively of this Sur. heretofore described.
	Thence N. 30° 8' E.
200.0	W. right of way fence, U.S. highway 80 bears N. 39° 13' W., and S.39° 13' E.
412.0	E. right of way fence, U.S. highway 80 bears N.39°13' W. and S. 39° 13' E.
1080.0	Wash 10 ft. wide, course northwesterly and southeasterly.
1500.0	Cor. No. 1 and the place of beginning.

AREAS	Acres
Total area, Tombstone Extension lode --	20.658
Total area, Tombstone Extension *1 lode --	20.661
Area in conflict with	
Sur. No.2615 McKinly lode ----	0.037
Sur. No. 827 Omega lode --	0.293
Sur. No. 827 Omega lode, exclusive of its conflict with Sur. No. 2613 McKinly lode -----	0.256
Total area, Tombstone Extension *2 lode --	20.661
Total area, ^{Tombstone} Extension *3 lode --	20.658
Total Area, ^{Extension} Tombstone *4 lode --	20.658
Total Area, in conflict with	
Sur. No. 263 San Diego lode -----	7.615
Sec.18,T.20 S.,R.23 E.S.S.079031 Pat.1128306 State of Ariz	0.383
Total area, Tombstone Extension No.5 lods -----	20.661
Area in conflict with	
Sur. No. 263 San Diego lode --	2.718
Sur. No. 2613 Mc Kinley lode --	4.542
Sur. No. 827 Omega lode ----	5.742
Sur. No. 827 Omega lode, exclusive of its conflict with Sur. No. 2613 Mc Kinly lode ---	1.207

AREAS

Acres

Total area; Blind Ledge lode	20.658
Total area, Blind Ledge No.2 lode	20.661
Total area, Blind Ledge No. 3 lode --	20.658
Total area, Chance lode -	20.658
Area in conflict with	
Sec. 7 T.20 S.,R23 E.SS 039145 State of Ariz -----	0.890
Sec. 18, T.20 S.23 E. SS 079031 Pat:1128306, State of Ariz	2.579
Total Area Chance No.1 lode	20.658

LOCATION

This survey is located in Secs. 12 and 13, T.20 S.R.22E and Secs 7 and 18 T. 20 S. R. 23 E. G. & S. R. M.

The survey is identical with the respective locations as staked on the ground.

IMPROVEMENTS

The improvements and the value of the labor and improvements made upon or for the benefit of each of the lode locations embraced in said mining claim by the claimants or their grantors are as follows:

No.1	The discovery shaft of the Tombstone Extension lode, the center of which being the discovery point is on the center line 500 ft. from the center of line 3-4, 6 x 7 ft. 8 ft. deep. Value \$100.0
No.2	A shaft, the center of which bears from Cor. No.3 Tombstone Extension lode, S. 1° 15' E., 580.0 ft. dist., 6x7 ft. 8 ft. deep. Value \$100.0
No. 3	A shaft (timbered) the center of which bears from Cor.No.2 Tombstone Extension lode N. 74°45' E., 542. ft. dist 4 x 6 ft. 15 ft. deep. Value \$150.
No. 4	A shaft, the center of which bears from Cor. No.3 Tombstone Extension lode S. 1° 10' W., 477. ft. dist. 4 X 4 ft. 40 ft. deep (caved) Value \$400.
No. 5	A shaft, the center of which bears from Cor. No.3 Tombstone Extension lode S. 1°15' W., 652 ft. dist., 4 x 6 ft. 25 ft. deep (caved) Value \$250.
No. 6	A shaft, the center of which bears Cor. No.3, Tombstone Extension lode S. 3°50' W., 690. ft. dist., 5 x 6 ft. 30 ft. deep (caved) Value \$690.
No. 7	A shaft, the center of which bears from Cor. No.3 Tombstone Extension lode S.3° 25' E., 760. ft. dist.5 x 7 ft. 8ft. deep. Value \$100.
No. 8	A shaft, the center of which bears from Cor. No.3 Tombstone Extension lode S. 16°10'E., 800. ft. dist. 5 x 5 ft. 5 ft. deep. Value \$50.

- No. 9 A shaft, the center of which bears from Cor. No.3, Tombstone Extension lode S. 14° 5' E., 841 ft. dist. 4 x 6 ft. 15 ft. deep.
Value \$150.
- No. 10 A shaft, the center of which bears from Cor. No.3 Tombstone Extension lode S. 9° E., 888. ft. dist 4x 7 ft. 8 ft. deep.
Value \$100.
- No. 11 A shaft, the center of which bears from Cor. No.2 Tombstone Extension lode N. 52° 30' E. 768. ft. dist. 4 x 7 ft. 4 ft. deep (caved)
Value \$100.
- No. 12 A shaft, the center of which bears from Cor. No.2 Tombstone Extension lode, N. 52° 45' E. 750 ft. dist. 3 x 5 ft. 60ft. deep.
Value \$600.0
- No.13 A shaft, the center of which bears from cor No.2 Tombstone Extension lode, N. 52°45' E., 712 ft. dist. 4 x 7 ft. 6 ft. deep.
Value \$60.
- No. 14 A shaft, the center of which bears from Cor. No.2 Tombstone Extension lode, N. 60° E., 755. ft. dist 4 X 4 ft. 20 ft. deep. (caved)
Value \$200.
- No. 15 A shaft, the center of which bears from Cor. No.2 Tombstone Extension lode, N. 60°50' E., 712 ft. dist. 4 x 4 X 10 ft. deep, concrete collar with plank cover, locked.
Value \$100.
- No.1 The discovery shaft of the Tombstone Extension #1 the center of which being the discovery point is on the center line 75 ft. from the center of line 1-2, 4 x 6 ft. 8 ft. deep.
Value \$100.
- No. 2 A shaft, the center of which bears from Cor. No.1 Tombstone Extension #1 lode, N. 74°10' W., 312. ft. dist. 4 x 6 ft. 8 ft. deep.
Value \$100.
- No.1 The discovery shaft of the Tombstone Extension #2 lode, the center of which being the discovery point is on the center line 75 ft. from the center of line 1-2, 4 x 6 ft. 8 ft. deep.
Value \$100.
- No.2 A shaft, the center of which bears from Cor No.1 Tombstone Extension #2 lode, N. 74° 10' W., 312 ft. dist. 4 x 6 ft. 8 ft. deep.
Value \$100.
- No.1 The discovery point of the Tombstone Extension #3 lode is on the center line 500 ft. from the center of line 1-2, a mound of stone on outcrop
No. value.
- No. 2 A shaft, the center of which bears from Cor. No.2, Tombstone Extension #3 lode, S. 61°45' W., 565 ft. dist. 4 x 6 ft. 72 ft. deep. At the 72 ft. level is a drift 5 x 7 ft running west 50 ft. to breast from same is a drift 5 x 7 ft. running east 15 ft. to breast.
Value shaft and drifts \$1370.
- No.3 A shaft, the center of which bears from Cor. No.3, Tombstone Extension 3 lode, S.14° W., 545 ft. dist. 4 x 6 ft. 54 ft. deep, at the bottom of which is a diamond drill hole 7/8 in. core 83 ft. deep.
Value shaft and drill hole \$706.

No. 1	The discovery cut of the Tombstone Extension #4 lode the face of which being the discovery point is on the center line 75 ft. from the center of line 3-4, (falls in highway right of way and completely filled) a mound of stone. No value
No. 2	A shaft, the center of which bears from Cor. No. 4, Tombstone extension #4 N. 85° W., 335 ft. dist. 8 x 10 ft. (timbered) 120 ft. deep. at the 70 ft. level is a drift 5 x 7 ft. running S. 30° W., 80 ft. to breast. At 70 ft. level is another drift 5 x 7 ft. running N. 30° E., 20 ft. to breast. Value Shafts and drifts \$ 2800.0
No. 3	A shaft, the center of which bears from Cor. No. 4, Tombstone Extension #4 lode. S. 69° W., 292 ft. dist. 5 x 7 ft. 4 ft. deep Value \$40.
No. 4	A shaft, the center of which bears from Cor. No. 4 Tombstone Extension #4 lode S. 66° 15' W., 308. ft. dist. 4 x 4 ft. 9 ft. deep. Value 80.0
No. 5	A shaft, the center of which bears from Cor. No. 4 Tombstone Extension #4 lode S. 70° 45' W., 399. ft. dist. 4 x 4 ft. 10 ft. deep. Value \$90.0
No. 6	A shaft, the center of which bears from Cor. No. 4 Tombstone Extension #4 lode S. 57° 30' W., 360. ft. dist. 4 x 6 ft. 5 ft. deep. Value \$50.
No. 7	A shaft, the center of which bears from Cor. No. 4 Tombstone Extension #4 lode, S. 62° 30' W., 407 ft. dist. 6 x 8 ft. 5 ft. deep. Value \$100.
No. 8	A shaft, the center of which bears from Cor. No. 4, Tombstone Extension #4 lode S. 65° W., 428 ft. dist. 4 x 6 ft. 35 ft. deep. Value \$350.
No. 9	A trench, the northerly end of which bears from Cor. No. 4 Tombstone Extension #4 lode, S. 51° 10' W., 472 ft. dist. 2 ft. wide 2 ft. deep, running S. 40° E., 8 ft. to southerly end. Value \$ 30.0
No. 10	A shaft, the center of which bears from Cor. No. 4 Tombstone Extension #4 lode S. 48° 5' W., 505. ft. dist. 4 x 6 ft. (timbered) 32 ft. deep. Value \$ 320.0
No. 11	A shaft, the center of which bears from Cor. No. 4, Tombstone Extension 4 lode S. 50° 15' W., 565. ft. dist. 4 x 6 ft. 13 ft. deep. Value \$130.
No. 1	The discovery shaft of the Tombstone Extension No. 5 lode, the center of which being the discovery point is on the center line 104 ft. from the center of line 1-2, 4 x 6 ft. 8 ft. deep. Value \$100.
No. 1	The discovery shaft of the Blind ledge lode, the center of which being the discovery point is on the center line 560. ft. from the center of line 1-2, 4 x 6 ft. 8 ft. deep. Value \$100.
No. 2	A shaft, the center of which bears from Cor. No. 1, Blind ledge lode S. 3° 50' E., 605 ft. dist. 4 x 6 ft. 6 ft. deep. Value \$ 60.

No.3	A shaft, the center of which bears from Cor. No.1 Blind Ledge lode S.3°20' E., 635 ft. dist. 6 x 9 ft., 6 ft. deep. Value \$90.
No.1	The discovery shaft of the Blind Ledge No.2 lode, the center of which being the discovery point is on the center line 467. ft. from the center of line 1-2, 4 x 6 ft. 8 ft. deep. Value \$100.
No.2	A shaft, the center of which bears from Cor. No.2 Blind Ledge No.2 lode, S.54° W., 535 ft. dist. 4 x 6 ft. 10 ft. deep. Value \$100.
No.1	The discovery shaft of the Blind Ledge No.3 lode, the center of which being the discovery point is on the center line 400 ft. from the center of line 1-2, 4 x 6 ft. 8 ft. deep. Value \$100.
No.2	A shaft, the center of which bears from Cor. No.1, Blind Ledge No.3 lode, N. 66° 10' E., 505. ft. dist. 4 x 6 ft. 5 ft. deep. Value \$100.
No.1	The discovery point of the Chance lode is on the center line 10 ft. from the center of line 3-4, a mound of stone on outcrop. No. Value.
No.2	A shaft, the center of which bears from Cor. No.3 Chance lode N.57°45' W. 288 ft. dist. 3 x 7 ft. 8 ft. deep. Value \$90.
No.3	A shaft, the center of which bears from Cor. No.1 Chance lode S. 22° W., 165 ft. dist. 4 x 6 ft. 20 ft. deep (timbered) Value \$250.
No.4	A shaft, the center of which bears from Cor. No.1, Chance lode S. 19°45' W., 562. ft. dist. 4 x 6 ft. 8 ft. deep. Value \$100.
No.5	A shaft, the center of which bears from Cor. No.1 Chance lode, S.25° 15' W., 610 ft. dist. 4 x 6 ft. 8 ft. deep. Value \$100.
No.6	A shaft, the center of which bears from Cor. No.4, Chance lode, S. 66°45' E., 120. ft. dist. 4 x 6 ft. 197 ft. deep. at the 124 ft. level is a cross-cut, 5 x 7 ft. running S.70° E., 22 ft. to breast. At the bottom of shaft. is a drift 5 x 7 ft. running N. 70° W., 15 ft. to breast. also a drift. 5 x 7 ft. running N. 29° E., 305. ft. dist to breast. At 10 ft. below collar of shaft. is a drift 4 x 6 ft., running N.22° E., 36 ft. to breast. Total value shaft, cross-cut and drifts \$ 3685.0
No.7	A shaft, the center of which bears from Cor. No.3 Chance lode N.57°52' W., 245 ft. dist. 4 x 6 ft. 9 ft. deep. Value \$100.
No.1	The discovery shaft of the Chance No.1 lode, the center of which being the discovery point is on the center line, 600 ft. from the center of line 3-4, 4 x 6 ft. 8 ft. deep. Value \$100.
No.2	A shaft, the center of which bears from Cor. No.3, Chance No.1 lode N. 51° E., 327 ft. dist. 4 x 6 ft. 6 ft. deep. Value \$60.
No. 3	A shaft, the center of which bears from Cor. No.3, Chance No.1 lode N.35°10' E., 345 ft. dist. 4 x 6 ft. 6 ft. deep. Value \$60.

An interest in a common improvement described as follows :

A shaft the center of the collar of which bears from Cor. No.3 Tombstone Extension lode , S. 4° 40' W. 575. ft. dist., 6 x 9 ft. timbered, 485. ft. deep.

At the 100 ft. level is a drift 5 x 7 ft. running N.20° 30' E., 120 ft. to Sta. 101 thence N. 18° 45' E., 27 ft. to Sta.102; thence N. 37°15'E., 19 ft. to Sta. 103; thence N.15°15' E.162 ft. to breast.

At the 100 ft. level is another drift 5 x 7 ft. running S. 27° W., 91 ft.; to Sta. 104; thence S.50° E., 50 ft. to breast

At Sta. 104 is a drift 5 x 7 ft. running N.50° W., 22 ft. to breast.

At Sta 104 is a drift 5 x 7 ft. running S.31° W., 40 ft. to Sta.105.

At Sta. 105 thence S. 19° W., 86 ft. to Sta.106.

At Sta. 106; thence S. 23°15' W., 51 ft. to Sta. 107

At Sta. 107; thence S. 33° W., 21 ft. to Sta. 108

At Sta. 108; thence S. 17°15' W., 90 ft. to Sta.109

At Sta. 109; thence S. 22°30' W., 51 ft. to Sta.110

At Sta.. 110; thence S. 32°30' W., 33 ft. to Sta.111

At Sta. 111; thence S. 26° W., 60. ft. to Sta. 112

At Sta. 112; thence S. 19° W., 49. ft. to Sta. 113

At Sta. 113; thence S. 22°30' W., 60 ft. to Sta. 114

At Sta. 114; thence S. 86° W., 113 ft. to breast.

At Sta. 114; thence S. 33° W., 82 ft. to Sta. 115

At Sta. 115; thence S. 30° W., 65 ft. to Sta. 116

At Sta. 116; thence S. 24° 30' W.123 ft. to breast

At the 200 ft. level is a drift 5 x 7 ft. running N.69°30' W.12 ft.; Thence N.37° E., 27 ft.; thence N.25°30' E., 28 ft.; thence N.15° E., 68 ft. to breast.

At Sta. 201 (N.69°30'W., 12 ft. from Shaft) is a drift 5 x 7 ft. running S.32°30'W., 76. ft to Sta. 204; thence S. 30° W., 20 ft. to Sta. 205; thence S.18°30' W., 62 ft. to Sta.206; thence S.20° W., 128. ft. to Sta. 207; thence S. 33° W., 27 ft. to Sta.208; thence S. 36° W., 42 ft. to Sta. 209; thence S. 22°30' W., 21 ft. to Sta. 210; thence S. 8° E., 59 ft. to Sta. 211; thence S. 34° W.47 ft. to Sta.212; thence S. 12° 15' E., 26 ft. to Sta. 213; thence S.20°15'W. 83 ft. to Sta.214; thence S.20° W., 128 ft. to Sta. 215; thence S.34°30' W., 123. ft. to breast. At Sta.212 is a cross-cut 5 x 7 ft. running S. 55° to face. At Sta.214 is a cross-cut 5 x 7 ft. running S. 86° W., 21 ft. to face.

At 250 ft. level a cross-cut 5 x 7 ft. running N. 60°30'W., 30 ft. to Sta. 251; thence N. 57° W., 562 ft. to face. At Sta 251 main drift N. 33° E., 45 ft. to Sta. 252; thence N. 24° E., 20 ft. to breast

At Sta. 252 a cross-cut 5 x 7 ft. running N.87° E., 40 ft. to face.

At Sta. 251 main drift S. 32°45'E., 84. ft. to Sta. 253; thence S. 16° W., 87 ft. to Sta. 254; thence S. 20° W., 123 ft. to Sta. 255; thence S. 30° W., 38 ft. to Sta. 256; thence S. 17°15'W., 55 ft. to breast.

At the 350 ft. level a cross-cut 5 x 7 ft. N. 61° W., 59 ft. to Sta. 351 in main drift; thence N.22° E., 20 ft. to breast.

At Sta. 351 main drift S.24° W., 90 ft. to Sta. 352; S21°30' W., 52 ft. to Sta. 353; thence S. 16°30' W., 162 ft. to Sta 354; thence S.22°30' W., 103 ft. to Sta. 355; thence S. 17° W., 105 ft. to Sta.356; thence S. 22°45' W., 80 ft. to Sta. 357; thence 21°30' W., 61 ft. to St. 358; thence S. 18° W., 28 ft. to breast.

At 485 ft. level is a cross-cut 5x7 ft. running N. 62° W., 66 ft. to Sta. 486, main drift; thence N. 20°30' E., 67 ft. to breast.

At Sta. 486 main drift, S. 19° W., 39 ft. to Sta. 487; thence S. 30° W. 67ft. to Sta. 488; thence S. 22°30' W., 117 ft. to Sta. 489; thence S. 18°30' W., 67 ft. to Sta. 490.; thence 21°30' W., 116 ft. to Sta. 491; thence S. 8°30' W., 65 ft. to Sta. 492; thence S.19°30' W., 132. ft. to Sta. 493; thence S.33°30' E., 28 ft. to Sta.494; thence S.9° W., 165 ft. to Sta. 495; thence S. 36° W., 30 ft. to breast .

At Sta.494 a cross-cut 5 x 7 ft. running N.27°30'E. 45 ft. to face.

Survey No. 4384

At Sta. 490 on the 485 ft. level is a winze 5 x 8 ft. (timbered) 65 ft. deep, to Sta. 550 on the 550 ft. level.

At Sta. 550 is a cross-cut 5 x 7 ft. running N. 63° W., 8 ft. to Sta. 551. At Sta. 551 is a drift 5 x 7 ft., running N. 27° E., 53 ft. to breast. At Sta. 551 another drift 5 x 7 ft. running S. 27° W., 40 ft. to breast.

Total value of shaft, winze, drifts and cross-cuts	---\$72,605.00
Value of 1/11 interest	----- \$ 6,600.45

This improvement is in the course of construction for the development of the eleven lodes of this survey, which are all the lode claims owned in common within the range of benefit of said improvement.

The surface is generally level, rising gradually to the south from the collar of this shaft, so that drifting and cross-cutting, with the necessary laterals, affords the most practical and economical means of developing each of the stated lodes at depth.

Five hundred dollars or over has been expended in this improvement in such a manner as tends to the development of each lode of this survey subsequent to its location and to the time since which common ownership and contiguity have prevailed; therefore an undivided 1/11 interest in its value is hereby credited to each of the said lodes.

No portion of or interest in this improvement has been credited heretofore as patent expenditure to any other lode claim.

OTHER IMPROVEMENTS.

A frame iron clad hoist house, the NW Cor. of which bears from Cor. No. 3, Tombstone Extension lode S. 5° 5' W., 550 ft. dist.
20 x 25 ft., course of long sides S. 60° E.

A frame ore bin, the NW cor. of which bears from Cor. No. 3, Tombstone Extension lode, S. 2° 15' W., 570 ft. dist.
20 x 30 ft., course of long sides S. 30° E.

OTHER CORNER DESCRIPTIONS.

Sur. No. 827 Omega lode, No evidence of any of the original corners of this survey could be found or identified. Its conflict with this survey was therefore calculated from the record bearing and distance from U.S.M.M. No. 1 and its relative position with Sur. No. 2613 Mc Kinly.

Sur. No. 2613 Mc Kinly lode; Cor. Nos. 1 and 4 consist of old stone monuments surrounding 4 x 4 in. decayed posts; alongside the old Cors are 2 x 4 in pine posts mkd 1 M C K and 4 M C K respectively.

Sur. No. 263 San Diego lode, all corners consist of old stone monuments, no markings.

ADJOINING CLAIMS.

On the north - Legion lode, unsurveyed, claimant herein.

On the east, Sur. NO 263 SanDiego lode ; Sur. No.2613 Mc Kinly lode; Sur. No.827 Omega lode and the Fairview lode, Uns.,claimant unknown.

On the south by Sur. No. 2613 Mc Kinly lode; Sur. No.827 Omega lode; Overlook and Overlook No.1 lodes, Uns.,Newmont Exploration Ltd, claimant.

On the West by Columbia and Coral, Uns. W.C. Humphrey, Claimant and Grand Prize lode, Uns. O. Gast, Claimant.

Field Assistants.


Name	Capacity
E.H. Jenkins	Chairman
J.J. Walden	"

UNITED STATES
DEPARTMENT OF THE INTERIOR
BUREAU OF LAND MANAGEMENT

CERTIFICATE OF SURVEYOR

I, T.N. Stevens, Mineral Surveyor,
 hereby certify upon honor that in pursuance of an order received from the
Office Cadastral Engineer, at Albuquerque, New Mexico,
 dated August 31, 1953, I have faithfully and correctly executed the survey
 of the mining claim of G.M. d'Autremont and H.W. Hasselgren, Trustees, known as the
Tombstone Extension, Tombstone Extension #1, Tombstone Extension #2, Tombstone Extension
Tombstone Extension #4, ~~known as the Tombstone Extension No. 5, Blind Ledge,~~
Blind Ledge No. 2, Blind Ledge No. 3, Chance and ~~(lode, placer, or both)~~
Chance Chance No. 1 lode mining claims, situate in Tombstone mining district
(12 and 13) T 20 S. R 22 East
Cochise County, in Sections (7 and 18) T. 20 S., R. 23 East,
G. & S. R. M. Meridian, Arizona, and designated
 as Survey No. 4384 (State)
 which is represented in the fore-
 going field notes as having been executed by me and under my direction, and that said
 survey has been made in strict conformity with said order, the Manual of Instructions
 for the Survey of the Public Lands of the United States, and in the specific manner
 described in the foregoing field notes, and I do further certify that the labor ex-
 pended and improvements made upon or for the benefit of the lode
(lode or placer)
 location— embraced in the said mining claim by claimant— or their grantors
 are fully stated in my report therein, and that the character, extent, location, and
 itemized value thereof are specified therein with particularity and full detail, and
 that no portion of, or interest in, said labor and improvements so credited to this
 claim has been included in the estimate of expenditures upon any other claim.

Tucson, Arizona
(Place)


(Mineral Surveyor)

December 8, 1953
(Date)

**CERTIFICATE OF APPROVAL OF FIELD NOTES AND SURVEY OF
MINING CLAIM**

**UNITED STATES
DEPARTMENT OF THE INTERIOR
BUREAU OF LAND MANAGEMENT
~~PUBLIC SURVEY OFFICE~~
Division of Cadastral Engineering**

At Albuquerque, New Mexico

February 10, 1954

I, Office Cadastral Engineer at Albuquerque, New Mexico

do hereby certify that the forgoing and hereto attached Field Notes and return of the Survey of the Mining Claim of C. M. d'Autremont and H. W. Hasselgren, Trustees

known as the Tombstone Extension, Tombstone Extension #1, Tombstone Extension #2, Tombstone Extension #3, Tombstone Extension #4, Tombstone Extension No. 5, Blind Ledge, Blind Ledge No. 2, Blind Ledge No. 3, Chance, and Chance No. 1 lode claims,
situate in Tombstone mining district,

Cochise County, Arizona

in Sections 12 and 13, Township No. 20 South, Range No. 22 East and
" 7 and 18 " " 20 South " " 23 East
G&SRM, Arizona, designated as Survey No. 4384

executed by T. N. Stevens, Mineral

Surveyer, September 15 to November 18 (incl.), 1953, under my instructions dated

August 31, 1953, have been critically examined and the necessary

corrections and explanations made, and the said Field Notes and Return, and the Survey they describe,

are hereby approved. The certified copy of the location certificate filed by the applicant for survey is

included and made a part of these field notes.

Geo. H. Well, Office Cadastral Engineer.

CERTIFICATE OF APPROVAL OF FIELD NOTES AND SURVEY OF MINING CLAIM

UNITED STATES DEPARTMENT OF THE INTERIOR BUREAU OF LAND MANAGEMENT

TO: [Faded text]

FROM: [Faded text]

DATE: [Faded text]

RE: [Faded text]

WHEREAS [Faded text]

AND WHEREAS [Faded text]

IT IS HEREBY CERTIFIED [Faded text]

[Faded signature]