

UNITED STATES
DEPARTMENT OF THE INTERIOR
BUREAU OF LAND MANAGEMENT

MINERAL SURVEY NO. 4515

Arizona Land District.

FIELD NOTES

Of The Survey Of The Mining Claim Of

CLARA B. DICKIE

Known As The

SILVER BELL NO. 1 Lode

MAYNARD Mining District,

MOHAVE County, ARIZONA

Section 20, Township 20 North, Range 15 West, G&SRM

Surveyed under order dated November 12, 1959

by Olaf Hondrum
Mineral Surveyor.

Claim located July 1, 1922

Survey commenced November 27, 1959

Survey completed December 2, 1959

Address of claimant c/o Dwight & Byrnes, Attorneys

7000 East Camelback Road

Scottsdale, Arizona

DATES OF AMENDED LOCATIONS

July 18, 1959

SURVEY NO. 4515

1

~~XXXXXX~~
Feet

This survey was made with a K. & E. transit, No. 129403, with horizontal limb 6.2 ins. diam., having two double opposite verniers, and full vertical circle 5 ins. diam., having one double vernier; the verniers read to one minute of arc; the eyepiece is equipped with a colored glass for making direct observation on the sun. The instrument was in good condition at the time of the survey and all adjustments were in good order.

All azimuths in this record were determined by the method of deflection angles referred to the meridian established by direct observation on the sun Nov. 27, 1959, at Cor. No. 1 of the Silver Bell No. 1 lode, latitude $35^{\circ} 06' N.$, longitude $113^{\circ} 54' W.$, turning from a reference point in the SW direction clockwise to the sun in the NE direction.

True bearing of reference point: $S. 30^{\circ} 00' W.$

The lines were measured with a Lufkin steel tape 300 ft. in length, graduated every foot, with the first and last foot graduated to hundredths of a foot. The tape was compared with a standard of the Arizona Highway Department and found correct.

All lines of this survey were run by direct methods.

The magnetic declination observed at each corner of the survey gave a uniform value of $15^{\circ} E.$

SILVER BELL NO. 1 LODE

At Cor. No. 1 of the Silver Bell No. 1 lode.

Set an iron post, 30 ins. long, $1\frac{1}{2}$ ins. diam., 16 ins. in the ground, with galvanized cap mkd. SBL-1-4515; from which

The cor. of Secs. 17, 18, 19 and 20, T. 20 N., R. 15 W., G&SRM, bears $N. 54^{\circ} 38' W.$, 2685.0 ft. dist., an iron post, $1\frac{1}{2}$ ins. diam., 18 ins. above ground, mkd. as described in the official record.

A standard $2\frac{1}{2}$ -in. Bureau of Land Management iron post, set, mkd. and witnessed as described in the official record bears $N. 30^{\circ} 00' E.$, 1.2 ft. dist.

A granite boulder, 10 x 15 ft., 8 ft. above ground, bears $N. 52^{\circ} 40' E.$, 64.0 ft. dist., mkd. XBO-SBL-1-4515.

Thence $S. 30^{\circ} 00' W.$

- 150.0 Gully, 5 ft. wide, course SW.
- 150.0 Power line bears NW and SE.
- 302.4 Lode line; discovery point bears $S. 52^{\circ} 45' E.$, 500.0 ft. dist.
- 312.0 Center of paved road, 26 ft. wide, bears NW and SE.
- 340.0 Wash, 5 ft. wide, course NW.
- 370.0 Road, bears NW and SE.
- 405.0 2-in. water line bears NW and SE.
- 604.8 Cor. No. 2, a regulation $2\frac{1}{2}$ -in. Bureau of Land Management iron post, set, mkd. and witnessed as described in the official record. Add marks SBL-2-4515; from which

XEBGHSK

Feet

A granite boulder, 6 x 20 ft., 6 ft. above ground, bears N. 58° 17' W., 12.5 ft. dist., mkd. XBO-SB1-2-4515.

Thence S. 52° 45' E.

422.0 Ridge bears N. and S.

525.0 Gully, 10 ft. wide, course N.

908.0 Ridge bears NW and SE.

995.0 Gully, 10 ft. wide, course N.

1498.2 Cor. No. 3, a regulation 2 1/2-in. Bureau of Land Management iron post, set, mkd. and witnessed as described in the official record. Add mks. SB1-3-4515; from which

A granite boulder, 2 x 2 ft., 12 ins. above ground, bears S. 52° 10' W., 9.75 ft. dist., mkd. XBO-SB1-3-4515.

Thence N. 30° 00' E.

141.0 Ridge bears NW and SE.

275.0 Wash, 5 ft. wide, course NW.

298.0 Road, bears NW and SE.

302.4 Lode line; discovery point bears N. 52° 45' W., 998.2 ft. dist.

440.0 Power line bears NW and SE.

440.0 Ridge bears NW and SE.

570.9 Cor. No. 1, a regulation 2 1/2-in. Bureau of Land Management iron post, set, mkd. and witnessed as described in the official record. Add mks. SB1-4-4515; from which

A granite boulder, 2 x 5 ft., even with the ground, bears S. 3° 45' W., 22.6 ft. dist., mkd. XBO-SB1-4-4515.

Thence N. 51° 28' W.

87.0 Ridge bears N. and S.

324.0 Wash, 5 ft. wide, course SW.

635.0 Center of paved road, 26 ft. wide, bears NE and SW.

861.0 Center of paved road, 26 ft. wide, bears NE and SW.

1070.0 Center of paved road, 26 ft. wide, bears NE and SW.

1359.0 Gully, 6 ft. wide, course SW.

1502.8 Cor. No. 1 and place of beginning.

AREAS

Total area, Silver Bell No. 1 lode 20.056 Acres

Chains
Feet

LOCATION

This survey is located in the $SE\frac{1}{4}NW\frac{1}{4}$, the $SW\frac{1}{4}NE\frac{1}{4}$ and the $NW\frac{1}{4}SE\frac{1}{4}$ of Section 20, T. 20 N., R. 15 W., G&SRM, Arizona.

The survey of the Silver Bell No. 1 lode is identical with the amended location as marked on the ground.

EXPENDITURES

The improvements and the value of the labor and improvements made upon or for the benefit of the lode location embraced in said mining claim by the claimant or her grantors are as follows:

- No. 1 The discovery point of the Silver Bell No. 1 lode is on the lode line 500 ft. from the center of line 1-2.
No value.
- No. 2 A tunnel, 5 x 7 ft. in size, the portal of which bears N. 83° 10' W., 528.0 ft. dist. from Cor. No. 4, Silver Bell No. 1 lode; thence S. 66° 18' E., 25.0 ft.; thence S. 51° E., 85.0 ft. to face; with a crosscut 25 ft. back from tunnel face, 20.0 ft. long, bears N. 38° E; and a 4 x 4 ft. shaft, 8.0 ft. deep at near end of crosscut.
Value of tunnel, crosscut and shaft, \$1200.
- No. 3 A cut bears S. 71° 30' W., 320.0 ft. dist. from Cor. No. 4, Silver Bell No. 1 lode, 6 x 14 ft., 9 ft. face, bears N. 30° E.
Value, \$60.

OTHER IMPROVEMENTS

None

FIELD ASSISTANTS

Don Hondrum
Alvin Graham

Head Chainman
Chainman

SURVEY NO. 1212

Chains	Description	Length	Remarks
	TACIT ON		
	<p>This survey is located in the NW 1/4 of Section 20, T. 20 N., R. 12 W., S. 12 E., Adams County, Iowa.</p> <p>The survey of the Silver Bell No. 1 lode is located in the NW 1/4 of Section 20, T. 20 N., R. 12 W., S. 12 E., Adams County, Iowa.</p>		
	ENTIRE		
	<p>The improvements and the value of the lode location are as follows:</p> <p>1. The discovery point of the Silver Bell No. 1 lode is on the line 50 ft. from the center of line 1-2.</p>		
	<p>A tunnel 5 x 7 ft. in size, the portal of which bears N. 70° 10' E. 228.0 ft. from Cor. No. 1, Silver Bell No. 1 lode; thence S. 60° 10' E. 110.0 ft.; thence S. 21° E. 8.0 ft. to face, with a crosscut 2 ft. back from tunnel face, 20.0 ft. from bears N. 30° E. and a 1/2 ft. shaft, 8.0 ft. deep at west end of crosscut.</p> <p>Value of tunnel, crosscut and shaft, \$1000.</p>		
	<p>A cut bears S. 71° 30' W. 320.0 ft. dist. from Cor. No. 1, Silver Bell No. 1 lode; S. 11° E. 9 ft. face, bears N. 30° E. value, \$50.</p>		
	OTHER IMPROVEMENTS		
	None		
	FIELD ASSISTANTS		
	<p>Lead Chainman Chainman</p>		
	<p>Don Johnson Alvin Johnson</p>		

UNITED STATES
DEPARTMENT OF THE INTERIOR
BUREAU OF LAND MANAGEMENT

7

CERTIFICATE OF SURVEYOR

December 3, 1959

I, Olaf Hondrum

Mineral Surveyor, hereby certify upon honor that in pursuance of an order received from the _____

Office Cadastral Engineer, at Phoenix, Arizona

dated November 12, 1959, I have faithfully and correctly executed the survey of

the mining claim of Clara B. Dickie

known as the Silver Bell No. 1 lode

(Lode, placer, or mill site)

situate in Maynard Mining District, Mohave County in Section 20

T. 20 North, R. 15 West, Gila & Salt River Meridian, Arizona, and

(State)

designated as Survey No. 4515, which is represented in the foregoing field notes as having been executed by me and under my direction, and that said survey has been made in strict conformity with said order, the Manual of Instructions for the Survey of the Public Lands of the United States, and in the specific manner described in the foregoing field notes, and I do further certify that the labor expended and improvements made

upon or for the benefit of the lode location(s) embraced in the said mining claim by

(Lode or placer)

claimant(s) or her grantors are fully stated in my report therein, and that the character, extent, location, and itemized value thereof are specified therein with particularity and full detail, and that no portion of, or interest in, said labor and improvements so credited to this claim has been included in the estimate of expenditures upon any other claim.

Olaf Hondrum

Olaf Hondrum

(Mineral Surveyor)

Phoenix, Arizona

(Place)

CERTIFICATE OF APPROVAL

Bureau of Land Management--Survey Office

(Office)

Phoenix, Arizona

(Place)

March 10, 1960

(Date)

The foregoing field notes of mineral survey No. 4515, in Maynard Mining District--

Section 20, T. 20 North, R. 15 West, Gila & Salt River Meridian,

Arizona

(State)

, executed by Olaf Hondrum, Mineral Surveyor,

under order dated 11-12-59, having been critically examined and the necessary corrections made prior to their certification by the surveyor, the field notes and the survey therein described are hereby approved.

Lester S. Mann

Lester S. Mann

Office Cadastral Engineer

(Title)

CERTIFICATE OF TRANSCRIPT

I CERTIFY that the foregoing transcript of field notes of the above described mineral survey No. _____ is a true copy of the original field notes.

(Title)

