

Form 4-683
(January 1963)

UNITED STATES
DEPARTMENT OF THE INTERIOR
BUREAU OF LAND MANAGEMENT

FIELD NOTES

Mineral Survey number
4551

State
Arizona

Land District
Arizona

Of the Survey of the Mining Claim of *(name and address of Claimant)*

V. W. Clifton
1707 West Griswold Road
Elyria, Ohio

Known as the *(name of group, if any)*

CONSISTING OF LOCATIONS NAMED AND LOCATED AS FOLLOWS

NAME OF LOCATION	DATE	
	LOCATED	AMENDED
Blue Knobb No. 30	4/29/57	10/5/64
Blue Knobb No. 31	4/29/57	10/5/64
Blue Knobb No. 32	4/29/57	10/5/64

Mining district Belmont			County Maricopa	
Section 10 & 11	Township 3 N.	Range 6 W.	Meridian G.&S.R.B.&M.	Survey under order dated 1/30/61 & Amended 11/3/64
Survey commenced 2/1/61		Survey completed 11/4/64	Name of Mineral Surveyor Harvey W. Smith	

1954	1954
1954	1954
1954	1954

REPORT OF THE
COMMISSIONER OF THE
DEPARTMENT OF HEALTH

1954

The following table shows the number of cases of the disease reported in the State of New York during the year 1954.

By County

The following table shows the number of cases of the disease reported in the State of New York during the year 1954.

County	1954	1953	1952	1951	1950
Albany	1	0	0	0	0
Albany	1	0	0	0	0
Albany	1	0	0	0	0

SURVEY NO. 4551

FEET

This survey was made with a Swiss Kern theodolite, model DKM1, No. 77769, having horizontal and vertical circles, 50 mm. in diam. The circles are graduated in degrees and twenty-minute increments. An optical micrometer, adjustable to the vertical and horizontal circles, permits the reading of angles direct to 10 seconds accuracy and estimating to one-second accuracy. The instrument is equipped with a colored eye-shade to be attached for making direct observations on the sun. The instrument was in good condition at the time of the survey and all adjustments were in good order.

All azimuths in this record were determined by the method of horizontal-angles-right referred to the meridian established by direct observation on the sun. At 09:30 A.M. on Feb. 9, 1961 at cor. No. 1 of the Blue Knobb No. 30 lode, latitude $33^{\circ}36'56''$ North, longitude $112^{\circ}51'03''$ West, turning from a reference pt. about 1800 ft. northeast, clockwise to the sun in a southeast direction.

True bearing of reference pt.
N. $29^{\circ}39'50''$ E.

The lines were measured with a Lufkin "Highway" steel tape, 300 ft. in length graduated every ft. for 299 ft. and the remaining ft. graduated to tenths and hundredths. One additional ft. at the "O" end of the tape is also graduated tenths and hundredths. The tape was compared to a standard and found to be correct. All lines and connections of this survey were run by direct methods.

The magnetic declination observed at each corner of the survey gave a uniform value of $13^{\circ}45'$ East.

SURVEY NO. 4551

At cor. No. 1 of the Blue Knobb No. 30 lode, identical with cor. No. 1 of the Blue Knobb No. 31 lode of this survey.

Set a galvanized iron post, $3/4$ in. diam., 30 ins. long, in a 25 pound concrete and rock base, 18 ins. in the ground, with a brass cap, 2 ins. diam., firmly secured to the iron post, mkd. USMS 4551 BK30 1 BK 31 1 X; from which

The $1/4$ cor. of Secs. 10 & 11, T.3N., R.6W., G.&S.R.B.&M., bears S. $8^{\circ}27'40''$ E., 211.41 ft. dist.; an iron post, 1 in. diam., 12 ins. above ground, firmly set, properly mkd. and witnessed as described in the official record.

A mound of stones constructed adjacent to the iron post.

Thence S. $27^{\circ}09'55''$ E.

600.0 Cor. No. 4 of the Blue Knobb No. 31 lode of this survey.

FEET	
1478.96	Cor. No. 2
	Set a galvanized iron post, 3/4 in. diam., 30 ins. long, in a 25 pound concrete and rock base, 18 ins. in the ground, with a brass cap, 2 ins. diam., firmly secured to the iron post, mkd. USMS 4551 BK 30 2 X; from which
	A mound of stones constructed adjacent to the iron post.
	Thence S. 42°17'35" W.
300.0	Lode line; discovery pt. bears N. 27°09'55" W., 750 ft. dist.
600.0	Cor. No. 3
	Set a galvanized iron post, 3/4 in. diam., 30 ins. long, in a 25 pound concrete and rock base, 18 ins. in the ground with a brass cap, 2 ins. diam., firmly secured to the iron post, mkd. USMS 4551 BK 30 3 X; from which
	A mound of stones constructed adjacent to the iron post.
	Thence N. 27°09'55" W.
1428.96	Left bank of drainage, 60 ft. wide, course, South.
1478.96	Cor. No. 4
	This cor. falls in the center of a drainage where a monument would soon be obliterated.
	Thence N. 42°17'35" E.
20.0	Left bank of drainage, 60 ft. wide, course, South.
120.26	Pt. for witness cor. for. cor. No. 4
	Set a galvanized iron post, 3/4 in. diam., 30 ins. long, in a 25 pound concrete and rock base, 18 ins. in the ground, with a brass cap, 2 ins. diam., firmly secured to the iron post, mkd. USMS 4551 BK 30 4W.C. X; from which
	A mound of stones constructed adjacent to the iron post.
300.0	Lode line; discovery pt. bears S. 27°09'55" E., 728.96 ft. dist.
600.0	Cor. No. 1 and the place of beginning.
BLUE KNOBB NO. 31 LODE	
	Beginning at cor. No. 1 of the Blue Knobb No. 31 lode, identical with cor. No. 1 of the Blue Knobb No. 30 lode of this survey; previously described.
	Thence N. 51°58'50" E.

SURVEY NO. 4551

FEET

1500.0 Cor. No. 2 identical with cor. No. 1 of the Blue Knobb No. 32 lode of this survey.

Set a galvanized iron post, 3/4 in. diam., 30 ins. long, in a 25 pound concrete and rock base, 18 ins. in the ground with a brass cap, 2 ins. diam., firmly secured to the iron post, mkd. USMS 4551 BK 31 2 BK 32 1 X; from which

The 1/4 cor. of Secs. 10 & 11, T. 3N., R. 6W., G. & S. R. B. & M., bears S. 45°26'30" W., 1614.77 ft. dist.; previously described.

A mound of stones constructed adjacent to the iron post.

Thence S. 27°09'55" E.

300.0 Lode line; discovery pt. bears S. 51°58'50" W., 750 ft. dist.

600.0 Cor. No. 3 identical with cor. No. 4 of the Blue Knobb No. 32 lode of this survey.

Set a galvanized iron post, 3/4 in. diam., 30 ins. long, in a 25 pound concrete and rock base, 18 ins. in the ground, with a brass cap, 2 ins. diam., firmly secured to the iron post, mkd. USMS BK 31 3 BK 32 4 X; from which

A mound of stones constructed adjacent the iron post.

Thence S. 51°58'50" W.

1500.0 Cor. No. 4, on line 1-2 of the Blue Knobb No. 30 lode of this survey.

Set a galvanized iron post, 3/4 in. diam., 30 ins. long, in a 25 pound concrete and rock base, 18 ins. in the ground, with a brass cap, 2 ins. diam., firmly secured to the iron post, mkd. USMS 4551 BK 31 4 X; from which

A mound of stones constructed adjacent to the iron post.

Thence N. 27°09'55" W.

300.0 Lode line; discovery pt. bears N. 51°58'50" E., 750 ft. dist.

600.0 Cor. No. 1 and the place of beginning.

BLUE KNOBB NO. 32

Beginning at cor. No. 1 of the Blue Knobb No. 32 lode, identical with cor. No. 2 of the Blue Knobb No. 31 lode of this survey; previously described.

Thence N. 34°25' E.

FEET	
1500.0	<p>Cor. No. 2</p> <p>Set a galvanized iron post, 3/4 in. diam., 24 ins. long, in a 25 pound concrete and rock base, 12 ins. in the ground, with a brass cap, 2 ins. diam., firmly secured to the iron post, mkd. USMS 4551 BK 32 2 X; from which</p> <p style="padding-left: 40px;">A mound of stones constructed adjacent to the iron post.</p> <p style="padding-left: 80px;">Thence S. 27°09'55" E.</p>
300.0	Lode line; discovery pt. bears S. 34°25' W., 750 ft. dist.
600.0	<p>Cor. No. 3</p> <p>Set a galvanized iron post, 3/4 in. diam., 24 ins. long, in a 25 pound concrete and rock base, 12 ins. in the ground, with a brass cap, 2 ins. diam., firmly secured to the iron post, mkd. USMS 4551 BK 32 3 X; from which</p> <p style="padding-left: 40px;">A mound of stones constructed adjacent to the iron post.</p> <p style="padding-left: 80px;">Thence S. 34°25' W.</p>
1500.0	<p>Cor. No. 4 identical with cor. No. 3 of the Blue Knobb No. 31 lode of this survey; previously described.</p> <p style="padding-left: 80px;">Thence N. 27°09'55' W.</p>
300.0	Lode line; discovery pt. bears N. 34°25' E., 750 ft. dist.
600.0	Cor. No. 1 and the place of beginning.

SURVEY NO. 4551

AREAS

	<u>Acres</u>
Total area, Blue Knobb No. 30 lode	19.076
Total area, Blue Knobb No. 31 lode	20.291
Total area, Blue Knobb No. 32 lode	18.172

LOCATION

This survey is located in the NE 1/4 & SE 1/4 of Sec. 10 and the NW 1/4 & SW 1/4 of Sec. 11, T. 3N., R. 6W., G. & S. R. B. & M.

The survey of the Blue Knobb Nos. 30, 31 & 32 lodes is identical with the respective location or amended location as marked on the ground.

EXPENDITURES

The improvements and the value of the labor and improvements made upon or for the benefit of each of the lode locations embraced in said mining claim by the claimant or his grantors are as follows:

SURVEY NO. 4551

FEET	
No. 1	<p>The discovery pt. of the Blue Knobb No. 30 lode is on the lode line, 750 ft. from a pt. on line 2-3, 300 ft. from cor. No. 2. Value, None</p>
No. 2	<p>A cut, the NE. cor. of which bears S. 69° W., 235 ft. from cor. No. 2 of the Blue Knobb No. 30 lode; 100 x 90 ft. in size, 1 ft. average depth. Value, \$100.00</p>
No. 3	<p>A cut, the SE. cor. which bears S. 80° W., 120 ft. from cor. No. 2 of the Blue Knobb No. 30 lode; 60 x 70 ft. in size, 1 ft. average depth. Value, \$85.00</p>
No. 4	<p>A timbered shaft, the SE. cor. of the collar bears S. 89° W., 200 ft. from cor. No. 2 of the Blue Knobb No. 30 lode; 4 x 8 ft. in size, 30 ft. deep. Value, \$2,000.00</p>
No. 5	<p>A cut, the SE. cor. of which bears N. 73° W., 185 ft. from cor. No. 2 of the Blue Knobb No. 30 lode; 50x60 ft. in size, 2 1/2 ft. average depth. Value, \$100.00</p>
No. 6	<p>A cut, the SE. end of which bears N. 60° W., 230 ft. from cor. No. 2 of the Blue Knobb No. 30 lode; 6 ft. wide, 3 ft. average depth, and running N. 45° W., 20 ft. Value, \$100.00</p>
No. 7	<p>A cut, the SE. cor. of which bears N. 60° W., 255 ft. from cor. No. 2 of the Blue Knobb No. 30 lode; 20 ft. wide, 4 ft. average depth and running N. 10° E., 60 ft. In the center is a pit, 10x10 ft. in size, 8 ft. deep. Value, \$250.00</p>
No. 8	<p>A cut, the SE. cor. of which bears N. 32°30' W., 605 ft. from cor. No. 2 of the Blue Knobb No. 30 lode; 12 ft. wide, 2 ft. average depth and running N. 40° E., 50 ft. Value, \$100.00</p>
No. 9	<p>A cut, the SE. cor. of which bears N. 28°30' W., 960 ft. from cor. No. 2 of the Blue Knobb No. 30 lode; 12 ft. wide, 2 ft. average depth and running N. 80° W., 60 ft. Value, \$100.00</p>
No. 1	<p>The discovery pt. of the Blue Knobb No. 31 lode is on the lode line, 750 ft. from a pt. on line 2-3, 300.0 ft. from cor. No. 2. Value, None</p>
No. 2	<p>A pit, the SW. cor. of which bears N. 31°30' E., 380 ft. from cor. No. 4 of the Blue Knobb No. 31 lode; 7x9 ft. in size, 10 ft. deep. Value, \$250.00</p>

FEET	
No. 3	<p>A cut, the SW. cor. of which bears N. 85° E., 100 ft. from cor. No. 1 of the Blue Knobb No. 31 lode; 11 ft. wide, 3 1/2 ft. deep and running N. 45° W., 60 ft. Value, \$200.00</p>
No. 4	<p>A pit, the SW. cor. of which bears N. 80° E., 700 ft. from cor. No. 1 of the Blue Knobb No. 31 lode; triangularly shaped, 7 ft. on each side, 4 ft. deep. Value, \$125.00</p>
No. 1	<p>The discovery pt. of the Blue Knobb No. 32 lode is on the lode line, 750 ft. from a pt. on line 2-3, 300.0 ft. from cor. No. 2. Value, None</p>
No. 2	<p>A cut, the NW. cor. of which bears S. 28° E., 170 ft. from cor. No. 2 of the Blue Knobb No. 32 lode; 7 ft. wide, running south 15 ft. to a 10 ft. face. Value apportioned this lode, \$100.00</p>

OTHER IMPROVEMENTS

None

OTHER CORNER DESCRIPTIONS AND SUPPLEMENTAL DATA

None

FIELD ASSISTANT

Name	Capacity
Jack Campbell	Chainman - Axeman

UNITED STATES
DEPARTMENT OF THE INTERIOR
BUREAU OF LAND MANAGEMENT

CERTIFICATE OF SURVEYOR

Name of Mineral Surveyor Harvey W. Smith	Date November 4, 1964
---	--------------------------

I HEREBY CERTIFY That in pursuance of an order received from the
State Director, at Phoenix, Arizona
dated 1/30/61 & Amended Nov. 3, 1964, I have carefully executed the survey of the claim
of V. W. Clifton
known as the (lode, placer, or mill site) Blue Knobb Nos. 30, 31 & 32 lodes
situated in Belmont Mining District, Maricopa County, Secs. 10 & 11
Township 3 N., Range 6 W., Gila & Salt River Base & Meridian, in the
State of Arizona

This survey, designated as number 4551, has been executed by me and under my direction
and has been made in strict conformity with said order, the Manual of Instructions for the Survey of Public
Lands of the United States, and in the specific manner described in the foregoing field notes.


I FURTHER CERTIFY That the labor expended and improvements made upon and for the benefit of
the (lode or placer) lode location(s)
embraced in the said mining claim by claimant(s) or his
grantors are fully stated in my report. The character, extent, location, and itemized value are specified in
full detail. No portion of, or interest in, said labor and improvements so credited to this claim has been in-
cluded in the estimate of expenditures upon any other claim.

Scottsdale, Arizona
(Location) 
(Signature of Mineral Surveyor)
Harvey W. Smith

CERTIFICATE OF APPROVAL

Bureau of Land Management Office Arizona State Office
Location Phoenix, Arizona
Date November 5, 1964

The foregoing field notes of mineral survey number 4551, in Sections 10 and 11
Township 3 N., Range 6 W., Gila & Salt River, surveyed unsurveyed
State of Arizona, executed by Harvey W. Smith
Mineral Surveyor, under order dated 1/30/61 & Nov. 3, 1964, having been critically examined and the
necessary corrections made prior to their certification by the surveyor, the field notes and the survey therein
described are hereby approved.


Raymond C. Cleghorn (Authorized Signature) Acting State Director (Title)

CERTIFICATE OF TRANSCRIPT

I CERTIFY That the foregoing transcript of field notes of the above described mineral survey
number is a true copy of the original field notes.

(Authorized Signature) (Title)

Title 18, U. S. C. section 1001, makes it a crime for any person knowingly and willfully to make to any department or
agency of the United States any false, fictitious, or fraudulent statements or representations as to any matter within
its jurisdiction.

RECEIVED
OFFICE OF THE SECRETARY
OF THE ARMY

WASHINGTON, D. C.

1918

THE SECRETARY OF THE ARMY

WASHINGTON, D. C.

TO THE SECRETARY OF THE ARMY
FROM THE SECRETARY OF THE ARMY

RE: [Illegible]

[Illegible text]

UNITED STATES DEPARTMENT OF THE INTERIOR 9605 (956)
BUREAU OF LAND MANAGEMENT M.S. 4551
ARIZONA STATE OFFICE

NOTICE OF CANCELLATION OF MINERAL SURVEY

The Blue Knobb No. 30, Blue Knobb No. 31 and Blue Knobb No. 32 lodes, Mineral Survey No. 4551, located in sections 10 and 11, Township 3 North, Range 6 West, Gila and Salt River Meridian, Arizona, are hereby canceled.

These claims have not been filed with the Arizona State Office, Bureau of Land Management, in accordance with Section 314, 90 STAT. 2769, (43 U.S.C. 1744).

This cancellation was necessitated to clear the record.

The Mineral Survey Plat should be noted as follows:

"Blue Knobb No. 30, Blue Knobb No. 31 and Blue Knobb No. 32 lodes, M.S. 4551, were canceled March 11, 2002, by memo 9605 (956) M.S. 4551, which is now a part of the original field notes."

March 11, 2002
Date



Chief Cadastral Surveyor of Arizona

