

Form 3400-11  
(September 1967)  
(formerly 4-683)

UNITED STATES  
DEPARTMENT OF THE INTERIOR  
BUREAU OF LAND MANAGEMENT

FIELD NOTES

Mineral Survey number  
4689

State  
Arizona

Land District  
Arizona

Of the Survey of the Mining Claim of *(name and address of Claimant)*

Globe Resources, Inc.  
P. O. Box 243  
Buckeye, Arizona 85326

Known as the *(name of group, if any)*

CONSISTING OF LOCATIONS NAMED AND LOCATED AS FOLLOWS

NAME OF LOCATION	DATE	
	LOCATED	AMENDED
Gold Spot #1	11/3/65	
GOLDSPOT #2	11/8/67	
GOLDEN WEST NO. 1	8/8/67	5/9/71

Mining district White Tanks			County Maricopa	
Section 12, 11 & 14	Township 1 N.	Range 4 W.	Meridian G&SR	Survey under order dated April 23, 1971
Survey commenced May 1, 1971		Survey completed June 21, 1971	Name of Mineral Surveyor Robert E. Adams	
			Amd. June 15, 1971	

The first part of the document discusses the importance of maintaining accurate records. It emphasizes that proper documentation is essential for ensuring the integrity and reliability of the data collected. This section also outlines the various methods used to gather information, including direct observation, interviews, and the use of standardized forms.

The second part of the document focuses on the analysis and interpretation of the data. It describes the statistical techniques employed to identify trends and patterns within the dataset. The authors note that while the data shows a general upward trend, there are significant fluctuations that require further investigation. They conclude that the findings have important implications for the field and suggest several areas for future research.

In conclusion, this study has provided valuable insights into the subject matter. The authors believe that the results presented here will be useful to other researchers and practitioners alike. They encourage continued collaboration and the sharing of knowledge to advance the field further.

FEET	
	<p>This survey was made with a Universal Wild T2 Theodolite No. T2-68064, reading by optical micrometer to one second of arc. The instrument was in good condition at the time of the survey and all adjustments were in good order.</p> <p>All azimuths in this record were determined by the method of deflection angles referred to the meridian determined by the following observation:</p> <p>On May 1, 1971 at Cor. No. 4 of the GOLDEN WEST NO. 1 lode, this survey, in latitude <math>33^{\circ} 26.1' N.</math>, and longitude <math>112^{\circ} 37.3' W.</math>, I made a series of six altitude observations upon the sun three each with the telescope in the direct and reversed positions, observing opposite limbs of the sun, and reading the horizontal angle from a reference point about 1,000 feet easterly, to the sun. The true bearing of this line is <math>N. 68^{\circ} 53' 20'' E.</math></p> <p>The lines were measured with a Lufkin steel tape, 300 feet in length graduated every foot throughout its length with the 99th, 199th, and 299th foot graduated to tenths and hundredths of a foot. The tape was compared with a standard tape at the time of survey and found to be correct.</p> <p>All lines and connections of this survey were run by direct methods.</p> <p>The magnetic declination observed at each corner of the survey gave a uniform value of <math>N. 14^{\circ} E.</math></p>
	<p><u>Gold Spot #1 LODE</u></p>
	<p>At Cor. No. 1 of the Gold Spot #1 lode</p> <p>Set a galvanized iron pipe, <math>3/4</math> in. diam., 25 in. long, 10 in. in the ground, in a mound of stones, with a brass cap 2 in. in diam. firmly secured to the iron pipe, mkd. GS1-1, 4689; from which</p> <p>The cor. to secs. 11, 12, 13, 14, T. 1 N., R. 4 W., G&amp;SRM, bears <math>S. 58^{\circ} 29' 00'' W., 346.72</math> ft. dist., a stone in a pile of stones marked and witnessed as described in the official record.</p> <p>A 4 x 6 in. wood post 5 ft. high is adjacent to the iron pipe.</p> <p>Thence <math>S. 68^{\circ} 53' 20'' W.</math></p>
415.	Road, 10 ft. wide, bears $N. 30^{\circ} W.$ and $S. 30^{\circ} E.$
451.19	Cor. No. 1 of the GOLDSPOT #2 lode, of this survey.

FEET	
1500.00	<p>Cor. No. 2, identical with Cor. No. 3 of the GOLDEN WEST NO. 1 lode, and on line 4-1 of the GOLDSPOT #2 lode, both of this survey.</p> <p>Set a galvanized iron pipe, 3/4 in. diam., 25 in. long, 14 in. in the ground, in a mound of stones, with a brass cap 2 in. in diam. firmly secured to the iron pipe, mkd. GS1-2, GW1-3, 4689; from which</p> <p style="padding-left: 40px;">A 4 x 6 in. wood post is adjacent to the iron pipe.</p> <p style="padding-left: 40px;">Thence N. 21° 06' 40" W.</p>
22	Ridge, bears E. and W.
170	Road, 10 ft. wide, bears N. 75° E. and S. 75° W.
300.00	Lode line; discovery point bears N. 68° 53' 20" E., 500 ft. dist.
325	Wash, 9 ft. wide, course N. 75° E.
560	Ridge, bears N. 57° E. and S. 57° W.
600.00	<p>Cor. No. 3, identical with Cor. No. 2 of the GOLDEN WEST NO. 1 lode, of this survey.</p> <p>Set a galvanized iron pipe, 3/4 in. diam., 25 in. long, 10 in. in the ground, in a mound of stones, with a brass cap, 2 in. in diam. firmly secured to the iron pipe, mkd. GS1-3, GW1-2, 4689; from which</p> <p style="padding-left: 40px;">A 4 x 6 in. wood post is adjacent to the iron pipe.</p> <p style="padding-left: 40px;">Thence N. 68° 53' 20" E.</p>
100	Ridge, bears N. 57° E. and S. 57° W.
325	Wash, 6 ft. wide, course N. 20° E.
400	Road, 10 ft. wide, bears N. 20° W. and S. 20° E.
905	Road, 10 ft. wide, bears N. and S.
1500.00	<p>Cor. No. 4</p> <p>Set a galvanized iron pipe, 3/4 in. diam., 25 in. long, 10 in. in the ground, in a mound of stones, with a brass cap 2 in. in diam. firmly secured to the iron pipe, mkd. GS1-4, 4689; from which</p> <p style="padding-left: 40px;">A 4 x 6 in. wood post is adjacent to the iron pipe.</p>

FEET	
	Thence S. 21° 06' 40" E.
274	Wash, 4 ft. wide, course S. 70° W.
300.00	Lode line; discovery point bears S. 68° 53' 20" W., 1,000 ft. dist.
500	Wash, 4 ft. wide, course N. 40° W.
600.00	Cor. No. 1, and place of beginning.
<u>GOLDEN WEST NO. 1 LODE</u>	
	At Cor. No. 1 of the GOLDEN WEST NO. 1 lode
	Set a galvanized iron pipe, 3/4 in. diam., 25 in. long, 10 in. in the ground, in a mound of stones, with a brass cap 2 in. in diam. firmly secured to the iron pipe, mkd. GW1-1, 4689; from which
	The 1/4 cor. to secs. 11, 14, T. 1 N. R. 4 W., G&SRM, bears N. 3° 23' 03" W., 313.39 ft. dist., a 3/8 in. iron pin. Two feet away from this iron pin I found a stone 5 x 10 x 18 in. with a 1/4 scribed on one face and lying flat on the ground.
	A 4 x 6 in. wood post 5 ft. high is adjacent to the iron pipe.
	Thence N. 68° 53' 20" E.
234	Wash, 8 ft. wide, course N. 20° W.
270	Road, 10 ft. wide, bears N. 23° W. and S. 23° E.
1400.00	Cor. No. 2, identical with Cor. No. 3 of the Gold Spot #1 lode of this survey.
	Thence S. 21° 06' 40" E.
40	Ridge, bears N. 57° E. and S. 57° W.
275	Wash, 9 ft. wide, course N. 75° E.
300.00	Lode line; discovery point bears S. 68° 53' 20" W., 545 ft. dist.
430	Road, 10 ft. wide, bears N. 75° E. and S. 75° W.
578	Ridge, bears E. and W.
600.00	Cor. No. 3, identical with Cor. No. 2 of the Gold Spot #1 lode, and on line 4-1 of the GOLDSPOT #2 lode, both of this survey.
	Thence S. 68° 53' 20" W.

FEET	
401	Ridge, bears E. and W.
451.19	Cor. No. 4 of the GOLDSLOT #2 lode, of this survey.
1400.00	<p>Cor. No. 4.</p> <p>Set a galvanized iron pipe, 3/4 in. diam., 25 in. long, 10 in. in the ground, in a mound of stones, with a brass cap 2 in. in diam. firmly secured to the iron pipe, mkd. GW1-4, 4689 from which</p> <p style="padding-left: 40px;">A 4 x 6 in. wood post 5 ft. high is adjacent to the iron pipe.</p> <p style="padding-left: 40px;">Thence N. 21° 06' 40" W.</p> <p>300.00 Lode line; discovery point bears N. 68° 53' 20" E., 855 ft. dist.</p> <p>500 Road, 10 ft. wide, bears E. and W.</p> <p>600.00 Cor. No. 1, and place of beginning.</p>
<u>GOLDSLOT #2 LODE</u>	
At Cor. No. 1 of the GOLDSLOT #2 lode, on line 1-2 of the Gold Spot #1 lode, of this survey.	
Set a galvanized iron pipe, 3/4 in. diam., 25 in. long, 10 in. in the ground, in a mound of stones, with a brass cap 2 in. in diam. firmly secured to the iron pipe, mkd. GS2-1, 4689 from which	
<p style="padding-left: 40px;">The cor. of secs. 11, 12, 13, 14, T. 1 N., R. 4 W., bears S. 81° 43' 57" E., 126.29 ft. dist.; previously described.</p> <p style="padding-left: 40px;">A 4 x 6 in. wood post 5 ft. high is adjacent to the iron pipe.</p> <p style="padding-left: 40px;">Thence S. 0° 53' 20" W.</p>	
323.56	Lode line; discovery point bears S. 68° 53' 20" W., 750 ft. dist.
365	Ridge, bears S. 85° W. and N. 85° E.
647.12	<p>Cor. No. 2</p> <p>Set a galvanized iron pipe, 3/4 in. diam., 25 in. long, 10 in. in the ground, in a mound of stones, with a brass cap 2 in. in diam. firmly secured to the iron pipe, mkd. GS2-2, 4689; from which</p> <p style="padding-left: 40px;">A 4 x 6 in. wood post 5 ft. high is adjacent to the iron pipe.</p> <p style="padding-left: 40px;">Thence S. 68° 53' 20" W.</p>

FEET	
228	Road, 12 ft. wide, bears E. and W.
263	Road, 10 ft. wide, bears N. 20° W. and S. 20° E.
704	Ridge, bears N. 45° W. and S. 45° E.
1500.00	Cor. No. 3  Set a galvanized iron pipe, 3/4 in. diam., 25 in. long, 10 in. in the ground, in a mound of stones, with a brass cap 2 in. in diam. firmly secured to the iron pipe, mkd. GS2-3, 4689; from which  A 4 x 6 in. wood post 5 ft. high is adjacent to the iron pipe.  Thence N. 0° 53' 20" E.
323.56	Lode line; discovery point bears N. 68° 53' 20" E., 750 ft. dist.
647.12	Cor. No. 4, on line 3-4 of the GOLDEN WEST NO. 1 lode, of this survey.  Set a galvanized iron pipe, 3/4 in. diam., 25 in. long, 9 in. in the ground, in a mound of stones, with a brass cap 2 in. in diam. firmly secured to the iron pipe, mkd. GS2-4, 4689; from which  A 4 x 6 in. wood post 5 ft. high is adjacent to the iron pipe.  Thence N. 68° 53' 20" E.
50.19	Ridge, bears E. and W.
451.19	Cor. No. 3 of the GOLDEN WEST NO. 1 lode, identical with Cor. No. 2 of the Gold Spot #1 lode, both of this survey.
1500.00	Cor. No. 1, and place of beginning.
AREAS	
	<u>Acres</u>
Total area, Gold Spot #1 lode	20.661
Total area, GOLDEN WEST NO. 1 lode	19.284
Total area, GOLDSPOT #2 lode	20.661
LOCATION	
<p>This survey is located in the NE 1/4, sec. 14; SE 1/4, sec. 11 and the SW 1/4, sec. 12 of T. 1 N., R. 4 W., Gila and Salt River Base and Meridian, Arizona.</p>	

FEET

The survey of the Gold Spot #1, GOLDSPOT #2, and GOLDEN WEST NO. 1 lode claims are identical with the respective locations or amended locations as marked on the ground.

## EXPENDITURES

The improvements and the value of the labor and improvements made upon or for the benefit of each of the lode locations embraced in said mining claim by the claimant or its grantors are as follows:

- No. 1 The discovery cut, a point within being the discovery point of the Gold Spot #1 lode, is on the lode line 1,000 ft. from the center of line 4-1, cut described as follows: The beginning of the cut bears S. 86° 31' W., 966 ft. dist. from Cor. No. 1, 10 ft. wide and running S. 83° W., 120 ft. dist. to face 35 ft. high and portal of tunnel 6 x 12 ft. in size running 44 ft. to breast 6 x 4 ft. in size.  
Value of cut and tunnel, \$8,500
- No. 2 Trench, the east end of which bears S. 66° 02' E., 377 ft., from Cor. No. 3 Gold Spot #1 lode; 4 ft. wide, 8 ft. deep, running S. 72° W., 47 ft. A trench 3 ft. wide, 3 ft. deep intersects the first trench near its midpoint and runs N. 18° W., 15 ft.  
Value of both trenches, \$600
- No. 3 Trench, 4 ft. wide, 2 ft. deep, extends across the lode line, 340 ft. from the center of line 4-1, Gold Spot #1 lode, running N. 6° W., 22 ft. and S. 6° E., 3 ft. from the lode line.  
Value, \$50
- No. 4 Trench, the east end of which bears N. 63° 02' W., 449 ft., from Cor. No. 1 Gold Spot #1 lode; 6 ft. wide, 2 ft. deep, running N. 81° W., 80 ft.  
Value, \$100
- No. 5 Trench, the east end of which bears N. 65° 35' W., 546 ft. from Cor. No. 1 Gold Spot #1 lode; 3 ft. wide, 2 ft. deep, running N. 53° W., 50 ft.  
Value, \$75
- No. 6 Trench, the west end of which bears N. 75° 23' W., 610 ft. from Cor. No. 1 Gold Spot #1 lode; 4 ft. wide, 2 ft. deep, running N. 70° E., 22 ft.  
Value, \$50
- No. 7 Access roads amounting to 1,200 ft. in length have been constructed for the

FEET		
	<p>purpose of providing access to and for the removal of ore and rock from the various improvements to the Gold Spot #1 lode. Value, \$300</p>	
No. 1	<p>The discovery point of the GOLDEN WEST NO. 1 lode, is on the lode line 545 ft. from the center of line 2-3. Value, None</p>	
No. 2	<p>Trench, 5 ft. wide, 1½ ft. deep, extends across lode line, GOLDEN WEST NO. 1 lode, 401 ft. from the center of line 4-1, running N. 21° W., 6 ft., and S. 21° E., 69 ft. from the lode line. Value, \$100</p>	
No. 3	<p>Trench, 8 ft. wide, 3 ft. deep, extends across lode line, GOLDEN WEST NO. 1 lode, 383 ft. from the center of line 4-1, running N. 36° W., 28 ft. and S. 36° E., 22 ft. from the lode line. Value, \$400</p>	
No. 4	<p>Access roads amounting to 600 ft. in length have been constructed for the purpose of providing access to and for the removal of ore and rock from the various improvements to the GOLDEN WEST NO. 1 lode. Value, \$200</p>	
No. 1	<p>The discovery point of the GOLDSPOT #2 lode, is on the lode line 750 ft. from the center of line 1-2. Value, None</p>	
No. 2	<p>Tunnel, 5 x 5 ft. in size, the entrance cut of which bears S. 88° 42' W., 550 ft. from Cor. No. 2 GOLDSPOT #2 lode, and runs N. 47° W., 26 ft. to face and portal of tunnel; thence N. 47° W., 6 ft.; thence N. 87° W., 18 ft. to center of 5 x 9 ft. shaft, 18 ft. deep; thence N. 87° W., 18 ft. to caved end of tunnel at a 7 x 13 ft. shaft, 18 ft. deep. Value of tunnel only, \$700</p>	
	<p>No portion of or interest in these improvements has been credited heretofore as patent expenditure to any lode claim.</p>	
	<p>OTHER IMPROVEMENTS</p> <p>Shaft, 4 ft. diam., 10 ft. deep, the center of which bears N. 75° 44' W., 745 ft., from Cor. No. 1 Gold Spot #1 lode.</p> <p>Shaft, 9 x 6 ft., 30 ft. deep to first level, additional depth unknown, the center of which bears N. 76° 22' W., 675 ft. from Cor. No. 1 Gold Spot #1 lode.</p>	

FEET

Shaft, 7 x 4 ft., 15 ft. deep, the center of which bears N. 75° 23' W., 610 ft., from Cor. No. 1 Gold Spot #1 lode.

Shaft, 6 x 5 ft., 29 ft. deep, the south edge of which bears N. 62° 07' W., 450 ft. from Cor. No. 1 Gold Spot #1 lode.

Shaft, 7 x 9 ft., 25 ft. deep, the center of which bears S. 53° 30' E., 308 ft., from Cor. No. 3 Gold Spot #1 lode. At bottom of shaft a 4 x 9 ft. drift runs N. 69° E., 18 ft. to breast. A second drift 4 x 7 ft. in size, runs S. 69° W., approximately 60 ft. to breast.

Shaft, 7 x 5 ft., 61 ft. deep, the center of which bears S. 86° 23' E., 745 ft., from Cor. No. 3 Gold Spot #1 lode.

Shaft, 6 x 9 ft., 43 ft. deep, the center of which bears N. 87° 56' W., 800 ft. from Cor. No. 1 Gold Spot #1 lode.

Shaft, approximately 300 ft. deep, the center of which bears N. 72° 53' W., 525 ft. from Cor. No. 1 Gold Spot #1 lode.

Shaft, 4 x 6 ft., 14 ft. deep, the center of which bears N. 63° 22' W., 392 ft. from Cor. No. 1 Gold Spot #1 lode.

Three pits, 5 x 10 ft., 5 ft. deep, the center of the east pit bears N. 43° 00' W., 356 ft. from Cor. No. 1 Gold Spot #1 lode.

Shaft, 3½ x 3½ ft., 13 ft. deep, the center of which bears N. 81° 29' W., 576 ft. from Cor. No. 1 Gold Spot #1 lode.

Claimant of each of the above unknown.

Pilot mill, partially completed. Includes a 13 ft. x 13 ft. concrete slab for ore storage, jaw crusher, arrastar and settlement basins. The west edge of the concrete slab for ore storage bears S. 89° 28' W., 971 ft. from Cor. No. 1 Gold Spot #1 lode.

Claimant herein.

Earth dam, 10 ft. wide, 80 ft. long, for water storage, the center of the dam bears S. 75° 25' W., 960 ft. from Cor. No. 1 Gold Spot #1 lode, runs N. 65° E.

Claimant herein.

Shaft, 6 x 4½ ft., 32 ft. deep, the center of which bears N. 65° 27' W., 370 ft. from Cor. No. 3 GOLDEN WEST NO. 1 lode. A trench, 4 ft. wide, 3 ft. deep,

FEET	
	<p>extends from the west edge of the shaft and runs S. 70° W., 30 ft.</p> <p>Shaft, 6 x 9 ft., 16 ft. deep, the center of which bears N. 69° 52' W., 464 ft. from Cor. No. 3 GOLDEN WEST NO. 1 lode.</p> <p>Shaft, 6 x 4 ft. 10 ft. deep, the center of which bears N. 85° 42' W., 827 ft. from Cor. No. 3 GOLDEN WEST NO. 1 lode.</p> <p>Shaft, 6 x 4 ft., 18 ft. deep, the center of which bears N. 88° 58' W., 806 ft. from Cor. No. 3 GOLDEN WEST NO. 3 lode.</p> <p>Shaft, 6 x 6 ft., 30 ft. deep to water, the center of which bears S. 88° 40' W., 886 ft. from Cor. No. 3 GOLDEN WEST NO. 1 lode.</p> <p>Claimant of each of the above unknown.</p> <p>Cut, pit and tunnel; beginning of cut bears S. 81° 50' W., 504 ft. from Cor. No. 2 GOLDSPOT #2 lode; 5 ft. wide, running N. 8° W., 40 ft.; to 9 ft. face and a 6 ft. pit; thence 4 ft. to portal of tunnel; thence N. 58° W., 50 ft. to breast.</p> <p>Shaft, 5 x 8 ft., inclined 10° from the vertical, approximately 60 ft. deep, the center of which bears S. 89° 36' W., 640 ft. from Cor. No. 2 GOLDSPOT #2 lode.</p> <p>Two shafts, the descriptions of which were described under improvement No. 2 GOLDSPOT #2 lode.</p> <p>Pit, 4 x 5 ft., 5 ft. deep, the center of which bears S. 89° 08' W., 707 ft. from Cor. No. 2 GOLDSPOT #2 lode.</p> <p>Pit, 4 x 9 ft., 8 ft. deep, the center of which bears S. 85° 37' W., 822 ft. from Cor. No. 2 GOLDSPOT #2 lode.</p> <p>Claimant of each of the above unknown.</p> <p>Concrete powder magazine 3½ ft. x 4½ ft., the center of which bears N. 24° 56' W., 595 ft. from Cor. No. 2 GOLDSPOT #2 lode.</p> <p>Claimant herein.</p> <p>OTHER CORNER DESCRIPTIONS AND SUPPLEMENTAL DATA</p> <p>None</p>

FEET

FIELD ASSISTANTS

Bill Troutman  
Don Wilson

Instrumentman  
Chainman

UNITED STATES  
DEPARTMENT OF THE INTERIOR  
BUREAU OF LAND MANAGEMENT

CERTIFICATE OF SURVEYOR

Name of Mineral Surveyor Robert E. Adams	Date August 25, 1971
---	-------------------------

I HEREBY CERTIFY That in pursuance of an order received from the Bureau of Land Management, at Phoenix, Arizona, dated April 23, & amended June 15, 1971, I have carefully executed the survey of the claim of Globe Resources, Inc. known as the ~~(lode, placer)~~ Gold Spot #1, GOLDSLOT #2, GOLDEN WEST NO.1, situated in Sec. 11, 12 & 14, Township 1 N., Range 4 W., Gila & Salt River Meridian, in the State of Arizona.

This survey, designated as number 4689, has been executed by me and under my direction and has been made in strict conformity with said order, the Manual of Instructions for the Survey of Public Lands of the United States, and in specific manner described in the foregoing field notes.

I FURTHER CERTIFY That the labor expended and improvements made upon and for the benefit of the (lode or placer) lode location(s) embraced in the said mining claim by claimant(s) or its grantors are fully stated in my report. The character, extent, location, and itemized value are specified in full detail. No portion of, or interest in, said labor and improvements so credited to this claim has been included in the estimate of expenditures upon any other claim.

Phoenix, Arizona  
(Location)

*Robert E. Adams*  
(Signature of Mineral Surveyor)

CERTIFICATE OF APPROVAL

BUREAU OF LAND MANAGEMENT

Office Arizona State Office
Location Phoenix, Arizona
Date December 16, 1971

The foregoing field notes of mineral survey number 4689, in Sections 11, 12 and 14 Range 4 W., Gila and Salt River Meridian, in the State of Arizona,  surveyed  unsurveyed Township 1 N., executed by Robert E. Adams, Mineral Surveyor, under order dated 4/23/71 & Amd. 6/15, 1971, having been critically examined and the necessary corrections made prior to their certification by the surveyor, the field notes and the survey therein described are hereby approved.

*Joe T. Fullum*  
(Authorized Signature)

State Director  
(Title)


~~CERTIFICATE OF TRANSCRIPT~~

~~I HEREBY CERTIFY That the foregoing transcript of field notes of the above described mineral survey number is a true copy of the original field notes.~~

~~(Authorized Signature)~~

~~(Title)~~

Title 18, U.S.C. section 1001, makes it a crime for any person knowingly and willfully to make to any department or agency of the United States any false, fictitious, or fraudulent statements or representations as to any matter within its jurisdiction.



UNITED STATES DEPARTMENT OF THE INTERIOR 9605 (956)  
BUREAU OF LAND MANAGEMENT M.S. 4689  
ARIZONA STATE OFFICE

---

NOTICE OF CANCELLATION OF MINERAL SURVEY

The Golden West No. 1, Gold Spot #1 and Goldspot #2 lodes, Mineral Survey No. 4689, located in sections 11, 12 and 14, Township 1 North, Range 4 West, Gila and Salt River Meridian, Arizona, are hereby canceled.


These claims have not been filed with the Arizona State Office, Bureau of Land Management, in accordance with Section 314, 90 STAT. 2769, (43 U.S.C. 1744).

This cancellation was necessitated to clear the record.

The Mineral Survey Plat should be noted as follows:

"Golden West No. 1, Gold Spot #1 and Goldspot #2 lodes, M.S. 4689, were canceled February 19, 2002, by memo 9605 (956) M.S. 4689, which is now a part of the original field notes."

February 19, 2002  
Date

  
\_\_\_\_\_  
Chief Cadastral Surveyor of Arizona



1