

Form 3400-11
(September 1967)
(formerly 4-683)

UNITED STATES
DEPARTMENT OF THE INTERIOR
BUREAU OF LAND MANAGEMENT

FIELD NOTES

Mineral Survey number	4742
State	Arizona
Land District	Arizona

Of the Survey of the Mining Claim of *(name and address of Claimant)*

Inspiration Consolidated Copper Company
c/o G. Henry Ladendorff, Attorney at Law
Suite 716 Arizona Bank Building
Phoenix, Arizona 85003


Known as the *(name of group, if any)*

Camelback

CONSISTING OF LOCATIONS NAMED AND LOCATED AS FOLLOWS

NAME OF LOCATION	DATE	
	LOCATED	AMENDED
Camelback 1	3/13/73	
Camelback 2	3/13/73	
Camelback 3	3/13/73	
Camelback 4	3/13/73	
Camelback 5	3/13/73	
Camelback 6	3/13/73	
Camelback 7	3/13/73	
Camelback 8	3/13/73	
Camelback 9	3/13/73	
Camelback 10	3/13/73	
Camelback 11	5/04/73	
Camelback 12	5/04/73	
Camelback 13	5/04/73	
Camelback 14	5/04/73	
Camelback 15	5/04/73	
Camelback 16	5/04/73	
Camelback 17	5/04/73	

Mining district Globe			County Gila	
Section (Uns.) 15 & 22	Township 1 North	Range 14 East	Meridian Gila and Salt River	Survey under order dated May 21, 1973
Survey commenced May 23, 1973		Survey completed May 30, 1973		Name of Mineral Surveyor Travis L. Gant



FEET

This survey was made with a W. & L. E. Gurley transit, No. 57289, equipped with horizontal limb $6\frac{1}{2}$ ins. diam., having two double opposite verniers, and a full vertical circle 5 ins. diam., having one double vernier; the horizontal verniers read to 30 secs. of arc; the vertical vernier reads to one minute of arc. This instrument was used for all-purpose taping and alignment procedures where great distances were not involved. Distances greater than 500 feet were measured with electronic distance measuring equipment, i.e., a Hewlett-Packard Model 3800 Distance Meter, Ser. No. 0987 A 00472, having a range of 10,000 feet and an absolute accuracy of 0.01 feet plus the distance measured divided by 100,000 in the normal operating temperature range. In all instances wherein the distance meter was used, vertical angles were measured with a Kern theodolite, Model DKM 2 AE, Ser. No. 145997, with automatic vertical indexing and microscopic angle-reading capabilities enabling the instrument man to read angles, either horizontal or vertical, to 1 sec. of arc. All three of these instruments were in good condition at the time of the survey and all adjustments were in good order.

All azimuths in this record were determined by the method of deflection angles referred to the meridian determined by the following observation:

May 23, 1973, at Cor. No. 1 of the Camelback 7 mill site in latitude $33^{\circ} 23' 00''$ N., and longitude $110^{\circ} 54' 46''$ W., (as determined by scaling from U.S.G.S. quadrangle INSPIRATION, dated 1945) I make a series of six altitude observations upon the sun for azimuth at approximately equal time intervals, three each with the theodolite telescope in direct and reversed positions, observing opposite limbs of the sun, and reading the horizontal angles from a reference point approximately 1600 feet southeasterly clockwise to the sun.

Mean time of observation, 105th
meridian, standard time 8:14:22 a.m.

Declination of sun at mean
time of observation = $20^{\circ} 37' 54''$ N.

Mean observed vertical angle
to sun's center, corrected for
refraction and parallax = $34^{\circ} 47' 20''$

Mean horizontal angle from
reference point to sun's center,
turned clockwise and to the
right to sun's center = $266^{\circ} 47' 07''$

True bearing to reference point
= S. $0^{\circ} 00' 11''$ W.

FEET

The lines were measured with either a Lufkin steel tape or with the aforementioned electronic distance meter. The tape was 500 feet in length, graduated every foot for 500 feet, with an added foot on the zero end graduated in tenths and hundredths; the tape was compared with a standard 100.00 foot tape at the time of the beginning of the survey and found to be correct. The distance meter was compared with a taped course, 1200 feet in length, measured as a base-line with a standard 100.00 foot tape, and found to be precise and accurate.

All lines and connections of this survey were run by direct methods.

The magnetic declination observed at each corner of the survey gave a uniform value of 13° 30' E.

Note concerning monumentation: With the exception of those corners which were monumented as otherwise described herein, I set iron posts at each corner of each mill site claim comprising this survey. Each iron post consists of a 3/4-inch nominal inside diam. galvanized water pipe having an exterior diam. of 1 inch; each pipe was placed in the ground in a foundation consisting of not less than 1/2 cu. ft. of high early strength portland cement concrete, mixed at the site. Brass caps were securely attached and marked as described, using 1/8-in. steel dies for stamping. Alongside every corner monument I erected a rock monument having a base two feet minimum diam., and a height of not less than two feet.

SURVEY NO. 4742

Camelback 1 Mill Site

At the true point for Cor. No. 1 of the Camelback 1 mill site, identical with Cors. Nos. 1 of the Camelback 17, Camelback 16, and Camelback 2 mill sites of this survey.

This corner falls in the bottom of an arroyo, course S. 70° E., where a permanent point cannot be established; witnessed SOUTH, 5.65 ft. dist., hereinafter described.

FEET	
	<p>From the true point for Cor. No. 1</p> <p>The cor. of secs. 15, 16, 21, and 22, T. 1 N., R. 14 E., G. & S.R.M., bears N. 79° 51' 01" W., 3974.83 ft. dist., an iron post, 2 ins. diam., 14 ins. above ground, firmly set, with brass cap marked as described in the official record.</p> <p>Thence S. 89° 57' 08" E.</p>
356	Road, bears N. 10° E. and S. 20° W.
659.50	<p>Cor. No. 2, identical with Cor. No. 2 of the Camelback 2 mill site of this survey, Cor. No. 4 Sur. No. 4606 Inspiration Mill Site No. 28, and Cor. No. 1 Sur. No. 4606 Inspiration Mill Site No. 18.</p> <p>To the surface of the 1½ ins. diam. copper-coated steel monument described in the official record of Sur. No. 4606, I add the following: CMS 1-2, and CMS 2-2-4742.</p> <p>Thence SOUTH</p>
221.65	Intersect line 3-4 Sur. No. 3924 Copper No. 8 lode at a point from which Cor. No. 3, identical with Cor. No. 3 Sur. No. 3924 Copper No. 9 lode, bears N. 83° 34' 11" W., 209.46 ft. dist.
310	Center of local drainage, 6 ft. wide, course S. 40° E.
330.00	<p>Cor. No. 3, identical with Cor. No. 4 Sur. No. 4606 Inspiration Mill Site No. 18.</p> <p>Set an iron post, 2 ft. long, 1 ins. diam., 15 ins. in the ground, with brass cap mkd. CMS 1-3-4742 and IMS 18-4-4606; from which</p> <p>Cors. Nos. 3 Sur. No. 3924 Copper No. 8 and Copper No. 9 lodes bear N. 57° 39' 20" W., 246.37 ft. dist.</p> <p>Thence N. 77° 56' 55" W.</p>
222.57	Intersect line 2-3 Sur. No. 3924 Copper No. 8 lode and line 3-4 Sur. No. 3924 Copper No. 9 lode at a point from which Cors. Nos. 3 bear N. 6° 21' 45" E., 85.87 ft. dist.
519	Road, bears N. 10° E. and S. 30° W.

FEET	
674.36	<p>Cor. No. 4, identical with Cor. No. 4 of the Camelback 17 mill site of this survey.</p> <p>Set an iron post, 2 ft. long, 1 ins. diam., 14 ins. in the ground, with brass cap mkd. CMS 1-4-4742 and CMS 17-4-4742.</p> <p style="text-align: center;">Thence NORTH</p>
41.55	<p>Intersect line 2-3 Sur. No. 3924 Copper No. 9 lode at a point from which Cor. No. 3, identical with Cor. No. 3 Sur. No. 3924 Copper No. 8 lode, bears S. 83° 36' 38" E., 454.18 ft. dist.</p>
184.10	<p>A point selected for witness Cor. No. 1, identical with witness Cors. Nos. 1 of the Camelback 17, Camelback 16, and Camelback 2 mill sites of this survey.</p> <p>Set an iron post, 2 ft. long, 1 ins. diam., 13 ins. in the ground, with brass cap mkd. WC - CMS 1-1, CMS 17-1, CMS 16-1, and CMS 2-1-4742.</p>
189.75	<p>Cor. No. 1, and place of beginning.</p>
Camelback 2 Mill Site	
<p>Beginning at the true point for Cor. No. 1 of the Camelback 2 mill site, identical with Cors. Nos. 1 of the Camelback 1, Camelback 17, and Camelback 16 mill sites of this survey, previously described, witnessed SOUTH, 5.65 ft. dist.</p>	
Thence S. 89° 57' 08" E.	
356	<p>Road, bears N. 10° E. and S. 20° W.</p>
659.50	<p>Cor. No. 2, identical with Cor. No. 4 Sur. No. 4606 Inspiration Mill Site No. 28, Cor. No. 1 Sur. No. 4606 Inspiration Mill Site No. 18, and Cor. No. 2 of the Camelback 1 mill site of this survey.</p> <p style="text-align: center;">Thence NORTH</p>
175	<p>Center of local drainage, 5 ft. wide, course N. 65° E.</p>
329.98	<p>Cor. No. 3, identical with Cor. No. 3 of the Camelback 3 mill site of this survey, Cor. No. 4 Sur. No. 4606 Inspiration Mill Site No. 29, and Cor. No. 1 Sur. No. 4606 Inspiration Mill Site No. 28.</p>

FEET	
	<p>To the surface of the 1½ ins. diam. copper-coated steel monument described in the official record of Sur. No. 4606, I add the following: CMS 2-3, and CMS 3-3-4742.</p> <p style="text-align: center;">Thence S. 89° 56' 37" W.</p>
240	Road, bears N. 40° E. and S. 40° W.
536	Center of local drainage, 5 ft. wide, course S. 65° E.
659.50	<p>Cor. No. 4, identical with Cors. Nos. 4 of the Camelback 16, Camelback 15, and Camelback 3 mill sites of this survey.</p> <p>Set an iron post, 2 ft. long, 1 ins. diam., 12 ins. in the ground, with brass cap mkd. CMS 2-4, CMS 16-4, CMS 15-4, and CMS 3-4-4742</p> <p style="text-align: center;">Thence SOUTH</p>
328.78	Cor. No. 1, and place of beginning.
	<p>Camelback 3 Mill Site</p> <p>At Cor. No. 1 of the Camelback 3 mill site, identical with Cors. Nos. 1 of the Camelback 15, Camelback 14, and Camelback 4 mill sites of this survey.</p> <p>Set an iron post, 2 ft. long, 1 ins. diam., 11 ins. in the ground, with brass cap mkd. CMS 3-1, CMS 15-1, CMS 14-1, and CMS 4-1-4742; from which</p> <p style="text-align: center;">The cor. of secs. 15, 16, 21, and 22 bears N. 89° 22' 43" W., 3912.86 ft. dist., previously described.</p> <p style="text-align: center;">Thence N. 89° 54' 47" E.</p>
452	Road, bears N. 10° E. and S. 10° W.
488	Center of local drainage, 4 ft. wide, course N. 70° E.
659.50	<p>Cor. No. 2, identical with Cor. No. 2 of the Camelback 4 mill site of this survey, and Cors. Nos. 1 Sur. No. 4606 Inspiration Mill Site No. 38 and Inspiration Mill Site No. 29.</p> <p>To the surface of the 1½ ins. diam. copper-coated steel monument described in the official record of Sur. No. 4606, I add the following: CMS 3-2, and CMS 4-2-4742.</p>

FEET	
	Thence SOUTH
329.58	Cor. No. 3, identical with Cor. No. 4 Sur. No. 4606 Inspiration Mill Site No. 29, Cor. No. 1 Sur. No. 4606 Inspiration Mill Site No. 28, and Cor. No. 3 of the Camelback 2 mill site of this survey.
	Thence S. 89° 56' 37" W.
240	Road, bears N. 40° E. and S. 40° W.
536	Center of local drainage, 5 ft. wide, course S. 65° E.
659.50	Cor. No. 4, identical with Cors. Nos. 4 of the Camelback 2, Camelback 16, and Camelback 15 mill sites of this survey.
	Thence NORTH
56	Center of local drainage, 4 ft. wide, course N. 75° E.
329.23	Cor. No. 1, and place of beginning.
	Camelback 4 Mill Site
	Beginning at Cor. No. 1 of the Camelback 4 mill site, identical with Cors. Nos. 1 of the Camelback 3, Camelback 15, and Camelback 14 mill sites of this survey.
	Thence N. 89° 54' 47" E.
452	Road, bears N. 10° E. and S. 10° W.
488	Center of local drainage, 4 ft. wide, course N. 70° E.
659.50	Cor. No. 2, identical with Cors. Nos. 1 Sur. No. 4606 Inspiration Mill Site No. 38 and Inspiration Mill Site No. 29, and Cor. No. 2 of the Camelback 3 mill site of this survey.
	Thence NORTH
70	Center of local drainage, 6 ft. wide, course East.
329.81	Cor. No. 3, identical with Cor. No. 3 of the Camelback 5 mill site of this survey, Cor. No. 1 Sur. No. 4606 Inspiration Mill Site No. 43, and Cor. No. 2 Sur. No. 4606 Inspiration Mill Site No. 38.

FEET	
	<p>Set an iron post, 2 ft. long, 1 ins. diam., 16 ins. in the ground, with brass cap mkd. CMS 4-3-4742 and CMS 5-3-4742, plus the following: IMS 43-1-4606 and IMS 38-2-4606.</p> <p style="text-align: center;">Thence S. 89° 56' 02" W.</p>
164	<p>Road, bears N. 20° E. and S. 20° W.</p>
659.50	<p>Cor. No. 4, identical with Cors. Nos. 4 of the Camelback 14, Camelback 13, and Camelback 5 mill sites of this survey.</p>
	<p>Set an iron post, 2 ft. long, 1 ins. diam., 18 ins. in the ground, with brass cap mkd. CMS 4-4, CMS 14-4, CMS 13-4, and CMS 5-4-4742.</p> <p style="text-align: center;">Thence SOUTH</p>
330.05	<p>Cor. No. 1, and place of beginning.</p>
	<p>Camelback 5 Mill Site</p>
	<p>At Cor. No. 1 of the Camelback 5 mill site, identical with Cors. Nos. 1 of the Camelback 13, Camelback 12, and Camelback 6 mill sites of this survey.</p>
	<p>Set an iron post, 2 ft. long, 1 ins. diam., 14 ins. in the ground, with brass cap mkd. CMS 5-1, CMS 13-1, CMS 12-1, and CMS 6-1-4742; from which</p>
	<p style="text-align: center;">The cor. of secs. 15, 16, 21, and 22 bears S. 81° 02' 16" W., 3960.98 ft. dist., previously described.</p> <p style="text-align: center;">Thence N. 89° 54' 07" E.</p>
518	<p>Road, bears N. 20° E. and S. 20° W.</p>
659.50	<p>Cor. No. 2, identical with Cor. No. 2 of the Camelback 6 mill site of this survey, and Cor. No. 4 of the Camelback 7 mill site of this survey, and Cor. No. 2 Sur. No. 4606 Inspiration Mill Site No. 43.</p>
	<p>To the surface of the 1½ ins. diam. copper-coated steel monument described in the official record of Sur. No. 4606, I add the following: CMS 5-2, CMS 6-2, and CMS 7-4-4742.</p> <p style="text-align: center;">Thence SOUTH</p>

FEET	
177	Center of local drainage, 4 ft. wide, course East.
329.81	Cor. No. 3, identical with Cor. No. 1 Sur. No. 4606 Inspiration Mill Site No. 43, Cor. No. 2 Sur. No. 4606 Inspiration Mill Site No. 38, and Cor. No. 3 of the Camelback 4 mill site of this survey. Thence S. 89° 56' 02" W.
164	Road, bears N. 20° E. and S. 20° W.
659.50	Cor. No. 4, identical with Cors. Nos. 4 of the Camelback 4, Camelback 14, and Camelback 13 mill sites of this survey. Thence NORTH
329.44	Cor. No. 1, and place of beginning.
Camelback 6 Mill Site	
	Beginning at Cor. No. 1 of the Camelback 6 mill site, identical with Cors. Nos. 1 of the Camelback 5, Camelback 13, and Camelback 12 mill sites of this survey. Thence N. 89° 54' 07" E.
518	Road, bears N. 20° E. and S. 20° W.
659.50	Cor. No. 2, identical with Cor. No. 4 of the Camelback 7 mill site of this survey, Cor. No. 2 Sur. No. 4606 Inspiration Mill Site No. 43, and Cor. No. 2 of the Camelback 5 mill site of this survey. Thence NORTH
329.83	Cor. No. 3, identical with Cor. No. 3 of the Camelback 9 mill site and Cors. Nos. 1 of the Camelback 8 and Camelback 7 mill sites of this survey. Set an iron post, 2 ft. long, 1 ins. diam., 12 ins. in the ground, with brass cap mkd. CMS 6-3, CMS 9-3, CMS 8-1, and CMS 7-1-4742. Thence S. 89° 52' 33" W.
133	Road, bears N. 55° W. and S. 55° E.
659.50	Cor. No. 4, identical with Cors. Nos. 4 of the Camelback 12, Camelback 11, and Camelback 9 mill sites of this survey.

FEET	
329.53	<p>Set an iron post, 2 ft. long, 1 ins. diam., 11 ins. in the ground, with brass cap mkd. CMS 6-4, CMS 12-4, CMS 11-4, and CMS 9-4-4742.</p> <p style="text-align: center;">Thence SOUTH</p> <p>Cor. No. 1, and place of beginning.</p>
660.14	<p style="text-align: center;">Camelback 7 Mill Site</p> <p>Beginning at Cor. No. 1 of the Camelback 7 mill site, identical with Cors. Nos. 3 of the Camelback 6 and Camelback 9 mill sites, and Cor. No. 1 of the Camelback 8 mill site of this survey; from which</p> <p style="padding-left: 40px;">The cor. of secs. 15, 16, 21, and 22 bears S. 78° 17' 09" W., 4669.37 ft. dist., previously described.</p> <p style="text-align: center;">Thence S. 89° 23' 02" E.</p> <p>Cor. No. 2, identical with Cor. No. 2 of the Camelback 8 mill site of this survey, Cor. No. 4 Sur. No. 4606 Inspiration Mill Site No. 52, and Cor. No. 2 Sur. No. 4606 Inspiration Mill Site No. 48.</p> <p>To the surface of the 1½ ins. diam. copper-coated steel monument described in the official record of Sur. No. 4606, I add the following: CMS 7-2 and CMS 8-2-4742.</p> <p style="text-align: center;">Thence S. 0° 05' 30" W.</p>
330.31	<p>Cor. No. 3, identical with Cors. Nos. 1 Sur. No. 4606 Inspiration Mill Site No. 48 and Inspiration Mill Site No. 44, and Cor. No. 3 Sur. No. 4606 Inspiration Mill Site No. 43.</p> <p>To the surface of the 1½ ins. diam. copper-coated steel monument described in the official record of Sur. No. 4606, I add the following: CMS 7-3-4742.</p> <p style="text-align: center;">Thence N. 89° 20' 30" W.</p>
659.62	<p>Cor. No. 4, identical with Cor. No. 2 Sur. No. 4606 Inspiration Mill Site No. 43, and Cors. Nos. 2 of the Camelback 5 and Camelback 6 mill sites of this survey.</p> <p style="text-align: center;">Thence NORTH</p>
329.83	<p>Cor. No. 1, and place of beginning.</p>

FEET		
	Camelback 8 Mill Site	
	Beginning at Cor. No. 1 of the Camelback 8 mill site, identical with Cor. No. 1 of the Camelback 7 mill site and Cors. Nos. 3 of the Camelback 6 and Camelback 9 mill sites of this survey.	
	Thence S. 89° 23' 02" E.	
660.14	Cor. No. 2, identical with Cor. No. 4 Sur. No. 4606 Inspiration Mill Site No. 52, Cor. No. 2 Sur. No. 4606 Inspiration Mill Site No. 48, and Cor. No. 2 of the Camelback 7 mill site of this survey.	
	Thence N. 0° 04' 38" W.	
330.06	Cor. No. 3, identical with Cor. No. 4 Sur. No. 4606 Inspiration Mill Site No. 55, and Cors. Nos. 1 Sur. No. 4606 Inspiration Mill Site No. 56 and Inspiration Mill Site No. 52.	
	To the surface of the 1½ ins. diam. copper-coated steel monument described in the official record of Sur. No. 4606, I add the following: CMS 8-3-4742.	
	Thence N. 89° 31' 33" W.	
304	Center of local drainage, 8 ft. wide, course N. 30° E.	
659.81	Cor. No. 4, identical with Cors. Nos. 2 of the Camelback 9 and Camelback 10 mill sites of this survey and Cor. No. 1 Sur. No. 4606 Inspiration Mill Site No. 55.	
	To the surface of the 1½ ins. diam. copper-coated steel monument described in the official record of Sur. No. 4606, I add the following: CMS 8-4, CMS 9-2, and CMS 10-2-4742.	
	Thence S. 0° 01' 15" E.	
91	Center of local drainage, 4 ft. wide, course East.	
328.42	Cor. No. 1, and place of beginning.	

FEET	
	<p>Camelback 9 Mill Site</p> <p>At Cor. No. 1 of the Camelback 9 mill site, identical with Cors. Nos. 1 of the Camelback 11 and Camelback 10 mill sites of this survey.</p> <p>Set an iron post, 2 ft. long, 1 ins. diam., 16 ins. in the ground, with brass cap mkd. CMS 9-1, CMS 11-1, and CMS 10-1-4742; from which</p> <p style="padding-left: 40px;">The cor. of secs. 15, 16, 21, and 22 bears S. 71° 56' 01" W., 4115.53 ft. dist., previously described.</p> <p style="padding-left: 40px;">Thence N. 89° 59' 20" E.</p>
274	Road, bears N. 30° E. and S. 45° W.
659.38	<p>Cor. No. 2, identical with Cor. No. 2 of the Camelback 10 mill site of this survey, Cor. No. 1 Sur. No. 4606 Inspiration Mill Site No. 55, and Cor. No. 4 of the Camelback 8 mill site of this survey.</p> <p style="padding-left: 40px;">Thence S. 0° 01' 15" E.</p>
91	Center of local drainage, 4 ft. wide, course East.
328.42	<p>Cor. No. 3, identical with Cors. Nos. 1 of the Camelback 8 and Camelback 7 mill sites, and Cor. No. 3 of the Camelback 6 mill site of this survey.</p> <p style="padding-left: 40px;">Thence S. 89° 52' 33" W.</p>
133	Road, bears N. 55° W. and S. 55° E.
659.50	<p>Cor. No. 4, identical with Cors. Nos. 4 of the Camelback 6, Camelback 12, and Camelback 11 mill sites of this survey.</p> <p style="padding-left: 40px;">Thence NORTH</p>
329.72	Cor. No. 1, and place of beginning.
	<p>Camelback 10 Mill Site</p> <p>Beginning at Cor. No. 1 of the Camelback 10 mill site, identical with Cors. Nos. 1 of the Camelback 9 and Camelback 11 mill sites of this survey.</p> <p style="padding-left: 40px;">Thence N. 89° 59' 20" E.</p>

FEET	
274	Road, bears N. 30° E. and S. 45° W.
659.38	<p>Cor. No. 2, identical with Cor. No. 1 Sur. No. 4606 Inspiration Mill Site No. 55, Cor. No. 4 of the Camelback 8 mill site, and Cor. No. 2 of the Camelback 9 mill site of this survey.</p> <p>Thence N. 0° 03' 20" W.</p>
330.01	<p>Cor. No. 3, identical with Cor. No. 4 Sur. No. 4606 Inspiration Mill Site No. 59 and Cor. No. 2 Sur. No. 4606 Inspiration Mill Site No. 55.</p> <p>To the surface of the 1½ ins. diam. copper-coated steel monument described in the official record of Sur. No. 4606, I add the following: CMS 10-3-4742.</p> <p>Thence S. 89° 58' 15" W.</p>
596	Road, bears N. 5° E. and S. 15° W.
659.06	<p>Cor. No. 4.</p> <p>Set an iron post, 2 ft. long, 1 ins. diam., 13 ins. in the ground, with brass cap mkd. CMS 10-4-4742.</p> <p>Thence SOUTH</p>
329.80	Cor. No. 1, and place of beginning.
	<p style="text-align: center;">Camelback 11 Mill Site</p> <p>Beginning at Cor. No. 1 of the Camelback 11 mill site, identical with Cors. Nos. 1 of the Camelback 10 and Camelback 9 mill sites of this survey.</p> <p>Thence N. 89° 44' 53" W.</p>
659.51	<p>Cor. No. 2.</p> <p>Set an iron post, 2 ft. long, 1 ins. diam., 17 ins. in the ground, with brass cap mkd. CMS 11-2-4742.</p> <p>Thence SOUTH</p>
329.75	<p>Cor. No. 3, identical with Cor. No. 3 of the Camelback 12 mill site of this survey.</p> <p>Set an iron post, 2 ft. long, 1 ins. diam., 18 ins. in the ground, with brass cap mkd. CMS 11-3-4742 and CMS 12-3-4742.</p>

FEET		
	Thence S. 89° 45' 02" E.	
659.51	Cor. No. 4, identical with Cors. Nos. 4 of the Camelback 9, Camelback 6, and Camelback 12 mill sites of this survey.	
	Thence NORTH	
329.72	Cor. No. 1, and place of beginning.	
Camelback 12 Mill Site		
Beginning at Cor. No. 1 of the Camelback 12 mill site, identical with Cors. Nos. 1 of the Camelback 6, Camelback 5, and Camelback 13 mill sites of this survey.		
	Thence N. 89° 44' 44" W.	
659.51	Cor. No. 2, identical with Cor. No. 2 of the Camelback 13 mill site of this survey.	
Set a brass tablet, 2 ins. diam., with stem 2½ ins. long, grouted into ledge rock, with disc surface mkd. CMS 12-2-4742 and CMS 13-2-4742.		
	Thence NORTH	
329.47	Cor. No. 3, identical with Cor. No. 3 of the Camelback 11 mill site of this survey.	
	Thence S. 89° 45' 02" E.	
659.51	Cor. No. 4, identical with Cors. Nos. 4 of the Camelback 11, Camelback 9, and Camelback 6 mill sites of this survey.	
	Thence SOUTH	
329.53	Cor. No. 1, and place of beginning.	
Camelback 13 Mill Site		
Beginning at Cor. No. 1 of the Camelback 13 mill site, identical with Cors. Nos. 1 of the Camelback 12, Camelback 6, and Camelback 5 mill sites of this survey.		
	Thence N. 89° 44' 44" W.	
659.51	Cor. No. 2, identical with Cor. No. 2 of the Camelback 12 mill site of this survey.	

FEET	
	Thence SOUTH
330.02	Cor. No. 3, identical with Cor. No. 3 of the Camelback 14 mill site of this survey.
	Set an iron post, 2 ft. long, 1 ins. diam., 15 ins. in the ground, with brass cap mkd. CMS 13-3-4742 and CMS 14-3-4742.
	Thence S. 89° 47' 45" E.
659.50	Cor. No. 4, identical with Cors. Nos. 4 of the Camelback 5, Camelback 4, and Camelback 14 mill sites of this survey.
	Thence NORTH
329.44	Cor. No. 1, and place of beginning.
	Camelback 14 Mill Site
	Beginning at Cor. No. 1 of the Camelback 14 mill site, identical with Cors. Nos. 1 of the Camelback 4, Camelback 3, and Camelback 15 mill sites of this survey.
	Thence N. 89° 44' 53" W.
659.51	Cor. No. 2, identical with Cor. No. 2 of the Camelback 15 mill site of this survey.
	Set an iron post, 2 ft. long, 1 ins. diam., 16 ins. in the ground, with brass cap mkd. CMS 14-2-4742 and CMS 15-2-4742.
	Thence NORTH
329.50	Cor. No. 3, identical with Cor. No. 3 of the Camelback 13 mill site of this survey.
	Thence S. 89° 47' 45" E.
659.50	Cor. No. 4, identical with Cors. Nos. 4 of the Camelback 13, Camelback 5, and Camelback 4 mill sites of this survey.
	Thence SOUTH
330.05	Cor. No. 1, and place of beginning.

FEET	
	<p>Camelback 15 Mill Site</p> <p>Beginning at Cor. No. 1 of the Camelback 15 mill site, identical with Cors. Nos. 1 of the Camelback 14, Camelback 4, and Camelback 3 mill sites of this survey.</p> <p style="text-align: center;">Thence N. 89° 44' 53" W.</p>
659.51	<p>Cor. No. 2, identical with Cor. No. 2 of the Camelback 14 mill site of this survey.</p> <p style="text-align: center;">Thence SOUTH</p>
329.66	<p>Cor. No. 3, identical with Cor. No. 3 of the Camelback 16 mill site of this survey.</p> <p>Set an iron post, 2 ft. long, 1 ins. diam., 15 ins. in the ground, with brass cap mkd. CMS 15-3-4742 and CMS 16-3-4742.</p> <p style="text-align: center;">Thence S. 89° 47' 07" E.</p>
659.50	<p>Cor. No. 4, identical with Cors. Nos. 4 of the Camelback 3, Camelback 2, and Camelback 16 mill sites of this survey.</p> <p style="text-align: center;">Thence NORTH</p>
56	<p>Center of local drainage, 4 ft. wide, course N. 75° E.</p>
329.23	<p>Cor. No. 1, and place of beginning.</p>
	<p>Camelback 16 Mill Site</p> <p>Beginning at the true point for Cor. No. 1 of the Camelback 16 mill site, identical with Cors. Nos. 1 of the Camelback 2, Camelback 1, and Camelback 17 mill sites of this survey, previously described, witnessed SOUTH, 5.65 ft. dist.</p> <p style="text-align: center;">Thence N. 89° 50' 50" W.</p>
659.50	<p>Cor. No. 2, identical with Cor. No. 2 of the Camelback 17 mill site of this survey.</p> <p>Set an iron post, 2 ft. long, 1 ins. diam., 14 ins. in the ground, with brass cap mkd. CMS 16-2-4742 and CMS 17-2-4742.</p> <p style="text-align: center;">Thence NORTH</p>
329.49	<p>Cor. No. 3, identical with Cor. No. 3 of the Camelback 15 mill site of this survey.</p>

FEET	
659.50	<p>Thence S. 89° 47' 07" E.</p> <p>Cor. No. 4, identical with Cors. Nos. 4 of the Camelback 15, Camelback 3, and Camelback 2 mill sites of this survey.</p>
328.78	<p>Thence SOUTH</p> <p>Cor. No. 1, and place of beginning.</p>
659.50	<p>Camelback 17 Mill Site</p> <p>Beginning at the true point for Cor. No. 1 of the Camelback 17 mill site, identical with Cors. Nos. 1 of the Camelback 16, Camelback 2, and Camelback 1 mill sites of this survey, previously described, witnessed SOUTH, 5.65 ft. dist.</p> <p>Thence N. 89° 50' 50" W.</p> <p>Cor. No. 2, identical with Cor. No. 2 of the Camelback 16 mill site of this survey.</p>
76.10	<p>Thence SOUTH</p> <p>Intersect line 2-3 Sur. No. 3924 Copper No. 9 lode at a point from which Cor. No. 2 bears N. 83° 36' 38" W., 383.83 ft. dist.</p>
120.55	<p>Cor. No. 3.</p> <p>Set an iron post, 2 ft. long, 1 ins. diam., 11 ins. in the ground, with brass cap mkd. CMS 17-3-4742; from which</p> <p>Cor. No. 2 Sur. No. 3924 Copper No. 9 lode bears N. 77° 07' 45" W., 391.28 ft. dist.</p>
663.31	<p>Thence S. 83° 51' 32" E.</p> <p>Cor. No. 4, identical with Cor. No. 4 of the Camelback 1 mill site of this survey.</p>
41.55	<p>Thence NORTH</p> <p>Intersect line 2-3 Sur. No. 3924 Copper No. 9 lode at a point from which Cor. No. 2 bears N. 83° 36' 38" W., 1047.45 ft. dist.</p>
184.10	<p>Witness Cor. No. 1, previously described.</p>
189.75	<p>Cor. No. 1, and place of beginning.</p>

FEET	AREAS	Acres
	Total area, Camelback 1 mill site	3.935
	Area in conflict with--	
	Sur. No. 3924 Copper No. 8 lode	0.477
	Sur. No. 3924 Copper No. 9 lode	0.658
	Total area, Camelback 2 mill site	4.987
	Total area, Camelback 3 mill site	4.987
	Total area, Camelback 4 mill site	4.995
	Total area, Camelback 5 mill site	4.991
	Total area, Camelback 6 mill site	4.991
	Total area, Camelback 7 mill site	5.000
	Total area, Camelback 8 mill site	4.988
	Total area, Camelback 9 mill site	4.982
	Total area, Camelback 10 mill site	4.993
	Total area, Camelback 11 mill site	4.992
	Total area, Camelback 12 mill site	4.989
	Total area, Camelback 13 mill site	4.992
	Total area, Camelback 14 mill site	4.993
	Total area, Camelback 15 mill site	4.988
	Total area, Camelback 16 mill site	4.983
	Total area, Camelback 17 mill site	2.349
	Area in conflict with--	
	Sur. No. 3924 Copper No. 9 lode	0.651
	LOCATION	
	This survey is located in Uns. secs. 15 and 22, T. 1 N., R. 14 E., of the Gila and Salt River Meridian, Gila County, Arizona.	
	The survey of the seventeen (17) mill site claims embraced in this order for mineral survey and described herein is identical with the respective locations as marked on the ground.	
	OTHER CORNER DESCRIPTIONS AND SUPPLEMENTAL DATA	
	Sur. No. 3924 Copper No. 8 lode: Cors. Nos. 2, 3, and 4 are iron posts, 3/4 ins. diam., with brass caps, 2 ins. diam., firmly set and properly marked. Line 2-3 was found to be N. 6° 21' 45" E., 600.20 ft., instead of N. 6° 26' E., 600 ft., as approved; line 3-4 was found to be S. 83° 34' 11" E., 1287.23 ft., instead of S. 83° 34' E., 1285.33 ft., as approved.	
	Sur. No. 3924 Copper No. 9 lode: Cors. 2, 3, and 4 are iron posts, 3/4 ins. diam., with brass caps, 2 ins. diam., firmly set and properly marked. Line 2-3 was found to be S. 83° 36' 38" E., 1501.63 ft., instead of S. 83° 34' E., 1500 ft., as approved; line 3-4 was found to be S. 6° 21' 45" W., 600.20 ft., instead of S. 6° 26' W., 600 ft. as approved.	

FEET

Note concerning all monuments found of the Sur. No. 4606 Inspiration Mill Site Group: All corners found were copper-jacket steel pins of the type commonly known as "Copper-Weld", having a flared top surface or disc, 1½ ins. diam., set flush with the ground. Since accessory rock mounds were missing in all cases, I caused to have erected rock mounds of sufficient size to aid in recovering these monuments in the future.

Sur. No. 4606 Inspiration Mill Site No. 18: Cor. No. 1 was found to be a monument of the type discussed above, firmly set and properly marked. Cor. No. 4 could not be found, so it was restored at approved distance and bearing from Cor. No. 1. The bearings of lines 1-2 and 3-4 are shown as approved. From Cor. No. 1 the cor. of secs. 15, 16, 21, and 22 bears N. 81° 17' 00" W., 4625.55 ft. dist., instead of N. 81° 19' 20" W., 4633.69 ft. dist., as approved.

Sur. No. 4606 Inspiration Mill Site No. 28: Cor. No. 1 was found firmly set and properly marked. Cor. No. 4 is identical with Cor. No. 1 Sur. No. 4606 Inspiration Mill Site No. 18, described above. Line 4-1 was found to be NORTH, 329.98 feet, instead of NORTH, 330 ft., as approved. The bearings of lines 1-2 and 3-4 are shown as approved. From Cor. No. 1 the cor. of secs. 15, 16, 21, and 22 bears N. 85° 21' 39" W., 4587.15 ft. dist., instead of N. 85° 23' 40" W., 4595.49 ft. dist., as approved.

Sur. No. 4606 Inspiration Mill Site No. 29: Cors. Nos. 1 and 4 were found firmly set and properly marked. Line 4-1 was found to be NORTH, 329.58 ft., instead of NORTH, 330 ft., as approved. The bearings of lines 1-2 and 3-4 are shown as approved. From Cor. No. 1 the cor. of secs. 15, 16, 21, and 22 bears N. 89° 28' 51" W., 4572.31 ft. dist., instead of N. 89° 30' 40" W., 4580.82 ft. dist., as approved.

Sur. No. 4606 Inspiration Mill Site No. 38: Cor. No. 1 is identical with Cor. No. 1 Sur. No. 4606 Inspiration Mill Site No. 29 described above; Cor. No. 2 was restored at the mid-point of the line connecting Cor. No. 1 with Cor. No. 2 Sur. No. 4606 Inspiration Mill Site No. 43. Line 1-2 was found to be NORTH, 329.81 ft., instead of NORTH, 330 ft., as approved. The bearings of lines 3-4 and 4-1 are shown as approved. Line 2-3 was found to be S. 89° 18' E., 660.88 ft., instead of S. 89° 28' E., 660 ft., as approved.

FEET

Sur. No. 4606 Inspiration Mill Site No. 43:
Cors. Nos. 2, 3, and 4 are firmly set and properly marked; Cor. No. 1 is identical with Cor. No. 2. Sur. No. 4606 Inspiration Mill Site No. 29 and was restored as described above. Line 1-2 was found to be NORTH, 329.81 ft., instead of NORTH, 330 ft., as approved; line 2-3 was found to be S. 89° 20' 30" E., 659.62 ft., instead of S. 89° 28' E., 660 ft.; line 3-4 was found to be S. 0° 13' E., 330.31 ft., instead of SOUTH, 330 ft., as approved; line 4-1 was found to be N. 89° 18' W., 660.88 ft., instead of N. 89° 28' W., 660.00 ft., as approved. From Cor. No. 1 the cor. of secs. 15, 16, 21, and 22 bears S. 86° 23' 28" W., 4581.21 ft., instead of S. 86° 22' W., 4589.88 ft., as approved.

Sur. No. 4606 Inspiration Mill Site No. 44:
Cors. Nos. 1 and 4 are firmly set and properly marked. Line 4-1 was found to be N. 0° 13' W., 330.31 ft., instead of NORTH, 330 ft., as approved; the bearing of line 1-2 is shown as approved. From Cor. No. 1 the cor. of secs. 15, 16, 21, and 22 bears S. 83° 20' 35" W., 5267.22 ft. dist., instead of S. 83° 18' 30" W., 5276.58 ft. dist., as approved.

Sur. No. 4606 Inspiration Mill Site No. 48:
Cor. No. 1 is identical with Cor. No. 1 Sur. No. 4606 Inspiration Mill Site No. 44 described above; Cor. No. 2 is firmly set and properly marked. Line 1-2 was found to be N. 0° 05' 30" E., 330.31 ft., instead of NORTH, 330 ft., as approved; the bearings of lines 2-3 and 4-1 are shown as approved.

Sur. No. 4606 Inspiration Mill Site No. 52:
Cors. Nos. 1 and 4 are firmly set and properly marked. Line 4-1 was found to be N. 0° 04' 38" W., 330.06 ft., instead of NORTH, 330 ft., as approved; the bearings of lines 1-2 and 3-4 are shown as approved. From Cor. No. 1 the cor. of secs. 15, 16, 21, and 22 bears S. 76° 20' 44" W., 5383.96 ft. dist., instead of S. 76° 19' 40" W., 5393.46 ft. dist., as approved.

Sur. No. 4606 Inspiration Mill Site No. 55:
All four cors. are firmly set and properly marked. Line 1-2 was found to be N. 0° 03' 20" W., 330.01 ft., instead of NORTH, 330 ft., as approved; line 2-3 was found to be S. 89° 31' 10" E., 659.75 ft., instead of S. 89° 28' E., 660 ft., as approved; line 3-4 was found to be S. 0° 03' 54" E., 329.94 ft., instead of SOUTH, 330 ft., as approved; line 4-1 was found to be N. 89° 31' 33" W., 659.81 ft., instead of N. 89° 42' W., 660 ft., as approved.

FEET

From Cor. No. 1 the cor. of secs. 15, 16, 21, and 22 bears S. $74^{\circ} 24' 04''$ W., 4746.84 ft. dist., instead of S. $74^{\circ} 22' 30''$ W., 4756.42 ft. dist., as approved.

Sur. No. 4606 Inspiration Mill Site No. 56: Cor. No. 1 is identical with Cor. No. 1 Sur. No. 4606 Inspiration Mill Site No. 52, described above; Cor. No. 2 is firmly set and properly marked. Line 1-2 was found to be N. $0^{\circ} 03' 54''$ W., 329.94 ft., instead of NORTH 330 ft., as approved; the bearing of line 4-1 is shown as approved.

Sur. No. 4606 Inspiration Mill Site No. 59: Cors. Nos. 1, 3, and 4 are firmly set and properly marked. Line 3-4 was found to be N. $89^{\circ} 31' 10''$ W., 659.75 ft., instead of N. $89^{\circ} 32' 32''$ W., 660 ft., as approved; line 4-1 was found to be N. $0^{\circ} 03' 20''$ W., 330.05 ft., instead of NORTH, 330 ft., as approved. From Cor. No. 1 the cor. of secs. 15, 16, 21, and 22 bears S. $67^{\circ} 02' 31''$ W., 4964.61 ft. dist., instead of S. $67^{\circ} 02' 10''$ W., 4974.91 ft. dist., as approved.

Two recently set B.L.M. brass-capped pipes were found, apparently a part of the governmental subdivision of T. 1 N., R. 14 E., G. & S.R.M. I find that the line between the cor. of secs. 15, 16, 21, and 22 and the newly-established closing cor. of secs. 15 and 22 upon the west boundary of sec. 23 bears S. $89^{\circ} 56' 32''$ E., 5267.77 ft. dist.; also that the line connecting said closing cor. monument with the cor. of secs. 14 and 23 bears N. $1^{\circ} 11'$ E., 27.16 ft. dist.

FIELD ASSISTANTS

<u>Name</u>	<u>Capacity</u>
Loren E. Bunney	Instrumentman
Edward E. Zaragoza	Assistant
Thomas E. Smith	Assistant

UNITED STATES
DEPARTMENT OF THE INTERIOR
BUREAU OF LAND MANAGEMENT

CERTIFICATE OF SURVEYOR

Name of Mineral Surveyor	Date
Travis L. Gant	May 31, 1973

I HEREBY CERTIFY That in pursuance of an order received from the U. S. Dept. of Interior, Bureau of Land Management, at Phoenix, Arizona, dated May 21, 1973, I have carefully executed the survey of the claim of Inspiration Consolidated Copper Company, known as the (lode, placer, or mill site) Camelback 1 - 17 mill sites, situated in Uns. Secs. 15 & 22, Township 1 North Range 14 East, Gila & Salt River Meridian, in the State of Arizona.

This survey, designated as number 4742, has been executed by me and under my direction and has been made in strict conformity with said order, the Manual of Instructions for the Survey of Public Lands of the United States, and in specific manner described in the foregoing field notes.

I FURTHER CERTIFY That the labor expended and improvements made upon and for the benefit of the (lode or placer) location(s) embraced in the said mining claim by claimant(s) or its grantors are fully stated in my report. The character, extent, location, and itemized value are specified in full detail. No portion of, or interest in, said labor and improvements so credited to this claim has been included in the estimate of expenditures upon any other claim.

Globe, Arizona (Location)	<i>Travis L. Gant</i> (Signature of Mineral Surveyor)
------------------------------	--

CERTIFICATE OF APPROVAL

Office	Arizona State Office
Location	Phoenix, Arizona
Date	January 16, 1974

The foregoing field notes of mineral survey number 4742, in Sections 15 & 22, Range 14 E., Gila and Salt River Meridian, in the State of Arizona, surveyed unsurveyed Township 1 N., executed by Travis L. Gant, Mineral Surveyor, under order dated May 21, 1973, having been critically examined and the necessary corrections made prior to their certification by the surveyor, the field notes and the survey therein described are hereby approved.

<i>Joe T. Fullin</i> Joe T. Fullin (Signature)	State Director (Title)
---	---------------------------

CERTIFICATE OF TRANSCRIPT

I HEREBY CERTIFY That the foregoing transcript of field notes of the above-described mineral survey number is a true copy of the original field notes.

(Authorized Signature)	(Title)
------------------------	---------

Title 18, U.S.C. section 1001, makes it a crime for any person knowingly and willfully to make to any department or agency of the United States any false, fictitious, or fraudulent statements or representations as to any matter within its jurisdiction.

