

Form 3400-11
(September 1967)
(formerly 4-683)

UNITED STATES
DEPARTMENT OF THE INTERIOR
BUREAU OF LAND MANAGEMENT

Mineral Survey number
4763 Amended

State
Arizona
Land District

FIELD NOTES

Of the Survey of the Mining Claim of *(name and address of Claimant)*

Phelps Dodge Corp.
c/o Evans, Kitchel & Jenckes
363 N. 1st Ave.
Phoenix, Arizona 85003

Known as the *(name of group, if any)*

CONSISTING OF LOCATIONS NAMED AND LOCATED AS FOLLOWS

| NAME OF LOCATION | DATE | |
|------------------|----------|---------|
| | LOCATED | AMENDED |
| Victoria No. 5-A | 9/14/73 | |
| VIH No. 69 | 11/21/60 | |
| VIH No. 70 | 12/10/70 | |
| VIH No. 71 | 6/21/73 | |

| | | | | |
|---------------------------------|----------------------|------------------|--|--|
| Mining district Copper Basin | | | County Yavapai | |
| Section 16 & 21 | Township 13 North | Range 3 West | Meridian Gila & Salt River | Survey under order dated May 26, 1976 |
| Survey commenced | | Survey completed | Name of Mineral Surveyor Robert Lenon | |

| FEET | | |
|------|--|--|
| | <p>This survey was made with a Lietz Precise Transit No. 65718, with horizontal limb 5½ ins. diam., having two double opposite verniers reading to 20 seconds of arc, and full vertical circle, 4½ ins. diam., having one double vernier reading to 1 minute of arc. The eyepiece has a removable colored glass for making direct observations upon the sun. The instrument was in good condition at the time of the survey and all adjustments were in good order.</p> <p>All azimuths in this record were referred to the meridian of the Phelps Dodge Copper Basin Project triangulation-system, set out on a local plane grid, with its origin the latitude and departure of U.S. Mineral Monument No. 1 as: 5,000.00; 5000.00 feet, as checked by observations made by me for Mineral Survey No. 4756 on October 21, 1973.</p> <p>The lines were measured with a Hewlett-Packard distance-meter, and a Chicago steel tape, 300 feet in length, graduated every foot, with the end feet graduated to tenths; which was compared with a Lufkin standard at the time of beginning the survey and found correct.</p> <p>All lines and connections of this survey were run by direct methods.</p> <p>The magnetic declination observed at each corner of the survey gave a uniform value of 14°00' E.</p> <p>In accordance with Amended Order dated May 26, 1976, I was directed to amend Mineral Survey No. 4763 so as to reflect its relationship with the position of M.S. No. 490 Snow Bird lode, M.S. No. 513 Bronze Statue lode, and M.S. No. 514 Head Center lode.</p> <p>This amendment was necessitated by the need for compliance with the verdict in the case in the Superior Court of Yavapai County: <u>White v. Phelps Dodge Corporation</u>, No. 29787, which held that the positions for the aforesaid three patented lode claims were at variance with their locations as set forth on the Plat of T. 13 N., R. 3 W., executed in 1934 by the BLM.</p> <p>As a result of the court decision, the Field Notes of M.S. No. 4763 are amended as follows:</p> | |
| | Mineral Survey No. 4763 Am. | |
| | <p style="text-align: center;">VIH No. 69 Lode</p> <p>At Cor. No. 1 of the VIH No. 69 lode, on line 1-2, M.S. No. 4488 Victoria No. 3 lode at a point from which Cor. No. 1 bears N. 81°39' W., 973.42 ft. dist.</p> <p>Set an iron pin, 5/8 in. diam., 24 ins. long, 18 ins. in the ground, stone mound alongside, with aluminum cap mkd. X-VIH69-1-4763AM, from which</p> | |

| FEET | | |
|---------|--|--|
| | <p>The cor. of secs. 16, 17, 20 and 21 bears S. 66°03'20" W., 393.36 ft. dist.</p> <p>Cors. No. 6, M.S. No. 490 Snow Bird lode, and M.S. No. 513 Bronze Statue lode, bears S. 86°00'30" E., 251.15 ft. dist.</p> <p>Thence N. 8°21' E.</p> | |
| 100.00 | Lode line; discovery point bears S. 81°39' E., 58 ft. dist. | |
| 141.54 | Intersect line 5-6, M.S. No. 490 Snow Bird lode, at a point from which Cor. No. 6 bears S. 55°35' 35" E., 278.76 ft. dist. | |
| 250. | Gulch, 10 ft. wide, course S. 70° E. | |
| 290.00 | <p>Cor. No. 2, identical with Cor. No. 1 of the VIH No. 70 lode.</p> <p>Set an iron pin, 5/8 in. diam., 24 ins. long, 18 ins. in the ground, stone mound alongside, with aluminum cap mkd. X-VIH69-2-VIH70-1-4763AM.</p> <p>Thence S. 81°39' E.</p> | |
| 90. | Gulch, 5 ft. wide, course S. 70° W. | |
| 175. | Road, 12 ft. wide, bears N. 25° E. and S. 25° W. | |
| 340.37 | Intersect line 6-1, M.S. No. 490 Snow Bird lode, identical with line 6-1, M.S. No. 513 Bronze Statue lode at a point from which Cors. Nos. 6 bears S. 26°43'05" W., 285.45 ft. dist. | |
| 405. | Copper Basin Wash, 15 ft. wide; course S. 40° W. to this point, and S. 60° W. below this point. | |
| 620. | Road, 12 ft. wide, bears N. 30° E. and S. 30° W. | |
| 770. | Gulch, 3 ft. wide, course S. 5° W. | |
| 800.00 | <p>Cor. No. 4 of the VIH No. 70 lode of this survey.</p> <p>Set an iron pin, 5/8 in. diam., 24 ins. long, 18 ins. in the ground, stone mound alongside, with aluminum cap mkd. X-VIH70-4-4763AM.</p> | |
| 1000.00 | <p>Cor. No. 3.</p> <p>Set an iron pin, 5/8 in. diam., 24 ins. long, 18 ins. in the ground, stone mound alongside, with aluminum cap mkd. X-VIH69-3-4763AM, from which</p> <p>Cors. Nos. 2, M.S. No. 490 Snow Bird lode, and M.S. No. 513 Bronze Statue lode, bears N. 45°40'05" W., 625.10 ft. dist.</p> <p>Thence S. 8°21' W.</p> | |
| 120.00 | <p>Cor. No. 2, VIH No. 71 lode, of this survey.</p> <p>Set an iron pin, 5/8 in. diam., 24 ins. long, 18 ins. in the ground, stone mound alongside, with aluminum cap mkd. X-VIH71-2-4763AM.</p> | |

| FEET | |
|---|--|
| 190.00 | Lode line; discovery point bears N. 81°39' W., 942 ft. dist. |
| 296.37 | Cor. No. 4, identical with Cor. No. 1 VIH No. 71 lode, on line 1-2, Victoria No. 5-A lode, of this survey. Set an iron pin, 5/8 in. diam., 24 ins. long, 18 ins. in the ground, stone mound alongside, with aluminum cap mkd. X-VIH69-4-VIH71-1-4763 AM. Thence N. 80°52'35" W. |
| 320. | Gulch, 5 ft. wide, course S. 40° W. |
| 472.18 | Cor. No. 5, identical with Cor. No. 1, Victoria No. 5-A lode of this survey, and with Cor. No. 2, M.S. No. 4488 Victoria No. 3 lode; an iron pipe, 1 in. diam., 6 ins. above ground, stone mound alongside, with galvanized cap mkd. X-VIC3-2-4488, to which I added: VIH69-5-VIC5A-1-4763AM. Thence N. 81°39' W. |
| 30. | Road, 12 ft. wide, bears N. 30° E. and S. 30° W. |
| 210. | Copper Basin Wash, 20 ft. wide, course South. |
| 224.35 | Intersect line 5-6, M.S. No. 513, Bronze Statue lode at a point from which Cor. No. 6 bears N. 61°52'30" W., 56.41 ft. dist. |
| 330. | Gulch, 15 ft. wide, course N. 5° E. |
| 380. | Road, 12 ft. wide, bears N. 10° W. and S. 20° E. |
| 410. | Gulch, 15 ft. wide, course S. 10° E. |
| 527.86 | Cor. No. 1, and place of beginning. |
| VIH No. 70 Lode | |
| At Cor. No. 1 of the VIH No. 70 lode, identical with Cor. No. 2, VIH No. 69 lode of this survey, heretofore described, from which | |
| The cor. of secs. 16, 17, 20 and 21, T. 13 N., R. 3 W., G. & S.R.M., Arizona, bears S. 41°57'55" W., 600.61 ft. dist. | |
| Thence N. 8°21' E. | |
| 205. | Lode line; discovery point bears S. 81°39' E., 75 ft. dist. |
| 400. | Gulch, 5 ft. wide, course S. 60° E. |
| 410.00 | Cor. No. 2. Set an iron pin, 5/8 in. diam., 24 ins. long, 18 ins. in the ground, stone mound alongside, with aluminum cap mkd. X-VIH70-2-4763 AM, from which |

| FEET | | |
|--------|--|--|
| | <p>Cors. Nos. 2, M.S. No. 490 Snow Bird lode, and M.S. No. 513 Bronze Statue lode bears S. 76°42'30" E., 496.02 ft. dist.</p> <p>Thence S. 81°39' E.</p> | |
| 210. | Road, 12 ft. wide, bears N. 20° E. and S. 20° W. | |
| 394.12 | <p>Intersect line 2-3, M.S. No. 490 Snow Bird lode, identical with the southerly side line of the Vista X unsur. at a point from which Cor. No. 2, M.S. No. 490 Snow Bird lode identical with Cor. No. 2, M.S. No. 513 Bronze Statue lode, the SE cor. of Vista X lode, unsur. and the SW cor. of Hazel lode unsur., bears S. 58°31'30" E., 108.80 ft. dist.</p> | |
| 465. | Copper Basin Wash, 10 ft. wide, course S. 5° E. | |
| 511.06 | <p>Intersect the easterly end line of Vista X lode unsur., identical with the westerly end line of the Hazel lode unsur., at a point from which the SE cor. of Vista X lode unsur., identical with the SW cor. of Hazel lode unsur., Cor. No. 2, M.S. No. 490 Snow Bird lode and Cor. No. 2 M.S. No. 513 Bronze Statue lode, bears S. 29° 54'10" W., 45.94 ft. dist.</p> | |
| 785. | Road, 12 ft. wide, bears N. 35° E. and S. 35° W. | |
| 800.00 | <p>Cor. No. 3.</p> <p>Set an iron pin, 5/8 in. diam., 24 ins. long, 18 ins. in the ground, stone mound alongside, with aluminum cap mkd. X-VIH70-3-4763AM.</p> <p>Thence S. 8°21' W.</p> | |
| 172.89 | <p>Intersect line 2-3, M.S. No. 513 Bronze Statue lode identical with the southerly side line of Hazel lode unsur., at a point from which Cor. No. 2 M.S. No. 513 Bronze Statue lode identical with Cor. No. 2 M.S. No. 490 Snow Bird lode, the SE cor. of Vista X lode unsur. and the SW cor. of Hazel lode unsur., bears N. 58°35'45" W., 332.37 ft. dist.</p> | |
| 205. | Lode line; discovery point bears N. 81°39' W., 725 ft. dist. | |
| 220. | Gulch, 2 ft. wide, course S. 35° W. | |
| 410.00 | <p>Cor. No. 4, on line 2-3, VIH No. 69 lode of this survey, heretofore described, from which</p> <p>Cors. Nos. 2, M.S. No. 490 Snow Bird lode, and M.S. No. 513 Bronze Statue lode, bears N. 31°26'10" W., 477.93 ft. dist.</p> <p>Thence N. 81°39' W.</p> | |
| 30. | Gulch, 3 ft. wide, course S. 5° W. | |

| FEET | |
|--|--|
| 180. | Road, 12 ft. wide, bears N. 30° E. and S. 30° W. |
| 395. | Copper Basin Wash, 15 ft. wide, course S. 40° W. to this point, and S. 60° W. below this point. |
| 459.63 | Intersect line 6-1, M.S. No. 490 Snow Bird lode, identical with line 6-1, M.S. No. 513 Bronze Statue lode, at a point from which Cors. Nos. 1 bears N. 26°43'05" E., 98.55 ft. dist. |
| 625. | Road, 12 ft. wide, bears N. 25° E. and S. 25° W. |
| 710. | Gulch, 5 ft. wide, course S. 70° W. |
| 800.00 | Cor. No. 1, and place of beginning. |
| <p>VIH No. 71 Lode</p> | |
| <p>At Cor. No. 1, VIH No. 71 lode, identical with Cor. No. 4, VIH No. 69 lode, on line 1-2, Victoria No. 5-A lode, both of this survey, heretofore described, from which</p> | |
| <p>The cor. of secs. 16, 17, 20 and 21 bears S. 89°39'15" W., 1348.00 ft. dist.</p> | |
| <p>Thence N. 8°21' W.</p> | |
| 86.37 | Lode line; discovery point bears S. 81°39' E., 50 ft. dist. |
| 176.37 | Cor. No. 2, on line 3-4, VIH No. 69 lode, of this survey, heretofore described. |
| <p>Thence S. 81°39' E.</p> | |
| 25. | Gulch, 2 ft. wide, course S. 5° E. |
| 120. | Gulch, 10 ft. wide, course S. 35° W. |
| 400.00 | Cor. No. 3. |
| <p>Set an iron pin, 5/8 in. diam., 24 ins. long, 18 ins. in the ground, stone mound alongside, with aluminum cap mkd. X-VIH71-3-4763AM.</p> | |
| <p>Thence S. 8°21' W.</p> | |
| 90. | Lode line; discovery point bears N. 81°39' W., 350 ft. dist. |
| 162.68 | Intersect line 2-3, M.S. No. 514 Head Center lode, at a point from which Cor. No. 3 bears N. 43°24'30" W., 189.62 ft. dist. |
| 181.78 | Cor. No. 4, on line 1-2, Victoria No. 5-A lode of this survey. |

(This form bound on left side)

| FEET | |
|-----------------------|---|
| | <p>Set an iron pin, 5/8 in. diam., 24 ins. long, 18 ins. in the ground, stone mound alongside, with aluminum cap mkd. X-VIH71-4-4763AM, from which</p> <p>Cor. No. 3, M.S. No. 514 Head Center lode, bears N. 39°09' W., 202.00 ft. dist.</p> <p>Thence N. 80°52'35" W.</p> |
| 248.82 | Intersect line 3-4, M.S. No. 514 Head Center lode at a point from which Cor. No. 4 bears S. 45°13'40" W., 128.37 ft. dist. |
| 370.22 | Gulch, 10 ft. wide, course S. 45° W. to this point and S. 35° W. below this point. |
| 400.04 | Cor. No. 1, and place of beginning. |
| Victoria No. 5-A Lode | |
| | <p>At Cor. No. 1, Victoria No. 5-A lode, identical with Cor. No. 5, VIH No. 69 lode of this survey, and with Cor. No. 2, M.S. No. 4488 Victoria No. 3 lode, from which</p> <p>The cor. of secs. 16, 17, 20 and 21 bears S. 84°37'20" W., 885.67 ft. dist.</p> <p>Cor. No. 5, M.S. No. 514 Head Center lode, bears S. 37°46'50" E., 500.75 ft. dist.</p> <p>Thence S. 80°52'35" E.</p> |
| 152.18 | Gulch, 5 ft. wide, course S. 40° W. |
| 472.18 | Cor. No. 4, VIH No. 69 lode, identical with Cor. No. 1 VIH No. 71 lode, both of this survey. |
| 502. | Gulch, 10 ft. wide, course S. 50° W. to this point and S. 55° W. below this point. |
| 623.40 | Intersect line 3-4, M.S. No. 514 Head Center lode, at a point from which Cor. No. 4 bears S. 45°13'40" W., 128.37 ft. dist. |
| 872.22 | Cor. No. 4 of the VIH No. 71 lode of this survey. |
| 896.88 | Intersect line 2-3, M.S. No. 514 Head Center lode, at a point from which Cor. No. 3 bears N. 43°24'30" W., 221.02 ft. dist. |
| 1025. | Gulch, 2 ft. wide, course S. 55° W. |
| 1105. | Road, 12 ft. wide, bears N. 20° E. and S. 20° W. |

| FEET | |
|---------|---|
| 1291.30 | Intersect line 3-4 M.S. No. 513 Bronze Statue lode, at a point from which Cor. No. 4 bears S. 30°17'10" W., 197.37 ft. dist. |
| 1335. | Road, 12 ft. wide, bears N. 40° E. and S. 30° W. |
| 1500.00 | <p>Cor. No. 2, identical with the NW cor. of VIH 68-A lode unsur.</p> <p>Set an iron pin, 5/8 in. diam., 24 ins. long, 18 ins. in the ground, stone mound alongside, with aluminum cap mkd. X-VIC5A-2-4763AM, from which</p> <p>The ½ cor. of secs. 16 and 21 bears N. 60°54'55" E., 313.43 ft. dist.</p> <p>Cor. No. 3, M.S. No. 513 Bronze Statue lode, bears N. 51°54'50" W., 196.45 ft. dist.</p> <p>Thence S. 15°39'40" W.</p> |
| 15. | Gulch, 5 ft. wide, course S. 60° W. |
| 301.94 | Lode line; discovery point bears N. 80°52'35" W. 1330 ft. dist. |
| 427.71 | Intersect line 2-3, M.S. No. 514 Head Center lode, at a point from which Cor. No. 2 bears S. 43°24'30" E., 585.75 ft. dist. |
| 515. | Gulch, 3 ft. wide, course N. 60° W. |
| 600.00 | <p>Cor. No. 3, identical with the SW cor. of VIH 68-A lode unsur., and on line 4-1 M.S. No. 4488 Victoria No. 2 lode, at a point from which Cor. No. 1 of Victoria No. 2, identical with the NW cor. of VIH 67-A unsur. bears S. 80°52'30" E., 289.18 ft. dist.</p> <p>Set an iron pin, 5/8 in. diam., 24 ins. long, 18 ins. in the ground, stone mound alongside, with aluminum cap mkd. X-VIC5A-3-4763AM, from which</p> <p>Cor. No. 5, M.S. No. 513 Bronze Statue lode, bears N. 58°25' W., 357.81 ft. dist.</p> <p>Cor. No. 2, M.S. No. 514 Head Center lode, bears S. 59°57'45" E., 518.69 ft. dist.</p> <p>Thence N. 80°52'30" W.</p> |
| 50. | Road, 12 ft. wide, bears N. 20° E. and S. 20° W. |
| 205. | Gulch, 15 ft. wide, course S. 65° W. to this point and S. 30° W. below this point. |
| 690. | Road, 12 ft. wide, bears N. 60° E. and S. 60° W. |

| FEET | |
|---------|--|
| 739.14 | Intersect line 5-6, M.S. No. 514 Head Center lode at a point from which Cor. No. 5 bears N. 43°01' 55" W., 413.96 ft. dist. |
| 1095. | Gulch, 5 ft. wide, course South. |
| 1210.82 | Cor. No. 4, identical with Cor. Nos. 4 and 2, Victoria No. 2 and Victoria No. 1 lodes, respectively, both of M.S. No. 4488. An iron pipe, 1 in. diam., 6 ins. above ground, stone mound alongside, with galvanized cap mkd. X-VIC2-4-VIC1-2-4488, to which I added: VIC5A-4-4763AM. Thence N. 81°38'30" W. |
| 205. | Road, 12 ft. wide, bears N. 35° E. and S. 35° W., and gulch, 10 ft. wide, course S. 50° W.; both entering channel of Copper Basin Wash, on left bank at this point; 30 ft. wide, course S. 15° E. |
| 235. | Leave channel of Copper Basin Wash on right bank 30 ft. wide, course S. 15° E. |
| 280. | Road, 12 ft. wide, bears N. 5° W. and S. 5° E. |
| 289.66 | Cor. No. 5, identical with Cor. No. 3, Victoria No. 3 lode, on line 1-2, Victoria No. 1 lode, both of M.S. No. 4488. An iron pipe, 1 in. diam., 6 ins. above ground, stone mound alongside, with galvanized cap mkd. X-VIC3-3-4488, to which I added: VIC5A-5-4763AM. Thence N. 15°39'40" E. |
| 30. | Road, 12 ft. wide, bears N. 20° W. and S. 5° E. |
| 120. | Enter channel of Copper Basin Wash, on right bank, 25 ft. wide, course S. 15° E. |
| 170. | Leave channel of Copper Basin Wash, on left bank, 25 ft. wide, course S. 15° E. |
| 301.94 | Lode line; discovery point bears S. 80°52'35" E. 170 ft. dist. |
| 320. | Road, 12 ft. wide, bears N. 5° W. and S. 10° E. |
| 526.15 | Intersect line 5-6, M.S. No. 513 Bronze Statue lode, at a point from which Cor. No. 5 bears S. 61°52'30" E., 1173.83 ft. dist. |
| 603.88 | Cor. No. 1, and place of beginning. |

| FEET | AREAS |
|-------|---|
| | <u>Acres</u> |
| | Total area, VIH No. 69 lode ----- 6.692 |
| | Area in conflict with -- |
| | M.S. No. 513 Bronze Statue lode ----- 4.733 |
| | M.S. No. 490 Snow Bird lode ----- 1.485 |
| | Total area, VIH No. 70 lode ----- 7.530 |
| | Area in conflict with -- |
| | M.S. No. 490 Snow Bird lode ----- 3.920 |
| | M.S. No. 513 Bronze Statue lode ----- 2.804 |
| | Vista X lode, unsurveyed ----- 0.057 |
| | Hazel lode, unsurveyed ----- 0.749 |
| | |
| | Total area, VIH No. 71 lode ----- 1.644 |
| | Area in conflict with -- |
| | M.S. No. 513 Bronze Statue lode ----- 1.644 |
| | M.S. No. 513 Bronze Statue lode, exclusive of its conflict with |
| | M.S. No. 514 Head Center lode ----- 1.227 |
| | M.S. No. 514 Head Center lode ----- 0.417 |
| | |
| | Total area, Victoria No. 5-A lode- 20.540 |
| | Area in conflict with -- |
| | M.S. No. 514 Head Center lode ----- 10.137 |
| | M.S. No. 514 Head Center lode, exclusive of its conflict with M.S. No. 513 |
| | Bronze Statue lode ----- 5.437 |
| | M.S. No. 513 Bronze Statue lode ----- 7.858 |
| | |
| | LOCATION |
| | This amended survey is located in Secs. 16 and 21, T. 13 N., R. 3 W., G. & S.R.M., Arizona. |
| | EXPENDITURES |
| | The improvements and the value of the labor and improvements made upon or for the benefit of each of the lode locations embraced in said mining claim by the claimant or its grantors are as follows: |
| No. 1 | The discovery point of the VIH No. 69 lode, being on the lode line 58 ft. from a point on line 1-2, 100 ft. from Cor. No. 1. No value. |
| No. 2 | A diamond drill hole, No. PD-1; 3 ins. diam. at the collar, 1124 ft. deep, the center of which bears N. 80°36' E., 582.8 ft. from Cor. No. 1, VIH No. 69 lode. Value, \$11,000. |
| No. 1 | The discovery point of the Victoria No. 5-A lode, being on the lode line 170 ft. from the center of line 5-1. No value. |
| No. 2 | A diamond drill hole, No. G-4; 3 ins. diam. at the collar, 1104 ft. deep, the center of which bears S. 33°38' E., 102.3 ft. from Cor. No. 1, Victoria No. 5-A lode. Value, \$11,000. |

| FEET | | |
|---|---|--|
| No. 3 | <p>A diamond drill hole, No. G-8; 3 ins. diam. at the collar, 1042 ft. deep, the center of which bears N. 29°20' W., 159.8 ft. from Cor. No. 4, Victoria No. 5-A lode. Value, \$10,000.</p> | |
| No. 4 | <p>A diamond drill hole, No. PD-3; 3 ins. diam. at the collar, 1082 ft. deep, the center of which bears N. 67°10' E., 355.0 ft. from Cor. No. 4, Victoria No. 5-A lode. Value, \$11,000.</p> | |
| No. 5 | <p>A diamond drill hole, No. PD-20; 3 ins. diam. at the collar, 1139 ft. deep, the center of which bears N. 53°57' W., 569.0 ft. from Cor. No. 3, Victoria No. 5-A lode. Value, \$11,000.</p> | |
| No. 6 | <p>A diamond drill hole, No. G-32; 3 ins. diam. at the collar, 1168 ft. deep, the center of which bears N. 9°20' W., 398.9 ft. from Cor. No. 3 Victoria No. 5-A lode. Value, \$12,000.</p> | |
| OTHER CORNER DESCRIPTIONS AND SUPPLEMENTAL DATA | | |
| <p>M.S. No. 490 Snow Bird lode: All corners except Nos. 2 and 5 were found; all were very old mounds of similar general appearance. Cor. No. 4 is a very large mound with a very old squared cedar post in it. Record lengths of the two sidelines are short by 33 to 67 ft.; all record bearings should be rotated about one degree of arc, clockwise.</p> | | |
| <p>M.S. No. 513 Bronze Statue lode: All corners except Nos. 2 and 5 were found; No. 1 is a very old mound; Nos. 3 and 4 look old, but had been rebuilt into higher monuments. Record lengths of the two sidelines are short by 19 to 42 ft.; the record bearings of the lines should be rotated from one to two degrees of arc, clockwise.</p> | | |
| <p>M.S. No. 514 Head Center lode: All corners except No. 5 were found; No. 2 is a large mound, with a very old squared cedar post in it, scribed HCN-1; Nos. 1 and 4 are very old mounds of similar appearance; No. 3 is only the base of a very old monument. The positions for Cor. No. 5 was calculated from Cor. No. 4, on record distance and bearing. Cor. No. 6 is a scattered old mound of large stones 8 ft. in diam. Record lengths of the sidelines are within 5 to 11 ft.; All bearings are reasonably close to record.</p> | | |
| <p>M.S. No. 4488: All corners found were iron pipes, 1 in. diam., 6 ins. above ground, stone mound alongside, with galvanized pipe-caps properly marked. All pertinent data checked out very well.</p> | | |
| <p>The W'ly half-mile common to Secs. 16 and 21 measures out at S. 89°56'45" W., 2636.69 ft., instead of West, 2639.33 ft. record. Both</p> | | |

| FEET | | | | | | | | | | |
|--------------------|---|---------------|------------|-----------------|---------------|-----------------|---------------|--------------------|--------|--|
| | <p>corners are standard G.L.O. brass-caps, firmly set and properly marked. All BO's were checked and found to be correct as set forth in the record of the 1934 survey.</p> <p style="text-align: center;">FIELD ASSISTANTS</p> <table><tr><td>Hoyd J. Patty</td><td>Transitman</td></tr><tr><td>Thomas S. Woods</td><td>Head Chainman</td></tr><tr><td>Stephen W. Dale</td><td>Rear Chainman</td></tr><tr><td>Bruce A. Schreiber</td><td>Axeman</td></tr></table> | Hoyd J. Patty | Transitman | Thomas S. Woods | Head Chainman | Stephen W. Dale | Rear Chainman | Bruce A. Schreiber | Axeman | |
| Hoyd J. Patty | Transitman | | | | | | | | | |
| Thomas S. Woods | Head Chainman | | | | | | | | | |
| Stephen W. Dale | Rear Chainman | | | | | | | | | |
| Bruce A. Schreiber | Axeman | | | | | | | | | |

FEET

Form 3860-7
(November 1976)
(formerly 3400-8)

UNITED STATES
DEPARTMENT OF THE INTERIOR
BUREAU OF LAND MANAGEMENT


CERTIFICATE OF SURVEYOR

| | |
|--|-----------------------|
| Name of Mineral Surveyor Robert Lenon | Date April 4, 1977 |
|--|-----------------------|

I HEREBY CERTIFY That in pursuance of an order received from the Bureau of Land Management, at Phoenix, Arizona Amended, dated May 26, 1976, I have carefully executed the/survey of the claim of Phelps-Dodge Corp. known as the (lode, placer, or mill site) Victoria No. 5-A, VIH No. 69, VIH No. 70 and situated in Secs. 16 and 21, VIH No. 71 lodes, Township 13 N., Range 3 W., Gila and Salt River Meridian, in the State of Arizona.

This survey, designated as number 4763, has been executed by me and under my direction and has been made in strict conformity with said order, the Manual of Instructions for the Survey of Public Lands of the United States, and in specific manner described in the foregoing field notes.


I FURTHER CERTIFY That the labor expended and improvements made upon and for the benefit of the ~~(lode or placer)~~ location(s) embraced in the said mining claim by claimant(s) or its grantors are fully stated in my report. The character, extent, location, and itemized value are specified in full detail. No portion of, or interest in, said labor and improvements so credited to this claim has been included in the estimate of expenditures upon any other claim.

| | |
|----------------------------------|---|
| Patagonia, Arizona (Location) |  (Signature of Mineral Surveyor) |
|----------------------------------|---|

CERTIFICATE OF APPROVAL

| |
|--------------------------------|
| Office Arizona State Office |
| Location Phoenix, Arizona |
| Date June 13, 1977 |

The foregoing field notes of mineral survey number 4763, in Secs. 16 and 21, Range 3 W., Gila and Salt River Meridian, in the State of Arizona, surveyed unsurveyed Township 13 N., executed by Robert Lenon, Mineral Surveyor, under order dated May 26, 1976, having been critically examined and the necessary corrections made prior to their certification by the surveyor, the field notes and the survey therein described are hereby approved.

| | |
|--|---|
|  Boyd S. Owens (Authorized Signature) | Chief, Br. of Cadastral Survey (Title) |
|--|---|

CERTIFICATE OF TRANSCRIPT

I HEREBY CERTIFY That the foregoing transcript of field notes of the above-described mineral survey number is a true copy of the original field notes.

| | |
|------------------------|---------|
| (Authorized Signature) | (Title) |
|------------------------|---------|

Title 18, U.S.C. section 1001, makes it a crime for any person knowingly and willfully to make to any department or agency of the United States any false, fictitious, or fraudulent statements or representations as to any matter within its jurisdiction.

Dear Sir,

I have the honor to acknowledge the receipt of your letter of the 15th inst.

in relation to the matter mentioned therein.

I am sorry that I cannot give you a more definite answer at this time.

Very respectfully,
J. H. [Name]

[Address]

[Address]