

Form 3860-10
(February 1987)

UNITED STATES
DEPARTMENT OF THE INTERIOR
BUREAU OF LAND MANAGEMENT

Mineral Survey Number
4867

State
Arizona

Land District
Arizona

FIELD NOTES

Of the Survey of the Mining Claim of *(name and address of claimant)*

Clay R. Thorne
501 South Rimview Circle
Payson, Arizona 85547

Known as the *(name of group, if any)*

NAME OF CLAIM(S)

NAME OF LOCATION	DATE			BLM MINING CLAIM SERIAL NUMBER
	LOCATED AND AMENDED	RECORDED WITH COUNTY	RECORDED WITH BLM	
Payson No. 1 Millsite	4/20/87	4/22/87	5/8/87	268995
Payson No. 2 Millsite	4/20/87	4/22/87	5/8/87	268996
Payson No. 3 Millsite	4/20/87	4/22/87	5/8/87	268997

LOCATION OF CLAIM(S)

Mining district Green Valley			County Gila	
Section 21 & 28	Township 10 N.	Range 10 E.	Meridian G. & S. R.	Survey under order dated May 21, 1987
Survey commenced July 6, 1987		Survey completed Aug. 10, 1987	Name of Mineral Surveyor O. T. Smith	

FFFF

This survey was made with a Topcon total station, model CTS2B No. J10844, having horizontal circle 3.228 ins. diam., and vertical circle 2.756 ins. diam., the circles are graduated in degrees and minute increments. An optical micrometer, adjusted to the vertical and horizontal circles permit the reading of angles direct to 6 seconds and estimating to 1 second accuracy. The instrument was in good condition at the time of the survey, and all adjustments were in good order.

All azimuths in the record were determined by the method of horizontal-angles-right and referred to the meridian determined by the following observation:

July 6, 1987 at cor. No. 2 Payson No. 3 Millsite, in latitude 34° 11' 14.5" N., and longitude 111°19'48.1" W., elevation 4,760 ft. above sea level, and temperature 92° F., make a series of six altitude observations on the sun for azimuth at approximately equal time intervals, three each with the telescope in direct and reverse positions, observing opposite limbs of the sun, and reading the horizontal angle right from a reference point about 820 ft. northward NE. to the sun.

- Mean time of observation,
105th meridian standard
time = 8:24 a.m.
- Declination of sun at mean
time of observation = 22°42'11.5" N.
- Mean observed vertical
angle to sun's center = 35°36'
- Mean horizontal angle from
reference point clockwise
to sun's center = 60°49'10"
- True bearing to reference
point = N 24°09' E.

The tie lines and corner distances were measured with a Topcon total station Model GTS2B No. J10844, all other distances were measured with a Lufkin steel tape 200 ft. in length graduated in feet, tenths and hundredths, and a steel tape 8 ft. in length graduated in feet, tenths and hundredths; both tapes were compared with a Lufkin Ranger standardized tape at the time of beginning the survey and found correct.

F111	<p>All lines and connections of this survey were run by direct methods.</p> <p>The magnetic declination observed at each corner of the survey gave a uniform value of 14°30' E.</p>
Mineral Survey No. 4867	
PAYSON NO. 1 MILLSITE	
<p>At Cor. No. 1 of the Payson No. 1 Millsite, identical with Cor. No. 1 of the Payson No. 2 Millsite of this survey, and on line 4-5 of the Payson No. 3 Millsite of this survey, and on the boundary line between secs. 21 and 28, T. 10 N., R. 10 E.</p>	
<p>Set an iron pin, 18 ins. long, 5/8 in. diam., 11 ins. in the ground, in a concrete and rock base, with an aluminum cap firmly secured to the iron pin, mkd. P1-1-P2-1-4867; from which</p>	
<p>The cor. of secs. 21, 22, 27 and 28, T. 10 N., R. 10 E., G. & S. R. M., bears N. 89°59'08" E., 973.64 ft. dist; monumented with an iron post, 3 ins. diam., 10 ins. above ground firmly set with a brass cap properly mkd., and with a mound of stone, 2 ft. high, E. of cor.</p>	
<p>No local bearing objects or bearing trees available</p>	
<p>Thence S 24°09' W.</p>	
152.	Center of road, 20 ft. wide, bears N. 9° W. and S. 9° E.
242.	Center of road, 12 ft. wide, bears N. 43° E. and S. 43° W.
362.	Northeast dam of dirt reservoir.
450.	Southwest dam of dirt reservoir.
492.12	Cor. No. 2, identical with Cor. No. 4 of the Payson No. 3 Millsite of this survey, and on the north right of way line of Forest Service Road.

FEET		
	<p>Set an iron pin, 18 ins. long, 5/8 in. diam. 11 ins. in the ground, in a concrete and rock base, with an aluminum cap firmly secured to the iron pin, mkd. P1-2-P3-4-4867.</p> <p>No local bearing objects or bearing trees available.</p> <p>Thence westerly along the arc of a 15°30'12" circular curve to the left, having a radius of 369.57 ft. and a distance of 62.70 ft. on the north right of way line of Forest Service Road, the chord of said arc bears N. 86°24'53" W., 62.62 ft. dist.</p>	
62.70	<p>Cor. No. 3, the end of curve on the north right of way of the Forest Service Road.</p> <p>Set an iron pin, 18 ins. long, 5/8 in. diam., 12 ins. in the ground, in a concrete and rock base, with an aluminum cap firmly secured to the iron pin, mkd. P1-3-4867.</p> <p>No local bearing objects or bearing trees available.</p> <p>Thence N. 88°43'30" W.</p>	
43.	Center of road, 12 ft. wide, bears N. 22° E.	
53.	Southeast cor. of the storage yard fence.	
102.18	<p>Cor No. 4 on the north right of way line of the Forest Service Road.</p> <p>Set an iron pin, 18 ins. long, 5/8 in. diam., 12 ins. in the ground, in a concrete and rock base, with an aluminum cap firmly secured to the iron pin, mkd. P1-4-4867.</p> <p>Thence N. 81°02' W.</p>	
110.	Center of road, 18 ft. wide, bears N. 24° E. and S. 24° W. to Forest Service Road right of way.	
138.	Center of dry wash, 3 ft. wide, course S. 15° W.	
292.76	Cor. No. 5, on the east right of way line of the Forest Service Road.	

	<p>FFF</p>	<p>Set an iron pin, 18 ins. long, 5/8 in. diam., 12 ins. in the ground, in a concrete and rock base, with an aluminum cap firmly secured to the iron pin, mkd. P1-5-4867; from which</p> <p>A copper plate, bears N. 81°30' E., 33.31 ft. dist., nailed in a blaze, 9 ins. above ground, on a juniper, 11 ins. diam. Copper plate mkd. XBT-P1-5-4867 and S. 81-30 W. 33.31 ft. to Cor. 5.</p> <p>A copper plate, bears N. 8°18' E., 16.04 ft. dist., nailed in a blaze, 11 ins. above ground, on a juniper, 6 ins. diam. Copper plate mkd. XBT-P1-5-4867 and S. 8-18 W., 16.04 ft. to Cor. 5.</p> <p>Thence northerly along the arc of a 78°03'35" circular curve to the right, having a radius of 73.40 ft. and distance of 32.08 ft. on the east right of way line of Forest Service Road, the chord of said arc bears N. 5°39'45" W., 31.83 ft. dist.</p>	
32.08		<p>Cor. No. 6 on the east right of way line of the Forest Service Road.</p> <p>Set an iron pin, 18 ins. long, 5/8 in. diam., 12 ins. in the ground, in a concrete and rock base, with an aluminum cap firmly secured to the iron pin, mkd. P1-6-4867; from which</p> <p>A copper plate, bears N. 77°12' E., 42.59 ft. dist., nailed in a blaze, 11 ins. above ground, on a juniper, 7 ins. diam. Copper plate mkd. XBT-P1-6-4867 and S. 77-12 W. 42.59 ft. to Cor. 6.</p> <p>A copper plate, bears N. 57°19' E., 36.61 ft. dist., nailed in a blaze, 8 ins. above ground, on a juniper, 12 ins. diam. Copper plate mkd. XBT-P1-6-4867 and S. 57-19 W., 36.61 ft. to Cor. 6.</p> <p>Thence N. 6°51'30" E.</p>	
26.14		<p>Cor. No. 7, on a line 200 ft. E. of the centerline</p>	

	FEET		
		<p>of State Route No. 87 Highway as described in Public Land Order 1229; and on the E. right of way line of the Forest Service Road.</p> <p>Set an iron pin, 18 ins. long, 5/8 in diam., 12 ins. in the ground, in a concrete and rock base, with an aluminum cap firmly secured to the iron pin, mkd. P1-7-4867; from which</p> <p style="padding-left: 40px;">A copper plate, bears N. 85°02' E., 19.45 ft. dist., nailed in a blaze, 10 ins. above ground, on a juniper, 11 ins. diam. Copper plate mkd. XBT-P1-7-4867 and S. 85-02 W. 19.45 ft. to Cor. 7.</p> <p style="padding-left: 40px;">A copper plate, bears N. 59°22' E., 12.75 ft. dist., nailed in a blaze, 7 ins. above ground, on a juniper, 6 ins. diam. Copper plate mkd. XBT-P1-7-4867 and S. 59-22 W. 12.75 ft. to Cor 7.</p> <p style="padding-left: 80px;">Thence N. 24°09' E.</p>	
	260.	Northwest cor. of dirt reservoir	
	377.02	<p>Cor. No. 8 on line 200 ft. E. of centerline of State Route No. 87 Highway as described in Public Land Order 1229; and on line 1-2 of the Payson No. 2 Millsite of this survey; and on the boundary line between secs. 21 and 28, T. 10 N., R. 10 E.</p> <p>Set an iron pin, 18 ins. long, 5/8 in. diam., 10 ins. in the ground, in a concrete and rock base, with an aluminum cap firmly secured to the iron pin, mkd. P1-8-4867; from which</p> <p style="padding-left: 40px;">A copper plate, bears S. 34°25' E., 47.91 ft. dist., nailed in a blaze, 10 ins. above ground, on a juniper, 12 ins. diam. Copper plate mkd. XBT-P1-8-4867 and N. 34-25 W. 47.91 ft. to Cor. 8.</p> <p style="padding-left: 40px;">A copper plate, bears N. 76°12' E., 8.35 ft. dist., nailed in a blaze, 10 ins. above ground, on a pinon pine, 7 ins. diam. Copper plate mkd. XBT-P1-8-4867 and S. 76-12 W. 8.35 ft. to Cor. 8.</p>	

FEET		
	Thence N. 89°59'08" E.	
141.	Center of a dry wash, 6 ft. wide, course S. 54° W.	
223	Center of a ditch, 2 ft. wide, course S. 12° E.	
248.	Center of a concrete slab, bears S. 5° W., 6 ft. and N. 5° E., 51 ft. dist.	
288.	Center of a fiberglass tank 4 ft. diam., and 6 ft. high.	
389.	Center of road, 16 ft. wide, bears N. 9° W. and S. 24° E.	
500.94	Cor. No. 1 and point of beginning. Payson No. 1 Millsite contains 4.936 acres.	
	PAYSON NO. 2 MILLSITE	
	Beginning at Cor No. 1 of the Payson No. 2 Millsite identical with Cor. No. 1 of the Payson No. 1 Millsite of this survey.	
	Thence S. 89°59'08" W.	
112.	Center of road, 16 ft. wide, bears N. 9° W. and S. 24° E.	
213.	Center of a fiberglass tank 4 ft. diam., and 6 ft. high.	
253.	Center of a concrete slab, bears S. 5° W., 6 ft. dist. and N. 5° E., 51 ft. dist.	
278.	Center of a ditch, 2 ft. wide, course S. 12° E.	
360.	Center of a dry wash, 6 ft. wide course S. 54° W.	
500.94	Cor. No. 8 Payson No. 1 Millsite of this survey.	
552.45	Set an iron pin, 18 ins. long, 5/8 in. diam., 12 ins. in the ground, in a concrete and rock base, with an aluminum cap firmly secured to the iron pin, for witness Corner No. 2, mkd. WC-P2-2-4867 and 7.68' to Cor. 2.	

<p style="text-align: center;">FEET</p> <p>560.13</p>	<p>Cor. No. 2, on the east right of way line of the State Route No. 87 Highway, and on the boundary line between secs. 21 and 28, T. 10 N., R. 10 E.</p> <p>This cor. falls on a concrete base, off the north edge of an aluminum cap 3 ins. diam., mkd. ADOT Highway Div., sec. line 844+78.21 Elev. 4773.64 160.02 Rt. 1978.</p> <p>Chiseled a cross in the concrete and drove a concrete nail in the center of the cross, and wired an aluminum tape to the nail, mkd. P2-2-4867.</p> <p>No local bearing objects or bearing trees available.</p> <p style="text-align: center;">Thence N. 24°09' E.</p>
<p>540.83</p>	<p>Cor. No. 3, on the east right of way line of State Route No. 87 Highway.</p> <p>Set an iron pin, 18 ins. long, 5/8 in. diam., 10 ins. in the ground, in a concrete and rock base, with an aluminum cap firmly secured to the iron pin, Mkd. P2-3-4867, from which</p> <p style="padding-left: 40px;">A copper plate, bears S. 28°10' W., 24.36 ft. dist., nailed in a blaze, 14 ins. above ground on a juniper, 17 ins. diam. Copper plate mkd. XBT-P2-3-4867 and N. 28-10 E. 24.36 ft. to Cor. 3.</p> <p style="padding-left: 40px;">A copper plate, bears N. 31°44' W., 3.39 ft. dist., nailed in a blaze, 10 ins. above ground, on a juniper 16 ins diam. Copper plate mkd. XBT-P2-3-4867 and S. 31-44 E. 3.39 ft. to Cor. 3.</p> <p style="text-align: center;">Thence S. 65°51' E.</p>
<p>120.</p>	<p>Power line 3 cables, lying on ground.</p>
<p>320.</p>	<p>Center of road, 12 ft. wide, bears N. 28° W. and S. 3° W.</p>
<p>350.</p>	<p>Center of dry wash, 8 ft. wide, course S. 55° W.</p>
<p>511.05</p>	<p>Cor. No. 4, identical with Cor. No. 5 of the Payson No. 3 Millsite of this survey.</p>

<p>FEET</p> <p>311.54</p>	<p>Set an iron pin, 18 ins. long, 5/8 in. diam., 11 ins. in the ground, in a concrete and rock base, with an aluminum cap firmly secured to the iron pin, mkd. P2-4-P3-5-4867.</p> <p>No local bearing objects or bearing trees available.</p> <p>Thence S. 24°09' W.</p> <p>Cor. No. 1, and the place of beginning.</p> <p>The Payson No. 2 Millsite contains 5.00 acres.</p>	
<p>820.36</p>	<p>PAYSON NO. 3 MILLSITE</p> <p>At Cor. No. 1 of the Payson No. 3 Millsite.</p> <p>Set an iron pin, 18 ins. long, 5/8 in. diam., 13 ins. in the ground, in a concrete and rock base, with an aluminum cap firmly secured to the iron pin, mkd. P3-1-4867; from which</p> <p>The cor. of secs. 21, 22, 27 and 28, T. 10 N., R. 10 E., G. & S. R. M., bears S. 73°46'17" E., 631.49 ft. dist; hereinbefore described.</p> <p>A granite rock in place, 18 X 12 X 14 ins. above ground, bears N. 15°33' W., 36.41 ft. dist. mkd. XBR-P3-1-4867.</p> <p>A granite rock in place, 16 X 13 X 4 ins. above ground, bears N. 19°34' E., 34.39 ft. dist., mkd. XBR-P3-1-4867.</p> <p>Thence S. 24°09' W.</p> <p>Cor. No. 2 on the northerly right of way line of Forest Service Road.</p> <p>Set an iron pin, 18 ins. long, 5/8 in. diam., 12 ins. in the ground, in a concrete and rock base, with an aluminum cap firmly secured to the iron pin, mkd. P3-2-4867; from which</p> <p>A copper plate, bears N. 12°40' E., 17.28 ft. dist., nailed in a blaze, 10 ins. above ground, on a juniper, 5 ins. diam. Copper</p>	

FEET		
	<p>plate Mkd. XBT-P3-2-4867 and S. 12-40 W. 17.28 to Cor. 2.</p> <p>A cor. of the location bears S. 24°15' W., 9.2 ft. dist.</p> <p>Thence N. 50°55'30" W.</p>	
70.00	<p>Cor. No. 3, on the northerly right of way line of the Forest Service Road.</p> <p>Set an iron pin, 18 ins. long, 5/8 in. diam., 11 ins. in the ground, in a concrete and rock base, with an aluminum cap firmly secured to the iron pin, mkd. P3-3-4867.</p> <p>No local bearing objects or bearing trees available.</p> <p>Thence northwesterly along the arc of a 15°30'12" circular curve to the left, having a radius of 369.57 ft. and a distance of 197.57 ft. on the north right of way line of Forest Service Road, the chord of said arc bears N. 66°14'23" W., 195.22 ft. dist.</p>	
197.57	<p>Cor. No. 4, identical with cor. No. 2 of the Payson No. 1 Millsite of this survey.</p> <p>Thence N. 24°09' E.</p>	
42.	Center of the southwest dam of the dirt reservoir.	
130.	Center of the northeast dam of the dirt reservoir.	
250.	Center of road, 14 ft. wide, bears N. 42° E. and S. 42° W.	
340.	Center of road, 20 ft. wide, bears N. 10° W. and S. 10° E.	
492.12	Cor. Nos. 1 and 1 of Payson No. 1 and Payson No. 2 Millsites.	
803.66	<p>Cor. No. 5, identical with Cor. No. 4 Payson No. 2 Millsite of this survey.</p> <p>Thence S. 65°51' E.</p>	
262.86	Cor. No. 1, and the place of beginning.	

FEET	<p>The Payson No. 3 Millsite contains 4.819 acres.</p>								
	<p>Mineral Survey No. 4867</p>								
	<table style="width: 100%; border-collapse: collapse;"> <thead> <tr> <th style="text-align: left; width: 70%;">AREAS</th> <th style="text-align: right; width: 30%;">Acres</th> </tr> </thead> <tbody> <tr> <td>Total area, Payson No. 1 Millsite</td> <td style="text-align: right;">4.936</td> </tr> <tr> <td>Total area, Payson No. 2 Millsite</td> <td style="text-align: right;">5.000</td> </tr> <tr> <td>Total area, Payson No. 3 Millsite</td> <td style="text-align: right;">4.819</td> </tr> </tbody> </table> <p style="text-align: center; margin-top: 10px;">LOCATION</p> <p>This survey is located in the SE. $\frac{1}{4}$ of sec. 21, and the NE. $\frac{1}{4}$ of sec. 28, of T. 10 N., R. 10 E., Gila and Salt River Meridian.</p> <p>The survey of the Payson No. 1 and Payson No. 2 Millsite wholly within the location as marked on the ground. The survey of the Payson No. 3 Millsite is wholly within the location as marked on the ground; Cors. Nos. 1, 3, 4 and 5 are identical with cors. of the location; Cor. No. 2 differs to the extent previously shown.</p> <p style="text-align: center; margin-top: 10px;">EXPENDITURES</p> <p style="text-align: center;">None</p> <p style="text-align: center; margin-top: 10px;">OTHER IMPROVEMENTS</p> <p>A house trailer, the SE. cor. of which bears N. 28°47' E., 162 ft. from Cor. Nos. 2 and 4 Payson Nos. 1 and 3 Millsites; 8 X 38 ft. in size; the long sides bear N. 19° E. Claimant herein.</p> <p>A dirt reservoir, the SE. cor. of which bears N. 57° E., 62 ft. from Cor. Nos. 2 and 4 Payson Nos. 1 and 3 Millsites; 60 X 80 ft., 3 ft. deep; the long sides bear N. 24° E. Claimant herein.</p> <p>A chain link fence around a storage yard. the SE. cor. of which bears S. 88°43'30" W., 53 ft. from Cor. No. 3 Payson No. 1 Millsite; 70 X 120 ft.,</p>	AREAS	Acres	Total area, Payson No. 1 Millsite	4.936	Total area, Payson No. 2 Millsite	5.000	Total area, Payson No. 3 Millsite	4.819
AREAS	Acres								
Total area, Payson No. 1 Millsite	4.936								
Total area, Payson No. 2 Millsite	5.000								
Total area, Payson No. 3 Millsite	4.819								

FEET		
	<p>6 ft. high; the long sides bear N. 21°30' E. Claimant herein.</p> <p>A coral, the SW. cor. of which bears N. 57° E., 202 ft. from Cor. No. 5 Payson No. 1 Millsite; 18 X 28 ft. in size; the long sides bear S. 61° E. Claimant herein.</p> <p>A dirt reservoir, the NE. cor. of which bears S. 20° E., 105 ft. from Cor. No. 8 Payson No. 1 Millsite; 55 X 80 ft., 3 ft. deep; the long sides bear S. 86° E. and N. 72° E. Claimant herein.</p> <p>A concrete slab, 12 X 57 ft., 2 ft. high; a foundation for a rock crusher, hammer mill, conveyor belt, ball mill, concentrators, mixing bowls, concentrator table and electric motors, bears S. 88°41' W., 246 ft. from Cor. Nos. 1 and 1 Payson Nos. 1 and 2 Millsites; the long sides bear N. 5° E. Claimant herein.</p> <p>A fiberglass tank, 4 ft. diam., 6 ft. high, the center of which bears S. 89°59' W., 213 ft. from Cor. No. 1 and 1 Payson Nos. 1 and 2 Millsites; Claimant herein.</p> <p>A frame laboratory building, the NE. cor. of which bears S. 85° W., 231 ft. from Cor. Nos. 1 and 1 Payson Nos. 1 and 2 Millsites; 14 X 24 ft. in size; the long sides bear S. 5°30' W. Claimant herein.</p> <p>A maintenance trailer, the SE. cor. of which bears S. 78°31' W., 194 ft. from Cor. Nos. 1 and 1 Payson Nos. 1 and 2 Millsites; 8 X 28 ft. in size; the long sides bear S. 84°30' W. Claimant herein.</p> <p>A well and pump, the center of which bears S. 55°18'30" W., 163 ft. from Cor. Nos. 1 and 1 Payson Nos. 1 and 2 Millsites. Claimant herein.</p> <p>An office and bunkhouse trailer, the NE. cor. of which bears S. 52°29' W., 148 ft. from Cor. Nos. 1 and 1 Payson Nos. 1 and 2 Millsites; 12 X 56 ft. in size, the long sides bears S. 3°08' E. Claimant herein.</p>	

	FEET		
		<p>A dirt reservoir, the NE. cor. of which bears S. 46° W., 230 ft. from Cor. Nos. 1 and 1 Payson Nos. 1 and 2 Millsites; 60 X 90 ft., 5 ft. deep; the long sides bear N. 69° W. Claimant herein.</p> <p>A fiberglass tank, 5 ft. diam., 9 ft. high, the center of which bears N. 89°15' W., 190 ft. from Cor. Nos. 1 and 1 Payson Nos. 1 and 2 Millsites. Claimant herein.</p> <p>A concrete leaching pad, the NE. cor. of which Bears N. 81°23' W., 168 ft. from Cor. Nos. 1 and 1 Payson Nos. 1 and 2 Millsites; 20 X 20 ft. in size, the N., W. and S. sides are 4 ft. high, and 6 ins. wide; the N. and S. sides bear N. 75°40' W. Claimant herein.</p> <p>A fiberglass tank, 5 ft. diam., 9 ft. high, the center of which bears N. 76°58' W., 207 ft. from Cor. Nos. 1 and 1 Payson Nos. 1 and 2 Millsites. Claimant herein.</p> <p>A fiberglass tank, 5 ft. diam., 9 ft. high, the center of which bears N. 88°03' W., 211 ft. from Cor. Nos. 1 and 1 Payson Nos. 1 and 2 Millsites. Claimant herein.</p> <p>A metal tank lying horizontal underground, measurements unknown, the center of which bears N. 83°22' W., 196 ft. from Cor. Nos. 1 and 1 Payson Nos. 1 and 2 Millsites. Claimant herein.</p> <p>An open top fiberglass tank, 5 ft. diam., 6 ft. high; setting in an open pit, 7 ft. deep; the center of the tank bears N. 80°33' W., 204 ft. from Cor. Nos. 1 and 1 Payson Nos. 1 and 2 Millsites. Claimant herein.</p> <p>An upright board panel 4 X 8 ft. in size, holding electrical fuse and switch boxes, the E. end of which bears N. 79°50' W., 206 ft. from Cor. Nos. 1 and 1 Payson Nos. 1 and 2 Millsites. Claimant herein.</p> <p>A frame electro winning building, the NE. cor. of which bears N. 82°13' W., 202 ft. from Cor. Nos.</p>	

FEEI

1 and 1 Payson Nos. 1 and 2 Millsites; 8 X 8 ft. in size; the N. and S. sides bear N. 75°22' W.
Claimant herein.

A frame refinery building, the NE. cor. of which is identical with the NW. cor. of the electro winning building and bears N. 85°43' W., 212 ft. from Cor. Nos. 1 and 1 Payson Nos. 1 and 2 Millsites; 14 X 24 ft. in size; the long sides bear N. 75°22' W.
Claimant herein.

A metal pickup bed, for tailings catch basin, the NE. cor. of which bears N. 86°17' W., 261 ft. from Cor. Nos. 1 and 1 Payson Nos. 1 and 2 Millsites; 7 X 10 ft. in size; the long sides bears S. 12°22' W.
Claimant herein.

A metal tank lying horizontal underground, measurements unknown, the center of which bears N. 89°07' W., 268 ft. from Cor. Nos. 1 and 1 Payson Nos. 1 and 2 Millsites.
Claimant herein.

A crusher setting on a Metal frame 8 ft. above a concrete foundation 6 X 6 ft., 1 ft. above ground, the SE. cor. of which bears N. 44°38' W., 150 ft. from Cor. Nos. 1 and 1 Payson Nos. 1 and 2 Millsites; the conveyor belt, 3 ft. in width on the south side of the crusher bears S. 13°51' W., 43 ft.
Claimant herein.

A wood frame privy, the SE. cor. of which bears S. 71°27' W., 270 ft. from Cor. Nos. 4 and 5 Payson Nos. 2 and 3 Millsites; 6 X 6 ft. in size, the east side bears N. 9° E.
Claimant herein.

A round propane tank, the north end center bears S. 11°11' E., 95 ft. from Cor. NOS. 4 and 5 Payson Nos. 2 and 3 Millsites; 8 X 50 ft. in size, the long sides bears N. 36° E.
Claimant herein.

OTHER CORNER DESCRIPTIONS AND
SUPPLEMENTAL DATA

None

	FHT	FIELD ASSISTANTS		
		Name	Capacity	
		Chet R. Schulte	Transitman	

UNITED STATES
DEPARTMENT OF THE INTERIOR
BUREAU OF LAND MANAGEMENT

CERTIFICATE OF SURVEYOR


Name of Mineral Surveyor	Date
O.T. SMITH	Feb. 25, 1988

I HEREBY CERTIFY That in pursuance of an order received from the Arizona State Office, Bureau of Land Management, at Phoenix, Arizona, dated May 21, 1987, I have carefully executed the survey of the claim of Clay R. Thorne, known as the Payson Nos. 1, 2, and 3 millsites, situated in surveyed sections 21 and 28, Township 10 North, Range 10 East, Gila and Salt River Meridian, in the State of Arizona.

This survey, designated as number 4867, has been executed by me and under my direction and has been made in strict conformity with said order, the Manual of Instructions for the Survey of Public Lands of the United States, and in specific manner described in the foregoing field notes.

I FURTHER CERTIFY That the labor expended and improvements made upon and for the benefit of the Payson Nos. 1, 2, and 3 millsites embraced in the said mining claim by claimant(s) or its grantors are fully stated in my report. The character, extent, location, and itemized value are specified in full detail. No portion of, or interest in, said labor and improvements so credited to this claim has been included in the estimate of expenditures upon any other claim.

Globe, Arizona
(Location)



(Signature of Mineral Surveyor)

Title 18, U.S.C. section 1001, makes it a crime for any person knowingly and willfully to make to any department or agency of the United States any false, fictitious, or fraudulent statements or representations as to any matter within its jurisdiction.

CERTIFICATE OF APPROVAL

Arizona State Office
Phoenix, Arizona
March 22, 1988

The foregoing field notes of mineral survey number 4867, in surveyed section 21 and 28, Township 10 North, Range 10 East, Gila and Salt River Meridian, in the State of Arizona, executed by O. T. Smith, Mineral Surveyor, under order dated May 21, 1987, having been critically examined and the necessary corrections made prior to their certification by the surveyor, the field notes and the survey therein described are hereby approved.



(Authorized Signature)

Chief Cadastral Surveyor of Arizona

(Title)