

3236

Book "N"  
4-679

JAN-1.1919

(Subdivisions)

BOOK 3236

# FIELD NOTES

OF THE SURVEY OF THE

SUBDIVISION LINES

of

TOWNSHIP 12 NORTH, RANGE 7 WEST,

Of the Gila and Salt River Base and Meridian,

In the State of Arizona.

EXECUTED BY

L. E. Wilkes, U. S. Surveyor,

and

H. M. Bradstreet, U.S. Transitman,

In the capacity of U.S. Surveyor, under instructions dated July 23, 1914, issued by the United States Surveyor General to govern surveys included in Group No. 36, which were approved by the Commissioner of the General Land Office, August 15, 1914.

Survey commenced February 15, 1915.

Survey completed March 5, 1915.

Executed under Assignment  
Instructions dated

3236

3236

11 37

40  
1A

3236

Book "N"

Group 36 - - - Arizona.

BOOK 3236

## INDEX DIAGRAM.

3224		Township 12 North,					Range 7 West.				
3rd Standard Parallel North											
6	35	5	25	4	19	3	13	2	6	1	
34	34		25		18		12		6		
7	33	8	24	9	18	10	12	11	5	12	
32	32		23		17		11		5		
18	31	17	23	16	17	15	11	14	4	13	
31	30		22		16		10		3		
19	29	20	22	21	16	22	9	23	3	24	
29	28		21		15		9		2		
30	28	29	21	28	14	27	8	26	2	25	
27	26		20		14		8		1		
31	25	32	19	33	13	34	7	35	1	36	

**—————** Subdivision lines surveyed under this group.

**—————** Township boundaries surveyed under this group.  
Notes in Book "A." 3223

**—————** Accepted surveys..

**-----** Unsurveyed.

Subdivision of Township 12 North, Range 7 West. 1. B

Chains.

Surveys hereinafter described were executed by L.E. Wilkes, U.S. Surveyor, and H.N. Bradstreet, U.S. Transitman, on dates shown on diagram on page 37 hereof, using Young and Son's light mountain transits Nos. 8541 and 7084, respectively.

Description, tests and approval of these instruments in Book "A." of this group.

In the following notes, the initials "L.E.W." and "H.N.B." are inserted at the beginning and end of those portions of the notes describing the surveys executed by L.E. Wilkes, U.S. Surveyor, and H.N. Bradstreet, U.S. Transitman, respectively.

L.E.W.

From the cor. of secs. 1, 2, 35 and 36, on S. bdy. of Tp., described in Book "A."

N. 0° 1' W., bet. secs. 35 and 36.

Over rolling land, thru. scattering brush.

Descend gradually.

10.00 Old road brs. NW. and SE.


36.70 Foot of rocky knoll, brs. E. and W.

Ascend 25 ft.

38.90 Top of knoll, 8 chs. long, covered with large volcanic boulders, bears E. and W.

Descend 15 ft. to

40.00 Set an iron post, 3 ft. long, 1 in. in diam., 26 ins. in the ground, for 1/4 sec. cor., marked on brass cap,



1915

and raise a mound of stone 2 ft. base, 1 1/2 ft. high, W. of cor.

From this cor. a tent house brs. N. 64° W.

Descend, 10 ft.

40.75 Foot of knoll, brs. E. and W. Thence over level land, thru. medium dense brush, bearing E. and W.



46.80 Dry bed of south fork of Santa Maria river, 10 ft. deep, 50 lks. wide, course W. about 5 chs., thence NW.

Wire fence brs. N. and SW., 150 lks. W. Ascend gradually.

Line parallels wire fence, 150 lks. E. from same.

77.10 Wash, 2 ft. deep, 15 lks. wide, course W.

80.00 Set an iron post 3 ft. long, 2 ins. in diam., 24 ins. in the ground, for cor. of secs. 25, 26, 35 and 36, marked on brass cap,



1915

Dig pits 18x18x12 ins., in each sec. 5 1/2 ft. dist., and raise a mound of earth, 4 ft. base, 2 ft. high, W. of cor.

Land, rolling.

Soil, sandy and rocky, 2nd and 4th rate.

Undergrowth, scattering mesquite, greasewood and catclaw.

No timber.

East, on a random line, bet. secs. 25 and 26.

40.00 Set temp. 1/4 sec. cor.

80.00 Intersect E bdy. of Tp., at the cor. of secs. 25, 30, 31 and 36, described in Book "A."

Thence,

West, on a true line, bet. secs. 25 and 36.

2. Subdivision of Township 12 North, Range 7 West.

Chains

West, on a true line, bet. secs. 25 and 36.  
 Over level bottom land, thru scattering brush, within a fenced inclosure belonging to Louis Schmitt.  
 19.20 Louis Schmitt's house brs. S. 100 lks. dist.  
 22.65 Wire fence brs. N. and S. Leave Schmitt's inclosure.  
 39.50 Wash, 10 lks. wide, course SW. Leave level bottom land.  
 40.00 Set an iron post, 3 ft. long, 1 in. in diam., 26 ins. in the ground, for  $\frac{1}{4}$  sec. cor., marked on brass cap,

$\frac{1}{4}$ S 25

S 36  
 1915

Dig pits 18x18x12 ins., E. and W. of post, 3 ft. dist., and raise a mound of earth  $3\frac{1}{2}$  ft. base,  $1\frac{1}{2}$  ft. high, N. of cor.

Ascend 30 ft.

50.00 Top of ascent, brs. NE. and SW. sloping SW. Descend gradually.

74.50 Wash, 15 lks. wide, 5 ft. deep, course S. 60° W.

80.00 The cor. of secs. 25, 26, 35 and 36.

Land, level and rolling.  
 Soil, sandy loam, 1st rate.  
 Scattering greasewood, 4 to 6 ft. high on rolling land.  
 Timber, scattering mesquite.

N. 0° 1' W., bet. secs. 25 and 26.  
 Over rolling land, thru low scattering brush.  
 Ascending gradually throughout the mile.

3.00 Cor. of wire fence brs. W. 140 lks. dist., from which fences extends W and S.

21.00 Wash, 12 lks. wide, 2 ft. deep, course SE.

40.00 Set an iron post 3 ft. long, 1 in. in diam., 26 ins. in the ground for  $\frac{1}{4}$  sec. cor., marked on brass cap,

$\frac{1}{4}$ S26 | S25

1915

Dig pits 18x18x12 ins., N. and S. of post, 3 ft. dist., and raise a mound of earth  $3\frac{1}{2}$  ft. base,  $1\frac{1}{2}$  ft. high, W. of cor.

80.00 Set an iron post 3 ft. long, 2 ins. in diam., 24 ins. in the ground for cor. of secs. 23, 24, 25 and 26, marked on brass cap,

T12N R 7W

S23 | S24

S26 | S25

1915

and raise a mound of stone 3 ft. base, 2 ft. high, W. of cor.

Land, rolling.  
 Soil, sandy loam, 1st and 2nd rate.  
 Undergrowth, scattering greasewood and cactus.  
 No timber.

East, on a random line, bet. secs. 24 and 25.

40.00 Set temp.  $\frac{1}{4}$  sec. cor.

79.98 Intersect E bdy. of Tp., 4 lks. S. of the cor. of secs. 19, 24, 25 and 30, described in Book "A."


Thence, S. 89° 58' W., on a true line, bet. secs. 24 and 25.

Over rolling S slope, thru scattering brush. Ascend gradually to  $\frac{1}{4}$  sec. cor.

Subdivision of Township 12 North, Range 7 West. 3.


Chains.

5.00 Road brs.N.3°W. and S.3°E. Extends NE. to Prescott and SE. to Phoenix.  
39.99 Set an iron post 3 ft.long, 1 in. in diam., 26 ins. in the ground, for 1/4 sec.cor., marked on brass cap,




Dig pits, 18x18x12 ins., N. and W. of post, 3 ft. dist., and raise a mound of earth 3 1/2 ft. base, 1 1/2 ft. high, N.of cor. Ascend 10 ft.  
42.50 Top of ascent, brs.N.&S.sloping S. Descend 25 ft.  
53.10 Wash, 10 lks.wide, 2 ft. deep, course S. Ascend 35 ft.  
59.00 Top of ascent, brs.N.and S., sloping S., descend gradually.  
79.98 The cor.of secs. 23, 24, 25 and 26.  
Land, rolling.  
Soil, sandy loam, 2nd rate.  
Undergrowth, scattering greasewood, catclaw and cacti.  
No timber.

N.0°1' W., bet. secs. 23 and 24.  
Over rolling SW.slope, thru.scattering brush.  
Ascend gradually 50 ft. to 1/4 sec.cor.  
40.00 Set an iron post 3 ft. long, 1 in. in diam., 26 ins. in the ground for 1/4 sec.cor., marked on brass cap,



Dig pits, 18x18x12 ins., N. and S. of post, 3 ft. dist., and raise a mound of earth 3 1/2 ft. base, 1 1/2 ft. high,W. of cor.  
This cor.is 75 lks.E. of a wash, 10 lks.wide, 4 ft. deep, course S. 20°W.  
46.50 Head of same wash. Ascend 150 ft., over S. slope,150 ft. to  
66.00 End of spur, sloping SE. Descend.along broken rocky E. slope.  
80.00 Set an iron post 3 ft. long, 2 ins. in diam., 24 ins. in the ground, for cor.of secs. 13,14,23 and 24, marked on brass cap,



and raise a mound of stone 3 ft. base, 2 ft. high,W. of cor.  
Land, rolling and mountainous, not very rough.  
Soil, sandy loam and rocky, 2nd and 3rd rate.  
Undergrowth, scattering greasewood, palo verde,catclaw and cacti.  
No timber.

N.89°55'E.on a random line, bet. secs. 13 and 24.  
40.00 Set temp.1/4 sec.cor.  
79.92 Intersect E\* bdy.of Tp., at the cor.of secs.13,18,19 and 24, described in Book "A,"  
Thence,  
S.89° 55'W. on a true line, bet. secs.13 and 24.

4. Subdivision of Township 12 North, Range 7 West.

Chains.

- Over heavily rolling S. slope, thru scattering brush. Ascend gradually.
- 9.25 Road brs. N. and S. Extends NE. to Prescott and SE. to Phoenix.
- 22.00 Spur, slopes S<sup>a</sup> 15° E. Extends about 5 chs. SE. Descend 50 ft.
- 25.00 Foot of descent; enter flat, bearing N. and S.
- 29.20 Wash, 30 lks. wide, course S. 20° E. Leave flat. Ascend 35 ft. to
- 39.96 Set an iron post 3 ft. long, 1 in. in diam., 26 ins. in the ground for  $\frac{1}{4}$  sec. cor., marked on brass cap,

S 13

S 24  
1915

Dig pits 18x18x12 ins., E. and W. of post, 3 ft. dist., and raise a mound of earth,  $3\frac{1}{2}$  ft. base,  $1\frac{1}{2}$  ft. high, N. of cor.

- Ascend gradually on E. slope.
- 51.75 Old road brs. S. 20° E. and N. 20° W.
- 60.00 Sour, slopes SE. near end of same. Descend 35 ft.
- 67.55 Wash, 51 lks. wide, course SE. Ascend 175 ft., over NE. slope.
- 79.92 The cor. of secs. 13, 14, 23 and 24. Land, heavily rolling. Soil, sandy and rocky, 2nd and 3rd rate. Undergrowth, scattering greasewood, catclaw and cactus. No timber.

N. 0° 1' W., bet. secs. 13 and 14.

Over mountainous land, thru scattering brush. Ascend 10 ft.

- 2.50 Short spur, slopes E. Descend 150 ft.
- 11.90 Wash, 10 lks. wide, course SE. Ascend 250 ft., over SW. slope.
- 26.70 Ridge brs. NW. and SE. Descend along broken rocky E. slope.
- 40.00 Set an iron post 3 ft. long, 1 in. in diam., 26 ins. in the ground, for  $\frac{1}{4}$  sec. cor., marked on brass cap,

S14 | S13

1915

and raise a mound of stone, 3 ft. base, 2 ft. high, W. of cor.

- Ascend along broken E. slope of ridge, bearing N. and S.
- 66.00 Short spur, slopes NE. Descend 175 ft. to sec. cor.
- 79.90 Wash, 5 lks. wide, course NE.
- 80.00 Set an iron post 3 ft. long, 2 ins. in diam., 24 ins. in the ground for cor., of secs. 11, 12, 13 and 14, marked on brass cap,

T12N R7 W  
S11 | S12

S14 | S13  
1915

and raise a mound of stone 3 ft. base, 2 ft. high, W. of cor.

Land, mountainous. Soil, scanty loam and rocky, 4th rate. Undergrowth scattering greasewood, palo verde and cactus.

Subdivision of Township 12 North, Range 7 West. 5.

Chains.

No timber.

- 40.00 N.89° 55' E., on a random line, bet. secs. 12 and 13.
- Set temp.  $\frac{1}{4}$  sec. cor.
- 79.98 Intersect E bdy, of Tp., 16 lks. S. of the cor. of secs. 7, 12, 13 and 18, described in Book "A."
- Thence,
- S.89° 48' W., on a true line, bet. secs. 12 and 13.
- Over mountainous land, thru. scattering brush.
- Ascend 250 ft. over E slope.
- 5.50 Road brs. N<sup>s</sup> and S. Extends NE. to Prescott and SE. to Phoenix.
- 27.00 Ridge brs. N. and S. Descend 75 ft. to
- 33.50 Draw, draining S. Thence along S. slope.
- 39.70 Small ravine and wash, course SE.
- 39.99 Set an iron post 3 ft. long, 1 in. in diam., 26 ins. in the ground for  $\frac{1}{4}$  sec. cor., marked on brass cap,

$\frac{1}{4}$ S 12

S 13  
1915

and raise a mound of stone, 2 ft. base, 1 $\frac{1}{2}$  ft. high, N. of cor. Ascend 125 ft. over E. slope.

- 53.75 Ridge, brs. N. and S.
- Descend 240 ft., over W. slope.
- 75.00 Foot of descent, enter flat. Old road brs. N. and S.
- Enter scattering cottonwoods, same bearing.
- 77.00 Lawler creek, 40 lks. wide, 6 ft. deep, course S. 20° E.
- Stream of running water in same 4 lks. wide, 1 in deep.
- Leave flat and scattering cottonwoods. Ascend 75 ft. to sec. cor.
- 79.25 Wash, 3 lks. wide, course NE.
- 79.98 The co. of secs. 11, 12, 13 and 14.
- Land, mountainous.
- Soil, rocky with scanty loam, 3rd rate.
- Undergrowth, scanty greasewood and cactus.
- Timber, scattering cottonwood and willow along Lawler creek.

- N.0°1' W., bet. secs. 11 and 12.
- Over mountainous land, thru. scattering brush.
- Along rocky, broken E. slope.
- 5.00 Foot of slope brs. NW. and SE. Enter flat land.
- 17.00 Lawler creek, 60 lks. wide, course S. 20° E. Running water 6 lks. wide, 1 in. deep.
- 25.20 Lawler creek, 30 lks. wide, course S. 25° W. Running water 3 lks. wide, 2 ins. deep. Leave flat; ascend 150 ft. over SE. slope.
- 33.00 E. end of spur, sloping E. from ridge to the W. Desc. 40 ft. over E. slope to
- 40.00 On E. end of spur, sloping E., set an iron post 3 ft. long, 1 in. in diam. 26 ins. in the ground, for  $\frac{1}{4}$  sec. cor., marked on brass cap,

$\frac{1}{4}$ S11 | S12

1915

and raise a mound of stone, 3 ft. base, 2 ft. high, W. of cor.

- Descend 100 ft. over rocky E. slope of ridge.
- 56.50 Lawler creek, 100 lks. wide, course S. 12° E. from NW. Running water, 5 lks. wide.
- Ascend 350 ft. over rocky, broken S. slope.
- 78.20 Ridge, brs. NW. and SE. near SE. end of same.
- Descend 65 ft. over large granite boulders on N. slope.
- 80.00 Set an iron post, 3 ft. long, 2 ins. in diam., 24 ins. in the ground, for cor. of secs. 1, 2, 11 and 12, marked

6. Subdivision of Township 12 North, Range 7 West.

Chains

on brass cap,

T12N R 7W  
S 2 | S 1  
S11 | S12  
1915

and raise a mound of stone 3 ft. base, 2 ft. high, W. of cor., from which,

A cross on a granite boulder, 5x3x4 ft. above ground bears S. 10°E., 6 lks. dist., marked with B O 12 beside the cross.

Land, mountainous.

Soil, rocky with scanty loam, 3rd and 4th rate.

Undergrowth, scattering greasewood and ocotillo on the steep slopes and mesquite, catclaw and hackberry on the flats along Lawler creek.

No timber, except scattering mesquite along the creek.

40.00 N. 89° 48' E., on a random line, bet. secs. 1 and 12.  
Set temp. 1/4 sec. cor.

79.96 Intersect E. bdy. of Tp. 8 lks. N. of the cor. of secs. 1, 6, 7 and 12, described in Book "A."

Thence,

S. 89° 51' W., on a true line, bet. secs. 1 and 12.

Over mountainous land, thru. scattering brush.

A scend 140 ft.

18.20 Spur, slopes SE. Descend 75 ft. over irregular and broken S. slope, to

39.98 Set an iron post, 3 ft. long, 1 in. in diam., 26 ins. in the ground, for 1/4 sec. cor., marked on brass cap,

1/4 S 1

S 12  
1915

and raise a mound of stone 3 ft. base, 2 ft. high, N. of cor. Ascend gradually.

77.75 Wash, 15 lks. wide, course SE.

79.96 The cor. of secs. 1, 2, 11 and 12, 120 ft. above 1/4 sec. cor., Land, mountainous.

Soil, light loam, among large boulders, 4th rate.

Undergrowth, scattering greasewood, palo verde and cactus. No timber.

2.10 N. 0° 1' W., bet. secs. 1 and 2.

Over mountainous land, thru. scattering brush.

Descend 25 ft.

2.10 Wash, 10 lks. wide, course SE.

Ascend 400 ft. to

35.00 Spur, slopes SW. Descend along rocky NW. slope, to

40.00 Set an iron post, 3 ft. long, 1 in. in diam., 26 ins. in the ground, for 1/4 sec. cor., marked on brass cap,

1/4 S 2 | S 1

1915

and raise a mound of stone, 3 ft. base, 2 ft. high, W. of cor.

Ascend 100 ft. on W. slope.


51.14 Intersect 3rd. Std. Par. N., 245 lks. E. of the reestablished standard cor. of secs. 35 and 36, a 3 in. iron post, with brass cap, firmly set, marked and witnessed as described by the surveyor general. At point of intersection,

Set an iron post, 3 ft. long, 2 ins. in diam., 24 ins. in

Subdivision of Township 12 North, Range 7 West. 7.

Chains.

the ground for closing cor., of secs. 1 and 2, marked on brass cap,



and raise a mound of stone 3 ft. base, 1 1/2 ft. high, S. of cor.

Land, mountainous.

Soil, rocky with scanty loam, 4th rate.

Undergrowth, greasewood, palo verde, hackberry, catclaw and cactus.

No timber.

L.E.W.

H.N.B.

From the cor. of secs. 2, 3, 34 and 35 on S. bdy. of Tp., described in Book "A,"

N. 0° 1' W., bet. secs. 34 and 35.

Over mountainous land, thru dense brush.

0.20 Wash, 15 lks. wide, 1 ft. deep, in bend from SW. to SE.

Ascend 115 ft., over S. slope.

4.90 Ridge, brs. E\* and W.; near E. end of same.


Descend 153 ft., over N. slope.

28.02 Enter gulch, from SW., course N. Thence descend 25 ft. in gulch.

36.17 Leave gulch, course NE. from S. Ascend 65 ft., over SE. slope.

39.15 Rim of gulch, brs. NE. and SW. Thence along E. slope.

40.00 Set an iron post 3 ft. long, 1 in. in diam., 26 ins. in the ground for 1/4 sec. cor., marked on brass cap,



and raise a mound of stone 3 ft. base, 2 ft. high, W. of cor. Ascend 20 ft. along E. slope.

45.00 SE. rim of ravine, brs. NE. and SW. Descend 90 ft. over NW. slope into ravine.

54.55 Wash, 15 lks. wide, 1 ft. deep, course NE.


Ascend 45 ft., over SE. slope.

60.00 NW\* rim of ravine, brs. NE. and SW. Leave ravine. Desc. 20 ft.

63.50 Wash, 1 ft. wide, 20 lks. wide. course NE

Ascend 50 ft. over rocky S. slope.

80.00 Set an iron post 3 ft. long, 2 ins. in diam., 24 ins. in the ground for cor. of secs. 26, 27, 34 and 35, marked on brass cap,



and raise a mound of stone 3 ft. base, 2 ft. high, W. of cor.

From this cor. a tent house brs. S. 83° E.

Land, mountainous and rolling.

Soil, sandy and rocky, 2nd and 4th rate.

Undergrowth, greasewood, palo verde, mesquite, catclaw and cactus.

No timber.

## 8. Subdivision of Township 12 North, Range 7 West


Chains.

- East, on a random line, bet. secs. 26 and 35.  
 40.00 Set temp.  $\frac{1}{4}$  sec. cor.  
 79.92 Intersect N. and S. line, 9 lks. S. of the cor. of secs. 25, 26, 35 and 36.  
 Thence,  
 S.  $89^{\circ}56'$  W., on a true line, bet. secs. 26 and 35.  
 Over rolling land, thru. scattering brush.  
 1.30 Three strand wire fence, brs. N. and S. Enter Geo. Phippeny's pasture, the north side of which is 3 chs. N. of line.  
 20.40 Wire fence, brs. N. and S. Leave Geo. Phippeny's pasture. Enter dense brush, brs. N. and S.  
 23.50 Wash, 5 lks. wide, 1 ft. deep, course SW.  
 39.96 Set an iron post, 3 ft. long, 1 in. in diam., 26 ins. in the ground, for  $\frac{1}{4}$  sec. cor., marked on brass cap,  
 S 26  
 S 35  
 1915  
 Dig pits 18x18x12 ins., E. and W. of post, 3 ft. dist., and raise a mound of earth  $3\frac{1}{2}$  ft. base,  $1\frac{1}{2}$  ft. high, N. of cor.  
 58.60 S. fork of Santa Maria river, (dry) 120 lks. wide, course NW.  
 63.60 Old road brs. NW and SE.  
 69.00 Wash, 2 ft. deep, 20 lks. wide, course NW.  
 71.65 Wash, 12 lks. wide, 2 ft. deep, course NW.  
 75.00 Leave rolling land, and ascend 70 ft. over rocky, mountainous E. slope.  
 79.92 The cor. of secs. 26, 27, 34 and 35, at rim of steep slope brs. NW and SW.  
 Land, rolling and mountainous.  
 Soil, sandy loam in the rolling land, rocky in mountainous land; 2nd and 4th, rate.  
 Undergrowth, dense mesquite, catclaw and greasewood.  
 No timber.
- 
- N.  $0^{\circ}1'$  W., bet. secs. 26 and 27.  
 Over mountainous land, thru. scattering brush, over granite boulders.  
 Along E. slope, near rim of steep slope, brs. NW and SW.  
 1.20 Rim of steep slope, brs. NW and SE. Descend over NE slope to  
 9.15 Foot of slope. Thence over level bottom land, covered with mesquite brush, bearing NW and SE.  
 13.42 Wash, 2 ft. deep, 8 lks. wide, course NW.  
 21.20 Old road brs. WNW. and ESE.  
 28.30 Enter south fork of Santa Maria river, 4 ft. deep, course N.  $70^{\circ}$  W. Thence across dry bed of same.  
 30.30 Leave river bed. Ascend 80 ft. over gradual SW. slope.  
 40.00 Set an iron post 3 ft. long, 1 in. in diam., 26 ins. in the ground, for  $\frac{1}{4}$  sec. cor., marked on brass cap,  
 S 27 | S 26  
 1915  
 and raise a mound of stone 2 ft. base,  $1\frac{1}{2}$  ft. high, W. of cor.  
 Ascend.  
 40.30 Spur, slopes N.  $70^{\circ}$  W.  
 Descend 60 ft., over NNE. slope.  
 46.50 Wash, 12 lks. wide, 1 ft. deep, course W. Ascend 85 ft. over SW. slope, to  
 54.55 Spur, slopes N.  $70^{\circ}$  W. Extends 4 chs. W.  
 Corral of O. X. Ranch, brs. S.  $82^{\circ}$  W. about 15 chs. dist.  
 Descend 90 ft. over NE. slope.  
 65.20 Wash, 50 lks. wide, course SW.  
 Ascend 155 ft. over SE. slope.  
 80.00 Set an iron post 3 ft. long, 2 ins. in diam., 24 ins. in

Subdivision of Township 12 North, Range 7 West. 9.

Chains


the ground, for cor. of secs. 22, 23, 26 and 27, marked on brass cap,



and raise a mound of stone 3 ft. base, 2 ft. high, W. of cor.

Land, mountainous.  
Soil, decomposed granite, coarse and sandy, 4th rate.  
Undergrowth, scattering catclaw, mesquite and scrub oak.  
No timber.

- 40.00 N. 89° 56' E., on a random line, bet. secs. 23 and 26. Set temp.  $\frac{1}{4}$  sec. cor.
- 80.12 Intersect N. and S. line, 2 lks. N. of the cor. of secs. 23, 24, 25 and 26.
- Thence,  
S 89° 57' W. on a true line, bet. secs. 23 and 26.  
Over slightly rolling land, thru. very scattering brush. Descend gradually.
- 14.00 Wash, 15 lks. wide, 4 ft. deep, course SSW. Enter adobe flat, brs. N. and S.
- 16.70 Wash, 8 lks. wide, 2 ft. deep, course S.
- 26.30 Leave adobe flat; enter wash, 30 lks. wide, course W. from N. 60° E.
- 28.90 Leave wash, course N. 80° W. from E.
- 33.70 Same wash, course S. 80° W. Ascend gradually over E. slope.
- 40.06 Set an iron post 3 ft. long, 1 in. in diam., 26 ins. in the ground, for  $\frac{1}{4}$  sec. cor., marked on brass cap,



and raise a mound of stone 2 ft. base, 1 1/2 ft. high, N. of cor.

- 48.10 Ascend 35 ft. to Spur, slopes SE. Extends 3 chs. SE. Descend 25 ft. over SW. slope.
- 60.55 Wash, 15 lks. wide, course S. Ascend 130 ft.
- 74.00 Spur, slopes SE. Extends SE. about 8 chs. Descend 70 ft. over granite boulders, over SW. slope.
- 80.12 The cor. of secs. 22, 23, 26 and 27.  
Land, level and rolling.  
Soil, rolling land, rocky, 4th rate; in level land, adobe, 2nd rate.  
Undergrowth, scattering catclaw and mesquite.  
No timber.

- N. 0° 1' W., bet. secs. 22 and 23.  
Over mountainous land.  
Ascend 40 ft. over SW. slope, over granite boulders.
- 3.00 Ridge, brs. NE. and SW. Extends 10 chs. SW. Descend 35 ft., over NW. slope.
- 10.30 Wash, 12 lks. wide, 1 ft. deep, course SW. Ascend 85 ft.
- 15.40 Spur, slopes W. Descend gradually, over rolling N. slope.
- 40.00 Set an iron post 3 ft. long, 1 in. in diam., 26 ins. in the ground for  $\frac{1}{4}$  sec. cor., marked on brass cap,

## 10 Subdivision of Township 12 North, Range 7 West.

Chains.

S22	S23
-----	-----

1915

and raise a mound of stone, 2 ft. base,  $1\frac{1}{2}$  ft. high, W. of cor.  
45.00 Change from N. to NW. slope, and from gradual to a steeper descent.

Descend 50 ft.

55.85 Wash, 20 lks. wide, course S.  $65^\circ$  W.

Ascend 40 ft. over SE. slope.

62.00 Spur, slopes SW. Extends 8 chs. SW. Descend slightly.

65.00 Ascend 200 ft. over S. slope.

80.00 Set an iron post 3 ft. long, 2 ins. in diam., 16 ins. in the ground, supported by a mound of stone, for cor. of secs. 14, 15, 22 and 23, marked on brass cap,

T12N R 7W

S15	S14
-----	-----

S22	S23
-----	-----

1915

and raise a mound of stone, 3 ft. base, 2 ft. high, W. of cor.

Land, mountainous and rolling.

Soil, decomposed granite and rocky, 4th rate.

Undergrowth, scattering greasewood, palo verde, catclaw and cactus.

No timber.

40.00 N.  $89^\circ 57'$  E., on a random line, bet. secs. 14 and 23.  
Set temp.  $\frac{1}{4}$  sec. cor.

79.94 Intersect N. and S line, 2 lks. N. of the cor. of secs. 13, 14, 23 and 24.

Thence,

S.  $89^\circ 58'$  W., on a true line, bet. secs. 14 and 23.

Over mountainous land, thru. scattering brush.

Ascend 140 ft. on SE. slope to

17.00 Ridge, bears SE. &amp; NW. Extends 20 chs. SE. Desc. 100 ft. over SW. slope.

29.25 Wash, 10 lks. wide, course S. Ascend 40 ft.

34.30 Spur, slopes SE. Extends 20 chs. SE. and joins a ridge bearing E. and W. at 4 chs. NW.

Descend 120 ft. to

39.97 Set an iron post 3 ft. long, 1 in. in diam., 26 ins. in the ground, for  $\frac{1}{4}$  sec. cor., marked on brass cap,

$\frac{1}{4}$ S 14
--------------------

S 23

1915

and raise a mound of stone, 3 ft. base, 2 ft. high, N. of cor.

Descend 10 ft. to

43.60 Wash, 25 lks. wide, course SE.

Ascend 125 ft., over SE. slope.

50.00 Spur, slopes ENE. Extends 9 chs. ENE. Descend 30 ft., over NW slope.

63.40 Enter gulch, course NE. from W. Thence ascend in gulch.

66.65 Head of gulch, course E. Ascend 125 ft. along S\* slope of spur.

79.94 The cor. of secs. 14, 15, 22 and 23.

Land, mountainous.


Soil, rocky, 4th rate.

Undergrowth, scattering greasewood, palo verde, catclaw and cactus.

No timber.


Subdivision of Township 12 North, Range 7 West, 11.

- Chains. N. 0° 1'W., bet. secs. 14 and 15.  
Over mountainous land, covered with large boulders, thru. scattering brush. Ascend 30 ft.
- 2.00 Spur, slopes E. Extends E. 3 chs. Descend 180 ft., over NE. slope.
- 12.70 Gulch, 100 lks.wide, course S.60°E. Ascend 100 ft., over S. slope.
- 20.00 Ridge, brs. E. and W. Descend 70 ft. over NE. slope.
- 29.50 Gulch, 20 lks.wide, course E. Ascend 30 ft. over SE. slope.
- 37.50 Spur, slopes E. Descend 5 ft. to
- 40.00 Set an iron post 3 ft. long, 1 in. in diam., on bedrock in a mound of stone for 1/4 sec.cor., marked on brass cap,



and raise a mound of stone, 3 ft. base, 2 ft. high, W. of cor, H.N.B.


- L.E.W. Descend 25 ft.
- 42.20 Wash, 10 lks.wide, course SE. Ascend 70 ft.
- 62.40 Spur, slopes E. Descend 65 ft.
- 68.00 Wash, 4 lks.wide, course E. Ascend 60 ft.
- 73.80 Spur, slopes E. Descend 50 ft.
- 80.00 Set an iron post 3 ft. long, 2 ins. in diam., 24 ins. in the ground, for cor. of secs. 10, 11, 14 and 15, marked on brass cap;



and raise a mound of stone, 3 ft. base, 2 ft. high, W. of cor.

Land, mountainous. Soil, rocky, 4th rate. Undergrowth, scrub oak, catclaw, greasewood and cactus. No timber.

- N.89° 58'E. on a random line, bet. secs. 11 and 14.
- 40.00 Set temp. 1/4 sec.cor.
- 79.94 Intersect N. and S\* line, 30 lks.N. of the cor. of secs. 11, 12, 13 and 14.
- Thence, N.89°49'W., on a true line, bet. secs. 11 and 14. Over mountainous land, thru. scattering brush. Ascend 210 ft., over E. slope.
- 22.50 Ridge, brs. N. and S. Descend 75 ft.
- 27.50 Wash, 10 lks.wide, course S. Ascend 70 ft.
- 33.00 Spur, slopes S. Descend 35 ft.
- 35.80 Wash, 20 lks.wide, course S. Ascend 25 ft. to
- 39.97 Set an iron post 3 ft. long, 1 in. in diam., 26 ins. in the ground for 1/4 sec.cor., marked on brass cap,



and raise a mound of stone 3 ft. base, 2 ft. high, N. of cor. This cor. is set 20 lks. S\* of head of short gulch, course N.80°E.

- 49.00 Spur, slopes S. Descend 160 ft.
- 78.75 Wash, 10 lks.wide, course SE. Ascend 25 ft.

12. Subdivision of Township 12 North, Range 7 West.

Chains.

79.94 The cor. of secs. 10, 11, 14 and 15.  
Land, mountainous.  
Soil, rocky with scanty loam among large boulders, 4th rate.  
Undergrowth, scattering scrub oak, catclaw and cactus.  
No timber.

N.0° 1'W. bet. secs. 10 and 11.  
Over mountainous land, thru. scattering brush.  
Descend 20 ft.

1.50 Wash, 5 lks. wide, course SE.  
Ascend 375 ft., over S. slope, rocky and broken.  
37.25 Spur, slopes SE. Extends SE. about 10 chs.  
Descend 45 ft. to  
40.00 Set an iron post 3 ft. long, 1 in. in diam., 26 ins. in the ground, for 1/4 sec. cor., marked on brass cap,

1/4 S10 | S11

1915

and raise a mound of stone 3 ft. base, 2 ft. high, W. of cor.

Descend 40 ft., over broken N<sup>w</sup> slope.  
59.50 Wash, 10 lks. wide, course S. 55° E.  
Ascend 190 ft., over S. slope.  
70.50 Spur, slopes SW. Descend 20 ft.  
80.00 Set an iron post, 3 ft. long, 2 ins. in diam., 24 ins. in the ground for cor. of secs. 2, 3, 10 and 11, marked on brass cap,

T12N R 7W

S 3 | S 2

S10 | S11

1915

and raise a mound of stone 3 ft. base, 2 ft. high, W. of cor.

Land, mountainous.  
Soil, rocky, 4th rate.  
Undergrowth, scattering greasewood, scruboak, mountain mahogany.  
No timber.

S. 89°49'E., on a random line, bet. secs. 2 and 11.  
40.00 Set temp. 1/4 sec. cor.  
79.80 Intersect N. and S. line, 14 lks. S. of the cor. of secs. 1, 2, 11 and 12.

Thence,  
N.89° 55'W., on a true line, bet. secs. 2 and 11.  
Over mountainous land, thru. scattering brush.  
Ascend 40 ft.

6.20 Ridge, brs. N. and S. Descend 145 ft.  
19.20 Wash, 25 lks. wide, course S. 10° E. Ascend 225 ft. to  
39.90 Set an iron post 3 ft. long, 1 in. in diam., 26 ins. in the ground, for 1/4 sec. cor., marked on brass cap,

1/4 S 2

S 11

1915

and raise a mound of stone 3 ft. base, 2 ft. high, N. of cor.


This cor. is set among large granite boulders. Ascend 15 ft.  
41.00 Ridge, brs. N. and S. Descend 150 ft.

Subdivision of Township 12 North, Range 7 West. 13.

Chains


47.00 Wash, 10 lks. wide, course S. 20° E. Ascend 100 ft.  
 54.00 Ridge, brs. N<sup>o</sup> and S. Descend 100 ft.  
 61.00 Wash, 10 lks. wide, course SE. Ascend 140 ft.  
 79.80 The cor. of secs. 2, 3, 10 and 11.  
 Land, mountainous, covered with large granite boulders.  
 Soil, rocky, with scanty loam, 4th rate.  
 Undergrowth, scattering greasewood, catclaw and cactus.  
 No timber.

N. 0° 1' W., bet. secs. 2 and 3.  
 Over mountainous land, thru. scattering brush.  
 Descend 150 ft., over N. slope.  
 13.20 Wash, 30 lks. wide, course SE.  
 Ascend 250 ft., over rocky S. slope.  
 32.00 Spur, slopes W.; extends W. 4 chs. Descend 30 ft. to  
 40.00 Set an iron post 3 ft. long, 1 in. in diam., 26 ins. in  
 the ground, for  $\frac{1}{4}$  sec. cor., marked on brass cap,



and raise a mound of stone 3 ft. base, 2 ft. high, W. of cor.


Descend 30 ft. over W. slope.  
 50.95 Intersect 3rd. Standard Parallel N. 235 lks. E. of the re-  
 established standard cor. of secs. 34 and 35, a 3 in.  
 iron post, with brass cap, firmly set, marked and wit-  
 nessed as described by the surveyor general.  
 At point of intersection,  
 Set an iron post 3 ft. long, 2 ins. in diam., 24 ins. in  
 the ground, for closing cor. of secs. 2 and 3, marked  
 on brass cap,



and raise a mound of stone, 3 ft. base, 2 ft. high, S. of cor.

Land, mountainous.  
 Soil, rocky with scanty loam, 4th rate.  
 Undergrowth, scattering greasewood, palo verde, scrub  
 oak, and cactus.  
 A small amount of grass.  
 No timber.

From the cor. of secs. 3, 4, 33 and 34 on S<sup>th</sup> bdy. of Tp.,  
 described in Book "A,"  
 N. 0° 2' W., bet. secs. 33 and 34.  
 Over mountainous land, thru. scattering brush.  
 Descend very gradually on irregular NE. slope.  
 49.00 Set an iron post 3 ft. long, 1 in. diam., 26 ins. in the  
 ground, for  $\frac{1}{4}$  sec. cor., marked on brass cap,



and raise a mound of stone 2 ft. base, 1 1/2 ft. high, W. of cor.

Ascend 60 ft. to  
 44.00 Spur, slopes E. from top of rocky hill, near center of sec.  
 33.

## 14. Subdivision of Township 12 North, Range 7 West.

Chains.

- Thence, over broken E. slope, covered with large granite boulders.
- 65.80 Spur, slopes E. Thence over N. slope, covered with scrub oak and hackberry brush, Descend 135 ft. to sec.cor.
- 75.00 Spur, slopes E.
- 80.00 Set an iron post, 3 ft. long, 2 ins. in diam., 24 ins. in the ground, for cor.of secs.27,28,33 and 34, marked on brass cap,

T12N R 7W  
S28 S27

S33 S34  
1915

and raise a mound of stone, 3 ft. base, 2 ft. high, W. of cor.

Land, mountainous.

Soil, scanty loam, among large boulders, 4th rate.

Undergrowth, scattering greasewood, palo verde, cactus, scrub oaks and hackberry.

No timber.

- East, on a random line, bet.secs.27 and 34.
- 40.00 Set a temp. sec.cor.
- 79.90 Intersect N. and S. line, 11 lks.N.of the cor.of secs.26, 27, 34 and 35.
- Thence,  
N.89°55'W., on a true line, bet. secs.27 and 34.
- Over mountainous land, thru.scattering brush.
- Ascend on SE slope, 90 ft.to
- 9.00 Top of hill, 50 ft. above line, brs.N, 2 chs.dist.
- Ascend gradually along S. slope.
- 27.00 Spur slopes N.from SW. Descend 65 ft.
- 33.60 Wash, 10 lks.wide, from SW., course N. for 4.50 chs.; thence NW.
- Ascend 75 ft.to
- 39.95 Set an iron post, 3 ft. long, 1 in. in diam., 26 ins. in the ground for 1/2 sec.cor., marked on brass cap,

S 27

S 34  
1915

and raise a mound of stone 3 ft. base, 2 ft. high, N.of cor. Ascend 55 ft.


- 43.00 Spur, slopes N. Descend 100 ft.
- 48.40 Wash, 10 lks.wide, from SW., course N. for 4 chs., thence NE. Ascend 190 ft.to sec.cor.
- 68.50 Spur, slopes NE. on rocky N. slope.
- 79.90 The cor.of secs.27,28, 33 and 34.
- Land, mountainous.
- Soil, rocky with scanty loam, 4th rate;
- Undergrowth, scattering greasewood, scrub oak and hackberry.
- No timber.

- N.0°2'W., bet. secs. 27 and 28.
- Over mountainous land, thru.scattering brush.
- Descend 90 ft., over N. slope.
- 9.00 Head of wash, course N. 85° W.
- Ascend over rocky SW. slope.
- 20.75 Ridge, brs.NW and SSE. Ascend 240 ft. over E. slope of ridge.

Subdivision of Township 12 North, Range 7 West. 15.

Chains.


29.00 Spur, slopes S<sup>80</sup>E. Descend 90 ft. to  
40.00 Set an iron post 3 ft. long, 1 in. in diam., 26 ins. in the ground for  $\frac{1}{4}$  sec. cor., marked on brass cap,



and raise a mound of stone 3 ft. base, 2 ft. high, W. of cor.

Descend 25 ft. to  
43.00 Head of ravine, course NE. Ascend along broken E. slope of ridge.

80.00 Set an iron post, 3 ft. long, 2 ins. in diam., 24 ins. in the ground for cor. of secs. 21, 22, 27 and 28, marked on brass cap,



and raise a mound of stone 3 ft. base, 2 ft. high, W. of cor.


Land, mountainous.  
Soil, rocky, with scanty loam, 4th rate.  
Undergrowth, scattering greasewood, scrub oak, hackberry and cacti.  
No timber.

40.00 S<sup>89°55'</sup>E., on a random line, bet. secs. 22 and 27.  
Set temp.  $\frac{1}{4}$  sec. cor.  
80.12 Intersect N. and S<sup>\*</sup> line, 7 lks. N. of the cor. of secs. 22, 23, 26 and 27.

Thence,  
N. 89°52' W., on a true line, bet. secs. 22 and 27.  
Over mountainous land, thru. scattering brush. Ascend 10 ft.

4.00 Ridge, brs. NE. and SW. at SW. end of same.

Descend 215 ft., over W. slope to  
40.06 Set an iron post 3 ft. long, 1 in. in diam., 26 ins. in the ground for  $\frac{1}{4}$  sec. cor., marked on brass cap,



and raise a mound of stone 3 ft. base, 2 ft. high, N. of cor.

Descend 45 ft.  
43.50 Enter S. fork of Santa Maria river, course W. from S. 60° E. Channel 10 ft. deep, 150 lks. wide; dry at this time.

55.00 Leave river channel, course S. 75° W. from E. Enter level bottom land.

60.40 Dry channel of Santa Maria river, 100 lks. wide, course N. 60° W. from S. 75° E.  
Leave river bottom. Ascend 350 ft. over rocky broken E. slope.

80.12 The cor. of secs. 21, 22, 27 and 28.  
Land, mountainous.  
Soil, sandy and rocky, 4th rate.  
Undergrowth, scattering greasewood and scrub oaks on mountains, and dense mesquite brush along the river.  
No timber, except scattering cottonwood and mesquite along the river.


16. Subdivision of Township 12 North, Range 7 West.

Chains.

N. 0°2' W., bet. secs. 21 and 22.  
Over mountainous land, thru. scattering brush.  
Ascend 20 ft.

2.70 East end of ridge, brs. E and W.  
Descend 355 ft., over steep rocky N. slope, to  
20.25 Southfork of Santa Maria river, 140 lks. wide, course N. 60° W.  
Dry at this time.

Ascend 225 ft. on SW. slope, to  
40.00 Set an iron post 3 ft. long, 1 in. indiam., 26 ins. in the  
ground, for 1/4 sec. cor., marked on brass cap,




and raise a mound of stone, 3 ft. base, 2 ft. high, W. of cor.

Ascend 80 ft. to  
49.00 Spur, slopes W., near end of same.  
Descend 60 ft., over broken N. slope.

61.70 Wash, 10 lks. wide, course SW.  
Ascend 175 ft., over broken S. slope.

80.00 Set an iron post 3 ft. long, 2 ins. in diam., 26 ins. in  
the ground for cor. of secs. 15, 16, 21 and 22, marked  
on brass cap,



and raise a mound of stone 3 ft. base, 2 ft. high, W. of cor.


Land, mountainous.  
Soil, sandy, scanty among rocks, 4th rate.  
Undergrowth, scattering greasewood, palo verde, scrub  
oaks and cactus.  
No timber.

-----  
40.00 S. 89° 52' E., on a random line, bet. secs. 15 and 22.  
Set temp. 1/4 sec. cor.

80.10 Intersect N. and S. line, 37 lks. S. of the cor. of secs. 14,  
15, 22 and 23.

Thence,  
S. 89° 52' W., on a true line, bet. secs. 15 and 22.  
Over mountainous land, thru. scattering brush and cacti.  
Ascend gradually along broken S. slope.

28.50 Spur, slopes SW. Descend 140 ft., over NW. slope to  
40.05 Set an iron post 3 ft. long, 1 in. in diam., 26 ins. in  
the ground for 1/4 sec. cor., marked on brass cap,



and raise a mound of stone 2 ft. base, 1 1/2 ft. high, N. of cor.

Descend 75 ft., over W. slope.  
44.00 Head of wash, 5 lks. wide, course SW. Descend 20 ft. over  
SW. slope,

58.00 Wash, 8 lks. wide, course SW. near head. Ascend 40 ft.

60.70 Short spur, slopes S. Descend 60 ft.

63.20 Wash, 5 lks. wide, course SW. from N. near head. Ascend 110  
ft.


72.50 Short spur, slopes S. Ascend. along S. slope, to

Subdivision of Township 12 North, Range 7 West, 17.


Chains.

80.10 The cor. of secs. 15, 16, 21 and 22.  
 Land, mountainous.  
 Soil, sandy and rocky, 4th rate.  
 Undergrowth, scattering greasewood, palo verde, scrub oak  
 and cactus.  
 No timber.

N.0°2'W., bet. secs. 15 and 16.  
 Over mountainous land, thru. scattering brush.  
 Ascend 175 ft., on S. slope to  
 8.00 Ridge brs. E and W. Descend 60 ft. over rocky W. slope.  
 26.50 Wash, 3 lks. wide, course SW. Ascend 50 ft. on S. slope  
 40.00 Set an iron post, 3 ft. long, 1 in. in diam., 26 ins. in  
 the ground for  $\frac{1}{4}$  sec. cor., marked on brass cap,




and raise a mound of stone 3 ft. base, 2 ft. high, W.  
 of cor.  
 Ascend 480 ft. on rocky S. slope.  
 75.20 Top of rocky peak.  
 Descend 300 ft. on broken N. slope, 300 ft. to  
 80.00 Set an iron post 3 ft. long, 1 in. in diam., 24 ins. in  
 the ground for cor. of secs. 9, 10, 15 and 16, marked on  
 brass cap,



and raise a mound of stone, 3 ft. base, 2 ft. high,  
 W. of cor.  
 Land, mountainous.  
 Soil, rocky, with scanty loam, 4th rate.  
 Undergrowth, scattering greasewood, scrub oak and cacti.  
 No timber.

N.89°52'E., on a random line, bet. secs. 10 and 15.  
 40.00 Set ~~tamp.~~  $\frac{1}{4}$  sec. cor.  
 80.18 Intersect N. and S<sup>s</sup> line, 7 lks. S. of the cor. of secs. 10,  
 11, 14 and 15.  
 Thence,  
 S.89°49'W., on a true line, bet. secs. 10 and 15.  
 Over mountainous land, thru. scattering brush.  
 Ascend gradually on rocky N. slope, nearly parallel with  
 a wash, course E. about 2 chs. N. of line.  
 25.00 Rocky ridge, brs. S.70°E. and N.60°W. Descend gradually  
 over rolling S. slope.  
 40.09 Head of wash, 10 lks. wide, course SE., Set an iron post,  
 3 ft. long, 1 in. in diam., 26 ins. in the ground, for  
 $\frac{1}{4}$  sec. cor., marked on brass cap,



and raise a mound of stone 2 ft. base, 1  $\frac{1}{2}$  ft. high, N.  
 of cor.  
 Ascend 25 ft., over rolling SE. slope, to  
 62.40 Same ridge, brs. NE. and SW. Descend along broken N. slope,

18. Subdivision of Township 12 North, Range 7 West.

Chains

80.18 The cor. of secs. 9, 10, 15 and 16.  
Land, mountainous.  
Soil, rocky, with scanty loam, 4th rate.  
Undergrowth, scattering greasewood, hackberry and cacti.  
No timber.

N. 0° 2' W., bet. secs. 9 and 10.  
Over mountainous land, thru scattering brush.  
Descend 335 ft., over N. slope, to

16.80 Wash, 4 lks. wide, course NW. Descend gradually, over rolling NW slope.

29.20 Wash, 5 lks. wide, course NW. Thence along rolling W. slope.

40.00 Set an iron post 3 ft. long, 1 in. indiam., 26 ins. in the ground, for  $\frac{1}{4}$  sec. cor., marked on brass cap,

S 9 | S 10  
1915

and raise a mound of stone 2 ft. base, 1 1/2 ft. high, W. of cor.

Descend 20 ft. to

42.50 Wash, 12 lks. wide, course W.  
Ascend, 30 ft., over rocky S. slope.

55.00 Low spur, slopes W.  
Descend 35 ft.

60.00 Wash, 15 lks. wide, course SW. Ascend over rolling SW. slope.

61.50 Wash, 3 lks. wide, from N. 20° E., course SW.

77.60 Wash, 3 lks. wide, course W.

80.00 Set an iron post 3 ft. long, 2 ins. in diam., 24 ins. in the ground, for cor. of secs. 3, 4, 9 and 10, marked on brass cap,

T12N R 7W  
S 4 | S 3  
-----  
S 9 | S 10  
1915

and raise a mound of stone 3 ft. base, 2 ft. high, W. of cor.

Land, mountainous and rolling.

Soil, in mountainous land, rocky, 4th rate; in rolling, sandy loam, 2nd rate.

Undergrowth, scattering greasewood, hackberry and cactus.  
No timber.

N. 89° 49' E., on a random line, bet. secs. 3 and 10.

40.00 Set temp.  $\frac{1}{4}$  sec. cor.

80.14 Intersect N. and S. line, 4 lks. S. of the cor. of secs. 2, 3, 10 and 11.

Thence,

S. 89° 47' W. on a true line, bet. secs. 3 and 10.

Over mountainous land, thru scattering brush.

Ascend 90 ft., over broken E. slope.

9.80 Short spur, slopes S. Descend gradually over broken S. slope, to

40.07 Set an iron post 3 ft. long, 1 in. in diam., 26 ins. in the ground, for  $\frac{1}{4}$  sec. cor., marked on brass cap,

$\frac{1}{4}$  S 3  
-----  
S 10  
1915

and raise a mound of stone, 2 ft. base, 1 1/2 ft. high, N. of cor., from which a cross (x) on a granite bluff

Subdivision of Township 12 North, Range 7 West. 19.


Chains.

10 ft. high, extending E. and NW., facing S. and SW., brs. N. 65°E., 9 lks. dist., marked with B O beside the cross. Marks 4 ft. above base of bluff.

- Ascend gradually along broken NE slope.
- 54.50 Ridge brs. NW and SE.
- Descend SW. slope 300 ft. to
- 72.50 Wash, 4 lks. wide, course SW. near head. Descend over rolling SW. slope.
- 80.14 The cor. of secs. 3, 4, 9 and 10.
- Land, mountainous and rolling.
- Soil, rocky and coarse, 2nd and 4th rate.
- Undergrowth, very scattering greasewood and hackberry.
- No timber.


N. 0° 2' W., bet. secs. 3 and 4.  
Over mountainous land, thru. very scattering brush.  
Ascend 450 ft., over SW. and S. slope.

- 34.00 Short spur, slopes west. Descend 75 ft.
- 39.00 Head of ravine, course W. Ascend 15 ft. to
- 40.00 On top of ridge, brs. N. 15° W. and S. 25° E., set an iron post, 3 ft. long, 1 in. in diam., 26 ins. in the ground, for 1/4 sec. cor., marked on brass cap,



and raise a mound of stone, 3 ft. base, 2 ft. high, W. of cor.

- Ascend 325 ft. along E. slope of ridge, near top.
- 51.30 Intersect 3rd. Standard Parallel N., 235 lks. E. of the re-established standard cor. of secs. 33 and 34, a 3 in. iron post, with brass cap, firmly set, marked and witnessed as described by the surveyor general.
- At point of intersection,
- Set an iron post, 3 ft. long, 2 ins. in diam., 24 ins. in the ground, for closing cor. of secs. 3 and 4, marked on brass cap,



and raise a mound of stone, 3 ft. base, 2 ft. high, S. of cor.

Land, mountainous.  
Soil, rocky, 4th rate.  
Undergrowth, very scanty greasewood, scrub oak, hackberry and cactus.  
No timber.

L.E. W.

H.N.B.  
From the cor. of secs. 4, 5, 32 and 33 on S. bdy. of Tp. described in Book "A,"  
N. 0° 2' W., bet. secs. 32 and 33.

- Over mountainous land, thru. scattering brush.
- Descend 240 ft. on NE slope, over large granite boulders.
- 18.40 Wash, 20 lks. wide, course NW.
- 19.40 Wash, 20 lks. wide, course W.
- Ascend 35 ft. to
- 26.70 Spur, slopes SW. Extends 4 chs. SW.
- Ascend 120 ft. on SW. slope.
- 39.00 Ridge, brs. E. and W., extends 2 chs. W. Descend 10 ft. on N. slope to
- 40.00 Set an iron post 3 ft. long, 1 in. in diam., 26 ins. in the ground, for 1/4 sec. cor., marked on brass cap,

## 20. Subdivision of Township 12 North, Range 7 West.

Chains.

S32	S33
-----	-----

1915

and raise a mound of stone 3 ft. base, 2 ft. high, W. of cor.

Descend 330 ft. on NW. slope.

- 55.00 Wash, 20 lks. wide, course WNW. Ascend 50 ft.  
 59.25 Spur, slopes NW. Extends 6 chs. NW. Descend 50 ft.  
 62.40 Wash, 40 lks. wide, course NW. Ascend 40 ft. over SW. slope.  
 65.65 Spur, slopes NW. Descend 100 ft. to  
 72.86 Wash, 20 lks. wide, course W. Ascend 60 ft. over NW. slope.  
 76.10 Spur, slopes NW. Descend 60 ft. over NE. slope.  
 79.75 Wash, 20 lks. wide, course W.; ascend.  
 80.00 Set an iron post 3 ft. long, 2 ins. in diam., 12 ins. in the ground, supported by a mound of stone for cor. of secs. 28, 29, 32 and 33, marked on brass cap,

T12N R 7W

S29	S28
-----	-----

S32	S33
-----	-----

1915

and raise a mound of stone, 3 ft. base, 2 ft. high, W. of cor.

Land, mountainous.

Soil, rocky, 4th rate.

Undergrowth, catclaw, greasewood and cactus.

No timber.

East, on a random line, bet. secs. 28 and 33.

- 40.00 Set temp.  $\frac{1}{4}$  sec. cor.  
 79.74 Intersect N. and S. line, 2  $\frac{3}{4}$  lks. S. of the cor. of secs. 27, 28, 33 and 34.  
 Thence,  
 S 89°50' W., on a true line, bet. secs. 28 and 33.  
 Over mountainous land, thru scattering brush.  
 Ascend 15 ft. to  
 2.50 Spur, slopes N. Extends N. 2 chs. Descend 40 ft.  
 4.95 Wash, 10 lks. wide, course NW. Ascend 65 ft.  
 14.00 Spur, slopes NW. Descend 70 ft.  
 20.45 Wash, 30 lks. wide, course NW. Ascend 60 ft.  
 29.50 Ridge, brs. SE. and NW. Descend 110 ft.  
 39.66 Wash, 30 lks. wide, course NW. Ascend 25 ft.  
 39.87 Set an iron post 3 ft. long, 1 in. in diam., 26 ins. in the ground for  $\frac{1}{4}$  sec. cor., marked on brass cap,

S 28	
------	--

S 33	
------	--

1915

and raise a mound of stone, 2 ft. base, 1  $\frac{1}{2}$  ft. high, N. of cor. Ascend 25 ft. to

- 41.70 Spur, slopes NW. Descend 125 ft.  
 47.65 Wash, 100 lks. wide, course NW. Ascend 70 ft.  
 53.60 Spur, slopes NW. Descend 140 ft.  
 61.37 Wash, 30 lks. wide, course NW. Ascend 35 ft.  
 70.50 Spur, slopes N. Descend 60 ft.  
 79.74 The cor. of secs. 28, 29, 32 and 33.

Land, mountainous.

Soil, rocky, 4th rate.

Undergrowth, scattering catclaw and greasewood.


No timber.

Subdivision of Township 12 North, Range 7 West. 21.

Chains



N.0°2'W. bet.secs.28 and 29.  
Over mountainous land, thru scattering brush.  
Ascend 70 ft.

- 5.40 End of spur, sloping W. Descend 115 ft.
- 13.10 Wash, 20 lks.wide, course NW. Ascend 115 ft.
- 25.10 Spur, sloping W.Extends 2 chs.W. Descend 75 ft.
- 30.00 Wash, 20 lks.wide, course SW. Ascend 30 ft. over SW.slope.  
to
- 40.00 Set an iron post 3 ft. long, 1 in. in diam., 26 ins. in  
the ground for  $\frac{1}{4}$  sec.cor., marked on brass cap,



and raise a mound of stone 3 ft. base, 2 ft. high,W.of cor.

- 41.50 Wash,10 lks.wide,,course SW. Ascend SW. slope.
- 48.30 Wash, 50 lks.wide, course SW.  
Ascend 130 ft. over S.,slope.
- 80.00 Set an iron post 3 ft. long, 2 ins. in diam., 10 ins. in  
the ground, supported by a mound of stone, for cor.of  
secs. 20,21,28 and 29, marked on brass cap,




and raise a mound of stone, 3 ft. base, 2 ft. high,W.of cor.

Land, mountainous.  
Soil, rocky, 4th rate.  
Undergrowth, scattering catclaw and scrub oak.  
No timber.

- 40.00 N.89°50'E; on a random line, bet. secs.21 and 28.  
Set temp. $\frac{1}{4}$  sec.cor.
- 79.90 Intersect N. and S. line, 40 lks.N.of the cor.of secs.21,  
22,27 and 28.

Thence,  
N.89°53'W., on a true line, bet. secs.21 and 28.  
Over mountainous land, thru scattering brush.  
Ascend 40 ft.

- 5.00 Ridge, brs.NE and SW. joining another ridge, bearing E.  
and W.at about 4 chs.NE.  
Descend 125 ft. on NW. slope.
- 15.55 Gulch, 16 lks.wide, course SW. near head. Ascend 100 ft.  
over SW. slope.
- 19.80 Spur, slopes SW. Thence descend 180 ft.along SW.slope of  
ridge.
- 39.95 Set an iron post 3 ft.long, 1 in. in diam., 26 ins. in  
the ground for  $\frac{1}{4}$  sec.cor., marked on brass cap,



and raise a mound of stone, 3 ft. base, 2 ft. high,N.of cor.

- Descend 20 ft.to
- 45.49 Wash, 20 lks.wide, course S. near head. Ascend 10 ft.
- 50.65 Spur, slopes S. Descend 35 ft.
- 56.00 Gulch, course SW. Thence over S. slope of ridge. Ascend 110  
ft. to sec.cor.
- 64.25 Gulch, 10 lks.wide, course S. near head.

22. Subdivision of Township 12 North, Range 7 West.

Chains.

68.35 Wash, 20 lks.wide, course S. near head. Ascend SE.slope.  
79.90 The cor.of secs. 20,21,28 and 29.  
Land, mountainous.  
Soil,rocky and decomposed granite, 4th rate.  
Undergrowth, scattering, greasewood and catclaw.  
No timber.

N.0°2'W., bet. secs..20 and 21.

Over mountainous land, thru.scattering brush.  
Ascend 30 ft. on S. slope.

6.00 Ridge, brs.E. and W. Descend 170 ft. on N. slope.  
16.50 Gulch, 20 lks.wide, course NW. Ascend 30 ft.  
19.80 Spur, slopes NW. Extends 1 chain NW. Descend 225 ft.on  
NW slope.  
32.58 South fork of Santa Maria river, 140 lks.wide, course W.  
Dry at this time.  
Ascend 205 ft. on S. slope, to  
40.00 Set an iron post 3 ft.long, 1 in. in diam., on bed rock,  
supported by a mound of stone, for  $\frac{1}{4}$  sec.cor., marked  
on brass cap,

$\frac{1}{4}$ S20 | S21  
1915

and raise a mound of stone 3 ft. base, 2 ft.high, W.of  
cor.

Ascend 400 ft. over irregular SE.slope.  
80.00 Set an iron post 3 ft.long, 2 ins. in diam., 24 ins. in  
the ground, for cor.of secs.16,17,20 and 21, marked  
on brass cap,

T12N R 7W  
S17 | S16  
-----  
S20 | S21  
1915

and raise a mound of stone 3 ft. base, 2 ft. high,W.  
of cor.

Land, mountainous.  
Soil, rocky, 4th rate..  
Undergrowth, scattering catclaw and scrub oak.  
No timber.

S.89°53'E. on a random line, bet. secs. 16 and 21.

40.00 Set temp. $\frac{1}{4}$  sec.cor.  
79.94 Intersect N. and S<sup>e</sup> line, 9 lks.S.of the cor.of secs.15,  
16, 21 and 22.

Thence,

N.89°57' W., on a true line, bet. secs.16 and 21.  
Over mountainous land, thru. scattering brush.

Descend 120 ft., over SW.slope.  
20.10 Wash, 50 lks.wide, course SE.  
Ascend 175 ft. over E. slope.  
37.40 Spur, slopes S. Descend 10 ft.  
39.97 Set an iron post, 3 ft. long, 1 in. in diam., 26 ins. in  
the ground for  $\frac{1}{4}$  sec.cor., marked on brass cap,

$\frac{1}{4}$ S 16  
-----  
S 21  
1915

and raise a mound of stone 2 ft. base, 1 $\frac{1}{2}$  ft. high,N.  
of cor.

Descend 35 ft.  
46.10 Wash, 30 lks.wide, course S. Ascend 60 ft.to

Subdivision of Township 12 North, Range 7 West.


Chains.

- 55.20 Spur, sloping S. from peak, 300 ft. above line, and N. of line 15 chs. dist. The top of the spur, extends about 2 chs. S. of line. Descend 100 ft.
- 61.20 Wash, 20 lks. wide, course S. Ascend 80 ft.
- 62.75 Spur, slopes S. Extends 2 chs. S. Descend 20 ft.
- 63.80 Wash, 30 lks. wide, course S. Ascend 115 ft.
- 67.85 Spur, slopes S. Descend 100 ft.
- 77.75 Wash, 10 lks. wide, course NW. Ascend 10 ft.
- 79.94 The cor. of secs. 16, 17, 20 and 21.  
Land, mountainous.  
Soil, rocky with scanty loam, among large boulders, 4th rate.  
Undergrowth, very scanty, catclaw, greasewood and cactus.  
No timber.

-----


N. 0° 2' W., bet. secs. 16 and 17.  
Over mountainous land, thru. scattering brush.  
Descend 25 ft.

- 1.40 Wash, 20 lks. wide, course NW. Ascend 110 ft.
- 10.00 Ridge, brs. E. and W. Descend 210 ft. over N. slope.
- 21.50 Wash, 20 lks. wide, course NW.  
Ascend 120 ft. over SW. slope.
- 30.25 Spur, slopes W.; extends 3 chs. W. Descend 10 ft.
- 32.40 Head of draw, course W. Ascend 65 ft. to
- 40.00 Set an iron post 3 ft. long, 1 in. in diam., 26 ins. in the ground for 1/4 sec. cor., marked on brass cap,



and raise a mound of stone, 3 ft. base, 2 ft. high, W. of cor.

- Ascend 25 ft.
- 44.50 Spur, slopes W.  
Descend 160 ft. on N. slope.
- 52.80 Gulch, 50 lks. wide, course W.  
Ascend 60 ft.
- 56.90 Spur, slopes W.  
Descend 90 ft. on N. slope.
- 65.55 Wash, 30 lks. wide, course SW.  
Ascend 70 ft. over S. slope.
- 73.30 Spur slopes W. Descend 25 ft.
- 75.30 Ascend 40 ft., over W. slope, to
- 80.00 Set an iron post, 3 ft. long, 2 ins. in diam., 24 ins. in the ground for cor. of secs. 8, 9, 16 and 17, marked on brass cap,



and raise a mound of stone 3 ft. base, 2 ft. high, W. of cor.

Land, mountainous.  
Soil, rocky, with scanty loam, 4th rate.  
Undergrowth, scattering catclaw, palo verde and scrub oak.  
No timber.

- 40.00 S. 89° 57' E. on a random line, bet. secs. 9 and 16.  
Set temp. 1/4 sec. cor.
- 80.18 Intersect N. and S. line, 19 lks. N. of the cor. of secs. 9, 10, 15 and 16.  
Thence,  
N. 89° 49' W., on a true line, bet. secs. 9 and 16.

24. Subdivision of Township 12 North, Range 7 West.

Chains.

Over mountainous land, thru scattering brush, among large sandstone boulders.

Ascend 40 ft. on broken NE. slope.

13.00 Ridge, bra. NW. and SE.

Descend 425 ft. on broken SW. and S. slope.

29.40 Wash, 20 lks. wide, course SW. near head. Ascend 10 ft.

30.00 Spur, slopes SW. Descend 95 ft., over NW. slope to

40.09 Head of draw, course SW., set an iron post 3 ft. long, 1 in. in diam., 26 ins. in the ground for 1/4 sec. cor., marked on brass cap,

1/4 S 9

S 16

1915

and raise a mound of stone 2 ft. base, 1 1/2 ft. high, N. of cor.

Ascend 35 ft.

54.10 Spur, slopes S. Extends 3 chs. S. Descend 135 ft.

66.30 Wash, 40 lks. wide, course SW. Ascend 140 ft.

69.60 Spur, slopes S. Descend 115 ft. to

80.18 The cor. of secs. 8, 9, 16 and 17.

Land, mountainous.

Soil, rocky with very scanty loam, 4th rate.

Undergrowth, scattering greasewood, catclaw, palo verde and cactus.

No timber.

N. 0° 2' W., bet. secs. 8 and 9,

Over mountainous land, thru very scattering brush.

Descend 100 ft. on NW. slope. over boulders.

10.65 Wash, 20 lks. wide, course SW.

11.74 Wash, 40 lks. wide, course SW. Ascend 150 ft. over S. slope.

20.90 Spur, slopes W.

Descend 80 ft. over NW. slope.

32.95 Gulch, 15 lks. wide, course SW.

Ascend 116 ft.

39.60 Spur, slopes W. Descend N. slope.

40.00 Set an iron post, 3 ft. long, 1 in. in diam., 26 ins. in the ground, for 1/4 sec. cor., marked on brass cap,

1/4 S 8 | S 9

1915

and raise a mound of stone 2 ft. base, 1 1/2 ft. high, W. of cor.

Descend 60 ft.

46.12 Wash, 10 lks. wide, course W. near head. Ascend 145 ft. over S. slope.

H.N.B.

L.E.W.

58.25 Top of ascent, 2 chs. east from top of butte or knob, descending in all directions. Descend 190 ft. over broken NE. slope.

68.40 Ravine 5 lks. wide, course S. 85° W., near head. Ascend 20 ft. along broken W. slope, to

80.00 Set an iron post, 3 ft. long, 2 ins. in diam., 24 ins. in the ground, for cor. of secs. 4, 5, 8 and 9, marked on brass cap,

T12N R 7W

S 5 | S 4

3 8 | S 9

1915

and raise a mound of stone 3 ft. base, 2 ft. high, W. of cor.

Chains. Land, mountainous.  
 Soil, rocky with scanty loam, 4th rate.  
 Undergrowth, scattering, scanty greasewood, palo verde and  
 catclaw.  
 No timber.

S.89°49'E., on a random line, bet. secs. 4 and 9.  
 40.00 Set temp.  $\frac{1}{4}$  sec. cor.  
 79.80 Intersect N. and S. line, 4 lks. N. of the cor. of secs. 3, 4,  
 9 and 10.  
 thence,  
 N.89°47'W., on a true line, bet. secs. 4 and 9.  
 Over mountainous land, thru scattering brush. Descend over  
 rocky SW. slope.  
 10.55 Wash 4 lks. wide, course SW.  
 15.25 Wash, 5 lks. wide, course S. 5° W.  
 26.00 Wash, 6 lks. wide, course S.  
 33.00 Wash, 5 lks. wide, course S.  
 39.90 Set an iron post 3 ft. long, 1 in. in diam., 26 ins. in  
 the ground for  $\frac{1}{4}$  sec. cor., marked on brass cap,

$\frac{1}{4}$ S 4  
 ———  
 S 9  
 1915

and raise a mound of stone 2 ft. base, 1  $\frac{1}{2}$  ft. high, N.  
 of cor.  
 46.10 Wash, 10 lks. wide, course S. from N. 30° E.  
 Ascend 260 ft., over rocky E. slope.  
 67.00 Ridge, brs. N. and S.  
 Descend 300 ft. over rocky W. slope, to  
 79.80 The cor. of secs. 4, 5, 8 and 9.  
 Land, hilly and mountainous.  
 Soil, sandy loam among large boulders; and rocky, 2nd and  
 4th rate.  
 Undergrowth, scattering greasewood, palo verde, catclaw  
 and cactus.  
 No timber.


N. 0° 2' W., bet. secs. 4 and 5.  
 Over mountainous land, thru scattering brush.  
 Ascend broken rocky W. slope.  
 16.50 Wash, 10 lks. wide, course SW. Ascend along E. slope.  
 24.00 Same wash, 5 lks. wide, course S. 5° E., near head.  
 35.00 Ridge, brs. E. and W. 400 ft. above sec. cor. Descend 40  
 ft. to  
 40.00 Set an iron post 3 ft. long, 1 in. in diam., 26 ins. in  
 the ground for  $\frac{1}{4}$  sec. cor., marked on brass cap,

$\frac{1}{4}$ S 5 | S 4  
 1915

and raise a mound of stone 3 ft. base, 2 ft. high, W. of  
 cor.  
 Descend 260 ft., over N. slope, to  
 51.05 Intersect 3rd. Std. Par. N., 2.17 chs. E. of the reestablished  
 standard cor. of secs. 32 and 33, a 3 in. iron post, with  
 brass cap, firmly set, marked and witnessed, as de-  
 scribed by the surveyor general. At point of intersec-  
 tion,  
 Set an iron post 3 ft. long, 2 ins. in diam., 24 ins. in  
 the ground, for closing cor. of secs. 4 and 5, marked  
 on brass cap,

## 26. Subdivision of Township 12 North, Range 7 West.

Chains.



and raise a mound of stone 3 ft. base, 2 ft. high, S. of cor.

Land, mountainous.

Soil, rocky, 4th rate.

Undergrowth, scattering greasewood, cactus, catclaw and hackberry.

No timber.

L.E.W.

H.N.B.

From the co. of secs. 5, 6, 31 and 32 on S. bdy. of Tp., described in Book "A,"

N. 0° 3' W., bet. secs. 31 and 32.

Over mountainous land, thru scattering brush.

Descend 35 ft.

3.60 Wash, 10 lks. wide, course W. Ascend 20 ft.

12.50 Spur, slopes W.

Descend 40 ft.

18.55 Wash, 15 lks. wide, course W.

Ascend 116 ft.


26.30 Low ridge, brs. NW. and SE.

Descend 155 ft. on NE. slope.

35.05 Wash, 20 lks. wide, course NW.

Ascend 80 ft., on SW. slope to

40.00 Set an iron post, 3 ft. long, 1 in. in diam., 22 ins. in the ground, supported by a mound of stone, for  $\frac{1}{4}$  sec. cor., marked on brass cap,



1915

and raise a mound of stone 3 ft. base, 2 ft. high, W. of cor.

40.50 Spur, slopes W.

Descend 115 ft.

49.75 Gulch, course NW. Ascend 170 ft.

73.80 Spur, slopes W.

Descend 140 ft. on NW. slope, to

80.00 Set an iron post 3 ft. long, 2 ins. in diam., 24 ins. in the ground for cor. of secs. 29, 30, 31 and 32, marked on brass cap,

T12N R 7W

S30 S29

S31 S32

1915

and raise a mound of stone, 3 ft. base, 2 ft. high, W. of cor.

Land, mountainous.

Soil, rocky, 4th rate.

Undergrowth, scattering catclaw, palo verde, cactus and mesquite.

No timber.

40.00 East, on a random line, bet. secs. 29 and 32.

Set temp.  $\frac{1}{4}$  sec. cor.

79.94 Intersect N. and S. line, 25 lks. S. of thd cor. of secs. 28, 29, 32 and 33.

Subdivision of Township 12 North, Range 7 West. 27.

Chains.

Thence,  
 S.89°49'W. on a true line, bet. secs. 29 and 32.  
 Over mountainous land, thru. scattering brush.  
 Descend 40 ft. on SW. slope.

3.30 Wash, 10 lks. wide, course N. from E. Ascend 55 ft.  
 7.10 Spur, slopes N. Descend 40 ft.  
 10.40 Wash, 8 lks. wide, course N.  
 Ascend, 125 ft. on E. slope.

18.00 Top, of spur, slopes NNE. from W. Thence along top of spur.  
 Ascend 40 ft.

33.90 Top of another spur, slopes NW. Descend 80 ft., over SW.  
 slope, to

39.97 Set an iron post 3 ft. long, 1 in. in diam., 26 ins. in  
 the ground for  $\frac{1}{4}$  sec. cor., marked on brass cap,

S 29

---

S 32  
 1915

and raise a mound of stone, 3 ft. base, 2 ft. high, N.  
 of cor.

Descend 40 ft.

41.05 Gulch, 50 lks. wide, stream of water in same, 2 lks. wide,  
 course NW.

44.50 Same gulch, and stream of water, 2 lks. wide, course SW.  
 Ascend 32 ft.

46.40 Low spur, slopes SW. Descend 46 ft. to

49.10 Same gulch, and stream of water, 2 lks. wide, course NW.  
 Ascend 75 ft. on E. slope.

52.40 Spur, slopes N. Descend 115 ft.

59.25 Gulch, 6 lks. wide, course N. Ascend 84 ft.

63.40 Top of ascent brs. N. and S. sloping N. Descend 15 ft.

65.44 Gulch, course NE. Ascend 20 ft.

75.80 Low ridge, brs. N. and S. Descend 35 ft. to

79.94 The cor. of secs. 29, 30, 31 and 32.  
 Land, mountainous.  
 Soil, rocky with little loam, 4th rate.  
 Undergrowth, scattering catclaw, palo verde and cacti.  
 No timber.

H.W.B.

-----

L.E.W.

West, on a random line, bet. secs. 30 and 31.

40.00 Set temp.  $\frac{1}{4}$  sec. cor.

85.85 Intersect W bdy. of Tp., 25 lks. S. of the cor. of secs. 30  
 and 31, described in Book "A."

Thence,  
 S.89°50'E., on a true line, bet. secs. 30 and 31.  
 Over mountainous land, thru. scattering brush.  
 Ascend 95 ft. on W. slope.

27.50 Short spur, slopes S. Descend 20 ft.

32.50 Wash, 10 lks. wide, course SW. from N. 85° E. Thence along  
 S. side of same wash.

45.85 Set an iron post 3 ft. long, 1 in. in diam., 26 ins. in  
 the ground, for  $\frac{1}{4}$  sec. cor., marked on brass cap,

S 30

---

S 31  
 1915

and raise a mound of stone, 2 ft. base, 1  $\frac{1}{2}$  ft. high, N.  
 of cor.

47.00 The above noted wash, brs. N. 50 lks. dist., course W. from  
 NE.

Ascend 315 ft., over W. slope.

70.00 Slope changes from W. to NW. Ascend 215 ft. over NW. slope.

28. Subdivision of Township 12 North, Range 7 West.

Chains.

85.85 The cor. of secs. 29, 30, 31 and 32.  
 Land, mountainous.  
 Soil, rocky with scanty loam, 4th rate:  
 Undergrowth, scanty greasewood, palo verde, catclaw, and  
 cactus.  
 No timber.

L.E.W.

H.N.B.  
 N. 0° 3' W., bet. secs. 29 and 30.  
 Over mountainous land, thru. scattering brush.  
 Descend.

1.30 Wash, 8 lks. wide, course NW. Ascend 55 ft. on SW. slope,  
 15.30 Ridge, brs. NW and SE. Thence along top of spur, extend-  
 ing N. from ridge.  
 Descend 425 ft.  
 32.25 Wash, 25 lks. wide, course W. Ascend 30 ft. over S. slope,  
 to  
 40.00 Set an iron post, 3 ft. long, 1 in. in diam., 26 ins. in the  
 ground, for  $\frac{1}{4}$  sec. cor., marked on brass cap,

$\frac{1}{4}$ S30 | S29

1915

and raise a mound of stone, 3 ft. base, 2 ft. high, W.  
of cor.

Ascend 190 ft. on SE. slope.  
 55.00 Spur, slopes W. Descend 65 ft.  
 60.30 Gulch, course NW. Ascend 55 ft.  
 66.10 Descend 70 ft. to  
 68.90 Gulch, course W. Ascend 250 ft.  
 79.50 Ridge, brs. E and W. Descend slightly on N. slope.  
 80.00 Set an iron post 3 ft. long, 2 ins. in diam., 24 ins. in  
 the ground for cor. of secs. 19, 20, 29 and 30, marked  
 on brass cap,

T12N R 7W  
S19 S20

S30 | S29  
1915

and raise a mound of stone, 3 ft. base, 2 ft. high, W.  
of cor.

Land, mountainous.  
 Soil, rocky, with scanty loam, 4th rate.  
 Undergrowth, scattering catclaw, palo verde, mesquite and  
 cactus.  
 No timber.

H.N.B.

L.E.W.  
 N. 89° 49' E., on a random line, bet. secs. 20 and 29.

40.00 Set temp.  $\frac{1}{4}$  sec. cor.  
 80.12 Intersect N. and S. line, 2 lks. S. of the cor. of secs. 20,  
 21, 28 and 29.

Thence,  
 S. 89° 48' W., on a true line, bet. secs. 20 and 29.

Over mountainous land, thru. scattering brush. Along  
 broken rough S. slope. Ascend 100 ft. to  
 40.06 Set an iron post, 3 ft. long, 1 in. in diam., 12 ins. in  
 the ground, in a mound of stone and earth, 3 ft. base,  
 14 ins. high for  $\frac{1}{4}$  sec. cor., marked on brass cap,

$\frac{1}{4}$ S 20.

S 29.  
1915

Subdivision of Township 12 North Range 7 West 29.

Chains.

and raise a mound of stone 3 ft. base, 2 ft. high, N. of cor.; from which;  
A cross (x) on a granite boulder 3x2x1 1/2 ft. above ground, brs. N. 45° W., 6 lks. dist., marked with B O 20 beside the cross.

71.00 Descend along S. slope, 200 ft. to Ridge, brs. NE. and S. 85° W. Descend 65 ft. to  
80.12 The cor. of secs. 19, 20, 29 and 30.  
Land, mountainous.  
Soil, rocky and snady, 4th rate.  
Undergrowth, greasewood, palo verde, catclaw and cactus.  
No timber.

-----  
N. 89° 50' W., on a random line, bet. secs. 19 and 30.  
40.00 Set temp. 1/4 sec. cor. on line.  
85.80 Intersect W. bdy. of Tp., 9 lks. S. of the cor. of secs. 19 and 30, described in Book "A." Thence, S. 89° 46' E., on a true line, bet. secs. 19 and 30.  
Over level bottom land, thru. dense brush.  
10.30 Enter dry channel of South fork of Santa Maria river, 3 ft. deep, course SW.  
13.40 Leave river channel. Thence over level bottom land, brs. NE. and SW.  
17.40 Leave level bottomland, and dense brush. Enter mountainous land and scattering brush, bearing NE. and SW.  
Ascend 110 ft. over NW. slope.  
25.00 Short spur, slopes N. Thence over broken N. slope to  
33.00 Spur, slopes N. Descend 85 ft.  
40.55 Wash, 30 lks. wide, course N. 5° W.  
Ascend 60 ft. to  
45.80 Set an iron post 3 ft. long, 1 in. in diam., 26 ins. in the ground for 1/4 sec. cor., marked on brass cap,

1/4 S 19  
-----  
S 30  
1915

and raise a mound of stone 2 ft. base, 1 1/2 ft. high, N. of cor.  
Ascend 110 ft. over NW. slope.  
56.00 Spur, slopes NW. from end of ridge, bearing E. and W. Thence over very rocky N. slope of said ridge. Ascend 350 ft. to  
85.80 The cor. of secs. 19, 20, 29 and 30.  
Land, mountainous and level.  
Soil, in bottom land, coarse, sandy and gravelly; in mountainous land, rocky with scanty loam, 2nd and 4th rate.  
Undergrowth, in bottom land, dense mesquite, catclaw and arrowweed, in mountainous land, scattering greasewood, palo verde, catclaw and cacti.  
No timber.

-----  
N. 0° 3' W., bet. secs. 19 and 20.  
Over mountainous land, thru. scattering brush.  
Descend 165 ft., over rocky N. slope.  
9.45 Wash, 5 lks. wide, course W. Ascend 165 ft.  
19.25 Long rocky spur, slopes NW.  
Descend 150 ft. on rocky N. slope.  
26.25 Wash, 10 lks. wide, course W.  
Ascend 80 ft., over very rocky S. slope.  
30.00 Spur, slopes W.  
Descend 90 ft. to  
40.00 Set an iron post 3 ft. long, 1 in. in diam., 26 ins. in the ground, for 1/4 sec. cor., marked on brass cap,

1/4 S 19 | S 20  
-----  
1915

## 30 Subdivision of Township 12 North, Range 7 West.

Chains.

- and raise a mound of stone, 3 ft. base, 2 ft. high, W. of cor.  
 Descend 180 ft.  
 54.10 Santa Maria river channel, 40 lks. wide, in box canyon, 70 ft. deep, course N. 60° W. Running water 6 ins. deep, 10 lks. wide.  
 Ascend 140 ft. over broken rocky SW. slope.  
 64.70 Spur, sloping W. Descend 100 ft.  
 69.80 Wash, 3 lks. wide, course W. Ascend 150 ft.  
 80.00 On rocky spur, sloping S. 80° W., set an iron post, 3 ft. long, 2 ins. in diam., 24 ins. in the ground, for cor. of secs. 17, 18, 19 and 20, marked on brass cap,

T12N R7 W

S18 | S17

S19 | S20

1915

and raise a mound of stone 3 ft. base, 2 ft. high, W. of cor.  
 Land, mountainous.  
 Soil, rocky, with scanty loam of decomposed granite, 4th rate.  
 Undergrowth, scattering rabbit brush, palo verde, cacti and greasewood.  
 No timber.

- 40.00 N. 89° 48' E. on a random line, bet. secs. 17 and 20.  
 Set temp. sec. cor.  
 80.10 Intersect N. and S. line, 37 lks. N. of the cor. of secs. 16, 17, 20 and 21.  
 Thence,  
 N. 89° 56' W., on a true line, bet. secs. 17 and 20.  
 Over mountainous land, covered with granite boulders, thru. scattering brush.  
 Ascend 60 ft.  
 7.30 Rocky ridge, brs. SE. and NW. for 3 chs., thence SW. Descend 130 ft. along S. slope.  
 23.10 Same ridge, brs. NE. and SW.  
 Descend 200 ft. over W. slope.  
 33.50 Wash, 10 lks. wide, course SW.  
 Ascend 75 ft. to  
 40.05 Point of rocky spur, sloping S., set an iron post, 3 ft. long, 1 in. in diam., 26 ins. in the ground, for 1/4 sec. cor., marked on brass cap,

S 17

S 20

1915

- and raise a mound of stone 2 ft. base, 1 1/2 ft. high, N. of cor.  
 Descend 300 ft. over broken SW. slope.  
 70.00 Wash, course S. for 300 lks., thence SW.  
 Ascend 115 ft. over rocky SE. slope.  
 77.00 Ridge, brs. NE. and SW.  
 Descend 50 ft. to  
 80.10 The cor. of secs. 17, 18, 19 and 20.  
 Land, mountainous.  
 Soil, rocky, covered with large granite boulders, 4th rate.  
 Undergrowth, scattering suharas, palo verde and cactus/  
 No timber.
-

Subdivision of Township 12 North, Range 7 West

Chains.

- 40.00 N.89° 46' W., on a random line, bet. secs.18 and 19. Set temp.  $\frac{1}{4}$  sec.cor.
- 85.74 Intersect W<sup>o</sup> bdy.of Tp. 26 lks.N.of the cor.of secs.18 and 19, described in Book "A."  
Thence,  
S.89°57'E., on a true line, bet. secs.18 and 19. Over broken land, thru.scattering brush. Descend 50 ft.
- 4.50 Wash, 20 lks.wide, course S.10° E. Thence over broken S. slope, to
- 15.25 Wash, 150 lks.wide, course S. Ascend 20 ft.
- 18.75 Spur, slopes S. Descend 20 ft.
- 20.00 Wash, 40 lks.wide, course S. Ascend 100 ft.
- 40.00 Ridge, brs.N. and S. Descend on top of spur, slopes E.
- 45.74 Spur turns from W. to S.18° E., set an iron post  $\frac{3}{4}$  ft. long, 1 in. in diam., 26 ins. in the ground, for  $\frac{1}{4}$  sec.cor., marked on brass cap,

$\frac{1}{4}$ S 18

S 19  
1915

and dig pits 18x18x12 ins., E. and W. of post,  $\frac{3}{4}$  ft. dist., and raise a mound of earth,  $3\frac{1}{2}$  ft. base,  $1\frac{1}{2}$  ft. high, N.of cor.

- Thence over broken S. slope.
- 56.00 Spur, slopes S.20°E. Descend 80 ft.
- 60.80 Wash, 10 lks.wide, course S. 20° E. Ascend gradually over broken S. slope, to
- 74.75 Leave broken S slope. Ascend 60 ft. over rocky SW. slope.
- 81.75 End of spur, sloping S. Descend 100 ft.
- 83.60 Wash, 20 lks.wide, course S. Ascend 140ft.over almost perpendicular W. slope.
- 85.74 The cor.of secs.17,18,19 and 20. Land, broken and mountainous. Soil, rocky, with very scanty loam in eastern part;gravelly in western part, 3rd and 4th rate. Undergrowth, scattering greasewood, mesquite, palo verde and cactus. No timber.

- 
- N.0°3'W. bet. secs.17 and 18. Over mountainous land, thru.very scattering brush. Descend 85 ft.,on rocky NW slope.
  - 3.50 Bend in wash, 25 lks.wide,courre S.30°W.from NW. Ascend on SW. slope, 130 ft.to
  - 7.50 Short spur, slopes W. Descend 100 ft.
  - 11.00 Bend in same wash from NW to SW. Thence over broken W. slope.
  - 20.60 Enter level land, bearing NE and SW.
  - 25.50 Wash, 100 lks.wide, course W:
  - 29.00 Leave flat; ascend 70 ft.,over S slope.
  - 35.00 Spur, slopes SW. Descend 40 ft.
  - 38.80 Wash, 10 lks.wide, course SW. for 4 chs.,thence S. Ascend 10 ft.to
  - 40.00 Set an iron post,  $\frac{3}{4}$  ft.long, 1 in. in diam., 26 ins. in the ground, for  $\frac{1}{4}$  sec.cor., marked on brass cap,

$\frac{1}{4}$ S18 | S17

1915


and raise a mound of stone 3 ft.base, 2 ft. high,W.of cor.

- Ascend over SW.slope.
- 45.00 Wash, 15 lks.wide, course SW.

32. Subdivision of Township 12 North Range 7 West

Chains.

- Ascend 75 ft.
- 60.00 Ridge brs.E. and SW. Descend 110 ft.
- 78.90 Wash, 15 lks.wide, course W. Ascend 5 ft.to
- 80.00 Set an iron post 3 ft.long, 2 ins. in diam., 24 ins. in the ground, for cor.of secs. 7,8,17 and 18, marked on brass cap,




and raise a mound of stone, 3 ft. base, 2 ft. high,W.of cor.

Land, mountainous and level.  
Soil,rocky with scanty loam, 4th rate.  
Undergrowth, greasewood, palo verde, catclaw, mesquite and cactus.  
No timber.

- S.89° 56' E., on a random line, bet. secs. 8 and 17.
- 40.00 Set temp.  $\frac{1}{4}$  sec.cor.
- 80.18 Intersect N. and S<sup>a</sup> line, 4 lks.S.of the cor.of secs.8,9, 16 and 17.

Thence,  
N.89°58'W., on a true line, bet. secs.8 and 17.  
Over mountainous land, thru.scattering brush.  
Descend 120 ft. over rocky W. slope.

- 18.00 Wash, 15 lks.wide, course S. Ascend 60 ft.
- 23.50 Ridge, brs.NE and SW.
- Descend 140 ft., over NW. slope, to
- 34.70 Head of ravine, course NW. for 5 chs.}thence W., along N.slope to
- 40.09 Set an iron post, 3 ft.long, 1 in. in diam., 26 ins. in the ground, for  $\frac{1}{4}$  sec.cor., marked on brass cap,



and raise a mound of stone 2 ft. base, 1 $\frac{1}{2}$  ft. high,N.of cor.

- Descend 120 ft.
- 65.00 Enter level land, brs.NE and SW.
- 77.70 Wash, 15 lks.wide, course W.from N.75°E.
- Thence along N. side of wash, continuing over level land.
- 80.18 The cor.of secs.7,8,17 and 18.
- Land, mountainous and level.  
Soil,rocky,with scanty loam, 4th rate.  
Undergrowth, scattering greasewood, palo verde. catclaw, and cactus.  
No timber.

- N.89° 57' W., on a random line, bet. secs.7 and 18.
- 40.00 Set temp.  $\frac{1}{4}$  sec.cor.
- 85.78 Intersect W. bdy.of Tp., 9 lks.N.of the cor.of secs.7 and 18, described in Book "A."
- Thence,  
N.89°59'E., on a true line, bet. secs.7 and 18.  
Over mountainous land, thru.scattering brush. Across top of long spur, sloping S.
- 2.75 Leave top of spur.
- Descend on E. slope 425 ft.
- 10.00 Wash, 10 lks.wide, course S. Ascend 80 ft.to

Subdivision of Township 12 North, Range 7 West. 33.

Chains.

- 13.50 Long spur slopes S. Descend 220 ft. on E. slope.
- 33.40 Wash, 10 lks.wide, course SE. Ascend 85 ft.
- 43.75 Spur, slopes S. Descend 25 ft. to
- 45.78 Set an iron post 3 ft.long, 1 in. in diam., 26 ins. in the ground for  $\frac{1}{4}$  sec.cor., marked on brass cap,

$\frac{1}{4}$ S 7

§ 18  
1915

and raise a mound of stone 2½ ft. base, 1½ ft. high, N. of cor.

- Descend 90 ft.
- 52.70 Wash, 10 lks.wide, in gulch, 20 ft. deep, course S. Enter level land, brs. N. and S.
- 60.35 Wash, 15 lks.wide, in gulch, 20 ft. deep, course S.
- 71.25 Wash, 20 lks.wide, course S. for 2 chs., thence SW.
- 81.40 Same wash, course NW. Leave level land. Ascend 55 ft.
- 82.30 End of short rocky spur, slopes S. Descend 25 ft. to
- 85.78 The cor. of secs. 7, 8, 17 and 18. Land, mountainous and level. Soil, rocky with scanty loam, 4th rate. Undergrowth, scattering greasewood, palo verde, catclaw and cacti. No timber.

N.0°3' W., bet. secs. 7 and 8.  
Over mountainous land, thru scattering brush.  
Ascend 300 ft. on S. slope.  
40.00 Set an iron post 3 ft. long, 1 in. in diam. 26 ins. in the ground for  $\frac{1}{4}$  sec.cor., marked on brass cap,

$\frac{1}{4}$ S 7 | S 8

1915

and raise a mound of stone, 2 ft. base, 1½ ft. high, W. of cor.

- Ascend 70 ft.
- 45.00 Rocky hill. Descend 85 ft.
- 53.25 Wash, 4 lks.wide, course W. Ascend 40 ft.
- 58.50 Spur, slopes W. Descend 30 ft.
- 66.70 Wash, 5 lks.wide, course SW. Ascend 75 ft. over SW. slope.
- 80.00 Set an iron post 3 ft. long, 2 ins. in diam., 24 ins. in the ground, for cor. of secs. 5, 6, 7 and 8, marked on brass cap,

T12N R 7W  
S 6 S 5

S 7 | S 8  
1915

and raise a mound of stone 3 ft. base, 2 ft. high, W. of cor., from which,

A cross (x) on a granite boulder 6x2 ft. in face of mountain, brs. N.38°W., 15 lks. dist., with B O 6 marked beside the cross.

Land, mountainous.  
Soil, rocky, 4th rate.  
Undergrowth, scattering greasewood, palo verde, catclaw and cactus.  
No timber.

## 34 Subdivision of township 12 North, Range 7 West.


Chains.

- S.  $89^{\circ} 58'$  E., on a random line, bet. secs. 5 and 8.  
 40.00 Set temp.  $\frac{1}{4}$  sec. cor.  
 79.82 Intersect N. and S. line, 2 lks. S. of the cor. of secs. 4, 5, 8 and 9.  
 Thence,  
 N.  $89^{\circ} 59'$  W., on a true line, bet. secs. 5 and 8.  
 Over mountainous land, covered with immense granite boulders, thru scattering brush.  
 Descend 15 ft. to  
 0.80 Wash, 12 lks. wide from N., course SE. for 100 lks.; thence SW.  
 Thence over broken rocky S. slope, to  
 5.00 Wash, 3 lks. wide, near head, course S  $10^{\circ}$  E.  
 Ascend 100 ft.  
 15.20 Rocky spur, slopes S.  $10^{\circ}$  E.  
 Descend 115 ft. to  
 25.00 Foot of descent; thence over rolling rocky mesa, bearing N. and S.  
 39.91 Set an iron post 3 ft. long, 1 in. in diam., 26 ins. in the ground, for  $\frac{1}{4}$  sec. cor., marked on brass cap,  
 S 5  
 S 8  
 1915  
 and raise a mound of stone 3 ft. base, 2 ft. high, N. of cor.  
 Leave mesa; descend 50 ft.  
 46.60 Wash, 5 lks. wide, course S.  
 Ascend 160 ft. over rocky E. slope.  
 68.80 Ridge, brs. N. and S.  
 Descend 140 ft., over very large granite boulders on NW. slope.  
 79.82 The cor. of secs. 5, 6, 7 and 8.  
 Land, mountainous.  
 Soil, rocky; the western 33.22 chs. has scarcely any loam, being composed of large granite boulders; the eastern 46.60 chs. has sandy loam among the boulders, and produces a scanty growth of grass, especially in the flat areas.  
 Undergrowth, scattering greasewood, palo verde, catclaw, cactus and coarse grass.  
 No timber.
- 
- S.  $89^{\circ} 59'$  W., on a random line, bet. secs. 6 and 7.  
 40.00 Set temp.  $\frac{1}{4}$  sec. cor.  
 85.70 Intersect W. bdy. of Tp., 9 lks. S. of the cor. of secs. 6 and 7, described in Book "A."  
 Thence,  
 S.  $89^{\circ} 57'$  E., on a true line, bet. secs. 6 and 7.  
 Over mountainous land, thru scattering brush.  
 Descend over E. slope.  
 1.70 Wash, 15 ft. deep, 10 lks. wide, course SE.  
 Descend 100 ft., over SE. slope.  
 18.75 Wash, 8 lks. wide, course SE.  
 Ascend 50 ft. to  
 22.00 Spur, slopes SE.  
 Descend 80 ft.  
 26.30 Wash, 5 lks. wide, course S  $10^{\circ}$  E.  
 Ascend 85 ft.  
 29.80 Spur, slopes S  $10^{\circ}$  E.  
 Descend 90 ft.  
 33.50 Wash, 15 lks. wide, course S. Ascend 60 ft.  
 35.35 Spur, slopes S.  
 Descend 40 ft.  
 38.60 Wash, course S. Ascend 80 ft., over broken S. slope, to  
 45.70 Set an iron post 3 ft. long, 1 in. in diam., 26 ins. in the

Subdivision of Township 12 North, Range 7 West. 35.

Chains.

ground for 1/4 sec.cor., marked on brass cap,



and raise a mound of stone 3 ft. base, 2 ft. high, N. of cor.


85.70 Continue over broken S. slope, covered with immense granite boulders. Ascend gradually to the cor. of secs. 5, 6, 7 and 8. Land, mountainous, eastern half not much broken, but covered with large granite boulders. Soil, rocky, among which is a sandy loam, which produces a scanty growth of coarse grass, 4th rate. Undergrowth, scattering greasewood, palo verde, catclaw and cactus. No timber.

N.0° 3' W., bet. secs. 5 and 6.

5.50 Over mountainous land, thru. very scattering brush. Ascend 165 ft. on S. slope. Rocky hill. Highest point is 12 ft. higher, and 30 lks. E. of line at this point. Descend 200 ft. on broken N. slope.

16.50 Head of wash 5 lks. wide, course NW. Ascend 70 ft., over rolling SW. slope, to

40.00 Set an iron post 3 ft. long, 1 in. in diam., 26 ins. in the ground for 1/4 sec. cor., marked on brass cap,



and raise a mound of stone 3 ft. base, 2 ft. high, W. of cor.


Ascend 40 ft.

42.00 Spur, slopes SW. Descend 40 ft.

43.60 Wash, 10 lks. wide, course W. Ascend 100 ft.

49.50 Rocky butte descends in all directions. Descend 50 ft. to

50.91 Intersect 3rd. Standard Parallel North 229 lks. E. of the reestablished ~~sid~~ cor. of secs. 31 and 32, a 3 in. iron post with brass cap, firmly set, marked and witnessed as described by the surveyor general. At point of intersection, Set an iron post 3 ft. long, 2 ins. in diam., 24 ins. in the ground for closing cor. of secs. 5 and 6, marked on brass cap,



and raise a mound of stone, 3 ft. base, 2 ft. high, S. of cor., from which,

A cross (x) on a 6x5x2 ft. above ground, brs. S. 34° E., 9 lks. dist, marked B O 5 beside the cross.

Land, mountainous. Soil, rocky, with scanty loam among the boulders, 4th rate. Undergrowth, scattering greasewood, palo verde, catclaw and cactus. No timber.

L.E.W.

36 Subdivision of Township 12 North, Range 7 West.

chains.

GENERAL DESCRIPTION.

L.E.W. and H.N.B.

In the southeastern part of the township the valley of the south fork of the Santa Maria river, is smooth, rolling land; the remainder of the surface is mountainous, highest along the north boundary.

Running water is found in the south fork of Santa Maria river, near the center of the township and in Lawler Creek, in the northeastern part of the township.

The soil, in the mountainous lands is coarse and rocky, composed largely of decomposed granite, of uncertain and irregular depth. The soil over the greater part of the township would be classed as 3rd and 4th rate.

In the higher portions, and on the north slopes, a scanty growth of coarse grass and weeds afford pasturage for a limited number of animals.

The valley land is a coarse loam, generally, several feet in depth, 1st and 2nd rate, which, with irrigation, will be very productive.

There is no timber, except scattering mesquite along some of the larger water courses. Undergrowth of several varieties is found over the entire township.

One settler is found in sec. 36, and one in sec. 35. Each has house and fences, which are the only improvements except two corrals in sec. 27.

There are no indications of mineral.

The Santa Fe Prescott and Phoenix R.R. passes in a northerly and southerly direction thru. the adjoining township on the east, which is not subdivided at this time. The R.R. is about one mile E. from the E. bdy. of this township. The nearest R.R. station is Hillside, which is located about one mile E. from the NE, cor. of the Tp.

L.E.W. and H.N.B.

Book "N"

BOOK 3286

Group 36 --- Arizona

Township 12 North, Range 7 West

DATE-DIAGRAM

3 RD STANDARD PARALLEL NORTH

3-5-15	6 3-5-15	2-27-15	5 2-27-15	2-27-15	4 2-23-15	2-23-15	3 2-22-15	2-22-15	2 2-21-15	2-21-15	1 2-21-15	2-15-15
3-1-15	7 3-1-15	2-27-15	8 2-26-15	2-23-15	9 2-23-15	2-23-15	10 2-20-15	2-22-15	11 2-22-15	2-21-15	12 2-16-15	2-15-15
3-1-15	18 3-1-15	2-26-15	17 2-26-15	2-23-15	16 2-22-15	2-20-15	15 2-20-15	2-20-15	14 2-18-15	2-16-15	13 2-16-15	2-15-15
3-1-15	19 2-25-15	2-25-15	20 2-25-15	2-22-15	21 2-22-15	2-20-15	22 2-18-15	2-18-15	23 2-18-15	2-16-15	24 2-16-15	2-15-15
2-25-15	30 2-24-15	2-24-15	29 2-24-15	2-21-15	28 2-21-15	2-18-15	27 2-18-15	2-18-15	26 2-15-15	2-16-15	25 2-16-15	2-15-15
2-24-15	31 2-24-15	2-24-15	32 2-21-15	2-21-15	33 2-18-15	2-18-15	34 2-15-15	2-15-15	35 2-16-15	2-16-15	36 2-15-15	2-15-15
	2-24-15		2-24-15		2-24-15 2-15-15		2-15-15		2-15-15		2-15-15	

Lines dated in black were executed by L. E. Wilkes,  
U. S. Surveyor.

Lines dated in red were executed by H. N. Bradstreet,  
U. S. Transitman.

For list of field assistants see Book "A".

78

38

BOOK 3286 For

CERTIFICATE OF UNITED STATES SURVEYOR. AND U.S. TRANSITMAN  
See Book "C" of this group.

I, \_\_\_\_\_, U. S. Surveyor, hereby certify upon honor that, in pursuance of special instructions received from the U. S. Surveyor General for \_\_\_\_\_ bearing date of the \_\_\_\_\_ day of \_\_\_\_\_, 191\_\_\_\_, I have well, faithfully, and truly in my own proper person, and in strict conformity with said instructions, the Manual of Surveying Instructions, and the laws of the United States, surveyed all those parts or portions of \_\_\_\_\_ of the \_\_\_\_\_ Meridian, in the State of \_\_\_\_\_, which are represented in the foregoing field notes as having been executed by me, and under my direction; and that all the corners of said survey have been established and perpetuated in strict accordance with the Manual of Surveying Instructions, and the special written instructions of the U. S. Surveyor General for \_\_\_\_\_ and in the specific manner described in the field notes, and that the foregoing are the original field notes of such survey.

\_\_\_\_\_  
U. S. Surveyor.

APPROVAL.

OFFICE OF THE UNITED STATES SURVEYOR GENERAL,

Phoenix, Arizona, Jan. 20, 1919, ~~1918~~


The foregoing field notes of the survey of the

Subdivision Lines of

TOWNSHIP 12 NORTH, RANGE 7 WEST,

of the Gila and Salt River Base and Meridian, in the State of Arizona,

executed by L. E. Wilkes, U. S. Surveyor, and H. N. Bradstreet, U. S. Transitman, under ~~his~~ special instructions dated July 23, 1914, for Group 36, Arizona, having been critically examined, and the necessary corrections and explanations made, the said field notes, and the surveys they describe, are hereby approved.

  
U. S. Surveyor General.

~~I certify that the foregoing transcript of the field notes of the above described surveys in~~  
~~Book "N", Group 36,~~ has been correctly copied from the original notes on file in this office.