

OR 135
1

Book "T".

4-679

DEC-5 1919

3341

ECCOCK 3341

FIELD NOTES

RE-
OF THE SURVEY OF THE

Second Standard Parallel North, Through Range 2 West,

SURVEY OF

North, East and West Boundaries and

Subdivision Lines of

TOWNSHIP 9 NORTH, RANGE 2 WEST.

Of the Gila and Salt River Base and Meridian,

In the State of Arizona.

EXECUTED BY

J. P. Davis,

In the capacity of U. S. Surveyor, under Special Instructions dated November 13, 1917, issued by the United States Surveyor General to govern surveys included in Group No. 61, which were approved by the Commissioner of the General Land Office, November 26, 1917, and Assignment Instructions dated January 8, 1919.

Resurvey and Survey commenced February 27, 1919.

Resurvey and Survey completed April 7, 1919.

3341

3341

BOOK 3341

INDEX DIAGRAM.

		Township 9 North				Range 2 West.						
		13	13	14	14	15	16					
12	6	48	5	39	4	38	3	27	2	21	1	8
	47		47		38		32		26		21	
11	7	46	8	38	9 A 1537	32	10	26	11	20	12	7
	45		45		37		31		26		20	
11	18	44	17	36	16	31 m	15	25	14	19	13	6
	44		43		36		30		25		19	
10	19	43	20	35	21	30	22	24	23	18	24	6
	42		42		35		29		23		18	
9	30	41	29	34	28	29	27	23	26	17	25	5
	41		40		34		28		22		17	
9	31	39	32	33	33	27	34	22	35	16	36	5
	4		3		3		2		1		1	

Second Standard Parallel North

- Lines surveyed under this group.
- Lines resurveyed under this group.
- Lines of accepted surveys.
- Unsurveyed.
- Lines resurveyed under group No. 60.

Independent Resurvey of 2nd. Std. Par. N. thru, Range 2 West 1 B

Chains.

Resurvey and Survey executed by J. P. Davis, U. S. Surveyor, on dates shown on page 49 hereof, using Young and Sons light mountain transit No. 8532, with Smith solar attachment. For description of instrument, certificate of approval, and tests of adjustment, see Book "S".

The 2nd Std. Par. N. through R. 1 W., was defective in measurement and alignment and was independently resurveyed under Group 60, therefore, make independent resurvey through R. 2 W., as hereinafter described. None of the original standard corners in R. 2 W. could be found.

From the standard cor. of Ts. 9 N., Rs. 1 and 2 W., which is an iron post, 3 fns. diam., properly set, marked and witnessed as described by the Surveyor-General, West on S. bdy. of sec. 36.

Over rough mountainous land, through dense undergrowth. Asc. 25 ft.

0.90 Top of knoll on spur, slopes N. Desc. 85 ft.

4.70 Draw, 3 lks. wide, course N. Asc. 45 ft.

7.36 Spur, slopes N. Thence along N. slope.

17.40 Desc. 200 ft., along spur, slopes W.

20.50 Point of spur, slopes W. Continue descent.

27.00 Draw, 8 lks. wide, course NW. Asc.

30.40 Desc. 55 ft.

36.30 Bend in draw, course N.70°W., from N.70°E.

40.00 Set an iron post, 3 ft. long, 1 in. diam., 8 ins. in the ground, in a mound of stone, for reestablished standard 1/4 sec. cor., marked on brass cap

SC
1/4 S36

1919

And raise a mound of stone, 2 ft. base, 1 1/2 ft. high, N. of cor.

40.60 Same draw, 10 lks. wide, course S. Asc. 30 ft.

41.00 Low spur, slopes S. Desc. 30 ft.

46.60 Same draw, course N.70°W. Asc. 50 ft.

50.50 Spur, slopes NW. Desc. 120 ft.

53.90 Same draw, course S.

55.70 Enter ^{Walker} gulch, course S.

57.30 Leave ^{Walker} gulch, course S. Asc.

58.45 Desc.

62.60 Draw, 8 lks. wide, course SE. Asc. 120 ft.

71.30 Knoll on spur, slopes E. Desc. 60 ft.

74.70 Draw, 8 lks. wide, course S. Asc.

76.00 Desc.

77.50 Draw, course S.60°E. Asc. 65 ft.

80.00 Set an iron post, 3 ft. long, 2 ins. diam., 20 ins. in the ground, in a mound of stone, for reestablished standard cor. of secs. 35 and 36, marked on brass cap

S C
T9N R2W
S35/S36

1919

And raise a mound of stone, 2 ft. base, 1 1/2 ft. high, N. of cor.

Land, rough mountainous.
Soil, rocky, 4th rate.
No timber.
Undergrowth, buck brush, mesquite and cat claw.

West on S. bdy. of sec. 35.
Over mountainous land, through scattering undergrowth. Asc. 95 ft.

6.30 Spur, slopes SE. Asc. 30 ft.

14.50 Desc. 35 ft.

15.90 Draw, 20 lks. wide, course S.70°E. Asc. 130 ft.

19.30 Point of spur, slopes N. Desc. 15 ft.

22.00 Draw, 6 lks. wide, course NE. Asc. 160 ft.

Independent Resurvey of the
Second Standard Parallel North Through Range 2 West.

Chains.
 26.90 Spur,, slopes NE. Continue ascent.
 29.60 Ridge, brs. N.30°W. and S. Desc. 645 ft.
 37.60 Head of draw, course N.75°W. Continue descent.
 40.00 Set an iron post, 3 ft. long, 1 in. diam., 16 ins. in the ground, in a mound of stone, for reestablished standard $\frac{1}{4}$ sec. cor., marked on brass cap

SC
±S35

1919

44.70 And raise a mound of stone, 2 ft. base, 1½ ft. high, N. of cor.
 51.80 Spur, slopes NW. Continue descent.
 67.50 Draw, 6 lks. wide, course SW. Continue descent.
 72.00 Banty Creek, course S.
 80.00 Draw, 20 lks. wide, course SE: Asc. Continue descent.
 Set an iron post, 3 ft. long, 2 ins. diam., 10 ins. in the ground, in a mound of stone, for reestablished standard cor. of secs. 34 and 35, marked on brass cap

S C
T9N R2W
S34 S35

1919

And raise a mound of stone, 2 ft. base, 1½ ft. high, N. of cor.
 Land, mountainous.
 Soil, rocky, 4th rate.
 No timber.
 Undergrowth, buck brush, mesquite and cat claw.

West on S. bdy. of sec. 34.
 Over mountainous land, through scattering undergrowth.
 Asc. 225 ft.
 8.30 Spur, slopes NE. Desc. 80 ft.
 18.60 Draw, course NE. Asc. 60 ft.
 23.20 Spur, slopes NE. Continue ascent, 290 ft.
 37.50 Ridge, brs. NW. and SE. Desc. 260 ft.
 40.00 Set a basalt stone, 16 X 8 X 6 ins., 11 ins. in the ground, for reestablished standard $\frac{1}{4}$ sec. cor., marked SC $\frac{1}{4}$ S34, 1919 on N. face; and raise a mound of stone, 2 ft. base, 1½ ft. high, N. of cor.
 51.70 Head of draw, course SE. Asc. 295 ft.
 60.00 Along base of cliff, 100 ft., high, facing N., brs. E. and W.
 67.56 Point of conglomerate cliff, 200 ft. high, brs. N. 0.40 chs. dist. Desc. 445 ft.
 80.00 Set an iron post, 3 ft. long, 2 ins. diam., 8 ins. in the ground, in a mound of stone, for reestablished standard cor. of secs. 33 and 34, marked on brass cap

S C
T9N R2W
S33 S34

1919

And raise a mound of stone, 2 ft. base, 1½ ft. high, N. of cor.
 Land, mountainous.
 Soil, rocky, 4th rate.
 No timber.
 Undergrowth, buck brush, mesquite and cat claw.

Independent Resurvey of the
Second Standard Parallel North Through Range 2 West

3

Chains.

West on S. bdy. of sec. 33.
Over mountainous land, through scattering undergrowth.
Desc. 85 ft.

4.20 Copperopolis Creek, 40 lks. wide, containing stream of water,
0.5 lks. wide, 2 ins. deep, course S. Asc. 150 ft.

14.20 Low ridge, brs. N. and S. Desc. 95 ft.

15.70 Road, brs. NE. to mine and SW. to Briggs.

21.15 Head of draw, course NW. Asc. 45 ft.

25.50 Spur, slopes NW. Champa Mine brs. N. 31° W. Desc. 115 ft.

30.50 Head of draw, course NW. Asc.

36.70 Spur, slopes NW. Desc. 50 ft.

38.85 Road, brs. N. to Champa Mine and SW. to Briggs.

40.00 The true point for reestablished standard $\frac{1}{4}$ sec. cor. falls
on granite boulder in place, 3 X $1\frac{1}{2}$ X $1\frac{1}{2}$ ft. above ground,
Mark a cross at the exact cor. point for reestablished
standard $\frac{1}{4}$ sec. cor., with SC $\frac{1}{4}$ S33 on stone; raise a
mound of stone, 2 ft. base, $1\frac{1}{2}$ ft. high, S. of cor.
(Creek bed prevents mound of stone to N.)

41.40 Gulch, course W., from NE.

43.00 Leave gulch, course SW. Asc. 45 ft.

43.98 Mouth of tunnel brs. N. 0.35 chs. dist.

45.00 Point of spur, slopes SW. Desc. 40 ft.

48.85 Draw, course S. Asc. 160 ft.

58.10 Ridge, brs. NW. and SE. Desc. 250 ft.

69.50 Gulch, course S. 20° E. Asc. 165 ft.

78.40 Ridge, brs. N. and S. Desc. 30 ft.

80.00 Set an iron post, 3 ft. long, 2 ins. diam., 14 ins. in the
ground, in a mound of stone, for reestablished standard
cor. of secs. 32 and 33, marked on brass cap

S C
T9N R2W
S32 S33

1919

And raise a mound of stone, 2 ft. base, $1\frac{1}{2}$ ft. high, N.
of cor.
Land, mountainous.
Soil, rocky, 4th rate.
No timber.
Undergrowth, buck brush, mesquite and cat claw.

West on S. bdy. of sec. 32.
Over mountainous land, through scattering undergrowth.
Desc. 70 ft.

5.80 Draw, course SW. Asc. 65 ft.

8.00 Point of spur, slopes S. Desc. 155 ft.

12.70 Castle Creek, 50 lks. wide, containing stream of water, 3
lks. wide, 3 ft. deep, course SE. Old stage road, brs.
NW. to Prescott and SE. to Phoenix. Asc. 85 ft.

22.00 Point of spur, slopes N. Desc. 45 ft.

26.80 Draw, 10 lks. wide, course N. 70° E. Asc. 45 ft.

28.00 Point of spur, slopes NE. Desc. 25 ft.

32.25 Draw, 20 lks. wide, course N. 70° E. Asc. 50 ft.

34.80 Point of spur, slopes S. Desc. 25 ft.

35.50 Same draw, 20 lks. wide, course SE. Asc. 230 ft.

40.00 Set an iron post, 3 ft. long, 1 in. diam., 20 ins. in the
ground, in a mound of stone, for reestablished standard
 $\frac{1}{4}$ sec. cor., marked on brass cap

SC
 $\frac{1}{4}$ S32

1919

And raise a mound of stone, 2 ft. base, $1\frac{1}{2}$ ft. high, N.
of cor.

Independent Resurvey of the
Second Standard Parallel North Through Range 2 West.

Chains.
50.00
56.00
60.50
62.60
68.15
71.70
73.90
80.00

Spur, slopes SE. Thence along broken S. slope.
Spur, slopes S.
Head of draw, course S. Asc. 25 ft.
Spur, slopes S. Desc.
Head of draw, course N. Asc. 35 ft.
Desc. 20 ft.
Head of draw, course NE. Asc. 100 ft.
Set an iron post, 3 ft. long, 2 ins. diam., 5 ins. in the ground, in a mound of stone, for reestablished standard cor. of secs. 31 and 32, marked on brass cap

S C
T9N R2W
S31 S32

1919

And raise a mound of stone, 2 ft. base, 1½ ft. high, N. of cor.
Land, mountainous.
Soil, rocky, 4th rate.
No timber.
Undergrowth, buck brush, mesquite and cactus.

4.70
25.30
29.90
40.00

West on S. bdy. of sec. 31.
Over mountainous land, through dense undergrowth.
Desc. 105 ft.
Draw, course SE. Asc. 400 ft.
Spur, slopes S. Desc. 105 ft.
Draw, course S. Asc. 185 ft.
Spur, slopes SE.
Set an iron post, 3 ft. long, 1 in. diam., 26 ins. in the ground, for reestablished standard ¼ sec. cor., marked on brass cap

SC
S31

1919

41.40
60.60
63.40
67.80
80.00

And raise a mound of stone, 2 ft. base, 1½ ft. high, N. of cor.
Desc. 35 ft.
Head of draw, course S. Asc. 335 ft.
Ridge, brs. N. and S. Desc. 95 ft.
Head of draw, course SW. Asc. 15 ft.
Spur, slopes SW. Desc. 155 ft.
Set an iron post, 3 ft. long, 3 ins. diam., 24 ins. in the ground, for reestablished standard cor. of Ts. 9 N., Rs. 2 and 3 W., marked on brass cap

SC T9N
R3W R2W
S36 S31


1919

And raise a mound of stone, 2 ft. base, 1½ ft. high, N. of cor.
Land, mountainous.
Soil, rocky, 4th rate.
No timber.
Undergrowth, cat claw, scrub oak, mesquite and mahogany.


Survey of the
East Boundary of T. 9 N., R. 2 W.

Chains.

From the standard cor. of Ts. 9 N., Rs. 1 and 2 W., here-
inbefore described,
North bet. secs. 31 and 36.
Over mountainous land, through dense undergrowth.
Desc. 55 ft.
2.35 Draw, 6 lks. wide, course W. Asc. 125 ft.
5.00 Spur, slopes SW. Thence along W. slope.
11.90 Low ridge, brs. N.60°W. and S.60°E. Desc. 45 ft.
15.60 Draw, 3 lks. wide, course NW. Asc. 55 ft., along broken W.
slope.
28.80 Desc. 15 ft.
33.80 Asc. 25 ft.
36.00 Point of spur, slopes N. Desc. 105 ft.
40.00 Set an iron post, 3 ft. long, 1 in. diam., 26 ins. in the
ground, for $\frac{1}{4}$ sec. cor., marked on brass cap




And raise a mound of stone, 2 ft. base, $1\frac{1}{2}$ ft. high, W.
of cor.
41.40 Draw, 15 lks. wide, course NW. Asc. 155 ft.
53.50 Head of draw, course SW. Continue ascent.
59.28 Low ridge, brs. E. and W. Desc. 120 ft.
66.70 Draw, 5 lks. wide, course W. Asc. 180 ft.
77.90 Spur, slopes SE. Desc.
80.00 Set an iron post, 3 ft. long, 2 ins. diam., 24 ins. in the
ground, for cor. of secs. 25, 30, 31 and 36, marked on
brass cap



And raise a mound of stone, 2 ft. base, $1\frac{1}{2}$ ft. high, W.
of cor.
Land, mountainous.
Soil, rocky, 4th rate.
No timber.
Undergrowth, buck brush, mesquite and cat claw.

North bet. secs. 25 and 30.
Over rolling mountainous land, through dense undergrowth.
Desc. 155 ft.
12.60 Draw, 20 lks. wide, course W. Old road, brs. W. to Prescott
and E. to Phoenix. Asc. 20 ft.
13.00 Trail, brs. E. and W.
13.60 Low spur, slopes W. Desc. 15 ft.
14.60 Wash, course SW. Asc. 180 ft.
32.50 Head of draw, course SW. Continue ascent.
40.00 Set an iron post, 3 ft. long, 1 in. diam., 18 ins. in the
ground, in a mound of stone, for $\frac{1}{4}$ sec. cor., marked on
brass cap



And raise a mound of stone, 2 ft. base, $1\frac{1}{2}$ ft. high, W.
of cor.
Desc. 20 ft.
41.50 Wash, course SW. Asc. 145 ft.
63.10 Desc. 25 ft.
64.15 Wash, 30 lks. wide, course SW. Asc. 95 ft.
80.00 Set an iron post, 3 ft. long, 2 ins. diam., 24 ins. in the
ground, for cor. of secs. 19, 24, 25 and 30, marked on
brass cap

Survey of the
East Boundary of T. 9 N., R. 2 W.

Chains.

T9N
R2W | R1W
S24 | S19
S25 | S30
1919

And raise a mound of stone, 2 ft. base, 1½ ft. high, W. of cor.
Land, rolling mountainous.
Soil, 2nd and 3rd rates.
No timber.
Undergrowth, cat claw and mesquite.

North bet. secs. 19 and 24.
Over mountainous land, through dense undergrowth.
Desc. 35 ft.

- 4.72 Wash, 15 lks. wide, course SW. Asc. 245 ft., over rough mountainous land.
- 18.00 Spur, slopes SW. Desc. 35 ft.
- 19.10 Head of draw, course SW. Asc. 85 ft.
- 21.70 Mouth of tunnel, brs. NE. 1 ch. dist.
- 29.40 Spur, slopes W. Desc. 30 ft.
- 31.90 Draw, course W. Asc. 185 ft.
- 32.70 Prospecthole on line.
- 38.10 Spur, slopes W. Tussock Spring brs. N.87°45'W.
- 40.00 Set an iron post, 3 ft. long, 1 in. diam., 26 ins. in the ground, for ¼ sec. cor., marked on brass cap

¼
S24 | S19
1919

And raise a mound of stone, 2 ft. base, 1½ ft. high, W. of cor.

- Desc. 35 ft.
- 43.90 Head of draw, course SW. Asc. 105 ft.
- 46.40 Spur, slopes W. Tussock Spring brs. S.85°30'W. Desc. 95 ft.
- 53.20 Head of draw, course W. Asc. 180 ft.
- 58.80 Spur, slopes SW. Desc. 60 ft.
- 62.60 Draw, course W. Asc. 185 ft.
- 69.20 Spur, slopes SW. Desc. 65 ft.
- 80.00 Set an iron post, 3 ft. long, 2 ins. diam., 24 ins. in the ground, for cor. of secs. 13, 18, 19 and 24, marked on brass cap

T9N
R2W | R1W
S13 | S18
S24 | S19
1919

And raise a mound of stone, 2 ft. base, 1½ ft. high, W. of cor.
Land, mountainous.
Soil, rocky, 4th rate.
No timber.
Undergrowth, cat claw and mesquite.


North bet. secs. 13 and 18.
Over mountainous land, through dense undergrowth.
Desc. 90 ft.

- 4.72 Draw, course W. Asc. 15 ft.
- 7.00 Spur, slopes W. Desc. 95 ft.
- 10.00 Draw, course W. Asc. 15 ft.
- 13.50 Point of spur, slopes W. Thence along W. slope.
- 16.00 Asc. 210 ft.
- 22.00 Spur, slopes W. Desc. 195 ft.

Survey of the
East Boundary of T. 9 N., R. 2 W.

Chains.

30.40 Draw, course W. Asc. 590 ft.
40.00 Set an iron post, 3 ft. long, 1 in. diam., 26 ins. in the
ground, for $\frac{1}{4}$ sec. cor., marked on brass cap




And raise a mound of stone, 2 ft. base, $1\frac{1}{2}$ ft. high, W. of cor.

42.15 Spur, slopes S.30°E. Asc. 475 ft.
62.75 Ridge, brs. NE. and SW. Thence along W. slope, ascending
50 ft.

68.00 Spur, slopes W. Desc. 250 ft.

77.00 Draw, course W. Spring brs. E. 3 chs. dist. Asc. 145 ft.

80.00 Set an iron post, 3 ft. long, 2 ins. diam., 24 ins. in the
ground, for cor. of secs. 7, 12, 13 and 18, marked on
brass cap



And raise a mound of stone, 2 ft. base, $1\frac{1}{2}$ ft. high, W. of cor.

Land, mountainous.
Soil, rocky, 4th rate.
No timber.
Undergrowth, cat claw and mesquite.

North bet. secs. 7 and 12.
Over mountainous land, through dense undergrowth.
Asc. 120 ft.

5.20 Ridge, brs. NE. and SW. Thence along W. slope.

10 10 Desc. 230 ft.

15.80 Draw, course W. Asc. 50 ft.


20.30 Spur, slopes W. Desc. 70 ft.

22.50 Draw, course W. Asc. 50 ft.

29.40 Spur, slopes SW. Desc. 195 ft.

37.10 Draw, course W. Asc. 25 ft.

40.00 Set an iron post, 3 ft. long, 1 in. diam., 26 ins. in the
ground, for $\frac{1}{4}$ sec. cor., marked on brass cap



And raise a mound of stone, 2 ft. base, $1\frac{1}{2}$ ft. high, W. of cor.

Thence along W. slope.

41.30 Desc. 45 ft.

47.20 Head of draw, course W. Asc. 80 ft.

69.75 Desc. 20 ft.

73.10 Asc. 70 ft.

75.30 Spur ridge, brs. N.60°E. and S.60°W. Desc.

79.48 Boaz Mill brs. N.23°W.

Shaft brs. N.18°20'W.

Building brs. N.29 $\frac{1}{2}$ °W.

80.00 Set an iron post, 3 ft. long, 2 ins. diam., 24 ins. in the
ground, for cor. of secs. 1, 6, 7 and 12, marked on
brass cap

Survey of the
East Boundary of T. 9 N., R. 2 W.

chains.

T9N
R2W | R1W
S 1 | S 6
S12 | S 7
1919

And raise a mound of stone, 2 ft. base, 1½ ft. high, W. of cor.
Land, mountainous.
Soil, rocky, 4th rate.
No timber.
Undergrowth, cat claw and mesquite.

- 1.00 Desc. 340 ft.
- 19.20 Asc. 110 ft.
- 31.10 Spur, slopes S. 50°W. Desc. 240 ft.
- 40.00 Set a granite stone, 16 X 12 X 6 ins., 12 ins. in the ground, for ¼ sec. cor., marked ¼ on W. face; and raise a mound of stone, 2 ft. base, 1½ ft. high, W. of cor.
- 40.16 Intersect line 5-6 of New York Mining Claim, survey No. 1674; Bradshaw Mining Dist., 0.29 chs. S. 57°2'E. of cor. No. 5, which is a post, 4 ins. square, 4 ft. long, set in a mound of stone, marked N Y No. 5 on N. face.
- 42.00 Draw, course SW. Asc. 250 ft.
- 49.56 Boaz Mill brs. N. 83½°W.
Shaft brs. N. 73½°W.
Buildings br. N. 79½°W.
- 51.00 Spur, slopes W. Desc. 140 ft.
- 55.00 Canyon, course W. Asc. 340 ft.
- 70.00 Spur, slopes W. Desc. 50 ft.
- 78.00 Main mountain, brs. E. and W.
- 80.00 Set an iron post, 3 ft. long, 3 ins. diam., 24 ins. in the ground, for cor. of Ts. 9 and 10 N., Rs. 1 and 2 W., marked on brass cap

T10N
R2W | R1W
S36 | S31
S 1 | S 6
T9N
1919


And raise a mound of stone, 2 ft. base, 1½ ft. high, S. of cor.
Land, mountainous.
Soil, rocky, 4th rate.
No timber.
Undergrowth, cat claw and mesquite.

Survey of the
West Boundary of T. 9 N., R. 2 W.

chains.

From the standard cor. of Ts. 9 N., Rs. 2 and 3 W., here-
inbefore described, on 2nd. Standard Parallel North,
North bet. secs. 31 and 36.
Over rough mountainous land, through scattering undergrowth.
Asc. 185 ft.
Spur, slopes NW. Desc. 345 ft., through dense undergrowth.
Draw, 10 lks. wide, course SW. Asc. 275 ft.
Set an iron post, 3 ft. long, 1 in. diam., 26 ins. in the
ground, for $\frac{1}{4}$ sec. cor., marked on brass cap


22.65
38.50
40.00



And raise a mound of stone, 2 ft. base, 1 1/2 ft. high, W.
of cor.

57.65
61.10
63.70
73.00
74.20
80.00

Ridge, brs. NW. and SE. Desc. 65 ft.
Head of draw, course E. Asc. 50 ft.
East end of granite cliff, 30 ft. high, brs. W. Desc. 310
ft.
Head of draw, course NW. Asc.
Low spur, slopes NW. Desc. 50 ft.
Set an iron post, 3 ft. long, 2 ins diam., 3 ins. in the
ground, in a mound of stone, for cor. of secs. 25, 30,
31 and 36, marked on brass cap




And raise a mound of stone, 2 ft. base, 1 1/2 ft. high, W.
of cor.

Land, rough mountainous.
Soil, rocky, 4th rate.
No timber.
Undergrowth, scrub oak, mesquite and cat claw.

North bet. secs. 25 and 30.
Over rough mountainous land, through dense undergrowth.
Desc. 65 ft.

5.90
6.40
9.70
15.50
23.00
30.20
30.70
40.00

Draw, 5 lks. wide, course NE. Asc. 50 ft.
Old road, brs. NE. to Crown Point Mine and SW.
Low spur, slopes E. Desc. 70 ft.
Same draw, course NW. Same road, brs. NW. and SE. Asc.
130 ft.
Spur, slopes NW. Desc. 105 ft.
Same road, brs. E. to Crown Point Mine and SW.
Head of draw, course W. Asc. 125 ft.
Set an iron post, 3 ft. long, 1 in. diam., 26 ins. in the
ground, for $\frac{1}{4}$ sec. cor., marked on brass cap



And raise a mound of stone, 2 ft. base, 1 1/2 ft. high, W.
of cor.

41.63
53.70
64.80
66.80
67.80

Crown Point Mine and Mill brs. N. 33° 25' E. Desc. 315 ft
Spur, slopes E. Continue descent.
Crown Point Mine Wash, 4 lks. wide, course NW. Road in wash, brs. NW. and
SE. to Crown Point Mine. Asc. 275 ft.
Fence, brs. NE. and SW.
Wash, course SW. Continue ascent.

Survey of the
West Boundary of T. 9 N., R. 2 W.

Chains.
68.55 Intersect line 1-2 Yankee Boy Mining Claim, Survey No. 1259, Castle Creek and Black Rock Mining District, 0.74 chs. S.61°28'E. of cor. No. 1.
74.05 Spur, slopes N.70°W. U. S. L. M. 1259, Castle Creek and Black Rock Mining District, brs. N.67°10'W., 1.60 chs. dist. Desc. 130 ft.
77.90 Fence, brs. NW. and SE.
79.29 Intersect line 3-4, Silver King Mining Claim, Survey No. 1259, Castle Creek and Black Rock Mining District, 4.66 chs. N.56°58'W. of cor. No. 4.
80.00 Set an iron post, 3 ft. long, 2 ins. diam., 26 ins. in the ground, for cor. of secs. 19, 24, 25 and 30, marked on brass cap

T9N
R3W | R2W
S24 | S19
S25 | S30
1919

And raise a mound of stone, 2 ft. base, 1½ ft. high, W. of cor.
From this cor., U. S. L. M. No. 1259, Castle Creek and Black Rock Mining District, brs. S.14°28'W., 5.50 chs. dist., a granite stone, 12 X 14 X 18 ins. above ground, marked and witnessed as described by the Surveyor-General.
Land, rough mountainous.
Soil, rocky, 4th rate.
No timber.
Undergrowth, scrub oak, mesquite and cat claw.

0.76 North bet. secs. 19 and 24.
18.45 Over mountainous land, through dense undergrowth.
25.00 Desc. 15 ft.
31.10 Head of draw, course NW. Asc. 145 ft.
34.90 Spur, slopes NW. Desc. 140 ft.
40.00 Wash, course W. Asc. 105 ft.
Spur, slopes NW. Desc. 70 ft.
Draw, course W. Asc. 275 ft.
Set an iron post, 3 ft. long, 1 in. diam., 4 ins. in the ground, on solid rock, in a mound of stone, for ¼ sec. cor., marked on brass cap

¼
S24 | S19
1919

44.40 And raise a mound of stone, 2 ft. base, 1½ ft. high, W. of cor.
47.80 Ridge, brs. E. and W. Desc. 190 ft.
49.90 Old road, brs. E. and W.
55.20 Head of draw, course NW. Asc.
57.60 Spur, slopes W. Desc. 70 ft.
65.40 Draw, course W. Asc. 45 ft.
74.35 Spur, slopes SW. Desc. 100 ft.
78.75 Draw, course W. Asc. 45 ft.
80.00 Desc. 25 ft.
Set an iron post, 3 ft. long, 2 ins. diam., 24 ins. in the ground, for cor. of secs. 13, 18, 19 and 24, marked on brass cap

T9N
R3W | R2W
S13 | S18
S24 | S19
1919

And raise a mound of stone, 2 ft. base, 1½ ft. high, W. of cor.
Land, mountainous.
Soil, rocky, 4th rate.


Survey of the
West Boundary of T. 9 N., R. 2 W.

Chains.

No timber.
Undergrowth, scrub oak, cat claw and mesquite.


North bet. secs. 13 and 18.
Over rough mountainous land, through scattering undergrowth.
Desc.

- 1.50 Head of draw, course SW. Asc. 200 ft.
- 8.00 Spur, slopes W. Desc., through dense undergrowth.
- 9.00 Head of draw, course NW. Asc.
- 13.00 Spur, slopes NW. Desc. 305 ft.
- 19.00 Draw, course NW. Asc. 105 ft.
- 23.70 Spur, slopes SW. Desc. 60 ft.
- 28.20 Draw, course SW. Asc. 275 ft.
- 37.30 Spur, slopes SW. Desc. 70 ft.
- 40.00 Set an iron post, 3 ft. long, 1 in. diam., 10 ins. in the ground, in a mound of stone, for $\frac{1}{4}$ sec. cor., marked on brass cap



And raise a mound of stone, 2 ft. base, $1\frac{1}{2}$ ft. high, W. of cor.

- 40.90 Head of draw, course W.
- 41.70 Head of draw, course SW. Asc. 165 ft.
- 47.00 Spur, slopes SW. Continue ascent, 105 ft.
- 55.35 Ridge, brs. NW. and SE. Desc. 50 ft.
- 58.35 Head of draw, course E. Asc. 180 ft.
- 76.15 Ridge, brs. NE. and SW. Thence along W. slope.
- 80.00 Set an iron post, 3 ft. long, 2 ins. diam., 10 ins. in the ground, in a mound of stone, for cor. of secs. 7, 12, 13 and 18, marked on brass cap




And raise a mound of stone, 2 ft. base, $1\frac{1}{2}$ ft. high, W. of cor.

Land, mountainous.
Soil, rocky, 4th rate.
No timber.
Undergrowth, scrub oak, mesquite and cat claw.

North bet. secs. 7 and 12.
Over mountainous land, through dense undergrowth.
Along W. slope.

- 5.00 Ridge, brs. N. 10° W. and S. 10° E. Desc. 335 ft.
- 20.60 Head of draw, course E. Asc. 95 ft.
- 29.75 Ridge, brs. W. and N. 70° E. Desc. 235 ft.
- 40.00 Set an iron post, 3 ft. long, 1 in. diam., 14 ins. in the ground, in a mound of stone, for $\frac{1}{4}$ sec. cor., marked on brass cap



And raise a mound of stone, 2 ft. base, $1\frac{1}{2}$ ft. high, W. of cor.

- 46.00 Head of draw, course W. Asc.
- 53.00

Survey of the
West Boundary of T. 9 N., R. 2 W.

12

Chains.

57.30 Ridge, brs. E. and W. Desc. 65 ft.
 66.10 Asc. 10 ft.
 67.15 Spur, slopes E. Desc. 95 ft.
 75.25 Gulch, course W. Asc. 25 ft.
 80.00 Set an iron post, 3 ft. long, 2 ins. diam., in a mound of stone, for cor. of secs. 1, 6, 7 and 12, marked on brass cap

T9N
 R3W | R2W
 S 1 | S 6
 S12 | S 7
 1919

And raise a mound of stone, 2 ft. base, 1½ ft. high, on overhanging boulder above cor.
 Land, mountainous.
 Soil, rocky, 4th rate.
 No timber.
 Undergrowth, scrub oak, mesquite and cat claw.

North bet. secs. 1 and 6.
 Over mountainous land, through dense undergrowth.
 Desc. 30 ft.

5.00 Asc. 45 ft.
 11.60 Desc. 195 ft.
 29.60 Head of draw, course SW. Asc. 130 ft.
 39.00 Granite cliff, brs. E. and W. Desc. 130 ft.
 40.00 Set an iron post, 3 ft. long, 1 in. diam., in crevice in granite ledge, and in a mound of stone, for ¼ sec. cor., marked on brass cap

¼
 S 1 | S 6
 1919

And raise a mound of stone, 2 ft. base, 1½ ft. high, W. of cor.

51.30 Gulch, course E. Asc. 40 ft.
 60.20 Ridge, brs. E. and W. Desc. 445 ft.
 72.40 Oak Creek, containing small stream of water, course NW. Asc. 65 ft.
 80.00 Set an iron post, 3 ft. long, 3 ins. diam., in a mound of stone, for cor. of Ts. 9 and 10 N., Rs. 2 and 3 W., marked on brass cap

T10N
 R3W | R2W
 S36 | S31
 S 1 | S 6
 T9N
 1919

And raise a mound of stone, 2 ft. base, 1½ ft. high, S. of cor.

At this cor., at 3 hrs p.m., l.m.t., March 19, 1919, the magnetic declination is 14°40'E.

Land, mountainous.
 Soil, rocky, 4th rate.
 No timber.
 Undergrowth, cat claw, scrub oak and mesquite.

Survey of the
North Boundary of T. 9 N., R. 2 W.

Chains.

From the cor. of Ts. 9 and 10 N., Rs. 1 and 2 W., hereinbefore described,
West on a random line, along the N. bdy. of T. 9 N., R. 2 W., setting temp. $\frac{1}{4}$ sec. and sec. cors. at intervals of 40.00 chs.; and at 479.68 chs., fall 25 lks. S. of the cor. of Ts. 9 and 10 N., Rs. 2 and 3 W., hereinbefore described. The falling answers to a correction of $0^{\circ}2'$, of 4 lks. N. per mile, counting from the NE. cor. of the Tp; therefore

S. $89^{\circ}58'E.$, on a true line, bet. secs. 6 and 31.
Over rough mountainous land, through dense undergrowth.
Asc. 335 ft.

14.60 Ridge, brs. NW. and SE. Desc. 125 ft.
20.60 Asc. 130 ft.
38.00 Spur, slopes NW. Desc. 20 ft.
39.68 Set an iron post, 3 ft. long, 1 in. diam., 10 ins. in the ground, in a mound of stone, for $\frac{1}{4}$ sec. cor., marked on brass cap

$\frac{1}{4}$ S31
S 6
1919

And raise a mound of stone, 2 ft. base, $1\frac{1}{2}$ ft. high, N. of cor.

43.70 Head of draw, course NW. Asc. 45 ft.
46.00 Spur, slopes NW. Desc. 145 ft.
54.40 Wash, 15 lks. wide, course NE. Asc. 210 ft.
79.68 Set an iron post, 3 ft. long, 2 ins. diam., 6 ins. in the ground, in a mound of stone, for cor. of secs. 5, 6, 31, and 32, marked on brass cap

T10N R2W
S31 | S32
S 6 | S 5
T9N
1919

And raise a mound of stone, 2 ft. base, $1\frac{1}{2}$ ft. high, W. of cor.
Land, rough mountainous.
Soil, rocky, 4th rate.
No timber.
Undergrowth, mesquite, cat claw and scrub oak.

S. $89^{\circ}58'E.$, on a true line, bet. secs. 5 and 32.
Over rolling mountainous land, through dense undergrowth.
Desc. 50 ft.

1.65 Draw, 10 lks. wide, course N. $20^{\circ}W.$ Asc. 45 ft.
3.90 Road, brs. N. to Prescott and S. to Phoenix.
11.15 Desc. 50 ft.
14.50 Old road, brs. N. and S.
15.00 Wash, 20 lks. wide, course SW. Asc. 70 ft.
20.65 Spur, slopes N. Desc. 35 ft.
24.40 Wash, 10 lks. wide, course NW. Asc. 135 ft.
40.00 Set an iron post, 3 ft. long, 1 in. diam., 20 ins. in the ground, in a mound of stone, for $\frac{1}{4}$ sec. cor., marked on brass cap

$\frac{1}{4}$ S32
S 5
1919

And raise a mound of stone, 2 ft. base, $1\frac{1}{2}$ ft. high, W. of cor.

43.79 U. S. B. M., elevation 3955, brs. S. $32^{\circ}W.$
48.92 U. S. B. M., elevation 3955, brs. S. $41^{\circ}W.$ Desc. 15 ft.
60.00 Asc. 85 ft.
72.75 Desc. 30 ft.
78.70 Head of draw, course SW. Asc.
80.00 Set an iron post, 3 ft. long, 2 ins. diam., in a mound of

Survey of the
North Boundary of T. 9 N., R. 2 W.

Chains.

stone, for cor. of secs. 4, 5, 32 and 33, marked on brass cap

T10N R2W	
S32	S33
S 5	S 4
T9N	
1919	

And raise a mound of stone, 2 ft. base, 1½ ft. high, W. of cor.

Land, rolling mountainous.

Soil, rocky, 4th rate.

No timber.

Undergrowth, mesquite, scrub oak and cat claw.

S.89°58'E., on a true line, bet. secs. 4 and 33.
Over rolling mountainous land, through dense undergrowth.
Asc. 140 ft.

- 8.90 Spur, slopes SW. Desc. 35 ft.
- 13.80 Draw, 8 lks. wide, course SW. Asc. 40 ft.
- 18.10 Spur, slopes S. Desc. 60 ft.
- 23.50 Head of draw, course SW. Asc. 75 ft.
- 29.30 Spur, slopes SW. Desc. 60 ft.
- 32.50 Draw, course SW. Asc. 25 ft.
- 35.90 Spur, slopes SW. Desc. 25 ft.
- 37.40 Draw, course SW. Asc. 165 ft.
- 40.00 Set an iron post, 3 ft. long, 1 in. diam., 12 ins. in the ground, in a mound of stone, for ¼ sec. cor., marked on brass cap

S33	
¼	S 4
1919	

And raise a mound of stone, 2 ft. base, 1½ ft. high, N. of cor.

- 45.10 Desc. 50 ft.
- 51.20 Head of draw, course NW. Asc. 280 ft.
- 61.80 Ridge, brs. NE. and SW. Desc. 50 ft.
- 72.60 Wash, course SW. Asc. 105 ft.
- 80.00 Set an iron post, 3 ft. long, 2 ins. diam., 4 ins. in the ground, in a mound of stone, for cor. of secs. 3, 4, 33 and 34, marked on brass cap

T10N R2W	
S33	S34
S 4	S 3
T9N	
1919	

And raise a mound of stone, 2 ft. base, 1½ ft. high, W. of cor.

Land, rolling mountainous.

Soil, rocky, 4th rate.

No timber.

Undergrowth, scrub oak, mesquite and cat claw.

S.89°58'E., on a true line, bet. secs. 3 and 34.
Over rough mountainous land, through dense undergrowth.
Asc. 55 ft.

- 4.00 Spur, slopes SW. Desc. 30 ft.
- 14.10 Asc. 250 ft.
- 23.00 Spur, slopes S.20°E. Desc. 400 ft.
- 36.20 Spur, slopes SE. Continue descent.
- 40.00 Set an iron post, 3 ft. long, 1 in. diam., 26 ins. in the ground, for ¼ sec. cor., marked on brass cap

Survey of the
North Boundary of T. 9 N., R. 2 W.

Chains.

1/4 S34
4 S 3
1919

And raise a mound of stone, 2 ft. base, 1 1/2 ft. high, N. of cor.

- 44.90 Wash, course SE. Asc. 60 ft.
- 53.00 Spur, slopes S. 40° E. Desc. 115 ft.
- 57.20 Draw, course SE. Asc. 20 ft.
- 57.80 Spur, slopes S. Desc. 15 ft.
- 59.90 Draw, course S. Asc. 140 ft.
- 66.00 Spur, slopes S. Desc. 175 ft.
- 74.60 Wash, course S. Asc. 60 ft.
- 77.20 Spur, slopes S. Desc. 25 ft.
- 80.00 Set an iron post, 3 ft. long, 2 ins. diam., 2 1/4 ins. in the ground, for cor. of secs. 2, 3, 34 and 35, marked on brass cap

T10N R2W
S34/S35
S 3 | S 2
T9N
1919

And raise a mound of stone, 2 ft. base, 1 1/2 ft. high, W. of cor.

Land, rough mountainous.
Soil, rocky, 4th rate.
No timber.
Undergrowth, scrub oak, cat claw and mesquite.

S. 89° 58' E., on a true line, bet. secs. 2 and 35.
Over rough mountainous land, through dense undergrowth.
Desc. 10 ft.

- 2.70 Draw, course S. Asc. 35 ft.
- 4.80 Spur, slopes S. Desc. 75 ft.
- 12.00 Oak Creek Wash, 4 lks. wide, course SW. Asc. 110 ft.
- 14.20 Road, brs. NE. to Crown King and SW. to Johnson and Wagoner.
- 31.50 Head of draw, course SW. Asc.
- 38.00 Low spur, slopes S. Desc. 25 ft.
- 39.50 Head of draw, course S. Asc. 620 ft.
- 40.00 Set an iron post, 3 ft. long, 1 in. diam., 16 ins. in the ground, in a mound of stone, for 1/4 sec. cor., marked on brass cap

1/4 S35
4 S 2
1919

And raise a mound of stone, 2 ft. base, 1 1/2 ft. high, N. of cor.

- 69.70 Ridge, brs. NW. and SE. Desc. 155 ft.
- 78.05 Head of draw, course N. Asc. 30 ft.
- 80.00 Set an iron post, 3 ft. long, 2 ins. diam., 2 1/4 ins. in the ground, for cor. of secs. 1, 2, 35 and 36, marked on brass cap

T10N R2W
S35/S36
S 2 | S 1
T9N
1919

And raise a mound of stone, 2 ft. base, 1 1/2 ft. high, W. of cor.

Land, rough mountainous.
Soil, rocky, 4th rate.
No timber.
Undergrowth, greasewood, mesquite, cat claw and scrub oak.

152

Survey of the
North Boundary of T. 9 N., R. 2 W.

Chains.

- S. 89° 58' E., on a true line, bet. secs. 1 and 36.
Over rough mountainous land, through dense undergrowth.
Asc. 65 ft.
- 4.00 Desc. 130 ft.
- 23.60 Wash, course NW. Asc. 85 ft.
- 28.40 Spur, slopes NW. Desc. 20 ft.
- 36.75 Head of wash, course N. Asc. 480 ft.
- 38.50 Old road, brs. N. and S.
- 40.00 Set an iron post, 3 ft. long, 1 in. diam., 20 ins. in the
ground, in a mound of stone, for $\frac{1}{4}$ sec. cor., marked on
brass cap

$\frac{1}{4}$ S36
 $\frac{1}{4}$ S1
 1919

- And raise a mound of stone, 2 ft. base, $1\frac{1}{2}$ ft. high, N.
of cor.
- 67.00 Road, brs. NE. to Crown King and SW. to Boaz Mine.
- 68.50 Telephone line, brs. NE. to Crown King and SW. to Boaz Mine.
- 75.00 Spur, slopes N. Desc. 45 ft.
- 78.10 Head of draw, course N. Asc. 45 ft.
- 80.00 The cor. of Ts. 9 and 10 N., Rs. 1 and 2 W. hereinbefore de-
scribed.
Land, rough mountainous.
Soil, rocky, 4th rate.
No timber.
Undergrowth, mesquite, cat. claw and scrub oak.

Survey of the
Subdivision of T. 9 N., R. 2 W.

- From the reestablished standard cor. of secs. 35 and 36,
on the S. bdy. of Tp., hereinbefore described,
N. 0° 1' W., bet. secs. 35 and 36.
Over rolling mountainous land, through dense undergrowth.
Desc. 20 ft.
- 1.20 Head of draw, 3 lks. wide, course S. 60° E. Asc. 40 ft.
- 3.40 Spur, slopes S. 60° E. Desc. 50 ft.
- 14.00 Draw, course E. Thence along E. slope.
- 19.45 Draw, course SE. Asc. 35 ft.
- 33.80 Low spur, slopes SE. Desc. 10 ft.
- 34.25 Draw, course W. Asc. 35 ft.
- 38.75 Desc. 10 ft.
- 39.20 Draw, course W. Asc. 335 ft.
- 40.00 Set an iron post, 3 ft. long, 1 in. diam., 26 ins. in the
ground, for $\frac{1}{4}$ sec. cor., marked on brass cap

$\frac{1}{4}$
 S35 | S36
 1919

- And raise a mound of stone, 2 ft. base, $1\frac{1}{2}$ ft. high, W.
of cor.
- 53.70 Spur, slopes S. 10° E. Continue ascent.
- 63.40 Top of mountain. Saddle 2 chs. E. and high peak W. Desc.
90 ft.
- 67.80 Head of draw, course NW. Asc. 20 ft.
- 73.00 Desc.
- 77.00 Head of draw, course S. 60° W. Asc.
- 80.00 Set an iron post, 3 ft. long, 2 ins. diam., 24 ins. in the
ground, for cor. of secs. 25, 26, 35 and 36, marked on
brass cap

T9N | R2W
 S26 | S25
 S35 | S36
 1919

And raise a mound of stone, 2 ft. base, $1\frac{1}{2}$ ft. high, W.
of cor.

Survey of the
Subdivision of T. 9 N., R. 2 W.

Chains.

Land, rolling mountainous.
Soil, rocky, 4th rate.
No timber.
Undergrowth, mesquite, scrub oak and cat claw.

- 40.00 East on a random line, bet. secs. 25 and 36.
- 80.04 Set temp. $\frac{1}{4}$ sec. cor.
Intersect E. bdy. of Tp., 5 lks. S. of the cor. of secs. 25, 30, 31 and 36, hereinbefore described.
- Thence
- 3.80 S. $89^{\circ}58'W.$, on a true line, bet. secs. 25 and 36.
- 10.05 Over rough mountainous land, through dense undergrowth.
- 19.35 Asc. 55 ft.
- 23.20 Desc. 270 ft.
- 29.95 Spur from hill, slopes SW. Continue descent.
- 30.55 Draw, 20 lks. wide, course SW. Asc. 55 ft.
- 32.85 Trail, brs. N. and S.
- 35.60 Spur, slopes S. Desc. 10 ft.
- 35.95 Draw, 4 lks. wide, course S. Asc. 35 ft.
- 37.25 Trail, brs. N. to Mine and S. to Shack.
- 38.60 Mine shaft and hoist br. N. $19^{\circ}E.$, 8 chs. dist.
- 40.02 Shack brs. S. about 10 chs. dist.
Prospect hole, 10 ft. deep, on line.
Mouth of tunnel, brs. S. 1 ch. dist.
Spur, slopes S. Desc. 60 ft.
Set an iron post, 3 ft. long, 1 in. diam., 10 ins. in the ground, in a mound of stone, for $\frac{1}{4}$ sec. cor., marked on brass cap

$\frac{1}{4}$ S25
 $\frac{1}{4}$ S36
1919

And raise a mound of stone, 2 ft. base, $1\frac{1}{2}$ ft. high, N. of cor.

- 41.00 Trail, brs. N. and S.
- 43.85 Draw, 15 lks. wide, course S. Asc. 170 ft.
- 49.15 Low ridge, brs. N. and S. Mouth of tunnel brs. S. $84^{\circ}45'E.$
Shack brs. S. $68^{\circ}E.$ Desc.
- 53.25 Draw, course S. Asc. 110 ft.
- 59.75 Spur, slopes SE. Desc. 25 ft.
- 66.15 Head of draw, course SE. Asc. 135 ft.
- 71.15 Ridge, brs. N. and S. Desc. 235 ft.
- 80.04 The cor. of secs. 25, 26, 35 and 36.
Land, rough mountainous.
Soil, rocky, 4th rate.
No timber.
Undergrowth, scrub oak, mesquite and cactus.

- 1.50 N. $0^{\circ}1'W.$, bet. secs. 25 and 26.
- 8.90 Over rolling hills, through scattering undergrowth.
- 12.70 Desc. 15 ft.
- 18.50 Head of draw, course SW. Asc. 170 ft.
- 25.65 Point of spur, slopes SW. Desc.
- 28.60 Asc. 70 ft.
- 31.40 Ridge, brs. NW. and SE. Thence along E. slope.
- 33.50 Desc. 25 ft.
- 40.00 Asc. 75 ft.
Spur, slopes E. Desc. 60 ft.
Head of draw, course NW. Asc. 35 ft.
Set an iron post, 3 ft. long, 1 in. diam., 26 ins. in the ground, for $\frac{1}{4}$ sec. cor., marked on brass cap

$\frac{1}{4}$ S26 | S25
1919

Survey of the
Subdivision of T. 9 N., R. 2 W.

Chains. And raise a mound of stone, 2 ft. base, 1½ ft. high, W. of cor.
41.12 Spur, slopes SW. House brs. S.41°W. Desc. 15 ft.
45.90 Trail, brs. NE. and SW. Asc. 15 ft.
48.02 Spur, slopes NW. Trail, brs. NE. and SW. Same house, brs. S.27°W. Desc. 180 ft.
65.00 Wash, 10 lks. wide, course S.15°W. Asc. 170 ft.
80.00 Set an iron post, 3 ft. long, 2 ins. diam., 24 ins. in the ground, for cor. of secs. 23, 24, 25 and 26, marked on brass cap

T9N R2W
S23 | S24
S26 | S25
1919

And raise a mound of stone, 2 ft. base, 1½ ft. high, W. of cor.
Land, rolling hills.
Soil, rocky, 4th rate.
No timber.
Undergrowth, scrub oak, mesquite and cat claw.

40.00 N.89°58'E., on a random line, bet. secs. 24 and 25.
Set temp. ¼ sec. cor.
79.92 Intersect E. bdy. of Tp., 23 lks. N. of the cor. of secs. 19, 24, 25 and 30, hereinbefore described.

Thence
N.89°52'W., on a true line, bet. secs. 24 and 25.
Over rolling hills, through scattering undergrowth.
Desc. 105 ft.
10.15 Wash, 15 lks. wide, course SW. Asc. 50 ft.
12.30 Spur, slopes SW. Desc. 105 ft.
18.20 Wash, 50 lks. wide, course S. Asc. 95 ft.
21.90 Hill, brs. N. and S. Desc. 165 ft.
27.90 Wash, 10 lks. wide, course S.20°W. Asc. 30 ft.
33.90 Desc. 55 ft.
37.35 Wash, 5 lks. wide, course SW. Asc. 25 ft.
39.96 Set an iron post, 3 ft. long, 1 in. diam., 26 ins. in the ground, for ¼ sec. cor., marked on brass cap


¼ S24
¼ S25
1919

And raise a mound of stone, 2 ft. base, 1½ ft. high, N. of cor.
Desc. 45 ft.
44.30 Wash, 20 lks. wide, course SW. Asc. 35 ft.
51.65 Old road, brs. N. and S.
54.40 Low ridge, brs. NE. and SW. Desc. 50 ft.
68.35 Wash, 10 lks. wide, course SW. Asc. 55 ft.
79.92 The cor. of secs. 23, 24, 25 and 26.
Land, rolling hills.
Soil, rocky, 4th rate.
No timber.
Undergrowth, mesquite, scrub oak and cactus.


N.0°1'W., bet. secs. 23 and 24.
Over rolling hills, through scattering undergrowth.
Asc. 40 ft.
6.00 Low ridge, brs. NE. and SW. Desc. 130 ft.
16.30 Tussock Creek, course SW. Asc. 110 ft.
25.00 Spur, slopes SW. Old road, brs. E. and W. Desc. 20 ft.
29.20 Head of draw, course SW. Asc. 260 ft.
40.00 Set an iron post, 3 ft. long, 1 in. diam., 26 ins. in the ground, for ¼ sec. cor., marked on brass cap

Survey of the
Subdivision of T. 9 N., R. 2 W.

Chains.




- And raise a mound of stone, 2 ft. base, 1½ ft. high, W. of cor.
- 43.70 Spur, slopes E. Desc. 20 ft., along E. slope.
- 59.60 Head of draw, course SE. Asc. 255 ft.
- 77.10 Spur, slopes E. Desc. 30 ft.
- 80.00 Set an iron post, 3 ft. long, 2 ins. diam., 6 ins. in the ground, in a mound of stone, for cor. of secs. 13, 14, 23 and 24, marked on brass cap



And raise a mound of stone, 2 ft. base, 1½ ft. high, W. of cor.
 Land, rolling hills.
 Soil, rocky, 4th rate.
 No timber.
 Undergrowth, scrub oak, mesquite and cat claw.

- S.89°52'E., on a random line, bet. secs. 13 and 24.
- 40.00 Set temp. ¼ sec. cor.
- 80.02 Intersect E. bdy. of Tp., 16 lks. S. of the cor. of secs. 13, 18, 19 and 24, hereinbefore described.
- Thence
- N.89°59'W., on a true line, bet. secs. 13 and 24.
- Over mountainous land, through scattering undergrowth.
- Desc. 640 ft.
- 33.10 Wash, containing stream of water, 2 ft. wide, course S. Asc. 60 ft.
- 36.15 Desc. 35 ft.
- 40.01 Set an iron post, 3 ft. long, 1 in. diam., 24 ins. in the ground, in a mound of stone, for ¼ sec. cor., marked on brass cap.



- And raise a mound of stone, 2 ft. base, 1½ ft. high, N. of cor.
- 43.00 Draw, course SW. Asc. 30 ft.
- 46.50 Spur, slopes SW. Desc. 210 ft.
- 67.80 Wash, 50 lks. wide, course S. Asc. 210 ft.
- 80.02 The cor. of secs. 13, 14, 23 and 24.
- Land, mountainous.
- Soil, rocky, 4th rate.
- No timber.
- Undergrowth, mesquite, scrub oak and cactus.

- N.0°1'W., bet. secs. 13 and 14.
- Over rough mountainous land, through scattering undergrowth.
- Desc. 35 ft.
- 0.85 Head of draw, course E. Asc. 285 ft.
- 17.26 Ridge, brs. NE. and SW., and top of cliff, 80 ft. high, faces SE. Shack brs. N.65°W. Desc. 305 ft.
- 40.00 Set an iron post, 3 ft. long, 1 in. diam., 26 ins. in the ground, for ¼ sec. cor., marked on brass cap

Survey of the
Subdivision of T. 9 N., R. 2 W.

Chains.

1/4
S14 | S13
1919

- 47.66 And raise a mound of stone, 2 ft. base, 1 1/2 ft. high, W. of cor.
- 62.70 Draw, course S.7°W. Asc. 190 ft.
- 65.66 Spur, slopes SE. Desc. 30 ft.
- 71.62 Head of draw, course SE. Asc. 110 ft.
- 78.60 Ridge, brs. E. and SW. Shack brs. N.21°15'W. Desc. 90 ft.
- 80.00 Spur, slopes W. Continue descent.
- Set an iron post, 3 ft. long, 2 ins. diam., 20 ins. in the ground, in a mound of stone, for cor. of secs. 11, 12, 13 and 14, marked on brass cap

T9N | R2W
S11 | S12
S14 | S13
1919

And raise a mound of stone, 2 ft. base, 1 1/2 ft. high, W. of cor.
Land, rough mountainous.
Soil, rocky, 4th rate.
No timber.
Undergrowth, mesquite, scrub oak and cat claw.

- 40.00 S.89°59'E., on a random line, bet. secs. 12 and 13.
- 79.98 Set temp. 1/4 sec. cor.
- Intersect E. bdy. of Tp., 23 lks. S. of the cor. of secs. 7, 12, 13 and 18, hereinbefore described.
- Thence
- S.89°51'W., on a true line, bet. secs. 12 and 13.
- Over mountainous land, through dense undergrowth.
- Asc. 45 ft.
- 6.40 Spur, slopes SW. Desc. 795 ft.
- 24.80 Desc. in draw, course W.
- 31.60 Leave draw, course S.80°W.
- 39.99 Set a granite stone, 16 X 14 X 8 ins., 6 ins. in the ground, for 1/4 sec. cor., marked 1/4 on N. face; and raise a mound of stone, 2 ft. base, 1 1/2 ft. high, N. of cor.
- 42.50 Draw, course SW., from N.80°W. Asc. 25 ft.
- 54.00 Spur, slopes SW. Desc. 380 ft
- 75.35 Draw, course N.70°W. Asc. 140 ft.
- 79.98 The cor. of secs. 11, 12, 13 and 14.
- Land, rough mountainous.
- Soil, rocky, 4th rate.
- No timber.
- Undergrowth, mesquite, scrub oak and cat claw.

- N.0°1'W., bet. secs. 11 and 12.
- Over rough mountainous land, through scattering undergrowth.
- Desc. 15 ft.
- 1.00 Draw, course NW. Asc. 20 ft.
- 3.50 Desc. 75 ft.
- 7.30 Draw, course W. Asc. 110 ft.
- 13.30 Spur, slopes W. Desc. 110 ft.
- 19.50 Wash, course SW. Asc. 295 ft.
- 34.10 Spur, slopes SW. Shack brs. S.49 1/2°W. Desc. 90 ft.
- 36.34 Head of draw, course W. Asc. 140 ft.
- 40.00 Set an iron post, 3 ft. long, 1 in. diam., 26 ins. in the ground, for 1/4 sec. cor., marked on brass cap

1/4
S11 | S12
1919

Survey of the
Subdivision of T. 9 N., R. 2 W.

Chains.

And raise a mound of stone, 2 ft. base, 1½ ft. high, W. of cor.

41.10 Point of spur, slopes W. Desc. 80 ft.
 42.80 Draw, course W. Asc. 110 ft.
 53.00 Point of spur, slopes W. Desc. 35 ft.
 56.25 Head of draw, course W. Asc. 230 ft.
 64.50 Spur, slopes W. Desc. 70 ft.
 74.60 Ryeland Creek, course SW. Asc. 70 ft.
 80.00 Set an iron post, 3 ft. long, 2 ins. diam., 12 ins. in the ground, in a mound of stone, for cor. of secs. 1, 2, 11 and 12, marked on brass cap

T9N R2W
 S 2 | S 1
 S11 | S12
 1919

And raise a mound of stone, 2 ft. base, 1½ ft. high, W. of cor.

Land, rough mountainous.
 Soil, rocky, 4th rate.
 No timber.
 Undergrowth, cat claw, scrub oak and mesquite.

40.00 N.89°51'E., on a random line, bet. secs. 1 and 12.
 Set temp. ¼ sec. cor.
 80.00 Intersect E. bdy. of Tp., 7 lks. N. of the cor. of secs. 1, 6, 7 and 12, hereinbefore described.

Thence
 S.89°54'W., on a true line, bet. secs. 1 and 12.
 Over rough mountainous land, through dense undergrowth.
 Desc. 70 ft.
 17.65 Asc. 30 ft.
 20.40 Desc. 115 ft.
 29.70 Draw, course SW. Asc. 160 ft.
 35.00 Point of spur, slopes SW. Desc. 210 ft.
 40.00 Set an iron post, 3 ft. long, 1 in. diam., 26 ins. in the ground, for ¼ sec. cor., marked on brass cap

¼ S 1
 ¼ S12
 1919

And raise a mound of stone, 2 ft. base, 1½ ft. high, N. of cor.

62.30 Draw, containing small stream of water, course NW. Asc. 50 ft.
 66.45 Point of spur, slopes N. Taylor's Cabin brs. N. 9 chs. dist. Desc. 180 ft.
 78.00 Ryeland Creek, course S.70°W. Asc. 20 ft.
 80.00 The cor. of secs. 1, 2, 11 and 12.
 Land, rough mountainous.
 Soil, rocky, 4th rate.
 No timber.
 Undergrowth, scrub oak, cat claw and mesquite.

40.00 N.0°1'W., on a random line, bet. secs. 1 and 2.
 Set temp. ¼ sec. cor.
 80.08 Intersect N. bdy. of Tp., 15 lks. W. of the cor. of secs. 1, 2, 35 and 36, hereinbefore described.

Thence
 S.0°5'W., on a true line, bet. secs. 1 and 2.
 Over rough mountainous land, through dense undergrowth.
 Asc. 115 ft.
 7.80 Head of draw, course NW. Continue ascent, 170 ft.
 15.70 Ridge, brs. E. and W. Desc. 370 ft.
 30.80 Wash, course SW. Asc. 65 ft.
 38.10 Point of spur, slopes SW. Desc. 80 ft.

158

Survey of the
Subdivision of T. 9 N., R. 2 W.

Chains.
40.08 Set an iron post, 3 ft. long, 1 in. diam., 24 ins. in the ground, in a mound of stone, for $\frac{1}{4}$ sec. cor., marked on brass cap

$\frac{1}{4}$
 S 2 | S 1
 1919

And raise a mound of stone, 2 ft. base, $1\frac{1}{2}$ ft. high, W. of cor.

43.40 Head of draw, course SW. Asc.
44.55 Desc. 60 ft.
53.05 Head of draw, course SW. Asc. 15 ft.
56.05 Ridge, brs. NE. and SW. Divide between Castle Creek and Hassayampa Creek. Desc. 70 ft.
67.40 Old road, brs. E. and W. Asc.
71.80 Spur, slopes SW. Desc. 140 ft.
80.08 The cor. of secs. 1, 2, 11 and 12.
Land, rough mountainous.
Soil, rocky, 4th rate.
No timber.
Undergrowth, mesquite, cat claw and scrub oak.

From the reestablished standard cor. of secs. 34 and 35, on the S. bdy. of Tp., hereinbefore described, N.0°1'W., bet. secs. 34 and 35. Over mountainous land, through scattering undergrowth. Desc. 95 ft.

7.70 Draw, 20 lks. wide, course S.15°E. Asc. 200 ft.
13.90 Spur, slopes E. Desc. 190 ft.
23.00 Head of draw, course NE. Asc. 20 ft.
25.00 Point of spur, slopes NE. Desc.
38.00 Draw, course S.30°E. Asc. 445 ft.
40.00 Set a mica schist, 18 X 12 X 4 ins., 12 ins. in the ground, for $\frac{1}{4}$ sec. cor., marked $\frac{1}{4}$ 1919 on W. face; and raise a mound of stone, 2 ft. base, $1\frac{1}{2}$ ft. high, W. of cor.

45.00 Draw, course S.20°E. Continue ascent.
52.00 Spur, slopes E. Desc. 220 ft.
60.20 Head of draw, course N.30°E.
63.00 Head of draw, course E. Asc. 190 ft.
70.00 Spur, slopes E. Desc. 285 ft.
80.00 Set an iron post, 3 ft. long, 2 ins. diam., 20 ins. in the ground, in a mound of stone, for cor. of secs. 26, 27, 34 and 35, marked on brass cap

T9N R2W
 S27 | S26
 S34 | S35
 1919

And raise a mound of stone, 2 ft. base, $1\frac{1}{2}$ ft. high, W. of cor.
Land, rough mountainous.
Soil, rocky, 4th rate.
No timber.
Undergrowth, mesquite, cat claw and scrub oak.

40.00 East on a random line, bet. secs. 26 and 35.
79.98 Set temp. $\frac{1}{4}$ sec. Intersect N. and S. line, at the cor. of secs. 25, 26, 35 and 36.
Thence West on a true line, bet. secs. 26 and 35. Over rough mountainous land, through dense undergrowth. Desc.

2.50 Gulch, course SW. Desc. 15 ft.
5.00 Desc.
9.50 Draw, 6 lks. wide, course SW. Asc. 55 ft.

Survey of the
Subdivision of T. 9 N., R. 2 W.

Chains.

- 16.50 Spur, slopes S. Desc. 210 ft.
- 23.70 Draw, 10 lks. wide, course S.10°W. Asc. 65 ft.
- 29.60 Saddle in ridge, brs. NE. and SW. Desc. 285 ft.
- 39.90 Draw, course N.70°W., from N.60°E. Continue descent.
- 39.99 Set an iron post, 3 ft. long, 1 in. diam., 18 ins. in the ground, in a mound of stone, for $\frac{1}{4}$ sec. cor., marked on brass cap

$\frac{1}{4}$ S26
 $\frac{1}{4}$ S35
 1919

And raise a mound of stone, 2 ft. base, 1½ ft. high, N. of cor.

- 52.35 Enter Bantley Creek, containing stream of water, 3 lks. wide, 2 ins. deep, course S.
- 54.00 Leave Bantly Creek; asc. 240 ft.
- 72.70 Desc. 25 ft.
- 79.98 The cor. of secs. 26, 27, 34 and 35.
Land, rough mountainous.
Soil, rocky, 4th rate.
No timber.
Undergrowth, mesquite, scrub oak and cactus.

N.0°1'W., bet. secs. 26 and 27.
Over rough mountainous land, through scattering undergrowth.
Desc. 75 ft.

- 3.30 Wash, 8 lks. wide, course NE. Asc. 40 ft.
- 9.20 Desc. 30 ft.
- 10.50 Wash, 10 lks. wide, course E. Thence along E. slope.
- 16.55 Wash, 20 lks. wide, course SE. Asc. 355 ft.
- 27.74 Ridge, brs. NW. and SE. Desc. 90 ft.
- 33.25 Head of draw, course E. Asc. 25 ft.
- 36.00 Spur, slopes N.60°E. Desc. 175 ft.
- 40.00 Set an iron post, 3 ft. long, 1 in. diam., 12 ins. in the ground, in a mound of stone, for $\frac{1}{4}$ sec. cor., marked on brass cap

$\frac{1}{4}$
 S27 | S26
 1919

And raise a mound of stone, 2 ft. base, 1½ ft. high, W. of cor.

- 45.54 Wash, 15 lks. wide, course E. Asc. 445 ft.
- 59.90 Spur, slopes SE. Desc. 275 ft.
- 70.35 Asc. 300 ft.
- 80.00 Set an iron post, 3 ft. long, 2 ins. diam., 24 ins. in the ground, for cor. of secs. 22, 23, 26 and 27, marked on brass cap

T9N R2W
 S22 | S23
 S27 | S26
 1919

And raise a mound of stone, 2 ft. base, 1½ ft. high, W. of cor.

Land, rough mountainous.
Soil, rocky, 4th rate.
No timber.
Undergrowth, cat claw, mesquite and scrub oak.

- 40.00 East on a random line, bet. secs. 23 and 26.
Set temp. $\frac{1}{4}$ sec. cor.
- 79.96 Intersect N. and S. line, 3 lks. N. of the cor. of secs. 23, 24, 25 and 26.
Thence
N.89°59'W., on a true line, bet. secs. 23 and 26.

Survey of the
Subdivision of T. 9 N., R. 2 W.

Chains.
Over rough mountainous land, through scattering undergrowth.
Asc. 80 ft.
6.00 Low ridge, brs. NE. and SW. Desc. 280 ft.
22.30 Tussock Creek, stream of water, 2 lks. wide, course SW.,
in bed of wash, 20 lks. wide, course SW. Asc. 40 ft.
24.75 Point of spur, slopes S. Desc. 45 ft.
26.60 Asc. 220 ft.
38.00 Point of spur, slopes S. Desc.
39.50 Head of draw, course SE. Asc. 250 ft.
39.98 Set an iron post, 3 ft. long, 1 in. diam., 24 ins. in the
ground, in a mound of stone, for $\frac{1}{4}$ sec. cor., marked on
brass cap

$\frac{1}{4}$ $\frac{S23}{S26}$
1919

And raise a mound of stone, 2 ft. base, $1\frac{1}{2}$ ft. high, N.
of cor.
50.16 Ridge, brs. N. and S. Desc. 440 ft.
67.90 Wash, 50 lks. wide, course S. Asc. 435 ft.
79.96 The cor. of secs. 22, 23, 26 and 27.
Land, rough mountainous.
Soil, rocky, 4th rate.
No timber.
Undergrowth, mesquite, cat claw and scrub oak.

N. 0° 1' W., bet. secs. 22 and 23.
Over rough mountainous land, through scattering undergrowth.
Asc. 155 ft.
4.23 Spur, slopes E. Desc. 90 ft.
11.35 Head of draw, course E. Asc. 55 ft.
18.00 Spur, slopes E. Desc. 15 ft.
21.10 Draw, course SE. Asc. 140 ft.
28.36 Spur, slopes SE. Desc. 140 ft.
40.00 Set an iron post, 3 ft. long, 1 in. diam., 26 ins. in the
ground, for $\frac{1}{4}$ sec. cor., marked on brass cap

$\frac{1}{4}$
S22 | S23
1919

And raise a mound of stone, 2 ft. base, $1\frac{1}{2}$ ft. high, W.
of cor.
42.90 Wash, 8 lks. wide, course SE. Spring in wash. Asc. 175 ft.
49.40 Spur, slopes SE. Desc. 150 ft.
55.30 Head of draw, course E. Asc. 130 ft.
59.25 Spur, slopes E. Desc. 115 ft.
65.00 Draw, course E. Asc. 70 ft.
67.60 Spur, slopes E. Desc. 110 ft.
70.65 Draw, course E. Asc. 85 ft.
75.50 Spur, slopes E. Desc. 75 ft.
80.00 Set an iron post, 3 ft. long, 2 ins. diam., 20 ins. in the
ground, in a mound of stone, for cor. of secs. 14, 15,
22 and 23, marked on brass cap

T9N | R2W
S15 | S14
S22 | S23
1919

And raise a mound of stone, 2 ft. base, $1\frac{1}{2}$ ft. high, W.
of cor.
Land, rough mountainous.
Soil, rocky, 4th rate.
No timber.
Undergrowth, mesquite, cat claw and scrub oak.

Survey of the
Subdivision of T. 9 N., R. 2 W.

Chains
 40.00 S. 89° 59' E. on a random line, bet. secs. 14 and 23.
 80.02 Set temp. $\frac{1}{4}$ sec. cor.
 Intersect N. and S. line, 2 lks. S. of the cor. of secs.
 13, 14, 23 and 24.
 Thence
 West on a true line, bet. secs. 14 and 23.
 Over rough mountainous land, through scattering undergrowth.
 2.50 Trail brs. NW. and SE. Asc. 410 ft.
 21.40 Ridge brs. N. and S. Desc. 605 ft.
 40.01 Set an iron post, 3 ft. long, 1 in. diam., 26 ins. in the
 ground for $\frac{1}{4}$ sec. cor., mkd. on brass cap

$\frac{1}{4}$ S 14
 $\frac{1}{4}$ S 23
 1919

and raise a mound of stone, 2 ft. base, $1\frac{1}{2}$ ft. high, N.
 of cor.
 43.80 Head of draw, course SW. Asc. 30 ft.
 45.45 Desc. 160 ft.
 54.00 Old road brs. NW. and SE.
 55.80 Ryland Creek, 60 lks. wide, containing stream of water,
 5 lks. wide, course S. Asc. 45 ft.
 57.00 Point of spur slopes S. Desc. 60 ft.
 62.00 Wash, 10 lks. wide, course S. Asc. 175 ft.
 67.70 Point of spur slopes S. Desc. 35 ft.
 76.00 Wash, 10 lks. wide, course SE. Asc. 90 ft.
 80.02 The cor. of secs. 14, 15, 22 and 23.
 Land, rough mountainous.
 Soil, rocky, 4th rate.
 No timber.
 Undergrowth, mesquite, cat claw and scrub oak.

N.0°1'W., bet. secs. 14 and 15.
 Over rough mountainous land, through scattering undergrowth.
 Desc. 60 ft.
 4.60 Draw, course SE. Asc. 75 ft.
 7.30 Spur, slopes E. Desc. 25 ft.
 11.60 Wash, course E. Asc. 75 ft.
 16.90 Desc. 10 ft.
 17.60 Draw, course SE. Asc. ... ft.
 23.00 Spur, slopes SE. Desc. 165 ft.
 34.20 Draw, course SE. Asc. 160 ft.
 40.00 Set an iron post, 3 ft. long, 1 in. diam., 26 ins. in the
 ground, for $\frac{1}{4}$ sec. cor., marked on brass cap

$\frac{1}{4}$ S 15
 $\frac{1}{4}$ S 14
 1919

and raise a mound of stone, 2 ft. base, $1\frac{1}{2}$ ft. high, W.
 of cor.
 Desc. 80 ft.
 54.00 Asc. 25 ft.
 58.90 Desc. 60 ft.
 63.50 Draw, course SE. Asc. 315 ft.
 74.15 Spur, slopes SE. Old road, brs. NW. and SE. Desc. 80 ft.
 80.00 Set a basalt stone, 12 X 12 X 4 ins., 6 ins. in the ground,
 in a mound of stone, for cor. of secs. 10, 11, 14 and 15,
 marked with 2 notches on E. and 4 notches on S. edge;
 and raise a mound of stone, 2 ft. base, $1\frac{1}{2}$ ft. high,
 W. of cor.
 Land, mountainous.
 Soil, rocky, 4th rate.
 No timber.
 Undergrowth, mesquite, cat claw and scrub oak.

Survey of the
Subdivision of T. 9 N., R. 2 W.

Chains

East on a random line bet. secs. 11 and 14.
 40.00 Set temp. $\frac{1}{4}$ sec. cor.
 80.04 Intersect N. and S. line, 5 lks. N. of the cor. of secs. 11, 12, 13 and 14.
 Thence
 N. $89^{\circ}58'W.$, on a true line bet. secs. 11 and 14.
 Over rough mountainous land, through scattering undergrowth.
 Asc.
 2.05 Spur, slopes NW. Desc. 145 ft.
 9.95 Draw, course NW. Asc. 25 ft.
 16.95 Spur, slopes NW. Desc. 105 ft.
 27.85 Ryeland Creek, course SW. Asc. 150 ft.
 34.55 Point of spur, slopes S. Desc. 160 ft.
 40.02 Set a granite stone, 14 X 14 X 5 ins., 6 ins. in the ground, in a mound of stone, for $\frac{1}{4}$ sec. cor., marked $\frac{1}{4}$ on N. face; and raise a mound of stone, 2 ft. base, $1\frac{1}{2}$ ft. high, N. of cor.
 40.55 Gulch, course SE. Asc. 375 ft.
 66.20 Desc. 35 ft.
 78.15 Draw, course NE., from NW. Asc. 70 ft.
 80.04 The cor. of secs. 10, 11, 14 and 15.
 Land, rough mountainous.
 Soil, rocky, 4th rate.
 No timber.
 Undergrowth, mesquite, cat claw and scrub oak.

N. $0^{\circ}1'W.$, bet. secs. 10 and 11.
 Over rough mountainous land, through scattering undergrowth.
 Desc. 40 ft.
 2.00 Head of draw, course E. Asc. 110 ft.
 8.50 Spur, slopes E. Desc. 150 ft.
 38.00 Draw, course S. $30^{\circ}E.$ Asc. 230 ft.
 40.00 Set a basalt stone, 14 X 16 X 8 ins., 6 ins. in the ground, in a mound of stone, for $\frac{1}{4}$ sec. cor., marked $\frac{1}{4}$ on W. face; and raise a mound of stone, 2 ft. base, $1\frac{1}{2}$ ft. high, N. of cor.
 46.00 Top of cliff, brs. NW. and SE., and faces SW. Desc. 55 ft.
 55.00 Asc. 225 ft.
 74.26 Ridge brs. E. and W. Divide between Castle Creek and Hassayampa Creek. Desc. 120 ft.
 80.00 Set an iron post, 3 ft. long, 2 ins. diam., 14 ins. in the ground, in a mound of stone, for cor. of secs. 2, 3, 10 and 11, marked on brass cap

T9N	R2W
S 3	S 2
S10	S11
1919	

and raise a mound of stone, 2 ft. base, $1\frac{1}{2}$ ft. high, W. of cor.
 Land, mountainous.
 Soil, rocky, 4th rate.
 No timber.
 Undergrowth, mesquite, cat claw, and scrub oak.

S. $89^{\circ}58'E.$, on a random line, bet. secs. 2 and 11.
 40.00 Set temp. $\frac{1}{4}$ sec. cor.
 79.90 Intersect N. and S. line, 5 lks. N. of the cor. of secs. 1, 2, 11 and 12.
 Thence
 N. $89^{\circ}56'W.$, on a true line, bet. secs. 2 and 11.
 Over mountainous land, through scattering undergrowth.
 Asc. 45 ft.

Survey of the
Subdivision of T. 9 N., R. 2 W.

Chains.
 2.90 Spur, slopes S. Desc. 60 ft.
 8.20 Draw, course SW. Asc. 65 ft.
 13.10 Spur, slopes SW. Desc. 180 ft.
 28.00 Draw, course SW. Asc. 115 ft.
 39.95 Set an iron post, 3 ft. long, 1 in. diam., 26 ins. in the ground, for $\frac{1}{4}$ sec. cor., marked on brass cap

$\frac{1}{4}$ S 2
 $\frac{1}{4}$ S 11
 1919

And raise a mound of stone, 2 ft. base, $1\frac{1}{2}$ ft. high, N. of cor.

Desc. 25 ft.
 51.15 Head of draw, course N. Asc. 40 ft.
 55.30 Desc. 75 ft.
 70.60 Asc. 30 ft.
 76.10 Spur, slopes N. Desc. 50 ft.
 79.90 The cor. of secs. 2, 3, 10 and 11.
 Land, mountainous and rolling.
 Soil, rocky, 4th rate.
 No timber.
 Undergrowth, mesquite, scrub oak and cat claw.

40.00 N.0°1'W., on a random line, bet. secs. 2 and 3.
 Set temp. $\frac{1}{4}$ sec. cor.
 79.95 Intersect N. bdy. of Tp., 7 lks. W. of the cor. of secs. 2, 3, 34 and 35, hereinbefore described.
 Thence
 S:0°2'W., on a true line, bet. secs. 2 and 3.
 Over rolling hills, through scattering undergrowth.
 Desc. 45 ft.
 5.05 Draw, course S.15°W. Asc. 75 ft.
 11.10 Desc. 45 ft.
 15.60 Asc. 15 ft.
 22.20 Desc. 135 ft.
 31.65 Pipe line, brs. NW. and SE..
 35.45 Oak Creek, course SW,
 36.15 Road, brs. NE. and SW.
 36.45 Fence, brs. NE. and SW.
 39.40 J. M. Johnson's house brs. N.35°E., 2.68 chs. dist.
 Reservoir brs. East 5 chs. dist.
 39.95 Set an iron post, 3 ft. long, 1 in. diam., 26 ins. in the ground, for $\frac{1}{4}$ sec. cor., marked on brass cap

$\frac{1}{4}$
 S 3 | S 2
 1919

Dig pits, 18 X 18 X 12 ins., N. and S. of post, 3 ft. dist.

From this cor., U. S. G. S. B. M., elevation No. 4354, a 3 in. iron post, brs. S.47°42'W., 19.80 chs. dist.
 42.65 Fence, brs. NE. and SW. Thence over level land.
 57.95 Old road, brs. E. and W.
 58.45 Wash, course W.
 63.35 Draw, course NW. Asc. 105 ft.
 72.95 Spur, slopes N.70°W. Desc.
 79.95 The cor. of secs. 2, 3, 10 and 11.
 Land, level and rolling hills.
 Soil, rocky, 4th rate.
 No timber.
 Undergrowth, mesquite, cat claw and scrub oak.

From the reestablished standard cor. of secs. 33 and 34, hereinbefore described, on S. bdy. of Tp. (2nd. Std. Par. N.).

Survey of the
Subdivision of T. 9 N., R. 2 W.

Chains.

N.0°2'W., bet. secs. 33 and 34.
Over rough mountainous land, through dense undergrowth.
Asc. 15 ft.
2.50 Desc. 60 ft.
11.82 Draw, course SW. Asc. 15 ft.
14.60 Desc. 25 ft.
15.60 Copperopolis Creek, 20 lks. wide, containing stream of
water, 0.5 ft. wide, 1 ft. deep, course SW. Asc. 25 ft.
18.00 Desc. 15 ft.
18.53 Same creek, course SE. Asc. 65 ft.
29.70 Desc. 20 ft.
31.40 Same creek, course SW. Asc. 90 ft.
40.00 Set an iron post, 3 ft. long, 1 in. diam., 26 ins. in the
ground, for $\frac{1}{4}$ sec. cor., marked on brass cap

$\frac{1}{4}$
 S33 | S34
 1919

And raise a mound of stone, 2 ft. base, $1\frac{1}{2}$ ft. high, W.
of cor.
From this cor., U. S. L. M. No. 1, Castle Creek Mining
District, which is a granite out crop, 12 X 10 X $1\frac{1}{2}$
ft. above ground, marked and witnessed as described
by the Surveyor-General, brs. N.81 $\frac{1}{2}$ °W., 23.06 chs. dist.
43.20 House on line. Desc. 25 ft.
45.63 Same creek, course S.15°E. Asc. 25 ft.
48.87 U. S. L. M. No. 1; Castle Creek Mining District, brs.
S.77°W. Desc. 45 ft.
50.85 Copperopolis Mine Shaft brs. East 2 chs. dist.
Same creek, course SW. Asc. 45 ft.
53.20 Desc.
55.60 Same creek, course S.20°E. Asc. 55 ft.
56.60 Desc. 45 ft.
59.20 Same creek, course S.20°W. Asc. 40 ft.
60.60 Desc. 20 ft.
61.85 Same creek, course SE. Asc. 60 ft.
66.80 Desc. 30 ft.
67.45 Same creek, course SW., from NW. Asc. 170 ft.
80.00 Set an iron post, 3 ft. long, 2 ins. diam., 19 ins. in the
ground, in a mound of stone, for cor. of secs. 27, 28,
33 and 34, marked on brass cap

T9N | R2W
 S28 | S27
 S33 | S34
 1919

And raise a mound of stone, 2 ft. base, $1\frac{1}{2}$ ft. high, W.
of cor.
Land, rough mountainous.
Soil, rocky, 4th rate.
No timber.
Undergrowth, mesquite, cat claw and scrub oak.

40.00 East on a random line, bet. secs. 27 and 34.
Set temp. $\frac{1}{4}$ sec. cor.
80.00 Intersect N. and S. line, 5 lks. N. of the cor. of secs.
26, 27, 34 and 35,
Thence
N.89°58'W., on a true line, bet. secs. 27 and 34.
Over mountainous land, through dense undergrowth.
Desc. 15 ft.
8.20 Head of draw, course NE. Asc. 435 ft.
23.00 Ridge, brs. N. and S. Desc. 165 ft.
29.40 Draw, course S. Asc. 270 ft.
37.00 Thence along S. slope.
40.00 Set an iron post, 3 ft. long, 1 in. diam., 24 ins. in the
ground, in a mound of stone, for $\frac{1}{4}$ sec. cor., marked on
brass cap

Survey of the
Subdivision of T. 9 N., R. 2 W.

Chains.

$\frac{1}{4}$ S27
 $\frac{1}{4}$ S34
1919

And raise a mound of stone, 2 ft. base, $1\frac{1}{2}$ ft. high, N. of cor.

51.30 Head of draw, course S. Asc. 75 ft.
 60.00 Spur, slopes S.20°W. Desc. 400 ft.
 75.30 Head of draw, course S. Asc. 45 ft.
 77.00 Spur, slopes SW. Desc. 100 ft.
 80.00 The cor. of secs. 27, 28, 33 and 34.
 Land, rough mountainous.
 Soil, very rocky, 4th rate.
 No timber.
 Undergrowth, palo verde, cat claw, buck brush and mesquite.

N.0°2'W., bet. secs. 27 and 28.
 Over rough mountainous land, through dense undergrowth.
 Asc. 400 ft.

6.00 Head of draw, course SW. Continue ascent.
 12.60 Spur, slopes SW. Desc. 210 ft.
 24.90 Draw, course W. Asc. 145 ft.
 29.30 Low spur, slopes SW. Desc. 85 ft.
 35.63 Draw, course W. Asc. 185 ft.
 40.00 Set an iron post, 3 ft. long, 1 in. diam., 26 ins. in the ground, for $\frac{1}{4}$ sec. cor., marked on brass cap

$\frac{1}{4}$
S28 | S27
1919

And raise a mound of stone, 2 ft. base, $1\frac{1}{2}$ ft. high, W. of cor.

42.20 Spur, slopes W. Desc. 140 ft.
 49.10 Copperopolis Creek, course W. Asc. 145 ft.
 54.00 Spur, slopes E. Lehman's Mill brs. N.34°E. Desc. 20 ft.
 55.20 Head of draw, course E. Asc. 40 ft.
 61.60 Desc. Trail brs. NE. and SW.
 65.25 Head of draw, course E. Asc. 190 ft.
 71.30 Desc. 155 ft.
 73.64 Lehman's Mill brs. S.76 $\frac{1}{2}$ °E.
 79.70 Two inch pipe line brs. SE. to Lehman's Mill.
 80.00 Set an iron post, 3 ft. long, 2 ins. diam., 12 ins. in the ground, in a mound of stone, for cor. of secs. 21, 22, 27 and 28, marked on brass cap

T9N R2W
S21 | S22
S28 | S27
1919

And raise a mound of stone, 2 ft. base, $1\frac{1}{2}$ ft. high, W. of cor.
 Land, mountainous.
 Soil, rocky, 4th rate.
 No timber.
 Undergrowth, palo verde, cat claw, buck brush and mesquite.

S.89°58'E., on a random line, bet. secs. 22 and 27.
 40.00 Set temp. $\frac{1}{4}$ sec. cor.
 80.02 Intersect N. and S. line, 5 lks. S. of the cor. of secs. 22, 23, 26 and 27.
 Thence
 West on a true line, bet. secs. 22 and 27.
 Over mountainous land, through dense undergrowth.
 Asc. 250 ft.
 4.67 Ridge, brs. N. and S. Desc. 175 ft.

Survey of the
Subdivision of T. 9 N., R. 2 W.

Chains.
 9.10 Head of draw, course S. Asc. 50 ft.
 17.55 Spur, slopes S. Desc. 210 ft.
 28.20 Draw, 15 lks. wide, course SE. Asc. 470 ft.
 40.01 Set an iron post, 3 ft. long, 1 in. diam., 9 ins. in the ground, in a mound of stone, for $\frac{1}{4}$ sec. cor., marked on brass cap

$\frac{1}{4}$ S22
 $\frac{1}{4}$ S27
 1919

And raise a mound of stone, 2 ft. base, $1\frac{1}{2}$ ft. high, N. of cor.

42.85 Ridge, brs. N. and S. Desc. 115 ft.
 45.00 Trail, brs. N. and S.
 47.20 Head of draw, course SW. Asc. 30 ft.
 50.70 Desc. 100 ft.
 55.00 Same draw, course NW. Asc. 80 ft.
 58.80 Spur, slopes NW. Desc. 150 ft.
 68.00 Draw, 30 lks. wide, course S. Old road in draw, brs. N. and S. Asc. 65 ft.
 76.55 Desc. 15 ft.
 77.90 Draw, 20 lks. wide, course S. 70° E. Asc. 15 ft.
 80.02 The cor. of secs. 21, 22, 27 and 28.
 Land, rough mountainous.
 Soil, rocky, 4th rate.
 No timber.
 Undergrowth, palo verde, buck brush, cat claw and mesquite.

N. $0^{\circ}2'$ W., bet. secs. 21 and 22.
 Over rough mountainous land, through dense undergrowth.
 Desc.

0.50 Draw, 20 lks. wide, course S. 70° E. Asc. 470 ft.
 14.17 Spur, slopes SE. Desc. 95 ft.
 20.00 Head of draw, course E. Asc. 135 ft.
 29.50 Spur, slopes E. Desc.
 29.80 Head of draw, course E. Asc. 165 ft.
 34.00 Spur, slopes E. Thence along E. slope.
 40.00 Set an iron post, 3 ft. long, 1 in. diam., 12 ins. in the ground, in a mound of stone, for $\frac{1}{4}$ sec. cor., marked on brass cap

$\frac{1}{4}$
 S21 | S22
 1919

And raise a mound of stone, 2 ft. base, $1\frac{1}{2}$ ft. high, W. of cor.
 Asc. 40 ft.
 Desc. 80 ft.

43.50 Head of draw, course E. Asc. 250 ft.
 46.20 Set an iron post, 3 ft. long, 2 ins. diam., 18 ins. in the ground, for cor. of secs. 15, 16, 21 and 22, marked on brass cap

T9N | R2W
 S16 | S15
 S21 | S22
 1919

And raise a mound of stone, 2 ft. base, $1\frac{1}{2}$ ft. high, W. of cor.
 Land, mountainous.
 Soil, rocky, 4th rate.
 No timber.
 Undergrowth, mesquite, scrub oak, buck brush and catclaw.

40.00 East on a random line, bet. secs. 15 and 22.
 Set temp. $\frac{1}{4}$ sec. cor.

Survey of the
Subdivision of T. 9 N., R. 2 W.

Chains	
80.06	Intersect N. and S. line, 4 lks. N. of the cor. of secs. 14, 15, 22 and 23, Thence N.89°58'W., on a true line, bet. secs. 15 and 22. Over rough mountainous land, through dense undergrowth. Asc. 360 ft.
15.25	Desc. 10 ft.
15.70	Head of draw, course NE. Asc. 260 ft.
21.70	Spur slopes SE.
28.45	U. S. G. S. B. M., elevation 4569, brs. S.16°W., 7.90 chs. dist.
29.80	Ridge brs, N, and S. Old road brs. N. and S. Desc. 205 ft.
38.00	Head of draw, course SW. Asc. 95 ft.
40.03	Set a granite stone, 16 X 12 X 12 ins., 8 ins. in the ground, in a mound of stone, for $\frac{1}{4}$ sec. cor., marked $\frac{1}{4}$ ft. high, N. of cor.
47.80	Spur, slopes S. Desc. 100 ft.
54.40	Head of draw, course S.60°E. Asc. 220 ft.
58.75	Point of spur, slopes S. Desc. 25 ft.
60.20	Head of draw, course SE. Asc. 280 ft.
66.40	Spur, slopes S. Desc. 90 ft.
77.00	Draw, course S. Asc. 80 ft.
80.06	The cor. of secs. 15, 16, 21 and 22. Land, rough mountainous. Soil, rocky, 4th rate. No timber. Undergrowth, palo verde, buck brush, mesquite and cat claw.
<hr/>	
	N.0°2'W., bet. secs. 15 and 16. Over rough mountainous land, through dense undergrowth.
1.28	Head of draw, course SE. Asc. 185 ft.
15.25	Ridge, brs. E. and W. Desc. 220 ft.
25.20	Head of draw, course W. Asc. 50 ft.
32.50	Desc. 15 ft.
33.50	Head of draw, course SW. Asc. 265 ft.
40.00	Set an iron post, 3 ft. long, 1 in. diam., 26 ins. in the ground, for $\frac{1}{4}$ sec. cor., marked on brass cap $\begin{array}{c} S16 \quad S15 \\ 1919 \end{array}$
	and raise a mound of stone, 2 ft. base, 1 $\frac{1}{2}$ ft. high, W. of cor.
45.20	Ridge, brs. E. and W. Desc. 270 ft.
54.00	Spur, slopes E. Continue descent.
59.25	Head of draw, course NE. Asc. 105 ft.
63.60	Spur, slopes NE. Desc. 145 ft.
77.15	Head of draw, course E. Asc.
80.00	Set an iron post, 3 ft. long, 2 ins. diam., 24 ins. in the ground for cor. of secs. 9, 10, 15 and 16, mkd. on brass cap $\begin{array}{c} T9N \quad R2W \\ S \quad 9 \quad S10 \\ S16 \quad S15 \\ 1919 \end{array}$
	and raise a mound of stone, 2 ft. base, 1 $\frac{1}{2}$ ft. high, W. of cor. Land, mountainous. --- Soil, rocky, 4th rate. No timber. --- Undergrowth, mesquite, buckbrush and palo verde.
<hr/>	
	S.89°58'E. on a random line bet. secs. 10 and 15.
40.00	Set temp. $\frac{1}{4}$ sec. cor.
80.10	Intersect N. and S. line 2 lks. S. of cor. of secs. 10, 11, 14 and 15. Thence N.89°59'W. on a true line bet. secs. 10 and 15. Over rough mountainous land, over brushy slopes. Asc. W. slope 400 ft.
4.10	Road brs. N. and SE. Continue asc.
18.10	Ridge brs. N. and S. Desc. 40 ft. to
33.10	Spur slopes NW. Desc. 152 ft.
40.05	Set an iron post, 3 ft. long, 1 in. diam., 26 ins. in the ground, for $\frac{1}{4}$ sec. cor., mkd. on brass cap $\begin{array}{c} S \quad 10 \\ S15 \quad S15 \\ 1919 \end{array}$

168

Survey of the
Subdivision of T. 9 N., R. 2 W.

32

Chains

41.60 and raise a mound of stone, 2 ft. base, 1½ ft. high, N. of cor.
 42.60 Head of draw, course N. Asc. 15 ft.
 48.55 Spur slopes N. Desc. 115 ft.
 50.60 Old road brs. N. and S.
 56.00 Wash, course N. Asc. 100 ft. to
 63.10 Spur slopes N. Desc. 115 ft.
 75.10 Wash, course N. Asc. 185 ft. over E. slope.
 78.45 Spur slopes N. Desc. 60 ft. to
 80.10 Draw, course N. Asc. 30 ft. to
 The cor. of secs. 9, 10, 15 and 16.
 Land, rough mountainous.---Soil, rocky, 4th rate.
 No timber.---Undergrowth, mesquite, scrub oak, buckbrush.

N.0°2'W., bet. secs. 9 and 10.
 Over rough mountainous land, through dense undergrowth.
 Desc. 80 ft.

5.10 Draw, course N.15°W. Asc. 40 ft.
 11.90 Point of spur, slopes NW. Desc. 245 ft.
 20.30 Wash, course N.15°W. Asc. 210 ft.
 40.00 Set an iron post, 3 ft. long, 1 in. diam., 12 ins. in the
 ground, in a mound of stone, for ¼ sec. cor., marked on
 brass cap

S 9 | S 10
 1919

46.60 And raise a mound of stone, 2 ft. base, 1½ ft. high, W. of cor.
 50.50 Spur, slopes W. Desc. 55 ft.
 61.00 Asc. 160 ft.
 72.50 Ridge, brs. E. and W. Desc. 225 ft.
 73.00 Oak Creek, dry, course W. Asc. 150 ft.
 80.00 Old road, brs. E. and W.

Set an iron post, 3 ft. long, 2 ins. diam., 8 ins. in the
 ground, in a mound of stone, for cor. of secs. 3, 4, 9
 and 10, marked on brass cap

T9N R2W
 S 4 | S 3
 S 9 | S 10
 1919

And raise a mound of stone, 2 ft. base, 1½ ft. high, W. of cor.
 Land, rough mountainous.---Soil, rocky, 4th rate.
 No timber.---Undergrowth, mesquite, catclaw, and scrub oak.

40.00 S.89°59'E., on a random line, bet. secs. 3 and 10.
 80.14 Set temp. ¼ sec. cor.
 Intersect N. and S. line, 9 lks. S. of the cor. of secs.
 2, 3, 10 and 11.

Thence S. 89°57'W., on a true line bet. secs. 3 and 10.
 Over rolling hills, through scattering undergrowth.
 Desc. 80 ft

14.85 Asc. 25 ft.
 22.35 Old road, brs. N. and S. Desc. 25 ft.
 34.45 Wash, course NW. Asc. 50 ft.
 36.50 Desc. 35 ft.

40.07 Set an iron post, 3 ft. long, 1 in. diam., 14 ins. in the
 ground, in a mound of stone, for ¼ sec. cor., mkd. on
 brass cap

S 3
 S 10
 1919

And raise a mound of stone 2 ft. base, 1½ ft. high N. of cor.
 Thence along N. slope, ascending 45 ft.

53.05 Point of spur, slopes N. Desc. 195 ft.
 70.95 Oak Creek, cry, course SW. Old road brs. NE. and SW.
 Asc. 140 ft.


80.14 The cor. of secs. 3, 4, 9 and 10.
 Land, rolling hills.
 Soil, rocky, 4th rate.
 No timber.

Undergrowth, palo verde, mesquite, scrub oak and buckbrush.

Survey of the
Subdivision of T. 9 N., R. 2 W.


Chains.

40.00 N.0°2'W., on a random line, bet. secs. 3 and 4.
Set temp. 1/4 sec. cor.
80.07 Intersect N. and S. line, 9 lks. W. of the cor. of secs.
3, 4, 33 and 34, hereinbefore described.
Thence
S.0°2'W., on a true line, bet. secs. 3 and 4.
Over mountainous land, through dense undergrowth.
Desc. 260ft.
18.35 Wash, course SW. Asc. 20 ft.
20.45 Desc. 20 ft.
23.80 Asc. 65 ft.
28.75 Desc. 135 ft.
30.05 Wash, course S.30°W. Asc.
39.05 Road, E. to Johnson's Ranch and W. to Crown Point.
40.07 Set an iron post 3 ft. long, 1 in. diam., 24 ins. in the
ground, in a mound of stone, for 1/4 sec. cor., marked on
brass cap



And raise a mound of stone, 2 ft. base, 1 1/2 ft. high, W.
of cor.
42.60 Desc. 70 ft.
48.25 Draw, course SW. Asc. 80 ft.
56.10 Desc. 35 ft.
57.45 Head of draw, course W. Asc. 155 ft.
64.05 Ridge, brs. N.70°E. and S.70°W. Desc. 190 ft., on spur,
slopes S.
80.07 The cor. of secs. 3, 4, 9 and 10.
Land, mountainous.
Soil, rocky, 4th rate.
No timber.
Undergrowth, palo verde, mesquite, scrub oak and buck brush.

From the reestablished standard cor. of secs. 32 and 33,
on the S. bdy. of Tp., hereinbefore described,
N.0°2'W., bet. secs. 32 and 33.
Over rough mountainous land, through scattering undergrowth.
Asc. 110 ft.
12.70 Ridge, brs. NW. and SE. Desc. 65 ft.
19.25 Head of draw, course SE. Asc. 100 ft.
28.35 Spur, slopes E. Desc. 100 ft.
36.10 Wash, course S.20°E. Asc. 90 ft.
40.00 Set an iron post, 3 ft. long, 1 in. diam., 9 ins. in the
ground, in a mound of stone, for 1/4 sec. cor., marked on
brass cap



And raise a mound of stone, 2 ft. base, 1 1/2 ft. high, W.
of cor.
Desc. 45 ft.
45.90 Head of draw, course W. Asc. 125 ft.
53.60 Spur, slopes E. Desc. 30 ft.
58.60 Asc. 60 ft.
63.50 Spur, slopes SE. Desc. 120 ft.
67.80 Creek, dry, course SE. from NE. Asc. 105 ft.
71.20 Point of spur, slopes E. Desc. 90 ft.
75.74 Creek, dry, course SE. Asc. 105 ft.
80.00 Set an iron post, 2 ft. long, 2 ins. in diam., 24 ins. in the
ground, for cor. of secs. 28, 29, 32 and 33, marked on brass
cap



Undergrowth, palo verde, mesquite, scrub oak and buck brush.
and raise a mound of stone,
2 ft. base, 1 1/2 ft. high, W. of cor.
Land, rough, mountainous, Soil, rocky, 4th rate. No timber.
Undergrowth, palo verde, mesquite, scrub oak and buck brush.

Survey of the
Subdivision of T. 9 N., R. 2 W.

Chains.
 40.00 East on a random line, bet. secs. 28 and 33.
 Set temp. $\frac{1}{4}$ sec. cor.
 79.98 Intersect N. and S. line, at the cor. of secs. 27, 28, 33
 and 34.
 Thence
 West on a true line, bet. secs. 28 and 33.
 Over rough mountainous land, through dense undergrowth.
 Desc. 65 ft.
 5.70 Copperopolis Creek, course SE. Asc. 330 ft.
 21.00 Trail to Lehman's Mill, brs. N. and S.
 22.00 Ridge, brs. NW. and SE. Trail, brs. NW. and SE. Desc. 55
 ft.
 23.90 Head of draw, course SW. Asc. 130 ft.
 31.00 Ridge, brs. N. and S. Desc. 245 ft.
 34.50 Trail, brs. NW. and SW.
 39.99 Set an iron post, 3 ft. long, 1 in. diam., 14 ins. in the
 ground, in a mound of stone, for $\frac{1}{4}$ sec. cor., marked on
 brass cap

$\frac{1}{4}$ S28
 $\frac{1}{4}$ S33
 1919

And raise a mound of stone, 2 ft. base, $1\frac{1}{2}$ ft. high, N.
 of cor.

40.20 Draw, course S. Asc. 70 ft.
 46.20 Spur, slopes SW. Desc. 110 ft.
 51.90 Head of draw, course SW. Asc. 50 ft.
 54.00 Spur, slopes S. Desc. 80 ft.
 58.30 Head of draw, course SW. Asc. 120 ft.
 66.75 Spur, slopes S. Desc. 115 ft.
 71.00 Head of draw, course SW. Asc.
 73.50 Spur, slopes SW. Desc. 150 ft.
 79.98 The cor. of secs. 28, 29, 32 and 33.
 Land, rough mountainous.
 Soil, rocky, 4th rate.
 No timber.
 Undergrowth, palo verde, mesquite, buck brush and cat claw.

N.0°2'W., bet. secs. 28 and 29.
 Over rough mountainous land, through scattering undergrowth.
 Desc. 55 ft.

3.23 Wash, course SW. from NW. Asc. 95 ft.
 5.70 Spur, slopes W. Desc. 25 ft.
 13.20 Wash, 15 lks. wide, course SW. Contains stream of water,
 1 link wide, 1 in. deep. Asc. 130 ft.
 17.80 Spur, slopes SE. Thence along E. slope.
 23.20 Asc. 65 ft.
 28.70 Spur, slopes SE. Desc. 115 ft.
 31.50 Same wash, course SE., from NE. Asc. 185 ft.
 37.70 Spur, slopes SE. Desc. 20 ft.
 40.00 Set an iron post, 3 ft. long, 1 in. diam., 26 ins. in the
 ground, for $\frac{1}{4}$ sec. cor., marked on brass cap

$\frac{1}{4}$
 S29 S28
 1919

And raise a mound of stone, 2 ft. base, $1\frac{1}{2}$ ft. high, W.
 of cor.

40.80 Head of draw, course E. Asc. 225 ft.
 62.71 Knoll on ridge, brs. NE. and S.30°W. Desc. 140 ft.
 70.60 Head of draw, course W. Asc. 70 ft.
 80.00 Set an iron post, 3 ft. long, 2 ins. diam., 12 ins. in the
 ground, in a mound of stone, for cor. of secs. 20, 21,
 28 and 29, marked on brass cap

Survey of the
Subdivision of T. 9 N., R. 2 W.

BOOK 8841

Chains.

T9N R2W
S20 | S21
S29 | S28
1919

And raise a mound of stone, 2 ft. base, 1½ ft. high, W. of cor.
Land, rough mountainous.
Soil, rocky, 4th rate.
No timber.
Undergrowth, palo verde, mesquite, cat claw and buck brush.

40.00 East on a random line, bet. secs. 21 and 28.
Set temp. ¼ sec. cor.
79.96 Intersect N. and S. line, at the cor. of secs. 21, 22, 27 and 28,
Thence
West on a true line, bet. secs. 21 and 28.
Over rough mountainous land, through dense undergrowth.
Asc. 615 ft.
25.95 Head of draw, course NE. Continue ascent.
36.55 Ridge, brs. NW. and SE. Desc. 255 ft.
39.98 Set an iron post, 3 ft. long, 1 in. diam., 26 ins. in the ground, for ¼ sec. cor., marked on brass cap

¼ S21
¼ S28
1919

And raise a mound of stone, 2 ft. base, 1½ ft. high, N. of cor.
48.50 Head of draw, course SW. Asc. 85 ft.
59.30 Ridge, brs. N.80°E. and S.80°W. Desc. 355 ft.
75.95 Head of draw, course N. Asc. 10 ft.
77.05 Desc. 70 ft.
79.96 The cor. of secs. 20, 21, 28 and 29.
Land, rough mountainous.
Soil, rocky, 4th rate.
No timber.
Undergrowth, palo verde, mesquite, cat claw and buck brush.

N.0°2'W., bet. secs. 20 and 21.
Over mountainous land, through scattering undergrowth.
Desc. 140 ft.
5.60 Wash, course W. Asc. 105 ft.
8.90 Spur, slopes SW. Desc. 15 ft.
10.15 Asc. 40 ft.
15.90 Spur, slopes W. Desc. 50 ft.
18.80 Draw, course SW. Asc.
20.05 Point of spur, slopes SW. Desc.
23.20 Draw, course SW. Asc. 530 ft.
40.00 Set an iron post, 3 ft. long, 1 in. diam., 21 ins. in the ground, in a mound of stone, for ¼ sec. cor., marked on brass cap

S20 | S21
1919

And raise a mound of stone, 2 ft. base, 1½ ft. high, W. of cor.
47.00 Spur, slopes SW. Desc. 105 ft.
58.45 Head of draw, course W. Asc. 40 ft.
60.40 Point of spur, slopes SW. Desc. 85 ft.
63.10 Head of draw, course W. Asc. 105 ft.
66.50 Spur, slopes SW. Trail, brs. E. and W. Desc. 105 ft.
70.20 Same trail, brs. NE. and SW.
71.00 Draw, 10 lks. wide, course SW. Asc. 105 ft.

Survey of the
Subdivision of T. 9 N., R. 2 W.

Chains.									
77.35	Desc. 15 ft.								
80.00	Set an iron post, 3 ft. long, 2 in. diam., 26 ins. in the ground, for cor. of secs. 16, 17, 20 and 21, marked on brass cap								
	<table border="1"> <tr><td>T9N</td><td>R2W</td></tr> <tr><td>S17</td><td>S16</td></tr> <tr><td>S20</td><td>S21</td></tr> <tr><td colspan="2">1919</td></tr> </table>	T9N	R2W	S17	S16	S20	S21	1919	
T9N	R2W								
S17	S16								
S20	S21								
1919									
	And raise a mound of stone, 2 ft. base, 1½ ft. high, W. of cor.								
	Land, rough mountainous.								
	Soil, rocky, 4th rate.								
	No timber.								
	Undergrowth, palo verde, mesquite, cat claw and buck brush.								
	East on a random line, bet. secs. 16 and 21.								
40.00	Set temp. ¼ sec. cor.								
79.94	Intersect N. and S. line, 10 lks. N. of the cor. of secs. 15, 16, 21 and 22.								
	Thence								
	N.89°56'W., on a true line, bet. secs. 16 and 21.								
	Over rough mountainous land, through scattering undergrowth.								
	Asc. 40 ft.								
3.45	Ridge, brs. NE. and SW. Desc. 280 ft.								
22.35	Draw, 8 lks. wide, course S. Asc. 50 ft.								
22.55	Point of spur, slopes S. Desc. 25 ft.								
24.15	Wash, 6 lks. wide, course S. Asc. 480 ft.								
25.65	Point of spur, slopes SE. Continue ascent.								
39.97	Set an iron post, 3 ft. long, 1 in. diam., 26 ins. in the ground, for ¼ sec. cor., marked on brass cap								
	<table border="1"> <tr><td>¼</td><td>S16</td></tr> <tr><td>¼</td><td>S21</td></tr> <tr><td colspan="2">1919</td></tr> </table>	¼	S16	¼	S21	1919			
¼	S16								
¼	S21								
1919									
	And raise a mound of stone, 2 ft. base, 1½ ft. high, N. of cor.								
47.40	U. S. G. S. B. M., elevation 3939, brs. S.26°26'E.								
47.55	Ridge, brs. N. and S. Desc. 370 ft.								
55.70	Draw, course NW. Asc.								
61.15	Point of spur, slopes N. Desc. 240 ft.								
71.85	Draw, 10 lks. wide, course S.10°W. Asc. 15 ft.								
75.00	Desc. 25 ft.								
78.20	Draw, course S. Asc. 25 ft.								
79.94	The cor. of secs. 16, 17, 20 and 21.								
	Land, rough mountainous.								
	Soil, rocky, 4th rate.								
	No timber.								
	Undergrowth, palo verde, mesquite, cat claw and buck brush.								
	N.0°2'W., bet. secs. 16 and 17.								
	Over mountainous land, through scattering undergrowth.								
	Asc. 255 ft.								
10.50	West end of mountain. Thence along W. slope.								
10.45	Mining claim cor. post, 4 ins square, 4 ft. above ground, brs. N.46°W.								
16.58	Same cor. brs. S.65°20'W.								
16.80	Desc. 80 ft.								
21.00	Head of draw, course W. Asc.								
22.50	Spur, slopes SW. Desc. 60 ft.								
27.70	Head of draw, course W. Asc. 50 ft.								
35.00	Spur, slopes W. Desc.								
39.20	Head of draw, course W. Asc. 115 ft.								

Survey of the
Subdivision of T. 9 N., R. 2 W.

Chains.
40.00 Set an iron post, 3 ft. long, 1 in. diam., 8 ins. in the ground, in a mound of stone, for $\frac{1}{4}$ sec. cor., marked on brass cap

$\frac{1}{4}$
 S17 | S16
 1919

And raise a mound of stone, 2 ft. base, $1\frac{1}{2}$ ft. high, W. of cor.
 Desc. 15 ft.
 41.90 Draw, course SW. Asc. 125 ft.
 53.40 Desc. 150 ft.
 59.20 Draw, course NW. Asc. 10 ft.
 62.65 Spur, slopes NW. Desc. 155 ft.
 71.08 Draw, course W. Asc. 120 ft.
 75.00 Head of draw, course SW. Asc. 120 ft.
 80.00 Set an iron post, 3 ft. long, 2 ins. diam., 6 ins. in the ground, in a mound of stone, for cor. of secs. 8, 9, 16 and 17, marked on brass cap

T9N R2W
 S 8 | S 9
 S17 | S16
 1919

And raise a mound of stone, 2 ft. base, $1\frac{1}{2}$ ft. high, W. of cor.
 Land, rough mountainous.
 Soil, rocky, 4th rate.
 No timber.
 Undergrowth, palo verde, mesquite, cat claw and buck brush.

40.00 S. $89^{\circ}56'E.$, on a random line, bet. secs. 9 and 16.
 Set temp. $\frac{1}{4}$ sec. cor.
 79.98 Intersect N. and S. line, 16 lks. S. of the cor. of secs. 9, 10, 15 and 16.
 Thence
 S. $89^{\circ}57'W.$, on a true line, bet. secs. 9 and 16.
 Over mountainous land, through scattering undergrowth.
 Asc. 100 ft.
 9.30 Spur, slopes N. Desc. 110 ft.
 12.80 Draw, course N. Asc. 140 ft.
 21.80 Ridge, brs. N. and S. Desc. 145 ft.
 30.00 Draw, course NW. Asc.
 33.00 Spur, slopes NW. Desc. 105 ft.
 39.99 Set an iron post, 3 ft. long, 1 in. diam., 18 ins. in the ground, in a mound of stone, for $\frac{1}{4}$ sec. cor., marked on brass cap

$\frac{1}{4}$ S 9
 S16
 1919

And raise a mound of stone, 2 ft. base, $1\frac{1}{2}$ ft. high, N. of cor.
 From this cor., U. S. L. M. No. 1537, Unknown Mining Dist., which is a granite stone, 24 X 8 X 18 ins. above ground, firmly set, marked and witnessed as described by the Surveyor-General, brs. N. $34^{\circ}6'W.$, 29.70 chs. Asc.

40.50 Spur, slopes SW. Desc. 120 ft.
 48.26 Head of draw, course SW. Asc. 15 ft.
 50.34 Spur, slopes SW. Desc. 110 ft.
 55.80 Head of draw, course SW. Continue descent.
 62.12 Head of draw, course SW. Asc. 15 ft.
 65.60 Spur, slopes SW. Desc. 25 ft.
 69.65 Asc. 30 ft.
 73.10 Desc. 75 ft.
 76.65 Head of draw, course SW. Asc. 55 ft.
 79.98 The cor. of secs. 8, 9, 16 and 17.
 Land, mountainous.
 Soil, rocky, 4th rate.

Survey of the
Subdivision of T. 9 N., R. 2 W.


38

Chains.

No timber.
Undergrowth, palo verde, mesquite, greasewood and buck brush.


N.0°2'W., bet. secs. 8 and 9.
Over rough mountainous land, through dense undergrowth.
Asc.

- 3.50 Spur, slopes W. Desc. 100 ft.
- 9.00 Head of draw, course W. Asc. 20 ft.
- 17.30 Spur, slopes SW. Desc. 75 ft.
- 20.80 Draw, 10 lks. wide, course W. Asc. 100 ft.
- 30.60 Spur, slopes NW. Desc. 110 ft.
- 33.20 Head of draw, course NW. Continue descent.
- 40.00 Set an iron post, 3 ft. long, 1 in. diam., 24 ins. in the ground, in a mound of stone, for $\frac{1}{4}$ sec. cor., marked on brass cap



And raise a mound of stone, 2 ft. base, $1\frac{1}{2}$ ft. high, W. of cor.

- 41.70 Head of draw, course SW. Asc. 85 ft.
- 45.00 Spur, slopes SW. Continue descent.
- 51.20 Spur, slopes W. Desc. 160 ft.
- 68.40 Draw, course NW. Asc. 55 ft.
- 76.80 Spur, slopes W. Desc. 45 ft.
- 80.00 Set an iron post, 3 ft. long, 2 ins. diam., 15 ins. in the ground, in a mound of stone, for cor. of secs. 4, 5, 8 and 9, marked on brass cap




And raise a mound of stone, 2 ft. base, $1\frac{1}{2}$ ft. high, W. of cor.

Land, rough mountainous.
Soil, rocky, 4th rate.
No timber.
Undergrowth, palo verde, mesquite, cat claw and scrub oak.

- 40.00 N.89°57'E., on a random line, bet. secs. 4 and 9. Set temp. $\frac{1}{4}$ sec. cor.
- 80.04 Intersect N. and S. line, 7 lks. S. of the cor. of secs. 3, 4, 9 and 10.

Thence
S.89°54'W., on a true line, bet. secs. 4 and 9.
Over mountainous land, through dense undergrowth.
Desc. 160 ft.

- 12.45 Oak Creek, course SW., from SE. Orchard containing 30 apple trees along creek. Asc. 100 ft.
- 17.55 Desc. 120 ft.
- 25.05 Wire corral brs. S. 5 chs. dist.
- 29.05 Oak Creek, course NW. Asc. 30
- 29.80 Desc. 30 ft.
- 33.75 Oak Creek, 50 lks. wide, course SW. Asc. 140 ft.
- 38.75 Saddle in spur, slopes S. Hill brs. N. 6 chs. dist. Desc. 175 ft.
- 40.02 Set an iron post, 3 ft. long, 1 in. diam., 4 ins. in the ground, in a mound of stone, for $\frac{1}{4}$ sec. cor., marked on brass cap



Survey of the
Subdivision of T. 9 N., R. 2 W.


Chains.

And raise a mound of stone, 2 ft. base, 1½ ft. high, N. of cor.

49.90 Oak Creek, 50 lks. wide, course NW. Asc. 210 ft.
 59.05 Spur, slopes N. Desc. 205 ft.
 70.80 Draw, course N. Asc. 45 ft.
 76.95 Desc. 50 ft.
 79.55 Head of draw, course NW. Asc.
 80.04 The cor. of secs. 4, 5, 8 and 9.
 Land, mountainous.
 Soil, rocky, 4th rate.
 No timber.
 Undergrowth, palo verde, mesquite, cat claw and buck brush.

N.0°2'W., on a random line, bet. secs. 4 and 5.
 40.00 Set temp. ¼ sec. cor.
 79.94 Intersect N. bdy. of Tp., 7 lks. W. of the cor. of secs. 4, 5, 32 and 33, hereinbefore described.
 Thence
 S.0°1'W., on a true line, bet. secs. 4 and 5.
 Over rolling hills, through scattering undergrowth.
 Asc. 10 ft.

2.20 Point of spur, slopes W. Desc. 40 ft.
 5.10 Wash, 6 lks. wide, course W. Asc. 50 ft.
 8.50 Spur, slopes SW. Desc. 105 ft.
 19.40 Wash, 20 lks. wide, course W. Asc. 70 ft.
 27.40 Low ridge, brs. NE. and SW. Desc. 50 ft.
 30.85 Head of draw, course W. Asc. 50 ft.
 35.90 Spur, slopes W. Road, brs. NE. to Crown King and SW. Desc. 20 ft.
 39.94 Set an iron post, 3 ft. long, 1 in. diam., 6 ins. in the ground, in a mound of stone, for ¼ sec. cor., marked on brass cap



And raise a mound of stone, 2 ft. base, 1½ ft. high, W. of cor.

41.80 Head of draw, course NW. Asc. 140 ft.
 49.50 Point of spur, slopes SW. Desc. 10 ft.
 50.70 Asc. 45 ft.
 57.20 Spur, slopes SW. Desc. 265 ft.
 69.80 Enter Oak Creek, course SW.
 70.73 Leave Oak Creek, course SW. Asc. 35 ft.
 79.39 Draw, course NW.
 79.94 The cor. of secs. 4, 5, 8 and 9.
 Land, rolling hills.
 Soil, rocky, 4th rate.
 No timber.
 Undergrowth, palo verde, mesquite, buck brush and cat claw.

From the reestablished standard cor. of secs. 31 and 32, hereinbefore described, on S. bdy. of Tp. (2nd. Std. Par. N.), N.0°3'W., bet. secs. 31 and 32.
 Over rough mountainous land, through dense undergrowth.
 Desc. 115 ft.

3.40 Desc. 20 ft.
 6.90 Wash, course E. Asc. 150 ft.
 11.60 Head of draw, course SE. Continue ascent.
 15.80 Spur, slopes E. Desc. 165 ft.
 24.50 Draw, course E. Asc. 65 ft.
 27.30 Spur, slopes E. Desc. 75 ft.
 32.70 Draw, course E. Asc. 30 ft.
 38.40 Desc.
 40.00 Set an iron post, 3 ft. long, 1 in. diam., 23 ins. in the ground, in a mound of stone, for ¼ sec. cor., marked on brass cap

Survey of the Su
Subdivision of T. 9 N., R. 2 W.

Chains.

1/4
S31 | S32
1919

- And raise a mound of stone, 2 ft. base, 1 1/2 ft. high, W. of cor.
- 41.50 Draw, course E. Asc. 75 ft.
- 47.48 Spur, slopes E. U. S. G. S. B. M., elevation 3939, brs. N.73°45'E. Desc. 100 ft.
- 54.10 Draw, course SE. Thence along E. slope.
- 62.70 Barn brs. W. 0.40 chs. dist.
- 64.30 House and spring brs. W. 3 chs. dist. Road, brs. NW. and SE. Desc. 15 ft.
- 71.25 Wash, 30 lks. wide, course S.15°E. Asc. 190 ft., on spur, slopes S.
- 80.00 Set an iron post, 3 ft. long, 2 ins. diam., 9 ins. in the ground, in a mound of stone, for cor. of secs. 29, 30, 31 and 32, marked on brass cap

T9N R2W
S30 | S29
S31 | S32
1919

And raise a mound of stone, 2 ft. base, 1 1/2 ft. high, W. of cor.
Land, rough mountainous and rolling.
Soil, rocky, 4th rate.
No timber.
Undergrowth, buck brush, palo verde, mesquite and cat claw.

- East on a random line, bet. secs. 29 and 32.
- 40.00 Set temp. 1/4 sec. cor.
- 80.06 Intersect N. and S. line, 5 lks. N. of the cor. of secs. 28, 29, 32 and 33.
- Thence N.89°58'W., on a true line, bet. secs. 29 and 32. Over mountainous land, through dense undergrowth. Desc. 80 ft.
- 2.80 Creek, course S. Asc. 215 ft.
- 9.85 Ridge, brs. NW and SE. Desc. 80 ft.
- 13.75 Head of draw, course S. Asc. 90 ft.
- 19.35 Spur, slopes S. Desc. 100 ft.
- 24.15 Head of draw, course S. Asc. 30 ft.
- 34.55 Point of spur, slopes S. Desc. 30 ft.
- 40.03 Head of draw, course S. Set an iron post, 3 ft. long, 1 in. diam., 26 ins. in the ground, for 1/4 sec. cor., marked on brass cap

1/4 S29
S32
1919

- And raise a mound of stone, 2 ft. base, 1 1/2 ft. high, N. of cor.
- Asc. 35 ft.
- 45.65 Low ridge, brs. NE. and SW. Desc. 90 ft.
- 59.95 Head of draw, course S.
- 62.95 Head of draw, 10 lks. wide, course SE. Asc. 60 ft.
- 69.45 Low ridge, brs. N. and SE. Desc. 35 ft.
- 74.05 Draw, 10 lks. wide, course SW. Asc. 165 ft.
- 80.06 The cor. of secs. 29, 30, 31 and 32.
Land, mountainous.
Soil, rocky, 4th rate.
No timber.
Undergrowth, palo verde, mesquite, cat claw and buck brush.

Survey of the
Subdivision of T. 9 N., R. 2 W.

Chains.

40.00 West on a random line, bet. secs. 30 and 31.
 Set temp. $\frac{1}{4}$ sec. cor.
 79.90 Intersect W. bdy. of Tp., 3 lks. N. of the cor. of secs.
 25, 30, 31 and 36, hereinbefore described.
 Thence
 N.89°59'E., on a true line, bet. secs. 30 and 31.
 Over rolling and mountainous land, through scattering
 undergrowth.
 Asc. 75 ft.
 6.50 Spur, slopes NW. Continue ascent.
 12.50 Ridge, brs. N.70°E. and S.70°W. Desc. 335 ft.
 36.24 Draw, 10 lks. wide, course N.70°E. Asc. 85 ft.
 39.90 Set an iron post, 3 ft. long, 1 in. diam., 26 ins. in the
 ground, for $\frac{1}{4}$ sec. cor., marked on brass cap

$\frac{1}{4}$ S30
 $\frac{1}{4}$ S31
 1919

And raise a mound of stone, 2 ft. base, 1 $\frac{1}{2}$ ft. high, N.
 of cor.
 Desc. 360 ft.
 57.20 Head of draw, course N. Continue descent.
 66.10 Draw, 20 lks. wide, containing small stream of water, course
 SE. Asc. 110 ft. 68.85
 68.85 Road, brs. NW. to Crown Point and SE. to Hot Springs.
 74.10 Desc. 15 ft.
 75.60 Head of draw, course S. Asc. 45 ft.
 79.90 The cor. of secs. 29, 30, 31 and 32.
 Land, rough mountainous and rolling.
 Soil, rocky, 4th rate.
 No timber.
 Undergrowth, scrub oak, mahogany, cat claw, mesquite and
 buck brush.

N.0°3'W., bet. secs. 29 and 30.
 Over mountainous land, through scattering undergrowth.
 Asc. 10 ft.
 1.00 Desc. 115 ft.
 6.30 Head of draw, course E. Asc.
 8.00 Low spur, slopes E. Desc. 25 ft.
 12.90 Draw, 8 lks. wide, course S.10°E. Asc. 70 ft.
 20.45 Desc. 30 ft.
 22.40 Same draw, course SW. Asc. 90 ft.
 28.00 Desc.
 29.20 Head of Draw, course SW. Asc. 35 ft.
 31.55 Desc. 15 ft.
 32.80 Draw, course SE. Asc. 365 ft.
 40.00 Set an iron post, 3 ft. long, 1 in. diam., 12 ins. in the
 ground, in a mound of stone, for $\frac{1}{4}$ sec. cor., marked on
 brass cap

$\frac{1}{4}$
 S30 | S29
 1919

And raise a mound of stone, 2 ft. base, 1 $\frac{1}{2}$ ft. high, W.
 of cor.
 46.60 Spur, slopes W. Thence along W. slope.
 51.60 Asc. 20 ft.
 56.60 Ridge, brs. NW. and SE. Desc. 60 ft.
 64.80 Point of spur, slopes E. Continue descent.
 66.30 Head of draw, course E. Asc. 200 ft.
 72.80 Spur, slopes SE. U. S. G. S. R. M., elevation 3939, brs.
 S.74°E. Desc. 85 ft.
 79.00 Head of draw, course E. Asc. 15 ft.
 80.00 Set an iron post, 3 ft. long, 2 ins. diam., 6 ins. in the
 ground, in a mound of stone, for cor. of secs. 19, 20,
 29 and 30, marked on brass cap

Survey of the
Subdivision of T. 9 N., R. 2 W.

Chains.

T9N R2W
S19 | S20
S30 | S29
1919

And raise a mound of stone, 2 ft. base, 1½ ft. high, W. of cor.
Land, mountainous.
Soil, rocky, 4th rate.
No timber.
Undergrowth, palo verde, mesquite, buck brush and cat claw.

S.89°58'E., on a random line, bet. secs. 20 and 29.
40.00 Set temp. ¼ sec. cor.
80.12 Intersect N. and S. line, 5 lks. N. of the cor. of secs. 20, 21, 28 and 29.
Thence
N.89°56'W., on true line, bet. secs. 20 and 29.
Over rough mountainous land, through scattering undergrowth.
Desc. 215 ft.
8.85 Draw, 30 lks. wide, course SW. Asc. 120 ft.
14.45 Spur, slopes S. Desc. 165 ft.
19.00 Draw, 10 lks. wide, containing small stream of water, course SE. Small corral brs. S. 2 chs. dist. Asc. 565 ft.
40.06 Set an iron post, 3 ft. long, 1 in. diam., 14 ins. in the ground, in a mound of stone, for ¼ sec. cor., marked on brass cap

¼ S20
¼ S29
1919

And raise a mound of stone, 2 ft. base, 1½ ft. high, W. of cor.
50.50 Ridge, brs. N. and S. Desc. 40 ft.
55.10 Head of draw, course S. Asc. 110 ft.
61.10 Ridge, brs. N. and S. Desc. 105 ft.
67.60 Head of draw, course SW. Asc.
69.00 Spur, slopes SW. Desc. 150 ft.
72.10 Head of draw, course SW. Asc.
73.00 Desc. 20 ft.
76.05 Draw, course S. Asc. 95 ft.
80.12 The cor. of secs. 19, 20, 29 and 30.
Land, rough mountainous.
Soil, rocky, 4th rate.
No timber.
Undergrowth, scrub oak, cat claw, mahogany and buck brush.

S.89°59'W., on a random line, bet. secs. 19 and 30.
40.00 Set temp. ¼ sec. cor.
79.80 Intersect W. bdy. of Tp., 11 lks. S. of the cor. of secs. 19, 24, 25 and 30, hereinbefore described.
Thence
S.89°56'W., on a true line, bet. secs. 19 and 30.
Over rough mountainous land, through scattering undergrowth.
Desc. 20 ft.
0.80 Head of draw, course NW. Asc. 670 ft.
12.30 Spur, slopes SW. Continue ascent.
20.10 Head of draw, course SW. Continue ascent.
29.40 Crown Point Mine and Mill brs. S.43½°W.
36.30 S. end of mountain, brs. N. Desc. 30 ft.
39.80 Set an iron post, 3 ft. long, 1 in. diam., 26 ins. in the ground, for ¼ sec. cor., marked on brass cap


¼ S19
¼ S30
1919

Survey of the
Subdivision of T. 9 N., R. 2 W.

Chains.

And raise a mound of stone, 2 ft. base, 1½ ft. high, N. of cor.
 Asc.
 45.20 Desc. 335 ft.
 63.40 Point of spur, slopes SE. Continue descent.
 69.80 Wash, 20 lks. wide, course S. Asc. 90 ft.
 70.60 Old Prescott and Phoenix road, brs. N. and S.
 73.30 Ridge, brs. NW. and SE. Desc. 160 ft.
 79.80 The cor. of secs. 19, 20, 29 and 30.
 Land, rough mountainous.
 Sól, rocky, 4th rate.
 No timber.
 Undergrowth, scrub oak, mahogany, cat claw and buck brush.

N.0°3'W., bet. secs. 19 and 20.
 Over mountainous land, through scattering undergrowth.
 Desc. 45 ft.
 5.13 Draw, 10 lks. wide, course S.25°E. Asc. 70 ft.
 9.65 Desc.
 12.20 Head of draw, course SW. Asc. 90 ft.
 17.15 Saddle in ridge, brs. E. and W. Desc. 80 ft.
 22.50 Draw, 10 lks. wide, course E. Asc. 55 ft.
 28.60 Spur, slopes SE. Desc. 100 ft.
 38.00 Draw, 20 lks. wide, course SE. Asc. 90 ft.
 40.00 Set an iron post, 3 ft. long, 1 in. diam., 15 ins. in the ground, in a mound of stone, for ¼ sec. cor., marked on brass cap



And raise a mound of stone, 2 ft. base, 1½ ft. high, W. of cor.
 46.80 Spur, slopes SE. Shed brs. W. 8 chs. dist. Thence along E. slope.
 52.80 Spur, slopes SE. Desc. 35 ft.
 66.80 Draw, course SE. Asc. 115 ft.
 80.00 Set an iron post, 3 ft. long, 2 ins. diam., 2 ins. in the ground, in a mound of stone, for cor. of secs. 17, 18, 19 and 20, marked on brass cap



And raise a mound of stone, 2 ft. base, 1½ ft. high, W. of cor.
 Land, mountainous.
 Sól, rocky, 4th rate.
 No timber.
 Undergrowth, palo verde, mesquite, cat claw and buck brush.

S.89°56'E., on a random line, bet. secs. 17 and 20.
 40.00 Set temp. ¼ sec. cor.
 80.14 Intersect N. and S. line, at the cor. of secs. 16, 17, 20 and 21.
 Thence
 N.89°56'W., on a true line, bet. secs. 17 and 20.
 Over rough mountainous land, through dense undergrowth.
 Desc. 55 ft.
 5.65 Head of draw, course S. Asc. 110 ft.
 12.65 Spur, slopes S. Desc. 90 ft.
 15.25 Head of draw, course S. Asc. 140 ft.
 21.35 Ridge, brs. NE. and SW. Desc. 115 ft.
 40.07 Set an iron post, 3 ft. long, 1 in. diam., 26 ins. in the

Survey of the
Subdivision of T. 9 N., R. 2 W.

Chains.

ground, for $\frac{1}{4}$ sec. cor., marked on brass cap

$\frac{1}{4}$ S17
S20
1919

And raise a mound of stone, 2 ft. base, $1\frac{1}{2}$ ft. high, N. of cor.

- 41.00 Draw, course N. Asc. 120 ft.
- 60.60 Spur, slopes S. Desc. 80 ft.
- 63.95 Head of draw, course S. Asc. 110 ft.
- 72.35 Spur, slopes SE. Desc. 40 ft.
- 80.14 The cor. of secs. 17, 18, 19 and 20.
Land, rough mountainous.
Soil, rocky, 4th rate.
No timber.
Undergrowth, palo verde, mesquite, buck brush and cat claw.

- 40.00 N. $89^{\circ}56'$ W., on a random line, bet. secs. 18 and 19.
Set temp. $\frac{1}{4}$ sec. cor.
- 79.78 Intersect W. bdy. of Tp., 9 lks. N. of the cor. of secs. 13, 18, 19 and 24, hereinbefore described.

Thence

- East on a true line, bet. secs. 18 and 19.
Over mountainous land, through scattering undergrowth.
Asc. 595 ft.
- 5.80 Spur, slopes SW. Continue ascent.
- 10.00 Head of draw, course SW. Continue ascent.
- 17.80 Spur, slopes NW. Continue ascent.
- 29.10 Knoll on N. end of mountain. Desc. 345 ft.
- 39.78 Set an iron post, 3 ft. long, 1 in. diam., 26 ins. in the ground, for $\frac{1}{4}$ sec. cor., marked on brass cap

$\frac{1}{4}$ S18
S19
1919

And raise a mound of stone, 2 ft. base, $1\frac{1}{2}$ ft. high, N. of cor.

- 46.33 Head of draw, course NE. Asc. 60 ft.
- 48.10 Old road, brs. N. and S.
- 62.50 Low ridge, brs. N. and S. Desc.
- 70.70 Spur, slopes S. Continue descent.
- 79.78 The cor. of secs. 17, 18, 19 and 20,
Land, rough mountainous.
Soil, rocky, 4th rate.
No timber.
Undergrowth, palo verde, mesquite, cat claw and scrub oak.

- N. $0^{\circ}3'$ W., bet. secs. 17 and 18.
Over rough mountainous land, through scattering undergrowth.
Asc. 245 ft.
- 16.10 Divide, brs. E. and W. Desc. 575 ft.
- 17.10 Stamp mill and mining camp br. N. $79\frac{1}{2}^{\circ}$ E.
Mine shaft brs. N. $88\frac{1}{4}^{\circ}$ E.
- 30.45 Stamp mill and mining camp br. S. $85\frac{1}{2}^{\circ}$ E.
Mine shaft brs. S. 81° E. Descend through dense undergrowth.
- 40.00 Set an iron post, 3 ft. long, 1 in. diam., 10 ins. in the ground, in a mound of stone, for $\frac{1}{4}$ sec. cor., marked on brass cap

$\frac{1}{4}$ S18
S17
1919

And raise a mound of stone, 2 ft. base, $1\frac{1}{2}$ ft. high, W. of cor.

Survey of the
Subdivision of T. 9 N., R. 2 W.

Chains.
 45.60 Head of draw, course NW. Continue descent.
 55.60 Head of draw, course W. Asc. 95 ft.
 65.35 Point of spur, slopes NW. Desc. 135 ft.
 70.05 Draw, course NE. Asc. 45 ft.
 73.40 Road, brs. NE. and SW.
 74.40 Desc. 15 ft.
 75.25 Head of draw, course E. Asc. 85 ft.
 80.00 Set an iron post, 3 ft. long, 2 ins. diam., 26 ins. in the ground, for cor. of secs. 7, 8, 17 and 18, marked on brass cap

T9N R2W
 S 7 | S 8
 S18 | S17
 1919

And raise a mound of stone, 2 ft. base, 1½ ft. high, W. of cor.
 Land, rough mountainous.
 Soil, rocky, 4th rate.
 No timber.
 Undergrowth, palo verde, mesquite, cat claw and cactus.

40.00 S. 89°56'E., on a random line, bet. secs. 8 and 17.
 Set temp. ¼ sec. cor.
 80.14 Intersect N. and S. line, 5 lks. S. of the cor. of secs. 8, 9, 16 and 17.

Thence
 N. 89°58'W., on a true line, bet. secs. 8 and 17.
 Over mountainous land, through dense undergrowth.
 Desc. 140 ft.

7.20 Draw, course SW. Asc. 55 ft.
 11.50 Spur, slopes S. Desc. 200 ft.
 22.20 Spur, slopes SW. Continue descent.
 39.95 Draw, course S. Asc. 40 ft.
 40.07 Set an iron post, 3 ft. long, 1 in. diam., 14 ins. in the ground, in a mound of stone, for ¼ sec. cor., marked on brass cap

S 8
 ¼ S17
 1919

And raise a mound of stone, 2 ft. base, 1½ ft. high, N. of cor.

41.60 Spur, slopes SW. Young's house brs. N. 78°20'W. Desc. 120 ft.
 53.50 Enter goat corral, brs. NW. and SE.
 56.90 Leave corral at fence, brs. NE. and SE.
 57.00 Spur, slopes SW. Continue descent.
 59.00 Old road, brs. NW. to Prescott and SE. to McKinzie Mine.
 62.10 Draw, course N. 70°W. Asc. 40 ft.
 67.00 Point of spur, slopes NW. Young's house brs. North. Desc. 35 ft.
 69.00 Wash, 30 lks. wide, course N. Old Phoenix and Prescott road in wash, brs. N. and S. Asc. 150 ft. Leave undergrowth.
 80.14 The cor. of secs. 7, 8, 17 and 18.
 Land, mountainous.
 Soil, rocky, 4th rate.
 No timber.
 Undergrowth, scrub oak, cat claw and mesquite.

40.00 West on a random line, bet. secs. 7 and 18.
 Set temp. ¼ sec. cor.
 79.72 Intersect W. bdy. of Tp., 7 lks. N. of the cor. of secs. 7, 12, 13 and 18, hereinbefore described.
 Thence
 N. 89°57'E., on a true line, bet. secs. 7 and 18.

Survey of the
Subdivision of T. 9 N., R. 2 W.

Chains.

- Over mountainous land, through scattering undergrowth. Asc. 20 ft.
- 0.70 Ridge, brs. NW. and SW. Desc. 400 ft.
- 14.30 Draw, course SE. Asc. 40 ft.
- 17.80 Spur, slopes SE. Desc. 175 ft.
- 28.85 Wash, 15 lks. wide, course N. Asc. 100 ft.
- 33.60 Spur, slopes NW. Desc.
- 36.00 Draw, course NW. Asc. 270 ft.
- 39.72 Set an iron post, 3 ft. long, 1 in. diam., 26 ins. in the ground, for $\frac{1}{4}$ sec. cor., marked on brass cap

$\frac{1}{4}$ S 7
 $\frac{1}{4}$ S 18
 1919

And raise a mound of stone, 2 ft. base, $1\frac{1}{2}$ ft. high, N. of cor.

- 47.30 Ridge, brs. NW. and SE. Desc. 215 ft.
- 57.50 Head of draw, course NE. Asc. 50 ft.
- 61.90 Desc. 170 ft.
- 75.80 Knoll on spur, slopes N. Desc.
- 79.72 The cor. of secs. 7, 8, 17 and 18.
Land, mountainous.
Soil, rocky, 4th rate.
No timber.
Undergrowth, palo verde, mesquite, cat claw and scrub oak.

N.0°3'W., bet. secs. 7 and 8.

- Over rolling hills, through scattering undergrowth. Desc. 160 ft.
- 9.00 Head of draw, course NW. Continue descent.
- 10.00 Point of spur, slopes NW. Continue descent.
- 13.00 Draw, 10 lks. wide, course NE. Asc. 10 ft.
- 15.80 Desc. 65 ft.
- 22.85 Fence, brs. E. 2 chs., and N.70°W., 5 chs., enclosing cultivated ground.
- 24.30 Fence, brs. E. and W. Leave cultivated land.
- 25.60 Enter wash, course W.
- 27.80 Leave wash, course W.
- 28.00 House, brs. E. 1.50 chs. dist.
- 29.80 Road, brs. E. and W. Asc. 35 ft.
- 35.25 Spur, slopes SW. Desc.
- 40.00 Set an iron post, 3 ft. long, 1 in. diam., 10 ins. in the ground, in a mound of stone, for $\frac{1}{4}$ sec. cor., marked on brass cap

$\frac{1}{4}$
 S 7 S 8
 1919

And raise a mound of stone, 2 ft. base, $1\frac{1}{2}$ ft. high, W. of cor.

- 40.05 Head of draw, course W.
- 42.50 Enter Oak Creek, course S.15°W.
- 43.60 Leave Oak Creek, course S.15°W. Asc. 165 ft.
- 73.20 Low ridge, brs. NE. and SW. Desc. 75 ft.
- 80.00 Set an iron post, 3 ft. long, 2 ins. diam., 24 ins. in the ground, for cor. of secs. 5, 6, 7 and 8, marked on brass cap

T9N R2W
 S 6 S 5
 S 7 S 8
 1919

And raise a mound of stone, 2 ft. base, $1\frac{1}{2}$ ft. high, W. of cor.

- Land, rolling hills.
- Soil, rocky, 4th rate.
- No timber.
- Undergrowth, palo verde, mesquite, cat claw and buck brush.

Survey of the
Subdivision of T. 9 N., R. 2 W.

Chains.
 40.00 S.89°58'E., on a random line, bet. secs. 5 and 8.
 Set temp. 1/4 sec. cor.
 80.18 Intersect N. and S. line, 5 lks. N. of the cor. of secs.
 4, 5, 8 and 9.
 Thence
 N.89°56'W., on a true line, bet. secs. 5 and 8.
 Over rough mountainous land, through dense undergrowth.
 Desc. 60 ft.
 5.30 Enter Oak Creek, course SW.
 5.83 Leave Oak Creek, course SW. Asc. 165 ft.
 15.65 Spur, slopes SW. Desc. 180 ft.
 25.55 Draw, course SW. Asc.
 30.20 Spur, slopes SW. Desc. 70 ft.
 33.20 Draw, course SW. Asc. 60 ft.
 40.09 Set an iron post, 3 ft. long, 1 in. diam., 26 ins. in the
 ground, for 1/4 sec. cor., marked on brass cap

1/4 S 5
 1/4 S 8
 1919

And raise a mound of stone, 2 ft. base, 1 1/2 ft. high, N.
 of cor.
 40.55 Spur, slopes S. Desc. 110 ft.
 53.20 Road, brs. N. to Prescott and S. to Phoenix.
 67.15 Draw, course S. Asc. 190 ft.
 72.90 Ridge, brs. N. and S. Desc. 145 ft.
 80.18 The cor. of secs. 5, 6, 7 and 8.
 Land, rough mountainous.
 Soil, rocky, 4th rate.
 No timber.
 Undergrowth, palo verde, mesquite, cat claw and scrub oak.

40.00 S.89°57'W., on a random line, bet. secs. 6 and 7.
 Set temp. 1/4 sec. cor.
 79.61 Intersect W. bdy. of Tp., 9 lks. S. of the cor. of secs.
 1, 6, 7 and 12, hereinbefore described.
 Thence
 S.89°59'E., on a true line, bet. secs. 6 and 7.
 Over rolling hills, through scattering undergrowth.
 Desc. 165 ft.
 15.20 Head of draw, course SE. Asc. 15 ft.
 18.20 Point of spur, slopes SE. Desc. 135 ft.
 23.00 Head of draw, course S. Asc. 65 ft.
 27.75 Desc. 75 ft.
 37.45 Draw, 8 lks. wide, course N. Asc.
 39.61 Set an iron post, 3 ft. long, 1 in. diam., 26 ins. in the
 ground, for 1/4 sec. cor., marked on brass cap

1/4 S 6
 1/4 S 7
 1919

And raise a mound of stone, 2 ft. base, 1 1/2 ft. high, N.
 of cor.
 Desc.
 41.50 Enter Oak Creek, course N.10°W.
 43.80 Leave Oak Creek, course N.10°W. Asc. 180 ft.
 60.35 Point of spur, slopes S. Desc. 60 ft.
 64.80 Head of draw, course S. Asc. 140 ft.
 72.50 Spur, slopes NW. Desc. 55 ft.
 77.60 Head of draw, course NW. Asc. 35 ft.
 79.61 The cor. of secs. 5, 6, 7 and 8.
 Land, rolling hills.
 Soil, rocky, 4th rate.
 No timber.
 Undergrowth, palo verde, mesquite, scrub oak and buck brush.

Survey of the
Subdivision of T. 9 N., R. 2 W.

Chains. N.0°3'W., on a random line, bet. secs. 5 and 6.
 40.00 Set temp. 1/4 sec. cor.
 79.92 Intersect N. bdy. of Tp., 21 lks. W. of the cor. of secs.
 5, 6, 31 and 32, hereinbefore described.
 Thence
 S.0°6'W., on a true line, bet. secs 5 and 6.
 Over rollinghills, through scattering undergrowth.
 Asc. 20 ft.
 7.50 Low spur, slopes W. Desc. 35 ft..
 11.40 Trail, brs. NW. and SE.
 12.90 Wash, 15 lks. wide, course N.70°W. Asc. 70 ft.
 20.00 Low hill, brs. NW. and SE. Desc. 65 ft.
 31.85 Draw, 6 lks. wide, course NW. Asc. 80 ft.
 39.92 Set an iron post, 3 ft. long, 1 in. diam., 6 ins. in the
 ground, in a mound of stone, for 1/4 sec. cor., marked
 on brasscap

1/4
 S 6 | S 5
 1919

And raise a mound of stone, 2 ft. base, 1 1/2 ft. high, W.
 of cor.
 45.20 Point of spur, slopes W. Desc. 20 ft.
 46.55 Asc. 45 ft.
 52.40 Point of spur, slopes W. Desc. 85 ft.
 61.00 Head of draw, course N.70°W. Asc. 60 ft.
 71.90 Spur, slopes NW. Desc. 25 ft.
 79.92 The cor. of secs. 5, 6, 7 and 8.
 Land, rolling hills.
 Soil, rocky, 4th rate.
 No timber.
 Undergrowth, palo verde, mesquite, buck brush and scrub oak.

Boundaries of T. 9 N., R. 2 W.

Latitudes, departures and closing errors.

Line designated.	True bearing.	Dist. chs.	Latitudes.		Departures.	
			N. chs.	S. chs.	E. chs.	W. chs.
South Boundary (2nd Std. Par. N.)	West.	480.00				480.00
West Boundary.	North.	480.00	480.00			
North Boundary.	S.89°58'E.	479.68		.28	479.68	
East Boundary.	South.	480.00		480.00		
Convergency.					.49	
Totals.			480.00	480.28	480.17	480.00
Error in latitude.				.28		
Error in departure.					.17	

GENERAL DESCRIPTION.

This township is mountainous, with a rocky 4th rate soil, and is unfit for agricultural purposes. There is no timber. Dense undergrowth of paloverde, mesquite, catclaw, scrub oak and buck brush is prevalent in all parts. There are no watercourses carrying a permanent flow of water. Castle Creek and Oak Creek are the principal watercourses, the former heading in sec. 30 and, with it's branches draining the SW. part of the Tp., and the latter drains the northern part. Copperopolis, Spring, Ryland, Tussock and Banty Creeks and Walker Gulch, course South, drain the remainder of the Tp. There are a number of good springs in various parts. There are three settlers; Taylor in sec. 1, J.M. Johnson in sec. 2 and Young in sec. 8. There are unoccupied buildings in all parts of the Tp.

General Description , continued.

The Tp. is mineral in character as evidenced by numerous shafts, prospect holes and other remains of mining operations. A large group of patented mining claims is located in sec. 1 and other patented claims are located in secs. 9, 30, 33 and 34.

Book "T".

Group 61 - - - Arizona.

Date Diagram

T. 9 N., R. 2 W.

	3/19/19	3/20/19	4/3/19	4/3/19	4/3/19	4/3/19
3/19/19	6	5	4	3	2	1
3/13/19	3/20/19	3/18/19	3/22/19	3/22/19	4/4/19	4/4/19
3/15/19	7	8	9	10	11	12
3/14/19	3/16/19	3/14/19	4/7/19	3/29/19	3/31/19	4/1/19
3/14/19	18	17	16	15	14	13
3/13/19	3/18/19	3/13/19	3/18/19	3/29/19	3/28/19	3/25/19
3/12/19	19	20	21	22	23	24
3/12/19	3/12/19	3/7/19	3/7/19	3/28/19	3/27/19	3/26/19
3/12/19	30	29	28	27	26	25
3/6/19	3/7/19	3/5/19	3/4/19	3/3/19	2/28/19	2/27/19
3/6/19	31	32	33	34	35	36
3/6/19	3/5/19	3/4/19	3/3/19	2/28/19	2/27/19	2/26/19
	3/6/19	3/1/19	3/1/19	3/3/19	3/3/19	2/26/19

Second Standard Parallel North.

RESURVEY

Lines executed by J. P. Davis, U. S. Surveyor, on the dates shown on the above diagram.

158

BOOK 3341

CERTIFICATE OF UNITED STATES SURVEYOR.

52

I, J. P. Davis, U. S. Surveyor, hereby certify upon honor that, in pursuance of special instructions received from the U. S. Surveyor General, for Group 61, Arizona, bearing date of the 13th day of November, 1917, I have well, faithfully, and truly in my own proper person, and in strict conformity with said instructions, the Manual of Surveying Instructions, and the laws of the United States, re-surveyed all those parts or portions of the Second Standard Parallel North, thru Range 2 West, and surveyed all these parts or portions of the North, East and West boundaries and subdivision lines of TOWNSHIP 9 NORTH, RANGE 2 WEST,

of the Gila and Salt River Base and Meridian, in the State of Arizona, which are represented in and by diagram, on page 49 hereof the foregoing field notes, as having been executed by me, and under my direction; and that all the corners of resurvey & said survey have been established and perpetuated in strict accordance with the Manual of Surveying Instructions, and the special written instructions of the U. S. Surveyor General, for Group 61, Arizona, and in the specific manner described in the field notes, and that the foregoing are the original field notes of such resurvey and survey.

Bois, Idaho, December 7, 1919

J. P. Davis

U. S. Surveyor.

APPROVAL.

OFFICE OF THE UNITED STATES SURVEYOR GENERAL,

Phoenix, Arizona, May 14, 1920.

The foregoing field notes of the ~~survey of~~ RESURVEY of the Second Standard Parallel North, Through Range 2 West, SURVEY of North, East and West Boundaries and Subdivision Lines of Township 9 North, Range 2 West, of the Gila and Salt River Base and Meridian, in the State of Arizona.

executed by J. P. Davis, U. S. Surveyor, under his special instructions dated November 13, 1917, for Group 61, Ariz, having been critically examined, and the necessary corrections and explanations made, the said field notes, and the ~~survey~~ resurveys and surveys they describe, are hereby approved.

Frank B. Smith U.S. Surveyor General. U.S. Surveyor General.

I certify that the foregoing transcript of the field notes of the above described surveys in, has been correctly copied from the original notes on file in this office.