

3394

Book "D".
4-679

BOOK 3394

FIELD NOTES

RE-
OF THE SURVEY OF THE

Gila and Salt River Base Line, through Range 10 East,

South and West Boundaries of

TOWNSHIP 1 SOUTH, RANGE 10 EAST,

SURVEY OF

East Boundary and Subdivision Lines of

TOWNSHIP 1 SOUTH, RANGE 10 EAST,

Of the Gila and Salt River Base and Meridian,

In the State of Arizona,

EXECUTED BY

Roy J. Gill,

In the capacity of U. S. Surveyor, under Special Instructions dated December 16, 1916,
issued by the United States Surveyor General to govern surveys included in Group
No. 71, which were approved by the Commissioner of the General Land
Office, January 5, 1917, and Assignment Instructions dated November 25, 1916.

Resurvey and Survey commenced May 10, 1917.

Resurvey and Survey completed June 9, 1917.

3394

3394

56
A


3394

BOOK 3394

INDEX DIAGRAM.

		Township 1 South				Range 10 East					
		3	3	4	5	5	6				
		<i>Gila</i>		<i>and</i>		<i>Salt</i>		<i>River</i>		<i>Base</i>	
										<i>Line</i>	
15	6 48	5 42	4 37	3 33	2 28	1 19					
	48	47	41	37	32	28					
15	7 47	8 41	9 36	10 32	11 27	12 19					
	46	46	41	36	31	27					
14	18 45	17 40	16 36	15 31	14 26	13 18					
	45	45	40	35	31	26					
13	19 44	20 39	21 35	22 30	23 25	24 18					
	44	43	39	34	30	25					
12	30 43	29 38	28 34	27 29	26 24	25 17					
	23	23	22	22	21	21					
12	31 42	32 38	33 33	34 29	35 24	36 17					
	7	8	8	9	10	10					

T.I.S. R.10E.

-  Lines surveyed under this group.
-  Lines resurveyed under this group.
-  Lines of accepted surveys.
-  Unsurveyed.
-  Areas surveyed as per accepted plats on file.

3394
Book "D".

Group 71 - - - Arizona.

Date Diagram

T. 1 S., R. 10 E.

- Resurveyed -

	5/30/17	5/30/17	6/6/17	6/6/17	6/7/17	6/7/17
	Gila & 6	Salt 5	River 4	Base 3	Line. 2	 1
5/28/17	5/31/17	6/4/17	6/9/17	6/9/17	5/23/17	5/24/17
5/28/17	5/31/17	6/2/17	6/8/17	6/9/17	5/17/17	5/10/17
5/28/17	5/28/17	5/29/17	6/1/17	6/8/17	5/23/17	5/22/17
5/28/17	5/28/17	6/2/17	6/8/17	5/23/17	5/17/17	5/10/17
5/28/17	5/16/17	5/26/17	6/1/17	5/22/17	5/18/17	5/18/17
5/16/17	5/25/17	5/25/17	5/21/17	5/19/17	5/19/17	5/19/17
5/16/17	5/16/17	5/26/17	5/21/17	5/18/17	5/17/17	5/10/17
5/16/17	5/12/17	5/12/17	5/11/17	5/11/17	5/11/17	5/11/17
5/16/17	5/12/17	5/12/17	5/11/17	5/11/17	5/11/17	5/10/17
5/12/17	5/12/17	5/12/17	5/14/17	5/14/17	5/15/17	5/15/17
5/12/17	5/16/17	5/12/17	5/14/17	5/14/17	5/15/17	5/15/17

- Resurveyed -

Surveys executed by Roy J. Gill, U. S. Surveyor, on the dates shown on the above diagram.

Resurveys and surveys executed by Roy J. Gill, U. S. Surveyor on dates shown on date diagram on page 1 hereof, using Buff and Buff transit No. 7732 with Smith solar attachment. For description of instrument, see Book "A".

Examine the adjustments of the transit and correct all errors, then to test the solar apparatus by comparing its indications with a meridian determined by direct observation on the sun, proceed as follows:

Direct observation of the sun for azimuth.

At the cor. of Ts. 1 and 2 S., Rs. 10 and 11 E.

May 7, 1917. Lat. = $33^{\circ}17'27''$ N. Long. = $111^{\circ}16'08''$ W.

		Hor. Angle	Vert. Angle	Time
(1)		$8^{\circ}04'$	$23^{\circ}45'$	7h 32m 30s
(6)		$6^{\circ}57'$	$25^{\circ}08'$	7h 36m 30s
(2)		$7^{\circ}22'$	$23^{\circ}54'$	
(5)		$7^{\circ}37'$	$25^{\circ}00'$	
(3)		$7^{\circ}53'$	$24^{\circ}02'$	
(4)		$7^{\circ}08'$	$24^{\circ}49'$	

True bearing of reference point = S. $87^{\circ}08'$ E.

The solar apparatus by a.m. and p.m. observations defines positions for meridians within $0^{\circ}01'$ of arc from the meridian determined by direct observation. Therefore conclude the adjustments of the instrument are satisfactory.

Make another altitude observation of the sun for azimuth at the S.C. of T. 1 N., Rs. 9 and 10 E., as follows:

May 30, 1917. Lat. = $33^{\circ}22'33''$ N. Long. = $111^{\circ}22'21''$ W.

		Hor. Angle.	Vert. Angle.	Time.
(1)		$17^{\circ}26'$	$36^{\circ}32'30''$	8h 19m 30s
(6)		$16^{\circ}08'$	$37^{\circ}01'30''$	8h 24m 30s
(2)		$16^{\circ}39'$	$36^{\circ}44'30''$	
(5)		$16^{\circ}55'30''$	$36^{\circ}48'30''$	
(3)		$17^{\circ}14'$	$36^{\circ}54'$	
(4)		$16^{\circ}23'$	$36^{\circ}37'$	

True bearing of reference point = S. $76^{\circ}45'30''$ E.

Independent Resurvey of Gila and Salt River

Base Line, through Range 10 East.

Chains The reestablished standard corner of T. 1 N., Rs. 9 and 10 E., is a 3-in. iron post, firmly set 12 ins. above ground, properly mkd. on brass cap and witnessed by a md. of stone N. of cor. No bearing trees.
 From a point 3 lks. S. of above described Tp. cor. N. 89° 58' E. on secant line south of sec. 31. Over rolling land, through scattering undergrowth.

- 19.80 Wash, course SE.
- 26.00 Small draw, 8 lks. wide, course SW.
- 29.70 Wash, course SW.
- 38.40 Small draw, course SW.
- 40.00 1 lk. N. of secant.

Set an iron post, 3 ft. long, 1 in. dia., 26 ins. in the ground, for reestablished Std. 1/4 sec. cor., of Sec. 31, marked on brass cap

S C
 1/4 S 31

1917

; raise a mound of stone,
 2 ft. base, 1 1/2 ft. high N. of cor.
 The original Std. 1/4 sec. cor., bears N. 27° 15' W., 3.83 chs. dist. Destroy all trace of same.

- 44.40 Wash, 50 lks. wide, course SW.
- 50.20 Road, bears NE. and SW.
- 63.40 Wash, course SW.

- 72.20 Asc. 125 ft. over NW. slope to
- 80.00 Set an iron post, 3 ft. long, 2 ins. dia., 6 ins. in the ground, in a mound of stone, for reestablished S.C. of secs. 31 and 32, marked on brass cap

S C
 T 1 N R 10 E
 S 31 | S 32

1917

; raise a mound of stone,
 2 ft. base, 1 1/2 ft. high N. of cor.
 The original S. C. of secs. 31 and 32, bears N. 26° 22' W., 3.83 chs. dist. Destroy all trace of same.

Land; rolling.
 Soil; 2nd. and 3d. rate, sandy and gravelly.
 Undergrowth; palo-verde, catclaw, mesquite and iron wood.
 No timber.

N. 89° 59' E. on secant line through Sec. 32.
 Over broken and rolling land, through scattering undergrowth.

- 2.40 Spur, slopes SW.
- 11.80 Spur, slopes NW.
- 16.00 Spur, slopes N.
- 28.20 Spur, slopes NE.
- 39.21 The original Std. 1/4 sec. cor., bears N. 22° 42' W. 3.74 chs. Destroy all trace of same.

- 40.00 1 lk. S. of secant.
 Set an iron post, 3 ft. long, 1 in. dia., 6 ins. in ground, in md. of stone, for reestablished Std. 1/4 sec. cor. of Sec. 32, marked on brass cap

S C
 1/4 S 32

1917

; raise a mound of stone,
 2 ft. base, 1 1/2 ft. high N. of cor.

- 47.00 Road, bears NE. and SW.
- 48.00 Enter wash

Independent Resurvey of Gila and Salt River
Base Line, through Range 10 East

4

Chains

- 49.50 Leave wash, course SW. Asc. 120. ft. over steep SW. slope
58.00 Spur, slopes NW. Desc.
59.80 Small draw, course NW.
67.80 Spur, slopes NW. Desc. 110. ft. to
80.00 2 lks. S. of secant. Set an iron post, 3 ft. long, 2 ins.
dia., 24 ins. in the ground, for reestablished Std.
cor. of secs. 32 and 33, marked on brass cap

S C
T 1 N R 10 E
S 32:S 33

1917

; raise a mound of stone,
2 ft. base, $1\frac{1}{2}$ ft. high N. of cor.
The original Std. cor. of secs. 32 and 33, bears N. 36°
25' W. Destroy all trace of same.

Land; rolling and broken.
Soil; rocky, 4th rate.
Undergrowth; mesquite, catclaw and palo-verde.
No timber.

- N. $89^{\circ} 59'$ E. on secant line through Sec. 33.
Over mountainous land, through scattering undergrowth.
3.40 Draw, 15 lks. wide, course NW. Asc. SW. slope.
19.80 Top of cliff, thence over top.
22.00 Desc. over precipitous cliff 150 ft., thence desc. NE.
slope.
32.10 Draw, course N. Asc. 133 ft. over W. slope to
40.00 2 lks. S. of secant,
Set an iron post, 3 ft. long, 1 in. dia., 26 ins. in the
ground, for reestablished std. $\frac{1}{4}$ sec., cor., of Sec. 33
marked on brass cap

S C
 $\frac{1}{4}$ S 33

1917

; raise a mound of stone, 2
ft. base, $1\frac{1}{2}$ ft. high N. of cor. Find no evidence
of original standard $\frac{1}{4}$ sec. cor.
Ascend 136 ft.

- 46.80 Fence, bears NE. and SW.
60.50 Ridge, bears N. and SW. Desc. 124 ft. over E. slope
67.40 Head of canyon, course S. Asc. 55 ft. over rocky NW.
slope to
80.00 3 lks. S. of secant.
Set an iron post, 3 ft. long, 2 ins. dia., in a mound of
stone, for reestablished Std. cor. of secs. 33 and 34,
marked on brass cap

S C
T 1 N R 10 E
S 33:S 34

1917

; raise a mound of stone,
2 ft. base, $1\frac{1}{2}$ ft. high N. of cor.
The original Std. cor. of secs. 33 and 34, bears N. 46°
15' W. 5.12 chs. dist. Destroy old cor.

Land; mountainous.
Soil, rocky, 4th rate.
Undergrowth; palo verde, mesquite and catclaw.
No timber.

Independent Resurvey of Gila and Salt River
Base Line, through Range 10 East.

Chains East on secant line through sec. 34.
Ascend over mountainous broken NW. slope.
Through scattering undergrowth.

12.30 Spur, slopes SW.
23.90 Low ridge, bears N. and S. Desc. 100 ft. to
40.00 2 lks. S. of secant.
Set an iron post, 3 ft. long, 1 in. dia., 26 ins. in the
ground, for reestablished std. $\frac{1}{4}$ sec. cor., of Sec. 34
marked on brass cap

S C
 $\frac{1}{4}$ S 34

1917

; raise a mound of stone,
2 ft. base, $1\frac{1}{2}$ ft. high N. of cor.
The original std. $\frac{1}{4}$ sec. cor., bears N. 45° 38' W., 5.45
chs. dist. Destroy this cor.

47.50 Canyon, course SE. Asc. 320 ft. over W. slope.
67.70 Spur, slopes S. Desc. 100 ft. over rocky SE. slope to
80.00 2 lks. S. of secant.
Set an iron post, 3 ft. long, 2 ins. dia., in a mound of
stone, for reestablished Std. cor. of secs. 34 and
35, marked on brass cap

S C
T 1 N | R 10 E
S 34 | S 35

1917

; raise a mound of stone,
2 ft. base, $1\frac{1}{2}$ ft. high N. of cor.
The original std. cor. of secs. 34 and 35, bears N. 50°
15' W., 5.72 chs. dist. Destroy this cor.

Land; mountainous.
Soil, rocky, 4th rate.
Undergrowth; palo-verde, mesquite and catclaw.
No timber.

S. 89° 59' E. on secant line through sec. 35
Over mountainous land through scattering undergrowth.
Desc. SE. slope.

5.10 Head of canyon, course SW. Asc. 390 ft. over W. slope.
24.80 Ridge, bears N. and SW. Desc. 380. ft. over E. slope.
39.90 Head of draw, course SE. Ascend.
40.00 1 lk. S. of secant.
Set an iron post, 3 ft. long, 1 in. dia., 26 ins. in the
ground, for reestablished std. $\frac{1}{4}$ sec. cor., of Sec.
35, marked on brass cap

S C
 $\frac{1}{4}$ S 35

1917

; raise a mound of stone,
2 ft. base, $1\frac{1}{2}$ ft. high N. of cor.
Find no evidence of original Std. $\frac{1}{4}$ sec. cor.

64.90 Desc. 355 ft. over steep rocky E. slope.
75.00 Canyon, course S., thence in bottom of canyon.
78.80 Creek, with stream of running water 6 lks. wide, 3 ins.
deep, course S. Asc. 60 ft. over W. slope to
80.00 Set an iron post, 3 ft. long, 2 ins. dia., 6 ins. in
ground, in mound of stone, for reestablished std. cor.
of secs. 35 and 36, marked on brass cap

S C
T 1 N | R 10 E
S 35 | S 36

1917 ;

Independent Resurvey of Gila and Salt River

Base Line, through Range 10 East.

6

Chains raise a mound of stone, 2 ft. base, 1½ ft. high N. of cor.
 Find no evidence of original std. cor. of secs. 35 and 36

Land; mountainous.
 Soil; rocky, 4th rate.
 Undergrowth; palo-verde, mesquite, and catclaw.
 No timber.

S. 89° 59' E. on secant line S. of sec. 36
 Over mountainous land, through scattering undergrowth.
 Asc. 120 ft. over rocky broken SW. slope.

15.00 Spur, slopes S. Desc. 50 ft.
 18.50 Draw, course SW. Asc. 400 ft. over cliffs and rocks to
 40.00 1 lk. N. of secant,
 Set an iron post, 3 ft. long, 1 in. dia., in mound of
 stone, for reestablished std. ¼ sec. cor., of sec. 36
 marked on brass cap.

S C
 ¼ S 36

1917

; raise a mound of stone,
 2 ft. base, 1½ ft. high N. of cor.
 Find no evidence of original std. ¼ sec. cor.
 Asc. 160 ft. over W. slope to

40.50 Foot of cliff 50 ft. high.
 41.10 Top of cliff.
 51.10 Ridge, bears NE. and S. Desc. 355 ft. over SE. slope to
 80.00 3 lks. N. of secant,
 Set an iron post, 3 ft. long, 3 ins. dia., 24 ins. in
 the ground, for reestablished std. cor. of T. 1 N.,
 Rs. 10 and 11 E., marked on brass cap

S C
 T 1 N
 R 10 E | R 11 E
 S 36 | S 31

1917

; raise a mound of stone,
 2 ft. base, 1½ ft. high N. of cor.
 Find no evidence of original std. Tp. cor.

Land; mountainous.
 Soil; rocky, 4th rate.
 Undergrowth; palo verde, mesquite and catclaw.
 No timber.

Chains The original cor. of Ts. 1 and 2 S., Rs. 10 and 11 E., is a mound of stone with no marks visible. No better identify this cor., retrace south 3 miles making diligent search for old corners at record distances, but without success.

Return to old mound of stone, which is on top of Comet Peak as described in the original notes.

Thence S. 89° 48' W. (record course) on random line on S. bdy. of Tp.

Make diligent search for original $\frac{1}{4}$ sec. and sec. cors. at record distances, but without success. Set temp. cors. at intervals of 40. chains until at

481.99 Fall 2.52 chs. N. of the reestablished cor. of Ts. 1 and 2 S., Rs. 9 and 10 E., which is a 3-in. iron post, projecting 12 ins. above ground, firmly set, properly mkd. on brass cap and witnessed by a md. of stone S. of cor. No bearing trees.

Thence N. 89° 30' E. on a true line on S. bdy. sec. 31. Over nearly level land, through scattering undergrowth.

39.41 (Proportional dist.) Set an iron post, 3 ft. long, 1 in. dia., 26 ins. in the ground, for reestablished $\frac{1}{4}$ sec. cor. for sec. 6 only, marked on brass cap

$\frac{1}{4}$ S 6

1917

41.99 Set an iron post, 3 ft. long, 1 in. dia., 26 ins. in the ground for reestablished $\frac{1}{4}$ sec. cor. of sec. 31, marked on brass cap

; raise a mound of stone, 2 ft. base, $1\frac{1}{2}$ ft. high S. of cor.

$\frac{1}{4}$ S 31

1917

45.00 Wash, 15 lks. wide, course SW.

79.64 (Proportional dist.) Set an iron post, 3 ft. long, 2 ins. dia., 24 ins. in the ground, for reestablished cor. of secs. 5 and 6 only, marked on brass cap

; raise a mound of stone, 2 ft. base, $1\frac{1}{2}$ ft. high N. of cor.

S 6 | S 5
T 2 S | R 10 E

1917

81.99 Set an iron post, 3 ft. long, 2 ins. dia., 24 ins. in the ground, for reestablished cor. of secs. 31 and 32, marked on brass cap.

; raise a mound of stone, 2 ft. base, $1\frac{1}{2}$ ft. high S. of cor.

T 1 S | R 10 E
S 31 | S 32

1917

2 ft. base, $1\frac{1}{2}$ ft. high N. of cor.

Land; level.
Soil; sandy, 3d rate.
Undergrowth; palo-verde, catclaw and mesquite.
No timber.

N. 89° 30' E., on true line, on S. bdy. sec. 32. Over level land, through scattering undergrowth.

12.23 Asc. 250 ft. over rough and rocky SE. slope.

27.13 Top of hog back brs. NE. & SW. Desc. 250 ft. over NE. slope.

37.73 Enter level land.

37.88 $\frac{1}{2}$ (Proportional dist. of 40.23 $\frac{1}{2}$ chs. from cor. of secs. 5 & 6.) Set an iron post, 3 ft. long, 1 in. dia., in

8 Dependent Resurvey of S. Bdy. of T. 1 S., R. 10 E.

Chains	<p>mound of stone, for reestablished $\frac{1}{4}$ sec. cor. of sec. 5 only, marked on brass cap</p> <p style="text-align: center;"><u>$\frac{1}{4}$ S 5</u></p> <p style="text-align: center;">1917</p> <p style="text-align: right;">; raise a mound of stone, 2</p> <p>ft. base, $1\frac{1}{2}$ ft. high S. of cor.</p> <p>40.00 Set an iron post, 3 ft. long, 1 in. dia., in mound of stone for reestablished $\frac{1}{4}$ sec. cor. of Sec. 32, marked on brass cap</p> <p style="text-align: center;"><u>$\frac{1}{4}$ S 32</u></p> <p style="text-align: center;">1917</p> <p style="text-align: right;">; raise a mound of stone,</p> <p>2 ft. base, $1\frac{1}{2}$ ft. high N. of cor.</p> <p>78.12 (Proportional dist. of 80.47 chs. from cor. of secs. 5 and 6). Set an iron post, 3 ft. long, 2 ins. dia., 24 ins. in the ground, for reestablished cor. of secs. 4 and 5 only, marked on brass cap</p> <p style="text-align: center;"><u>S 5 S 4</u> T 2 S R 10 E</p> <p style="text-align: center;">1917</p> <p style="text-align: right;">; raise a mound of stone,</p> <p>2 ft. base, $1\frac{1}{2}$ ft. high S. of cor.</p> <p>80.00 Set an iron post, 3 ft. long, 2 ins. dia., 24 ins. in ground, for reestablished cor. of secs. 32 and 33, marked on brass cap</p> <p style="text-align: center;"><u>T 1 S R 10 E</u> <u>S 32 S 33</u></p> <p style="text-align: center;">1917</p> <p style="text-align: right;">; raise a mound of stone,</p> <p>2 ft. base, $1\frac{1}{2}$ ft. high N. of cor.</p> <p>Land; level. Soil; 2nd rate and sandy. Undergrowth; palo verde. No timber.</p> <hr/> <p>N. 89° 30' E. on true line on S. bdy. of sec. 33. Over level land, through scattering undergrowth.</p> <p>38.35$\frac{1}{2}$ (Proportional dist. of 40.23$\frac{1}{2}$ chs. from cor. of secs. 4 and 5) Set an iron post, 3 ft. long, 1 in. dia., 20 ins. in the ground, supported in mound of stone, for reestablished $\frac{1}{4}$ sec. cor. of sec. 4 only, marked on brass cap</p> <p style="text-align: center;"><u>$\frac{1}{4}$ S 4</u></p> <p style="text-align: center;">1917</p> <p style="text-align: right;">; raise a mound of stone,</p> <p>2 ft. base, $1\frac{1}{2}$ ft. high S. of cor.</p> <p>40.00 Set an iron post, 3 ft. long, 1 in. dia., 15 ins. in ground in mound of stone for reestablished $\frac{1}{4}$ sec. cor. of sec. 33, marked on brass cap</p> <p style="text-align: center;"><u>$\frac{1}{4}$ S 33</u></p> <p style="text-align: center;">1917</p> <p style="text-align: right;">; raise a mound of stone,</p> <p>2 ft. base, $1\frac{1}{2}$ ft. high N. of cor.</p> <p>78.59 (Proportional dist. of 80.47 chs. from cor. of secs. 4 and 5) Set an iron post, 3 ft. long, 2 ins. dia.,</p>
--------	--

Dependent Resurvey of S. Bdy. of T. 1 S., R. 10 E. 9

Chains 6 ins. in the ground, supported in a mound of stone, for reestablished cor. of secs. 3 and 4 only, marked on brass cap

$$\begin{array}{c} \hline S 4 | S 3 \\ \hline T 2 S | R 10 E \end{array}$$

1917

80.00 ; raise a mound of stone, 2 ft. base, 1½ ft. high S. of cor.
 Set an iron post, 3 ft. long, 2 ins. dia., 12 ins. in the ground in a mound of stone, for reestablished cor. of secs. 33 and 34, marked on brass cap

$$\begin{array}{c} T 1 S | R 10 E \\ \hline S 33 | S 34 \end{array}$$

1917

stone, 2 ft. base, 1½ ft. high N. of cor.

Land; level.
 Soil; 3d. rate and gravelly.
 Undergrowth: palo verde, iron wood and bunch grass.
 No timber.

12.00 N. 89° 30' E., on true line, on S. bdy. of sec. 34.
 Over level land, through dense undergrowth.
 Enter Queen Creek, dry at this point, course S. 70° W.
 33.00 Leave Queen Creek.
 38.82½ (Proportional dist. of 40.23½ chs. from cor. of secs. 3 and 4). Set an iron post, 3 ft. long, 1 in. dia., in mound of stone, for reestablished ¼ sec. cor. of sec. 3 only, marked on brass cap

$$\begin{array}{c} \hline \frac{1}{4} S 3 \\ \hline \end{array}$$

1917

40.00 ; Raise a mound of stone, 2 ft. base, 1½ ft. high S. of cor.
 Set an iron post, 3 ft. long, 1 in. dia., in a mound of stone, for reestablished ¼ sec. cor., of sec. 34, marked on brass cap

$$\begin{array}{c} \hline \frac{1}{4} S 34 \\ \hline \end{array}$$

1917

54.33 ; raise a mound of stone, 2 ft. base, 1½ ft. high N. of cor.
 Thence over gently rolling land.
 Road, bears N. and S.
 79.06 (Proportional dist. of 80.47 chs. from cor. of secs. 3 and 4) Set an iron post, 3 ft. long, 2 ins. dia., 24 ins. in the ground, for reestablished cor. of secs. 2 and 3 only, marked on brass cap

$$\begin{array}{c} \hline S 3 | S 2 \\ \hline T 2 S | R 10 E \end{array}$$

1917

80.00 ; raise a mound of stone, 2 ft. base, 1½ ft. high S. of cor.
 Set an iron post, 3 ft. long, 2 ins. dia., 24 ins. in the ground, for reestablished cor. of secs. 34 and 35, marked on brass cap

$$\begin{array}{c} T 1 S | R 10 E \\ \hline S 34 | S 35 \\ \hline 1917 \end{array}$$

10 Dependent Resurvey of S. Bdy. T. 1 S., R. 10 E.

Chains ; raise a mound of stone, 2 ft. base, 1 1/2 ft. high N. of cor.

Land; level and gently rolling.
Soil; 3d. rate; gravelly.
Undergrowth; dense palo verde, catclaw and mesquite.
No timber.

16.43 Spur, slopes N.
20.03 Draw, course NW.
39.29 1/2 (Proportional dist. of 40.23 1/2 chs. from cor. of secs. 2 and 3) Set an iron post, 3 ft. long, 1 in. dia., 6 ins. in the ground, supported in a mound of stone, for reestablished 1/4 sec. cor., of sec. 2 only, marked on brass cap.

1/4 S 2

1917

40.00 ; raise a mound of stone, 2 ft. base, 1 1/2 ft. high S. of cor. Set an iron post, 3 ft. long, 1 in. dia., in mound of stone, for reestablished 1/4 sec. cor. of sec. 35, marked on brass cap

1/4 S 35

1917

53.13 ; raise a mound of stone, 2 ft. base, 1 1/2 ft. high N. of cor. Spur, slopes N.

60.63 Draw, course N.

73.53 Spur slopes N. Desc of 60.63 chs. from cor. of sec.

79.53 (Proportional dist. of 80.47 chs. from cor. of secs. 2 and 3) Set an iron post, 3 ft. long, 2 ins. dia., 24 ins. in the ground, for reestablished cor. of Secs. 1 and 2 only, marked on brass cap

S 2 | S 1
T 2 S | R 10 E

1917

80.00 ; raise a mound of stone, 2 ft. base, 1 1/2 ft. high S. of cor. Set an iron post, 3 ft. long, 2 ins. dia., 24 ins. in the ground, for reestablished cor. of secs. 35 and 36, marked on brass cap

T 1 S | R 10 E
S 35 | S 36

1917

; raise a mound of stone, 2 ft. base, 1 1/2 ft. high N. of cor.

Land; rolling.
Soil; 3d. rate; gravelly.
Undergrowth; palo verde and mesquite.
No timber.

8.77 N. 89° 30' E. on true line on S. bdy. of sec. 36. Over rolling land, through scattering undergrowth. Spur, slopes N.

Dependent Resurvey of S. Bdy. T. 1 S., R. 10 E.

Chains

- 20.77 Road, bears NE. and SW.
- 26.47 Wash, course NE.
- 37.17 Spur, slopes NE.
- 39.76 $\frac{1}{2}$ (Proportional dist. of 40.23 $\frac{1}{2}$ chs. from cor. of secs. 1 and 2.) Set an iron post, 3 ft. long, 1 in. dia., in a mound of stone, for reestablished $\frac{1}{4}$ sec. cor. of sec. 1 only, marked on brass cap

$\frac{1}{4}$ S 1

1917


- 40.00 ; raise a mound of stone, 2 ft. base, 1 $\frac{1}{2}$ -ft. high S. of cor. Set an iron post, 3 ft. long, 1 in. dia., 20 ins. in the ground, supported in mound of stone, for reestablished $\frac{1}{4}$ sec. cor. of sec. 36, marked on brass cap

$\frac{1}{4}$ S 36

1917

- 40.67 ; raise a mound of stone, 2 ft. base, 1 $\frac{1}{2}$ ft. high N. of cor. Draw, course N. Asc. 55 ft.
- 51.87 Spur, slopes SW. Desc. 60 ft.
- 64.07 Draw, course S. Leave rolling and enter mountainous land. Asc. 100 ft
- 67.47 Spur, slopes SW. Asc. broken SW. slope to top of Comet Peak.

- 80.00 (80.47 chs. from cor. of secs. 1 and 2) Intersect the original cor. of Ts. 1 and 2 S., Rs. 10 and 11 E., hereinbefore described. On N. side of old stone mound, set an iron post 3 ft. long, 3 ins. dia., in a mound of stone, for reestablished cor. of Ts. 1 and 2 S., Rs. 10 and 11 E., marked on brass cap



1917

Note: The old mound of stone was further identified as being the remains of the original corner by a Mexican who worked on the original survey.

Land; rolling and mountainous.
 Soil, rocky, 4th rate.
 Undergrowth; palo verde, mesquite and catclaw.
 No timber.

12.

Dependent Resurvey of West Boundary of T. 1 S., R. 10 E.

Chains

The east boundary of T. 1 S., R. 9 E., having been originally surveyed in 1913 by Sidney E. Blout, U. S. Surveyor, under the Group system it is not considered necessary to rechain the intervals between the existent corners unless an error of closure should be found in the west tier of secs. in T. 1 S., R. 10 E., therefore, as a new set of corners are required on the line to refer to sections and quarter-sections in T. 1 S., R. 10 E., the position of said new cors. is determined by measuring N. from each existent cor. a dist. of 4.35 chs., which is the falling obtained by surveying a sectional correction line west through T. 1 S., R. 10 E., as herein-after described. This method gives computed regular intervals of 40.00 chains for the new corners on the line, with the exception of the S. 1-2 of W. bdy. of Sec. 31, and the N. 1-2 of W. bdy. of Sec. 6. In the following notes of the resurvey of the line, the distances which were actually chained are so noted and others are either described as "from record" or "computed from record" as the case may be, the items of topography being omitted but the general description of each mile copied from record. Such a procedure was adopted in order to present the resurvey in proper form.

From the original cor. of Ts. 1 and 2 S., Rs. 9 and 10 E., hereinbefore described,

North, on W. bdy. of Sec. 31.

40.00 The original $\frac{1}{4}$ sec. cor. of Secs. 31 and 36, which is an iron post, 1 in. in diam., 10 ins. above ground, firmly set, properly marked on brass cap, and witnessed by pits N. and S. of post, and md. of earth W. of cor. (From record)

Change this cor. to refer to Sec. 36 only, by obliterating markings on brass cap, referring to area east of this line.

44.35 (Computed from record) Thence, chain measurement, North 4.35 chs. to Set an iron post, 3 ft. long, 1 in. dia., 8 ins. in the ground, supported in a mound of stone, for $\frac{1}{4}$ sec. cor., marked on brass cap



1917


; raise a mound of stone,

2 ft. base, $1\frac{1}{2}$ ft. high E. of cor.

80.00 (From record) The original cor. of Secs. 25, 30, 31 and 36, which is an iron post, 3 ins. in diam., 12 ins. above ground, firmly set, properly marked on brass cap, witnessed by bearing trees NE., SE., SW., and NW.

Change this cor. to refer to Secs. 25 and 36 only, by obliterating markings on brass cap, referring to area east of this line, and by obliterating markings on NE. and SE. bearing trees.

84.35 (Computed from record) Thence, chain measurement, North 4.35 chs. to Set an iron post, 3 ft. long, 2 ins. dia., 24 ins. in the ground, for cor. of secs. 30 and 31, marked on brass cap



1917

; raise a mound of stone,

2 ft. base, $1\frac{1}{2}$ ft. high E. of cor.

Land; rolling. Soil; poor, stony, clay loam 6 to 12 ins. Timber, scattering mesquite and palo verde.

35.65 (Computed from record) Thence North on W. bdy. sec. 30. The original $\frac{1}{4}$ sec. cor. of secs. 25 and 30, which is an iron post 1 in. in dia., 10 ins. above ground, firmly set, properly marked on brass cap, md. of stone W.

Dependent Resurvey of West Boundary of T. 1 S., R. 10 E.

Chains

Change this cor. to refer to Sec. 25 only, by obliterating markings on brass cap, referring to area east of this line.

40.00 (Computed from record) Thence, chain measurement, North 4.35 chs. to Set an iron post, 3 ft. long, 1 in. dia., 18 ins. in the ground, supported in mound of stone, for 1/4 sec. cor. of sec. 30, marked on brass cap




1917

; raise a mound of stone, 2 ft. base, 1 1/2 ft. high E. of cor.

75.65 (Computed from record) The original cor. of secs. 19, 24, 25 and 30, which is an iron post, 3 ins. in diam., 12 ins. above ground, firmly set, properly marked on brass cap, witnessed by bearing trees NE., SE., SW., and NW.

Change this cor. to refer to Secs. 24 and 25 only, by obliterating markings on brass cap, referring to area east of this line, and by obliterating markings on NE. and SE. bearing trees.

80.00 (Computed from record) Thence, chain measurement, North 4.65 chs. to Set an iron post, 3 ft. long, 2 ins. dia., 12 ins. in ground, supported in mound of stone, for cor. of secs. 19 and 30, marked on brass cap



1917


; raise a mound of stone, 2 ft. base, 1 1/2 ft. high E. of cor.

Land, rolling and hilly, drains to the SW. Soil, poor, dry, stony, clay loam about 8 ins. deep on dry stony, clay subsoil. Light growth bunch grass. Timber, scattering mesquite and pale verde.

35.65 (Computed from record) Change North on W. bdy. Sec. 19. The original 1/4 sec. cor. of secs. 19 and 24, which is an iron post 1 in. in dia., 10 ins. above ground, firmly set, properly marked on brass cap, md. of stone W.

Change this cor. to refer to Sec. 24, only, by obliterating markings on brass cap, referring to area east of this line.

40.00 (Computed from record) Thence, chain measurement, North 4.35 chs. to Set an iron post, 3 ft. long, 1 in. dia., 8 ins. in the ground, supported in mound of stone, for 1/4 sec. cor. of sec. 19, marked on brass cap



1917

; raise a mound of stone, 2 ft. base, 1 1/2 ft. high E. of cor.

75.65 (Computed from record) The original cor. of secs. 13, 18, 19 and 24, which is an iron post 3 ins. in dia. 12 ins. above ground, firmly set, properly marked on brass cap, witnessed by bearing trees NE., SE., SW., and NW.

Change this cor. to refer to Secs. 13 and 24 only, by obliterating markings on brass cap, referring to area east of this line, and obliterating markings on

Chains NE. and SE. bearing trees.
 Thence, chain measurement, North 4.35 chs. to
 80.00 Set an iron post, 3 ft. long, 2 ins. dia., 4 ins. in the
 ground, supported in mound of stone, for cor. of secs.
 18 and 19, marked on brass cap (Computed from record)

T 1 S
 S 18
 S 19
 R 10 E

1917

; raise a mound of stone, 2
 ft. base, 1½ ft. high E. of cor.

Land, rolling, hilly and mountainous.
 Soil, poor, stony clay loam, 4 to 10 ins. deep on dry,
 clay and stone subsoil. Very little bunch grass.
 Timber, scattering mesquite and palo verde.

Thence North on W. Bdy. Sec. 18.
 35.65 (Computed from record) The original ¼ sec. cor. of
 Secs. 13 and 18, which is an iron post, 1 in. diam.,
 10 ins. above ground, firmly set, properly marked on
 brass cap, md. of stone W.

Change this cor. to refer to Sec. 13 only, by
 obliterating markings on brass cap, referring to
 area east of this line.

Thence, chain measurement, North 4.35 chs. to
 40.00 (Computed from record) Set an iron post, 3 ft. long,
 1 in. dia., 26 ins. in the ground, for ¼ sec. cor. of
 sec. 18, marked on brass cap

¼
 S 18

1917

; raise a mound of stone,
 2 ft. base, 1½ ft. high E. of cor.

75.65 (Computed from record) The original cor. of Secs. 7,
 12, 13 and 18, which is an iron post, 3 ins. in diam.,
 12 ins. above ground, firmly set, properly marked on
 brass cap, witnessed by bearing trees NE., SE., SW.,
 and NW.

Change this cor. to refer to Secs. 12 and 13
 only, by obliterating markings on brass cap, referring
 to area east of this line, and by obliterating mark-
 ings on NE. and SE. bearing trees.

Thence, chain measurement, North 4.35 chs. to
 80.00 (Computed from record) Set an iron post, 3 ft. long, 2
 ins. dia., 24 ins. in ground, for cor. of secs. 7 and
 18, marked on brass cap

T 1 S
 S 7
 S 18
 R 10 E

1917

; raise a mound of stone,
 2 ft. base, 1½ ft. high E. of cor.

Land, low, rolling hills, drains to the SW., soil, poor
 dry, stony clay loam, on dry clay and shale subsoil.
 Very little grass.
 Timber, scattering palo verde and mesquite.

Dependent Resurvey of the West Boundary of T. 1 S., R. 10 E. 15

Chains
 35.65 Thence North on W. Bdy. Sec. 7.
 (Computed from record) The original $\frac{1}{4}$ sec. cor. of Secs. 7 and 12, which is an iron post, 1 in. dia., 10 ins. above ground, firmly set, properly marked on brass cap, md. of stone W., and witnessed by bearing trees NE. and NW.
 Change this cor. to refer to Sec. 12 only, by obliterating markings on brass cap, referring to area east of this line, and by obliterating markings on NE. B.T.

40.00 Thence, chain measurement, North 4.35 chs. to
 (Computed from record) Set an iron post, 3 ft. long, 1 in. dia., 20 ins. in the ground, supported in mound of stone, for $\frac{1}{4}$ sec. cor., of sec. 7, marked on brass cap



1917

75.65 ; raise a mound of stone, 2 ft. base, $1\frac{1}{2}$ ft. high E. of cor.
 (Computed from record) The original cor. of secs. 1, 6, 7 and 12, which is an iron post, 3 ins. in dia., 12 ins. above ground, firmly set, properly marked on brass cap, witnessed by bearing trees NE., SE., SW., and NW.

Change this cor. to refer to Secs. 1 and 12 only by obliterating markings on brass cap, referring to area east of this line, and by obliterating markings on NE. and SE. bearing trees.

80.00 Thence, chain measurement, North 4.35 chs. to
 (Computed from record) Set an iron post, 3 ft. long, 2 ins. dia., 24 ins. in the ground, for cor. of secs. 6 and 7, marked on brass cap



1917

; raise a mound of stone, 2 ft. base, $1\frac{1}{2}$ ft. high E. of cor.

Land, hilly, drains to the SW.
 Soil, poor, dry, stony clay loam 6 ins. deep on clay and limestone subsoil. Light growth of bunch grass.
 Timber, scattering mesquite, palo verde and ironwood.

35.65 North on W. Bdy. Sec. 6.
 (Computed from record) The original $\frac{1}{4}$ sec. cor. of Secs. 1 and 6, which is an iron post, 1 in. dia., 10 ins. above ground, firmly set, properly marked on brass cap, md. of stone W.
 Change this cor. to refer to Sec. 1 only, by obliterating markings on brass cap, referring to area east of this line.

39.70 Thence, chain measurement, North 4.05 chs. to
 (Computed from record) Set an iron post, 3 ft. long, 1 in. dia., 26 ins. in the ground, for W. C. to the $\frac{1}{4}$ sec. cor. of sec. 6, marked on brass cap



1917

; raise a mound of stone, 2 ft. base, $1\frac{1}{2}$ ft. high E. of cor.

16 Dependent Resurvey of the West Boundary of T. 1 S., R. 10 E.

Chains

40.00 True point for cor. falls in wash, a place unsuitable for cor.

68.03 (Computed from record) Intersect the Gila and Salt River Base line 86 lks. west of the standard cor. of Tps. 1 N., Rs. 9 and 10 E., the original closing corner of Tps. 1 S., Rs. 9 and 10 E., is an iron post, 3 ins. dia., 12 ins. above ground, firmly set, properly marked on brass cap, with md. of stone S. of cor.

Land, rolling and hilly.

Soil, poor, dry, stony clay loam with considerable sand and gravel 8 to 14 ins. deep on dry, stony clay and gravel subsoil.

Timber, scattering mesquite and palo verde.

Survey of E. Bdy. of T. 1 S., R. 10 E.

Chains From the reestablished cor. of Ts. 1 and 2 S., Rs. 10 and 11 E., hereinbefore described, North, bet. secs. 31 and 36. Over mountainous land; through scattering undergrowth. Desc. from Comet Peak over steep and rocky NE. slope.

23.30 Enter valley, bears E. and W. Thence over rolling land

31.40 Road, Phoenix to Superior, bears SE. and NW.

32.30 S. bank of Queen Creek Wash, brs. E. and W. Thence across said wash, course W.

35.90 N. bank of Queen Creek Wash, bears E. and W. Thence over level bottom land.

40.00 Set an iron post, 3 ft. long, 1 in. dia., 26 ins. in the ground, for $\frac{1}{4}$ sec. cor., marked on brass cap

$\frac{1}{4}$
 S 36 | S 31

1917

; raise a mound of stone, 2 ft. base, $1\frac{1}{2}$ ft. high W. of cor.

41.00 Leave level bottom land. Enter rolling land. Asc. gentle SW. slope.

51.90 Draw, course SW.

80.00 Set an iron post, 3 ft. long, 2 ins. dia., 14 ins. in the ground, supported in mound of stone, for cor. of secs. 25, 30, 31 and 36, marked on brass cap

T 1 S
 R 10 E | R 11 E
 S 25 | S 30
 S 36 | S 31

1917

; raise a mound of stone, 2 ft. base, $1\frac{1}{2}$ ft. high W. of cor. Land; mountainous, rolling and level. Soil; rocky, 4th rate. Undergrowth; buck brush, catclaw, mesquite and greasewood. No timber.

North, bet. secs. 25 and 30. Over rough and broken land, through scattering undergrowth. Asc.

12.70 Spur, slopes SW.

16.20 Draw, course SW.

21.80 Ridge, bears NE. and SW. Desc. 100 ft.

29.70 Draw, course SW.

36.20 Spur, slopes SW.

40.00 Set an iron post, 3 ft. long, 1 in. dia., 15 ins. in the ground, supported in a mound of stone, for $\frac{1}{4}$ sec. cor. marked on brass cap

$\frac{1}{4}$
 S 25 | S 30

1917

; raise a mound of stone, 2 ft. base, $1\frac{1}{2}$ ft. high W. of cor.

42.30 Draw, course SW.

46.30 Spur, slopes SW.

50.90 Draw, course SW.

63.40 Spur, slopes SW.

69.70 Desc. over NW. slope 100 ft. to

76.00 Draw, course W. Asc. 100 ft.

80.00 Set an iron post, 3 ft. long, 2 ins. dia., 6 ins. in the ground, supported in a mound of stone, for cor. of secs. 19, 24, 25 and 30, marked on brass cap

T 1 S
 R 10 E | R 11 E
 S 24 | S 19
 S 25 | S 30

1917

Chains

3.74; ; raise a mound of stone,
 2 ft. base, 1½ ft. high W. of cor.
 Land; rough and broken.
 Soil; 3d. and 4th rate, gravelly and rocky.
 Undergrowth; palo verde, catclaw, mesquite and ocatilla.
 No timber.

North bet. secs. 19 and 24.
 Over broken and rolling land, through scattering
 undergrowth. Asc.

- 8.10 Ridge, bears NE. and SW. Desc. NW. slope.
- 23.40 Draw, course SW.
- 40.00 Set an iron post, 3 ft. long, 1 in. dia., 4 ins. in the
 ground, supported in mound of stone, for ¼ sec. cor.,
 marked on brass cap

¼
 S 24:S 19

1917

; raise a mound of stone,
 2 ft. base, 1½ ft. high W. of cor.

- 46.80 Ridge, bears E. and W.
- 51.50 Draw, course SW.
- 56.60 Small spur, slopes SE.
- 58.90 Enter wash, 20 lks. wide, course SE.
- 64.00 Leave wash. Asc. 100 ft. over SE. slope to
- 80.00 Set an iron post, 3 ft. long, 2 ins. dia., 6 ins. in the
 ground, supported in mound of stone, for cor. of secs.
 13, 18, 19 and 24, marked on brass cap

T 1 S
 R 10 E:R 11 E
 S 13:S 18
 S 24:S 19

1917

; raise a mound of stone,
 2 ft. base, 1½ ft. high W. of cor.
 Land; broken and rolling.
 Soil; rocky, 3d rate, gravelly.
 Undergrowth; palo verde, ocatilla, giant cacti and iron-
 wood.
 No timber.

North, bet. secs. 13 and 18.
 Over broken and rolling land, through scattering
 undergrowth. Asc.

- 7.10 Ridge, bears NE. and SW. Desc. 80 ft. over NE. slope.
- 18.70 Draw, course SW.
- 31.00 Spur, slopes SW. Desc. 75 ft. over NW. slope.
- 40.00 Set an iron post, 3 ft. long, 1 in. dia., 4 ins. in
 ground, supported in mound of stone, for ¼ sec. cor.
 marked on brass cap

¼
 S 13:S 18

1917

; raise a mound of stone, 2
 ft. base, 1½ ft. high W. of cor.

- 42.10 Draw, course SW.
- 46.50 Spur, slopes SW.
- 58.40 Small draw, course SW.
- 63.30 Spur, slopes S. Desc. 75 ft. over NW. slope to
- 76.20 Draw, 20 lks. wide, course SW.

Survey of E. Bdy. of T. 1 S., R. 10 E.

Chains

80.00 Set an iron post, 3 ft. long, 2 ins. dia., 24 ins. in ground; for cor. of secs. 7, 12, 13 and 18, marked on brass cap

T 1 S
R 10 E:R 11 E
S 12:S 7
S 13:S 18

1917

; raise a mound of stone, 2 ft. base, 1 1/2 ft. high W. of cor.
Land; rolling and broken.
Soil; 3d rate, gravelly.
Undergrowth; palo verde and mesquite.
No timber.

24.30 North, bet. secs. 7 and 12.
Over rolling land, through scattering undergrowth.
Spur slopes W. Thence along broken S. and SE. slope.

40.00 Set an iron post, 3 ft. long, 1 in. dia., 12 ins. in the ground, in a mound of stone, for 1/4 sec. cor., marked on brass cap

1/4
S 12:S 7

1917

; raise a mound of stone, 2 ft. base, 1 1/2 ft. high W. of cor.,

80.00 Set an iron post, 3 ft. long, 2 ins. dia., 20 ins. in ground, supported in mound of stone, for cor. of secs. 1, 6, 7 and 12, marked on brass cap

T 1 S
R 10 E:R 11 E
S 1:S 6
S 12:S 7

1917

; raise a mound of stone, 2 ft. base, 1 1/2 ft. high W. of cor.
Land; rolling and broken.
Soil; 3d rate, gravelly.
Undergrowth; palo verde, mesquite, catclaw, and buck brush.
No timber.

7.50 North bet. secs. 1 and 6.
Over rolling land, through scattering undergrowth.
Wash, 20 lks. wide, course SW.

40.00 Set an iron post, 3 ft. long, 1 in. dia., 8 ins. in ground, supported in mound of stone, for 1/4 sec. cor. marked on brass cap

1/4
S 1:S 6

1917

; raise a mound of stone, 2 ft. base, 1 1/2 ft. high W. of cor.

50.00 Leave rolling land and enter mountainous land. Asc. 80 ft. over broken SW. slope to

63.90 Draw, course SW. Asc. 230 ft. over rocky SE. slope to

68.27 Intersect Gila and Salt River Base Line, 110 lks. E. of the reestablished Std. cor. of T. 1 N., Rs. 10 and 11 E., hereinbefore described.

At point of intersection, set an iron post, 3 ft. long,

Chains

3 ins. dia., in a mound of stone, for closing cor. of T. 1 S., Rs. 10 and 11 E., marked on brass cap

S 1: S 6
R 10 E: R 11 E
T 1 S
C C


1917

; raise a mound of stone,
2 ft. base, 1½ ft. high S. of cor.
Land; rolling and broken, and mountainous.
Soil; 3d and 4th rate; gravelly and rocky.
Undergrowth; palo verde, mesquite, buck brush and catclaw.
No timber.

Survey of Subdivision of T. 1 S., R. 10 E.

Chains From the cor. of secs. 25, 30, 31 and 36 on E. bdy. of Tp. hereinbefore described, West on Sectional Correction Line bet. secs. 25 and 36. Over broken and rolling land, through scattering undergrowth.

- 5.00 Asc. NE. slope 170 ft. to
- 19.50 Spur, slopes N. Desc. 110 ft. to
- 25.00 Draw, course N. Asc. 130 ft. over NE. slope.
- 29.30 Ridge, bears N. and S.
- 37.70 Enter draw.
- 38.80 Leave draw, course SW.
- 40.00 Set an iron post, 3 ft. long, 1 in. dia., 8 ins. in the ground, supported in mound of stone, for $\frac{1}{4}$ sec. cor. marked on brass cap




1917

; raise a mound of stone,

2 ft. base, $1\frac{1}{2}$ ft. high N. of cor.

- 42.00 Draw, course NW.
- 49.20 Draw, course SW. Asc. 135 ft. over SE. slope.
- 61.20 Ridge, bears NE. and SW. Desc. W. slope.
- 68.90 Foot of descent.
- 79.00 Draw, course SW.
- 80.00 Set an iron post, 3 ft. long, 2 ins. dia., 12 ins. in ground, supported in mound of stone, for cor. of secs. 25, 26, 35 and 36, marked on brass cap



1917


; raise a mound of stone,

2 ft. base, $1\frac{1}{2}$ ft. high W. of cor.

Land; rolling and broken.
Soil; 3d rate, and gravelly.
Undergrowth; palo verde, catclaw, mesquite and buck brush.
No timber.

West, on sectional correction line, bet. secs. 26 and 35. Over rolling land, through scattering undergrowth.

- 9.00 Road bears SE. and NW.
- 22.50 Spur, slopes SW.
- 28.40 Draw, 20 lks. wide, course SW.
- 35.70 Spur, slopes S.
- 37.20 Draw, course S.
- 40.00 Set an iron post, 3 ft. long, 1 in. dia., 8 ins. in ground, supported in mound of stone, for $\frac{1}{4}$ sec. cor., marked on brass cap




1917

; raise a mound of stone

2 ft. base, $1\frac{1}{2}$ ft. high N. of cor.

- 42.50 Ridge, bears NE. and SW.
- 58.80 Wash, 20 lks. wide, course S.
- 68.40 Low spur, slopes SW.
- 80.00 Set an iron post, 3 ft. long, 2 in. dia., 6 ins. in the ground, supported in mound of stone, for cor. of secs. 26, 27, 34 and 35, marked on brass cap



1917

Chains	<p>; raise a mound of stone, 2 ft. base, $1\frac{1}{2}$ ft. high W. of cor. Land; rolling. Soil; 2nd and 3d rate, sandy and gravelly. Undergrowth; palo verde, catclaw and mesquite. No timber.</p>
13.00	West, on sectional correction line, bet. secs. 27 and 34. Over rolling land, through scattering undergrowth. Desc. Draw, course SW.
23.80	Small spur, slopes SW.
31.30	Wash, 1 ch. wide, course SW.
36.00	Draw, 10 chs. wide, course S.
40.00	Set an iron post, 3 ft. long, 1 in. dia., in mound of stone, for $\frac{1}{4}$ sec. cor., marked on brass cap
	<p>S 27 $\frac{1}{4}$ ---- S 34</p> <p>1917</p>
43.00	; raise a mound of stone, 2 ft. base, $1\frac{1}{2}$ ft. high N. of cor. Spur, slopes S. Desc. SW. slope 130 ft.
47.90	Small draw, course SE.
69.00	Ridge, bears SE. and NW. Thence along broken top.
72.40	Leave top, thence along broken S. slope.
80.00	Set an iron post, 3 ft. long, 2 ins. dia., in mound of stone, for cor. of secs. 27, 28, 33 and 34, marked on brass cap
	<p>T 1 S R 10 E S 28:S 27 S 33:S 34</p> <p>1917</p>
	; raise a mound of stone, 2 ft. base, $1\frac{1}{2}$ ft. high W. of cor. Land; rolling and mountainous. Soil; rocky, 4th rate. Undergrowth; palo verde, catclaw and mesquite. No timber.
	West, on sectional correction line, bet. secs. 28 and 33. Over mountainous land, through scattering undergrowth, along S. slope.
2.20	Desc. abrupt SW. slope 335 ft.
14.20	Foot of descent, thence over rolling land.
40.00	Set an iron post, 3 ft. long, 1 in. dia., 14 ins. in the ground, supported in mound of stone, for $\frac{1}{4}$ sec. cor., marked on brass cap
	<p>S 28 $\frac{1}{4}$ ---- S 33</p> <p>1917</p>
57.00	; raise a mound of stone, 2 ft. base, $1\frac{1}{2}$ ft. high N. of cor. Wash, course SW.
80.00	Set an iron post, 3 ft. long, 2 ins. dia., 24 ins. in ground, for cor. of secs. 28, 29, 32 and 33, marked on brass cap,
	<p>T 1 S R 10 E S 29:S 28 S 32:S 33</p> <p>1917</p>
	; raise a mound of stone,

Survey of Subdivision of T. 1 S., R. 10 E.

Chains 2 ft. base, 1½ ft. high W. of cor.
 Land; mountainous and rolling, drains S.
 Soil; E. half rocky, 4th rate; W. half sandy, 2nd rate.
 Undergrowth; palo verde, mesquite, ironwood, catclaw,
 and greasewood.
 No timber.

West, on sectional correction line, bet. secs. 29 and 32.
 Over rolling land, through scattering undergrowth.
 7.50 Road, bears SE. and NW.
 25.20 Wash, 15 lks. wide, course SE. Asc. rocky E. slope
 125 ft.
 39.00 Ridge, bears SE. and NW. Desc. gentle W. slope.
 40.00 Set an iron post, 3 ft. long, 1 in. dia., 12 ins. in the
 ground, supported in mound of stone, for ¼ sec. cor.,
 marked on brass cap

S 29
 ¼ ----
 S 32

1917

; raise a mound of stone,
 2 ft. base, 1½ ft. high N. of cor.
 47.50 Foot of descent.
 75.10 Point of ridge, bears N. and S.
 80.00 Set an iron post, 3 ft. long, 2 ins. dia., 10 ins. in
 ground, supported in mound of stone, for cor. of secs.
 29, 30, 31 and 32, marked on brass cap

T 1 S R 10 E
 S 30:S 29
 S 31:S 32

1917

; raise a mound of stone,
 2 ft. base, 1½ ft. high W. of cor.
 Land; rolling.
 Soil; 2nd to 3d rate, sandy and gravelly.
 Undergrowth; catclaw, palo verde, buck brush, ironwood
 and mesquite.
 No timber.

West, on sectional correction line, bet. secs. 30 and 31.
 Over broken and rolling land, through scattering undergrowth.
 17.50 Wash, 20 lks. wide, course S.
 19.80 Road, bears NE. and SW.
 21.20 Wash, 20 lks. wide, course SE.
 40.00 Set an iron post, 3 ft. long, 1 in. dia., 12 ins. in the
 ground, supported in mound of stone, for ¼ sec. cor.,
 marked on brass cap

S 30
 ¼ ----
 S 31

1917

; raise a mound of stone,
 2 ft. base, 1½ ft. high N. of cor.
 82.19 Intersect E. bdy. of T. 1 S., R. 9 E., at a point 4.35
 chs. N. of orig. cor. of secs. 25, 30, 31 and 36. At
 point of intersection reestablish cor. of secs. 30
 and 31 as hereinbefore described in notes of dependent
 resurvey of W. bdy. of T. 1 S., R. 10 E.
 Land; gently rolling.
 Soil; 2nd rate, sandy.
 Undergrowth; palo verde, mesquite, ironwood and grease-
 wood.
 No timber.

Chains From the cor. of secs. 25, 26, 35 and 36.
 S. 0° 01' E. on random line bet. secs. 35 and 36.
 40.00 Set temp. $\frac{1}{4}$ sec. cor.
 80.64 Fall 14 lks. E. of the reestablished cor. of secs. 35 and 36 on S. bdy. of Tp. hereinbefore described.
 Thence N. 0° 05' E. on true line bet. secs. 35 and 36.
 Over rolling land through scattering undergrowth.
 Desc. gentle N. slope.
 24.40 Draw, course NW.
 26.20 Fence, bears SE. and NW.
 28.70 Same fence, bears NE. and SW.
 29.20 Enter bottom land.
 30.50 Channel of Queen Creek, dry, course SW.
 38.80 Leave creek bottom and ascend.
 39.80 Irrigation ditch, course W.
 40.64 Set an iron post, 3 ft. long, 1 in. dia., 14 ins. in the ground, supported in mound of stone, for $\frac{1}{4}$ sec. cor. marked on brass cap
 $\frac{1}{4}$
 S 35:S 36
 1917
 ; raise a mound of stone,
 2 ft. base, $1\frac{1}{2}$ ft. high W. of cor.
 42.50 Wash, course SE.
 43.20 Road, bears SE. and NW.
 47.50 Wash, course SW. Road, bears SE. and NW. Asc. SW. slope.
 58.00 Wash, course SW.
 60.00 Wash, course SE.
 80.64 The cor. of secs. 25, 26, 35 and 36.
 Land; rolling.
 Soil; 2nd and 3d rate, sandy and gravelly.
 Undergrowth; palo verde, catclaw, mesquite and ocatilla.
 No timber.

N. 0° 01' W. bet. secs. 25 and 26. Over broken and rolling land, through scattering undergrowth.
 Asc. broken S. slope.
 19.10 Ridge, bears E. and W. Desc. NW. slope 90 ft. to
 23.50 Foot of descent.
 26.50 Wash, 25 lks. wide, course SW.
 28.00 Road, bears NE. and SW.
 30.50 Leave bottom and asc. 25 ft.
 37.60 Spur, slopes SW.
 40.00 Set an iron post, 3 ft. long, 1 in. dia., 4 ins. in the ground, supported in mound of stone, for $\frac{1}{2}$ sec. cor., marked on brass cap
 $\frac{1}{2}$
 S 26:S 25
 1917
 ; raise a mound of stone,
 2 ft. base, $1\frac{1}{2}$ ft. high W. of cor.
 42.50 Ridge, bears SE. and NW. Desc. NE. slope 70 ft. to
 47.60 Wash, 20 lks. wide, course W. Asc. SE. slope 120 ft.
 66.00 Ridge, bears NE. and SW., descend.
 70.00 Small draw, course W. Asc. 110 ft.
 76.30 Ridge, bears N. and SE.
 79.80 Desc. NW. slope.
 80.00 Set an iron post, 3 ft. long, 2 ins. dia., 14 ins. in ground, supported in mound of stone, for cor. of secs. 23, 24, 25 and 26, marked on brass cap

T 1 S R 10 E
 S 23:S 24
 S 26:S 25


1917

; raise a mound of stone

Survey of Subdivision of T. 1 S., R. 10 E.

Chains 2 ft. base, 1½ ft. high W. of cor.
 Land; broken and rolling.
 Soil; 3d and 4th rate, gravelly and rocky.
 Undergrowth; palo verde, greasewood, mesquite and catclaw.
 No timber.


East on random line, bet. secs. 24 and 25.
 40.00 Set temp. ¼ sec. cor.
 79.94 Fall 8 lks. S. of cor. of secs. 19, 24, 25 and 30 on E.
 bdy. of Tp., hereinbefore described.
 Thence S. 89° 57' W. on true line bet. secs. 24 and 25.
 Over broken land, through scattering undergrowth.
 1.74 Small draw, course SE.
 6.54 Ridge, bears NE. and SW.
 15.94 Draw, course SW.
 23.44 Spur, slopes S.
 31.14 Draw, course S.
 37.44 Ridge, bears NE. and SW.
 39.97 Set an iron post, 3 ft. long, 1 in. dia., 13 ins. in the
 ground, supported in mound of stone, for ¼ sec. cor.
 marked on brass cap



1917

; raise a mound of stone,
 2 ft. base, 1½ ft. high N. of cor.
 45.74 Draw, course SW.
 49.74 Spur, slopes SW.
 55.00 Draw, course SW.
 59.14 Spur, slopes SW.
 61.44 Wash, course S.
 64.00 Spur, slopes S.
 64.74 Road, bears NE. and SW.
 72.84 Small draw, course SE. Asc. 90 ft. to
 78.24 Top of ascent.
 79.94 The cor. of secs. 23, 24, 25 and 26.
 Land; broken.
 Soil; 3d rate, gravelly.
 Undergrowth; palo verde, catclaw, and mesquite.
 No timber.

N. 0° 01' W. bet. secs. 23 and 24. Over broken and
 mountainous land, through scattering undergrowth.
 Desc. NW. slope.
 8.50 Draw, course SW.
 16.10 Spur, slopes W.
 23.00 Draw, course SW. Asc. broken SW. slope 220 ft. to
 40.00 Set an iron post, 3 ft. long, 1 in. dia., 10 ins. in the
 ground, supported in mound of stone, for ¼ sec. cor.
 marked on brass cap



1917

; raise a mound of stone,
 2 ft. base, 1½ ft. high W. of cor.
 41.50 Ridge, bears NE. and SW., thence along broken W. slope.
 45.00 Desc. rocky NW. slope 325 ft. to creek at 62.80 ch. station
 49.10 Rocky spur, slopes NW. Desc. over cliff 150 ft.
 52.10 Foot of cliff.
 62.80 Spring branch, 4 lks. wide, 3 ins. deep, course SW.
 Asc. 200 ft. to
 80.00 Set an iron post, 3 ft. long, 2 ins. dia., 8 ins. in the
 ground, supported in mound of stone, for cor. of secs.
 13, 14, 23, and 24, marked on brass cap

Chains

T 1 S R 10 E
 S 14:S 13
 S 23:S 24

1917

; raise a mound of stone, 2 ft. base, 1½ ft. high W. of cor.
 Land; broken and mountainous.
 Soil; 3d and 4th rate, gravelly and rocky.
 Undergrowth; palo verde, catclaw and mesquite.
 No timber.

- N. 89° 57' E. on a random line bet. secs. 13 and 24.
- 40.00 Set temp. ¼ sec. cor.
- 79.96 Fall 9 lks. S. of the cor. of secs. 13, 18, 19 and 24 on E. bdy. of Tp., hereinbefore described.
- Thence S. 89° 53' W. on true line bet. secs. 13 and 24.
- Over broken and rolling land. Asc. 20 ft. to
- 1.00 Ridge, bears NE. and SW.
- 10.46 Draw, course SW.
- 22.16 Spur, slopes SW. Desc. 160 ft. to
- 33.16 Foot of descent.
- 38.16 Small spur, slopes N.
- 39.56 Road, bears NE. and SW.
- 39.98 Set an iron post, 3 ft. long, 1 in. dia., 26 ins. in the ground, for ¼ sec. cor., marked on brass cap

S 13

¼ ----
 S 24

1917

- ; raise a mound of stone, 2 ft. base, 1½ ft. high N. of cor.
- 41.66 Wash, 15 lks. wide,
- 51.26 Low divide, bears N. and S.
- 61.26 Small draw, course SW.
- 72.96 Small draw, course S.
- 79.96 The cor. of secs. 13, 14, 23 and 24.
- Land; broken and rolling.
- Soil; 3d and 4th rate, gravelly and rocky.
- Undergrowth; palo verde, mesquite and catclaw.
- No timber.

- N. 0° 01' W., bet. secs. 13 and 14. Over mountainous land, through scattering undergrowth.
- Asc. SE. slope 90 ft. to
- 4.40 Ridge, bears NE. and SW. Desc. NW. slope 240. ft.
- 14.00 Draw, course SW. Asc. SW. slope 200 ft.
- 22.20 Spur, slopes W.
- 40.00 Set an iron post, 3 ft. long, 1 in. dia., 8 ins. in the ground, supported in mound of stone, for ¼ sec. cor. marked on brass cap

¼
 S 14:S 13

1917

- ; raise a mound of stone, 2 ft. base, 1½ ft. high W. of cor.
- 43.50 Wash, 30 lks. wide, course SW.
- 52.40 Spur, slopes E.
- 55.90 Draw, course SE.
- 80.00 Set an iron post, 3 ft. long, 2 ins. dia., on ledge of rock, supported in a mound of stone, for cor. of secs. 11, 12, 13 and 14, marked on brass cap

Chains

T 1 S R 10 E
S 11:S 12
S 14:S 13

1917

; raise a mound of stone,
2 ft. base, 1½ ft. high W. of cor.

Land; mountainous.
Soil; 3d and 4th rate, gravelly and rocky.
Undergrowth; palo verde, mesquite, catclaw and buck brush.
No timber.

40.00 N. 89° 53' E. on random line bet. secs. 12 and 13.
Set temp. ¼ sec. cor.
79.97 Fall 9 lks. N. of the cor. of secs. 7, 12, 13 and 18 on
E. bdy. of Tp., hereinbefore described.
Thence S. 89° 57' W. on true line bet. secs. 12 and 13.
Over rocky broken and mountainous land.
8.00 Road, bears N. and SW.
19.87 Gulch, course SW.
38.64 Ridge, bears NE. and SW.
39.98½ Set an iron post, 3 ft. long, 1 in. dia., 8 ins. in the
ground, supported in mound of stone, for ¼ sec. cor.
marked on brass cap

¼ S 12

S 13

1917

; raise a mound of stone,
2 ft. base, 1½ ft. high N. of cor.

48.80 Draw, course SW.
55.50 Spur, slopes S.
63.40 Draw, course SE.
79.97 The cor. of secs. 11, 12, 13 and 14.

Land; mountainous and broken.
Soil; 4th rate, and rocky.
Undergrowth; palo verde, mesquite, catclaw, and buck brush.
No timber.

N. 0° 01' W., bet. secs. 11 and 12. Over mountainous
land, through scattering undergrowth. Asc. SE. slope.
2.80 Spur, slopes E.
11.20 Desc. broken NE. slope.
16.60 Low saddle in ridge, bears NE. and SW.
20.50 Ridge, bears N. and SE. Thence along top.
23.20 Desc. from ridge 375 ft.
40.00 Set an iron post, 3 ft. long, 1 in. dia., in a mound of
stone, for ¼ sec. cor., marked on brass cap

¼
S 11:S 12

1917

; raise a mound of stone, 2
ft. base, 1½ ft. high W. of cor.

41.70 Draw, course SW.
47.70 Spur, slopes W. Desc. NW. slope 260 ft.
59.00 Wash, 15 lks. wide, course SW. Asc. SW. slope.
73.20 Top of ascent, thence along W. slope.
80.00 Set an iron post, 3 ft. long, 2 ins. dia., in a mound of
stone, for cor. of secs. 1, 2, 11 and 12, marked on
brass cap

T 1 S R 10 E
S 2:S 1
S 11:S 12
1917

Chains

; raise a mound of stone, 2 ft. base, 1 1/2 ft. high W. of cor.

Land; mountainous.
Soil; 4th rate, and rocky.
Undergrowth; palo verde, buck brush and mesquite.
No timber.

- N. 89° 57' E., on random line bet. secs. 1 and 12.
- 40.00 Set temp. 1/4 sec. cor.
- 79.92 Intersect E. bdy. of Tp. 12 lks. N. of the cor. of secs. 1, 6, 7 and 12, hereinbefore described.
- Thence N. 89° 58' W., on true line bet. secs. 1 and 12. Over mountainous land, through scattering undergrowth.
- 9.00 Draw, course NW. Ascend.
- 39.96 Set an iron post, 3 ft. long, 1 in. dia., 26 ins. in the ground, for 1/4 sec. cor., marked on brass cap

S 1
1/4 ---
S 12

1917

- ; raise a mound of stone, 2 ft. base, 1 1/2 ft. high N. of cor.
- 42.42 Ridge, bears NE. and SW.
- 47.60 Spur, slopes S.
- 61.70 Small draw, course S.
- 67.60 Spur, slopes SW. Desc. NW. slope 260 ft. to
- 79.92 The cor. of secs. 1, 2, 11 and 12.

Land; rough and mountainous.
Soil; rocky, 4th rate.
Undergrowth; palo verde, mesquite and catclaw.
No timber.

- N. 0° 01' W. bet. secs. 1 and 2. Over mountainous land. Desc. broken NW. slope 140 ft. to
- 6.00 Draw, course W. Asc. broken SW. slope.
- 14.50 Spur, slopes SW.
- 20.00 Enter wash of Whitlow Canyon Creek, thence along bottom through dense brush.
- 25.00 Creek, 1 ch. wide, course SW.
- 40.00 Set an iron post, 3 ft. long, 1 in. dia., 26 ins. in the ground, for 1/4 sec. cor., marked on brass cap.

1/4
S 2:S 1

1917

- ; raise a mound of stone, 2 ft. base, 1 1/2 ft. high W. of cor.
- 54.40 Same creek, course SE. Asc. steep and rocky SW. slope.
- 60.70 Spur, slopes W.
- 66.10 Draw, course SW.
- 68.16 Intersect Gila and Salt River Base Line 125 lks. E. of the reestablished S. C. of secs. 35 and 36, hereinbefore described.
- At point of intersection, set an iron post, 3 ft. long, 2 ins. dia., in a mound of stone, for closing cor. of secs. 1 and 2, marked on brass cap.

S 2:S 1
T 1 S:R 10 E
C C

1917

; raise a mound of stone,

Survey of Subdivision of T. 1 S., R. 10 E.

Chains 2 ft. base, 1½ ft. high S. of cor.
 Land; broken and mountainous.
 Soil; 4th rate, and rocky.
 Undergrowth; mesquite, palo verde and catclaw.
 No timber.

From the cor. of secs. 26, 27, 34 and 35.
 S. 0° 05' W. on random line bet. secs. 34 and 35.
 40.00 Set temp. ¼ sec. cor.
 81.58 Intersect S. bdy. of Tp., at the reestablished cor. of
 secs. 34 and 35, hereinbefore described.
 Thence N. 0° 05' E. on true line bet. secs. 34 and 35.
 Over rolling and broken land.
 7.28 Fence, bears E. and W.
 7.58 Enter wash. Thence across same.
 13.58 Main channel of Queen Creek, course W.
 16.88 Leave Queen Creek Wash.
 27.88 Road, Phoenix to Superior, bears NE. and SW.
 30.38 Wash, 20 lks. wide, course SW. Asc.
 41.58 Set an iron post, 3 ft. long, 1 in. dia., 12 ins. in the
 ground, supported in mound of stone, for ¼ sec. cor.
 marked on brass cap

¼
 S 34:S 35

1917

; raise a mound of stone,
 2 ft. base, 1½ ft. high W. of cor.
 50.18 Ridge, bears NE. and SW.
 58.30 Same ridge, bears SE. and NW.
 71.58 Draw, course SE. Asc. SE. slope.
 78.18 Spur, slopes SE. Desc.
 81.58 The cor. of secs. 26, 27, 34 and 35.

Land; broken, and rolling.
 Soil; 2nd rate, gravelly.
 Undergrowth; palo verde, mesquite, greasewood and catclaw.
 No timber.

N. 0° 01' W. bet. secs. 26 and 27, over mountainous land.
 Desc. gentle N. slope.
 7.50 Draw, course SW. Asc. gentle SE. slope.
 22.70 Spur, slopes NE. Continue ascent.
 29.90 Ridge, bears NE. and SW. Desc. abruptly 185 ft.
 39.50 Foot of descent.
 40.00 Set an iron post, 3 ft. long, 1 in. dia., 20 ins. in the
 ground, supported in mound of stone, for ¼ sec. cor.,
 marked on brass cap

¼
 S 27:S 26

1917

; raise a mound of stone, 2
 ft. base, 1½ ft. high W. of cor.
 40.50 Draw, 15 lks. wide, course SW. Asc. over rocky land 270
 ft.
 58.40 Ridge, bears NE. and SW. Desc. NW. slope 260 ft. to
 72.70 Draw, course W. Asc.
 80.00 Set an iron post, 3 ft. long, 2 ins. dia., 24 ins. in the
 ground, for cor. of secs. 22, 23, 26 and 27, marked on
 brass cap

T 1 S R 10 E
 S 22:S 23
 S 27:S 26

1917

; raise a mound of stone,
 2 ft. base, 1½ ft. high W. of cor.

Chains

Land; rough and mountainous.
Soil; 3d and 4th rate, gravelly and rocky.
Undergrowth; palo verde, mesquite and buck brush.
No timber.

East on random line bet. secs. 23 and 26.

40.00 Set temp. $\frac{1}{4}$ sec. cor.

80.04 Fall 4 lks. N. of the cor. of secs. 23, 24, 25 and 26.
Thence N. $89^{\circ} 58'$ W. on a true line bet. secs. 23 and 26. Over mountainous land. Asc.

.60 Ridge, bears NE. and SW. Desc.

11.70 Draw, course SW.

16.00 Spur, slopes SW.

18.60 Draw, course SE. Asc. gentle E. slope.

40.02 Set an iron post, 3 ft. long, 1 in. dia., 12 ins. in the ground, supported in a mound of stone, for $\frac{1}{4}$ sec. cor. marked on brass cap

S 23

$\frac{1}{4}$

S 26

1917

; raise a mound of stone,

2 ft. base, $1\frac{1}{2}$ ft. high N. of cor.

56.80 Ridge, bears NE. and SW. Desc. broken SW. slope 300 ft.

77.00 Enter bottom land.

80.04 The cor. of secs. 22, 23, 26 and 27.

Land; mountainous.
Soil; 3d rate, gravelly.
Undergrowth; palo verde, catclaw and mesquite.
No timber.

N. $0^{\circ} 01'$ W. bet. secs. 22 and 23. Over rolling and mountainous land, through scattering undergrowth.

3.60 Whitlow Canyon Creek, 1 ch. wide, course SW. Asc. SE. slope.

25.30 Top of ascent, thence over E. slope.

31.60 Desc. rocky NE. slope 80 ft.

40.00 Set an iron post, 3 ft. long, 1 in. dia., 26 ins. in the ground, for $\frac{1}{4}$ sec. cor., marked on brass cap

$\frac{1}{4}$

S 22:S 23

1917

; raise a mound of stone,

2 ft. base, $1\frac{1}{2}$ ft. high W. of cor.

43.10 Draw, 15 lks. wide, course SE. Asc. SW. slope 75 ft.

56.70 Top of ascent.

67.50 Draw, course SW. Asc. S. slope.

71.50 Slope changes to a SE.

80.00 Set an iron post, 3 ft. long, 2 ins. dia., 12 ins. in the ground, supported in a mound of stone, for cor. of secs. 14, 15, 22 and 23, marked on brass cap

T 1 S R 10 E

S 15:S 14

S 22:S 23

1917

; raise a mound of stone,

2 ft. base, $1\frac{1}{2}$ ft. high W. of cor.

Land; rolling and mountainous.
Soil; 3d and 4th rate, gravelly and rocky.
Undergrowth; palo verde, mesquite and catclaw.
No timber.

Survey of Subdivision of T. 1 S., R. 10 E.

Chains S. 89° 58' E. on random line bet. secs. 14 and 23.
 40.00 Set temp. $\frac{1}{4}$ sec. cor.
 80.05 Fall 7 lks. N. of the cor. of secs. 13, 14, 23 and 24.
 Thence N. 89° 55' W. on true line bet. secs. 14 and
 23. Over mountainous land, through scattering undergrowth.
 .55 Ridge, bears SE. and NW. Desc. NW. slope 320 ft. to
 15.45 Enter bottom.
 17.85 Draw, 20 lks. wide, course SW.
 18.35 Leave bottom.
 31.45 Spur, slopes S.
 40.02 $\frac{1}{4}$ Set an iron post, 3 ft. long, 1 in. dia., 24 ins. in the
 ground, for $\frac{1}{4}$ sec. cor., marked on brass cap

S 14
 $\frac{1}{4}$ ----
 S 23

1917

; raise a mound of stone,
 2 ft. base, $1\frac{1}{2}$ ft. high N. of cor.
 Cor. stands at high water mark on E. side Whitlow Creek.
 43.50 Main channel of Whitlow Creek, course S.
 44.50 Leave Whitlow Canyon and asc. SE. slope 350 ft.
 57.25 Ridge, bears NE. and SW.
 64.50 Spur, slopes NW. Desc. rocky SW. slope 290 ft. to
 77.00 Draw, course SE.
 80.05 The cor. of secs. 14, 15, 22 and 23.

Land, rough and mountainous.
 Soil; 4th rate, rocky.
 Undergrowth; palo verde, mesquite, ironwood and buck
 brush.
 No timber.

N. 0° 01' W. bet. secs. 14 and 15.
 Over mountainous land, through scattering undergrowth. Asc.
 24.90 Small spur, slopes W. Desc. NW. slope.
 40.00 Set an iron post, 3 ft. long, 1 in. dia., 14 ins. in the
 ground, supported in a mound of stone, for $\frac{1}{4}$ sec. cor.
 marked on brass cap

$\frac{1}{4}$
 S 15:S 14

1917

; raise a mound of stone, 2 ft.
 base, $1\frac{1}{2}$ ft. high W. of cor.
 Cor. stands in draw, course SW.
 49.30 Spur, slopes SW. Desc. abrupt NW. slope.
 60.50 Draw, course W. Thence over rocky broken W. slope.
 80.00 Set an iron post, 3 ft. long, 2 ins. dia., in a mound of
 stone, for cor. of secs. 10, 11, 14 and 15, marked on
 brass cap

T 1 S R 10 E
 S 10:S 11
 S 15:S 14

1917

; raise a mound of stone,
 2 ft. base, $1\frac{1}{2}$ ft. high W. of cor.
 Land; mountainous.
 Soil, rocky, 4th rate.
 Undergrowth; palo verde, mesquite and buck brush.
 No timber.

S. 89° 55' E. on random line bet. secs. 11 and 14.
 40.00 Set temp. $\frac{1}{4}$ sec. cor.
 79.90 Fall 28 lks. N. of the cor. of secs. 11, 12, 13 and 14.

Chains Thence N. 89° 43' W. on true line bet. secs. 11 and 14.
 Over mountainous land, through scattering undergrowth.
 5.00 Ridge, bears N. and S. Desc. rocky W. slope.
 35.70 Canyon, course S., Asc. E. slope.
 39.95 Set an iron post, 3 ft. long, 1 in. dia., in a mound of
 stone, for $\frac{1}{4}$ sec. cor., marked on brass cap

S 11
 $\frac{1}{4}$ ---
 S 14
 1917

; raise a mound of stone,
 2 ft. base, $1\frac{1}{2}$ ft. high N. of cor.
 60.00 Ridge, bears N. and S. Desc. W. slope over cliffs.
 79.90 The cor. of secs. 10, 11, 14 and 15.

Land; mountainous.
 Soil; 4th rate, rocky.
 Undergrowth; palo verde, mesquite and buck brush.
 No timber.

N. 0° 01' W. bet. secs. 10 and 11. Over rough mountainous
 land, through scattering undergrowth.
 34.30 Ridge, bears SE. and NW.
 40.00 Set an iron post, 3 ft. long, 1 in. dia., 6 ins. in the
 ground, supported in a mound of stone, for $\frac{1}{4}$ sec. cor.,
 marked on brass cap

$\frac{1}{4}$
 S 10:S 11
 1917

; raise a mound of stone, 2 ft.
 base, $1\frac{1}{2}$ ft. high W. of cor.
 60.40 Ridge, bears NE. and SW. Desc. rocky NW. slope 290 ft.
 76.40 Draw, course SW.

80.00 Set an iron post, 3 ft. long, 2 ins. dia., 10 ins. in
 the ground, supported in mound of stone, for cor. of
 secs. 2, 3, 10 and 11, marked on brass cap

T 1 S R 10 E
 S 3:S 2
 S 10:S 11

1917
 ; raise a mound of stone,
 2 ft. base, $1\frac{1}{2}$ ft. high W. of cor.

Land; rough and mountainous.
 Soil; 4th rate, rocky.
 Undergrowth; palo verde, buck brush and mesquite.
 No timber.

S. 89° 43' E. on random line bet. secs. 2 and 11.
 40.00 Set temp. $\frac{1}{4}$ sec. cor.
 80.00 Fall 21 lks. S. of the cor. of secs. 1, 2, 11 and 12.
 Thence N. 89° 52' W. on a true line bet. secs. 2 and
 11. Over mountainous land. Desc. rocky and
 broken NW. slope 300 ft.
 10.00 Desc. abruptly over cliffs.
 17.00 Whitlow Canyon Creek, course SW. Asc. steep SE. slope
 500 ft. to
 37.50 Spur, slopes SE. and NW.
 39.07 Set an iron post, 3 ft. long, 1 in. dia., in a mound of
 stone, for W. C. to the $\frac{1}{4}$ sec. cor., marked on brass
 cap

S 2
 W C $\frac{1}{4}$ ---
 S 11
 1917

Chains ; raise a mound of stone, 2 ft. base, 1½ ft. high N. of cor.
 40.00 True point for cor. falls on face of cliff. Desc. over cliffs 240 ft.
 48.20 Draw, course S. Asc. SE. slope 600 ft.
 71.80 Ridge, bears SE. and NW.
 80.00 The cor. of secs. 2, 3, 10 and 11.

Land; mountainous.
 Soil; 4th rate, rocky.
 Undergrowth; palo verde and buck brush.
 No timber.

N. 0° 01' W. bet. secs. 2 and 3. Over mountainous land. Desc. rocky NW. slope to
 15.80 Draw, course W. Asc. S. slope 135 ft. to
 21.00 Spur, slopes W. Desc. NW. slope 270 ft.
 40.00 Set an iron post, 3 ft. long, 1 in. dia., 26 ins. in the ground, for ¼ sec. cor., marked on brass cap

¼
 S 3:S 2

1917

; raise a mound of stone, 2 ft. base, 1½ ft. high W. of cor.
 42.00 Draw, course W. Asc. rocky SE. slope;
 54.80 Spur, slopes SW.
 63.00 Canyon, course SW. Asc. SE. slope 75 ft. to
 67.98 Intersect Gila and Salt River Base Line 148 lks. E. of the reestablished S. C. of secs. 34 and 35, hereinbefore described.

At point of intersection, set an iron post, 3 ft. long, 2 ins. dia., 18 ins. in the ground, in rock mound, for C. C. of secs. 2 and 3, marked on brass cap

S 3:S 2
 T 1 S R 10 E
 C C
 1917

; raise a mound of stone, 2 ft. base, 1½ ft. high S. of cor.
 Land; mountainous.
 Soil; rocky, 4th rate.
 Undergrowth; palo verde, mesquite and catclaw.
 No timber.

From the cor. of secs. 27, 28, 33 and 34.
 S. 0° 05' W. on a random line bet. secs. 33 and 34.
 40.00 Set temp. ¼ sec. cor.
 82.15 Intersect S. bdy. of Tp. at the reestablished cor. of secs. 33 and 34, hereinbefore described. Thence N. 0° 05' E. on true line bet. secs. 33 and 34. Over mountainous land. Asc. SE. slope.
 5.00 Top of ascent. Thence level.
 5.30 Road, Phoenix to Superior, bears SE. and NW.
 15.90 Leave level land and asc. rocky SW. slope.
 39.10 Spur, slopes SW, thence over top of spur.
 41.80 Leave top and descend a NW. slope.
 42.15 Set an iron post, 3 ft. long, 1 in. dia., 8 ins. in the ground, supported in mound of stone, for ¼ sec. cor., marked on brass cap

¼
 S 33:S 34
 1917

; raise a mound of stone, 2 ft. base, 1½ ft. high W. of cor.

Chains

- 51.05 Draw, course SW. Asc. rocky S. slope.
- 54.55 Spur, slopes W. Desc. NW. slope.
- 63.55 Draw, course SW. Asc. rocky SW. slope.
- 74.75 Slope changes to a gentle S.
- 82.15 The cor. of secs. 27, 28, 33 and 34.

Land; mountainous.
Soil; rocky; 4th rate.
Undergrowth; palo verde and greasewood.
No timber.

N. 0° 02' W. bet. secs. 27 and 28. Over mountainous land.
Asc. gentle SW. slope over rocky land.

- 14.40 Ridge, bears NE. and SW. Desc. NE. slope 150 ft.
- 26.40 Draw, course SW. Asc. SW. slope.
- 40.00 Set an iron post, 3 ft. long, 1 in. dia., 4 ins. in the ground, supported in a mound of stone, for $\frac{1}{4}$ sec. cor. marked on brass cap

$\frac{1}{4}$
S 28:S 27

1917

; raise a mound of stone, 2 ft. base, $1\frac{1}{2}$ ft. high W. of cor.

- 41.00 Enter small flat.
- 51.00 Leave flat and asc. a SW. slope.
- 56.00 Ridge, bears N. and SW. Thence over rocky top.
- 61.80 Desc. rocky NW. slope 215 ft.
- 70.60 Draw, course SW. Asc. S. slope 230 ft.
- 76.80 Ridge, bears SE. and NW.
- 79.00 Small draw, course SE.
- 80.00 Set an iron post, 3 ft. long, 2 ins. dia., 6 ins. in the ground, supported in a mound of stone, for cor. of secs. 21, 22, 27 and 28, marked on brass cap

T 1 S R 10 E
S 21:S 22
S 28:S 27
1917

; raise a mound of stone, 2 ft. base, $1\frac{1}{2}$ ft. high W. of cor.

Land; mountainous.
Soil; very rocky, 4th rate.
Undergrowth; palo verde and buck brush.
No timber.

East on random line bet. secs. 22 and 27

- 40.00 Set temp. $\frac{1}{4}$ sec. cor.
- 79.89 Fall 16 lks. S. of the cor. of secs. 22, 23, 26 and 27. Thence S. 89° 53' W. on true line bet. secs. 22 and 27. Over mountainous land, scattering undergrowth.
- 3.60 Main channel of Whitlow Creek, 1 ch. wide, course SW.
- 15.20 Ridge, bears NE. and SW.
- 32.00 Draw, course SW.
- 39.94 $\frac{1}{2}$ Set an iron post, 3 ft. long, 1 in. dia., 12 ins. in the ground, supported in a mound of stone, for $\frac{1}{4}$ sec. cor., marked on brass cap

S 22

S 27
1917

; raise a mound of stone, 2 ft. base, $1\frac{1}{2}$ ft. high N. of cor.

- 43.70 Draw, course SW.

Chains
46.80
54.90
58.30
79.89

Spur, slopes SW.
Draw, 15 lks. wide, course S. Asc. over cliffs.
Top of cliffs, continue ascent.
The cor. of secs. 21, 22, 27 and 28.

Land; rough and mountainous.
Soil; rocky, 4th rate.
Undergrowth; palo verde, catclaw and buck brush.
No timber.

7.00
27.70
40.00

N. 0° 02' W., bet. secs. 21 and 22. Over mountainous land. Asc. SE. slope.
Ridge, bears NE. and SW. Thence over broken top.
Leave top and descend broken NW. slope.
Set an iron post, 3 ft. long, 1 in. dia., 26 ins. in the ground, for 1/4 sec. cor., marked on brass cap

1/4
S 21:S 22
1917

40.90
55.80
80.00

; raise a mound of stone 2 ft. base, 1 1/2 ft. high W. of cor.
Draw, course SW.
Spur, slopes SW. Thence along a broken and rocky W. slope.
Set an iron post, 3 ft. long, 2 ins. dia., in a mound of stone on ledge of rock, for cor. of secs. 15, 16, 21, and 22, marked on brass cap

T 1 S R 10 E
S 16:S 15
S 21:S 22

1917

; raise a mound of stone, 2 ft. base, 1 1/2 ft. high W. of cor.
Land; rough and mountainous.
Soil; rocky, 4th rate.
Undergrowth; palo verde, buck brush and mesquite.
No timber,

40.00
79.81

4.80
14.70
17.30
19.50
39.90 1/2

N. 89° 53' E. on random line bet. secs. 15 and 22.
Set temp. 1/4 sec. cor.
Fall 2 lks. N. of the cor. of secs. 14, 15, 22 and 23. Thence S. 89° 54' W. on true line bet. secs. 15 and 22. Over mountainous land. Asc. E. slope.
Spur, slopes S.
Draw, course SW.
Spur, slopes S.
Draw, course SE.
Set an iron post, 3 ft. long, 1 in. dia., in a mound of stone, on bed rock, for 1/4 sec. cor., marked on brass cap

S 15
1/4
S 22

1917

; raise a mound of stone, 2 ft. base, 1 1/2 ft. high N. of cor.

43.30
56.50
69.80
76.80
79.81

Spur, slopes N.
Ridge, bears SE. and NW.
Draw, course S.
Draw, course S.
The cor. of secs. 15, 16, 21 and 22.
Land; mountainous.

Chains	<p>Soil; rocky, 4th rate. Undergrowth; palo verde and buck brush. No timber.</p>
	<p>N. 0° 02' W. bet. secs. 15 and 16. Over mountainous land. Asc. gradually over broken SW. slope.</p> <p>19.00 Ridge, bears E. and W. Desc. rocky NE. slope.</p> <p>40.00 Set an iron post, 3 ft. long, 1 in. dia., 6 ins. in the ground, in rock mound, for $\frac{1}{4}$ sec. cor., marked on brass cap</p> <p style="text-align: center;">$\frac{1}{4}$ S 16:S 15</p> <p style="text-align: center;">1917</p> <p style="text-align: right;">; raise a mound of stone,</p> <p>2 ft. base, $1\frac{1}{2}$ ft. high W. of cor.</p> <p>48.50 Draw, course E.</p> <p>54.40 Spur, slopes SE. Desc. NE. slope.</p> <p>58.60 Draw, course SE. Asc. SW. slope.</p> <p>74.00 Spur, slopes SE.</p> <p>80.00 Set an iron post, 3 ft. long, 2 ins. dia., 24 ins. in the ground, for cor. of secs. 9, 10, 15 and 16, marked on brass cap,</p> <p style="text-align: center;">T 1 S R 10 E S 9:S 10 <u>S 16:S 15</u></p> <p style="text-align: center;">1917</p> <p style="text-align: right;">; raise a mound of stone,</p> <p>2 ft. base, $1\frac{1}{2}$ ft. high W. of cor.</p> <p>Land; mountainous. Soil, 4th rate, rocky. Undergrowth; palo verde, mesquite and catclaw. No timber.</p>
	<p>N. 89° 54' E. on random line bet. secs. 10 and 15.</p> <p>40.00 Set temp. $\frac{1}{4}$ sec. cor.</p> <p>79.90 Fall 37 lks. N. of the cor. of secs. 10, 11, 14 and 15. Thence N. 89° 50' W. on true line bet. secs. 10 and 15. Over mountainous land, scattering undergrowth.</p> <p>9.00 Asc. E. slope 120 ft.</p> <p>23.10 Spur, slopes S. Desc. rocky W. slope 240 ft.</p> <p>39.95 Set an iron post, 3 ft. long, 1 in. dia., in a mound of stone, for $\frac{1}{4}$ sec. cor., marked on brass cap</p> <p style="text-align: center;">S 10 $\frac{1}{4}$ ---- S 15</p> <p style="text-align: center;">1917</p> <p style="text-align: right;">; raise a mound of stone,</p> <p>2 ft. base, $1\frac{1}{2}$ ft. high N. of cor.</p> <p>43.80 Canyon, course S. Asc. E. slope.</p> <p>52.30 Spur, slopes SE. Desc. W. slope 190 ft.</p> <p>76.10 Draw, course S. Asc.</p> <p>79.90 The cor. of secs. 9, 10, 15 and 16.</p> <p>Land; mountainous. Soil; 4th rate, rocky. Undergrowth; palo verde, mesquite and catclaw. No timber.</p>
	<p>N. 0° 02' W., bet. secs. 9 and 10. Over mountainous land. Asc. SE. slope of spur 300 ft.</p>

Survey of Subdivision of T. 1 S., R. 10 E.

Chains

19.40 Ridge, bears SE. and NW. Desc. NE. slope 200 ft. to
40.00 Set an iron post, 3 ft. long, 1 in. dia., 6 ins. in the ground, in mound of stone, for 1/4 sec. cor., marked on brass cap

1/4
S 9:S 10

1917

; raise a mound of stone, 2 ft. base, 1 1/2 ft. high W. of cor. Continue to desc. NE. slope 160 ft. to

50.30 Foot of descent, thence along E. slope of Tully Canyon.

80.00 Set an iron post, 3 ft. long, 2 ins. dia., 24 ins. in the ground, for cor. of secs. 3, 4, 9 and 10, marked on brass cap

T 1 S R 10 E
S 4:S 3
S 9:S 10

1917

; raise a mound of stone, 2 ft. base, 1 1/2 ft. high W. of cor.

Land; mountainous.

Soil; 3d and 4th rate, gravelly and rocky.

Undergrowth; mesquite, catclaw and palo verde.

No timber.

S. 89° 50' E. on a random line bet. secs. 3 and 10.

40.00 Set temp. 1/4 sec. cor.

79.95 Fall 37 lks. S. of the cor. of secs. 2, 3, 10 and 11.

Thence S. 89° 54' W. on true line bet. secs. 3 and 10.

Over broken and mountainous land. Desc. W. slope over rocks and bluffs 390 ft. to

19.00 Canyon, course SW. Asc. SE. slope 310 ft. to

39.97 1/2 Set an iron post, 3 ft. long, 1 in. dia., 26 ins. in the ground, for 1/4 sec. cor., marked on brass cap

S 3
1/4 ----
S 10

1917

; raise a mound of stone, 2 ft. base, 1 1/2 ft. high N. of cor. Continue ascent 380 ft. to

54.45 Spur, slopes S. Desc. rocky W. slope 290 ft. to

77.75 Tully Canyon, course SE.

79.95 The cor. of secs. 3, 4, 9 and 10.

Land; broken and mountainous.

Soil; rocky 4th rate.

Undergrowth; palo verde, mesquite and catclaw.

No timber.

N. 0° 02' W. bet. secs. 3 and 4. Over broken and rolling land. Along E. slope of Tully Canyon.

6.70 Enter Tully Canyon, course S. Thence over bottom of same.

40.00 Set an iron post, 3 ft. long, 1 in. dia., 18 ins. in the ground, supported in a mound of stone, for 1/4 sec. cor. marked on brass cap

1/4
S 4:S 3

1917

; raise a mound of stone, 2 ft. base, 1 1/2 ft. high W. of cor.

Chains Cor. stands about 1 ch. W. of bed of canyon.
 44.50 Leave bed of canyon and asc. S. slope.
 67.50 Spur, slopes SW.
 67.95 Intersect the Gila and Salt River Base Line 162 lks. E.
 of the reestablished standard corner of secs. 33 and
 34, hereinbefore described.
 At point of intersection, set an iron post, 3 ft. long,
 2 ins. dia., 24 ins. in the ground, for closing corner
 of secs. 3 and 4, marked on brass cap

S 4:S 3
 T 1 S R 10 E
 C C
 1917

; raise a mound of stone,
 2 ft. base, $1\frac{1}{2}$ ft. high S. of cor.
 Land; rolling and broken.
 Soil; 3d rate, gravelly.
 Undergrowth; palo verde, mesquite and catclaw.
 No timber.

From the cor. of secs. 28, 29, 32 and 33.
 S. $0^{\circ} 05'$ W. on random line bet. secs. 32 and 33.
 40.00 Set temp. $\frac{1}{4}$ sec. cor.
 82.88 Intersect S. bdy. of Tp., at the reestablished cor. of
 secs. 32 and 33 hereinbefore described.
 Thence N. $0^{\circ} 05'$ E. on true line bet. secs. 32
 and 33. Over nearly level desert land.
 3.88 Road, bears NE. and SW.
 12.18 Road, Phoenix to Superior, bears E. and W.
 42.88 Set an iron post, 3 ft. long, 1 in. dia., 10 ins. in the
 ground, supported in mound of stone, for $\frac{1}{4}$ sec. cor.,
 marked on brass cap

$\frac{1}{4}$
 S 32:S 33

1917

; raise a mound of stone,
 2 ft. base, $1\frac{1}{2}$ ft. high W. of cor.
 65.88 Road, bears SE. and NW.
 74.08 Wash, 10 lks. wide, course NW.
 82.88 The cor. of secs. 28, 29, 32 and 33.

Land; nearly level.
 Soil; 2nd rate, sandy and gravelly.
 Undergrowth; palo verde, mesquite, greasewood and iron-
 wood.
 No timber.

N. $0^{\circ} 02'$ W. bet. secs. 28 and 29.
 Over rolling land, through scattering undergrowth.
 24.00 Draw, 15 lks. wide, course W.
 40.00 Set an iron post, 3 ft. long, 1 in. dia., 18 ins. in the
 ground, supported in mound of stone, for $\frac{1}{4}$ sec. cor.,
 marked on brass cap

$\frac{1}{4}$
 S 29:S 28

1917

; raise a mound of stone,
 2 ft. base, $1\frac{1}{2}$ ft. high W. of cor.
 48.00 Wash, course SW.
 73.50 Asc. gentle SW. slope 50 ft. to
 80.00 Set an iron post, 3 ft. long, 2 ins. dia., 10 ins. in the
 ground, supported in mound of stone, for cor. of secs.
 20, 21, 28 and 29, marked on brass cap

Chains

T 1 S R 10 E
 S 20:S 21
 S 29:S 28
 1917

; raise a mound of stone,
 2 ft. base, 1½ ft. high W. of cor.
 Land; rolling.
 Soil; S. 70 chs. sandy and gravelly, 2nd rate; N. 10 chs.
 rocky, 4th rate.
 Undergrowth; catclaw, greasewood, palo verde and ironwood.
 No timber.

East on random line bet. secs. 21 and 28.

40.00
 80.14
 2.65
 11.14
 17.20
 26.40
 35.10
 40.07

Set temp. ¼ sec. cor.
 Fall 14 lks. N. of cor. of secs. 21, 22, 27 and 28.
 Thence N. 89° 54' W. on true line bet. secs. 21 and 28
 Over rolling land, through scattering undergrowth.
 Ridge, bears SE. and NW.
 Ravine, course SW.
 Spur, slopes S.
 Spur, slopes SW. Desc. SW. slope.
 Foot of descent.
 Set an iron post, 3 ft. long, 1 in. dia., 26 ins. in the
 ground, for ¼ sec. cor., marked on brass cap

S 21
 ¼ ----
 S 28
 1917

; raise a mound of stone,
 2 ft. base, 1½ ft. high N. of cor.

41.20
 65.30
 67.84
 75.00
 80.14

Wash, 15 lks. wide, course SW.
 Wash, course SE.
 Asc. steep SE. slope 140 ft.
 Spur, slopes S. Desc.
 The cor. of secs. 20, 21, 28 and 29.

Land; rolling and broken.
 Soil; E. half, rocky, 4th rate; W. half, gravelly and
 rocky, 2nd to 4th rate.
 Undergrowth; palo verde, catclaw, ironwood and mesquite.
 No timber.

N. 0° 02' W. bet. secs. 20 and 21. Over mountainous land.
Over broken W. slope.

17.50
 27.30
 40.00

Desc. N. slope.
 Wash, course SW. Asc. SE. slope.
 Set an iron post, 3 ft. long, 1 in. dia., in a mound of
 stone, for ¼ sec. cor., marked on brass cap

¼
 S 20:S 21
 1917

; Raise a mound of stone,
 2 ft. base, 1½ ft. high W. of cor.

44.80
 53.00
 63.70
 80.00

Spur, slopes SE. Desc. rocky N. slope.
 Draw, course SE. Asc. rocky S. slope.
 Spur, slopes SE.
 Set an iron post, 3 ft. long, 2 ins. dia., 4 ins. in the
 ground, supported in mound of stone, for cor. of secs.
 16, 17, 20 and 21, marked on brass cap

T 1 S R 10 E
 S 17:S 16
 S 20:S 21
 1917

Chains ; raise a mound of stone, 2 ft. base, 1½ ft. high W. of cor.
 Land; mountainous.
 Soil; rocky, 4th rate.
 Undergrowth; palo verde, mesquite, catclaw and buck brush
 No timber.

S. 89° 54' E. on random line bet. secs. 16 and 21.
 40.00 Set temp. ¼ sec. cor.
 79.90 Fall 14 lks. S. of the cor. of secs. 15, 16, 21 and 22.
 Thence West on true line bet. secs. 16 and 21. Over mountainous land. Desc. W. slope.
 11.10 Draw, course S. Asc. SE. slope.
 32.60 Ridge, bears N. and S.
 39.95 Set an iron post, 3 ft. long, 1 in. dia., 26 ins. in the ground, for ¼ sec. cor., marked on brass cap

S 16
 ¼ ----
 S 21

1917

; raise a mound of stone, 2 ft. base, 1½ ft. high N. of cor.
 53.10 Draw, course S.
 60.40 Spur, slopes SW.
 71.30 Draw, course S. Asc. over rocky E. slope.
 79.90 The cor. of secs. 16, 17, 20 and 21.

Land; mountainous.
 Soil; 4th rate, rocky.
 Undergrowth; palo verde, mesquite and catclaw.
 No timber.

N. 0° 02' W. bet. secs. 16 and 17. Over rolling land. Desc: gradual E. slope over rocky land.
 21.90 Head of draw, course SE. Asc. SW. slope to
 27.00 Spur, slopes SW.
 36.50 Low divide. Thence over broken NW. slope.
 40.00 Set an iron post, 3 ft. long, 1 in. dia., 10 ins. in the ground, supported in mound of stone, for ¼ sec. cor., marked on brass cap

¼
 S 17:S 16

1917

; raise a mound of stone, 2 ft. base, 1½ ft. high W. of cor.
 55.30 Spur, slopes W. Desc.
 78.00 Draw, course W.
 80.00 Set an iron post, 3 ft. long, 2 ins. dia., 16 ins. in the ground, supported in mound of stone, for cor. of secs. 8, 9, 16 and 17, marked on brass cap

T 1 S R 10 E
 S 8:S 9
 S 17:S 16

1917

; raise a mound of stone, 2 ft. base, 1½ ft. high W. of cor.
 Land; heavy rolling.
 Soil; rocky, 4th rate.
 Undergrowth; ironwood, mesquite and palo verde.
 No timber.

Chains East on random line bet. secs. 9 and 16.
 40.00 Set a temp. $\frac{1}{4}$ sec. cor.
 79.92 Fall 21 lks. S. of the cor. of secs. 9, 10, 15 and 16.
 Thence S. $89^{\circ} 51'$ W. on true line bet. secs. 9 and 16
 Over mountainous land. Asc. E. slope to.
 1.20 Spur, slopes SE. Desc. SW. slope.
 24.70 Draw, course SE.
 31.00 Asc. E. slope over cliffs and rocks.
 37.90 Set an iron post, 3 ft. long, 1 in. dia., in a mound of
 stone on ledge of rock, for witness cor. to the $\frac{1}{4}$ sec.
 cor., marked on brass cap

S 9
 W C $\frac{1}{4}$ ----
 S 16

1917

; raise a mound of stone,
 2 ft. base, $1\frac{1}{2}$ ft. high N. of cor.
 39.96 True point for $\frac{1}{4}$ sec. cor. falls on cliff.
 56.20 Ridge, bears N. and S. Desc. broken rocky W. slope.
 75.60 Draw, course SW. Asc. SE. slope.
 79.92 The cor. of secs. 8, 9, 16 and 17.

Land; mountainous.
 Soil; rocky, 4th rate.
 Undergrowth; palo verde, mesquite, catclaw and ironwood.
 No timber.

N. $0^{\circ} 02'$ W. bet. secs. 8 and 9. Over mountainous land.
 Over broken W. slope of ridge.

1.90 Small spur, slopes W.
 40.00 Set an iron post, 3 ft. long, 1 in. dia., in a mound of
 stone, for $\frac{1}{4}$ sec. cor., marked on brass cap

$\frac{1}{4}$
 S 8:S 9
 1917

; raise a mound of stone,
 2 ft. base, $1\frac{1}{2}$ ft. high W. of cor.
 43.60 Head of draw, course W.
 60.00 Draw, course W. Asc. S. slope 130 ft. to
 73.40 Spur, slopes W.
 80.00 Set an iron post, 3 ft. long, 2 ins. dia., 24 ins. in
 the ground, for cor. of secs. 4, 5, 8 and 9, marked on
 brass cap

T 1 S R 10 E
 S 5:S 4
 S 8:S 9

1917

; raise a mound of stone,
 2 ft. base, $1\frac{1}{2}$ ft. high W. of cor.
 Land; mountainous.
 Soil; 3d and 4th rate, gravelly and rocky.
 Undergrowth; ironwood, palo verde and mesquite.
 No timber.

N. $89^{\circ} 51'$ E. on random line bet. secs. 4 and 9.

40.00 Set temp. $\frac{1}{4}$ sec. cor.
 80.06 Fall 7 lks. N. of the cor. of secs. 3, 4, 9 and 10.
 Thence S. $89^{\circ} 54'$ W. on true line bet. secs. 4 and 9.
 Over mountainous land. Asc. E. slope 410 ft. to
 24.10 Spur, slopes S. Desc. W. slope 150 ft.
 27.20 Draw, course SE. Asc. E. slope 350 ft.
 40.03 Set an iron post, 3 ft. long, 1 in. dia., in a mound of
 stone, for $\frac{1}{4}$ sec. cor., marked on brass cap

Chains

S 4

 $\frac{1}{4}$

S 9

1917

- ; raise a mound of stone,
2 ft. base, $1\frac{1}{2}$ ft. high N. of cor.
40.50 Ridge, bears N. and S. Desc. broken W. slope 920 ft. to
63.20 Head of draw, course SW.
80.06 The cor. of secs. 4, 5, 8 and 9.

Land; mountainous.

Soil; 4th rate, rocky.

Undergrowth; palo verde, mesquite and catclaw.

No timber.

N. $0^{\circ} 02' W.$ bet. secs. 4 and 5. Over mountainous land.
Asc. rocky broken S. slope 300 ft. to

- 13.10 Spur, slopes W. Desc. N. slope 150 ft. to
20.80 Draw, course W. Asc. S. slope.
26.40 Spur, slopes W. Desc. NW. slope 300 ft.
40.00 Set an iron post, 3 ft. long, 1 in. dia., in a mound of
stone for $\frac{1}{4}$ sec. cor., marked on brass cap

 $\frac{1}{4}$

S 5:S 4

1917

- ; raise a mound of stone,
2 ft. base, $1\frac{1}{2}$ ft. high W. of cor.
40.50 Head of draw, course W.
50.90 Low pass in ridge, which bears SE. and W. Desc. NE.
slope 250 ft. to
68.02 Intersect Gila and Salt River Base Line 150 lks. E. of
the reestablished standard corner of secs. 32 and 33,
hereinbefore described.
At point of intersection, set an iron post, 3 ft. long,
2 ins. dia., 24 ins. in the ground, for closing corner
of secs. 4 and 5, marked on brass cap

S 5:S 4

T 1 S:R 10 E

C C

1917

; raise a mound of stone,
2 ft. base, $1\frac{1}{2}$ ft. high S. of cor.
Land; mountainous.
Soil; rocky, 4th rate.
Undergrowth; palo verde and ironwood.
No timber.

- From the cor. of secs. 29, 30, 31 and 32,
S. $0^{\circ} 05' W.$ on random line bet. secs. 31 and 32.
40.00 Set temp. $\frac{1}{4}$ sec. cor.
83.68 Fall 27 lks. E. of the reestablished cor. of secs. 31 and
32 on S. bdy. of Tp., hereinbefore described.
Thence N. $0^{\circ} 16' E.$ on true line bet. secs. 31
and 32. Over rolling land, scattering undergrowth.
15.00 Asc. gentle SW. slope.
25.90 Spur, slopes W. Desc. NW. slope.
29.00 Foot of descent, thence over rolling land.
30.50 Road Phoenix to Superior, bears E. and W.
38.80 Wash, 20 lks. wide, course SW. Thence over rolling land.
43.68 Set an iron post, 3 ft. long, 1 in. dia., 8 ins. in the
ground, supported in mound of stone, for $\frac{1}{4}$ sec. cor.
marked on brass cap

Chains

$\frac{1}{4}$
S 31:S 32

1917

; raise a mound of stone,
2 ft. base, $1\frac{1}{2}$ ft. high W. of cor.
Continue over rolling land.

83.68 The cor. of secs. 29, 30, 31 and 32.

Land; rolling.
Soil; gravelly, 3d rate.
Undergrowth; palo verde, catclaw, ironwood and mesquite.
No timber.

7.00 N. $0^{\circ} 03'$ W. bet. secs. 29 and 30. Over rolling land.
Wash; course SW.

38.90 Wash, 30 lks. wide, course SW.

40.00 Set an iron post, 3 ft. long, 1 in. dia., 26 ins. in the
ground, for $\frac{1}{4}$ sec. cor., marked on brass cap

$\frac{1}{4}$
S 30:S 29

1917

; raise a mound of stone,
2 ft. base, $1\frac{1}{2}$ ft. high W. of cor.
80.00 Set an iron post, 3 ft. long, 2 ins. dia., 12 ins. in
the ground, supported in mound of stone, for cor. of
secs. 19, 20, 29 and 30, marked on brass cap

T 1 S R 10 E
S 19:S 20
S 30:S 29

1917

; raise a mound of stone, 2
ft. base, $1\frac{1}{2}$ ft. high W. of cor.
Land; gently rolling.
Soil; sandy, 2nd rate.
Undergrowth; palo verde, catclaw, ironwood and mesquite.
No timber.

40.00 East on random line bet. secs. 20 and 29.
Set temp. $\frac{1}{4}$ sec. cor.

80.00 Fall 2 lks. S. of the cor. of secs. 20, 21, 28 and 29.
Thence S. $89^{\circ} 59'$ W. on true line bet. secs. 20 and
29. Over rolling land. Desc. rocky W. slope
50 ft. to

3.00 Foot of descent.

17.00 Draw, 20 lks. wide, course SW. thence over rolling land.

40.00 Set an iron post, 3 ft. long, 1 in. dia., 12 ins. in the
ground, supported in a mound of stone, for $\frac{1}{4}$ sec. cor.
marked on brass cap

S 20
 $\frac{1}{4}$ ----
S 29

1917

; raise a mound of stone,
2 ft. base, $1\frac{1}{2}$ ft. high N. of cor.
54.20 Road, bears SE. and NW.

55.00 Draw, 15 lks. wide, course SW.

62.40 Wash, 25 lks. wide, course S.

78.10 Wash, course S. Asc. gentle SE. slope.

80.00 The cor. of secs. 19, 20, 29 and 30.

Land; rolling.
Soil; sandy, 2nd rate.

Chains Undergrowth; palo verde, mesquite and ironwood.
No timber.

West on random line bet. secs. 19 and 30.
40.00 Set temp. $\frac{1}{4}$ sec. cor.
82.30 Intersect W. bdy. of Tp. 2 lks. S. of the reestablished
cor. of secs. 19 and 30, hereinbefore described.
Thence S. $89^{\circ} 59'$ E. on true line bet. secs. 19
and 30. Over rolling desert land.
11.30 Wash, 30 lks. wide, course SW.
41.90 Small draw, course SW.
42.30 Set an iron post, 3 ft. long, 1 in. dia., 12 ins. in the
ground, supported in mound of stone, for $\frac{1}{4}$ sec. cor.,
marked on brass cap

$\frac{1}{4}$ S 19

S 30

1917

; raise a mound of stone,
2 ft. base, $1\frac{1}{2}$ ft. high N. of cor.

55.80 Desc. gentle SE. slope 25 ft. to
67.30 Draw, course SW.
77.30 Spur, slopes S. Desc. gentle E. slope.
82.30 The cor. of secs. 19, 20, 29 and 30.

Land; rolling.
Soil; 2nd rate, sandy.
Undergrowth; palo verde, catclaw, ironwood and mesquite.
No timber.

N. $0^{\circ} 03'$ W. bet. secs. 19 and 20.
Over rolling land, sloping East.
13.60 Draw, course SE. Thence asc. gentle SW. slope.
33.00 ~~Top of ascent~~, desc. gentle NE. slope.
40.00 Set an iron post, 3 ft. long, 1 in. dia., 6 ins. in the
ground, supported in mound of stone, for $\frac{1}{4}$ sec. cor.
marked on brass cap

$\frac{1}{4}$
S 19:S 20

1917

; raise a mound of stone,
2 ft. base, $1\frac{1}{2}$ ft. high W. of cor.
Continue over rolling land.

45.00 Draw, course SE.
55.00 Enter same draw, course SW.
56.50 Leave draw and asc. gentle SE. slope.
80.00 Set an iron post, 3 ft. long, 2 ins. dia., 18 ins. in
the ground, supported in mound of stone, for cor. of
secs. 17, 18, 19 and 20, marked on brass cap

T 1 S R 10 E
S 18:S 17

S 19:S 20

1917

; raise a mound of stone,
2 ft. base, $1\frac{1}{2}$ ft. high W. of cor.
Land; rolling.
Soil; sandy and gravelly, 2nd and 3d rate.
Undergrowth; palo verde, catclaw, ironwood and greasewood.
No timber.

Survey of Subdivision of T. 1 S., R. 10 E.

Chains N. 89° 59' E. on random line bet. secs. 17 and 20.
 40.00 Set temp. $\frac{1}{4}$ sec. cor.
 79.95 Fall 2 lks. S. of cor. of secs. 16, 17, 20 and 21.
 Thence S. 89° 58' W. on true line bet. secs. 17 and 20.
 Over mountainous land. Asc. E. slope.
 13.00 Spur, slopes S. Desc. rocky W. slope.
 39.97 $\frac{1}{2}$ Set an iron post, 3 ft. long, 1 in. dia., in mound of
 stone, for $\frac{1}{4}$ sec. cor., marked on brass cap

$\frac{1}{4}$ S 17

 $\frac{1}{4}$ S 20

1917

; raise a mound of stone 2
 ft. base, $1\frac{1}{2}$ ft. high N. of cor.

45.00 Foot of descent, thence over rolling land.
 58.80 Draw, course SW.
 67.00 Low spur, slopes SW.
 70.20 Road, bears NE. and SW.
 71.50 Wash, 1 ch. wide, course SW.
 79.95 The cor. of secs. 17, 18, 19 and 20.

Land; broken and rolling.
 Soil; rocky, 4th rate.
 Undergrowth; palo verde, mesquite and catclaw.
 No timber.

N. 89° 59' W. on random line bet. secs. 18 and 19.
 40.00 Set temp. $\frac{1}{4}$ sec. cor.
 82.27 Intersect W. bdy. of Tp. 5 lks. N. of the reestablished
 cor. of secs. 18 and 19, hereinbefore described.
 Thence N. 89° 59' E. on true line bet. secs. 18
 and 19. Over rolling land. Asc. gradual NE.
 slope.
 12.30 Top of ascent.
 42.27 Set an iron post, 3 ft. long, 1 in. dia., 10 ins. in the
 ground, supported in a mound of stone, for $\frac{1}{4}$ sec. cor.,
 marked on brass cap

$\frac{1}{4}$ S 18

 $\frac{1}{4}$ S 19

1917

; raise a mound of stone,
 2 ft. base, $1\frac{1}{2}$ ft. high N. of cor.

57.90 Wash, 50 lks. wide, course SW. Asc. E. slope.
 67.30 Small ridge, bears N. and S. Desc.
 72.30 Foot of descent.
 82.27 The cor. of secs. 17, 18, 19 and 20.

Land; rolling.
 Soil; 3rd rate, gravelly.
 Undergrowth; palo verde, greasewood, buck brush, mesquite,
 and ironwood.
 No timber.

N. 0° 03' W. bet. secs. 17 and 18.
 Over rolling land, through scattering undergrowth.
 33.60 Wash, 1 ch. wide, course SW.
 40.00 Set an iron post, 3 ft. long, 1 in. dia., 26 ins. in the
 ground, for $\frac{1}{4}$ sec. cor., marked on brass cap

$\frac{1}{4}$
 S 18:S 17

1917

; raise a mound of stone, 2
 ft. base, $1\frac{1}{2}$ ft. high W. of cor.

Chains

- 47.20 Wash, 1 ch. wide, course SW..
- 64.40 Draw, course SE. Asc. SW. slope.
- 80.00 Set an iron post 3 ft. long, 2 ins. dia., 6 ins. in the ground, supported in mound of stone, for cor. of secs. 7, 8, 17 and 18, marked on brass cap

T 1 S R 10 E
 S 7:S 8
 S 18:S 17

1917

; raise a mound of stone, 2 ft. base, 1½ ft. high W. of cor.

Land; rolling.
 Soil; 3d rate, gravelly and rocky.
 Undergrowth; mesquite, palo verde, catclaw and willow.
 No timber.

- N. 89° 58' E. on random line bet. secs. 8 and 17.
- 40.00 Set temp. ¼ sec. cor.
- 79.95 Fall 9 lks. N. of the cor. of secs. 8, 9, 16 and 17.
 Thence N. 89° 58' W. on true line bet. secs. 8 and 17.
 Over broken and rolling land, scattering undergrowth
- 3.70 Small spur, slopes SW.
- 31.20 Gulch, 40 lks. wide, course SW.
- 35.70 Wash, 80 lks. wide, course S.
- 39.97½ Set an iron post, 3 ft. long, 1 in. dia., 26 ins. in the ground, for ¼ sec. cor., marked on brass cap

S 8
 ¼ ----
 S 17

1917

; raise a mound of stone, 2 ft. base, 1½ ft. high N. of cor.

- 65.40 Wash, 110 lks. wide, course S.
- 68.70 Road, bears N. and S.
- 69.50 Asc. E. slope to
- 79.95 The cor. of secs. 7, 8, 17 and 18.

Land; rolling.
 Soil; gravelly and rocky 3d rate.
 Undergrowth; palo verde, mesquite, catclaw and ironwood.
 No timber.

- S. 89° 59' W. on random line bet. secs. 7 and 18.
- 40.00 Set temp. ¼ sec. cor.
- 82.10 Intersect W. bdy. of Tp. 14 lks. S. of the reestablished cor. of secs. 7 and 18, hereinbefore described.
 Thence S. 89° 55' E. on true line bet. secs. 7 and 18. Over rolling land, through scattering undergrowth
- .20 Wash, 20 lks. wide, course SW.
- 29.40 Spur, slopes S.
- 34.60 Gulch, course S.
- 38.40 Wash, 20 lks. wide, course SW.
- 42.10 Set an iron post, 3 ft. long, 1 in. dia., 12 ins. in the ground, supported in mound of stone, for ¼ sec. cor., marked on brass cap

S 7
 ¼ ----
 S 18

1917

; raise a mound of stone, 2 ft. base, 1½ ft. high N. of cor.

Chains

52.50 Draw, course SW.
82.10 The cor. of secs. 7, 8, 17 and 18.

Land; rolling.
Soil; gravelly and rocky, 3rd rate.
Undergrowth; palo verde, mesquite and catclaw.
No timber.

N. 0° 03' W. bet. secs. 7 and 8. Over rolling land.
Asc. gentle S. slope.
8.00 Spur, slopes E. Desc. N. slope.
13.90 Draw, course SE. Asc. S. slope.
18.80 Top of ascent, thence over broken NW. slope.
40.00 Set an iron post, 3 ft. long, 1 in. dia., 6 ins. in the ground, supported in mound of stone, for 1/4 sec. cor., marked on brass cap

1/4
S 7:S 8

1917

; raise a mound of stone,
2 ft. base, 1 1/2 ft. high W. of cor.
44.50 Head of draw, course SW.
57.60 Spur, slopes W.
80.00 Set an iron post, 3 ft. long, 2 ins. dia., 18 ins. in the ground, supported in mound of stone, for cor. of secs. 5, 6, 7 and 8, marked on brass cap

T 1 S R 10 E
S 6:S 5
S 7:S 8

1917

; raise a mound of stone,
2 ft. base, 1 1/2 ft. high W. of cor.

Land; heavy rolling hills.
Soil; gravelly and rocky, 3d and 4th rate.
Undergrowth; palo verde, mesquite, ironwood and catclaw.
No timber:

S. 89° 58' E. on random line bet. secs. 5 and 8.
40.00 Set temp. 1/4 sec. cor.
79.90 Intersect the cor. of secs. 4, 5, 8 and 9.
Thence N. 89° 58' W. on true line bet. secs. 5 and 8.
Over heavy rolling land, through scattering undergrowth.
18.80 Asc. E. slope of spur 130 ft.
28.30 Spur, slopes S.
39.95 Set an iron post, 3 ft. long, 1 in. dia., in a mound of stone, for 1/4 sec. cor., marked on brass cap

S 5
1/4 ---
S 8

1917

; and raise a mound of
stone, 2 ft. base, 1 1/2 ft. high N. of cor.
58.00 Road, bears N. and S.
60.80 Wash, course S.
76.70 Spur, slopes SW.
79.90 The cor. of secs. 5, 6, 7 and 8.

Land; rolling and broken.
Soil; gravelly and rocky, 3d and 4th rate.

Chains Undergrowth; palo verde, ironwood, mesquite, and catclaw. No timber.

N. 89° 55' W. on random line bet. secs. 6 and 7.

40.00 Set temp. 1/4 sec. cor.

82.26 Intersect W. bdy. of Tp., 14 lks. N. of the reestablished cor. of secs. 6 and 7, hereinbefore described.

Thence N. 89° 59' E. on true line bet. secs. 6 and 7. Over rolling land, through scattering undergrowth.

17.26 Draw, course SW.

40.00 Foot of cliff 50 ft. high.

41.16 Top of cliff.

42.26 Set an iron post, 3 ft. long, 1 in. dia., in a mound of stone, for 1/4 sec. cor., marked on brass cap

S 6
1/4 ---
S 7

1917

; raise a mound of stone, 2 ft. base, 1 1/2 ft. high N. of cor.

Asc. W. slope of hill.

44.00 Top of hill. Desc. broken E. slope.

63.56 Draw, course SE.

71.16 Spur, slopes S.

73.16 Draw, course SW. Asc. W. slope to

82.26 The cor. of secs. 5, 6, 7 and 8.

Land; heavy rolling hills.

Soil; gravelly and rocky, 3d and 4th rate.

Undergrowth; ironwood, palo verde, mesquite, and catclaw. No timber.

N. 0° 03' W. bet. secs. 5 and 6. Over mountainous land. Along W. slope.

7.40 Head of draw, course SW.

18.80 Spur, course SE.

26.90 Draw, course E. Asc. S. slope.

33.80 Spur, slopes E. desc. N. slope to

36.50 Draw, course E. Asc. S. slope.

40.00 Set an iron post, 3 ft. long, 1 in. dia., 6 ins. in the ground, supported in a mound of stone, for 1/4 sec. cor. marked on brass cap

1/4
S 6:S 5

1917

; and raise a mound of stone, 2 ft. base, 1 1/2 ft. high W. of cor.

52.20 Low ridge, bears NE. and SW.

57.50 Head of draw, course W. Asc. S. slope.

68.20 Intersect Gila and Salt River Base Line 150 lks. E. of the reestablished standard corner of Secs. 31 and 32, hereinbefore described.

At point of intersection, set an iron post, 3 ft. long, 2 ins. dia., 14 ins. in the ground, supported in a mound of stone, for closing cor. of secs. 5 and 6, marked on brass cap

S 6:S 5
T 1 S R 10 E
C C

1917

; and raise a mound of stone 2 ft. base, 1 1/2 ft. high S. of cor.

Chains Land; mountainous.
 Soil; rocky, 4th rate.
 Undergrowth; palo verde, mesquite, ironwood and catclaw.
 No timber.

Boundaries of T. 1 S., R. 10 E.

Latitudes, departures, and closing errors.

Line designated.	True bearing.	Distance.	Latitudes.		Departures.	
			N. chs.	S. chs.	E. chs.	W. chs.
S. Bdy.	S. 89° 30' W.	481.99		4.21		481.99
W. Bdy.	North	472.38	472.38			
N. Bdy. (G. & S.R. Base Line)	East	481.96			481.96	
E. Bdy.	South	468.27		468.27		
Convergency					.47	
Totals			472.38	472.48	482.43	481.99
				472.38	481.99	
Error in latitude - - - - -			.00			
Error in departure - - - - -					.44	

GENERAL DESCRIPTION.

The greater part of the surface of this township is mountainous and heavily rolling with a gravelly and rocky soil, 3rd and 4th rates. In the southwestern quarter is a large area of gently rolling surface with a sandy soil, 2nd rate.

There is no timber.

A scattering undergrowth of catclaw, greasewood, ocotillo, scrub palo verde, ironwood and mesquite is prevalent in all sections.

There is no permanent running water.

The general course of the drainage is south into Queen Creek, course west thru sections 36, 35 and 34, which drains the entire township.

There are no settlers or improvements.

There are no indications of valuable mineral deposits.

A road bearing east to Superior and west to Mesa, crossing the township thru the south tier of sections, and a road bearing north and south thru the west half of the township are the only important roads.

CERTIFICATE OF UNITED STATES SURVEYOR.

BOOK 3394

I, Roy J. Gill, U. S. Surveyor, hereby certify upon honor that, in pursuance of special instructions received from the U. S. Surveyor General, for Group 71, Arizona, bearing date of the 16th day of December, 1916, I have well, faithfully, and truly in my own proper person, and in strict conformity with said instructions, the Manual of Surveying Instructions, and the laws of the United States, re surveyed all those parts or portions of the Gila and Salt River Base Line, through Range 10 East, the South and West Boundaries of TOWNSHIP 1 SOUTH, RANGE 10 EAST, and SURVEYED all those parts or portions of the East Boundary and Subdivision Lines of TOWNSHIP 1 SOUTH, RANGE 10 EAST

of the Gila and Salt River Base and Meridian, in the State of Arizona, which are represented in and diagram on page 1 hereof the foregoing field notes, as having been executed by me, and under my direction; and that all the corners of resurvey and said survey have been established and perpetuated in strict accordance with the Manual of Surveying Instructions, and the special written instructions of the U. S. Surveyor General, for Group 71, Arizona, and in the specific manner described in the field notes, and that the foregoing are the original field notes of such resurvey and survey.

Phoenix, Arizona, July 5, 1920. by Roy J. Gill (deceased) U. S. Surveyor.

APPROVAL. Asst. Supervisor of Surveys District No. 5. OFFICE OF THE UNITED STATES SURVEYOR GENERAL,

Phoenix, Arizona, February 7, 1921.

The foregoing field notes of the Resurvey of the Gila and Salt River Base Line through Range 10 East, the South and West Boundaries of TOWNSHIP 1 SOUTH, RANGE 10 EAST, and the SURVEY of the East Boundary and Subdivision Lines of TOWNSHIP 1 SOUTH, RANGE 10 EAST, of the Gila and Salt River Base and Meridian, in the State of Arizona,

executed by Roy J. Gill, U. S. Surveyor, under his special instructions dated December 16, 1916, for Group 71, Arizona, having been critically examined, and the necessary corrections and explanations made, the said field notes, and the surveys and surveys they describe, are hereby approved.

U. S. Surveyor General.

I certify that the foregoing transcript of the field notes of the above described surveys in has been correctly copied from the original notes on file in this office.

U. S. Surveyor General.