

3688

4-679

ORIG  
1

263

BOOK "I"

BOOK 3688

# FIELD NOTES

OF THE SURVEY OF THE

9TH. STANDARD PARALLEL NORTH

THROUGH RANGE 12 WEST,

THE WEST BOUNDARY,

THE NORTH BOUNDARY,

and

THE SUBDIVISION LINES

of

TOWNSHIP 37 NORTH, RANGE 12 WEST

Of the Gila and Salt River Base and Meridian,

In the State of Arizona

EXECUTED BY

William E. Hiester, U.S. Surveyor

and

Charles E. Hunter, U.S. Transitman

*In the capacity of U. S. Surveyors, under Special Instructions dated April 23, 1923, issued by the United States Surveyor General to govern surveys included in Group No. 122, Arizona, which were approved by the Commissioner of the General Land Office, May 17, 1923, and Assignment Instructions dated Nov. 15, 1923*

Survey commenced April 8, 1924.

Survey completed April 29, 1924.

3688

3688

1A

Book "I"

Group 122 - - Arizona.

BOOK 3688

INDEX DIAGRAM.

Township		37 North		Range		12 West		
12	12	13	14	14	15			
10	6 47	5 39	4 33	3 27	2 21	1		
	47	46	38	32	26	21		
9	7 46	8 38	9 32	10 26	11 20	12		
	45	45	37	31	25	20		
9	18 44	17 37	16 31	15 25	14 19	13		
	44	43	T. 37 N., R. 12 W.		36	30	24	19
8	19 43	20 36	21 29	22 24	23 18	24		
	42	42	35	29	23	17		
7	30 41	29 34	28 28	27 23	26 17	25		
	41	40	34	28	22	16		
7	31 39	32 33	33 27	34 22	35 16	36		
	6	5	4	4	3	3		

9th. Standard Parallel North

- Lines surveyed under this group.
- Lines resurveyed under this group.
- Accepted surveys.
- Unsurveyed.

BOOK 3688

4-679 b

DATE

~~INDEX~~ DIAGRAM.

Township 37 North, Range 12 West

	4-22-24	4-22-24	4-22-24	4-21-24	4-21-24	4-21-24
4-18-24	4-22-24 6 4-25-24	4-26-24 5 4-26-24	4-28-24 4 4-28-24	4-21-24 3 4-29-24	4-18-24 2 4-18-24	4-12-24 1 4-12-24
4-18-24	4-25-24 7 4-25-24	4-26-24 8 4-24-24	4-28-24 9 4-24-24	4-28-24 10 4-17-24	4-17-24 11 4-16-24	4-12-24 12 4-12-24
4-18-24	4-24-24 18 4-23-24	4-24-24 17 4-23-24	4-24-24 16 4-21-24	4-17-24 15 4-14-24	4-16-24 14 4-13-24	4-11-24 13 4-11-24
4-17-24	4-18-24 19 4-23-24	4-11-24 20 4-22-24	4-21-24 21 4-22-24	4-14-24 22 4-12-24	4-16-24 23 4-12-24	4-11-24 24 4-11-24
4-17-24	4-17-24 30 4-16-24	4-11-24 29 4-16-24	4-16-24 28 4-16-24	4-14-24 27 4-14-24	4-12-24 26 4-12-24	4-10-24 25 4-10-24
4-17-24	4-11-24 31 4-10-24	4-11-24 32 4-10-24	4-16-24 33 4-10-24	4-14-24 34 4-14-24	4-12-24 35 4-12-24	4-10-24 36 4-10-24
	4-10-24	4-10-24	4-10-24	4-8-24	4-8-24	4-8-24

For dates of resurvey of this line see Book "H"  
Surveyed in 1915

9th Std. Par. N.

6-4817

Lines in red surveyed by William E. Hiester, U.S. Surveyor.

Lines in green surveyed by Charles E. Hunter, U.S. Transitman.

## BOOK 3688

Survey commenced April 8, 1924, and executed by William E. Hiester, U.S. Surveyor and Charles E. Hunter, U.S. Transitman, on dates shown on diagram on page 1 hereof, using Buff transit No. 9977 and Young and Sons transit No. 8535 respectively. Both instruments are equipped with full vertical circle and the Smith solar attachment, and were approved by the Assistant Supervisor of Surveys, conditional upon satisfactory field tests. Unless otherwise specified all azimuth determinations are accomplished with the solar attachments.

We examine the adjustments of the instruments and correct all errors, then to test the solar apparatus by comparing their indications resulting from solar observation made during a.m. and p.m. hours with a meridian determined from observation on Polaris, proceed as follows:

April 9, 1924: in camp near the cor. of secs. 14, 15, 22 and 23, T.37 N., R.12 W., Gila and Salt River Base and Meridian, Arizona, in latitude  $36^{\circ}36'N.$ , longitude  $113^{\circ}35'W.$ , of Greenwich, at 6h 17.7m p.m., l.m.t., we observe Polaris at western elongation, making four observations, two each with telescope in direct and reversed positions and mark the mean point of the line thus determined on a peg driven firmly in the ground 8 chs. N.

Azimuth of Polaris at western elongation =  $1^{\circ}22'25''$ .

We lay off the azimuth of Polaris  $1^{\circ}22\frac{1}{2}'$  to the east and mark the meridian thus determined by a tack in a stake driven firmly in the ground 8 chs. N.

April 10: at 7h 0m a.m., app.t., we set off  $36^{\circ}36'N.$ , on the latitude arcs,  $8^{\circ}1'N.$ , on the declination arcs, and determine meridians with the solars which agree with the true meridian.

April 13: at 8h 0m a.m., app.t., we set off  $36^{\circ}36'N.$ , on the latitude arcs,  $9^{\circ}7'N.$ , on the declination arcs, and determine meridians with the solars which agree with the true meridian.

At app. noon, with the latitude arcs unchanged, we observe the sun on the meridian with each instrument, the resulting readings of the declination arcs are  $9^{\circ}10'N.$ , which agrees with the computed declination of the sun.

At 4h 0m p.m., app.t., with the latitude arcs unchanged, we set off  $9^{\circ}14\frac{1}{2}'N.$  on the declination arcs, and determine meridians with the solars which agree with the true meridian.

As all the solar observations during the usual hours of solar work come within  $1'30''$  of the true meridian, we conclude that the adjustments of the instruments are satisfactory.

Unless otherwise specified all measurements are made with Lufkin steel tapes 5 chs. in length compared with a Lufkin standard steel tape and found correct. The measurements are made on the slope, the vertical angle determined and the slope measurement properly reduced to true horizontal distances.

9th. Standard Parallel North  
through R.12 W.

Chains The S.C. of Ts. 37 N., Rs. 11 and 12 W., is an iron post,  
3 ins. diam., 12 ins. above ground, firmly set, properly  
marked, and witnessed by a mound of stone, N. of cor.

Thence  
West, on S. bdy. of sec. 36.  
Over rolling land, through scattering timber and under-  
growth.

24.70 Wash, 10 lks. wide, course NW.  
24.80 Road, bears NE. and SW.  
30.00 Asc. 57 ft. over E. slope.  
40.00 Set an iron post, 3 ft. long, 1 in. diam., 6 ins. in the  
ground to bed rock, with marked cross (+) stone along-  
side, supported in a mound of stone, for standard  $\frac{1}{4}$   
sec. cor. marked on brass cap

S C  
 $\frac{1}{4}$  S 36

1924

80.00 Set an iron post, 3 ft. long, 3 ins. diam., 26 ins. in  
the ground for standard cor. of secs. 35 and 36, marked  
on brass cap

S C  
T37N R12W  
S 35 | S 36

1924

Raise a mound of stone, 3 ft. base, 2 ft. high N. of  
cor.

Land; rolling.  
Soil; rocky, 3rd. rate.  
Timber; cedar.  
Undergrowth; sagebrush and juniper.

West, on S. bdy. of sec. 35.  
Over rolling land, through scattering timber and under-  
growth.

28.30 Wash, 20 lks. wide, course NE.  
40.00 Set an iron post, 3 ft. long, 1 in. diam., 26 ins. in  
the ground for  $\frac{1}{4}$  sec. cor. marked on brass cap

S C  
 $\frac{1}{4}$  S 35

1924

From which,  
A cedar, 6 ins. diam., bears N.87  $\frac{3}{4}$ °E., 190 lks.  
dist., marked S C  $\frac{1}{4}$  S 35 B T  
A cedar, 6 ins. diam., bears N.79°W., 90 lks. dist.  
marked S C  $\frac{1}{4}$  S 35 B T

60.00 Desc. 57 ft. over W. slope.  
63.50 Asc. 36 ft.  
80.00 Desc. 118 ft. to  
Set an iron post, 3 ft. long, 3 ins. diam., 28 ins. in  
the ground for standard cor. of secs. 34 and 35, marked  
on brass cap

S C  
T37N R12W  
S 34 | S 35

1924

Raise a mound of stone, 5 ft. base, 2 ft. high N. of  
cor.

9th. Standard Parallel North,  
through R.12 W.

Chains

Land; rolling.  
Soil; rocky, 3rd. rate.  
Timber; cedar.  
Undergrowth; sagebrush.

West, on S. bdy. of sec. 34.  
Over rolling land, through scattering timber and undergrowth.

1.40 Road, bears N. and S.  
3.00 Wash, 20 lks. wide, course N.  
Asc. 145 ft. over E. slope.  
4.00 Road, to St. Thomas, bears N. and SW.  
35.00 Desc. 23 ft. to  
40.00 Set an iron post, 3 ft. long, 1 in. diam., 28 ins. in the ground for standard  $\frac{1}{4}$  sec. cor. marked on brass cap

S C  
 $\frac{1}{4}$  S 34

1924

From which,

A cedar, 6 ins. diam., bears N.46°E., 46 lks. dist.  
marked S C  $\frac{1}{4}$  S 34 B T  
A cedar, 8 ins. diam., bears N.62°W., 160 lks. dist.  
marked S C  $\frac{1}{4}$  S 34 B T

Enter heavy timber and dense undergrowth.

63.50 Asc. 162 ft. over E. slope.  
80.00 Top of ascent. Desc. 60 ft. to  
Set an iron post, 3 ft. long, 3 ins. diam., 28 ins. in the ground for standard cor. of secs. 33 and 34 marked on brass cap

S C  
T37N | R12 W  
S 33 | S 34

1924

From which,

A cedar, 20 ins. diam., bears N.39 $\frac{1}{2}$ °E., 95 lks. dist.  
marked S C T 37 N R 12 W S 34 B T  
A cedar, 6 ins. diam., bears N.18 $\frac{1}{2}$ °W., 61 lks. dist.  
marked S C T 37 N R 12 W S 33 B T

Land; rolling.  
Soil; rocky, 3rd. rate.  
Timber; cedar.  
Undergrowth; sagebrush.

West, on S. bdy. of sec. 33.  
Over rolling land, through heavy timber and dense undergrowth.

7.90 Desc. 23 ft. over W. slope to  
Wash, 10 lks. wide, course S.  
Asc. 110 ft. over E. slope.  
30.00 Top of ascent. Desc. 50 ft. over W. slope.  
39.10 Head of draw, course S.  
40.00 Set an iron post, 3 ft. long, 1 in. diam., 24 ins. in the ground for standard  $\frac{1}{4}$  sec. cor. marked on brass cap

S C  
 $\frac{1}{4}$  S 33

1924

From which,

A cedar, 6 ins. diam., bears N.27°E., 30 lks. dist.  
marked S C  $\frac{1}{4}$  S 33 B T  
A cedar, 6 ins. diam., bears N.40°W., 78 lks. dist.  
marked S C  $\frac{1}{4}$  S 33 B T

50.00 Asc. 53 ft. over E. slope.  
Top of ascent. Desc.

9th. Standard Parallel North,  
through R.12 W.

## Chains

50.50 Wash, 10 lks. wide, course N.  
60.00 asc. 70 ft. to  
70.00 Desc. 80 ft.  
80.00 Set an iron post, 3 ft. long, 3 ins. diam., 20 ins. in  
the ground to bed rock, supported in a mound of stone,  
for standard cor. of secs. 32 and 33, marked on brass  
cap

S C  
T37N R12W  
S 32 | S 33

1924

From which,

A cedar, 10 ins. diam., bears N.32 $\frac{1}{2}$ °E., 164 lks. dist.  
marked S C T37 N R 12 W S 33 B T  
A cedar, 8 ins. diam., bears N.43 $\frac{1}{2}$ °W., 134 lks. dist.  
marked S C T 37 N R 12 W S 32 B T

Land; rolling.  
Soil; rocky, 3rd. rate.  
Timber; cedar.  
Undergrowth; sagebrush.

West, on S. bdy. of sec. 32.  
Over rolling land, through heavy timber and dense under-  
growth.

21.00 Asc. 115 ft. over E. slope to  
37.00 Top of ascent.  
40.00 Head of draw, course N.  
Set an iron post, 3 ft. long, 1 in. diam., 24 ins. in  
the ground for standard  $\frac{1}{4}$  sec. cor. marked on brass  
cap.

S C  
 $\frac{1}{4}$  S 32

1924

From which,

A cedar, 6 ins. diam., bears N.8°W., 93 lks. dist.  
marked S C  $\frac{1}{4}$  S 32 B T  
A cedar, 8 ins. diam., bears N.69°W., 45 lks. dist.  
marked S C  $\frac{1}{4}$  S 32 B T

52.20 Desc. 100 ft. over NW. slope to  
65.90 Wash, 20 lks. wide, course NE.  
80.00 Asc. 70 ft. to  
Set an iron post, 3 ft. long, 3 ins. diam., 30 ins. in  
the ground for standard cor. of secs. 31 and 32 marked  
on brass cap

S C  
T37N R12W  
S 31 | S 32

1924

From which,

A cedar, 6 ins. diam., bears N.12°E., 152 lks. dist.  
marked S C T 37 N R 12 W S 32 B T  
A cedar, 10 ins. diam., bears N.15 $\frac{1}{2}$ °W., 78 lks. dist.  
marked S C T 37 N R 12 W S 31 B T

Land; rolling.  
Soil; rocky, 4th. rate.  
Timber; cedar.  
Undergrowth; sagebrush.

9th. Standard Parallel North,  
through R.12 W.

Chains

West, on S. bdy. of sec. 31  
Over rolling land, through heavy timber and dense under-  
growth.

5.00  
17.50  
40.00

Asc. 50 ft. to  
Desc. 120 ft. over W. slope.  
Wash, 20 lks. wide, course NE.  
Set an iron post, 3 ft. long, 1 in. diam., 28 ins. in the  
ground for standard  $\frac{1}{4}$  sec. cor. marked on brass cap

S C  
 $\frac{1}{4}$  S 31

1924

From which,

- A cedar, 6 ins. diam., bears N.  $25\frac{1}{2}^{\circ}$  E., 49 lks. dist.  
marked S C  $\frac{1}{4}$  S 31 B T
- A cedar, 6 ins. diam., bears N.  $46^{\circ}$  W., 46 lks. dist.  
marked S C  $\frac{1}{4}$  S 31 B T

65.00  
80.00

Asc. gradual E. slope.  
Ridge, bears N. and S.  
Desc. 110 ft. over W. slope.  
Set an iron post, 3 ft. long, 3 ins. diam., 16 ins. in  
the ground to bed rock, supported in a mound of stone,  
for standard cor. of T37 N., R. 12 and 13 W., marked  
on brass cap

S C  
T37N  
R13W | R12W  
S36 | S 31

1924

From which,


- A cedar, 6 ins. diam., bears N.  $14^{\circ}$  E., 121 lks. dist.  
marked S C T 37 N R 12 W S 31 B T
- A cedar, 14 ins. diam., bears N.  $82\frac{1}{2}^{\circ}$  W., 78 lks. dist.  
marked S C T 37 N R 13 W S 36 B T

Land; rolling.  
Soil; rocky, 4th. rate.  
Timber; cedar.  
Undergrowth; sagebrush.

West Boundary of T.37 N.,R.12 W.


Chains From the S.C. of Ts. 37 N.,Rs. 12 and 13 W., hereinbefore described,  
North, bet. secs. 31 and 36.  
Over rolling land, through heavy timber and dense undergrowth.

10.50 Desc. 34 ft. over N. slope.  
30.00 Draw, course W. Asc. 110 ft. over SW. slope.  
40.00 Desc. 88 ft. over N. slope.  
Set an iron post, 3 ft. long, 1 in. diam., 30 ins. in the ground for  $\frac{1}{4}$  sec. cor. marked on brass cap



From which,  
A cedar, 12 ins. diam., bears S.50°E., 68 lks. dist. marked  $\frac{1}{4}$  S 31 B T  
A cedar, 6 ins. diam., bears S.59 3/4°W., 31 lks. dist., marked  $\frac{1}{4}$  S 36 B T

40.10 Draw, course W. Asc. 120 ft. to  
50.50 Spur, slopes W. Desc. 208 ft. over NW. slope to  
80.00 Set an iron post, 3 ft. long, 2 ins. diam., 26 ins. in the ground for cor. of secs. 25, 30, 31 and 36, marked on brass cap




From which,  
A cedar, 6 ins. diam., bears N.48 1/4°E., 95 lks. dist. marked T 37 N R 12 W S 30 B T  
A cedar, 6 ins. diam., bears S.55°E., 48 lks. dist. marked T 37 N R 12 W S 31 B T  
A cedar, 6 ins. diam., bears S.36 1/2°W., 145 lks. dist. marked T 37 N R 13 W S 36 B T  
A cedar, 7 ins. diam., bears N.54 3/4°W., 108 lks. dist., marked T 37 N R 13 W S 25 B T

Land; rolling.  
Soil; rocky, 4th. rate.  
Timber; cedar.  
Undergrowth; sagebrush.

North, bet. secs. 25 and 30.  
Over rolling land, through heavy timber and dense undergrowth.

9.40 Desc. 50 ft. over NW. slope.  
14.70 Draw, course SW. Asc. 150 ft.  
20.00 Timber becomes scattering.  
29.50 Top of ascent. Desc. 23 ft. to  
40.00 Set an iron post, 3 ft. long, 1 in. diam., 8 ins. in the ground to bed rock, supported in a mound of stone, for  $\frac{1}{4}$  sec. cor. marked on brass cap




From which,  
A cedar, 6 ins. diam., bears S.82 3/4°E., 43 lks. dist., marked  $\frac{1}{4}$  S 30 B T  
A cedar, 6 ins. diam., bears S.54 3/4°W., 144 lks. dist., marked  $\frac{1}{4}$  S 25 B T

61.64 Desc. 160 ft. over N. slope.  
Draw, course NW. Asc. 40 ft. over SW. slope.

Chains  
67.60  
76.40  
80.00

Top of ascent. Thence along W. slope.  
Desc. 63 ft. to  
Set an iron post, 3 ft. long, 2 ins. diam., 28 ins. in the ground for cor. of secs. 19, 24, 25 and 30, marked on brass cap




From which,  
A cedar, 12 ins. diam., bears N.52°E., 79 lks. dist. marked T 37 N R.13 W S 19 B T  
A cedar, 10 ins. diam., bears S.70½°E., 10 lks. dist. marked T 37 N R 12 W S 30 B T  
A cedar, 12 ins. diam., bears S.80½°W., 120 lks. dist. marked T 37 N R 13 W S 25 B T  
A cedar, 10 ins. diam., bears N.32¼°W., 23 lks. dist. marked T 37 N R 13 W S 24 B T

Land; rolling.  
Soil; rocky, 4th. rate.  
Timber; cedar.  
Undergrowth; sagebrush.


North, bet. secs. 19 and 24.  
Over rolling land, through heavy timber and dense undergrowth.

Asc. 23 ft. to  
5.00 Low spur, slopes W. Desc. 50 ft.  
11.20 Wash, 10 lks. wide, course NE.  
12.60 Road, bears NE. and SW.  
Asc. 58 ft. over rolling E. slope.  
31.50 Desc. 90 ft. to  
40.00 Set an iron post, 3 ft. long, 1 in. diam., 16 ins. in the ground to bed rock, supported in a mound of stone, for ¼ sec. cor. marked on brass cap



From which,  
A cedar, 6 ins. diam., bears N.37°E., 2 lks. dist. marked ¼ S 19 B T  
A cedar, 6 ins. diam., bears S.47°W., 19 lks. dist. marked ¼ S 24 B T

53.00 Desc. 97 ft. to  
Wash, 10 lks. wide, course NE.  
Asc. 60 ft. over SW. slope.  
67.80 Spur, slopes NE. Desc.  
80.00 Set an iron post, 3 ft. long, 2 ins. diam., 28 ins. in the ground for cor. of secs. 18, 19 and 24, marked on brass cap



From which,  
A cedar, 4 ins. diam., bears N.10½°E., 30 lks. dist. marked B T T R 12 W S 19 B T  
A cedar, 8 ins. diam., bears S.69¼°E., 50 lks. dist. marked T 37 N R 12 W S 19 B T  
A cedar, 8 ins. diam., bears S.6½°W., 79 lks. dist. marked T 37 N R 13 W S 24 B T  
A cedar, 4 ins. diam., bears N.19 3/4°W., 45 lks. marked B T

West Boundary of T.37 N., R.12 W.


Chains

Land; rolling.  
Soil; rocky, 3rd. rate.  
Timber; cedar.  
Undergrowth; sagebrush.

North, bet. secs. 13 and 18.  
Over rolling land, through scattering timber and undergrowth.

11.20  
40.00


Desc. 154 ft. over NW. slope.  
Foot of descent. Thence over level land.  
Set an iron post, 3 ft. long, 1 in. diam., 28 ins. in the ground for  $\frac{1}{4}$  sec. cor. marked on brass cap



From which,  
A cedar, 12 ins. diam., bears N.33°E., 44 lks. dist. marked  $\frac{1}{4}$  S 18 B T  
A cedar, 12 ins. diam., bears S.31 $\frac{1}{2}$ °W., 39 lks. dist. marked  $\frac{1}{4}$  S 13 B T

52.00  
55.70  
56.30  
60.00  
80.00

Wash, 10 lks. wide, course NW.  
Wash, 10 lks. wide, course W.  
Road, bears E. and W.  
Enter rolling land, Asc. 160 ft. to  
Set an iron post, 3 ft. long, 2 ins. diam., 20 ins. in the ground to bed rock, supported in a mound of stone, for cor. of secs. 7, 12, 13 and 18, marked on brass cap




From which,  
A cedar, 12 ins. diam., bears N.23 $\frac{1}{2}$ °E., 56 lks. dist. marked T 37 N R 12 W S 7 B T  
A cedar, 6 ins. diam., bears S.27°E., 33 lks. dist. marked T 37 N R 12 W S 18 B T  
A cedar, 6 ins. diam., bears S.3 3/4°W., 62 lks. dist. marked T 37 N R 13 W S 13 B T  
A cedar, 8 ins. diam., bears N.52 3/4°W., 32 lks. dist., marked T 37 N R 13 W S 12 B T

Land; rolling and level.  
Soil; rocky, 3rd. rate.  
Timber; cedar.  
Undergrowth; sagebrush.

North, bet. secs. 7 and 12.  
Over rolling land, through heavy timber and dense undergrowth.

7.00  
21.93  
39.30  
40.00

Desc. 46 ft. to  
Wash, 5 lks. wide, course NE. Asc. 30 ft.  
Spur, slopes E.  
Wash, 10 lks. wide, course E.  
Set an iron post, 3 ft. long, 1 in. diam., 6 ins. in the ground to bed rock, supported in a mound of stone, for  $\frac{1}{4}$  sec. cor. marked on brass cap



From which,  
A cedar, 12 ins. diam., bears N.20 $\frac{1}{4}$ °E., 16 lks. dist.

West Boundary of T.37 N., R.12 W.

Chains


marked  $\frac{1}{4}$  S 7 B T  
A cedar, 14 ins. diam., bears S.89 $\frac{1}{2}$ °W., 23 lks. dist.  
marked  $\frac{1}{4}$  S 12 B T

51.00

Spur, slopes E. 34 ft. above  $\frac{1}{4}$  sec. cor.  
Desc. 134 ft. to

80.00

Set an iron post, 3 ft. long, 2 ins. diam., 30 ins. in  
the ground for cor. of secs. 1, 6, 7 and 12, marked  
on brass cap



From which,

- A cedar, 8 ins. diam., bears N.46 $\frac{1}{2}$ °E., 87 lks. dist.  
marked T 37 N R 12 W S 6 B T
- A cedar, 4 ins. diam., bears S.44 $\frac{1}{2}$ °E., 38 lks. dist.  
marked B T
- A cedar, 14 ins. diam., bears S.45 $\frac{1}{2}$ °W., 89 lks. dist.  
marked T 37 N R 13 W S 12 B T
- A cedar, 4 ins. diam., bears N.27°W., 70 lks. dist.  
marked B T

Land; rolling.  
Soil; rocky, 3rd. rate.  
Timber; cedar.  
Undergrowth; sagebrush.

North, bet. secs. 1 and 6.  
Over rolling land, through heavy timber and dense under-  
growth.

2.50

Wash, 10 lks. wide, course W.

3.60

Road, bears E. and W.

9.90


Asc. 107 ft. over SE. slope.

32.90

Spur, slopes NE. Desc. 75 ft. over N. slope.

40.00

Set an iron post, 3 ft. long, 1 in. diam., 26 ins. in  
the ground for  $\frac{1}{4}$  sec. cor. marked on brass cap



From which,

- A cedar, 20 ins. diam., bears East, 2 lks. dist.  
marked  $\frac{1}{4}$  S 6 B T
- A cedar, 6 ins. diam., bears N.74 $\frac{1}{2}$ °W., 42 lks. dist.  
marked  $\frac{1}{4}$  S 1 B T

Desc. 125 ft. over N. slope.

53.42

Draw, course NW.

54.42

Road, bears SE. and NW. Asc. 170 ft. to

65.20


Spur, slopes W. Desc. 150 ft.

74.90

Draw, course SW. Asc. 76 ft. to

80.00

Set an iron post, 3 ft. long, 3 ins. diam., 32 ins. in  
the ground for cor. of Ts. 37 and 38 N., Rs. 12 and 13  
W., marked on brass cap



From which,

- A cedar, 10 ins. diam., bears N.82 $\frac{1}{4}$ °E., 17 lks. dist.  
marked T 38 N R 12 W S 31 B T
- A cedar, 18 ins. diam., bears S.50 $\frac{1}{2}$ °E., 130 lks. dist.  
marked T 37 N R 12 W S 6 B T
- A cedar, 10 ins. diam., bears S.52°W., 77 lks. dist.  
marked T 37 N R 13 W S 1 B T

West Boundary of T.37 N.,R.12 W.

Chains

A cedar, 14 ins. diam., bears N.15 $\frac{1}{2}$ °W., 54 lks. dist.  
marked T 38 N R 13 W S 36 B T

Land; rolling.  
Soil; rocky, 3rd. and 4th. rates.  
Timber; cedar.  
Undergrowth; sagebrush.

North Boundary of T.37 N.,R.12 W.

Chains

From the cor. of Ts. 37 and 38 N.,Rs. 11 and 12 W., West, on a random line along the N. bdy. of T.37 N.,R. 12 W., setting temp.  $\frac{1}{4}$  sec. and sec. cors. at intervals of 40.00 chs. until at 480.49 chs. fall 75 lks. N. of the cor. of Ts. 37 and 38 N.,Rs. 12 and 13 W., hereinbefore described.

Thence

N.89°55'E., on a true line bet. secs. 6 and 31.

Over rolling land, through heavy timber and dense undergrowth.

Desc. 40 ft. to

12.35 Draw, course SW. Asc. 220 ft. to  $\frac{1}{4}$  sec. cor.

30.06 Draw, course NW.

40.49 Set an iron post, 3 ft. long, 1 in. diam., 20 ins. in the ground to bed rock, supported in a mound of stone, for  $\frac{1}{4}$  sec. cor. marked on brass cap

$\frac{1}{4}$   $\frac{S\ 31}{S\ 6}$   
1924

From which,

A cedar, 14 ins. diam., bears N.11 $\frac{1}{2}$ °W., 80.lks. dist. marked  $\frac{1}{4}$  S 31 B T

A cedar, 14 ins. diam., bears S.29  $\frac{3}{4}$ °E., 87 lks. dist., marked  $\frac{1}{4}$  S 6 B T

Asc. 11 ft. to

43.00 Spur, slopes N. Desc. 75 ft.

59.50 Draw, course N. Asc. 34 ft.

65.50 Spur, slopes N. Desc. 40 ft.

80.29 Head of draw, course NW.

80.49 Set an iron post, 3 ft. long, 2 ins. diam., 28 ins. in the ground for cor. of secs. 5, 6, 31 and 32, marked on brass cap

T38N R12W  
S 31 | S 32  
S 6 | S 5  
T37N  
1924

From which,

A cedar, 14 ins. diam., bears N.21  $\frac{3}{4}$ °E., 175 lks. dist., marked T 38 N R 12 W S 32 B T

A cedar, 6 ins. diam., bears S.51 $\frac{1}{4}$ °E., 83 lks. dist. marked T 37 N R 12 W S 5 B T

A cedar, 10 ins. diam., bears S.48 $\frac{1}{2}$ °W., 164 lks. dist., marked T 37 N R 12 W S 6 B T

A cedar, 14 ins. diam., bears N.34  $\frac{3}{4}$ °W., 154 lks. dist., marked T 38 N R 12 W S 31 B T

Land; rolling.

Soil; rocky, 3rd. and 4th. rates.

Timber; cedar.

Undergrowth; sagebrush.

N.89°55'E., on a true line bet. secs. 5 and 32.

Over rolling land, through heavy timber and dense undergrowth.

Asc. 32 ft.

8.00 Desc. 85 ft. to

18.50 Draw, course N.

40.00 Set an iron post, 3 ft. long, 1 in. diam., 28 ins. in the ground for  $\frac{1}{4}$  sec. cor. marked on brass cap

$\frac{1}{4}$   $\frac{S\ 32}{S\ 5}$   
1924

From which,

A cedar, 28 ins. diam., bears N.4°W., 123 lks. dist. marked  $\frac{1}{4}$  S 32 B T

A cedar, 18 ins. diam., bears S.18  $\frac{3}{4}$ °E., 126 lks.

North Boundary of T.37 N., R.12 W.

Chains

marked  $\frac{1}{4}$  S 5 B T

60.00  
63.95  
69.00  
80.00

Leave timber, enter sagebrush flat.  
Wash, 8 lks. wide, course NW.  
Enter timber, bears SE. and NW.  
Asc. 17 ft. over W. slope.  
Set an iron post, 3 ft. long, 2 ins. diam., 30 ins. in the ground for cor. of secs. 4, 5, 32 and 33, marked on brass cap

T38N R12W  
S 32 | S 33  
S 5 | S 4  
T37N  
1924

From which,

- A cedar, 12 ins. diam., bears N.18  $\frac{3}{4}$ °E., 55 lks. dist., marked T 38 N R 12 W S 33 B T
- A cedar, 14 ins. diam., bears S.29  $\frac{1}{4}$ °E., 141 lks. dist., marked T 37 N R 12 W S 4 B T
- A cedar, 12 ins. diam., bears S.6  $\frac{1}{2}$ °W., 135 lks. dist., marked T 37 N R 12 W S 5 B T
- A cedar, 14 ins. diam., bears N.7  $\frac{1}{4}$ °W., 120 lks. dist., marked T 38 N R 12 W S 32 B T

Land; rolling.  
Soil; rocky, 3rd. rate.  
Timber; cedar.  
Undergrowth; sagebrush.

N.89°55'E., on a true line bet. secs. 4 and 33.  
Over rolling land, through heavy timber and dense undergrowth.

26.15  
40.00

Wash, 10 lks. wide, course NW.  
Asc. 46 ft.  
Set an iron post, 3 ft. long, 1 in. diam., 15 ins. in the ground to bed rock, supported in a mound of stone, for  $\frac{1}{4}$  sec. cor. marked on brass cap

S 33  
 $\frac{1}{4}$  S 4  
1924

From which,

- A cedar, 14 ins. diam., bears N.19  $\frac{1}{4}$ °W., 115 lks. dist., marked  $\frac{1}{4}$  S 33 B T
- A cedar, 14 ins. diam., bears S.13  $\frac{1}{2}$ °E., 99 lks. dist., marked  $\frac{1}{4}$  S 4 B T

80.00

Set an iron post, 3 ft. long, 2 ins. diam., 28 ins. in the ground for cor. of secs. 3, 4, 33 and 34, marked on brass cap

T38N R12W  
S 33 | S 34  
S 4 | S 3  
T37N  
1924

From which,

- A cedar, 16 ins. diam., bears N.20°E., 60 lks. dist. marked T 38 N R 12 W S 34 B T
- A cedar, 24 ins. diam., bears S.80°E., 57 lks. dist. marked T 37 N R 12 W S 3 B T
- A cedar, 8 ins. diam., bears S.50  $\frac{1}{2}$ °W., 15 lks. dist. marked T 37 N R 12 W S 4 B T
- A cedar, 7 ins. diam., bears N.20  $\frac{1}{2}$ °W., 103 lks. dist. marked T 38 N R 12 W S 33 B T

Land; rolling. Soil; rocky, 3rd. rate.  
Timber; cedar.  
Undergrowth; sagebrush.

North Boundary of T.37 N., R.12 W.

Chains N.89°55'E., on a true line bet. secs. 3 and 34.  
Over rolling land, through heavy timber and dense undergrowth.

40.00 Set an iron post, 3 ft. long, 1 in. diam., 28 ins. in the ground for  $\frac{1}{4}$  sec. cor. marked on brass cap

$\frac{1}{4}$   $\frac{S\ 34}{S\ 3}$   
1924

From which,  
A cedar, 12 ins. diam., bears N.58 $\frac{1}{2}$ °E., 96 lks. dist. marked  $\frac{1}{4}$  S 34 B T  
A cedar, 10 ins. diam., bears S.29°E., 50 lks. dist. marked  $\frac{1}{4}$  S 3 B T

53.00 Leave heavy and enter scattering timber, bears N. and S.  
62.70 Desc: 37 ft. to

67.00 Draw, course NE. Asc. 63 ft.

77.00 Spur, slopes N. Desc. 19 ft. to

80.00 Set an iron post, 3 ft. long, 2 ins. diam., 8 ins. in the ground to bed rock, with marked cross (+) stone alongside, supported in a mound of stone, for cor. of secs. 2, 3, 34 and 35, marked on brass cap

T38N R12W  
S 34 | B 35  
S 3 | S 2  
T37N  
1924

From which,  
A cedar, 14 ins. diam., bears N.73 $\frac{1}{2}$ °E., 262 lks. dist. marked T 38 N R 12 W S 35 B T  
A cedar, 10 ins. diam., bears S.27 $\frac{1}{4}$ °E., 239 lks. dist. marked T 37 N R 12 W S 2 B T  
A cedar, 6 ins. diam., bears S.16 $\frac{1}{2}$ °W., 198 lks. dist. marked T 37 N R 12 W S 3 B T

Land; rolling.  
Soil; rocky, 3rd. rate.  
Timber; cedar.  
Undergrowth; sagebrush.

N.89°55'E.; on a true line bet. secs. 2 and 35.  
Over rolling land, through scattering timber and dense undergrowth.

2.50 Desc. 44 ft. over E. slope.  
11.00 Draw, course N. Asc. 60 ft. to

23.50 Top of ascent. Enter heavy timber, bears N. and S.

28.50 Desc: 30 ft. to

33.50 Draw, course NE. Asc. 30 ft.

39.50 Point of spur, slopes NE. Desc. 55 ft. to

40.00 Draw, course NE.

Set an iron post, 3 ft. long, 1 in. diam., 28 ins. in the ground for  $\frac{1}{4}$  sec. cor. marked on brass cap

$\frac{1}{4}$   $\frac{S\ 35}{S\ 2}$   
1924

From which,  
A cedar, 16 ins. diam., bears N.54°E., 80 lks. dist. marked  $\frac{1}{4}$  S 35 B T  
A cedar, 10 ins. diam., bears S.55 $\frac{1}{4}$ °E., 28 lks. dist. marked  $\frac{1}{4}$  S 2 B T

49.40 Draw, course NE. Asc. 17 ft. to

59.50 Spur, slopes SE. Desc. 47 ft.

73.80 Wash, 10 lks. wide, course N.

80.00 Set an iron post, 3 ft. long, 2 ins. diam., 28 ins. in the ground for cor. of secs. 1, 2, 35 and 36, marked on brass cap

North Boundary of T.37 N., R.12 W.

Chains

T38N R12W  
 S 35 | S 36  
 S 2 | S 1  
 T37N  
 1924

From which,

- A cedar, 36 ins. diam., bears N.57 3/4°E., 159 lks. dist., marked T 38 N R 12 W S 36 B T
- A cedar, 12 ins. diam., bears S.11 1/2°E., 160 lks. dist., marked T 37 N R 12 W S 1 B T
- A cedar, 24 ins. diam., bears S.24°W., 200 lks. dist. marked T 37 N R 12 W S 2 B T
- A cedar, 16 ins. diam., bears N.1 3/4°W., 268 lks. dist., marked T 38 N R 12 W S 35 B T

Land; rolling.  
 Soil; rocky, 3rd. rate.  
 Timber; cedar.  
 Undergrowth; sagebrush.

N.89°55'E., on a true line bet. seos. 1 and 36.  
 Over rolling land, through scattering timber and undergrowth.

40.00

Set an iron post, 3 ft. long, 1 in. diam., 26 ins. in the ground for 1/4 sec. cor. marked on brass cap

1/4 S 36  
 S 1  
 1924

From which,

- A cedar, 16 ins. diam., bears S.3 1/4°E., 393 lks. dist. marked 1/4 S 1 B T
- A cedar, 6 ins. diam., bears S.24 1/2°W., 380 lks. dist. marked 1/4 S 1 B T
- No B. T. in Sec. 36.

63.70  
 64.00  
 80.00

Road to Wolf Hole, bears N. and S.  
 Wash, 20 lks. wide, course N.  
 The cor. of Ts. 37 and 38 N., Rs. 11 and 12 W., which is an iron post, 3 ins. diam., 12 ins. above ground, firmly set, properly marked, and witnessed by a mound of stone S. of cor.

Land; rolling.  
 Soil; rocky, 3rd. rate.  
 Timber; cedar.  
 Undergrowth; sagebrush.


Subdivision of T.37 N., R.12 W.

Chains

From the S.C. of secs. 35 and 36 on S. bdy. of Tp., hereinbefore described, N.0°10'E., bet. secs. 35 and 36. Over rolling land, through scattering timber and undergrowth.

40.00

Desc. 70 ft. to Set an iron post, 3 ft. long, 1 in. diam., 4 ins. in the ground to bed rock, supported in a mound of stone, for 1/4 sec. cor. marked on brass cap




From which, A cedar, 20 ins. diam., bears N.61 1/4°E., 391 lks. dist. marked 1/4 S 36 B T A cedar, 20 ins. diam., bears N.66 1/2°W., 220 lks. dist., marked 1/4 S 35 BT

47.00

Draw, course NE.

80.00

Set an iron post, 3 ft. long, 2 ins. diam., 24 ins. in the ground for cor. of secs. 25, 26, 35 and 36, marked on brass cap



From which, A cedar, 12 ins. diam., bears N.6 3/4°E., 683 lks. dist., marked T 37 N R 12 W S 25 B T A cedar, 8 ins. diam., bears S.88 3/4°W., 186 lks. dist., marked T 37 N R 12 W S 35 B T A cedar, 14 ins. diam., bears N.24°W., 650 lks. dist. marked T 37 N R 12 W S 26 B T Dig pits 18 x 18 x 12 ins. one in each sec. NE., SE. SW. and NW. of cor. 3 ft. dist.

Land; rolling. Soil; rocky, 3rd. rate. Timber; cedar. Undergrowth; sagebrush.

40.00

East, on a random line bet. secs. 25 and 36.

80.06

Set temp. 1/4 sec. cor. Fall 6 lks. S. of the cor. of secs. 25, 30, 31 and 36 on E. bdy. of Tp. which is an iron post, 3 ins. diam., 12 ins. above ground, firmly set, properly marked, and witnessed by a mound of stone W. of cor.

Thence S.89°57'W., on a true line bet. secs. 25 and 36. Over rolling land, through scattering timber and undergrowth.

8.56

Desc. 46 ft. over W. slope.

8.76

Draw, course N.

Road, bears N. and S.


Asc. 96 ft. over E. slope.

23.00

Top of ascent.

40.03

Set an iron post, 3 ft. long, 1 in. diam., 6 ins. in the ground to bed rock, with marked cross (+) stone alongside, supported in a mound of stone, for 1/4 sec. cor., marked on brass cap



46.66

Draw, course N.

58.86

Road, bears SE. and NW.

Subdivision of T.37 N., R.12 W.

Chains  
80.06

The cor. of secs. 25, 26, 35 and 36.


Land; rolling.  
Soil; rocky, 3rd. rate.  
Timber; cedar.  
Undergrowth; sagebrush.

2.50  
3.00  
40.00

N.0°10'E., bet. secs. 25 and 26.  
Over rolling land, through scattering timber and undergrowth.

Draw, course E.  
Road, bears E. and W. •  
Asc. gradually.

Set an iron post, 3 ft. long, 1 in. diam., 30 ins. in the ground for  $\frac{1}{4}$  sec. cor. marked on brass cap




From which,

- A cedar, 14 ins. diam., bears S.88 $\frac{1}{2}$ °E., 125 lks. dist., marked  $\frac{1}{4}$  S 25 B T
- A cedar, 6 ins. diam., bears N.80 $\frac{1}{4}$ °W., 30 lks. dist., marked  $\frac{1}{4}$  S 26 B T

80.00

Desc. 87 ft. over N. slope to  
Set an iron post, 3 ft. long, 2 ins. diam., 16 ins. in the ground to bed rock, supported in a mound of stone, for cor. of secs. 23, 24, 25 and 26, marked on brass cap



From which,

- A cedar, 16 ins. diam., bears N.61 $\frac{1}{4}$ °E., 60 lks. dist. marked T 37 N R 12 W S 24 B T
- A cedar, 10 ins. diam., bears S.12  $\frac{3}{4}$ °E., 149 lks. dist., marked T 37 N R 12 W S 25 B T
- A cedar, 6 ins. diam., bears S.65°W., 38 lks. dist. marked T 37 N R 12 W S 26 B T
- A cedar, 16 ins. diam., bears N.36 $\frac{1}{2}$ °W., 309 lks. dist., marked T 37 N R 12 W S 23 B T

Land; rolling.  
Soil; rocky, 3rd. rate.  
Timber; cedar.  
Undergrowth; sagebrush.

40.00  
80.04

N.89°57'E., on a random line bet. secs. 24 and 25.  
Set temp.  $\frac{1}{4}$  sec. cor.

Fall 12 lks. S. of the cor. of secs. 19, 24, 25 and 30 on E. bdy. of Tp., which is an iron post, 3 ins. diam., properly marked and set in a mound of stone, with a witness mound west of cor.

Thence

S.89°52'W., on a true line bet. secs. 24 and 25.  
Over rolling land, through scattering timber and undergrowth.

12.70  
14.60  
40.02

Desc. 164 ft. over W. slope.  
Road, bears N. and S.  
Wash, 10 lks. wide, course N.  
Asc. 67 ft. over E. slope.  
Set an iron post, 3 ft. long, 1 in. diam., 28 ins. in

## Subdivision of T.37 N., R.12 W.

Chains

the ground for  $\frac{1}{4}$  sec. cor. marked on brass cap
$$\begin{array}{r} \frac{1}{4} \\ \hline S\ 24 \\ S\ 25 \\ \hline 1924 \end{array}$$

From which,

A cedar, 10 ins. diam., bears N.  $9\frac{3}{4}^{\circ}$ W., 215 lks. dist., marked  $\frac{1}{4}$  S 24 B TA cedar, 20 ins. diam., bears S.  $67^{\circ}$ W., 89 lks. dist. marked  $\frac{1}{4}$  S 25 B T

80.04 The cor. of secs. 23, 24, 25 and 26.

Land; rolling.

Soil; rocky, 3rd. rate.

Timber; cedar.

Undergrowth; sagebrush.

N.  $0^{\circ}10'E.$ , bet. secs. 23 and 24.

Over rolling land, through scattering timber and undergrowth.

8.00 Desc. NW. slope.

15.00 Draw, course NE. Asc.

40.00 Set an iron post, 3 ft. long, 1 in. diam., 20 ins. in the ground to bed rock, supported in a mound of stone, for  $\frac{1}{4}$  sec. cor. marked on brass cap
$$\begin{array}{c} \frac{1}{4} \\ S\ 23 \quad | \quad S\ 24 \\ \hline 1924 \end{array}$$

From which,

A cedar, 24 ins. diam., bears S.  $83\frac{1}{4}^{\circ}$ E., 29 lks. dist. marked  $\frac{1}{4}$  S 24 B TA cedar, 12 ins. diam., bears S.  $83\frac{1}{2}^{\circ}$ W., 37 lks. dist. marked  $\frac{1}{4}$  S 23 B T

65.70 Desc. 75 ft. along E. slope to

73.20 Draw, course NE.

80.00 Desc. 57 ft. to

Set an iron post, 3 ft. long, 2 ins. diam., 30 ins. in the ground for cor. of secs. 13, 14, 23 and 24, marked on brass cap

$$\begin{array}{c} T37N\ R12W \\ S\ 14\ | \ S\ 13 \\ \hline S\ 23\ | \ S\ 24 \\ \hline 1924 \end{array}$$

From which,

A cedar, 14 ins. diam., bears N.  $30\frac{1}{2}^{\circ}$ E., 614 lks. dist., marked T 37 N R 12 W S 13 B TA cedar, 20 ins. diam., bears S.  $48\frac{3}{4}^{\circ}$ E., 621 lks. dist., marked T 37 N R 12 W S 24 B TA cedar, 6 ins. diam., bears S.  $20\frac{1}{2}^{\circ}$ W., 272 lks. dist., marked T 37 N R 12 W S 23 B TA cedar, 20 ins. diam., bears N.  $41\frac{1}{2}^{\circ}$ W., 320 lks. dist., marked T 37 N R 12 W S 14 B T

Land; rolling.

Soil; rocky, 3rd. rate.

Timber; cedar.

Undergrowth; sagebrush.

Subdivision of T.37 N., R.12 W.

Chains

40.00 N.89°52'E., on a random line bet. secs. 13 and 24.  
 Set temp.  $\frac{1}{4}$  sec. cor.  
 80.04 Fall 12 lks. N. of the cor. of secs. 13, 18, 19 and 24  
 on E. bdy. of Tp., described in Book "H".

Thence  
 S.89°57'W., on a true line bet. secs. 13 and 24.  
 Over rolling land, through scattering timber and under-  
 growth.

3.96 Wash, 6 lks. wide, course NW.  
 18.04 Road, bears N. and S.  
 18.94 Wash, 15 lks. wide, course N.  
 20.00 Reservoir, bears S. 8.70 chs. dist.  
 40.02 Set an iron post, 3 ft. long, 1 in. diam., 18 ins. in  
 the ground to bed rock, supported in a mound of stone,  
 for  $\frac{1}{4}$  sec. cor. marked on brass cap

$\frac{1}{4}$  S 13  
 S 24  
 1924

From which,  
 A cedar, 10 ins. diam., bears N.51°W., 95 lks. dist.  
 marked  $\frac{1}{4}$  S 13 B T  
 A cedar, 4 ins. diam., bears S.21°E., 68 lks. dist.  
 marked  $\frac{1}{4}$  S 24 B T

75.00 Draw, course N.  
 80.04 The cor. of secs. 13, 14, 23 and 24.

Land; rolling. Soil; rocky, 3rd. rate.  
 Timber; cedar. Undergrowth; sagebrush.

N.0°10'E., bet. secs. 13 and 14.  
 Over rolling land, through scattering timber and under-  
 growth.

40.00 Set an iron post, 3 ft. long, 1 in. diam., 28 ins. in  
 the ground for  $\frac{1}{4}$  sec. cor. marked on brass cap

$\frac{1}{4}$   
 S 14 | S 13  
 1924

From which,  
 A cedar, 16 ins. diam., bears S.18°E., 222 lks. dist.  
 marked  $\frac{1}{4}$  S 13 B T  
 A cedar, 8 ins. diam., bears S.40°W., 238 lks. dist.  
 marked  $\frac{1}{4}$  S 14 B T

49.70 Road, bears NE. and SW.  
 50.00 Draw, course NE.  
 55.00 Road, bears NE. and SW.  
 80.00 Set an iron post, 3 ft. long, 2 ins. diam., 6 ins. in  
 the ground to bed rock, with marked cross (+) stone  
 alongside, supported in a mound of stone, for cor. of  
 secs. 11, 12, 13 and 14, marked on brass cap

T37N R12W  
 S 11 | S 12  
 S 14 | S 13  
 1924

From which,  
 A cedar, 8 ins. diam., bears S.30 $\frac{1}{2}$ °E., 215 lks. dist.  
 marked T 37 N R 12 W S 13 B T  
 A cedar, 7 ins. diam., bears N.24 $\frac{1}{4}$ °W., 359 lks. dist.  
 marked T 37 N R 12 W S 11 B T

Land; rolling. Soil; rocky, 3rd. rate.  
 Timber; cedar.  
 Undergrowth; sagebrush.

Subdivision of T.37 N., R.12 W.

Chains N.89°57'E., on a random line bet. secs. 12 and 13.  
40.00 Set temp.  $\frac{1}{4}$  sec. cor.  
79.94 Fall 7 lks. N. of the cor. of secs. 7, 12, 13 and 18 on  
E. bdy. of Tp., described in Book "H".

Thence  
West, on a true line bet. secs. 12 and 13.  
Over rolling land, through scattering timber and under-  
growth.

39.97 Set an iron post, 3 ft. long, 1 in. diam., 28 ins. in the  
ground for  $\frac{1}{4}$  sec. cor. marked on brass cap

$\frac{1}{4}$  S 12  
S 13  
1924

Dig pits 18 x 18 x 12 ins. one each on line E. and W.  
of cor. 3 ft. dist.

46.50 Draw, course N.  
59.24 Road, bears NE. and SW.  
79.94 The cor. of secs. 11, 12, 13 and 14.

Land; rolling. Soil; rocky, 3rd. rate.  
Timber; cedar. Undergrowth; sagebrush.

---

N.0°10'E., bet. secs. 11 and 12.  
Over rolling land, through scattering timber and under-  
growth.

40.00 Set an iron post, 3 ft. long, 1 in. diam., 24 ins. in  
the ground for  $\frac{1}{4}$  sec. cor. marked on brass cap

$\frac{1}{4}$   
S 11 | S 12  
1924

From which,  
A cedar, 5 ins. diam., bears N.84°E., 155 lks. dist.  
marked  $\frac{1}{4}$  S 12 B T  
Raise a mound of stone, 2 ft. base, 1 $\frac{1}{2}$  ft. high W. of  
cor.

45.00 Desc.  
80.00 Draw, course E. Asc. 130 ft.  
Set an iron post, 3 ft. long, 2 ins. diam., 16 ins. in  
the ground to bed rock, supported in a mound of stone,  
for cor. of secs. 1, 2, 11 and 12, marked on brass cap

T37N R12W  
S 2 | S 1  
S 11 | S 12  
1924

From which,  
A cedar, 6 ins. diam., bears N.37 $\frac{1}{2}$ °E., 292 lks. dist.  
marked T 37 N R 12 W S 1 B T  
A cedar, 8 ins. diam., bears S.87 $\frac{1}{2}$ °E., 159 lks. dist.  
marked T 37 N R 12 W S 12 B T  
A cedar, 16 ins. diam., bears S.12 $\frac{1}{2}$ °W., 158 lks. dist.  
marked T 37 N R 12 W S 11 B T  
A cedar, 12 ins. diam., bears N.46 $\frac{1}{2}$ °W., 81 lks. dist.  
marked T 37 N R 12 W S 2 B T

Land; rolling.  
Soil; rocky, 3rd. rate.  
Timber; cedar.  
Undergrowth; sagebrush.

Subdivision of T.37 N., R.12 W.

Chains East, on a random line bet. secs. 1 and 12.  
 40.00 Set temp.  $\frac{1}{4}$  sec. cor.  
 79.90 Fall 7 lks. N. of the cor. of secs. 1; 6, 7 and 12 on  
 E. bdy. of Tp., described in Book "H".

Thence  
 N.89°57'W., on a true line bet. secs. 1 and 12.  
 Over rolling land, through scattering timber and under-  
 growth.

20.30 Wash, 15 lks. wide, course N.

23.30 Road, bears N. and S.

39.95 Set an iron post, 3 ft. long, 1 in. diam., 26 ins. in  
 the ground for  $\frac{1}{4}$  sec. cor. marked on brass cap

$\frac{1}{4}$  S 1  
 S 12  
 1924

Dig pits 18 x 18 x 12 ins. one each on line E. and W.  
 of cor. 3 ft. dist.

Asc. over E. slope.

73.50 Draw, course NE. Asc.

79.90 The cor. of secs. 1, 2, 11 and 12.

Land; rolling.  
 Soil; rocky, 3rd. rate.  
 Timber; cedar.  
 Undergrowth; sagebrush.

40.00 N.0°10'E., on a random line bet. secs. 1 and 2.  
 Set temp.  $\frac{1}{4}$  sec. cor.

80.36 Fall 14 lks. E. of the cor. of secs. 1, 2, 35 and 36,  
 on N. bdy. of Tp., hereinbefore described.

Thence  
 S.0°4'W., on a true line bet. secs. 1 and 2.  
 Over rolling land, through scattering timber and under-  
 growth.

40.36 Set an iron post, 3 ft. long, 1 in. diam., 30 ins. in the  
 ground for  $\frac{1}{4}$  sec. cor. marked on brass cap

$\frac{1}{4}$   
 S 2 | S 1  
 1924

From which,  
 A cedar, 6 ins. diam., bears N.64 $\frac{1}{2}$ °E., 191 lks. dist.  
 marked  $\frac{1}{4}$  S 1 B T  
 A cedar, 6 ins. diam., bears N.47 $\frac{3}{4}$ °W., 113 lks. dist.  
 marked  $\frac{1}{4}$  S 2 B T

80.36 The cor. of secs. 1, 2, 11 and 12.

Land; rolling.  
 Soil; rocky, 3rd. rate.  
 Timber; cedar.  
 Undergrowth; sagebrush.


Subdivision of T.37 N., R.12 W.

Chains

From the S.O. of secs. 34 and 35 on S. bdy. of Tp., here-  
inbefore described,  
N.0°10'E., bet. secs. 34 and 35.  
Over rolling land, through scattering timber and under-  
growth.

10.20  
12.80  
20.00  
29.00  
40.00

Wash, 20 lks. wide, course NE.  
Road, bears NE. to St. George and SW. to Poverty Mt.  
Asc. 60 ft. over SE. slope to  
Top of small knoll. Desc. gradual NE. slope.  
Set an iron post, 3 ft. long, 1 in. diam., 30 ins. in  
the ground for  $\frac{1}{4}$  sec. cor. marked on brass cap




From which,

A cedar, 12 ins. diam., bears N.50°E., 144 lks. dist.  
marked  $\frac{1}{4}$  S 35 B T  
A cedar, 14 ins. diam., bears S.49°W., 116 lks. dist.  
marked  $\frac{1}{4}$  S 34 B T

80.00

Set an iron post, 3 ft. long, 2 ins. diam., 30 ins. in  
the ground for cor. of secs. 26, 27, 34 and 35, marked  
on brass cap



From which,

A cedar, 4 ins. diam., bears N.71 $\frac{1}{2}$ °E., 256 lks. dist.  
marked B 37 R 12 W S 26 B T  
A cedar, 4 ins. diam., bears S.21 $\frac{1}{2}$ °E., 207 lks. dist.  
marked B T  
A cedar, 10 ins. diam., bears S.4 $\frac{1}{4}$ °W., 260 lks. dist.  
marked T 37 N R 12 W S 34 B T  
A cedar, 4 ins. diam., bears N.60°W., 103 lks. dist.  
marked B T

Land; rolling.  
Soil; rocky, 3rd. rate.  
Timber; cedar,  
Undergrowth; sagebrush.


40.00  
80.04

East, on a random line, bet. secs. 26 and 35.  
Set temp.  $\frac{1}{4}$  sec. cor.  
Fall 2 lks. S. of the cor. of secs. 25, 26, 35 and 36.

Thence  
S.89°59'W., on a true line bet. secs. 26 and 35.  
Over rolling land, through scattering timber and under-  
growth.

36.64  
40.02

Wash, 10 lks. wide, course NW.  
Set an iron post, 3 ft. long, 1 in. diam., 30 ins. in the  
ground for  $\frac{1}{4}$  sec. cor. marked on brass cap



From which,

A cedar, 10 ins. diam., bears N.25 $\frac{1}{2}$ °W., 31 lks. dist.  
marked  $\frac{1}{4}$  S 26 B T  
A cedar, 12 ins. diam., bears S.4 $\frac{1}{4}$ °W., 71 lks. dist.  
marked  $\frac{1}{4}$  S 35 B T

44.20  
70.20  
70.90  
80.04


Low ridge, bears N. and S.  
Wash, 20 lks. wide, course NE.  
Road, bears NE. and SW.  
The cor. of secs. 26, 27, 34 and 35.

Subdivision of T.37 N., R.12 W.

Chains Land; rolling.  
Soil; rocky, 3rd. rate.  
Timber; cedar.  
Undergrowth; sagebrush.


N.0°10'E., bet. secs. 26 and 27.  
Over rolling land, through scattering timber and dense  
sagebrush.

40.00 Set an iron post, 3 ft. long, 1 in. diam., 30 ins. in the  
ground for  $\frac{1}{4}$  sec. cor. marked on brass cap



From which,  
A cedar, 16 ins. diam., bears S.25 3/4°E., 180 lks.  
dist.; marked  $\frac{1}{4}$  S 26 B T  
A cedar, 6 ins. diam., bears S.66 1/4°W., 230 lks. dist.  
marked  $\frac{1}{4}$  S 27 B T

80.00 Over level land.  
Set an iron post, 3 ft. long, 2 ins. diam., 30 ins. in  
the ground with marked cross (+) stone alongside base  
of post, for cor. of secs. 22, 23, 26 and 27, marked  
on brass cap




From which,  
A cedar, 14 ins. diam., bears S.85 1/4°W., 473 lks. dist.  
marked T 37 N R 12 W S 27 B T  
A cedar, 16 ins. diam., bears N.72 1/4°W., 527 lks. dist.  
marked T 37 N R 12 W S 22 B T

Land; rolling.  
Soil; rocky, 3rd. rate.  
Timber; cedar.  
Undergrowth; sagebrush.

40.00 N.89°59'E., on a random line bet. secs. 23 and 26.  
Set temp.  $\frac{1}{4}$  sec. cor.  
80.10 Fall 9 lks. N. of the cor. of secs. 23, 24, 25 and 26.

Thence  
N.89°57'W., on a true line bet. secs. 23 and 26.  
Over rolling land, through scattering timber and under-  
growth.

7.40 Wash, 10, lks. wide, course N.  
40.05 Set an iron post, 3 ft. long, 1 in. diam., 24 ins. in the  
ground for  $\frac{1}{4}$  sec. cor. marked on brass cap



From which,  
A cedar, 8 ins. diam., bears N.57 3/4°E., 77 lks. dist.  
marked  $\frac{1}{4}$  S 23 B T  
A cedar, 8 ins. diam., bears S.8°W., 30 lks. dist.  
marked  $\frac{1}{4}$  S 26 B T

77.90 Desc. 120 ft. over W. slope.  
Road, bears N. and S.  
78.60 Wash, 20 lks. wide, course N.  
80.10 The cor. of secs. 22, 23, 26 and 27.

Subdivision of T.37 N., R.12 W.

Chains

Land; rolling.  
Soil; rocky, 3rd. rate.  
Timber; cedar.  
Undergrowth; sagebrush.

N.0°10'E., bet. secs. 22 and 23.  
Over rolling land, through scattering timber and undergrowth.

40.00 Set an iron post, 3 ft. long, 1 in. diam., 14 ins. in the ground to bed rock, supported in a mound of stone, for  $\frac{1}{4}$  sec. cor. marked on brass cap

$\frac{1}{4}$   
S 22 | S 23  
1924

From which,  
A cedar, 10 ins. diam., bears N.56 $\frac{1}{4}$ °E., 42 lks. dist. marked  $\frac{1}{4}$  S 23 B T  
A cedar, 6 ins. diam., bears S.49°E., 18 lks. dist. marked  $\frac{1}{4}$  S 22 B T

80.00 asc. 180 ft. over SE. slope to  
Set an iron post, 3 ft. long, 2 ins. diam., 14 ins. in the ground to bed rock, supported in a mound of stone, for cor. of secs. 14, 15, 22 and 23, marked on brass cap

T37N R12W  
S 15 | S 14  
S 22 | S 23  
1924

From which,  
A cedar, 10 ins. diam., bears N.37  $\frac{3}{4}$ °E., 96 lks. dist., marked T 37 N R 12 W S 14 B T  
A cedar, 26 ins. diam., bears S.21 $\frac{1}{4}$ °E., 105 lks. dist. marked T 37 N R 12 W S 23 B T  
A cedar, 8 ins. diam., bears S.37°W., 170 lks. dist. marked T 37 N R 12 W S 22 B T  
A cedar, 14 ins. diam., bears N.40°W., 114 lks. dist. marked T 37 N R 12 W S 15 B T

Land; rolling.  
Soil; rocky, 3rd. rate.  
Timber; cedar.  
Undergrowth; sagebrush.

40.00 S.89°57'E., on a random line bet. secs. 14 and 23.  
80.04 Set temp.  $\frac{1}{4}$  sec. cor.  
Fall 2 lks. S. of the cor. of secs. 13, 14, 23 and 24.

Thence  
N.89°58'W., on a true line bet. secs. 14 and 23.  
Over rolling land, through scattering timber and undergrowth.

12.74 Asc. 80 ft. over E. slope.  
Fence, bears N. and S.  
Desc. 110 ft. over W. slope.

38.54 Draw, course NE.  
39.74 Fence, bears SE. and NW.

40.02 Set an iron post, 3 ft. long, 1 in. diam., 18 ins. in the ground to bed rock, supported in a mound of stone, for  $\frac{1}{4}$  sec. cor. marked on brass cap

$\frac{1}{4}$  S 14  
S 23  
1924

From which,  
A cedar, \_\_\_ ins. diam., bears N.36°E., 130 lks. dist.

Subdivision of T.37 N., R.12 W.

Chains


marked  $\frac{1}{4}$  S 14 B T  
 A cedar, ins. diam., bears S.69  $3/4^\circ$ E., 694 lks.  
 dist., marked  $\frac{1}{4}$  S 23 B T  
 Fence cor., bears N.49  $1/2^\circ$ W., 57 lks. dist.  
 NE. cor. of house, bears N.37  $1/2^\circ$ W., 252 lks. dist.  
 The Sullivan Dam, bears S. 278.lks. dist.

41.11 Fence, bears N. and S.  
 41.77 Road, bears N. and S.  
 Asc. 230 ft. over E. slope.  
 80.04 The cor. of secs. 14, 15, 22 and 23.

Land; rolling.  
 Soil; rocky, 3rd. rate.  
 Timber; cedar.  
 Undergrowth; sagebrush.


N.0°10'E., bet. secs. 14 and 15.  
 Over rolling land, through scattering timber and undergrowth.

20.00 Draw, course NE.  
 40.00 Set an iron post, 3 ft. long, 1 in. diam., 28 ins. in the ground for  $\frac{1}{4}$  sec. cor. marked on brass cap



From which,  
 A cedar, 12 ins. diam., bears N.35  $1/4^\circ$ E., 47 lks. dist.  
 marked  $\frac{1}{4}$  S 14 B T  
 A cedar, 16 ins. diam., bears N.60°W., 110 lks. dist.  
 marked  $\frac{1}{4}$  S 15 B T

80.00 Set an iron post, 3 ft. long, 2 ins. diam., 26 ins. in the ground for cor. of secs. 10, 11, 14 and 15, marked on brass cap



From which,  
 A cedar, 10 ins. diam., bears N.16  $1/4^\circ$ E., 96 lks. dist.  
 marked T 37 N R 12 W S 11 B T  
 A cedar, 12 ins. diam., bears S.50  $1/4^\circ$ E., 54 lks. dist.  
 marked T 37 N R 12 W S 14 B T  
 A cedar, 8 ins. diam., bears S.13°W., 74 lks. dist.  
 marked T 37 N R 12 W S 15 B T  
 A cedar, 8 ins. diam., bears N.50  $1/4^\circ$ W., 77 lks. dist.  
 marked T 37 N R 12 W S 10 B T

Land; rolling.  
 Soil; rocky, 3rd. rate.  
 Timber; cedar.  
 Undergrowth; sagebrush.

40.00 S.89°58'E., on a random line bet. secs. 11 and 14.  
 79.98 Set temp.  $\frac{1}{4}$  sec. cor.  
 Fall 7 lks. S. of the cor. of secs. 11, 12, 13 and 14.

Thence  
 S.89°59'W., on a true line bet. secs. 11 and 14.  
 Over rolling land, through scattering timber and undergrowth.

Asc. 190 ft. over E. slope.  
 39.99 Set an iron post, 3 ft. long, 1 in. diam., 26 ins. in the ground for  $\frac{1}{4}$  sec. cor. marked on brass cap

Subdivision of T.37 N., R.12 W.

Chains

S 11  
S 14  
1924

From which,

A cedar, 10 ins. diam., bears N.4 $\frac{1}{4}$ °W., 148 lks. dist.  
marked  $\frac{1}{4}$  S 11 B T

A cedar, 12 ins. diam., bears S.13°E., 131 lks. dist.  
marked  $\frac{1}{4}$  S 14 B T

67.00  
79.98

Draw, course N.  
The cor. of secs. 10, 11, 14 and 15.

Land; rolling.  
Soil; rocky, 3rd. rate.  
Timber; cedar.  
Undergrowth; sagebrush.

---

N.0°10'E., bet. secs. 10 and 11.  
Over rolling land, through scattering timber and under-  
growth.

40.00

Set an iron post, 3 ft. long, 1 in. diam., 28 ins. in the  
ground for  $\frac{1}{4}$  sec. cor. marked on brass cap

$\frac{1}{4}$   
S 10 | S 11  
1924

From which,

A cedar, 14 ins. diam., bears N.72  $\frac{3}{4}$ °E., 209 lks.  
dist., marked  $\frac{1}{4}$  S 11 B T

A cedar, 5 ins. diam., bears N.25°W., 150 lks. dist.  
marked  $\frac{1}{4}$  S 20 B T

47.30  
80.00

Wash, 6 lks. wide, course NE.  
Set an iron post, 3 ft. long, 2 ins. diam., 24 ins. in  
the ground for cor. of secs. 2, 3, 10 and 11, marked  
on brass cap

T37N R12W  
S 3 | S 2  
S 10 | S 11  
1924

From which,

A cedar, 24 ins. diam., bears N.28  $\frac{3}{4}$ °E., 64 lks.  
dist., marked T 37 N R 12 W S 2 B T

A cedar, 24 ins. diam., bears S.17  $\frac{3}{4}$ °E., 47 lks.  
dist., marked T 37 N R 12 W S 11 B T

A cedar, 20 ins. diam., bears S.43 $\frac{1}{4}$ °W., 90 lks. dist.  
marked T 37 N R 12 W S 10 B T

A cedar, ins. diam., bears N.48 $\frac{1}{4}$ °W., 87 lks. dist.  
marked T 37 N R 12 W S 3 B T

Land; rolling.  
Soil; rocky, 3rd. rate.  
Timber; cedar.  
Undergrowth; sagebrush.

40.00  
80.16

---

N.89°59'E., on a random line bet. secs. 2 and 11.  
Set temp.  $\frac{1}{4}$  sec. cor.  
Fall 14 lks. S. of the cor. of secs. 1, 2, 11 and 12.

Thence  
S.89°53'W., on a true line bet. secs. 2 and 11.  
Over rolling land, through scattering timber and under-  
growth.

40.08

Set an iron post, 3 ft. long, 1 in. diam., 12 ins. in  
the ground to bed rock, supported in a mound of stone,  
for  $\frac{1}{4}$  sec. cor. marked on brass cap

Subdivision of T.37 N., R.12 W.

Chains S 2  
S 11  
1924

From which,  
 A cedar, 10 ins. diam., bears N.8½°W., 308 lks. dist.  
 marked ¼ S 2 B T  
 A cedar, 26 ins. diam., bears S.6°W., 47 lks. dist.  
 marked ¼ S 11 B T


80.16 The cor. of secs. 2, 3, 10 and 11.

Land; rolling.  
 Soil; rocky, 3rd. rate.  
 Timber; cedar.  
 Undergrowth; sagebrush.

40.00 N.0°4'E., on a random line bet. secs. 2 and 3.  
 Set temp. ¼ sec. cor.  
 80.40 Fall 7 lks. W. of the cor. of secs. 2, 3, 34 and 35 on  
 N. bdy. of Tp., hereinbefore described.

Thence  
 S.0°7'W., on a true line bet. secs. 2 and 3.  
 Over rolling land, through scattering timber and under-  
 growth.

40.40 Set an iron post, 3 ft. long, 1 in. diam., 4 ins. in the ground to bed rock, supported in a mound of stone, for ¼ sec. cor. marked on brass cap




From which,  
 A cedar, 10 ins. diam., bears S.61 ¾°E., 82 lks. dist., marked ¼ S 2 B T  
 A cedar, 8 ins. diam., bears S.71°W., 27 lks. dist. marked ¼ S 3 B T

80.40 The cor. of secs. 2, 3, 10 and 11.

Land; rolling.  
 Soil; rocky, 3rd. rate.  
 Timber; cedar.  
 Undergrowth; sagebrush.

From the S.C. of secs. 33 and 34 on S. bdy. of Tp., hereinbefore described,  
 N.0°9'E., bet. secs. 33 and 34.  
 Over rolling land, through heavy timber and dense under-  
 growth.

17.50 Draw, course NW. Asc.  
 28.00 Leave heavy and enter scattering timber.  
 40.00 Set an iron post, 3 ft. long, 1 in. diam., 12 ins. in the ground to bed rock, supported in a mound of stone, for ¼ sec. cor. marked on brass cap



From which,  
 A cedar, 6 ins. diam., bears N.43°E., 110 lks. dist. marked ¼ S 34 B T  
 A cedar, 16 ins. diam., bears S.63°W., 108 lks. dist. marked ¼ S 33 B T

## Subdivision of T.37 N., R.12 W.

Chains

49.20

80.00

Point of spur, slopes W. Desc. 100 ft. to  
Set an iron post, 3 ft. long, 2 ins. diam., 28 ins. in  
the ground for cor. of secs. 27, 28, 33 and 34, marked  
on brass cap

T37N R12W  
S 28 | S 27  
S 33 | S 34  
1924

From which,

A cedar, 7 ins. diam., bears N.25 $\frac{1}{4}$ °E., 371 lks. dist.  
marked T 37 N R 12 W S 27 B T

A cedar, 6 ins. diam., bears S.63 3/4°E., 204 lks.  
dist., marked T 37 N R 12 W S 34 B T

A cedar, 14 ins. diam., bears S.52 3/4°W., 142 lks.  
dist., marked T 37 N R 12 W S 33 B T

A cedar, 16 ins. diam., bears N.77 $\frac{1}{2}$ °W., 128 lks.  
dist., marked T 37 N R 12 W S 28 B T

Land; rolling.

Soil; clay, rocky, 3rd. and 4th. rates.

Timber; cedar.

Undergrowth; sagebrush.

40.00

79.90

East, on a random line bet. secs. 27 and 34.

Set temp.  $\frac{1}{4}$  sec. cor.

Fall 4 lks. N. of the cor. of secs. 26, 27, 34 and 35.

Thence

N.89°58'W., on a true line bet. secs. 27 and 34.

Over rolling land, through scattering timber and under-  
growth.

Asc. 140 ft. over E. slope.

39.95

Set an iron post, 3 ft. long, 1 in. diam., 6 ins. in the  
ground to bed rock, supported in a mound of stone, for  
 $\frac{1}{4}$  sec. cor. marked on brass cap

S 27  
S 34  
1924

From which,

A cedar, 6 ins. diam., bears N.85°E., 101 lks. dist.  
marked  $\frac{1}{4}$  S 27 B T

A cedar, 6 ins. diam., bears S.36 $\frac{1}{4}$ °E., 45 lks. dist.  
marked  $\frac{1}{4}$  S 34 B T

40.00

43.20

67.40

79.90

Ridge bears N. and S. Desc.

Draw, course NE. Asc. 40 ft.

Desc. 120 ft. over W. slope.

The cor. of secs. 27, 28, 33 and 34.

Land; rolling.

Soil; rocky, 3rd. rate.

Timber; cedar.

Undergrowth; sagebrush.

15.95

40.00

N.0°9'E., bet. secs. 27 and 28.

Over rolling land, through scattering timber and dense  
undergrowth.

Wash, 8 lks. wide, course NE.

Set an iron post, 3 ft. long, 1 in. diam., 26 ins. in the  
ground, for  $\frac{1}{4}$  sec. cor. marked on brass cap

S 28 | S 27  
1924

From which,

A cedar, 12 ins. diam., bears N.89 3/4°E., 77 lks.

## Subdivision of T.37 N., R.12 W.

Chains	marked $\frac{1}{4}$ S 27 B T A cedar, 20 ins. diam., bears S. $31\frac{1}{4}^{\circ}$ W., 38 lks. dist. marked $\frac{1}{4}$ S 28 B T
52.70 80.00	Wash, 8 lks. wide, course NW. Asc. Set an iron post, 3 ft. long, 2 ins. diam., 12 ins. in the ground to bed rock, supported in a mound of stone, for cor. of secs. 21, 22, 27 and 28, marked on brass cap  T37N, R12W S 21 S 22 S 28 S 27 1924  From which, A cedar, 6 ins. diam., bears N. $73\frac{3}{4}^{\circ}$ E., 60 lks. dist., marked T 37 N R 12 WS 22 B T A cedar, 5 ins. diam., bears S. $7\frac{1}{2}^{\circ}$ E., 99 lks. dist. marked B 37 N R 12 WS 27 B T A cedar, 16 ins. diam., bears S. $79^{\circ}$ W., 146 lks. dist. marked T 37 N R 12 W S 28 B T A cedar, 5 ins. diam., bears N. $34\frac{1}{2}^{\circ}$ W., 154 lks. dist. marked B T  Land; rolling. Soil; rocky, 3rd. rate. Timber; cedar. Undergrowth; sagebrush.
40.00 79.86	S. $89^{\circ}58'$ E., on a random line bet. secs. 22 and 27. Set temp. $\frac{1}{4}$ sec. cor. Fall 7 lks. S. of the cor. of secs. 22, 23, 26 and 27.  Thence S. $89^{\circ}59'$ W., on a true line bet. secs. 22 and 27. Over rolling land, through scattering timber and undergrowth. Asc. 230 ft. over E. slope to Set an iron post, 3 ft. long, 1 in. diam., 12 ins. in the ground to bed rock, supported in a mound of stone, for $\frac{1}{4}$ sec. cor. marked on brass cap  $\frac{1}{4}$ S 22 S 27 1924  From which, A cedar, 7 ins. diam., bears N. $42\frac{3}{4}^{\circ}$ E., 24 lks. dist., marked $\frac{1}{4}$ S 22 B T A cedar, 14 ins. diam., bears S. $44\frac{1}{2}^{\circ}$ W., 80 lks. dist., marked $\frac{1}{4}$ S 27 B T
39.93	Desc. 43 ft. over W. slope to Head of draw, course SW. Desc. 46 ft. to Wash, 10 lks. wide, course N. Asc. 46 ft. over E. slope. The cor. of secs. 21, 22, 27 and 28.
49.86 73.70 79.86	Land; rolling. Soil; rocky, 3rd. rate. Timber; cedar. Undergrowth; sagebrush.
33.45 40.00	N. $0^{\circ}9'$ E., bet. secs. 21 and 22. Over rolling land, through scattering timber and dense undergrowth. Desc. 60 ft. over N. slope to Wash, 10 lks. wide, course NW. Asc. Set an iron post, 3 ft. long, 1 in. diam., 28 ins. in the ground for $\frac{1}{4}$ sec. cor. marked on brass cap

Subdivision of T.37 N., R.12 W.

Chains

$\frac{1}{4}$   
S 21  $\frac{1}{4}$  S 22  
1924.

From which,  
A cedar, 12 ins. diam., bears S.63°E., 73 lks. dist.  
marked  $\frac{1}{4}$  S 22 B T  
A cedar, 6 ins. diam., bears S.28  $\frac{3}{4}$ °W., 65 lks.  
dist., marked  $\frac{1}{4}$  S 21 B T

45.65  
49.22  
58.50  
76.44  
80.00

Asc. 23 ft. over S. slope.  
Spur, slopes W. Desc. 24 ft. over NE. slope.  
Draw, course W. Asc. 50 ft. to  
Spur, slopes W. Desc. 80 ft.  
Wash, 8 lks. wide, course W.  
Asc. 13 ft..  
Set an iron post, 3 ft. long, 2 ins. diam., 26 ins. in  
the ground for cor. of secs. 15, 16, 21 and 22, marked  
on brass cap

T37N R12W  
S 16 S 15  
S 21 S 22  
1924

From which,  
A cedar, 5 ins. diam., bears N.57 $\frac{1}{2}$ °E., 142 lks. dist.  
marked B T 7 1 2 15 B T  
A cedar, 8 ins. diam., bears S.47°E., 245 lks. dist.  
marked T 37 N R 12 W S 22 B T  
A cedar, 5 ins. diam., bears S.73 $\frac{1}{2}$ °W., 248 lks. dist.  
marked B T  
A cedar, 5 ins. diam., bears N.14°W., 98 lks. dist.  
marked B T

Land; rolling.  
Soil; rocky, 3rd. rate.  
Timber; cedar.  
Undergrowth; sagebrush.

40.00  
79.98

N.89°59'E., on a random line bet. secs. 15 and 22.  
Set temp.  $\frac{1}{4}$  sec. cor.  
Fall 5 lks. N. of the cor. of secs. 14, 15, 22 and 23.

Thence  
N.89°59'W., on a true line bet. secs. 15 and 22.  
Over rolling land, through scattering timber and under-  
growth.

39.99

Desc. 120 ft. to  
Set an iron post, 3 ft. long, 1 in. diam., 30 ins. in  
the ground for  $\frac{1}{4}$  sec. cor. marked on brass cap

$\frac{1}{4}$  S 15  
S 22  
1924

From which,  
A cedar, 6 ins. diam., bears N.5 $\frac{1}{2}$ °E., 73 lks. dist.  
marked  $\frac{1}{4}$  S 15 B T  
A cedar, 14 ins. diam., bears S.17°E., 125 lks. dist.  
marked  $\frac{1}{4}$  S 22 B T

52.08  
52.80  
59.50  
79.98


Road, bears SE. and NW.  
Draw, course NW. Asc. 34 ft. to  
Spur, slopes NW. Desc. 46 ft. to  
The cor. of secs. 15, 16, 21 and 22.

Land; rolling.  
Soil; rocky, 3rd. rate.  
Timber; cedar.  
Undergrowth; sagebrush.

Subdivision of T.37 N., R.12 W.


Chains N.0°9'E., bet. secs, 15 and 16.  
Over rolling land, through scattering timber and undergrowth.

14.00 Draw, course NW.  
17.20 Road,, bears SE. and NW,  
31.00 Draw, course NW. Asc. SW. slope.  
40.00 Set an iron post, 3 ft. long, 2 in. diam., 3 ins. in the ground to bed rock, supported in a mound of stone for  $\frac{1}{4}$  sec. cor. marked on brass cap



From which,  
A cedar, 10 ins. diam., bears N.24°E., 158 lks. dist. marked  $\frac{1}{4}$  S 15 B T.  
A cedar, 8 ins. diam., bears N.25°W., 93 lks. dist. marked  $\frac{1}{4}$  S 16 B T

41.50 Draw, course W. Asc. 60 ft.  
50.00 Spur, slopes W. Desc. 63 ft.  
56.50 Draw, course NW. Asc. 86 ft. over S. slope.  
74.00 Top of ascent. Desc.  
80.00 Set an iron post, 3 ft. long, 2 ins. diam., 8 ins. in the ground to bed rock, supported in a mound of stone, for cor. of secs. 9, 10, 15 and 16, marked on brass cap




From which,  
A cedar, 10 ins. diam., bears N.18  $\frac{3}{4}$ °E., 173 lks. dist., marked T 37 N R 12 W S 10 B T  
A cedar, 6 ins. diam., bears S.8  $\frac{1}{4}$ °E., 66 lks. dist. marked T 37 N R 12 W S 15 B T  
A cedar, 8 ins. diam., bears S.43  $\frac{3}{4}$ °W., 88 lks. dist., marked T 37 N R 12 W S 16 B T  
A cedar, 8 ins. diam., bears N.83  $\frac{1}{4}$ °W., 91 lks. dist. marked T 37 N R 12 W S 9 B T

Land; rolling.  
Soil; rocky, 3rd. rate.  
Timber; cedar.  
Undergrowth; sagebrush.

40.00 S.89°59'E., on a random line bet. secs. 10 and 15.  
79.98 Set temp.  $\frac{1}{4}$  sec. cor.  
Fall 2 lks. N. of the cor. of secs. 10, 11, 14 and 15,

Thence  
N.89°58'W., on a true line bet. secs. 10 and 15.  
Over rolling land, through scattering timber and undergrowth.

7.80 Desc. 58 ft. over W. slope.  
20.00 Draw, course N. Asc. 90 ft. over NE. slope.  
35.50 Top of ascent.  
39.99 Draw, course NW. Asc.  
Set an iron post, 3 ft. long, 1 in. diam., 12 ins. in the ground to bed rock, supported in a mound of stone, for  $\frac{1}{4}$  sec. cor. marked on brass cap



From which,  
A cedar, 16 ins. diam., bears N.0°30'E., 104 lks. dist., marked  $\frac{1}{4}$  S 10 B T

Subdivision of T.37 N., R.12 W.


Chains A cedar, 12 ins. diam., bears S.13°E., 47 lks. dist.  
marked  $\frac{1}{4}$  S 15 B T

50.00 Desc. 54 ft. to  
65.70 Draw, course NW. Asc.  
79.98 The cor. of secs. 9, 10, 15 and 16.

Land; rolling.  
Soil; rocky, 3rd. rate.  
Timber; cedar.  
Undergrowth; sagebrush.


N.0°9'E., bet. secs. 9 and 10.  
Over rolling land, through scattering timber and under-  
growth.

40.00 Set an iron post, 3 ft. long, 1 in. diam., 28 ins. in  
the ground for  $\frac{1}{4}$  sec. cor. marked on brass cap



From which,  
A cedar, 7 ins. diam., bears N.25 $\frac{1}{2}$ °E., 121 lks. dist.  
marked  $\frac{1}{4}$  S 10 B T  
A cedar, 8 ins. diam., bears S.67  $\frac{3}{4}$ °W., 344 lks.  
dist., marked  $\frac{1}{4}$  S 9 B T

47.50 Draw, course NW. Asc. 46 ft. over SW. slope.  
78.00 Desc. 23 ft. to  
80.00 Set an iron post, 3 ft. long, 2 ins. diam., 24 ins. in  
the ground for cor. of secs. 3, 4, 9 and 10, marked  
on brass cap




From which,  
A cedar, 8 ins. diam., bears N.22  $\frac{3}{4}$ °E., 28 lks. dist.  
marked T 37 N R 12 W S 3 B T  
A cedar, 20 ins. diam., bears S.35°E., 110 lks. dist.  
marked T 37 N R 12 W S 10 B T  
A cedar, 12 ins. diam., bears S.73 $\frac{1}{4}$ °W., 189 lks. dist.  
marked T 37 N R 12 W S 9 B T  
A cedar, 20 ins. diam., bears N.63 $\frac{1}{4}$ °W., 117 lks. dist.  
marked T 37 N R 12 W S 4 B T

Land; rolling.  
Soil; rocky, 3rd. rate.  
Timber; cedar.  
Undergrowth; sagebrush.

40.00 S.89°58'E., on a random line bet. secs. 3 and 10.  
Set temp.  $\frac{1}{4}$  sec. cor.  
80.02 Fall 8 lks. S. of the cor. of secs. 2, 3, 10 and 11.

Thence  
S.89°59'W., on a true line bet. secs. 3 and 10.  
Over rolling land, through scattering timber and under-  
growth.

40.01 Set an iron post, 3 ft. long, 1 in. diam., 28 ins. in  
the ground for  $\frac{1}{4}$  sec. cor. marked on brass cap



From which,

Subdivision of T.37 N., R.12 W.

Chains A cedar, 6 ins. diam., bears N.30°E., 76 lks. dist.  
marked  $\frac{1}{4}$  S 3 B T  
A cedar, 20 ins. diam., bears S.40°E., 33 lks. dist.  
marked  $\frac{1}{4}$  S 10 B T

80.02 The cor. of secs. 3, 4, 9 and 10.

Land; rolling.  
Soil; rocky, 4th. rate.  
Timber; cedar.  
Undergrowth; sagebrush.

40.00 N.0°6'E., on a random line bet. secs. 3 and 4.  
Set temp.  $\frac{1}{4}$  sec. cor.

80.27 Fall 9 lks. E. of the cor. of secs. 3, 4, 33 and 34 on  
N. bdy. of Tp., hereinbefore described.

Thence  
S.0°2'W., on a true line bet. secs. 3 and 4.  
Over rolling land, through scattering timber and under-  
growth.

29.87 Draw, course W.

40.27 Set an iron post, 3 ft. long, 1 in. diam., 4 ins. in the  
ground to bed rock, supported in a mound of stone, for  
 $\frac{1}{4}$  sec. cor. marked on brass cap

S 4 | S 3

1924

From which,

A cedar, 6 ins. diam., bears N.53 3/4°E., 51 lks.  
dist., marked  $\frac{1}{4}$  S 3 B T

A cedar, 20 ins. diam., bears S.86 1/4°W., 58 lks. dist.  
marked  $\frac{1}{4}$  S 4 B T

80.27 The cor. of secs. 3, 4, 9 and 10.

Land; rolling.  
Soil; rocky, 3rd. rate.  
Timber; cedar.  
Undergrowth; sagebrush.

From the S.C. of secs. 32 and 33 on S. bdy. of Tp., here-  
inbefore described,

N.0°8'E., bet. secs. 32 and 33.

Over rolling land, through heavy timber and dense under-  
growth. Desc.

7.18 Wash, 10 lks. wide, course NE.

Asc. 50 ft.

13.50 Point of spur, slopes NE. Desc. 34 ft.

22.50 Wash, 20 lks. wide, course E. Asc. 34 ft.

29.50 Spur, slopes E. Desc. 30 ft.

40.00 Set an iron post, 3 ft. long, 1 in. diam., 14 ins. in  
the ground to bed rock, supported in a mound of stone,  
for  $\frac{1}{4}$  sec. cor. marked on brass cap

S 32 | S 33

1924

From which,

A cedar, 6 ins. diam., bears N.19 1/2°E., 51 lks. dist.  
marked  $\frac{1}{4}$  S 33 B T

A cedar, 20 ins. diam., bears N.72 1/2°W., 89 lks. dist.  
marked  $\frac{1}{4}$  S 32 B T

Subdivision of T.37 N., R.12 W.

Chains  
55.00  
74.90  
80.00

Asc. over S. slope.  
Desc. 115 ft. over N. slope.  
Wash, 8 lks. wide, course W. Asc. 40 ft.  
Set an iron post, 3 ft. long, 2 ins. diam., 12 ins. in the ground to bed rock, supported in a mound of stone, for cor. of secs. 28, 29, 32 and 33, marked on brass cap

T37N R12W  
S 29 S 28  
S 32 S 33  
1924

From which,

- A cedar, 14 ins. diam., bears N.34°E., 67 lks. dist. marked T 37 N R 12 W S 28 B T
- A cedar, 6 ins. diam., bears S.89½°E., 61 lks. dist. marked T 37 N R 12 W S 33 B T
- A cedar, 8 ins. diam., bears S.43¼°W., 14 lks. dist. marked T 37 N R 12 W S 32 B T
- A cedar, 12 ins. diam., bears N.34¼°W., 73 lks. dist. marked T 37 N R 12 W S 29 B T

Land; rolling.  
Soil; rocky, 3rd. rate.  
Timber; cedar.  
Undergrowth; sagebrush.

40.00  
80.10

East, on a random line bet. secs. 28 and 33.  
Set temp. ¼ sec. cor.  
Fall 2 lks. S. of the cor. of secs. 27, 28, 33 and 34.

Thence  
S.89°59'W., on a true line bet. secs. 28 and 33.  
Over rolling land, through heavy timber and dense undergrowth.

.60  
18.90  
37.00  
40.05

Wash, 6 lks. wide, course NW.  
Draw, course N.  
Draw, course NE.  
Set an iron post, 3 ft. long, 1 in. diam., 10 ins. in the ground to bed rock, supported in a mound of stone for ¼ sec. cor. marked on brass cap

¼ S 28  
S 33  
1924

From which,

- A cedar, 6 ins. diam., bears N.10 3/4°W., 41 lks. dist., marked ¼ S 28 B T
- A cedar, 8 ins. diam., bears S.6½°E., 40 lks. dist. marked ¼ S 33 B T

49.50  
62.00  
68.00  
75.00  
80.10

Draw, course SE. Asc. 74 ft. to  
Spur, slopes S. Desc. 50 ft.  
Draw, course N.  
Draw, course SW. Asc.  
The cor. of secs. 28, 29, 32 and 33.

Land; rolling.  
Soil; rocky, 3rd. rate.  
Timber; cedar.  
Undergrowth; sagebrush.

2.70  
7.50  
22.50  
40.00

N.0°8'E., bet. secs. 28 and 29.  
Over rolling land, through heavy timber and dense undergrowth.  
Asc. 30 ft. over S. slope.  
Top of konll. Desc. 80 ft. to  
Head of draw, course NE. Asc. 75 ft.  
Spur, slopes W. Desc. 115 ft. to  
Set an iron post, 3 ft. long, 1 in. diam., 20 ins. in the ground to bed rock, supported in a mound of stone.

Subdivision of T.37 N., R.12 W.

Chains

for  $\frac{1}{4}$  sec. cor. marked on brass cap

$\frac{1}{4}$

S 29 | S 28

1924

From which,

- A cedar, 6 ins. diam., bears N.72 $\frac{1}{2}$ °E., 47 lks. dist. marked  $\frac{1}{4}$  S 28 B T
- A cedar, 7 ins. diam., bears N.58 $\frac{1}{2}$ °W., 35 lks. dist. marked  $\frac{1}{4}$  S 29 B T

Desc. 50 ft.

48.50

Wash, 10 lks. wide, course NE.

75.80

Draw, course SE.

80.00

Set an iron post, 3 ft. long, 2 ins. diam., 30 ins. in the ground for cor. of secs. 20, 21, 28 and 29, marked on brass cap

T37N R12W

S 20 | S 21

S 29 | S 28

1924

From which,

- A cedar, 10 ins. diam., bears N.79 $\frac{1}{2}$ °E., 44 lks. dist. marked T 37 N R 12 W S 21 B T
- A cedar, 5 ins. diam., bears S.17 $\frac{1}{2}$ °E., 64 lks. dist. marked T 37 N R 12 W S 28 B T
- A cedar, 26 ins. diam., bears S.56°W., 64 lks. dist. marked T 37 N R 12 W S 29 B T
- A cedar, 20 ins. diam., bears N.54 $\frac{1}{2}$ °W., 25 lks. dist. marked T 37 N R 12 W S 20 B T

Land; rolling.

Soil; rocky, 3rd. rate.

Timber; cedar.

Undergrowth; sagebrush.

40.00

N.89°59'E., on a random line bet. secs. 21 and 28.

80.04

Set temp.  $\frac{1}{4}$  sec. cor.

Fall 5 lks. N. of the cor. of secs. 21, 22, 27 and 28.

Thence

N.89°59'W., on a true line bet. secs. 21 and 28.

Over rolling land, through scattering timber and undergrowth.

24.00

Desc. 90 ft. over W. slope.

24.24

Draw, course NW. Asc.

40.02

Road, bears SE. and NW.

Set an iron post, 3 ft. long, 1 in. diam., on ledge of rock, supported in a mound of stone, for  $\frac{1}{4}$  sec. cor. marked on brass cap

$\frac{1}{4}$  S 21

S 28

1924

From which,

- A cedar, 6 ins. diam., bears N.86°E., 64 lks. dist. marked  $\frac{1}{4}$  S 21 B T
- A cedar, 16 ins. diam., bears S.27  $\frac{3}{4}$ °E., 88 lks. dist., marked  $\frac{1}{4}$  S 28 B T

52.00

Draw, course NE.

80.04

Asc. 114 ft. over E. slope.

The cor. of secs. 20, 21, 28 and 29.

Land; rolling.

Soil; rocky, 3rd. rate.

Timber; cedar.

Undergrowth; sagebrush.


Subdivision of T.37 N., R.12 W.

Chains

N.0°8'E., bet. secs. 20 and 21.  
Over rolling land, through scattering timber and undergrowth.

28.70  
40.00


Draw, course NE. Asc. 160 ft. over S. slope.  
Set an iron post, 3 ft. long, 1 in. diam., 14 ins. in the ground to bed rock, supported in a mound of stone, for  $\frac{1}{4}$  sec. cor. marked on brass cap



From which,  
A cedar, 14 ins. diam., bears N.84 3/4°E., 30 lks. dist., marked  $\frac{1}{4}$  S 21 B T  
A cedar, 8 ins. diam., bears N.50 1/2°W., 65 lks. dist. marked  $\frac{1}{4}$  S 20 B T

80.00

Set an iron post, 3 ft. long, 2 ins. diam., 26 ins. in the ground for cor. of secs. 16, 17, 20 and 21, marked on brass cap



From which,  
A cedar, 10 ins. diam., bears N.29 3/4°E., 24 lks. dist., marked T 37 N R 12 W S 16 B T  
A cedar, 10 ins. diam., bears S.17 1/2°E., 84 lks. dist. marked T 37 N R 12 W S 21 B T  
A cedar, 10 ins. diam., bears S.69 1/2°W., 87 lks. dist. marked T 37 N R 12 W S 20 B T  
A cedar, 12 ins. diam., bears N.54°W., 74 lks. dist. marked T 37 N R 12 W S 17 B T

Land; rolling.  
Soil; rocky, 3rd. rate.  
Timber; cedar.  
Undergrowth; sagebrush.

40.00  
79.96

S.89°59'E., on a random line bet. secs. 16 and 21.  
Set temp.  $\frac{1}{4}$  sec. cor.  
Fall 5 lks. S. of the cor. of secs. 15, 16, 21 and 22.

Thence  
S.89°59'W., on a true line bet. secs. 16 and 21.  
Over rolling land, through scattering timber and undergrowth. Desc.

9.50  
34.80  
39.98

Draw, course N.  
Wash, 10 lks. wide, course N.  
Set an iron post, 3 ft. long, 1 in. diam., 28 ins. in the ground for  $\frac{1}{4}$  sec. cor. marked on brass cap



From which,  
A cedar, 6 ins. diam., bears N.9 3/4°W., 70 lks. dist., marked  $\frac{1}{4}$  S 16 B T  
A cedar, 8 ins. diam., bears S.7°W., 235 lks. dist. marked  $\frac{1}{4}$  S 21 B T

53.00  
53.80  
68.00  
79.96

Desc. 60 ft. to  
Draw, course NE.  
Road, bears NE. and SW.  
Asc. 125 ft. over E. slope.  
Small spur, slopes N.  
The cor. of secs. 16, 17, 20 and 21.

Subdivision of T.37 N., R.12 W.

Chains

Land; rolling.  
Soil; rocky, 4th. rate.  
Timber; cedar.  
Undergrowth; sagebrush.

N.0°8'E., bet. secs. 16 and 17.  
Over rolling land, through scattering timber and undergrowth.  
Desc. over NE. slope.

40.00

Set an iron post, 3 ft. long, 1 in. diam., 12 ins. in the ground to bed rock, supported in a mound of stone, for  $\frac{1}{4}$  sec. cor. marked on brass cap

$\frac{1}{4}$   
S 17 | S 16  
1924

From which,

- A cedar, 16 ins. diam., bears S.66 $\frac{1}{2}$ °E., 37 lks. dist. marked  $\frac{1}{4}$  S 16 B T
- A cedar, 6 ins. diam., bears S.41°W., 39 lks. dist. marked  $\frac{1}{4}$  S 17 B T

80.00

Set an iron post, 3 ft. long, 2 ins. diam., 26 ins. in the ground for cor. of secs. 8, 9, 16 and 17, marked on brass cap

T37N R12W  
S 8 | S 9  
S 17 | S 16  
1924

From which,

- A cedar, 10 ins. diam., bears N.15 $\frac{1}{4}$ °E., 73 lks. dist. marked T 37 N R 12 W S 8 B T
- A cedar, 10 ins. diam., bears S.60  $\frac{3}{4}$ °E., 109 lks. dist., marked T 37 N R 12 W S 16 B T
- A cedar, 16 ins. diam., bears S.63 $\frac{1}{4}$ °W., 27 lks. dist. marked T 37 N R 12 W S 17 B T
- A cedar, 10 ins. diam., bears N.37 $\frac{1}{4}$ °W., 66 lks. dist. marked T 37 N R 12 W S 8 B T

Land; rolling.  
Soil; rocky, 4th. rate.  
Timber; cedar.  
Undergrowth; sagebrush.

40.00

N.89°59'E., on a random line bet. secs. 9 and 16.  
Set temp.  $\frac{1}{4}$  sec. cor.

80.00

Fall 2 lks. W. of the cor. of secs. 9, 10, 15 and 16.

Thence

West, on a true line bet. secs. 9 and 16.  
Over rolling land, through scattering timber and undergrowth.

23.00

Desc. 90 ft. over SW. slope.

40.00

Set an iron post, 3 ft. long, 1 in. diam., 18 ins. in the ground to bed rock, supported in a mound of stone, for  $\frac{1}{4}$  sec. cor. marked on brass cap

$\frac{1}{4}$  S 9  
S 16  
1924

From which,

- A cedar, 8 ins. diam., bears N.53  $\frac{3}{4}$ °E., 61 lks. dist., marked  $\frac{1}{4}$  S 9 B T
- A cedar, 10 ins. diam., bears S.33°W., 39 lks. dist. marked  $\frac{1}{4}$  S 16 B T

Desc. 65 ft. over W. slope.

Subdivision of T.37 N., R.12 W.

Chains

70.40

Road, bears N. and S.

71.00

Draw, course N. Asc.

80.00

The cor. of secs, 8, 9, 16 and 21 1/2 ins. diam.,

Land; rolling.

Soil; rocky, 3rd. rate.

Timber; cedar.

Undergrowth; sagebrush.

N. 0° 8' E., bet. secs. 8 and 9.

Over rolling land, through scattering timber and undergrowth.

Asc.

8.00

Desc. 80 ft. to

18.00

Draw, course NW.


18.90

Road, bears SE. and NW.

Asc. 100 ft. over SW. slope.

40.00

Set an iron post, 3 ft. long, 1 in. diam., 22 ins. in the ground to bed rock, supported in a mound of stone, for 1/4 sec. cor. marked on brass cap



From which,

A cedar, 10 ins. diam., bears S. 25 3/4° E., 91 lks. dist., marked 1/4 S 9 B T

A cedar, 8 ins. diam., bears N. 14 1/2° W., 89 lks. dist. marked 1/4 S 8 B T

Asc. 34 ft.

47.20

Top of slope. Desc. 50 ft.

53.40

Draw, course W. Asc. 50 ft.

68.80

Desc.

80.00

Set an iron post, 3 ft. long, 2 ins. diam., 18 ins. in the ground to bed rock, supported in a mound of stone, for cor. of secs. 4, 5, 8 and 9, marked on brass cap



From which,

A cedar, 8 ins. diam., bears N. 62 1/2° E., 81 lks. dist. marked T 37 N R 12 W S 4 B T

A cedar, 24 ins. diam., bears S. 20 3/4° E., 64 lks. dist., marked T 37 N R 12 W S 9 B T

A cedar, 26 ins. diam., bears S. 72 1/2° W., 150 lks. dist., marked T 37 N R 12 W S 8 B T

A cedar, 18 ins. diam., bears N. 78 1/4° W., 66 lks. dist. marked T 37 N R 12 W S 5 B T

Land; rolling.

Soil; rocky, 3rd. rate.

Timber; cedar.

Undergrowth; sagebrush.

40.00

East, on a random line bet. secs. 4 and 9.

79.98

Set temp. 1/4 sec. cor.

Intersect the cor. of secs. 3, 4, 9 and 10.

Thence

West, on a true line bet. secs. 4 and 9.

Over rolling land, through scattering timber and undergrowth.

Asc. gradually.

9.30

Desc. 86 ft. over SW. slope.


35.00

Draw, course N.

Subdivision of T.37 N., R.12 W.

Chains  
39.99

Set an iron post, 3 ft. long, 1 in. diam., 24 ins. in the ground for  $\frac{1}{4}$  sec. cor. marked on brass cap



From which,

A cedar, 6 ins. diam., bears N.75  $\frac{3}{4}$ °E., 69 lks. dist., marked  $\frac{1}{4}$  S 4 B T

A cedar, 8 ins. diam., bears S.33°E., 98 lks. dist. marked  $\frac{1}{4}$  S 9 B T

79.98 The cor. of secs. 4, 5, 8 and 9.

Land; rolling.  
Soil; rocky, 3rd. rate.  
Timber; cedar.  
Undergrowth; sagebrush.

40.00  
80.20

N.0°1'E., on a random line bet. secs. 4 and 5.

Set temp.  $\frac{1}{4}$  sec. cor.

Fall 2 lks. E. of the cor. of secs. 4, 5, 32 and 33, on N. bdy. of Tp., hereinbefore described.

Thence


South, on a true line bet. secs. 4 and 5.

Over rolling land, through scattering timber and undergrowth.

Desc. gentle S. slope.

23.90 Draw, course NW. Asc. 50 ft. to

40.20 Set an iron post, 3 ft. long, 1 in. diam., 28 ins. in the ground for  $\frac{1}{4}$  sec. cor. marked on brass cap



From which,

A cedar, 10 ins. diam., bears S.68 $\frac{1}{2}$ °E., 57 lks. dist. marked  $\frac{1}{4}$  S 4 B T

A cedar, 14 ins. diam., bears N.49  $\frac{3}{4}$ °W., 21 lks. dist., marked  $\frac{1}{4}$  S 5 B T

80.20 The cor. of secs. 4, 5, 8 and 9.

Land; rolling.  
Soil; rocky, 3rd. rate.  
Timber; cedar.  
Undergrowth; sagebrush.

5.00  
40.00

From the standard cor. of secs. 31 and 32 on S. bdy. of Tp., hereinbefore described,


N.0°8'E., bet. secs. 31 and 32.

Over rolling land, through heavy timber and dense undergrowth.

Asc. S. slope.

Point of spur, slopes SE. Desc.

Set an iron post, 3 ft. long, 1 in. diam., 30 ins. in the ground for  $\frac{1}{4}$  sec. cor. marked on brass cap



From which,

Subdivision of T.37 N., R.12 W.

Chains  
 A cedar, 6 ins. diam., bears S.72½°E., 76 lks. dist.  
 marked ¼ S 32 B T  
 A cedar, 18 ins. diam., bears N.53¼°W., 179 lks. dist.  
 marked ¼ S 31 B T  
 40.50 Draw, course NE. Asc. 90 ft. over SE. slope.  
 59.50 Point of spur, slopes SE.  
 Desc. 40 ft. over NE. slope.  
 68.00 Draw, course E. Asc. 80 ft.  
 73.10 Top of ascent.  
 80.00 Set an iron post, 3 ft. long, 2 ins. diam., 28 ins. in  
 the ground for cor. of secs. 29, 30, 31 and 32, marked  
 on brass cap

T37N, R12W  
 S 30 | S 29  
 S 31 | S 32  
 1924

From which,  
 A cedar, 6 ins. diam., bears N.55°E., 74 lks. dist.  
 marked T 37 N R 12 W S 29 B T  
 A cedar, 8 ins. diam., bears S.72¼°E., 62 lks. dist.  
 marked T 37 N R 12 W S 32 B T  
 A cedar, 7 ins. diam., bears S.8¼°W., 54 lks. dist.  
 marked T 37 N R 12 W S 31 B T  
 A cedar, 18 ins. diam., bears N.54¼°W., 131 lks.  
 dist., marked T 37 N R 12 W S 30 B T

Land; rolling.  
 Soil; rocky, 4th. rate.  
 Timber; cedar.  
 Undergrowth; sagebrush.

40.00 East, on a random line bet. secs. 29 and 32.  
 80.00 Set temp. ¼ sec. cor.  
 Fall 5 lks. S. of the cor. of secs. 28, 29, 32 and 33.  
 Thence  
 S.89°58'W., on a true line bet. secs. 29 and 32.  
 Over rolling land, through heavy timber and dense under-  
 growth.  
 Desc. 80 ft. over SW. slope.  
 9.90 Wash, 20 lks. wide, course NW.  
 Asc. 17 ft. to  
 15.50 Point of spur, slopes N. Desc. 22 ft.  
 19.00 Draw, course N. Asc.  
 29.00 Point of spur, slopes N.  
 Desc. 75 ft.  
 35.20 Draw, course NE. Asc.  
 40.00 Set an iron post, 3 ft. long, 1 in. diam., 22 ins. in the  
 ground for ¼ sec. cor. marked on brass cap

¼ S 29  
 S 32  
 1924

From which,  
 A cedar, 6 ins. diam., bears N.51°E., 71 lks. dist.  
 marked ¼ S 29 B T  
 A cedar, ins. diam., bears S.64°E., 91 lks. dist.  
 marked ¼ S 32 B T

46.00 Asc. 82 ft. over E. slope.  
 51.10 Top of knoll. Desc. 63 ft. to  
 75.00 Draw, course S. Asc. 123 ft.  
 80.00 Spur, slopes N. Desc. 30 ft.  
 The cor. of secs. 29, 30, 31 and 32.

Land; rolling.  
 Soil; rocky, 3rd. rate.  
 Timber; cedar.  
 Undergrowth; sagebrush.

Subdivision of P. 37 N., R. 12 W.

Chains  
40.00  
79.93

West, on a random line bet. secs. 30 and 31.  
Set temp.  $\frac{1}{4}$  sec. cor.  
Fall 6 lks. S. of the cor. of secs. 25, 30, 31 and 36 on  
W. bdy. of Tp., hereinbefore described.

Thence  
S.  $89^{\circ}57'$  E., on a true line bet. secs. 30 and 31.  
Over rolling land, through heavy timber and dense under-  
growth.

14.59  
21.40  
36.50  
39.93

Asc. 140 ft. over NW. slope.  
Spur, slopes NE. Desc. 50 ft.  
Draw, course NE. Asc. 63 ft.  
Spur, slopes NE. Desc. E. slope.  
Set an iron post, 3 ft. long, 1 in. diam., 8 ins. in  
the ground to bed rock, supported in a mound of stone,  
for  $\frac{1}{4}$  sec. cor. marked on brass cap.

$\frac{1}{4}$  S 30  
S 31  
1924

From which,  
A cedar, 8 ins. diam., bears N.  $14^{\circ}$  E., 65 lks. dist.  
marked  $\frac{1}{4}$  S 30 B T  
A cedar, 6 ins. diam., bears S.  $23\frac{1}{4}^{\circ}$  E., 15 lks. dist.  
marked  $\frac{1}{4}$  S 31 B T

50.10  
67.40  
79.93

Desc. 67 ft.  
Wash, 16 lks. wide, course N.  
Asc. 115 ft.  
Spur, slopes S. Desc. 67 ft. over E. slope.  
The cor. of secs. 29, 30, 31 and 32.

Land; rolling.  
Soil; rocky, 3rd. rate.  
Timber; cedar.  
Undergrowth; sagebrush.

8.50  
15.50  
40.00

N.  $0^{\circ}8'$  E., bet. secs. 29 and 30.  
Over rolling land, through heavy timber and dense under-  
growth.

Desc. 50 ft. over N. slope.  
Draw, course E. Asc. 57 ft.  
Top of knoll. Desc. 210 ft. over N. slope.  
Set an iron post, 3 ft. long, 1 in. diam., 24 ins. in  
the ground for  $\frac{1}{4}$  sec. cor. marked on brass cap

$\frac{1}{4}$   
S 30 | S 29  
1924

From which,  
A cedar, 6 ins. diam., bears S.  $89\frac{1}{4}^{\circ}$  E., 78 lks. dist.  
marked  $\frac{1}{4}$  S 29 B T  
A cedar, 6 ins. diam., bears S.  $87\frac{3}{4}^{\circ}$  W., 24 lks.  
dist., marked  $\frac{1}{4}$  S 30 B T

46.70  
60.00  
65.80  
75.80  
80.00

Desc. 40 ft.  
Draw, course NE. Asc. 40 ft.  
Desc. 40 ft.  
Draw, course E. Asc. 74 ft. over S. slope.  
Desc. 70 ft. to  
Set an iron post, 3 ft. long, 2 ins. diam., 28 ins. in  
the ground for cor. of secs. 19, 20, 29 and 30, marked  
on brass cap

T37N R12W  
S 19 | S 20  
S 30 | S 29  
1924

From which,  
A cedar, 14 ins. diam., bears N.  $58\frac{1}{2}^{\circ}$  E., 248 lks.

Subdivision of T.37 N., R.12 W.

Chains

marked T 37 N R 12 W S 20 B T  
A cedar, 4 ins. diam., bears S.48°E., 154 lks. dist.  
marked B T  
A cedar, 16 ins. diam., bears S.11 3/4°W., 83 lks.  
dist., marked T 37 N R 12 W S 30 B T  
A cedar, 14 ins. diam., bears N.1 1/4°W., 144 lks. dist.  
marked T 37 N R 12 W S 19 B T

Land; rolling.  
Soil; rocky, 3rd. rate.  
Timber; cedar.  
Undergrowth; sagebrush.

40.00  
79.90

N.89°58'E., on a random line bet. secs. 20 and 29.  
Set temp. 1/4 sec. cor.  
Fall 7 lks. N. of the cor. of secs. 20, 21, 28 and 29.

Thence  
N.89°59'W., bet. secs. 20 and 29.  
Over rolling land, through scattering timber and under-  
growth.

39.00  
39.95

Draw, course NE.  
Set an iron post, 3 ft. long, 1 in. diam., 30 ins. in  
the ground for 1/4 sec. cor. marked on brass cap

S 20  
S 29  
1924

From which,  
A cedar, 26 ins. diam., bears N.49 1/2°E., 37 lks. dist.  
marked 1/4 S 20 B T  
A cedar, 8 ins. diam., bears S.31 1/2°W., 23 lks. dist.  
marked 1/4 S 29 B T

68.70  
79.90

Draw, course N.  
The cor. of secs. 19, 20, 29 and 30.

Land; rolling.  
Soil; rocky, 3rd. rate.  
Timber; cedar.  
Undergrowth; sagebrush.

40.00  
80.12

N.89°57'W., on a random line bet. secs. 19 and 30.  
Set temp. 1/4 sec. cor.  
Fall 16 lks. N. of the cor. of secs. 19, 24, 25 and 30  
on W. bdy. of Tp., hereinbefore described.

Thence  
N.89°56'E., on a true line bet. secs. 19 and 30.  
Over rolling land, through scattering timber and under-  
growth.

40.12

Set an iron post, 3 ft. long, 1 in. diam., 30 ins. in  
the ground for 1/4 sec. cor. marked on brass cap

S 19  
S 30  
1924

From which,  
A cedar, 6 ins. diam., bears N.56°W., 90 lks. dist.  
marked 1/4 S 19 B T  
A cedar, 10 ins. diam., bears S.38°E., 93 lks. dist.  
marked 1/4 S 30 B T

42.90  
80.12

Draw, course NE.  
The cor. of secs. 19, 20, 29 and 30.

Land; rolling. Soil; rocky, 3rd. rate.  
Timber; cedar. Undergrowth; sagebrush.



Subdivision of T.37 N., R.12 W.

Chains  
79.98

Asc. 37 ft. to  
The cor. of secs. 17, 18, 19, and 20.

Land; rolling.  
Soil; rocky, 3rd. rate.  
Timber; cedar.  
Undergrowth; sagebrush.

40.00  
80.30

S.89°56'W., on a random line bet. secs. 18 and 19.  
Set temp.  $\frac{1}{4}$  sec. cor.  
Fall 9 lks. N. of the cor. of secs. 13, 18, 19 and 24,  
on W. bdy. of Tp., hereinbefore described.

Thence  
N.29°52'E., on a true line bet. secs. 18 and 19.  
Over rolling land, through scattering timber and under-  
growth.

2.75  
19.70  
19.85  
40.30

Asc. 50 ft. over W. slope.  
Desc. 186 ft. over E. slope.  
Road, bears N. and S.  
Draw, course N. Asc. 45 ft.  
Set an iron post, 3 ft. long, 1 in. diam., 22 ins. in  
the ground to bed rock, supported in a mound of stone,  
for  $\frac{1}{4}$  sec. cor., marked on brass cap

$\frac{1}{4}$  S 18  
S 19  
1924

From which,  
A cedar, 12 ins. diam., bears N.36  $\frac{3}{4}$ °W., 48 lks.  
dist., marked  $\frac{1}{4}$  S 18 B T  
A cedar, 10 ins. diam., bears S.57°W., 79 lks. dist.  
marked  $\frac{1}{4}$  S 19 B T

43.40  
73.00  
80.30

Draw, course NW.  
Draw, course NW.  
The cor. of secs. 17, 18, 19 and 20.

Land; rolling.  
Soil; rocky, 4th. rate.  
Timber; cedar.  
Undergrowth; sagebrush.

8.40  
18.10  
40.00

N.0°8'E., bet. secs. 17 and 18.  
Over rolling land, through scattering timber and under-  
growth.

Draw, course NW.  
Draw, course W. Asc. 100 ft. over SW. slope.  
Set an iron post, 3 ft. long, 1 in. diam., 26 ins. in  
the ground for  $\frac{1}{4}$  sec. cor. marked on brass cap

$\frac{1}{4}$   
S 18 | S 17  
1924

From which,  
A cedar, 10 ins. diam., bears S.87 $\frac{1}{2}$ °E., 40 lks. dist.  
marked  $\frac{1}{4}$  S 17 B T  
A cedar, 20 ins. diam., bears S.43°W., 33 lks. dist.  
marked  $\frac{1}{4}$  S 18 B T

48.50  
80.00

Spur, slopes NW. Desc. 127 ft. over NE. slope.  
Set an iron post, 3 ft. long, 2 ins. diam., 28 ins. in  
the ground for cor. of secs. 7, 8, 17 and 18, marked  
on brass cap

T37N R12W  
S 7 | S 8  
S 18 | S 17  
1924

Subdivision of T. 37 N., R. 12 W.

Chains

From which,  
 A cedar, ins. diam., bears N.  $67\frac{3}{4}^{\circ}$  E., 147 lks. dist., marked T 37 N R 12 W S 8 B T  
 A cedar, ins. diam., bears S.  $46^{\circ}$  E., 142 lks. dist. marked T 37 N R 12 W S 17 B T  
 A cedar, 12 ins. diam., bears S.  $49\frac{1}{2}^{\circ}$  W., 134 lks. dist. marked T 37 N R 12 W S 18 B T  
 A cedar, 12 ins. diam., bears N.  $85\frac{1}{4}^{\circ}$  W., 58 lks. dist. marked T 37 N R 12 W S 7 B T

Land; rolling.  
 Soil; rocky, 3rd. rate.  
 Timber; cedar.  
 Undergrowth; sagebrush.

40.00 S.  $89^{\circ}58'$  E., on a random line bet. secs. 8 and 17.  
 79.96 Set temp.  $\frac{1}{4}$  sec. cor.  
 Fall 19 lks. W. of the cor. of secs. 8, 9, 16 and 17.

Thence  
 N.  $89^{\circ}50'$  W., on a true line bet. secs. 8 and 17.  
 Over rolling land, through scattering timber and undergrowth.

34.10 Draw, course N. Asc. E. slope.  
 39.98 Set an iron post, 3 ft. long, 1 in. diam., 26 ins. in the ground for  $\frac{1}{4}$  sec. cor. marked on brass cap

$\frac{1}{4}$  S 8  
 S 17  
 1924

From which,  
 A cedar, 20 ins. diam., bears N.  $51\frac{1}{2}^{\circ}$  E., 75 lks. dist. marked  $\frac{1}{4}$  S 8 B T  
 A cedar, 12 ins. diam., bears S.  $57\frac{1}{4}^{\circ}$  E., 74 lks. dist. marked  $\frac{1}{4}$  S 17 B T

46.00 Top of small spur.  
 78.20 Draw, course NW.  
 79.96 The cor. of secs. 7, 8, 17 and 18.

Land; rolling.  
 Soil; rocky; 3rd. rate.  
 Timber; cedar.  
 Undergrowth; sagebrush.

40.00 S.  $89^{\circ}52'$  W., on a random line bet. secs. 7 and 18.  
 80.53 Set temp.  $\frac{1}{4}$  sec. cor.  
 Intersect the cor. of secs. 7, 12, 13 and 18 on W. bdy. of Tp., hereinbefore described.

Thence  
 N.  $89^{\circ}52'$  E., on a true line bet. secs. 7 and 18.  
 Over rolling land, through scattering timber and undergrowth.

33.93 Desc. 60 ft. over E. slope.  
 40.53 Road, bears NE: and SW.  
 Set an iron post, 3 ft. long, 1 in. diam., 28 ins. in the ground for  $\frac{1}{4}$  sec. cor. marked on brass cap

$\frac{1}{4}$  S 7  
 S 18  
 1924

From which,  
 A cedar, 26 ins. diam., bears N.  $52^{\circ}$  W., 38 lks. dist. marked  $\frac{1}{4}$  S 7 B T  
 A cedar, 6 ins. diam., bears S.  $12^{\circ}$  W., 35 lks. dist. marked  $\frac{1}{4}$  S 18 B T

47.73 Draw, course NW.

Subdivision of T.37 N., R.12 W.

Chains  
64.50  
80.53


Asc. 80 ft. over W. slope.  
Desc. 70 ft. over E. slope.  
The cor. of secs. 7, 8, 17 and 18.

Land; rolling.  
Soil; rocky, 3rd. rate.  
Timber; cedar.  
Undergrowth; sagebrush.

N.0°8'E., bet. secs. 7 and 8.  
Over rolling land, through scattering timber and undergrowth.

20.10  
40.00


Asc. 70 ft. over SE. slope.  
Top of spur, Desc. 75 ft. to  
Set an iron post, 3 ft. long, 1 in. diam., on ledge of rock, supported in a mound of stone, for  $\frac{1}{4}$  sec. cor. marked on brass cap



From which,  
A cedar, 8 ins. diam., bears N.42 $\frac{1}{2}$ °E., 38 lks. dist. marked  $\frac{1}{4}$  S 8 B T  
A cedar, 16 ins. diam., bears N.35  $\frac{3}{4}$ °W., 169 lks. dist., marked  $\frac{1}{4}$  S 7 B T

42.90  
57.90  
68.80  
80.00

Asc.  
Desc. 63 ft. to  
Draw, course NE. Asc. 86 ft. over SE. slope.  
Spur, slopes NE. Desc. 50 ft. to  
Set an iron post, 3 ft. long, 2 ins. diam., 12 ins. in the ground to bed rock, supported in a mound of stone, for cor. of secs. 5, 6, 7 and 8, marked on brass cap



From which,  
A cedar, 10 ins. diam., bears N.49°E., 38 lks. dist. marked T 37 N R 12 W S 5 B T  
A cedar, 12 ins. diam., bears S.31 $\frac{1}{2}$ °E., 104 lks. dist. marked T 37 N R 12 W S 8 B T  
A cedar, 8 ins. diam., bears S.10°W., 69 lks. dist. marked T 37 N R 12 W S 7 B T  
A cedar, 26 ins. diam., bears N.16 $\frac{1}{2}$ °W., 45 lks. dist. marked T 37 N R 12 W S 6 B T

Land; rolling.  
Soil; rocky, 3rd. rate.  
Timber; cedar.  
Undergrowth; sagebrush.

40.00  
79.88

S.89°50'E., on a random line bet. secs. 5 and 8.  
Set temp.  $\frac{1}{4}$  sec. cor.  
Intersect the cor. of secs. 4, 5, 8 and 9.

Thence  
N.89°50'W., on a true line bet. secs. 5 and 8.  
Over rolling land, through scattering timber and undergrowth.

26.60  
36.50  
39.94

Desc. 112 ft. over W. slope to  
Draw, course SW. Asc.  
Set an iron post, 3 ft. long, 1 in. diam., 26 ins. in the ground for  $\frac{1}{4}$  sec. cor. marked on brass cap

Subdivision of T.37 N., R.12 W.

Chains

$\frac{1}{4}$   $\frac{S\ 5}{S\ 8}$   
1924

From which,

- A cedar, 8 ins. diam., bears N.18°W., 150 lks. dist. marked  $\frac{1}{4}$  S 5 B T
- A cedar, 7 ins. diam., bears S.26°W., 89 lks. dist. marked  $\frac{1}{4}$  S 8 BT

- 50.20 Asc. 40 ft. to
- 71.00 Desc. 144 ft. over SW. slope.
- 71.50 Road, bears SE. and NW.
- 71.50 Draw, course NW.
- 79.88 Asc. 54 ft. over E. slope.
- 79.88 The cor. of secs. 5, 6, 7 and 8.

Land; rolling.  
Soil; rocky, 3rd. rate.  
Timber; cedar.  
Undergrowth; sagebrush.

- 40.00 S.89°52'W., on a random line bet. secs. 6 and 7.
- 80.57 Set temp.  $\frac{1}{4}$  sec. cor.
- 80.57 Fall 8 lks. N. of the cor. of secs. 1, 6, 7 and 12 on W. bdy. of Tp., hereinbefore described.

Thence  
N.89°49'E., on a true line bet. secs. 6 and 7.  
Over rolling land, through scattering timber and undergrowth.

- 15.47 Draw, course NW.
- 15.67 Road, bears SE. and NW. Asc. 92 ft. over W. slope.
- 25.50 Top of ascent.
- 27.00 Desc. 67 ft. to
- 40.57 Set an iron post, 3 ft. long, 1 in. diam., 12 ins. in the ground to bed rock, supported in a mound of stone, for  $\frac{1}{4}$  sec. cor. marked on brass cap

$\frac{1}{4}$   $\frac{S\ 6}{S\ 7}$   
1924

From which,

- A cedar, 8 ins. diam., bears N.40 $\frac{1}{2}$ °E., 35 lks. dist. marked  $\frac{1}{4}$  S 6 B T
- A cedar, 10 ins. diam., bears S.7 $\frac{1}{4}$ °E., 35 lks. dist. marked  $\frac{1}{4}$  S 7 B T

- 59.00 Asc. 116 ft. over W. slope.
- 71.00 Top of ascent.
- 80.57 Desc. 87 ft. to
- 80.57 The cor. of secs. 5, 6, 7 and 8.

Land; rolling.  
Soil; rocky, 3rd. rate.  
Timber; cedar.  
Undergrowth; sagebrush.

- 40.00 N.0°1'W., on a random line bet. secs. 5 and 6.
- 79.97 Set temp.  $\frac{1}{4}$  sec. cor.
- 79.97 Fall 7 lks. E. of the cor. of secs. 5, 6, 31 and 32 on N. bdy. of Tp., hereinbefore described.

Thence  
S.0°4'E., on a true line bet. secs. 5 and 6.  
Over rolling land, through scattering timber and undergrowth.

- 36.20 Desc. 87 ft. over S. slope.
- 39.97 Draw, course SW. Asc. 32 ft.
- 39.97 Set an iron post, 3 ft. long, 1 in. diam., 6 ins. in

Subdivision of T.37 N., R.12 W.

Chains

the ground to bed rock, supported in a mound of stone, for  $\frac{1}{4}$  sec. cor. marked on brass cap

$\frac{1}{4}$   
 S 6 | S 5  
 1924

From which,

A cedar, 7 ins. diam., bears S.66 $\frac{1}{2}$ °E., 25 lks. dist. marked  $\frac{1}{4}$  S 5 B T

A cedar, 12 ins. diam., bears S.79 $\frac{1}{2}$ °W., 55 lks. dist. marked  $\frac{1}{4}$  S 6 B T

61.80  
62.20  
79.97

Road, bears SE. and NW.  
Draw, course NW.  
The cor. of secs. 5, 6, 7 and 8.

Land; rolling.  
Soil; rocky, 3rd. rate.  
Timber; cedar.  
Undergrowth; sagebrush.

Boundaries of T.37 N., R.12 W.

Latitudes, departures, and closing errors.

Line designated	True bearing.	Dist- ance.	Latitudes.		Departures.	
			N.	S.	E.	W.
South Bdy. (9th. Std. Par.)	West	480.00				480.00
West Bdy.	North	480.00	480.00			
North Bdy.	N.89°55'E.	480.49	.70		480.49	
East Bdy.	S.0°10'W. South	320.57 160.00		320.57 160.00		.93
Convergency					.54	
Totals.			480.70	480.57	481.03	480.93
Error in latitude			480.57		480.93	
			0.23			
Error in departure					0.10	

The continued satisfactory adjustment of the instruments throughout the survey of this township was indicated from frequent tests on meridians established by observations on Polaris.

GENERAL DESCRIPTION.

The land within this township is mostly rolling, except in the northeastern portion which is level and good soil. The south and west portions of the township are rough and rolling with heavy growth of cedar and pinyon timber, the soil is not agricultural in character. In sec. 23 is located a watering hole known as "Sullivan" Dam - good water, used for stock-watering. The land in this township is at present used for grazing of stock. There is a good road through the township from sec. 1 to sec. 36, Wolf Hole, Arizona, to Poverty Mountain, Arizona; also a branch road passing through sec. 34 leading to St. Thomas, Nevada.



CERTIFICATE OF UNITED STATES TRANSITMAN.

Transitman

I, Charles E. Hunter, U. S. Surveyor, hereby certify upon honor that, in pursuance

of special instructions received from the U. S. Surveyor General, for Group 122, Arizona

bearing date of the 23rd day of April, 1923, I have well, faithfully, and truly

in my own proper person, and in strict conformity with said instructions, the Manual of Surveying Instructions, and the laws of the United States, surveyed all those parts or portions of

the Subdivisional Lines of

Township 37 North, Range 12 West

of the Gila and Salt

River Base and Meridian, in the State of Arizona, which are represented in

the foregoing field notes and by diagram on page 1 hereof as having been executed by me, and under my direction; and that all the corners of

said survey have been established and perpetuated in strict accordance with the Manual of Surveying Instructions, and the special written instructions of the U. S. Surveyor General, for Group 122, Arizona

and in the specific manner described in the field notes, and that the foregoing are the original field notes of

such survey.

Place: Phoenix, Arizona

Charles E. Hunter

U. S. Transitman

Date: October 28, 1925

APPROVAL

Office of the United States Surveyor General

The foregoing field notes of the survey of

executed by under his special instructions dated 19 , having been critically examined, and the necessary corrections and explanations made, the said field notes, and the surveys they describe, are hereby approved.

U. S. Surveyor General.

I certify that the foregoing transcript of the field notes of the above-described surveys in , has been correctly copied from the original notes on file in this office.

U. S. Surveyor General



CERTIFICATE OF UNITED STATES SURVEYOR.

I, William E. Hiester, U. S. Surveyor, hereby certify upon honor that, in pursuance of special instructions received from the U. S. Surveyor General, for Group 122, Arizona bearing date of the 23rd. day of April, 19 23 I have well, faithfully, and truly in my own proper person, and in strict conformity with said instructions, the Manual of Surveying Instructions, and the laws of the United States, surveyed all those parts or portions of the 9th Standard Parallel North in Range 12 West, the West and North boundaries and Subdivision Lines of Township 37 North, Range 12 West of the Gila and Salt River Base and Meridian, in the State of Arizona, which are represented in the foregoing field notes <sup>and by diagram on page 1 hereof</sup> as having been executed by me, and under my direction; and that all the corners of said survey have been established and perpetuated in strict accordance with the Manual of Surveying Instructions, and the special written instructions of the U. S. Surveyor General, for Group 122, Arizona and in the specific manner described in the field notes, and that the foregoing are the original field notes of such survey.

Place: Phoenix Arizona  
 Date: Oct 27, 1925

William E. Hiester  
 U. S. Surveyor.

APPROVAL.

OFFICE OF THE UNITED STATES SUPERVISOR OF SURVEYS.

Denver, Colorado, March 8, 1926.

The foregoing field notes of the survey of the 9th Standard Parallel North thru Range 12 West, the West and North boundaries and Subdivision lines

of Township 37 North, Range 12 West, of the Gila and Salt River Base and Meridian in the State of Arizona, executed by William E. Hiester, U.S. Surveyor and Charles E. Hunter, U.S. Transitman.

~~executed by~~ under special instructions dated April 23, 1923 for Group 122, Arizona 1923, having been critically examined, and the necessary corrections and explanations made, the said field notes, and the surveys they describe, are hereby approved.

Charles E. Hunter  
 U. S. Supervisor of Surveys.

I certify that the foregoing transcript of the field notes of the above-described surveys in \_\_\_\_\_, has been correctly copied from the original notes on file in this office.

U. S. Surveyor General.