

4-679

BOOK 3725

FIELD NOTES

OF THE SURVEY OF THE

ESTE HOOKS

Part of the Subdivision Lines

(North half)

of

Township 9 South, Range 1 East

Of the Gila and Salt River Base and Meridian,

In the State of Arizona

EXECUTED BY

Charles E. Hunter, U. S. Transitman

In the capacity of U. S. Surveyor, under Special Instructions dated May 24, 1924, issued by the United States Surveyor General to govern surveys included in Group No. 101, Arizona, which were approved by the Commissioner of the General Land Office, June 5, 1924, and Assignment Instructions dated February 20, 1925

Survey commenced March 4, 1925

Survey completed March 10, 1925

3725

3725

16

Book "C"
 Group 101--Arizona
 Township 9 South, Range 1 East
 DATE DIAGRAM
 1925

Gila and Salt River Meridian.
 Resurveyed in 1914 under Group No. 38.

Surveyed in 1915, under Group No. 38.

6 3-10	5 3-10	4 3-9	3 3-9	2 3-6	1 3-5
7 3-10	8 3-10	9 3-9	10 3-6	11 3-6	12 3-5
18 3-4	17 3-4	16 3-4	15 3-4	14 3-4	13 3-4
19	20	21	22	23	24
28	29	28	27	26	25
31	32	33	34	35	36

————— Indicates lines surveyed by Charles E. Hunter, U.S. Transitman, on dates shown thereon.

————— Surveyed under this Group, notes and dates in Book "B"

————— Accepted surveyed or resurveyed lines.

- - - - - Unsurveyed lines.

The partial subdivision of Township 9 South, Range 1 East was executed from the same camp, and between the same dates, as Township 8 South, Range 1 East. The preliminary and final instrument and tape tests are identical with those of that survey, which is described in Book "B" of this Group.



This is a reproduction of a survey map. The original map is located in the office of the Surveyor General, State of Texas, at Austin, Texas.


Partial Survey of
Subdivisions of Township 9 South, Range 1 East.

Chains

Note: Only the North half of Township 9 South, Range 1 East is subdivided at this time. The Third Latitudinal section line is run West on a true line for 5 miles from the East boundary of the township; thence random West and true easterly remaining mile.


From the cor. of secs. 13, 18, 19 and 24, on the E. bdy. of the tp., which was established by W.K. Kierulff, U.S. Transitman in 1915, under Group NO. 38, and is an iron post 3 ins. in dia., projecting 12 ins. above ground, firmly set, with brass cap properly marked, witnessed by pits;

40.90 West, on a true line, bet. secs. 13 and 24. Over level land; through scattering undergrowth. Set an iron post, 3 ft. long, 1 in. in dia., 26 ins. in the ground for $\frac{1}{4}$ sec. cor., with brass cap marked




Dig pits 18 x 18 x 12 ins., one each 3 ft. dist. E. and W.

73.70 Road brs. N. and S.
80.00 Set an iron post, 3 ft. long, 2 ins. in dia., 24 ins. in the ground for cor. of secs. 13, 14, 23 and 24, with brass cap marked




Dig pits 18 x 18 x 12 ins., one in each sec. 3 ft. dist.
Land: level.
Soil: adobe, 1st rate.
Timber: none.
Undergrowth: mesquite and greasewood.

40.00 West, on a true line, bet. secs. 14 and 23. Over level land; through scattering undergrowth. Set an iron post, 3 ft. long, 1 in. in dia., 26 ins. in the ground for $\frac{1}{4}$ sec. cor., with brass cap marked



Dig pits 18 x 18 x 12 ins., one each E. and W. on line 3 ft. dist.

80.00 Set an iron post, 3 ft. long, 2 ins. in dia., 24 ins. in the ground for cor. of secs. 14, 15, 22 and 23, with brass cap marked



Dig pits 18 x 18 x 12 ins., one in each sec. 3 ft. dist.
Land: level.
Soil: sandy loam, 1st rate.
Timber: none.

Chains

Undergrowth: greasewood and mesquite.

West, on a true line, bet. secs. 15 and 22.
Over level land; through scattering timber and brush.
4.00 Wash, 10 lks. wide, course NE.
40.00 Set an iron post, 3 ft. long, 1 in. in dia., 26 ins. in
the ground for $\frac{1}{4}$ sec. cor., with brass cap marked

$$\begin{array}{r} S15 \\ \frac{1}{4} \\ S22 \\ 1925 \end{array}$$
Dig pits, 18 x 18 x 12 ins., one each E. and W. 3 ft.
dist.

46.00 Wash, 10 lks. wide, course NE.
50.00 Wash, 10 lks. wide, course N.
51.70 Wash, 10 lks. wide, course N.
80.00 Set an iron post, 3 ft. long, 2 ins. in dia., 26 ins.
in the ground for cor. of secs. 15, 16, 21 and 22,
with brass cap marked

$$\begin{array}{r} T9S R1E \\ S16 | S15 \\ \frac{1}{4} \\ S21 | S22 \\ 1925 \end{array}$$
Dig pits, 18 x 18 x 12 ins., one in each sec. 3 ft.
dist.

Land: level.
Soil: sandy loam, 1st rate.
Timber: mesquite.
Undergrowth: same and greasewood and palo verde.

West, on a true line, bet. secs. 16 and 21.
Over level land; through scattering undergrowth.
5.50 Wash, 10 lks. wide, course NE.
24.60 Wash, 10 lks. wide, course NE.
40.00 Set an iron post, 3 ft. long, 1 in. in dia., 26 ins. in
the ground for $\frac{1}{4}$ sec. cor., with brass cap marked

$$\begin{array}{r} S16 \\ \frac{1}{4} \\ S21 \\ 1925 \end{array}$$
Dig pits 18 x 18 x 12 ins., one each E. and W. 3 ft.
dist.

80.00 Set an iron post, 3 ft. long, 2 ins. in dia., 26 ins. in
the ground for cor. of secs. 16, 17, 20 and 21, with
brass cap marked

$$\begin{array}{r} T9S R1E \\ S17 | S16 \\ \frac{1}{4} \\ S20 | S21 \\ 1925 \end{array}$$
Dig pits 18 x 18 x 12 ins., one in each sec. 3 ft.
dist.

Land: level.
Soil: sandy loam, 1st rate.
Timber: none.
Undergrowth: greasewood, mesquite and palo verde.

West, on a true line, bet. secs. 17 and 20.

Partial Survey of
Subdivisions of Township 9 South, Range 1 East.

Chains West, on true line, bet. secs. 17 and 20, undergrowth.
Over level land thru scattering undergrowth.
1.60 Wash, 10 lks. wide, course NE.
12.50 Wash, 10 lks. wide, course NE.
40.00 Set an iron post, 3 ft. long, 1 in. in dia., 26 ins. in
the ground for $\frac{1}{4}$ sec. cor., with brass cap marked

S17
+S20
1925

Raise a mound of stone, 3 ft. base, 1 $\frac{1}{2}$ ft. high, N.
of post.

75.40 Wash, 40 lks. wide, course NE.
80.00 Set an iron post, 3 ft. long, 2 ins. in dia., 26 ins.
in the ground for cor. of secs. 17, 18, 19 and 20,
with brass cap marked

T9S R1E
S18 | S17
+-----+
S19 | S20
1925

Raise a mound of stone, 3 ft. base, 1 $\frac{1}{2}$ ft. high, W.
of post.

Land: level.
Soil: gravel, 2nd rate.
Timber: none.
Undergrowth: greasewood, palo verde and ironwood.

40.00 West, on a random line, bet. secs. 18 and 19.
Set temp. $\frac{1}{4}$ sec. cor.
79.30 Fall 7 lks. N. of the cor. of secs. 13, 18, 19 and 24, on
the W. bdy, of the tp., which was re-established by
W.H. Thorn, U.S.S., in 1914 under Group No. 38. This
cor. is an iron post, 3 ins. in dia., projecting 12
ins. above a mound of stone 3 ft. base, 1 $\frac{1}{2}$ ft. high,
firmly set, properly marked and witnessed by a mound
of stone W.

Thence
N. 89° 57' E., on a true line bet. secs. 18 and 19.
Over level land; through scattering undergrowth.

0.10 Wash, 10 lks. wide, course NE.
20.50 Wash, 10 lks. wide, course N.
31.60 Wash, 10 lks. wide, course N.
39.30 Set an iron post, 3 ft. long, 1 in. in dia., 26 ins. in
the ground for $\frac{1}{4}$ sec. cor., with brass cap marked

S18
+S19
1925

Raise a mound of stone, 3 ft. base, 1 $\frac{1}{2}$ ft. high, N.
of post.


42.40 Wash, 10 lks. wide, course NE.
47.20 Wash, 10 lks. wide, course N.
68.10 Wash, 10 lks. wide, course N.
79.30 The cor. of secs. 17, 18, 19 and 20.

Land: level,
Soil: gravel, 2nd rate.
Timber: none.
Undergrowth: greasewood, palo verde and ironwood.


Partial Survey of
Subdivisions of Township 9 South, Range 1 East.

Chains

From the cor. of secs. 13, 14, 23 and 24, hereinbefore described
N. 0° 01' W., bet. secs. 13 and 14.
Over level land; through scattering undergrowth.
40.00 Set an iron post, 3 ft. long, 1 in. in dia., 26 ins. in the ground for $\frac{1}{4}$ sec. cor., with brass cap marked




80.00 Dig pits 18 x 18 x 12 ins., one each N. and S. 3 ft. dist.
Set an iron post, 3 ft. long 2 ins. in dia., 26 ins. in the ground for cor. of secs. 11, 12, 13 and 14, with brass cap marked



Dig pits 18 x 18 x 12 ins., one in each sec. 3 ft. dist.
Land: level.
Soil: gravel, 2nd rate.
Timber: none.
Undergrowth: greasewood and mesquite.

40.00 East, on a random line bet. secs. 12 and 13.
Set temp. $\frac{1}{4}$ sec. cor.
80.04 Intersect the cor. of secs. 7, 12, 13 and 18, on the E. bdy. of the Tp., which was established in 1915 under Group No. 38. This cor. is an iron post, 3 ins. in dia., projecting 12 ins. above ground, properly marked on brass cap, firmly set, and witnessed by pits.
Thence

40.02 West, on a true line, bet. secs. 12 and 13.
Over level land; through scattering undergrowth.
Set an iron post, 3 ft. long, 1 in. in dia., 26 ins. in the ground for $\frac{1}{4}$ sec. cor., with brass cap marked



60.40 Dig pits 18 x 18 x 12 ins., one each E. and W. 3 ft. dist.

65.40 Road brs. NW. and SE.
80.04 Road brs. N. and S.
The cor. of secs. 11, 12, 13 and 14.
Land: level.
Soil: adobe, 1st rate.
Timber: none.
Undergrowth: greasewood and mesquite.

28.60 N. 0° 01' W., bet. secs. 11 and 12.
30.70 Over level land; through scattering undergrowth.
40.00 Road brs. NE. and SW.
Road brs. NE. and SW.
Set an iron post, 3 ft. long, 1 in. in dia., 26 ins. in the ground for $\frac{1}{4}$ sec. cor., with brass cap marked



Partial Survey of
Subdivisions of Township 9 South, Range 1 East.

Chains

Dig pits 18 x 18 x 12 ins. one each N. and S. 3 ft. dist.

80.00 Set an iron post, 3 ft. long, 2 ins. in dia., 26 ins. in the ground for cor. of secs. 1,2,11 and 12, with brass cap marked

T9S R1E
S2 | S1
S11 | S12
1925

Dig pits 18 x 18 x 12 ins., one in each sec. 3 ft. dist.

Land: level.
Soil: adobe, 1st rate.
Timber: none.
Undergrowth: greasewood.

East, on a random line bet. secs. 1 and 12.

40.00 Set temp. 1/4 sec. cor.

80.02 Fall 5 lks. N. of the cor. of secs. 1,6,7 and 12, on the E. bdy. of the Tp., which was established in 1915 under Group No. 38. This cor. is an iron post, 3 ins. in dia., projecting 10 ins. above ground, firmly set, properly marked on brass cap, and witnessed by pits.

Thence
N. 89° 58' W., on a true line bet. secs. 1 and 12.
Over level, grass-covered land.

11.00 Wash, 10 lks. wide, course NW.

40.01 Set an iron post, 3 ft. long, 1 in. in dia., 26 ins. in the ground for 1/4 sec. cor., with brass cap marked

1/4 S1
S12
1925

Dig pits 18 x 18 x 12 ins., one each E. and W. 3 ft. dist.

59.10 Road hrs. NW. and SE.

80.02 The cor. of secs. 1, 2, 11 and 12.

Land: level.
Soil: adobe, 1st rate.
Timber: none.
Undergrowth: none.

North, on a random line bet. secs. 1 and 12.

40.00 Set temp. 1/4 sec. cor.

79.97 Fall 5 lks. W. of the cor. of secs. 1,2,35 and 36, on the N. bdy. of the Tp., described in Book "B" of this Group.

Thence
S. 0° 02' W., on a true line bet. secs. 1 and 2.
Over level land; through scattering undergrowth.

5.60 Road hrs. NW. and SE.

39.97 Set an iron post, 3 ft. long, 1 in. in dia., 26 ins. in the ground for 1/4 sec. cor., with brass cap marked

1/4 S2 | S1
1925

Dig pits 18 x 18 x 12 ins., one each N. and S. 3 ft. dist.

79.97 The cor. of secs. 1,2,11 and 12.

Land: level.

Chains	<p>Soil: adobe, 1st rate. Timber: none. Undergrowth: greasewood and mesquite.</p>
0.06 24.10 40.00	<p>From the cor. of secs. 14, 15, 22 and 23, hereinbefore described N. 0° 01' W., on a true line bet. secs. 14 and 15. Over level land; through scattering undergrowth. Fence brs. E. and W. Wash, 10 lks. wide, course NE. Set an iron post, 3 ft. long, 1 in. in dia., 26 ins. in the ground for $\frac{1}{4}$ sec. cor., with brass cap marked</p>
	$\begin{array}{c} \uparrow \\ S15 \mid S14 \\ 1925 \end{array}$
57.70 73.00 80.00	<p>Dig pits 18 x 18 x 12 ins., one each N. and S. 3 ft. dist; Road brs. NE. and SW. Reservoir brs. E., 5 chs. dist. Set an iron post, 3 ft. long, 2 ins. in dia., 26 ins. in the ground for cor. of secs. 10, 11, 14 and 15, with brass cap marked</p>
	$\begin{array}{c} T9S \ R1E \\ S10 \mid S11 \\ \hline S15 \mid S14 \\ 1925 \end{array}$
	<p>Dig pits 18 x 18 x 12 ins., one in each sec. 3 ft. dist; Land: level. Soil: adobe, 1st rate. Timber: none. Undergrowth: greasewood and mesquite.</p>
40.00 80.06	<p>East, on a random line bet. secs. 11 and 14. Set temp. $\frac{1}{4}$ sec. cor. Intersect the cor. of secs. 11, 12, 13 and 14. Thence West, on a true line bet. secs. 11 and 14. Over level land; through scattering undergrowth. Set an iron post, 3 ft. long, 1 in. in dia., 26 ins. in the ground for $\frac{1}{4}$ sec. cor., with brass cap marked</p>
40.03	$\begin{array}{c} S11 \\ \hline \frac{1}{4} S14 \\ 1925 \end{array}$
58.40 80.06	<p>Dig pits 18 x 18 x 12 ins., one each E. and W. 3 ft. dist. Road brs. NE. and SW. The cor. of secs. 10, 11, 14 and 15. Land: level. Soil: adobe, 1st rate. Timber: none. Undergrowth: greasewood and mesquite.</p>
8.90 40.00	<p>N. 0° 01' W., bet. secs. 10 and 11. Over level land; through scattering undergrowth. Wash, 10 lks. wide, course NE. Set an iron post, 3 ft. long, 1 in. in dia., 26 ins. in the ground for $\frac{1}{4}$ sec. cor., with brass cap marked</p>

Partial Survey of
Subdivisions of Township 9 South, Range 1 East.

Chains

S10 | S11
1925

79.95 Dig pits 18 x 18 x 12 ins., one each N. and S. 3 ft.
89.00 dist.
Wash, 10 lks. wide, course NE.
Set an iron post, 3 ft. long, 2 ins. in dia., 26 ins. in
the ground for cor. of secs. 2, 3, 10 and 11, with brass
cap marked

T9S R1E
S3 | S2
S10 | S11
1925

from which
A mesquite, 5 ins. in dia., brs. N. 64 1/2° E., 47 lks.
dist., marked T9S R1E S2 BT.
A mesquite, 4 ins. in dia., brs. S. 46 1/2° E., 230 lks.
dist., marked T9S R1E S11 BT.
A mesquite, 8 ins. in dia., brs. S. 49° W., 70 lks.
dist., marked T9S R1E S10 BT.
A mesquite, 6 ins. in dia., brs. N. 37 1/2° W., 81 lks.
dist., marked T9S R1E S3 BT.

Land: level.
Soil: adobe, 1st rate.
Timber: none.
Undergrowth: greasewood and mesquite.

40.00 East, on a random line bet. secs. 2 and 11.
79.98 Set temp. 1/4 sec. cor.
Fall 5 lks. N. of the cor. of secs. 1, 2, 11 and 12.
Thence
N. 89° 58' W., on a true line bet. secs. 2 and 11.
Over level land thru scattering timber and undergrowth.
Wash, 15 lks. wide, course N.
34.00 Set an iron post, 3 ft. long, 1 in. in dia., 26 ins. in
39.99 the ground for 1/4 sec. cor., with brass cap marked

S2
S11
1925

79.98 Dig pits 18 x 18 x 12 ins., one each E. and W. 3 ft.
dist.
The cor. of secs. 2, 3, 10 and 11.
Land: level.
Soil: adobe, 1st rate.
Timber: mesquite.
Undergrowth: same and greasewood.

40.00 N. 0° 02' E., on a random line bet. secs. 2 and 3.
79.93 Set temp. 1/4 sec. cor.
Intersect the cor. of secs. 2, 3, 34 and 35, on the N.
bdy of the Tp., described in Book "B" of this Group.
Thence
S. 0° 02' W., on a true line bet. secs. 2 and 3.
Over level land; through scattering undergrowth.
0.70 Wash, 10 lks. wide, course NE,
3.30 Wash, 10 lks. wide, course E.
6.30 Wash, 10 lks. wide, course NE.
39.93 Set an iron post, 3 ft. long, 1 in. in dia., 26 ins. in
the ground for 1/4 sec. cor., with brass cap marked

S3 | S2
1925

Partial Survey of
Subdivisions of Township 9 South, Range 1 East.

Chains

Dig pits 18 x 18 x 12 ins., one each N. and S. 3 ft. dist.

- 49.50 Wash, 10 lks. wide, course NE.
- 79.40 Wash, 10 lks. wide, course E.
- 79.93 The cor. of secs. 2, 3, 10 and 11.
Land: level.
Soil: adobe, 1st rate.
Timber: none.
Undergrowth: greasewood and mesquite.

From the cor. of secs. 15, 16, 21 and 22, hereinbefore described

N. 0° 02' W., on a true line bet. secs. 15 and 16.
Over level land; through scattering undergrowth.
Fence brs. E. and W.

- 0.08
- 1.70 Wash, 10 lks. wide, course NE.
- 12.00 Wash, 10 lks. wide, course NE.
- 39.80 Wash, 10 lks. wide, course NE.
- 40.00 Set an iron post, 3 ft. long, 1 in. in dia., 18 ins. in the ground, supported by a mound of stone, for $\frac{1}{4}$ sec. cor., with brass cap marked

$\frac{1}{4}$
 S16 | S15
 1925

from which

A mesquite, 6 ins. in dia., brs. S. 27° E., 12 lks. dist., marked $\frac{1}{4}$ S15 BT.

A mesquite, 4 ins. in dia., brs. S. 37 $\frac{1}{2}$ ° W., 218 lks. dist., marked $\frac{1}{4}$ S16 BT.

- 51.80 Wash, 10 lks. wide, course E.
- 57.00 Wash, 10 lks. wide, course NE.
- 67.30 Wash, 10 lks. wide, course NE.
- 79.20 Wash, 10 lks. wide, course NE.
- 80.00 Set an iron post, 3 ft. long, 2 ins. in dia., 26 ins. in the ground for cor. of secs. 9, 10, 15 and 16, with brass cap marked

T9S R1E
39 | S10
 S16 | S15
 1925

Dig pits 18 x 18 x 12 ins., one in each sec. 3 ft. dist.

Land: level.
Soil: sandy loam, 1st rate.
Timber: none.
Undergrowth: greasewood and mesquite.

West, on a random line, bet. secs. 10 and 15.

- 40.00 Set temp. $\frac{1}{4}$ sec. cor.
- 79.90 Fall 5 lks. N. of the cor. of secs. 10, 11, 14 and 15.
Thence
N. 89° 58' W., on a true line bet. secs. 10 and 15.
Over level land; through scattering undergrowth.
- 7.60 Wash, 10 lks. wide, course NE.
- 39.95 Set an iron post, 3 ft. long, 1 in. in dia., 26 ins. in the ground for $\frac{1}{4}$ sec. cor., with brass cap marked

$\frac{1}{4}$ S10
4 S15
 1925

Partial Survey of
Subdivisions of Township 9 South, Range 1 East.

Chains

Dig pits 18 x 18 x 12 ins., one each E. and W. 3 ft. dist.

40.70 Wash, 10 lks. wide, course NE.
76.70 Wash, 10 lks. wide, course NE.
79.90 The cor. of secs. 9, 10, 15 and 16.

Land: level.
Soil: sandy loam, 1st rate.
Timber: none.
Undergrowth: greasewood and mesquite.

N. 0° 02' W., bet. secs. 9 and 10.

35.20 Over level land; through scattering undergrowth;
40.00 Wash, 10 lks. wide, course NE.
Set an iron post, 3 ft. long, 1 in. in dia., 26 ins. in the ground for 1/4 sec. cor., with brass cap marked

S9 | S10
1925

Dig pits 18 x 18 x 12 ins., one each N. and S. 3 ft. dist.

80.00 Set an iron post, 3 ft. long, 2 ins. in dia., 26 ins. in the ground for cor. of secs. 3, 4, 9 and 10, with brass cap marked

T9S R1E
S4 | S3
S9 | S10
1925

from which

- A palo verde, 6 ins. in dia., brs. N. 48 1/2° E., 172 lks. dist., marked T9S R1E S3 BT.
- A mesquite, 7 ins. in dia., brs. S. 48 1/2° E., 283 lks. dist., marked T9S R1E S10 BT.
- A mesquite, 10 ins. in dia., brs. S. 2 1/2° W., 537 lks. dist., marked T9S R1E S9 BT.
- A mesquite, 5 ins. in dia., brs. N. 2 1/2° W., 330 lks. dist., marked T9S R1E S4 BT.

Land: level.
Soil: sandy loam, 1st. rate.
Timber: none.
Undergrowth: greasewood and mesquite.

40.00 S. 89° 58' E., on a random line bet. secs. 3 and 10.
79.90 Set temp. 1/4 sec. cor.
Fall 10 lks. S. of the cor. of secs. 2, 3, 10 and 11.

Thence
S. 89° 58' W., on a true line bet. secs. 3 and 10.

4.70 Over level land; through scattering undergrowth.
39.95 Wash. 10 lks. wide, course NE.
Set an iron post, 3 ft. long, 1 in. in dia., 26 ins. in the ground for 1/4 sec. cor., with brass cap marked

S3
S10
1925

Dig pits 18 x 18 x 12 ins., one each E. and W. 3 ft. dist.

76.20 Wash, 10 lks. wide, course SE.
79.90 The cor. of secs. 3, 4, 9 and 10.
Land: level.
Soil: sandy loam, 1st rate.

Chains

Timber: none.
Undergrowth: greasewood and mesquite.

40.00 N. 0°02'E., on a random line bet. secs. 3 and 4.
Set temp. $\frac{1}{4}$ sec. cor.
79.82 Intersect the cor. of secs. 3, 4, 33 and 34, on the N. bdy.
of the Tp., described in Book "B" of this Group.
Thence
S. 0°02'W., on a true line bet. secs. 3 and 4.
Over level land; through scattering undergrowth.
5.10 Wash, 10 lks. wide, course NE.
7.90 Wash, 10 lks. wide, course NE.
22.20 Wash, 10 lks. wide, course NE.
24.90 Wash, 10 lks. wide, course NE.
39.82 Set an iron post, 3 ft. long, 1 in. in dia., 26 ins. in
the ground for $\frac{1}{4}$ sec. cor., with brass cap marked

S4 | S3
1925

44.80 Dig pits 18 x 18 x 12 ins., one each N. and S. 3 ft.
dist.
79.82 Wash, 20 lks. wide, course NE.
The cor. of secs. 3, 4, 9 and 10.
Land: level.
Soil: sandy loam, 2nd rate.
Timber: none.
Undergrowth: greasewood and mesquite.

From the cor. of secs. 16, 17, 20 and 21, hereinbefore
described.
N. 0°02'W., on a true line bet. secs. 16 and 17.
Over level land; through scattering undergrowth.
1.50 Wash, 10 lks. wide, course NE.
14.80 Wash, 20 lks. wide, course NE.
40.00 Set an iron post, 3 ft. long, 1 in. in dia., 20 ins. in
the ground, supported by a mound of stone, for $\frac{1}{4}$
sec. cor., with brass cap marked

S17 | S16
1925

from which
A palo verde, 8 ins. in dia., brs. N. 12 $\frac{1}{4}$ °E., 353
lks. dist., marked $\frac{1}{4}$ S16 BT.
A mesquite, 14 ins. in dia., brs. S. 14 $\frac{1}{4}$ °W., 326
lks. dist., marked $\frac{1}{4}$ S17 BT.
43.00 Wash, 20 lks. wide, course NE.
48.60 Wash, 10 lks. wide, course NE.
68.70 Wash, 10 lks. wide, course NE.
70.80 Wash, 10 lks. wide, course NE.
77.40 Wash, 10 lks. wide, course NE.
80.00 Set an iron post, 3 ft. long, 2 ins. in dia., 24 ins.
in the ground for cor. of secs. 8, 9, 16 and 17, with
brass cap marked

T9S R1E
S8 | S9
S17 | S16
1925

from which
A palo verde, 5 ins. in dia., brs. N. 5 $\frac{1}{2}$ °E., 236
lks. dist., marked T9S R1E S9 BT.

Partial Survey of the
Subdivisions of Township 9 South, Range 1 East.

Chains

A mesquite, 5 ins. in dia., brs. S.50°E., 165 lks. dist., marked T9S R1E S16 BT.
A palo verde, 8 ins. in dia., brs. S.39°W., 294 lks. dist., marked T9S R1E S17 BT.
A palo verde, 5 ins. in dia., brs. N.39½°W., 359 lks. dist., marked T9 S R1E S8 BT.

Land: level.
Soil: sandy loam, 1st rate.
Timber: none.
Undergrowth: greasewood and palo verde and mesquite.

40.00 East, on a random line bet. secs. 9 and 16.
79.96 Set temp. ¼ sec. cor.
Fall 5 lks. S. of the cor. of secs. 9,10,15 and 16.
Thence
S.89°58'W., on a true line bet. secs. 9 and 16.
Over level land; through scattering undergrowth.
13.90 Wash, 10 lks. wide, course NE.
26.70 Wash, 10 lks. wide, course NE.
39.98 Set an iron post, 3 ft. long, 1 in. in dia., 26 ins. in the ground for ¼ sec. cor., with brass cap marked

S9
S16
1925

Dig pits 18 x 18 x 12 ins., one each E. and W., 3 ft. dist.

47.90 Wash, 10 lks. wide, course NE.
61.10 Wash, 10 lks. wide, course NE.
74.70 Wash, 15 lks. wide, course NE.
79.96 The cor. of secs. 8,9,16 and 17.

Land: level.
Soil: sandy loam, 1st rate.
Timber: none.
Undergrowth: greasewood, palo verde and mesquite.

20.60 N.0°02'W., on a true line bet. secs. 8 and 9.
25.90 Over level land; through scattering undergrowth.
40.00 Wash, 10 lks. wide, course NE.
Wash, 40 lks. wide, course E.
Set an iron post, 3 ft. long, 1 in. in dia., 26 ins. in the ground for ¼ sec. cor., with brass cap marked

S8 | S9
1925

from which

54.50 A palo verde, 5 ins. in dia., brs. N.75°E., 144 lks. dist., marked ¼ S9 BT.
73.60 A palo verde, 10 ins. in dia., brs. S.77½°W., 295 lks. dist., marked ¼ S8 BT.
80.00 Wash, 20 lks. wide, course NE.
Wash, 10 lks. wide, course NE.
Set an iron post, 3 ft. long, 2 ins. in dia., 26 ins. in the ground for cor. of secs. 4,5,8 and 9, with brass cap marked

T9S R1E
S5 | S4
S8 | S9
1925

Chains

Dig pits 18 x 18 x 12 ins., one in each sec. 3 ft. dist.

Land: level.

Soil: gravel, 2nd rate.

Timber: none.

Undergrowth: greasewood, palo verde and mesquite.

40.00 N. 89° 58' E., on a random line bet. secs. 4 and 9.
Set temp. $\frac{1}{4}$ sec. cor.
79.98 Fall 2 lks. N. of the cor. of secs. 3, 4, 9 and 10,
Thence
S. 89° 59' W., on a true line bet. secs. 4 and 9.
Over level land; through scattering undergrowth.
22.40 Wash, 10 lks. wide, course NE.
38.40 Wash, 10 lks. wide, course NE.
39.99 Set an iron post, $\frac{3}{4}$ ft. long, 1 in. in dia., 26 ins. in
the ground for $\frac{1}{4}$ sec. cor., with brass cap marked

S4
S9
1925

Dig pits 18 x 18 x 12 ins., one each E. and W. 3 ft. dist.

63.40 Wash, 20 lks. wide, course NE.

79.98 The cor. of secs. 4, 5, 8 and 9.

Land: level.

Soil: sandy loam 1st rate.

Timber: none.

Undergrowth: greasewood, palo verde and mesquite.

40.00 N. 0° 02' E., on a random line bet. secs. 4 and 5.
Set temp. $\frac{1}{4}$ sec. cor.
79.90 Fall 2 lks. E. of the cor. of secs. 4, 5, 32 and 33, on
the N. bdy. of the Tp., described in Book "B" of
this Group.
Thence
S. 0° 01' W., on a true line bet. secs. 4 and 5.
Over level land; through scattering undergrowth.
14.90 Wash, 10 lks. wide, course NE.
37.70 Wash, 30 lks. wide, course NE.
39.90 Set an iron post, $\frac{3}{4}$ ft. long, 1 in. in dia., 26 ins. in
the ground for $\frac{1}{4}$ sec. cor., with brass cap marked

S5 | S4
1925

from which

A palo verde, 4 ins. in dia., brs. S. 8 $\frac{1}{2}$ ° E., 208
lks. dist., marked $\frac{1}{4}$ S4 BT.

A mesquite, 12 ins. in dia., brs. N. 24 $\frac{1}{2}$ ° W., 158
lks. dist., marked $\frac{1}{4}$ S5 BT.

63.30 Wash, 10 lks. wide, course NE.

72.50 Wash, 10 lks. wide, course NE.

79.90 The cor. of secs. 4, 5, 8 and 9.

Land: level.

Soil: gravel, 2nd rate.

Timber: none.


Undergrowth: greasewood, palo verde and mesquite.

Partial Survey of
Subdivisions of Township 9 South, Range 1 East.

Chains


From the cor. of secs. 17,18,19 and 20, hereinbefore described.

- N.0°03'W., on a true line, bet. secs. 17 and 18.
- Over level land; through scattering undergrowth.
- 8.10 Wash, 10 lks. wide, course NE.
- 24.40 Wash, 10 lks. wide, course NE.
- 40.00 Set an iron post, 3 ft. long, 1 in. in dia., 26 ins. in the ground for $\frac{1}{4}$ sec. cor., with brass cap marked



From which


- A palo verde, 7 ins. in dia., brs. S.62 $\frac{1}{4}$ °E., 212 lks. dist., marked $\frac{1}{4}$ S17 BT.
- A palo verde, 5 ins. in dia., brs. N.34 $\frac{3}{4}$ °W., 150 lks. dist., marked $\frac{1}{4}$ S18 BT.
- 46.50 Wash, 15 lks. wide, course NE.
- 74.60 Wash, 40 lks. wide, course NE.
- 80.00 Set an iron post, 3 ft. long, 2 ins. in dia., 26 ins. in the ground for cor. of secs. 7,8,17 and 18, with brass cap marked



Raise a mound of stone 3 ft. base, 1 $\frac{1}{2}$ ft. high, W. of post.

Land: level.
 Soil: gravel, 2nd rate.
 Timber: none.
 Undergrowth: greasewood, palo verde and mesquite.

- East, on a random line, bet. secs. 8 and 17.
- 40.00 Set temp. $\frac{1}{4}$ sec. cor.
- 80.08 Intersect the cor. of secs. 8,9,16 and 17.
- Thence
- West, on a true line bet. secs. 8 and 17.
- Over level land; through scattering undergrowth.
- 19.30 Wash, 10 lks. wide, course NE.
- 27.00 Wash, 10 lks. wide, course NE.
- 40.04 Set an iron post, 3 ft. long, 1 in. in dia., 26 ins. in the ground for $\frac{1}{4}$ sec. cor., with brass cap marked



from which

- A palo verde, 7 ins. in dia., brs. S. 36 $\frac{1}{2}$ °E., 316 lks. dist., marked $\frac{1}{4}$ S17 BT.
- A mesquite, 5 ins. in dia., brs. N.80°W., 140 lks. dist., marked $\frac{1}{4}$ S8 BT.
- 41.60 Wash, 10 lks. wide, course NE.
- 53.00 Wash, 10 lks. wide, course NE.
- 71.00 Wash, 10 lks. wide, course NE.
- 73.80 Wash, 10 lks. wide, course NE.
- 80.08 The cor. of secs. 7,8,17 and 18.
- Land: level.
- Soil: gravel, 2nd rate.
- Timber: none.
- Undergrowth: greasewood, palo verde and mesquite.

Partial Survey of
Subdivisions of Township 9 South, Range 1 East.

Chains

S.89°57'W., on a random line bet. secs. 7 and 18.
 40.00 Set temp. $\frac{1}{4}$ sec. cor.
 79.23 Fall 4 lks. N. of the cor. of secs. 7, 12, 13 and 18, on the
 W. bdy. of the Tp., which was re-established in 1914,
 under Group No. 38. This cor. is an iron post, 3 ins. in dia.
 in dia. $\frac{1}{4}$ firmly set, properly marked on brass cap,
 and witnessed by pits.

Thence
 N.89°55'E., on a true line bet. secs. 7 and 18.
 Over level land; through scattering undergrowth.
 19.50 Wash, 10 lks. wide, course SE.
 26.70 Wash, 10 lks. wide, course SE.
 33.90 Wash, 10 lks. wide, course SE.
 39.23 Set an iron post, 1 in. in dia., 3 ft. long, 26 ins. in
 the ground for $\frac{1}{4}$ sec. cor., with brass cap marked

S7
 S18
 1925

from which

An ironwood, 9 ins. in dia., brs. S.9°E., 65 lks.
 dist., marked $\frac{1}{4}$ S18 BT.
 An ironwood, 6 ins. in dia., brs. N.17 $\frac{1}{2}$ °W., 90 lks.
 dist., marked $\frac{1}{4}$ S7 BT.

79.23 The cor. of secs. 7, 8, 17 and 18.
 Land: level.
 Soil: gravel, 2nd rate.
 Timber: none.
 Undergrowth: greasewood, palo verde and ironwood.

N.0°03'W., on a true line bet. secs. 7 and 8.
 Over level land; through scattering undergrowth.
 7.70 Wash, 10 lks. wide, course NE.
 9.80 Wash, 20 lks. wide, course SE.
 25.30 Wash, 10 lks. wide, course NE.
 38.60 Wash, 10 lks. wide, course E.
 40.00 Set an iron post, 3 ft. long; 1 in. in dia., 26 ins. in
 the ground for $\frac{1}{4}$ sec. cor., with brass cap marked

S7 | S8
 1925

from which

A palo verde, 6 ins. in dia., brs. S.9 $\frac{1}{4}$ °E., 125
 lks. dist., marked $\frac{1}{4}$ S8 BT.
 A palo verde, 6 ins. in dia., brs. S.35°W., 101
 lks. dist., marked $\frac{1}{4}$ S7 BT.

45.40 Wash, 10 lks. wide, course NE.
 48.10 Wash, 20 lks. wide, course SE.
 60.10 Wash, 10 lks. wide, course NE.
 64.50 Wash, 10 lks. wide, course E.
 79.00 Wash, 10 lks. wide, course NE.
 80.00 Set an iron post, 3 ft. long, 2 ins. in dia., 22 ins. in
 the ground, supported by a mound of stone, for cor. of
 secs. 5, 6, 7 and 8; with brass cap marked

T9S R1E
 S6 | S5
 S7 | S8
 1925

from which

An ironwood, 8 ins. in dia., brs. N.64 $\frac{1}{2}$ °E., 51 lks.
 dist., marked T9S R1E S5 BT.

Partial Survey of
Subdivisions of Township 9 South, Range 1 East.

Chains

A palo verde, 5 ins. in dia., brs. S.24 $\frac{1}{2}$ °E., 232
lks. dist., marked T9S R1E S8 BT.
An ironwood, 8 ins. in dia., brs. S.56 $\frac{1}{2}$ °W., 22
lks. dist., marked T9S R1E S7 BT.
A palo verde, 6 ins. in dia., brs. N.49°W., 334
lks. dist., marked T9S R1E S6 BT.

Land: level.

Soil: gravel, 2nd rate.

Timber: ironwood and palo verde.

Undergrowth: same and greasewood.

40.00 East, on a random line bet secs. 5 and 8.
Set temp. $\frac{1}{4}$ sec. cor:
80.06 Fall 94 lks. N. of the cor. of secs. 4, 5, 8 and 9.
Thence
N.89°58'W., on a true line bet. secs. 5 and 8.
Over level land; through scattering undergrowth.
22.40 Wash, 10 lks. wide, course NE.
40.03 Set an iron post, 3 ft. long, 1 in. in dia., 26 ins. in
the ground for $\frac{1}{4}$ sec. cor., with brass cap marked

S5
S8
1925

from which

An ironwood, 5 ins. in dia., brs. N.55°E., 90 lks.
dist., marked S5 BT.
An ironwood, 4 ins. in dia., brs. S.89 $\frac{1}{2}$ °W., 43 lks.
dist., marked $\frac{1}{4}$ S8 BT.
49.20 Wash, 10 lks. wide, course NE.
77.70 Wash, 10 lks. wide, course NE.
80.06 The cor. of secs. 5, 6, 7 and 8.

Land: level.

Soil: gravel, 2nd rate.

Timber: ironwood.

Undergrowth: same and palo verde and greasewood.

40.00 S.89°55'W., on a random line bet. secs. 6 and 7.
Set temp. $\frac{1}{4}$ sec. cor.
79.15 Fall 9 lks. S. of the cor. of secs. 1, 6, 7 and 12, on the
W. bdy. of the Tp., which was re-established in 1914,
under Group No. 38. This cor. is an iron post, 3 ins.
in dia., projecting 12 ins. above ground, firmly set,
properly marked on brass cap, and witnessed by pits.
Thence
N.89°59'E., on a true line bet. secs. 6 and 7.
Over level land; through scattering undergrowth.
39.15 Set an iron post, 3 ft. long, 1 in. in dia., 20 ins. in
the ground, supported by a mound of stone, for $\frac{1}{4}$ sec.
cor., with brass cap marked

S6
S7
1925

from which

A palo verde, 5 ins. in dia., brs. N.5°E., 92 lks.
dist., marked $\frac{1}{4}$ S6 BT.
A palo verde, 6 ins. in dia., brs. S.15 $\frac{1}{2}$ °W., 39 lks.
dist., marked $\frac{1}{4}$ S7 BT.
60.00 Wash, 10 lks. wide, course NE.
79.15 The cor. of secs. 5, 6, 7 and 8.
Land: level.
Soil: gravel, 2nd rate.

Partial Survey of
Subdivisions of Township 9 South, Range 1 East.

Chains

Timber: ironwood and palo verde.
Undergrowth: same and greasewood.

40.00
79.82

N. 9° 01' E., on a random line bet. secs. 5 and 6.
Set temp. $\frac{1}{4}$ sec. cor.
Fall 14 lks. W. of the cor. of secs. 5, 6, 31 and 32, on
the N. bdy. of the Tp., described in Book "B" of this
Group.

8.50
29.80
36.40
39.82

Thence
S. 9° 07' E., on a true line bet. secs. 5 and 6.
Over level land; through scattering undergrowth.
Wash, 10 lks. wide, course NE.
Wash, 10 lks. wide, course E.
Wash, 10 lks. wide, course E.
Set an iron post, 3 ft. long, 1 in. in dia., 26 ins. in
the ground for $\frac{1}{4}$ sec. cor., with brass cap marked

S6 S5
1925

from which

45.00
52.30
64.30
70.00
79.82

An ironwood, 8 ins. in dia., brs. N. 59° E., 179 lks.
dist., marked S5 BT.
A palo verde, 12 ins. in dia., brs. S. 59° W., 170
lks. dist., marked S6 BT.
Wash, 10 lks. wide, course NE.
Wash, 10 lks. wide, course NE.
Wash, 10 lks. wide, course E.
Wash, 10 lks. wide, course E.
The cor. of secs. 5, 6, 7 and 8.
Land: level.
Soil: gravel, 2nd rate.
Timber: none.
Undergrowth: palo verde, ironwood and greasewood.

Latitudes, departures and closing errors.

Line designated	True Bearing	Dist- ance	Latitudes		Departures	
			N.	S.	E.	W.
Subdivisional Bdy.s	West S. 89° 57' W.	400.00 79.30				400.00 79.30
West Bdy. (G. & S. R. Mer.)	North	240.00	240.00			
North Bdy.	S. 89° 59' E.	479.34		.14	479.34	
East Bdy.	South	240.00		240.00		
Convergency					.23	
Totals			240.00	240.21	479.57	479.30
				240.00	479.30	
Error in latitude-----			-0.21			
Error in departure-----			-0.27			

GENERAL DESCRIPTION

The north half of this township has a level surface, draining to the North and Northeast.

The soil is adobe, sandy and gravelly, 1st and 2nd rate. There is very little timber.

The undergrowth is scattering and consists of greasewood, scrub mesquite, catclaw, paloverde, ocotillo and creosote. There is some giant cactus in the western part.

A fair growth of native grasses is prevalent in all sections.

There is no permanent running water.

A reservoir for periodical storage of water is located in the NW. 1/4 of sec. 14.

There are no settlers residing in the township, and the only improvement consists of a fence extending E. and W. thru the tp. along the middle latitudinal sec. line, and N. and S. along the north half of the East bdy. of the tp.

There are no indications of valuable mineral deposits of any kind.

The south half of this township is entirely within the Papago Indian Reservation.

CERTIFICATE OF UNITED STATES TRANSITMAN.

I, Charles E. Hunter, U.S. Transitman, hereby certify upon honor that, in pursuance of special instructions received from the U. S. Surveyor General, for Group 101, Arizona bearing date of the 24th day of May, 1924, I have well, faithfully, and truly in my own proper person, and in strict conformity with said instructions, the Manual of Surveying Instructions, and the laws of the United States, surveyed all those parts or portions of the

Subdivision lines of

TOWNSHIP 9 SOUTH, RANGE 1 EAST,

of the Gila and Salt

River Base and Meridian, in the State of Arizona, which are represented in the foregoing field notes/as having been executed by me, and under my direction; and that all the corners of said survey have been established and perpetuated in strict accordance with the Manual of Surveying Instructions, and the special written instructions of the U. S. Surveyor General, for Group 101, Arizona and in the specific manner described in the field notes, and that the foregoing are the original field notes of such survey.

Place Phoenix Arizona.

Date May 1, 1926.

Charles E. Hunter
U.S. Transitman.

APPROVAL.

OFFICE OF THE UNITED STATES Supervisor of Surveys

Denver, Colorado, August 23, 1926

The foregoing field notes of the survey of the Subdivision lines of the North half of

TOWNSHIP 9 SOUTH, RANGE 1 EAST,

of the Gila and Salt River Base and Meridian, in the State of Arizona,

executed by Charles E. Hunter, U.S. Transitman

under his special instructions dated February 3, 1925, for Group 101, Arizona having been critically examined, and the necessary corrections and explanations made, the said field notes, and the surveys they describe, are hereby approved.

U.S. Supervisor of Surveys.

I certify that the foregoing transcript of the field notes of the above described surveys in has been correctly copied from the original notes on file in this office.