

4-679

Book "B"

BOOK 3976

# FIELD NOTES

OF THE SURVEY OF THE

SOUTH and WEST BOUNDARIES

and

SUBDIVISIONS

of

T.6 N., R.9 W.

3976

Of the Gila and Salt River Base and Meridian,

In the State of ARIZONA.

EXECUTED BY

Dupree R. Averill.

3976

In the capacity of U. S. Surveyor..., under Special Instructions dated October 6..., 19 31, issued by the District Cadastral Engineer to govern surveys included in Group No. 171..., which were approved by the Commissioner of the General Land Office, Dec. 1..., 1931..., and Assignment Instructions dated Nov. 18..., 19 31.

Survey commenced December 2., 19 31.

Survey completed December 31., 19 31.

BOOK 3976

# INDEX DIAGRAM.

Township 6 North, Range 9 West.

9	6	50	5	38	4	29	3	22	2	15	1
	49		48		37		28		21		14
8	7	47	8	36	9	28	10	20	11	14	12
	47		46		35		27		20		13
7	13	45	17	34	16	26	15	19	14	13	18
	44		43		34		25		18		12
6	19	43	20	33	21	25	22	18	23	12	24
	42		41		32		24		17		11
6	30	40	29	31	28	24	27	17	26	11	25
	40		39		30		23		16		10
5	31	38	32	30	33	22	34	16	35	10	36
	4		3		3		2		2		1

SOUTH BOUNDARY OF T.6 N.,R.9 W.

chains


The survey was executed with a light mountain transit made by Buff & Buff, Serial No. I7992. For description of equipment and test of instrument see field notes of the first standard parallel north through R.9 W., surveyed under this group.

The east and north boundaries of the township were surveyed by Hesse and Oliver, U.S. Surveyors in 1910. Closing corners were established on the east boundary under the survey of the subdivisions of T.6 N.,R.8 W.. executed by Dupree R. Averill, U.S. Surveyor in 1929. the original corners being appropriately altered to refer to sections of R.9 W., only.

From the cor. of Tps.5 and 6 N.,R.9 W.

West, on a random line, setting temp. 1/4 sec. and sec. cors. at intervals of 40 chs. along the line bet. Tps. 5 and 6 N.,R.9 W. At 480.40 chs. intersect N. and S. line 69 lks. N. of the cor. of Tps. 5 and 6 N.,Rs. 9 and 10 W.

The cor. of Tps. 5 and 6 N.,R.9 W. is an iron post, 3 ins. diam., 12 ins. above ground, mkd on brass cap.



witnessed by a mound of stone 2 1/2 ft. base, 1 1/2 ft. high, W. of cor.


Thence

S.89°55'W. on true line bet. secs. 1 and 36.

Over gently rolling land, through scattered undergrowth.

7.90 Old road, bears N.30°W. and S.30°E.


40.00 Set an iron post, 3 ft. long, 1 in. diam., 18 ins. in the ground, to bedrock, with marked (X) stone deposited alongside, and in a mound of stone to top, for 1/4 sec. cor., with brass cap mkd.



50.20 Drain, course N.60°W.

78.50 Drain, course N.

80.00 Set an iron post, 3 ft. long, 2 ins. diam., 20 ins. in the ground, to bedrock, with marked (X) stone deposited alongside, and in a mound of stone to top, for the cor. of secs. 1, 2, 35 and 36, with brass cap mkd.



Land, gently rolling. Soil, rocky, 2nd. rate. No timber; undergrowth, greasewood.

## SOUTH BOUNDARY OF T.6 N., R.9 W.

chains	S.89°55'W. bet.secs. 2 and 35. Over rolling land, through scattered undergrowth.
16.00	Wash, 15 lks. wide, course NW.
37.70	Old road, bears NE. and SW.
37.90	Wire fence, bears N.50°E. and S.50°W. Across flat bottom land, draining SW.
40.00	Set an iron post, 3 ft. long, 1 in. diam. 30 ins. in the ground, with marked (X) stone deposited alongside. for $\frac{1}{4}$ sec. cor., with brass cap mkd.
	$\frac{1}{4} \frac{S \ 35}{S \ 2}$ 1931
50.00	Leave bottom land.
69.10	Wire fence, bears N.14°E. and S.14°W.
69.80	Road, bears N.15°E. to Aguila, and S.15°W. to Tiger Mine.
80.00	Set an iron post, 3 ft. long, 2 ins. diam. 30 ins. in the ground, with marked (X) stone deposited alongside. for the cor. of secs., 2, 3, 34 and 35, with brass cap mkd.
	$\begin{array}{c} T6N \ R9W \\ S \ 34 \ S \ 35 \\ S \ 3 \ S \ 2 \\ T5N \\ 1931 \end{array}$
	Well and pump. bears S.27°E. 23.50 chs. dist., Ranch house (Crabbs) bears S.24°E. 30.50 chs. dist. Land, gently rolling and level. Soil, gravelly and clay gumbo, 2nd. rate. Timber, scattered paloverde and mesquite; undergrowth, greasewood and catclaw.
	-----
	S.89°55'W. bet.secs. 3 and 34. Over rolling land, through scattered paloverde and undergrowth.
2.90	Flat wash, 30 lks. wide, course S.30°E.
40.00	Set an iron post, 3 ft. long, 1 in. diam., 24 ins. in the ground, to bedrock, with marked (X) stone deposited alongside, and in a mound of stone to top, for $\frac{1}{4}$ sec. cor., with brass cap mkd.
	$\frac{1}{4} \frac{S \ 34}{S \ 3}$ 1931
44.40	Small wash, course S.10°E.
59.00	Old road, (abandoned) bears NW. and SE.
59.90	Wash, 10 lks. wide, course SE.; asc. 30 ft.
72.50	Low spur, extends SE.; desc. 30 ft.

SOUTH BOUNDARY OF T.6 N.,R.9 W.

BOOK 3976

chains

80.00

Set an iron post, 3 ft. long, 2 ins. diam. .30 ins. in the ground, for the cor. of secs. 3, 4, 33 and 34, with brass cap mkd.

T6N R9W	
S 33	S 34
S 4	S 3
T5N	
1931	

raise a mound of stone 3 ft. base, 2 ft. high, W. of cor.

Land, gently rolling.  
Soil, gravelly and rocky, 2nd. rate.  
Timber, scattered paloverde; undergrowth, greasewood and cacti.

S.89°55'W. bet. secs. 4 and 33.

Over rolling land, through scattered paloverde and greasewood.

0.40 Flat wash, 60 lks. wide, course S.

10.00 Drain, course S.20°E.

33.10 Wash, 30 lks. wide, course S.

40.00 Set an iron post, 3 ft. long, 1 in. diam. .30 ins. in the ground, for 1/4 sec. cor. with brass cap mkd.

1/4 S 33
S 4

1931

raise a mound of stone, 2 ft. base, 1 1/2 ft. high, N. of cor.

50.90 Wash, 15 lks. wide, course S.25°E.

62.90 Wash, 20 lks. wide, course S.30°E.

71.50 Wash, 30 lks. wide, course S.30°E.

79.25 Small wash, course S.30°E.

80.00 Set an iron post, 3 ft. long, 2 ins. diam. .30 ins. in the ground, for the cor. of secs. 4, 5, 32 and 33, with brass cap mkd.

T6N R9W	
S 32	S 33
S 5	S 4
T5N	
1931	

raise a mound of stone, 3 ft. base, 2 ft. high, W. of cor.

Land, rolling.  
Soil, gravelly and rocky, 2nd. rate.  
Timber, paloverde; undergrowth, greasewood and cacti.

S.89°55'W. bet. secs. 5 and 32.

Over rolling land, through scattered paloverde and undergrowth.

## SOUTH BOUNDARY OF T.6 N., R.9 W.

chains

- 11.10 Wash, 10 lks. wide, course S.20°E.  
 20.20 Wash, 10 lks. wide, course S.10°E.  
 34.30 Wash, 30 lks. wide, course S.  
 40.00 Set an iron post, 3 ft. long, 1 in. diam., 30 ins. in the ground, with marked (X) stone deposited alongside, for  $\frac{1}{4}$  sec. cor., with brass cap mkd.

$$\frac{1}{4} \begin{array}{l} S \ 32 \\ S \ 5 \end{array}$$

1931

- 52.70 Wash, 30 lks. wide, course S.  
 61.70 Wash, 30 lks. wide, course S.  
 74.50 Wash, 15 lks. wide, course S.  
 80.00 Set an iron post, 3 ft. long, 2 ins. diam., 30 ins. in the ground, with marked (X) stone deposited alongside, for the cor. of secs. 5, 6, 31 and 32, with brass cap mkd.

$$\begin{array}{c} T6N \ R9W \\ S \ 31 \ | \ S \ 32 \\ S \ 6 \ | \ S \ 5 \end{array}$$

T5N

1931

Land, rolling.  
 Soil, rocky and gravelly, 2nd. and 3rd. rate.  
 Timber, scattered paloverde and mesquite; undergrowth.  
 greasewood and cacti.

S.89°55'W. bet. secs. 6 and 31.

Over rolling and broken land, through scattered paloverde and greasewood.

- 7.70 Gully, course S.20°E.  
 20.00 Enter washed land, course S.  
 32.00 Leave wash, course S.20°W.  
 40.00 Set an iron post, 3 ft. long, 1 in. diam., 30 ins. in the ground, for  $\frac{1}{4}$  sec. cor., with brass cap mkd.

$$\frac{1}{4} \begin{array}{l} S \ 31 \\ S \ 6 \end{array}$$

1931

of stone, 3 ft. base, 2 ft. high, N. of cor. raise a mound

- 44.50 Wash, 20 lks. wide, course SE.; asc. 100 ft. over NE. slope.  
 60.50 Spur, slopes SE.; desc. 60 ft. over SW. slope.  
 71.00 Shallow draw, course SE.; asc. 90 ft. over NE. slope.  
 79.50 Spur, slopes SE.  
 80.40 The cor. of Tps. 5 and 6 N., Rs. 9 and 10 W., described in the field notes of the west boundary of T.5 N., R.9 W., surveyed under this group.

SOUTH BOUNDARY OF T.6 N.,R.9 W.

BOOK 3976

chains

Land, rolling and broken.  
Soil, gravelly and rocky, 3rd. rate.  
Timber, scattered paloverde and mesquite; undergrowth,  
greasewood and cacti.

WEST BOUNDARY OF T.6 N.,R.9 W.

North, on a random line, setting temp.  $\frac{1}{4}$  sec. and sec.  
cors. at intervals of 40 chs.; and at 481.60 chs.  
intersect an E. and W. line 122 lks. W. of the cor. of  
Tps.6 and 7 N.,Rs.9 and 10 W.


Return to the cor. of Tps.5 and 6 N.,Rs.9 and 10 W.

Thence

N.0°09'E., on true line, bet. secs. 31 and 36.

Over rolling land, through scattered paloverde and under-  
growth.


- 0.80 Spur, slopes SE., desc. 70 ft. over N. slope.
- 4.90 Gully, course S.70°E.
- 15.90 Small draw, course SE.; asc 85 ft.
- 20.50 Spur, slopes S.30°E.; desc. 60 ft. over NE. slope.
- 34.10 Enter wash, course S.60°E.
- 38.50 Leave wash.
- 40.00 Set an iron post, 3 ft. long, 1 in. diam., .30 ins. in the  
ground, for  $\frac{1}{4}$  sec. cor., with brass cap mkd.



raise a mound  
of stone, 3 ft. base, 2 ft. high, W. of cor.

Asc. gradually 120 ft. over SE. slope.

- 50.90 Gully, course S.80°E.
- 62.40 Gully, course E.
- 64.60 Gully, course S.70°E.
- 68.80 Spur, slopes E.; desc 45 ft.
- 73.20 Draw, course S.70°E.; asc., 125 ft. over S. slope.
- 79.40 Rocky spur, slopes S.75°E.; desc. 10 ft.
- 80.00 Set an iron post, 3 ft. long, 2 ins. diam., .12 ins. in the  
ground, to rock, with marked (X) stone deposited along-  
side, and in a mound of stone to top, for the cor. of  
secs. 25, 30, 31 and 36, with brass cap mkd.



## WEST BOUNDARY OF T.6 N., R.9 W.

chains

Land, rolling and broken, and hilly.  
Soil, rocky, 3rd. rate.  
Timber, scattered paloverde and mesquite; undergrowth,  
greasewood and cacti.

N.0°09'E. bet. secs. 25 and 30.

Over broken, hilly land, through scattered undergrowth.

Desc. 50 ft. over N. slope.

2.20 Draw, course E.; asc. 85 ft. over S. slope.

7.50 Rocky spur, slopes E.; desc. 50 ft.

13.90 Draw, course S.80°E.; asc 170 ft. over SE. slope.

23.90 Spur, slopes S.70°E.; desc. 115 ft. over NE. slope.

32.90 Draw, course S.60°E.; asc. 200 ft. over S. slope.

37.60 Rocky spur, slopes S.70°E.; desc. 50 ft. over NE. slope.

40.00 Set an iron post, 3 ft. long, 1 in. diam., over cross (X)  
on surface rock, supported in a mound of stone to top,  
for  $\frac{1}{4}$  sec. cor. with brass cap mkd.

$\frac{1}{4}$   
 S 25 | S 30  
 1931

42.60 Draw, course S.60°E.; asc. 100 ft. over SW. slope.

47.20 Spur, slopes SE.; desc. 60 ft. over NE. slope.

52.90 Draw, course S.50°E.; asc. 175 ft. over SW. slope.

57.90 Spur, slopes S.60°E.; desc. 140 ft. over NE. slope.

68.80 Gulch, course SE.; asc. 165 ft. over SE. slope.

72.70 Spur, slopes NE.; desc. NE. slope 175 ft.

80.00 Set an iron post, 3 ft. long, 2 ins. diam., on cross (X)  
on surface rock, supported in a mound of stone to top,  
for the cor. of secs. 19, 24, 25 and 30, with brass cap  
mkd.

T 6 N  
 R10W, R9W  
 S 24 | S 19  
 S 25 | S 30

1931

Land, broken and mountainous.  
Soil, rocks, 4th. rate.  
No timber; undergrowth, greasewood and cacti.

N.0°09'E. bet. secs. 19 and 24.

Over broken mountainous land, thru scattered undergrowth.


Desc. 75 ft. over NE. slope.

WEST BOUNDARY OF T.6 N.,R.9 W.

BOOK 3976

chains

- 7.30 Drain, course NW.
- 12.50 Draw, course N.80°E.;Asc. 335 ft. over rocky SE. slope.
- 27.35 Spur, slopes E.; desc. 175 ft. over NE. slope.
- 34.00 Gulch, course N.60°E.
- 40.00 Set an iron post, 3 ft. long, 1 in. diam.. against cross (X) on granite boulder, supported in a mound of stone to top, for 1/4 sec. cor. with brass cap mkd.




Desc. 160 ft.

- 51.80 Browns Canyon. wash, 1.50 chs. wide,, course S.60°E.
- Asc. rolling SW. slope 280 ft.

79.70 Small spur, slopes W.

- 80.00 Set an iron post, 3 ft. long, 2 ins. diam.. 6 ins. in the ground, to bedrock, with marked (X) stone deposited alongside, and in a mound of stone to top. for the cor. of secs. 13,18,19 and 24, with brass cap mkd.




Land, rough and broken mountains.  
 Soil, rocky, 4th. rate.  
 No timber; scattered greasewood and cacti.

-----  
 N.0°09'E. bet.secs. 13 and 18.

Over rolling hilly land, thru scattered paloverde and greasewood.

Desc. 85 ft. over NW. slope.

- 5.20 Head of small draw. course S.70°W.; asc. 150 ft. over S. slope.
- 17.70 Flat spur, extends E.; desc. 50 ft.
- 24.40 Drain, course E.; asc. 50 ft.
- 31.00 Low divide, bears N.80°E. and S.80°W.; desc.,N. slope 150 ft.
- 37.00 Short spur, extends NW.
- 40.00 Set an iron post, 3 ft. long, 1 in. diam., 30 ins. in the ground, for 1/4 sec. cor., with brass cap mkd.



WEST BOUNDARY OF T.6 N., R.9 W.

chains

raise a mound

of stone, 3 ft. base, 2 ft. high, W. of cor.

Abandoned mine shaft, and hoist, bears N.15°E. about 22.00 chs. dist.

Desc., NE. slope 100 ft.

46.30 Draw, course N.80°W.; asc. 90 ft. over gradual SW. slope.


59.50 Wash, 30 lks. wide, course W.

61.40 Old road, bears E. to mine shaft, and W. to Aguila.

73.30 Gulch, course S.50°W.

79.60 Desc. 12 ft.

80.00 Set an iron post, 3 ft. long, 2 ins. diam..16 ins. in the ground, to bedrock, with marked (X) stone deposited alongside, and in a mound of stone to top, for the cor. of secs. 7, 12, 13 and 18, with brass cap mkd.



Land, rolling and broken hills.

Soil, rocky. 3rd. rate.

Timber, paloverde; undergrowth, greasewood and cacti.

N.0°09'E. bet. secs. 7 and 12.

Over mountainous land, through scattered paloverde and undergrowth.

0.25 Gully, course SW.; asc. 45 ft. over S. slope.

4.20 Small spur, slopes S.80°W.; desc. 40 ft.

7.70 Draw, course S.80°W.; asc. 210 ft. over SW. slope.


21.30 Gully, course S.75°W.

24.50 Gully, course SW.

32.30 Spur, slopes S.60°W.; desc. 40 ft. over W. slope.

36.00 Draw, course S.60°W.; asc. 50 ft. over SW. slope.

40.00 Set an iron post, 3 ft. long, 1 in. diam..18 ins. in the ground, to bedrock, with marked (X) stone deposited alongside, and in a mound of stone to top, for 1/4 sec. cor., with brass cap mkd.



40.50 Gulch, course S.20°W.; asc. 680 ft. over SE. slope.

62.40 Cross in saddle between two peaks on shoulder of high spur from the SE.; desc. 90 ft. over NW. slope.

WEST BOUNDARY OF T.6 N.,R.9 W.

BOOK 3976

chains

- 65.90 Head of gully, course N.70°W.; along W. slope.
- 70.00 Sharp spur, slopes NW.; desc. NE. slope 150 ft.
- 76.00 Change of slope to N.; desc. 180 ft.
- 80.00 Set an iron post, 3 ft. long, 2 ins. diam. 16 ins. in the ground, to bedrock, with marked (X) stone deposited alongside, and in a mound of stone to top, for the cor. of secs. 1, 6, 7 and 12, with brass cap mkd.

T 6 N	
R10W	R9W
S 1	S 6
S 12	S 7

1931

Land, broken and mountainous.  
 Soil, rocky, 3rd. and 4th. rate.  
 Timber, scattered paloverde; undergrowth. greasewood and cacti.

N.0°09'E. bet. secs. 1 and 6.

Over mountainous land, through scattered undergrowth.

Desc. 760 ft. over N. slope.

- 15.00 Slope becomes more gradual.

- 40.00 Set an iron post, 3 ft. long, 1 in. diam. 20 ins. in the ground, to bedrock, with marked (X) stone deposited alongside, and in a mound of stone to top, for 1/4 sec. cor., with brass cap mkd.

1/4	
S 1	S 6

1931

- 55.00 Over level land.

- 68.90 Wash. course N.10°E.

- 73.80 Wash. 15 lks. wide. course NW.

- 75.00 Asc. 40 ft. over SW. slope.

- 81.60 The cor. of Tps. 6 and 7 N., Rs. 9 and 10 W.. which is an iron post, 3 ins. diam. extending 26 ins. above ground supported in a mound of stone to top, mkd. and witnessed as described in the official record.

Land, mountainous and rolling.  
 Soil, rocky, 3rd. and 4th. rate.  
 Timber, scattered paloverde; undergrowth, greasewood and cacti.

## SUBDIVISION OF T.6 N., R.9 W.

chains

From the cor. of secs. 1, 2, 35 and 36. on the S. bdy. of the Tp. hereinbefore described.

N.0°01'W. bet. secs. 35 and 36.

Over nearly level land, through scattered undergrowth.

38.90 Old road, bears NE. and SW.

39.40 Wire fence, bears NE. and SW.

40.00 Set an iron post, 3 ft. long, 1 in. diam., 28 ins. in the ground, with marked (X) stone deposited alongside, for  $\frac{1}{4}$  sec. cor. with brass cap mkd.

$\frac{1}{4}$   
S 35 | S 36  
1931

80.00 Set an iron post, 3 ft. long, 2 ins. diam., 28 ins. in the ground, with marked (X) stone deposited alongside, for the cor. of secs. 25, 26, 35 and 36, with brass cap mkd.

T6N R9W  
S 26 | S 25  
S 35 | S 36  
1931

Land, level.

Soil, gravelly and clay, 2nd. rate.

No timber; undergrowth, greasewood.

N.89°55'E. on a random line bet. secs. 25 and 36.

40.00 Set temp.  $\frac{1}{4}$  sec. cor.

80.00 Intersect the E. bdy. of the Tp. 7 lks. S. of the cor. of secs. 25 and 36, which is an iron post, 3 ins. diam. 15 ins. above ground, mkd. and witnessed as described in the official record.

Thence

S.89°52'W. on true line bet. secs. 25 and 36.

Over level land, through scattered undergrowth.

15.40 Old road, bears NE. and SW.

40.00 Set an iron post, 3 ft. long, 1 in. diam., 30 ins. in the ground, with marked (X) stone deposited alongside, for  $\frac{1}{4}$  sec. cor., with brass cap mkd.

$\frac{1}{4}$  S 25  
S 36  
1931

41.30 Old road, bears N.30°W. and S.30°E.

48.60 Wire fence, bears N.50°W. and S.50°E. for a dist. of 2.10 chs. thence bears S.34 $\frac{1}{2}$ °W.

80.00 The cor. of secs. 25, 26, 35 and 36.

SUBDIVISIONS OF T.6 N.,R.9 W.

BOOK 3976

chains


Land, nearly level.  
Soil. gravelly clay, 2nd. rate.  
No timber; undergrowth, greasewood.

N.0°01'W. bet.secs. 25 and 26.

Over level land, thru scattered undergrowth.


5.80 Wire fence, bears N.61½°E. and S.61½°W.

40.00 Set an iron post, 3 ft. long, 1 in. diam., 30 ins. in the ground, with marked (X) stone deposited alongside, for ¼ sec. cor., with brass cap mkd.



77.50 Flat wash, course SE.

80.00 Set an iron post, 3 ft. long, 2 ins. diam., 30 ins. in the ground, with marked (X) stone deposited alongside, for the cor. of secs. 23, 24, 25 and 26, with brass cap mkd.



Land, nearly level.  
Soil, gravelly clay, 2nd. rate.  
No timber; undergrowth, greasewood.

N.89°52'E., on a random line bet.secs. 24 and 25.

40.00 Set temp. ¼ sec. cor.


80.00 Intersect E. bdy. of Tp. 10 lks. S. of the cor. of secs. 24 and 25, which is an iron post, 3 ins. diam., 12 ins. above ground, marked and witnessed as described in the official record.

Thence

S.89°48'W., on true line bet.secs. 24 and 25.

Over level land, thru scattered undergrowth.

40.00 Set an iron post, 3 ft. long, 1 in. diam., 28 ins. in the ground, with marked (X) stone deposited alongside, for ¼ sec. cor., with brass cap mkd.



70.30 Old road, bears N. and S.

74.50 Drain, course S.

80.00 The cor. of secs. 23, 24, 25 and 26.

## SUBDIVISIONS OF T.6 N., R.9 W.

chains

Land, level.  
Soil, sandy clay, 2nd. rate.  
No timber; undergrowth, greasewood.

N.0°01'W. bet. secs. 23 and 24.

Over level land, through scattered undergrowth.

15.10 Flat wash, 5 lks wide, course SE.

40.00 Set an iron post, 3 ft. long, 1 in. diam., 28 ins. in the ground, with marked (X) stone deposited alongside, for  $\frac{1}{4}$  sec. cor. with brass cap mkd.

$$\begin{array}{c} \frac{1}{4} \\ | \\ S\ 23\ | S\ 24 \\ | \\ 1931 \end{array}$$

66:60 Road, bears N.20°E. to Aguila, and S.20°W. to Tiger Mines.

80.00 Set an iron post, 3 ft. long, 2 ins. diam., 28 ins. in the ground, with marked (X) stone deposited alongside, for the cor. of secs. 13, 14, 23 and 24, with brass cap mkd.

$$\begin{array}{c} T6N\ R9W \\ S\ 14\ | S\ 13 \\ \hline S\ 23\ | S\ 24 \\ 1931 \end{array}$$

Land, nearly level.  
Soil, sandy clay, 2nd. rate.  
No timber; undergrowth, greasewood.

N.89°48'E. on a random line bet. secs. 13 and 24.

40.00 Set temp.,  $\frac{1}{4}$  sec. cor.

80.06 Intersect the cor. of secs. 13 and 24, on the E. bdy. of Tp. which is an iron post, 3 ins. diam., 10 ins. above ground, mkd. and witnessed as described in the official record.

Thence

S.89°48'W. on true line bet. secs. 13 and 24.

Over level land, through scattered undergrowth.

40.03 Set an iron post, 3 ft. long, 1 in. diam., 30 ins. in the ground, with marked (X) stone deposited alongside, for  $\frac{1}{4}$  sec. cor., with brass cap mkd.

$$\begin{array}{c} \frac{1}{4} \\ | \\ S\ 13 \\ | \\ S\ 24 \\ 1931 \end{array}$$

78.70 Road, bears N.10°E. to Aguila, and S.10°W. to Tiger Mine.

80.06 The cor. of secs. 13, 14, 23 and 24.

SUBDIVISIONS OF T.6 N.,R.9 W.

BOOK 3976

chains

Land, nearly level.  
Soil, gravelly clay, 2nd. rate.  
No timber; undergrowth, greasewood.


N.0°01'W. bet.secs. 13 and 14.

Over level land, through scattered undergrowth.

28.40 Wash, 5 lks. wide, course E.


36.20 Wash, 5 lks. wide, course E.

40.00 Set an iron post, 3 ft. long, 1 in. diam., 30 ins. in the ground, with marked (X) stone deposited alongside, for 1/4 sec. cor., with brass cap mkd.



41.20 Wash, 5 lks. wide, course S.70°E.

80.00 Set an iron post, 3 ft. long, 2 ins. diam., 30 ins. in the ground, with marked (X) stone deposited alongside, for the cor. of secs. 11, 12, 13 and 14, with brass cap mkd.



Land, nearly level.  
Soil, gravelly clay, 2nd. rate.  
No timber; undergrowth, greasewood, catclaw and cacti.

N.89°48'E. on a random line bet.secs. 12 and 13.

40.00 Set temp. 1/4 sec. cor.

80.06 Intersect E. bdy. of Tp. 5 lks. S. of the cor. of secs. 12 and 13, which is an iron post, 3 ins. diam., 12 ins. above ground, marked and witnessed as described in the official record.

Thence


S.89°46'W., on true line bet.secs. 12 and 13.

Over level land, through scattered undergrowth.

4.00 Wash, 10 lks. wide, course S.60°E.

26.00 Old road, bears NW. and SE.

40.03 Set an iron post, 3 ft. long, 1 in. diam., 30 ins. in the ground, with marked (X) stone deposited alongside, for 1/4 sec. cor., with brass cap mkd.



## SUBDIVISIONS OF T.6 N., R.9 W.

chains

- 46.30 Wash. 5 lks. wide, course S.75°E.  
 71.00 Road, bears N. to Aguila and S. to Tiger Mine.  
 80.06 The cor. of secs..11,12,13 and 14.

Land, nearly level, drains E.  
 Soil, gravelly clay, 2nd. rate.  
 No timber; undergrowth, greasewood and cacti.

-----  
 N.0°01'W. bet.secs. 11 and 12.

Over level land, through scattered undergrowth.

- 2.70 Wash, 10 lks. wide, 2 ft. deep, course E.  
 25.30 Wash, 10 lks. wide, 1 ft. deep, course N.80°E.  
 37.60 Drain, course E.  
 40.00 Set an iron post, 3 ft. long, 1 in. diam., 30 ins. in the ground, with marked (X) stone deposited alongside, for  $\frac{1}{4}$  sec. cor., with brass cap mkd.

$\frac{1}{4}$   
 S 11 | S 12  
 1931

- 60.45 Enter road, bears N. to Aguila, and S.20°E. to Tiger Mine.  
 Corner of wire fence, extending W. and N., bears W. 25 lks. dist.

- 80.00 Set an iron post, 3 ft. long, 2 ins. diam., 36 ins. in the ground, with marked (X) stone deposited alongside, for the cor. of secs..1,2,11 and 12, with brass cap mkd.

T6N R9W  
 S 2 | S 1  
 S 11 | S 12

1931

Land, nearly level, drains N. and E.  
 Soil, sandy clay, 2nd. rate.  
 No timber; undergrowth, greasewood, catclaw and cacti.

-----  
 N.89°46'E., on a random line bet.secs. 1 and 12.

- 40.00 Set temp.  $\frac{1}{4}$  sec. cor.  
 80.14 Intersect E. bdy. of Tp. 7 lks. S. of the cor. of secs. 1 and 12, which is an iron post 3 ins. diam. 12 ins. above ground, marked and witnessed as described in the official record.

Thence

S.89°43'W. on true line bet.secs. 1 and 12.

Over level land, through scattered undergrowth.


- 40.07 Set an iron post, 3 ft. long, 1 in. diam., 30 ins. in

SUBDIVISIONS OF T.6 N.,R.9 W.

BOOK 3976

chains

the ground, with marked (X) stone deposited alongside, for 1/4 sec. cor., with brass cap mkd.



1931

74.25 Wire fence, bears N.36 1/2°W. and S.36 1/2°E.

80.14 The cor. of secs. 1,2,11 and 12.

Land, nearly level, drains NE.  
Soil, sandy clay and gumbo, 2nd. rate.  
No timber; undergrowth, greasewood.


-----  
N.0°08'E. on true line bet.secs.1 and 2, the objective cor. being visible.

Over level land. along road, bearing N. and S.

7.90 Cross cattle guard; cor. of fencing, extending N. and S.32°E. bears E. 70 lks. dist.. N. and S. fencing bears W. 30 lks. dist.

17.20 Wash, 10 lks. wide, course E.

40.00 Set an iron post, 3 ft. long. 1 in. diam..36 ins. in the ground, with marked (X) stone deposited alongside, for 1/4 sec. cor., with brass cap mkd.



61.45 Corner of fencing, extending N. S. and W., bears W. 36 lks. dist.

Residence of Thomas B. Atkins bears N.69°W. about 25.00 chs. dist.

80.08 Corner of wire fencing, extending S. and W.. bears W. 42 lks. dist.

80.30 Roadway, extends W.

80.50 The cor. of secs. 1,2,35 and 36. on the N. bdy. of Tp. which is an iron post, 3 ins. diam..12 ins. above ground properly mkd. on brass cap.

Wire fencing, extending N. and S. bears E. 42 lks. dist.

Corner of wire fencing, extending N. and W., bears W. 42 lks. dist.

Road to Aguila extends N.

Land, nearly level, drains NE. and N.  
Soil, sandy clay and gumbo, 2nd. rate.  
No timber; undergrowth, scattered greasewood.


-----

SUBDIVISIONS OF T.6 N., R.9 W.


chains

From the cor. of secs. 2,3,34 and 35, on S. bdy. of Tp. N.0°01'W. bet.secs. 34 and 35,hereinbefore described. Over gently rolling land, through scattered undergrowth. Asc., 50 ft.

40.00 Set an iron post,3 ft. long, 1 in. diam.,30 ins. in the ground, with marked (X) stone deposited alongside, for 1/4 sec. cor., with brass cap mkd.



80.00 Set an iron post,3 ft. long,2 ins. diam.,30 ins. in the ground. with marked (X) stone deposited alongside, for the cor. of secs. 26,27,34 and 35, with brass cap mkd.



Land, nearly level. Soil,sandy clay, 2nd. rate. Timber, none; undergrowth, greasewood.

N.89°55'E. on a random line bet.secs. 26 and 35.

40.00 Set temp. 1/4 sec. cor.

80.00 Intersect N. and S. line. 12 lks. S. of the cor. of secs. 25,26,35 and,36.


Thence

S.89°50'W. on true line bet.secs. 26 and 35.

Over gently rolling land, through scattered undergrowth.

9.25 Wire fencing, bears S.44°W. and extends N.44°E. about 2.00 chs.. then N.61 1/2°E.

40.00 Set an iron post,3 ft. long, 1 in. diam.,28 ins. in the ground, with marked (X) stone deposited alongside, for 1/4 sec. cor., with brass cap mkd.



59.10 Road, bears N. to Aguila and S. to the Tiger Mine.

65.40 Drain, course SE.

70.20 Wash, 10 lks. wide, 2 ft. deep, course S.25°E.

80.00 The cor. of secs..26,27,34 and 35.

Land, nearly level, drains S. Soil, gravelly and sandy clay, 2nd. rate. No timber; undergrowth, greasewood.

chains


N.0°01'W. bet.secs. 26 and 27.

Over nearly level land, through scattered undergrowth; ascend gradual slope 100 ft.

10.10 Wash, 10 lks. wide, 1 ft. deep, course SE.

34.20 Drain, course S.20°E.


40.00 Set an iron post, 3 ft. long, 1 in. diam., 30 ins. in the ground, with marked (X) stone deposited alongside, for 1/4 sec. cor., with brass cap mkd.



46.40 Wash. 5 lks. wide, course S.20°E.

76.80 Wash, 25 lks. wide, 1 ft. deep; course S.30°E.

80.00 Set an iron post, 3 ft. long, 2 ins. diam., 30 ins. in the ground, with marked (X) stone deposited alongside, for the cor. of secs. 22, 23, 26 and 27, with brass cap mkd.



Land, nearly level.  
Soil, sandy clay, 2nd. rate.  
No timber; undergrowth, greasewood.

N.89°50'E. on a random line bet.secs. 23 and 26.

40.00 Set temp. 1/4 sec. cor.

80.00 Intersect N. and S. line 2 lks. N. of the cor. of secs. 23, 24, 25 and 26.

Thence

S.89°51'W. on true line bet.secs.. 23 and 26.


Over nearly level land, through scattered undergrowth; asc. 50 ft.

0.80 Wash, 8 lks. wide, course S.20°E.

29.10 Wash, 15 lks. wide, course S.10°E.

34.20 Road, bears N.20°E. to Aguila and S.20°W. to Tiger Mine.

40.00 Set an iron post, 3 ft. long, 1 in. diam., 30 ins. in the ground, with marked (X) stone deposited alongside, for 1/4 sec. cor., with brass cap mkd.



61.40 Wash, 8 lks. wide, course S.30°E.

## SUBDIVISIONS OF T.6 N., R.9 W.

chains

67.90 Wash. 5 lks. wide, course S.

76.40 Wash, 8 lks. wide, course S.30°E.

80.00 The cor. of secs..22,23,26 and 27,

Land, nearly level.

Soil, gravelly clay, 2nd. rate.

No timber; undergrowth, greasewood and cacti.

-----  
N.0°01'W. bet.secs. 22 and 23.Over nearly level land, through scattered undergrowth;  
asc. 60 ft.

2.40 Wash, 5 lks wide, course SE.

12.30 Wash, 5 lks wide, course SE.

40.00 Set an iron post, 3 ft. long, 1 in. diam., 30 ins. in the  
ground, with marked (X) stone deposited alongside, for  
 $\frac{1}{4}$  sec. cor., with brass cap mkd.
$$\begin{array}{c} \frac{1}{4} \\ \text{S } 22 \mid \text{S } 23 \\ 1931 \end{array}$$

52.50 Wash, 5 lks. wide, course SE.

69.50 Wash, 20 lks. wide, course S.70°E.

79.90 Wash, 4 lks. wide, 1 ft. deep, course S.70°E.

80.00 Set an iron post, 3 ft. long, 2 ins. diam., 30 ins. in the  
ground, with marked (X) stone deposited alongside, for  
the cor. of secs., 14, 15, 22 and 23, with brass cap mkd.
$$\begin{array}{c} \text{T6N } \text{R9W} \\ \text{S } 15 \mid \text{S } 14 \\ \text{S } 22 \mid \text{S } 23 \\ 1931 \end{array}$$

Land, level.

Soil, gravelly clay, 2nd. rate.

No timber; undergrowth, greasewood and cacti.

-----  
N.89°51'E. on a random line bet.secs..14 and 23.40.00 Set temp.  $\frac{1}{4}$  sec. cor.79.98 Intersect N. and S. line 7 lks. S. of the cor. of secs.  
13, 14, 23 and 24.

Thence

S.89°48'W. on true line bet.secs. 14 and 23.

Over nearly level land, through scattered undergrowth;  
asc. very gradually.

13.40 Wash, 10 lks. wide, course SE.

27.40 Wash. 15 lks. wide, course SE.

SUBDIVISIONS OF T.6 N.,R.9 W.

BOOK 3976

chains	
35.90	Wash. 10 lks. wide, 2 ft. deep, course SE.
39.99	Set an iron post, 3 ft. long, 1 in. diam. .30 ins. in the ground, with marked (X) stone deposited alongside, for $\frac{1}{4}$ sec. cor., with brass cap mkd.
	$\frac{1}{4} \begin{array}{l} S 14 \\ S 23 \end{array}$
	1931
55.30	Road, bears NW. and SE.
58.65	Road, bears NW. and SE.
60.50	Wash. 10 lks. wide, course S.20°E.
66.50	Wash, 5 lks. wide, course SE.
79.98	The cor. of secs..14,15,22 and 23.
	Land, nearly level. Soil, sandy clay, 2nd. rate. No timber; undergrowth, greasewood.
-----	
	N.0°01'W. bet.secs. 14 and 15.
	Over slightly broken land, through scattered undergrowth.
24.20	Wash, 15 lks. wide, course SE.
31.30	Old road, bears NW. and SE.
40.00	Set an iron post, 3 ft. long. 1 in. diam. .30 ins. in the ground, with marked (X) stone deposited alongside. for $\frac{1}{4}$ sec. cor., with brass cap mkd.
	$\frac{1}{4} \begin{array}{l} S 15 \\ S 14 \end{array}$
	1931
41.80	Drain. 2 lks. wide, course S.70°E.
51.30	Wash. 15 lks. wide, course S.60°E.
60.00	Road, bears NW. and SE.
80.00	Set an iron post, 3 ft. long, 2 ins. diam. .30 ins. in the ground, with marked (X) stone deposited alongside. for the cor. of secs. 10,11,14 and 15. with brass cap mkd.
	$\begin{array}{c} T6N R9W \\ S 10   S 11 \\ S 15   S 14 \end{array}$
	1931
	Land, nearly level. Soil, gravelly and rocky. 2nd. and 3rd. rate. No timber; undergrowth, greasewood and cacti.
-----	

## SUBDIVISIONS OF T.6 N.,R.9 W.

chains	N.89°48'E. on a random line bet.secs. 11 and 14.
40.00	Set temp. $\frac{1}{4}$ sec. cor.
80.00	Intersect N. and S. line 5 lks. S. of the cor. of secs. 11,12,13 and 14.
	Thence
	S.89°46'W. on true line bet.secs. 11 and 14.
	Over nearly level land, through scattered undergrowth; asc. gradually.
40.00	Set an iron post, 3 ft. long, 1 in. diam., 30 ins. in the ground, with marked (X) stone deposited alongside. for $\frac{1}{4}$ sec. cor., with brass cap mkd.
	$\frac{1}{4}$ $\frac{S\ 11}{S\ 14}$
	1931
80.00	The cor. of secs. 10,11,14 and 15.
	Land, level.
	Soil, gravelly, 2nd. rate.
	No timber; undergrowth, greasewood and cacti..
-----	
	N.0°01'W. bet.secs. 10 and 11.
	Over slightly rolling land, through scattered undergrowth.
9.50	Wash, 20 lks. wide, course E.
15.60	Wash. 10 lks. wide, course N.70°E.
18.30	Wash, 10 lks. wide, course N.70°E.
20.40	Wash. 30 lks. wide, course N.70°E.
33.50	Wash. 10 lks. wide, course E.
40.00	Set an iron post, 3 ft. long, 1 in. diam., 28 ins. in the ground, with marked (X) stone deposited alongside, for $\frac{1}{4}$ sec. cor., with brass cap mkd.
	$\frac{1}{4}$
	S 10 S 11
	1931
46.80	Wash, 20 lks. wide, course N.70°E.
62.70	Wash. 10 lks. wide, course N.70°E.
70.85	Wash, 15 lks. wide, course E.; asc. gradual SW. slope 40 ft.
80.00	Set an iron post, 3 ft. long, 2 ins. diam., on broken surface rock, with marked (X) stone deposited alongside supported in a mound of stone to top, for the cor. of secs. 2,3,10 and 11, with brass cap mkd.

SUBDIVISIONS OF T.6 N., R.9 W.

BOOK 3976

chains

T6N R9W	
S 3	S 2
S 10	S 11

1931

Land, nearly level.  
Soil, gravelly and rocky, 2nd. and 3rd. rate.  
Timber, scattered paloverde; undergrowth, greasewood and cacti.

N.89°46'E. on a random line bet.secs. 2 and 11.

40.00 Set temp.  $\frac{1}{4}$  sec. cor.

80.08 Intersect N. and S. line 7 lks. S. of the cor. of secs. 1,2,11 and 12.

Thence

S.89°43'W. on true line bet.secs. 2 and 11.

Over broken hills, through scattered paloverde and undergrowth.

0.27 Wire fence, bears N. and S.

4.50 Asc. 80 ft. over E. slope.

9.40 Short rocky spur, slopes S.; desc. 60 ft.

14.50 Foot of slope; over level land.

20.00 Flat wash, 40 lks. wide, course N.30°E.

24.50 Asc. 100 ft. over SE. slope.

36.70 Rocky spur, slopes S.10°E.; desc. 60 ft. over SW. slope.

40.04 Set an iron post, 3 ft. long, 1 in. diam., 12 ins. in the ground, to bedrock, with marked (X) stone deposited alongside, and in a mound of stone to top, for  $\frac{1}{4}$  sec. cor., with brass cap mkd.

$\frac{1}{4}$ S 2
S 11

1931

Over slightly rolling land.

46.00 Drain, course S.20°E.

54.50 Wash, 10 lks. wide, course S.30°E.; asc. 185 ft. over SE. slope.

68.20 Rocky spur, slopes S.30°E.; desc. SW. slope 120 ft.

80.08 The cor. of secs. 2,3,10 and 11.

Land, broken hills, and rolling.  
Soil, gravelly and rock, 2nd. and 4th. rate.  
Timber, scattered paloverde and mesquite; undergrowth, greasewood and cacti.

SUBDIVISIONS OF T.6 N., R.9 W.

chains N.0°08'E. on a random line bet.secs. 2 and 3.

40.00 Set temp.  $\frac{1}{4}$  sec. cor.

81.05 Intersect N. bdy. of Tp. 10 lks. E. of the cor. of secs. 2,3,34 and 35, which is an iron post, 3 ins. diam., 12 ins. above ground, properly mkd. on brass cap.

From cor. roadway extends N. to Aguila, 2 miles dist. Cor. of fencing, extending N. and E. bears E. 44 lks. dist.

Thence

S.0°04'W. on true line bet.secs. 2 and 3.

Over level land, through scattered paloverde and undergrowth.

14.15 Wash, 20 lks. wide, course E.

18.30 Wash, 10 lks. wide, course N.75°E.; enter hills, asc. N. slope 330 ft.

41.05 Set an iron post, 3 ft. long, 1 in. diam., 18 ins. in the ground, to rock, with marked (X) stone deposited alongside, and in a mound of stone to top, for  $\frac{1}{4}$  sec. cor., with brass cap mkd.

$\frac{1}{4}$   
S 3 | S 2  
1931

Asc. 50 ft.

45.50 Spur, slopes NW.; desc. 145 ft. over SW. slope.

55.15 Head of gully, course NW.; asc. 30 ft. over NW. slope.

56.30 Saddle in ridge, bearing NE. and SW.; asc. NE. slope 140 ft.

65.00 Sharp rocky spur, slopes SE.; desc. 320 ft. over SW. slope.

81.05 The cor. of secs. 2,3,10 and 11.

Land, level, and broken hills.  
Soil, gravelly clay, and rock, 2nd. and 4th. rate.  
Timber, scattered paloverde; undergrowth, greasewood and cacti.

-----


From the cor. of secs. 3,4,33 and 34, on S. bdy. of Tp. N.0°02'W. bet.secs. 33 and 34, hereinbefore described.

Over rolling land, through scattered paloverde and undergrowth. Asc. gradually.


17.80 Old road, bears NW. and SE.

40.00 Set an iron post, 3 ft. long, 1 in. diam., 28 ins. in the ground, with marked (X) stone deposited alongside, for  $\frac{1}{4}$  sec. cor., with brass cap mkd.

chains



- 60.00 Small spur, extends S.25°E.
- 76.90 Drain, course E.
- 80.00 Set an iron post, 3 ft. long, 2 ins. diam., 28 ins. in the ground, for the cor. of secs. 27, 28, 33 and 34, with brass cap mkd.



raise a mound  
of stone, 2 ft. base, 1½ ft. high, W. of cor.

Land, gently rolling.  
Soil, gravelly and rocky, 3rd. and 2nd. rate.  
Timber, paloverde; undergrowth, greasewood and cacti.

N.89°55'E. on a random line bet. secs. 27 and 34.


- 40.00 Set temp. ¼ sec. cor.
- 80.02 Intersect N. and S. line 2 lks. N. of the cor. of secs. 26, 27, 34 and 35.

Thence

S.89°56'W. on true line bet. secs. 27 and 34.

Over nearly level land, through scattered undergrowth; asc. gradually 100 ft.

- 1.20 Wash. 10 lks. wide, course S.10°W.
- 10.70 Wash. 8 lks. wide, course S.30°E.
- 23.50 Wash. 5 lks. wide, 1 ft. deep, course SE.
- 35.70 Wash. 5 lks. wide, 2 ft. deep, course S.20°E.
- 40.01 Set an iron post, 3 ft. long, 1 in. diam., 25 ins. in the ground, for ¼ sec. cor., with brass cap mkd.



raise a mound  
of stone 2 ft. base, 1½ ft. high, N. of cor.

- 59.40 Wash. 25 lks. wide, course S.10°W.; enter rolling land.
- 76.50 Wash, 10 lks. wide, course S.
- 80.02 The cor. of secs. 27, 28, 33 and 34.

Land, level and slightly rolling.  
Soil, gravelly, 2nd. and 3rd. rate.  
Timber, scattered paloverde; undergrowth, greasewood and cacti.

SUBDIVISIONS OF T.6 N., R.9 W.

chains


N.0°02'W. bet.secs. 27 and 28.

Over rolling land, through scattered paloverde and undergrowth.; asc. gradual slope 100 ft.

26.90 Wash, 6 lks. wide, course SE.

38.60 Wash. 15 lks. wide, course SE.

40.00 Set an iron post, 3 ft. long, 1 in. diam., 28 ins. in the ground, for 1/4 sec., cor. with brass cap mkd.




of stone, 2 ft. base; 1 1/2 ft. high, W. of cor. raise a mound

49.40 Wash, 15 lks. wide, course S.60°E.

56.20 Same wash. course S.5°W.

63.80 Same wash, course S.20°E.

80.00 Set an iron post, 3 ft. long, 2 ins. diam., 18 ins. in the ground, to bedrock, with marked (X) stone deposited alongside, and in a mound of stone to top, for the cor. of secs. 21, 22, 27 and 28. with brass cap mkd.



Land, gently rolling.  
Soil, rocky, 3rd. rate.  
Timber, scattered paloverde and mesquite; undergrowth.  
greasewood and cacti.

N.89°56'E. on a random line bet.secs. 22 and 27.

40.00 Set temp. 1/4 sec. cor.

80.00 Intersect N. and S. line 7 lks. S. of the cor. of secs. 22, 23, 26 and 27.


Thence

S.89°53'W. on true line bet.secs. 22 and 27.

Asc. gradually through scattered undergrowth.

2.90 Wash, 20 lks. wide, course SE.

40.00 Set an iron post, 3 ft. long, 1 in. diam., 28 ins. in the ground, with marked (X) stone deposited alongside, for 1/4 sec. cor., with brass cap mkd.



47.10 Wash, 20 lks. wide, course S.

72.70 Wash, 10 lks. wide, course S.30°E.

chains

78.10 Wash, 30 lks. wide, course S.30°E.

80.00 The cor. of secs..21,22,27 and 28.

Land, nearly level.  
Soil, gravelly clay, 2nd. rate.  
No timber; undergrowth. greasewood and cacti.


-----  
N.0°02'W. bet.secs. 21 and 22.

Over slightly rolling land, through scattered paloverde and undergrowth.; asc. gradually 100 ft.

1.00 Wash, 30 lks. wide, course S.60°E.

36.50 Wash, 8 lks. wide, course S.70°E.

40.00 Set an iron post,3 ft. long, 1 in. diam.,20 ins. in the ground, to bedrock, with marked (X) stone deposited alongside, and in a mound of stone to top. for  $\frac{1}{4}$  sec. cor., with brass cap mkd.



46.40 Wash, 8 lks. wide, course S.40°E.


50.80 Wash, 25 lks. wide, course S.30°E.

52.80 Wash, 35 lks. wide. course SE.

67.20 Wash, 15 lks. wide, course SE.

72.90 Gully, course E.; asc. SE. slope 15 ft.

80.00 Set an iron post,3 ft. long. 2 ins. diam., 10 ins. in the ground, to bedrock, with marked (X) stone deposited alongside, and in a mound of stone to top. for the cor. of secs. 15,16,21 and 22. with brass cap mkd.



Land, rolling.  
Soil, rocky, 3rd. rate.  
Timber, scattered paloverde and mesquite.; undergrowth. greasewood and cacti.

-----  
N.89°53'E. on a random line bet.secs. 15 and 22.

40.00 Set temp.  $\frac{1}{4}$  sec. cor.

80.04 Intersect N. and S. line. 2 lks. S. of the cor. of secs. 14,15,22 and 23.

Thence


S.89°52'W. on true line bet.secs. 15 and 22.

Asc. gradual slope 100 ft.,through scattered undergrowth.

SUBDIVISION OF T.6 N., R.9 W.

chains

- 0.20 Wash, 3 lks. wide, 1 ft. deep, course SE.
- 15.00 Wash, 15 lks. wide, course SE.
- 40.02 Set an iron post, 3 ft. long, 1 in. diam., 30 ins. in the ground, with marked (X) stone deposited alongside, for  $\frac{1}{4}$  sec. cor., with brass cap mkd.



1931


- 54.00 Wash, 15 lks. wide, course SE.
- 71.00 Small spur, slopes SE.; desc. 20 ft.
- 73.85 Drain, course S.20°W.; asc. 25 ft.
- 80.04 The cor. of secs., 15, 16, 21 and 22.

Land, level and rolling.  
Soil, gravelly and rocky, 2nd. and 3rd. rate.  
Timber, scattered paloverde and mesquite in W.  $\frac{1}{2}$ ;  
undergrowth, greasewood and cacti.

N.0°02'W. bet. secs. 15 and 16.

Over broken foothills, through scattered undergrowth.  
Asc. 95 ft., over SE. slope.

- 8.00 Change of slope to NE.; desc. 40 ft.
- 10.70 Gulch, course S.80°E.; asc. 210 ft. over SE. slope.
- 16.20 Gully, course SE.; change of slope to S.
- 23.80 Spur, slopes E.; desc. 30 ft.
- 25.70 Draw, course E.; asc. 50 ft. over S. slope.
- 29.00 Spur, slopes S.70°E.; desc. 80 ft. over NE. slope.
- 32.20 Draw, course E.; asc. 80 ft. over SE. slope.
- 36.30 Spur, slopes E.; desc. 60 ft.
- 40.00 Set an iron post, 3 ft. long, 1 in. diam., 30 ins. in the ground, for  $\frac{1}{4}$  sec. cor., with brass cap mkd.



1931

raise a mound of stone, 3 ft. base, 2 ft. high, W. of cor.

Desc. 12 ft.

- 40.70 Draw, course E.; asc. SE. slope 45 ft.
- 44.20 Spur, slopes E.; desc. 175 ft. over NE. slope.
- 53.60 Wash, 25 lks. wide, course E.; along broken E. slope.

SUBDIVISIONS OF T.6 N., R.9 W.

BOOK 3976

- chains
- 65.40 Gully, course E.
- 69.40 Point of spur, sloping E.
- 74.30 Wash, 10 lks. wide, course N.80°E.
- 79.10 Wash, 15 lks. wide, course E.
- 80.00 Set an iron post, 3 ft. long, 2 ins. diam., 28 ins. in the ground, for the cor. of secs. 9, 10, 15 and 16, with brass cap mkd.

T6N	R9W
S 9	S 10
S 16	S 15

1931

raise a mound of stone 3 ft. base, 2 ft. high. W. of cor.

Land, broken and hilly.  
 Soil, rocky, 3rd. rate.  
 Timber, scattered paloverde; undergrowth, greasewood and cacti.

N.89°52'E. on a random line bet. secs. 10 and 15.

- 40.00 Set temp. 1/4 sec. cor.
- 80.04 Intersect N. and S. line 12 lks. S. of the cor. of secs. 10, 11, 14 and 15.

Thence

S.89°47'W. on true line bet. secs. 10 and 15.

Asc. 100 ft. over gently rolling land, through scattered undergrowth.

- 7.15 Road, bears N.20°W. to Aguila, and S.20°E.
- 25.40 Wash, 30 lks. wide, course S.60°E.
- 40.02 Set an iron post, 3 ft. long, 1 in. diam., 20 ins. in the ground, to bedrock, with marked (X) stone deposited alongside. for 1/4 sec. cor., with brass cap mkd.

1/4 S 10
S 15

1931

- 50.00 Wash, 8 lks. wide, course S.70°E.
- 57.50 Old road, bears N.70°W. and SE.
- 62.60 Enter wash, 10 lks. wide, course S.70°E.
- 66.00 Leave wash.
- 80.04 The cor. of secs. 9, 10, 15 and 16.

Land, gently rolling.  
 Soil, gravelly and rocky, 2nd. and 3rd. rate.  
 Timber, scattered paloverde; undergrowth, greasewood and cacti.

SUBDIVISIONS OF T.6 N.,R.9 W.

chains

N.0°02'W. bet.secs. 9 and 10.

Over broken land, through scattered paloverde and undergrowth.; desc. gradually.


2.00 Drain, course E.

4.00 Old road, bears E. and W.

7.00 Wash, 25 lks. wide, course E.

31.40 Wash, 15 lks. wide, course N.60°E.

40.00 Set an iron post,3 ft. long, 1 in. diam.,20 ins. in the ground, to bedrock, with marked (X) stone deposited alongside, and in a mound of stone to top, for 1/4 sec. cor. with brass cap mkd.



41.40 Wash, 25 lks. wide, course N.70°E.; along foot of rocky E.slope.

48.50 Gully, course S.70°E.; asc. 55 ft.

59.30 Point of spur, sloping E.; desc. 30 ft.


62.50 Draw, course S.70°E.; Asc. 320 ft. over S. slope.

74.00 Shoulder of spur, from S.75°W.

Concrete water trough bears S.71 1/2°E. about 30 chs. dist. Desc. 190 ft. over N. slope.

78.70 Head of gully, course NW. ; along W. slope.

80.00 Set an iron post,3 ft. long, 2 ins. diam.,30 ins. in the ground, for the cor. of secs. 3,4,9 and 10, with brass cap mkd.



of stone,3 ft base,2 ft. high,W. of cor. raise a mound

Land, broken and hills.  
Soil, rocky, 3rd. rate.  
Timber, paloverde and ironwood; undergrowth, greasewood and cacti.

N.89°47'E. on a random line bet.secs. 3 and 10.

40.00 Set temp. 1/4 sec. cor.

80.02 Intersect the cor. of secs. 2,3,10 and 11.

Thence

S.89°47'W. on true line bet.secs. 3 and 10.

Over gently rolling land, through scattered undergrowth.

chains

Desc., 20 ft. over SW. slope.

12.20 Wash, 8 lks. wide, course SE.

34.20 Road, bears N.10°W. to Aguila, and S.10°E.

37.90 Old road, bears NW. and SE.

40.01 Set an iron post, 3 ft. long, 1 in. diam., 30 ins. in the ground, for  $\frac{1}{4}$  sec. cor., with brass cap mkd.

$$\frac{1}{4} \begin{array}{l} S \ 3 \\ S \ 10 \end{array}$$

1931

raise a mound of stone, 3 ft. base, 2 ft. high, N. of cor.

56.60 Wash, 40 lks. wide, course N.; asc. 320 ft. over NE. slope.

71.50 Change of slope to N.; continue ascent.

75.00 Short spur, slopes N.; desc. 110 ft. over W. slope.

80.02 The cor. of secs. 3, 4, 9 and 10.

Land, gently rolling, and hilly.

Soil, rocky, 3rd. rate.

Timber, scattered paloverde; undergrowth, greasewood and cacti.

-----  
North on true line bet. secs. 3 and 4, the objective cor. being visible.

Over mountainous land, through scattered undergrowth.

Desc. 250 ft. over NW. slope.

5.00 Small spur, slopes NW.; change of slope to N.

13.00 Wash, 10 lks. wide, course NE.; over gentle N. slope.

17.80 Old road, bears N.70°W. and S.70°E.

28.50 Wash, 20 lks. wide, course N.80°E.

40.00 Set an iron post, 3 ft. long, 1 in. diam. 30 ins. in the ground, with marked (X) stone deposited alongside, for  $\frac{1}{4}$  sec. cor., with brass cap mkd.

$$\frac{1}{4} \begin{array}{l} S \ 4 \ | \ S \ 3 \end{array}$$

1931

65.00 Asc. gradual SW. slope 10 ft.

72.00 Low spur. extends NW.; desc. 10 ft.

80.00 Foot of slope.

81.42 The cor. of secs. 3, 4, 33 and 34, on the N. bdy. of Tp., which is an iron post, 3 ins. diam., 13 ins. above ground, marked and witnessed as described in the official record.

## SUBDIVISIONS OF T.6 N., R.9 W.

chains

Land, broken hills, and level.  
Soil, rocky and sandy clay, 3rd. and 2nd. rate.  
No timber; undergrowth, greasewood and cacti.

-----  
From the cor. of secs. 4, 5, 32 and 33, on S. bdy. of Tp.  
hereinbefore described.

N.0°02'W. bet. secs. 32 and 33.

Over rolling land, through scattered paloverde and  
undergrowth. Asc. 100 ft.

- 1.00 Drain course SE.  
14.00 Wash, 30 lks. wide, course SE.  
29.60 Gully, course SE.  
36.40 Low spur, slopes S. 30°E.  
40.00 Set an iron post, 3 ft. long, 1 in. diam., 28 ins. in the  
ground, for  $\frac{1}{4}$  sec. cor. with brass cap mkd.

$\frac{1}{4}$   
 S 32 | S 33  
 1931

raise a mound  
of stone, 3 ft. base, 2 ft. high, W. of cor.

- 44.30 Gully, course S.60°E.  
53.60 Wash, 10 lks. wide, course SE.; asc. 35 ft.  
60.00 Spur, slopes SE.; Desc. 35 ft.  
64.50 Wash, 20 lks. wide, course S.60°E.; asc. 50 ft.  
72.70 Spur, slopes S.70°E.; desc. 20 ft.  
74.50 Wash, 50 lks. wide, course S.80°E.  
78.50 Old road, bears N.70°W. and S.70°E.  
80.00 Set an iron post, 3 ft. long, 2 ins. diam., 30 ins. in the  
ground, for the cor. of secs. 28, 29, 32 and 33, with  
brass cap mkd.

T6N R9W  
 S 29 | S 28  
 S 32 | S 33  
 1931

raise a mound  
of stone, 3 ft. base, 2 ft. high. W. of cor.

Land, rolling.  
Soil, rocky, 2nd. and 3rd. rate.  
Timber, scattered paloverde; undergrowth, greasewood and  
cacti.

-----  
N.89°55'E. on a random line bet. secs. 28 and 33.

- 40.00 Set temp.  $\frac{1}{4}$  sec. cor.  
80.02 Intersect N. and S. line 3 lks. N. of the cor. of secs.

SUBDIVISIONS OF T.6 N., R.9 W.

BOOK 8976

chains

27, 28, 33 and 34.

Thence

S.89°56'W. on true line bet.secs. 28 and 33.

Over rolling land, through scattered paloverde and undergrowth. Asc. 20 ft.

3.80 Low spur, extends S.; desc. 30 ft.

8.60 Wash, 15 lks. wide, course S.

16.00 Wash, 10 lks. wide, course S.20°E.

23.60 Wash, 30 lks. wide, course S.

29.70 Wash, 15 lks. wide, course S.60°E.; asc. 30 ft.

40.01 Set an iron post, 3 ft. long, 1 in. diam., 28 ins. in the ground, for 1/4 sec. cor. with brass cap mkd.

1/4 S 28  
S 33

1931

raise a mound of stone, 3 ft. base, 2 ft. high. N. of cor.

Desc. 10 ft.

42.00 Gully, course S.

51.20 Wash, 20 lks. wide, course S.60°E.; asc. 40 ft.

58.00 Low spur, slopes S.60°E.; desc. 20 ft.

80.02 The cor. of secs. 28, 29, 32 and 33.

Land, rolling.  
Soil, gravelly and rocky, 2nd. rate.  
Timber, scattered paloverde and mesquite.; undergrowth.  
greasewood and cacti.

N.0°02'W. bet.secs. 28 and 29.

Over rolling and broken land, through scattered paloverde and undergrowth.

Asc. 50 ft. over S. slope.

7.40 Drain, course SE.

12.60 Spur, slopes S.60°E.; desc. 30 ft.

17.10 Small draw, course S.60°E.; asc. 50 ft.

24.00 Spur, slopes S.70°E.; desc. 40 ft.

31.50 Draw, course SE.; asc. 60 ft.

36.30 Spur, slopes S.70°E.; desc. 15 ft.

40.00 Set an iron post, 3 ft. long, 1 in. diam., 30 ins. in the ground, for 1/4 sec. cor. with brass cap mkd.

1/4  
S 29 | S 28

1931

SUBDIVISIONS OF T.6 N., R.9 W.

chains

of stone, 3 ft. base, 2 ft. high. W. of cor. raise a mound

48.40 Drain, course S.80°E.; Asc. rocky S. slope 590 ft.

75.50 Sharp spur, slopes S.70°E.; desc. NE. slope 100 ft.

80.00 True point for cor. falls upon face of granite ledge, 15 ft. high, facing NE. A witness cor. is set N.0°02'W. 0.25 chs. dist., as hereinafter described.

Land, rolling and mountainous.  
Soil, rocky, 2nd. and 4th. rate.  
Timber, scattered paloverde; undergrowth, greasewood.

N.89°56'E. on a random line bet.secs. 21 and 28.

40.00 Set temp. 1/4 sec. cor.

80.08 Intersect N. and S. line 2 lks. N. of the cor. of secs. 21,22,27 and 28.

Thence

S.89°57'W. on true line bet.secs. 21 and 28.

Over gently rolling land, through scattered paloverde and undergrowth. Asc. 70 ft.

8.20 Wash, 10 lks. wide, course S.30°E.

11.60 Wash, 10 lks. wide, course S.60°E.


26.70 Wash, 10 lks. wide, course S.10°E.

28.40 Wash, 15 lks. wide, course S.60°E.

32.40 Wash, 10 lks. wide, course S.80°E.

39.10 Wash, 10 lks. wide, course S.70°E.

40.04 Set an iron post, 3 ft. long, 1 in. diam., 12 ins. in the ground, to bedrock, with marked (X) stone deposited alongside, and in a mound of stone to top, for 1/4 sec. cor., with brass cap mkd.



1931

Asc. E. slope 100 ft.

62.90 Gulch, course S.60°E.; change of slope to NE., asc. 320 ft.

80.08 True point for cor. of secs. 20,21,28 and 29.

Land, rolling and mountainous.  
Soil, rocky, 3rd. and 4th. rate.  
Timber, paloverde and ironwood; undergrowth, greasewood and cacti.

SUBDIVISIONS OF T.6 N., R.9 W.

chains

From true point for cor. of secs. 20, 21, 28 and 29.


N.0°02'W. bet. secs. 20 and 21.

Over mountainous land, through scattered undergrowth.

Desc. 10 ft. over granite bluff.

0.25 Foot of bluff.

Set an iron post, 3 ft. long, 2 ins. diam., 12 ins. in the ground, to rock, with marked (X) stone deposited alongside, and in a mound of stone, for witness cor. to true point for cor. of secs. 20, 21, 28 and 29, with brass cap mkd.




Desc. NE. slope 80 ft., continuing measurement.

3.20 Gulch, course E.

14.60 Draw, course S.60°E.; asc. rocky SE. slope 600 ft.

34.00 Shoulder of spur, extends N.70°E.; desc. 80 ft.

40.00 Set an iron post, 3 ft. long, 1 in. diam., in granite boulders, against cross (X) on rock, supported in a mound of stone to top, for 1/4 sec. cor., with brass cap mkd.



Desc. NE. slope 100 ft.

41.30 Drain, course N.60°E.


46.70 Gulch, course E.

58.40 Gulch, course E.; asc. 30 ft.

72.00 Change of slope to E.; desc. 20 ft.

80.00 Low divide on spur, extending NE.

Set an iron post, 3 ft. long, 2 ins. diam., on bedrock with marked (X) stone deposited alongside, and in a mound of stone to top, for the cor. of secs. 16, 17, 20 and 21, with brass cap mkd.



Land, mountainous.  
Soil, rocky, 4th. rate.  
No timber; undergrowth, greasewood and cacti.

chains

N.89°57'E. on a random line bet.secs. 16 and 21.

40.00 Set temp.  $\frac{1}{4}$  sec. cor.

80.00 Intersect N. and S. line 2 lks. N. of the cor. of secs. 15,16,21 and 22.

Thence

S.89°58'W. on true line bet.secs. 16 and 21.

Over mountainous land, through scattered undergrowth.

Asc. SE. slope 30 ft.

2.60 Small spur, slopes S.; along S. slope.

8.60 Gully, course S.30°E.; asc. SE. slope 120 ft.

17.60 Spur, slopes S.30°E.; along S. slope.

24.40 Gulch, course S.30°E.; asc. SE. slope 225 ft.

39.00 Steep spur, slopes SE.; along S. slope.

40.00 Set an iron post, 3 ft. long, 1 in. diam., 20 ins. in the ground, to rock, with marked (X) stone deposited alongside, and in a mound of stone to top, for  $\frac{1}{4}$  sec. cor., with brass cap mkd. $\frac{1}{4}$  S 16  
S 21

1931

41.30 Gulch, course SE.; asc. 300 ft. over precipitous E.slope.

49.00 Spur, slopes SE.; along S. slope.

55.00 Desc.. 55 ft.

59.20 Gulch, course S.; asc. 45 ft.

64.20 Short spur, slopes S.; along S. slope.

67.50 Gully, course S.

71.00 Desc. SW. slope 70 ft.

74.70 Gully, head of draw, course SE.; asc. SE. slope 100 ft.

80.00 The cor. of secs. 16,17,20 and 21.

Land, broken mountains.

Soil, rocky, 3rd. and 4th. rate.

No timber; undergrowth, greasewood and cacti.

-----  
N.0°02'W. bet.secs. 16 and 17.

Over rolling mountainous land, through scattered undergrowth.

Desc. NW. slope 25 ft.


2.80 Draw, course N.25°E.; asc. 45 ft.

12.90 Spur, slopes E.; desc. 65 ft.


SUBDIVISIONS OF T.6 N., R.9 W.

BOOK 3976

- chains
- 15.90 Draw, course E.; asc. 75 ft.
- 21.90 Spur. slopes E.; desc. N. slope 90 ft .
- 25.10 Draw, course N.70°E..
- 27.10 Draw, course E.; asc. S. slope 370 ft.
- 39.40 Spur, extends S.70°E.; desc. 10 ft.
- 40.00 Set an iron post, 3 ft. long, 1 in. diam., 15 ins. in the ground, to bedrock, with marked (X) stone deposited alongside, and in a mound of stone to top, for 1/4 sec. cor., with brass cap mkd.



- 40.20 Head of drain, course E.; along E. slope.
- 45.70 Head of draw, course S.60°E.; asc. 70 ft. over SE. slope.
- 49.30 Spur, slopes E.; desc. NE. slope 155 ft.
- 60.30 Draw, course E.; asc. SE. slope 135 ft.
- 68.70 Spur, slopes S.60°E.; desc. NE. slope 260 ft.
- 72.50 Change of slope to N.
- 80.00 Set an iron post, 3 ft. long, 2 ins. diam., over cross (X) on surface rock, supported in a mound of stone to top, for the cor. of secs. 8, 9, 16 and 17, with brass cap mkd.



Land, rolling mountains.  
 Soil, rocky, 3rd. and 4th. rate.  
 No timber; undergrowth, greasewood and cacti.

- 
- N.89°58'E on a random line bet.secs. 9 and 16.
  - 40.00 Set temp. 1/4 sec. cor.
  - 80.00 Intersect N. and S. line 2 lks. N. of the cor. of secs. 9, 10, 15 and 16.
  - Thence
  - S.89°59'W. on true line bet.secs. 9 and 16.
  - Over broken and mountainous land, through scattered undergrowth.; asc. gradually, 100 ft.
  - 12.60 Old road, bears N.70°E. and S.70°W.
  - 18.25 Wash, 10 lks. wide, course N.60°E.
  - 23.25 Small reservoir, and water trough, bears S. about 4 chs. dist.

## SUBDIVISIONS OF T.6 N., R.9 W.

chains	
23.25	Well and windmill, bears S.32½°W. about 15 chs. dist.
25.75	Wash, 30 lks. wide, course N.20°E.
28.00	Wash. 20 lks. wide, course N.60°E.
35.00	Same wash, course S.70°E.
40.00	Set an iron post, 3 ft. long, 2 ins. diam., 30 ins. in the ground, for ¼ sec. cor., with brass cap mkd.
	$\frac{1}{4} \begin{array}{c} S 9 \\ S 16 \end{array}$
	1931
	raise a mound
	of stone, 3 ft. base, 2 ft. high, N. of cor.
42.00	Same wash, 15 lks. wide, course N.80°E.
45.00	Asc. E. slope 700 ft.
70.00	Change of slope to NE.
72.50	Flat spur, slopes NE.
80.00	The cor. of secs., 8, 9, 16 and 17.
	Land, broken mesa and mountains. Soil, rocky, 3rd. and 4th. rate. Timber, scattered paloverde and ironwood; undergrowth. greasewood.
-----	
	N.0°02'W. bet. secs. 8 and 9.
	Over mountainous land, through scattered undergrowth.
0.30	Wash, 10 lks. wide, course N.70°E.; asc. 75 ft. over SE. slope.
8.70	Rocky spur, slopes E.; desc. 310 ft. over NE. slope.
16.50	Draw, course N.60°E.; asc. 90 ft. over SE. slope.
17.60	Abandoned mine tunnel, bears W. 30 lks. dist.
31.00	Spur, extends NE.; desc. NW. slope 285 ft.
40.00	Set an iron post, 3 ft. long, 1 in. diam., over cross (X) on surface rock, supported in a mound of stone to top, for ¼ sec. cor., with brass cap mkd.
	$\frac{1}{4} \begin{array}{c} S 8 \\ S 9 \end{array}$
	1931
	Desc. 100 ft. over N. slope.
45.00	Gulch, course NW.
48.00	Small spur, slopes NW.; desc. 200 ft. over W. slope.
57.60	Gulch, course N.60°W.
72.70	Wash, 30 lks. wide, 6 ft. deep, course N.30°E.

SUBDIVISIONS OF T.6 N.,R.9 W.

BOOK 3976  
BOOK 397

chains

Over gradual N. slope.

80.00 Set an iron post, 3 ft. long, 2 ins. diam., 20 ins. in the ground, to bedrock, and in a mound of stone to top, for the cor. of secs. 4, 5, 8 and 9. with brass cap mkd.

T6N R9W  
S 5 | S 4  
S 8 | S 9

1931

of stone 3 ft. base, 2 ft. high, W. of cor. raise a mound

Land, mountainous.  
Soil, rocky, 4th. and 3rd. rate.  
Timber, scattered paloverde; undergrowth, greasewood and cacti.

N.89°59'E. on a random line bet. secs. 4 and 9.

40.00 Set temp. 1/4 sec. cor.

80.02 Intersect N. and S. line 7 lks. S. of the cor. of secs. 3, 4, 9 and 10.

Thence

S.89°56'W. on true line bet. secs. 4 and 9.

Over broken hills, through scattered undergrowth.

Desc., NW. slope 190 ft.

0.70 Gully, course NW.

5.70 Head of gulch, course N.

18.00 Draw, course N.; asc. 85 ft.

25.90 Spur. slopes N.; desc. 35 ft.

30.10 Draw, course N.25°E.; asc. SE. slope 80 ft.

37.50 Spur, extends N.60°E.; desc. NW. slope 25 ft.

40.01 Set an iron post, 3 ft. long, 1 in. diam., 24 ins. in the ground. to bedrock, with marked (X) stone deposited alongside, and in a mound of stone to top, for 1/4 sec. cor., with brass cap mkd.

1/4 S 4  
S 9

1931

Desc. 100 ft. over NW. slope.

53.80 Gully, course N20°W.

59.70 Wash, 40 lks. wide, course N. Over broken mesa.

71.70 Wash, 10 lks. wide, course N.

76.00 Wash, 30 lks. wide, 5 ft. deep, course N.10°E.

80.02 The cor. of secs., 4, 5, 8 and 9.

## SUBDIVISIONS OF T.6 N., R.9 W.

chains

Land, broken and hilly.  
Soil, rocky, 3rd. rate.  
Timber, scattered paloverde; undergrowth, greasewood and cacti.

-----  
North on a random line bet. secs. 4 and 5.

40.00 Set temp.  $\frac{1}{4}$  sec. cor.

81.66 Intersect N. bdy. of Tp. 17 lks. E. of the cor. of secs. 4, 5, 32 and 33, which is an iron post, 3 ins. diam., 14 in. above ground, marked and witnessed as described in the official record.

Thence

S.0°07'E. on true line bet. secs. 4 and 5.

Over nearly level land, through scattered paloverde and undergrowth. Asc. gradually.

2.40 Drain, course N.30°W.

21.00 Wash, 30 lks. wide, course N.30°E.

31.30 Old road, bears N.70°W. and S.70°E.

41.66 Set an iron post, 3 ft. long, 1 in. diam., 30 ins. in the ground, for  $\frac{1}{4}$  sec. cor., with brass cap mkd.

$\frac{1}{4}$   
S 5 | S 4  
1931

raise a mound of stone 3 ft. base, 2 ft. high, W. of cor.

Asc. gradual N. slope 85 ft.

68.90 Wash, 15 lks. wide, course N.30°W.

81.66 The cor. of secs. 4, 5, 8 and 9.

Land, nearly level.

Soil, gravelly and rocky, 2nd. and 3rd. rate.

Timber, paloverde; undergrowth, greasewood and cacti.

-----  
From the cor. of secs. 5, 6, 31 and 32, on the S. bdy. of Tp. hereinbefore described.

N.0°03'W. bet. secs. 31 and 32.

Over gently rolling land, through scattered paloverde and undergrowth. Asc. gradually 60 ft. over SW. slope.

36.10 Drain, course W.

40.00 Set an iron post, 3 ft. long, 1 in. diam. 12 ins. in the ground, to rock, with marked (X) stone deposited alongside, and in a mound of stone to top, for  $\frac{1}{4}$  sec. cor. with brass cap mkd.


$\frac{1}{4}$   
S 31 | S 32  
1931

SUBDIVISIONS OF T.6 N.,R.9 W.

BOOK 3976

chains

- 40.30 Gully, course W.
- 48.10 Wash, 20 lks. wide, course S.10°W.; over level land.
- 80.00 Set an iron post, 3 ft. long, 2 ins. diam., 20 ins. in the ground, to bedrock, with marked (X) stone deposited alongside, and in a mound of stone to top, for the cor. of secs. 29, 30, 31 and 32, with brass cap mkd.




1931

Land, gently rolling and level.  
 Soil, rocky, 2nd. and 3rd. rate.  
 Timber, scattered paloverde and mesquite; undergrowth.  
 greasewood and cacti.

N.89°55'E. on a random line bet. secs. 29 and 32.

- 40.00 Set temp. 1/4 sec. cor.
- 80.00 Intersect the cor. of secs. 28, 29, 32 and 33.
- Thence
- S.89°55'W. on true line bet. secs. 29 and 32.
- Over rolling and broken land, through paloverde and greasewood.
- 2.70 Old road, bears NW. and SE.
- 6.20 Wash, 30 lks. wide, course SE.; asc. 30 ft.
- 11.40 Spur, slopes SE.; desc. 35 ft.
- 18.60 Small draw, course S.30°E.; asc. 45 ft.
- 29.20 Spur, slopes S.30°E.; desc. 45 ft.
- 34.80 Draw, course SE.; asc. 50 ft.
- 38.60 Spur, slopes S. ; desc. 20 ft.
- 40.00 Set an iron post, 3 ft. long, 1 in. diam., 28 ins. in the ground, for 1/4 sec. cor. with brass cap mkd.



1931

raise a mound

of stone 3 ft. base, 2 ft. high, N. of cor.

Desc. 65 ft. over SW. slope.

- 43.00 Gully, course S.30°W.
- 38.60 Small draw, course S.; asc. 30 ft.
- 52.00 Spur, slopes S. ; desc. 30 ft.
- 54.40 Wash, 20 lks. wide, course S.; asc. 70 ft.
- 66.50 Spur, slopes S.; desc. 65 ft. over W. slope.

## SUBDIVISIONS OF T.6 N., R.9 W.


chains	
73.70	Wash, 20 lks. wide, course S.; over level land.
80.00	The cor. of secs. 29,30,31 and 32. Land, rolling and broken. Soil, rocky, 3rd. rate. Timber, paloverde; undergrowth, greasewood, catclaw, and cacti.
	-----
	West on true line bet. secs. 30 and 31, the objective cor. being visible. Over level and broken land, through scattered timber and undergrowth.
3.80	Drain, course S.
11.00	Wash. 5 lks. wide, course S.
21.30	Wash. 50 lks. wide, course S.20°W.
31.90	Wash. 1.20 chs. wide, course S.20°W.
35.60	Branch of same wash, 60 lks. wide, course S.; asc. 10 ft. over E. slope.
40.00	Set an iron post, 3 ft. long, 1 in. diam., 20 ins. in the ground, with marked (X) stone deposited alongside and in a mound of stone to top, for $\frac{1}{4}$ sec. cor., with brass cap mkd. $\frac{1}{4} \begin{array}{l} S \ 30 \\ S \ 31 \end{array}$
	Asc. 20 ft.
40.70	Gully, course S.
46.70	Wash, 10 lks. wide, course S.10°E.
53.70	Wash, 30 lks. wide, course S.30°E.; asc. 60 ft.
58.80	Gully, course S.20°E.
64.50	Point of spur, sloping SE.; desc. 25 ft.
68.70	Draw, course SE.; asc. 130 ft. over NE. slope.
79.00	Along N. slope.
80.14	Intersect the cor. of secs. 25,30,31 and 36. on W. bdy. of Tp.. hereinbefore described. Land, broken, and hilly. Soil, gravelly and rocky, 2nd. and 4th. rate. Timber, paloverde, mesquite and Ironwood; undergrowth. greasewood, catclaw and cacti.
	-----
	From the cor. of secs. 29,30,31 and 32. N.0°07'W. bet. secs. 29 and 30. Over broken land, through scattered timber and under- growth.
27.50	Enter washed land, course S.30°W.
40.00	Set an iron post, 3 ft. long, 1 in. diam. 10 ins. in the

SUBDIVISIONS OF T.6 N.,R.9 W.

BOOK 3976

chains

ground, to rock, with marked (X) stone deposited along-  
side, and in a mound of stone to top, for 1/4 sec. cor.  
with brass cap mkd.



A small corral bears S.45°E. about 15 chs. dist.

40.30 Enter channel of wash, course S.30°W.

43.50 Leave wash; asc. rocky bank 10 ft. high.


44.00 Continue ascent 100 ft. over gradual SE. slope.

68.00 Concrete water trough bears E. about 1.20 chs. dist.

70.60 Wash, Browns Canyon, 100 lks. wide, course S.70°E.,  
flowing a small stream of water.

Asc. S. slope 50 ft.

80.00 Set an iron post, 3 ft. long, 2 ins. diam. 10 ins. in the  
ground, to bedrock, with marked (X) stone deposited  
alongside, and in a mound of stone to top, for the cor.  
of secs. 19,20,29 and 30, with brass cap mkd.



Land, slightly rolling and broken.  
Soil, rocky, 3rd. and 2nd. rate.  
Timber, paloverde, ironwood and mesquite; undergrowth,  
greasewood, catclaw and cacti.

N.89°55'E. on a random line bet.secs. 20 and 29.

40.00 Set temp. 1/4 sec. cor.

80.04 Intersect N. and S. line 3 lks. S. of true point for cor.  
of secs. 20,21,28 and 29.

Thence, from true point.

S.89°54'W. on true line bet.secs. 20 and 29.

Over rough mountainous land, through scattered under-  
growth.

Asc.560 ft. over NE. slope.

13.30 Shoulder of ridge, from NW., spur, slopes SE.; desc.  
SW.slope 750 ft.

19.50 Sharp spur, slopes SW.;change of slope to W.

30.25 Gulch, course S.60°W.; change of slope to SW.

40.02 Set an iron post, 3 ft. long, 1 in. diam. 12 ins. in the  
ground, to bedrock, with marked (X) stone deposited  
alongside, and in a mound of stone to top, for 1/4 sec.  
cor., with brass cap mkd.

## SUBDIVISIONS OF T.6 N., R.9 W.

chains

 $\frac{1}{4}$  S 20  
S 29

1931

Continue descent 200 ft.

47.75 Gulch, course S.50°W.

52.40 Gulch, course S.30°W.

57.00 Draw, course S.; asc. SE. slope 70 ft.

61.00 Small spur, slopes S.; desc. SW. slope 70 ft.

69.30 Gully, course S.30°W.

71.40 Gully, course S.30°W.

80.04 The cor. of secs. 19,20,29 and 30.

Land, mountainous.

Soil, rocky, 4th. rate.

No timber; undergrowth, greasewood and cacti.

-----  
West on a random line bet.secs. 19 and 30.40.00 Set temp. $\frac{1}{4}$  sec. cor.79.98 Intersect W. bdy. of Tp. 3 lks. S. of the cor. of secs.  
19,24,25 and 30, hereinbefore described.

Thence

S.89°59'E. on true line bet.secs. 19 and 30.

Over mountainous land. through scattered undergrowth.

Desc. 40 ft. over NE. slope.

1.80 Gully, course N.; asc. 30 ft.

10.00 Low saddle in spur, bearing NE. and SW.; asc. NW. slope  
250 ft.20.30 Flat elongated peak of spur, bears SE. and NW.; along  
N. slope.25.00 Top of spur, slopes SE.; desc. precipitous NE. slope  
360 ft.39.98 Set an iron post, 3 ft. long. 1 in. diam., 8 ins. in the  
ground, to bedrock, with marked (X) stone deposited  
alongside, and in a mound of stone to top, for  $\frac{1}{4}$  sec.  
cor., with brass cap mkd. $\frac{1}{4}$  S 19  
S 30

1931

Desc. NE. slope 75 ft.

43.60 Draw, course S.70°E.; along S. slope.

67.30 Gully, course S.20°E.

68.50 Desc. E. slope 60 ft.

SUBDIVISIONS OF T.6 N.,R.9 W.

BOOK 3976

chains

72.00 Wash, Browns Canyon. 50 lks. wide, flowing a small stream of water; a concrete dam across wash bears NW. about 6 chs. dist.

Asc. SW. slope 75 ft.

79.98 The cor. of secs. 19,20,29 and 30.

Land, broken and rough mountains.  
Soil, rocky, 4th.rate.  
Timber, scattered paloverde; undergrowth, greasewood, catclaw and cacti.

N.0°03'W. bet.secs. 19 and 20.

Over broken and mountainous land, through scattered paloverde and undergrowth.


Asc. 50 ft. over S. slope.

4.00 Low spur, slopes SW.; along broken W. slope.

12.90 Draw, course S.60°W.; Asc. SW. slope 230 ft.

31.50 Gulch, course S.25°W.

40.00 Set an iron post, 3 ft. long, 1 in. diam., 28 ins. in the ground, for  $\frac{1}{4}$  sec. cor., with brass cap mkd.



1931

raise a mound of stone 3 ft. base, 2 ft. high west of cor.

40.90 Gully, course SW.; asc. 300 ft. over SW. slope.


45.50 Gully, course SW.

60.20 Gully, course SW.

63.10 Spur, slopes S.60°W.; desc. 40 ft.

67.90 Draw, course S.60°W.; asc. 250 ft. over S. slope.

80.00 Set an iron post, 3 ft. long, 2 ins. diam., 18 ins. in the ground, to bedrock, with marked (X) stone deposited alongside, and in a mound of stone to top, for the cor. of secs. 17,18,19 and 20, with brass cap mkd.



1931

Land, rough and mountainous.  
Soil, rock, 3rd. and 4th.rate.  
Timber, scattered paloverde; undergrowth, greasewood and cacti.

N.89°54'E. on a random line bet.secs. 17 and 20.

40.00 Set temp.  $\frac{1}{4}$  sec. cor.

79.98 Intersect N. and S. line 5 lks. S. of the cor. of secs. 16,17,20 and 21.

chains

Thence

S. 89°52'W. on true line bet.secs. 17 and 20.

Over rolling mountains, through scattered undergrowth.

Along gentle N. slope.

3.70. Small draw, course NE.; asc. SE. slope 570 ft.

25.00 Along S. slope.

35.00 Change of slope to E.

38.00 Flat spur, slopes N.80°E.

39.99 Set an iron post, 3 ft. long, 1 in. diam., 6 ins. in the ground, to bedrock, with marked (X) stone deposited alongside, and in a mound of stone to top, for  $\frac{1}{4}$  sec. cor., with brass cap mkd.
$$\frac{1}{4} \begin{array}{l} S 17 \\ S 20 \end{array}$$

1931

Asc. gentle NE. slope 30 ft.

46:00 Ridge, bears N.10°W. and S.10°E.; desc. 600 ft. over W. slope.

54.80 Draw, course S.60°W.; asc. 70 ft. over SE. slope.

72.00 Change of slope to SW.; desc. 100 ft.

79.98 The cor. of secs. 17, 18, 19 and 20.

Land, rolling mountains.

Soil, rocky, 3rd. and 4th. rate.

No timber; undergrowth. greasewood and cacti.

-----  
N.89°59'W. on a random line bet.secs. 18 and 19.40.00 Set temp.  $\frac{1}{4}$  sec. cor.

79.78 Intersect W. bdy. of Tp. 5 lks. S. of the cor. of secs. 13, 18, 19 and 24, hereinbefore described.

Thence

S.89°57'E. on true line bet.secs. 18 and 19.

Over broken land, through scattered paloverde and undergrowth.

Asc. 15 ft.

1.80 Small spur, extends S.; desc. 130 ft. over E. slope.

9.20 Draw, course S.

11.60 Draw, course S.30°W.; asc. 120 ft. over NW. slope.

22.30 Spur, slopes S.; desc. 60 ft.

26.20 Draw, course S.20°E.; asc. 75 ft. over broken SW. slope.

35.80 Gulch, course S.20°W.

39.78 Set an iron post, 3 ft. long, 1 in. diam., 12 ins. in the

SUBDIVISIONS OF T.6 N., R.9 W.

BOOK 3976

chains

ground, to rock, with marked (X) stone deposited along-side, and in a mound of stone to top, for 1/4 sec. cor. with brass cap mkd.

1/4 S 18 / S 19

1931

- 41.80 Gulch. course S.10°W.
- 43.40 Small spur, slopes S.10°W.; desc. 70 ft.
- 46.90 Draw, course S.10°W.; asc. 450 ft. over SW. slope.
- 68.40 Draw, course S.70°W.
- 72.70 Gully, course S.60°W.
- 79.78 The cor., of secs. 17,18,19 and 20.

Land, broken and mountainous.  
Soil, rocky, 4th. rate.  
Timber, scattered paloverde; undergrowth, greasewood.  
cacti and catclaw.

N.0°03'W. bet.secs. 17 and 18.

Over rough mountainous land, through scattered undergrowth.

Asc. 440 ft. over SW. slope.

- 2.80 Short spur, slopes SW.
- 10.10 Draw, course SW.; change of slope to S.
- 18.70 Spur, slopes S.60°W.; desc. 160 ft.
- 24.70 Draw, course S.60°W.; asc. 370 ft. over SW. slope.
- 26.80 Gully, course S.30°W.
- 34.80 Spur, slopes S.70°W.; desc. 120 ft. over NW. slope.
- 40.00 Set an iron post, 3 ft. long, 1 in. diam., against cross (X) on rock, and in a mound of stone to top, for 1/4 sec. cor., with brass cap mkd.

1/4 S 18 | S 17

1931

Desc. N. slope 20 ft.

- 40.30 Gulch, course N.80°W.
- 42.50 Draw, course S.70°W.; asc. 165 ft. over S. slope.
- 46.20 Spur, slopes S.60°W.; desc. 60 ft.
- 52.10 Draw, course SW.; asc. 230 ft. over S. slope.
- 56.60 Spur, slopes S.60°W.; desc. 55 ft.
- 60.90 Draw, course S.60°W.; asc. 420 ft. over SW. slope.


SUBDIVISIONS OF T.6 N., R.9 W.

chains

65.70 Gulch, course S.30°W.

71.40 Ridge, bears N.70°W. and S.70°E.; desc. precipitous N. slope 350 ft.

80.00 Set an iron post, 3 ft. long, 2 ins. diam. .16 ins. in the ground, to rock, with marked (X) stone deposited alongside, and in a mound of stone to top, for the cor. of secs. 7, 8, 17 and 18, with brass cap mkd.



1931

Land, rough mountains.  
Soil, rocky, 4th. rate.  
Timber, scattered paloverde; undergrowth, greasewood, cacti, catclaw, and scrub oak.

N.89°52'E. on a random line bet. secs. 8 and 17.

40.00 Set temp. 1/4 sec. cor.

80.00 Intersect N. and S. line 7 lks. N. of the cor. of secs. 8, 9, 16 and 17.

Thence

S.89°55'W. on true line bet. secs. 8 and 17.


Over mountainous land, through scattered undergrowth.

1.30 Draw, course N.70°E.; asc. SE. slope 335 ft.

15.25 Spur, extends N.60°E.; change of slope to NE., asc. 250 ft.

31.70 Gully, course NE.

40.00 Set an iron post, 3 ft. long, 1 in. diam., 30 ins. in the ground, for 1/4 sec. cor., with brass cap mkd.



1931

raise a mound of stone 3 ft. base, 2 ft. high N. of cor. Asc. 35 ft.

41.80 Flat spur, slopes N.; desc. 55 ft.

44.80 Gulch, course N.; asc. 90 ft. over NE. slope.

49.50 Change of slope to N.

57.00 Desc. 30 ft. over NW. slope.

60.60 Gully, course N.; asc. 100 ft. over NE. slope.

64.30 Spur, slopes N.10°W.; desc. 125 ft. over NW. slope.

69.20 Gulch, course N.10°W.; asc. 50 ft.

73.30 Spur, slopes N.; desc.; NW. slope 100 ft.

SUBDIVISIONS OF T.6 N.,R.9 W.

chains  
 80.00 The cor. of secs. 7,8,17 and 18.  
 Land, rolling and rough mountains.  
 Soil, rocky, 4th. rate.  
 Timber, scattered paloverde; undergrowth, greasewood and cacti.

-----  
 N.89°57'W. on a random line bet.secs. 7 and 18.

40.00 Set temp.  $\frac{1}{4}$  sec. cor.  
 79.50 Intersect W. bdy. of Tp. 10 lks. N. of the cor. of secs. 7,12,13 and 18. hereinbefore described.

Thence  
 N.89°59'E. on true line bet.secs. 7 and 18.

Over mountainous land, through scattered paloverde and undergrowth.  
 Asc. 570 ft. over broken SW. slope.

5.20 Small gulch, course N.70°W.

30.50 Head of draw, course S.60°W.

39.50 Set an iron post,3 ft. long. 1 in. diam..16 ins. in the ground, to bedrock, with marked (X) stone deposited alongside, and in a mound of stone to top. for  $\frac{1}{4}$  sec. cor., with brass cap mkd.

$\frac{1}{4} \frac{S 7}{S 18}$

1931

Asc. 160 ft.

45.20 Sharp spur, slopes N.80°W.; desc. 70 ft. over NE. slope.

48.70 Draw, course N.70°W., asc. 770 ft. over W. slope.

70.40 Ridge. bears N.30°W. and S.30°E.; desc. 190 ft. over NE. slope.

76.60 Head of draw, course N.; asc. 55 ft.

79.50 The cor. of secs. 7,8,17 and 18.

Land. broken and rough mountains.  
 Soil, rocky, 4th. rate.  
 Timber, scattered paloverde; undergrowth, greasewood. cacti and catclaw.

-----  
 N.0°03'W. bet.secs. 7 and 8.

Over rough mountains, through scattered undergrowth.

Desc. 70 ft. over NW. slope.

2.20 Small spur, slopes N.20°W.; desc. 530 ft. over NE. slope.

12.60 Draw, course N.30°W.; asc. 20 ft.

15.00 Point of spur, slopes NW.; desc. 135 ft. over NW. slope.

## SUBDIVISIONS OF T.6 N., R.9 W.

chains

17.10 Draw, course N.60°W.; asc. 100 ft. over SW. slope.

22.00 Spur, slopes NW.; desc. N. slope 400 ft.

40.00 Set an iron post, 3 ft. long, 1 in. diam., 18 ins. in the ground, to bedrock, with marked (X) stone deposited alongside, and in a mound of stone to top, for  $\frac{1}{4}$  sec. cor., with brass cap mkd.
$$\frac{1}{4}$$

S	7	S	8
1931			

Continue descent 350 ft. over lessening slope.

62.20 Gully, course N.20°E.

72.30 Same gully, course N.30°W.

80.00 Set an iron post, 3 ft. long, 2 ins. diam., 24 ins. in the ground, to bedrock, and in a mound of stone to top, for the cor. of secs. 5, 6, 7 and 8, with brass cap mkd.

T6N R9W			
S	6	S	5
S	7	S	8
1931			

of stone 4 ft. base, 2 ft. high, W. of cor. raise a mound

Land, rough and mountainous, sloping to desert mesa.

Soil, rocky, 4th. and 3rd. rate.

Timber, paloverde; undergrowth, greasewood, cacti and catclaw.

-----  
N.89°55'E. on a random line bet. secs. 5 and 8.40.00 Set temp.  $\frac{1}{4}$  sec. cor.

80.06 Intersect N. and S. line 27 lks. S. of the cor. of secs. 4, 5, 8 and 9.

Thence

S.89°43'W. on true line bet. secs. 5 and 8.

Over broken land, through paloverde and undergrowth.

Asc., gradual NE. slope 130 ft.

7.25 Wash, 10 lks. wide, course N.

17.30 Wash, 15 lks. wide, course N.

23.90 Wash, 15 lks. wide, course N.

32.80 Wash, 20 lks. wide, course N.

40.03 Set an iron post, 3 ft. long, 1 in. diam., 12 ins. in the ground, to bedrock, with marked (X) stone deposited alongside, and in a mound of stone to top, for  $\frac{1}{4}$  sec. cor., with brass cap mkd.
$$\frac{1}{4} \frac{S \cdot 5}{S \cdot 8}$$

1931

SUBDIVISIONS OF T.6 N., R.9 W.

BOOK 3976

chains	
46.00	Wash, 15 lks. wide, course N.
52.85	Wash, 10 lks. wide, course N.
57.60	Wash, 15 lks. wide, course N.
66.55	Wash, 25 lks. wide, course N.
75.75	Old road, bears N. and S., on low spur, sloping N.
	Desc.. 15 ft.
80.06	The cor. of secs. 5,6,7 and 8.
	Land, broken mesa.
	Soil, rocky, 3rd. rate.
	Timber, paloverde; undergrowth, greasewood, cacti and catclaw.
-----	
	S.89°59'W. on a random line bet.secs. 6 and 7.
40.00	Set temp. $\frac{1}{4}$ sec. cor.
79.38	Intersect W. bdy. of township, .12 lks. S. of the cor. of secs. 1,6,7 and 12. hereinbefore described.
	Thence
	S.89°54'E. on true line bet.secs. 6 and 7.
	Over mountainous land, through scattered timber and undergrowth.
	Asc. 12 ft.
0.80	Spur, slopes N.; desc. 70 ft. over NE. slope.
4.60	Small draw, course N.; asc. 40 ft.
9.80	Spur, slopes N.; desc. 145 ft. over NE. slope.
14.50	Draw, course N.10°E.; asc. 45 ft. over NW. slope.
19.60	Small spur, slopes N.30°E.; desc. 330 ft. over NE. slope.
30.60	Gully, course N.20°E.
39.38	Set an iron post, 3 ft. long, 1 in. diam., 30 ins. in the ground, for $\frac{1}{4}$ sec. cor., with brass cap mkd.
	$\frac{1}{4} \frac{S 6}{S 7}$
	1931
	raise a mound of stone, 3 ft.base, 2 ft. high, N. of cor.
	Desc. 60 ft.
45.00	Gully, course N.30°E.
49.30	Small draw, course N.20°E.; asc. gradual NW. slope 70 ft.
58.25	Gully, course N.10°W.
71.50	Wash, 30 lks. wide, course N.10°E.
79.38	The cor. of secs.,5,6,7 and 8.

16

## SUBDIVISIONS OF T.6 N., R.9 W.

chains

Land, mountainous, and broken mesa.  
Soil, rocky, 3rd. rate.  
Timber, paloverde; undergrowth, greasewood, cacti and  
catclaw.

-----  
N.0°07'W. on true line bet. secs. 5 and 6, the objective  
cor. being visible.

Over rolling mesa, through scattered paloverde and  
undergrowth.

Desc. 180 ft. over N. slope.

31.20 Wash. 15 lks. wide, course N.10°W.

40.00 Set an iron post, 3 ft. long, 1 in. diam., 26 ins. in the  
ground, for  $\frac{1}{4}$  sec. cor., with brass cap mkd.

↑  
S 6 | S 5  
1931

raise a mound  
of stone, 3 ft. base, 2 ft. high, W. of cor.

Continue descent 50 ft.

42.80 Same wash, 20 lks. wide, course N.10°E.

56.20 Drain, course N.10°E.

58.80 Same drain, course N.10°W.

65.60 Same drain, 5 lks. wide, course N.50°E.

81.88 The cor. of secs. 5, 6, 31 and 32, on N. bdy. of Tp.,  
which is an iron post, 3 ins. diam., 14 ins. above ground,  
mkd. and witnessed as described in the official record.

Land, rolling mesa.  
Soil, rocky, gravelly and sandy, 2nd. and 3rd. rate.  
Timber, paloverde; undergrowth, greasewood and cacti.

-----  
FINAL TEST OF SOLAR ATTACHMENT

Dec. 31, 1931. At camp in sec. 2, T.5 N., R.9 W., at 9h.  
0m. a.m., appt. t., set off 33°48'N. on the lat. arc;  
23°07'S., on the decl., arc. and orient the instrument  
with the solar; the line of sight agrees with the  
meridian established by Polaris observation.

At 4h.0m., p.m., appt. t., with the lat., arc unchanged.  
set off 23°04'N. on the decl. arc, and repeat the test  
of the solar; the line of sight agrees with the true  
meridian.  
-----

## GENERAL DESCRIPTION

BOOK 3976

The land embraced within the township varies from a level to a rough mountainous formation; the apex of Eagle Eye Mountain lying in the north west quarter of section 17, at an elevation of about 5000 feet. above sea level. Eagle Eye, which is an elongated aperture in the crest of a sharp volcanic hill, is situated near the center of section 2, and is a noted and prominent landmark throughout the region. The level land throughout the eastern and southern portions of the township is of fair soil content, being of a sandy clay texture. The foothills and mountain afford some fair range for live stock; the territory is so in use at the present. There is apparently no possible future agricultural development; the region is too arid, and there is a lack of water supply that would forever hinder any extended improvements.

Browns Canyon drains the extreme southwestern portion, running, in the winter season, a very small stream of pure water. The flow is conserved by means of a small concrete dam in section 19, the water being piped to troughs further down the draw. A well and windmill in the northeast quarter of section 16 furnishes a sufficient supply of water to attend the needs of cattle grazed in that vicinity.

The roadway from Aguila, to the north, extends south through the eastern part of the township leading to the Tiger Mines, in T.5 N., R.9 W., and on to the Centennial Valley.

Mr. Thomas B. Atkins is homesteading in section 2; has improved his land with a residence and allied buildings, and is cultivating about 15 acres of land.

There is some slight evidence of mineral deposits; abandoned prospects are noted in sections 6 and 7, and a little prospecting is under way in section 8.

The township is sparsely covered with paloverde timber, some scattered ironwood and mesquite, and more densely overgrown with greasewood and cacti. The verdure at most is of a scattered character, the grass yield is poor and grazing is afforded to only a restricted number of cattle.

---



BOOK 3976

CERTIFICATE OF UNITED STATES SURVEYOR

I, Dupree R. Averill, U. S. Surveyor, hereby certify upon honor that, in pursuance of special instructions received from the District Cadastral Engineer for Arizona bearing date of the 6th day of October, 1931, I have well, faithfully, and truly in my own proper person, and in strict conformity with said instructions, the Manual of Surveying Instructions, and the laws of the United States, surveyed all those parts or portions of South and West Boundaries and Subdivisions of T.6 N., R.9 W. of the Gila and Salt River Base and Meridian, in the State of Arizona, which are represented in the foregoing field notes as having been executed by me, and under my direction; and that all the corners of said survey have been established and perpetuated in strict accordance with the Manual of Surveying Instructions, and the special written instructions of the District Cadastral Engineer for Arizona and in the specific manner described in the field notes, and that the foregoing are the original field notes of such survey.

San Francisco, California.  
 April 19, 1932.

*Dupree R. Averill*  
 Dupree R. Averill U. S. Surveyor.

APPROVAL

OFFICE OF U. S. SUPERVISOR OF SURVEYS,

Denver, Colorado, MAR 20 1933, 1933

The foregoing field notes of the survey of the South and West boundaries and subdivisions of T.6 N., R.9 W., of the Gila and Salt River Base and Meridian in the State of Arizona

executed by Dupree R. Averill, U.S. Surveyor under his special instructions dated October 6, 1931, 1931, having been critically examined, and the necessary corrections and explanations made, the said field notes, and the surveys they describe, are hereby approved.

*Samuel H. Benson*  
 U. S. Supervisor of Surveys.

I certify that the foregoing transcript of the field notes of the above-described surveys in Arizona, has been correctly copied from the original notes on file in this office.

U. S. Supervisor of Surveys.