

Book G.

BOOK 3993

FIELD NOTES

OF THE SURVEY OF THE

subdivisional lines

of

Township 35 North, Range 16 West,

Of the Gila and Salt River Meridian,

In the State of Arizona

EXECUTED BY

William E. Hiester and Walter H. Good,

U.S. Surveyors,

Under special instructions dated June 30, 1931, which provided for the surveys included under Group No. 169, bearing the approval of the Commissioner of the General Land Office under date of September 21, 1931 and assignment instructions dated Jan. 27 and Mar. 7, 1933.

Survey commenced February 18, 1933.

Survey completed March 20, 1933.

3993

3993

BOOK 3993

INDEX DIAGRAM.

337+10M Township 35 North, Range 16 W

45 6	43	5	32	4	24	3	17	2	8	1
42	41		31		23		16		8	
44 7	41	8	30	9	23	10	15	11	7	12
40	40		29		22		14		6	
44 18	39	17	29	16	21	15	14	14	6	18
38	37		28		21		13		5	
44 19	36	20	27	21	20	22	12	23	4	24
36	35		27		19		11		3	
44 30	34	29	26	28	19	27	10	26	2	25
34	33		25		18		10		2	
43 31	32	30	24	33	17	34	9	35	1	36

Chains.

The survey was executed with a light mountain transit made by Buff and Buff, Serial No. 19423, used by William E. Hiester, U. S. Surveyor; and Buff and Buff transit No. 14189, used by Walter H. Good, U.S. Surveyor. For description and tests of instrumental equipment and for preliminary observations, see field notes of the resurvey of a portion of the Arizona and Nevada State Boundary, resurveyed under this group.

I commence the subdivisional survey at the cor. of secs. 1, 2, 35, and 36, on the S. bdy. of the Tp.

N.0°01'W., bet. secs. 35 and 36.

Over rolling land, through scattered desert growth.

Ascend 30 ft. over SE. slope.

8.20 Spur, slopes E.

17.30 Drain, 4 lks. wide, course SE.; continue ascending 188 ft. over SE. slope.

40.00 Set an iron post, 3 ft. long, 1 in. diam., (on spur slopes SE) 18 ins. in the ground to bedrock, with a lava stone, 14x12x8 ins. mkd. X, deposited at the base, and in a mound of stone to top, for $\frac{1}{4}$ sec. cor. with brass cap mkd.

$\frac{1}{4}$
S 35 | S 36
1933

Descend 92 ft. over broken NE. slope.

45.28 Drain, course NE.

50.00 Drain, course SE.; asc. 77 ft. over E. slope.

59.00 Top of ascent; desc. 8 ft.

64.00 Wash, 20 lks. wide, course SE.; asc. 199 ft. over broken SW. slope.

80.00 Set an iron post, 3 ft. long, 2 ins. diam., 26 ins. in the ground, for cor. of secs. 25, 26, 35, and 36, with brass cap mkd.

T35N R16W
S 26 | S 25
S 35 | S 36
1933

raise a mound
of stone, 4 ft. base, $3\frac{1}{2}$ ft. high, W. of cor.

Land, rolling.

Soil, rocky; 4th rate.

Timber, none; undergrowth. catclaw and cactus.

SUBDIVISION OF T. 35 N., R. 16 W.

Chains. East on a random line bet. secs. 25 and 36.

40.00 Set temp. $\frac{1}{4}$ sec. cor.

80.08 Intersect E. bdy. of Tp., 5 lks. S. of the cor. of secs. 25, 30, 31, and 36.

Thence

S.89°58'W., on a true line bet. secs. 25 and 36.

Over rolling land, through scattered desert growth.

3.50 Ascend 97 ft. over E. slope.

11.00 Old road, bears N. and S.

21.50 Spur, slopes S.; desc. 132 ft. over SW. slope.

28.00 Wash, 3 lks. wide, course SE.

40.04 Set an iron post, 3 ft. long, 1 in. diam., 26 ins. in the ground, for $\frac{1}{4}$ sec. cor. with brass cap mkd.

$\frac{1}{4}$ S 25
S 36
1933

raise a mound

of stone, 4 ft. base, 2 $\frac{1}{2}$ ft. high, N. of cor.

Continue over level land.

62.50 Wash, 20 lks. wide, course SE.

64.00 Leave level land,; asc. 194 ft. over NE. slope.

80.08 The cor. of secs. 25, 26, 35, and 36.

Land, rolling.
Soil, rocky; 4th rate.
Timber, none; undergrowth, catclaw, cactus, joshua and greasewood.

N.0°01'W., bet. secs. 25 and 26.

Over rolling land, through scattered desert growth.

.30 Low spur, slopes SE.; desc. 136 ft. over broken NE. slope.

5.40 Enter draw, course NW.

18.42 Wash, 20 lks. wide, course SE.

20.00 Leave draw, course SW.; asc. 259 ft. over steep SW. slope.

38.00 Top of rimrocks, 20 ft. high, bears E. and W.; continue over rolling bench land.

40.00 Set an iron post, 3 ft. long, 1 in. diam., 26 ins. in the ground, for $\frac{1}{4}$ sec. cor. with brass cap mkd.

$\frac{1}{4}$
S 26 | S 25
1933

Chains.	<p style="text-align: right;">raise a mound of stone, 4 ft. base, 2½ ft. high, W. of cor.</p>
70.50	<p>Top of rimrocks, bears NW. and SE.; leave bench land.; desc. 273 ft. over steep, rocky NE. slope.</p>
80.00	<p>Set an iron post, 3 ft. long, 2 ins. diam., 26 ins. in the ground, for cor. of secs. 23, 24, 25, and 26. with brass cap mkd.</p>
	<p>T35N R16W S 23 S 24 S 26 S 25 1933</p>
	<p style="text-align: right;">raise a mound of stone, 4 ft. base, 3 ft. high, W. of cor.</p> <p>Land, level and rolling. Soil, sandy loam and rocky, 3rd and 4th rates. Timber, none; undergrowth, catclaw, cactus, joshua and black sage.</p>
	<p>N. 89° 58' E., on a random line bet. secs. 24 and 25.</p>
40.00	<p>Set temp. ¼ sec. cor.</p>
80.10	<p>Intersect E. bdy. of Tp., 10 lks. N. of the cor. of secs. 19, 24, 25, and 30.</p>
	<p>Thence</p> <p>N. 89° 58' W., on a true line bet. secs. 24 and 25.</p> <p>Over rolling land, through scattered desert growth.</p> <p>Ascend 55 ft. along broken S. slope.</p>
5.10	<p>Top of ascent; desc. 58 ft. over broken SW. slope.</p>
17.50	<p>Creek, 2 lks. wide, in Pakoon Wash, 40 lks. wide, 20 ft. deep, course SE.</p>
17.81	<p>Enter cultivated field, bears N. about 15.00 chs. and S. about 15.00 chs. dist.</p>
21.55	<p>Leave cultivated field, bears N. and S.</p>
21.60	<p>Irrigation ditch, 2 ft. deep, 1 ft. wide, course SW.</p>
21.62	<p>Fence, bears NE. and SW.</p>
21.82	<p>Road to Pakoon Spring, bears NE.; asc. 74 ft. over SE. slope.</p>
27.10	<p>Spur, slopes S.; desc. 20 ft. over SW. slope.</p>
35.10	<p>Spur, slopes SW.; desc. 68 ft. over rocky NW. slope.</p>
38.30	<p>Fence along bluffs, 50 ft. high, bears N.</p>
40.05	<p>True point for ¼ sec. cor. falls in wash, 60 lks. wide, course S.</p>
41.20	<p>Set an iron post, 3 ft. long, 1 in. diam., 18 ins. in the ground to bedrock, with a lava stone 12x10x6 ins. mkd. X, deposited at the base, and in a mound of stone to top, for witness ¼ sec. cor. with brass cap mkd.</p>

Chains.

$$\frac{1}{4} \frac{S 24}{S 25} WC$$
 1933

- Ascend 29 ft. over gradual SE. slope.
- 48.50 Low spur, slopes SE; desc. 14 ft. over SW. slope.
- 58.60 Wash, 30 lks. wide, course SE.
- 62.10 Base of slope bears NW. and SE.; asc. 251 ft. over NE. slope.
- 73.50 Point of rocky spur, slopes N.; desc. 53 ft. over NW. slope.
- 80.10 The cor. of secs. 23, 24, 25, and 26.

Land, rolling and level.
 Soil, sandy loam 1st rate; and rocky 4th rate.
 Timber, none; undergrowth catclaw, joshua, cactus and black sage.

N.0°01'W., bet. secs. 23 and 24.

- Over rolling land, through scattered desert growth.
 Descend 104 ft. over broken NE. slope.
- 2.50 Base of slope, bears NW. and SE.
- 4.19 Wash, 20 lks. wide, course SE.; asc. 29 ft. over SW. slope.
- 23.50 Low spur, slopes SE.; desc. 40 ft. over NE. slope.
- 34.26 Wash, 100 lks. wide, course SE.
- 40.00 Set an iron post, 3 ft. long, 1 in. diam., 26 ins. in the ground, for $\frac{1}{4}$ sec. cor. with brass cap mkd.

$$\frac{1}{4}$$

$$S 23 | S 24$$
 1933

raise a mound of stone, 4 ft. base, 3 ft. high, W. of cor.

R.J.White's house, bears S.68°30'E.
 Pakoon Spring, bears S.69°45'E.
 Shed, bears S.66°E.
 Pond, bears S.65°15'E.
 Barn, bears S.64°E.

- 47.40 Road to Pakoon Spring, bears E.
- 50.00 Base of slope, bears E. and W.; asc. 208 ft. over broken SE. slope.
- 80.00 Set an iron post, 3 ft. long, 2 ins. diam., 18 ins. in the ground to bedrock, with a lava stone, 8x6x4 ins. mkd. X, deposited at the base, and in a mound of stone to top, for cor. of secs. 13, 14, 23, and 24, with brass cap mkd.

SUBDIVISION OF T. 35 N., R. 16 W.

Chains.

T35N R16W
S 14 | S 13
S 23 | S 24
1933

from which

- R.J. White's house, bears S.41°30'E.
- Shed, bears S.39°30'E.
- Barn, bears S.38°50'E.
- Pond, bears S.38°30'E.
- Pakoon Spring bears S.42°30'E.

Land, rolling.
Soil, sandy 2nd rate; and rocky 4th rate.
Timber, none; undergrowth, catclaw, joshua and cactus.

- 40.00 S.89°58'E., on a random line bet. secs. 13 and 24.
Set temp. $\frac{1}{4}$ sec. cor.
- 80.26 Intersect E. bdy. of Tp., 2 lks. N. of the cor. of secs. 13, 18, 19, and 24.
Thence
N.89°57'W., on a true line bet. secs. 13 and 24.
Over rolling land, through scattered desert growth.
Descend 63 ft. over SW. slope.
- 18.68 Wash, 15 lks. wide, course SE.; continue over level land.
- 40.13 Set an iron post, 3 ft. long, 1 in. diam., 26 ins. in the ground, for $\frac{1}{4}$ sec. cor. with brass cap mkd.
 $\frac{1}{4}$ S 13
S 24
1933
raise a mound of stone, 3 ft. base, 2 ft. high, N. of cor.
- 61.69 Wash, 3 lks. wide, course SW.; asc. 93 ft. over SE. slope.
- 68.30 Spur, slopes S.; desc. 64 ft. over W. slope.
- 74.91 Wash, 5 lks. wide, course S.; asc. 129 ft. over E. slope.
- 80.26 The cor. of secs. 13, 14, 23, and 24.
Land, rolling.
Soil, sandy 2nd rate; and rocky; 4th rates.
Timber, none; undergrowth, joshua, cactus and catclaw.

Chains.	N.0°01'W., bet. secs. 13 and 14. Over rolling land, through scattered desert growth. Along E. slope of spur.
5.00	Sharp spur, slopes SSW.; asc. 93 ft. over SW. slope.
33.00	Continue along top of spur, slopes W.
37.50	Leave spur.; desc. 16 ft. over NW. slope.
40.00	Set an iron post, 3 ft. long, 1 in. diam., 14 ins. in the ground to bedrock, with a lava stone 14x10x8 ins. mkd. X, deposited at the base, and in a mound of stone to top, for $\frac{1}{4}$ sec. cor. with brass cap mkd.
	$\frac{1}{4}$ S 14 S 13 1933
	Descend 126 ft. over NW. slope.
50.75	Wash, 20 lks. wide, course SW.; asc. 58 ft. over SE. slope.
56.00	Spur, slopes E.; desc. 41 ft. over NE. slope.
60.24	Bend in wash, from ^{NE to} SE.; asc. 97 ft. over SE. slope.
80.00	Set an iron post, 3 ft. long, 2 ins. diam., 18 ins. in the ground to bedrock, with a lava stone, 6x4x3 ins. mkd. X, deposited at the base, and in a mound of stone to top, for cor. of secs. 11, 12, 13, and 14, with brass cap mkd.
	T35N R16W S 11 S 12 S 14 S 13 1933
	Land, rolling. Soil, rocky; 4th rate. Timber, none; undergrowth, catclaw, cactus and joshua.
40.00	S.89°57'E., on a random line bet. secs. 12 and 13. Set temp. $\frac{1}{4}$ sec. cor.
80.12	Intersect E. bdy. of Tp., 16 lks. S. of the cor. of secs. 7, 12, 13, and 18. Thence S.89°56'W., on a true line bet. secs. 12 and 13. Over rolling and mountainous land, through scattered desert growth. Descend 65 ft. over W. slope.
4.27	Wash, 5 lks. wide, course S.; asc. 182 ft. over steep SE. slope.
16.12	Top of rimrocks, 20 ft. high, bears NE. and SW.
26.92	Top of ascent; continue over bench land.

SUBDIVISION OF T.35 N., R. 16 W.

Chains. 40.06	<p>Set an iron post, 3 ft. long, 1 in. diam., 6 ins. in the ground to bedrock, with a limestone. 14x16x10 ins. mkd. X, deposited at the base, and in a mound of stone to top, for $\frac{1}{4}$ sec. cor. with brass cap mkd.</p> <p style="text-align: center;"> $\frac{1}{4}$ S 12 S 13 1933 </p>
57.42	Leave bench land,; desc. 290 ft. over NW. slope.
76.46	Wash, 15 lks. wide, course SW.; asc. 56 ft. over SE. slope.
80.12	<p>The cor. of secs. 11, 12, 13, and 14.</p> <p>Land, rolling and mountainous. Soil, rocky; 4th rate. Timber, none; undergrowth, cactus. catclaw, joshua and black sage.</p>
<p>N.0°01'W., bet. secs. 11 and 12.</p> <p>Over mountainous land, through scattered desert growth.</p> <p>Ascend 132 ft. over SE. slope.</p>	
9.00	Spur, slopes SW.; continue ascending 97 ft. along broken W. slope.
39.00	Top of rimrocks, 20 ft. high, bears NW. and SE.; continue over bench land.
40.00	<p>Set an iron post, 3 ft. long, 1 in. diam., 18 ins. in the ground to bedrock, with a lava stone, 8x6x4 ins. mkd. X, deposited at the base, and in a mound of stone to top, for $\frac{1}{4}$ sec. cor. with brass cap mkd.</p> <p style="text-align: center;"> $\frac{1}{4}$ S 11 S 12 1933 </p>
49.70	Top of rimrocks, 20 ft. high, bears NE. and SW.; desc. 172 ft. over NW. slope.
65.00	Base of slope, bears NW. and SE.; continue over rolling land.
80.00	<p>Set an iron post, 3 ft. long, 2 ins. diam., 26 ins. in the ground, for cor. of secs. 1, 2, 11, and 12, with brass cap mkd.</p> <p style="text-align: center;"> T35N R16W S 2 S 1 S 11 S 12 1933 </p> <p style="text-align: right;">raise a mound</p> <p>of stone, $3\frac{1}{2}$ ft. base, $2\frac{1}{2}$ ft. high, W. of cor.</p> <p>Land, rolling and mountainous. Soil, rocky; 4th rate. Timber, none; undergrowth, joshua, cactus and catclaw.</p>

SUBDIVISION OF T. 35 N., R. 16 W.

Chains	N.89°56'E., on a random line bet. secs. 1 and 12.
40.00	Set temp. $\frac{1}{4}$ sec. cor.
80.08	Intersect E. bdy. of Tp., 12 lks. S. of the cor. of secs. 1, 6, 7, and 12.
	Thence
	S.89°51'W., on a true line bet. secs. 1 and 12.
	Over rolling land, through scattered desert growth.
	Descend 97 ft. over W. slope.
34.49	Wash, 10 lks. wide, course S.; asc. 69 ft. over E. slope.
40.04	Set an iron post, 3 ft. long, 1 in. diam., 26 ins. in the ground, for $\frac{1}{4}$ sec. cor. with brass cap mkd.
	$\frac{1}{4}$ <u>S 1</u> S 12 1933
	raise a mound of
	stone, 4 ft. base, 3 ft. high, N. of cor.
40.60	Spur, slopes S.; desc. 70 ft. over NW. slope.
51.68	Wash, 5 lks. wide, course SW.; asc. 55 ft. over E. slope.
56.60	Spur, slopes S.; desc. 43 ft. over W. slope.
60.90	Wash, 20 lks. wide, course S.; asc. 156 ft. over E. slope.
72.00	Spur, slopes S.; desc. 181 ft. over NW. slope.
74.00	Top of rimrocks. 20 ft. high, bears N. and S.; continue descending.
80.08	The cor. of secs. 1, 2, 11, and 12.
	Land, rolling.
	Soil, rocky; 4th rate.
	Timber, none; undergrowth catclaw, joshua and cactus.
	N.0°01'W., bet. secs. 1 and 2.
40.00	Set temp. $\frac{1}{4}$ sec. cor.
80.26	Intersect N. bdy. of Tp., 18 lks. W. of the cor. of secs. 1, 2, 35, and 36.
	Thence
	S.0°07'W., on a true line bet. secs. 1 and 2.
	Over rolling land, through scattered desert growth.
	Ascend 97 ft. over NW. slope.
7.00	Spur, slopes W.; desc. 116 ft. over SW. slope.
19.17	Wash, 5 lks. wide, course SE.; asc. gradual NE. slope.
40.26	Set an iron post, 3 ft. long, 1 in. diam., 26 ins. in the ground, for $\frac{1}{4}$ sec. cor. with brass cap mkd.

Chains.

$\frac{1}{4}$
 S 2 | S 1
 1933

raise a mound
of stone, 4 ft. base, 2 $\frac{1}{2}$ ft. high, W. of cor.

Ascend 121 ft. over NE. slope.

- 43.50 Road, bears NE. and SW.
- 51.50 Top of ascent; continue along top of spur, slopes SE.
- 61.50 Leave spur.; desc. 229 ft. over SW. slope.
- 80.26 The cor. of secs. 1, 2, 11, and 12.

Land, rolling.
Soil, rocky; 4th rate.
Timber, none; undergrowth. Gatclaw, cactus and joshua.

From the cor. of secs. 2, 3, 34 and 35, on the S. bdy. of the Tp.

N.0°01'W., bet. secs. 34 and 35.

Over mountainous land, through scattered desert growth.

Ascend 256 ft. over steep rocky SE. slope.

- 10.60 Wash, 10 lks. wide, course SE.; continue ascending.
- 20.00 Same wash, course SW.; continue ascending over rolling bench land.
- 37.00 Low spur, slopes SE.
- 40.00 Set an iron post, 3 ft. long, 1 in. diam., 8 ins. in the ground to bedrock, with a limestone, 14x12x6 ins. mkd. X, deposited at the base, and in a mound of stone to top, for $\frac{1}{4}$ sec. cor. with brass cap mkd.

$\frac{1}{4}$
 S 34 | S 35
 1933

Descend 26 ft. over NE. slope.

- 44.68 Wash, 3 lks. wide, course SE.; asc. 23 ft. over SW. slope.
- 77.00 Descend 21 ft. over N. slope.

- 80.00 Set an iron post, 3 ft. long, 2 ins. diam., 4 ins. in the ground to bedrock, with a lava stone, 10x8x6 ins. mkd. X, deposited at the base, and in a mound of stone to top, for cor. of secs. 26, 27, 34, and 35, with brass cap mkd.

T35N R16W
 S 27 | S 26
 S 34 | S 35
 1933

Land, rolling and mountainous.

SUBDIVISION OF T. 35 N., R. 16 W.

Chains.	Soil, sandy; 3rd rate, and rocky; 4th rate. Timber, none; undergrowth, catclaw, joshua and cactus.
	East on a random line bet. secs. 26 and 35.
40.00	Set temp. $\frac{1}{4}$ sec. cor.
79.94	Intersect N. and S. line, 7 lks. S. of the cor. of secs. 25, 26, 35, and 36.
	Thence
	S.89°57'W., on a true line, bet. secs. 26 and 35.
	Over mountainous land, through scattered desert growth.
	Ascend 17 ft. over E. slope.
.90	Spur, slopes SE.; desc. 164 ft. over broken SW. slope.
9.00	Wash, 20 lks. wide, course SE.; asc. 401 ft. over NE. slope.
26.40	Top of rimrocks, 20 ft. high, bears NW. and S.; continue over rolling bench land.
39.97	Set an iron post, 3 ft. long, 1 in. diam., 18 ins. in the ground to bedrock, with a lava stone, 10x10x4 ins. mkd. X, deposited at the base, and in a mound of stone to top, for $\frac{1}{4}$ sec. cor. with brass cap mkd.
	$\frac{1}{4}$ <u>S 26</u> S 35 1933
46.00	Drain, course NE.; asc. 40 ft. along SE. slope.
63.00	Top of ascent; desc. 23 ft. over SW. slope.
64.00	Wash, 10 lks. wide, course SE.; continue along same.
70.00	Leave wash, from NW.; asc. 44 ft. along NE. slope.
79.94	The cor. of secs. 26, 27, 34, and 35.
	Land, rolling and mountainous. Soil, rocky; 4th rate. Timber, none; undergrowth, catclaw, joshua and cactus.
	N.0°01'W., bet. secs. 26 and 27.
	Over rolling land, through scattered desert growth.
	Descend 27 ft. over N. slope.
3.28	Wash, 2 lks. wide, course E.; asc. 20 ft. over SE. slope.
7.90	Spur, slopes E.
16.60	Wash, 5 lks. wide, course SE.; asc. 41 ft. over SW. slope.
25.00	Top of low ridge, 5.00 chs. wide, bears NW. and SE.; desc. 23 ft. over N. slope.
32.00	Wash, 5 lks. wide, course E.

1933

Chains. 40.00 Set an iron post, 3 ft. long, 1 in. diam., 4 ins. in the ground to bedrock, with a lava stone, 14x12x6 ins. mkd. X, deposited at the base, and in a mound of stone to top, for $\frac{1}{4}$ sec. cor. with brass cap mkd.

$\frac{1}{4}$
 S 27 | S 26
 1933

Ascend 34 ft. over SE. slope.

43.70 Top of ascent; desc. 19 ft. over broken NE. slope.

63.74 Wash, 10 lks. wide, course SE.; asc. 42 ft. over SW. slope.

69.00 Spur, slopes SE.; desc. 34 ft. over NE. slope.

79.19 Wash, 12 lks. wide, course SE.

80.00 Set an iron post, 3 ft. long, 2 ins. diam., 18 ins. in the ground to bedrock, with a limestone, 10x8x6 ins. mkd. X, deposited at the base, and in a mound of stone to top, for cor. of secs. 22, 23, 26, and 27, with brass cap mkd.

T35N R16W
 S 22 | S 23
 S 27 | S 26
 1933

Land, rolling.
 Soil, rocky; 4th rate.
 Timber, none; undergrowth, catclaw, joshua and cactus.

N.89°57'E., on a random line bet. secs. 23 and 26.

40.00 Set temp. $\frac{1}{4}$ sec. cor.

79.90 Intersect N. and S. line, 7 lks. S. of the cor. of secs. 23, 24, 25, and 26.

Thence

S.89°54'W., on a true line bet. secs. 23 and 26.

Over mountainous land, through scattered desert growth.

Along N. slope.

19.90 Wash, 20 lks. wide, course NE.; asc. 241 ft. over steep rocky, SE. slope.

28.20 Top of rimrocks, 10 ft. high, bears N. and S.

29.90 Spur, slopes SE.; continue over bench land.

36.60 Top of rimrocks, 10 ft. high, bears NW. and SE.; leave bench land,; desc. 71 ft. over SW. slope.

39.95 Set an iron post, 3 ft. long, 1 in. diam., 18 ins. in the ground to bderock, with a lava stone, 14x12x8 ins. mkd. X, deposited at the base, and in a mound of stone to top, for $\frac{1}{4}$ sec. cor. with brass cap mkd.

SUBDIVISION OF T. 35 N., R. 16 W.

Chains.

$\frac{1}{4}$ S 23
S 26
1933

Descend 56 ft. over rocky SW. slope.

46.01 Wash, 10 lks. wide, course SE.; asc. 262 ft. over steep rocky, NE. slope.

52.50 Top of rimrocks, 10 ft. high, bears N. and S.

59.40 Spur, slopes SE.; continue along top of same.

69.40 Leave spur.; desc. 32 ft. over SW. slope.

79.90 The cor. of secs. 22, 23, 26, and 27.

Land, rolling and mountainous.

Soil, rocky; 4th rate.

Timber, none; undergrowth, catclaw, cactus and joshua.

N.0°01'W., bet. secs. 22 and 23.

Over rolling land, through scattered desert growth.

Ascend 78 ft. over SW. slope.

10.50 Spur, slopes E.; desc. 100 ft. over N. slope.

15.29 Wash, 10 lks. wide, course SE.; asc. 51 ft. along broken E. slope.


33.34 Wash, 5 lks. wide, course SE.; asc. 77 ft. over SW. slope.

39.80 Spur, slopes SE.

40.00 Set an iron post, 3 ft. long, 1 in. diam., 6 ins. in the ground to bedrock, with a limestone, 10x6x4 ins. mkd. X, deposited at the base, and in a mound of stone to top, for $\frac{1}{4}$ sec. cor. with brass cap mkd.

$\frac{1}{4}$
S 22 | S 23
1933

In order to determine the distance over bluffs, impracticable to chain, I use the above station as point A, and set a flag B on line on opposite side of bluffs, also a flag C on opposite side of bluffs, which from point A, bears N.44°25'E.; the base, B C, bears East. 39.30 chs. dist.; all bearings checked by direct reading of the solar and all angles checked by deflection.



Dist. on true line 40.00 chs.
Dist. by triangulation 40.09 chs.

80.09

Dist. by return meas.

.09

80.00

48.73 Edge of bluff 100 ft. high. Thence over broken E. slope.

SUBDIVISION OF T. 35 N., R. 16 W.

Chains. 80.00 → Set an iron post, 3 ft. long, 2 ins. diam., on bedrock with a cross X, mkd. at the base, and in a mound of stone to top, for cor. of secs. 14, 15, 22, and 23, with brass cap mkd.

T35N R16W
 S 15 | S 14
 S 22 | S 23
 1933

Land, rolling and broken.
 Soil, rocky; 4th rate.
 Timber, none; undergrowth, catclaw, cactus and joshua.

N.89°54'E., on a random line bet. secs. 14 and 23.

40.00 Set temp. 1/4 sec. cor.

79.80 Intersect N. and S. line, 5 lks. N. of the cor. of secs. 13, 14, 23, and 24.

Thence

S.89°56'W., on a true line bet. secs. 14 and 23.

Over mountainous land, through scattered desert growth.

.50 Low spur, slopes SW.; desc. 159 ft. over SW. slope.

9.00 Base of slope, bears NE. and SW.

11.78 Road, bears NW. and SE. in center of wash, 60 lks. wide course SE.

15.00 Base of slope, bears N. and S.; asc. 377 ft. over rocky NE. slope.

33.00 Top of rimrocks, 20 ft. high, bears N. and S.; continue over level bench land.

39.90 Set an iron post, 3 ft. long, 1 in. diam., on bedrock, with a lava stone 18x16x8 ins. mkd. X, deposited at the base, and in a mound of stone to top, for 1/4 sec. cor. with brass cap mkd.

1/4 S 14
 S 23
 1933

49.30 Top of rimrocks, 20 ft. high, bears NE. and SW.; leave level bench land;; desc. 173 ft. over SW. slope.

55.13 Wash, 5 lks. wide, course S.; asc. 136 ft. over broken SE. slope.

73.85 Drain, 5 lks. wide, course SE.; asc. 58 ft. over SE. slope.

79.80 The cor. of secs. 14, 15, 22, and 23.

Land, level and mountainous.
 Soil, sandy; 3rd rate, and rocky; 4th rate.
 Timber, none; undergrowth, catclaw, cactus, joshua and black sage.

Chains	N.0°01'W.; bet. secs. 14 and 15. Over mountainous land, through scattered desert growth. Ascend 146 ft. along broken E. slope.
40.00	Set an iron post, 3 ft. long, 1 in. diam., 6 ins. in the ground to bedrock, with a limestone, 14x10x6 ins. mkd. X, deposited at the base, and in a mound of stone to top, for $\frac{1}{4}$ sec. cor. with brass cap mkd. $\frac{1}{4}$ S 15 S 14 1933
	Ascend 24 ft. over SE. slope.
41.28	Spur, slopes NE.; desc. 229 ft. over NW. slope.
56.70	Wash, 15 lks. wide, course NE.; asc. 176 ft. over broken SE. slope.
63.50	Top of ascent; desc. 50 ft. over NW. slope.
69.50	Ascend 126 ft. over broken E. slope.
77.50	Spur, slopes E.; desc. 67 ft. over NW. slope.
80.00	Set an iron post, 3 ft. long, 2 ins. diam., 26 ins. in the ground, for cor. of secs. 10, 11, 14, and 15, with brass cap mkd. T35N R16W S 10 S 11 S 15 S 14 1933
	of stone, $3\frac{1}{2}$ ft. base, $2\frac{1}{2}$ ft. high, W. of cor. raise a mound
	Land, mountainous. Soil, rocky; 4th rate. Timber, none; undergrowth catclaw, cactus and joshua.
	N.89°56'E., on a random line bet. secs. 11 and 14.
40.00	Set temp. $\frac{1}{4}$ sec. cor.
79.86	Intersect N. and S. line, 5 lks. S. of the cor. of secs. 11, 12, 13, and 14. Thence
	S.89°54'W., on a true line bet. secs. 11 and 14. Over mountainous land, through scattered desert growth. Ascend 50 ft. over SE. slope.
4.00	Spur, slopes S.; desc. 131 ft. over W. slope.
20.40	Center of wash, 40 lks.wide, course S.
20.50	Road, bears N. and S.; asc. 214 ft. over steep E.slope.
33.50	Top of Volcanic Butte, bears S. 2.00 chs. dist.; desc. 109 ft. over NW. slope.

SUBDIVISION OF T. 35 N., R. 16 W.

Look

Chains.
39.93

Set an iron post, 3 ft. long, 1 in. diam., 26 ins. in the ground, for $\frac{1}{4}$ sec. cor. with brass cap mkd.

$\frac{1}{4}$ S 11
S 14
1933

raise a mound of stone, $3\frac{1}{2}$ ft. base, $2\frac{1}{2}$ ft. high, N. of cor.

Descend 40 ft. over NW. slope.

42.00 Base of descent; asc. 89 ft. over broken SE. slope.

61.26 Wash, 10 lks. wide, course SE.; continue ascending 302 ft. over broken SE. slope.

75.50 Top of ascent; desc. 86 ft. over NW. slope.

79.86 The cor. of secs. 10, 11, 14, and 15.

Land, mountainous.
Soil, rocky; 4th rate.
Timber, none; undergrowth catclaw.

N.0°01'W., bet. secs. 10 and 11.

Over mountainous land, through scattered desert growth.

Descend 40 ft. over NW. slope.

1.37 Wash, 5 lks. wide, course NE.; asc. 200 ft. over broken SE. slope.

16.50 Spur, slopes E.; desc. 79 ft. over NW. slope.

27.39 Wash, 5 lks. wide, course NE.; asc. 61 ft. over SE. slope.

31.00 Top of ascent; desc. 93 ft. along broken E. slope.

38.47 Drain, 3 lks. wide, course E.

40.00 Set an iron post, 3 ft. long, 1 in. diam., on solid rock, with a lava stone, 8x6x4 ins. mkd. X, deposited at the base and in a mound of stone to top, for $\frac{1}{4}$ sec. cor. with brass cap mkd.

$\frac{1}{4}$
S 10 | S 11
1933

42.25 Drain, 3 lks. wide, course E.; continue descending 158 ft. along broken E. slope.

65.40 Ascend 145 ft. over SE. slope.

80.00 Set an iron post, 3 ft. long, 2 ins. diam., 8 ins. in the ground to bedrock, with a limestone, 12x8x6 ins. mkd. X, deposited at the base, and in a mound of stone to top, for cor. of secs. 2, 3, 10, and 11, with brass cap mkd.

Chains.

T35N R16W
 S 3 | S 2
 S 10 | S 11
 1933

Land, mountainous.
 Soil, sandy 3rd rate; and rocky; 4th rate.
 Timber, none; undergrowth, joshua, cactus, catclaw and
 black sage.

N.89°54'E., on a random line bet. secs. 2 and 11.

40.00 Set temp. $\frac{1}{4}$ sec. cor.

79.74 Intersect N. and S. line, 14 lks. N. of the cor. of secs
 1, 2, 11, and 12.

Thence

West, on a true line bet. secs. 2 and 11.

Over rolling land, through scattered desert growth.

Descend 29 ft. over W. slope.

6.05 Wash, 30 lks. wide, course S.; asc. 139 ft. over NE.
 slope.

6.10 Road, bears N. and S.

37.00 Top of ascent.; black rimrocks, 20 ft. high, bears S.
 3.00 chs. dist.; desc. 24 ft. over NW. slope.

39.87 Set an iron post, 3 ft. long, 1 in. diam., 26 ins. in
 the ground, for $\frac{1}{4}$ sec. cor. with brass cap mkd.

$\frac{1}{4}$ $\frac{S 2}{S 11}$
 1933

raise a mound
 of stone, $3\frac{1}{2}$ ft. base, $2\frac{1}{2}$ ft. high, N. of cor.

Descend 82 ft. along top of spur, slopes SE.

49.06 Wash, 5 lks. wide, course S.; asc. 135 ft. over E.
 slope.

59.00 Spur, slopes SE.; desc. 63 ft. over SW. slope.

64.30 Wash, 5 lks. wide, course SE.; asc. 177 ft. over broken
 E. slope.

79.74 The cor. of secs. 2, 3, 10, and 11.

Land, rolling.
 Soil, rocky; 4th rate.
 Timber, none; undergrowth catclaw, joshua and cactus.

N.0°07'E., on a random line bet. secs. 2 and 3.

40.00 Set temp. $\frac{1}{4}$ sec. cor.

80.32 Intersect N. bdy. of Tp., 35 lks. E. of the cor. of secs.
 2, 3, 34, and 35.

SUBDIVISION OF T. 35 N., R. 16 W.

EC

Chains	Thence
	S.0°08'E., on a true line bet. secs. 2 and 3.
	Over rolling land, through scattered desert growth.
	Along broken E. slope.
11.51	Drain, 6 lks. wide, course E.
39.62	Drain, 3 lks. wide, course E.
40.32	Set an iron post, 3 ft. long, 1 in. diam., on bedrock. with a cross X, mkd. at the base, and in a mound of stone to top, for 1/4 sec. cor. with brass cap mkd.
	$\frac{1}{4}$ S 3 S 2 1933
	Ascend 29 ft. over N. slope.
44.76	Drain, 3 lks. wide, course E.; continue ascending 148 ft. over NE. slope.
50.32	Spur, slopes E.; desc. 129 ft. along broken E. slope.
73.32	Wash, 4 lks. wide, course E.; asc. 75 ft. over NE. slope.
80.32	The cor. of secs. 2, 3, 10, and 11.
	Land, rolling. Soil, rocky; 4th rate. Timber, none; undergrowth, catclaw, joshua, cactus and black sage.
<hr/>	
	From true point for cor. of secs. 3, 4, 33, and 34. on S. bdy. of Tp. 12 lks. W. of the witness cor. for same.
	N.0°02'W., bet. secs. 33 and 34.
	Over mountainous land, through scattered desert growth.
	Descend 396 ft. over steep, rocky NW. slope.
8.00	Trail, bears E. and W.
13.16	Wash, 12 lks. wide, course W.; asc. 256 ft. over rocky S. slope.
23.00	Spur, slopes W.; desc. 257 ft. over NW. slope.
39.00	Base of slope, bears E. and W.; continue over small valley.
40.00	Set an iron post, 3 ft. long, 1 in. diam., 18 ins. in the ground to bedrock, with a limestone, 8x6x4 ins. mkd. X, deposited at the base, and in a mound of stone to top, for 1/4 sec. cor. with brass cap mkd.
	$\frac{1}{4}$ S 33 S 34 1933

Chains.	
51.30	Wash, 20 lks. wide, course SW.; leave valley, bears NE. and SW.; asc. 465 ft. over steep, rocky E. slope.
70.00	Top of rocky knoll, bears W. 100 lks. dist.; continue along broken E. slope.
80.00	Set an iron post, 3 ft. long, 2 ins. diam., on bedrock, with a cross X, mkd. at the base, and in a mound of stone to top, for cor. of secs. 27, 28, 33, and 34, with brass cap mkd.
	T35N R16W S 28 S 27 S 33 S 34 1933
	Land, mountainous. Soil, rocky; 4th rate. Timber, none; undergrowth, catclaw.
	East on a random line bet. secs. 27 and 34.
40.00	Set temp. $\frac{1}{4}$ sec. cor.
80.18	Intersect N. and S. line, 5 lks. N. of the cor. of secs. 26, 27, 34, and 35.
	Thence
	N. 89° 58' W., on a true line bet. secs. 27 and 34.
	Over mountainous land, through scattered desert growth.
	Ascend 73 ft. over NE. slope.
5.00	Spur, slopes S.; desc. 69 ft. over W. slope.
14.40	Wash, 5 lks. wide, course SE.; asc. 107 ft. over broken E. slope.
22.40	Top of rocky spur, slopes SE.; desc. 69 ft. over SW. slope.
28.70	Wash, 10 lks. wide, course SE.; asc. 36 ft. over E. slope.
40.09	Set an iron post, 3 ft. long, 1 in. diam., 18 ins. in the ground to bedrock, with a limestone 12x8x4 ins. mkd. X, deposited at the base, and in a mound of stone to top, for $\frac{1}{4}$ sec. cor. with brass cap mkd.
	$\frac{1}{4}$ S 27 S 34 1933
	Ascend 43 ft. over broken SE. slope.
42.08	Top of sharp rocky ridge, bears N. and S.; desc. 618 ft. over rocky W. slope.
68.83	Wash, 30 lks. wide, course S.; asc. 312 ft. over steep E. slope.
80.18	The cor. of secs. 27, 28, 33, and 34.
	Land, mountainous. Soil, rocky; 4th rate. Timber, none; undergrowth, catclaw and cactus.

SUBDIVISION OF T. 35 N., R. 16 W.

BOOK 301

Chains. N.0°02'W., bet. secs. 27 and 28.
 Over mountainous land, through scattered desert growth.
 Descend 179 ft. along broken E. slope.

2.50 Spur ridge, bears NE. and SW.; continue along top of same.

12.50 Leave spur; continue descending over NW. slope.

26.60 Drain, course NW.; continue along broken W. slope.

40.00 Set an iron post, 3 ft. long, 1 in. diam., 18 ins. in the ground to bedrock, with a lava stone, 8x8x6 ins. mkd. X, deposited at the base, and in a mound of stone to top, for $\frac{1}{4}$ sec. cor. with brass cap mkd.

$\frac{1}{4}$
 S 28 | S 27
 1933

43.79 Bend in wash, 40 lks. wide, from NW. course SW.; continue along E. bank of wash.

55.00 Leave wash.; asc. 82 ft. over broken W. slope.

78.12 Drain, 4 lks. wide, course SW.

80.00 Set an iron post, 3 ft. long, 2 ins. diam., 26 ins. in the ground, for cor. of secs. 21, 22, 27 and 28, with brass cap mkd.

T35N R16W
 S 21 | S 22
 S 28 | S 27
 1933

raise a mound
 of stone $3\frac{1}{2}$ ft. base, $2\frac{1}{2}$ ft. high, W. of cor.

Land, mountainous.
 Soil, rocky; 4th rate.
 Timber, none; undergrowth, catclaw and cactus.

S.89°58'E., on a random line, bet. secs. 22 and 27.

40.00 Set temp. $\frac{1}{4}$ sec. cor.

80.26 Intersect N. and S. line, 14 lks. N. of the cor. of secs. 22, 23, 26, and 27.

Thence

N.89°52'W., on a true line bet. secs. 22 and 27.

Over mountainous land, through scattered desert growth.

.60 Wash, 10 lks. wide, course SE.; asc. 102 ft. over NE. slope.

9.70 Spur, slopes N.; desc. 62 ft. over W. slope.

11.78 Same wash, 10 lks. wide, course N.; asc. 207 ft. over broken E. slope.

Chains. 38.00	Wash, 5 lks. wide, course SE.; asc. 26 ft.
40.13	Set an iron post, 3 ft. long, 1 in. diam., 18 ins. in the ground to bedrock, with a limestone, 8x6x4 ins. mkd. X, deposited at the base, and in a mound of stone to top, for $\frac{1}{4}$ sec. cor. with brass cap mkd.
	$\frac{1}{4}$ $\frac{S\ 22}{S\ 27}$ 1933
	Ascend 121 ft. over broken E. slope.
45.00	Top of sharp ridge, bears N. and S.; desc. 520 ft. over rocky W. slope.
80.26	The cor. of secs. 21, 22, 27, and 28.
	Land, mountainous. Soil, rocky; 4th rate. Timber, none; undergrowth catclaw, joshua and cactus.
N.0°02'W., bet. secs. 21 and 22.	
Over rolling land, through scattered desert growth.	
Along broken W. slope.	
21.00	Enter draw, course SW. Continue along draw.
30.30	Wash, 10 lks. wide, course SW.; continue along W. bank of same.
40.00	Set an iron post, 3 ft. long, 1 in. diam., 14 ins. in the ground to bedrock, with a limestone 12x8x6 ins. mkd. X, deposited at the base, and in a mound of stone to top, for $\frac{1}{4}$ sec. cor. with brass cap mkd.
	$\frac{1}{4}$ S 21 S 22 1933
52.00	from NE. Leave draw, asc. 29 ft. over broken SE. slope.
79.90	Drain, course SE.
80.00	Set an iron post, 3 ft. long, 2 ins. diam., 6 ins. in the ground to bedrock, with a limestone, 8x8x3 ins. mkd. X, deposited at the base, and in a mound of stone to top, for cor. of secs. 15, 16, 21, and 22, with brass cap mkd.
	T35N R16W S 16 S 15 S 21 S 22 1933
	Land, rolling. Soil, rocky; 4th rate. Timber, none; undergrowth, joshua, cactus and catclaw.

SUBDIVISION OF T. 35 N., R. 16 W.

BOOK 3886

Chains. S.89°52'E., on a random line bet. secs. 15 and 22.

40.00 Set temp. $\frac{1}{4}$ sec. cor.

80.12 Intersect N. and S. line, 42 lks. S. of the cor. of secs. 14, 15, 22, and 23.

Thence

S.89°50'W., on a true line bet. secs. 15 and 22.

Over mountainous land, through scattered desert growth.

Ascend 99 ft. over broken SE. slope.

7.00 Spur, slopes S.; desc. 141 ft. over SW. slope.

12.15 Wash, 15 lks. wide, course S.; asc. 311 ft. over broken E. slope.

15.00 Drain 3 lks. wide, course NE.

19.20 Same drain, course SE.

32.00 Top of sharp ridge, bears N. and S.; desc. 308 ft. over W. slope.

40.06 Set an iron post, 3 ft. long, 1 in. diam., 18 ins. in the ground to bedrock, with a limestone, 10x6x4 ins. mkd. X, deposited at the base, and in a mound of stone to top, for $\frac{1}{4}$ sec. cor. with brass cap mkd.

$\frac{1}{4}$ S 15
S 22
1933

Descend 172 ft. over broken W. slope.

55.00 Base of slope; asc. 21 ft.

68.00 Top of sandstone ledge, 20 ft. high; bears NE. and SW.

Descend 71 ft. over NW. slope.

70.58 Wash, 15 lks. wide, course SW.; asc. 60 ft. over E. slope.

80.12 The cor. of secs. 15, 16, 21, and 22.

Land, mountainous.
Soil, rocky; 4th rate.
Timber, none; undergrowth, catclaw, joshua and cactus.

N.0°02'W., bet. secs. 15 and 16.

Over rolling land, through scattered desert growth.

Ascend 117 ft. over broken SE. slope.

40.00 Set an iron post, 3 ft. long, 1 in. diam., 8 ins. in the ground to bedrock, with a limestone, 16x8x6 ins. mkd. X, deposited at the base, and in a mound of stone to top, for $\frac{1}{4}$ sec. cor. with brass cap mkd.

$\frac{1}{4}$
S16 | S15
1933

SUBDIVISION OF T. 35 N., R. 16 W.

Chains.	Ascend 261 ft. over SE. slope.
40.20	Drain, course SE.
79.80	Drain, course SE.
80.00	Set an iron post, 3 ft. long, 2 ins. diam., 18 ins. in the ground to bedrock, with a limestone, 10x6x4 ins. mkd. X, deposited at the base, and in a mound of stone to top, for cor. of secs, 9, 10, 15, and 16, with brass cap mkd.
	T35N R16W S 9 S 10 S 16 S 15 1933
	Land, mountainous. Soil, rocky; 4th rate. Timber, none; undergrowth catclaw, cactus and joshua.
	N.89°50'E., on a random line bet. secs. 10 and 15.
40.00	Set temp. $\frac{1}{4}$ sec. cor.
80.26	Intersect the cor. of secs. 10, 11, 14 and 15. Thence S.89°50'W., on a true line bet. secs. 10 and 15. Over mountainous land, through scattered desert growth. Ascend 114 ft. over NE. slope.
7.50	Spur, slopes N.; desc. 108 ft. over NW. slope.
11.30	Wash, 5 lks. wide, course NE.; asc. 292 ft. over broken SE. slope.
24.70	Top of sharp ridge, bears N. and S.; desc. 399 ft. over W. slope.
40.13	Set an iron post, 3 ft. long, 1 in. diam., 18 ins. in the ground to bedrock, with a limestone 8x6x4 ins. mkd. X, deposited at the base, and in a mound of stone to top, for $\frac{1}{4}$ sec. cor. with brass cap mkd.
	$\frac{1}{4}$ S 10 S 15 1933
	Descend 216 ft. over W. slope.
66.34	Wash, 10 lks. wide, course S.; asc. 158 ft. over broken E. slope.
80.26	The cor. of secs. 9, 10, 15, and 16. Land, mountainous. Soil, rocky; 4th rate. Timber, none; undergrowth, catclaw, cactus and joshua.

SUBDIVISION OF T. 35 N., R. 16 W.

Chains. N.0°02'W., bet. secs. 9 and 10.

Over rolling land, through scattered desert growth.

Ascend 135 ft. along broken E. slope.

6.55 Wash, 3 lks. wide, course E.

40.00 Set an iron post, 3 ft. long, 1 in. diam., 18 ins. in the ground to bedrock, with a limestone, 12x6x6 ins. mkd. X, deposited at the base, and in a mound of stone to top, for 1/4 sec. cor. with brass cap mkd.

1/4
S 9 | S 10
1933

60.00 Low divide, bears NE. and SW.; continue over gradual NW. slope, nearly level.

79.90 Wash, 4 lks. wide, course SW.

80.00 Set an iron post, 3 ft. long, 2 ins. diam., 18 ins. in the ground to bedrock, with a limestone, 10x6x4 ins. mkd. X, deposited at the base, and in a mound of stone to top, for cor. of secs. 3, 4, 9, and 10, with brass cap mkd.

T35N R16W
S 4 | S 3
S 9 | S 10
1933

Land, rolling.
Soil, sandy; 3rd rate.
Timber, none; undergrowth, catclaw, joshua and cactus.

N.89°50'E., on a random line bet. secs. 3 and 10.

40.00 Set temp. 1/4 sec. cor.

80.30 Intersect N. and S. line, 28 lks. N. of the cor. of secs. 2, 3, 10, and 11.

Thence

N.89°58'W., on a true line bet. secs. 3 and 10.

Over mountainous land, through scattered desert growth.

Ascend 534 ft. over broken E. slope.

31.75 Top of sharp ridge, 100 ft. high on W. face, bears N. and S.; desc. 474 ft. over broken W. slope.

40.15 Set an iron post, 3 ft. long, 1 in. diam., on bedrock, with a cross X, mkd. at the base, and in a mound of stone to top, for 1/4 sec. cor. with brass cap mkd.

1/4 S 3
S 10
1933

Descend 244 ft. over W. slope.

57.00 Divide, bears NE. and SW.; continue descending over NW. slope.

SUBDIVISION OF T. 35 N., R. 16 W.

Chains.	
79.90	Wash, 10 lks. wide, course SW.
80.30	The cor. of secs. 3, 4, 9, and 10. Land, mountainous. Soil, rocky; 4th rate. Timber, none; undergrowth, joshua, catclaw and cactus.
	N.0°08'W., on a random line bet. secs. 3 and 4.
40.00	Set temp. $\frac{1}{4}$ sec. cor.
80.36	Intersect N. bdy. of Tp., 35 lks. W. of the cor. of secs. 3, 4, 33, and 34. Thence S.0°07'W., on a true line bet. secs. 3 and 4. Over rolling land, through scattered desert growth.
11.96	Old road, bears E. and W.
39.26	Old road, bears NE. and SW.
40.36	Set an iron post, 3 ft. long, 1 in. diam., 26 ins. in the ground, for $\frac{1}{4}$ sec. cor. with brass cap mkd. $\begin{array}{c} \frac{1}{4} \\ S\ 4\ \ S\ 3 \\ 1933 \end{array}$ raise a mound of stone $3\frac{1}{2}$ ft. base, $2\frac{1}{2}$ ft. high, W. of cor.
68.36	Wash, 10 lks. wide, course SW.
80.36	The cor. of secs. 3, 4, 9, and 10. Land, rolling and level. Soil, sandy; 3rd rate. Timber, none; undergrowth, joshua, catclaw, and cactus.
	From the cor. of secs. 4, 5, 32, and 33, on the S. bdy. of the Tp. N.0°03'W., bet. secs. 32 and 33. Over rolling land, through scattered desert growth. Ascend 119 ft. over broken SE. slope.
16.83	Top of ledge, 15 ft. high, bears NE. and SW.; continue over top of spur slopes SW.
30.50	Leave spur.; desc. 23 ft. over NW. slope.
39.00	Wash, 5 lks. wide, course SW.
40.00	Set an iron post, 3 ft. long, 1 in. diam., 26 ins. in the ground, for $\frac{1}{4}$ sec. cor. with brass cap mkd.

SUBDIVISION OF T. 35 N., R. 16 W.

Chains.

$\frac{1}{4}$
 S 32 | S 33
 1933

raise a mound
of stone, 4 ft. base, 3 ft. high. W. of cor.

Ascend 134 ft. over SE. slope.

57.00 Head of draw, course SW.

61.00 Spur, slopes SE.; continue ascending.

62.70 Bend in same spur from SE. slopes SW.; desc. 105 ft. over broken NE. slope.

80.00 Set an iron post, 3 ft. long, 2 ins. diam., 26 ins. in the ground, for cor. of secs. 28, 29, 32, and 33, with brass cap mkd.

T35N R16W
 S 29 | S 28
 S 32 | S 33
 1933

raise a mound
of stone, 4 ft. base, 3 ft. high, W. of cor.

Land, rolling.
Soil, rocky; 4th rate.
Timber, none; undergrowth black sage, catclaw, cactus and joshua.

East on a random line bet. secs. 28 and 33.

40.00 Set temp. $\frac{1}{4}$ sec. cor.

80.18 Intersect N. and S. line, 7 lks. S. of the cor. of secs. 27, 28, 33 and 34.

Thence

S. 89° 57' W., on a true line bet. secs. 28 and 33.

Over mountainous land, through scattered desert growth.

.50 High rocky ridge, bears N. and S.; desc. 706 ft. over rocky W. slope.

39.64 Set an iron post, 3 ft. long, 1 in. diam., 26 ins. in the ground, for witness $\frac{1}{4}$ sec. cor. with brass cap mkd.

WC $\frac{1}{4}$ S 28
 S 33
 1933

raise a mound
of stone, 4 ft. base, 3 ft. high, N. of cor.

40.09 True point for $\frac{1}{4}$ sec. cor. falls in wash, 40 lks. wide, course S.; asc. 143 ft. over E. slope.

49.20 Spur, slopes S.; desc. 208 ft. over W. slope.

67.00 Wash, 20 lks. wide, course S.

Chains.

67.78

Old salt well, bears S. 4.00 chs. dist.

Ascend 37 ft. over E. slope.

69.40

Spur, slopes S.; desc. 152 ft. over SW. slope.

73.85

Wash, 5 lks. wide, course SE.; asc. 96 ft. over broken NE. slope.

80.18

The cor. of secs. 28, 29, 32, and 33.

Land, mountainous.

Soil, rocky; 4th rate.

Timber, none; undergrowth, black sage, cactus and joshua.

N.0°03'W., bet. secs. 28 and 29.

Over rolling land, through scattered desert growth.

Descend 74 ft. over broken NE. slope.

6.05

Wash, 5 lks. wide, course SE.; asc. 49 ft. over SW. slope.

40.00

Set an iron post, 3 ft. long, 1 in. diam., 18 ins. in the ground to bedrock, with a shale rock, 8x8x6 ins. mkd. X, deposited at the base, and in a mound of stone to top, for $\frac{1}{4}$ sec. cor. with brass cap mkd.
$$\begin{array}{c} \frac{1}{4} \\ \text{S } 29 \mid \text{S } 28 \\ 1933 \end{array}$$

43.90

Low spur, slopes SE.

51.50

Wash, 15 lks. wide, course SE.

70.00

Low spur, slopes W.; desc. 23 ft.

78.80

Wash, 3 lks. wide, course SW.

80.00

Set an iron post, 3 ft. long, 2 ins. diam., 26 ins. in the ground, for cor. of secs. 20, 21, 28, and 29, with brass cap mkd.

$$\begin{array}{c} \text{T35N R16W} \\ \text{S } 20 \mid \text{S } 21 \\ \text{S } 29 \mid \text{S } 28 \\ 1933 \end{array}$$

raise a mound
of stone, 4 ft. base, 3 ft. high, W. of cor.

Land, rolling.

Soil, sandy; 3rd rate.

Timber, none; undergrowth, catclaw, cactus, joshua and black sage.

SUBDIVISION OF T. 35 N., R. 16 W.

Chains. N.89°57'E., on a random line bet. secs. 21 and 28.

40.00 Set temp. $\frac{1}{4}$ sec. cor.

80.08 Intersect N. and S. line, 7 lks. N. of the cor. of secs. 21, 22, 27, and 28.

Thence

West on a true line bet. secs. 21 and 28.

Over mountainous land, through scattered desert growth.

Descend 12 ft. over W. slope.

2.50 Wash, 15 lks. wide, course S.; asc. 185 ft. over E. slope.

15.00 Spur, slopes S.; desc. 236 ft. over SW. slope.

32.15 Wash, 3 lks. wide, course SE.; asc. 34 ft. over NE. slope.

40.04 Set an iron post, 3 ft. long, 1 in. diam., 18 ins. in the ground to bedrock, with a lava stone, 8x6x4 ins. mkd. X, deposited at the base, and in a mound of stone to top, for $\frac{1}{4}$ sec. cor. with brass cap mkd.

$\frac{1}{4}$ S 21
S 28
1933

Ascend 131 ft. over broken NE. slope.

51.60 Wash, 5 lks. wide, course NE.

57.50 Spur, slopes SE.; desc. 391 ft. over SW. slope.

78.35 Wash, 5 lks. wide, course SW.

80.08 The cor. of secs. 20, 21, 28, and 29.

Land, mountainous.
Soil, rocky; 4th rate.
Timber, none; undergrowth, catclaw and black sage.

N.0°03'W., bet. secs. 20 and 21.

Over rolling land, through scattered desert growth.

Ascend 24 ft. over SE. slope.

3.00 Spur, slopes E.; desc. 19 ft. over NE. slope.

5.37 Wash, 5 lks. wide, course SE.; continue along bottom of same.

7.50 Leave wash, from NE.; asc. 157 ft. over broken SE. slope.

37.10 Drain, course SE.

40.00 Set an iron post, 3 ft. long, 1 in. diam., 8 ins. in the ground to bedrock, with a limestone, 16x14x6 ins. mkd. X, deposited at the base, and in a mound of stone to top, for $\frac{1}{4}$ sec. cor. with brass cap mkd.

Chains.

 $\frac{1}{4}$

S 20 | S 21

1933

Ascend 119 ft. over broken SE. slope.

49.00 Spur, slopes SW.; desc. 85 ft. over NW. slope.

57.00 Wash, 5 lks. wide, course SW.; asc. 212 ft. over SW. slope.

65.00 Spur, slopes SW.; desc. 85 ft. over NW. slope.

74.23 Wash, 30 lks. wide, course SW.; asc. 43 ft. over SE. slope. Road in wash, bears NE and SW.

80.00 Set an iron post, 3 ft. long, 2 ins. diam., 26 ins. in the ground, for cor. of secs. 16, 17, 20, and 21, with brass cap mkd.

T35N R16W

S 17 | S 16

S 20 | S 21

1933

of stone, 4 ft. base, 3 ft. high, W. of cor. raise a mound

Land, rolling.

Soil, rocky; 4th rate.

Timber, none; undergrowth, catclaw, cactus and joshua.

East on a random line bet. secs. 16 and 21.

40.00 Set temp. $\frac{1}{4}$ sec. cor.

80.08 Intersect N. and S. line, 28 lks. S. of the cor. of secs. 15, 16, 21, and 22.

Thence

S.89°48'W., on a true line bet. secs. 16 and 21.

Over mountainous land, through scattered desert growth.

Ascend 604 ft. over broken E. slope.

1.00 Drain, 3 lks. wide, course SE.

19.00 Low spur, slopes S.; continue ascending over NE. slope.

40.04 Set an iron post, 3 ft. long, 1 in. diam., 18 ins. in the ground to bedrock, with a limestone, 14x12x6 ins. mkd. X, deposited at the base, and in a mound of stone to top, for $\frac{1}{4}$ sec. cor. with brass cap mkd. $\frac{1}{4}$ S 16

S 21

1933

Ascend 25 ft. over NE. slope.

41.00 Spur, slopes S.; desc. 747 ft. over broken NW. slope.

75.88 Wash, 50 lks. wide, course SW.; asc. 12 ft. over SE. slope. Road in wash.

SUBDIVISION OF T. 35 N., R. 16 W.

Chains.
80.08

The cor. of secs. 16, 17, 20, and 21.


Land, mountainous.
Soil, rocky; 4th rate.
Timber, none; undergrowth, joshua, catclaw, cactus and black sage.

N.0°03'W., bet. secs. 16 and 17.

Over rolling land, through scattered desert growth.
Ascend 75 ft. over SE. slope.

38.00 Spur, slopes SW.; desc. 21 ft. over NW. slope.

40.00 Set an iron post, 3 ft. long, 1 in. diam., 18 ins. in the ground to bedrock, with a limestone, 10x8x6 ins. mkd. X, deposited at the base, and in a mound of stone to top, for $\frac{1}{4}$ sec. cor. with brass cap mkd.




Descend 78 ft. over NW. slope.

53.72 Wash, 20 lks. wide, course SW.; asc. 46 ft. over SE. slope.

57.00 Continue along E. slope.

80.00 Set an iron post, 3 ft. long, 2 ins. diam., 18 ins. in the ground to bedrock, with a limestone, 8x6x4 ins. mkd. X, deposited at the base, and in a mound of stone to top, for cor. of secs. 8, 9, 16, and 17, with brass cap mkd.



Land, rolling.
Soil, sandy; 3rd rate.
Timber, none, undergrowth, catclaw, cactus, joshua and black sage.

N.89°48'E., on a random line bet. secs. 9 and 16.

40.00 Set temp. $\frac{1}{4}$ sec. cor.

80.18 Intersect N. and S. line, 5 lks. N. of the cor. of secs. 9, 10, 15, and 16.

Thence

S.89°50'W., on a true line, bet. secs. 9 and 16.

Over mountainous land, through scattered desert growth.

Ascend 185 ft. over broken E. slope.

SUBDIVISION OF T. 35 N., R. 16 W.

Chains.	
13.00	Ridge, bears N. and S.; desc. 327 ft. over broken NW. slope.
30.00	Base, of slope, bears NE. and SW.; continue over level land.
40.09	Set an iron post, 3 ft. long, 1 in. diam., 18 ins. in the ground to bedrock, with a limestone. 10x8x8 ins. mkd. X, deposited at the base, and in a mound of stone to top, for $\frac{1}{4}$ sec. cor. with brass cap mkd.
	$\frac{1}{4}$ <u>S 9</u> S 16 1933
	Leave level land,; desc. 40 ft. over NW. slope.
52.48	Center of wash, 40 lks. wide, course SW.
52.55	Road, bears NE. and SW.; asc. 67 ft. over SE. slope.
63.00	Spur, 4.00 chs. wide, slopes SW.; desc. 83 ft. over NW. slope.
75.80	Top of ledge, 30 ft. high, bears N. and S.; continue descending.
77.01	Wash, 20 lks. wide, course S.; asc. 37 ft. over E. slope.
80.18	The cor. of secs. 8, 9, 16, and 17.
	Land, mountainous. Soil, sandy; 3rd rate. Timber, none; undergrowth, cactus, joshua and catclaw.
	N.0°03'W., bet. secs. 8 and 9.
	Over rolling land, through scattered desert growth.
15.00	Top of ledge, 30 ft. high, bears NW. and SE.; desc. 30 ft. over NE. slope.
19.28	Wash, 20 lks. wide, course SE.; continue along same.
26.00	Leave wash, course NE.; asc. 42 ft. over SE. slope.
29.00	Top of ledge, 20 ft. high, bears NE. and SW.; continue over nearly level land.
39.00	Same wash, 20 lks. wide, course SE.
40.00	Set an iron post, 3 ft. long, 1 in. diam., 18 ins. in the ground to bedrock, with a limestone, 8x6x4 ins. mkd. X, deposited at the base, and in a mound of stone to top, for $\frac{1}{4}$ sec. cor. with brass cap mkd.
	$\frac{1}{4}$ S 8 S 9 1933
	Ascend 36 ft. over gradual SW. slope.
49.50	Top of ascent.; continue over rolling land.
60.00	Same wash, 20 lks. wide, course SW.

SUBDIVISION OF T. 35 N., R. 16 W.

1908


Chains. 74.50	Base of steep ascent, bears NW. and SE.; asc. 46 ft. over SW. slope.
80.00	Set an iron post, 3 ft. long, 2 ins. diam., 26 ins. in the ground, for cor. of secs. 4, 5, 8, and 9, with brass cap mkd.
	<p>T35N R16W S 5 S 4 S 8 S 9 1933</p>
	raise a mound of stone, 4 ft. base, 3 ft. high, W. of cor.
	Land, rolling. Soil, sandy; 3rd rate. Timber, none; undergrowth, catclaw, cactus and joshua.
	N.89°50'E., on a random line bet. secs. 4 and 9.
40.00	Set temp. $\frac{1}{4}$ sec. cor.
80.00	Intersect N. and S. line, 9 lks. N. of the cor. of secs. 3, 4, 9, and 10.
	Thence
	S.89°54'W., on a true line bet. secs. 4 and 9.
	Over rolling land, through scattered desert growth.
.65	Wash, 5 lks. wide, course S.
10.00	Center of wash, 30 lks. wide, course S.
10.20	Road, bears N. and S.
40.00	Set an iron post, 3 ft. long, 1 in. diam., 6 ins. in the ground to bedrock, with a limestone 9x9x2 ins. mkd. X, deposited at the base, and in a mound of stone to top, for $\frac{1}{4}$ sec. cor. with brass cap mkd.
	<p>$\frac{1}{4}$ <u>S 4</u> S 9 1933</p>
56.84	Wash, 15 lks. wide, course SW.; asc. 166 ft. over broken SE. slope.
76.60	Low spur, slopes S.; desc. 62 ft. over SW. slope.
80.00	The cor. of secs. 4, 5, 8, and 9.
	Land, rolling. Soil, sandy; 3rd rate, and rocky; 4th rate, Timber, none; undergrowth, catclaw, cactus and joshua.

Chains.	N.0°07'E., on a random line bet. secs. 4 and 5.
40.00	Set temp. $\frac{1}{4}$ sec. cor.
80.36	Intersect N. bdy. of Tp., 14 lks. E. of the cor. of secs. 4, 5, 32, and 33.
	Thence
	S.0°01'W., on a true line bet. secs. 4 and 6.
	Over rolling land, through scattered desert growth.
.76	Drain, course SE.
3.36	Low spur, slopes SE.; desc. 30 ft. over SW. slope.
6.36	Base of slope, bears SE. and NW.
10.56	Wash, 10 lks. wide, course SE.; asc. 29 ft. over NE. slope.
20.40	Spur, slopes SE.; desc. 75 ft. over SW. slope.
40.36	Set an iron post, 3 ft. long, 1 in. diam., 8 ins. in the ground to bedrock, with a limestone, 10x6x4 ins. mkd. X, deposited at the base, and in a mound of stone to top, for $\frac{1}{4}$ sec. cor. with brass cap mkd.
	$\frac{1}{4}$
	S 5 S 4
	1933
	Descend 57 ft. over SW. slope.
48.06	Drain, 3 lks. wide, course SE.
53.14	Wash, 10 lks. wide, course SW.; asc. 49 ft. over NW. slope.
63.36	Top of ascent; continue along top of spur, slopes SW.
76.36	Leave spur; desc. 73 ft. over SW. slope.
80.36	The cor. of secs. 4, 5, 8, and 9.
	Land, rolling. Soil, rocky; 4th rate. Timber, none; undergrowth, joshua, catclaw, cactus and black sage.
	From the cor. of secs. 5, 6, 31, and 32 on the S. bdy. of the Tp.
	N.0°03'W., bet. secs. 31 and 32.
	Over rolling land, through scattered desert growth.
	Descend 5 ft. over N. slope.
.90	Wash, 10 lks. wide, course E.
4.00	Low spur, slopes SE.
12.70	Wash, 30 lks. wide, course SE.; asc. 76 ft. over SW. slope.

SUBDIVISION OF T. 35 N., R. 16 W.


6000 1000

Chains.
 15.00 Top of ledge, 30 ft. high, bears NW. and SE.
 18.50 Spur, slopes SE.; desc. 23 ft. over NE. slope.
 25.25 Wash, 3 lks. wide, course SE.; continue over level land.
 40.00 Set an iron post, 3 ft. long, 1 in. diam., 8 ins. in the ground to bedrock, with a sandstone, 16x14x10 ins. mkd. X, deposited at the base, and in a mound of stone to top, for $\frac{1}{4}$ sec. cor. with brass cap mkd.



Ascend 30 ft. over SW. slope.

55.00 Spur, slopes SE.; desc. 26 ft. along NE. slope.
 67.70 Same spur, slopes E.; desc. 40 ft. over NE. slope.
 76.70 Wash, 3 lks. wide, course E.; asc. 16 ft. over SE. slope.
 80.00 Set an iron post, 3 ft. long, 2 ins. diam., 16 ins. in the ground to bedrock, with a sandstone, 12x12x10 ins. mkd. X, deposited at the base, and in a mound of stone to top, for cor. of secs. 29, 30, 31, and 32, with brass cap mkd.



Land, rolling.
 Soil, gravelly; 3rd rate.
 Timber, none; undergrowth, catclaw, joshua and cactus.

East on a random line bet. secs. 29 and 32.
 40.00 Set temp. $\frac{1}{4}$ sec. cor.
 80.06 Intersect N. and S. line, 7 lks. S. of the cor. of secs. 28, 29, 32, and 33.
 Thence
 S.89°57'W., on a true line bet. secs. 29 and 32.
 Over rolling land, through scattered desert growth.
 Ascend 121 ft. over NE. slope.
 10.00 Spur ridge, 300 lks. wide, bears N. and S.; desc. 99 ft. over broken W. slope.
 25.86 Wash, 20 lks. wide, course S.
 32.66 Wash, 10 lks. wide, course SE.; asc. 34 ft. over E. slope.
 40.03 Set an iron post, 3 ft. long, 1 in. diam., 26 ins. in the ground, for $\frac{1}{4}$ sec. cor. with brass cap mkd.

Chains.

$$\frac{1}{4} \frac{S 29}{S 32}$$
 1933

raise a mound

of stone, 4 ft. base, 3 ft. high, N. of cor.

Ascend 34 ft. over E. slope.

42.00 Long spur, slopes S.; desc. 50 ft. over SW. slope.

54.00 Continue over level land.

70.56 Road, bears N. and S.

76.41 Wash, 10 lks. wide, course S.; asc. 30 ft. over SE. slope.

80.06 The cor. of secs. 29, 30, 31, and 32.

Land, rolling.

Soil, sandy; 3rd rate.

Timber, none; undergrowth, joshua, catclaw and cactus.

West bet. secs. 30 and 31.

Over rolling land, through scattered desert growth.

Ascend 15 ft. over gradual SE. slope.

3.10 Spur, slopes S.; desc. 23 ft. over NW. slope.

14.10 Drain, course SW.

22.10 Intersect the Arizona and Nevada State Boundary.

Set an iron post, 3 ft. long, 2 ins. diam., 26 ins. in the ground, for closing cor. of frac. secs. 30 and 31, with brass cap mkd.

	T35N	
	S 30 C	
NEV	S 31 C	
	R16W	
	1933	

raise a mound

of stone, $3\frac{1}{2}$ ft. base, 2 ft. high, E. of cor.

From this point the ~~344+78~~ Mi. Cor., heretofore described bears N. $0^{\circ}14'E.$, 31.48 chs. dist.

Land, rolling.

Soil, sandy; 3rd rate.

Timber, none; undergrowth, catclaw, cactus and joshua.

From the cor. of secs. 29, 30, 31 and 32.

N. $0^{\circ}03'W.$, bet. secs. 29 and 30.

Over rolling land, through scattered desert growth.

Ascend 34 ft. over SE. slope.

1.00 Spur, slopes E.; desc. 34 ft. over NE. slope.

Chains.
 2.91 Wash, 10 lks. wide, course SE.; continue along W. slope.
 28.70 Same wash, 8 lks. wide, course SW.
 36.00 Low spur, slopes SW.; desc. 18 ft. over NW. slope.
 40.00 Set an iron post, 3 ft. long, 1 in. diam., 26 ins. in the ground, for $\frac{1}{4}$ sec. cor. with brass cap mkd.

$\frac{1}{4}$
 S 30 | S 29
 1933

raise a mound
 of stone, 4 ft. base, 3 ft. high, W. of cor.

41.00 Wash, 3 lks. wide, course SW.; asc. 29 ft. over S. slope.
 51.00 Spur, slopes W.; descend gradually.
 55.30 Wash, 5 lks. wide, course SW.; asc. 9 ft.
 67.00 Low spur, slopes SW.; desc. 12 ft. over NW. slope.
 71.80 Road, bears NE. and SW.
 76.67 Wash, 5 lks. wide, course SW.
 80.00 Set an iron post, 3 ft. long, 2 ins. diam., 12 ins. in the ground to bedrock, with a limestone, 8x6x4 ins. mkd. X, deposited at the base, and in a mound of stone to top, for cor. of secs. 19, 20, 29, and 30, with brass cap mkd.

T35N R16W
 S 19 | S 20
 S 30 | S 29
 1933

Land, rolling.
 Soil, sandy; 3rd rate.
 Timber, none; undergrowth, cactus, catclaw and joshua.

N.89°57'E., on a random line bet. secs. 20 and 29;
 40.00 Set temp. $\frac{1}{4}$ sec. cor.
 80.02 Intersect N. and S. line, 2 lks. N. of the cor. of secs. 20, 21, 28, and 29.

Thence
 S.89°58'W., on a true line bet. secs. 20 and 29.
 Over rolling land, through scattered desert growth.
 Ascend 22 ft. over SE. slope.
 1.80 Spur, slopes S.; desc. 29 ft. over SW. slope.
 7.00 Wash, 15 lks. wide, course SE.; asc. 99 ft. over NE. slope.
 39.00 Spur, slopes SE.

SUBDIVISION OF T. 35 N., R. 16 W.

Chains.
40.01

Set an iron post, 3 ft. long, 1 in. diam., 26 ins. in the ground, for $\frac{1}{4}$ sec. cor. with brass cap mkd.

$\frac{1}{4}$ S 20
S 29
1933

raise a mound of stone, 4 ft. base, 3 ft. high, N. of cor.

Continue over nearly level land.

47.20 Wash, 30 lks. wide, course S.

47.30 Road, bears N. and S.

71.20 Drain, course SW.

77.30 Wash, 5 lks. wide, course SW.

80.02 The cor. of secs. 19, 20, 29, and 30.

Land, rolling.
Soil, sandy; 3rd rate.
Timber, none; undergrowth, catclaw, cactus and joshua.

West bet. secs. 19 and 30.

Over rolling land, through scattered desert growth.

11.58 Wash, 20 lks. wide, course S.; asc. 15 ft. over E. slope.

21.83 Intersect the Arizona and Nevada State Boundary.

Set an iron post, 3 ft. long, 2 ins. diam., 12 ins. in the ground to bedrock, with a limestone, 16x14x10 ins. mkd. X, deposited at the base, and in a mound of stone to top, for closing cor. of frac. secs. 19 and 30, with brass cap mkd.

T35N
NEV | S 19 C
| S 30 C
R16W
1933

From this point the 341 Mi. Cor., heretofore described, bears N.0°04'E., 28.60 chs. dist.

Land, rolling.
Soil, sandy; 4th rate.
Timber, none; undergrowth, joshua and cactus.

From the cor. of secs. 19, 20, 29, and 30.

N.0°03'W., bet. secs. 19 and 20.

Over rolling land, through scattered desert growth.

15.00 Descend 33 ft. over NW. slope.

15.67 Wash, 30 lks. wide, course SW.; asc. 62 ft. over SE. slope.

FOOTING

Chains.	
25.00	Spur, slopes SW.; desc. 23 ft. over NW. slope.
29.97	Wash, 5 lks. wide, course SW.; asc. 40 ft. over SE. slope.
40.00	Set an iron post, 3 ft. long, 1 in. diam., 26 ins. in the ground, for $\frac{1}{4}$ sec. cor. with brass cap mkd.
	$\frac{1}{4}$ S 19 S 20 1933
	raise a mound of stone, 4 ft. base, 3 ft. high, W. of cor.
	Ascend 12 ft. over SE. slope.
41.50	Spur, slopes SW; desc. 21 ft. over NW. slope.
44.37	Wash, 3 lks. wide, course SW.; asc. 44 ft. over SE. slope.
50.00	Spur, slopes SW.; desc. 66 ft. over NW. slope.
58.70	Wash, 10 lks. wide, course SW.; asc. 18 ft. over SE. slope.
72.00	Spur, slopes SW.; desc. 14 ft. over NW. slope.
77.59	Wash, 6 lks. wide, course SW.; asc. 14 ft. over SE. slope.
80.00	Set an iron post, 3 ft. long, 2 ins. diam., 26 ins. in the ground, for cor. of secs. 17, 18, 19. and 20, with brass cap mkd.
	T35N R16W S 18 S 17 S 19 S 20 1933
	raise a mound of stone, 4 ft. base, 3 ft. high, W. of cor.
	Land, rolling. Soil, sandy; 3rd rate, and rocky; 4th rate. Timber, none; undergrowth, black sage, cactus, catclaw and joshua.
	N.89°58'E., on a random line bet. secs. 17 and 20.
40.00	Set temp. $\frac{1}{4}$ sec. cor.
80.04	Intersect N. and S. line, 9 lks. N. of the cor. of secs. 16, 17, 20, and 21.
	Thence
	N.89°58'W., on a true line bet. secs. 17 and 20.
	Over rolling land, through scattered desert growth.
	Ascend 131 ft. over SE. slope.
11.50	Spur, slopes SW.; desc. 58 ft. over NW. slope.

SUBDIVISION OF T. 35 N., R. 16 W.

Chains.	
16.55	Wash, 5 lks. wide, course SW.; asc. 45 ft. over SE. slope.
23.00	Spur, slopes SW.; desc. 138 ft. over W. slope.
29.06	Wash, 30 lks. wide, course S.; asc. 94 ft. over E. slope.
38.60	Spur, slopes S.
39.04	Head of draw, course SW.
40.02	Set an iron post, 3 ft. long, 1 in. diam., 24 ins. in the ground, for $\frac{1}{4}$ sec. cor. with brass cap mkd.
	$\frac{1}{4}$ <u>S 17</u> S 20 1933
	raise a mound of stone, 4 ft. base, 3 ft. high, N. of cor.
	Descend 101 ft. over SW. slope.
44.56	Wash, 5 lks. wide, course S.; asc. 107 ft. over SE. slope.
50.00	Spur, slopes S.; desc. 97 ft. over NW. slope.
61.54	Wash, 10 lks. wide, course SW.; asc. 11 ft. over nearly level land.
78.65	Wash, 5 lks. wide, course SW.
80.04	The cor. of secs. 17, 18, 19, and 20.
	Land, rolling. Soil, sandy; 3rd rate. Timber, none; undergrowth catclaw, joshua and catclaw.
	West bet. secs. 18 and 19.
	Over rolling land, through scattered desert growth.
	Ascend 52 ft over broken SE. slope.
9.30	Drain, course SE.
13.90	Spur, slopes SW.; desc. 80 ft. over NW. slope.
21.00	Wash, 10 lks. wide, course SW.
21.52	Intersect the Arizona and Nevada State Boundary.
	Set an iron post, 3 ft. long, 2 ins. diam., 26 ins. in the ground, for closing cor. of frac. secs. 18 and 19, with brass cap mkd.
	T35N NEV <u>S 18</u> C S 19 C R16W 1933
	raise a mound of stone, $3\frac{1}{2}$ ft. base, $2\frac{1}{2}$ ft. high, E. of cor.

Chains. From this point the 340 Mi. Cor., heretofore described, bears N.0°19'E., 25.49 chs. dist.

Land, rolling.
Soil, rocky; 4th rate.
Timber, none; undergrowth, cactus, catclaw, joshua and black sage.

From the cor. of secs. 17, 18, 19, and 20.

N.0°03'W., bet. secs. 17 and 18.

Over rolling land, through scattered desert growth.

Ascend 131 ft. over broken SE. slope.

17.80 Spur ridge, bears NE. and SW.; desc. 106 ft. over NW. slope.

31.47 Wash, 10 lks. wide, course SW; asc. 23 ft. over SE. slope.

40.00 Set an iron post, 3 ft. long, 1 in. diam., 8 ins. in the ground to bedrock, with a limestone, 10x6x4 ins. mkd. X, deposited at the base, and in a mound of stone to top, for 1/4 sec. cor. with brass cap mkd.

1/4
S 18 | S 17
1933

Ascend 29 ft. over SE. slope.

45.00 Top of ascent; continue over level land.

69.70 Top of ledge, 40 ft. high, bears NE. and SW.; desc. 41 ft. over NW. slope.

80.00 Set an iron post, 3 ft. long, 2 ins. diam., 26 ins. in the ground, for cor. of secs. 7, 8, 17, and 18, with brass cap mkd.

T35N R16W
S 7 | S 8
S 18 | S 17
1933

raise a mound of stone, 3 1/2 ft. base, 2 1/2 ft. high, W. of cor.

Land, level and rolling.
Soil, sandy; 3rd rate.
Timber, none; undergrowth black sage and joshua.

S.89°58'E., on a random line bet. secs. 8 and 17.

40.00 Set temp. 1/4 sec. cor.

80.02 Intersect N. and S. line, 2 lks. S. of the cor. of secs. 8, 9, 16, and 17.


Thence

Chains.	N.89°59'W., on a true line bet. secs. 8 and 17. Over rolling land, through scattered desert growth.
17.20	Wash, 5 lks. wide, course S.; asc. 34 ft. over SE. slope.
29.00	Spur, slopes SW.; desc. 62 ft. over W. slope.
34.56	Wash, 5 lks. wide, course SW.; asc. 63 ft. over SE. slope.
38.50	Spur, slopes S.; desc. 13 ft. over SW. slope.
40.01	Set an iron post, 3 ft. long, 1 in. diam., 26 ins. in the ground, for $\frac{1}{4}$ sec. cor. with brass cap mkd. $\frac{1}{4}$ $\frac{S 8}{S 17}$ 1933 raise a mound of stone, $3\frac{1}{2}$ ft. base, $2\frac{1}{2}$ ft. high, N. of cor.
40.70	Wash, 3 lks. wide, course S.; asc. 102 ft. over SE. slope.
48.20	Spur, slopes SW.; desc. 148 ft. over NW. slope.
73.20	Ascend 46 ft. over E. slope.
80.02	The cor. of secs. 7, 8, 17, and 18. Land, rolling. Soil, sandy; 3rd rate. Timber, none; undergrowth, catclaw, cactus, joshua and black sage.
	West bet. secs. 7 and 18. Over rolling land, through scattered desert growth.
1.00	Wash, 15 lks. wide, course SW.; asc. 89 ft. over broken E. slope.
21.25	Intersect the Arizona and Nevada State Boundary. Set an iron post, 3 ft. long, 2 ins. diam., 18 ins. in the ground to bedrock, with a limestone, 10x8x6 ins. mkd. X, deposited at the base, and in a mound of stone to top, for closing cor. of frac. secs. 7 and 18, with brass cap mkd. NEV $\frac{T35N}{S 7} C$ $\frac{S 18}{R16W} C$ 1933 From this point the 339+3m. Cor., heretofore described, bears N.0°01'E., 26.00 chs. dist. Land, rolling. Soil, sandy; 3rd rate. Timber, none; undergrowth, black sage and joshua.

SUBDIVISION OF T. 35 N., R. 16 W.

BOOK 3998

Chains. N.0°03'W., bet. secs. 7 and 8.
 Over rolling land, through scattered desert growth.
 .30 Wash, 10 lks. wide, course SW.; asc. 111 ft. over SE. slope.
 26.00 Top of ascent; desc. 23 ft. over NW. slope.
 31.70 Drain, course SW.; asc. 80 ft. over SE. slope.
 40.00 Set an iron post, 3 ft. long, 1 in. diam., 18 ins. in the ground to bedrock, with a limestone, 6x4x2 ins. mkd. X, deposited at the base, and in a mound of stone to top, for $\frac{1}{4}$ sec. cor. with brass cap mkd.




Ascend 67 ft. over SE. slope.

43.50 Spur, slopes SW.; desc. 168 ft. over NW. slope.

48.60 Base of slope, bears NE. and SW.; continue over nearly level land.

72.60 Wash, 5 lks. wide, course SW.; asc. 25 ft. over S. slope.

80.00 Set an iron post, 3 ft. long, 2 ins. diam., 8 ins. in the ground to bedrock, with a limestone, 14x10x6 ins. mkd. X, deposited at the base, and in a mound of stone to top, for cor. of secs. 5, 6, 7, and 8, with brass cap mkd.



Land, rolling.
Soil, sandy; 3rd rate, and rocky; 4th rate.
Timber, none; undergrowth, cactus, joshua and catclaw.

S.89°59'E., on a random line bet. secs. 5 and 8.

40.00 Set temp. $\frac{1}{4}$ sec. cor.

80.02 Intersect N. and S. line, 2 lks. S. of the cor. of secs. 4, 5, 8, and 9.

Thence

West on a true line, bet. secs. 5 and 8.

Over rolling land, through scattered desert growth.

Descend 23 ft. over SW. slope.

1.87 Drain, course S.; asc. 78 ft. over SE. slope.

8.50 Spur, slopes SW.; desc. 97 ft. over NW. slope.

SUBDIVISION OF T. 35 N., R. 16 W.

Chains. 30.03 Wash, 10 lks. wide, course SW.; asc. 21 ft. over SE. slope.

40.01 Set an iron post, 3 ft. long, 1 in. diam., 16 ins. in the ground to bedrock, with a limestone, 6x6x4 ins. mkd. X, deposited at the base, and in a mound of stone to top, for 1/4 sec. cor. with brass cap mkd.

1/4 S 5 S 8 1933

Ascend 41 ft. over SE. slope.

48.00 Spur, slopes S.; desc. 53 ft. over W. slope.

52.65 Wash, 6 lks. wide, course S.; asc. 24 ft. over E. slope.

61.00 Spur, slopes S.; desc. 87 ft. over NW. slope.

71.22 Wash, 15 lks. wide, course SW.

80.02 The cor. of secs. 5, 6, 7, and 8.

Land, rolling; Soil, rocky; 4th rate. Timber, none; undergrowth, joshua and cactus.

West bet. secs. 6 and 7.

Over rolling land, through scattered desert growth.

Descend 29 ft. over W. slope.

6.70 Wash, 4 lks. wide, course S.; asc. 96 ft. over SE. slope.

16.00 Spur, slopes S.; desc. 18 ft. over W. slope.

21.23 Intersect the Arizona and Nevada State Boundary.

Set an iron post, 3 ft. long, 2 ins. diam., on bedrock, with a cross X, mkd. at the base, and in a mound of stone to top, for closing cor. of frac. secs. 6 and 7, with brass cap mkd.

T35N S 6 C S 7 C R16W 1933

From this point the 338⁺³² Mi. Cor., heretofore described, bears S.1°27'E., 3.30 chs. dist.

Land, rolling. Soil, rocky; 4th rate. Timber, none; undergrowth, catclaw, cactus, joshua and black sage.

Chains. From the cor. of secs. 5, 6, 7, and 8.
 N.0°01'E., on a random line bet. secs. 5 and 6.
 40.00 Set temp. $\frac{1}{4}$ sec. cor.
 80.40 Intersect N. bdy. of Tp., 21 lks. W. of the cor. of
 secs. 5, 6, 31 and 32.
 Thence
 S.0°10'W., on a true line bet. secs. 5 and 6.
 Over mountainous land, through scattered desert growth.
 Ascend 24 ft. over NE. slope.
 2.44 Drain, 3 lks. wide, course SE.
 10.40 Spur, slopes SE.; desc. 379 ft. over broken SW. slope.
 40.40 Set an iron post, 3 ft. long, 1 in. diam., 18 ins. in
 the ground to bedrock, with a limestone, 6x4x3 ins.
 mkd. X, deposited at the base, and in a mound of
 stone to top, for $\frac{1}{4}$ sec. cor. with brass cap mkd.
 $\frac{1}{4}$
 S 6 | S 5
 1933
 Descend 84 ft. over SW. slope.
 48.26 Wash, 10 lks. wide, course SE.; asc. 12 ft. over NE.
 slope.
 53.40 Spur, slopes SE.; desc. 86 ft. over broken SW. slope.
 80.40 The cor. of secs. 5, 6, 7, and 8.
 Land, mountainous.
 Soil, sandy; 3rd rate.
 Timber, none; undergrowth, greasewood, cactus, joshua
 and catclaw.

At a point N.0°14'E., 12.49 chs. dist., from the 343
 Mile Cor., on the Arizona and Nevada State Boundary
 heretofore described, midway in latitude bet. the SW.
 and NW. cors. of sec. 31.

Set an iron post, 3 ft. long, 1 in. diam., 26 ins. in
 the ground for $\frac{1}{4}$ sec. cor. of sec. 31, with brass
 cap mkd.

NEV | $\frac{1}{4}$ S31
 1933

raise a mound of
 stone 3 ft. base, 2 $\frac{1}{2}$ ft. high, E. of cor.

Chains.

At a point N.0°04'E., 8.50 chs. dist., from the 341+78.00 chs. Mile Cor., on the Arizona and Nevada State Boundary, heretofore described, midway bet. the NW. and SW. cors. of sec. 30.

Set an iron post, 3 ft. long, 1 in. diam., 26 ins. in the ground, for $\frac{1}{4}$ sec. cor. of sec. 30, with brass cap mkd.

NEV | $\frac{1}{4}$ S30
1933

raise a mound
of stone, 4 ft. base, 3 ft. high, E. of cor.

At a point N.0°19'E., 11.38 chs. dist., from the 341 Mile Cor. on the Arizona and Nevada State Boundary, heretofore described, midway bet. the NW. and SW. cors. of sec. 19.

Set an iron post, 3 ft. long, 1 in. diam., 20 ins. in the ground for $\frac{1}{4}$ sec. cor. of sec. 19, with brass cap mkd.

NEV | $\frac{1}{4}$ S19
1933

raise a mound
of stone, 4 ft. base, 3 ft. high, E. of cor.

At a point N.0°01'E., 14.48 chs. dist., from the 340 Mile Cor. on the Arizona and Nevada State Boundary, heretofore described, midway, bet. the NW. and SW. cors. of sec. 18.

Set an iron post, 3 ft. long, 1 in. diam., 6 ins. in the ground to bedrock, with a limestone, 8x6x4 ins. mkd. X, deposited at the base, and in a mound of stone to top, for $\frac{1}{4}$ sec. cor. of sec. 18, with brass cap mkd.

NEV | $\frac{1}{4}$ S18
1933

At a point N.0°07'E., 14.10 chs. dist., from the 339+3 Mile Cor. on the Arizona and Nevada State Boundary, heretofore described, midway bet. the NW. and SW. cors. of sec. 7.

Set an iron post, 3 ft. long, 1 in. diam., 26 ins. in the ground, for $\frac{1}{4}$ sec. cor. of sec. 7, with brass cap mkd.

NEV | $\frac{1}{4}$ S7
1933

raise a mound of
stone, 4 ft. base, 3 ft. high, E. of cor.

Chains.

At a point 40.00 chs. in latitude N. from the SW. cor. of sec. 6. on the Arizona and Nevada State Boundary.

Set an iron post, 3 ft. long, 1 in. diam., 18 ins. in the ground to bedrock, with a limestone, 10x8x6 ins. mkd. X, deposited at the base, and in a mound of stone to top, for $\frac{1}{4}$ sec. cor. of sec. 6, with brass cap mkd.

NEV | $\frac{1}{4}$ s 6
1933

FINAL TEST OF INSTRUMENT.

For final test of instrument No. 19423, see field notes of the resurvey of a portion of the Arizona and Nevada State Boundary, resurveyed under this group.

GENERAL DESCRIPTION.

The land in T. 35 N., R. 16 W., is rolling and mountainous. The general elevation of the township is about 3,000 ft. above sea level. The soil throughout the township, is sandy and rocky. There is no timber within the township. The undergrowth consists of cat-claw, cactus, joshua and greasewood. The predominating *interest* is stock grazing.

4-680
(August, 1926)

BOOK 3993

FIELD ASSISTANTS.

NAMES.	CAPACITY.
Elliott Pearson	1st.Chainman
Henry Hiester	2nd.Chainman
Richard Andrus	2nd.Chainman
A.L.Lovelady	Flagman
Wayne Yates	Moundman
Lamar Sorenson	Axeman

CERTIFICATE OF UNITED STATES SURVEYOR

We, William E. Hiester, U.S. Surveyor and

Walter H. Good, U. S. Surveyor, hereby certify upon honor that, in pursuance of special instructions received from the District Cadastral Engineer for Arizona

bearing date of the 30th day of June, 1931, we have well, faithfully, and truly in our own proper persons, and in strict conformity with said instructions, the Manual of Surveying Instructions, and the laws of the United States, surveyed ~~all these parts~~ ~~of~~ the ~~subdivisional~~ lines, completing the survey of Township 35 North, Range 16 West,

of the Gila and Salt River Meridian, in the State of Arizona, which are represented in the foregoing field notes as having been executed by ~~me~~ ^{us}, and under ~~my~~ ^{our} direction; and that all the corners of said survey have been established and perpetuated in strict accordance with the Manual of Surveying Instructions, and the special written instructions of the District Cadastral Engineer for Arizona and in the specific manner described in the field notes, and that the foregoing are the original field notes of such survey.

Walter H. Good U.S. Surveyor William E. Hiester U. S. Surveyor.

Boise, Idaho Sept. 7, 1933

APPROVAL

Glendale, California, August 26, 1933.

OFFICE OF U. S. SUPERVISOR OF SURVEYS, Denver, Colorado, April 28, 1934.

The foregoing field notes of the survey of the subdivisional lines, completing the survey of Township 35 North, Range 16 West, of the Gila and Salt River Meridian, in the State of Arizona,

executed by William E. Hiester and Walter H. Good, U.S. Surveyors, under their special instructions dated June 30, 1931, ~~1931~~, having been critically examined, and the necessary corrections and explanations made, the said field notes, and the surveys they describe, are hereby approved.

[Signature] U. S. Supervisor of Surveys.

I certify that the foregoing transcript of the field notes of the above-described surveys in ~~has~~ has been correctly copied from the original notes on file in this office.

U. S. Supervisor of Surveys.