

Original

3994

4-679
(April 1933)

Book H.

BOOK 3994

FIELD NOTES

OF THE SURVEY OF THE

subdivisional lines

of

Township 36 North, Range 16 West,

3994

Of the Gila and Salt River Meridian,

In the State of Arizona

EXECUTED BY

Benjamin J. Kinsey, William E. Hiester and Walter H. Good,

U.S. Surveyors,

3994

Under special instructions dated June 30, 1931, which provided for the surveys included under Group No. 169, bearing the approval of the Commissioner of the General Land Office under date of September 21, 1931, and assignment instructions dated July 27, 1932, January 14, 1933 and March 7, 1933.

Survey commenced December 5, 1932 ~~xxxx~~

Survey completed March 24, 1933 ~~xxxx~~

1A

BOOK 3994

INDEX DIAGRAM.

Township 36 North, Range 16 West

	32	33	34	35	36	37
50 6	48 5	36 4	27 3	18 2	8 1	
47	47	35	26	17	7	
50 7	46 8	34 9	25 10	16 11	7 12	
45	44	34	25	16	6	
50 18	43 17	33 16	24 15	15 14	5 13	
43	42	32	23	14	4	
50 19	41 20	31 21	22 22	13 23	4 24	
41	40	30	22	12	3	
49 30	39 29	29 28	21 27	11 26	2 25	
39	38	29	20	10	1	
49 31	37 32	28 33	19 34	9 35	1 36	

6-151

Chains.

The survey was executed with light mountain transits made by Buff and Buff, Serial No. 16740, used by Benjamin J. Kinsey, U. S. Surveyor, No. 19423, used by William E. Hiester, U. S. Surveyor, and No. 14189 used by Walter H. Good, U. S. Surveyor. For description and tests of instrumental equipment and for preliminary observations of instrument No. 16740, see field notes of the survey of the 8th and 9th Standard Parallels North, surveyed under this group, and for instruments Nos. 19423 and 14189, see field notes of the 8th and 9th Standard Parallels, surveyed under this group. . . . North

I commence the subdivisional survey at the cor. of secs. 1, 2, 35 and 36, on the S. bdy. of the Tp.


N.0°01'W., bet. secs. 35 and 36.

Over rolling land, through scattered desert growth.

19.00 Wash, 40 lks. wide, course SE.; asc. 174 ft. over SW. slope.

29.50 Small spur, slopes W.; continue ascending.


40.00 Set an iron post, 3 ft. long, 1 in. diam., 12 ins. in the ground to bedrock, with a lava stone, 10x6x6 ins. mkd. X, deposited at the base, and in a mound of stone to top, for ¼ sec. cor. with brass cap mkd.



60.00 Base of rimrocks, 30 ft. high, bears NE. and SW.

70.00 Top of same; desc. 56 ft. along W. slope.

80.00 Set an iron post, 3 ft. long, 2 ins. diam., 16 ins. in the ground to bedrock, with a lava stone, 10x6x6 ins. mkd. X, deposited at the base, and in a mound of stone to top, for cor. of secs. 25, 26, 35, and 36, with brass cap mkd.



Land, rolling and mountainous.
Soil, rocky; 4th rate.
Timber, none; undergrowth, joshua, cactus and greasewood.

East on a random line bet. secs. 25 and 36.

40.00 Set temp. ¼ sec. cor.

80.04 Intersect E. bdy. of Tp., at the cor. of secs. 25, 30, 31 and 36.

Thence

West on a true line bet. secs. 25 and 36.

SUBDIVISION OF T. 36 N., R. 16 W.

Chains. Over mountainous land, through scattered desert growth.
Ascend 34 ft. over gradual E. slope.

10.00 Broad, spur, slopes SE.; desc. 34 ft. over W. slope.

20.34 Wash, 20 lks. wide, course S.; asc. 12 ft. over gradual E. slope.

23.00 Spur, slopes S.

24.10 Draw, course SE.; asc. 16 ft. over E. slope.

40.02 Set an iron post, 3 ft. long, 1 in. diam., 16 ins. in the ground to bedrock, with a lava stone, 10x6x6 ins. mkd. X, deposited at the base, and in a mound of stone to top, for $\frac{1}{4}$ sec. cor. with brass cap mkd.

$\frac{1}{4}$ S 25
S 36
1932

51.64 Road, on ridge, bears N. and S.; desc. 20 ft. over W. slope.

55.14 Wash, 15 lks. wide, course S.; asc. 17 ft. over E. slope.

59.00 Spur, slopes S.; desc. 87 ft. over W. slope.

65.04 Wash, 50 lks. wide, course S.; asc. 96 ft. over E. slope.

66.54 Top of rimrocks, 50 ft. high, bears N. and S.; continue ascending.

76.00 Spur, slopes S. ; desc. 85 ft. over W. slope.

78.04 Top of rimrocks, bears N. and S.; continue descending.

80.04 The cor. of secs. 25, 26, 35, and 36.

Land, mountainous.
Soil, rocky; 4th rate.
Timber, none; undergrowth, joshua, sage brush, cactus and greasewood.

N.0°01'W., bet. secs. 25 and 26.

Over rolling land, through scattered desert growth.
Ascend 8 ft. along SW. slope.

10.00 Small rocky spur, slopes W.; desc. 24 ft.

15.00 Foot of descent; asc. 103 ft. over edge of canyon.

40.00 Set an iron post, 3 ft. long, 1 in. diam., 4 ins. in the ground to bedrock, with a lava stone, 10x6x4 ins. mkd. X, deposited at the base, and in a mound of stone to top, for $\frac{1}{4}$ sec. cor. with brass cap mkd.

$\frac{1}{4}$
S 26 | S 25
1932

SUBDIVISION OF T. 36 N., R. 16 W.

BOOK 3994

Chains.	Continue along W. slope.									
75.00	Spur, slopes SE.; continue along E. slope.									
80.00	Set an iron post, 3 ft. long, 2 ins. diam., 20 ins. in the ground to bedrock, with a lava stone, 10x10x6 ins. mkd. X, deposited at the base, and in a mound of stone to top, for cor. of secs. 23, 24, 25, and 26, with brass cap mkd.									
	<p>T 36 N R 16 W.</p> <table style="margin: auto;"> <tr> <td>S 23</td> <td> </td> <td>S 24</td> </tr> <tr> <td>S 26</td> <td> </td> <td>S 25</td> </tr> <tr> <td colspan="3" style="text-align: center;">1932</td> </tr> </table>	S 23		S 24	S 26		S 25	1932		
S 23		S 24								
S 26		S 25								
1932										
	<p>Land, rolling. Soil, sandy; 3rd rate and rocky; 4th rate. Timber, none; undergrowth, joshua, cactus, greasewood and sage brush.</p>									
	East on a random line bet. secs. 24 and 25.									
40.00	Set temp. $\frac{1}{4}$ sec. cor.									
80.04	Intersect the E. bdy. of Tp., at the cor. of secs. 19, 24, 25, and 30.									
	Thence									
	West on a true line bet. secs. 24 and 25.									
	Over rolling land, through scattered desert growth.									
	Ascend 196 ft. over NE. slope of cedar Canyon, course SE.									
14.00	Top of rimrocks along Cedar Canyon, bears NE. and SW.									
15.00	Spur, slopes SE.; desc. 17 ft. over gradual SW. slope.									
23.62	Wash, 15 lks. wide, course SE.; asc. 29 ft. over SE. slope.									
35.00	Small spur, slopes SE.; desc. 29 ft. over SW. slope.									
40.02	Set an iron post, 3 ft. long, 1 in. diam., 20 ins. in the ground to bedrock, with a lava stone, 10x10x10 ins. mkd. X, deposited at the base, and in a mound of stone to top, for $\frac{1}{4}$ sec. cor. with brass cap mkd.									
	<p>$\frac{1}{4}$ S 24</p> <p>S 25</p> <p>1932</p>									
41.20	Draw, 20 lks. wide, course SE.; asc. 35 ft. over NE. slope.									
46.00	Spur, slopes SE.; desc. gradually.									
49.95	Wash, 10 lks. wide, course SE.; asc. 37 ft.									
55.00	Spur, slopes S.; desc. 40 ft. over W. slope.									
60.20	Draw, course S.; asc. 31 ft. over E. slope.									
64.06	Old road, bears N. and S. on spur slopes S.; desc. 46 ft. over W. slope.									

Chains.
70.42

Wash, 30 lks. wide, course S.; asc. 46 ft. over E. slope.

80.04

The cor. of secs. 23, 24, 25, and 26.
Land, rolling.
Soil, sandy; 3rd rate and rocky; 4th rate.
Timber, none; undergrowth, cactus, joshua and greasewood.

N.0°01'W., bet. secs. 23 and 24.


Over rolling land, through scattered desert growth.
Descend 53 ft. over gradual NE. slope.

33.40

Wash, 20 lks. wide, course SE.; asc. 38 ft. over S. slope. Road in wash.

40.00


Set an iron post, 3 ft. long, 1 in. diam., 20 ins. in the ground to bedrock, (on spur slopes S) with a limestone, 12x6x6 ins. mkd. X, deposited at the base, and in a mound of stone to top, for 1/4 sec. cor. with brass cap mkd.



Ascend 53 ft. along W. slope of spur.

80.00

Set an iron post, 3 ft. long, 2 ins. diam., 15 ins. in the ground to bedrock, with a limestone, 6x6x4 ins. mkd. X, deposited at the base, and in a mound of stone to top, for cor. of secs. 13, 14, 23, and 24, with brass cap mkd.



Land, rolling.
Soil sandy; 3rd rate.
Timber, none; undergrowth, joshua, greasewood, cactus and sage brush.

East on a random line bet. secs. 13 and 24.

40.00

Set temp. 1/4 sec. cor.

80.00

Intersect E. bdy. of Tp., at the cor. of secs. 13, 18, 19, and 24.

Thence

West on a true line bet. secs. 13 and 24.

Over rolling land, through scattered desert growth.

Ascend 15 ft. over gradual SW. slope.

2.50

Spur, bears S. ; desc. 40 ft. over W. slope.

SUBDIVISION OF T. 36 N., R. 16 W.

BOOK 3994

- Chains.
- 6.10 Wash, 15 lks. wide, course SE.; asc. 67 ft. over gradual E. slope.
 - 17.50 Spur, slopes S.; desc. 250 ft. over W. slope.
 - 23.50 Top of rimrocks, 30 ft. high, bears N. and S.
 - 30.00 Continue descending over gradual W. slope.
 - 40.00 Set an iron post, 3 ft. long, 1 in. diam., 16 ins. in the ground to bedrock, with a lava stone, 10x6x6 ins. mkd. X, deposited at the base, and in a mound of stone to top, for $\frac{1}{4}$ sec. cor. with brass cap mkd.

$\frac{1}{4}$ S 13
S 24
1932

Canyon

- 44.20 Cedar Wash, 150 lks. wide, course SE.; asc. 298 ft. over rocky E. slope.
- 55.50 Top of rimrocks, 30 ft. high, bears SE. and NW.
- 60.50 Spur, slopes SE.; desc. 17 ft. over SW. slope.
- 66.30 Draw, 10 lks. wide, course SE.; asc. 46 ft. over NE. slope.
- 71.50 Spur, slopes SE.; desc. 17 ft. over SW. slope.
- 75.00 Draw, course SE.; asc. 45 ft. over NE. slope.
- 80.00 The cor. of secs. 13, 14, 23, and 24.

Land, rolling and mountainous.
Soil, rocky; 4th rate.
Timber, none; undergrowth, joshua, cactus and sage brush.

N.0°01'W., bet. secs. 13 and 14.

Over rolling land, through scattered desert growth.
Ascend 31 ft. over gradual SE. slope.

- 25.00 Spur, slopes SE.; desc. 58 ft. over NE. slope.
- 32.00 Top of rimrocks 30 ft. high, bears NW. and SE.
- 36.63 Same rimrocks, bears NE. and SW.
- 40.00 Set an iron post, 3 ft. long, 1 in. diam., 10 ins. in the ground to bedrock, with a lava stone, 12x12x10 ins. mkd. X, deposited at the base, and in a mound of stone to top, for $\frac{1}{4}$ sec. cor. with brass cap mkd.

$\frac{1}{4}$
S 14 | S 13
1932

Descend 183 ft. over rocky NE. slope.

- 65.70 Center of Cedar Wash, 200 lks. wide, course SE.
- 71.10 Wash, 30 lks. wide, course SE.; asc. 23 ft. over SW. slope.

Chains.
80.00

Set an iron post, 3 ft. long, 2 ins. diam., 10 ins. in the ground to bedrock, with a lava stone, 12x10x10 ins. mkd. X, deposited at the base, and in a mound of stone to top, for cor. of secs. 11,12,13, and 14, with brass cap mkd.

T 36 N R 16 W
S 11 | S 12
S 14 | S 13
1932

Land, rolling.
Soil, rocky; 4th rate.
Timber, none; undergrowth, greasewood, cactus. joshua and sage brush.

- 40.00 East on a random line bet. secs. 12 and 13.
Set temp. $\frac{1}{4}$ sec. cor.
- 80.06 Intersect E. bdy. of Tp., at the cor. of secs. 7,12,13, and 18.
Thence
West on a true line bet. secs. 12 and 13.
Over rolling land, through scattered desert growth.
Ascend 103 ft. over SE. slope.
- 10.00 Spur, slopes SE.; desc. 87 ft. over NW. slope.
- 19.00 Small spur, slopes SW.; continue descending.
- 23.63 Draw, 10 lks. wide, course SW.; asc. 46 ft. over SE. slope.
- 27.00 Spur, slopes S.; desc. 38 ft. over SW. slope.
- 30.52 Center of draw, 100 lks. wide course SE.; asc. 63 ft. over NE. slope.
- 40.03 Set an iron post, 3 ft. long, 1 in. diam., 18 ins. in the ground to bedrock, with a lava stone, 8x8x6 ins. mkd. X, deposited at the base, and in a mound of stone to top, for $\frac{1}{4}$ sec. cor. with brass cap mkd.
- $\frac{1}{4}$ S 12
S 13
1932
- 41.00 Spur, slopes SE.; desc. 28 ft. over SW. slope.
- 46.10 Head of draw, course S.; asc. 48 ft. over SE. slope.
- 52.00 Spur, slopes SW.; desc. 313 ft. over rocky NW. slope.
- 53.70 Top of rimrocks, 20 ft. high, hears NE. and SW.
- 68.02 Center of wash, 200 lks. wide, course SW.; asc. 32 ft. over SE. slope.
- 75.00 Spur, slopes S.; desc. gradual SW. slope.
- 80.06 The cor. of secs. 11,12,13, and 14.


SUBDIVISION OF T. 36 N., R. 16 W.

BOOK 3994

Chains. Land, rolling.
 Soil, rocky; 4th rate.
 Timber, none; undergrowth, cactus, joshua and greasewood.

N.0°01'W., bet. secs. 11 and 12.
 Over mountainous land, through scattered desert growth.
 Ascend 351 ft. over SW. slope.

40.00 Set an iron post, 3 ft. long, 1 in. diam., 8 ins. in the ground to bedrock, with a lava stone, 10x8x6 ins. mkd. X, deposited at the base, and in a mound of stone to top, for 1/4 sec. cor. with brass cap mkd.



40.50 Spur, slopes SW.


42.50 Spur, slopes SE.; desc. 166 ft. over NE. slope.

57.90 Wash, 50 lks. wide, course SE.; asc. 81 ft. over SW. slope.

65.00 Spur, slopes SE.; continue along SE. slope.

76.00 Descend 28 ft. over gradual NE. slope.

80.00 Set an iron post, 3 ft. long, 2 ins. diam., 18 ins. in the ground to bedrock, with a lava stone 10x4x4 ins. mkd. X, deposited at the base, and in a mound of stone to top, for cor. of secs. 1, 2, 11, and 12, with brass cap mkd.



Land, mountainous.
 Soil rocky; 4th rate.
 Timber, none; undergrowth, cactus, joshua and greasewood.

East on a random line bet. secs. 1 and 12.

40.00 Set temp. 1/4 sec. cor.

79.96 Intersect E. bdy. of Tp., 7 lks. S. of the cor. of secs. 1, 6, 7, and 12.

Thence

S.89°57'W., on a true line, bet. secs. 1 and 12.

Over rolling land, through scattered desert growth.

5.00 Spur, slopes S.; desc. 149 ft. over NE. slope.

17.80 Top of rimrocks, 20 ft. high, bears N. and S.; continue descending.

24.10 Wash, 20 lks. wide, course SW.; asc. 86 ft. over rocky SE. slope.

Chains.	
28.30	Top of black knoll.; desc. 161 ft. over NW. slope.
35.40	Wash, 40 lks. wide, course SW.; asc. 112 ft. over SE. slope.
39.98	Set an iron post, 3 ft. long, 1 in. diam., 6 ins. in the ground to bedrock, with a lava stone, 12x10x10 ins. mkd. X, deposited at the base, and in a mound of stone to top, for $\frac{1}{4}$ sec. cor. with brass cap mkd.
	$\frac{1}{4}$ <u>S 1.</u>
	S 12 1932
	Ascend 26 ft. over SE. slope.
40.50	Top of ascent on S. slope of black knoll.; desc. 64 ft. over W. slope.
44.04	Draw, 30 lks. wide, course SE.; asc. 84 ft. over SE. slope.
48.00	Top of ascent; desc. 86 ft. over SW. slope.
54.30	Wash, 30 lks. wide, course SE.; asc. 124 ft. over NE. slope.
62.50	Top of spur, slopes SE.; desc. 202 ft. over W. slope.
78.00	Wash, 40 lks. wide, course SW.
79.96	The cor. of secs. 1, 2, 11, and 12.
	Land, rolling and mountainous. Soil rocky; 4th rate. Timber, none; undergrowth, cactus, joshua and greasewood.

N.0°01'W., bet. secs. 1 and 2.

Over rolling land, through scattered desert growth.

.50	Wash, 30 lks. wide, course SE.
1.80	Enter wash, course SW.
2.70	Leave same, course SW.
15.76	Enter wash, course SE
18.30	Leave same course SW.
25.00	Center of same wash, 250 lks. wide, course SE.; asc. 85 ft. over SW. slope.
39.75	Draw, course SW.; continue along W. slope.
40.00	Set an iron post, 3 ft. long, 1 in. diam., 14 ins. in the ground to bedrock, with a lava stone, 10x8x8 ins. mkd. X, deposited at the base, and in a mound of stone to top, for $\frac{1}{4}$ sec. cor. with brass cap mkd.


$\frac{1}{4}$

S 2 | S 1

1932

Chains.

- 59.50 Enter draw, course SW.
 - 60.50 Leave same.
 - 70.00 Same draw, course SE.; asc. 182 ft. over S. slope.
 - 81.73 Intersect the Ninth Standard Parallel North.
- Set an iron post, 3 ft. long, 2 ins. diam., 12 ins. in the ground to bedrock, with a limestone, 12x8x4 ins. mkd. X, deposited at the base, and in a mound of stone to top, for closing cor. of secs. 1 and 2. with brass cap mkd.



From this point the standard $\frac{1}{4}$ sec. cor. of sec. 36. on the S. bdy. of T. 37 N., R. 16 W., heretofore described, bears East 7.12 chs. dist.

Land, rolling.
Soil, sandy; 3rd rate, and rocky; 4th rate.
Timber, none; undergrowth, joshua, cactus and greasewood.

From the cor. of secs. 2, 3, 34, and 35, on the S. bdy. of the Tp.

N.0°01'W., bet. secs. 34 and 35.

Over rolling land, through scattered desert growth.

Descend 64 ft. over N. slope.

- 2.30 Gulch, 20 lks. wide, course E.
- 5.00 Spur, slopes E.; desc. 47 ft. over N. slope.
- 7.60 Gulch, 20 lks. wide, course E.; asc. 38 ft. over S. slope.
- 10.00 Spur, slopes E.; desc. 38 ft. over N. slope.
- 11.60 Gulch, 20 lks. wide, course E.; asc. 29 ft. over S. slope.
- 15.00 Spur, slopes E. ; desc. 61 ft. over N. slope.
- 17.83 Gulch, 20 lks. wide, course E.; asc. 17 ft. over S. slope.
- 20.00 Spur, slopes E.; desc. 50 ft. over N. slope.
- 26.86 Wash, 15 lks. wide, course E.; asc. 70 ft. over S. slope.
- 33.50 Spur, slopes E.; desc. 106 ft. over N. slope.
- 38.55 Gulch, 20 lks. wide, course E.; asc. 29 ft. over S. slope.

Chains. 40.00	Set an iron post, 3 ft. long, 1 in. diam., on bedrock with a cross X, mkd. at the base, and in a mound of stone to top, for $\frac{1}{4}$ sec. cor. with brass cap mkd.
	$\frac{1}{4}$ S 34 S 35 1932.
43.00	Spur, slopes SE.; desc. 55 ft. over NE. slope.
48.46	Wash, 20 lks. wide, course SE.; asc. 35 ft. over SE. slope.
57.00	Spur, slopes SE.; desc. 84 ft. over NE. slope.
63.50	Wash, 20 lks. wide, course NE.
65.00	Point of spur, slopes E.
66.00	Wash, 20 lks. wide, course E.; asc. 85 ft. along E. slope.
75.00	Spur, slopes E.; desc. 23 ft. over NE. slope.
79.90	Wash, 20 lks. wide, course E.
80.00	Set an iron post, 3 ft. long, 2 ins. diam., 15 ins. in the ground to bedrock, with a limestone, 10x10x10 ins. mkd. X, deposited at the base, and in a mound of stone to top, for cor. of secs. 26, 27, 34, and 35, with brass cap mkd.
	T 36 N R 16 W S 27 S 26 S 34 S 35 1932.
	Land, rolling. Soil, sandy; 3rd rate, and rocky; 4th rate. Timber, none; undergrowth, joshua, cactus, sage brush and greasewood.
	East on a random line bet. secs. 26 and 35.
40.00	Set temp. $\frac{1}{4}$ sec. cor.
80.10	Intersect N. and S. line, 9 lks. N. of the cor. of secs. 25, 26, 35, and 36.
	Thence.
	N. 89° 56' W., on a true line bet. secs. 26 and 35.
	Over rolling land, through scattered desert growth.
	Descend 27 ft. over W. slope.
2.10	Wash. 30 lks. wide, course S.; asc. 115 ft.
2.80	Top of rimrocks, 20 ft. high, bears N. and S.
3.60	Spur, slopes S..
5.60	Top of rimrocks, 20 ft. high, bears N. and S.; desc. 107 ft. over rocky W. slope.

Chains.	
9.80	Wash, 30 lks. wide, course S.; asc. 113 ft. over SW. slope.
13.10	Top of rimrocks, 20 ft. high, bears N. and S.
15.10	Spur, slopes SE.; desc. 57 ft. over SW. slope.
20.10	Head of small canyon, course S.; asc. 80 ft. over SE. slope.
30.10	Spur, slopes S.
30.60	Top of rimrocks, 30 ft. high, bears N. and S.; desc. 190 ft. over W. slope.
40.05	Set an iron post, 3 ft. long, 1 in. diam., 18 ins. in the ground to bedrock, with a lava stone, 12x12x10 ins. mkd. X, deposited at the base, and in a mound of stone to top, for $\frac{1}{4}$ sec. cor. with brass cap mkd.
	$\frac{1}{4}$ S 26 S 35 1932
42.60	Wash, 20 lks. wide, course SW.
47.30	Wash, 100 lks. wide, course S.; asc. 40 ft. over E. slope.
50.10	Spur, slopes S.; desc. gradual W. slope.
52.30	Wash, 15 lks. wide, course S.; asc. 32 ft. over E. slope.
57.30	Spur, slopes S.; desc. 79 ft. over W. slope.
65.90	Road, bears SE. and NW. in wash, course SE.; asc. 28 ft. over SE. slope.
67.10	Spur, slopes SE.; desc. 21 ft. over SW. slope.
70.70	Wash, 15 lks. wide, course SE.
77.50	Wash, course SE.
79.40	Same wash. 20 lks. wide, course NE.
80.10	The cor. of secs. 26, 27, 34, and 35.
	Land, rolling. Soil, rocky; 4th rate. Timber, none; undergrowth, cactus, joshua, greasewood and sage brush.

N.0°01'W., bet. secs. 26 and 27.

Over rolling land, through scattered desert growth.
Ascend 74 ft. over SE. slope.

5.00	Spur, slopes SE.; desc. 59 ft. over NE. slope.
10.00	Wash, 10 lks. wide, course NE.; asc. gradual SW. slope.
19.60	Road, bears SE. to Pakoon Wash and NW. to St Thomas Nevada.

Chains	
23.90	Wash, 20 lks. wide, course SE.
25.00	Spur, slopes SE.
29.00	Wash, 30 lks. wide, course SE. Ascend SW slope.
37.80	Wash, 20 lks. wide, course SE.
39.90	Same wash, course SW.
40.00	Set an iron post, 3 ft. long, 1 in. diam., 8 ins. in the ground to bedrock, with a limestone, 12x10x10 ins. mkd. X, deposited at the base, and in a mound of stone to top, for $\frac{1}{4}$ sec. cor. with brass cap mkd.
	$\frac{1}{4}$ S 27 S 26 1932
	Ascend 28 ft. over SE. slope.
40.84	Road, bears SW. and NE.; Ascend SW slope.
52.70	Same road, bears NW. and SE.
60.00	Spur, bears SE.
65.20	Wash, 30 lks. wide, course SE.; asc. 32 ft. over SW. slope.
70.00	Spur, slopes SE.
73.50	Wash, 20 lks. wide, course SE.
75.00	Same wash, course SW.; asc. 45 ft. over SW. slope.
80.00	Set an iron post, 3 ft. long, 2 ins. diam., 16 ins. in the ground to bedrock, with a limestone, 10x8x8 ins. mkd. X, deposited at the base, and in a mound of stone to top, for cor. of secs. 22, 23, 26, and 27, with brass cap mkd.
	T 36 N R 16 W S 22 S 23 S 27 S 26 1932
	Land, rolling. Soil, sandy; 3rd rate, and rocky; 4th rate. Timber, none; undergrowth, joshua, sage brush, cactus and greasewood.
	S. 89° 56' E., on a random line bet. secs. 23 and 26.
40.00	Set temp. $\frac{1}{4}$ sec. cor.
80.00	Intersect N. and S. line 19 lks. S. of the cor. of secs. 23, 24, 25, and 26.
	Thence
	S. 89° 56' W., on a true line net. secs. 23 and 26.
	Over rolling land, through scattered desert growth.
	Ascend 22 ft. over E. slope.
2.50	Spur, slopes S.; desc. 84 ft. over W. slope.

- Chains.
- 9.70 Wash, 20 lks. wide, course S.; asc. 72 ft. over NE. slope.
- 19.50 Spur, slopes S.; desc. 83 ft. over W. slope.
- 26.80 Draw, 30 lks. wide, course S.; asc. 70 ft. over E. slope.
- 31.50 Spur, slopes S.; desc. 106 ft. over SW. slope.
- 40.00 Set an iron post, 3 ft. long, 1 in. diam., 5 ins. in the ground to bedrock, with a limestone, 8x8x4 ins. mkd. X, deposited at the base, and in a mound of stone to top, for $\frac{1}{4}$ sec. cor. with brass cap mkd.

$\frac{1}{4}$ S 23
S 26
1932

Descend 46 ft. over SW. slope.

- 45.80 Wash, 50 lks. wide, course SW.; asc. 16 ft. over E. slope.
- 51.00 Small spur, slopes S.
- 54.14 Wash, 30 lks. wide, course S.; asc. 153 ft. over NE. slope.
- 67.00 Spur, slopes SE.
- 70.00 Spur, slopes S.; desc. 77 ft. over W. slope.
- 76.30 Wash, 20 lks. wide, course S.
- 80.00 The cor. of secs. 22, 23, 26, and 27.

Land, rolling.
Soil, sandy; 3rd rate and rocky; 4th rate.
Timber, none; undergrowth, catclaw, cactus, joshua and greasewood.

N.0°01'W., bet. secs. 22 and 23.

Over rolling land, through scattered desert growth.

- 3.30 Wash, 30 lks. wide, course SW.; asc. 68 ft. over SW. slope.
- 6.23 Same wash, course SE.
- 18.00 Spur, slopes SE.; desc. 23 ft. over NE. slope.
- 32.10 Draw, 15 lks. wide, course SE.; asc. 49 ft. over SW. slope.
- 40.00 Set an iron post, 3 ft. long, 1 in. diam., 18 ins. in the ground to bedrock, with a limestone, 8x8x4 ins. mkd. X, deposited at the base, and in a mound of stone to top, for $\frac{1}{4}$ sec. cor. with brass cap mkd.

$\frac{1}{4}$
S 22 | S 23
1932

Descend 37 ft. over NE. slope.

- Chains.
 51.60 Wash, 20 lks. wide, course SE. ; asc. 43 ft. over SW. slope.
 58.00 Spur, slopes SE.; desc. 10 ft. over NE. slope.
 63.80 Wash, 20 lks. wide, course SE.; asc. 40 ft. over SW. slope.
 72.50 Small spur, slopes SE.; desc. 36 ft. over NW. slope,
 80.00 Set an iron post, 3 ft. long, 2 ins. diam., 18 ins. in the ground to bedrock, with a limestone, 10x10x10 ins. mkd. X, deposited at the base, and in a mound of stone to top, for cor. of secs, 14,15,22, and 23, with brass cap mkd.

T 36 N R 16 W
 S 15 | S 14
 S 22 | S 23
 1932

Land, rolling.
 Soil, sandy; 3rd rate.
 Timber, none; undergrowth, cactus, joshua and greasewood.

- N.89°56'E., on a random line bet. secs. 14 and 23.
 40.00 Set temp. $\frac{1}{4}$ sec. cor.
 80.04 Intersect N. and S. line, 9 lks. N. of the cor. of secs. 13,14,23, and 24.
 Thence
 West on a true line bet. secs. 14 and 23.
 Over rolling land, through scattered desert growth.
 Descend 86 ft. over SW. slope.
 11.24 Rocky wash, 30 lks. wide, course SE.; asc. 49 ft. over NE. slope.
 18.50 Spur, slopes S.; desc. 80 ft. over SW. slope.
 25.00 Draw, course S.
 34.00 Spur, slopes S.; desc. 65 ft. over SW. slope.
 40.02 Set an iron post, 3 ft. long, 1 in. diam., 16 ins. in the ground to bedrock, with a limestone, 8x8x4 ins. mkd. X, deposited at the base, and in a mound of stone to top, for $\frac{1}{4}$ sec. cor. with brass cap mkd.
- $\frac{1}{4}$ S 14
 S 23
 1932
- Descend 23 ft. over SW. slope.
 42.04 Wash, 30 lks. wide, course S.; asc. 22 ft. over NE. slope.
 47.50 Spur, slopes SE.; desc. 32 ft. over W. slope.
 52.64 Wash, 10 lks. wide, course S.

SUBDIVISION OF T. 36 N., R. 16 W.

BOOK 8994

Chains.


- 57.00 Spur, slopes S.; desc. 30 ft. over NW. slope.
- 61.04 Wash, 15 lks. wide, course SW.
- 62.64 Old road, bears N. and S.
- 67.34 Wash, 15 lks. wide, course SE.
- 80.04 The cor. of secs. 14, 15, 22, and 23.

Land, rolling.
 Soil, sandy; 3rd rate.
 Timber, none; undergrowth, cactus, joshua and grease-wood.

N.0°01'W., bet. secs. 14 and 15.


Over rolling land, through scattered desert growth.

- 4.20 Draw, course SE.
- 4.90 Road, bears E. and W.; asc. 41 ft. over SW. slope.
- 9.00 Spur, slopes SE.; continue along E. slope.
- 23.60 Draw, course E.
- 25.00 Draw, course SW.
- 28.80 Same draw, course SE.; asc. 83 ft. over SW. slope.
- 37.90 Spur, slopes SE.
- 40.00 Set an iron post, 3 ft. long, 1 in. diam., 16 ins. in the ground to bedrock, with a limestone, 8x4x4 ins. mkd. X, deposited at the base, and in a mound of stone to top, for $\frac{1}{4}$ sec. cor. with brass cap mkd.



Descend 28 ft. over NE. slope.

- 53.90 Center of draw, 50 lks. wide, course SE.; asc. 90 ft. over SW. slope.
- 70.00 Spur, slopes SE.; desc. 20 ft. over NE. slope.
- 80.00 Set an iron post, 3 ft. long, 2 ins. diam., 16 ins. in the ground to bedrock, with a limestone, 12x10x10 ins. mkd. X, deposited at the base, and in a mound of stone to top, for cor. of secs. 10, 11, 14, and 15, with brass cap mkd.



Land, rolling.
 Soil, sandy; 3rd rate.
 Timber, none; undergrowth, cactus, joshua and sage brush.

Chains. East on a random line bet. secs. 11 and 14.

40.00 Set temp. $\frac{1}{4}$ sec. cor.

80.06 Intersect N. and S. line at the cor. of secs. 11, 12, 13, and 14.

Thence

West on a true line bet. secs. 11 and 14.

Over mountainous land, through scattered desert growth.

13.26 Cedar Wash, 200 lks. wide, course SE.; asc. 274 ft. over NE. slope.

40.03 Set an iron post, 3 ft. long, 1 in. diam., 20 ins. in the ground to bedrock, with a limestone, 8x4x4 ins. mkd. X, deposited at the base, and in a mound of stone to top, for $\frac{1}{4}$ sec. cor. with brass cap mkd.

$\frac{1}{4}$ S 11
S 14
1932

Ascend 21 ft. over NE. slope.

43.00 Spur, slopes SE.; desc. 29 ft. over SW. slope.

45.00 Draw, course SE.; asc. 33 ft. over NE. slope.

56.50 Spur, slopes SE.; desc. 74 ft. over SW. slope.

66.03 Draw, course S.; asc. 83 ft. over NE. slope.

72.00 Spur, slopes SE.; desc. 20 ft. over SW. slope.

78.98 Wash, 20 lks. wide, course SE.

80.06 The cor. of secs. 10, 11, 14, and 15.

Land, mountainous.
Soil, rocky; 4th rate.
Timber, none; undergrowth, joshua, cactus, catclaw and greasewood.

N.0°01'W., bet. secs. 10 and 11.

Over rolling land, through scattered desert growth.

Ascend 58 ft. over SW. slope.

13.00 Spur, slopes SE.; desc. 29 ft. over NE. slope.

23.10 Draw, course SE.; asc. 56 ft. over SW. slope.

31.00 Spur, slopes SE.; desc. 23 ft. over NE. slope.

40.00 Set an iron post, 3 ft. long, 1 in. diam., 18 ins. in the ground to bedrock, (in small draw course SE) with a sandstone, 8x8x8 ins. mkd. X, deposited at the base, and in a mound of stone to top, for $\frac{1}{4}$ sec. cor. with brass cap mkd.

Chains.

1/4
S 10 | S 11

1932

Ascend 45 ft. over SW. slope.

52.90 Trail, bears SE. and NW.

58.50 Ridge, bears NW. and SE.; desc. 239 ft. over NE. slope.

76.90 Enter Cedar Wash, course SE.

79.30 Leave same; continue over level land.

80.00 Set an iron post, 3 ft. long, 2 ins. diam., 26 ins. in the ground, for cor. of secs. 2, 3, 10 and 11, with brass cap mkd.

T 36 N R 16 W
S 3 | S 2
S 10 | S 11
1932

raise a mound
of stone, 4 ft. base, 3 ft. high, W. of cor.

Land, rolling.

Soil, sandy; 3rd rate, and rocky; 4th rate.

Timber, none; undergrowth. joshua, cactus and catclaw.

East on a random line bet. secs. 2 and 11.

40.00 Set temp. 1/4 sec. cor.

80.06 Intersect N. and S. line, 9 lks. S. of the cor. of secs. 1, 2, 11, and 12.

Thence

S. 89° 56' W., on a true line bet. secs. 2 and 11.

Over mountainous land, through scattered desert growth.

Ascend 194 ft. over NE. slope.

3.00 Spur, slopes NE.

8.90 Top of red sandstone ledge, 20 ft. high, bears N. and S.

10.00 Sharp spur, slopes SE.; desc. 57 ft. over SW. slope.

17.50 Spur, slopes SW.; continue descending 154 ft. over NW. slope.


32.20 Wash, 30 lks. wide, course SW.; asc. 80 ft. over SE. slope.

38.00 Spur, slopes SW.; desc. 30 ft. over SW. slope.

40.03 Set an iron post, 3 ft. long, 1 in. diam., 18 ins. in the ground to bedrock, with a limestone, 8x8x4 ins. mkd. X, deposited at the base, and in a mound of stone to top, for 1/4 sec. cor. with brass cap mkd.

Chains.	$\frac{1}{4}$ <table style="margin-left: auto; margin-right: auto;"> <tr> <td style="text-align: center;">S</td> <td style="text-align: center;">2</td> </tr> <tr> <td style="text-align: center;">—</td> <td style="text-align: center;">—</td> </tr> <tr> <td style="text-align: center;">S</td> <td style="text-align: center;">11</td> </tr> </table> 1932	S	2	—	—	S	11				
S	2										
—	—										
S	11										
42.40	Head of draw, course S.; asc. 29 ft. over SE. slope.										
46.00	Small spur, slopes SW.; desc. 81 ft. over NW. slope.										
49.00	Wash, 30 lks. wide, course SW.; continue over rolling land.										
80.06	The cor. of secs. 2, 3, 10, and 11. Land, rolling and mountainous. Soil, sandy; 3rd rate, and rocky; 4th rate. Timber, none; undergrowth, cactus, joshua, greasewood and sage brush.										
N.0°01'W., bet. secs. 2 and 3.											
Over mountainous land, through scattered desert growth.											
Ascend 171 ft. over SW. slope.											
8.50	Spur, slopes SE.; desc. 57 ft. over NE. slope.										
20.00	Wash, 20 lks. wide, course SE.; asc. 177 ft. over SW. slope.										
29.00	Head of same wash, course SW.										
35.00	Small knoll, slopes SE. and SW.; descend along gradual N. slope.										
40.00	Set an iron post, 3 ft. long, 1 in. diam., 10 ins. in the ground to bedrock, with a sandstone, 8x6x6 ins. mkd. X, deposited at the base, and in a mound of stone to top, for $\frac{1}{4}$ sec. cor. with brass cap mkd.										
$\frac{1}{4}$ <table style="margin-left: auto; margin-right: auto;"> <tr> <td style="text-align: center;">S</td> <td style="text-align: center;">3</td> <td style="text-align: center;"> </td> <td style="text-align: center;">S</td> <td style="text-align: center;">2</td> </tr> <tr> <td colspan="5" style="text-align: center;">1932</td> </tr> </table>		S	3		S	2	1932				
S	3		S	2							
1932											
Ascend 92 ft. over SW. slope.											
52.00	Spur, slopes SE.; continue along E. slope.										
62.00	Spur, slopes SE. Desc. 22 ft. over NE. slope.										
70.00	Head of draw, course SE.; asc. 34 ft. over SW. slope.										
73.00	Spur, slopes SE.										
78.80	Wash, 20 lks. wide, course SE.										
81.48	Intersect the Ninth Standard Parallel North. Set an iron post, 3 ft. long, 2 ins. diam., 26 ins. in the ground, for closing cor. of secs. 2 and 3, with brass cap mkd.										

Chains.



raise a mound of stone, 4 ft. base, 3 ft. high, S. of cor.

From this point the standard 1/4 sec. cor. of sec. 35 on the S. bdy. of T. 37 N., R. 16 W., heretofore described, bears East, 7.02 chs. dist.

Land, mountainous. Soil, sandy; 3rd rate, and rocky; 4th rate. Timber, none; undergrowth, cactus, joshua, catclaw and greasewood.

From the cor. of secs. 3,4,33, and 34, on the S. bdy. of the Tp.

N.0°02'W., bet. secs. 33 and 34.


Over rolling land, through scattered desert growth.

Ascend 23 ft. over SW. slope.

5.00 Spur, slopes SE.; desc. 7 ft.


11.00 Wash, 5 lks. wide, course SE.

40.00 Set an iron post, 3 ft. long, 1 in. diam., 18 ins. in the ground to bedrock, with a sandstone, 8x6x6 ins. mkd. X, deposited at the base, and in a mound of stone to top, for 1/4 sec. cor. with brass cap mkd.



71.00 Center of wash, 150 lks. wide, course SW.

80.00 Set an iron post, 3 ft. long, 2 ins. diam., 18 ins. in the ground to bedrock, with a limestone, 10x8x8 ins. mkd. X, deposited at the base, and in a mound of stone to top, for cor. of secs. 27,28,33, and 34, with brass cap mkd.



Land, rolling. Soil, sandy; 3rd rate. Timber, none; undergrowth, cactus, joshua, catclaw and greasewood.

Chains.	East on a random line bet. secs. 27 and 34.
40.00	Set temp. $\frac{1}{4}$ sec. cor.
80.00	Intersect N. and S. line, at the cor. of secs. 26, 27, 34, and 35.
	Thence
	West on a true line bet. secs. 27 and 34.
	Over mountainous land, through scattered desert growth.
.70	Wash, 20 lks. wide, course ^{from NW} E.; asc. 101 ft. over NE. slope.
7.00	Spur, slopes N.; ^{desc.} NW. slope.
10.30	Small draw, course NE.; asc. 244 ft. over SE. slope.
15.00	Short spur, slopes NE.; continue ascending.
18.50	Draw, course NE.
22.50	Ridge, bears N. 20° W. and S. 20° E.; desc. 165 ft. over SW. slope.
40.00	True point for $\frac{1}{4}$ sec. cor. falls in wash, 20 lks. wide, course SW.; road in wash bears NE. and SW.
40.10	Set an iron post, 3 ft. long, 1 in. diam., 16 ins. in the ground to bedrock, with a limestone 10x8x8 ins. mkd. X, deposited at the base, and in a mound of stone to top, for witness $\frac{1}{4}$ sec. cor. with brass cap mkd.
	$\frac{1}{4}$ <u>S 27</u> WC S 34 1932
42.50	Wash, 20 lks. wide, course S.; asc. 48 ft. over E. slope.
47.00	Spur, slopes S.; desc. 17 ft. over SW. slope.
49.30	Wash, 20 lks. wide, course S.; asc. 17 ft. over SE. slope.
51.50	Spur, slopes S.; desc. 40 ft. over SW. slope.
55.50	Wash, 10 lks. wide, course SE.; asc. 14 ft.
57.00	Spur, slopes SE.; desc. 12 ft.
60.00	Wash, 20 lks. wide, course SE.
60.10	Road, bears SE. and NW.; asc. 20 ft. over NE. slope.
62.50	Spur, slopes SE.; desc. 12 ft.
64.50	Wash, 20 lks. wide, course SE.; asc. 52 ft. over NE. slope.
71.00	Spur, slopes SE.; desc. 28 ft. over SW. slope.
79.25	Wash, 150 lks. wide, course S.

SUBDIVISION OF T.36 N., R. 16 W.

BOOK 3904

Chains.
80.00

The cor. of secs. 27, 28, 33, and 34.
Land, rolling and mountainous.
Soil, sandy; 3rd rate.
Timber, none; undergrowth, catclaw, cactus and joshua.

N.0°02'W., bet. secs. 27 and 28.

Over rolling land, through scattered desert growth.

5.00 Wash, 150 lks. wide, course SE.; continue along same.


9.00 Leave wash from NW.

15.47 Road to Pakoon, ^{Spring,} bears SE. and NW. to St. Thomas Nevada.

21.90 Same wash, 100 lks. wide, from NW.; asc. 93 ft. over SE. slope.

35.00 Spur, slopes SW.; descend NW slope.

40.00 Set an iron post, 3 ft. long, 1 in. diam., 4 ins. in the ground to bedrock, with a limestone 10x10x8 ins. mkd. X, deposited at the base, and in a mound of stone to top, for 1/4 sec. cor. with brass cap mkd.




47.90 Wash, 10 lks. wide, course SW.

55.05 Wash, 50 lks. wide, course SW.

67.30 Wash, 30 lks. wide, course SE.; asc. 46 ft. over SW. slope.

79.00 Spur, slopes SE.

80.00 Set an iron post, 3 ft. long, 2 ins. diam., 2 ins. in the ground to bedrock, with a sandstone, 12x12x10 ins. mkd. X, deposited at the base, and in a mound of stone to top, for cor. of secs. 21, 22, 27, and 28, with brass cap mkd.



Land, rolling.
Soil, sandy; 3rd rate.
Undergrowth, joshua, cactus, catclaw and greasewood.

East on a random line bet. secs. 22 and 27.

40.00 Set temp. 1/4 sec. cor.

80.02 Intersect N. and S. line, 9 lks. N. of the cor. of secs. 22, 23, 26, and 27.

Thence

Chains.	N.89°56'W., on a true line bet. secs. 22 and 27. Over rolling land, through scattered desert growth.
1.12	Wash, 20 lks. wide, course S.; asc. 34 ft. over NE. slope.
5.50	Spur, slopes SE.
6.52	Road, bears SE. and NW.; desc. 50 ft. over SW. slope.
12.92	Wash, 20 lks. wide, course SE.; asc. 42 ft. over NE. slope.
20.00	Desc. SW slope 17 feet.
29.92	Draw, course SE.; asc. 21 ft. over E. slope.
35.50	Small spur, slopes SE.
38.82	Wash, 20 lks. wide, course SE.
40.01	Set an iron post, 3 ft. long, 1 in. diam., 12 ins. in the ground to bedrock, with a sandstone, 12x8x4 ins. mkd. X, deposited at the base, and in a mound of stone to top, for $\frac{1}{4}$ sec. cor. with brass cap mkd.
	$\frac{1}{4}$ <u>S 22</u> S 27
	1932
	Ascend 90 ft. over NE. slope.
47.00	Spur, slopes SE.; desc. 46 ft. over SW. slope.
56.75	Wash, 30 lks. wide, course SE.; asc. 77 ft. over NE. slope.
67.00	Spur, slopes S.; desc. 17 ft. over SW. slope.
77.72	Wash, course SE.
80.02	The cor. of secs. 21, 22, 27, and 28. Land, rolling, Soil, sandy; 3rd rate. Timber, none; undergrowth, cactus, joshua and greasewood.
	N.0°02'W., bet. secs. 21 and 22. Over rolling land, through scattered desert growth.
8.50	Wash, 10 lks. wide, course SE.; asc. 34 ft. over SW. slope.
15.60	Spur, slopes SE.
29.25	Draw, course SE.; asc. 21 ft.
32.00	Spur, slopes SE.; desc. 28 ft. over NE. slope.
38.00	Wash, 10 lks. wide, course SE.
40.00	Set an iron post, 3 ft. long, 1 in. diam., 12 ins. in the ground to bedrock, with a sandstone 8x6x6 ins. mkd. X, deposited at the base, and in a mound of stone to top, for $\frac{1}{4}$ sec. cor. with brass cap mkd.

SUBDIVISION OF T. 36 N., R. 16 W.

BOOK 3994

Chains.	$\frac{1}{4}$ S 21 S 22 1932 Ascend 38 ft. over SW. slope. 48.00 Spur, slopes SE. 60.00 Drawn course SE.; asc. 29 ft. over SW. slope. 65.00 Low spur, slopes SE.; desc. 37 ft. over NE. slope. 80.00 Set an iron post, 3 ft. long, 2 ins. diam., 20 ins. in the ground to bedrock, with a sandstone 8x8x8 ins. mkd. X, deposited at the base, and in a mound of stone to top, for cor. of secs. 15, 16, 21, and 22, with brass cap mkd. T 36 N R 16 W S 16 S 15 S 21 S 22 1932 Land, rolling. Soil, sandy; 3rd rate. Timber none; undergrowth, joshua, cactus and catclaw.
	S. 89° 56' E., on a random line bet. secs, 15 and 22.
40.00	Set temp. $\frac{1}{4}$ sec. cor.
80.00	Intersect N. and S. line, 9 lks. S. of the cor. of secs. 14, 15, 22, and 23.
	Thence West on a true line bet. secs. 15 and 22. Over rolling land, through scattered desert growth. Ascend 68 ft. over NE. slope.
10.00	Spur, slopes SE;; desc. 34 ft. over NW. slope.
13.90	Draw, course SE.; asc. 20 ft. over E. slope.
30.00	Spur, slopes S.; desc. 40 ft. over W. slope.
35.00	Wash, 30 lks. wide, course S.; asc. 34 ft. over E. slope.
40.00	Set an iron post, 3 ft. long, 1 in. diam., 18 ins. in the ground to bedrock, with a limestone, 12x12x10 ins. mkd. X, deposited at the base, and in a mound of stone to top, for $\frac{1}{4}$ sec. cor. with brass cap mkd. S 15 S 22 1932
41.30	Wash, 15 lks. wide, course S.; asc. 17 ft. over SE. slope.
44.00	Low spur, slopes SE.; desc. 34 ft. over SW. slope.

Chains.	
54.00	Wash, 20 lks. wide, course SE.; asc. 55 ft. over NE. slope.
59.50	Spur, slopes SE.
62.20	Draw, course SE.
75.00	Enter wash, course SE.
79.25	Leave same, from NW.
80.00	The cor. of secs. 15, 16, 21, and 22.
	Land, rolling. Soil, sandy; 3rd rate and rocky; 4th rate. Timber, none; undergrowth, cactus, joshua, catclaw and greasewood.
	N.0°02'W., bet. secs. 15 and 16. Over rolling land, through scattered desert growth.
.10	Wash, 30 lks. wide, course SE.
2.50	Road, bears NW. and SE.; asc. 62 ft. over SW. slope.
8.00	Spur, slopes SE.;
13.00	Draw, course SE. Ascend SW slope.
40.00	Set an iron post, 3 ft. long, 1 in. diam., 18 ins. in the ground to bedrock, with a sandstone, 6x6x6 ins. mkd. X, deposited at the base, and in a mound of stone to top, for $\frac{1}{4}$ sec. cor. with brass cap mkd.
	$\frac{1}{4}$ S 16 S 15 1932
46.90	Descend slight E. slope. Wash, 15 lks. wide, course SE.; asc. 63 ft. over SW. slope.
60.00	Spur, slopes SE.; desc. 46 ft. over NE. slope.
67.10	Wash, 20 lks. wide, course SE.; asc. 50 ft. over SW. slope.
73.00	Spur, slopes SE. ; desc. 34 ft. over NE. slope.
78.95	Wash, 20 lks. wide, course SE.
80.00	Set an iron post, 3 ft. long, 2 ins. diam., 3 ins. in the ground to bedrock, with a limestone, 12 x10x10 ins. mkd. X, deposited at the base, and in a mound of stone to top, for cor. of secs. 9, 10, 15, and 16, with brass cap mkd.
	T 36 N R 16 W S 9 S 10 S 16 S 15 1932
	Land, rolling. Soil, sandy; 3rd rate. Timber, none; undergrowth, cactus, catclaw and joshua.

SUBDIVISION OF T. 36 N., R. 16 W.

BOOK 3994

Chains.	East on a random line bet. secs. 10 and 15.
40.00	Set temp. $\frac{1}{4}$ sec. cor.
80.10	Intersect N. and S. line 5 lks. N. of the cor. of secs. 10, 11, 14 and 15.
	Thence
	N. 89° 58' W., on a true line bet. secs. 10 and 15.
	Over rolling land, through scattered desert growth.
	Ascend 25 ft. over SE. slope.
2.00	Spur, slopes SE.; desc. 58 ft. over SW. slope.
8.50	Large draw, course SE.; asc. 23 ft. over SE. slope.
13.00	Spur, slopes SE.
16.60	Draw, course SE.; asc. 52 ft. over NE. slope.
27.00	Spur, slopes SE.; continue over broken land.
40.05	Set an iron post, 3 ft. long, 1 in. diam., 20 ins. in the ground to bedrock, with a sandstone 12x12x10 ins. mkd. X, deposited at the base, and in a mound of stone to top, for $\frac{1}{4}$ sec. cor. with brass cap mkd.
	$\frac{1}{4}$ <u>S 10</u> S 15 1932
	Ascend 28 ft. over SE. slope.
49.20	Wash, 20 lks. wide, course SE.
55.00	Spur, slopes SE.; desc. 16 ft.
57.00	Spur, slopes SE.; desc. 29 ft. over NW. slope.
68.36	Draw, course SE.; asc. 88 ft. over SE. slope.
73.00	Spur, slopes S.; desc. 23 ft. over SW. slope.
80.10	The cor. of secs. 9, 10, 15, and 16.
	Land, rolling. Soil, gravelly; 3 rd rate. Undergrowth, cactus, joshua and greasewood.
	N. 0° 02' W., bet. secs. 9 and 10.
	Over rolling land, through scattered desert growth.
	Ascend 61 ft. over SW. slope.
7.20	Spur, slopes SE.; desc. 55 ft. over NE. slope.
21.80	Wash, 15 lks. wide, course SE.; asc. 165 ft. over SW. slope.
38.00	Continue along W. slope.
40.00	Set an iron post, 3 ft. long, 1 in. diam., 15 ins. in the ground to bedrock, with a limestone 7x8x11 ins. mkd. X, deposited at the base, and in a mound of stone to top, for $\frac{1}{4}$ sec. cor. with brass cap mkd.

Chains

$$\frac{1}{4}$$

S 9		S 10
1933		

Continue along W. slope.

48.20 Descend 23 ft. over NW. slope.

56.00 Spur, slopes SE.; desc. 30 ft. over NE. slope.

61.80 Wash, 10 lks. wide, course SE.; asc. 116 ft. over SW. slope.

72.00 Spur, slopes SE.; desc. 56 ft. over NE. slope.

80.00 Set an iron post, 3 ft. long, 2 ins. diam., 16 ins. in the ground to bedrock, with a limestone, 14x12x10 ins. mkd. X, deposited at the base, and in a mound of stone to top, for cor. of secs. 3, 4, 9, and 10, with brass cap mkd.

T 36 N R 16 W		
S 4		S 3
S 9		S 10
1933		

Land, rolling.

Soil, sandy; 3rd rate; and rocky 4th rate.

Timber, none; undergrowth, cactus, joshua, catclaw, and greasewood.

S. 89°58'E., on a random line bet. secs. 3 and 10.

40.00 Set temp. $\frac{1}{4}$ sec. cor.

80.10 Intersect N. and S. line, 2 lks. N. of the cor. of secs. 2, 3, 10, and 11.

Thence

N. 89°57'W., on a true line bet. secs. 3 and 10.

Over mountainous land, through scattered desert growth.

5.30 Enter Cedar Canyon, bears SE. and NW.

8.30 Cedar Wash, 200 lks. wide, course SE.

11.90 Leave Cedar Canyon, bears SE. and NW.; asc. 286 ft. over rocky NE. slope.

37.20 Ridge, bears SE. and NW.;

40.05 Set an iron post, 3 ft. long, 1 in. diam., 18 ins. in the ground to bedrock, with a limestone, 12x12x10 ins. mkd. X, deposited at the base, and in a mound of stone to top, for $\frac{1}{4}$ sec. cor. with brass cap mkd.

$\frac{1}{4}$	S 3
	S 10
	1932

Ascend 70 ft. over NE. slope.

47.50 Spur, slopes SE.; desc. 15 ft. over SW. slope.

51.90 Draw, 20 lks. wide, course SE.; asc. 41 ft. over SE.

SUBDIVISION OF T. 36 N., R. 16 W.

BOOK 8894

- Chains slope.
- 57.00 Spur, slopes SE.; desc. 14 ft.
- 61.00 Head of draw, course SE.; asc. 46 ft. over NE. slope.
- 65.00 Spur, slopes SE.; desc. 45 ft. over SW. slope.
- 71.50 Small spur, slopes SE.
- 76.00 Wash, 20 lks. wide, course SE.; asc. 46 ft. over E. slope.
- 80.10 The cor. of secs. 3,4,9, and 10.

Land, mountainous.
 Soil, sandy; 3rd rate; and gravelly; 4th rate.
 Timber, none; undergrowth, cactus, catclaw, joshua and greasewood.

N.0°02'W., bet. secs. 3 and 4.

Over rolling land, through scattered desert growth.
 Along E. slope.

- 9.50 Head of wash, course SE.; asc. 63 ft. over SW. slope.
- 16.60 Ridge bears NE. and SW.; desc. 163 ft. over NW. slope.
- 36.60 Wash, 5 lks. wide, course NE.; asc. 6 ft.
- 39.00 Low spur, slopes NE.
- 40.00 Set an iron post, 3 ft. long, 1 in. diam., 18 ins. in the ground to bedrock, with a limestone, 10x8x6 ins. mkd. X, deposited at the base, and in a mound of stone to top, for $\frac{1}{4}$ sec. cor. with brass cap mkd.

$\frac{1}{4}$
 S 4 | S 3
 1933

Descend 23 ft. over NW. slope.


- 42.05 Wash, 50 lks. wide, course NE.; asc. 14 ft. over SE. slope.
- 47.00 Spur, slopes NE.; desc. 16 ft. over NW. slope.
- 48.00 Wash, 20 lks. wide, course NE.; asc. 16 ft. over SE. slope.
- 55.50 Low spur, slopes NE.; desc. 16 ft.
- 59.60 Wash, 5 lks. wide, course NE.; asc. 34 ft. over SE. slope.
- 63.00 Spur, slopes E.; desc. 3 ft.
- 67.30 Wash, 20 lks. wide, course SE.
- 81.33 Intersect the Ninth Standard Parallel North.

Set an iron post, 3 ft. long, 2 ins. diam., 18 ins. in the ground to bedrock, with a limestone, 10x8x6 ins.

SUBDIVISION OF T. 36 N., R. 16 W.

Chains

mkd. X, deposited at the base, and in a mound of stone to top, for closing cor. of secs. 3 and 4, with brass cap mkd.



From this point the standard $\frac{1}{4}$ sec. cor. of sec. 34. on the S. bdy. of T. 37 N., R. 16 W., heretofore described, bears East, 7.28 chs. dist.

Land, rolling.
Soil, sandy; 3rd rate.
Timber, none; undergrowth, cactus, joshua, catclaw and greasewood.

From the cor. of secs. 4, 5, 32, and 33, on the S. bdy. of the Tp.

N.0°03'W., bet. secs. 32 and 33.


Over rolling land, through scattered desert growth.

Ascend 41 ft. over SW. slope.

3.00 Low spur, slopes SE.; desc. 21 ft. over NE. slope.

17.40 Wash, 15 lks. wide, course SE.; asc. 52 ft. over SW. slope.

40.00 Set an iron post, 3 ft. long, 1 in. diam., 18 ins. in the ground to bedrock, with a limestone 8x8x6 ins. mkd. X, deposited at the base, and in a mound of stone to top, for $\frac{1}{4}$ sec. cor. with brass cap mkd.




50.00 Small wash, course SE.

52.80 Wash, 50 lks. wide, course SE.

72.30 Wash, 20 lks. wide, course SE.

80.00 Set an iron post, 3 ft. long, 2 ins. diam., 18 ins. in the ground to bedrock, with a limestone, 10x8x6 ins. mkd. X, deposited at the base, and in a mound of stone to top, for cor. of secs. 28, 29, 32, and 33, with brass cap mkd.



Land, rolling.
Soil, sandy loam; 2nd rate; and gravelly; 3rd rate.
Timber, none; undergrowth, joshua, cactus, catclaw and greasewood.

SUBDIVISION OF T. 36 N., R. 16 W.

BOOK 3984

Chains East on a random line bet. secs. 28 and 33.

40.00 Set temp. $\frac{1}{4}$ sec. cor.

80.00 Intersect N. and S. line, 12 lks. N. of the cor. of secs. 27, 28, 33, and 34.

Thence

N. $89^{\circ}55'$ W., on a true line bet. secs. 28 and 33.

Over rolling land, through scattered desert growth.

Ascend 70 ft. over E. slope.

6.50 Spur, slopes S.; desc. 20 ft. over SW. slope.

12.00 Spur, slopes S.; desc. 47 ft. over SW. slope.

17.50 Wash, 50 lks. wide, course S.; asc. 29 ft. over SE. slope.

32.00 Spur, slopes SE.

35.77 Wash, 30 lks. wide, course SE; asc. 29 ft. over NE. slope.

40.00 Set an iron post, 3 ft. long, 1 in. diam., 14 ins. in the ground to bedrock, with a limestone, 6x6x4 ins. mkd. X, deposited at the base, and in a mound of stone to top, for $\frac{1}{4}$ sec. cor. with brass cap mkd.

$\frac{1}{4}$ S 28
S 33
1932

Ascend 26 ft. over NE. slope.

42.50 Spur, slopes SE.; desc. 43 ft. over NW. slope.

47.20 Wash, 20 lks. wide, course S.

57.80 Wash, 30 lks. wide, course SE.

66.20 Wash, 15 lks. wide, course SE.

80.00 The cor. of secs. 28, 29, 32, and 33.

Land, rolling.
Soil, sandy; 3rd rate.
Timber, none; undergrowth, cactus, catclaw, joshua and greasewood.

N. $0^{\circ}03'$ W., bet. secs. 28 and 29.

Over rolling land, through scattered desert growth.
Ascend 23 ft. over SW. slope.

20.46 Wash, 20 lks. wide, course SE.; asc. 26 ft. over SW. slope.

39.10 Wash, 30 lks. wide, course SE.

40.00 Set an iron post, 3 ft. long, 1 in. diam., 18 ins. in the ground to bedrock, with a limestone, 10x10x10 ins. mkd. X, deposited at the base, and in a mound of stone to top, for $\frac{1}{4}$ sec. cor. with brass cap mkd.

SUBDIVISION OF T. 36 N., R. 16 W.

Chains

$$\frac{1}{4}$$

S 29	S 28
1932	

Ascend 26 ft. over SW. slope.

55.00 Spur, slopes SE.

60.00 Wash, 5 lks. wide, course SE.; asc. 14 ft. over gradual SW. slope.

78.00 Spur, slopes SE.

80.00 Set an iron post, 3 ft. long, 2 ins. diam., 20 ins. in the ground to bedrock, with a limestone, 10x6x6 ins. mkd. X, deposited at the base, and in a mound of stone to top, for cor. of secs. 20, 21, 28, and 29, with brass cap mkd.

T 36 N R 16 W	
S 20	S 21
S 29	S 28
1932	

Land, rolling.

Soil, sandy; 3rd rate.

Timber, none; undergrowth, cactus, catclaw, joshua and greasewood.

S. 89°55'E., on a random line bet. secs. 21 and 28.

40.00 Set temp. $\frac{1}{4}$ sec. cor.

80.04 Intersect N. and S. line, 7 lks. S. of the cor. of secs. 21, 22, 27, and 28.

Thence

N. 89°58'W., on a true line bet. secs. 21 and 28.

Over rolling land, through scattered desert growth.

7.64 Wash, 50 lks. wide, course SE.; asc. 62 ft. over NE. slope.

15.00 Spur, slopes SE.; desc. 52 ft. over SW. slope.

20.51 Junction of washes, from N. and NW.; course SE.; asc. 68 ft. over NE. slope.

27.50 Spur, slopes SE.; desc. 56 ft. over SW. slope.

31.74 Wash, 20 lks. wide, course SE.; asc. 69 ft. over NE. slope.

40.02 Set an iron post, 3 ft. long, 1 in. diam., 4 ins. in the ground to bedrock, with a sandstone, 6x6x6 ins. mkd. X, deposited at the base, and in a mound of stone to top, for $\frac{1}{4}$ sec. cor. with brass cap mkd.

$\frac{1}{4}$ S 21
S 28
1932

44.04 Draw, course SE.; asc. 8 ft.

SUBDIVISION OF T. 36 N., R. 16 W.

BOOK 3994

- Chains.
- 47.00 Top of ascent; desc. 32 ft. over SW. slope.
- 50.74 Center of wash, 75 lks. wide, course SE.; asc. 32 ft. over NE. slope.
- 57.50 Spur, slopes SE.; desc. 18 ft. over SW. slope.
- 67.94 Wash, 30 lks. wide, course SE.
- 75.14 Road, bears SE. to Pakoon, and NW. to St Thomas Nevada.
- 80.04 The cor. of secs. 20, 21, 28, and 29.

Land, rolling.
 Soil, sandy; 3rd rate.
 Timber, none; undergrowth, cactus, catclaw and joshua.


N.0°03'W., bet. secs. 20 and 21.

Over rolling land, through scattered desert growth.

- 6.10 Road bears SE. to Pakoon, ^{Spring} and NW. to St Thomas Nevada.
 - 11.10 Wash, 30 lks. wide, course SE.; asc. 46 ft. over SW. slope.
 - 18.00 Spur, slopes SE.; continue over nearly level land.
 - 28.40 Draw, 20 lks. wide, course SE.
 - 40.00 Set an iron post, 3 ft. long, 1 in. diam., 20 ins. in the ground to bedrock, with a limestone, 12x10x10 ins. mkd. X, deposited at the base, and in a mound of stone to top, for $\frac{1}{4}$ sec. cor. with brass cap mkd.
- $\frac{1}{4}$
 S 20 | S 21
 1932
- 43.90 Wash, 50 lks. wide, course SE.; asc. 52 ft. over SW. slope.
 - 47.50 Spur, slopes SE.
 - 55.00 Low spur, slopes SE.
 - 58.50 Draw, course SE.; asc. 23 ft. over SW. slope.
 - 62.00 Small spur, slopes SE.
 - 65.76 Wash, 10 lks. wide, course SE.; asc. 40 ft. over SW. slope.
 - 74.50 *Small wash*, course SE.
 - 76.50 Draw, course SE.
 - 80.00 Set an iron post, 3 ft. long, 2 ins. diam., 16 ins. in the ground to bedrock, with a limestone, 12x12x10 ins. mkd. X, deposited at the base, and in a mound of stone to top, for cor. of secs 16, 17, 20, and 21, with brass cap mkd.

SUBDIVISION OF T. 36 N., R. 16 W.

Chains



Land, rolling.
 Soil, sandy; 3rd rate.
 Timber, none; undergrowth, cactus, joshua, catclaw and
 greasewood.

S.89°58'E., on a random line bet. secs. 16 and 21.

40.00 Set temp. 1/4 sec. cor.

80.06 Intersect N. and S. line, 2 lks.S. of the cor.of secs.
 15,16,21,and 22.

Thence

N.89°59'W., on a true line bet. secs. 16 and 21.

Over rolling land, through scattered desert growth.

Ascend 29 ft. over NE. slope.


7.00 Small spur, slopes NE.; desc. 17 ft. over NW. slope.

10.06 Draw, 30 lks. wide, course NE.; asc. 57 ft. over NE.

30.00 Spur, slopes SE.; desc. 46 ft. over SW. slope.

39.76 Wash, 30 lks. wide, course S.

40.03 Set an iron post, 3 ft. long, 1 in. diam., 6 ins. in
 the ground to bedrock, with a limestone, 8x8x6 ins.
 mkd. X, deposited at the base, and in a mound of stone
 to top, for 1/4 sec. cor. with brass cap mkd.



Ascend 86 ft. over SE. slope.

50.00 Spur, slopes SE.; continue ascending.

58.00 Spur, slopes S.; continue over broken land.

62.56 Head of draw, course SE.

68.50 Spur, slopes SE.; desc. 7 ft.

76.06 Wash, 40 lks. wide, course SE.; asc. 40 ft. over NE.
 slope.


80.06 The cor. of secs. 16,17,20,and 21.

Land, rolling.
 Soil, sandy; 3rd rate.
 Timber, none; undergrowth, catcts, catclaw, joshua and
 greasewood.


SUBDIVISION OF T. 36 N., R. 16 W.

BOOK 3094

Chains. N.0°03'W., bet. secs. 16 and 17.
 Over rolling land, through scattered desert growth.
 7.40 Wash, 20 lks. wide, course SE.; asc. 47 ft. over SW. slope.
 13.00 Spur, slopes SE.; desc. 23 ft. over NE. slope.
 23.60 Draw, course SE.; asc. 86 ft. over SW. slope.
 35.00 Spur, slopes SE.; desc. 10 ft. along NE. slope.
 40.00 Set an iron post, 3 ft. long, 1 in. diam. & 8 ins. in the ground to bedrock, with a sandstone, 10x10x8 ins. mkd. X, deposited at the base, and in a mound of stone to top, for 1/4 sec. cor. with brass cap mkd.



43.50 Draw, course SE.; asc. 29 ft. over SW. slope.
 46.00 Spur, slopes SE.; desc. 17 ft. over NE. slope.
 51.70 Draw, course SE.; continue over broken land.
 54.00 Low spur, slopes SE.
 56.20 Draw, course SE.; asc. 29 ft. over SW. slope.
 62.00 Spur, slopes SE.; desc. 18 ft. over NE. slope.
 67.10 Draw, 20 lks. wide, course SE.; asc. 23 ft. over SW. slope.
 73.50 Spur, slopes SE.; desc. 48 ft. over NE. slope.
 75.23 Wash, 50 lks. wide, course SE.
 80.00 Set an iron post, 3 ft. long, 2 ins. diam., 12 ins. in the ground to bedrock, with a limestone, 8x8x6 ins. mkd. X, deposited at the base, and in a mound of stone to top, for cor. of secs. 8,9,16, and 17. with brass cap mkd.



Land, rolling.
 Soil, sandy; 3rd rate.
 Timber, none; undergrowth, cactus, joshua, catclaw and greasewood.

S.89°59'E., on a random line bet. secs. 9 and 16.
 40.00 Set temp. 1/4 sec. cor.
 80.08 Intersect N. and S. line, 2 lks. N. of the cor. of secs. 9,10,15, and 16.
 Thence

Chains N.89°58'W., on a true line bet. secs. 9 and 16.

Over rolling land, through scattered desert growth.

Descend 12 ft. over SW. slope.

.90 Wash, 10 lks. wide, course SE.; asc. 97 ft. over NE. slope.

9.00 Spur, slopes SE.; desc. 92 ft. over SW. slope.

20.00 Small spur, slopes SW.

25.00 Wash, 20 lks. wide, course SW.; asc. 17 ft. over SE. slope.

28.00 Spur, slopes SE.; desc. SW. slope.

32.60 Draw, course SE.; asc. 57 ft. over NE. slope.

40.04 Set an iron post, 3 ft. long, 1 in. diam., 12 ins. in the ground to bedrock, with a limestone 10x8x8 ins. mkd. X, deposited at the base, and in a mound of stone to top, for $\frac{1}{4}$ sec. cor. with brass cap mkd.

$\frac{1}{4}$ S 9
S 16
1932

Ascend 96 ft. over NE. slopes

45.50 Spur, slopes SE.; desc. 55 ft. over SW. slope.

52.20 Wash, 10 lks. wide, course S.; asc. 29 ft. over SE. slope.

55.00 Spur, slopes S.; desc. 21 ft. over SW. slope.

62.00 Draw, 200 lks. wide, course SE.; asc. 68 ft. over NE. slope.

72.00 Spur, slopes SE.; desc. 29 ft. over SW. slope.

80.08 The cor. of secs. 8, 9, 16, and 17.

Land, rolling.

Soil, sandy; 3rd rate.

Timber, none; undergrowth, cactus, catclaw, joshua and greasewood.

N.0°03'W., bet. secs. 8 and 9.

Over rolling land, through scattered desert growth.

Ascend 159 ft. over SW. slope.

15.00 Spur, slopes SE.; desc. 64 ft. over NE. slope.

32.76 Head of wash, course SE.; asc. 53 ft. over SW. slope.

40.00 Set an iron post, 3 ft. long, 1 in. diam., 18 ins. in the ground to bedrock, with a limestone 8x8x4 ins. mkd. X, deposited at the base, and in a mound of stone to top, for $\frac{1}{4}$ sec. cor. with brass cap mkd.

Chains.

$\frac{1}{4}$
S 8 | S 9
1933

- 40.50 Ridge, bears NE. and SW.; desc. 120 ft. over NW. slope.
- 48.50 Wash, 5 lks. wide, course NE.; continue descending.
- 50.80 Fence, bears NE. and SW.
- 57.80 Wash, 12 lks. wide, course E.; asc. 14 ft. over S. slope.
- 60.00 Continue along top of spur, slopes E.
- 65.10 Leave same.; desc. 20 ft. over N. slope.
- 68.20 Wash, 10 lks. wide, course E.
- 71.80 Road, bears SE. and W.
- 77.70 Road, bears NE. and SW.
- 79.50 Wash, 20 lks. wide, course NE.
- 80.00 Set an iron post, 3 ft. long, 2 ins. diam., 26 ins. in the ground, for cor. of secs. 4, 5, 8, and 9, with brass cap mkd.

T 36 N R 16 W
S 5 | S 4
S 8 | S 9
1933

raise a mound
of stone, 4 ft. base, 3 ft. high, W. of cor.

Land, rolling.
Soil, sandy; 3rd rate.
Timber, none; undergrowth, cactus, catclaw, joshua and greasewood.

- S. 89° 58' E., on a random line bet. secs. 4 and 9.
- 40.00 Set temp. $\frac{1}{4}$ sec. cor.
- 80.22 Intersect N. and S. line, 2 lks. S. of the cor. of secs. 3, 4, 9, and 10.
- Thence
- N. 89° 59' W., on a true line bet. secs. 4 and 9.
- Over rolling land, through scattered desert growth.
- Ascend 102 ft. over NE. slope.
- 6.50 Ridge, bears NE. and SW.; desc. 196 ft. over NW. slope.
- 29.00 Wash, 10 lks. wide, course SW.; asc. 29 ft. over SE. slope.
- 38.00 Spur, slopes S.; desc. 21 ft. over W. slope.
- 40.11 Set an iron post, 3 ft. long, 1 in. diam., 16 ins. in the ground to bedrock, with a sandstone, 6x6x8 ins.

SUBDIVISION OF T. 36 N., R. 16 W.

Chains	<p>mkd. X, deposited at the base, and in a mound of stone to top, for $\frac{1}{4}$ sec. cor. with brass cap mkd.</p> <p style="text-align: center;"> $\frac{1}{4}$ <u>S 4</u> S 9 1933 </p> <p>Descend 27 ft. over NW. slope.</p> <p>43.00 Fence, bears NE. and SW.</p> <p>43.90 Wash, 20 lks wide, course NW.</p> <p>52.70 Enter cultivated land, bears N. and S.</p> <p>66.00 Leave same, bears N. and S.</p> <p>67.80 Fence, bears N. and S. ; asc. 23 ft. over E. slope.</p> <p>74.00 Spur, slopes NE.; continue over rolling land.</p> <p>76.70 Road, bears NE. and SW.</p> <p>78.70 Wash, 15 lks. wide, course NE.</p> <p>80.22 The cor. of secs. 4, 5, 8, and 9.</p> <p>Land, rolling. Soil, sandy loam; 1st rate and sandy; 3rd rate. Timber, none; undergrowth, joshua, cactus, catclaw and greasewood.</p>
	<p>N.0°03'W., bet. secs. 4 and 5.</p> <p>Over rolling land, through scattered desert growth.</p> <p>Ascend 28 ft. over broken SE. slope.</p> <p>4.98 Wash, 5 lks. wide, course SE.</p> <p>24.00 Spur, slopes E.; desc. 15 ft. over NE. slope.</p> <p>30.00 Wash, 10 lks. wide, course E.; asc. 15 ft.</p> <p>32.00 Spur, slopes E.; continue along E. slope.</p> <p>40.00 Set an iron post, 3 ft. long, 1 in. diam., 18 ins. in the ground to bedrock, with a limestone, 10x10x8 ins. mkd. X, deposited at the base, and in a mound of stone to top, for $\frac{1}{4}$ sec. cor, with brass cap mkd.</p> <p style="text-align: center;"> $\frac{1}{4}$ S 5 S 4 1933 </p> <p style="text-align: right;">from which</p> <p>A spring 4 ins. wide, (near lone cottonwood tree, 26 ins. diam.) bears N. 54$\frac{1}{2}$°W., 11.05 chs. dist.</p> <p>Descend 55 ft. over NW. slope.</p> <p>45.95 Fence, bears NW. and SE.</p> <p>49.47 Wash, 5 lks. wide, course NE.</p> <p>61.55 Wash, 50 lks. wide, course E.; asc. 12 ft. over gradual S. slope.</p>

Chains.
81.47

Intersect the Ninth Standard Parallel North.

Set an iron post, 3 ft. long, 2 ins. diam.; 18 ins. in the ground to bedrock, with a limestone, 8 x 6 x 6 ins. mkd. X, deposited at the base; and in a mound of stone to top, for closing cor. of secs. 4 and 5, with brass cap mkd.

T 37 N R 16 W	
S 33	
S 5	S 4
C	C
T 36 N R 16 W	
1933	

From this point the standard $\frac{1}{4}$ sec. cor. of sec. 33, on the S. bdy. of T. 37 N., R. 16 W., heretofore described, bears East, 7.53 chs. dist.

Land, rolling.

Soil, sandy loam; 1st rate; and sandy; 3rd rate.

Timber, none; undergrowth, catclaw, cactus and greasewood.

From the cor. of secs. 5, 6, 31, and 32 on the S. bdy. of the Tp.

N.0°03'W., bet. secs. 31 and 32.

Over rolling land, through scattered desert growth.

Ascend 58 ft. over SW. slope.

5.00 Spur, slopes SE.; desc. 11 ft.

16.00 Draw, course SE.

17.80 Wash, 35 lks. wide, course SE.; asc. 23 ft. over SE. slope.

25.00 Spur, slopes SE.; desc. 51 ft. over NW. slope.

40.00 Set an iron post, 3 ft. long, 1 in. diam., 12 ins. in the ground to bedrock, with a limestone; 8x8x8 ins. mkd. X, deposited at the base, and in a mound of stone to top, for $\frac{1}{4}$ sec. cor. with brass cap mkd.

$\frac{1}{4}$	
S 31	S 32
1932	

Descend 36 ft. over NW. slope.

42.22 Wash, 30 lks. wide, course E.; asc. 62 ft. over SE. slope.

48.20 Spur, slopes SE.; desc. 26 ft. over NE. slope.

52.43 Wash, 30 lks. wide, course SE.; continue along SW. slope.

55.00 Spur, slopes SE.; desc. 34 ft. over NE. slope.

57.21 Wash, 20 lks. wide, course SE.; asc. 111 ft. over SW. slope.

Chains.	
65.00	Spur, slopes SE.; desc. 30 ft. over NE. slope.
69.60	Draw, course SE.; asc. 98 ft. over SW. slope.
76.00	Spur, slopes SE.
80.00	Set an iron post, 3 ft. long, 2 ins. diam., 12 ins. in the ground to bedrock, with a limestone, 18x14x8 ins. mkd. X, deposited at the base, and in a mound of stone to top, for cor. of secs. 29, 30, 31, and 32, with brass cap mkd.
	T 36 N R 16 W S 30 S 29 S 31 S 32 1932
	Land, rolling. Soil, sandy; 3rd rate. Timber, none; undergrowth, joshua, cactus and greasewood.
	East on a random line bet. secs. 29 and 32.
40.00	Set temp. $\frac{1}{4}$ sec. cor.
79.90	Intersect N. and S. line, 9 lks. N. of the cor. of secs. 28, 29, 32, and 33.
	Thence
	N. 89° 56' W., on a true line bet. secs. 29 and 32.
	Over rolling land through scattered desert growth.
17.50	Wash, 50 lks. wide, course SE.; asc. 44 ft. over NE. slope.
23.00	Spur, slopes SE.; desc. 25 ft. over SW. slope.
32.30	Wash, 30 lks. wide, course SE.
39.95	Set an iron post, 3 ft. long, 1 in. diam., 12 ins. in the ground to bedrock, with a limestone, 10x10x10 ins. mkd. X, deposited at the base, and in a mound of stone to top, for $\frac{1}{4}$ sec. cor. with brass cap mkd.
	$\frac{1}{4}$ S 29 S 32 1932
	Ascend 221 ft. over NE. slope.
62.00	
62.00	Wash, 30 lks. wide, course SE.; continue ascending.
70.00	Spur, slopes SE.; continue ascending.
79.90	The cor. of secs. 29, 30, 31, and 32.
	Land, rolling. Soil, rocky; 4th rate. Timber, none; undergrowth, greasewood and cactus.

Chains. West bet. secs. 30 and 31.
 Over mountainous land, through scattered desert growth.
 Ascend 426 ft, over E. slope.

27.68 Intersect the Arizona and Nevada State Boundary.

Set an iron post, 3 ft. long, 2 ins. diam., on bedrock, with a cross X, mkd. at the base, and in a mound of stone to top, for closing cor. of secs. 30 and 31, with brass cap mkd.

	T 36 N	
NEV	S 30	C
	S 31	C
	R 16 W	

1933

From this point the 336 Mi. Cor. heretofore described bears N.3°24'W., 18.35 chs. dist.

Land, mountainous.
 Soil, rocky; 4th rate.
 Timber, none; undergrowth, greasewood.

From the cor. of secs. 29, 30, 31 and 32.
 N.0°03'W., bet. secs. 29 and 30.
 Over mountainous land, through scattered desert growth.
 Along E. slope.

7.50 Rocky wash, 30 lks. wide, course E.; desc. 75 ft.

25.60 Rocky wash, 30 lks. wide, course SE.

32.00 Spur, slopes E.

37.50 Wash, 30 lks. wide, course SE.

40.00 Set an iron post, 3 ft. long, 1 in. diam., 18 ins. in the ground to bedrock, with a sandstone 10x8x8 ins. mkd. X, deposited at the base, and in a mound of stone to top, for $\frac{1}{4}$ sec. cor. with brass cap mkd.

	$\frac{1}{4}$	
	S 30	S 29

1932

Ascend 16 ft. over SW. slope.

42.00 Spur, slopes SE.; desc. 37 ft. over NE. slope.

55.00 Wash, 50 lks. wide, course SE.; asc. 121 ft. over SW. slope.

65.00 Spur, slopes SE.; desc. 98 ft. over NE. slope.

77.16 Draw, 30 lks. wide, course SE.; asc. 34 ft. over SW. slope.

77.80 Spur, slopes SE.; desc. 18 ft. over NE. slope.

Chains.
80.00

Set an iron post, 3 ft. long, 2 ins. diam., 8 ins. in the ground to bedrock, with a limestone, 10x8x6 ins. mkd. X, deposited at the base, and in a mound of stone to top, for cor. of secs. 19, 20, 29, and 30, with brass cap mkd.

T 36 N R 16 W
S 19 | S 20
S 30 | S 29
1932

Land, mountainous.
Soil, rocky; 4th rate.
Timber, none; undergrowth, cactus, joshua, catclaw and greasewood.

S. 89° 56' E., on a random line bet. secs. 20 and 29.

40.00 Set temp. $\frac{1}{4}$ sec. cor.

80.00 Intersect N. and S. line, 9 lks. S. of the cor. of secs. 20, 21, 28, and 29.

Thence

West on a true line bet. secs. 20 and 29.

Over rolling land, through scattered desert growth.

Ascend 28 ft. over E. slope.

3.50 Spur, slopes SE.; desc. 7 ft.

10.00 Wash, 30 lks. wide, course SE.; asc. 52 ft. over E. slope.

17.50 Flat spur, slopes SE.

25.00 Draw, course SE.; asc. 29 ft. over NE. slope.

30.00 Spur, slopes SE.; desc. 25 ft. over SW. slope.

34.50 Wash, 20 lks. wide, course SE.; asc. 25 ft. over NE. slope.

40.00 Set an iron post, 3 ft. long, 1 in. diam., 20 ins. in the ground to bedrock, (on spur slopes SE) with a sandstone 12x12x10 ins. mkd. X, deposited at the base and in a mound of stone to top, for $\frac{1}{4}$ sec. cor. with brass cap mkd.

$\frac{1}{4}$ S 20
S 29
1932

Descend 17 ft. over SW. slope.

55.90 Wash, 20 lks. wide, course SE.; asc. 173 ft. over NE. slope.


80.00 The cor. of secs. 19, 20, 29, and 30.

Land, rolling.
Soil, rocky; 4th rate.
Timber, none; undergrowth, catclaw, cactus and joshua.

SUBDIVISION OF T. 36 N., R. 16 W.

BOOK 3994


Chains West bet. secs. 19 and 30.
 Over rolling land, through scattered desert growth.
 Ascend 118 ft. over NE. slope.
 10.00 Continue along top of spur, slopes SE.
 14.00 Leave spur; desc. 23 ft. over SW. slope.
 32.60 Wash, 20 lks. wide, course SE.; asc. 21 ft. along wash.
 32.82 Intersect the Arizona and Nevada State Boundary.
 Set an iron post, 3 ft. long, 2 ins. diam., 16 ins. in the ground to bedrock, with a limestone, 10x10x6 ins. mkd. X, deposited at the base, and in a mound of stone to top, for closing cor. of secs. 19 and 30, with brass cap mkd.



From this point the 335 Mi. Cor. heretofore described, bears N.3°45'W., 19.44 chs. dist.

Land, rolling.
 Soil, rocky; 4th rate.
 Timber, none; undergrowth, cactus, catclaw and greasewood.

From the cor. of secs. 19, 20, 29, and 30.
 N.0°03'W., bet. secs. 19 and 20.
 Over rolling land, through scattered desert growth.
 Descend 29 ft. over N. slope.
 6.00 Wash, 30 lks. wide, course NE.
 15.00 Wash, 50 lks. wide, course SE.; asc. 58 ft. over SE. slope.
 30.00 Spur, slopes SE.
 38.50 Draw, course SE. Ascend SW slope.
 40.00 Set an iron post, 3 ft. long, 1 in. diam., 18 ins. in the ground to bedrock, with a limestone, 12x10x10 ins. mkd. X, deposited at the base, and in a mound of stone to top, for 1/4 sec. cor. with brass cap mkd.



On broad spur, slopes SE.
 59.30 Wash, 30 lks. wide, course SE.; asc. 51 ft. over SW. slope.

Chains.
 63.50 Spur, slopes SE.; desc. 12 ft. over NE. slope.
 72.00 Wash, 50 lks. wide, course SE.
 73.00 Road, bears SE. to Pakoon Spring.
 79.10 Draw, course SE.
 80.00 Set an iron post, 3 ft. long, 2 ins. diam., 10 ins. in the ground to bedrock, with a limestone 10x10x10 ins. mkd. X, deposited at the base, and in a mound of stone to top, for cor. of secs. 17,18,19, and 20, with brass cap mkd.

T 36 N R 16 W
 S 18 | S 17
 S 19 | S 20
 1932

Land, rolling.
 Soil, rocky; 4th rate.
 Timber, none; undergrowth, cactus catclaw, joshua and greasewood.

East on a random line, bet. secs. 17 and 20.
 40.00 Set temp. $\frac{1}{4}$ sec. cor.
 79.96 Intersect N. and S. line, 5 lks. N. of the cor. of secs. 16,17,20, and 21.
 Thence
 N.89°58'W., on a true line bet. secs. 17 and 20.
 Over rolling land, through scattered desert growth.
 15.56 Draw, course SE.; asc. 34 ft. over NE. slope.
 24.00 Ridge bears SE. and NW.; desc. 26 ft. over SW. slope.
 35.06 Draw, course SE. ; asc. 29 ft. over SE. slope.
 39.98 Set an iron post, 3 ft. long, 1 in. diam., 18 ins. in the ground to bedrock, with a limestone, 8x8x6 ins. mkd. X, deposited at the base, and in a mound of stone to top, for $\frac{1}{4}$ sec. cor. with brass cap mkd.

$\frac{1}{4}$ S 17
 S 20
 1932

40.50 Spur, slopes SE.; desc. 29 ft. over SW. slope.
 43.46 Wash, 30 lks. wide, course SE.; asc. 69 ft. over NE. slope.
 52.00 Spur, slopes SE.; continue over broken land.
 65.00 Junction of washes, from W. and NW, course SE.; asc. 63 ft. over NE. slope.
 73.20 Road SE to Pakoon Spring and NW to St. Thomas, Nevada.
 77.50 Spur, slopes SE.; desc. 17 ft.
 79.96 The cor. of secs. 17,18,19, and 20.


Chains. Land, rolling.
 Soil, sandy; 3rd rate.
 Timber, none; undergrowth, joshua, cactus and greasewood.

West bet. secs. 18 and 19.

Over rolling land, through scattered desert growth.

- 1.30 Head of draw, course SE.
- 7.90 Road, bears SE. to Pakoon^{Spring} and NW. to St Thomas Nevada.
- 13.10 Sand wash, 670 lks. wide, course SE.; asc. 29 ft. over NE. slope.
- 15.00 Low ridge, bears SE. and NW.; continue ascending 173 ft. over mountainous land.
- 25.00 Spur, slopes SE.; continue ascending.
- 31.50 Wash, 30 lks. wide, course SE.
- 35.00 Spur, slopes SE.
- 35.73 Intersect the Arizona and Nevada State Boundary.

Set an iron post, 3 ft. long, 2 ins. diam., 10 ins. in the ground to bedrock, with a sandstone 12x8x6 ins. mkd. X, deposited at the base, and in a mound of stone to top, for closing cor. of secs. 18 and 19, with brass cap mkd.



From this point the 334 Mi. Cor. heretofore described, bears N.1°28'W., 22.85 chs. dist.

Land, rolling and mountainous.
 Soil, rocky; 4th rate.
 Timber, none; undergrowth, cactus, joshua and greasewood.

From the cor. of secs. 17, 18, 19, and 20.


N.0°03'W., bet. secs. 17 and 18.

Over rolling land, through scattered desert growth.

Ascend 12 ft. over SW. slope.


- 2.00 Small spur, slopes SE.
- 11.60 Draw, course SE.; asc. 17 ft.
- 15.00 Low spur, slopes SE.; desc. 17 ft.
- 16.60 Draw, course SE.
- 23.50 Wash, 50 lks. wide, course SE.; asc. 29 ft. over SW. slope.
- 26.00 Spur, slopes SE.; desc. 52 ft. over NE. slope.

- Chains.
 29.80 Wash, 50 lks. wide, course SE.; asc. 104 ft. over SW. slope.
 32.50 Ridge, bears NW. and SE.; continue along same.
 38.00 Spur, slopes SE.; desc. 21 ft. over NE. slope.
 40.00 Set an iron post, 3 ft. long, 1 in. diam., 24 ins. in the ground for $\frac{1}{4}$ sec. cor. with brass cap mkd.



raise a mound of stone, 4 ft. base, 3 ft. high, W. of cor.

- 41.30 Wash, 20 lks. wide, course SE.; asc. 54 ft. over SW. slope.
 46.00 Spur, slopes SE.; continue along NE. slope.
 48.65 Wash, 5 lks. wide, course SE.; asc. 32 ft. over SW. slope.
 54.00 Spur, slopes SE.; desc. 32 ft. over NE. slope.
 56.80 Wash, 5 lks. wide, course SE.; asc. 95 ft. over SW. slope.
 78.00 Spur, slopes SE.; desc. 29 ft. over NE. slope.
 80.00 Set an iron post, 3 ft. long, 2 ins. diam., 16 ins. in the ground to bedrock, with a limestone, 12x10x8 ins. mkd. X, deposited at the base, and in a mound of stone to top, for cor. of secs. 7, 8, 17, and 18, with brass cap mkd.



Land, rolling.
 Soil, sandy; 3rd rate.
 Timber, none; undergrowth, joshua, cactus and greasewood.

- S.89°58'E., on a random line bet. secs. 8 and 17.
 40.00 Set temp. $\frac{1}{4}$ sec. cor.
 79.68 Intersect N. and S line, 28 lks. S. of the cor. of secs. 8, 9, 16, and 17.
 Thence
 S.89°50'W., on a true line bet. secs. 8 and 17.
 Over rolling land, through scattered desert growth.
 Descend 14 ft. over SW. slope.
 2.40 Wash, 20 lks. wide, course SE.; asc. 68 ft. over NE. slope.

SUBDIVISION OF T. 36 N., R. 16 W.

BOOK 3994

Chains.

- 6.50 Spur, slopes SE.; desc. 17 ft. over SW. slope.
- 13.08 Wash, 20 lks. wide, course SE.; asc. 45 ft. over NE. slope.
- 22.00 Broad spur, slopes SE.; desc. 20 ft. over SW. slope.
- 26.50 Small spur, slopes SE.
- 31.30 Wash, 30 lks. wide, course SE.; asc. 29 ft. over NE. slope.
- 34.00 Spur, slopes SE.; desc. 23 ft. over SW. slope.
- 39.84 Set an iron post, 3 ft. long, 1 in. diam.; 26 ins. in the ground, for $\frac{1}{4}$ sec. cor. with brass cap mkd.

$\frac{1}{4}$ S 8
 S 17
 1932

- 40.20 Wash, 200 lks. wide, course S.; asc. 146 ft. over NE. slope.
- 50.00 Broad spur, slopes SE.; continue ascending.
- 62.00 Spur, slopes SE.; desc. 18 ft. along SW. slope.
- 75.75 Wash, 30 lks. wide, course SE.; asc. 29 ft. over NE. slope.
- 79.68 The cor. of secs. 7, 8, 17, and 18.

Land, rolling.
 Soil, sandy; 3rd rate.
 Timber, none; undergrowth, catclaw, cactus, joshua and greasewood.

West bet. secs. 7 and 18.

Over rolling land, through scattered desert growth.

Ascend 140 ft. over NE. slope.

- 4.60 Continue ascending over SE. slope.
 - 9.90 Road, bears NE. and SW.
 - 19.60 Spur, slopes S.; desc. 30 ft. over SW. slope.
 - 24.87 Wash, 5 lks. wide, course S.
 - 35.57 Intersect the Arizona and Nevada State Boundary.
- Set an iron post, 3 ft. long, 2 ins. diam., 8 ins. in the ground to bedrock, with a limestone 12x10x8 ins. mkd. X, deposited at the base, and in a mound of stone to top, for closing cor. of secs. 7 and 18, with brass cap mkd.

T36 N
 S 7 C

 S 18 C
 R 16 W
 1933

SUBDIVISION OF T. 36 N., R. 16 W.

Chains

From this point the 333 Mi. Cor. heretofore described, bears N.0°49'E., 21.87 chs. dist.

Land, rolling.

Soil, sandy; 3rd rate, and rocky; 4th rate.

Timber, none; undergrowth, joshua, cactus and catclaw.

From the cor. of secs. 7, 8, 17, and 18.

N.0°03'W., bet. secs. 7 and 8.

Over rolling land, through scattered desert hrowth


- .19 Wash, 5 lks. wide, course SE.; asc. 51 ft. over SW. slope.
- 5.00 Top of spur, slopes SE.; continue along top of same.
- 11.40 Leave spur,; desc. 40 ft. over NE. slope.
- 13.50 Wash, 5 lks. wide, course SE.; asc. 77 ft. over SW. slope.
- 17.00 Spur, slopes E.; continue along NE slope of same.
- 31.23 Fence, bears E. and W.
- 32.30 House, bears N.85½°W. 795 lks. dist.; spring bears W. 600 lks. dist.
- 32.40 Wash, 10 lks. wide, course SE.
- 38.90 Wash, 5 lks. wide, course SE.; asc. 28 ft. over SW. slope.
- 40.00 Set an iron post, 3 ft. long, 1 in. diam., 18 ins. in the ground to bedrock, with a limestone, 10x8x8 ins. mkd. X, deposited at the base, and in a mound of stone to top, for ¼ sec. cor. with brass cap mkd.
- ¼
- S 7 | S 8
- 1933
- Ascend 40 ft. over SW. slope.
- 44.00 Spur, slopes SE.; desc. 25 ft. over NE. slope.
- 46.00 Wash, 5 lks. wide, course SE.; reservoir in same bears NW. 1.50 chs. dist., supplied by spring water.
- 47.00 Road, bears NE. and SW.; asc. 33 ft. over N. slope.
- 49.00 Divide, bears E. and W.; desc. 89 ft. over N. slope.
- 64.30 Wash, 10 lks. wide, course E.; asc. 213 ft. over S. slope.
- 78.00 Spur, slopes E.; continue over top of same.
- 80.00 Set an iron post, 3 ft. long, 2 ins. diam., 6 ins. in the ground to bedrock, with a limestone, 12x10x8 ins. mkd. X, deposited at the base, and in a mound of stone to top, for cor. of secs. 5, 6, 7, and 8, with brass cap mkd.

Chains.	<p style="text-align: center;">T 36 N R 16 W S 6 S 5 S 7 S 8 1933</p>
	<p>Land rolling. Soil, sandy; 3rd rate. Timber, none; undergrowth, joshua, cactus and greasewood.</p>
	<p>N.89°50'E., on a random line, bet. secs. 5 and 8.</p>
40.00	Set temp $\frac{1}{4}$ sec. cor:
79.76	Intersect N. and S. line, 9 lks. N. of the cor. of secs. 4,5,8, and 9.
	Thence
	S.89°54'W., on a true line bet. secs. 5 and 8.
	Over rolling land, through scattered desert growth.
28.76	Wash, 10 lks. wide, course SE.; asc. 86 ft. over SE. slope.
33.76	Top of sandstone ledges on rocky spur, slopes S.; desc. 34 ft. over ledges.
39.06	Wash, 15 lks. wide, course SE.
39.88	Set an iron post, 3 ft. long, 1 in. diam., 16 ins. in the ground to bedrock, with a sandstone, 12x4x4 ins. mkd. X, deposited at the base, and in a mound of stone to top, for $\frac{1}{4}$ sec. cor. with brass cap mkd.
	$\frac{1}{4}$ $\frac{S 5}{S 8}$ 1933
	Ascend 156 ft. over gradual E. slope.
68.80	Spur, slopes SE.; desc. 8 ft. over SW. slope.
69.26	Wash, 10 lks. wide, course SE.; asc. 117 ft. over NE. slope.
79.76	The cor. of secs. 5,6,7, and 8.
	<p>Land, rolling. Soil, rocky; 4th rate. Timber, scattered juniper, Undergrowth, joshua, cactus, catclaw and greasewood.</p>
	West bet. secs. 6 and 7.
	Over mountainous land, through scattered timber and desert growth.
	Ascend 58 ft. over SE. slope.
10.50	Spur, slopes SE.; desc. 19 ft. over SW. slope.
14.74	Wash, 10 lks. wide, course S.; asc. 501 ft. over SE. slope.

Chains.
36.07

Intersect the Arizona and Nevada State Boundary.

Set an iron post, 3 ft. long, 2 ins. diam., 16 ins. in the ground to bedrock, with a limestone, 10x8x6 ins. mkd. X, deposited at the base, and in a mound of stone to top, for closing cor. of secs. 6 and 7, with brass cap mkd.



From this point the the ⁺⁵⁵331 Mi. Cor. heretofore described, bears N.0°51'W., 46.09 chs. dist.


Land, mountainous.
Soil, rocky; 4th rate.
Timber, scattered juniper.
Undergrowth, greasewood.

From the cor. of secs. 5, 6, 7, and 8.

N.0°03'W., bet. secs. 5 and 6.

Over mountainous land, through scattered timber and undergrowth.

- 2.20 Descend 87 ft. over NE. slope.
- 6.60 Wash, 20 lks. wide, course SE.; asc. 120 ft. over SW. slope.
- 15.00 Spur, slopes E.; desc. 62 ft. over N. slope.
- 19.30 Wash, 5 lks. wide, course SE.; asc. 62 ft. over SE. slope.
- 25.00 Spur, slopes SE.; desc. 32 ft. over NE. slope.
- 27.20 Wash, 10 lks. wide, course SE.; asc. 154 ft. over SW. slope.
- 38.00 Spur, slopes SE.; desc. 11 ft. over NE. slope.
- 40.00 Set an iron post, 3 ft. long, 1 in. diam., 12 ins. in the ground to bedrock, with a limestone, 14x12x10 ins. mkd. X, deposited at the base, and in a mound of stone to top, for 1/4 sec. cor. with brass cap mkd.



Descend 9 ft. over NE. slope.

- 42.60 Wash, 5 lks. wide, course SE.; asc. 66 ft. over SW. slope.
- 48.50 Spur, slopes SE.; desc. 55 ft. over NE. slope.
- 56.70 Wash, 20 lks. wide, course SE.; asc. 77 ft. over SW. slope.
- 64.50 Spur, slopes E.; desc. 281 ft. over NW. slope.

SUBDIVISION OF T. 36 N., R. 16 W.

BOOK 3994

Chains.
79.28

Wash, 10 lks. wide, course NE.; asc. 19 ft. over a SE. slope.

81.39

Intersect the Ninth Standard Parallel North.

Set an iron post, 3 ft. long, 2 ins. diam., 18 ins. in the ground to bedrock, with a limestone, 12x8x4 ins. mkd. X, deposited at the base, and in a mound of stone to top, for closing cor. of secs. 5 and 6, with brass cap mkd.

T 37 N R 16 W
 S 32
 S 6 | S 5
 C | C
 T 36 N R 16 W
 1933

From this point the standard $\frac{1}{4}$ sec. cor. of sec. 32, on the S. bdy. of T. 37 N., R. 16 W., heretofore described, bears East, 7.30 chs. dist.

Land, mountainous.
 Soil, rocky; 4th rate.
 Timber, scattered pinyon and juniper; undergrowth, cat-claw, and greasewood.

At a point N.3°24'W., 21.85 chs., from the 337 + 10.00 chs. Mile Cor. on the Arizona and Nevada State Boundary, heretofore described, midway in latitude bet. the SW. $\frac{1}{4}$ cor. of sec. 31. and NW

Set an iron post, 3 ft. long, 1 in. diam., 12 ins. in the ground to bedrock, with a limestone, 6x4x2 ins. mkd. X, deposited at the base, and in a mound of stone to top, for $\frac{1}{4}$ sec. cor. of sec. 31, with brass cap mkd.

NEV | $\frac{1}{4}$ S31
 1933

At a point N.3°45'W., 21.60 chs. dist., from the 336 Mile Cor. on the Arizona and Nevada State Boundary heretofore described, midway in latitude bet. the SW. $\frac{1}{4}$ cor. of sec. 30. and NW

Set an iron post, 3 ft. long, 1 in. diam., on solid rock, with a cross X, mkd. at the base, and in a mound of stone to top, for $\frac{1}{4}$ sec. cor. of sec. 30, with brass cap mkd.

NEV | $\frac{1}{4}$ S30
 1930

Chains. At a point N.1°28'W., 20.41 chs. dist., from the 335 Mile Cor. on the Arizona and Nevada State Boundary, heretofore described, midway in latitude bet. the SW. and NW. [✓]cors. of sec. 19, and NW

Set an iron post, 3 ft. long, 1 in. diam., 18 ins. in the ground to bedrock, with a granite stone, 8x6x4 ins. mkd. X, deposited at the base, and in a mound of stone to top, for $\frac{1}{4}$ sec. cor. of sec. 19, with brass cap mkd.

NEV | $\frac{1}{4}$ S19

1933

At a point N.0°49'E., 17.13 chs. dist., from the 334 Mile Cor. on the Arizona and Nevada State Boundary, heretofore described, midway bet. the NW. and SW. cors. of sec. 18.

Set an iron post, 3 ft. long, 1 in. diam., 28 ins. in the ground, for $\frac{1}{4}$ sec. cor. of sec. 18, with brass cap mkd.

NEV | $\frac{1}{4}$ S18

1933

raise a mound of stone, 4 ft. base, 3 ft. high, E. of cor.

At a point N.0°51'W., 18.13 chs. dist., from the 333 Mile Cor. on the Arizona and Nevada State Boundary, heretofore described, midway bet. the NW. and SW. cors. of sec. 7.

Set an iron post, 3 ft. long, 1 in. diam., 28 ins. in the ground, for $\frac{1}{4}$ sec. cor. of sec. 7, with brass cap mkd.

NEV | $\frac{1}{4}$ S7

1933

raise a mound of stone, 4 ft. base, 3 ft. high, E. of cor.

At a point N.0°51' W., 40.00 chs. in latitude from the SW. cor. of sec. 6, on the Arizona and Nevada State Boundary, and S.0°51'E., 6.09 chs. dist. from the 331+55 Mile Cor

Set an iron post, 3 ft. long, 1 in. diam., on bedrock, with a cross X, mkd. at the base, and in a mound of stone to top, for $\frac{1}{4}$ sec. cor. of sec. 6, with brass cap mkd.

NEV | $\frac{1}{4}$ S6

1933

Chains.

FINAL TEST OF SOLAR ATTACHMENT.

Jan. 2, 1933, with instrument No. 16740, used by Benjamin J. Kinsey, U.S. Surveyor, near the $\frac{1}{4}$ sec. cor. of secs. 27 and 34, T. 36 N., R. 16 W., in latitude $36^{\circ}29\frac{1}{2}'$ N., and longitude $114^{\circ}00'49''$ W., I make an hour angle observation of Polaris east of the meridian, making four readings two each with the telescope in direct and reversed positions, marking the mean point in the line thus determined, on a peg driven firmly in the ground 10.00 chs. N. of station.

Mean watch time of observation	6h 25m 44s p.m.
Mean azimuth of Polaris, east	$00^{\circ}20'45''$ ✓
Bearing of point on peg	$N.0^{\circ}20'45''$ E.

Jan 3; on the meridian above described, at 8h 30m/a.m. app.t., I set off $36^{\circ}29\frac{1}{2}'$ N., on the lat. arc; $22^{\circ}46'$ S. on the decl. arc; and orient the instrument with the solar; the line of sight agrees with the meridian established by Polaris observation.

At 3h 30m p.m. app. t., I set off $36^{\circ}29\frac{1}{2}'$ N., on the lat. arc; $22^{\circ}45'$ S. on the decl. arc; and repeat the test of the solar; the line of sight agrees with the meridian established by Polaris observation.

Jan. 3, 1933.

For final test of instrument No. 19423, used by William E. Hiester U.S. Surveyor, and instrument No. 14189 used by Walter H. Good, U.S. Surveyor, see field notes of the resurvey of a portion of the Arizona and Nevada State Boundary, resurveyed under this group.

GENERAL DESCRIPTION.

The land embraced within T. 36 N., R. 16 W., is rolling and mountainous. The soil is sandy; 3rd rate and rocky; 4th rate. There is a scattered growth of pinyon and juniper timber in the extreme NW. portion of the township. The undergrowth consists of cactus, catclaw, joshua and greasewood. There is one settler in the SE $\frac{1}{4}$ of sec. 7 who has small fields in secs. 4 and 9. A small spring is located near the house in sec. 7, and one in sec. 5 near the $\frac{1}{4}$ sec. cor. of secs. 4 and 5. The predominating interest is stock grazing.

CERTIFICATE OF UNITED STATES SURVEYOR

We, Benjamin J. Kinsey, William E. Hiester and Walter H. Good, U. S. Surveyors, hereby certify upon honor that, in pursuance of special instructions received from the District Cadastral Engineer for Arizona

bearing date of the 30th day of June, 1931, we have well, faithfully, and truly in our own proper person, and in strict conformity with said instructions, the Manual of Surveying Instructions, and the laws of the United States, surveyed all those parts or portions of the subdivisional lines, completing the survey of fractional Township 36 North, Range 16 West,

of the Gila and Salt River Meridian, in the State of Arizona, which are represented in the foregoing field notes as having been executed by us, and under our direction; and that all the corners of said survey have been established and perpetuated in strict accordance with the Manual of Surveying Instructions, and the special written instructions of the District Cadastral Engineer for Arizona and in the specific manner described in the field notes, and that the foregoing are the original field notes of such survey.

Benjamin J. Kinsey, U.S. Surveyor, Prescott, Ariz., Sept. 15, 1933.

William E. Hiester, U.S. Surveyor, Glendale, California, August 26, 1933.

Walter H. Good, U.S. Surveyor, Boise, Idaho, Sept. 9, 1933.

APPROVAL

OFFICE OF U. S. SUPERVISOR OF SURVEYS, Denver, Colorado, April 28, 1934.

The foregoing field notes of the survey of the subdivisional lines, completing the survey of fractional Township 36 North, Range 16 West, of the Gila and Salt River Meridian, in the State of Arizona,

executed by

Benjamin J. Kinsey, William E. Hiester and Walter H. Good, U.S. Surveyors,

under his special instructions dated June 30, 1931, having been critically examined, and the necessary corrections and explanations made, the said field notes, and the surveys they describe, are hereby approved.

[Signature] U.S. Supervisor of Surveys.

I certify that the foregoing transcript of the field notes of the above described surveys in, has been correctly copied from the original notes on file in this office.

U. S. Supervisor of Surveys.