

Original.

4-679

BOOK 4013

Book B.

FIELD NOTES

of the

resurvey of a part of the Second Standard Parallel North, through
Range 7 West; and of the resurvey of the East boundary and survey
of the subdivisional lines of Township 9 North, Range 7 West,

4013

Of the Gila and Salt River Base and Meridian,

In the State of Arizona

EXECUTED BY

Theodore Vander Meer, U.S. Transitman

4013

In the capacity of U. S. Surveyor, under Special Instructions dated Sept. 8
1932, issued by the District Cadastral Engineer to govern surveys included in Group
No. 178, which were approved by the Commissioner of the General Land
Office, Sept. 19, 1932, and Assignment Instructions dated January 3, 1933

Survey commenced January 9, 1933

Survey completed January 26, 1933

(A)

BOOK 4013

INDEX DIAGRAM.

Township 9 North, Range 7 West

38	38 5 37	29 4 29	23 3 23	17 2 17	11 1 11	3
36	37 8 35	28 9 28	22 10 22	16 11 16	10 12 10	2
34	35 17 34	27 16 27	21 15 21	15 14 15	9 13 9	2
33	33 20 32	26 21 25	20 22 20	14 23 13	8 24 8	2
31	31 29 30	25 28 24	19 27 18	13 26 12	7 25 6	2
5	30 28 4	24 28 4	18 24 18	12 25 12	6 26 6	2

Resurvey of the E. bdy. of T. 9 N., R. 7 W.

BOOK 4013

The survey of T. 9 N., R. 7 W., was executed with a Buff & Buff light mountain transit, Serial No. 9977, property of the General Land Office. The horizontal circle has a diameter of $4\frac{1}{2}$ ins. and two double verniers opposite each other reading to single minutes; the diameter of the vertical circle is 4 ins., with one double vernier reading to single minutes; the telescope has fixed stadia wires, ratio 1-132, with a focal constant of 1.2 lks. The instrument is equipped with the improved Smith solar attachment, radius of latitude arc $2\frac{1}{2}$ ins., and of declination arc $3\frac{1}{2}$ ins., each with verniers reading to single minutes. The instrument was in good condition and, having been placed in satisfactory adjustment prior to beginning the survey, was approved by the district cadastral engineer for Arizona on Jan. 5, 1933. I examined all the instrumental adjustments before making the field tests hereinafter recorded.

The directions of the lines were determined by solar transit method. The measurements were made on the slope with a Lallie steel tape, 5 chs. in length, graduated every link for the first 100 lks., and the balance at intervals of 10 lks. The tape was tested by comparison with a Lufkin standard steel tape and found correct. The vertical angle of the slope measurements was ascertained with a clinometer in good adjustment; the horizontal equivalents are entered in the field note record.

The data furnished with the special instructions gives the geographic position for the SE. cor. of the Tp. as follows: latitude $34^{\circ}04'11''$ N., longitude $112^{\circ}55'45''$ W. As this has been checked by recent adjacent surveys, no observation for latitude is made.

Jan. 10, 1933, in camp near the $\frac{1}{4}$ sec. cor. of secs. 22 and 23, T. 9 N., R. 7 W., Ariz., at $0^{\text{h}}18^{\text{m}}$ a.m., l.m.t., I observe Polaris at western elongation, making two sights each with the telescope in direct and reversed positions, and mark the mean point in the line thus determined by a tack in a stake driven firmly into the ground about 8 chs. N. After sunrise I lay off the azimuth of Polaris, $1^{\circ}16'00''$ to the E., and mark the meridian thus determined by identifying a point on the Date Creek Mts., about 10 miles N.

Every hour from 8 to 11 a.m. and from 1 to 4 p.m., I make proper settings on the arcs of the solar attachment and ascertain that the resulting orientation of the instrument, when compared with the meridian established by Polaris observation, has a maximum error of less than $1'30''$.

I repeat the tests of the arcs daily by noon observation, and verify the meridional indications at frequent intervals throughout the survey.

Magnetic declination observed in sec. 35 was $15^{\circ}10'E$.

The E. bdy. of T. 9 N., R. 7 W., was surveyed by P. Contzen, U.S.D.S., in 1897. The Second Standard Parallel North, through Range 7 West, was surveyed by A. N. Oliver, U.S. Surveyor, in 1911.

No retracements or resurveys of any part of said lines are of record.

The following notes describe a resurvey of the East boundary and a resurvey of the West three miles of the Second Standard Parallel North, through Range 7 West.

Resurvey of the E. Bdy. of T.9 N., R.7 W.

Chains	From the standard cor. of Ts. 9 N., Rs. 6 and 7 W., North, on a random line bet. secs. 31 and 36.
40.04	Fall 1 lk. E. of the $\frac{1}{4}$ sec. cor. The true course and distance = N.0°01'W., 40.04 chs. From $\frac{1}{4}$ sec. cor. North, on a random line bet. secs. 31 and 36.
40.07	Fall 5 lks. E. of the cor. of secs. 25, 30, 31, and 36. The true course and distance = N.0°04'W., 40.07 chs. From cor. North, on a random line bet. secs. 25 and 30.
40.10	Fall 7 lks. E. of the $\frac{1}{4}$ sec. cor. The true course and distance = N.0°06'W., 40.10 chs. From $\frac{1}{4}$ sec. cor. North, on a random line bet. secs. 25 and 30.
40.04	Fall 4 lks. E. of the cor. of secs. 19, 24, 25 and 30. The true course and distance = N.0°03'W., 40.04 chs. From cor., North, on a random line bet. secs. 19 and 24.
40.05	Fall 4 lks. E. of the $\frac{1}{4}$ sec. cor. The true course and distance = N.0°03'W., 40.05 chs. From $\frac{1}{4}$ sec. cor. North, on a random line bet. secs. 19 and 24.
40.10	Fall 4 lks. E. of the cor. of secs. 13, 18, 19 and 24. The true course and distance = N.0°03'W., 40.10 chs. From cor. North, on a random line bet. secs. 13 and 18.
40.05	Fall 2 lks. W. of the $\frac{1}{4}$ sec. cor. The true course and distance = N.0°02'E., 40.05 chs. From $\frac{1}{4}$ sec. cor. North, on a random line bet. secs. 13 and 18.
30.12	A 4 in. iron post, which is U.S. Bench Mark No. 2783 bears west, 50 lks. dist.
40.05	Fall $\frac{3}{4}$ lks. E. of the cor. of secs. 7, 12, 13 and 18. The true course and distance = N.0°03'W., 40.05 chs. From cor. North, on a random line bet. secs. 7 and 12.

Resurvey of the E. Bdy. of T.9 N.,R.7 W.

BOOK 4018

Chains	
20.65	Center line of county road, under construction, bears N.62°15'E. and S.62°15'W.
40.05	Fall 5 lks. E. of the $\frac{1}{4}$ sec. cor. The true course and distance = N.0°04'W.,40.05 chs. From $\frac{1}{4}$ sec. cor. North, on a random line bet. secs. 7 and 12.
40.03	Fall 2 lks. E. of the cor. of secs. 1, 6, 7, and 12. The true course and distance = N.0°02'W.,40.03 chs. From cor. North, on a random line bet. secs. 1 and 6.
40.02	Fall 3 lks. E. of the $\frac{1}{4}$ sec. cor. The true course and distance = N.0°03'W.,40.02 chs. From $\frac{1}{4}$ sec. cor. North, on a random line bet. secs. 1 and 6.
40.05	Intersect the cor. of Ts. 9 and 10 N.,Rs. 6 and 7 W. The true course and distance = North, 40.05 chs. The foregoing resurvey discloses that the E. bdy. of T.9 N.,R.7 W.,is in substantial agreement with the record for the entire distance. The mean bearing is N.0°02 $\frac{1}{2}$ 'W. All of the $\frac{1}{4}$ sec., sec., and Tp. cors. on this line were found, and in a good state of preservation, conforming to the description given in the official record. No rehabilitation was deemed necessary.
Resurvey of a Portion of the 2nd. Standard Parallel North, thru R.7 W. -----	
	From the standard cor. of secs. 33 and 34, West, on a random line on S. bdy. of sec. 33.
10.35	Intersect the closing cor. of secs. 3 and 4, T.8 N.,R.7 W.
40.09	Intersect the standard $\frac{1}{4}$ sec. cor. of sec. 33.
80.22	Intersect the standard cor. of secs. 32 and 33. Thence West, on a random line on S. bdy. of sec. 32.
40.11	The original point for standard $\frac{1}{4}$ sec. cor. of sec. 32. as determined old pits and mound of earth.
80.23	Intersect the standard cor. of secs. 31 and 32. Thence West, on a random line on S. bdy. of sec. 31.

Resurvey of a Portion of the 2nd. Standard
Parallel North, through R.7 W.

Chains							
9.78	Intersect the closing cor. of secs. 5 and 6, T.8 N., R.7 W.						
40.11	Intersect the standard $\frac{1}{2}$ sec. cor. of sec. 31						
80.19	Intersect the standard cor. of Ts. 9 N., Rs. 7 and 8 W.						
	I return to the standard cor. of secs. 33 and 34, which is an iron post, 3 ins. diam., firmly set, marked and witnessed as described in the official record.						
	Thence						
	West, on a true line on S. bdy. of sec. 33.						
	Over gently rolling land.						
4.80	Wash, 10 lks. wide, course SW.						
10.35	The closing cor. of secs. 3 and 4, of T.8 N., which is an iron post, 2 ins. diam., firmly set, marked and witnessed as described in the official record.						
40.09	The standard $\frac{1}{2}$ sec. cor. of sec. 33, which is an iron post 1 in. diam., firmly set, marked and witnessed as described in the official record.						
49.90	Wash, 4 lks. wide, course SW.						
64.90	Old road, bears N. and S.						
80.00	Set an iron post, 3 ft. long, 2 ins. diam., 27 ins. in the ground for standard cor. of secs. 32 and 33, with brass cap marked						
	<table border="1" style="margin-left: auto; margin-right: auto;"> <tr><td>S</td><td>C</td></tr> <tr><td>T9N</td><td>R7W</td></tr> <tr><td>S 32</td><td>S 33</td></tr> </table>	S	C	T9N	R7W	S 32	S 33
S	C						
T9N	R7W						
S 32	S 33						
	1933						
	dig pits 18 x 18 x 12						
	ins. one each on line N., E., and W. of cor. 3 ft. dist.						
	Land, gently rolling.						
	Soil, sandy loam, 2nd. rate.						
	Timber, none.						
	Undergrowth, mesquite, greasewood, catclaw, and yucca.						
	West, on a true line on S. bdy. of sec. 32.						
	Over gently rolling land.						
.22	The old standard cor. of secs. 32 and 33, which is an iron post, 3 ins. diam., 9 ins. above ground, marked and witnessed as described in the official record.						
	As this cor. now becomes an angle point, and serves only to govern the alinement of the standard parallel, I obliterate the marks referring to sec. 33 on brass cap and mark same A P						
10.22	Proportionate point for Clos. Cor. of secs. 4 and 5, T.8 N. Corner not reestablished.						
15.80	Wash, 10 lks. wide, course SW.						
40.00	Set an iron post, 3 ft. long, 1 in. diam., 27 ins. in the ground for standard $\frac{1}{2}$ sec. cor. with brass cap marked						
	<table border="1" style="margin-left: auto; margin-right: auto;"> <tr><td>S</td><td>C</td></tr> <tr><td>$\frac{1}{2}$ S 32</td><td></td></tr> </table>	S	C	$\frac{1}{2}$ S 32			
S	C						
$\frac{1}{2}$ S 32							
	1933						
	dig pits 18 x 18 x 12						

Resurvey of a Portion of the 2nd. Standard
Parallel North, through R. 7 W.

BOOK 4013

Chains	ins. one each on line E. and W. of cor. 3 ft. dist. of sec. 32
40.33	The original point for standard $\frac{1}{4}$ sec. cor. as determined from old pits and mound of earth. As there is no angle in the standard parallel at this point, it was considered unnecessary to perpetuate same with an iron post.
80.00	Set an iron post, 3 ft. long, 2 ins. diam., 27 ins. in the ground for standard cor. of secs. 31 and 32, with brass cap marked S C T9N R7W S 31 S 32 1933 dig pits 18 x 18 x 12 ins., one each on line N., E., and W. of cor. 3 ft. dist.
	Land, gently rolling. Soil, sandy loam, 2nd. rate. Timber, none. Undergrowth, mesquite, yucca, catclaw and greasewood.
	West, on a true line on S. bdy. of sec. 31. Over nearly level land.
.45	The original standard cor. of secs. 31 and 32, which is an iron post, 3 ins. diam., 9 ins. above ground, marked and witnessed as described in the official record. As this cor. now becomes an angle point, I obliterate the marks referring to sec. 32 and mark A P on brass cap.
10.23	The closing cor. of secs. 5 and 6, of T. 8 N., R. 7 W., which is an iron post, 2 ins. diam., firmly set, marked and witnessed as described in the official record.
20.00	Wash, 10 lks. wide, course SW.
40.00	Set an iron post, 3 ft. long, 1 in. diam., 27 ins. in the ground for $\frac{1}{4}$ sec. cor. with brass cap marked S C $\frac{1}{4}$ S 31 1933 dig pits 18 x 18 x 12 ins. one each on line E. and W. of cor. 3 ft. dist.
40.56	The original $\frac{1}{4}$ sec. cor. of sec. 31, which is an iron post 1 in. diam., 9 ins. above ground, marked and witnessed as described in the official record. As this cor. now becomes an angle point, I change marks on brass cap to read S 31 A P
80.64	The standard cor. of Ts. 9 N., Rs. 7 and 8 W., which is an iron post, 3 ins. diam., firmly set, marked and witnessed as described in the official record. Land, nearly level. Soil, sandy loam, 2nd. rate. Timber, none. Undergrowth, mesquite, yucca, greasewood, and cactus.

Subdivision of T. 9 N., R. 7 W.

Chains	<p>The standard cor. of secs. 35 and 36, on S. bdy. of Tp., is an iron post, 3 ins. diam., 9 ins. above ground, marked and witnessed as described in the official record.</p> <p>Thence,</p> <p>N.0°03'W., bet. secs. 35 and 36.</p> <p>Over broken land, along E. slope.</p> <p>16.50 Gulch, 15 lks. wide, course SE.</p> <p>22.60 Wash, 25 lks. wide, course SE. Asc. 180 ft. over S. slope.</p> <p>40.00 Set an iron post, 3 ft. long, 1 in. diam., 8 ins. in the ground to bed rock, in a mound of stone to top, for $\frac{1}{4}$ sec. cor. with brass cap marked</p> <p style="text-align: center;">$\frac{1}{4}$</p> <p style="text-align: center;">S 35 S 36</p> <p style="text-align: center;">1933</p> <p>No accessories available.</p> <p>Continue ascent 55 ft.</p> <p>43.50 Ridge, bears E. and W. Desc. 270 ft. over N. slope.</p> <p>65.00 Gulch, 10 lks. wide, course NE.</p> <p>70.10 Wash, 20 lks. wide, course NE.</p> <p>80.00 Set an iron post, 3 ft. long, 2 ins. diam., 27 ins. in the ground for cor. of secs. 25, 26, 35 and 36, with brass cap marked</p> <p style="text-align: center;">T9N R7W</p> <p style="text-align: center;">S 26 S 25</p> <p style="text-align: center;">S 35 S 36</p> <p style="text-align: center;">1933</p> <p style="text-align: right;">raise a mound of stone</p> <p>3 ft. base, 2 ft. high W. of cor.</p> <p>Land, broken and rolling. Soil, sandy and rocky, 4th. rate. Timber, none. Undergrowth, palo verde, mesquite, ocotillo, greasewood, and cactus.</p>
40.00	<p>East, on a random line bet. secs. 25 and 36.</p> <p>Set temp. $\frac{1}{4}$ sec. cor.</p>
80.00	<p>Intersect E. bdy. of Tp. 7 lks. S. of the cor. of secs. 25, 30, 31, and 36.</p> <p>Thence</p> <p>S.89°57'W., on a true line bet. secs. 25 and 36.</p> <p>Over nearly level land.</p>
10.10	Road, bears N.10°W. and S.10°E.
33.10	Asc. 60 ft. over gradual NE. slope.
40.00	Set an iron post, 3 ft. long, 1 in. diam., 18 ins. in the

Subdivision of T.9 N., R.7 W.

BOOK 4013

Chains

ground to bed rock, and in a mound of stone to top, for $\frac{1}{4}$ sec. cor. with brass cap marked

$\frac{1}{4}$
S 25
S 36
1933

No accessories available.

Continue ascent 60 ft.

43.00 Rocky spur, slopes N.25°E.

50.20 Spur, slopes N.20°W. Desc. 75 ft. over NW. slope.

65.00 Shallow wash, 60 lks. wide, course NE. Thence over gentle E. slope.

80.00 The cor. of secs. 25, 26, 35, and 36.

Land, rolling on E. portion, broken on W. portion.
Soil, sandy and rocky, 2nd. to 4th. rate.
Timber, none.
Undergrowth, palo verde, mesquite, cactus and yucca.

N.0°03'W., bet. secs. 25 and 26.

Over rolling land.

11.00 Wash, 40 lks. wide, course NE.

34.00 Enter washed land.

40.00 Set an iron post, 3 ft. long, 1 in. diam., 27 ins. in the ground for $\frac{1}{4}$ sec. cor. with brass cap marked

$\frac{1}{4}$
S 26 | S 25
1933

raise a mound of stone,
3 ft. base, 2 ft. high W. of cor.

44.00 Leave washed land.

52.00 Wash, 10 lks. wide, course NE.

67.30 Wash, 15 lks. wide, course NE.

78.70 Wash, 50 lks. wide, 4 ft. deep, course SE.

80.00 Set an iron post, 3 ft. long, 2 ins. diam., 27 ins. in the ground for cor. of secs. 23, 24, 25, and 26, with brass cap marked

T9N R7W
S 23 | S 24
S 26 | S 25
1933

raise a mound of stone,
3 ft. base, 2 ft. high W. of cor.

Land, rolling.
Soil, sandy and rocky.
Timber, none.
Undergrowth, palo verde, mesquite, greasewood and yucca.

Chains	N.89°57'E., on a random line bet. secs. 24 and 25.
40.00	Set temp. $\frac{1}{4}$ sec. cor.
79.90	Intersect the E. bdy. of Tp., 9 lks. S. of the cor. of secs. 19, 24, 25 and 30.
	Thence
	S.89°53'W., on a true line bet. secs. 24 and 25.
	Over slightly rolling land.
4.90	Wash, 60 lks. wide, 5 ft. deep, course S.
39.95	Set an iron post, 3 ft. long, 1 in. diam., 27 ins. in the ground for $\frac{1}{4}$ sec. cor. with brass cap marked
	$\frac{1}{4}$ S 24 <hr/> S 25 1933
	raise a mound of stone, 3 ft. base, 2 ft. high N. of cor.
45.30	Wash, 25 lks. wide, course S.
70.70	Road, bears SE. and NW.
79.90	The cor. of secs. 23, 24, 25 and 26.
	Land, gently rolling. Soil, sandy and gravelly, 2nd. rate. Undergrowth, catclaw, yucca, and mesquite.
	N.0°03'W., bet. secs. 23 and 24.
	Over rolling land, through scattering undergrowth.
5.30	Road, bears SE. and NW.
8.00	Gulch, 10 lks. wide, course SW.
40.00	Set an iron post, 3 ft. long, 1 in. diam., 27 ins. in the ground for $\frac{1}{4}$ sec. cor. with brass cap marked
	$\frac{1}{4}$ S 23 S 24 <hr/> 1933
	raise a mound of stone, 3 ft. base, 2 ft. high W. of cor.
80.00	Set an iron post, 3 ft. long, 2 ins. diam., 27 ins. in the ground for cor. of secs. 13, 14, 23 and 24, with brass cap marked
	T9N R7W S 14 S 13 <hr/> S 23 S 24 1933
	raise a mound of stone, 3 ft. base, 2 ft. high W. of cor.
	Land, slightly rolling. Soil, sand and gravel, 3rd. rate. Undergrowth, cactus, mesquite, yucca, and catclaw.

Subdivision of T.9 N., R.7 W.

BOOK 4018

Chains	N.89°53'E., on a random line bet. secs. 13 and 24.				
40.00	Set temp. $\frac{1}{4}$ sec. cor.				
79.92	Intersect E. bdy. of Tp., 12 lks. S. of the cor. of secs. 13, 18, 19, and 24.				
	Thence				
	S.89°48'W., on a true line bet. secs. 13 and 24.				
	Over level land.				
18.40	Wash, 35 lks. wide, course S.				
39.96	Set an iron post, 3 ft. long, 1 in. diam., 27 ins. in the ground for $\frac{1}{4}$ sec. cor. with brass cap marked				
	$\frac{1}{4}$ <table style="margin-left: auto; margin-right: auto;"> <tr><td>S 13</td></tr> <tr><td>—</td></tr> <tr><td>S 24</td></tr> <tr><td>1933</td></tr> </table>	S 13	—	S 24	1933
S 13					
—					
S 24					
1933					
	dig pits 18 x 18 x 12 ins. one each on line E. and W. of cor. 3 ft. dist.				
79.92	The cor. of secs. 13, 14, 23 and 24.				
	Land, level. Soil, sandy loam, 2nd. rate. Undergrowth, cactus, yucca, and mesquite.				
	N.0°03'W., bet. secs. 13 and 14.				
	Over gently rolling land, through dense undergrowth.				
34.80	Road, bears SE. and NW.				
38.40	Road, bears E. and W.				
40.00	Set an iron post, 3 ft. long, 1 in. diam., 27 ins. in the ground for $\frac{1}{4}$ sec. cor. with brass cap marked				
	$\frac{1}{4}$ <table style="margin-left: auto; margin-right: auto;"> <tr><td>S 14 S 13</td></tr> <tr><td>1933</td></tr> </table>	S 14 S 13	1933		
S 14 S 13					
1933					
	raise a mound of stone, 3 ft. base, 2 ft. high W. of cor.				
41.30	Wash, 15 lks. wide, course SW.				
59.00	County road under construction, bears N.62°15'E. and S.62°15'W.				
80.00	Set an iron post, 3 ft. long, 2 ins. diam., 27 ins. in the ground for cor. of secs. 11, 12, 13 and 14, with brass cap marked				
	<table style="margin-left: auto; margin-right: auto;"> <tr><td>T9N R7W</td></tr> <tr><td>S 11 S 12</td></tr> <tr><td>S 14 S 13</td></tr> <tr><td>1933</td></tr> </table>	T9N R7W	S 11 S 12	S 14 S 13	1933
T9N R7W					
S 11 S 12					
S 14 S 13					
1933					
	raise a mound of stone, 3 ft. base, 2 ft. high W. of cor.				
	Land, gently rolling. Soil, sandy. Undergrowth, cactus, yucca, and mesquite.				

Subdivision of T.9 N., R.7 W.

Chains N.89°48'E., on a random line bet. secs. 12 and 13.
 40.00 Set temp. $\frac{1}{4}$ sec. cor.
 79.94 Intersect E. bdy. of Tp., 5 lks. S. of the cor. of secs. 7, 12, 13 and 18.
 Thence
 S.89°46'W., on a true line bet. secs. 12 and 13.
 Over level land.
 11.80 Drain, 4 lks. wide, course SE.
 18.50 Road, bears N. and S.
 29.30 Road, bears NE. and SW.
 34.20 Wash, 15 lks. wide, course SW.
 38.97 Set an iron post, 3 ft. long, 1 in. diam., 27 ins. in the ground for witness $\frac{1}{4}$ sec. cor. with brass cap marked

S 12
 WC $\frac{1}{4}$ ———
 S 13
 1933

dig pits 18 x 18 x 12
 ins. one each on line E. and W. of cor. 3 ft. dist.

39.80 Center line of county road, under construction, bears N.62°15'E. and S.62°15'W.
 39.97 The true point for $\frac{1}{4}$ sec. cor. falls in road.
 79.94 The cor. of secs. 11, 12, 13 and 14.

Land, level.
 Soil, sandy, 2nd. rate.
 Undergrowth, mesquite and cactus.

N.0°03'W., bet. secs. 11 and 12.

Over gently rolling land.

40.00 Set an iron post, 3 ft. long, 1 in. diam., 27 ins. in the ground for $\frac{1}{4}$ sec. cor. with brass cap marked

$\frac{1}{4}$
 S 11 | S 12
 1933

raise a mound of stone,
 3 ft. base, 2 ft. high W. of cor.

80.00 Set an iron post, 3 ft. long, 2 ins. diam., 27 ins. in the ground for cor. of secs. 1, 2, 11 and 12, with brass cap marked

T9N R7W
 S 2 | S 1
 S 11 | S 12
 1933

raise a mound of stone,
 3 ft. base, 2 ft. high W. of cor.

Land, slightly rolling. Soil, sandy.
 Undergrowth, cactus, mesquite and yucca.

Subdivision of T.9 N., R.7 W.

BOOK 4013

Chains	N.89°46'E., on a random line bet. secs. 1 and 12.
40.00	Set temp. $\frac{1}{4}$ sec. cor.
79.92	Intersect E. bdy. of Tp., 12 lks. S. of the cor. of secs. 1, 6, 7, and 12.
	Thence
	S.89°41'W., on a true line bet. secs. 1 and 12.
	Over gently rolling land.
16.00	Road, bears N. and S.
39.96	Set an iron post, 3 ft. long, 1 in. diam., 27 ins. in the ground for $\frac{1}{4}$ sec. cor. with brass cap marked
	$\frac{1}{4}$ S 1 <hr style="width: 10%; margin: auto;"/> S 12 1933
	raise a mound of stone, 3 ft. base, 2 ft. high N. of cor.
68.20	Drain, course S.
79.92	The cor. of secs. 1, 2, 11, and 12.
	Land, slightly rolling. Soil, sandy. Undergrowth, mesquite, yucca, and cactus.
	N.0°03'W., on a random line bet. secs. 1 and 2.
40.00	Set temp. $\frac{1}{4}$ sec. cor.
80.54	Intersect the N. bdy. of Tp., 43 lks. E. of the cor. of secs. 1, 2, 35 and 36, which is an iron post, 2 ins. diam., 9 ins. above ground, marked and witnessed as described in the official record.
	Thence
	S.0°21'E., on a true line bet. secs. 1 and 2.
	Over nearly level land.
4.89	Main road, bears E. to Congress Junction and W.
40.54	Set an iron post, 3 ft. long, 1 in. diam., 27 ins. in the ground for $\frac{1}{4}$ sec. cor. with brass cap marked
	$\frac{1}{4}$ S 2 S 1 1933
	dig pits 18 x 18 x 12 ins. one each N. and S. of cor. 3 ft. dist.
80.54	The cor. of secs. 1, 2, 11 and 12.
	Land, nearly level. Soil, sandy, 2nd. rate. Undergrowth, cactus and mesquite.

Subdivision of T.9 N., R.7 W.

Chains	<p>The standard cor. of secs. 34 and 35; on S. bdy. of Tp., is an iron post, 3 ins. diam., firmly set, marked and witnessed as described in the official record.</p> <p>Thence</p> <p>N.0°04'W., bet. secs. 34 and 35.</p> <p>Over mountainous land. Asc. 220 ft. over S. slope.</p> <p>3.50 Rocky gulch, course SW. Asc. 220 ft. over S. slope.</p> <p>14.25 Spur, slopes SW.</p> <p>20.10 Gulch, course SW. Asc. 190 ft. over broken SW. slope.</p> <p>25.90 Ridge, bears SE. and NW. Desc. 315 ft. over N. slope.</p> <p>40.00 Set an iron post, 3 ft. long, 1 in. diam., 27 ins. in the ground for $\frac{1}{4}$ sec. cor., with brass cap marked</p> <p style="text-align: center;">$\frac{1}{4}$</p> <p style="text-align: center;">S 34 S 35</p> <p style="text-align: center;">1933</p> <p style="text-align: center;">raise a mound of stone, 3 ft. base, 2 ft. high W. of cor.</p> <p>Continue descent 50 ft. over N. slope to</p> <p>43.20 Gulch, course NE. Along broken E. slope.</p> <p>55.10 Gulch, 15 lks. wide, course S.70°E. Asc. 300 ft. over S. slope.</p> <p>74.00 Ridge, bears E. and W. Asc. 25 ft. to</p> <p>78.80 Rocky spur, slopes NW. Desc. 60 ft. over NW. slope.</p> <p>80.00 Set an iron post, 3 ft. long, 2 ins. diam., on bed rock, in mound of stone, 10 ft. base to top of post, for cor. of secs. 26, 27, 34 and 35, with brass cap marked</p> <p style="text-align: center;">T9N R7W</p> <p style="text-align: center;">S 27 S 26</p> <p style="text-align: center;">S 34 S 35</p> <p style="text-align: center;">1933</p> <p>Land, mountainous. Soil, rocky, 4th. rate. Undergrowth, palo verde, ocotillo, cactus, mesquite, and greasewood.</p>
	<p>East, on a random line bet. secs. 26 and 35.</p> <p>40.00 Set temp. $\frac{1}{4}$ sec. cor.</p> <p>80.40 Intersect the cor. of secs. 25, 26, 35 and 36.</p> <p>Thence</p> <p>West, on a true line bet. secs. 26 and 35.</p> <p>Over broken land.</p> <p>10.00 Wash, 40 lks. wide, course NE.</p> <p>24.90 Gulch, course SE. Asc. 145 ft. over SE. slope.</p>

Subdivision of T.9 N., R.7 W.

BOOK 4013

Chains 40.20	<p>Set an iron post, 3 ft. long, 1 in. diam., 6 ins. in the ground to bed rock, and in a mound of stone to top, for $\frac{1}{4}$ sec. cor. with brass cap marked</p> $\begin{array}{r} S\ 26 \\ \frac{1}{4} \\ \hline S\ 35 \end{array}$ <p>Asc. 110 ft. over broken S. slope.</p>
66.60	Gully, course SE. Asc. 260 ft. over SE. slope.
76.80	Ridge, bears NE. and SW. Desc. 90 ft. over NW. slope.
80.40	The cor. of secs. 26, 27, 34 and 35.
	<p>Land, mountainous. Soil, rocky, 4th. rate. Undergrowth, palo verde, mesquite, catclaw and cactus.</p>
	<p>N.0°04'W., bet. secs. 26 and 27. Over mountainous land. Desc. 190 ft. over NW. slope.</p>
10.20	Gulch, course W. Asc. 80 ft. over SW. slope.
14.20	Spur, slopes NW. Desc. 340 ft. over steep N. slope.
32.80	Foot of steep descent. Desc. gradually.
40.00	<p>Set an iron post, 3 ft. long, 1 in. diam., 20 ins. in the ground to bed rock, and in a mound of stone to top, for $\frac{1}{4}$ sec. cor. with brass cap marked</p> $\begin{array}{r} \frac{1}{4} \\ S\ 27\ S\ 26 \\ \hline 1933 \end{array}$ <p>Continue descent over gradual N. slope.</p>
58.70	Wash, 10 lks. wide, course NE.
75.30	Wash, 10 lks. wide, course NE.
80.00	<p>Set an iron post, 3 ft. long, 2 ins. diam., 27 ins. in the ground for cor. of secs. 22, 23, 26, and 27, with brass cap marked</p> $\begin{array}{r} T9N\ R7W \\ S\ 22\ S\ 23 \\ \hline S\ 27\ S\ 26 \\ \hline 1933 \end{array}$ <p>3 ft. base, 2 ft. high W. of cor. raise a mound of stone,</p>
	<p>Land, mountainous on S. half, rolling, N. half. Soil, rocky, and sandy. Undergrowth, palo verde, ocotillo, cactus, mesquite, and greasewood.</p>
	<p>East, on a random line bet. secs. 23 and 26.</p>
40.00	Set temp. $\frac{1}{4}$ sec. cor.
80.44	Intersect the cor. of secs. 23, 24, 25, and 26.

Chains	Thence					
	West, on a true line bet. secs. 23 and 26. Over nearly level land, through scattering undergrowth.					
1.30	Wash, 50 lks. wide, course SE.					
25.80	Wash, 20 lks. wide, course NE.					
34.60	Wash, 20 lks. wide, course NE.					
40.22	Set an iron post, 3 ft. long, 1 in. diam., 27 ins. in the ground for $\frac{1}{4}$ sec. cor. with brass cap marked					
	$\frac{1}{4}$ <table style="margin-left: auto; margin-right: auto;"> <tr><td>S 23</td></tr> <tr><td>—</td></tr> <tr><td>S 26</td></tr> <tr><td>1933</td></tr> </table>	S 23	—	S 26	1933	
S 23						
—						
S 26						
1933						
	raise a mound of stone, 3 ft. base, 2 ft. high N. of cor.					
55.40	Wash, 30 lks. wide, course NE.					
78.10	Wash, 15 lks. wide, course N.10°E.					
80.44	The cor. of secs. 22, 23, 26 and 27. Land, nearly level. Soil, sandy and gravelly. Undergrowth, mesquite, greasewood, yucca, and cactus.					
	N.0°04'W., bet. secs. 22 and 23. Over gently rolling land.					
6.00	Wash, 20 lks. wide, course NE.					
39.60	Draw, course SE.					
40.00	Set an iron post, 3 ft. long, 1 in. diam., 27 ins. in the ground for $\frac{1}{4}$ sec. cor. with brass cap marked					
	$\frac{1}{4}$ <table style="margin-left: auto; margin-right: auto;"> <tr><td>S 22 S 23</td></tr> <tr><td>—</td></tr> <tr><td>1933</td></tr> </table>	S 22 S 23	—	1933		
S 22 S 23						
—						
1933						
	raise a mound of stone, 3 ft. base, 2 ft. high W. of cor.					
45.00	A dam, 3 ft. high, bears E. and W. 80 lks. then SW.					
45.30	Wash, 30 lks. wide, course SE., overflow from earth reservoir, $1\frac{1}{2}$ chs. wide, formed by the dam.					
50.80	Road, bears NE. and SW.					
63.30	Wash, 15 lks. wide, course SW.					
80.00	Set an iron post, 3 ft. long, 2 ins. diam., 27 ins. in the ground for cor. of secs. 14, 15, 22, and 23, with brass cap marked					
	<table style="margin-left: auto; margin-right: auto;"> <tr><td>T9N R7W</td></tr> <tr><td>S 15 S 14</td></tr> <tr><td>—</td></tr> <tr><td>S 22 S 23</td></tr> <tr><td>1933</td></tr> </table>	T9N R7W	S 15 S 14	—	S 22 S 23	1933
T9N R7W						
S 15 S 14						
—						
S 22 S 23						
1933						
	dig pits 18 x 18 x 12 ins., one in each sec. 3 ft. dist.					

Subdivision of T.9 N., R.7 W.

BOOK 4013

Chains	Land, slightly rolling. Soil, sandy loam, 2nd. rate. Undergrowth, mesquite, yucca, cactus and catclaw.
	East, on a random line bet. secs. 14 and 23.
40.00	Set temp. $\frac{1}{4}$ sec. cor.
80.44	Intersect the cor. of secs. 13, 14, 23 and 24.
	Thence
	West, on a true line bet. secs. 14 and 23.
	Over nearly level land.
40.22	Set an iron post, 3 ft. long, 1 in. diam., 27 ins. in the ground for $\frac{1}{4}$ sec. cor. with brass cap marked
	$\begin{array}{r} S\ 14 \\ \frac{1}{4} \\ \hline S\ 23 \\ 1933 \end{array}$
	ins., one each on line E. and W. of cor. 3 ft. dist. dig pits 18 x 18 x 12
51.44	Drain, 4 lks. wide, course S.
60.44	U.S.G.S. Bench Mark No. 2728, bears N.14°45'E., 15.48 chs.
69.74	Road, bears NE. and SW.
77.40	Wash, 10 lks. wide, course SW.
80.44	The cor. of secs. 14, 15, 22 and 23.
	Land, nearly level. Soil, sandy loma, 2nd. rate. Undergrowth, cactus, yucca, and mesquite.
	N.0°04'W., bet. secs. 14 and 15.
	Over level land.
16.60	County road, under construction, bears N.62°15'E. and S.62°15'W.
40.00	Set an iron post, 3 ft. long, 1 in. diam., 27 ins. in the ground for $\frac{1}{4}$ sec. cor. with brass cap marked
	$\begin{array}{r} \frac{1}{4} \\ S\ 15 \mid S\ 14 \\ 1933 \end{array}$
	ins., one each on line N. and S. of cor. 3 ft. dist. dig pits 18 x 18 x 12
80.00	Set an iron post, 3 ft. long, 2 ins. diam., 27 ins. in the ground, for cor. of secs. 10, 11, 14, and 15, with brass cap marked
	$\begin{array}{r} T9N\ R7W \\ S\ 10 \mid S\ 11 \\ S\ 15 \mid S\ 14 \\ 1933 \end{array}$
	ins., one in each sec. 3 ft. dist. dig pits 18 x 18 x 12

Subdivision of T.9 N., R.7 W.

Chains	Land, level. Soil, sandy loam, 2nd. rate. Undergrowth, mesquite, cactus, yucca, and catclaw.
	East, on a random line bet. secs. 11 and 14.
40.00	Set temp. $\frac{1}{4}$ sec. cor.
80.48	Intersect N. and S. line 5 lks. S. of the cor. of secs. 11, 12, 13, and 14.
	Thence
	S.89°58'W., on a true line bet. secs. 11 and 14.
	Over nearly level land, sloping gently to the south.
40.24	Set an iron post, 3 ft. long, 1 in. diam., 27 ins. in the ground for $\frac{1}{4}$ sec. cor. with brass cap marked
	$\frac{1}{4} \begin{array}{r} \text{S 11} \\ \hline \text{S 14} \\ 1933 \end{array}$
	dig pits 18 x 18 x 12
	ins., one each on line E. and W. of cor. 3 ft. dist.
65.70	Drain, 5 lks. wide, course S.
80.48	The cor. of secs. 10, 11, 14, and 15.
	Land, level. Soil, sandy loam. Undergrowth, cactus and mesquite.
	N.0°04'W., bet. secs. 10 and 11.
	Over level land.
22.60	Wash, 10 lks. wide, course SW.
40.00	Set an iron post, 3 ft. long, 1 in. diam., 27 ins. in the ground for $\frac{1}{4}$ sec. cor. with brass cap marked
	$\frac{1}{4} \begin{array}{r} \text{S 10} \mid \text{S 11} \\ \hline 1933 \end{array}$
	dig pits 18 x 18 x 12
	ins. N. and S. of post, 3 ft. dist.
80.00	Set an iron post, 3 ft. long, 2 ins. diam., 27 ins. in the ground for cor. of secs. 2, 3, 10, and 11, with brass cap marked
	$\begin{array}{r} \text{T9N R7W} \\ \text{S 3} \mid \text{S 2} \\ \hline \text{S 10} \mid \text{S 11} \\ 1933 \end{array}$
	dig pits 18 x 18 x 12
	ins., one in each sec. 3 ft. from cor.
	Land, level. Soil, sandy loam. Undergrowth, mesquite and dense cactus.

Subdivision of T.9 N., R.7 W.

BOOK 4013

- Chains N.89°58'E., on a random line bet. secs. 2 and 11.
- 40.00 Set temp. $\frac{1}{4}$ sec. cor.
- 80.46 Intersect N. and S. line 12 lks. S. of the cor. of secs. 1, 2, 11, and 12.
- Thence
- S.89°53'W., on a true line bet. secs. 2 and 11.
- Over nearly level land, draining S.
- 16.35 Wash, 6 lks. wide, course SE.
- 40.23 Set an iron post, 3 ft. long, 1 in. diam., 27 ins. in the ground for $\frac{1}{4}$ sec. cor. with brass cap marked
- $$\begin{array}{r} S\ 2 \\ \frac{1}{4} \text{---} \\ S\ 11 \\ 1933 \end{array}$$
- ins. E. and W. of post, 3 ft. dist. dig pits 18 x 18 x 12
- 58.26 Enter wash, course S.
- 60.80 Leave wash.
- 80.46 The cor. of secs. 2, 3, 10, and 11.
- Land, level. Soil, sandy and gravelly.
Undergrowth, cactus, mesquite, and palo verde.
-
- N.0°21'W., on a random line bet. secs. 2 and 3.
- 40.00 Set temp. $\frac{1}{4}$ sec. cor.
- 80.63 Intersect N. bdy. of Tp., 19 lks. W. of the cor. of secs. 2, 3, 34, and 35, which is an iron post, 2 ins. diam., 9 ins. above ground, marked and witnessed as described in the official record.
- Thence
- S.0°13'E., on a true line bet. secs. 2 and 3.
- Over level land, through dense undergrowth.
- 4.13 Drain, 5 lks. wide, course SW.
- 40.63 Set an iron post, 3 ft. long, 1 in. diam., 27 ins. in the ground for $\frac{1}{4}$ sec. cor. with brass cap marked
- $$\begin{array}{r} \frac{1}{4} \\ S\ 3 \mid S\ 2 \\ 1933 \end{array}$$
- ins. N. and S. of post, 3 ft. dist. dig pits 18 x 18 x 12
- 63.60 Enter road, bears N.15°E. and S.
- 72.10 Leave road, bears SW.
- 80.63 The cor. of secs. 2, 3, 10; and 11.
- Land, level. Soil, sandy and gravelly.
Undergrowth, cactus, yucca, and mesquite.

Subdivision of T.9 N., R.7 W.

Chains	<p>The standard cor. of secs. 33 and 34, on S. bdy. of Tp., is an iron post, 3 ins. diam., firmly set, marked and witnessed as described in the official record.</p> <p>Thence</p> <p>N.0°04'W., bet. secs. 33 and 34.</p> <p>Over gently rolling land.</p> <p>3.40 Wash, 10 lks. wide, course SW.</p> <p>31.60 Wash, 30 lks. wide, course SW.</p> <p>40.00 Set an iron post, 3 ft. long, 1 in. diam., 27 ins. in the ground for $\frac{1}{4}$ sec. cor. with brass cap marked</p> <p style="text-align: center;">$\frac{1}{4}$ S 33 S 34 1933</p> <p>raise a mound of stone, 3 ft. base, 2 ft. high W. of cor.</p> <p>40.90 Drain, 5 lks. wide, course SW. Asc. 490 ft. over rocky S. slope.</p> <p>62.50 Sharp spur, slopes SE.</p> <p>69.20 Spur, slopes SW. Desc. 134 ft.</p> <p>78.50 Short spur, slopes NW. Desc. NW. slope.</p> <p>80.00 Set an iron post, 3 ft. long, 2 ins. diam., 16 ins. in the ground to bed rock, and in a mound of stone to top, for cor. of secs. 27, 28, 33 and 34, with brass cap marked</p> <p style="text-align: center;">T9N R7W S 28 S 27 S 33 S 34 1933</p> <p>Land, gently rolling on S. half, N. half mountainous. Soil, sandy, gravelly and rocky. Undergrowth, paloverde, yucca, cactus, and greasewood.</p> <hr/> <p>East, on a random line bet. secs. 27 and 34.</p> <p>40.00 Set temp. $\frac{1}{4}$ sec. cor.</p> <p>80.16 Intersect the cor. of secs. 26, 27, 34 and 35.</p> <p>Thence</p> <p>West, on a true line bet. secs. 27 and 34.</p> <p>Over mountainous land. Desc. 280 ft. over NW. slope.</p> <p>10.50 Small gully, course NW.</p> <p>14.00 Small gully, course NW.</p> <p>15.00 Gulch, 15 lks. wide, course NE. Asc. 120 ft. over NE. slope.</p> <p>31.80 Spur, slopes N.20°W. Desc. 40 ft. over NW. slope.</p> <p>35.50 Draw, course N. Asc. 70 ft. over NE. slope.</p>
--------	--

Subdivision of T.9 N., R.7 W.

ECCOK 4016

Chains 40.08	<p>Set an iron post, 3 ft. long, 1 in. diam., 12 ins. in the ground to bed rock, and in a mound of stone to top, for $\frac{1}{4}$ sec. cor. with brass cap marked</p> $\begin{array}{r} \frac{1}{4} \\ \hline S\ 27 \\ S\ 34 \\ 1933 \end{array}$ <p>Asc. 210 ft. over NE. slope.</p>
55.00	Ridge, bears SE. and NW.
56.70	Long spur, bears S.60°W. Desc. 320 ft. over broken NW. slope.
61.05	Cliff, 40 ft. high, bears SE. and NW.
80.16	The cor. of secs. 27, 28, 33 and 34.
	<p>Land, mountainous. Soil, rocky, 4th. rate. Undergrowth, palo verde, cactus, ocotillo, and greasewood.</p>
	<p>N.0°04'W., bet. secs. 27 and 28.</p> <p>Over mountainous land. Desc. 230 ft. over NW. slope.</p>
29.40	Gulch, course W.
32.00	Gulch, course SW. Asc. 20 ft. to
40.00	<p>Set an iron post, 3 ft. long, 1 in. diam., 27 ins. in the ground for $\frac{1}{4}$ sec. cor. with brass cap marked</p> $\begin{array}{r} \frac{1}{4} \\ \hline S\ 28\ \ S\ 27 \\ 1933 \end{array}$ <p>raise a mound of stone, 3 ft. base, 2 ft. high W. of cor.</p> <p>Asc. 45 ft. over S. slope.</p>
42.10	Spur, slopes S.70°W. Over broken W. slope.
67.50	Gulch, course SW. Asc. 300 ft. over steep S. slope.
79.60	Ridge, bears SE. and NW.
80.00	<p>Set an iron post, 3 ft. long, 2 ins. diam., 24 ins. in the ground to bed rock, for cor. of secs. 21, 22, 27 and 28, with brass cap marked</p> $\begin{array}{r} T9N\ R7W \\ \hline S\ 21\ \ S\ 22 \\ S\ 28\ \ S\ 27 \\ 1933 \end{array}$ <p>raise a mound of stone, 3 ft. base, 2 ft. high W. of cor.</p> <p>Land, mountainous and rolling. Soil, rocky, 4th. rate. Undergrowth, mesquite, palo verde, yucca, cactus, and greasewood.</p>

BOOK 4013

Subdivision of T.9 N., R.7 W.

Chains	East, on a random line bet. secs. 22 and 27.
40.00	Set temp. $\frac{1}{4}$ sec. cor.
80.12	Intersect the cor. of secs. 22, 23, 26, and 27.
	Thence
	West, on a true line bet. secs. 22 and 27.
	Over nearly level land.
6.50	Wash, 30 lks. wide, course NE.
32.30	Wash, 12 lks. wide, course NE.
34.70	Old road, bears NE. and SW.
40.06	Set an iron post, 3 ft. long, 1 in. diam., 27 ins. in the ground for $\frac{1}{4}$ sec. cor. with brass cap marked
	$\frac{1}{4}$ S 22 S 27 1933
	dig pits 18 x 18 x 12 ins. E. and W. of post, 3 ft. dist.
	Asc. gentle NE. slope.
63.00	Base of mountains, bears SE. and NW. Asc. 370 ft. over E. slope.
80.12	The cor. of secs. 21, 22, 27 and 28.
	Land, E. 63 chs., nearly level, balance, mountainous. Soil, sandy and rocky, 3rd. and 4th. rates. Undergrowth, palo verde, mesquite, catclaw, and yucca.
	N.0°04'W., bet. secs. 21 and 22.
	Over mountainous land. Desc. 50 ft. along E. slope.
7.30	Spur, slopes NE. Desc. 320 ft. over broken NE. slope.
13.70	Trail, bears NE. and SW., 1:50 chs. to prospect hole.
15.00	Small gulch, course NE.
25.15	Foot of steep descent at base of mountains. Desc. gentle NE. slope.
40.00	Set an iron post, 3 ft. long, 1 in. diam., 27 ins. in the ground for $\frac{1}{4}$ sec. cor. with brass cap marked
	$\frac{1}{4}$ S 21 S 22 1933
	No accessories available.
58.70	Wash, 15 lks. wide, course NE.
60.60	Road, bears NE. and SW.
80.00	Set an iron post, 3 ft. long, 2 ins. diam., 27 ins. in the ground for cor. of secs. 15, 16, 21, and 22, with brass cap marked

Subdivision of T.9 N., R.7 W.

BOOK 4013

Chains

T9N R7W	
S 16	S 15
S 21	S 22
1933	

dig pits 18 x 18 x 12

ins., one in each sec. 3 ft. dist.

Land, mountainous and gently rolling.
Soil, rocky, and sandy, 2nd. and 4th. rates.
Undergrowth, palo verde, greasewood, ocotillo, and mesquite.

East, on a random line bet. secs. 15 and 22.

40.00 Set temp. $\frac{1}{4}$ sec. cor.

80.12 Intersect the cor. of secs. 14, 15, 22, and 23.

Thence

West, on a true line bet. secs. 15 and 22.

Over nearly level land, sloping SW.

12.50 Wash, 6 lks. wide, course S.20°W.

22.40 Wash, 4 lks. wide, course S.20°W.

32.00 County road, under construction, bears NE. and SW.

38.50 Dim road, bears SE. and NW.

40.06 Set an iron post, 3 ft. long, 1 in. diam., 27 ins. in the ground for $\frac{1}{4}$ sec. cor. with brass cap marked

$\frac{1}{4}$	S 15
	S 22
	1933

dig pits 18 x 18 x 12

ins. E. and W. of post, 3 ft. dist.

42.70 Road, bears SE. and NW.

58.20 Wash, 6 lks. wide, course SE. Asc. gentle NE. slope.

59.00 Road, bears SE. and NW.

80.12 The cor. of secs. 15, 16, 21 and 22.

Land, nearly level.
Soil, sandy, and gravelly, 2nd. rate.
Undergrowth, mesquite, caetus, yucca, and catclaw.

N.0°04'W., bet. secs. 15 and 16.

Over gently rolling land, desc. gradual NE. slope.

7.60 Road, bears SE. and NW.

8.50 Draw, course SE. Asc. gentle SE. slope.

40.00 Set an iron post, 3 ft. long, 1 in. diam., 27 ins. in the ground for $\frac{1}{4}$ sec. cor. with brass cap marked

$\frac{1}{4}$	S 16	S 15
	1933	

BOOK 4013


Subdivision of T.9 N., R.7 W.

Chains

Dig pits 18 x 18 x 12 ins., N. and S. of post, 3 ft. dist.

Continue gradual ascent, over general S. slope.

80.00 Set an iron post, 3 ft. long, 2 ins. diam., 27 ins. in the ground for cor. of secs. 9, 10, 15, and 16, with brass cap marked



ins., one in each sec. 3 ft. dist. dig pits 18 x 18 x 12

Land, slightly rolling.
Soil, sandy and gravelly, 2nd. rate.
Undergrowth, mesquite, cactus and catclaw.

East, on a random line bet. secs. 10 and 15.

40.00 Set temp. 1/4 sec. cor.

80.14 Intersect the cor. of secs. 10, 11, 14, and 15.


Thence

West, on a true line bet. secs. 10 and 15.

Over nearly level land.

19.40 Road, bears N. and S.

40.07 Set an iron post, 3 ft. long, 1 in. diam., 27 ins. in the ground for 1/4 sec. cor. with brass cap marked



ins. E. and W. of cor. 3 ft. dist. dig pits 18 x 18 x 12

47.00 Wash, 15 lks. wide, course SE.


80.14 The cor. of secs. 9, 10, 15, and 16.

Land, nearly level.
Soil, sand and gravelly loam.
Undergrowth, mesquite, cactus, and greasewood.

N.0°04'W., bet. secs. 9 and 10.

Over level land, through dense undergrowth.

40.00 Set an iron post, 3 ft. long, 1 in. diam., 27 ins. in the ground for 1/4 sec. cor. with brass cap marked



dig pits 18 x 18 x 12 ins.
N. and S. of cor. 3 ft. dist.

80.00 Set an iron post, 3 ft. long, 2 ins. diam., 27 ins. in the

Subdivision of T.9 N., R.7 W.

BOOK 4013

Chains	<p>ground for cor. of secs. 3, 4, 9, and 10, with brass cap marked</p> <div style="text-align: center;"> <table border="1"> <tr><td>T9N</td><td>R7W</td></tr> <tr><td>S 4</td><td>S 3</td></tr> <tr><td>S 9</td><td>S 10</td></tr> <tr><td colspan="2">1933'</td></tr> </table> </div> <p>dig pits 18 x 18 x 12 ins. one in each sec. 3 ft. from cor.</p> <p>Land, level. Soil, sandy loam. Undergrowth, cactus, joshua, yucca, and mesquite.</p>	T9N	R7W	S 4	S 3	S 9	S 10	1933'	
T9N	R7W								
S 4	S 3								
S 9	S 10								
1933'									
	<p>East, on a random line bet. 3 and 10.</p>								
40.00	Set temp. $\frac{1}{4}$ sec. cor.								
80.12	Intersect N. and S. line 2 lks. S. of the cor. of secs. 2, 3, 10, and 11.								
	Thence								
	S.89°59'W., on a true line bet. secs. 3 and 10.								
	Over nearly level land, through dense undergrowth.								
2.80	Road, bears NE. and SW.								
31.50	Wash, 10 lks. wide, course S.								
40.06	Set an iron post, 3 ft. long, 1 in. diam., 27 ins. in the ground for $\frac{1}{4}$ sec. cor. with brass cap marked								
	<div style="text-align: center;"> <table border="1"> <tr><td>S 3</td></tr> <tr><td>$\frac{1}{4}$</td></tr> <tr><td>S 10</td></tr> <tr><td>1933</td></tr> </table> </div> <p>dig pits 18 x 18 x 12 ins. E. and W. of post, 3 ft. dist.</p>	S 3	$\frac{1}{4}$	S 10	1933				
S 3									
$\frac{1}{4}$									
S 10									
1933									
44.50	Wash, 4 lks. wide, course S.								
80.12	The cor. of secs. 3, 4, 9, and 10.								
	Land, nearly level. Soil, sandy loam, 2nd. rate. Undergrowth, catclaw, mesquite, and yucca.								
	N.0°13'W., on a random line bet. secs. 3 and 4.								
40.00	Set temp. $\frac{1}{4}$ sec. cor.								
80.58	Intersect N. bdy. of Tp., 23 lks. W. of the cor. of secs. 3, 4, 33, and 34, which is an iron post, 2 ins. diam., firmly set, marked and witnessed as described in the official record.								
	Thence								
	S.0°03'E., on a true line bet. secs. 3 and 4.								
	Over level land.								
40.58	Set an iron post, 3 ft. long, 1 in. diam., 27 ins. in the ground for $\frac{1}{4}$ sec. cor., with brass cap marked								

Subdivision of T.9 N., R.7 W.

Chains

$\frac{1}{4}$
S 4 | S 3

1933

dig pits 18 x 18 x 12
ins. N. and S. of cor. 3 ft. dist.

53.50 Drain, 4 lks. wide, course S. 30°W.

80.58 The cor. of secs. 3, 4, 9, and 10.

Land, level.
Soil, sandy loam, 2nd. rate.
Undergrowth, cactus, mesquite, and yucca.

From standard cor. of secs. 32 and 33, on S. bdy. of Tp.,
hereinbefore described,
N. 0°05'W., bet. secs. 32 and 33.

Over slightly rolling land, sloping SW.

40.00 Set an iron post, 3 ft. long, 1 in. diam., 27 ins. in the
ground for $\frac{1}{4}$ sec. cor., with brass cap marked

$\frac{1}{4}$
S 32 | S 33

1933

raise a mound of stone,
3 ft. base, 2 ft. high W. of cor.

58.80 Wash, 3 lks. wide, course SW.

80.00 Set an iron post, 3 ft. long, 2 ins. diam., 27 ins. in the
ground for cor. of secs. 28, 29, 32, and 33, with brass
cap marked

T9N R7W
S 29 | S 28
S 32 | S 33
1933

dig pits 18 x 18 x 12
ins., one in each sec. 3 ft. dist.

Land, slightly rolling.
Soil, sandy loam, 2nd. rate.
Undergrowth, greasewood, yucca, mesquite, palo verde, and
sahauo.

East, on a random line bet. secs. 28 and 33.

40.00 Set temp. $\frac{1}{4}$ sec. cor.

80.12 Intersect the cor. of secs. 27, 28, 33, and 34.

Thence

West, on a true line bet. secs. 28 and 33.

Over mountainous land. Desc. 370 ft. over NW. slope.

25.00 Small drain, course SW., at base of mountains. Desc. over
gradual SW. slope.

40.06 Set an iron post, 3 ft. long, 1 in. diam., 27 ins. in the
ground for $\frac{1}{4}$ sec. cor. with brass cap marked

Subdivision of T.9 N., R.7 W.

BOOK 4013

Chains	$\begin{array}{r} S\ 28 \\ \hline \frac{1}{4} \\ S\ 33 \\ 1933 \end{array}$ <p>raise a mound of stone, 3 ft. base, 2 ft. high N. of cor.</p>
43.10	Wash, 15 lks. wide, course SW.
80.12	The cor. of secs. 28, 29, 32, and 33. Land, E. 25 chs. mountainous, balance, nearly level. Soil, rocky and sandy. Undergrowth, palo verde, ocotillo, cactus, and yucca.
40.00	<p>N.0°05'W., bet. secs. 28 and 29. Over gently rolling land, sloping SW.</p> <p>Set an iron post, 3 ft. long, 1 in. diam., 27 ins. in the ground for $\frac{1}{4}$ sec. cor. with brass cap marked</p> $\begin{array}{r} \frac{1}{4} \\ S\ 29 S\ 28 \\ \hline 1933 \end{array}$ <p>dig pits 18 x 18 x 12 ins. N. and S. of post, 3 ft. dist.</p>
60.30	Wash, 10 lks. wide, course SW.
63.20	Road, bears NE. and SW. Asc. gentle S. slope.
80.00	Set an iron post, 3 ft. long, 2 ins. diam., 27 ins. in the ground for cor. of secs. 20, 21, 28, and 29, with brass cap marked
	$\begin{array}{r} T9N\ R7W \\ S\ 20 S\ 21 \\ \hline S\ 29 S\ 28 \\ 1933 \end{array}$ <p>raise a mound of stone, 3 ft. base, 2 ft. high W. of cor.</p> <p>Land, slightly rolling. Soil, sandy loam. Undergrowth, cactus, yucca, mesquite, and palo verde.</p>
40.00	<p>East, on a random line bet. secs. 21 and 28.</p> <p>Set temp. $\frac{1}{4}$ sec. cor.</p>
80.22	Intersect the cor. of secs. 21, 22, 27, and 28. Thence
	West, on a true line bet. secs. 21 and 28. Over mountainous land. Asc.
.50	Ridge, bears SE. and NW. Continue ascent.
5.90	Spur, slopes SW. Desc. 360 ft. over SW. slope.
23.90	Short spur, slopes SW. Desc. 150 ft. over SW. slope.
36.70	Gulch, course SW. Asc. 50 ft. over E. slope.

Subdivision of T.9 N., R.7 W.

Chains

- 40.11 Set an iron post, 3 ft. long, 1 in. diam., 6 ins. in the ground to bed rock, and in a mound of stone to top, for $\frac{1}{4}$ sec. cor. with brass cap marked
- $\frac{1}{4}$ S 21
S 28
1933
- Asc. 35 ft. over E. slope.
- 40.90 Short spur, slopes S., also outcrop, 25 ft. high. Desc. 90 ft. over W. slope.
- 46.70 Foot of descent, at base of mountains, bears SE. and NW.
- 61.70 Wash, 15 lks. wide, course SW.
- 65.50 Wash, 10 lks. wide, course SW.
- 66.80 Road, bears NE. and SW.
- 80.22 The cor. of secs. 20, 21, 28, and 29.
- Land, mountainous and rolling.
Soil, rocky and sandy.
Undergrowth, cactus, yucca, mesquite, and palo verde.
-
- N.0°05'W., bet. secs. 20 and 21.
- Asc. 70 ft. over broken SE. slope.
- 35.20 Gulch, 10 lks. wide, course SE. Asc. 35 ft. over SW. slope.
- 40.00 Set an iron post, 3 ft. long, 1 in. diam., 6 ins. in the ground to bed rock, and in a mound of stone to top, for $\frac{1}{4}$ sec. cor. with brass cap marked
- $\frac{1}{4}$
S 20 | S 21
1933
- Asc. 155 ft. over SW. slope.
- 52.30 Spur, slopes SE. Desc. 75 ft. over NE. slope.
- 58.30 Gulch, course SE. Asc. 30 ft. over S. slope.
- 60.80 Low ridge, bears E. and W. Desc. 20 ft. over N. slope.
- 62.50 Gulch, course N.60°E. Asc. 95 ft. over SE. slope.
- 69.00 Spur, slopes S.60°E. Desc. 55 ft. over NE. slope.
- 80.00 Set an iron post, 3 ft. long, 2 ins. diam., 15 ins. in the ground to bed rock, and in a mound of stone to top, for cor. of secs. 16, 17, 20, and 21, with brass cap marked
- T9N R7W
S 17 | S 16
S 20 | S 21
1933
- Land, broken. Soil, rocky.
Undergrowth, palo verde, greasewood, and cactus.

Subdivision of T.9 N., R.7 W.

BOOK 4013

Chains	East, on a random line bet. secs. 16 and 21.				
40.00	Set temp. $\frac{1}{4}$ sec. cor.				
80.18	Intersect N. and S. line 2 lks. S. of the cor. of secs. 15, 16, 21, and 22.				
	Thence				
	S. $89^{\circ}59'W.$, on a true line bet. secs. 16 and 21.				
	Over level land.				
6.25	Wire fence, bears N. and S. 1.45 chs. then west.				
40.09	Set an iron post, 3 ft. long, 1 in. diam., 27 ins. in the ground for $\frac{1}{4}$ sec. cor. with brass cap marked				
	$\frac{1}{4}$ <table style="margin-left: auto; margin-right: auto;"> <tr><td>S 16</td></tr> <tr><td>—</td></tr> <tr><td>S 21</td></tr> <tr><td>1933</td></tr> </table>	S 16	—	S 21	1933
S 16					
—					
S 21					
1933					
	dig pits 18 x 18 x 12 ins. E. and W. of cor. 3 ft. dist.				
55.30	Gulch, 10 lks. wide, course NE.				
63.50	Wire fence, bears NW. and SE. 1.80 chs. then E.				
70.00	Base of mountains, bears SE. and NW. Asc. 110 ft. over E. slope.				
80.18	The cor. of secs. 16, 17, 20, and 21.				
	Land, level and hilly. Soil, sandy and rocky. Undergrowth, cactus, yucca, and mesquite.				
N. $0^{\circ}05'W.$, bet. secs. 16 and 17.					
	Over mountainous land, desc. 140 ft. over NE. slope.				
17.00	Foot of mountains, bears SE. and NW. Desc. over gradual NE. slope.				
25.00	Fence, bears NE. and SW.				
28.70	Wash, 10 lks. wide, course NE.				
40.00	Set an iron post, 3 ft. long, 1 in. diam., 27 ins. in the ground for $\frac{1}{4}$ sec. cor. with brass cap marked				
	$\frac{1}{4}$ <table style="margin-left: auto; margin-right: auto;"> <tr><td>S 17 S 16</td></tr> <tr><td>1933</td></tr> </table>	S 17 S 16	1933		
S 17 S 16					
1933					
	dig pits 18 x 18 x 12 ins. N. and S. of post, 3 ft. dist.				
51.10	Road, bears SE. and NW.				
53.75	Wash, 10 lks. wide, course N. $70^{\circ}W.$				
63.50	Wash, 10 lks. wide, course S. $60^{\circ}W.$ Asc. gentle S. slope.				
65.00	Earth reservoir, bears W. about 20 chs. dist.				
80.00	Set an iron post, 3 ft. long, 2 ins. diam., 27 ins. in the ground for cor. of secs. 8, 9, 16, and 17, with brass cap marked				

Chains

T9N	R7W
S 8	S 9
S 17	S 16
1933	

raise a mound of stone
and bones, 3 ft. base, 2 ft. high W. of cor.

Land, hilly and nearly level.

Soil, rocky and sandy.

Undergrowth, palo verde, ocotillo, mesquite, yucca, and
cactus.

N.89°59'E., on a random line bet. secs. 9 and 16.

40.00 Set temp. $\frac{1}{4}$ sec. cor.

80.16 Intersect N. and S. line 2 lks. S. of the cor. of secs.
9, 10, 15, and 16.

Thence

S.89°58'W., on a true line bet. secs. 9 and 16.

Over level land, through dense undergrowth.

3.50 Fence, bears S. and N. 1 ch. then west.

40.08 Set an iron post, 3 ft. long, 1 in. diam., 27 ins. in the
ground for $\frac{1}{4}$ sec. cor. with brass cap marked

$\frac{1}{4}$	S 9
	S 16
1933	

ins. E. and W. of cor. 3 ft. dist. dig pits 18 x 18 x 12

80.16 The cor. of secs. 8, 9, 16, and 17.

Land, level.

Soil, sandy loam, 2nd. rate.

Undergrowth, cactus, mesquite, and yucca.

N.0°05'W., bet. secs. 8 and 9.

Over level land, through dense cactus and scattering
other growths.

1.35 Fence, bears E. and W.

40.00 Set an iron post, 3 ft. long, 1 in. diam., 27 ins. in the
ground for $\frac{1}{4}$ sec. cor. with brass cap marked

$\frac{1}{4}$	S 8	S 9
1933		

on line N. and S. of post, 3 ft. dist. dig pits 18 x 18 x 12 ins.

80.00 Set an iron post, 3 ft. long, 2 ins. diam., 27 ins. in
the ground for cor. of secs. 4, 5, 8, and 9, with brass
cap marked

T9N	R7W
S 5	S 4
S 8	S 9
1933	

Subdivision of T.9 N., R.7 W.

BOOK 4013

Chains	<p>dig pits 18 x 18 x 12 ins., one in each sec. 3 ft. from post.</p> <p>Land, level. Soil, sandy loam. Undergrowth, cactus, yucca, and mesquite.</p>
	<p>N.89°58'E., on a random line bet. secs. 4 and 9.</p>
40.00	Set temp. $\frac{1}{4}$ sec. cor.
80.16	Intersect N. and S. line 2 lks. S. of the cor. of secs. 3, 4, 9, and 10.
	Thence
	S.89°57'W., on a true line bet. secs. 4 and 9.
	Over level land.
18.77	Wash, 4 lks. wide, course S.
40.08	Set an iron post, 3 ft. long, 1 in. diam., 27 ins. in the ground for $\frac{1}{4}$ sec. cor. with brass cap marked
	$\begin{array}{r} \frac{1}{4} \\ \hline S 4 \\ S 9 \\ 1933 \end{array}$
	dig pits 18 x 18 x 12 ins. on line E. and W. of post, 3 ft. dist.
57.00	Enter thicket of arrow weeds.
62.00	Leave thicket.
80.16	The cor. of secs. 4, 5, 8, and 9.
	Land, level. Soil, sandy loam. Undergrowth, cactus, mesquite, joshua, and yucca.
	N.0°03'W., on a random line bet. secs. 4 and 5.
40.00	Set temp. $\frac{1}{4}$ sec. cor.
80.50	Intersect N. bdy. of Tp., 30 lks. W. of the cor. of secs. 4, 5, 32, and 33, which is an iron post, 2 ins. diam., 9 ins. above ground, properly marked and witnessed by pits.
	Thence
	S.0°10'W., on a true line bet. secs. 4 and 5.
	Over nearly level land.
40.50	Set an iron post, 3 ft. long, 1 in. diam., 27 ins. in the ground for $\frac{1}{4}$ sec. cor. with brass cap marked
	$\begin{array}{r} \frac{1}{4} \\ S 5 \mid S 4 \\ 1933 \end{array}$
	dig pits 18 x 18 x 12 ins. on line N. and S. of cor. 3 ft. dist.

Subdivision of T.9 N., R.7 W.

Chains 80.50	The cor. of secs. 4, 5, 8, and 9. Land, nearly level. Soil, sandy loam. Undergrowth, cactus, greasewood, joshua, mesquite, and arrow weed.
10.65	From the standard cor. of secs. 31 and 32, on S. bdy. of Tp., hereinbefore described, N.0°05'W., bet. secs. 31 and 32. Over nearly level land, sloping SW.
40.00	Wash, 8 lks. wide, course SW. Set an iron post, 3 ft. long, 1 in. diam., 27 ins. in the ground for $\frac{1}{4}$ sec. cor. with brass cap marked $\frac{1}{4}$ S 31 S 32 1933 dig pits 18 x 18 x 12 ins. on line N. and S. of cor. 3 ft. dist.
77.00	Wash, 10 lks. wide, course SW.
77.80	Road, bears NE. to Congress Junction and SW. to Aquila.
80.00	Set an iron post, 3 ft. long, 2 ins. diam., 27 ins. in the ground for cor. of secs. 29, 30, 31, and 32, with brass cap marked T9N R7W S 30 S 29 S 31 S 32 1933 raise a mound of stone, 3 ft. base, 2 ft. high W. of cor.
	Land, nearly level. Soil, sandy loam, 2nd. rate. Undergrowth, mesquite, greasewood, yucca, cactus, and joshua.
40.00	East, on a random line bet. secs. 29 and 32. Set temp. $\frac{1}{4}$ sec. cor.
80.00	Intersect the cor. of secs. 28, 29, 32 and 33. Thence West, on a true line bet. secs. 29 and 32. Over nearly level land, sloping SW.
12.00	Wash, 10 lks. wide, course S.
23.20	Wash, 10 lks. wide, course SW.
30.30	Wash, 5 lks. wide, course SW.
40.00	Set an iron post, 3 ft. long, 1 in. diam., 27 ins. in the ground for $\frac{1}{4}$ sec. cor., with brass cap marked

Subdivision of T.9 N., R.7 W.

BOOK 4018

Chains	<p style="text-align: right;">S 29 <u>1/4</u> S 32 1933</p> <p>ins. on line E. and W. of cor. dig pits 18 x 18 x 12 3 ft. dist.</p> <p>64.00 Wash, 8 lks. wide, course SW.</p> <p>76.20 Wash, 8 lks. wide, course SW.</p> <p>77.20 Road, Congress Junction to Aquila, bears NE. and SW.</p> <p>80.00 The cor. of secs. 29, 30, 31, and 32.</p> <p>Land, nearly level. Soil, sandy loam, 2nd. rate. Undergrowth, mesquite, greasewood, yucca, and cactus.</p>
	<p>West, on a random line bet. secs. 30 and 31.</p> <p>40.00 Set temp. 1/4 sec. cor.</p> <p>80.55 Intersect the W. bdy. of Tp., 2 lks. S. of, the cor. of secs. 25, 30, 31, and 36, which is an iron post, 3 ins. diam., 9 ins. above ground, marked and witnessed as described in the official record.</p> <p>Thence S.89°59'E., on a true line bet. secs. 30 and 31.</p> <p>Over nearly level land, draining SW.</p> <p>40.55 Set an iron post, 3 ft. long, 1 in. diam., 20 ins. in the ground to bed rock, and in a mound of stone to top, for 1/4 sec. cor. with brass cap marked</p> <p style="text-align: right;">S 30 <u>1/4</u> S 31 1933</p>
	<p>40.75 Drain, 3 lks. wide, course S.</p> <p>58.95 Wash, 5 lks. wide, course SW.</p> <p>80.55 The cor. of secs. 29, 30, 31, and 32.</p> <p>Land, nearly level. Soil, sandy and gravelly. Undergrowth, mesquite, greasewood, cactus, and joshua.</p>
	<p>N.0°05'W., bet. secs. 29 and 30.</p> <p>Over slightly rolling land, sloping SW.</p> <p>8.10 Wash, 5 lks. wide, course SW.</p> <p>18.80 Wash, 10 lks. wide, course SW.</p> <p>40.00 Set an iron post, 3 ft. long, 1 in. diam., 27 ins. in the ground for 1/4 sec. cor. with brass cap marked</p> <p style="text-align: center;">1/4 S 30 S 29 1933</p>

Subdivision of T. 9 N., R. 7 W.

Chains	dig pits 18 x 18 x 12 ins. on line N. and S. of cor. 3 ft. dist.
46.80	Wash, 6 lks. wide, course SW.
80.00	Set an iron post, 3 ft. long, 2 ins. diam., 27 ins. in the ground for cor. of secs. 19, 20, 29, and 30, with brass cap marked
	T9N R7W S 19 S 20 S 30 S 29 1933
	raise a mound of stone, 3 ft. base, 2 ft. high W. of cor.
	Land, slightly rolling. Soil, sandy and gravelly. Undergrowth, mesquite, cactus, greasewood, and joshua.
	East, on a random line bet. secs. 20 and 29.
40.00	Set temp. $\frac{1}{4}$ sec. cor.
80.06	Intersect N. and S. line 2 lks. S. of the cor. of secs. 20, 21, 28, and 29.
	Thence
	S. 89° 59' W., on a true line bet. secs. 20 and 29.
	Over broken land.
16.00	Gully, course S. Asc. 70 ft. over E. slope.
21.50	Short spur, slopes S. Desc. 30 ft. over SW. slope.
28.00	Gulch, course S. Asc. 60 ft. over E. slope.
31.00	Spur, slopes S. 20° W. Desc. 110 ft. over W. slope.
39.85	Rocky gulch, course SW.
40.03	Set an iron post, 3 ft. long, 1 in. diam., 27 ins. in the ground for $\frac{1}{4}$ sec. cor. with brass cap marked
	$\frac{1}{4}$ S 20 S 29 1933
	raise a mound of stone, 3 ft. base, 2 ft. high N. of cor.
43.85	Gulch, course S.
59.00	Gulch, 15 lks. wide, course S.
63.50	Gulch, 8 lks. wide, course S. Asc. 50 ft. over SE. slope.
70.00	Flat spur, slopes S. Desc. 70 ft. over SW. slope.
80.06	The cor. of secs. 19, 20, 29, and 30.
	Land, broken. Soil, rocky, 4th. rate. Undergrowth, palo verde, cactus, ocotillo, and grease- wood.

Subdivision of T.9 N., R.7 W.

BOOK 4013

Chains	N.89°59'W., on a random line bet. secs. 19 and 30.				
40.00	Set temp. $\frac{1}{4}$ sec. cor.				
80.40	Intersect W. bdy. of Tp. at the cor. of secs. 19, 24, 25, and 30, which is an iron post, 3 ins. diam., firmly set, marked and witnessed as described in the official record.				
	Thence				
	S.89°59'E., on a true line bet. secs. 19 and 30.				
	Over slightly rolling land, draining SW.				
40.40	Set an iron post, 3 ft. long, 1 in. diam., 27 ins. in the ground for $\frac{1}{4}$ sec. cor. with brass cap marked				
	$\frac{1}{4}$ <table style="margin-left: auto; margin-right: auto;"> <tr><td>S 19</td></tr> <tr><td>—</td></tr> <tr><td>S 30</td></tr> <tr><td>1933</td></tr> </table>	S 19	—	S 30	1933
S 19					
—					
S 30					
1933					
	dig pits 18 x 18 x 12 ins. on line E. and W. of cor. 3 ft. dist.				
53.20	Wash, 10 lks. wide, course SW.				
70.00	Wash, 15 lks. wide, course SW.				
80.40	The cor. of secs. 19, 20, 29, and 30.				
	Land, slightly rolling. Soil, sandy loam, 2nd. rate. Undergrowth, greasewood, yucca, cactus, and joshua.				
	N.0°05'W., bet. secs. 19 and 20.				
	Over broken land, along foot of mountains.				
9.60	Enter wash, 15 lks. wide, course SW. from N.				
20.00	Leave wash, course S. from NE.				
40.00	Set an iron post, 3 ft. long, 1 in. diam., 27 ins. in the ground for $\frac{1}{4}$ sec. cor. with brass cap marked				
	$\frac{1}{4}$ <table style="margin-left: auto; margin-right: auto;"> <tr><td>S 19 S 20</td></tr> <tr><td>1933</td></tr> </table>	S 19 S 20	1933		
S 19 S 20					
1933					
	3 ft. base, 2 ft. high W. of cor. raise a mound of stone,				
46.80	Wash, 20 lks. wide, course SW.				
52.20	Wash, 15 lks. wide, course SW.				
58.60	Gulch, 10 lks. wide, course SW. Asc. 110 ft. over SE. slope.				
69.00	Detached spur, bears SW. Desc. 95 ft. over N. slope.				
76.20	Gulch, 10 lks. wide, course W.				
80.00	Set an iron post, 3 ft. long, 2 ins. diam., 18 ins. in the ground to bed rock, and in a mound of stone to top, for cor. of secs. 17, 18, 19, and 20, with brass cap marked				

Subdivision of T.9 N., R.7 W.

Chains

T9N R7W	
S 18	S 17
S 19	S 20
1933	

Land, broken.
Soil, rocky, 4th. rate.
Undergrowth, palo verde, ocotillo, cactus, and catclaw.

N.89°59'E., on a random line bet. secs. 17 and 20.

40.00 Set temp. $\frac{1}{4}$ sec. cor.

80.02 Intersect N. and S. line 5 lks. N. of the cor. of secs. 16, 17, 20, and 21.

Thence

N.89°59'W., on a true line bet. secs. 17 and 20.

Over mountainous land. Asc. 185 ft. over E. slope.

5.90 Spur, slopes NE. Asc. 30 ft. over NE. slope.

11.80 Ridge, bears NE. and SW. Desc. 170 ft. over SW. slope.

18.10 Small gulch, course SW. Asc. 100 ft. over broken S. slope.

36.50 Spur, slopes S.20°W. Desc. 50 ft. to

40.01 Set an iron post, 3 ft. long, 1 in. diam., 18 ins. in the ground to bed rock, and in a mound of stone to top, for $\frac{1}{4}$ sec. cor. with brass cap marked

$\frac{1}{4}$	S 17
	S 20
	1933

Asc. 90 ft. over SE. slope.

50.20 Spur, slopes SW. Desc. 350 ft. over W. slope.

66.50 Gully, course SW. at foot of mountains. Desc. gradually over SW. slope.

80.02 The cor. of secs. 17, 18, 19, and 20.

Land, mountainous.
Soil, rocky, 4th. rate.
Undergrowth, palo verde, ocotillo, and cactus.

N.89°59'W., on a random line bet. secs. 18 and 19.

40.00 Set temp. $\frac{1}{4}$ sec. cor.

80.37 Intersect W. bdy. of Tp. 43 lks. S. of the cor. of secs. 13, 18, 19, and 24, which is an iron post, 3 ins. diam., 9 ins. above ground, marked and witnessed as described in the official record.

Thence

S.89°41'E., on a true line bet. secs. 18 and 19.

Over slightly rolling land.

Subdivision of T.9 N., R.7 W.

ECCP 4013

Chains	
21.70	Wash, 35 lks. wide, course SW.
40.37	Set an iron post, 3 ft. long, 1 in. diam., 30 ins. in the ground for $\frac{1}{4}$ sec. cor. with brass cap marked
	$\begin{array}{r} S\ 18 \\ \hline \frac{1}{4} \\ S\ 19 \\ 1933 \end{array}$
	ins. on line E. and W. of cor. dig pits 18 x 18 x 12 3 ft. dist.
45.40	Wash, 7 lks. wide, course SW.
46.50	Draw, 4 lks. wide, course SW.
80.37	The cor. of secs. 17, 18, 19, and 20.
	Land, slightly rolling. Soil, sand and clay loam. Undergrowth, greasewood, palo verde, yucca, cactus and mesquite.
<hr/>	
	N.0°05'W., bet. secs. 17 and 18.
	Over broken land, along W. slope.
21.20	Spur, slopes W. Desc. 60 ft. over NW. slope.
32.20	Foot of mountains, bears NE. and SW.
40.00	Set an iron post, 3 ft. long, 1 in. diam., 27 ins. in the ground for $\frac{1}{4}$ sec. cor. with brass cap marked
	$\begin{array}{r} \frac{1}{4} \\ S\ 18\ \ S\ 17 \\ \hline 1933 \end{array}$
	3 ft. base, 2 ft. high W. of cor. raise a mound of stone,
40.20	Wash, 15 lks. wide, course S.60°W.
47.10	Wash, 6 lks. wide, course S.60°W.
80.00	Set an iron post, 3 ft. long, 2 ins. diam., 27 ins. in the ground for cor. of secs. 7, 8, 17, and 18, with brass cap marked
	$\begin{array}{r} T9N\ R7W \\ S\ 7\ \ S\ 8 \\ \hline S\ 18\ \ S\ 17 \\ \hline 1933 \end{array}$
	ins., one in each sec. 3 ft. from post. dig pits 18 x 18 x 12
	Land, broken and rolling. Soil, rocky, sand and clay. Undergrowth, palo verde, ocotillo, greasewood, cactus and mesquite.
<hr/>	
	S.89°59'E., on a random line bet. secs. 8 and 17.
40.00	Set temp. $\frac{1}{4}$ sec. cor.
79.98	Intersect N. and S. line 2 lks. S. of the cor. of secs.

Chains	8, 9, 16, and 17.
	Thence West, on a true line bet. secs. 8 and 17. Over level land, through dense undergrowth.
3.80	Wire fence, bears N. and S.; 1.50 chs. N. fence turns E.
15.00	Road, bears NE. and SW.
24.00	Wash, 15 lks. wide, course S.
39.99	Set an iron post, 3 ft. long, 1 in. diam., 27 ins. in the ground for $\frac{1}{4}$ sec. cor. with brass cap marked
	$\begin{array}{r} S\ 8 \\ \frac{1}{4} \text{ ---} \\ S\ 17 \\ 1933 \end{array}$
	raise a mound of stone, 3 ft. base, 2 ft. high N. of cor.
42.60	Road, bears SE. and NW.
79.98	The cor. of secs. 7, 8, 17, and 18. Land, level. Soil, sand and clay loam. Undergrowth, cactus, yucca, and mesquite.
	N.89°41'W., on a random line bet. secs. 7 and 18.
40.00	Set temp. $\frac{1}{4}$ sec. cor.
80.16	Intersect W. bdy. of Tp., 2 lks. S. of the cor. of secs. 7, 12, 13, and 18, which is an iron post, 3 ins. diam., 9 ins. above ground, marked and witnessed as described in the official record.
	Thence S.89°40'E., on a true line bet. secs. 7 and 18. Over level land, through dense undergrowth.
5.00	Wash, 10 lks. wide, course SW.
40.16	Set an iron post, 3 ft. long, 1 in. diam., 30 ins. in the ground for $\frac{1}{4}$ sec. cor. with brass cap marked
	$\begin{array}{r} S\ 7 \\ \frac{1}{4} \text{ ---} \\ S\ 18 \\ 1933 \end{array}$
	dig pits 18 x 18 x 12 ins. on line E. and W. of cor. 3 ft. dist.
80.16	The cor. of secs. 7, 8, 17, and 18. Land, level. Soil, sand and clay loam. Undergrowth, greasewood, cactus, mesquite, and joshua.

Subdivision of T.9 N., R.7 W.

BOOK 401a

Chains	N.0°05'W., bet. secs. 7 and 8. Over level land, through dense undergrowth.
10.00	Drain, course SW.
27.70	Road, bears SE. and NW.
40.00	Set an iron post, 3 ft. long, 1 in. diam., 27 ins. in the ground for $\frac{1}{4}$ sec. cor. with brass cap marked $\begin{array}{c} \frac{1}{4} \\ S\ 7 S\ 8 \\ 1933 \end{array}$ dig pits 18 x 18 x 12 ins. on line N. and S. of cor. 3 ft. dist.
80.00	Set an iron post, 3 ft. long, 2 ins. diam., 27 ins. in the ground for cor. of secs. 5, 6, 7, and 8, with brass cap marked $\begin{array}{c} T9N\ R7W \\ S\ 6 S\ 5 \\ \hline S\ 7 S\ 8 \\ 1933 \end{array}$ 3 ft. base, 2 ft. high W. of cor. raise a mound of stone, Land, level. Soil, sand and clay loam. Undergrowth, cactus, mesquite, yucca, and joshua.
	East, on a random line bet. secs. 5 and 8.
40.00	Set temp. $\frac{1}{4}$ sec. cor.
79.96	Intersect N. and S. line 2 lks. S. of the cor. of secs. 4, 5, 8, and 9. Thence S.89°59'W., on a true line bet. secs. 5 and 8. Over nearly level land,
39.98	Set an iron post, 3 ft. long, 1 in. diam., 27 ins. in the ground for $\frac{1}{4}$ sec. cor. with brass cap marked $\begin{array}{c} S\ 5 \\ \frac{1}{4} \overline{S\ 8} \\ 1933 \end{array}$ ins. on line E. and W. of cor. 3 ft. dist. dig pits 18 x 18 x 12
55.00	Wash, 12 lks. wide, course S.
79.96	The cor. of secs. 5, 6, 7, and 8. Land, nearly level. Soil, sand and clay loam. Undergrowth, greasewood, cactus, yucca, and joshua.

Subdivision of T.9 N., R.7 W.

Chains N.89°40'W., on a true line bet. secs. 6 and 7.
 40.00 Set temp. $\frac{1}{4}$ sec. cor.
 80.06 Intersect the W. bdy. of Tp., 2 lks. N. of the cor. of
 secs. 1, 6, 7, and 12, which is an iron post, 3 ins.
 diam., 9 ins. above ground, marked and witnessed as de-
 scribed in the official record.

Thence

S.89°41'E., on a true line bet. secs. 6 and 7.

Over gently rolling land.

20.75 Wash, 6 lks. wide, course SW.

40.06 Set an iron post, 3 ft. long, 1 in. diam., 27 ins. in the
 ground for $\frac{1}{4}$ sec. cor. with brass cap marked

$$\frac{1}{4} \begin{array}{r} S 6 \\ \hline S 7 \\ 1933 \end{array}$$

raise a mound of stone,

3 ft. base, 2 ft. high N. of cor.

41.00 Wash, 15 lks. wide, course S.

42.10 Wash, 20 lks. wide, course S.

43.15 Wash, 60 lks. wide, course S.

52.46 Road, bears N. and S.

62.55 Draw, 4 lks. wide, course SW.

80.06 The cor. of secs. 5, 6, 7, and 8.

Land, gently rolling.

Soil, sand and clay.

Undergrowth, greasewood, cactus, yucca, and joshua.

N.0°10'E., on a random line bet. secs. 5 and 6.

40.00 Set temp. $\frac{1}{4}$ sec. cor.

80.58 Intersect N. bdy. of Tp., 5 lks. E. of the cor. of secs.
 5, 6, 31, and 32, which is an iron post, 2 ins. diam.,
 9 ins. above ground, marked and witnessed as described
 in the official record.

Thence

S.0°08'W., on a true line bet. secs. 5 and 6.

Over gently rolling land.

40.58 Set an iron post, 3 ft. long, 1 in. diam., 27 ins. in the
 ground for $\frac{1}{4}$ sec. cor. with brass cap marked

$$\frac{1}{4} \begin{array}{r} S 6 | S 5 \\ \hline 1933 \end{array}$$

raise a mound of stone,

3 ft. base, 2 ft. high W. of cor.

Subdivision of T.9 N., R.7 W.

BOOK 4013

Chains

47.60 Draw, 2 chs. wide, course SW.

80.58 The cor. of secs. 5, 6, 7, and 8.

Land, gently rolling.

Soil, sand and clay loam.

Undergrowth, cactus, greasewood, yucca, and joshua.

FINAL TEST

For evidence of the continued satisfactory adjustment of the solar apparatus of Buff Transit No. 9977, see preliminary test for T.11 N., R.8 W., surveyed under this Group.

GENERAL DESCRIPTION

The township lies about 10 miles SW. of the town of Congress Junction, Arizona. A secondary highway from Congress Junction to Aguila was being constructed at the time of the survey. Nearly every part of the Tp. can be reached by some sort of road.

A range of mountains about $1\frac{1}{2}$ miles wide runs SouthEasterly through the township from sec. 18. The remainder of the township is level desert. The drainage of the E. part is SE. to the Hassayampa River and of the W. part NW. to the Bill Williams.

The rough part of the Tp. is of granite formation, rocky with shallow soil and little vegetation, used only for grazing by a few deer. There is some small evidence of mineral, a few scattered prospect holes. The level portion is loam soil of excellent depth and quality with a more-than average amount of the desert growth usual to the elevation (2,800) in Arizona. Considerable desert willow undergrowth was noted in the NW. cor. of the Tp.

The only water noted was behind an earth dam in sec. 22. There are no residents. An unused cabin is located in sec. 12.

42

BOOK 4013

CERTIFICATE OF UNITED STATES SURVEYOR

I, Theodore Vander Meer, U.S. Transitman, hereby certify upon honor that, in pursuance of special instructions received from the District Cadastral Engineer for Arizona bearing date of the 8th. day of September, 1932, I have well, faithfully, and truly in my own proper person, and in strict conformity with said instructions, the Manual of Surveying Instructions, and the laws of the United States, resurveyed a part of the Second Standard Parallel North, through Range 7 West; and resurveyed the East boundary and surveyed the subdivisional lines of Township 9 North, Range 7 West,

..... of the Gila and Salt River Meridian, in the State of Arizona, which are represented in the foregoing field notes as having been executed by me, and under my direction; and that all the corners of said survey and resurvey have been established and perpetuated in strict accordance with the Manual of Surveying Instructions, and the special written instructions of the District Cadastral Engineer for Arizona and in the specific manner described in the field notes, and that the foregoing are the original field notes of such survey and resurvey.

Glendale, Calif.,
May 23, 1934.

Theodore Vander Meer
U.S. Transitman

APPROVAL

OFFICE OF U. S. SUPERVISOR OF SURVEYS,
Denver, Colorado, December 3, 1934.

The foregoing field notes of the resurvey of a part of the Second Standard Parallel North, through Range 7 West; and of the resurvey of the East boundary and survey of the subdivisional lines of Township 9 North, Range 7 West, of the Gila and Salt River Meridian, in the State of Arizona,

executed by Theodore Vander Meer, U.S. Transitman, under his special instructions dated September 8, 1932, having been critically examined, and the necessary corrections and explanations made, the said field notes, and the surveys and resurveys they describe, are hereby approved.

Monte S. Johnson
U. S. Supervisor of Surveys.

I certify that the foregoing transcript of the field notes of the above-described surveys in _____, has been correctly copied from the original notes on file in this office.

Monte S. Johnson
U. S. Supervisor of Surveys.