

4-679  
(April 1933)

Book C.

BOOK 4062

# FIELD NOTES

OF THE SURVEY OF THE

Subdivisional Lines of Township 9 South, Range 3 West.

4062

Of the Gila & Salt River Meridian,

In the State of Arizona

### EXECUTED BY

Charles E. Bronson, and Cyril Gilliam, U.S. Transitmen.

4062

Under special instructions dated December 12, 1933, which provided for the surveys included under Group No. 198, bearing the approval of the Commissioner of the General Land Office under date of March 26, 1934 and assignment instructions dated December 15, 1933

Survey commenced January 2, 1934

Survey completed January 20, 1934

1A

BOOK 4062

# INDEX DIAGRAM.

Township 9 S., Range 3 W.

6	40 5	31 4	24 3	16 2	8 1
40	39	31	24	16	8
7	39 8	30 9	23 10	15 11	7 12
38	38	29	22	14	7
18	37 17	29 16	21 15	14 14	6 13
37	36	28	21	13	5
19	36 20	27 21	20 22	12 23	4 24
35	34	27	19	11	3
30	33 29	26 28	19 27	11 26	3 25
33	32	25	18	10	2
31	32 32	25 33	17 34	9 35	1 36

Chains.

The subdivisional survey of township 9 south, range 3 west, was executed with Young & Sons transits Nos. 8567 and 8527, property of the General Land Office, each with full vertical circles reading to single minutes. The instruments were in good condition and having been placed in satisfactory adjustment prior to beginning the survey, and tested and found free from appreciable error, were approved by the district cadastral engineer on Dec. 15, 1933.

As the lines to be established run over desert and rolling mountainous country with sparse timber and undergrowth, the direction of the lines were determined and verified by horizontal deflection angles from meridians determined by Polaris and direct altitude observations of the sun for azimuth, described in the field notes of the 2nd standard parallel south through Rs. 3 and 4 W., resurveyed under this group.

The bearings were deflected from meridians by repetition of angles taking the mean of direct and reversed sights at each instrument station. The back and foresight method was selected, making proper offsets on the latitudinal lines as required, and checked against each other frequently, and on meridians determined by direct altitude observations of the sun for azimuth throughout the survey.

The measurements were made with Lallie steel tapes 5 chs. in length, graduated every link for the first 100 lks. and the balance at intervals of 10 lks. The tapes were tested by comparison with a Lufkin standard and found correct. The measurements were made on the slope and the vertical angle of each interval was ascertained by clinometers in good adjustment; the horizontal equivalents are entered in the field note record.


Beginning at the standard cor. of secs. 35 and 36 on the S. bdy. of the Tp., which is an iron post, 2 ins. diam., firmly set in a mound of stone, 4 ft. base, 2 1/2 ft. high, mkd. and witnessed as described in the official record.

N.0°01'W., bet. secs. 35 and 36.

Over rough desert hills, through scattering undergrowth.

Ascend 125 ft. over S. slope.


- 4.10 Spur, slopes SE.; desc. 125 ft. over NE. slope.
- 16.50 Wash, 10 lks. wide, course N.60°E.
- 23.07 Wash, 10 lks. wide, course N.65°E.
- 26.82 Small spur, slopes E.
- 39.35 Wash, .25 lks. wide, course W.
- 40.00 Set an iron post, 3 ft. long, 1 in. diam., 28 ins. in the ground, for 1/4 sec. cor., with brass cap mkd.



raise a mound of stone, 2 ft. base, 1 1/2 ft. high, W. of cor.


Chains, 45.00	Ascend 300 ft. over steep S. slope.				
57.95.	Top of steep ascent, bears E. and W.; continue ascending 100 ft. over rough SE. slope.				
71.08	Ridge, bears E. and W.; desc. 100 ft. over NW. slope.				
79.81	Wash, 10 lks. wide, course NE.				
80.00	Set an iron post, 3 ft. long, 2 ins. diam., 28 ins. in the ground, for cor. of secs. 25, 26, 35 and 36, with brass cap mkd.				
	<table style="margin-left: auto; margin-right: auto;"> <tr><td>T 9 S R 3 W</td></tr> <tr><td>S 26   S 25</td></tr> <tr><td>S 35   S 36</td></tr> <tr><td>1934</td></tr> </table>	T 9 S R 3 W	S 26   S 25	S 35   S 36	1934
T 9 S R 3 W					
S 26   S 25					
S 35   S 36					
1934					
	raise a mound of stone, 2 ft. base, 1½ ft. high, W. of cor.				
	Land, rough desert hills. Soil, rocky; 4th rate. Timber, scattering palo verde, mesquite and ironwood; undergrowth, scattering greasewood, sage brush and cactus.				
-----					
	East on a random line bet. secs. 25 and 36.				
40.00	Set temp. ¼ sec. cor.				
80.02	Intersect E. bdy. of Tp., 14 lks. S. of the cor. of secs. 25, 30, 31 and 36; described in the field notes of the E. bdy. of T. 9 S., R. 3 W., surveyed under this group.				
	Thence				
	S. 89° 54' W., on a true line bet. secs. 25 and 36.				
	Over level desert land, through scattering timber and undergrowth.				
9.45	Wash, 10 lks. wide, course N.				
40.01	Set an iron post, 3 ft. long, 1 in. diam., 3 ins. in the ground to bedrock, and in a mound of stone to top, for ¼ sec. cor., with brass cap mkd.				
	<table style="margin-left: auto; margin-right: auto;"> <tr><td>¼ S 25</td></tr> <tr><td>S 36</td></tr> <tr><td>1934</td></tr> </table>	¼ S 25	S 36	1934	
¼ S 25					
S 36					
1934					
	raise a mound of stone, 2 ft. base, 1½ ft. high, N. of cor.				
42.00	Leave desert land, bears N. and S.; asc. 300 ft. over broken NE. slope.				
77.50	Spur, slopes N.; desc. 20 ft. over NW. slope.				
79.30	Wash, 5 lks. wide, course NE.; thence along N. slope.				
80.02	The cor. of secs. 25, 26, 35 and 36.				
	Land, level and rough hills. Soil, rocky; 4th rate. Timber, scattering palo verde, ironwood and mesquite; undergrowth, scattering greasewood, sage brush and cactus.				

Chains N.0°01'W., bet. secs. 25 and 26.  
 Over desert hills, through scattering timber and undergrowth.  
 Ascend 15 ft. over SE. slope.  
 7.20 Spur, slopes E.  
 16.19 Descend 185 ft. over N. slope.  
 24.42 Base of slope, bears E. and W.; asc. 20 ft. over S. slope.  
 27.30 Top of hill, bears E. and W.; desc. 70 ft. over N. slope.  
 32.30 Base of slope, bears E. and W.; continue over rolling desert land.  
 34.50 Wash, 15 lks. wide, course E.  
 40.00 Set an iron post, 3 ft. long, 1 in. diam., 28 ins. in the ground, for  $\frac{1}{4}$  sec. cor. with brass cap mkd.



raise a mound

of stone, 2 ft. base,  $1\frac{1}{2}$  ft. high, N. of cor.  
 46.25 Wash, 10 lks. wide, course E.; asc. 80 ft. over S. slope.  
 51.65 Top of hill, bears E. and W.; desc. 205 ft. over N. slope.  
 73.40 Base of slope, bears E. and W.; continue over desert land.  
 80.00 Set an iron post, 3 ft. long, 2 ins. diam., 28 ins. in the ground, for cor. of secs. 23, 24, 25 and 26, with brass cap mkd.



raise a mound

of stone, 2 ft. base,  $1\frac{1}{2}$  ft. high, W. of cor.  
 Land, rough hills and desert.  
 Soil, rocky, 4th rate.  
 Timber, scattering palo verde, ironwood and mesquite; undergrowth, scattering greasewood, sage brush and cactus.

-----  
 N.89° 54' W., on a random line bet. secs. 24 and 25.  
 40.00 Set temp.  $\frac{1}{4}$  sec. cor.  
 80.26 Intersect E. bdy. of Tp., 14 lks. S. of the cor. of secs. 19, 24, 25 and 30; described in the field notes of the E. bdy. of T.9 S., R.3 W., surveyed under this group.  
 Thence  
 S.89° 48' W., on a true line bet. secs. 24 and 25,  
 Over desert land through scattering brush.  
 5.50 Road, bears NW. and SE.  
 7.25 Wash, 60 lks. wide, course NW.

## Chains

- 8.90 Wash, 8 lks. wide, course N.  
 23.05 Wash, 15 lks. wide, course N.  
 27.85 Base of slope, bears N. and S.; leave desert.; asc. 290 ft. over E. slope.  
 38.65 Top of ridge, bears N. and S.; desc. 10 ft. over W. slope.  
 40.13 Set an iron post, 3 ft. long, 1 in. diam., 6 ins. in the ground to bedrock, and in a mound of stone to top, for  $\frac{1}{4}$  sec. cor., with brass cap mkd.

$$\frac{1}{4} \begin{array}{r} S 24 \\ S 25 \\ 1934 \end{array}$$

- raise a mound of stone, 2 ft. base,  $1\frac{1}{2}$  ft. high, N. of cor.  
 Descend 155 ft. over W. slope.

- 48.10 Wash, 15 lks. wide, course N.  
 52.60 Wash, 10 lks. wide, course N.; asc. 85 ft. over SE. slope.  
 57.45 Low ridge, bears NW and SE.; desc. 155 ft. over N. slope.  
 62.85 Wash, 10 lks. wide, course SW.; continue over rolling desert land.  
 80.26 The cor. of secs. 23, 24, 25 and 26.  
 Land, rough hills and desert.  
 Soil, rocky; 4th rate.  
 Timber, scattering palo verde, ironwood and mesquite; undergrowth, greasewood, sage brush and cactus.

N.0° 01'W., bet. secs. 23 and 24.

Over rolling desert land, through scattering timber and undergrowth.

- 5.97 Wash, 10 lks. wide, course N.; continue along same.  
 12.00 Leave wash, course W.; asc. 250 ft. over S. slope.  
 22.50 Spur, slopes SW.; desc. 55 ft. over NW. slope.  
 27.95 Ravine, course W.; asc. 70 ft. over SW. slope.  
 33.26 Spur, slopes NW.; desc. 65 ft. over NE. slope.  
 40.00 Set an iron post, 3 ft. long, 1 in. diam., 28 ins. in the ground, for  $\frac{1}{4}$  sec. cor., with brass cap mkd.

$$\frac{1}{4} \begin{array}{r} S 23 | S 24 \\ 1934 \end{array}$$

raise a mound of stone, 3 ft. base,  $1\frac{1}{2}$  ft. high, W. of cor.

Chains. Descend 260 ft. over NE. slope.  
 49.30 Wash, 10 lks. wide, course W.; continue over rolling desert land.  
 59.20 Wash, 40 lks. wide, course W.  
 69.10 Wash, 10 lks. wide, course SW.; asc. 100 ft. over S. slope.  
 80.00 Set an iron post, 3 ft. long, 2 ins. diam., 28 ins. in the ground, for cor. of secs. 13, 14, 23 and 24, with brass cap mkd.

T 9 S R 3 W  
 S 14 | S 13  
 S 23 | S 24  
 1934

raise a mound  
of stone, 2 ft. base, 1½ ft. high, W. of cor.

Land, rough hills and desert.  
 Soil, rocky; 4th rate.  
 Timber, scattering palo verde, greasewood and mesquite;  
 undergrowth, greasewood, sage brush and cactus.

N. 89°48'E., on a random line bet. secs. 13 and 24.  
 40.00 Set temp. ¼ sec. cor.  
 80.10 Intersect E. bdy. of Tp., 7 lks. N. of the cor. of secs. 13, 18, 19 and 24; described in the field notes of the E. bdy. of T. 9 S., R. 3 W., surveyed under this group.  
 Thence  
 S. 89°51'W., on a true line bet. secs. 13 and 24.  
 Over level desert land, through scattering timber and undergrowth.  
 21.65 Wash, 50 lks. wide, course NW.  
 26.30 Dim road, bears N. and S.  
 27.30 Wash, 100 lks. wide, course N.  
 34.50 Wash, 60 lks. wide, course N.  
 40.05 Set an iron post, 3 ft. long, 1 in. diam., 28 ins. in the ground, for ¼ sec. cor., with brass cap mkd.

¼ S 13  
 S 24  
 1934

raise a mound  
of stone, 2 ft. base, 1½ ft. high, N. of cor.

50.40 Wash, 10 lks. wide, course N.; leave desert land; asc. 160 ft. over gradual E. slope.  
 78.50 Top of low hill, bears N. and S.  
 80.10 The cor. of secs. 13, 14, 23 and 24.  
 Land, desert and rough hills.

Chains.	Soil, rocky; 4th rate, Timber, scattering palo verde, ironwood and mesquite; undergrowth, greasewood, sage brush and cactus.
	N.0°01'W., bet. secs. 13 and 14. Over rough desert hills, through scattering timber and undergrowth. Descend 45 ft. over N. slope.
5.00	Ravine, course SW.; asc. 170 ft. over SW. slope.
17.00	Spur, slopes W.; desc. 40 ft. over NW. slope.
21.20	Ravine, course W.; asc. 115 ft. over SW. slope.
33.00	Top of mountain, bears E. and W.; desc. 50 ft. over N. slope.
40.00	Set an iron post, 3 ft. long, 1 in. diam., 6 ins. in the ground to bedrock, and in a mound of stone to top, for $\frac{1}{4}$ sec. cor., with brass cap mkd.
	$\frac{1}{4}$ S 14   S 13 1934
	raise a mound of stone, 2 ft. base, $1\frac{1}{2}$ ft. high, W. of cor. Descend 450 ft. over N. slope.
64.30	Wash, 30 lks. wide, course NW.; continue over level desert land.
69.30	Wash, 150 lks. wide, course W.
80.00	Set an iron post, 3 ft. long, 2 ins. diam., 28 ins. in the ground, for cor. of secs. 11, 12, 13 and 14, with brass cap mkd.
	T 9 S R 3 W S 11   S 12 S 14   S 13 1934
	raise a mound of stone, 2 ft. base, $1\frac{1}{2}$ ft. high, W. of cor. Land, rough desert hills and level. Soil, rocky; 4th rate. Timber, scattering palo verde, ironwood and mesquite; undergrowth, greasewood, sage brush and cactus.
	N.89°51'E., on a random line bet. secs. 12 and 13.
40.00	Set temp. $\frac{1}{4}$ sec. cor.
79.98	Intersect E. bdy. of Tp., 5 lks. N. of the cor. of secs. 7, 12, 13 and 18.; described in the field notes of the E. bdy. of T. 9 S., R. 3 W., surveyed under this group.
	Thence

Subdivision of T. 9 S., R. 3 W.

Chains.	S.89°53'W., on a true line bet. secs. 12 and 13. Over rolling land, through scattering timber and undergrowth.
14.30	Wash, 10 lks. wide, course NE.; asc. 30 ft. over E. slope.
24.30	Top of hill, bears N. and S.; desc. 130 ft. over W. slope.
35.00	Base of slope, bears N. and S.; continue over level desert land.
39.99	Set an iron post, 3 ft. long, 1 in. diam., 28 ins. in the ground, for $\frac{1}{4}$ sec. cor., with brass cap mkd.  $\frac{1}{4} \begin{array}{l} S 12 \\ S 13 \\ 1934 \end{array}$
	raise a mound of stone, 2 ft. base, $1\frac{1}{2}$ ft. high, N. of cor.
63.50	Road, bears NW. and SE.
79.98	The cor. of secs. 11, 12, 13 and 14. Land, rolling and level. Soil, rocky; 4th rate. Timber, palo verde, ironwood and mesquite; undergrowth, greasewood, sage brush and cactus.
-----	
	N.0°01'W., bet. secs. 11 and 12. Over rolling desert land, through scattering timber and undergrowth.
10.00	Road, bears NW. and SE.
27.30	Wash, 20 lks. wide, course NW.
29.70	Wash, 20 lks. wide, course NW.
40.00	Set an iron post, 3 ft. long, 1 in. diam., 28-ins. in the ground, for $\frac{1}{4}$ sec. cor., with brass cap mkd.  $\frac{1}{4} \begin{array}{l} S 11   S 12 \\ 1934 \end{array}$
	raise a mound of stone, 2 ft. base, $1\frac{1}{2}$ ft. high, W. of cor.
49.00	Wash, 10 lks. wide, course W.; asc. 45 ft. over S. slope.
54.00	Low ridge, bears E. and W.; desc. 55 ft. over N. slope.
64.90	Wash, 10 lks. wide, course NW.
80.00	Set an iron post, 3 ft. long, 2 ins. diam., 28 ins. in the ground, for cor. of secs. 1, 2, 11 and 12, with brass cap mkd.  $\begin{array}{l} T 9 S R 3 W \\ S 2   S 1 \\ S 11   S 12 \\ 1934 \end{array}$

Chains.	raise a mound of stone, 2 ft. base, $1\frac{1}{2}$ ft. high, W. of cor.
	Land, rolling. Soil, sandy and gravelly; 3rd rate. Timber, scattering palo verde, ironwood and mesquite; undergrowth, greasewood, sage brush and cactus.
	-----
	N. $89^{\circ}53'E.$ , on a random line, bet. secs. 1 and 12.
40.00	Set temp. $\frac{1}{4}$ sec. cor.
79.96	Intersect E. bdy. of Tp., at the cor. of secs. 1, 6, 7 and 12.; described in the field notes of the E. bdy. of T. 9 S., R. 3 W., surveyed under this group.
	Thence
	S. $89^{\circ}53'W.$ , on a true line bet. secs. 1 and 12.
	Over level desert land, through scattering timber and undergrowth.
17.96	Wash, 20 lks. wide, course NW.
39.98	Set an iron post, 3 ft. long, 1 in. diam.; 28 ins. in the ground, for $\frac{1}{4}$ sec. cor., with brass cap mkd.
	$\frac{1}{4}$ $\frac{S\ 1}{S\ 12}$ 1934
	raise a mound of stone, 2 ft. base, $1\frac{1}{2}$ ft. high, N. of cor.
79.96	The cor. of secs. 1, 2, 11 and 12.
	Land, level. Soil, sandy; 2nd. rate. Timber, scattering palo verde, ironwood and mesquite; undergrowth, greasewood, cactus and ocotillo.
	-----
	North on a random line bet. secs. 1 and 2.
40.00	Set temp. $\frac{1}{4}$ sec. cor.
80.11	Intersect N. bdy. of Tp., 7 lks. E. of the cor. of secs. 1, 2, 35 and 36; described in the field notes of the N. bdy. of T. 9 S., R. 3 W., surveyed under this group.
	Thence
	S. $0^{\circ}03'E.$ , on a true line bet. secs. 1 and 2.
	Over level desert land, through scattering timber and undergrowth.
10.60	Wash, 20 lks. wide, course SW.
14.10	Wash, 30 lks. wide, course W.
19.10	Wash, 10 lks. wide, course NW.
25.80	Wash, 10 lks. wide, course NW.
33.80	Wash, 10 lks. wide, course NW.

Chains. 37:40	Wash, 30 lks. wide, course NW.
40.11	Set an iron post, 3 ft. long; 1 in. diam., 28 ins. in the ground, for $\frac{1}{4}$ sec. cor., with brass cap mkd.  $\frac{1}{4}$ S 2   S 1 1934  raise a mound of stone, 2 ft. base, $1\frac{1}{2}$ ft. high, W. of cor.
41.10	Wash, 20 lks. wide, course NW.
80.11	The cor. of secs. 1, 2, 11 and 12.
	Land, level. Soil, sandy; 2nd rate. Timber, very scattering palo verde, mesquite and ironwood; undergrowth, greasewood, sage brush and cactus.
	From the standard cor. of secs. 34 and 35 on the S. bdy. of the Tp., which is an iron post, 2 ins. diam., 18 ins. above ground, firmly set, mkd. and witnessed as described in the official record.  N.0°01'W., bet. secs. 34 and 35.  Over level desert land, through scattering timber and undergrowth.
9.50	Wash, 10 lks. wide, course NE.
18.90	Wash, 10 lks. wide, course SE.
24.20	Road, bears SE. and NW.
29.99	Wash, 15 lks. wide, course SE.; asc. 70 ft. over S. slope.
35.00	Top of knoll, bears E. and W.
40.00	Set an iron post, 3 ft. long; 1 in. diam., on surface rock, with a cross X, mkd. at the base, and in a mound of stone to top, for $\frac{1}{4}$ sec. cor., with brass cap mkd.  $\frac{1}{4}$ S 34   S 35 1934  raise a mound of stone, 2 ft. base, $1\frac{1}{2}$ ft. high, W. of cor.
	Continue over rolling land; asc. 40 ft. over SW. slope.
45.07	Spur, slopes W.; desc. 100 ft. over N. slope.
55.27	Wash, 45 lks. wide, course W.; asc. 345 ft. over S. slope of rough mountainous land.
68.35	Spur, slopes SE.; continue along E. slope.
70.30	Small saddle in ridge, bears E. and W.; desc. 50 ft. over N. slope.

Chains.  
80.00

Set an iron post, 3 ft. long, 2 ins. diam., 18 ins. in the ground to bedrock, and in a mound of stone to top, for cor. of secs. 26, 27, 34 and 35, with brass cap mkd.

T 9 S R 3 W  
S 27 | S 26  
S 34 | S 35  
1934

raise a mound  
of stone, 2 ft. base, 1½ ft. high, W. of cor.

Land, level and mountainous.  
Soil, rocky; 4th rate.  
Timber, scattering mesquite, palo verde and ironwood;  
undergrowth, greasewood, sage brush and cactus.

East on a random line bet. secs. 26 and 35.

40.00 Set temp. ¼ sec. cor.

80.12 Intersect E. bay. of Tp., 2 lks. N. of the cor. of secs. 25, 26, 35 and 36.

Thence

N. 89° 59' W., on a true line bet. secs. 26 and 35.

Over mountainous land, through scattering timber and undergrowth.

Ascend 120 ft. over E. slope.

4.00 Top of ascent, bears N. and S.; desc. 55 ft. over gradual W. slope.

16.60 Base of slope, bears N. and S.; asc. 45 ft. over gradual E. slope.

22:00 High point on ridge, bears N. and S.; desc. 345 ft. over W. slope.

40.06 Set an iron post, 3 ft. long, 1 in. diam., 18 ins. in the ground to bedrock, and in a mound of stone to top, for ¼ sec. cor., with brass cap mkd.

¼ S 26  
S 35  
1934

raise a mound  
of stone, 2 ft. base, 1½ ft. high, N. of cor.

Thence over desert land.

51.50 Wash, 20 lks. wide, course S.; leave desert land, bears NE. and SW.; asc. 470 ft. over E. slope.

62.80 Top of bluff, 60 ft. high, bears N. and S.

67.40 Spur, slopes SW.; desc. 155 ft. over W. slope.

75.50 Gulch, course SW.; asc. 45 ft. over E. slope.

80.12 The cor. of secs. 26, 27, 34 and 35.

Land, mountainous.

Subdivision of T. 9 S., R. 3 W.

Chains. N.0°01'W., bet. secs. 26 and 27.

Over rough mountainous land, through scattering timber and undergrowth.

Descend 70 ft. over NE. slope.

1.80 Wash; 10 lks. wide, course E.

5.50 Wash, 15 lks. wide, course E.

12.90 Wash, 40 lks. wide, course SE.; asc. 330 ft. over SW. slope.

29.70 East side of peak on ridge, bears N.10°W. and S.10°E.; desc. 295 ft. over NE. slope.

40.00 Set an iron post, 3 ft. long, 1 in. diam., 15 ins. in the ground to bedrock, and in a mound of stone to top, for 1/4 sec. cor., with brass cap mkd.

1/4

S 27 | S 26

1934

raise a mound of stone, 2 ft. base, 1 1/2 ft. high, W. of cor.

44.60 Wash, 30 lks. wide, course NW.; asc. 130 ft. over S. slope.

51.77 Spur, slopes S.20°E.; desc. 260 ft. over NE. slope,

67.45 Wash, 30 lks. wide, course NW.; asc. 195 ft. over S. slope.

79.70 Top of bluff, 120 ft. high, faces SW. bears N.20°W., and S.20°E.

80.00 Set an iron post, 3 ft. long, 2 ins. diam., 6 ins. in the ground to bedrock, and in a mound of stone to top, for cor. of secs. 22, 23, 26 and 27, with brass cap mkd.

T 9 S R 3 W

S 22 | S 23

S 27 | S 26

1934

raise a mound of stone, 2 ft. base, 1 1/2 ft. high, W. of cor.

Land, mountainous.

Soil, rocky; 4th rate.

Timber, scattering palo verde, mesquite and ironwood; undergrowth, greasewood, sage brush and cactus.

S.89°59'E.; on a random line bet. secs. 23 and 26.

40:00 Set temp. 1/4 sec. cor.

79.88 Intersect N. and S. line, 5 lks. S. of the cor. of secs. 23, 24, 25 and 26.

Thence

S.89°59'W., on a true line bet. secs. 23 and 26.

Over mountainous land, through scattering timber and undergrowth.

Chains	
.45	Wash, 15 lks. wide, course N.; asc. 135 ft. over E. slope.
13.25	Flat spur, slopes NW.; desc. 20 ft. over W. slope.
15.55	Wash, 12 lks. wide, course N.; asc. 110 ft. over NE. slope.
19.35	Saddle in ridge, bears NW. and SE.; desc. 160 ft. over W. slope.
32.06	Wash, 30 lks. wide, course NW.; asc. 60 ft. over NE. slope.
39.94	Set an iron post, 3 ft. long, 1 in. diam., 4 ins. in the ground to bedrock, and in a mound of stone to top, for $\frac{1}{4}$ sec. cor., with brass cap mkd.
	$\frac{1}{4}$ S 23 S 26 1934
	raise a mound of stone, 2 ft. base, $1\frac{1}{2}$ ft. high, N. of cor.
	The $\frac{1}{4}$ sec. cor. is located on top of spur, slopes N. Descend 80 ft. over W. slope.
45.15	Wash, 15 lks. wide, course NW.; asc. 27 ft. over NE. slope.
49.90	Spur, slopes NW.; desc. 95 ft. over NW. slope.
55:10	Wash, 20 lks. wide; course N.; asc. 325 ft. over E. slope.
73:45	Spur, slopes NW.; desc. 150 ft. over W. slope.
79:88	The cor. of secs. 22, 23, 26 and 27.
	Land, mountainous. Soil, rocky; 4th rate. Timber, scattering palo verde, and mesquite; undergrowth, sage brush, cactus, ocotillo and greasewood.
-----	
	N. 0° 01' W., bet. secs. 22 and 23. Over rolling and mountainous land, through scattering timber and undergrowth. Ascend 75 ft. over SW. slope.
7.65	Spur, slopes W.; desc. 160 ft. over N. slope.
15.05	Ravine, course W.; asc. 55 ft. over SW. slope.
29.10	Ridge, bears NW. and SE.; desc. 190 ft. over NE. slope.
34.50	Top of bluff, 35 ft. high, faces N.
40.00	Set an iron post, 3 ft. long, 1 in. diam., 24 ins. in the ground, for $\frac{1}{4}$ sec. cor., with brass cap mkd.
	$\frac{1}{4}$ S 22   S 23 1934
	raise a mound of stone, 2 ft. base, $1\frac{1}{2}$ ft. high, W. of cor.

Subdivision of T. 9 S., R. 3 W.

BOOK 4062

Chains.	
43.00	Wash, 40 lks. wide, course W.
48.00	Wash, 26 lks. wide, course SW.; asc. 135 ft. over S. slope.
56.70	Spur, slopes W.; desc. 115 ft. over W. slope.
66.40	Base of slope, bears E. and W.; continue over rolling land.
80.00	Set an iron post, 3 ft. long, 2 ins. diam., 12 ins. in the ground to bedrock, and in a mound of stone to top, for cor. of secs. 14, 15, 22 and 23, with brass cap mkd.
	T 9 S. R 3 W S 15   S 14 S 22   S 23 1934
	raise a mound of stone, 2 ft. base, 1½ ft. high, W. of cor.
	Land, rolling and mountainous. Soil, sandy, 3rd rate; and rocky, 4th rate. Timber, scattering palo verde, mesquite and ironwood; undergrowth, greasewood, cactus, sage brush and ocotillo.
	N. 89° 59' E., on a random line bet. secs. 14 and 23.
40.00	Set temp. ¼ sec. cor.
79.76	Intersect N. and S. line, 5 lks. S. of the cor. of secs. 13, 14, 23 and 24.
	Thence
	S. 89° 57' W., on a true line bet. secs. 14 and 23.
	Over rough mountainous land, through scattering timber and undergrowth.
	Descend 70 ft. over gradual W. slope.
10.40	Ravine, course SE.; asc. 145 ft. over gradual E. slope.
15.30	Ridge, bears N. and S.; desc. 160 ft. over W. slope.
21.65	Wash, 15 lks. wide, course NW.
31.95	Wash, 20 lks. wide, course NW.; continue over rolling land.
39.88	Set an iron post, 3 ft. long, 1 in. diam., on surface rock, with a cross X mkd. at the base, and in a mound of stone to top, for ¼ sec. cor., with brass cap mkd.
	S 14 S 23 1934
44.25	Ascend 105 ft. over E. slope.
60.60	Spur, slopes NW.; desc. 110 ft. over W. slope.
79.76	The cor. of secs. 14, 15, 22 and 23.
	Land, mountainous and rolling.

Chains

Soil, rocky; 4th rate.  
 Timber, scattering palo verde, mesquite and ironwood;  
 undergrowth, greasewood, sage brush and cactus.

N.0°01'W., bet. secs. 14 and 15.

Over rolling desert land, through scattering timber and undergrowth.

11.20 Wash, 20 lks. wide, course NE.

.23.10 Wash, 15 lks. wide, course NW.

40.00 Set an iron post, 3 ft. long, 1 in. diam., 15 ins. in the ground to bedrock, and in a mound of stone to top, for  $\frac{1}{4}$  sec. cor., with brass cap mkd.

$\frac{1}{4}$   
 S 15 | S 14  
 1934

raise a mound of stone, 2 ft. base,  $1\frac{1}{2}$  ft. high, W. of cor.

51.30 Wash, 20 lks. wide, course W.

59.00 Wash, 10 lks. wide, course W.

62.30 Wash, 25 lks. wide, course SW.

79.00 Set an iron post, 3 ft. long, 2 ins. diam., 28 ins. in the ground; for witness cor. of secs. 10, 11, 14 and 15, with brass cap mkd.

W C  
 T 9 S R 3 W  
 S 10 | S 11  
 S 15 | S 14  
 1934

raise a mound of stone, 2 ft. base,  $1\frac{1}{2}$  ft. high, W. of cor.

80.00 True point for cor. of secs. 10, 11, 14 and 15, falls in wash, 110 lks. wide, course W.

Land, rolling.  
 Soil, gravelly and rocky; 4th rate.  
 Timber, scattering palo verde, ironwood and mesquite;  
 undergrowth, greasewood, sage brush and cactus.

N.89°57'E., on a random line bet. secs. 11 and 14.

40.00 Set temp.  $\frac{1}{4}$  sec. cor.

79.80 Intersect N. and S. line, 17 lks. N. of the cor. of secs. 11, 12, 13 and 14.

Thence

N.89°55'W., on a true line bet. secs. 11 and 14.

Over desert washland, through scattering timber and undergrowth:

Chains.	
11.80	Enter wash, 80 lks. wide, course W., from NE.
27.50	Leave wash, course S.70°W.
37.50	Same wash, 100 lks. wide, course NW.
39.90	Set an iron post, 3 ft. long, 1 in. diam., 28 ins. in the ground, for $\frac{1}{4}$ sec. cor., with brass cap mkd.
	$\frac{1}{4}$ $\frac{S 11}{S 14}$ 1934
	raise a mound
	of stone, 2 ft. base, $1\frac{1}{2}$ ft. high, N. of cor.
47.70	Same wash, 100 lks. wide, course S.70°W.
74.60	Enter same wash, 100 lks. wide, course W.
79.80	The true point for cor. of secs. 10, 11, 14 and 15.
	Land, desert washland.
	Soil, gravelly and rocky; 3rd rate.
	Timber, scattering palo verde, ironwood and mesquite;
	undergrowth, greasewood, sage brush and cactus.
-----	
	N.0°01'W., bet. secs. 10 and 11.
	Over rolling desert land, through scattering timber and undergrowth.
10.00	Ascend 120 ft. over SW. slope.
18.80	E. slope of saddle in ridge, bears E. and W.; desc. 40 ft. over N. slope.
23.10	Ravine, course NW.; asc. 75 ft. over SW. slope.
28.25	Spur, slopes W.; desc. 75 ft. over S. slope.
34.35	Ravine, course W.; asc. 75 ft. over S. slope.
40.00	Set an iron post, 3 ft. long, 1 in. diam., 5 ins. in the ground to bedrock, and in a mound of stone to top, for $\frac{1}{4}$ sec. cor., with brass cap mkd.
	$\frac{1}{4}$ S 10   S 11 1934
	raise a mound
	of stone, 2 ft. base, $1\frac{1}{2}$ ft. high, W. of cor.
	The $\frac{1}{4}$ sec. cor. is located on top of spur, slopes W.
	Ascend 60 ft. over SW. slope.
46.00	Spur, slopes NW.; desc. 250 ft. over N. slope.
64.15	Wash, 10 lks. wide, course NW.; asc. 40 ft. over gradual S. slope.
80.00	Set an iron post, 3 ft. long, 2 ins. diam., 12 ins. in the ground to bedrock, and in a mound of stone to top, for cor. of secs. 2, 3, 10 and 11 with brass cap mkd.

Chains

T 9 S R 3 W  
 S 3 | S 2  
 S 10 | S 11  
 1934

raise a mound of stone, 2 ft. base, 1½ ft. high, W. of cor.

Land, rolling.  
 Soil, gravelly, 3rd rate and rocky, 4th rate.  
 Timber, scattering palo verde, ironwood and mesquite;  
 undergrowth, greasewood, sage brush and cactus.

S.89°55'E., on a random line bet. secs. 2 and 11.

- 40.00 Set temp. ¼ sec. cor.
- 79.82 Intersect N. and S. line, at the cor. of secs. 1, 2, 11 and 12.

Thence

N.89°55'W., on a true line bet. secs. 2 and 11.

Over level desert land, through scattering timber and undergrowth.

- 14.10 Wash, 40 lks. wide, course NW.
- 25.35 Enter same wash, 50 lks. wide course W.
- 35.35 Leave wash, course NW.
- 39.91 Set an iron post, 3 ft. long, 1 in. diam., 24 ins. in the ground, for ¼ sec. cor., with brass cap mkd.

¼ S 2.  
 S 11  
 1934

raise a mound of stone, 2 ft. base, 1½ ft. high, N. of cor.

- 63.70 Dim road, bears SE. and NW.
- 79.82 The cor. of secs. 2, 3, 10 and 11.

Land, level.  
 Soil, gravelly and rocky; 3rd rate.  
 Timber, scattering palo verde, ironwood and mesquite;  
 undergrowth, greasewood, sage brush and cactus.

N.0°03'W., on a random line bet. secs. 2 and 3.

- 40.00 Set temp. ¼ sec. cor.
- 80.00 Intersect N. bdy. of Tp., 40 lks. E. of the cor. of secs. 2, 3, 34 and 35; described in the field notes of the N. bdy. of T. 9 S., R. 3 W., surveyed under this group.

Thence


S.0°20'E., on a true line bet. secs. 2 and 3.

Over rolling desert land, through scattering timber and undergrowth.

Chains.	
15.00	Wash, 60 lks. wide, course W.
18.50	Wash, 30 lks. wide, course W.
37.50	Road, bears SE. and NW.
40.00	Set an iron post, 3 ft. long, 1 in. diam., 28 ins. in the ground, for $\frac{1}{4}$ sec. cor., with brass cap mkd.
	$\frac{1}{4}$
	S 3   S 2
	1934
	raise a mound
	of stone, 2 ft. base, $1\frac{1}{2}$ ft. high, W. of cor.
54.23	Wash, 70 lks. wide, course W.
65.23	Wash, 10 lks. wide, course NW.
68.70	Ascend 100 ft. over N. slope.
77.70	Ridge, bears E. and W.; desc. 70 ft. over S. slope.
80.00	The cor. of secs. 2, 3, 10 and 11.
	Land, rolling.
	Soil, gravelly; 3rd rate.
	Timber, scattering palo verde, ironwood and mesquite; undergrowth, greasewood, sage brush and cactus.
-----	
	From the standard cor. of secs. 33 and 34 on the S. bdy. of the Tp., which is an iron post, 2 ins. diam., firmly set in a mound of stone, 4 ft. base, $2\frac{1}{2}$ ft. high, mkd. and witnessed as described in the official record.
	N.0°02'W., bet. secs. 33 and 34.
	Over rolling and mountainous land, through scattering timber and undergrowth.
	Ascend 185 ft. over SW. slope.
12.75	Spur; slopes S.10°E.; continue ascending 85 ft. over gradual SE. slope.
31.30	Same spur, slopes S.10°W.; continue ascending 200 ft. over SW. slope.
40.00	Set an iron post, 3 ft. long, 1 in. diam., 28 ins. in the ground, for $\frac{1}{4}$ sec. cor., with brass cap mkd.
	$\frac{1}{4}$
	S 33   S 34
	1934.
	raise a mound
	of stone, 2 ft. base, $1\frac{1}{2}$ ft. high, W. of cor.
	The $\frac{1}{4}$ sec. cor. is located on ridge, bears E. and W.
	Descend 260 ft. over broken NW. slope.
51.55	Gulch, course NW.; asc. 190 ft. over SW. slope.

**Chains**

- 68.20 Rocky spur, slopes W.; desc. 35 ft. over NW. slope.
- 73.20 Small ravine, course W.; asc. 95 ft. over SW. slope.
- 79.20 Ridge, bears NW. and SE.; desc. 30 ft. over NE. slope.
- 80.00 Set an iron post, 3 ft. long, 2 ins. diam., 28 ins. in the ground, for cor. of secs. 27, 28, 33 and 34, with brass cap mkd.



raise a mound  
of stone; 2 ft. base, 1½ ft. high, W: of cor.

Land, rolling and mountainous.  
Soil, sandy, 3rd rate; and rocky, 4th rate.  
Timber, scattering palo verde, mesquite and ironwood;  
undergrowth, greasewood, sage brush, mesquite and iron-  
wood.

East on a random line bet: secs. 27 and 34.

- 40.00 Set temp. ¼ sec. cor.
- 80.26 Intersect N. and S. line, 14 lks. N. of the cor. of secs. 26, 27, 34 and 35.


Thence

N. 89° 54' W., on a true line bet. secs. 27 and 34.

Over rolling land, through scattering timber and under-  
growth.

Ascend 155 ft: over E. slope.

- 8.00 Ridge, bears N. and S.; desc. 455 ft. over W. slope.
- 39.15 Dim road, bears SE. and NW.
- 40.13 Set an iron post, 3 ft. long, 1 in. diam., 28 ins. in the ground, for ¼ sec. cor., with brass cap mkd.



raise a mound  
of stone, 2 ft. base, 1½ ft. high, N. of cor.

- 45.40 Wash, 80 lks. wide, course NW.; asc. 155 ft. over NE. slope.
- 57.55 Spur, slopes N.; desc. 65 ft. over NW. slope.
- 63.10 Wash, 30 lks. wide, course NW.; asc. 390 ft. over E. slope.
- 80.26 The cor. of secs. 27, 28, 33 and 34.

Land, rolling and mountainous..  
Soil, sandy, 3rd rate; and rocky, 4th rate.  
Timber, scattering palo verde, mesquite and ironwood;  
undergrowth, greasewood, sage brush, cactus and ocotillo.

Chains.	N.0°02'W., bet. secs. 27 and 28. Over mountainous land, through scattering timber and undergrowth. Descend 455 ft. over broken NE. slope.
9.55	Wash, 25 lks. wide, course E.
27.50	Base of slope, bears NW. and SE.; continue over level desert land.
36.20	Wash, 15 lks. wide, course NW.
40.00	Set an iron post, 3 ft. long, 1 in. diam., 28 ins. in the ground, for $\frac{1}{4}$ sec. cor., with brass cap mkd.
	$\frac{1}{4}$ S 28   S 27 1934
	raise a mound
42.30	of stone, 2 ft. base, $1\frac{1}{2}$ ft. high, W. of cor. Road, bears NW. and SE.
45.50	Wash, 50 lks. wide, course NW.
47.10	Wash, 50 lks. wide, course NW.
63.20	Wash, 50 lks. wide, course NW.; leave level land, bears NW. and SE.; asc. 125 ft. over SW. slope.
76.15	Spur, slopes W.; desc. 70 ft. over NW. slope.
86.00	Set an iron post, 3 ft. long, 2 ins. diam., 28 ins. in the ground, for cor. of secs. 21, 22, 27 and 28, with brass cap mkd.
	T 9 S R 3 W S 21   S 22 S 28   S 27 1934
	raise a mound
	of stone, 2 ft. base, $1\frac{1}{2}$ ft. high, W. of cor. Land, mountainous and level. Soil, sandy, 3rd rate; and rocky 4th rate. Timber, scattering palo verde, mesquite and ironwood; undergrowth; greasewood, sage brush and ecotillo.
-----	
	S. 89°54'E., on a random line bet. secs. 22 and 27.
40.00	Set temp. $\frac{1}{4}$ sec. cor.
80.18	Intersect N. and S. line, at the cor. of secs. 22, 23, 26 and 27.
	Thence
	N.89°54'W., on a true line bet. secs. 22 and 27.
	Over mountainous land, through scattering timber and undergrowth.
	Descend 215 ft. over SW. slope.
2.00	Top of bluff, 40 ft. high, faces SW.

Chains.

11.50 Base of slope, bears NW. and SE.; continue over level desert land.

12.90 Wash, 20 lks. wide, course N.

40.09 Set an iron post, 3 ft. long, 1 in. diam., 6 ins. in the ground to bedrock, and in a mound of stone to top, for 1/2 sec. cor., with brass cap mkd.

1/4 S 22  
S 27  
1934

raise a mound of stone, 2 ft. base, 1 1/2 ft. high, N. of cor.

45.30 Wash, 5 lks. wide, course N.

58.00 Wash, 10 lks. wide, course N.

69.50 Wash, 10 lks. wide, course N.

80.18 The cor. of secs. 21, 22, 27 and 28.

Land, mountainous and level.  
Soil, sandy, 3rd rate; and rocky, 4th rate.  
Timber, scattering palo verde, mesquite and ironwood;  
undergrowth, greasewood, sage brush, cactus and ocotillo.

N.0°02'W., bet. secs. 21 and 22.

Over rolling desert land, through scattering timber and undergrowth.

Descend 65 ft. over gradual N. slope.

40.00 Set an iron post, 3 ft. long, 1 in. diam., 6 ins. in the ground to bedrock, and in a mound of stone to top, for 1/4 sec. cor., with brass cap mkd,

1/4  
S 21 | S 22  
1934

raise a mound of stone, 2 ft. base, 1 1/2 ft. high, W. of cor.

60.00 Top of low ridge, 50 ft. high, bears NW. and SE.

69.29 Wash, .50 lks. wide, course NW.

80.00 Set an iron post, 3 ft. long, .2 ins. diam., 6 ins. in the ground to bedrock, and in a mound of stone to top, for cor. of secs. 15, 16, 21 and 22, with brass cap mkd,

T 9 S R 3 W  
S 16 | S 15  
S 21 | S 22  
1934

raise a mound of stone, 2 ft. base, 1 1/2 ft. high; W. of cor.

Land, rolling.  
Soil, sandy, 3rd rate; and rocky, 4th rate.

Chains.	Timber, scattering palo verde, ironwood and mesquite; undergrowth, greasewood, sage brush and cactus.
	-----
	S.89°54'E., on a random line bet. secs. 15 and 22.
40.00	Set temp. $\frac{1}{4}$ sec. cor.
80.28	Intersect N. and S. line, 2 lks. N. of the cor. of secs. 14,15,22 and 23.
	Thence
	N.89°53'W., on a true line bet. secs. 15 and 22.
	Over rolling desert land, through scattering timber and undergrowth.
	Descend 70 ft. over gradual W. slope.
32.80	Wash, 30 lks. wide, course SW.; asc. 130 ft. over E. slope.
37.70	Bluff, 40 ft. high, faces E.
38.30	Spur, slopes S.; desc. 65 ft. over SW. slope.
40.14	Set an iron post, 3 ft. long, 1 ins. diam., 6 ins. in the ground to bedrock, and in a mound of stone to top, for $\frac{1}{4}$ sec. cor., with brass cap mkd.
	$\frac{1}{4} \frac{S 15}{S 22}$ 1934
	raise a mound
	of stone, 2 ft. base, $1\frac{1}{2}$ ft. high, N. of cor.
	Continue descending 50 ft. over SW. slope.
42.25	Ravine, course S.; asc. 105 ft. over SE. slope,
46.75	Rocky spur, slopes SW.
55.90	Wash, 10 lks. wide, course S.; asc. 85 ft. over broken SW. slope.
65.60	Spur, slopes S.; desc. 20 ft. over SW. slope.
80.28	The cor. of secs. 15,16,21 and 22.
	Land, rolling.
	Soil, sandy, 3rd rate; and rocky, 4th rate.
	Timber, scattering palo verde, mesquite and ironwood; undergrowth, greasewood, sage brush and cactus.
	-----
	N.0°02'W., bet. secs. 15 and 16.
	Over rolling desert hills, through scattering timber and undergrowth.
23.50	Wash, 10 lks. wide, course SW.; asc. 155 ft. over S. slope.
28.30	Rocky spur, slopes W.; desc. 85 ft. over N. slope.
33.70	Base of slope, bears E. and W.; asc. 65 ft. over S. slope.

Chains.  
38.40

Rocky spur, slopes NW.; desc. 40 ft. over NE. slope.

40.00

Set an iron post, 3 ft. long, 1 in. diam., 6 ins. in the ground to bedrock, and in a mound of stone to top, for  $\frac{1}{4}$  sec. cor., with brass cap mkd.

$\frac{1}{4}$   
S 16 | S 15  
1934

of stone; 2 ft. base,  $1\frac{1}{2}$  ft. high, W. of cor. raise a mound

Continue descending 160 ft. over NE. slope.

61.50

Wash, 30 lks. wide, course NW.

77.50

Wash, 15 lks. wide, course W.

79.40

Set an iron post, 3 ft. long, 2 ins. diam., 28 ins. in the ground, for witness cor. of secs. 9, 10, 15 and 16, with brass cap mkd.

W C  
T 9 S R 3 W  
S 9 | S 10  
S 16 | S 15  
1934

from which

A mesquite, 10 ins. diam., bears N.69°E., 66 lks. dist., mkd. WC T 9 S R 3 W S 10 B T.

A palo verde, 8 ins. diam., bears S.44°E., 45 lks. dist., mkd. WC T 9 S R 3 W S 15 B T.

An ironwood, 8 ins. diam., bears N.39°W., 79 lks. dist., mkd. WC T 9 S R 3 W S 9 B T.

Raise a mound of stone, 2 ft. base,  $1\frac{1}{2}$  ft. high, W. of cor.

80.00

True point for cor. of secs. 9, 10, 15 and 16, falls in wash, 50 lks. wide, course W.

Land, rolling desert hills.  
Soil, sandy, 3rd rate; and rocky, 4th rate.  
Timber, scattering palo verde, ironwood and mesquite; undergrowth; greasewood, sage brush and cactus.

S.89°53'E., on a random line bet. secs. 10 and 15.

40.00

Set temp.  $\frac{1}{4}$  sec. cor.

80.32

Intersect N. and S. line, 5 lks. S. of the true point for cor. of secs. 10, 11, 14 and 15.

Thence

N.89°55'W., on a true line bet. secs. 10 and 15.

Over level desert land, through scattering timber and undergrowth,

Along irregular wash, 50 lks. wide, course W.

Chains. 40.16	<p>Set an iron post, 3 ft. long, 1 in. diam., 28 ins. in the ground, for <math>\frac{1}{4}</math> sec. cor., with brass cap mkd.</p> <p style="text-align: center;"><math>\frac{1}{4}</math> S 10 S 15 1934</p> <p style="text-align: right;">raise a mound</p> <p>of stone, 2 ft. base, <math>1\frac{1}{2}</math> ft. high, N. of cor.</p>
80.32	<p>The true point for cor. of secs. 9, 10, 15 and 16.</p> <p>Land, level and rolling. Soil, sandy; 3rd rate. Timber, scattering, palo verde, ironwood and mesquite; undergrowth, greasewood, sage brush and cactus.</p> <hr/> <p>N.0°02'W., bet. secs. 9 and 10.</p> <p>Over rolling desert land, through scattering timber and undergrowth.</p>
7.20	Wash, 10 lks. wide, course W.
18.20	Wash, 10 lks. wide, course W.
40.00	<p>Set an iron post, 3 ft. long, 1 in. diam., 28 ins. in the ground, for <math>\frac{1}{4}</math> sec. cor., with brass cap mkd.</p> <p style="text-align: center;"><math>\frac{1}{4}</math> S 9   S 10 1934</p> <p style="text-align: right;">raise a mound</p> <p>of stone, 2 ft. base, <math>1\frac{1}{2}</math> ft. high, W. of cor.</p>
41.00	Wash, 10 lks. wide, course NW.
47.80	Wash, 20 lks. wide, course NW.
51.30	Wash, 40 lks. wide, course NW.
74.70	Wash, 30 lks. wide, course W.
80.00	<p>Set an iron post, 3 ft. long, 2 ins. diam., 28 ins. in the ground, for cor. of secs. 3, 4, 9 and 10, with brass cap mkd.</p> <p style="text-align: center;">T 9 S R 3 W S 4   S 3 S 9   S 10 1934</p> <p style="text-align: right;">raise a mound</p> <p>of stone, 2 ft. base, <math>1\frac{1}{2}</math> ft. high, W. of cor.</p> <p>Land, rolling. Soil, sandy; 3rd rate. Timber, scattering palo verde, mesquite and ironwood; undergrowth, greasewood, sage brush cactus and ocotillo.</p> <hr/> <p>S.89°55'E., on a random line bet. secs. 3 and 10.</p>
40.00	Set temp. $\frac{1}{4}$ sec. cor.

Chains.  
80.38

Intersect N. and S. line, 7 lks. N. of the cor. of secs. 2, 3, 10 and 11.

Thence

N.89°52'W., on a true line bet. secs. 3 and 10.

Over rolling and level desert land, through scattering timber and undergrowth.

Descend 40 ft. over SW. slope.

5.00 Base of slope, bears N. and S.; continue over level land.

28.00 Wash, 20 lks. wide, course N.70°W.

40.19 Set an iron post, 3 ft. long, 1 in. diam., 28 ins. in the ground for 1/4 sec. cor., with brass cap mkd.

1/4 S 3  
S 10  
1934

raise a mound of stone, 2 ft. base, 1 1/2 ft. high, N. of cor.

63.20 Wash, 20 lks. wide, course SW.; continue over rolling land.

80.38 The cor. of secs. 3, 4, 9 and 10.

Land, level and rolling.

Soil, sandy, 3 rd rate; and rocky, 4th rate.

Timber, scattering palo verde, ironwood and mesquite; undergrowth, greasewood, sage brush and cactus.

N.0°20'W., on a random line bet. secs. 3 and 4.

40.00 Set temp. 1/4 sec. cor.

79.86 Intersect N. bdy. of Tp., 46 lks. W. of the cor. of secs. 3, 4, 33 and 34; described in the field notes of the N. bdy. of T. 9 S., R. 3 W., surveyed under this group.

Thence

South, on a true line bet. secs. 3 and 4.

Over level desert land, through scattering timber and undergrowth.

2.35 Wash, 50 lks. wide, course W.

7.35 Wash, 50 lks. wide, course W.

19.85 Wash, 10 lks. wide, course W.

36.15 Wash, 20 lks. wide, course NW.

39.86 Set an iron post, 3 ft. long, 1 in. diam., 18 ins. in the ground to bedrock, and in a mound of stone to top, for 1/4 sec. cor., with brass cap mkd.

1/4  
S 4 | S 3

1934

Chains.	raise a mound of stone, 2 ft. base, 1½ ft. high, W. of cor.
49.85	Wash, 10 lks. wide, course W.
79.86	The cor. of secs. 3, 4, 9 and 10.
	Land, level. Soil, sandy, 3rd rate; and rocky, 4th rate. Timber, scattering palo verde, ironwood and mesquite; undergrowth, greasewood, sage brush and cactus.
-----	
	From the standard cor. of secs. 32 and 33 on the S.bdy. of the Tp., which is an iron post, 3 ins. diam., 12 ins. above ground, firmly set, mkd. and witnessed as described in the official record.
	N.0°02'W., bet. secs. 32 and 33.
	Over rolling desert land, through scattering timber and undergrowth.
22.30	Wash, 30 lks. wide, course W.
40.00	Set an iron post, 3 ft. long, 1 in. diam., 28 ins. in the ground, for ¼ sec. cor., with brass cap mkd.
	$\frac{1}{4}$ S 32   S 33 1934
	raise a mound of stone, 2 ft. base, 1½ ft. high, W. of cor.
42.00	Wash, 30 lks. wide, course NE.
69.00	Dim road, bears NE. and SW.
80.00	Set an iron post, 3 ft. long, 2 ins. diam., 28 ins. in the ground, for cor. of secs. 28, 29, 32 and 33, with brass cap mkd.
	T 9 S R 3 W S 29   S 28 S 32   S 33 1934
	raise a mound of stone, 2 ft. base, 1½ ft. high, W. of cor.
	Land, rolling. Soil, rocky; 4th rate. Timber, scattering palo verde, ironwood and mesquite; undergrowth, greasewood, sage brush and cactus.
-----	
	East on a random line bet. secs. 28 and 33.
40.00	Set temp. ¼ sec. cor.
79.90	Intersect N. and S. line, at the cor. of secs. 27, 28, 33 and 34.
	Thence West, on a true line bet. secs. 28 and 33.

Subdivision of T. 9 S., R. 3 W.

Chains.

T 9 S R 3 W

S 20 | S 21

S 29 | S 28

1934

raise a mound of stone, 2 ft. base, 1 1/2 ft. high, W. of cor.

Land, level.

Soil, gravelly; 3rd rate.

Timber, very scattering palo verde, ironwood and mesquite; undergrowth, greasewood, catclaw and cactus.

East, on a random line bet. secs. 21 and 28.

40.00 Set temp. 1/4 sec. cor.

79.82 Intersect N. and S. line, 9 lks. N. of the cor. of secs. 21, 22, 27 and 28.

Thence

N. 89° 56' W., on a true line bet. secs. 21 and 28.

Over rolling desert land, through scattering timber and undergrowth.

Along N. slope.

1.35 Spur, slopes N.; desc. 80 ft. over NW. slope.

23.80 Wash, 90 lks. wide, course NW.

39.91 Set an iron post, 3 ft. long, 1 in. diam., 27 ins. in the ground, for 1/4 sec. cor., with brass cap mkd.

1/4 S 21

S 28

1934

raise a mound of stone, 2 ft. base, 1 1/2 ft. high, N. of cor.

43.80 Road, bears NW. to Gila Bend, and SE. to Papago Indian Reservation.

64.80 Wash, 20 lks. wide, course N.

73.80 Wash, 30 lks. wide, course NE.

79.82 The cor. of secs. 20, 21, 28 and 29:

Land, level:

Soil, sandy and gravelly; 3rd rate.

Timber, scattering palo verde, ironwood and mesquite; undergrowth, greasewood, catclaw and cactus.

N. 0° 02' W., bet. secs. 20 and 21.

Over rolling desert land, through scattering timber and undergrowth.

21.50 Wash, 15 lks. wide, course NW.; asc. 55 ft. over S. slope.

36.95 Spur, slopes E.; desc. 30 ft. over NE. slope.

Chains.	Over mountainous land, through scattering timber and undergrowth, Ascend 20 ft. over E. slope.
1.45	Spur, slopes NW.; desc. 430 ft. over SW. slope.
16.85	Wash, 15 lks. wide, course NW.; asc. 65 ft. over E. slope.
20.50	Spur, slopes N.; desc. 75 ft. over NW. slope.
22.00	Base of slope, bears N. and S.; asc. 140 ft. over SE. slope.
38.25	Spur, slopes S.
39.95	Set an iron post, 3 ft. long, 1 in. diam., on surface rock, with a cross X, mkd. at the base, and in a mound of stone to top, for $\frac{1}{4}$ sec. cor., with brass cap mkd. $\begin{array}{r} \frac{1}{4} \text{ S } 28 \\ \text{S } 33 \\ 1934 \end{array}$
	raise a mound of stone, 2 ft. base, $1\frac{1}{2}$ ft. high, N. of cor. Descend 215 ft. over W. slope.
53.70	Wash, 25 lks. wide, course N.; continue over level land.
61.90	Wash, 50 lks. wide, course NE.
79.90	The cor. of secs. 28, 29, 32 and 33. Land, mountainous and level. Soil, sandy; 3rd rate; and rocky, 4th rate. Timber, scattering palo verde, ironwood and mesquite; undergrowth, greasewood, sage brush and cactus.
-----	
	N.0°02'W.; bet. secs. 28 and 29. Over level desert land, through scattering timber and undergrowth.
40.00	Set an iron post, 3 ft. long, 1 in. diam., 18 ins. in the ground to bedrock, and in a mound of stone to top, for $\frac{1}{4}$ sec. cor., with brass cap mkd. $\begin{array}{r} \frac{1}{4} \\ \text{S } 29 \text{   } \text{S } 28 \\ 1934 \end{array}$
	raise a mound of stone, 2 ft. base, $1\frac{1}{2}$ ft. high, W. of cor.
50.00	Wash, 10 lks. wide, course NW.
64.90	Wash, 15 lks. wide, course W. for 8 chs. thence N.
80.00	Set an iron post, 3 ft. long, 2 ins. diam., 18 ins. in the ground to bedrock, and in a mound of stone to top, for cor. of secs. 20, 21, 28 and 29, with brass cap mkd.

Chains.  
40.00

Set an iron post, 3 ft. long, 1 in. diam., 14 ins. in the ground to bedrock, and in a mound of stone to top, for  $\frac{1}{4}$  sec. cor., with brass cap mkd.

$\frac{1}{4}$   
S 20 | S 21

1934

raise a mound of stone, 2 ft. base,  $1\frac{1}{2}$  ft. high, W. of cor.

Continue over level land.

49.90

Road, bears NW. to Gila Bend, and SE. to Papago Indian Reservation.

54.50

Wash, 60 lks. wide, course NW.

80.00

Set an iron post, 3 ft. long, 2 ins. diam., 28 ins. in the ground, for cor. of secs. 16, 17, 20 and 21, with brass cap mkd.

T 9 S R 3 W  
S 17 | S 16  
S 20 | S 21  
1934

raise a mound of stone, 2 ft. base,  $1\frac{1}{2}$  ft. high, W. of cor.

Land, rolling and level.  
Soil, sandy and gravelly; 3rd rate.  
Timber, scattering palo verde, ironwood and mesquite; undergrowth, greasewood, sage brush and cactus.

s.89°56'E., on a random line bet. secs. 16 and 21.

40.00

Set temp.  $\frac{1}{4}$  sec. cor.

79.70

Intersect N. and S. line, 7 lks. S. of the cor. of secs. 15, 16, 21 and 22.

Thence

N.89°59'W., on a true line bet. secs. 16 and 21.

Over level desert land, through scattering timber and undergrowth.

6.20

Wash, 30 lks. wide, course N.40°W.

8.10

Wash, 15 lks. wide, course N.20°W.; continue over rolling land.

39.85

Set an iron post, 3 ft. long, 1 in. diam., 27 ins. in the ground, for  $\frac{1}{4}$  sec. cor., with brass cap mkd.

$\frac{1}{4}$  S 16  
S 21  
1934

raise a mound of stone, 2 ft. base,  $1\frac{1}{2}$  ft. high, N. of cor.

59.90

Wash, 25 lks. wide, course N.20°W.

Chains. 79.70	<p>The cor. of secs. 16,17,20 and 21.</p> <p>Land, level. Soil, gravelly and sandy; 3rd rate. Timber, scattering palo verde, ironwood and mesquite; undergrowth, greasewood, sage brush and cactus.</p> <hr/> <p>N.0°02'W., bet. secs. 16 and 17.</p> <p>Over level desert land, through scattering timber and undergrowth.</p>
25.90	Wash, 15 lks. wide, course N.10°W:
40.00	<p>Set an iron post, 3 ft. long, 1 in. diam., 27 ins. in the ground, for <math>\frac{1}{4}</math> sec. cor., with brass cap mkd.</p> <p style="text-align: center;"><math>\frac{1}{4}</math></p> <p style="text-align: center;">S 17   S 16</p> <p style="text-align: center;">1934</p> <p style="text-align: right;">raise a mound of stone, 2 ft. base, <math>1\frac{1}{2}</math> ft. high, W. of cor.</p>
80.00	<p>Set an iron post, 3 ft. long, 2 ins. diam., 28 ins. in the ground, for cor. of secs. 8,9,16 and 17, with brass cap mkd.</p> <p style="text-align: center;">T 9 S R 3 W S 8   S 9 S 17   S 16 1934</p> <p style="text-align: right;">raise a mound of stone, 2 ft. base, <math>1\frac{1}{2}</math> ft. high, W. of cor.</p> <p>Land, level. Soil, gravelly and sandy; 3rd rate. Timber, scattering palo verde, ironwood and mesquite; undergrowth, greasewood, sage brush and cactus.</p> <hr/> <p>S.89°59'E., on a random line bet. secs. 9 and 16.</p>
40.00	Set temp. $\frac{1}{4}$ sec. cor.
79.62	<p>Intersect N. and S. line, at the true point for cor. of secs. 9,10,15 and 16.</p> <p>Thence</p> <p>N.89°59'W., on a true line bet. secs. 9 and 16.</p> <p>Over level desert land, through scattering timber and undergrowth:</p>
7.80	Wash, 35 lks. wide, course NW.
10.80	Same wash, 35 lks. wide, course SW.
34.60	Wash, 50 lks. wide, course N.10°W.
39.81	Set an iron post, 3 ft. long, 1 in. diam., 27 ins. in the ground, for $\frac{1}{4}$ sec. cor., with brass cap mkd.

Chains.

$\frac{1}{4}$  S 9  
S 16  
1934

raise a mound of stone, 2 ft. base,  $1\frac{1}{2}$  ft. high, N. of cor.

51.20 Wash, 15 lks. wide, course N.10°W.

79.62 The cor. of secs. 8,9,16 and 17.

Land, level.  
Soil, gravelly and sandy; 3rd rate.  
Timber, very scattering palo verde, ironwood and mesquite;  
undergrowth, greasewood, sage brush and cactus.

N:0°02'W., bet. secs. '8 and '9.

Over level desert land, through scattering timber and undergrowth.

6.50 Wash, 10 lks. wide, course NW.

34.40 Wash, 20 lks. wide, course NW.

36.10 Wash, 80 lks. wide, course NW.

40.00 Set an iron post, 3 ft. long, 1 in. diam., 28 ins. in the ground, for  $\frac{1}{4}$  sec. cor., with brass cap mkd.

$\frac{1}{4}$   
S 8 | S 9  
1934

raise a mound of stone, 2 ft. base,  $1\frac{1}{2}$  ft. high, W. of cor.

44.30 Wash, 20 lks. wide, course NW.

50.00 Wash, 20 lks. wide, course W.

71.60 Wash, 10 lks. wide, course NW.

77.50 Wash, 30 lks. wide, course W.

80.00 Set an iron post, 3 ft. long, 2 ins. diam., 28 ins. in the ground, for cor. of secs. 4,5,8 and 9, with brass cap mkd.

T 9 S R 3 W  
S 5 | S 4  
S 8 | S 9  
1934

raise a mound of stone, 2 ft. base,  $1\frac{1}{2}$  ft. high, W. of cor.

Land, level.  
Soil, sandy, 3rd rate; and rocky; 4th rate.  
Timber, scattering palo verde, ironwood and mesquite;  
undergrowth, greasewood, catclaw, sage and cactus.

## Subdivision of T.9 S., R.3 W.

BOOK 4062

Chains	S.89° 59'E., on a random line bet. secs. 4 and 9.
40.00	Set temp. $\frac{1}{4}$ sec. cor.
79.70	Intersect N. and S. line, 14 lks. N. of the cor. of secs. 3, 4, 9 and 10.
	Thence
	N.89° 53'W., on a true line bet. secs. 4 and 9.
	Over level desert land, through scattering timber and undergrowth.
20.70	Wash, 20 lks. wide, course N.70°W.
39.85	Set an iron post, 3 ft. long, 1 in. diam., 28 ins in the ground, for $\frac{1}{4}$ sec. cor. with brass cap mkd.
	$\begin{array}{r} \frac{1}{4} \text{ S } 4 \\ \frac{1}{4} \text{ S } 9 \\ \hline 1934 \end{array}$
	raise a mound
	of stone, 2 ft. base, $1\frac{1}{2}$ ft. high N. of cor.
57.60	Wash, 20 lks. wide, course SW.
78.30	Wash, 15 lks. wide, course SW.
79.70	The cor. of secs. 4, 5, 8 and 9.
	Land, level.
	Soil, sandy, 3rd rate; rocky, 4th rate.
	Timber, scattering palo verde, ironwood and mesquite;
	undergrowth, greasewood, sage brush and cactus.
	-----
	North, on a random line bet. secs. 4 and 5.
40.00	Set temp $\frac{1}{4}$ sec. cor.
79.76	Intersect N. bdy. of Tp., 23 lks. E. of the cor. of secs. 4, 5, 32 and 33; described in the field notes of the N. bdy. of T.9 S., R.3 W., surveyed under this group.
	Thence
	S.0° 10'E., on a true line bet. secs. 4 and 5.
	Over level desert land, through scattering timber and undergrowth.
16.40	Wash, 10 lks. wide, course W.
25.70	Wash, 10 lks. wide, course W.
39.76	Set an iron post, 3 ft. long, 1 in. diam., 28 ins. in the ground, for $\frac{1}{4}$ sec. cor., with brass cap mkd.
	$\begin{array}{r} \frac{1}{4} \\ \text{S } 5 \text{   } \text{S } 4 \\ \hline 1934 \end{array}$
	raise a mound
	of stone, 2 ft. base, $1\frac{1}{2}$ ft. high, W. of cor.
44.70	Wash, 10 lks. wide, course W.

## Chains

79.76

The cor. of secs. 4, 5, 8 and 9.

Land, level.

Soil, sandy and gravelly; 3rd rate.

Timber, scattering palo verde, ironwood and mesquite; undergrowth, greasewood, sage brush and cactus.

-----

From the standard cor. of secs. 31 and 32 on the S. bdy. of the Tp.; described in the field notes of a portion of the 2nd standard parallel south, through R. 3 W., resurveyed under this group.

N.0°03'W., bet. secs. 31 and 32.

Over level desert land, through scattering timber and undergrowth.

40.00 Set an iron post, 3 ft. long, 1 in. diam., 27 ins. in the ground, for  $\frac{1}{4}$  sec. cor., with brass cap mkd.

$\frac{1}{4}$   
 S 31 | S 32  
 1934

raise a mound

of stone, 2 ft. base,  $1\frac{1}{2}$  ft. high, W. of cor.

50.00 Leave level land, bears NW. and SE.; asc. 230 ft. over SW. slope.

70.67 Ridge, bears NW. and SE.; desc. 140 ft. over NE. slope.

80.00 Mark a malpais stone in place, 12 ins square, 6 ins. above ground, with a cross X on top, 1 groove on S. and 5 grooves on E. face, for cor. of secs. 29, 30, 31 and 32, and raise a mound of stone, 2 ft. base,  $1\frac{1}{2}$  ft. high, W of cor.

Land, level and hilly.

Soil, gravelly, 3rd rate; and rocky, 4th rate.

Timber, scattering palo verde and mesquite; undergrowth, greasewood, sage brush and cactus.

-----

East, on a random line bet. secs. 29 and 32.

40.00 Set temp.  $\frac{1}{4}$  sec. cor.

80.04 Intersect N. and S. line, at the cor. of secs. 28, 29, 32 and 33.

Thence

West, on a true line bet. secs. 29 and 32.

Over level and rolling desert land, through scattering timber and undergrowth.

31.25 Wash, 20 lks. wide, course N.15°W.

40.02 Set an iron post, 3 ft. long, 1 in. diam., 27 ins. in the ground, for  $\frac{1}{4}$  sec. cor., with brass cap mkd.

Chains.	$\frac{1}{4}$ S 29 S 32 1934
	raise a mound of stone, 2 ft. base, $1\frac{1}{2}$ ft. high, N. of cor.
47.70	Wash, 20 lks. wide, course N.25°E.
65.10	Ascend 80 ft. over NE. slope.
80.04	The cor. of secs. 29,30,31 and 32.
	Land, level and rolling. Soil, gravelly; 3rd rate. Timber, scattering palo verde, ironwood and mesquite; undergrowth, greasewood, sage brush and cactus.
	-----
	West on a random line bet. secs. 30 and 31.
40.00	Set temp. $\frac{1}{4}$ sec. cor.
80.01	Intersect W. bdy. of Tp., at the cor. of secs. 25,30,31 and 36; described in the field notes of the W. bdy. of T. 9 S., R. 3 W., surveyed under this group.
	Thence
	East on a true line bet. secs. 30 and 31.
	Over rolling desert land, through scattering timber and undergrowth.
12.05	Wash, 30 lks. wide, course S.
40.01	Set an iron post, 3 ft. long, 1 in. diam., 20 ins. in the ground to bedrock, and in a mound of stone to top, for $\frac{1}{4}$ sec. cor., with brass cap mkd.
	$\frac{1}{4}$ S 30 S 31 1934
	raise a mound of stone, 2 ft. base, $1\frac{1}{2}$ ft. high, N. of cor.
68.65	Wash, 35 lks. wide, course N.20°E.; asc. 90 ft. over NW. slope.
75.00	Spur, slopes N.; desc. 30 ft. over NE. slope.
80.01	The cor. of secs. 29,30,31 and 32.
	Land, rolling. Soil, rocky; 4th rate. Timber, scattering palo verde, ironwood and mesquite; undergrowth, greasewood, sage brush and cactus.
	-----
	N.0°03'W., bet. secs. 29 and 30.
	Over mountainous land, through scattering timber and undergrowth.
	Descend 75 ft. over N. slope.
10.00	Base of slope, bears NW. and SE.; continue over level land.

Chains.	
13.95	Wash, 25 lks. wide, course NE.
25.00	Leave level land, bears NE. and SW.; asc. 365 ft. over SE. slope.
40.00	Set an iron post; 3 ft. long, 1 in. diam., 14 ins. in the ground to bedrock, and in a mound of stone to top, for $\frac{1}{4}$ sec. cor.; with brass cap mkd.
	$\frac{1}{4}$ S 30   S 29 1934
	raise a mound of stone, 2 ft. base, $1\frac{1}{2}$ ft. high, W. of cor.
	Ascend 25 ft. over SE. slope.
45.00	Ridge, bears E. and W.; desc. 325 ft. over N. slope.
61.70	Base of slope, bears SE. and NW.; asc. 230 ft. over S. slope.
72.50	Spur, slopes S. $10^{\circ}$ E.; desc. 105 ft. over NE. slope.
77.95	Wash, 15 lks. wide, course S. $20^{\circ}$ E.; asc. 50 ft. over SE. slope.
80.00	Set an malpais stone; 20x8x8 ins. 14 ins. in the ground, for cor. of secs. 19, 20, 29 and 30, mkd. with 2 notches on S. and 5 notches on E. face; and raise a mound of stone, 2 ft. base, $1\frac{1}{2}$ ft. high, W. of cor.
	Land, mountainous. Soil, rocky; 4th rate. Timber, scattering palo verde, and mesquite; undergrowth, greasewood, catclaw and cactus.
	-----
	East on a random line bet. secs. 20 and 29.
40.00	Set temp. $\frac{1}{4}$ sec. cor.
80.20	Intersect N. and S. line, 16 lks. N. of the cor. of secs. 20, 21, 28 and 29.
	Thence
	N. $89^{\circ}53'$ W., on a true line bet. secs. 20 and 29.
	Over rolling hills, through scattering timber and undergrowth.
11.25	Wash, 50 lks. wide, course NW.; asc. 230 ft. over NE. slope.
33.75	Ridge, bears NW. and SE.; desc. 160 ft. over SW. slope.
40.10	Set an iron post, 3 ft. long, 1 in. diam., 7 ins. in the ground to bedrock, and in a mound of stone to top, for $\frac{1}{4}$ sec. cor., with brass cap mkd.
	$\frac{1}{4}$ S 20 S 29 1934

Chains	<p>of stone, 2 ft. base, 1½ ft. high, N. of cor. raise a mound</p> <p>Continue descending 110 ft. over SW. slope.</p>
62.00	<p>Base, of slope, bears NW. and SE.; asc. 170 ft. over SE. slope.</p>
80.20	<p>The cor. of secs. 19, 20, 29 and 30.</p> <p>Land, rolling. Soil, rocky; 4th rate. Timber, scattering palo verde and mesquite; undergrowth, greasewood, sage brush and cactus.</p> <p>-----</p> <p>West on a random line bet. secs. 19 and 30.</p>
40.00	<p>Set tmp. ¼ sec. cor.</p>
80.08	<p>Intersect W. bdy. of Tp., 12 lks. N. of the cor. of secs. 19, 24, 25 and 30; described in the field notes of the W. bdy. of T. 9 S., R. 3 W., surveyed under this group.</p> <p>Thence</p> <p>N. 89° 55' E., on a true line bet. secs. 19 and 30.</p> <p>Over mountainous land, through scattering timber and undergrowth.</p> <p>Ascend 95 ft. over NW. slope.</p>
13.10	<p>Spur, slopes N.; desc. 20 ft. over NE. slope.</p>
17.10	<p>Ravine, course N.; asc. 118 ft. over NW. slope.</p>
19.50	<p>Spur, slopes NE.; desc. 340 ft. over NE. slope.</p>
40.08	<p>Set an iron post, 3 ft. long, 1 in. diam., 6 ins. in the ground to bedrock, and in a mound of stone to top, for ¼ sec. cor., with brass cap mkd.</p> <p style="text-align: center;"> <math display="block">\frac{1}{4} \begin{array}{l} S 19 \\ S 30 \\ 1934 \end{array}</math> </p> <p>raise a mound</p> <p>of stone, 2 ft. base, 1½ ft. high, N. of cor.</p> <p>Continue descending 170 ft. over NE. slope.</p>
50.40	<p>Wash, 30 lks. wide, course S.; asc. 310 ft. over SW. slope.</p>
64.10	<p>Spur, slopes SE.; desc. 230 ft. over NE. slope.</p>
77.30	<p>Ravine, course SE.</p>
80.08	<p>The cor. of secs. 19, 20, 29 and 30.</p> <p>Land, mountainous. Soil, rocky; 4th rate. Timber, scattering palo verde and mesquite; undergrowth, greasewood, sage brush and cactus.</p> <p>-----</p>

Chains.	N.0°03'W., bet. secs. 19 and 20. Over mountainous land, through scattering timber and undergrowth. Ascend 70 ft. over SE. slope.
2.07	Spur, slopes SE.; desc. 130 ft. over NE. slope.
11.36	Wash, 15 lks. wide, course E.; asc. 140 ft. over SE. slope.
19.58	Ridge, bears E. and W.; desc. 140 ft. over NE. slope.
40.00	Set an iron post, 3 ft. long, 1 in. diam., on surface rock, with a cross X, mkd. at the base, and in a mound of stone to top, for $\frac{1}{4}$ sec. cor., with brass cap mkd. $\frac{1}{4}$ S 19   S 20 1934 raise a mound of stone, 2 ft. base, $1\frac{1}{2}$ ft. high, W. of cor.
	Continue descending 260 ft. over NE. slope..
54.66	Base of slope, bears SW. and NE.; continue over level land.
80.00	Set a malpais stone, 20x8x6 ins., 14 ins. in the ground, for cor. of secs. 17, 18, 19 and 20, mkd. with a cross X on top, 3 grooves on S. and 5 grooves on E. face; and raise a mound of stone, 2 ft. base, $1\frac{1}{2}$ ft. high, W. of cor. Land, mountainous and level. Soil, rocky; 4th rate.. Timber, scattering palo verde; undergrowth, greasewood and cactus.
	S.89°53'E., on a random line bet. secs. 17 and 20.
40.00	Set temp. $\frac{1}{4}$ sec. cor.
80.24	Intersect N. and S. line, 19 lks. N. of the cor. of secs. 16, 17, 20 and 21, Thence N.89°45'W., on a true line bet. secs. 17 and 20. Over level desert land, through scattering timber and undergrowth.
12.74	Wash, 80 lks. wide, course N.
16.74	Wash, 20 lks. wide, course NW.
40.12	Set an iron post, 3 ft. long, 1 in. diam., 28 ins. in the ground, for $\frac{1}{4}$ sec. cor., with brass cap mkd. $\frac{1}{4}$ S 17 S 20 1934 raise a mound of stone, 2 ft. base, $1\frac{1}{2}$ ft. high, N. of cor.

Chains.	
40.15	Dim road, bears NW. and SE.
50.24	Wash, 50 lks. wide, course N.70°W.
55.24	Wash, 50 lks. wide, course NW.
70.74	Wash, 60 lks. wide, course NW.
80.24	The cor. of secs. 17,18,19 and 20.
	Land, level. Soil, sandy and gravelly; 3rd rate. Timber, scattering palo verde, ironwood and mesquite; undergrowth, greasewood, sage brush and cactus.
	S.89°55'W., on a random line bet. secs. 18 and 19.
40.00	Set temp. $\frac{1}{4}$ sec. cor.
79.96	Intersect W. bdy. of Tp., 23 lks. N. of the cor. of secs. 13,18,19 and 24 ; described in the field notes of the W. bdy. of T. 9 S., R. 3 W., surveyed under this group.
	Thence
	N.89°45'E., on a true line bet. secs. 18 and 19.
	Over rolling land, through scattering timber and undergrowth.
	Ascend 65 ft. over NW. slope.
7.55	Spur, slopes NE.; desc. 490 ft. over E. slope.
24.75	Wash, 30 lks. wide, course NE.; continue descending 110 ft. over NE. slope.
39.96	Set a malpais stone, 20x10x6 ins., 12 ins. in the ground, for $\frac{1}{4}$ sec. cor., mkd. $\frac{1}{4}$ on N. face; and raise a mound of stone, 2 ft. base, $1\frac{1}{2}$ ft. high, N. of cor.
40.96	Wash, 20 lks. wide, course N.
69.96	Wash, 20 lks. wide, course N.; continue over level land.
79.96	The cor. of secs. 17,18,19 and 20.
	Land, rolling and level. Soil, sandy, 2nd rate; and gravelly, 3rd rate. Timber, scattering palo verde, ironwood and mesquite; undergrowth, greasewood, sage brush and cactus.
	N.0°03'W., bet. secs. 17 and 18.
	Over level desert land, through scattering timber and undergrowth.
15.00	Wash, 90 lks. wide, course NW.
40.00	Set an iron post, 3 ft. long, 1 in. diam., 27 ins. in the ground for $\frac{1}{4}$ sec. cor., with brass cap mkd.

$\frac{1}{4}$   
S 18 | S 17

1934

Chains.	of stone, 2 ft. base, 1½ ft. high, W. of cor. raise a mound
52.20	Dim road, bears NW. to Gila Bend, and SE. to Papago Indian Reservation.
80.00	Set a malpais stone, 20x10x8 ins., 15 ins. in the ground, for cor. of secs. 7, 8, 17 and 18, mkd. with a cross X on top, 4 notches on S. and 5 notches on E. face; and raise a mound of stone, 2 ft. base, 1½ ft. high, W. of cor.  Land, level. Soil, sandy, 2nd rate; and gravelly, 3rd rate. Timber, scattering palo verde, ironwood and mesquite; undergrowth, greasewood, sage brush and cactus.
	-----
	S. 89° 45' E., on a random line bet. secs. 8 and 17.
40.00	Set temp. ¼ sec. cor.
80.34	Intersect N. and S. line, 5 lks. S. of the cor. of secs. 8, 9, 16 and 17.  Thence  N. 89° 47' W., on a true line bet. secs. 8 and 17.  Over level desert land, through scattering timber and undergrowth.
20.35	Wash, 15 lks. wide, course N.
40.17	Set a malpais stone, 20x12x4 ins., 12 ins. in the ground, for ¼ sec. cor., mkd. with a cross on top, ¼ on N. S 8 on N, and S 17 on S. face; and raise a mound of stone, 2 ft. base, 1½ ft. high, N. of cor.
59.35	Wash, 30 lks. wide, course N. 60° W.
65.35	Wash, 30 lks. wide, course N.
75.35	Wash, 20 lks. wide, course N. 10° W.
80.34	The cor. of secs. 7, 8, 17 and 18.  Land, level. Soil, sandy, 2nd rate; and rocky, 3rd rate. Timber, scattering palo verde, ironwood and mesquite; undergrowth, greasewood, sage brush and cactus.
	-----
	S. 89° 45' W., on a random line bet. secs. 7 and 18.
40.00	Set temp. ¼ sec. cor.
79.90	Intersect W. bdy. of Tp., at the cor. of secs. 7, 12, 13 and 18; described in the field notes of the W. bdy. of T. 9 S., R. 3 W., surveyed under this group.  Thence  N. 89° 45' E., on a true line bet. secs. 7 and 18.  Over level desert land, through scattering timber and undergrowth.
16.20	Wash, 50 lks. wide, course N. 30° W.

Chains.	
39.90	Set a malpais stone, 20x10x6 ins., 12 ins. in the ground, for $\frac{1}{4}$ sec. cor., mkd. with a cross X $\frac{1}{4}$ on top, 7 on N., and 18 on S. face; and raise a mound of stone, 2 ft. base $1\frac{1}{2}$ ft. high, N. of cor.
58.90	Dim road, bears NW. and SE.
79.90	The cor. of secs. 7, 8, 17 and 18.
	Land, level. Soil, sandy, 2nd rate; and gravelly, 3rd rate. Timber, scattering palo verde, ironwood and mesquite; undergrowth, greasewood, sage brush and cactus.
-----	
	N.0°03'W., bet. secs. 7 and 8.
	Over level desert land, through scattering timber and undergrowth.
6.00	Wash, 20 lks. wide, course NW.
29.40	Wash, 20 lks. wide, course N.20°W.
40.00	Set a malpais stone, 20x14x10 ins., 14 ins. in the ground, for $\frac{1}{4}$ sec. cor., mkd. $\frac{1}{4}$ on W. face; and raise a mound of stone, 2 ft. base, $1\frac{1}{2}$ ft. high, W. of cor.
75.50	Wash, 25 lks. wide, course NW.
80.00	Set a malpais stone, 20x6x6 ins., 15 ins. in the ground, for cor. of secs. 5, 6, 7 and 8, mkd. with a cross X on top, 5 grooves on S., and 5 grooves on E. face; and raise a mound of stone, 2 ft. base, $1\frac{1}{2}$ ft. high, W. of cor.
	Land, level. Soil, sandy, 2nd rate; and gravelly, 3rd rate. Timber, scattering palo verde, ironwood and mesquite; undergrowth, greasewood, sage brush and cactus.
-----	
	S.89°47'E., on a random line bet. secs. 5 and 8.
40.00	Set temp. $\frac{1}{4}$ sec. cor.
80.28	Intersect N. and S. line, 5 lks. S. of the cor. of secs. 4, 5, 8 and 9.
	Thence
	N.89°49'W., on a true line bet. secs. 5 and 8.
	Over level desert land, through scattering timber and undergrowth.
14.30	Wash, 40 lks. wide, course NW.
38.40	Wash, 30 lks. wide, course N.15°W.
40.14	Set a malpais stone, 20x8x6 ins., 15 ins. in the ground, for $\frac{1}{4}$ sec. cor., mkd. $\frac{1}{4}$ on N. face; and raise a mound of stone, 2 ft. base, $1\frac{1}{2}$ ft. high, N. of cor.
80.28	The cor. of secs. 5, 6, 7 and 8.
	Land, level. Soil, sandy, 2nd rate; and gravelly, 3rd rate. Timber, scattering palo verde, ironwood and mesquite; undergrowth, greasewood, sage brush and cactus.

Chains.	S.89°45'W., on a random line bet. secs. 6 and 7.
40.00	Set temp. $\frac{1}{4}$ sec. cor.
79.90	Intersect W. bdy. of Tp., 7 lks. N. of the cor. of secs. 1, 6, 7 and 12; described in the field notes of the W. bdy. of T. 9 S., R. 3 W., surveyed under this group.
	Thence
	N.89°42'E., on a true line bet. secs. 6 and 7.
	Over level desert land, through scattering timber and undergrowth.
13.00	Dim road, bears NW. to Gila Bend, and SE. to Papago Indian Reservation.
35.90	Wash, 80 lks. wide, course N.
39.90	Set a malpais stone, 20x8x8 ins., 16 ins. in the ground, for $\frac{1}{4}$ sec. cor., mkd. $\frac{1}{4}$ on N. face; and raise a mound of stone, 2 ft. base, $1\frac{1}{2}$ ft. high, N. of cor.
77.90	Wash, 25 lks. wide, course NW.
79.90	The cor. of secs. 5, 6, 7 and 8.
	Land, level, Soil, sandy, 2nd rate; and gravelly, 3rd rate. Timber, scattering palo verde, ironwood and mesquite; undergrowth, greasewood, sage brush and cactus.
	-----
	N.0°10'W., on a random line bet. secs. 5 and 6.
40.00	Set temp. $\frac{1}{4}$ sec. cor.
79.60	Intersect N. bdy. of Tp., 23 lks. W. of the cor. of secs. 5, 6, 31 and 32; described in the field notes of the N. bdy. of T. 9 S., R. 3 W., surveyed under this group.
	Thence
	South on a true line bet. secs. 5 and 6.
	Over level desert land, through scattering timber and undergrowth.
13.10	Enter wash, 90 lks. wide, course NW. from S.
17.60	Leave same wash, 90 lks. wide, course N. from SE.
28.60	Wash, 60 lks. wide, course NW.
39.60	Set a malpais stone, 20x8x8 ins., 14 ins. in the ground, for $\frac{1}{4}$ sec. cor., mkd. $\frac{1}{4}$ on W. face; and raise a mound of stone, 2 ft. base, $1\frac{1}{2}$ ft. high, W. of cor.
54.60	Wash, 10 lks. wide, course NW.
79.60	The cor. of secs. 5, 6, 7 and 8.
	Land, level. Soil, sandy, 2nd rate; and gravelly, 3rd rate. Timber, scattering palo verde, ironwood and mesquite; undergrowth, greasewood, sage brush and cactus.
	-----

## GENERAL DESCRIPTION.

The land within township 9 south, range 3 west is desert and mountainous. The general elevation of the township in the desert is about 800 to 1000 ft. above sea level. The mountains are of a volcanic origin being very rough and covered with loose rock and lava, and are of a height of 500 to 600 ft. above the desert. The northern portion of the township is level and rolling broken desert land, cut by numerous small washes that flow northwesterly to the Gila River. The soil is a sand alluvial silt of light buff color, but covered with loose lava rock, 2nd and 3rd rate.

The SE. and W. portions of the township is rolling and mountainous. The soil of the mountainous country is rocky 4th rate. At the base of the hills the surface is often strewn by numerous black volcanic boulders.

The timber consists chiefly of scattering ironwood, mesquite and palo verde, with some catclaw. The undergrowth is a kind of sage and several varieties of cactus.

There are two old roads which traverse through the township, northwesterly to Gila Bend, and southeasterly to Papago Indian Reservation.

There are no settlers located within the township.

No evidence of mineral deposits were found.

The average magnetic declination of the township is 14°E.

BOOK 4062

4-680  
(August, 1926)

FIELD ASSISTANTS.

NAMES.	CAPACITY.
Sloan A. Amos	1st Chainman
E. W. Fields	2nd Chainman
Rody G. Capron	Cornerman
J. W. Peterson	Flagman
F. O. Colson	Axeman
M. L. Patrick	Axeman
Erwin Peterson	Moundsman
Elbert T. Mosley	Moundsman

42A 134  
BOOK 4062

CERTIFICATE OF UNITED STATES SURVEYOR

We, Charles E. Bronson and Cyril Gilliam, U.S. Transitmen, hereby certify upon honor that, in pursuance

of special instructions received from the District Cadastral Engineer for Arizona

bearing date of the 12th day of December, 1933, we have well, faithfully, and truly

our own proper persons, and in strict conformity with said instructions, the Manual of Surveying Instructions, and the laws of the United States, surveyed the subdivisional lines of Township 9 South, Range 3 West,

of the Gila and Salt River Meridian, in the State of Arizona, which are represented in

the foregoing field notes as having been executed by us, and under our direction; and that all the corners of said survey have been established and perpetuated in strict accordance with the Manual of Surveying Instructions, and the special written instructions of the District Cadastral Engineer for Arizona and in the specific manner described in the field notes, and that the foregoing are the original field notes of such survey.

For signature of Cyril Gilliam, see attached certificate.

Chas. E. Bronson  
U.S. Transitman  
Sentinel, Arizona,  
January 31, 1934.

APPROVAL

OFFICE OF U. S. SUPERVISOR OF SURVEYS,

19

The foregoing field notes of the survey of

executed by under his special instructions dated, 19, having been critically examined, and the necessary corrections and explanations made, the said field notes, and the surveys they describe, are hereby approved.

U. S. Supervisor of Surveys.

I certify that the foregoing transcript of the field notes of the above-described surveys in, has been correctly copied from the original notes on file in this office.

U. S. Supervisor of Surveys.

4-680  
(August, 1926)

FIELD ASSISTANTS.

NAMES.	CAPACITY.
Jess R.Horak	1st Chainman
Thomas T.Cage	2nd Chainman
Foster William Kelly	2nd Chainman
Omer S.Boswell	Flagman
Carrol White	Cornerman
Thomas L.Bond	Axeman
Otis L.Mosley	Axeman
Donovan D.Boyer	Moundsman

44 136 BOOK 4062

CERTIFICATE OF UNITED STATES SURVEYOR

We, Charles E. Bronson and Cyril Gilliam, U.S. Transitmen, hereby certify upon honor that, in pursuance

of special instructions received from the District Cadastral Engineer for Arizona

bearing date of the 12th day of December, 1933, we have well, faithfully, and truly

in our own proper persons, and in strict conformity with said instructions, the Manual of Surveying Instructions, and the laws of the United States, surveyed the subdivisional lines of Township 9 South, Range 3 West,

of the Gila and Salt River Meridian, in the State of Arizona, which are represented in

the foregoing field notes as having been executed by us, and under our direction; and that all the corners of said survey have been established and perpetuated in strict accordance with the Manual of Surveying Instructions, and the special written instructions of the District Cadastral Engineer for Arizona

and in the specific manner described in the field notes, and that the foregoing are the original field notes of such survey.

Cyril Gilliam

U.S. Transitman  
Sentinel, Arizona,  
February 16, 1934.

APPROVAL

OFFICE OF U. S. SUPERVISOR OF SURVEYS,

Denver, Colorado, May 4, 1935.

The foregoing field notes of the survey of the subdivisional lines of Township 9 South, Range 3 West, of the Gila and Salt River Meridian, in the State of Arizona,

executed by Charles E. Bronson and Cyril Gilliam, U.S. Transitmen, under his special instructions dated December 12, 1933, having been critically examined, and the necessary corrections and explanations made, the said field notes, and the surveys they describe, are hereby approved.

Charles E. Bronson

U. S. Supervisor of Surveys.

I certify that the foregoing transcript of the field notes of the above-described surveys in \_\_\_\_\_, has been correctly copied from the original notes on file in this office.

U. S. Supervisor of Surveys.