

Book "D" 4118

ORIGINAL 101

(1)

4-679  
(April 1933)

BOOK 4118

# FIELD NOTES

4118

RESURVEY of

WEST BOUNDARY,

NORTH BOUNDARY

and

SUBDIVISION LINES

of

TOWNSHIP 7 NORTH, RANGE 29 EAST

Of the Gila and Salt River Base and Meridian,

In the State of ARIZONA

## EXECUTED BY

Roger F. Wilson, U. S. Surveyor

Benjamin J. Mollette, U. S. Transitman

Robert H. Fischer, U. S. Transitman

<sup>supplemental</sup> Under special instructions dated January 31, 1936, which provided for the surveys included under Group No. 192, Arizona bearing the approval of the Commissioner of the General Land Office under date of April 2, 1936 and assignment instructions dated July 31, and Aug. 12, 1936

Re Survey commenced September 5, 1936

Re Survey completed October 8, 1936

4118

# INDEX DIAGRAM.

Township \_\_\_\_\_, Range \_\_\_\_\_

6	5	4	3	2	1
7	8	9	10	11	12
18	17	16	15	14	13
19	20	21	22	23	24
30	29	28	27	26	25
31	32	33	34	35	36

4118

1A

INDEX-DIAGRAM

Book No. 4118

BOOK 4118

	31 14	32 15 16	33 17	34 18	35 19	36 20 21	
12	84		55		33		
11	6 84	5 68 83	4 67 66	3 44 55	2 43	1 33 32	6
10	7 80 81	8 66 65 80	9 54 53 64 63	10 42 53 52	11 31 41	12 30	7
9	18 77 78	17 63 62 77 76	16 51 50 T. 7 N. 50 62	15 40 R. 29 E. 50 49	14 29 39	13 28	18
8	19 75 74 75	20 61 74 73	21 49 48 60	22 38 48 47	23 27 38 37	24 26	19
6	30 71	29 59 58 70	28 47 46 58	27 37 36 46	26 25 24 36 35	25 24	30
5	31 69	32 57 56	33 45 44	34 35 34	35 23 22	36	31
4							
	6	5	4	3	2	1	

Accepted surveys.

Resurveyed under this group.

BOOK 4118

15

The resurveys herein described were executed by Roger F. Wilson, U. S. Surveyor, using Buff & Buff solar transit No. 10125 from Sept. 4 to Oct. 13, 1936, and Buff & Buff solar transit No. 23829 thereafter; by Benjamin J. Mollette, U. S. Transitman, using Buff and Buff solar transit No. 9984; and by Robert H. Fischer, U. S. Transitman, using a Young and Sons transit No. 8477. These instruments are each equipped with improved Smith solar attachment, and otherwise conform to the standard specifications of the General Land Office. The transits were examined, tested and approved by the District Cadastral Engineer just prior to their assignment to field work on this group, conditional upon satisfactory results of field tests of same.

#### PRELIMINARY FIELD TESTS OF INSTRUMENTS

September 3, 1936, in camp at  $\frac{1}{2}$  sec. cor. of secs. 29 and 30, T. 7 N., R. 29 E., G. & S.R. Meridian, Arizona, in latitude  $33^{\circ} 58'$  N., and longitude  $109^{\circ} 19'$  W., determined from data accompanying the instructions for Group No. 192, Arizona. We examine the instructions and find no appreciable errors, then test the indications of the solar apparatus by comparison with the meridian established this day by Polaris observation by Roger F. Wilson, U. S. Surveyor, using Buff and Buff transit No. 10125 as follows:

Watch checked in Springerville, Arizona at 3 p.m. on Sept. 3, 1936; make an hour angle observation on Polaris E. of the meridian turning left from W. top of pine snag about  $\frac{1}{2}$  mile dist. accumulating the angle of 4 readings, 2 direct and 2 reverse.

Mean watch time p.m.	7 <sup>h</sup> 2.5 <sup>m</sup>
Watch fast of L.M.T.	17.3 <sup>m</sup>
Accumulated angle reference point to Polaris	71° 54'
Mean Angle	17° 58' 30"
Azimuth of Polaris	1° 02' 18"
Bearing of reference point	19° 00' 48"
Mean observed altitude	33° 27'
Reduced latitude	33° 58' 11" N.

Then turn  $19^{\circ} 00' 48''$  left from reference point and establish a point in the meridian about 10.00 chs. N. by driving a tack in a stake firmly set in ground.

Test of Buff and Buff transit No. 10125 by Roger F. Wilson, U.S. Surveyor.

September 4, 1936, at 8h 00m a.m. app.t., set off  $33^{\circ} 58'$  N., on the latitude arc;  $7^{\circ} 07'$  N., on the declination arc; and determine a meridian with the solar which agrees with the true meridian.

At app.t. noon, with the latitude arc unchanged; observe the sun on the meridian and obtain a reading of  $7^{\circ} 03'$  N. on the declination arc; which agrees with the computed declination of the sun.

At 4h 00m p.m., app.t., with the latitude arc unchanged set off  $7^{\circ} 00'$  N., on the declination arc and determine a meridian with the solar which agrees within 1' with the true meridian.

Preliminary test of Buff and Buff transit No. 23829 by Roger F. Wilson, U.S. Surveyor, on Oct. 15, 1936, described in notes of resurvey of T. 6 N., R. 29 E.

Test of Buff and Buff transit No. 9984, by Benjamin J. Mollette, U.S. Transitman.

September 4, 1936, at 8h 00m, a.m., app.t., set off  $33^{\circ} 58'$  N. on the latitude arc;  $7^{\circ} 07'$  N., on the declination arc; and determine a meridian with the solar, which agrees within 1' with the true meridian.

At app.t noon with the latitude arc unchanged; observe the sun on the meridian and obtain a reading of  $7^{\circ} 03'$  N. on the declination arc, which agrees with the computed declination of the sun.

At 4h 00m p.m., app.t., with the latitude arc unchanged set off  $7^{\circ} 00'$  N. on the declination arc, and determine a meridian with the solar, which agrees with the true meridian.

Test of Young and Sons transit No. 8477 by Robert H. Fischer, U.S. Transitman.

September 4, 1936, at 8h 00m, a.m., app.t., set off  $33^{\circ} 58'$  N. on the latitude arc;  $7^{\circ} 07'$  N. on the declination arc; and determine a meridian with the solar which agrees within 1' 30" with the true meridian.

At app.t. noon with the latitude arc unchanged; observe the sun on the meridian and obtain a reading of  $7^{\circ} 03'$  N., on the declination arc which agrees with the computed declination of the sun.

At 4h 00m, p.m., app.t., with the latitude arc unchanged; set off  $7^{\circ} 00'$  N., on the declination arc, and determine a meridian with the solar which agrees within 1' with the true meridian.

All of the solar observation with these transits during the usual hours of solar work coming within 1' 30" of the true meridian, demonstrates that they are in satisfactory adjustment on this date.

All measurements are made with Lallie and Lufkin steel tapes, 5 chs. long, graduated every link for the first 100 lks. and the balance at intervals of 10 lks. The tapes were tested with a Lufkin standard, by comparison and found correct. The measurements are made on the slope; the vertical angle of each interval is determined with a clinometer in good adjustment, and the horizontal equivalents are entered in the field note record.

## RESURVEY: WEST BOUNDARY OF T. 7 N., R. 29 E.

418

3.

Chains

The West Boundary of T. 7 N., R. 29 E., was surveyed in 1883 by W. R. Fitzgerald, U.S.D.S., establishing  $\frac{1}{4}$  sec. and sec. cors., alternately, at 40.00 ch. intervals counting from the North, with common references to areas both sides of the line. No retracement or resurvey of any part of this line is of record. The following notes describe a dependent resurvey of the entire line, reconstructing all existing corners with brass capped iron posts, except  $\frac{1}{4}$  sec. cor. of secs. 7 and 12, retaining their original references.

## RETRACEMENT FOR RESURVEY

- From the cor. of Ts. 7 and 8 N., Rs. 28 and 29 E.  
South on random line, bet. secs. 1 and 6 ( $N\frac{1}{2}$ ).
- 39.64 A point 32 lks. E. of original  $\frac{1}{4}$  sec. cor.  
True course and dist. of  $N\frac{1}{2}$  of line, bet. secs. 1 and 6 are therefore, N.  $0^{\circ} 28'$  E., 39.64 chs.  
Thence,  
South on random line, bet. secs. 1 and 6 ( $S\frac{1}{2}$ ).
- 40.11 A point 20 lks. W. of original cor. of secs. 1, 6, 7 and 12.  
True course and dist. of  $S\frac{1}{2}$  of line bet. secs. 1 and 6 are therefore, N.  $0^{\circ} 17'$  W., 40.11 chs.  
South on random line, bet. secs. 7 and 12 ( $N\frac{1}{2}$ ).
- 39.65 A point 49 lks. E. of original  $\frac{1}{4}$  sec. cor.  
True course and dist. of  $N\frac{1}{2}$  of line bet. secs. 7 and 12 are therefore, N.  $0^{\circ} 42'$  E., 39.65 chs.  
Thence,  
South on random line, bet. secs. 7 and 12 ( $S\frac{1}{2}$ ).
- 39.34 A point 38 lks. W. of original cor. of secs. 7, 12, 13 and 18.  
True course and dist. of  $S\frac{1}{2}$  of line bet. secs. 7 and 12 are therefore, N.  $0^{\circ} 33'$  W., 39.34 chs.  
South on random line, bet. secs. 13 and 18 ( $N\frac{1}{2}$ ).
- 39.90 A point 5 lks. W. of original  $\frac{1}{4}$  sec. cor.  
True course and dist. of  $N\frac{1}{2}$  of line bet. secs. 13 and 18 are therefore, N.  $0^{\circ} 04'$  W., 39.90 chs.  
Thence,  
South on random line, bet. secs. 13 and 18 ( $S\frac{1}{2}$ ).
- 39.97 A point 6 lks. W. of original cor. of secs. 13, 18, 19 and 24.  
True course and dist. of  $S\frac{1}{2}$  of line bet. secs. 13 and 18 are therefore, N.  $0^{\circ} 05'$  W., 39.97 chs.  
South on random line, bet. secs. 19 and 24 ( $N\frac{1}{2}$ ).
- 39.38 A point 24 lks. E. of original  $\frac{1}{4}$  sec. cor. of secs. 19 and 24.  
True course and dist. of  $N\frac{1}{2}$  of line bet. secs. 19 and 24 are therefore, N.  $0^{\circ} 21'$  E., 39.38 chs.

ECC

## RESURVEY: WEST BOUNDARY OF T. 7 N., R. 29 E.

4.

Chains	Thence, South on random line, bet. secs. 19 and 24 ( $S\frac{1}{2}$ ).
39.65	A point 38 lks. E. of original cor. of secs. 19, 24, 25 and 30. True course and dist. of $S\frac{1}{2}$ of line bet. secs. 19 and 24, are therefore, N. $0^{\circ} 33'$ E., 39.65 chs.
40.04	South on random line, bet. secs. 25 and 30 ( $N\frac{1}{2}$ ). A point 3 lks. W. of original $\frac{1}{4}$ sec. cor. of secs. 25 and 30. True course and dist. of $N\frac{1}{2}$ of line bet. secs. 25 and 30, are therefore, N. $0^{\circ} 03'$ W., 40.04 chs.
40.03	Thence, South on random line, bet. secs. 25 and 30 ( $S\frac{1}{2}$ ). A point 28 lks. E. of original cor. of secs. 25, 30, 31 and 36. True course and dist. of $S\frac{1}{2}$ of line bet. secs. 25 and 30, are therefore, N. $0^{\circ} 24'$ E., 40.03 chs.
39.95	South on random line, bet. secs. 31 and 36 ( $N\frac{1}{2}$ ). A point 23 lks. E. of original $\frac{1}{4}$ sec. cor. True course and dist. of $N\frac{1}{2}$ of line bet. secs. 31 and 36, are therefore, N. $0^{\circ} 20'$ E., 39.95 chs.
40.06	Thence, South on random line, bet. secs. 31 and 36 ( $S\frac{1}{2}$ ). A point 80 lks. W. of the cor. of Ts. 6 and 7 N., Rs. 28 and 29 E. True course and dist. of $S\frac{1}{2}$ of line bet. secs. 31 and 36, are therefore, N. $1^{\circ} 09'$ W., 40.07 chs.
RESURVEY	
2.00	From the cor. of Ts. 6 and 7 N., Rs. 28 and 29 E. reconstructed in original position under this group, which is an iron post, 3 ins. diam., projecting 10 ins. above ground, firmly set with brass cap mkd. and witnessed as described in the notes of resurvey of W. bdy. of T. 6 N., R. 29 E., with notes of resurvey of said township. Thence; N. $1^{\circ} 09'$ W., on true line, bet. secs. 31 and 36 ( $S\frac{1}{2}$ ). Over nearly level land on top of ridge bearing N. and S., devoid of timber and undergrowth. Ascend 34 ft.
16.90	S. edge of patch of dense timber, brs. E. 3.00 chs. and W. 5.00 chs., thence N.
28.30	Leave top of ridge, brs. N. $30^{\circ}$ E., and S., thence along W. slope, descending 15 ft. to road. Leave dense timber, brs. N. $30^{\circ}$ E. and S. $30^{\circ}$ W. and enter open grassy land.

RESURVEY: WEST BOUNDARY OF T. 7 N., R. 29 E.

5.

Chains

28.60

Road, brs. N. 30° E. and S. 30° W. Asc. 12 ft. over SW. slope to  $\frac{1}{4}$  sec. cor.

40.07

Intersect original  $\frac{1}{4}$  sec. cor. of secs. 31 and 36, which is an unmarked lava stone, 14x8x6 ins. firmly set in a mound of stone. No accessories.  
Reconstruct this cor. monument as follows: remove the mound of stone and the original cor. stone, and in same place, set an iron post, 3 ft. long, 1 in. diam., 26 ins. in the ground, with the original cor. stone reset alongside, for  $\frac{1}{4}$  sec. cor., with brass cap mkd.



from which

An aspen, 10 ins. diam., brs. S. 48 $\frac{1}{2}$ ° E., 537 lks. dist., mkd.  $\frac{1}{4}$  S31 BT.

No other bearing tree available.

Pat's knoll U.S.F.S. lookout tower, brs. N. 42° 08' E., (vertical angle + 6 $\frac{1}{2}$ °).

Thence,

N. 0° 20' E., on true line; bet. secs. 31 and 36 (N $\frac{1}{2}$ ).

Over gently rolling grassy land, devoid of timber and undergrowth. Asc. 20 ft. over SW. slope.

15.00

Asc. 48 ft. over S. slope.


35.00

Low spur, slopes S. 60° W. Descend slightly over W. slope to

39.95

Intersect original cor. of secs. 25, 30, 31 and 36, which is an unmarked lava stone, 9x9x6 ins. firmly set in a mound of stone.

Reconstruct this cor. monument as follows: remove the mound of stone, and the original cor. stone, and in same place, set an iron post, 3 ft. long, 2 ins. diam., 24 ins. in the ground; with original cor. stone reset alongside, and in a mound of stone to top, for cor. of secs. 25, 30, 31 and 36, with brass cap mkd.



1936

Land, gently rolling.  
Soil, lava stone over dark loam, 1st and 3rd rates.  
Timber, yellow pine, aspen and fir.  
Undergrowth, scrub timber.  
Fair grass.

N. 0° 24' E., on true line, bet. secs. 25 and 30 (S $\frac{1}{2}$ ).

Over gently rolling grassy land, devoid of timber and undergrowth. Asc. 12 ft. over W. and SW. slopes.

15.45

Fence cor. brs. E. 16 lks. dist., from which 4 strand barbed wire fences extend S. 80° W. and N. 15° E.

## RESURVEY: WEST BOUNDARY OF T. 7 N., R. 29 E.

6.

Chains

- 18.30 Spur, slopes W., desc. 112 ft. over NW. slope to
- 40.03 Intersect original  $\frac{1}{4}$  sec. cor. of secs. 25 and 30, which is an unmarked sandstone, 14x10x6 ins. firmly set in a mound of stone. No accessories.  
Reconstruct this cor. monument as follows: remove the mound of stone and the original cor. stone and in same place, set an iron post, 3 ft. long, 1 in. diam., 22 ins. in the ground, to bedrock with the original cor. stone reset alongside, and in a mound of stone to top, for  $\frac{1}{4}$  sec. cor., with brass cap mkd.
- $$\begin{array}{c} \frac{1}{4} \\ \text{S25} \quad | \quad \text{S30} \\ \hline 1936 \end{array}$$
- from which
- Fence cor. brs. N. 31° 37' E., about 13 chs. dist., from which wire fences extend NE., S. 15° W. and N. 30° W.
- Thence,
- N. 0° 03' W., on true line, bet. secs. 25 and 30 (N $\frac{1}{2}$ ).
- Over gently rolling grassy land, devoid of timber and undergrowth. Desc. 10 ft. over NW. slope.
- 6.60 Road, brs. N. 70° E. to Pat's Knoll cabins and S. 70° W., to Springerville highway.
- 15.00 Desc. 51 ft. over W. slope.
- 21.30 Road, brs. S. 30° E. to Pat's Knoll cabins and N. 30° W., to Springerville highway.
- 22.00 Low ridge, brs. N. 30° W. and S. 30° E., desc. gradually over NE. slope to sec. cor.
- 22.62 Fence ( 4 strand barbed wire) brs. S. 30 $\frac{1}{4}$ ° E., and N. 30 $\frac{1}{4}$ ° W., Pat's Knoll sign on highway, brs. N. 40° 10' W.
- 31.60 Graded highway, brs. NE. to Springerville and SW.
- 40.04 Intersect original cor. of secs. 19, 24, 25 and 30, which is a sandstone, 26x16x6 ins. firmly set in a mound of stone, mkd. with 2 grooves on S. face and 4 grooves on N. face. No accessories.  
Reconstruct this cor. monument as follows: remove the mound of stone and the original cor. stone, and in same place, set an iron post, 3 ft. long, 2 ins. diam., 18 ins. in the ground to bedrock with the original cor. stone reset alongside, for cor. of secs. 19, 24, 25 and 30, with brass cap mkd.
- $$\begin{array}{c} \text{T7N} \\ \text{R28E} \quad | \quad \text{R29E} \\ \text{S24} \quad | \quad \text{S19} \\ \hline \text{S25} \quad | \quad \text{S30} \\ \hline 1936 \end{array}$$
- from which
- Outlet to reservoir in draw, brs. N. 72 $\frac{1}{4}$ ° E.,
- Land, gently rolling.  
Soil, lava and sandstone, over dark loam, 1st and 3rd rates.

Chains	Timber, none. Undergrowth, none. Fair grass.
	N. 0° 33' E., on true line, bet. secs. 19 and 24 (S $\frac{1}{2}$ ). Over gently rolling grassy land, devoid of timber and undergrowth. Desc. 52 ft. over NE. slope.
2.10	Graded highway, in curve, brs. NW. and SE.
9.10	Same highway, brs. NE. and SW.
10.30	Draw, course E., an 18 in. culvert under highway, brs. E., 50 lks. dist. Asc. 21 ft. over S. slope.
20.70	Low ridge, brs. E. and W., desc. 40 ft. over NE. slope.
26.82	S. edge of lake, about 17 chs. long, 10 chs. wide, brs. N. 79° E., and N. 80° W. Discontinue chaining on Tp. bdy. owing to water in lake and measure to N. edge of same by traverse line, thru sec. 19 as follows: N. 79° E., 8.00 chs. thence, N. 41° W., 11.95 chs. returning to Tp. bdy. at 37.48 ch. station.
30.80	(Approx) bottom of draw in lake, course S. 72 $\frac{1}{2}$ ° E.
37.48	N. edge of lake, brs. N. 67° W., and S. 41° E., leave lake thence, N. 0° 33' E., on Tp. bdy. line, continuing measurement from sec. cor. Asc. 13 ft. over SW. slope to
39.65	Intersect original $\frac{1}{4}$ sec. cor. of secs. 19 and 24, which is a lava stone, 20x11x4 ins. mkd. $\frac{1}{4}$ on W. face, and firmly set in a mound of stone. No accessories. Reconstruct this cor. monument as follows: remove the mound of stone, and the original cor. stone, and in same place, set an iron post, 3 ft. long, 1 in. diam., 26 ins. in the ground, with the old cor. stone, reset alongside, for $\frac{1}{4}$ sec. cor., with brass cap mkd.  <div style="text-align: center;"> <math display="block">\begin{array}{c} \frac{1}{4} \\ \text{S24} \quad   \quad \text{S19} \\ \text{1936} \end{array}</math> </div> and raise a mound of stone, 2 ft. base, 1 $\frac{1}{2}$ ft. high, W. of cor. Thence,
	N. 0° 21' E., on true line, bet. secs. 19 and 24 (N $\frac{1}{2}$ ). Over gently rolling grassy land, devoid of timber and undergrowth. Asc. 25 ft. over SW. slope.
1.50	Telephone line, over 4 strand barbed wire fence, brs. N. 71 $\frac{1}{2}$ ° E., and S. 71 $\frac{1}{2}$ ° W.
5.80	Ridge, brs. S. 55° E. and N. 70° W., enter mountainous land. Desc. 124 ft. over N. slope to
14.40	S. edge of lake, about 17 chs. long, 12 chs. wide, brs. N. 72° W. and S. 60° E. Discontinue chaining on Tp. bdy. owing to water in lake, and measure to N. edge of same by traverse line, thru sec. 24, as follows: N. 72° W. 9.00 chs., thence, N. 13 $\frac{1}{2}$ ° E., 10.00 chs. thence N. 45° E., 5.00 chs. thence, N. 78° E., 2.75 chs., return-

RESURVEY: WEST BOUNDARY OF T. 7 N., R. 29 E.

BOOK 4110

Chains ing to Tp. bdy. at 31.01 ch. station.

22.85 (Approx) Bottom of draw, in lake, course NE.

31.01 N. edge of lake, brs. S. 85° E. and S. 78° W. Center of rock dam in draw, brs. N. 79½° E.; 325 lks. dist., leave lake, thence, N. 0° 21' E., on Tp. bdy. continuing measurement from ¼ sec. cor. Asc. 36 ft. over S. slope.

35.50 Ridge, brs. E. and W., circles lake to SW. Leave mountainous and enter gently rolling land: Descend 16 ft. over N. slope to

39.38 Intersect original cor. of secs. 13, 18, 19 and 24, which is a lava stone; 14x8x8 ins: mkd: with 3 grooves on each of N. and S. faces, and firmly set in a mound of stone. No accessories.  
Reconstruct this cor. monument as follows: remove the mound of stone and the original cor. stone, and in same place, set an iron post, 3 ft. long, 2 ins. diam., 24 ins. in the ground, with the original cor. stone reset alongside; and in a mound of stone to top, for cor. of secs. 13, 18, 19 and 24, with brass cap mkd.

T7N	
R28E	R29E
S13	S18
S24	S19

1936

Land, gently rolling and mountainous.  
Soil, lava and sandstone, over dark loam, 1st and 3rd rates  
Timber, none.  
Undergrowth, none.  
Fair grass.

N. 0° 05' W., on true line, bet. secs. 13 and 18 (S½).

Over gently rolling grassy land, devoid of timber and undergrowth. Desc. 44 ft. over N. slope.

13.60 Seep spring in draw, course NE. At 2 chs. SW. this draw is joined by another draw, course N.  
Asc. 25 ft. over SE. slope.

17.40 Old highway; brs. N. 68° E. and S. 60° W. At 10 chs. NE. this highway turns to N.

32.60 Fence ( 4 strand barbed wire) brs. N. 40° E. and S. 40° W.

34.90 Point of low spur, slopes SE. Enter E. edge of timbered area brs. N. and SW. Desc. 15 ft. over NE. slope to

39.97 Intersect original ¼ sec. cor. of secs. 13 and 18, which is a sandstone, 10x10x8 ins. above ground; firmly set and mkd. ¼ on W. face. No accessories.  
Reconstruct this cor. monument as follows: alongside the original cor. stone, set an iron post, 3 ft. long, 1 in. diam., 12 ins. in the ground to bedrock and in a mound of stone to top, for ¼ sec. cor. with brass cap mkd.

S13	¼	S18
1936		

from which

## RESURVEY: WEST BOUNDARY OF T. 7 N., R. 29 E.

9

## Chains

A spruce, 9 ins. diam., brs. N. 5° E., 88 lks. dist.,  
mkd.  $\frac{1}{4}$  S18 BT.

A spruce, 16 ins. diam., brs. S. 56 $\frac{1}{4}$ ° W., 60 lks. dist.  
mkd.  $\frac{1}{4}$  S13 BT.

Thence,

N. 0° 04' W., on true line, bet. secs. 13 and 18 (N $\frac{1}{2}$ ).

Over gently rolling land, along E. edge of timbered area,  
bearing N. and S.

Desc. 22 ft. over NE. slope.

4.78 Left bank of reservoir brs. NW. and SE. in draw, course  
NW. Thence across upper end of reservoir.

7.00 Right bank of reservoir, brs. NW. and SE. Leave reservoir.  
Asc. 21 ft. over SW. slope to.

17.70 Draw, course S. 60° W. Center of rock dam brs. E. about  
15.00 chs. dist., asc. 67 ft. over SE. slope.

22.80 East edge of timbered area turns from S. to NE. and be-  
comes dense.

31.80 Ridge, brs. N. 30° E. and S. 30° W. Desc. 10 ft. over NW.  
slope to

39.90 Intersect original cor. of secs. 7, 12, 13 and 18, which  
is an unmarked lava stone, 16x16x8 ins. firmly set in  
a mound of stone, and witnessed by the two record bear-  
ing trees.

Reconstruct this cor. monument as follows: remove the  
mound of stone and the original cor. stone, and in same  
place, set an iron post, 3 ft. long, 2 ins. diam., 22  
ins. in the ground, with the original cor. stone, reset  
alongside, and in a mound of stone to top, for cor. of  
secs. 7, 12, 13 and 18, with brass cap mkd.

T7N	
R28E	R29E
S12	S7
S13	S18

1936

from which

the original bearing trees:

A yellow pine (dead) 18 ins. diam., brs. S. 76° E.,  
48 lks. dist., mkd. T7N R29E S18 BT.

A yellow pine (dead) 14 ins. diam., brs. N. 38 $\frac{1}{2}$ ° W.,  
27 lks. dist., mkd. T7N R28E S12 BT.

and establish additional bearing trees:

A yellow pine, 10 ins. diam., brs. N. 83 $\frac{1}{2}$ ° E., 41 lks.  
dist., mkd. T7N R29E S7 BT.

A yellow pine, 10 ins. diam., brs. S. 61 $\frac{1}{2}$ ° E., 63 lks.  
dist., mkd. T7N R29E S18 BT.

A yellow pine, 10 ins. diam., brs. S. 24° W., 42 lks.  
dist., mkd. T7N R28E S13 BT.

A yellow pine, 12 ins. diam., brs. N. 47 $\frac{1}{2}$ ° W., 30 lks.  
dist., mkd. T7N R28E S12 BT.

BOOK 412

RESURVEY: WEST BOUNDARY OF T. 7 N., R. 29 E.

10

Chains	
	Land, gently rolling. Soil, rocky over dark loam, 1st and 3rd rates. Timber, yellow pine, Undergrowth, none. Fair grass.
	N. 0° 33' W. on true line, bet. secs. 7 and 12 (S $\frac{1}{2}$ ). Over gently rolling land, thru dense timber and scattering undergrowth. Desc. 21 ft. over W. slope to
15.00	Desc. 77 ft. over NW. slope to
25.93	Leave gently rolling and enter mountainous land. Desc. 267 ft. over NW. slope to creek.
32.50	Side hill drain, course NW.
37.00	Water Canyon Creek, 30 lks. wide, 6 ft. deep, course N. 20° E., with stream of water 3 lks. wide, 2 ins. deep. Leave mountainous and enter rolling land. Ascend 6 ft. over SE. slope to
39.34	Intersect original $\frac{1}{4}$ sec. cor. of secs. 7 and 12, which is an aspen tree, 10 ins. diam., mkd. $\frac{1}{4}$ S on W. face, Remark on bark, $\frac{1}{4}$ S7 on E. face, and $\frac{1}{4}$ S12 on W. face. Find to trace of the record bearing tree NE.  This tree cor. monument being in perfect condition, do not set regulation brass capped iron post alongside.  Establish new bearing trees:  A fir, 8 ins. diam., brs. N. 46° E., 28 lks. dist., mkd. $\frac{1}{4}$ S7 BT.  A fir, 12 ins. diam., brs. S. 62° W., 22 lks. dist., mkd. $\frac{1}{4}$ S12 BT.  Thence, N. 0° 42' E. on true line, bet. secs. 7 and 12 (N $\frac{1}{2}$ ). Over rolling land, thru dense timber and scattering undergrowth. Asc. 42 ft. over SE. slope.
6.05	Desc. 41 ft. over NE. slope to
12.10	Enter mountainous land. Desc. 100 ft. over steep NE. and E. slopes to
21.60	W. bank of Water Canyon Creek, in bend, course N. 30° E., from S. 10° E., with a stream of running water, 5 lks. wide, 3 ins. deep. Asc. 146 ft. over SE. slope to
34.46	Desc. 177 ft. over NE. slope to
39.65	Intersect original cor. of secs. 1, 6, 7 and 12, which is an unmarked lava stone, 18x12x5 ins. firmly set in a mound of stone, and witnessed by one of the two record bearing trees. Reconstruct this cor. monument as follows: remove the mound of stone and the original cor. stone, and in same place, set an iron post, 3 ft. long, 2 ins. diam., 26 ins. in the ground, with the original cor. stone reset

RESURVEY: WEST BOUNDARY OF T. 7 N., R. 29 E.

BOOK 2116

11

Chains

alongside, for cor. of secs. 1, 6, 7 and 12, with brass cap mkd.

T7N	
R28E	R29E
S1	S6
S12	S7

1936

from which

one of the original bearing trees:

A fir, 12 ins. diam., brs. S. 75° W., 26 lks. dist., mkd. T7N R28E S12 BT.

Find no trace of the record bearing tree SE.

Establish additional bearing trees:

A spruce, 9 ins. diam., brs. N. 63° E., 40 lks. dist., mkd. T7N R29E S6 BT.

A spruce, 10 ins. diam., brs. S. 61° E., 28 lks. dist., mkd. T7N R29E S7 BT.

A spruce, 10 ins. diam., brs. S. 43° W., 54 lks. dist., mkd. T7N R28E S12 BT.

A spruce, 20 ins. diam., brs. N. 29° W., 29 lks. dist., mkd. T7N R28E S1 BT.

Land, gently rolling and mountainous.

Soil, lava stone over dark loam, 4th rate.

Timber, fir, aspen, spruce and yellow pine.

Undergrowth, scrub timber and bunch grass.

N. 0° 17' W. on true line, bet. secs. 1 and 6 (S $\frac{1}{2}$ ).

Over mountainous land, thru dense timber and scattering undergrowth. Desc. 57 ft. over rocky NE. slope.

9.40 Ascend 264 ft. over SE. slope.

35.80 Point of spur, slopes E. from ridge bearing N. and S. about 2.00 chs. W. Desc. 51 ft. over NE. slope to

39.50 Asc. slightly over SE. slope to

40.11 Intersect point of original location of the  $\frac{1}{4}$  sec. cor. of secs. 1 and 6, determined from the record tie to the one original bearing tree:

A yellow pine, 14 ins. diam., N. 10 $\frac{1}{2}$ ° W., 41 lks. dist., with mks. overgrown. Remark  $\frac{1}{4}$  S1 BT.

Reconstruct this cor. monument as follows: at original point, set an iron post, 3 ft. long, 1 in. diam., 24 ins. in the ground, and in a mound of stone to top for  $\frac{1}{4}$  sec. cor. with brass cap mkd.

S1		S6
	$\frac{1}{4}$	

1936

from which

establish additional bearing tree:

## RESURVEY: WEST BOUNDARY OF T. 7 N., R. 29 E.

12

Chains

A yellow pine, 14 ins. diam., brs. N.  $56\frac{1}{2}^{\circ}$  E., 37 lks. dist., mkd.  $\frac{1}{2}$  S1 BT.

Thence,

N.  $0^{\circ} 28'$  E. on true line, bet. secs. 1 and 6 ( $N\frac{1}{2}$ ).

Over gently rolling land, thru dense timber and scattering undergrowth. Asc. 6 ft. over SE. slope.

3.50 Spur, slopes N.  $50^{\circ}$  E., desc. 21 ft. over N. slope.

6.30 Draw, course N.  $50^{\circ}$  E., near head, asc. 41 ft. over SE. slope.

12.50 Ridge, brs. N.  $60^{\circ}$  E. and S.  $70^{\circ}$  W., desc. 17 ft.

14.30 S. edge of lake, brs. N.  $60^{\circ}$  E. and S.  $70^{\circ}$  W., about 12 chs. long, N. and S. and 5 chs. wide E. and W. Thence across lake, shallow water. No outlet.

26.40 N. edge of lake, brs. S.  $60^{\circ}$  E. and S.  $45^{\circ}$  W. Leave lake, asc. 10 ft. over SE. slope.

32.40 Ridge, brs. N.  $65^{\circ}$  E. and S.  $30^{\circ}$  W., desc. 36 ft. over NW. slope to


39.64 Intersect original point of location of the cor. of Ts. 7 and 8 N., Rs. 28 and 29 E., determined from ties to the three original bearing trees:

A yellow pine, 20 ins. diam., brs. N.  $86^{\circ}$  E., 33 lks. dist., mkd. T8N R29E S31 BT.

A yellow pine, 20 ins. diam., brs. S.  $27\frac{1}{2}^{\circ}$  E., 9 lks. dist., mkd. T7N R29E S6 BT.

A yellow pine, 14 ins. diam., brs. N.  $49^{\circ}$  W., 75 lks. dist., mkd. T8N R28E S36 BT.

Reconstruct this cor. monument as follows: at original point, set an iron post, 3 ft. long, 3 ins. diam., 26 ins. in the ground, for cor. of Ts. 7 and 8 N., Rs. 28 and 29 E., with brass cap mkd.



1936

from which

establish additional bearing trees:

A yellow pine, 15 ins. diam., brs. S.  $76^{\circ}$  W., 80 lks. dist., mkd. T7N R28E S1 BT.

A yellow pine, 24 ins. diam., brs. N.  $52^{\circ}$  W., 77 lks. dist., mkd. T8N R28E S36 BT.

Land, mountainous and gently rolling.

Soil, lava and sandstone, over dark loam, 1st and 4th rates.

Timber, fir, aspen, spruce and yellow pine.

Undergrowth, scrub timber and bunch grass.

## RESURVEY: NORTH BOUNDARY OF T. 7 N., R. 29 E.

BOOK 1018

13

Chains	<p>The North bdy. of T. 7 N., R. 29 E., was surveyed in 1875 by C. B. Foster, U.S.D.S. establishing <math>\frac{1}{4}</math> sec. and sec. cors. alternately, at 40.00 ch. intervals, counting from the E., with common references to areas both sides of the line. The entire line was retraced and resurveyed in 1883, by W.R.Fitzgerald, U.S.D.S., reestablishing all missing cors. at proportional intervals. No other re-tracement or resurvey of this line is of record.</p> <p>The following notes describe a dependent resurvey of the entire line, reconstructing all existing cors. retaining their original references and reestablishing all missing cors. by proportional measurement and monumenting all cors. with regulation brass capped iron posts.</p>
	RETRACEMENT FOR RESURVEY.
	<p>From the cor. of Ts. 7 and 8 N., Rs. 28 and 29 E. East on random line, bet. secs. 6 and 31.</p>
38.76	No trace of original $\frac{1}{4}$ sec. cor. Set temp. cor.
77.67	<p>A point 5 lks. N. of original cor. of secs. 5, 6, 31 and 32. True course and dist. of line bet. secs. 6 and 31, are therefore, S. 89° 58' E., 77.67 chs.</p>
	<p>East on random line, bet. secs. 5 and 32.</p>
40.00	No trace of original $\frac{1}{4}$ sec. cor. Set temp. cor.
79.13	<p>A point 322 lks. N. of original cor. of secs. 4, 5, 32 and 33. True course and dist. of line bet. secs. 5 and 32, are therefore, S. 87° 40' E., 79.20 chs.</p>
	<p>East on random line, bet. secs. 4 and 33.</p>
40.00	No trace of previously reestablished $\frac{1}{4}$ sec. cor. Set temp. cor.
80.48	<p>A point 37 lks. S. of original cor. of secs. 3, 4, 33 and 34. True course and dist. of line bet. secs. 4 and 33, are therefore, N. 89° 44' E., 80.48 chs.</p>
	<p>East on random line, bet. secs. 3 and 34.</p>
40.00	No trace of original $\frac{1}{4}$ sec. cor. Set temp. cor.
80.32	<p>A point 84 lks. S. of original cor. of secs. 2, 3, 34 and 35. True course and dist. of line bet. secs. 3 and 34, are therefore, N. 89° 24' E., 80.32 chs.</p>
	<p>East on random line, bet. secs. 2 and 35.</p>
40.00	No trace of original $\frac{1}{4}$ sec. cor. Set temp. cor.
81.05	<p>A point 87 lks. S. of cor. of secs. 1, 2, 35 and 36. True course and dist. of line bet. secs. 2 and 35, are therefore, N. 89° 23' E., 81.05 chs.</p>

## RESURVEY: NORTH BOUNDARY OF T. 7 N., R. 29 E.

14

Chains	East on random line, bet. secs. 1 and 36.
40.00	No trace of original $\frac{1}{4}$ sec. cor. Set temp. cor.
80.75	A point 2.07 chs. S. of the cor. of Ts. 7 and 8 N., Rs. 29 and 30 E. True course and dist. of line bet. secs. 1 and 36, are therefore, N. $88^{\circ} 32'$ E., 80.78 chs.
RESURVEY.	
	From the cor. of Ts. 7 and 8 N., Rs. 28 and 29 E., hereinbefore described.
	S. $89^{\circ} 58'$ E., on true line, bet. secs. 6 and 31.
	Over rolling land, thru dense timber and scattering undergrowth. Asc. 34 ft. over NW. slope.
14.40	Ridge, brs. N. $60^{\circ}$ E. and S. $70^{\circ}$ W. Leave rolling and enter mountainous land; desc. 244 ft. over SE. slope.
30.25	Ravine, course N., asc. 38 ft. over W. slope.
33.00	Spur, slopes N., desc. 69 ft. over E. slope.
36.85	Ravine, course N. $30^{\circ}$ E., asc. 10 ft. over NW. slope to
38.12	(Proportional dist.) Set an iron post, 3 ft. long, 1 in. diam., 12 ins. in the ground to bedrock, and in a mound of stone to top for $\frac{1}{4}$ sec. cor., with brass cap mkd.
	$\frac{1}{4} \frac{S 31}{S 6}$
	1936
	from which
	A fir, 12 ins. diam., brs. N. $48\frac{1}{4}^{\circ}$ E., 105 lks. dist., mkd. $\frac{1}{4}$ S31 BT.
	A yellow pine, 16 ins. diam., brs. S. $82\frac{1}{4}^{\circ}$ E., 99 lks. dist., mkd. $\frac{1}{4}$ S6 BT.
	Asc. slightly over NW. slope.
39.95	Spur, slopes N., from SW., desc. 229 ft. over E. slope.
48.40	Draw, course N. $10^{\circ}$ E., asc. 12 ft. over NW. slope.
50.89	Spur, slopes N. $10^{\circ}$ E., desc. 33 ft. over E. slope.
53.35	Draw, course NE., asc. 30 ft. over NW. slope.
55.10	Point of spur, slopes NE., desc. 94 ft. over NE. slope.
62.40	Creek with stream of running water, 4 lks. wide, 3 ins. deep, course S. $20^{\circ}$ E., asc. 88 ft. over SW. slope.
67.16	Spur, slopes S. $20^{\circ}$ E. Leave mountainous and enter rolling land. Desc. 12 ft. over SE. slope.
75.60	Asc. 12 ft. over SW. slope.
77.00	Spur, slopes E. from NW. Desc. slightly along spur, to
77.67	Intersect original cor. of secs. 5, 6, 31 and 32, which

RESURVEY: NORTH BOUNDARY OF T. 7 N., R. 29 E.

BOOK

15

## Chains

is a mound of stone, 4 ft. base, 2 ft. high. No marked stone or accessories.

Reconstruct this cor. monument as follows: remove the mound of stone and in the center of its position, set an iron post, 3 ft. long, 2 ins. diam., 22 ins. in the ground to bedrock, and in a mound of stone to top, for cor. of secs. 5, 6, 31 and 32, with brass cap mkd.

T8N	R29E
S31	S32
S6	S5
T7N	

1936

from which

A yellow pine, 14 ins. diam., brs. N.  $8\frac{1}{4}^{\circ}$  E., 94 lks. dist., mkd. T8N R29E S32 BT.

A yellow pine, 20 ins. diam., brs. S.  $67\frac{1}{2}^{\circ}$  E., 183 lks. dist., mkd. T7N R29E S5 BT.

A yellow pine, 20 ins. diam., brs. S.  $41^{\circ}$  W., 23 lks. dist., mkd. T7N R29E S6 BT.

A yellow pine, 10 ins. diam., brs. N.  $39\frac{1}{2}^{\circ}$  W., 35 lks. dist., mkd. T8N R29E S31 BT.

Land, mountainous and rolling.

Soil, lava and sandstone, over dark loam, 1st and 4th rates.

Timber, yellow pine, fir, aspen and spruce.

Undergrowth, scrub timber.

S.  $87^{\circ} 40'$  E., on true line, bet. secs. 5 and 32.

Over rolling land, thru dense timber and scattering undergrowth. Desc. 100 ft. along top of spur, sloping E.

20.40 Leave spur, slopes S.  $50^{\circ}$  E. from W.

Leave rolling and enter mountainous land. Desc. 143 ft. over NE. slope.

26.30 Ravine, course S.  $30^{\circ}$  E., asc. 89 ft. over SW. slope.

33.30 Point of spur, slopes S.  $70^{\circ}$  E. Desc. 113 ft. over E. slope.

39.00 Head of draw, course S. Asc. slightly over SW. slope to

39.60 (Mid point). Set an iron post, 3 ft. long, 1 in. diam., 18 ins. in the ground to bedrock, and in a mound of stone to top, for  $\frac{1}{4}$  sec. cor. with brass cap mkd.

$\frac{1}{4}$	S 32
	S 5

1936

from which

A yellow pine, 14 ins. diam., brs. N.  $14^{\circ}$  E., 40 lks. dist., mkd.  $\frac{1}{4}$  S32 BT.

A yellow pine, 16 ins. diam., brs. S.  $48\frac{1}{4}^{\circ}$  W., 33 lks. dist., mkd.  $\frac{1}{4}$  S5 BT.

Asc. 17 ft. over SW. slope.

## Chains

- 45.45 Ridge, brs. N. 75° W., and E., thence along top of ridge; desc. 26 ft. to
- 47.50 Leave top of ridge, brs. N. 70° E. and W.; desc. 177 ft. over SE. slope.
- 54.80 Water Canyon Creek, with stream of running water, 12 lks. wide, 6 ins. deep, course N. 75° E.; asc. 122 ft. over NW. slope.
- 64.37 Spur, slopes N. 15° E.; desc. 98 ft. over NE. slope.
- 70.65 Creek with stream of water 4 lks. wide, 2 ins. deep, course N.; asc. 113 ft. over NW. slope to
- 79.20 Intersect. original cor. of secs. 4, 5, 32 and 33, which is a lava stone, 10x10x8 ins. mkd. with 2 grooves on W. face and 4 grooves on E. face, firmly set in a mound of stone and witnessed by three bearing trees.  
Reconstruct this cor. monument, as follows: remove the mound of stone and the original cor. stone and in same place, set an iron post, 3 ft. long, 2 ins. diam., 24 ins. in the ground to bedrock, with the original corner stone reset alongside, and in mound of stone to top for cor. of secs. 4, 5, 32 and 33, with brass cap mkd.

T8N	R29E
S32	S33
S5	S4
T7N	

1936

from which

the original bearing trees:

A yellow pine, 12 ins. diam., (dead and fallen) brs. N. 7° E., 44 lks. dist., mkd. T8N R29E S33 BT.

A yellow pine, 10 ins. diam., (half dead) brs. S. 57½° E., 69 lks. dist., mkd. T7N R29E S4 BT.

A yellow pine, 14 ins. diam., brs. S. 83° W., 50 lks. dist., mkd. T7N R29E S5 BT.

Establish additional bearing trees:

A yellow pine, 8 ins. diam., brs. N. 60½° E., 30 lks. dist., mkd. T8N R29E S33 BT.

A yellow pine, 16 ins. diam., brs. S. 51½° E., 67 lks. dist., mkd. T7N R29E S4 BT.

A yellow pine, 8 ins. diam., brs. S. 61½° W., 19 lks. dist., mkd. T7N R29E S5 BT.

A yellow pine, 8 ins. diam., brs. N. 50° W., 30 lks. dist., mkd. T8N R29E S32 BT.

Land, rolling and mountainous.

Soil, lava and sandstone, over dark loam, 3rd and 4th rates.

Timber, yellow pine, juniper, aspen, fir and spruce.

Undergrowth, scrub timber.

RESURVEY: NORTH BOUNDARY OF T. 7 N., R. 29 E.

Chains  
 N. 89° 44' E. on true line, bet. secs. 4 and 33.  
 Over mountainous land, thru dense timber and scattering undergrowth. Asc. 27 ft. over NW. slope.

1.45 Spur, slopes N. 60° W.; desc. 6 ft. over NE. slope.

2.63 Ravine, course N. 60° W.; asc. 406 ft. over NW. slope.

8.90 U.S. Forest Service telephone line, brs. S. 30° E. and N. 30° W.

9.17 Graded highway, brs. N. 30° W. to Springerville and south.

19.81 W. rim of mesa, brs. N. 75° E. and S. 30° W. Leave mountainous and enter nearly level land on mesa. Timber becomes scattering.

31.50 Leave scattering timber, brs. NE. and SW. and enter open grassy land.

40.24 (Mid point) Set an iron post, 3 ft. long, 1 in. diam., 26 ins. in the ground, for  $\frac{1}{4}$  sec. cor., with brass cap mkd.

$\frac{1}{4}$   $\frac{S\ 33}{S\ 4}$

1936

from which

Right fork of juniper, 6 ins. diam., brs. N. 29° E., 308 lks. dist., mkd.  $\frac{1}{4}$  S33 BT.

A scrub pine, 10 ins. diam., brs. N. 74 $\frac{1}{2}$ ° W., 197 lks. dist., mkd.  $\frac{1}{4}$  S33 BT.

Continue over open grassy land on mesa. Asc. 40 ft. over SW. slope to.

76.30 E. rim of mesa brs. NE. and SW. Leave nearly level top of mesa and enter gently rolling grassy land, thru very scattering timber. Desc. 6 ft. over S. slope to

80.48 Intersect original cor. of secs. 3, 4, 33 and 34, which is a lava stone, 18x16x6 ins. mkd. with 3 grooves on each of E. and W. faces, firmly set in a mound of stone, and witnessed by one record bearing tree NE.  
 Reconstruct this cor. monument as follows: remove the mound of stone and the original cor. stone, and in same place, set an iron post, 3 ft. long, 2 ins. diam., 24 ins. in the ground to bedrock, with the original corner stone reset alongside, and in mound of stone to top for cor. of secs. 3, 4, 33 and 34, with brass cap mkd.

T8N	R29E
S33	S34
S4	S3
T7N	

1936

from which

the original bearing tree:

A juniper fork, 5 ins. diam., brs. N. 38 $\frac{1}{2}$ ° E., 189 lks. dist., mkd. BT. Remark T8N R29E S34 BT.

and establish additional bearing trees:

Chains

A juniper fork, 6 ins. diam., brs. S. 89 1/4° E., 370 lks. dist., mkd. T7N R29E S3 BT.

A scrub pine, 10 ins. diam., brs. S. 60° W., 198 lks. dist., mkd. T7N R29E S4 BT.

A scrub pine, 12 ins. diam., brs. N. 0° 15' W., 294 lks. dist., mkd. T8N R29E S33 BT.

Saffell Knoll brs. N. 50° E., vertical angle + 9°.

Land, mountainous, nearly level and gently rolling. Soil, lava and sandstone over dark loam, 1st and 4th rates. Timber, yellow and scrub pine. Undergrowth, scrub timber. Fair grass.

N. 89° 24' E., on true line, bet. secs. 3 and 34.

Over gently rolling grassy land, thru scattering timber.

Desc. 62 ft. over S. slope to

35.00 Low ridge bears E. and N. 80° W. Desc. 26 ft. along broad top of ridge to

40.16 (Mid point) Set an iron post, 3 ft. long, 1 in. diam., 22 ins. in the ground to bedrock, and in a mound of stone to top, for 1/4 sec. cor., with brass cap mkd.

1/4 S 34 / S 3

1936

from which

A juniper fork, 6 ins. diam., brs. N. 17 1/4° E., 72 lks. dist., mkd. BT only.

A juniper, 6 ins. diam., brs. S. 18 1/4° W., 320 lks. dist., mkd. 1/4 S3 BT.

Saffell Knoll brs. N. 59° W.

Continue along broad top of ridge bearing E. and W., thru scattering timber and over grassy land. Desc. 135 ft. to

80.32 Intersect original cor. of secs. 2, 3, 34 and 35, which is a lava stone, 16x16x8 ins. mkd. with 2 grooves on E. face and 4 grooves on W. face, firmly set in a mound of stone. No accessories.

Reconstruct this cor. monument as follows: remove the mound of stone and the original cor. stone, and in same place, set an iron post, 3 ft. long, 2 ins. diam., 24 ins. in the ground to bedrock, with the original cor. stone reset alongside and in mound of stone to top for cor. of secs. 2, 3, 34 and 35, with brass cap mkd.

T8N | R29E  
S34 | S35  
---  
S3 | S2  
T7N

1936

from which

A juniper fork, 6 ins. diam., brs. N. 15° E., 445 lks. dist., mkd. T8N R29E S35 BT.

## RESURVEY: NORTH BOUNDARY OF T. 7 N., R. 29 E.

19

## Chains

A juniper, 4 ins. diam., brs. S.  $29\frac{1}{2}^{\circ}$  E., 101 lks. dist., mkd. T7N R29E S4 BT.

A juniper, 30 ins. diam., brs. S.  $5^{\circ}$  W., 291 lks. dist., mkd. T7N R29E S3 BT.

A juniper, 6 ins. diam., brs. N.  $87\frac{1}{4}^{\circ}$  W., 374 lks. dist., mkd. T7N R29E S3 BT.

Land, gently rolling.  
Soil, lava and sandstone over dark loam, 1st and 4th rates.  
Timber, scrub pine and juniper.  
Undergrowth, scrub timber.  
Fair grass.

N.  $89^{\circ} 23'$  E. on true line, bet. secs. 2 and 35.

Over gently rolling grassy land, thru scattering timber and undergrowth.

Desc. 40 ft. along broad top of ridge, bearing E. and W.

15.00 Leave top of ridge, bears W. and S.  $60^{\circ}$  E. Enter rolling land. Desc. 200 ft. over NE. slope to

40.52 (Mid point) Set an iron post, 3 ft. long, 1 in. diam., 28 ins. in the ground, and in a mound of stone to top, for  $\frac{1}{4}$  sec. cor., with brass cap mkd.

$$\frac{1}{4} \frac{S 35}{S 2}$$

1936

from which

A juniper, 5 ins. diam., brs. N.  $22^{\circ}$  E., 43 lks. dist., mkd.  $\frac{1}{4}$  S35 BT.

A juniper, 10 ins. diam., brs. S.  $80^{\circ}$  W., 130 lks. dist., mkd.  $\frac{1}{4}$  S2 BT.

Desc. 63 ft. over NE. slope.

52.20 Wash, 10 lks. wide, 2 ft. deep, course N.  $30^{\circ}$  W.; asc. 41 ft. over NW. slope.

56.15 Fence (4 strand barbed wire) brs. N. and S. Fence cor. brs. S., 150 lks. dist. from which fences extend E., W. and N.

59.60 Fence (4 strand barbed wire) brs. N.  $62\frac{1}{2}^{\circ}$  E. and S.  $62\frac{1}{2}^{\circ}$  W.

60.00 North Rim of mesa brs. N.  $60^{\circ}$  E. and S.  $60^{\circ}$  W. Asc. 9 ft. across mesa to

70.00 N. rim of mesa brs. N.  $75^{\circ}$  W. and S.  $75^{\circ}$  E. Leave mesa. Desc. 33 ft. over NE. and N. slopes to

81.05 Intersect original cor. of secs. 1, 2, 35 and 36, which is a sandstone, 12x12x8 ins. mkd. with 1 groove on E. face and 5 grooves on W. face, firmly set in a mound of stone.

Reconstruct this cor. monument as follows: remove the mound of stone and the original cor. stone and in same place, set an iron post, 3 ft. long, 2 ins. diam., 2 ins. in the ground to bedrock, resetting the original stone alongside, for the cor. of secs. 1, 2, 35 and 36, with brass cap mkd.

BOOK 100

. RESURVEY: NORTH BOUNDARY OF T. 7 N., R. 29 E.

20.

Chains

$$\begin{array}{c} \text{T8N R29E} \\ \hline \text{S35 | S36} \\ \hline \text{S2 | S1} \\ \hline \text{T7N} \end{array}$$

1936

from which

A juniper, 10 ins. diam., brs. N.  $46\frac{3}{4}^\circ$  E., 143 lks. dist., mkd. T8N R29E S36 BT.

A juniper, 6 ins. diam., brs. S.  $21\frac{1}{2}^\circ$  E., 98 lks. dist., mkd. T7N R29E S1 BT.

A juniper, 9 ins. diam., brs. S.  $32\frac{1}{4}^\circ$  W., 136 lks. dist., mkd. T7N R29E S2 BT.

A juniper, 5 ins. diam., brs. N.  $30\frac{1}{2}^\circ$  W., 112 lks. dist., mkd. BT only.

Land, rolling.

Soil, lava and sandstone, over dark loam, 1st and 4th rates.

Timber, scrub pine and juniper.

Undergrowth, scrub timber.

Fair grass.

N.  $88^\circ 32'$  E.; on true line, bet. secs. 1 and 36.

Over gently rolling land, thru scattering timber and undergrowth. Desc. slightly over N. slope to

- 4.00 N. rim of mesa brs. N.  $70^\circ$  E. and S.  $70^\circ$  W. Thence across mesa. Desc. 6 ft. to
- 14.00 N. rim of mesa brs. NW. and SE. Leave mesa. Desc. 42 ft. over NE. slope to
- 22.45 Leave gently rolling, and enter mountainous land. Desc. 197 ft. over steep NE. slope to
- 37.16 Leave mountainous and enter rolling land. Desc. 11 ft. over N. slope to
- 40.39 (Mid point) Set an iron post, 3 ft. long, 1 in. diam., 24 ins. in the ground to bedrock and in a small mound of stone to top, for  $\frac{1}{4}$  sec. cor., with brass cap mkd.
 

$$\frac{1}{4} \frac{\text{S36}}{\text{S1}}$$

1936

from which

A juniper, 6 ins. diam., brs. N.  $87\frac{1}{4}^\circ$  E., 101 lks. dist., mkd.  $\frac{1}{4}$  S36 BT.

A juniper, 6 ins. diam., brs. S.  $64\frac{1}{2}^\circ$  W., 182 lks. dist., mkd.  $\frac{1}{4}$  S1 BT.
- Desc. 29 ft. over N. slope.
- 50.42 Asc. 18 ft. over NW. slope.
- 52.40 Short spur, slopes N. Desc. 75 ft. over NE. slope.
- 58.90 Wash, 25 lks. wide, 6 ft. deep, course N.  $75^\circ$  E., from N.  $75^\circ$  W.; asc. 40 ft. over NW. slope.

RESURVEY: NORTH BOUNDARY OF T. 7 N., R. 29 E.

Chains

62.30 Desc. slightly over N. slope to

67.00 N. rim of mesa brs. N. 85° E. and S. 70° W. Thence across rolling top of mesa. Desc. 100 ft. to

80.78 Intersect the corner of Ts. 7 and 8 N., Rs. 29 and 30 E., which is an iron post, 3 ins. diam., projecting 12 ins. above ground, firmly set, mkd. on brass cap and witnessed as described in the official record.

Land, gently rolling, rolling and mountainous.  
Soil, lava and sandstone, over dark loam, 1st and 4th rates.

Timber, yellow and scrub pine, pinyon and juniper.  
Undergrowth, scrub timber and bunch grass.

## RESURVEY: SUBDIVISION LINES, T. 7 N., R. 29 E.

22

## Chains

The subdivision lines of T. 7 N., R. 29 E. were surveyed in 1883 by W.R.Fitzgerald, U.S.D.S. and no retracement or resurvey of any part of same is of record. The following notes describe a dependent resurvey of all of the subdivision lines of said Tp. reconstructing all existing corner monuments, reestablishing all missing corners by proportional measurement, and, unless otherwise stated herein, monumenting all subdivisional corners in the Tp. with regulation brass-capped iron posts.

Commence said dependent resurvey at the cor. of secs. 1, 2, 35 and 36, on S. bdy. of the Tp. Reconstructed under this group and described in notes of resurvey of N. bdy. of T. 6 N., R. 29 E.

Thence,

N. 0° 12' E., on true line, bet. secs. 35 and 36 (S.  $\frac{1}{2}$ ).

Over nearly level, open cultivated land, along fence, bearing N. and S.

- 18.70 Summer ranch house, brs. W., about 4.00 chs. dist.
- 19.20 White Mountain Ranch house, brs. E., about 7.00 chs. dist.
- 20.14 Intersect fence cor. from which fences extend W. and S.
- 35.00 Leave cultivated land.
- 35.75 Wash, 25 lks. wide, 8 ft. deep, course SE. Leave nearly level and enter rolling land. Asc. 33 ft. over S. slope to  $\frac{1}{4}$  sec. cor.
- 36.05 Intersect fence cor. from which fences extend W. and N.
- 36.15 Road, brs. W. and SE. Leave open land and enter dense timber and scattering undergrowth, brs. E. and W.
- 39.91 Intersect original  $\frac{1}{4}$  sec. cor. of secs. 35 and 36, which is a sandstone, 15x12x10 ins. mkd.  $\frac{1}{4}$  on W. face and firmly set in a mound of stone. No accessories. Reconstruct this cor. monument as follows: remove the mound of stone and the original cor. stone, and in same place, set an iron post, 3 ft. long, 1 in. diam., 27 ins. in the ground, with the original cor. stone reset alongside, for  $\frac{1}{4}$  sec. cor. with brass cap mkd.

$$\begin{array}{c} \frac{1}{4} \\ S35 \mid S36 \\ 1936 \end{array}$$

from which

A juniper, 24 ins. diam., brs. S. 64 $\frac{1}{2}$ ° W., 78 lks. dist., mkd.  $\frac{1}{4}$  S35 BT.

An oak, 7 ins. diam., brs. S. 74 $\frac{1}{2}$ ° E., 71 lks. dist., mkd.  $\frac{1}{4}$  S36 BT.

Thence,

N. 0° 30' E. on true line, bet. secs. 35 and 36 (N.  $\frac{1}{2}$ ).

Over rolling land, thru dense timber and scattering undergrowth.

Asc. 29 ft. over S. slope.

## RESURVEY: SUBDIVISION LINES, T. 7 N., R. 29 E.

23

## Chains

- 3.10 Spur, slopes E.; desc. 60 ft. over gradual N. slope.
- 4.07 Intersect fence cor. from which fences extend N., S.; and W.
- 4.95 Leave rolling and enter mountainous land. Desc. 26 ft. over N. slope to
- 9.40 Colter Creek, with stream of running water, 6 lks. wide, 6 ins. deep, course E.; asc. 425 ft. over S. slope to

39.15 Intersect original cor. of secs. 25, 26, 35 and 36, which is a lava stone, 16x12x10 ins., mkd. with 1 groove on each of E. and S. faces, firmly set in a mound and witnessed by the two record bearing trees.  
Reconstruct this cor. monument as follows: remove the mound of stone and the original cor. stone, and in same place, set an iron post, 3 ft. long, 2 ins. diam., 27 ins. in the ground, with the original cor. stone reset alongside, for cor. of secs. 25, 26, 35 and 36, with brass cap mkd.

T7N	R29E
S26	S25
S35	S36

1936

from which

the original bearing trees:

A yellow pine, 18 ins. diam., N. 52° E., 57 lks. dist. mkd. T7N R29E S25 BT.

A juniper, 30 ins. diam., S. 71½° W., 20 lks. dist., mkd. T7N R29E S35 BT.

and establish additional bearing trees:

A yellow pine, 12 ins. diam., brs. N. 50° E., 58 lks. dist., mkd. T7N R29E S25 BT.

A yellow pine, 20 ins. diam., brs. S. 33½° E., 83 lks. dist., mkd. T7N R29E S36 BT.

A yellow pine, 20 ins. diam., brs. S. 39° W., 38 lks. dist., mkd. T7N R29E S35 BT.

A yellow pine, 9 ins. diam., brs. N. 33½° W., 134 lks. dist., mkd. T7N R29E S26 BT.

Land, nearly level, rolling and mountainous.  
Soil, volcanic loam, 1st and 4th rates.  
Timber, yellow pine, juniper and oak.  
Undergrowth, scrub timber and bunchgrass.

From the cor. of secs. 25, 30, 31 and 36, on E. bdy. of the Tp., which is an iron post, 2 ins. diam., projecting 10 ins. above ground, firmly set, mkd. on brass cap and witnessed as described in the official record.

N. 89° 30' W., on true line, bet. secs. 25 and 36.

Over mountainous land, thru dense timber and scattering undergrowth. Desc. 30 ft. over SW. slope.

5.30 Draw, course SE., asc. 270 ft. over E. slope.

## RESURVEY: SUBDIVISION LINES, T. 7 N., R. 29 E.

24

Chains

- 19.30 Spur, slopes SE.; desc. 47 ft. over SW. slope.
- 22.30 Drain, course SE.; asc. 23 ft. over E. slope.
- 24.00 Short spur, slopes SE.; desc. 37 ft. over SW. slope.
- 29.75 Drain, course SE.; asc. 163 ft. over SE. slope to
- 39.65 (Mid point) Set an iron post, 3 ft. long, 1 in. diam., 27 ins. in the ground, for  $\frac{1}{4}$  sec. cor., with brass cap mkd.
- $\frac{1}{4}$   $\frac{S\ 25}{S\ 36}$
- 1936
- from which
- A yellow pine, 8 ins. diam., brs. S.  $38\frac{1}{2}^{\circ}$  E., 88 lks. dist., mkd.  $\frac{1}{4}$  S36 BT.
- A yellow pine, 8 ins. diam., brs. N.  $46^{\circ}$  W., 33 lks. dist., mkd.  $\frac{1}{4}$  S25 BT.
- Asc. 227 ft. over SE. slope to
- 54.25 Leave mountainous and enter rolling land. Asc. 82 ft. over S. slope to
- 79.30 The cor. of secs. 25, 26, 35 and 36.
- Land, mountainous and rolling.  
Soil, volcanic loam, 3rd and 4th rates.  
Timber, pine; juniper and oak.  
Undergrowth, scrub timber and bunch grass.
- 
- N.  $0^{\circ} 30'$  W., on true line, bet. secs. 25 and 26. (S.  $\frac{1}{2}$ ).
- Over rolling land, thru dense timber and scattering undergrowth. Asc. 20 ft. over S. slope.
- 6.00 Ridge, brs. E. and W. Desc. 63 ft. over N. slope.
- 14.85 Draw, course E.; asc. 86 ft. over SE. slope to
- 25.80 S. edge of flat top of spur brs. NE. and SW. Thence across top of spur sloping NE. Desc. 15 ft. to
- 34.40 N. edge of top of spur, brs. NE. and SW. Leave top of spur. Desc. 44 ft. over NW. slope.
- 39.90 Drain, course N.  $60^{\circ}$  E. Asc. slightly over SE. slope to
- 40.04 Intersect original  $\frac{1}{4}$  sec. cor. of secs. 25 and 36, which is a lava stone, 14x10x8 ins. mkd.  $\frac{1}{4}$  on W. face, firmly set in a mound of stone and witnessed by the original bearing tree SE.
- Reconstruct this cor. monument as follows: remove the mound of stone and the original cor. stone, and in same place, set an iron post, 3 ft. long; 1 in. diam., 27 ins. in the ground, with the original cor. stone reset alongside, for  $\frac{1}{4}$  sec. cor., with brass cap mkd.

$\frac{1}{4}$   
S26 | S25

1936

from which

RESURVEY: SUBDIVISION LINES, T. 7 N., R. 29 E.

Chains

the original bearing tree:

A yellow pine, 24 ins. diam., brs. S.  $73\frac{1}{4}^{\circ}$  E., 28 lks. dist., mkd.  $\frac{1}{4}$  S BT.

and establish additional bearing trees:

A yellow pine, 8 ins. diam., brs. N.  $45\frac{1}{2}^{\circ}$  E., 22 lks. dist., mkd.  $\frac{1}{4}$  S25 BT.

A yellow pine, 8 ins. diam., brs. S.  $52^{\circ}$  E., 54 lks. dist., mkd.  $\frac{1}{4}$  S26 BT.

Thence,

N.  $0^{\circ} 14'$  E., on true line, bet. secs. 25 and 26 ( $N.\frac{1}{2}$ ).

Over rolling land, thru dense timber and scattering undergrowth.

Asc. slightly over SE. slope.

6.97 Spur, slopes E; desc. 134 ft. over N. slope.

14.68 Leave timber and undergrowth, brs. NE. and SW. and enter open grassy land.

19.68 Riggs Creek, with stream of running water, 3 lks. wide, 3 ins. deep, course NE. Asc. 16 ft. over SE. slope.

20.68 Fence ( 4 strand barbed wire) brs. E. and W. Enter cultivated field, thence across W. side of same, about 3.50 chs. E. of fence bearing N. and S.

21.70 Leave cultivated field, brs. E. and W.

24.65 Ascend gradually over E. slope.

24.80 NE. cor. of deserted log cabin, 18 x 24 ft.

26.00 Enter cultivated land, brs. E. and W.

34.00 Leave cultivated land, brs. E. and W. Asc. 34 ft. over SE. slope to

39.67 Intersect original cor. of secs. 23, 24, 25 and 26, which is a lava stone, 14x10x6 ins. mkd. with 1 notch on E. face and 2 notches on S. face, firmly set in a mound of stone and witnessed by the one record bearing tree SE. Reconstruct this cor. monument as follows: remove the mound of stone and the original cor. stone, and in same place set an iron post, 3 ft. long, 2 ins. diam., 27 ins. in the ground, with the original cor. stone reset alongside, for cor. of secs. 23, 24, 25 and 26, with brass cap mkd.

T7N	R29E
S23	S24
S26	S25

1936

from which

the original bearing tree:

A yellow pine, 18 ins. diam., brs. S.  $16^{\circ}$  E., 45 lks. dist., mkd. T7N R29E S25 BT.

and establish additional bearing trees:

## RESURVEY: SUBDIVISION LINES, T. 7 N., R. 29 E.

26

Chains	<p>A yellow pine, 10 ins. diam., brs. N. <math>38\frac{1}{2}^{\circ}</math> E., 107 lks. dist., mkd. T7N R29E S24 BT.</p> <p>A yellow pine, 24 ins. diam., brs. S. <math>9^{\circ}</math> E., 58 lks. dist., mkd. T7N R29E S25 BT.</p> <p>A yellow pine, 22 ins. diam., brs. S. <math>72^{\circ}</math> W., 93 lks. dist., mkd. T7N R29E S26 BT.</p> <p>A yellow pine, 8 ins. diam., brs. N. <math>24\frac{1}{2}^{\circ}</math> W., 72 lks. dist., mkd. T7N R29E S23 BT.</p> <p>Land, rolling. Soil, rocky, volcanic loam, 1st and 4th rates. Timber, yellow pine and juniper. Undergrowth, scrub timber. Fair grass.</p>
	<p>From the cor. of secs. 19, 24, 25 and 30, on E. bdy. of the Tp., which is an iron post, 2 ins. diam., projecting 12 ins. above ground, firmly set mkd. on brass cap and witnessed as described in the official record.</p> <p>N. <math>89^{\circ} 17'</math> W., on true line, bet. secs. 24 and 25.</p> <p>Over mountainous land, thru timber and scattering undergrowth.</p> <p>Asc. 155 ft. over SE. slope to</p> <p>9.60 Rim of mesa, brs. NE. and SW. Leave mountainous land and timber. Thence over gently rolling land on mesa, thru scattering undergrowth. Asc. 52 ft. over E. slope to</p> <p>19.50 Leave gently rolling and enter nearly level land, continuing over mesa.</p> <p>39.54 (Mid point) Set an iron post, 3 ft. long, 1 in. diam., 18 ins. in the ground to bedrock, with a lava stone, 4x4x6 ins. mkd. with a cross (X) deposited at base of post, and in a mound of stone to top, for <math>\frac{1}{4}</math> sec. cor., with brass cap mkd.</p> <p style="text-align: center;"><math>\frac{1}{4} \frac{S24}{S25}</math></p> <p style="text-align: center;">1936</p> <p>Continue over nearly level land on mesa, thru scattering undergrowth.</p> <p>41.00 Fence ( 4 strand barbed wire) brs. N. and S.</p> <p>49.50 Rim of mesa brs. NE. and SW. Leave mesa and enter mountainous land and dense timber. Desc. 118 ft. over NW. slope.</p> <p>58.00 Leave timber, brs. NE. and SW.</p> <p>61.10 Riggs Creek, with stream of water, 5 lks. wide, 10 ins. deep, course NE. Leave mountainous and enter nearly level cultivated land.</p> <p>74.00 Leave nearly level cultivated land and enter rolling land, scattering timber and undergrowth. Asc. 34 ft. over SE. slope to</p> <p>79.08 The cor. of secs. 23, 24, 25 and 26.</p>

## RESURVEY: SUBDIVISION LINES, T. 7 N., R. 29 E.

27

## Chains

Land, mountainous, gently rolling and nearly level.  
Soil, rocky, over volcanic loam, 2nd and 4th rates.  
Timber, yellow pine, fir and aspen.  
Undergrowth, scrub timber and bunch grass.

N. 0° 08' W., on true line, bet. secs. 23 and 24 (S.  $\frac{1}{2}$ ).

Over rolling land, thru scattering timber and undergrowth.  
Asc. 24 ft. over SE. slope to

2.30 Rim of mesa, brs. NE. and W. Thence across nearly level top of mesa.

27.30 Shallow draw, course NE. Descend gradually over E. slope to

40.52 Intersect original  $\frac{1}{4}$  sec. cor. of secs. 23 and 24, which is a lava stone, 14x8x6 ins. mkd.  $\frac{1}{4}$  on W. face, firmly set in a mound of stone. No accessories.  
Reconstruct this cor. monument as follows: remove the mound of stone and the original cor. stone, and in same place, set an iron post, 3 ft. long, 1 in. diam., 26 ins. in the ground, with the original cor. stone reset alongside, for  $\frac{1}{4}$  sec. cor., with brass cap mkd.

S23 | S24  
1936

from which

A yellow pine, 8 ins. diam., brs. S. 82° W., 77 lks. dist., mkd.  $\frac{1}{4}$  S24 BT.

A yellow pine, 12 ins. diam., brs. S. 55° E., 24 lks. dist., mkd.  $\frac{1}{4}$  S23 BT.

Thence,

North on true line, bet. secs. 23 and 24 (N.  $\frac{1}{2}$ ).

Over nearly level land, on mesa, thru scattering timber and undergrowth. Desc. gradually over NE. slope.

0.80 Fence (4 strand barbed wire) brs. E. and W. Fence cor. brs. E. 38 lks. dist. from which fences extend N. 5° E., E. and W.

5.10 Rim of mesa, brs. E. and W. Leave nearly level land on mesa and enter rolling land. Desc. 40 ft. over N. slope.

13.30 Draw, course NE.; asc. 125 ft. over SE. slope to

40.31 Intersect original cor. of secs. 13, 14, 23 and 24, which is a lava stone, 12x10x8 ins. mkd. with 1 notch on E. face and 3 notches on S. face, firmly set in a mound of stone and witnessed by the one record bearing tree NW.  
Reconstruct this cor. monument as follows: remove the mound of stone and the original cor. stone, and in same place, set an iron post, 3 ft. long, 2 ins. diam., 26 ins. in the ground, with the original cor. stone reset alongside, for cor. of secs. 13, 14, 23 and 24, with brass cap mkd.

T7N R29E  
S14 | S13  
S23 | S24

1936

Chains	<p style="text-align: right;">from which</p> <p>the original bearing tree:</p> <p>A juniper, 30 ins. diam., brs. N. 42½° W., 128 lks. dist., mkd. T7N R29E S14 BT.</p> <p>and establish additional bearing trees:</p> <p>A yellow pine, 8 ins. diam., brs. N. 43½° E., 169 lks. dist., mkd. T7N R29E S13 BT.</p> <p>A juniper, 10 ins. diam., brs. N. 38½° W., 59 lks. dist., mkd. T7N R29E S14 BT.</p> <p>A juniper, 6 ins. diam., brs. S. 44½° E., 111 lks. dist., mkd. T7N R29E S24 BT.</p> <p>A yellow pine, 6 ins. diam., brs. S. 77° W., 115 lks. dist., mkd. T7N R29E S23 BT.</p> <p>Land, rolling and nearly level. Soil, rocky, volcanic loam, 2nd and 3rd rates. Timber, yellow pine, juniper and oak. Undergrowth, scrub timber and bunch grass.</p> <hr/> <p>From the cor. of secs. 13, 18, 19 and 24, on E. bdy. of the Tp. which is an iron post, 2 ins. diam., firmly set in a mound of stone, mkd. on brass cap and witnessed as described in the official record.</p> <p>N. 89° 05' W., on true line, bet. secs. 13 and 24.</p> <p>Over rolling land, thru scattering timber and undergrowth.</p> <p>Desc. 26 ft. over NW. slope.</p> <p>4.88 Riggs Creek, with stream of running water, 3 lks. wide, 2 ins. deep, course NE.; asc. 52 ft. over SE. slope.</p> <p>12.90 Spur, slopes NE. Ascend 30 ft. over N. slope to ¼ sec. cor.</p> <p>23.78 Fence ( 4 strand barbed wire) brs. N. and S.</p> <p>39.64 (Mid point) Set an iron post, 3 ft. long, 1 in. diam., 22 ins. in the ground, to bedrock, and in a mound of stone to top, for ¼ sec. cor., with brass cap mkd.</p> <div style="text-align: center;"> <p>¼ <math>\frac{S 13}{S 24}</math></p> <p>1936</p> </div> <p>No bearing trees available, raise a mound of stone, 3 ft. base, 2 ft. high, N. of cor.</p> <p>Descend 10 ft. over NW. slope.</p> <p>45.78 Draw, course N. 60° E., asc. 155 ft. over SE. slope to sec. cor.</p> <p>66.54 Fence ( 4 strand barbed wire) brs. N. and S.</p> <p>79.28 The cor. of secs. 13, 14, 23 and 24.</p> <p>Land, rolling. Soil, lava stone over volcanic loam, 2nd and 3rd rates.</p>
--------	---

## RESURVEY: SUBDIVISION LINES, T. 7 N., R. 29 E.

29

Chains	Timber, pine and juniper. Undergrowth, scrub timber and bunch grass.
	N. 0° 14' E., on true line, bet. secs. 13 and 14. Over rolling land, thru scattering timber and undergrowth. Asc. 57 ft. over SE. slope to
7.95	S. edge of top of spur brs. NE. and W. Thence across top of spur sloping E.
15.40	N. edge of top of spur, brs. E. and W. Leave top of spur and enter mountainous land. Desc. 100 ft. over N. slope.
21.47	Drain, course E., asc. 36 ft. over S. slope.
26.43	Spur, slopes E.; desc. 139 ft. over N. slope.
39.24	Old road, brs. E. and W.
39.86	Guich, with water in pools, course E. Asc. slightly over S. slope to
40.02	(Mid point) Set an iron post, 3 ft. long, 1 in. diam., 27 ins. in the ground, for $\frac{1}{4}$ sec. cor., with brass cap mkd.  <div style="text-align: center;"> <math>\frac{1}{4}</math>            S14.   S13.            1936         </div> <div style="text-align: right;">from which</div> A yellow pine, 8 ins. diam., brs. N. 52° E., 33 lks. dist., mkd. $\frac{1}{4}$ S13 BT.  A yellow pine, 8 ins. diam., brs. N. 87° W., 25 lks. dist., mkd. $\frac{1}{4}$ S14 BT.  Asc. 168 ft. over S. slope to
51.88	Short spur sloping E. from rim of mesa, bearing NE. and SW. Leave mountainous land and timber. Thence over gently rolling land on mesa, thru scattering undergrowth. Desc. 58 ft. over NE. slope to
80.04	Intersect original cor. of secs. 11, 12, 13 and 14, which is a sandstone, 8x6x4 ins. above ground, mkd. with 1 groove on E. face and firmly set. No accessories. Reconstruct this cor. monument as follows: alongside the original cor. stone, set an iron post, 3 ft. long, 2 ins. diam., 27 ins. in the ground, for cor. of secs. 11, 12, 13 and 14, with brass cap mkd.  <div style="text-align: center;">           T7N R29E            S11   S12            S14   S13            1936         </div> <div style="text-align: right;">and raise a</div> mound of stone, 3 ft. base, 2 ft. high, W. of cor.  Land, rolling. Soil, volcanic loam, 2nd and 3rd rates. Timber, pine, juniper and oak. Undergrowth, scrub timber.

BOOK 4118

## RESURVEY: SUBDIVISION LINES, T.7 N., R. 29 E.

30

Chains	
	From the cor. of secs. 7, 12, 13 and 18, on E. bdy. of the Tp. which is an iron post, 2 ins. diam. projecting 12 ins. above ground, firmly set, mkd. on brass cap and witnessed as described in the official record.
	N. 89° 50' W., on true line, bet. secs. 12 and 13.
	Over rolling land, thru scattering timber and undergrowth. Asc. 70 ft. over SE. slope, along N. side of fence bearing E. and W.
9.96	Rim of mesa bears NE. and SW. Thence across mesa.
10.44	Intersect fence cor. from which fences extend E. and SW.
14.95	Dim road, brs. NE. and SW.
15.00	Rim of mesa, brs. NE. and SW. Leave mesa, desc. 20 ft. over NW. slope.
20.74	Wash, 25 lks. wide, course NE. Asc. 43 ft. over SE. slope.
25.01	Fence ( 4 strand barbed wire) brs. N. and S.
30.90	Spur, slopes NE. Desc. 45 ft. over NW. slope.
33.71	Irrigation ditch, course NE.
34.11	Dim road, brs. NE. and SW.
37.35	Draw, course NE. Asc. 6 ft. over E. slope to
39.46	(Mid point) Set an iron post, 3 ft. long, 1 in. diam., 27 ins. in the ground, for $\frac{1}{4}$ sec. cor., with brass cap mkd.
	$\frac{1}{4}$ S 12°
	S13
	1936°
	from which
	A yellow pine, 6 ins. diam., brs. S. 43° E., 60 lks. dist., mkd. $\frac{1}{4}$ S13 BT.
	A yellow pine, 8 ins. diam., brs. N. 37° E., 46 lks. dist., mkd. $\frac{1}{4}$ S12 BT.
	Asc. 109 ft. over gradual E. slope to
58.00	Leave rolling and enter mountainous land. Asc. 206 ft. over steep E. slope to
66.50	Rim of mesa brs. NE. and SW. Leave mountainous land and enter gently rolling land on mesa. Ascend gradually over NE. slope thru scattering undergrowth.
78.92	The cor. of secs. 11, 12, 13 and 14.
	Land, rolling, mountainous and gently rolling. Soil, rocky, over dark loam, 1st and 4th rates. Timber, pine, juniper and oak. Undergrowth, scrub timber and bunch grass.
	N. 0° 30' E., on true line, bet. secs. 11 and 12.
	Over gently rolling open land on mesa. Desc. gradually over NE. slope.

## RESURVEY: SUBDIVISION LINES, T. 7 N., R. 29 E.

31

## Chains

- 15.13 Enter scattering timber and undergrowth, brs. NE. and SW.
- 19.13 Rim of mesa bears NE. and SW. Leave mesa and enter rolling land. Desc. 26 ft. over NW. slope.
- 22.71 Ravine; near head, course NW., asc. 79 ft. over SW. slope to
- 31.20 Rim of mesa; brs. NE. and SE. Leave rolling and enter mountainous land; desc. 86 ft. over NW. slope to
- 35.40 S. end of nearly level bench bearing N. and S. on W. wall of mesa. Desc. 18 ft. to

40.12 (Mid point) Set an iron post, 3 ft. long, 1 in. diam., 18 ins. in the ground to bedrock, with a lava stone, 6x6x4 ins. mkd. with a cross (x) at base of post, and in a mound of stone to top, for  $\frac{1}{4}$  sec. cor.; with brass cap mkd.

$$\begin{array}{c} \frac{1}{4} \\ S11 \quad | \quad S12 \\ 1936 \end{array}$$

from which

A yellow pine, 28 ins. diam.; brs. West, 68 lks. dist. mkd.  $\frac{1}{4}$  S11 BT.

No other bearing tree available.

Continue along narrow nearly level bench bearing N. and S. on W. wall of mesa.

- 51.50 Leave bench and enter mountainous land. Asc. 195 ft. over SW. slope to
- 61.00 Bend in W. rim of mesa, brs. S. 20° E. and NE.; desc. 352 ft. over NW. slope to sec. cor.
- 75.50 Telephone line bears NE. and SW.
- 80.24 Intersect original cor. of secs. 1, 2, 11 and 12, which is an unmarked sandstone, 8x6x4 ins. firmly set in a mound of stone, and witnessed by the one record bearing tree SE.

Reconstruct this cor. monument as follows: remove the mound of stone and the original cor. stone, and in same place, set an iron post, 3 ft. long, 2 ins. diam., 28 ins. in the ground, for cor. of secs. 1, 2, 11 and 12, with brass cap mkd.

$$\begin{array}{c} T7N \quad R29E \\ S2 \quad | \quad S1 \\ \hline S11 \quad | \quad S12 \end{array}$$

1936

from which

the original bearing tree:

A yellow pine, 30 ins. diam., brs. S. 52 $\frac{1}{2}$ ° E., 53 lks. dist., mkd. T7N R29E S12 BT.

and establish additional bearing trees:

A yellow pine, 4 ins. diam., brs. N. 17 $\frac{1}{2}$ ° E., 59 lks. dist., mkd. BT only.

## RESURVEY: SUBDIVISION LINES, T. 7 N., R. 29 E.

32

Chains

A yellow pine, 26 ins. diam., brs. S.  $59\frac{1}{2}^{\circ}$  E., 157 lks. dist., mkd. T7N R29E S12 BT.

A yellow pine, 26 ins. diam., brs. S.  $9\frac{1}{2}^{\circ}$  W., 141 lks. dist., mkd. T7N R29E S11 BT.

A yellow pine, 4 ins. diam., brs. N.  $7^{\circ}$  W., 44 lks. dist., mkd. BT only.

Land, gently rolling, nearly level, rolling and mountainous.

Soil, rocky, over volcanic loam, 1st and 4th rates.

Timber, yellow pine, aspen, juniper, fir and oak.

Undergrowth, scrub timber and bunch grass.

From the cor. of secs. 1, 6, 7 and 12, on E. bdy. of the Tp. which is an iron post, 2 ins. diam., projecting 12 ins. above ground, firmly set, mkd. on brass cap and witnessed as described in the official record.

N.  $88^{\circ} 38'$  W., on true line, bet. secs. 1 and 12 ( $E.\frac{1}{2}$ ).

Over nearly level open grassy land, sloping E.

0.50 Wire fence, brs. N. and S. Fence cor. brs. N. 50 lks. dist. from which fences extend E. and S. Another fence cor. brs. S. 50 lks. dist. from which fences extend E., W. and N.

5.00 Reservoir, about 5 chs. diam., brs. N. about 5 chs. dist.

19.50 Leave nearly level open grassy land, and enter mountainous land, scattering timber and undergrowth. Asc. 226 ft. over NE. slope to  $\frac{1}{4}$  sec. cor.

28.70 Fence (4 strand barbed wire) brs. NW. and SE.

39.85 Intersect original  $\frac{1}{4}$  sec. cor. of secs. 1 and 12, which is an unmarked sandstone, 16x12x6 ins. firmly set in a mound of stone and witnessed by the one record bearing tree NW.

Reconstruct this cor. monument as follows: remove the mound of stone and the original cor. stone, and in same place, set an iron post, 3 ft. long, 1 in. diam., 18 ins. in the ground to bedrock, with the original cor. stone reset alongside and in a mound of stone to top, for  $\frac{1}{4}$  sec. cor., with brass cap mkd.

$$\frac{1}{4} \frac{S 1}{S 12}$$

1936

from which

the original bearing tree:

A yellow pine 20 ins. diam., brs. N.  $30^{\circ}$  W., 43 lks. dist., mkd.  $\frac{1}{4}$ S BT.

and establish additional bearing trees:

A yellow pine, 22 ins. diam., brs. N.  $16\frac{1}{2}^{\circ}$  W., 77 lks. dist., mkd.  $\frac{1}{4}$  S1 BT.

A yellow pine, 5 ins. diam., brs. S.  $69\frac{1}{2}^{\circ}$  W., 27 lks. dist., mkd.  $\frac{1}{4}$  S12 BT.

Thence;

## RESURVEY: SUBDIVISION LINES, T. 7 N., R. 29 E.

33

Chains	
	N. 88° 47' W., on true line, bet. secs. 1 and 12 ( $W\frac{1}{2}$ ).
..	Over mountainous land, thru scattering timber and undergrowth.
..	Asc. 159 ft. over NE. slope.
8.63	Spur, slopes NW., from S., desc. 230 ft. over SW. slope.
21.80	Draw, course NW. Desc. 72 ft. over NW. slope.
23.17	Wash, course N., asc. 130 ft. over E. slope.
30.16	Point of spur, slopes N.; desc. 132 ft. over NW. slope to sec. cor.
35.07	Telephone line, brs. NE. and SW.
38.24	The cor. of secs. 1, 2, 11 and 12.
	Land, nearly level and mountainous. Soil, volcanic loam, 2nd and 3rd rates.. Timber, yellow pine, juniper, fir and oak. Undergrowth, scrub timber. Fair grass.

	From the cor. of secs. 1, 2, 35 and 36, on N. bdy. of the Tp. hereinbefore described.
	S. 0° 11' W., on true line, bet. secs. 1 and 2 ( $N.\frac{1}{2}$ )
	Over gently rolling land, thru scattering timber and undergrowth. Ascend 30 ft. over N. slope to
5.90	N. edge of nearly level top of mesa, brs. NE. and W. Thence across top of mesa. Desc. 30 ft. to
23.60	Top of cliff 40 ft. high, bearing E. and W., facing S. forming S. rim of mesa. Leave mesa and enter mountainous land; desc. 171 ft. over S. slope.
34.05	Milligan Creek, 30 lks. wide, containing a stream of running water, 2 lks. wide, 3 ins. deep, course E., asc. 100 ft. over N. slope to
39.15	Intersect original $\frac{1}{4}$ sec. cor. of secs. 1 and 2, which is a yellow pine tree, 18 ins. diam., mkd. $\frac{1}{4}$ S on W. side and witnessed by the two record bearing trees:  A yellow pine, 18 ins. diam., brs. N. 54° E., 22 lks. dist., mkd. $\frac{1}{4}$ S BT.  A yellow pine, 18 ins. diam., brs. S. 52 $\frac{1}{2}$ ° W., 23 lks. dist., mkd. $\frac{1}{4}$ S BT.
	Thence,
	S. 2° 56' E., on true line, bet. secs. 1 and 2 ( $S.\frac{1}{2}$ ).
	Over mountainous land, thru dense timber and scattering undergrowth. Asc. 122 ft. over N. slope to mesa.
0.10	Set an iron post, 3 ft. long, 1 in. diam., 27 ins. in the ground for witness cor. to $\frac{1}{4}$ sec. cor., with brass cap mkd.

WC  
 $\frac{1}{4}$   
 S2 | S1  
 1936

RESURVEY: SUBDIVISION LINES, T. 7 N., R. 29 E.

34

Chains	
	<p>from which</p> <p>A yellow pine, 8 ins. diam., brs. N. <math>48\frac{1}{2}^{\circ}</math> W., 30 lks. dist., mkd. WC <math>\frac{1}{4}</math> S2 BT.</p> <p>A yellow pine, 5 ins. diam., brs. S. <math>68\frac{1}{2}^{\circ}</math> E., 43 lks. dist., mkd. WC <math>\frac{1}{4}</math> S2 BT.</p>
9.00	N. rim of mesa, brs. E. and W. Leave mountainous and enter gently rolling land on mesa.
20.75	Top of cliff 50 ft. high, brs. E. and W., facing S. and forming S. rim of mesa. Leave mesa and enter mountainous land. Desc. 312 ft. over S. slope.
35.59	Dim road, brs. NE. and W.
36.94	Rudd Creek, 70 lks. wide, with stream of running water, 6 lks. wide, 6 ins. deep, course NE. Asc. 25 ft. over NW. slope to
39.11	The cor. of secs. 1, 2, 11 and 12.
	<p>Land, gently rolling, nearly level and mountainous. Soil, rocky, dark loam, 1st and 4th rates. Timber, yellow pine, aspen and juniper. Undergrowth, scrub timber and bunch grass.</p>
	<p>From the cor. of secs, 2, 3, 34 and 35, on S. bdy. of the Tp. reconstructed under this group as described in notes of resurvey of N. bdy. of T. 6 N., R. 29 E.</p> <p>N. <math>8^{\circ} 01'</math> W., on true line, bet. secs. 34 and 35.</p> <p>Over mountainous land, thru dense timber and scattering undergrowth. Asc. 15 ft. over W. slope.</p>
10.00	Desc. 106 ft. over W. slope..
18.10	Trail, brs. NE. and SW.
30.50	Point of spur, slopes NW. Desc. 338 ft. over N. slope to
41.41	(Mid point) Set an iron post, 3 ft. long, 1 in. diam., 18 ins. in the ground to bedrock and in a mound of stone to top, for $\frac{1}{4}$ sec. cor., with brass cap mkd.
	<p style="text-align: center;"> <math>\frac{1}{4}</math>                      S34   S35                      1936                 </p> <p style="text-align: right;">from which</p> <p>A fir, 10 ins. diam., brs. N. <math>70^{\circ}</math> E., 3 lks. dist., mkd. <math>\frac{1}{4}</math> S35 BT.</p> <p>A fir, 6 ins. diam., brs. N. <math>42^{\circ}</math> W., 27 lks. dist., mkd. <math>\frac{1}{4}</math> S34 BT.</p> <p>Desc. 40 ft. over N. slope.</p>
44.01	Fence ( 4 strand barbed wire) brs. NE. and SW.
45.61	Bend in draw, course NW. from SW. Desc. 23 ft. over NW. slope to
47.66	Colter Creek, with stream of running water, 12 lks. wide, 1 ft. deep, course N. $70^{\circ}$ E., asc. 561 ft. over S. slope to sec. cor.


RESURVEY: SUBDIVISION LINES, T. 7 N., R. 29 E.

Chains

55.20 Top of cliff, 50 ft. high, brs. E. and W. facing S.

82.82 Intersect original cor. of secs. 26, 27, 34 and 35, which is an unmarked lava stone, 14x6x5 ins. firmly set, in a mound of stone and witnessed by the two record bearing trees.

Reconstruct this cor. monument as follows: remove the mound of stone and the original cor. stone, and in same place, set an iron post, 3 ft. long, 2 ins. diam., 27 ins. in the ground, with the original cor. stone reset alongside, for cor. of secs. 26, 27, 34 and 35, with brass cap mkd.



1936

from which

the original bearing trees:

A yellow pine, 30 ins. diam., brs. S. 31° E., 54 lks. dist., mks. overgrown. Remark T7N R29E S35 BT.

A yellow pine, 15 ins. diam., brs. N. 54½° W., 41 lks. dist., mks. overgrown. Remark T7N R29E S27 BT.

and establish additional bearing trees:

A yellow pine, 8 ins. diam., brs. N. 60½° E., 96 lks. dist., mkd. T7N R29E S26 BT.

A yellow pine, 18 ins. diam., brs. S. 52° E., 129 lks. dist., mkd. T7N R29E S35 BT.

A yellow pine, 10 ins. diam., brs. S. 58¼° W., 105 lks. dist., mkd. T7N R29E S34 BT.

A yellow pine, 12 ins. diam., brs. N. 74° W., 66 lks. dist., mkd. T7N R29E S27 BT.

Land, mountainous.

Soil, rocky, volcanic loam, 3rd and 4th rates.

Timber, yellow pine, fir, aspen, spruce and sugar pine.

Undergrowth, scrub timber and bunch grass.

From the cor. of secs. 25, 26, 35 and 36.

N. 87° 13' W., on true line, bet. secs. 26 and 35.


Over mountainous land, thru dense timber and scattering undergrowth. Desc. 30 ft. over S. slope.

18.78 Asc. 54 ft. over S. slope.

26.28 Desc. 25 ft. over S. slope.

39.15 Head of draw, course SE.; asc. 75 ft. over SE. slope to

47.50 (Mid point) Set an iron post, 3 ft. long, 1 in. diam., 27 ins. in the ground, for ¼ sec. cor., with brass cap mkd.



1936

from which

## RESURVEY: SUBDIVISION LINES, T. 7 N., R. 29 E.

36

Chains	
	A yellow pine, 20 ins. diam., brs. N. $4\frac{1}{2}^{\circ}$ E., 53 lks. dist. mkd. $\frac{1}{4}$ S26 BT.
	An oak, 5 ins. diam., brs. S. $51\frac{1}{2}^{\circ}$ W., 95 lks. dist., mkd. $\frac{1}{4}$ S35 BT.
	Asc. 219 ft. over SE. slope.
50.44	Fence, brs. NW. and SE.
67.65	Ridge, brs. N. $70^{\circ}$ E. and S. $70^{\circ}$ W., desc. 27 ft. along N. slope of ridge to
74.14	Same ridge, brs. N. $75^{\circ}$ W. and S. $70^{\circ}$ E., desc. 90 ft. over SW. slope.
85.03	Desc. 46 ft. over S. slope to
95.00	The cor. of secs. 26, 27, 34 and 35.
	Land, mountainous. Soil, volcanic loam, 3rd and 4th rates. Timber, yellow pine, fir, aspen and juniper. Undergrowth, scrub timber and bunch grass.
	N. $0^{\circ} 06'$ W., on true line, bet. secs. 26 and 27 (S. $\frac{1}{2}$ ). Over mountainous land, thru dense timber and scattering undergrowth. Asc. 34 ft. over S. slope.
4.50	Ridge, brs. E. and W., desc. 80 ft. over N. slope.
16.50	Riggs Creek, 12 lks. wide, 2 ft. deep, containing a small stream of running water, course E., asc. 287 ft. over S. slope to
39.53	Intersect original $\frac{1}{4}$ sec. cor. of secs. 26 and 27, which is a sandstone, 12x10x8 ins. mkd. $\frac{1}{4}$ on W. face, firmly set in a mound of stone and witnessed by the one record bearing tree. Reconstruct this cor. monument as follows: remove the mound of stone and the original cor. stone, and in same place, set an iron post, 3 ft. long, 1 in. diam., 18 ins. in the ground to bedrock, with the original cor. stone reset alongside and in a mound of stone to top, for $\frac{1}{4}$ sec. cor., with brass cap mkd.
	$\begin{array}{c} \frac{1}{4} \\ \text{S27} \quad   \quad \text{S26} \\ 1936 \end{array}$
	from which
	the original bearing tree:
	A yellow pine, 18 ins. diam., brs. S. $40^{\circ}$ W., 50 lks. dist., mks. overgrown. Remark $\frac{1}{4}$ S27 BT.
	and establish additional bearing trees:
	An oak, 6 ins. diam., brs. S. $60\frac{3}{4}^{\circ}$ E., 48 lks. dist., mkd. $\frac{1}{4}$ S26 BT.
	A yellow pine, 6 ins. diam., brs. N. $44\frac{3}{4}^{\circ}$ W., 45 lks. dist., mkd. $\frac{1}{4}$ S27 BT.
	Thence,

## RESURVEY: SUBDIVISION LINES, T. 7 N., R. 29 E.

37

Chains

- N. 15° 00' E., on true line, bet. secs. 26 and 27 (N.  $\frac{1}{2}$ ).  
Over mountainous land, thru dense timber and scattering undergrowth.  
Asc. 265 ft. over S. slope.
- 12.60 Spur, slopes E., desc. 343 ft., over NE. and E. slopes to
- 42.14 Point for reestablishment of the sec. cor. determined by double proportion between original cors. 1 mile N., E. and W., and  $\frac{1}{2}$  mile S.; at which point: set an iron post, 3 ft. long, 2 ins. diam., 20 ins. in the ground to bed-rock, and in a mound of stone to top, for cor. of secs. 22, 23, 26 and 27, with brass cap mkd.
- |     |      |
|-----|------|
| T7N | R29E |
| S22 | S23  |
| S27 | S26  |
- 1936
- from which
- A yellow pine, 6 ins. diam., brs. N. 12° E., 64 lks. dist., mkd. T7N R29E S23 BT.
- A yellow pine, 12 ins. diam., brs. S. 3 $\frac{1}{4}$ ° E., 165 lks. dist., mkd. T7N R29E S26 BT.
- A fir, 8 ins. diam., brs. S. 47 $\frac{3}{4}$ ° W., 25 lks. dist., mkd. T7N R29E S27 BT.
- A yellow pine, 14 ins. diam., brs. N. 61 $\frac{1}{2}$ ° W., 107 lks. dist., mkd. T7N R29E S22 BT.
- Land, mountainous.  
Soil, rocky, volcanic loam, 3rd and 4th rate.  
Timber, yellow pine, fir, aspen and oak.  
Undergrowth, scrub timber and bunch grass.
- 
- From the cor. of secs. 23, 24, 25 and 26.  
N. 86° 46' W., on true line, bet. secs. 23 and 26.  
Over rolling land, thru scattering timber and undergrowth.  
Asc. 60 ft. over SE. slope.
- 3.40 Fence (4 strand barbed wire) bears N. and S.
- 10.24 Short spur, slopes SE. Asc. 33 ft. over S. slope.
- 21.94 Draw, course S. 20° E. Asc. 132 ft. over E. slope to
- 36.88 Short spur, slopes S.; desc. 50 ft. over W. slope.
- 40.84 Gulch, course SE. Leave rolling and enter mountainous land; asc. 30 ft. over SE. slope to
- 41.87 (Mid point) Set an iron post, 3 ft. long, 1 in. diam., 27 ins. in the ground, for  $\frac{1}{4}$  sec. cor., with brass cap mkd.
- |               |      |
|---------------|------|
| $\frac{1}{4}$ | S 23 |
|               | S 26 |
- 1936
- from which
- A yellow pine, 30 ins. diam., brs. S. 44° W., 32 lks. dist., mkd.  $\frac{1}{4}$  S26 BT.

## RESURVEY: SUBDIVISION LINES, T. 7 N., R. 29 E.

38

Chains	
	A yellow pine, 40 ins. diam., brs. N. 8° E., 5 lks. dist., mkd. $\frac{1}{4}$ S23 BT.
	Asc. 360 ft. over SE. slope.
64.31	Spur slopes N. 70° E. from N. 86° W. Asc. 65 ft. along spur to
70.65	Leave spur, slopes S. 86° E. from N. 40° W.; desc. 80 ft. over SW. slope.
75.94	Head of draw, course S. 20° E.; asc. 126 ft. over E. slope to
83.74	The cor. of secs. 22, 23, 26 and 27.
	Land, rolling and mountainous. Soil, rocky, volcanic loam, 3rd and 4th rates. Timber, yellow pine, juniper, fir, aspen and oak. Undergrowth, scrub timber and bunch grass.
	N. 6° 50' W., on true line, bet. secs. 22 and 23.
	Over mountainous land, thru dense timber and scattering undergrowth. Asc. 517 ft. over steep E. and SE. slopes.
20.36	Ridge, brs. NE. and SW., and spur sloping SE. Asc. 14 ft. over W. slope to
23.25	Desc. 57 ft. over NW. slope to
27.66	Rocky ledge 20 ft. high, brs. NE. and SW. Desc. 90 ft. over NW. slope to
33.50	Rocky ledge, 25 ft. high, brs. NE. and SW.; desc. 170 ft. over NW. slope to
41.00	(Mid point) Set an iron post, 3 ft. long, 1 in. diam., 27 ins. in the ground, for $\frac{1}{4}$ sec. cor., with brass cap mkd.
	$\begin{array}{c} \frac{1}{4} \\ \text{S22} \quad   \quad \text{S23} \\ 1936 \end{array}$
	from which
	A yellow pine, 12 ins. diam., brs. N. 33 $\frac{1}{2}$ ° E., 30 lks. dist., mkd. $\frac{1}{4}$ S23 BT.
	A yellow pine, 7 ins. diam., brs. N. 34° W., 57 lks. dist., mkd. $\frac{1}{4}$ S22 BT.
	Desc. 768 ft. over W. and NW. slopes to
82.00	Intersect original cor. of secs. 14, 15, 22 and 23, which is an oak post, 3 ins. square, faintly mkd. and notched projecting 25 ins. above ground, firmly set and witnessed by one of the three record bearing trees: Reconstruct this cor. monument as follows: alongside the wood post, set an iron post, 3 ft. long, 2 ins. diam., 27 ins. in the ground, for cor. of secs. 14, 15, 22 and 23, with brass cap mkd.
	$\begin{array}{c} \text{T7N} \quad \text{R29E} \\ \text{S15} \quad   \quad \text{S14} \\ \hline \text{S22} \quad   \quad \text{S23} \\ 1936 \end{array}$
	from which

## RESURVEY: SUBDIVISION LINES, T. 7 N., R. 29 E.

39

## Chains

the original bearing tree:

An aspen, 18 ins. diam., brs. S.  $64\frac{1}{2}^{\circ}$  W., 36 lks. dist.  
mkd. T7N R29E S22 BT.

and establish additional bearing trees:

A yellow pine, 8 ins. diam., brs. N.  $15^{\circ}$  E., 31 lks.  
dist., mkd. T7N R29E S14 BT.

A yellow pine, 9 ins. diam., brs. S.  $73^{\circ}$  E., 33 lks.  
dist., mkd. T7N R29E S23 BT.

A yellow pine, 5 ins. diam., brs. S.  $43^{\circ}$  W., 33 lks.  
dist., mkd. T7N R29E S22 BT.

A yellow pine, 7 ins. diam., brs. N.  $30^{\circ}$  W., 41 lks.  
dist., mkd. T7N R29E S15 BT.

Land, mountainous.

Soil, rocky, volcanic loam, 4th rate.

Timber, fir, spruce, aspen and yellow pine.

Undergrowth, scrub timber.

From the cor. of secs. 13, 14, 23 and 24.

N.  $86^{\circ} 43'$  W., on true line, bet. secs. 14 and 23.

Over rolling land, thru scattering timber and undergrowth.  
Asc. 213 ft. over SE. slope to

30.30 SE. edge of top of ridge, brs. NE. and SW. Thence across  
level top of ridge.

33.90 NW. edge of top of ridge, brs. NE. and SW. Enter dense  
timber. Leave top of ridge. Desc. 41 ft. over N. slope  
to

46.87 (Mid point) Set an iron post, 3 ft. long, 1 in. diam., 27  
ins. in the ground, for  $\frac{1}{4}$  sec. cor., with brass cap mkd.

$$\frac{1}{4} \frac{S 14}{S 23}$$

1936

from which

An oak, 8 ins. diam., brs. S.  $7\frac{1}{2}^{\circ}$  W., 47 lks. dist.,  
mkd.  $\frac{1}{4}$  S23 BT.

A yellow pine, 18 ins. diam., brs. N.  $5\frac{1}{2}^{\circ}$  E., 32 lks.  
dist., mkd.  $\frac{1}{4}$  S14 BT.

Thence over mountainous land. Asc. 40 ft. over N. slope.

51.82 Asc. 30 ft. over NE. slope.

53.90 Short spur, slopes N.; desc. 73 ft. over NW. slope.

62.20 Draw, course N., asc. 23 ft. over NE. slope.

68.00 Asc. gradually over N. slope to

73.68 Asc. 30 ft. over NE. slope.

81.60 Spur, slopes N.; desc. 185 ft. over NW. slope to

93.74 The cor. of secs. 14, 15, 22 and 23.

RESURVEY: SUBDIVISION LINES, T. 7 N., R. 29 E.

Chains	Land, rolling, nearly level and mountainous. Soil, rocky, over volcanic loam, 3rd and 4th rates. Timber, yellow pine, juniper, fir, spruce and aspen. Undergrowth; scrub timber.
	N. 3° 40' E., on true line. bet. secs. 14 and 15.
	Over mountainous land, thru dense timber and scattering undergrowth:
	Desc. 30 ft. over NW. slope to
2.35	Draw, course N. 15° E. Leave mountainous and enter rolling land. Desc. 40 ft. over E. slope.
6.45	Fence ( 4 strand barbed wire) brs. E. and W. At 1.00 ch. W. this fence turns to NW.
18.00	Same draw, course NW. Leave timber and enter nearly level cultivated land, brs. NW. and SE.
36.10	Head of wash, course NW., asc. slightly over S. slope.
38.10	Fence ( 4 strand barbed wire) brs. E. and W. Leave open cultivated land and enter scattering undergrowth.
38.95	(Mid point) Set an iron post, 3 ft. long, 1 in. diam., 27 ins. in the ground, for $\frac{1}{4}$ sec. cor., with brass cap mkd.
	$\begin{array}{c} \frac{1}{4} \\ S15 \quad   \quad S14 \\ 1936 \end{array}$
	from which
	A yellow pine; 18 ins. diam., brs. N. 37 $\frac{1}{2}$ ° E., 167 lks. dist., mkd. $\frac{1}{4}$ S14 BT.
	No other bearing tree available.
	Thence over rolling land, thru scattering timber and undergrowth. Asc. 57 ft. over SW. slope.
48.90	Flat topped spur, slopes NW.; desc. 30 ft. along E. slope to
56.00	Same spur, slopes NE. Enter mountainous land; desc. 159 ft. over NW. slope to wash.
60.65	Leave mountainous and enter rolling land.
70.50	Wash, course N. 60° W. Ascend 40 ft. over SW. and W. slopes to
77.91	Point for reestablishment of the sec. cor. determined by double proportion bet. original cors. 1 mile N., E. and S., and $\frac{1}{2}$ mile W., at which point: Set an iron post, 3 ft. long, 2 ins. diam., 27 ins. in the ground, for cor. of secs. 10, 11, 14 and 15, with brass cap mkd.
	$\begin{array}{c} T7N \quad R29E \\ \hline S10 \quad   \quad S11 \\ \hline S15 \quad   \quad S14 \end{array}$
	1936
	from which
	A juniper, 16 ins. diam., brs. N. 46 $\frac{1}{2}$ ° E., 215 lks. dist.; mkd. T7N R29E S11 BT.

## RESURVEY: SUBDIVISION LINES, T. 7 N., R. 29 E.

Chains	<p>A yellow pine, 18 ins. diam., brs. S. <math>16\frac{3}{4}^{\circ}</math> E., 196 lks. dist., mkd. T7N R29E S14 BT.</p> <p>A yellow pine, 6 ins. diam., brs. S. <math>15\frac{1}{2}^{\circ}</math> W., 103 lks. dist., mkd. T7N R29E S15 BT.</p> <p>A yellow pine, 22 ins. diam., brs. N. <math>7^{\circ}</math> W., 195 lks. dist., mkd. T7N R29E S10 BT.</p> <p>Land, mountainous, rolling and nearly level. Soil, volcanic loam and clay, 2nd and 3rd rates. Timber, yellow pine, juniper, aspen and fir. Undergrowth, scrub timber and bunch grass.</p>
	<p>From the cor. of secs. 11, 12, 13 and 14. N. <math>88^{\circ} 14'</math> W., on true line, bet. secs. 11 and 14. Over gently rolling, open land on mesa.</p>
8.00	<p>Rim of mesa, bears NE. and SW. Leave mesa and enter mountainous land, scattering timber and undergrowth. Desc. 97 ft. over W. slope.</p>
13.31	<p>Ravine, course N. <math>30^{\circ}</math> E., asc. 150 ft. over SE. slope.</p>
28.53	<p>Spur slopes NE. Desc. 155 ft. over NW. slope.</p>
40.80	<p>Gulch, course NE. Leave mountainous and enter rolling land. Asc. 20 ft. over SE. slope to <math>\frac{1}{4}</math> sec. cor.</p>
43.50	<p>Telephone line, brs. NE. and SW.</p>
44.49	<p>(Mid point) Set an iron post, 3 ft. long, 1 in. diam., 27 ins. in the ground, for <math>\frac{1}{4}</math> sec. cor., with brass cap mkd.</p>
	<p style="text-align: center;"><math>\frac{1}{4} \frac{S 11}{S 14}</math></p> <p style="text-align: center;">1936</p> <p style="text-align: right;">from which</p>
	<p>A yellow pine, 6 ins. diam., brs. N. <math>61^{\circ}</math> E., 54 lks. dist., mkd. <math>\frac{1}{4}</math> S11 BT.</p>
	<p>A yellow pine, 30 ins. diam., brs. S. <math>20\frac{1}{4}^{\circ}</math> W., 116 lks. dist., mkd. <math>\frac{1}{4}</math> S14 BT.</p>
	<p>Asc. 126 ft. over SE. slope.</p>
69.40	<p>Spur, slopes NE. Enter mountainous land. Desc. 310 ft. over W. slope to sec. cor.</p>
85.00	<p>Leave mountainous and enter rolling land.</p>
88.98	<p>The cor. of secs. 10, 11, 14 and 15.</p>
	<p>Land, gently rolling, mountainous and rolling. Soil, rocky, volcanic loam, 2nd and 4th rates. Timber, yellow pine, juniper and oak. Undergrowth, scrub timber and bunch grass.</p>
	<p>N. <math>6^{\circ} 40'</math> E., on true line, bet. secs. 10 and 11.</p>
	<p>Over rolling land, thru scattering timber and undergrowth.</p>
	<p>Asc. 30 ft. over SW. slope.</p>
3.00	<p>Short spur, slopes W., desc. 130 ft. over NW. slope to</p>

## RESURVEY.: SUBDIVISION LINES, T. 7 N., R. 29 E.

42

Chains	Rudd Creek. . .
19.50	Fence ( 4 strand barbed wire) brs. S. 2° W., and NE. Leave timber and undergrowth and enter open grassy land, brs. NE. and SW.
31.50	Rudd Creek, with stream of water 3 lks. wide, 4 ins. deep, course NE. Asc. 10 ft. over SE. slope to
34.00	Leave rolling open grassy land, and enter mountainous land, dense timber and scattering undergrowth, brs. NE. and SW. Asc. 137 ft. over steep SE. slope to
39.15	(Mid point) Set an iron post, 3 ft. long, 1 in. diam., 27 ins. in the ground, for $\frac{1}{4}$ sec. cor., with brass cap mkd. <div style="text-align: center;"> <math>\frac{1}{4}</math>  S10   S11  1936  from which  A yellow pine, 24 ins. diam., brs. S. 65° E., 83 lks. dist., mkd. <math>\frac{1}{4}</math> S11 BT.  A juniper, 9 ins. diam., brs. N. 66<math>\frac{1}{2}</math>° W., 20 lks. dist. mkd. <math>\frac{1}{4}</math> S10 BT.  Asc. 75 ft. over SE. slope to </div>
43.00	Rim of bench, bears NE. and SW. Leave mountainous and enter open nearly level land on bench.
58.00	Leave bench, brs. E. and W. Enter mountainous land, asc. 143 ft. over S. slope to
73.20	Rim of mesa, brs. NE. and SW. Leave mountainous and enter gently rolling open land on mesa.
78.29	Intersect original cor. of secs. 2, 3, 10 and 11, which is a lava stone, 10x10x6 ins. mkd. with 2 notches on E. face and 5 notches on S. face, firmly set in a mound of stone. No accessories. Reconstruct this cor. monument as follows: remove the mound of stone and the original cor. stone, and in same place, set an iron post, 3 ft. long, 2 ins. dian., 20 ins. in the ground to bedrock, with the original cor. stone reset alongside and in mound of stone to top for cor. of secs. 2, 3, 10 and 11, with brass cap mkd. <div style="text-align: center;"> T7N   R29E  S3   S2  S10   S11  1936 </div>
	Land, rolling, nearly level, mountainous and gently rolling. Soil, rocky, volcanic loam, 2nd and 3rd rates. Timber, yellow pine, juniper, aspen and fir. Undergrowth, scrub timber and bunch grass.
	From the cor. of secs. 1, 2, 11 and 12. N. 89° 07' W., on true line, bet. secs. 2 and 11 (E. $\frac{1}{2}$ ). Over rolling land thru scattering timber and undergrowth. Desc. 15 ft. over NW. slope.
3.60	Wash, 20 lks. wide, 2 ft. deep, course N. 20° E. Leave

## RESURVEY: SUBDIVISION LINES, T. 7 N., R. 29 E.

43

Chains	rolling and enter mountainous land. Asc. 167 ft. over NE. and N. slopes to
21.29	Desc. 98 ft. over NW. slope.
28.80	Rudd Creek, with a small stream of water, course NE.; asc. 130 ft. over SE. slope to
35.80	E. end of base of cliff, 30 ft. high, brs. E. and W., facing S. Ascend 33 ft. over S. slope along base of cliff.
40.08	Intersect original $\frac{1}{4}$ sec. cor. of secs. 2 and 11, which is a lava stone, 10x8x6 ins., mkd. $\frac{1}{4}$ on N. face, firmly set in a mound of stone and witnessed by the two record bearing trees. Reconstruct this cor. monument as follows: remove the mound of stone and the original cor. stone, and in same place, set an iron post, 3 ft. long, 1 in. diam., 20 ins. in the ground, to bedrock with the original cor. stone reset alongside, and in a mound of stone to top, for $\frac{1}{4}$ sec. cor., with brass cap mkd.
	$\frac{1}{4} \frac{S 2}{S 11}$
	1936
	from which
	the original bearing trees:
	A yellow pine, 15 ins. diam., brs. N. 38° E., 120 lks. dist., mkd. $\frac{1}{4}$ S BT.
	A yellow pine, 15 ins. diam., brs. S. 67 $\frac{1}{2}$ ° W., 37 lks. dist., mkd. $\frac{1}{4}$ S BT.
	and establish additional bearing trees:
	A pinyon, 10 ins. diam., brs. N. 71 $\frac{3}{4}$ ° W., 42 lks. dist., mkd. $\frac{1}{4}$ S 2 BT.
	A juniper, 10 ins. diam., brs. S. 12 $\frac{1}{2}$ ° W., 59 lks. dist., mkd. $\frac{1}{4}$ S 11 BT.
	Thence,
	N. 89° 52' W., on true line, bet. secs. 2 and 11 (W. $\frac{1}{2}$ ).
	Over mountainous land, thru scattering timber and undergrowth.
	Asc. 210 ft. over S. and SE. slopes to
29.80	Rim of mesa; brs. NE. and SW. Leave mountainous land, timber and undergrowth, and enter gently rolling open land on mesa. Asc. 34 ft. over NE. slope to
40.46	The cor. of secs. 2, 3, 10 and 11. Land, rolling, mountainous and gently rolling. Soil, volcanic loam, 2nd and 3rd rates. Timber, yellow pine, pinyon, juniper, oak and aspen. Undergrowth, scrub timber and bunch grass.
	From the cor. of secs. 2, 3, 34 and 35, on N. bdy. of the Tp., hereinbefore described.
	S. 1° 42' E., on true line, bet. secs. 2 and 3.

## RESURVEY: SUBDIVISION LINES, T. 7 N., R. 29 E.

44

Chains	
8.09	Over gently rolling grassy land, on broad top of ridge bearing E. and W., thru scattering timber. Desc. 23 ft. to
26.28	S. edge of top of ridge, brs. E. and W. Leave top of ridge and enter mountainous land. Desc. 292 ft. over S. slope to
31.18	Side hill drain, course S. 30° E. Enter rolling land. Desc. 34 ft. over SE. slope to
38.61	Same drain, course S. 30° W. Desc. 30 ft. over SW. slope to
38.61	(Proportional dist.) Set an iron post, 3 ft. long, 1 in. diam., 27 ins. in the ground, for $\frac{1}{4}$ sec. cor., with brass cap mkd.
	<div style="text-align: center;"> <math display="block">\begin{array}{c} \frac{1}{4} \\ 32 \quad   \quad 33 \\ 1936 \end{array}</math> </div>
	No bearing trees available,  raise a mound of stone, 3 ft. base, 2 ft. high, W. of cor. Desc. slightly over S. slope.
39.25	Milligan Creek, 50 lks. wide, 6 ft. deep, containing a small stream of water, course E.; asc. 34 ft. over N. slope.
47.48	Fence (4 strand barbed wire) brs. E. and W. At 2.00 chs. E. this fence turns to N.
47.50	Leave rolling and enter mountainous land. Asc. 218 ft. over N. slope to
61.98	Rim of mesa, brs. E. and W. Leave mountainous land, timber and undergrowth, and enter gently rolling land on mesa. Asc. 20 ft. over NE. slope to
76.98	The cor. of secs. 2, 3, 10 and 11.  Land, gently rolling, mountainous and rolling. Soil, volcanic loam, 2nd and 3rd rates. Timber, juniper, pinyon and yellow pine. Undergrowth, scrub timber and bunch grass.
	From the cor. of secs. 3, 4, 33 and 34, on S. bdy. of the Tp., reconstructed under this group and described in notes of resurvey of N. bdy. of T. 6 N., R. 29 E.
	N. 5° 17' W., on true line, bet. secs. 33 and 34.
	Over mountainous land, thru dense timber and scattering undergrowth. Asc. 131 ft. over SE. slope.
12.30	Ridge, brs. E. and W.; desc. 73 ft. over N. slope to
24.70	Desc. 407 ft. over NW. slope to
40.99	(Mid point) Set an iron post, 3 ft. long, 1 in. diam., 20 ins. in the ground to bedrock, and in a mound of stone to top, for $\frac{1}{4}$ sec. cor., with brass cap mkd.

## RESURVEY: SUBDIVISION LINES, T. 7 N., R. 29 E.

45

Chains

S33		S34
-----	--	-----

1936

from which

An aspen, 12 ins. diam., brs. S.  $44\frac{3}{4}^{\circ}$  W., 34 lks. dist., mkd.  $\frac{1}{2}$  S33 BT.

An aspen, 7 ins. diam., brs. N.  $41^{\circ}$  E., 27 lks. dist., mkd.  $\frac{1}{4}$  S34 BT.

Desc. 84 ft. over NW. slope.

44.10' Creek, with stream of water 5 lks. wide, 4 ins. deep, course NE. Asc. 742 ft. over steep S. slope.

76.97' Ridge, brs. N.  $70^{\circ}$  E. and S.  $70^{\circ}$  W. Desc. 30 ft. over N. slope to

81.97' Intersect the original cor. of secs. 27, 28, 33 and 34, which is an unmarked lava stone, 14x10x8 ins. firmly set in a mound of stone and witnessed by the one record bearing tree.

Reconstruct this cor. monument as follows: remove the mound of stone and the original cor. stone, and in same place, set an iron post, 3 ft. long, 2 ins. diam., 22 ins. in the ground to bedrock with the original cor. stone reset alongside, and in a mound of stone to top, for cor. of secs. 27, 28, 33 and 34, with brass cap mkd.

T7N	R29E
S28	S27
S33	S34

1936

from which

the original bearing tree:

A fir, 6 ins. diam., brs. N.  $55^{\circ}$  W., 5 lks. dist., mks. overgrown. Remark T7N R29E S28 BT.

and establish additional bearing trees:

A yellow pine, 4 ins. diam., brs. N.  $46^{\circ}$  E., 51 lks. dist., mkd. BT only.

A yellow pine, 10 ins. diam., brs. S.  $75^{\circ}$  E., 78 lks. dist., mkd. T7N R29E S34 BT.

A yellow pine, 12 ins. diam., brs. S.  $36\frac{1}{2}^{\circ}$  W., 82 lks. dist., mkd. T7N R29E S33 BT.

A yellow pine, 4 ins. diam., brs. N.  $63^{\circ}$  W., 62 lks. dist., mkd. BT only.

Land, mountainous.

Soil, rocky, volcanic loam, 3rd and 4th rates.

Timber, fir, spruce, yellow pine and aspen.

Undergrowth, scrub timber and bunch grass.

From the cor. of secs. 26, 27, 34 and 35.

S.  $89^{\circ}$  34' W., on true line, bet. secs. 27 and 34.

Over mountainous land, thru dense timber and scattering undergrowth.

RESURVEY: SUBDIVISION LINES, T. 7 N., R. 29 E.

46

Chains

Asc. 146 ft. over S. and SE. slopes to

30.57 Head of drain, course SE., asc. 271 ft. over E. slope to

37.03 (Mid point) Set an iron post, 3 ft. long, 1 in. diam., 27 ins. in the ground, for  $\frac{1}{4}$  sec. cor. with brass cap mkd.

$\frac{1}{4}$  S 27  
S 34

1936

from which

A yellow pine, 20 ins. diam., brs. S. 15° W., 14 lks. dist., mkd.  $\frac{1}{4}$  S34 BT.

An oak, 6 ins. diam., brs. N. 66° W., 62 lks. dist., mkd.  $\frac{1}{4}$  S27 BT.

Asc. 100 ft. over E. slope to

42.07 Spur, slopes SE.; asc. 306 ft. over S. and SE. slopes to

57.07 Ridge, brs. N. 75° E. and S. 75° W., desc.

74.07 The cor. of secs. 27, 28, 33 and 34.

Land, mountainous.

Soil, rocky, volcanic loam, 3rd and 4th rates.

Timber, fir, spruce, yellow pine, aspen and oak.

Undergrowth, scrub timber.

N. 0° 44' E., on true line, bet. secs. 27 and 28 (S.  $\frac{1}{2}$ ).

Over mountainous land, thru dense timber and scattering undergrowth.

Desc. 280 ft. over steep N. slope.

15.50 Old road, brs. E. and W.

16.00 Riggs Creek, 10 lks. wide, 2 ft. deep (dry) course E.; asc. 261 ft. over S. slope.

34.65 Ridge, brs. E. and W.; desc. 47 ft. over N. slope to

40.10 Intersect original  $\frac{1}{4}$  sec. cor. of secs. 27 and 28, which is an unmarked lava stone, 12x10x8 ins. above ground, firmly set and witnessed by the two record bearing trees. Reconstruct this cor. monument as follows: alongside the original cor. stone, set an iron post, 3 ft. long, 1 in. diam., 27 ins. in the ground; for  $\frac{1}{4}$  sec. cor., with brass cap mkd.

S28 | S27

1936

from which

the original bearing trees:

A fir, 12 ins. diam., brs. S. 45° E., 29 lks. dist., mkd.  $\frac{1}{4}$  S BT.

A fir, 8 ins. diam., brs. N. 64° W., 19 lks. dist., mkd.  $\frac{1}{4}$  S BT.

## RESURVEY: SUBDIVISION LINES, T. 7 N., R. 29 E.

47

Chains

and establish additional bearing trees:

A yellow pine, 14 ins. diam., brs. N. 6° E., 25 lks.  
dist., mkd.  $\frac{1}{4}$  S27 BT.

A yellow pine, 10 ins. diam., brs. S. 42° W., 32 lks.  
dist., mkd.  $\frac{1}{4}$  S28 BT.

Thence,

N. 0° 50' E., on true line, bet. secs. 27 and 28 (N.  $\frac{1}{2}$ ).

Over mountainous land, thru dense timber and scattering  
undergrowth. Desc. 73 ft. over N. slope.

6.40 Small drain, course NE.; asc. 63 ft. over SE. slope.

18.10 Short spur, slopes E.; desc. 78 ft. over NE. slope.

26.65 Head of draw, course E.; asc. 45 ft. over SE. slope to

32.00 Asc. 10 ft. over E. slope to

39.55 Intersect original cor. of secs. 21, 22, 27 and 28, which  
is a mound of stone, containing fragments of wood post.  
Reconstruct this cor. monument as follows: remove the  
mound of stone and in the center of its position, set  
an iron post, 3 ft. long, 2 ins. diam., 20 ins. in the  
ground to bedrock, and in a mound of stone to top, for  
cor. of secs. 21, 22, 27 and 28, with brass cap mkd.

T7N	R29E
S21	S22
S28	S27

1936

from which

A yellow pine, 12 ins. diam., brs. N. 27 $\frac{1}{2}$ ° E., 83 lks.  
dist., mkd. T7N R29E S22 BT.

A pinyon, 16 ins. diam., brs. S. 18 $\frac{1}{2}$ ° E., 150 lks.  
dist., mkd. T7N R29E S27 BT.

A pinyon, 18 ins. diam., brs. S. 29 $\frac{1}{2}$ ° W., 61 lks.  
dist., mkd. T7N R29E S28 BT.

A pinyon, 14 ins. diam., brs. N. 66 $\frac{1}{2}$ ° W., 55 lks.  
dist., mkd. T7N R29E S21 BT.

Land, mountainous.

Soil, rocky, volcanic loam, 3rd and 4th rates.

Timber, fir, spruce, yellow pine, aspen and oak.

Undergrowth, scrub timber.

From the cor. of secs. 22, 23, 26 and 27.

S. 89° 17' W., on true line, bet. secs. 22 and 27.

Over mountainous land, thru dense timber and scattering  
undergrowth.

Asc. 594 ft. over steep, rocky E. slope.

10.04 Rocky ridge, brs. N. 20° E. and S. 20° W.; desc. 170 ft.  
over NW. slope.

18.24 Ravine, course N. 20° E.; asc. 300 ft. over E. slope.

Chains	
32.14	Ridge, brs. N. 20° E. and SW.; desc. 83 ft. over NW. slope to
41.92	(Mid point) Set an iron post, 3 ft. long, 1 in. diam., 18 ins. in the ground and in a mound of stone to top, for $\frac{1}{4}$ sec. cor., with brass cap mkd.
	$\frac{1}{4}$ $\frac{S\ 22}{S\ 27}$
	1936
	from which
	A fir, 8 ins. diam., brs. N. 25° E., 48 lks. dist., mkd. $\frac{1}{4}$ S22 BT.
	A fir, 12 ins. diam., brs. S. 28 $\frac{1}{2}$ ° W., 37 lks. dist., mkd. $\frac{1}{4}$ S27 BT.
	Desc. 563 ft. over NW. slope to ravine.
52.24	Top of cliff, 80 ft. high, brs. NE. and SW., facing NW.
73.98	Ravine, course N.; asc. 307 ft. over E. slope to
83.84	The cor. of secs. 21, 22, 27 and 28.
	Land, mountainous. Soil, rocky, volcanic loam, 3rd and 4th rates. Timber, fir, spruce, yellow pine, aspen and oak. Undergrowth, scrub timber.
	N. 0° 12' E., on true line, bet. secs. 21 and 22.
	Over mountainous land, thru dense timber and scattering undergrowth. Desc. 15 ft. over E. slope to
5.57	Desc. 740 ft. over NE. slope to
38.00	Leave mountainous and enter nearly level land, brs. NE. and SW.
39.39	(Mid point). Set an iron post, 3 ft. long, 1 in. diam., 27 ins. in the ground, for $\frac{1}{4}$ sec. cor., with brass cap mkd.
	$\frac{1}{4}$ S21   S22
	1936
	from which
	A yellow pine, 8 ins. diam., brs. N. 9° W., 22 lks. dist., mkd. $\frac{1}{4}$ S21 BT.
	A yellow pine, 10 ins. diam., brs. N. 70° E., 24 lks. dist., mkd. $\frac{1}{4}$ S22 BT.
40.27	Leave timber and undergrowth, brs. E. and W. and enter open grassy land.
53.49	Benton Creek, with a small stream of water, course NE.
59.30	Leave nearly level and enter rolling land. Asc. 154 ft. over SE. slope.
62.57	Fence ( 5 strand barbed wire) brs. N. 70° E; and S. 70° W. Leave open grassy land, and enter dense timber and scattering undergrowth.

RESURVEY: SUBDIVISION LINES, T. 7 N., R. 29 E.

Chains


74.00

Ascend gradually over E. slope to

78.77

Intersect original cor. of secs. 15, 16, 21 and 22, which is an unmarked lava stone, 14x12x8 ins. loosely set in a mound of stone and witnessed by the three record bearing trees.

Reconstruct this cor. monument as follows: remove the mound of stone and the original cor. stone, and in same place, set an iron post, 3 ft. long, 2 ins. diam., 27 ins. in the ground with original cor. stone reset alongside, for cor. of secs. 15, 16, 21 and 22, with brass cap mkd.



1936.

from which

the original bearing trees:

A yellow pine, 24 ins. diam., brs. N. 27° E., 25 lks. dist., mks. overgrown. Remark T7N R29E S15 BT.

A yellow pine, 26 ins. diam., brs. S. 17½° E., 20 lks. dist., mks. overgrown. Remark T7N R29E S22 BT.

Decayed stump of a yellow pine, 24 ins. diam., no mks. visible, brs. N. 17° W., 62 lks. dist.

and establish additional bearing trees:

A yellow pine, 14 ins. diam., brs. N. 32½° E., 85 lks. dist., mkd. T7N R29E S15 BT.

A yellow pine, 12 ins. diam., brs. S. 60° E., 84 lks. dist., mkd. T7N R29E S22 BT.

A yellow pine, 14 ins. diam., brs. S. 56¼° W., 86 lks. dist., mkd. T7N R29E S21 BT.

A yellow pine, 6 ins. diam., brs. N. 46¼° W., 45 lks. dist., mkd. T7N R29E S16 BT.

Land, mountainous, nearly level and rolling. Soil, rocky, volcanic loam, 2nd and 4th rates. Timber, yellow pine, fir, spruce, aspen and oak. Undergrowth, scrub timber and bunch grass.

From the cor. of secs. 14, 15, 22 and 23.


S. 87° 15' W., on true line, bet. secs. 15 and 22.

Over mountainous land, thru dense timber and scattering undergrowth. Desc. 18 ft. over NW. slope.

1.00 Drain, course N. 15° E., asc. 227 ft. over NE. slope.

18.23 Spur, slopes N. Enter rolling land, desc. 152 ft. over NW. slope to

36.86 (Mid point) Set an iron post, 3 ft. long, 1 in. diam., 27 ins. in the ground, for ¼ sec. cor., with brass cap mkd.



1936

## RESURVEY: SUBDIVISION LINES, T. 7 N., R. 29 E.

50

Chains	from which
	A yellow pine, 12 ins. diam., brs. S. $51\frac{1}{2}^{\circ}$ W., 35 lks. dist., mkd. $\frac{1}{4}$ S22 BT.
	A yellow pine, 8 ins. diam., brs. N. $62\frac{1}{2}^{\circ}$ E., 67 lks. dist., mkd. $\frac{1}{4}$ S15 BT.
	Desc. 23 ft. over NW. slope.
43.33	Draw, course N., asc. 16 ft. over NE. slope.
49.78	Spur, slopes N. Enter mountainous land, desc. 100 ft. over NW. slope.
57.11	Dim road, brs. NE. and SW.
57.90	Benton Creek, with stream of water, 8 lks. wide, 4 ins. deep, course NE.; asc. 287 ft. over E. slope to sec. cor.
61.27	Fence ( 5 strand barbed wire) brs. N. and S.
73.73	The cor. of secs. 15, 16, 21 and 22.
	Land, mountainous and rolling. Soil, rocky, volcanic loam, 3rd and 4th rates. Timber; yellow pine, fir, spruce and aspen. Undergrowth, scrub timber and bunch grass.
	N. $7^{\circ} 26'$ W., on true line, bet. secs. 15 and 16 (S. $\frac{1}{2}$ ).
	Over mountainous land, thru dense timber and undergrowth. Desc. 12 ft. over E. slope.
6.77	Desc. 172 ft. over NE. slope.
20.10	Head of draw, course SE. Asc. 40 ft. over SE. slope.
33.05	Spur slopes NE. Desc. 65 ft. over NW. slope to $\frac{1}{4}$ sec. cor.
40.47	Fence ( 3 strand barbed wire) brs. NE. and SW.
44.97	Intersect original $\frac{1}{4}$ sec. cor. of secs. 15 and 16, which is a stone, 14x8x6 ins. mkd. $\frac{1}{4}$ and loosely set in a mound of stone. No accessories. Reconstruct this cor. monument as follows: remove the mound of stone and the original cor. stone, and in same place, set an iron post, 3 ft. long, 1 in. diam., 27 ins. in the ground, with the original cor. stone reset alongside, for $\frac{1}{4}$ sec. cor., with brass cap mkd.
	$\frac{1}{4}$ S16   S15 1936
	from which
	A yellow pine, 8 ins. diam., brs. S. $30\frac{1}{2}^{\circ}$ E., 32 lks. dist., mkd. $\frac{1}{4}$ S15 BT.
	A yellow pine, 8 ins. diam., brs. N. $65\frac{1}{2}^{\circ}$ W., 19 lks. dist., mkd. $\frac{1}{4}$ S16 BT.
	Thence,
	N. $0^{\circ} 06'$ E., on true line, bet. secs. 15 and 16 (N. $\frac{1}{2}$ )
	Over mountainous land, thru dense timber and scattering undergrowth. Desc. 150 ft. over N. slope to

RESURVEY: SUBDIVISION LINES, T. 7 N., R. 29 E.

Chains							
10.24	Enter draw, course N. from SE. Leave mountainous and enter rolling land. Desc. 40 ft. in draw to						
15.64	Leave draw, course NE. from S. Desc. 35 ft. over NE. slope:						
23.34	Draw, course NE. Asc. 5 ft. over SE. slope.						
24.10	Low spur slopes NE. Desc. 20 ft. over N. slope.						
32.64	Dim road, brs. NE. and SW.						
34.85	Draw, 7 lks. wide, 2 ft. deep, course E. Asc. 10 ft. over S. slope to						
37.00	Spur, slopes E. Enter mountainous land. Desc. 32 ft. over N. slope to						
39.64	Intersect original cor. of secs. 9, 10, 15 and 16, which is a lava stone, 20x12x10 ins. mkd. with 3 grooves on E. face and 4 grooves on S. face, firmly set in a mound of stone and witnessed by one of the two record bearing trees: Reconstruct this cor. monument as follows: remove the mound of stone and the original cor. stone and in same place, set an iron post, 3 ft. long, 2 ins. diam., 24 ins. in the ground to bedrock, with original cor. stone reset alongside, and in a mound of stone to top, for cor. of secs. 9, 10, 15 and 16, with brass cap mkd.						
	<table border="0"> <tr><td>T7N</td><td>R29E</td></tr> <tr><td>S9</td><td>S10</td></tr> <tr><td>S16</td><td>S15</td></tr> </table>	T7N	R29E	S9	S10	S16	S15
T7N	R29E						
S9	S10						
S16	S15						
	1936						
	from which						
	the original bearing trees:						
	A pinyon, 24 ins. diam., brs. S. 54½° W., 17 lks. dist., mks. overgrown. Remark T7N R29E S16 BT.						
	and establish additional bearing trees:						
	A pinyon, 8 ins. diam., brs. N. 69¼° E., 69 lks. dist. mkd. T7N R29E S10 BT.						
	A pinyon, 16 ins. diam., brs. S. 33¾° E., 56 lks. dist. mkd. T7N R29E S15 BT.						
	A pinyon, 24 ins. diam., brs. S. 54½° W., 17 lks. dist. mkd. T7N R29E S16 BT.						
	A pinyon, 12 ins. diam., brs. N. 40° W., 48 lks. dist. mkd. T7N R29E S9 BT.						
	Land, mountainous and rolling. Soil, rocky, volcanic loam, 2nd and 4th rates. Timber, yellow pine, pinyon, fir, aspen and oak. Undergrowth, scrub timber and bunch grass.						
	From the cor. of secs. 10, 11, 14 and 15.						
	N. 86° 33' W., on true line, bet. secs. 10 and 15 (E. ½).						
	Over gently rolling land, thru scattering timber. Desc. 38 ft. over SW. slope.						

## RESURVEY: SUBDIVISION LINES, T. 7 N.; R. 29 E.

52

Chains	
1.07	Fence (4 strand barbed wire) brs. N. and S., leave timber and enter cultivated land, brs. N. and S.
7.28	Benton Creek, 20 lks. wide, containing a small stream of running water, course NE.; asc. 59 ft. over SE. slope.
10.00	Leave cultivated land, brs. N. and S. and enter scattering timber and undergrowth, brs. N. and S.
17.20	Low spur, slopes NE.; desc. 17 ft. over NW. slope.
25.43	Leave timber and undergrowth and enter cultivated land, brs. N. and S.
28.13	Wash, 10 lks. wide, 6 ft. deep, course NE. Leave gently rolling and enter nearly level land.
34.63	SE. cor. of corral on line.
35.93	SW. cor. of same corral on line. Barn brs. N. 50 lks. dist.
36.83	SW. cor. of old cabin, brs. N., about 3.00 chs. dist.
37.95	Leave cultivated land and enter scattering timber and undergrowth, brs. N. and S.
40.20	Leave nearly level and enter gently rolling land. Asc. 20 ft. over E. slope.
43.70	Low spur slopes NE. Desc. slightly over NW. slope to $\frac{1}{4}$ sec. cor.
44.70	Fence (4 strand barbed wire) brs. N. and S. Turns to W. at about 3 chs. N.
44.73	Intersect original $\frac{1}{4}$ sec. cor. of secs. 10 and 15, which is a sandstone, 16x14x10 ins. firmly set in a mound of stone, and witnessed by the two record bearing trees. Reconstruct this cor. monument as follows: remove the mound of stone and the original cor. stone and in same place, set an iron post, 3 ft. long, 1 in. diam., 27 ins. in the ground, resetting the original stone alongside, for $\frac{1}{4}$ sec. cor. with brass cap mkd.  $\frac{1}{4} \frac{S 10}{S 15}$ 1936  from which  the original bearing trees:  A yellow pine (dead) 10 ins. diam., brs. N. 41° W., 58 lks. dist., mkd. $\frac{1}{4}$ S BT.  A yellow pine, 14 ins. diam., brs. S. 67½° E., 33 lks. dist., mkd. $\frac{1}{4}$ S BT.  and establish additional bearing trees:  A yellow pine, 8 ins. diam., brs. N. 10° E., 89 lks. dist., mkd. $\frac{1}{4}$ S10 BT.  A yellow pine, 24 ins. diam., brs. S. 19° E., 67 lks. dist., mkd. $\frac{1}{4}$ S15 BT.  Thence,  N. 89° 15' W., on true line, bet. secs. 10 and 15 (W. $\frac{1}{4}$ ).

## RESURVEY: SUBDIVISION LINES, T. 7 N., R. 29 E.

53

Chains	Over gently rolling land thru scattering timber and undergrowth. Desc. 25 ft. over NW. slope to
5.05	Leave gently rolling and enter nearly level land at S. edge of valley.
9.50	Enter gently rolling land. Asc. 60 ft. over NE. slope.
13.94	Fence (3 strand barbed wire) brs. S. 15° W. and N. 15° E. 3.00 chs. thence E.
19.50	Low spur slopes S. 75° E. Asc. 10 ft. along S. slope to
23.52	Same spur, slopes N. 75° E. from S. 20° W.; desc. 26 ft. over NW. slope.
29.77	Dim road, brs. NE. and SW.
30.19	Wash, 30 lks. wide, 5 ft. deep, course NE.; asc. 30 ft. over NE. slope to
35.50	Enter mountainous land. Asc. 30 ft. over N. slope to
39.97	The cor. of secs. 9, 10, 15 and 16.
	Land, gently rolling, nearly level and mountainous. Soil, volcanic loam, 1st and 3rd rates. Timber, yellow pine, pinyon, fir, spruce and aspen. Undergrowth, scrub timber and bunch grass.
	From the cor. of secs. 9, 10, 15 and 16.
	N. 10° 08' E., on true line, bet. secs. 9 and 10.
	Over mountainous land, thru scattering timber and undergrowth.
	Desc. 48 ft. over N. slope.
2.90	Rudd Creek, with stream of water 5 lks. wide, 8 ins. deep, course NE.; asc. 149 ft., over SE. slope.
3.50	Road, brs. E. and W.
10.80	Same road, brs. NE. and SW.
16.20	Ridge, brs. NE. and SW.; desc. 153 ft. over NW. slope.
25.30	Leave timber and undergrowth, brs. E. and W.
27.35	Foot of descent, brs. NE. and SW. Leave mountainous and enter nearly level, open, grassy land.
28.60	Same road, brs. E. and NW.
38.47	(Mid point) Set an iron post, 3 ft. long, 1 in. diam., 27 ins. in the ground, for $\frac{1}{4}$ sec. cor., with brass cap mkd.
	and raise a mound of stone, 3 ft. base, 2½ ft. high, W. of cor.
	A cabin brs. N. 75° 42' W., about 15 chs. dist.
	Continue over nearly level, open, grassy land.

BOOK 110

## RESURVEY: SUBDIVISION LINES, T. 7 N., R. 29 E.

54

## Chains

- 39.27 Fence (6 strand barbed wire) brs. N. 85° E., and S. 85° W.
- 40.57 Irrigation ditch, 12 lks. wide, 4 ft. deep, course SE. Milligan
- 62.02 / Creek, 50 lks. wide, 15 ft. deep, containing a stream of running water, 3 lks. wide, 2 ins. deep, course NE. Leave nearly level, and enter gently rolling, open, grassy land. Asc. 45 ft. over SE. slope.
- 67.97 Enter cultivated land, brs. NE. and SW.
- 72.97 Leave cultivated land, brs. NE. and SW. Continue over gently rolling grassy land.
- 73.97 Enter scattering timber and undergrowth, brs. E. and W.
- 75.50 Low spur, slopes NE.; desc. 5 ft. over NW. slope to
- 76.94 Intersect the original cor. of secs. 3, 4, 9 and 10, which is a lava stone, 24x20x18 ins. mkd. with 3 notches on E. face and 5 notches on S. face, firmly set in a mound of stone and witnessed by the one record bearing tree NE.

Reconstruct this cor. monument as follows: remove the mound of stone and the original cor. stone, and in same place, set an iron post, 3 ft. long, 2 ins. diam., 27 ins. in the ground, with the original cor. stone reset alongside, for cor. of secs. 3, 4, 9 and 10, with brass cap mkd.

T7N	R29E
S4	S3
S9	S10

1936

from which

the original bearing tree:

A pinyon, 16 ins. diam., brs. N. 50½° E., 146 lks. dist., mks. overgrown, Remark T7N R29E S3 BT.

and establish additional bearing trees:

A juniper, 10 ins. diam., brs. S. 84½° E., 137 lks. dist., mkd. T7N R29E S10 BT.

A pinyon, 12 ins. diam., brs. S. 66½° W., 233 lks. dist., mkd. T7N R29E S9 BT.

A pinyon, 6 ins. diam., brs. N. 44½° W., 143 lks. dist. mkd. T7N R29E S4 BT.

Sherman Lumpkins Cabin, brs. N. 42° E., about 20.00 chs. dist.

Old Cabin, brs. N. 34° W., about 15.00 chs. dist.

Shed and corral, brs. N. 56½° W., about 16.00 chs. dist.

Land, mountainous, nearly level and gently rolling.  
Soil, clay and volcanic loam, 2nd and 3rd rates.  
Timber, pinyon, juniper and yellow pine.  
Undergrowth, scrub timber.  
Fair grass.

## RESURVEY: SUBDIVISION LINES, T. 7 N., R. 29 E.

55

Chains	
	From the cor. of secs. 2, 3, 10 and 11. N. 89° 27' W., on true line, bet. secs. 3 and 10 (E. $\frac{1}{2}$ ). Over nearly level open land on mesa.
39.16	Rim of mesa brs. NE. and SW. Leave mesa, and enter mountainous land, scattering timber and undergrowth. Desc. 11 ft. over NW. slope to
40.16	Intersect the original $\frac{1}{4}$ sec. cor. of secs. 3 and 10, which is a lava stone, 10x8x6 ins. mkd. $\frac{1}{4}$ on N. face and firmly set in a mound of stone. No accessories. Reconstruct this cor. monument as follows: remove the mound of stone and the original cor. stone and in same place, set an iron post, 3 ft. long, 1 in. diam., 27 ins. in the ground, with the original cor. stone reset alongside, for $\frac{1}{4}$ sec. cor., with brass cap mkd.  $\frac{1}{4} \begin{array}{l} S 3 \\ S 10 \end{array}$ 1936  from which A yellow pine, 8 ins. diam., brs. N. 5 $\frac{1}{2}$ ° E., 96 lks. dist., mkd. $\frac{1}{4}$ S3.BT. A yellow pine, 6 ins. diam., brs. S. 8 $\frac{1}{2}$ ° E., 44 lks. dist., mkd. $\frac{1}{4}$ S10 BT.  Thence, N. 89° 24' W., on true line, bet. secs. 3 and 10 (W. $\frac{1}{2}$ ). Over mountainous land, thru scattering timber and undergrowth. Desc. 209 ft. over NW. slope.
13.60	Fence ( 4 strand barbed wire) brs. N. and S.
17.82	Bend in Milligan Creek, 25 lks. wide, 2 ft. deep, with small stream of water, course N. from SW. Leave mountainous and enter gently rolling land; asc. 68 ft. over SE. slope.
38.46	Low spur, slopes NE.; desc. 5 ft. over NW. slope to.
39.68	The cor. of secs. 3, 4, 9 and 10. Land, nearly level, mountainous and gently rolling. Soil, clay and volcanic loam, 2nd and 3rd rates. Timber, yellow pine, pinyon and oak. Undergrowth, scrub timber and bunch grass.
	From the cor. of secs. 3, 4, 33 and 34, on N. bdy. of the Tp., hereinbefore described. S. 2° 05' E., on true line, bet. secs. 3 and 4. Over gently rolling land, thru scattering timber. Desc. 116 ft. over gradual S. slope to
15.00	Leave gently rolling and enter mountainous land, brs. E. and W. Desc. 145 ft. over steep S. slope.
24.60	Wash, course E.; asc. 105 ft. over NE. slope.

## RESURVEY: SUBDIVISION LINES, T. 7 N., R. 29 E.

56

Chains	
28.60	Fence ( 4 strand barbed wire) brs. E. and W. Cliff, 50 ft. high, bearing NW. and SE., facing NE. brs. W. 20 lks. dist.
31.30	Spur, slopes E., desc. 156 ft. over S. slope to
37.75	(Proportional dist.) Set an iron post, 3 ft. long, 1 in. diam., 22 ins. in the ground to bedrock, and in a mound of stone to top, for $\frac{1}{4}$ sec. cor., with brass cap mkd.
	from which
	A juniper, 30 ins. diam., brs. S. 46° E., 109 lks. dist., mkd. $\frac{1}{4}$ S4 BT.
	A juniper, 24 ins. diam., brs. S. 82° W., 146 lks. dist., mkd. $\frac{1}{4}$ S3 BT.
	Desc. 168 ft. over steep S. slope to
44.41	Leave mountainous and enter gently rolling land. Desc. 65 ft. over gradual S. slope.
47.61	Road, brs. E. and W.
54.05	Dim road, brs. E. and NW.
54.90	Fence ( 4 strand barbed wire) brs. E. and W.
56.70	Leave gently rolling land and scattering timber, and enter nearly level open land.
59.06	Enter cultivated land, brs. E. and W.
62.96	Drain, course S. 80° E.
66.90	Drain, course E.
71.20	Road, brs. E. and W. Leave nearly level cultivated land and enter gently rolling land, scattering timber and undergrowth. Asc. 10 ft. over NW. slope to
75.34	The cor. of secs. 3, 4, 9 and 10.
	Land, mountainous, gently rolling and nearly level.. Soil, clay and volcanic loam, 2nd and 3rd rates. Timber, yellow pine, pinyon, aspen and oak. Undergrowth, scrub timber and bunch grass.
	From the cor. of secs. 4, 5, 32 and 33, on S. bdy. of the Tp. reconstructed under this group and described in notes of resurvey of N. bdy. of T. 6 N., R. 29 E.
	N. 1° 15' W., on true line, bet. secs. 32 and 33.
	Over gently rolling land, thru dense timber and scattering undergrowth. Desc. 45 ft. over NW. slope.
2.30	Trail, brs. NW. and SE.
15.00	Desc. 23 ft. over W. slope to
18.95	Spur slopes NW. Leave gently rolling and enter mountainous land. Desc. 153 ft. over N. slope.


RESURVEY: SUBDIVISION LINES, T. 7 N., R. 29 E.

Chains

26.70 Creek, with stream of running water, 3 lks. wide, 3 ins. deep, course NE. from NW. Asc. 173 ft. over SW. slope to  $\frac{1}{4}$  sec. cor.

35.80 Drain, 20 lks. wide, course SW.

39.69 (Mid point) Set an iron post, 3 ft. long, 1 in. diam., 24 ins. in the ground to bedrock, and in a mound of stone to top, for  $\frac{1}{4}$  sec. cor., with brass cap mkd.



from which

A yellow pine, 8 ins. diam., brs. S.  $67\frac{1}{2}^\circ$  E., 110 lks. dist., mkd.  $\frac{1}{4}$  S33 BT.

A yellow pine, 14 ins. diam., brs. S.  $36\frac{1}{2}^\circ$  W., 39 lks. dist., mkd.  $\frac{1}{4}$  S32 BT.


Thence over rolling land, thru scattering timber and undergrowth. Asc. 140 ft. over SW. slope.

40.00 Marshy draw, 50 lks. wide, course SW.

68.15 Rim of mesa, brs. NW. and SE. Thence over nearly level land on mesa.

79.38 Intersect the original cor. of secs. 28, 29, 32 and 33, which is a mound of stone witnessed by one of the two record bearing trees.

Reconstruct this cor. monument as follows: remove the mound of stone and in the center of its position, set an iron post, 3 ft. long, 2 ins. diam., 22 ins. in the ground to bedrock, and in a mound of stone to top, for cor. of secs. 28, 29, 32 and 33, with brass cap mkd.



1936

from which

the original bearing tree:

A yellow pine, 36 ins. diam., brs. N.  $57^\circ$  W., 15 lks. dist., mks. overgrown. Remark T7N R29E S29 BT.

and establish additional bearing trees:

A spruce, 6 ins. diam., brs. N.  $52\frac{3}{4}^\circ$  E., 66 lks. dist. mkd. T7N R29E S28 BT.

A yellow pine, 30 ins. diam., brs. S.  $7\frac{1}{4}^\circ$  E., 130 lks. dist., mkd. T7N R29E S33 BT.

A yellow pine, 14 ins. diam., brs. S.  $32^\circ$  W., 89 lks. dist., mkd. T7N R29E S32 BT.

Land, gently rolling, mountainous, rolling and nearly level. Soil, volcanic loam, 2nd and 3rd rates. Timber, spruce, fir, yellow pine, aspen and oak. Undergrowth, sorub timber and bunch grass.

## RESURVEY: SUBDIVISION LINES, T. 7 N., R. 29 E.

58

Chains

From the cor. of secs. 27, 28, 33 and 34.

S.  $87^{\circ} 49'$  W., on true line, bet. secs. 28 and 33.

Over mountainous land, thru dense timber and scattering undergrowth.

Desc. 64 ft. along N. slope.

24.45 Ridge, brs. N.  $70^{\circ}$  W. and S.  $70^{\circ}$  E.; asc. 106 ft. over S. and SE. slopes to37.16 (Mid point) Set an iron post, 3 ft. long, 1 in. diam., 20 ins. in the ground to bedrock, and in a mound of stone to top, for  $\frac{1}{4}$  sec. cor., with brass cap mkd. $\frac{1}{4}$   $\frac{S\ 28}{S\ 33}$ 

1936

from which

A yellow pine, 8 ins. diam., brs. N.  $70^{\circ}$  E., 30 lks. dist., mkd.  $\frac{1}{4}$  S28 BT.A yellow pine, 16 ins. diam., brs. S.  $24\frac{1}{2}^{\circ}$  E., 59 lks. dist., mkd.  $\frac{1}{4}$  S33 BT.

Thence over rolling land, thru dense timber and scattering undergrowth.

Asc. 84 ft. over SE. slope.

49.42 Same ridge, brs. N.  $75^{\circ}$  E. and S.  $70^{\circ}$  W. Desc. 35 ft. over NW. slope

63.00 Leave timber and undergrowth, and enter open grassy land, brs. NE. and SW.

67.20 Draw, course NE.; asc. 61 ft. over E. slope.

71.00 Leave open grassy land and enter dense timber and scattering undergrowth, brs. NW. and SW.

72.80 Rim of mesa brs. N. and S. Enter nearly level land on mesa.

74.32 The cor. of secs. 28, 29, 32 and 33.

Land, mountainous and rolling.

Soil, volcanic loam, 2nd and 3rd rates.

Timber, fir, yellow pine, aspen and spruce.

Undergrowth, scrub timber and bunch grass.

N.  $0^{\circ} 13'$  W., on true line, bet. secs. 28 and 29 (S.  $\frac{1}{2}$ ).

Over nearly level land, on mesa, thru dense timber and scattering undergrowth.

4.00 Rim of mesa, brs. NW. and SE. Leave mesa and enter rolling land. Desc. 127 ft. over NE. slope to wash.

10.90 Leave dense timber and scattering undergrowth, brs. NE. and SW. and enter open grassy land.

15.00 Leave open grassy land, brs. NW. and SE. and enter scattering timber and undergrowth.

31.00 Wash, 15 lks. wide, 4 ft. deep, course NE., asc. 70 ft. over SE. slope to  $\frac{1}{4}$  sec. cor.


RESURVEY: SUBDIVISION LINES, T. 7 N., R. 29 E.

Chains

36.80 Top of cliff, 40 ft. high, bearing NE. and SW. facing SE.

39.84 Intersect original 1/4 sec. cor. of secs. 28 and 29, which is a lava stone, 27x16x12 ins. above ground, mkd. 1/4 on S. face, firmly set and witnessed by the one record bearing tree NE.

Reconstruct this cor. monument as follows: alongside the original cor. stone, set an iron post, 3 ft. long, 1 in. diam., 12 ins. in the ground to bedrock, and in a mound of stone to top, for 1/4 sec. cor., with brass cap mkd.



from which

the original bearing tree:

A yellow pine, 30 ins. diam., brs. N. 66 1/2° E., 44 lks. dist., mks. overgrown. Remark 1/4 S28 BT.

and establish additional bearing tree:

A yellow pine, 24 ins. diam., brs. N. 33° W., 183 lks. dist., mkd. 1/2 S29 BT.

Thence,

N. 1° 23' E., on true line, bet. secs. 28 and 29 (N. 1/2).

Over gently rolling land, thru scattering timber and undergrowth. Asc. 56 ft. over SE. slope.

25.00 S. edge of top of spur, brs. NE. and SW. Thence across top of spur sloping NE. Desc. 9 ft. to


28.00 N. edge of top of spur, brs. NE. and SW. Leave top of spur, and enter mountainous land. Desc. 181 ft. over N. and NE. slopes to Benton Creek.

28.40 Fence (4 strand barbed wire) brs. NW. and SE.

39.20 Benton Creek with stream of running water, 5 lks. wide, 5 ins. deep, course SE. Asc. slightly over SW. slope to

39.47 Intersect original cor. of secs. 20, 21, 28 and 29, which is a lava stone, 10x10x6 ins. above ground, firmly set, mkd. with 4 notches on E. face and 2 notches on S. face and witnessed by the record bearing tree SE.

Reconstruct this cor. monument as follows: alongside the original cor. stone, set an iron post, 3 ft. long, 2 ins. diam., 16 ins. in the ground to bedrock, and in a mound of stone to top, for cor. of secs. 20, 21, 28 and 29, with brass cap mkd.



1936

from which

the original bearing tree:

A fir, 12 ins. diam., brs. S. 40° E., 20 lks. dist., mkd. T7N R29E S28 BT.

and establish additional bearing trees:

## RESURVEY: SUBDIVISION LINES, T. 7 N., R. 29 E.

60

Chains	
	<p>A fir, 30 ins. diam., brs. N. <math>37\frac{1}{2}^{\circ}</math> E., 77 lks. dist., mkd. T7N R29E S21 BT.</p> <p>A fir, 6 ins. diam., brs. S. <math>10\frac{3}{4}^{\circ}</math> E., 40 lks. dist., mkd. T7N R29E S28 BT.</p> <p>A fir, 8 ins. diam., brs. S. <math>43\frac{1}{2}^{\circ}</math> W., 37 lks. dist., mkd. T7N R29E S29 BT.</p> <p>A fir, 24 ins. diam., brs. N. <math>7^{\circ}</math> W., 67 lks. dist., mkd. T7N R29E S20 BT.</p> <p>Land, nearly level, rolling, gently rolling and mountainous. Soil, rocky, volcanic loam, 2nd and 3rd rates. Timber, fir, aspen and pine. Undergrowth, scrub timber and bunch grass.</p>
	<p>From the cor. of secs. 21, 22, 27 and 28.</p> <p>S. <math>87^{\circ} 31'</math> W., on true line, bet. secs. 21 and 28.</p> <p>Over mountainous land, thru dense timber and scattering undergrowth.</p> <p>Asc. 80 ft. over E. slope.</p>
9.88	Spur, slopes N.; desc. 80 ft. over W. slope.
17.82	Draw, course N.; asc. 227 ft. over E. slope.
34.80	Spur, slopes N.; desc. 20 ft. over W. slope to
37.44	(Mid point) Set an iron post, 3 ft. long, 1 in. diam., 27 ins. in the ground, for $\frac{1}{4}$ sec. cor., with brass cap mkd.
	$\frac{1}{4} \frac{S 21}{S 28}$
	1936
	from which
	<p>A pine, 18 ins. diam., brs. N. <math>72^{\circ}</math> E., 69 lks. dist., mkd. <math>\frac{1}{4}</math> S21 BT.</p> <p>A pine, 16 ins. diam., brs. S. <math>68\frac{3}{4}^{\circ}</math> E., 19 lks. dist., mkd. <math>\frac{1}{4}</math> S28 BT.</p>
	Desc. 307 ft. over steep broken W. slope.
49.40	Benton Creek, with a stream of running water, 5 lks. wide, 4 ins. deep, course NE.; asc. 270 ft. over rocky E. slope.
63.40	Spur, slopes SE., desc. 125 ft. over SW. slope to
74.88	The cor. of secs. 20, 21, 28 and 29.
	<p>Land, mountainous. Soil, rocky, volcanic loam, 3rd and 4th rates. Timber, fir, yellow pine, spruce and aspen. Undergrowth, scrub timber.</p>
	<p>N. <math>1^{\circ} 34'</math> W., on true line, bet. secs. 20 and 21 (S. <math>\frac{1}{2}</math>).</p> <p>Over mountainous land, thru dense timber and scattering undergrowth.</p> <p>Asc. 253 ft. over SW. slope.</p>



RESURVEY: SUBDIVISION LINES, T. 7 N., R. 29 E.

Chains	<p>and establish additional bearing tree:</p> <p>A yellow pine, 30 ins. diam., brs. N. 42° E., 66 lks. dist., mkd. T7N R29E S16 BT.</p> <p>Land, mountainous and gently rolling. Soil, volcanic loam, 2nd and 4th rates. Timber, aspen, pinyon and yellow pine, Undergrowth, scrub timber.</p>
30.58	<p>From the cor. of secs. 15, 16, 21 and 22.</p> <p>S. 88° 40' W., on true line, bet. secs. 16 and 21.</p> <p>Over mountainous land, thru dense timber and scattering undergrowth. Asc. 549 ft. over E. and SE. slopes.</p>
38.94	<p>Ridge, brs. NE. and SW.; desc. 90 ft. over NW. slope to</p> <p>(Mid point) Set an iron post, 3 ft. long, 1 in. diam., 18 ins. in the ground to bedrock, and in a mound of stone to top, for <math>\frac{1}{4}</math> sec. cor., with brass cap mkd.</p> <p style="text-align: center;"><math>\frac{1}{4}</math> <math>\frac{S\ 16}{S\ 21}</math></p> <p style="text-align: center;">1936</p> <p style="text-align: right;">from which</p> <p>A yellow pine, 16 ins. diam., brs. N. 42<math>\frac{3}{4}</math>° W., 39 lks. dist., mkd. <math>\frac{1}{4}</math> S16 BT.</p> <p>A yellow pine, 10 ins. diam., brs. S. 19° W., 44 lks. dist., mkd. <math>\frac{1}{4}</math> S21 BT.</p>
43.58	<p>Desc. 128 ft. over NW. slope.</p> <p>Draw, course NW.; asc. 55 ft. over NE. slope.</p>
49.10	<p>Spur, slopes NW.; desc. 136 ft. over W. slope.</p>
57.95	<p>Draw, course NE.; asc. 357 ft. over SE. slope to</p>
77.88	<p>The cor. of secs. 16, 17, 20 and 21.</p> <p>Land, mountainous. Soil, gravelly, rocky, volcanic loam, 3rd and 4th rates. Timber, pinyon, yellow pine, aspen and juniper. Undergrowth, scrub timber.</p>
1.00	<p>N. 5° 00' W., on true line, bet. secs. 16 and 17.</p> <p>Over mountainous land, thru dense timber and scattering undergrowth. Asc. 10 ft. over SE. slope.</p> <p>Spur, slopes NE. Desc. 110 ft. over NW. slope.</p>
17.40	<p>Draw, course NE.; desc. 425 ft. over NE. slope to</p>
42.51	<p>(Mid point) Set an iron post, 3 ft. long, 1 in. diam., 27 ins. in the ground, for <math>\frac{1}{4}</math> sec. cor., with brass cap mkd.</p> <p style="text-align: center;">S17   S16</p> <p style="text-align: center;">1936</p> <p style="text-align: right;">from which</p>

RESURVEY: SUBDIVISION LINES, T. 7 N., R. 29 E.

Chains

. A spruce, 6 ins. diam., brs. S.  $73\frac{3}{4}^{\circ}$  E., 20 lks. dist. mkd.  $\frac{1}{4}$  S16 BT.  
 . An aspen, 6 ins. diam., brs. S.  $68\frac{3}{4}^{\circ}$  W., 42 lks. dist. mkd.  $\frac{1}{4}$  S17 BT.  
 Desc. 214 ft. over NE. slope.


48.80 Fence ( 4 strand barbed wire) brs. NE. and SW.

50.10 Rudd Creek, with stream of running water 6 lks. wide, 5 ins. deep, course NE.; asc. 310 ft. over SE. slope to sec. cor.

59.60 Draw, course SE.

69.80 Spring branch, with small stream of running water, course SE.

85.02 Intersect original cor. of secs. 8, 9, 16 and 17, which is an unmarked lava stone, 12x10x6 ins. above ground, firmly set and witnessed by the two record bearing trees. Reconstruct this cor. monument as follows: alongside the original cor. stone, set an iron post, 3 ft. long, 2 ins. diam., 20 ins. in the ground to bedrock and in a mound of stone to top, for cor. of secs. 8, 9, 16 and 17, with brass cap mkd.



1936

from which

the original bearing trees:

A yellow pine, 36 ins. diam., brs. S.  $30\frac{1}{2}^{\circ}$  E., 13 lks. dist., mks. overgrown. Remark T7N R29E S16 BT.

A pinyon, 12 ins. diam., brs. S.  $49\frac{1}{4}^{\circ}$  W., 14 lks. dist., mks. overgrown. Remark T7N R29E S17 BT.

and establish additional bearing trees:

A pinyon, 14 ins. diam., brs. N.  $41\frac{1}{2}^{\circ}$  W., 38 lks. dist., mkd. T7N R29E S8 BT.

A pinyon, 27 ins. diam., brs. N.  $27^{\circ}$  E., 64 lks. dist. mkd. T7N R29E S9 BT.

Land, mountainous.  
 Soil, rocky, 4th rate.  
 Timber, pinyon and yellow pine, fir, spruce and aspen.  
 Undergrowth, scrub timber.

From the cor. of secs. 9, 10, 15 and 16.

S.  $89^{\circ} 07'$  W., on true line, bet. secs. 9 and 16 ( $E.\frac{1}{2}$ ).

Over mountainous land, thru dense timber and scattering undergrowth. Asc. 35 ft. along N. slope.

6.78 Desc. 40 ft. over NW. slope.

16.77 Rudd Creek, with stream of running water 5 lks. wide, 4 ins. deep course NE., from W., asc. slightly along creek to

RESURVEY: SUBDIVISION LINES, T. 7 N., R. 29 E.

64

Chains	
17.37	Leave creek, course E. and NE. from SW.; asc. 274 ft. over SE. slope to $\frac{1}{4}$ sec. cor.
26.07	Fence ( 4 strand barbed wire) brs. N. 55° E. and S. 55° W.
27.87	Trail, brs. NE. and SW.
39.78	<p>Intersect original <math>\frac{1}{4}</math> sec. cor. of secs. 9 and 16, which is a lava stone, 10x8x5 ins. above ground, mkd. <math>\frac{1}{4}</math> on N. face, firmly set, and witnessed by the two record bearing trees.</p> <p>Reconstruct this cor. monument as follows: alongside the original cor. stone, set an iron post, 3 ft. long, 1 in. diam., 18 ins. in the ground to bedrock, and in a mound of stone to top, for <math>\frac{1}{4}</math> sec. cor., with brass cap mkd.</p> <div style="text-align: center;"> <math display="block">\frac{1}{4} \frac{S 9}{S 16}</math> <p>1936</p> </div> <p style="text-align: right;">from which</p> <p>the original bearing trees:</p> <p>A pinyon, 14 ins. diam., brs. S. 85<math>\frac{1}{2}</math>° E., 35 lks. dist., mkd. <math>\frac{1}{4}</math> S BT.</p> <p>A yellow pine, 36 ins. diam., brs. N. 76° W., 36 lks. dist., mkd. <math>\frac{1}{4}</math> S BT.</p> <p>and establish additional bearing trees:</p> <p>A pinyon, 8 ins. diam., brs. North, 91 lks. dist., mkd. <math>\frac{1}{4}</math> S9 BT.</p> <p>A yellow pine, 14 ins. diam., brs. S. 6<math>\frac{1}{4}</math>° W., 86 lks. dist., mkd. <math>\frac{1}{4}</math> S16 BT.</p> <p>Thence,</p> <p>S. 88° 35' W., on true line, bet. secs. 9 and 16 (W.<math>\frac{1}{2}</math>).</p> <p>Over mountainous land, thru dense timber and scattering undergrowth.</p> <p>Asc. 315 ft. over S. and SE. slopes to sec. cor.</p>
20.80	Draw, course S.
29.70	Draw, course S.
39.69	<p>The cor. of secs. 8, 9, 16 and 17.</p> <p>Land, mountainous.</p> <p>Soil, black loam, gravelly, 2nd and 3rd rates.</p> <p>Timber, pinyon, yellow pine, aspen and juniper.</p> <p>Undergrowth, scrub timber.</p>
	<p>N. 11° 09' E. on true line, bet. secs. 8 and 9 (S.<math>\frac{1}{2}</math>).</p> <p>Over mountainous land, thru dense timber and scattering undergrowth.</p> <p>Asc. 35 ft. over SE. slope.</p>
2.50	<p>Spur, slopes NE. Leave mountainous and enter rolling land. Desc. 44 ft. over N. slope.</p>



## RESURVEY: SUBDIVISION LINES, T. 7 N., R. 29 E.

66

Chains

32.20 G.B.Leseur's cabin, brs. S.  $61\frac{1}{2}^{\circ}$  E., about 25.00 chs. dist.

38.94 Intersect original cor. of secs. 4, 5, 8 and 9, which is a lava stone, 12x10x4 ins. above ground, mkd. with 4 grooves on E. face and 5 grooves on S. face, firmly set and witnessed by the three record bearing trees. Reconstruct this cor. monument as follows: alongside the original cor. stone, set an iron post, 3 ft. long, 2 ins. diam., 14 ins. in the ground to bedrock, and in a mound of stone to top, for cor. of secs. 4, 5, 8 and 9, with brass cap mkd.

T7N	R29E
S5	S4
S8	S9

1936

from which

the original bearing trees:

A pinyon, 8 ins. diam., brs. N.  $51\frac{1}{2}^{\circ}$  E., 54 lks. dist. mkd. T7N R29E S4 BT.

A pinyon, 36 ins. diam., brs. S.  $30\frac{1}{2}^{\circ}$  W., 34 lks. dist. mkd. T7N R29E S8 BT.

A pinyon, 12 ins. diam., brs. S.  $40\frac{1}{2}^{\circ}$  E., 41 lks. dist. mkd. T7N R29E S9 BT.

and establish additional bearing trees:

A pinyon, 12 ins. diam., brs. N.  $54\frac{1}{2}^{\circ}$  E., 74 lks. dist. mkd. T7N R29E S4 BT.

A yellow pine, 14 ins. diam., brs. S.  $62\frac{3}{4}^{\circ}$  E., 56 lks. dist., mkd. T7N R29E S9 BT.

A pinyon, 16 ins. diam., brs. N.  $16\frac{1}{2}^{\circ}$  W., 87 lks. dist., mkd. T7N R29E S5 BT.

Land, mountainous and rolling.

Soil, rocky, 4th rate.

Timber, pinyon, yellow pine, aspen and juniper.

Undergrowth, scrub timber.

From the cor. of secs. 3, 4, 9 and 10.

N.  $89^{\circ} 57'$  W., on true line, bet. secs. 4 and 9 (E.  $\frac{1}{2}$ )

Over gently rolling land, thru scattering timber and undergrowth. Desc. 40 ft. over NW. slope.

10.00 Fence cor. brs. S. 75 lks. dist., from which fences extend W. and S.

20.30 Fence cor. brs. S. 1.00 ch. dist., from which fences extend E. and S.  $85^{\circ}$  W.

20.50 Draw, course NE. Leave gently rolling and enter rolling land. Asc. 29 ft. over SE. slope to

24.00 Road, brs. NE. and SW. Leave rolling and enter mountainous land, brs. NE. and SW. Asc. 185 ft. over SE. slope.

38.80 Bend in ridge, brs. NE. and NW.; desc. 16 ft. over SW. slope to.

## RESURVEY: SUBDIVISION LINES, T. 7 N., R. 29 E.

67

## Chains

39.74

Intersect original  $\frac{1}{4}$  sec. cor. of secs. 4 and 9, which is a lava stone, 12x10x4 ins. above ground, firmly set, mkd.  $\frac{1}{4}$  on S. face and witnessed by the one record bearing tree.

Reconstruct this cor. monument as follows: alongside the original cor. stone, set an iron post, 3 ft. long, 1 in. diam., 27 ins. in the ground, for  $\frac{1}{4}$  sec. cor., with brass cap mkd.

$$\frac{1}{4} \frac{S 4}{S 9}$$

1936

from which

the original bearing tree:

A pine, 12 ins. diam., brs. S. 54° W., 26 lks. dist., mkd.  $\frac{1}{4}$  S BT.

and establish additional bearing tree:

A pinyon, 12 ins. diam., brs. N. 8 $\frac{1}{2}$ ° E., 34 lks. dist. mkd.  $\frac{1}{4}$  S4 BT.

Thence,

N. 88° 56' W., on true line, bet. secs. 4 and 9 (W.  $\frac{1}{2}$ ).

Desc. 100 ft. over SW. slope.

7.90

Fence (4 strand barbed wire) brs. N. 30° E. and S. 30° W. Turns to W. at 50 lks. SW.

10.60

Wash, 6 lks. wide, 3 ft. deep, course SE. Leave mountainous and enter rolling land. Asc. 60 ft. over E. slope.

12.00

Fence (4 strand barbed wire) brs. N. and S. Fence cor. brs. S. 1.00 ch. dist., from which fences extend E. and N.

13.30

Road, brs. NNW and SSE.

13.70

Road, brs. NNE and SSW. Joins above road at 50 lks. N., thence N.

17.70

Spur, slopes SE. Leave rolling and enter mountainous land. Asc. 86 ft. over S. slope to

27.60

Draw, course SE. Asc. 175 ft. over E. slope to

34.20

Spur, slopes SE. Asc. 85 ft. over S. and SE. slopes to

39.02

The cor. of secs. 4, 5, 8 and 9.

Land, gently rolling. rolling and mountainous.  
Soil, rocky, volcanic loam, 2nd and 3rd rates.  
Timber, juniper, pinyon and yellow pine.  
Undergrowth, scrub timber.

From the cor. of secs. 4, 5, 32 and 33, on N. bdy. of the Tp., hereinbefore described.


S. 3° 26' E., on true line, bet. secs. 4 and 5.

Over mountainous land, thru dense timber and scattering undergrowth. Asc. 75 ft. over NW. slope.

RESURVEY: SUBDIVISION LINES, T. 7 N., R. 29 E.

Chains

- 2.64 Wash, 6 lks. wide, 3 ft. deep, course NW.
- 7.94 Draw, course NW.; asc. 156 ft. over NE. slope.
- 13.94 Spur, slopes NW.; desc. 37. ft. over SW. slope.
- 14.74 Springerville Highway, in curve, bearing NE. and SE., brs. E. about 70 lks. dist.
- 16.04 Draw, course W.; asc. 160 ft. over NW. slope.
- 21.34 Springerville Highway, brs. NE. and SW.
- 28.24 Thence along W. slope, descending slightly to
- 30.24 Desc. 75 ft. over SW. slope to
- 37.06 (Proportional dist.) Set an iron post, 3 ft. long, 1 in. diam., 27 ins. in the ground, for  $\frac{1}{4}$  sec. cor. with brass cap mkd.



from which

A pinyon, 6 ins. diam., brs. S.  $81\frac{1}{2}^{\circ}$  E., 66 lks. dist. mkd.  $\frac{1}{4}$  S4 BT.

A pinyon, 8 ins. diam., brs. N.  $53\frac{1}{4}^{\circ}$  W., 62 lks. dist. mkd.  $\frac{1}{4}$  S5 BT.

Desc. 50 ft. over S. slope.

- 38.44 Milligan Valley road, brs. E. and W. Joins Springerville Highway at a point 2 chs. W.
- 40.44 Telephone line, brs. NW. and SE.
- 44.24 Creek, with stream of running water, 3 lks. wide, 1 in. deep, course E., asc. 345 ft. over N. and NW. slopes.
- 53.24 Springerville Highway, brs. NW. and SE.
- 56.64 Springerville Highway, brs. NE. and SW.
- 65.05 Ridge, brs. NE. and SW. Desc. 185 ft. over steep broken SE. slope to
- 74.14 The cor. of secs. 4, 5, 8 and 9.

Land, mountainous.  
 Soil, gravelly and rocky, 3rd and 4th rates.  
 Timber, pinyon, fir, juniper and yellow pine.  
 Undergrowth, scrub timber and bunch grass.

From the cor. of secs. 5, 6, 31 and 32, on S. bdy. of the Tp., reconstructed under this group as described in notes of resurvey of N. bdy. of T. 6 N., R. 29 E.

N.  $0^{\circ} 24'$  E., on true line, bet. secs. 31 and 32 ( $S.\frac{1}{2}$ ).

Over gently rolling land, thru scattering timber and undergrowth.

Asc. 135 ft. over SE. slope to

## RESURVEY: SUBDIVISION LINES, T. 7 N., R. 29 E.

69

## Chains

- 28.90 Asc. 28 ft. over SW. slope.
- 33.00 Low ridge, brs. NW. and SE. Spurs slope SW. and N. from ridge about 1 ch. NW. Desc. 20 ft. over NE. slope to
- 39.83 Intersect point of original location of the  $\frac{1}{4}$  sec. cor. of secs. 31 and 32, determined by reference to the almost obliterated remains of the stumps of the two record bearing trees.  
Reconstruct this cor. monument as follows: at original point, set an iron post, 3 ft. long, 1 in. diam., 27 ins. in the ground, for  $\frac{1}{4}$  sec. cor. with brass cap mkd.
- $\frac{1}{4}$   
 S31 | S32  
 1936
- from which
- A fir, 24 ins. diam., brs. N.  $74\frac{3}{4}^{\circ}$  E., 15 lks. dist., mkd.  $\frac{1}{4}$  S32 BT.
- A fir, 16 ins. diam., brs. S.  $17\frac{1}{4}^{\circ}$  W., 11 lks. dist., mkd.  $\frac{1}{4}$  S31 BT.
- Lake, 15.00 chs. long N. and S. and 10.00 chs. wide E. and W., brs. West, about 10.00 chs. dist.
- Thence,
- N.  $0^{\circ} 08'$  W., on true line, bet. secs. 31 and 32 (N.  $\frac{1}{2}$ ).
- Over gently rolling land, thru scattering timber and undergrowth. Desc. 70 ft. over E. and NE. slopes.
- 8.00 Leave timber and undergrowth and enter open grassy land, brs. E. and W.
- 9.00 Enter nearly level land. Desc. slightly over N. slope to draw.
- 18.90 Lake, about 2.00 chs. diam., brs. E. about 2.00 chs. dist.
- 33.90 Draw, course N.  $80^{\circ}$  E. Ascend slightly over E. slope to sec. cor.
- 39.53 Telephone line, brs. E. and W.
- 40.00 Intersect original cor. of secs. 29, 30, 31 and 32, which is a faintly mkd. lava stone, 20x14x4 ins. firmly set in a mound of stone. No accessories.  
Reconstruct this cor. monument as follows: remove the mound of stone, and the original cor. stone and in same place, set an iron post, 3 ft. long, 2 ins. diam., 10 ins. in the ground to bedrock, with original cor. stone reset alongside and in a mound of stone to top, for cor. of secs. 29, 30, 31 and 32, with brass cap mkd.
- T7N R29E  
 S30 | S29  
 S31 | S32  
 1936
- Pats Knoll Lookout brs. S.  $85^{\circ} 43'$  W.
- Land, gently rolling and nearly level.  
Soil, rocky and black loam, 3rd and 4th rates.

## RESURVEY: SUBDIVISION LINES, T. 7 N., R. 29 E.

70

Chains	<p>Timber, pine, aspen and fir. Undergrowth, scrub timber. Fair grass.</p>
	<p>From the cor. of secs. 28, 29, 32 and 33. N. 89° 29' W., on true line, bet. secs. 29 and 32. Over nearly level land on mesa; thru dense timber and scattering undergrowth.</p>
14.10	<p>Leave dense timber and scattering undergrowth, brs. NE. and SW., and enter very scattering timber. Thence over grassy land.</p>
37.80	<p>W. end of lake about 15.00 chs. long. E. and W. and 10.00 chs. wide, brs. N. about 3.00 chs. dist.</p>
39.11	<p>(Mid point) Set an iron post; 3 ft. long, 1 in. diam., 24 ins. in the ground, and in a mound of stone to top, for <math>\frac{1}{4}</math> sec. cor., with brass cap mkd.</p>
	<p style="text-align: center;"><math>\frac{1}{4}</math> <math>\frac{S\ 29^\circ}{S\ 32}</math></p>
	<p style="text-align: center;">1936</p>
	<p style="text-align: right;">from which</p>
	<p>A pinyon, 18 ins. diam., brs. N. 65° W., 56 lks. dist. mkd. <math>\frac{1}{4}</math> S29 BT;</p>
	<p>A pinyon, 24 ins. diam., brs. S. 34<math>\frac{1}{2}</math>° W., 203 lks. dist., mkd. <math>\frac{1}{4}</math> S32 BT.</p>
46.31	<p>Gate in fence, brs. N. and S. Leave very scattering timber and enter open grassy land.</p>
46.50	<p>Leave nearly level land on mesa, and enter gently rolling land. Desc. 30 ft. over SW. slope.</p>
54.11	<p>Creek, with a small stream of running water, in channel, 15 lks. wide, 2 ft. deep, course SE.</p>
59.51	<p>Same creek, course NE., asc. 70 ft. over SE. slope.</p>
64.90	<p>E. fence of old corral, brs. N. and S. Thence across corral.</p>
68.20	<p>Leave gently rolling and enter nearly level land.</p>
68.90	<p>W. fence of same corral, brs. N. and S. Leave corral.</p>
78.21	<p>The cor. of secs. 29, 30, 31 and 32. Land, nearly level and gently rolling. Soil, black gravelly loam, 2nd and 3rd rates. Timber, pinyon, aspen and fir. Undergrowth, scrub timber. Fair grass.</p>
	<p>From the cor. of secs. 25, 30, 31 and 36, on W. bdy. of the Tp., hereinbefore described.</p>
	<p>S. 89° 36' E., on true line, bet. secs. 30 and 31.</p>
	<p>Over gently rolling open grassy land. Asc. 37 ft. over W. and NW. slopes to</p>

## RESURVEY: SUBDIVISION LINES, T. 7 N., R. 29 E.

71

Chains	
11.63	Low spur, slopes S. 60° W. Asc. 180 ft. over S. and SW. slopes to ridge.
13.27	Enter dense timber and scattering undergrowth, brs. N. and S.
21.50	Enter mountainous land.
30.97	U.S. Forest Service Pats Knoll lookout tower, brs. S. 23° 50' E.
31.00	Ridge, brs. NW. and SE.; desc. 130 ft. over NE. slope to $\frac{1}{4}$ sec. cor.
37.97	Lookout trail, brs. NE. and SW.
39.37	(Proportional dist.) Set an iron post, 3 ft. long, 1 in. diam., 27 ins. in the ground, and in a mound of stone to top, for $\frac{1}{4}$ sec. cor., with brass cap mkd.
	$\frac{1}{4}$ $\frac{S\ 30}{S\ 31}$
	1936
	from which
	An aspen, 12 ins. diam., brs. N. 87 $\frac{1}{4}$ ° W., 25 lks. dist., mkd. $\frac{1}{4}$ S30 BT.
	An aspen, 12 ins. diam., brs. S. 23° W., 27 lks. dist., mkd. $\frac{1}{4}$ S31 BT.
	Desc. 178 ft. over NE. slope to
54.35	Leave mountainous and enter gently rolling land. Desc. 25 ft. over NE. slope to
59.50	Enter nearly level land, brs. N. and S.
64.40	Dim road, brs. N. and S. Leave dense timber and scattering undergrowth and enter open grassy land.
79.17	The cor. of secs. 29, 30, 31 and 32.
	Land, gently rolling, mountainous and nearly level. Soil, black loam, rocky, 3rd and 4th rates. Timber, fir, pine, spruce and aspen. Undergrowth, scrub timber. Fair grass.
	N. 0° 30' W., on true line, bet. secs. 29 and 30 (S. $\frac{1}{2}$ ). Over nearly level open grassy land.
21.50	Seep of water, on line.
30.00	Enter scattering timber, brs. NE. and SW.
33.40	Road, brs. NE. and SW. Leave timber.
37.40	Old corral, brs. W., about 3.00 chs. dist.
40.18	Intersect original $\frac{1}{4}$ sec. cor. of secs. 29 and 30, which is a mound of stone, witnessed by stump of one of the two record bearing trees: Reconstruct this cor. monument as follows: remove the mound of stone, and in the center of its position, set an iron post, 3 ft. long, 1 in. diam., 27 ins. in the ground and in a mound of stone to top, for $\frac{1}{4}$ sec. cor.

## RESURVEY: . SUBDIVISION LINES, T. 7 N., R. 29 E.

72

Chains

with brass cap mkd.

$$S30 \begin{array}{c} \frac{1}{4} \\ | \\ S29 \end{array}$$

1936

from which

A pinyon, 24 ins. diam., brs. N.  $18\frac{1}{2}^{\circ}$  E., 228 lks. dist. mkd.  $\frac{1}{2}$  S29 BT.

A yellow pine, 24 ins. diam., brs. S.  $86\frac{1}{2}^{\circ}$  W., 160 lks. dist., mkd.  $\frac{1}{4}$  S30 BT.

A fir stump, 30 ins. diam., brs. S.  $35\frac{1}{2}^{\circ}$  E., 27 lks. dist., mkd.  $\frac{1}{4}$  S BT.

U.S. Forest Service Cabin, brs. N.  $76\frac{1}{2}^{\circ}$  E., about 7.00 chs. dist.

Fence cor. from which fences extend E. and NNE. brs. N.  $83\frac{1}{2}^{\circ}$  E., about 4.00 chs. dist.

Bunk house chimney, brs. N.  $24^{\circ}$  W., about 5.00 chs. dist.

Thence,

N.  $0^{\circ} 32'$  W., on true line, bet. secs. 29 and 30 (N.  $\frac{1}{2}$ ).

Over nearly level open grassy land.

3.20 Road, brs. E. to cabin and W. to Springerville Highway.

5.60 Seep spring, brs. W., 25 lks. dist.

7.50 Dim road, brs. NE. and SW.

10.00 Leave open land and enter scattering timber, brs. NE. and SW.

14.60 Telephone line, brs. NE. and SW.

20.00 Enter dense timber, brs. NE. and SW.

37.40 Fence (4 strand barbed wire), brs. N.  $60^{\circ}$  W., and S.  $60^{\circ}$  E.

40.57 Point for reestablishment of the sec. cor. determined by double proportion bet. original cor.  $1\frac{1}{2}$  miles N., and  $\frac{1}{2}$  mile E.; S. and W.; at which point;  
Set an iron post, 3 ft. long, 2 ins. diam., 20 ins. in the ground to bedrock, and in a mound of stone to top, for cor. of secs. 19, 20, 29 and 30, with brass cap mkd.

$$\begin{array}{c|c} T7N & R29E \\ S19 & S20 \\ \hline S30 & S29 \end{array}$$

1936

from which

A yellow pine, 18 ins. diam., brs. N.  $15\frac{1}{2}^{\circ}$  E., 104 lks. dist., mkd. T7N R29E S20 BT.

A pinyon, 10 ins. diam., brs. S.  $8\frac{1}{2}^{\circ}$  E., 60 lks. dist., mkd. T7N R29E S29 BT.

A pinyon, 14 ins. diam., brs. S.  $70\frac{1}{2}^{\circ}$  W., 25 lks. dist., mkd. T7N R29E S30 BT.

RESURVEY: SUBDIVISION LINES, T. 7 N., R. 29 E.

Chains

A yellow pine, 12 ins. diam., brs. N. 50 1/2° E., 123 lks. dist., mkd. T7N R29E S19 BT.

Land, nearly level.  
Soil, gravelly, black loam, 2nd and 3rd rates.  
Timber, aspen, yellow pine, pinyon and fir.  
Undergrowth, scrub timber.  
Fair grass.

From the cor. of secs. 20, 21, 28 and 29,  
N. 87° 52' W., on true line, bet. secs. 20 and 29 (E. 1/2).

Over mountainous land, thru dense timber and scattering undergrowth.

0.20 Benton Creek, with stream of running water 9 lks. wide, 5 ins. deep, course SE., asc. 132 ft. over NE. slope to

6.20 Leave mountainous and enter rolling land. Asc. 55 ft. over N. slope.

28.70 Desc. 26 ft. over NW. slope.

31.30 Fence ( 4 strand barbed wire) brs. N. 30° W. and S. 30° E.

37.00 Benton Creek, with stream of running water 8 lks. wide, 4 ins. deep, course NE. Asc. 24 ft. over NE. slope to 1/4 sec. cor.

39.80 Fence (.5 strand barbed wire) brs. N. and S..

39.82 Intersect. original 1/4 sec. cor. of secs. 20 and 29, which is a mound of stone, witnessed by the one record bearing tree SW.

Reconstruct this cor. monument as follows: remove the mound of stone, and in the center of its position, set an iron post, 3 ft. long, 1 in. diam., 27 ins. in the ground, and in a mound of stone to top, for 1/4 sec. cor., with brass cap mkd.

$$\frac{1}{4} \frac{S 20}{S 29}$$

1936

from which

the original bearing tree:

A yellow pine, 36 ins. diam. (dead) brs. S. 3° W., 53 lks. dist., mkd. 1/4 S BT.

and establish additional bearing trees:

A yellow pine, 36 ins. diam., brs. N. 1 1/4° E., 83 lks. dist., mkd. 1/4 S20 BT.

A yellow pine, 24 ins. diam., brs. S. 64° E., 81 lks. dist., mkd. 1/4 S29 BT.

Thence,

N. 89° 16' W., on true line, bet. secs. 20 and 29 (W. 1/2).

Over rolling land, thru dense timber and scattering undergrowth. Asc. 69 ft. over NE. slope.

3.50 Fence ( 5 strand barbed wire) brs. N. 70° W. and S. 70° E.

## RESURVEY: SUBDIVISION LINES, T. 7 N., R. 29 E.

74

Chains	
7.00	Same fence, brs. N. 80° E. and S. 80° W., Leave timber and undergrowth, brs. NE. and SW. and enter open grassy land.
10.00	Desc. 20 ft. over NW. slope.
17.10	E. edge of shallow lake, brs. NW. and SE., thence over water surface of same.
26.20	W. edge of lake, brs. NW. and SE.. Leave lake. Thence over nearly level open grassy land.
31.20	Dim road, brs. S. and NW. Leave open grassy land and enter dense timber and scattering undergrowth, brs. N. and S.
38.80	Telephone line, brs. N. and S.
39.96	The cor. of secs. 19, 20, 29 and 30.  Land, mountainous, rolling and nearly level. Soil, gravelly, dark loam, 2nd and 3rd rates. Timber, aspen, pinyon, fir and yellow pine. Undergrowth, scrub timber. Fair grass.
	From the cor. of secs. 19, 24, 25 and 30, on W. bdy. of the Tp., hereinbefore described.
	S. 86° 38' E., on true line, bet. secs. 19 and 30. (W. $\frac{1}{2}$ ).
	Over gently rolling open grassy land. Desc. 40 ft. over NE. slope.
1.17	Springerville Highway, in curve, brs. NW. and S.
5.62	Draw, course N. Asc. 52 ft. over NW. slope.
24.05	Thence over N. slope.
33.27	Point of low spur, slopes NE. Cabin brs. S. 25° 10' E., about 15.00 chs. dist. Corral gate, brs. S. 1 $\frac{1}{2}$ ° E.
	Desc. 17 ft. over E. slope to
38.65	Intersect original $\frac{1}{4}$ sec. cor. of secs. 19 and 30, which is a lava stone, 12x8x5 ins. mkd. $\frac{1}{4}$ on N. face, firmly set in a mound of stone. No accessories. Reconstruct this cor. monument as follows: remove the mound of stone, and the original cor. stone, and in same place, set an iron post, 3 ft. long, 1 in. diam., 20 ins. in the ground to bedrock, with the original cor. stone reset alongside, and in a mound of stone to top, for $\frac{1}{4}$ sec. cor., with brass cap mkd.
	$\frac{1}{4} \frac{S 19}{S 30}$
	1936
	N. 86° 43' E., on true line, bet. secs. 19 and 30 (E. $\frac{1}{2}$ ).
	Over gently rolling open grassy land. Desc. slightly over E. slope.
0.55	Wash, 3 lks. wide, 1 ft. deep, course NE. Leave gently rolling and enter nearly level land.

## RESURVEY: SUBDIVISION LINES, T. 7 N., R. 29 E. BLOCK 179

75

Chains	
11.75	Dim road brs. NW. and SE. Leave open grassy land and enter dense timber and scattering undergrowth, brs. NE. and SW.
22.65	Fence ( 6 strand barbed wire) brs. N. 40° E. and S. 40° W.
24.80	Leave nearly level and enter gently rolling land. Asc. 30 ft. over NW. slope to
29.70	Reenter nearly level land.
36.85	Fence ( 4 strand barbed wire) brs. S. 40° E. and N. 40° W.
39.78	The cor. of secs. 19, 20, 29 and 30.
	Land, gently rolling and nearly level. Soil, black loam, gravelly, 2nd and 3rd rates. Timber, aspen, yellow pine and fir. Undergrowth, scrub timber. Fair grass.
	N. 0° 37' W., on true line, bet. secs. 19 and 20.
	Over nearly level land, thru dense timber and scattering undergrowth.
12.60	Telephone line, brs. NW. and SE.
16.60	Trail, brs. NE. and W.
18.30	Dim road, brs. NW. and SE.
32.50	Leave nearly level and enter rolling land, brs. NE. and SW., desc. 100 ft. over NW. slope to $\frac{1}{4}$ sec. cor.
36.87	Enter mountainous land.
40.57	(Mid point) Set an iron post, 3 ft. long, 1-in. diam., 27 ins. in the ground, and in a mound of stone to top, for $\frac{1}{4}$ sec. cor. with brass cap mkd.
	$\begin{array}{ccc} & \frac{1}{4} & \\ &   & \\ S19 & & S20 \\ & 1936 & \end{array}$
	from which
	A fir; 10 ins. diam., brs. N. 32° E., 61 lks. dist., mkd. $\frac{1}{4}$ S20 BT.
	A fir, 16 ins. diam., brs. S. 47 $\frac{1}{2}$ ° W., 42 lks. dist., mkd. $\frac{1}{4}$ S19 BT.
	Desc. 83 ft. over NW. slope.
43.90	Rudd Creek (dry) 6-lks. wide, 2 ft. deep, course NE., asc. 75 ft. over steep SE. slope to.
47.88	Leave mountainous and enter rolling land, brs. NE. and SW. Asc. 65 ft. over gradual SE. slope to
71.50	Ridge, brs. NE. and SW. Leave dense and enter scattering timber. Desc. 35 ft. over NW. slope to sec. cor.
77.50	Center of earth dam for reservoir, brs. W. about 10.00 chs. dist.
81.14	Point for reestablishment of the sec. cor: determined by double proportion bet. original cors. $\frac{1}{2}$ mile N., 1 mile

## RESURVEY: SUBDIVISION LINES, T. 7 N., R. 29 E.

76

Chains

E. and W., and  $1\frac{1}{2}$  miles S.; at which point  
Set an iron post, 3 ft. long, 2 ins. diam., 27 ins. in the  
ground, for cor. of secs. 17, 18, 19 and 20, with brass  
cap mkd.

T7N	R29E
S18	S17
S19	S20

1936

from which

A yellow pine, 36 ins. diam., brs. N.  $80\frac{1}{2}^{\circ}$  E., 132  
lks. dist., mkd. T7N R29E S17 BT.

A yellow pine, 36 ins. diam., brs. S.  $35^{\circ}$  E., 168 lks.  
dist., mkd. T7N R29E S20 BT.

A pinyon, 16 ins. diam., brs. S.  $16^{\circ}$  W., 118 lks. dist.  
mkd. T7N R29E S19 BT.

A yellow pine, 16 ins. diam., brs. N.  $38\frac{1}{2}^{\circ}$  W., 82 lks.  
dist., mkd. T7N R29E S18 BT.

Land, nearly level, rolling and mountainous.  
Soil, gravelly and rocky, 3rd and 4th rates.  
Timber, pinyon, aspen, yellow pine and fir.  
Undergrowth, scrub timber and bunch grass.

From the cor. of secs, 16, 17, 20 and 21.

N.  $87^{\circ} 35'$  W., on true line, bet. secs. 17 and 20.

Over mountainous land, thru dense timber and scattering  
undergrowth.

Asc. 28 ft. over SE. slope.

2.46 Spur, slopes NE. Desc. 162 ft. over NW. slope.

21.30 Draw, course NE.; asc. 66 ft. over SE. slope.

26.30 Spur slopes NE.; desc. 130 ft. over NW. slope to

38.96 (Mid point) Set an iron post, 3 ft. long, 1 in. diam.,  
27 ins. in the ground and in a mound of stone to top,  
for  $\frac{1}{4}$  sec. cor., with brass cap mkd.

$\frac{1}{4}$	S 17
	S 20

1936

from which

A fir, 6 ins. diam., brs. N.  $4\frac{1}{4}^{\circ}$  W., 6 lks. dist., mkd.  
 $\frac{1}{4}$  S17 BT.

A fir, 8 ins. diam., brs. S.  $45^{\circ}$  W., 46 lks. dist.,  
mkd.  $\frac{1}{4}$  S20 BT.

Desc. 160 ft. over NW. slope.

41.65 Line tree, a yellow pine, 36 ins. diam., mkd. with 2  
notches on each of E. and W. faces.

49.40 Rudd Creek, with stream of running water, 8 lks. wide, 5  
ins. deep, course NE., asc. 325 ft. over SE. slope.

## RESURVEY: SUBDIVISION LINES, T. 7 N., R. 29 E. BOOK

77

Chains	
66.50	Ridge, brs. NE. and SW. Leave mountainous land and dense timber and enter rolling land and scattering timber brs. NE. and SW. Desc. 26 ft. over NW. slope to
77.92	The cor. of secs. 17, 18, 19 and 20. Land, mountainous and rolling. Soil, gravelly and rocky, 3rd and 4th rates. Timber, pinyon, fir, aspen and yellow pine. Undergrowth, scrub timber and bunch grass.
	From the cor. of secs. 13, 18, 19 and 24, on W. bdy. of the Tp., hereinbefore described. N. 88° 31' E., on true line, bet. secs. 18 and 19. Over gently rolling open grassy land, desc. slightly over N. slope.
1.10	Desc. 35 ft. over NE. slope.
1.75	Old road, brs. NW. and SE.
5.93	Draw, course N.; asc. 46 ft. over W. slope to
16.95	Leave gently rolling and enter nearly level land, brs. NE. and SW.
25.33	Springerville Highway, brs. NE. and SW.
30.53	Leave open grassy land and enter dense timber and scattering undergrowth, brs. N. and S.
38.05	(Proportional dist.) Set an iron post, 3 ft. long, 1 in. diam., 22 ins. in the ground to bedrock, and in a mound of stone to top, for $\frac{1}{4}$ sec. cor., with brass cap mkd. $\frac{1}{4} \frac{S 18}{S 19}$ 1936 from which A pinyon, 18 ins. diam., brs. N. 5 $\frac{1}{2}$ ° E., 63 lks. dist., mkd. $\frac{1}{4}$ S18 BT. A pinyon, 36 ins. diam., brs. S. 5 $\frac{1}{2}$ ° W., 95 lks. dist., mkd. $\frac{1}{4}$ S19 BT.
41.70	Leave nearly level and enter mountainous land, brs. NE. and SW. Desc. 67 ft. over SE. slope to
46.10	Leave mountainous and enter rolling land, brs. NE. and SW. Desc. 35 ft. over SE. slope.
47.73	Telephone line, brs. S. and NE.
50.23	Leave timber, brs. N. and S. and continue thru scattering undergrowth.
50.85	Dim road, brs. NE. and SW.
52.03	Leave rolling and enter nearly level land, brs. NE. and SW.
59.83	Fence ( 4 strand barbed wire) brs. NE. and SW., enter scattering timber, brs. NE. and SW.

Chains	
63.13	Center of reservoir, brs. S. about 10.00 chs. dist.
66.00	Leave nearly level and enter rolling land: Desc. 15 ft. over SE. slope.
66.33	NW, end of earth dam about 6 chs. long, brs. SE., 20 lks. dist.
70.09	Wash; 6 lks. wide, course NE.; asc. 50 ft. over NW. slope to
76.95	The cor. of secs. 17, 18, 19 and 20.
	Land, gently rolling, nearly level, mountainous and rolling. Soil, gravelly and rocky, 3rd and 4th rates. Timber, pinyon, yellow pine, aspen and fir. Undergrowth, scrub timber. Fair grass.
	N. 2° 41' E., on true line, bet. secs. 17 and 18 (S. $\frac{1}{2}$ ).
	Over rolling land, thru scattering timber and undergrowth. Desc. 20 ft. over gradual NW. slope to
6.70	Leave rolling and enter mountainous land; desc. 105 ft. over steep NW. slope.
11.20	Fence ( 4 strand barbed wire) brs. NE. and SW.
11.80	Wash, 8 lks. wide, 2 ft. deep, course NE. Leave mountainous and enter rolling land. Asc. 50 ft. over SE. slope.
12.40	Trail, brs. NE. and SW.
30.00	Spur, slopes NE. Leave rolling and enter mountainous land. Desc. 91 ft. over NW. slope.
34.40	Wash, 8 lks. wide, 2 ft. deep, course NE.; asc. 85 ft. over SE. slope to
40.62	Intersect point of original location of the $\frac{1}{2}$ sec. cor. of secs. 17 and 18, determined by reference to the record bearing tree NW.
	Reconstruct this cor. monument as follows: at true cor. point, set an iron post, 3 ft. long, 1 in. diam., 27 ins. in the ground, and in a mound of stone to top, for $\frac{1}{2}$ sec. cor., with brass cap mkd.
	$\begin{array}{ccc} & \frac{1}{4} & \\ &   & \\ S18 & & S17 \\ &   & \\ & 1936 & \end{array}$
	from which
	the original bearing tree:
	A pinyon, 10 ins. diam., brs. N. 25° W., 20 lks. dist., mkd. $\frac{1}{2}$ S BT.
	and establish additional bearing tree:
	A pinyon, 10 ins. diam., brs. S. 38 $\frac{1}{2}$ ° E., 61 lks. dist., mkd. $\frac{1}{2}$ S17 BT.
	Thence,
	N. 1° 20' E., on true line, bet. secs. 17 and 18 (N. $\frac{1}{2}$ ).

## RESURVEY: SUBDIVISION LINES, T. 7 N., R. 29 E.

79

Chains	<p>Over mountainous land, thru dense timber and scattering undergrowth. Asc. 53 ft. over steep SE. slope to</p> <p>2.37 Leave mountainous and enter rolling land. Asc. 35 ft. over S. slope.</p> <p>12.20 Point of spur, slopes SE.; desc. 102 ft. over NE. slope to draw.</p> <p>22.00 Enter aspen thicket, bears E. and W.</p> <p>27.20 Leave aspen thicket, bears E. and W. Continue thru dense timber.</p> <p>34.50 Draw, course E., asc. 30 ft. over SE. slope to</p> <p>39.57 Intersect original cor. of secs. 7, 8, 17 and 18, which is a lava stone, 14x12x10 ins. mkd. with 5 notches on E. face and 4 notches on S. face, firmly set in a mound of stone, and witnessed by the two record bearing trees: Reconstruct this cor. monument as follows: remove the mound of stone and the original cor. stone, and in same place set an iron post, 3 ft. long, 2 ins. diam., 27 ins. in the ground and in a mound of stone to top, with the original cor. stone reset alongside, for cor. of secs. 7, 8, 17 and 18, with brass cap mkd.</p> <div style="text-align: center;"> <table border="1"> <tr> <td>T7N</td> <td>R29E</td> </tr> <tr> <td>S7</td> <td>S8</td> </tr> <tr> <td>S18</td> <td>S17</td> </tr> </table> <p>1936</p> <p style="text-align: right;">from which</p> <p>the original bearing trees:</p> <p>A yellow pine, 24 ins. diam. (fallen) brs. S. 75° W., 60 lks. dist. mkd. T7N R29E S18 BT.</p> <p>A yellow pine, 30 ins. diam., brs. N. 30° E., 10 lks. dist., mks. overgrown. Remark T7N R29E S8 BT.</p> <p>and establish additional bearing trees:</p> <p>A yellow pine, 30 ins. diam., brs. S. 74½° E., 78 lks. dist., mkd. T7N R29E S17 BT.</p> <p>A yellow pine, 40 ins. diam., brs. S. 25½° W., 91 lks. dist., mkd. T7N R29E S18 BT.</p> <p>A pinyon, 12 ins. diam., brs. N. 62½° W., 117 lks. dist., mkd. T7N R29E S7 BT.</p> <p>Land, rolling and mountainous. Soil, black loam. gravelly and rocky; 3rd and 4th rates. Timber, pinyon, yellow pine, fir and aspen. Undergrowth, scrub timber and bunch grass.</p> </div>	T7N	R29E	S7	S8	S18	S17
T7N	R29E						
S7	S8						
S18	S17						
3.56	<p>From the cor. of secs. 8, 9, 16 and 17.</p> <p>S. 88° 56' W., on true line, bet. secs. 8 and 17.</p> <p>Over mountainous land, thru dense timber and scattering undergrowth.</p> <p>Asc. 77 ft. over SE. slope.</p> <p>Spur, slopes NE.; desc. 80 ft. over NW. slope.</p>						

## RESURVEY: SUBDIVISION LINES, T. 7 N., R. 29 E.

80

Chains	
6.25	Canyon, course NE., asc. 180 ft. over E. slope to
14.50	W. rim of canyon, brs. NE. and SW. Leave mountainous and enter gently rolling land. Ascend 75 ft. over E. slope to
33.78	(Mid point) Set an iron post, 3 ft. long, 1 in. diam., 20 ins. in the ground to bedrock, and in a mound of stone to top, for $\frac{1}{4}$ sec. cor., with brass cap mkd.  $\frac{1}{4} \begin{array}{l} S 8 \\ S 17 \end{array}$ 1936  from which  A yellow pine, 12 ins. diam., brs. N. $21\frac{1}{2}^{\circ}$ E., 20 lks. dist., mkd. $\frac{1}{4}$ S8 BT.  A yellow pine, 14 ins. diam., brs. S. $39\frac{1}{2}^{\circ}$ W., 68 lks. dist., mkd. $\frac{1}{4}$ S17 BT.  Asc. 30 ft. over NE. slope.
39.66	Low ridge, brs. NW. and SE.; desc. 109 ft. over SW. slope.
63.26	Draw, course SE., asc. 40 ft. over SE. slope to sec. cor.
67.14	Line tree, a yellow pine, 12 ins. diam., mkd. with 2 notches on each of E. and W. faces.
67.56	The cor. of secs. 7, 8, 17 and 18.  Land, mountainous and rolling. Soil, gravelly and rocky, 3rd and 4th rates. Timber, pinyon, yellow pine and aspen. Undergrowth, scrub timber.
	From the cor. of secs. 7, 12, 13 and 18, on W. bdy. of the Tp., hereinbefore described:  East, on true line, bet. secs. 7 and 18 ( $W.\frac{1}{2}$ ).  Over gently rolling land, thru dense timber and scattering undergrowth. Ascend 100 ft. over W. slope.
7.18	Leave timber and undergrowth, and enter open grassy land, brs. N. and S.
16.18	Leave open grassy land and reenter dense timber, brs. N. and S.
25.48	Low ridge, brs. NW. and SE.; desc. 60 ft. over NE. slope to
35.00	Foot of slope brs. NW. and SE. Leave gently rolling and enter nearly level land.
38.50	Leave dense and enter scattering timber, brs. NW. and SE.
39.98	Intersect original $\frac{1}{4}$ sec. cor. of secs. 7 and 18, which is a lava stone, 20x10x4 ins. mkd. $\frac{1}{4}$ on N. face, loosely set in a mound of stone. No accessories. Reconstruct this cor. monument as follows: remove the mound of stone and the original cor. stone and in same place, set an iron post, 3 ft. long, 1 in. diam., 12 ins. in the ground to bedrock, with original cor. stone reset alongside, and in a mound of stone to top, for $\frac{1}{4}$ sec. cor., with brass cap mkd.

## RESURVEY: SUBDIVISION LINES, T. 7 N., R. 29 E.

Chains

 $\frac{1}{4} \frac{S 7}{S 18}$ 

1936

from which

A yellow pine, 36 ins. diam., brs. S.  $67^{\circ}$  W., 112 lks. dist., mkd.  $\frac{1}{4}$  S18 BT.

A yellow pine, 40 ins. diam., brs. N:  $75\frac{3}{4}^{\circ}$  W., 124 lks. dist., mkd.  $\frac{1}{4}$  S7 BT.

Thence

N.  $86^{\circ} 32'$  E., on true line, bet. secs. 7 and 18 (E.  $\frac{1}{2}$ ).

Over nearly level land, thru scattering timber and undergrowth.

- 1.61 Fence ( 4 strand barbed wire) brs. NE. and SW.  
 2.61 Enter dense timber, brs. N. and S.  
 3.11 Center of old log corral, 50 lks. diam., on line.  
 10.31 Leave dense timber, brs. NW. and SE. Continue thru scattering undergrowth.  
 21.81 Wash, 15 lks. wide; 2 ft. deep, course NE. Leave nearly level and enter rolling land. Asc. 76 ft. over NW. slope.  
 22.51 Old road, brs. NE. and SW,  
 23.71 Springerville Highway, brs. NE. and SW. Enter dense timber, brs. N. and S.  
 25.71 Center of reservoir; brs. N. about 15.00 chs. dist. Telephone line, brs. N. and S.  
 29.51 Ridge, brs. NE. and SW.; desc. 86 ft. over SE. slope to  
 39.91 The cor. of secs. 7, 8, 17 and 18.  
 Land, gently rolling, nearly level and rolling.  
 Soil, black loam, gravelly and rocky, 3rd and 4th rates.  
 Timber, pinyon, yellow pine and aspen.  
 Undergrowth, scrub timber.  
 Fair grass.

N.  $0^{\circ} 31'$  E., on true line, bet. secs. 7 and 8.

Over rolling land, thru dense timber and scattering undergrowth.

Asc. 80 ft. over SE. slope to

- 7.40 Desc. 30 ft. over E. slope to  
 11.30 Trail; brs. NW. and SE. Reservoir, brs. W. about 10.00 chs. dist.  
 12.40 Ridge, brs. NE. and SW. Desc. 45 ft. over gradual NW. slope.  
 14.80 Telephone line, brs. NE. and SW.  
 23.50 Springerville Highway, brs. NE. and SW.  
 27.36 Enter mountainous land. Desc. 100 ft. over steep NW. slope to

BOOK 118

## RESURVEY: SUBDIVISION LINES, T. 7 N., R. 29 E.

82

Chains	
34.60	Draw, 15 lks. wide, 1 ft. deep, course NE.; asc. 60 ft. over SE. slope to
38.70	Leave mountainous and enter rolling land. Asc. slightly over SE. slope to
39.06	(Midpoint) Set an iron post, 3 ft. long, 1 in. diam., 18 ins. in the ground to bedrock, and in a mound of stone to top, for $\frac{1}{4}$ sec. cor., with brass cap mkd.
	$\begin{array}{c} \frac{1}{4} \\ S7 \quad   \quad S8 \\ 1936 \end{array}$
	from which
	A pinyon, 14 ins. diam., brs. S. $85\frac{1}{4}^{\circ}$ E., 91 lks. dist., mkd. $\frac{1}{4}$ S8 BT.
	A pinyon, 6 ins. diam., brs. S. $59\frac{1}{2}^{\circ}$ W., 63 lks. dist. mkd. $\frac{1}{4}$ S7 BT.
	Asc. 30 ft. over SE. slope.
45.15	Ridge, brs. NE. and SW. Desc. 39 ft. over NW. and W. slopes.
55.00	Leave timber and undergrowth, brs. NE. and SW. and enter open grassy land.
57.06	E. edge of circular lake, 12.00 chs. diam. on line. Ascend gradually over W. and SW. slopes.
68.06	Leave open grassy land and enter dense timber and scattering undergrowth. Bears E. and W.
71.46	Desc. 57 ft. over NW. slope.
77.26	Draw. course NE.; asc. slightly over SE. slope to
78.12	Point for reestablishment of the sec. cor. determined by double proportion bet. original cors. 1 mile N., E., S. and W., at which point, set an iron post, 3 ft. long, 2 ins. diam., 20 ins. in the ground, for cor. of secs. 5, 6, 7 and 8, with brass cap mkd.
	$\begin{array}{c} T7N \quad R29E \\ S6 \quad   \quad S5 \\ \hline S7 \quad   \quad S8 \\ 1936 \end{array}$
	from which
	A pinyon, 6 ins. diam., brs. N. $49^{\circ}$ E., 57 lks. dist. mkd. T7N R29E S5 BT.
	A yellow pine, 30 ins. diam., brs. S. $65^{\circ}$ E., 67 lks. dist., mkd. T7N R29E S8 BT.
	A yellow pine, 30 ins. diam., brs. S. $59\frac{1}{4}^{\circ}$ W., 21 lks. dist., mkd. T7N R29E S7 BT.
	A pinyon, 12 ins. diam., brs. N. $22\frac{1}{4}^{\circ}$ W., 45 lks. dist., mkd. T7N R29E S6 BT.
	Land, rolling. Soil, black loam, gravelly and rocky, 3rd and 4th rates. Timber, pinyon, yellow pine, aspen and fir. Undergrowth, scrub timber. Fair grass.

## RESURVEY: SUBDIVISION LINES, T. 7 N., R. 29 E.

83

## Chains

From the cor. of secs. 4, 5, 8 and 9.

S. 89° 11' W., on true line, bet. secs. 5 and 8.

Over mountainous land, thru dense timber and scattering undergrowth.

Asc. 320 ft. over SE. slope to

14.68 Ridge, brs. NE. and SW., thence along N. slope descending gradually to

23.18 Desc. 168 ft. over NW. slope to spring branch.

39.34 Set an iron post, 3 ft. long, 1 in. diam., 27 ins. in the ground, for witness cor. to  $\frac{1}{4}$  sec. cor., with brass cap mkd.

W  $\frac{1}{4}$  S 5  
C  $\frac{1}{4}$  S 8

1936

from which

A fir, 24 ins. diam., brs. N. 53 $\frac{1}{2}$ ° E., 88 lks. dist., mkd.  $\frac{1}{4}$  S5 WC BT.

A fir, 24 ins. diam., brs. S. 71 $\frac{1}{2}$ ° W., 18 lks. dist., mkd.  $\frac{1}{4}$  S8 WC BT.

40.64 (Midpoint) True point for  $\frac{1}{4}$  sec. cor. of secs. 5 and 8, falls in Springerville Highway bearing NE. and SW. where it is impracticable to monument the cor., therefore establish witness cor. at 1.30 ch's. N. 89° 11' E. as described above.

42.28 Spring branch, with stream of running water, 2 lks. wide, 1 in. deep, course NE., asc. 404 ft. over SE. slope.

45.38 Springerville Highway, brs. NW. and SE.

51.38 Fence (4 strand barbed wire) brs. SE. and NW.

52.88 Springerville Highway, brs. NE. and SW.

56.08 Spur, slopes NE., desc. 200 ft. over NW. slope.

60.68 Creek, with stream of water, 3 lks. wide, 4 ins. deep, course NE., asc. 150 ft. over E. slope.

69.08 Spur, slopes NE.; desc. 28 ft. over NW. slope.

73.18 Draw, course N. near head. Leave mountainous and enter rolling land. Asc. 40 ft. over E. slope.

77.30 Point of spur, slopes N., desc. 30 ft. over NW. slope.

80.50 Draw, course NE.; asc. slightly over SE. slope to

81.28 The cor. of secs. 5, 6, 7 and 8.

Land, mountainous and rolling.

Soil, rocky black soil, 4th rate.

Timber, fir, pinyon, yellow pine and aspen.

Undergrowth, scrub timber and bunch grass.

From the cor. of secs. 1, 6, 7 and 12, on W. bdy. of the Tp. hereinbefore described.

Chains

N. 88° 59' E., on true line, bet. secs. 6 and 7.

Over mountainous land, thru dense timber and scattering undergrowth.

Desc. 48 ft. over NE. slope.

3.08 Water Canyon Creek, with stream of water, 5 lks. wide, 3 ins. deep, course NNE., asc. 357 ft. over W. slope.

19.08 Ridge, brs. N. and S., desc. 90 ft. over E. slope.

28.38 Creek, with stream of running water 3 lks. wide, 6 ins. deep, course NE.; asc. 64 ft. over NW. slope.

35.88 Spur, slopes N. Leave mountainous and enter rolling land. Desc. 20 ft. over NE. slope to

39.63 (Proportional dist.) Set an iron post, 3 ft. long, 1 in. diam., 27 ins. in the ground, for  $\frac{1}{4}$  sec. cor., with brass cap mkd.

$$\frac{2}{4} \frac{S 6}{S 7}$$

1936

from which

A pinyon, 24 ins. diam., brs. N. 30° E., 99 lks. dist., mkd.  $\frac{1}{4}$  S6 BT.

A yellow pine, 30 ins. diam., brs. South, 86 lks. dist., mkd.  $\frac{1}{4}$  S7 BT.

Desc. 21 ft. over NE. slope.

44.96 Head of draw, course NW.; asc. 45 ft. over NW. slope.

65.40 Ridge, brs. NE. and SW., desc. 75 ft. over SE. slope

74.56 Fence (4 strand barbed wire) brs. N. 20° E. and S. 20° W.

80.36 The cor. of secs. 5, 6, 7 and 8.

Land, mountainous and rolling.  
Soil, gravelly and rocky; 3rd and 4th rates.  
Timber, pinyon, yellow pine, aspen and spruce.  
Undergrowth, scrub timber and bunch grass.

From the cor. of secs. 5, 6, 31 and 32, on N. bdy. of the Tp., hereinbefore described.

S. 1° 40' E., on true line; bet. secs. 5 and 6.

Over rolling land, thru dense timber and scattering undergrowth. Desc. 10 ft. over S. slope.

2.25 Head of drain, course E. Asc. 12 ft. over NE. slope.

4.75 Line tree, a yellow pine, 12 ins. diam., mkd. with 2 notches on each of N. and S. faces.

5.85 Spur slopes E. from NW. Leave rolling and enter mountainous land; desc. 219 ft. over steep S. slope.

14.85 Water Canyon Creek, with stream of running water, 9 lks. wide, 6 ins. deep; course NE.; asc. 200 ft. over steep N. slope to

## RESURVEY: SUBDIVISION LINES, T. 7 N., R. 29 E.

85

Chains

25.00 S. rim of canyon, brs. E. and W. Leave mountainous and enter gently rolling land; asc. 30 ft. over NW. slope.

32.00 Low spur, slopes NE. Desc. 15 ft. over SE. slope.

37.45 Swale, course NE. Asc. 10 ft. over NW. slope to

39.38 (Proportional dist.) Set an iron post, 3 ft. long, 1 in. diam., 27 ins. in the ground, for  $\frac{1}{4}$  sec. cor., with brass cap mkd.

S6.  $\frac{1}{4}$  S5

1936

from which

A fir, 40 ins. diam., brs. S. 50° E., 26 lks. dist., mkd.  $\frac{1}{4}$  S5 BT.

A yellow pine, 10 ins. diam., brs. S. 50 $\frac{1}{2}$ ° W., 64 lks. dist., mkd.  $\frac{1}{4}$  S6 BT.

Asc. 18 ft. over NW. slope to

42.40 Leave gently rolling and enter mountainous land; asc. 447 ft. over steep NW. slope to

62.00 Leave mountainous and enter rolling land; asc. 55 ft. over gradual NW. slope to

69.45 Ridge, brs. NE. and SW.; desc. 28 ft. over SE. slope to

78.45 The cor. of secs. 5, 6, 7 and 8.

Land, rolling, mountainous and gently rolling.  
Soil, gravelly and rocky, 3rd and 4th rates.  
Timber, fir, pinyon, yellow pine and aspen.  
Undergrowth, scrub timber and bunch grass.

The continued satisfactory adjustment of the instruments used in the execution of the resurveys described in the foregoing field notes is indicated from the final tests of same described in the notes of resurvey of T. 6 N., R. 29 E.

This township, situated just north of the divide between the Salt River and the Colorado River, has nearly every variety of surface from nearly level to mountainous. The mountainous surface predominates, several sections being wholly of that character, and all sections having some mountainous land, consisting of ridges, spurs and steep slopes from mesas. About one tenth of the total area is rolling and occurs in scattered areas in all parts of the township. Gently rolling is the character of the surface of about 2000 acres in the valleys and on the mesas in various parts of the township, and about the same total area has a nearly level surface, also in the valleys and on the mesas. The maximum elevation, about 9500 feet above sea level, is in the southwest part, and the minimum about 7500 feet is in the north-east corner.

The soil of this township is of several varieties, rocky 4th rate predominating and being confined mostly to the mountainous areas, gravelly 3rd rate in the rolling land, and a sandy black loam, 1st and 2nd rates in the

## Chains

nearly level and gently rolling surface of the valleys.

Many kinds of timber are prevalent in this township, such as yellow pine, sugar pine, pinyon, fir, spruce and aspen, and occurs in dense and scattering growths, the dense growth predominating, though there are many areas devoid of timber.

The undergrowth consists of scrub varieties of the timber mentioned, and bunch grass. A fair growth of grass covers many of the areas in the valleys where the land is clear of timber and undergrowth.

Colter, Riggs, Benton, Rudd and Milligan Creeks, each carrying a permanent flow of water in normal years, have a general northeasterly course, and drain most of the township. These creeks flow into Nutrioso Creek in the adjoining township on the east, and which creek is a tributary of the Little Colorado River. The northwest part of the township is drained by Water Canyon Creek, also carrying a permanent flow of water, course northerly directly into the Little Colorado River in the adjoining township on the north. There are a number of small lakes and reservoirs in the western part of the township, and springs in the mountainous portions.

About ten or twelve settlers are located in this township, tho a small part of them maintain permanent residence here. They are located mostly in the northern and eastern parts of the township.

The improvements of the settlers consist of houses and outbuildings, corrals, and fences. The U.S. Forest Service has a lookout station on Pats Knoll in section 31, and other improvements in that vicinity such as cabins, corrals and fences and telephone lines extending from the lookout station.

There are no indications of valuable mineral deposits in the township, the main value of the land being for the timber, stockgrazing ranking second, and agricultural crops by cultivation of the soil, third.

A graded road extending northerly to Springerville thru the west half of the township, and secondary roads connecting therewith, forms a means of travel outlet for the western and northern parts of the township. Several secondary roads in the eastern part, connect with U.S. Highway No. 260 in the portion thereof between Alpine and Springerville, extending northerly thru the west half of the adjoining township to the east.

The nearest towns are Nutrioso, Arizona, a post office, situated about one mile east from the southeast corner of the Tp., and Springerville, Arizona, also a post office, located about 7 miles north from the N. bdy. of section 4 of this township. Neither of these towns are railroad stations, both being served by stage service.

This entire township is within the Apache National Forest which Forest lies partly in the State of Arizona, and partly in the State of New Mexico.



68

194

BOOK 4118

# CERTIFICATE OF UNITED STATES SURVEYOR

I, Benjamin J. Mollette, U.S. Transitman, hereby certify upon honor that, in pursuance of <sup>supplemental</sup> special instructions received from the District Cadastral Engineer for Arizona

bearing date of the 31st day of January, 1936, I have well, faithfully, and truly in my own proper person, and in strict conformity with said instructions, the Manual of Surveying Instructions, and the laws of the United States, ~~resurveyed~~ all those parts or portions of

The Subdivision lines of

Township 7 North, Range 29 East of the Gila and Salt River Base and Meridian, in the State of Arizona

which are represented in the foregoing field notes as having been executed by me, and under my direction; and that all the corners of said ~~resurvey~~ <sup>supplemental</sup> have been established and perpetuated in strict accordance with the Manual of Surveying Instructions, and the <sup>supplemental</sup> special written instructions of the District Cadastral Engineer for Arizona

and in the specific manner described in the field notes, and that the foregoing are the original field notes of such ~~resurvey~~. Phoenix Arizona  
April 13, 1937.

*Benjamin J. Mollette*  
U.S. Transitman.

## APPROVAL

OFFICE OF U. S. SUPERVISOR OF SURVEYS,

1937

~~The foregoing field notes of the survey of~~

executed by \_\_\_\_\_, under his special instructions dated \_\_\_\_\_, 19\_\_\_\_, having been critically examined, and the necessary corrections and explanations made, the said field notes, and the surveys they describe, are hereby approved.

U. S. Supervisor of Surveys.

I certify that the foregoing transcript of the field notes of the above described surveys in \_\_\_\_\_, has been correctly copied from the original notes on file in this office.

U. S. Supervisor of Surveys.

4-680  
(August, 1926)

BOOK 433

**FIELD ASSISTANTS.**

To

Roger F. Wilson

U. S. Surveyor

NAMES.	CAPACITY.
William J. Martin	Principal Assistant
Walter Wright	Chainman
Ellis W. Murphy	Flagman
James D. Kappen	Axman
Clark Blevins	Axman
A. C. Terry	Cornerman

196

CERTIFICATE OF UNITED STATES SURVEYOR

I, Roger F. Wilson, U. S. Surveyor, hereby certify upon honor that, in pursuance of supplemental special instructions received from the District Cadastral Engineer for Arizona

bearing date of the 31st day of January, 1936, I have well, faithfully, and truly

in my own proper person, and in strict conformity with said instructions, the Manual of Surveying Instructions, and the laws of the United States, resurveyed all those parts or portions of

the West Boundary and

the North Boundary of

Township 7 North, Range 29 East of the Gila and Salt

River Base and Meridian, in the State of Arizona, which are represented in

the foregoing field notes as having been executed by me, and under my direction; and that all the corners of said resurvey have been established and perpetuated in strict accordance with the Manual of Surveying Instruc-

tions, and the supplemental special written instructions of the District Cadastral Engineer for Arizona

and in the specific manner described in the field notes, and that the foregoing are the original field notes of such resurvey.

Phoenix, Arizona
April 29, 1937

Roger F. Wilson
U. S. Surveyor.

APPROVAL

OFFICE OF U. S. SUPERVISOR OF SURVEYS,

Denver, Colorado, October 2, 1937.

The foregoing field notes of the resurvey of

West Boundary,

North Boundary and

Subdivision Lines

of

Township 7 North, Range 29 East

of the Gila and Salt River Base and Meridian, State of Arizona

executed by Roger F. Wilson, U.S. Surveyor, Benjamin J. Mollette and Robert H. Fischer, U.S. Transitmen.

under supplemental special instructions dated January 31, 1936 for Gp. 192, Arizona, having been critically examined, and the necessary corrections and explanations made, the said field notes, and the resurveys they describe, are hereby approved.

U. S. Supervisor of Surveys.

I certify that the foregoing transcript of the field notes of the above described surveys in

has been correctly copied from the original notes on file in this office.

U. S. Supervisor of Surveys.

191  
91

FORM 4112

4-680  
(August, 1926)

**FIELD ASSISTANTS.**

Robert H. Fischer

To

U. S. Transitman

NAMES.	CAPACITY.
H. R. Ruddell	Principal Assistant
Buel Samuel	Chairman
Harold E. Grimes	Axman
Fred Wright	Axman
Robert G. Burns	Cornerman
G.B.Ruiz	Flagman

192  
BOOK 4118

CERTIFICATE OF UNITED STATES SURVEYOR

I, Robert H. Fischer, U.S. Transitman, hereby certify upon honor that, in pursuance of <sup>supplemental</sup> special instructions received from the District Cadastral Engineer for Arizona bearing date of the 31st day of January, 1936, I have well, faithfully, and truly in my own proper person, and in strict conformity with said instructions, the Manual of Surveying Instructions, and the laws of the United States, ~~resurveyed~~ all those parts or portions of

the subdivision lines of

Township 7 North, Range 29 East of the Gila and Salt River Base and Meridian, in the State of Arizona, which are represented in the foregoing field notes as having been executed by me, and under my direction; and that all the corners of said ~~resurvey~~ have been established and perpetuated in strict accordance with the Manual of Surveying Instructions, and the <sup>supplemental</sup> special written instructions of the District Cadastral Engineer for Arizona and in the specific manner described in the field notes, and that the foregoing are the original field notes of such ~~resurvey~~.

*Robert H. Fischer*  
U.S. Transitman  
*Miami Arizona*  
April 8, 1937.

APPROVAL

OFFICE OF U. S. SUPERVISOR OF SURVEYS,

The foregoing field notes of the survey of

executed by

under his special instructions dated \_\_\_\_\_, 19\_\_\_\_, having been critically examined, and the necessary corrections and explanations made, the said field notes, and the surveys they describe, are hereby approved.

U. S. Supervisor of Surveys.

I certify that the foregoing transcript of the field notes of the above-described surveys in \_\_\_\_\_, has been correctly copied from the original notes on file in this office.

U. S. Supervisor of Surveys.