

4-679
(April 1933)

BOOK 4180

Book J.

FIELD NOTES

4180

of the

Dependent resurvey of the subdivisional lines

of

Township 9 North, Range 26 East,

Of the Gila and Salt River Meridian,

In the State of Arizona

EXECUTED BY

Roger F. Wilson, Surveyor.

F. Wayne Forrest, Public Land Surveyor

Elliott Pearson, Transitman

General Land Office

Under special instructions dated January 28, 1937, which provided for the surveys included under Group No. 192, bearing the approval of the Commissioner of the General Land Office under date of February 18, 1937, and assignment instructions dated June 11 and 21, 1937.

Survey commenced June 13, 1937.

Survey completed July 7, 1937.

4180

(1A)

BOOK 4180

INDEX DIAGRAM.

Township 9 North, Range 26 East

| | | | | | |
|----------|-------------|-------------|-------------|-------------|------------|
| 6 63 | 64 5 62 | 48 4 47 | 36 3 35 | 25 2 24 | 12 1 12 |
| 7 60 | 61 8 59 | 46 9 46 | 34 19 33 | 22 11 21 | 10 12 9 |
| 18 57 | 58 17 56 | 44 16 43 | 32 15 31 | 20 14 19 | 8 13 7 |
| 19 54 | 55 20 53 | 42 21 41 | 30 22 29 | 18 23 17 | 6 24 5 |
| 30 51 | 52 29 51 | 39 28 38 | 28 27 27 | 15 26 15 | 4 25 3 |
| 31 | 49 32 | 37 33 | 26 34 | 13 35 | 1 36 |

1B

Resurvey of the Subdivisions of T. 9 N., R. 26 E.

Chains

The resurveys herein described were executed with Buff and Buff solar transits Nos. 23,829 and 18,002, and Young and Sons solar transit No. 8541. The instruments comply with the standard specifications of the General Land Office and were placed in satisfactory adjustment prior to the beginning of the survey, and were approved by the district cadastral engineer on June 11, 1937.

The direction of the lines were determined by the solar transit method. The measurements were made with Lufkin steel tapes, 5 chs. in length, graduated every link for the first 100 lks. and the balance at intervals of 10 lks.. The tapes were tested by comparison with a Lufkin standard and found correct. The measurements were made on the slope and the vertical angle of each interval was ascertained with a clinometer in good adjustment; the horizontal equivalents are entered in the field note record.

The data furnished with the special instructions gives the geographic position for the SE. cor. of T. 9 N., R. 26 E., as follows: latitude $34^{\circ} 07'$ N., and longitude $109^{\circ} 31' 30''$ W.

The establishment of a meridian by polaris observation in camp in the SE. $\frac{1}{4}$ of sec. 15, T. 9 N., R. 26 E., is given in the field notes of the boundaries of T. 9 N., R. 26 E., resurveyed under this group.

June 13, 1937, every 30 min. from 7 to 10:30 a.m. and 1:30 to 5 p.m. the proper settings were made on the arcs of the solar attachments. The resulting orientation of the instruments, when compared with the meridian established by Polaris observation, had a maximum error of less than $1' 30''$.

The tests of the arcs were repeated daily by noon observations, and the meridional indications were verified at frequent intervals throughout the survey.

Resurvey of the Subdivisions of T. 9 N., R. 26 E.

The subdivisions of T. 9 N., R. 26 E. were surveyed by A. P. Johnson, Deputy Surveyor, in 1882. No resurveys are of record. The following field notes are a record of a dependent resurvey. All lines were run random and true, but the true lines only are reported in the following field notes. All of the original section cors. were found, and all of the missing $\frac{1}{4}$ sec. cors. were reestablished by the method of single proportional measurement.

Beginning at the standard cor. of secs. 35 and 36, on the S. bdy. of the Tp., which is an iron post, 2 ins. diam., 8 ins. above ground, mkd., set and witnessed as described in the official record.

N. $4^{\circ} 00'$ E., on true line bet. secs. 35 and 36.

Desc. 160 ft. over a gentle NW. slope, thru timber.

DORR

Resurvey of the Subdivisions of T. 9 N., R. 26 E.

Chains

40.59

Proportional distance:

Set an iron post, 3 ft. long, 1 in. diam., 28 ins. in the ground, for $\frac{1}{4}$ sec. cor., with brass cap mkd.

$$\begin{array}{c} \frac{1}{4} \\ \hline S\ 35 \mid S\ 36 \end{array}$$

1937

from which

A yellow pine, 8 ins. diam., bears S. 33° E., 34 lks. dist., mkd. $\frac{1}{4}$ S 36 B T.

A yellow pine, 12 ins. diam., bears N. $37\frac{1}{2}^{\circ}$ W., 50 lks. dist., mkd. $\frac{1}{4}$ S 35 B T.

45.70

Desc. 30 ft. over a NW. slope.

47.94

4 strand barbed wire fence, bears NE. and SW.

49.93

One wire telephone line, bears NE. and SW.

51.70

Slope changes to NE., desc. 37 ft.

54.50

Slope changes to NW., desc. 73 ft.

69.20

Draw, 4 chs. wide, asc. 40 ft. over a gentle SE. slope.

81.18

The cor. of secs. 25, 26, 35 and 36, which is a lava stone, 18x10x6 ins., set in a mound of stone, 3 ft. base, 1 ft. high, mkd. with 1 notch on the S. face.

At point for cor.

Set an iron post, 3 ft. long, 2 ins. diam., 28 ins. in the ground, with the original stone set alongside, for cor. of secs. 25, 26, 35 and 36, with brass cap mkd.

$$\begin{array}{c} T9N\ R26E \\ S\ 26 \mid S\ 25 \\ \hline S\ 35 \mid S\ 36 \\ 1937 \end{array}$$

from which

Original bearing trees:

A yellow pine stump, 22 ins. diam., bears N. 16° E., 87 lks. dist., mkd. T 9 N R 26 E S 25 B T.

A yellow pine, 18 ins. diam., dead and fallen, bears S. 43° E., 37 lks. dist., mkd. T 9 N R 26 E S 36 B T.

A yellow pine stump, 18 ins. diam., bears S. $49\frac{1}{2}^{\circ}$ W., 16 lks. dist., mkd. T 9 N R 26 E S 35 B T.

A yellow pine stump, 18 ins. diam., bears N. $59\frac{1}{2}^{\circ}$ W., 7 lks. dist., mkd. T 9 N R 26 E S 26 B T.

New bearing trees:

A yellow pine, 12 ins. diam., bears N. 60° E., 133 lks. dist., mkd. T 9 N R 26 E S 25 B T.

Resurvey of the Subdivisions of T. 9 N., R. 26 E.

Chains

A yellow pine, 10 ins. diam., bears S. $20\frac{1}{2}^{\circ}$ E.,
128 lks. dist., mkd. T 9 N R 26 E S 36 B T.

A yellow pine, 24 ins. diam., bears S. $75\frac{3}{4}^{\circ}$ W., 112
lks. dist., mkd. T 9 N R 26 E S 35 B T.

A yellow pine, 18 ins. diam., bears N. $12\frac{1}{4}^{\circ}$ W.,
130 lks. dist., mkd. T 9 N R 26 E S 26 B T.

Land, rolling and hilly.

Soil, lava rock over sandy loam, 3d rate.

Timber, yellow pine and aspen; undergrowth, none.

From the cor. of secs. 25, 30, 31 and 36 on the E. bdy.
of the Tp., described in the field notes of the E. Bdy.
of T. 9 N., R. 26 E., resurveyed under this group.

N. $88^{\circ} 03'$ W., on true line bet. secs. 25 and 36.

Asc. 47 ft. over a NE. slope thru timber.

1.90 Steep, rocky spur, slopes N.

5.05 Thence along a N. slope.

8.05 Asc. 64 ft. over a NE. slope.

12.00 Short spur, slopes N., desc. 56 ft. over a NW. slope.

15.15 Slope changes to NE.; asc. 192 ft.

28.50 Ridge, bears NW. and SE.; desc. slightly along a NW.
slope.

37.48 Proportional distance:

Set an iron post, 3 ft. long, 1 in. diam., 22 ins. in
the ground to underlying rock, and in a mound of stone
to top, for $\frac{1}{4}$ sec. cor., with brass cap mkd.

$$\begin{array}{r} S 25 \\ \frac{1}{4} S 36 \\ \hline 1937 \end{array}$$

from which

A yellow pine, 12 ins. diam., bears N. 64° E.,
8 lks. dist., mkd. $\frac{1}{4}$ S 25 B T.

A yellow pine, 12 ins. diam., bears S. $26\frac{1}{2}^{\circ}$ E.,
115 lks. dist., mkd. $\frac{1}{4}$ S 36 B T.

Desc. 60 ft. over a NW. slope.

37.68 4 strand barbed wire fence, bears N. 35° E. and S. 35° W.

42.25 Slope becomes more steep.

48.00 Side hill wash, 4 ft. wide, 1 ft. deep, course N. 15° W.;
desc. 46 ft. over a broken NW. slope.

54.60 Side hill ravine, 5 ft. wide, course N.; continue along
a broken N. slope.

54.75 Spur, slopes NW.; desc. 44 ft. over a NW. slope.

Resurvey of the Subdivisions of T. 9 N., R. 26 E.

Chains

62.20 Boulder strewn draw, 1 ch. wide, course N.; asc. 146 ft. over a NE. slope.

67.15 Top of a rocky bluff, 85 ft. high, facing E.; thence over rolling land.

74.96 The cor. of secs. 25, 26, 35 and 36.

Land, rolling mountainous.

Soil, rocky over sandy loam, 3d rate.

Timber, aspen, fir, spruce and yellow pine; undergrowth, none.

N. 0° 36' W., on true line bet. secs. 25 and 26.

Over top of a broad ridge, thru timber.

6.10 Leave ridge and desc. 28 ft. over a NE. slope.

25.10 Short spur, slopes N. 70° E.; desc. 160 ft. over a NE. slope.

30.10 Thence over rolling land.

40.13 The $\frac{1}{4}$ sec. cor., which is a lava stone, 14x8x7 ins., set in a mound of stone, 3 ft. base, 1 ft. high, no markings legible.

At point for cor.

Set an iron post, 3 ft. long, 1 in. diam., 28 ins. in the ground, with the original stone set alongside, for $\frac{1}{4}$ sec. cor., with brass cap mkd.

$$\begin{array}{c} \frac{1}{4} \\ \text{S } 26 \text{ | } \text{S } 25 \\ 1937 \end{array}$$

from which

Original bearing trees:

A yellow pine, 30 ins. diam., bears S. 65 $\frac{1}{2}$ ° E., 14 lks. dist., mkd. $\frac{1}{4}$ S B T.

A yellow pine, 24 ins. diam., bears S. 76 $\frac{1}{4}$ ° W., 76 lks. dist., mkd. $\frac{1}{4}$ S B T.

N. 0° 44' W., on true line bet. secs. 25 and 26.

Over nearly level land thru timber.

12.15 Desc. 30 ft. over a N. slope.

14.00 Thence over nearly level land.

38.30 Old road, winding E. and W.

40.45 The cor. of secs. 23, 24, 25 and 26, which is a lava stone, 16x8x6 ins., set in a mound of stone, 3 ft. base, 1 ft. high, no legible markings.

At point for cor.

Resurvey of the Subdivisions of T. 9 N., R. 26 E.

Chains

Set an iron post, 3 ft. long, 2 ins. diam., 20 ins. in the ground to underlying rock, and in a mound of stone, 5 ft. base, 16 ins. high, with the original stone set alongside, for cor. of secs. 23, 24, 25 and 26, with brass cap mkd.

| | |
|------|------|
| T9N | R26E |
| S 23 | S 24 |
| S 26 | S 25 |
| 1937 | |

from which

Original bearing trees:

A yellow pine, 16 ins. diam., bears N. $0\frac{1}{4}^{\circ}$ E.,
32 lks. dist., mkd. T 9 N R 26 E S 23 B T.

A yellow pine, 16 ins. diam., bears N. 76° E.,
57 lks. dist., mkd. T 9 N R 26 E S 24 B T.

A yellow pine, 10 ins. diam., bears S. $64\frac{1}{2}^{\circ}$ E.,
42 lks. dist., mkd. T 9 N R 26 E S 25 B T.

A yellow pine, 20 ins. diam., bears S. $83\frac{1}{2}^{\circ}$ W.,
36 lks. dist., mkd. T 9 N R 26 E S 26 B T.

New bearing trees:

A yellow pine, 10 ins. diam., bears N. $19\frac{1}{4}^{\circ}$ E.,
77 lks. dist., mkd. T 9 N R 26 E S 24 B T.

A yellow pine, 20 ins. diam., bears S. 58° E.,
110 lks. dist., mkd. T 9 N R 26 E S 25 B T.

A yellow pine, 16 ins. diam., bears N. $53\frac{1}{4}^{\circ}$ W.,
90 lks. dist., mkd. T 9 N R 26 E S 23 B T.

Land, rolling and hilly.

Soil, rocky over sandy loam, 3d rate.

Timber, yellow pine and aspen; undergrowth, none.

From the cor. of secs. 19, 24, 25 and 30, on the E. bdy. of the Tp., described in the field notes of the E. bdy. of T. 9 N., R. 26 E., resurveyed under this group.

N. $88^{\circ} 05'$ W., on true line bet. secs. 24 and 25.

Asc. 48 ft. over a rolling SE. slope.

23.30 Dim road, bears N. and winding SE.

26.90 Shallow wash, 5 ft. wide, course N. 80° E.

27.60 Same road, bears N. 80° E. and S. 80° W.

38.31 Proportional distance:

Set an iron post, 3 ft. long, 1 in. diam., 18 ins. in the ground to underlying rock, and in a mound of stone, 4 ft. base, $1\frac{1}{2}$ ft. high, for $\frac{1}{4}$ sec. cor., with brass cap mkd.

Resurvey of the Subdivisions of T. 9 N., R. 26 E.

Chains

| | |
|-------|--------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| | $\frac{1}{4} \begin{array}{l} S 24 \\ \hline S 25 \\ 1937 \end{array}$ <p style="text-align: right;">from which</p> <p>A yellow pine, 18 ins. diam., bears N. $6\frac{1}{2}^{\circ}$ W., 50 lks. dist., mkd. $\frac{1}{4}$ S 24 B T.</p> <p>A yellow pine, 24 ins. diam., bears S. 21° W., 99 lks. dist., mkd. $\frac{1}{4}$ S 25 B T.</p> <p>Asc. 15 ft. over a SE. slope.</p> |
| 48.60 | Slope changes to E., asc. 74 ft. |
| 56.60 | Slope changes to rolling SE.; asc. 18 ft. |
| 76.62 | The cor. of secs. 23, 24, 25 and 26. |
| | <p>Land, rolling hills. Soil, gravelly and rocky over sandy loam, 3d rate. Timber, 1st and 2nd growth yellow pine; undergrowth, none.</p> |
| | <p>N. $4^{\circ} 12'$ W., on true line bet. secs. 23 and 24. Over rolling, rocky land, thru timber.</p> |
| 5.00 | Asc. 54 ft. over a rocky SW. slope. |
| 12.75 | Low, rocky ridge, bears E. and W.; desc. 32 ft. over a NE. slope. |
| 18.85 | Head of draw, 1 ch. wide, course E.; asc. 15 ft. over a S. slope. |
| 21.80 | Broad, low ridge, bears E. and W., continue across same. |
| 26.80 | Leave ridge and desc. 30 ft. over a NE. slope. |
| 34.00 | Traveled road, bears NE. and SW. |
| 38.87 | Proportional distance: |
| | <p>Set an iron post, 3 ft. long, 1 in. diam., 24 ins. in the ground, for $\frac{1}{4}$ sec. cor., with brass cap mkd.</p> $\frac{1}{4} \begin{array}{l} S 23 S 24 \\ \hline 1937 \end{array}$ <p style="text-align: right;">from which</p> <p>A yellow pine, 14 ins. diam., bears N. $81\frac{1}{2}^{\circ}$ E., 65 lks. dist., mkd. $\frac{1}{4}$ S 24 B T.</p> <p>A yellow pine, 12 ins. diam., bears S. $89\frac{1}{2}^{\circ}$ W., 100 lks. dist., mkd. $\frac{1}{4}$ S 23 B T.</p> |
| | Desc. 185 ft. over a rolling NE. slope. |
| 77.74 | The point for the cor. of secs. 13, 14, 23 and 24, as determined from the original bearing trees. |
| | At point for cor. |

Resurvey of the Subdivisions of T. 9 N., R. 26 E.

Chains

Set an iron post, 3 ft. long, 2 ins. diam., 27 ins. in the ground, for cor. of secs. 13, 14, 23 and 24, with brass cap mkd.

| | |
|------|------|
| T9N | R26E |
| S 14 | S 13 |
| S 23 | S 24 |
| 1937 | |

from which

Original bearing trees:

A yellow pine, 16 ins. diam., bears N. $66\frac{1}{2}^{\circ}$ E., 59 lks. dist., mkd. T 9 N R 26 E S 13 B T.

A yellow pine stump, 30 ins. diam., bears S. $28\frac{1}{2}^{\circ}$ E., 54 lks. dist., mkd. T 9 N R 26 E S 24 B T.

A yellow pine, 16 ins. diam., bears S. 31° W., 177 lks. dist., mkd. T 9 N R 26 E S 23 B T.

A yellow pine, 16 ins. diam., bears N. 47° W., 124 lks. dist., markings overgrown, I remark this tree T 9 N R 26 E S 14 B T.

A new bearing tree:

A yellow pine, 20 ins. diam., bears S. $48\frac{1}{2}^{\circ}$ E., 169 lks. dist., mkd. T 9 N R 26 E S 24 B T.

Land, rolling.

Soil, rocky over sandy loam, 3d rate.

Timber, 1st and 2nd growth yellow pine and scattering aspen; undergrowth, none.

From the cor. of secs. 13, 18, 19 and 24, on the E. bdy. of the Tp., described in the field notes of the E. bdy. of T. 9 N., R. 26 E., resurveyed under this group.

S. $89^{\circ} 38'$ W., on true line bet. secs. 13 and 24.

Desc. slightly over a NW. slope, thru timber.

0.58 4 strand barbed wire fence, bears N. and S.

2.10 Shallow draw, 1 ch. wide, course NE.; asc. 292 ft. over an E. slope.

34.00 Slope changes to SE., continue ascent.

40.21 The $\frac{1}{4}$ sec. cor., which is a lava stone, 8x8x8 ins. above ground, mkd. $\frac{1}{4}$ on N. face.

At point for cor.

Set an iron post, 3 ft. long, 1 in. diam., 27 ins. in the ground, with the original stone set alongside, for $\frac{1}{4}$ sec. cor., with brass cap mkd.

S 13

S 24

1937

from which

Resurvey of the Subdivisions of T. 9 N., R. 26 E.

Chains

Original bearing trees:

A yellow pine, 14 ins. diam., now dead, bears N. $0\frac{3}{4}^{\circ}$ E.,
21 lks. dist., mkd. $\frac{1}{4}$ S 13 B T.

A yellow pine, 22 ins. diam., bears S. 28° E., 110
lks. dist., markings overgrown, I remark this tree
 $\frac{1}{4}$ S 24 B T.

A new bearing tree:

A yellow pine, 14 ins. diam., bears N. $2\frac{1}{4}^{\circ}$ W.,
125 lks. dist., mkd. $\frac{1}{4}$ S 13 B T.

S. $89^{\circ} 57'$ W., on true line bet. secs. 13 and 24.

Asc. 144 ft. over a SE. slope.

8.10 Ridge, bears N. 25° E. and S.; desc. 188 ft. over a NW.
slope.

22.90 Draw, 50 lks. wide, course SW.; desc. 39 ft. over a SW.
slope.

31.10 Head of draw, 1 ch. wide, course N.; asc. 34 ft. over a
rocky NE. slope.

34.40 Spur, slopes NW.; desc. 12 ft. over a W. slope.

39.88 The cor. of secs. 13, 14, 23 and 24.

Land, rolling mountainous.

Soil, gravelly to rocky over sandy loam, 3d rate.

Timber, 1st and 2nd growth yellow pine, and scattering
aspens; undergrowth, none.

N. $5^{\circ} 26'$ W., on true line bet. secs. 13 and 14.

Desc. 150 ft. along a gentle NE. slope, thru timber.

4.00 Forest service work road, bears NE. and SW.

14.00 Same road, bears NW. and SE.

28.60 New forest service road at curve, bears NE. and NW.

40.68 The $\frac{1}{4}$ sec. cor., which is a lava stone, 10x10x4 ins.
above ground, mkd. $\frac{1}{4}$ on W.

At point for cor.

Set an iron post, 3 ft. long, 1 in. diam., 27 ins. in
the ground, with the original stone set alongside, for
 $\frac{1}{4}$ sec. cor., with brass cap mkd.

$\frac{1}{4}$
S 14 | S 13
1937

from which

Original bearing trees:

Resurvey of the Subdivisions of T. 9 N., R. 26 E.

Chains

A yellow pine, 22 ins. diam., bears S. $85\frac{3}{4}^{\circ}$ E., 95 lks. dist., markings overgrown, I remark this tree $\frac{1}{2}$ S 13 B T.

A yellow pine, 14 ins. diam., bears S. $81\frac{1}{2}^{\circ}$ W., 89 lks. dist., markings overgrown, I remark this tree $\frac{1}{2}$ S 14 B T.

N. $0^{\circ} 22'$ W., on true line bet. secs. 13 and 14.

Continue over nearly level land, thru timber.

5.00 Desc. 63 ft. over a NE. slope.

20.00 Slope changes to E., continue along same.

25.00 Low, rocky ridge, bears E. and W.; desc. 73 ft. over a N. slope.

34.00 Draw, 50 lks. wide, course N. 75° E.; asc. 32 ft. over a SE. slope.

40.34 The cor. of secs. 11, 12, 13 and 14, which is a lava stone, 10x10x6 ins. above ground, mkd. with 4 notches on the S. face and 1 notch on the E. face.

At point for cor.

Set an iron post, 3 ft. long, 2 ins. diam., 28 ins. in the ground, with the original stone set alongside, for cor. of secs. 11, 12, 13 and 14, with brass cap mkd.

| | |
|------------|------|
| T9N. R26E. | |
| S 11 | S 12 |
| S 14 | S 13 |
| 1937 | |

from which

A yellow pine, 6 ins. diam., bears N. 40° E., 40 lks. dist., mkd. S 12 B T.

A yellow pine, 6 ins. diam., bears S. $47\frac{3}{4}^{\circ}$ E., 11 lks. dist., mkd. S 13 B T.

A yellow pine, 6 ins. diam., bears S. $81\frac{1}{2}^{\circ}$ W., 18 lks. dist., mkd. S 14 B T.

A yellow pine, 6 ins. diam., bears N. $66\frac{3}{4}^{\circ}$ W., 107 lks. dist., mkd. S 11 B T.

A yellow pine, 4 ins. diam., bears N. 58° W., 26 lks. dist., mkd. T 9 N R 26 E S 11 B T.

Land, rolling hills.

Soil, gravelly over sandy loam, 3d rate.

Timber, 1st and 2nd growth yellow pine; undergrowth, none.

From the cor. of secs. 7, 12, 13 and 18, on the E. bdy. of the Tp., described in the field notes of the E. bdy. of T. 9 N., R. 26 E., resurveyed under this group.

N. $89^{\circ} 52'$ W., on true line bet. secs. 12 and 13.

Over rolling land, on bench which bears N. and S.

Resurvey of the Subdivisions of T. 9 N., R. 26 E.

| Chains | |
|--------|--------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| 30.00 | Leave bench and desc. 18 ft. over a W. slope. |
| 35.00 | Wash 15 lks. wide, course N. |
| 38.00 | New forest service road, bears N. 20° E. and S. 20° W.; enter scattering timber. |
| 42.05 | The $\frac{1}{4}$ sec. cor., which is a lava stone, 16x12x10 ins., set in a mound of stone, 3 ft. base, 1 ft. high, mkd. $\frac{1}{4}$ on N. face. |
| | At point for cor. |
| | Set an iron post, 3 ft. long, 1 in. diam., 20 ins. in the ground to underlying rock, and in a mound of stone to top; with the original stone set alongside, for $\frac{1}{4}$ sec. cor., with brass cap mkd. |
| | $\frac{1}{4} \begin{array}{r} S 12 \\ \hline S 13 \\ 1937 \end{array}$ |
| | from which |
| | An original bearing tree: |
| | A yellow pine, 16 ins. diam., now dead and broken, bears N. 80 $\frac{1}{4}$ ° E., 149 lks. dist., markings overgrown; this bearing tree is not of record. |
| | New bearing trees: |
| | A yellow pine fork, 20 ins. diam., bears N. 79 $\frac{1}{4}$ ° E., 152 lks. dist., mkd. $\frac{1}{4}$ S 12 B T. |
| | A yellow pine, 6 ins. diam., bears S. 43° W., 124 lks. dist., mkd. $\frac{1}{4}$ S 13 B T. |
| | Over benchland thru timber. |
| 52.05 | Leave bench and desc. slightly over a SW. slope, timber becomes more dense. |
| 54.85 | Head of rocky wash, 30 ft. wide, 20 ft. deep, course NE.; asc. 117 ft. over a SE. slope. |
| 67.05 | Slope changes to NE., continue ascent. |
| 75.65 | Broad ridge, bears NE. and S.; desc. slightly over a SW. slope. |
| 82.41 | The cor. of secs. 11, 12, 13 and 14. |
| | Land, rolling hills. Soil, gravelly and rocky over sandy loam, 3d rate. Timber, 1st and 2nd growth yellow pine; undergrowth, none. |
| | N. 0° 26' W., on true line bet. secs. 11 and 12. |
| | Asc. 82 ft. over a broken SE. slope, thru timber. |
| 16.00 | Leave timber, bears E. and W. |
| 29.95 | Spurs, slope NW, and NE., from ridge which bears SW.; desc. 128 ft. over a NE. slope. |
| 32.45 | Enter scattering timber. |

Resurvey of the Subdivisions of T. 9 N., R. 26 E.

Chains

- 39.50 Short, rocky spur, slopes NE.; desc. slightly over a N. slope.
- 40.62 The $\frac{1}{4}$ sec. cor., which is a lava stone, 12x12x6 ins., set in a small mound of stone, mkd. $\frac{1}{4}$ on W. face.
- At point for cor.
- Set an iron post, 3 ft. long, 1 in. diam., 26 ins. in the ground, and in a mound of stone to top, with the original stone set alongside, for $\frac{1}{4}$ sec. cor., with brass cap mkd.
- | |
|---------------|
| $\frac{1}{4}$ |
| S 11 S 12 |
| 1937 |
- from which.
- A yellow pine, 6 ins. diam., bears S. $2\frac{3}{4}^{\circ}$ E., 430 lks. dist., mkd. $\frac{1}{4}$ S 12 B T.
- A yellow pine, 16 ins. diam., bears N. 79° W., 443 lks. dist., mkd. $\frac{1}{4}$ S 11 B T.
- N. $0^{\circ} 46'$ W., on true line bet. secs. 11 and 12.
- Desc. 233 ft. over a N. slope, thru scattering timber.
- 10.10 Side hill ravine, 6 ft. wide, course NE.; continue along an E. slope.
- 32.10 Low, short spur, slopes NE.; desc. 74 ft. over a NE. slope.
- 40.00 The cor. of secs. 1, 2, 11 and 12, which is a lava stone, 14x14x6 ins. above ground, in a small mound of stone.
- At point for cor.
- Set an iron post, 3 ft long, 2 ins. diam., 10 ins. in the ground to underlying rock, and in a mound of stone, 5 ft. base, 26 ins. high, with the original stone set alongside, for cor. of secs. 1, 2, 11 and 12, with brass cap mkd.
- | | |
|-------------|------|
| T9N | R26E |
| S 2 S 1 | |
| S 11 S 12 | |
| 1937 | |
- from which
- A juniper, 4 ins. diam., bears N. 74° E., 103 lks. dist., mkd. S 1 B T.
- A juniper fork, 8 ins. diam., bears S. $58\frac{1}{2}^{\circ}$ E., 168 lks. dist., mkd. S 12 B T.
- A juniper fork, 5 ins. diam., bears S. $27\frac{1}{4}^{\circ}$ W., 137 lks. dist., mkd. S 11 B T.
- A juniper fork, 6 ins. diam., bears N. 87° W., 243 lks. dist., mkd. S. 2 B T.
- Land, rolling mountainous.
Soil, gravelly and rocky over sandy loam, 3d rate.
Timber, yellow pine and juniper; undergrowth, none.

Resurvey of the Subdivisions of T. 9 N., R. 26 E.

| Chains | |
|--------|---------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| | From the cor. of secs. 1, 6, 7 and 12, on the E. bdy. of the Tp., described in the field notes of the E. bdy. of T. 9 N., R. 26 E., resurveyed under this group. |
| | N. 89° 46' W., on true line bet. secs. 1 and 12. |
| | Desc. 46 ft. over a SW. slope, thru timber. |
| 0.94 | New barbed wire fence, bears N. and S. |
| 2.57 | Old barbed wire fence, bears N. and S. |
| 7.50 | Small draw, course NW.; asc. 98 ft. over a NE. slope. |
| 24.50 | Broad spur, slopes N.; desc. 96 ft. over a NW. slope. |
| 36.30 | Wash, 15 ft. wide, course N. 10° E.; asc. 44 ft. over an E. slope. |
| 39.50 | Broad spur, slopes N. 15° E.; desc. slightly. |
| 40.76 | Proportional distance: Set an iron post, 3 ft. long, 1 in. diam., 26 ins. in the ground and in a mound of stone to top, for $\frac{1}{4}$ sec. cor., with brass cap mkd. |
| | $\frac{\frac{1}{4} \text{ S } 1}{\text{S } 12}$ 1937 |
| | from which |
| | A juniper, 8 ins. diam., bears N. 79 $\frac{1}{2}$ ° E., 166 lks. dist., mkd. $\frac{1}{4}$ S 1 B T. |
| | A yellow pine, 12 ins. diam., bears S. 27 $\frac{3}{4}$ ° E., 490 lks. dist., mkd. $\frac{1}{4}$ S 12 B T. |
| 41.10 | Graded road, bears N. 15° E. to Springerville and S. 15° W. to Greens' Peak. |
| 52.80 | Desc. 92 ft. over a NW. slope. |
| 56.10 | Traveled road, bears NW. and SE. |
| 72.04 | Wash, 25 ft. wide, course N. 30° W.; asc. 15 ft. over a NE. slope. |
| 74.90 | Dim road, bears NW. and SE. |
| 81.52 | The cor. of secs. 1, 2, 11 and 12. Land, rolling hills. Soil, sandy loam and rocky, 3d rate. Timber, scattering yellow pine and juniper; undergrowth, none. |
| | N. 0° 02' E., on true line bet. secs. 1 and 2. |
| | Desc. 31 ft. over a NE. slope, thru scattering timber. |
| 8.50 | Rocky wash, 10 ft. wide, 2 ft. deep, course N. 60° E.; asc. 90 ft. over a SE. slope, leave timber. |
| 22.00 | Slope changes to W.; continue over broad bench, bears NE. and SW. |

Resurvey of the Subdivisions of T. 9 N., R. 26 E.

Chains

- 40.66 Proportional distance:
Set an iron post, 3 ft. long, 1 in. diam., 27 ins. in the ground, for $\frac{1}{4}$ sec. cor., with brass cap mkd.
- $\frac{1}{4}$
 S 2 | S 1
 1937
- raise a mound of stone, 3 ft. base, 1 ft. high, W. of cor.
- From this cor., the Mallory Spring bears S. 89° 50' W., 31.00 chs. dist., a spring of good water enclosed in a wooden box, 6 ft. diam., 6 ft. deep.
- 41.80 Traveled road, bears E. and W.
- 51.00 Wash, 12 ft. wide, 1 ft. deep, course NE.; asc. 53 ft. over a SE. slope.
- 55.00 Enter very scattering timber.
- 64.15 Top of broad bench, bears NE. and SW.; continue across same; leave timber.
- 80.71 The cor. of secs. 1, 2, 35 and 36, on the N. bdy. of the Tp., described in the field notes of the N. bdy. of T. 9 N., R. 26 E., resurveyed under this group.
- Land, rolling hills.
Soil, rocky over sandy loam, 3d rate.
Timber, scattering yellow pine and juniper; undergrowth, none.
-
- From the standard cor. of secs. 34 and 35, on the S. bdy. of the Tp., an iron post, 2 ins. diam., 7 ins. above ground, mkd. set and witnessed as described in the official record.
- N. 0° 57' E., on true line bet. secs. 34 and 35.
Desc. 107 ft. over a rolling NE. slope, thru timber.
- 33.30 Leave timber, bears NW. and SE.
- 35.80 Traveled road, bears NW. and SE.; in center of draw, course NW.; asc. slightly over a S. slope.
- 40.16 The $\frac{1}{4}$ sec. cor., which is a mound of earth surrounded by 3 stones.
- At point for cor.
- Set an iron post, 3 ft. long, 1 in. diam., 27 ins. in the ground, and in a mound of stone to top, for $\frac{1}{4}$ sec. cor., with brass cap mkd.
- $\frac{1}{4}$
 S 34 | S 35
 1937

Resurvey of the Subdivisions of T. 9 N., R. 26 E.

Chains

from which

An original bearing tree:

A yellow pine stump, 54 ins. diam., bears N. $46\frac{1}{2}^{\circ}$ W.,
174 lks. dist., mkd. $\frac{1}{4}$ S B T.

New bearing trees:

A yellow pine, 16 ins. diam., bears N. $50\frac{1}{2}^{\circ}$ E.,
234 lks. dist., mkd. $\frac{1}{4}$ S 35 B T.

A yellow pine, 28 ins. diam., bears N. 68° W.,
113 lks. dist., mkd. $\frac{1}{4}$ S 34 B T.

N. $0^{\circ} 28'$ E., on true line bet. secs. 25 and 26.

Over rolling land sloping gently S.

7.50 Enter timber, bears E. and W.

10.00 Slope changes to slightly W.

25.00 Asc. 55 ft. over a SW. slope.

40.23 The cor. of secs. 26, 27, 34 and 35, which is a red
sandstone, 22x16x10 ins., in a mound of stone, 4 ft.
base, 2 ft. high, mkd. with 1 notch on the S. face and
2 notches on the E. face.

At point for cor.

Set an iron post, 3 ft. long, 2 ins. diam., 26 ins. in
the ground, and in amount of stone to top, with the
original stone set alongside, for cor. of secs. 26, 27,
34 and 35, with brass cap mkd.

| | |
|------|------|
| T9N | R26E |
| S 27 | S 26 |
| S 34 | S 35 |
| 1937 | |

from which

Original bearing trees:

A spruce, 12 ins. diam., bears S. 20° E., 15 lks.
dist., markings obliterated.

A spruce, 60 ins. diam., bears N. 55° W., 59 lks.
dist., markings obliterated.

No evidence of the original NE. and SW. bearing trees.

New bearing trees:

A fir, 12 ins. diam., bears N. $26\frac{3}{4}^{\circ}$ E., 48 lks.
dist., mkd. T 9 N R 26 E S 26 B T.

A yellow pine, 12 ins. diam., bears S. $3\frac{1}{4}^{\circ}$ E., 75
lks. dist., mkd. T 9 N R 26 E S 35 B T.

A yellow pine, 10 ins. diam., bears S. $76\frac{1}{2}^{\circ}$ W.,
74 lks. dist., mkd. T 9 N R 26 E S 34 B T.

A yellow pine, 8 ins. diam., bears N. 67° W., 82
lks. dist., mkd. T 9 N R 26 E S 27 B T.

Resurvey of the Subdivisions of T. 9 N., R. 26 E.

Chains

Land, rolling hills.
Soil, rocky over sandy loam, 3d rate.
Timber, yellow pine, aspen, fir and spruce; undergrowth, none.

From the cor. of secs. 25, 26, 35 and 36, hereinbefore described.

N. 89° 50' W., on true line bet. secs. 26 and 35.

Over rolling land, slope generally E., thru timber.

15.10 Asc. 272 ft. over a SE. slope.

34.40 Long, steep spur, slopes SE.; desc. slightly over a SW. slope.

36.30 Side hill ravine, 5 ft. wide, course SE.; asc. 230 ft. over an E. slope.

42.70 Proportional distance:

Set an iron post, 3 ft. long, 1 in. diam., 27 ins. in the ground, for $\frac{1}{4}$ sec. cor., with brass cap mkd.

$$\begin{array}{r} S\ 26 \\ \frac{1}{4} \\ \hline S\ 35 \\ 1937 \end{array}$$

from which

A yellow pine, 10 ins. diam., bears S. 16 $\frac{1}{2}$ ° E., 132 lks. dist., mkd. $\frac{1}{4}$ S 35 B T.

A yellow pine, 10 ins. diam., bears N. 14° W., 142 lks. dist., mkd. $\frac{1}{4}$ S 26 B T.

Asc. 206 ft. over a SE. slope:

52.25 Ridge-spur, slopes SW. from St. Peter's Dome, which bears N., about 5 chs. dist.; desc. 604 ft. over a W. slope.

85.40 The cor. of secs. 26, 27, 34 and 35.

Land, rolling mountainous.
Soil, gravelly over sandy loam, 3d rate.
Timber, yellow pine, fir, spruce and aspen; undergrowth, none.

N. 5° 00' E., on true line bet. secs. 26 and 27.

Desc. 134 ft. over a NW. slope, thru timber.

25.00 Slope changes to NE., continue descent.

28.00 Slope changes to NW., continue descent.

40.07 The $\frac{1}{4}$ sec. cor., which is a lava stone, 16x16x6 ins. above ground, mkd. $\frac{1}{4}$ on top.

At point for cor.

Set an iron post, 3 ft. long, 1 in. diam., 27 ins. in the ground, with the original stone set alongside, for $\frac{1}{4}$ sec. cor., with brass cap mkd.

Resurvey of the Subdivisions of T. 9 N., R. 26 E.

Chains

$$\begin{array}{c} \frac{1}{4} \\ \text{S } 27 \mid \text{S } 26 \\ 1937 \end{array}$$

from which

Original bearing trees:

A yellow pine, 16 ins. diam., bears N. $17\frac{1}{2}^{\circ}$ E.,
20 lks. dist., markings overgrown.

An aspen, 12 ins. diam., bears S. 71° W., 42 lks.
dist., markings overgrown.

New bearing trees:

A yellow pine, 12 ins. diam., bears N. $87\frac{1}{2}^{\circ}$ E.,
24 lks. dist., mkd. $\frac{1}{4}$ S 26 B T.

A white pine, 28 ins. diam., bears S. $65\frac{1}{4}^{\circ}$ W.,
59 lks. dist., mkd. $\frac{1}{4}$ S 27 B T.

N. $0^{\circ} 26'$ E., on true line bet. secs. 26 and 27.

Over nearly level land, slope generally NW.

23.00 Traveled road, bears NE. and SW.

40.14 The cor. of secs. 22, 23, 26 and 27, which is a lava
stone, 18x10x7 ins. above ground, mkd. with 2 notches
on each of the S. and E. faces.

At point for cor.

Set an iron post, 3 ft. long, 2 ins. diam., 27 ins. in
the ground, with the original stone set alongside, for
cor. of secs. 22, 23, 26 and 27, with brass cap mkd.

$$\begin{array}{c} \text{T9N R26E} \\ \text{S } 22 \mid \text{S } 23 \\ \hline \text{S } 27 \mid \text{S } 26 \\ 1937 \end{array}$$

from which

Original bearing trees:

A yellow pine, 12 ins. diam., bears N. 30° E.,
62 lks. dist., markings overgrown.

An aspen, 12 ins. diam., now dead and fallen, bears
S. 89° E., 85 lks. dist., markings rotted away.

A yellow pine stump, 14 ins. diam., bears S. 49° W.,
15 lks. dist., markings rotted away.

No evidence of the original NW. bearing tree.

New bearing trees:

A yellow pine, 12 ins. diam., bears N. $33\frac{1}{2}^{\circ}$ E.,
70 lks. dist., mkd. T 9 N R 26 E S 23 B T.

A yellow pine, 28 ins. diam., bears S. 59° E.,
158 lks. dist., mkd. T 9 N R 26 E S 26 B T.

Resurvey of the Subdivisions of T. 9 N., R. 26 E.

Chains

A yellow pine, 16 ins. diam., bears S. $35\frac{1}{2}^{\circ}$ W.,
40 lks. dist., mkd. T 9 N R 26 E S 27 B T.

A yellow pine, 14 ins. diam., bears N. $68\frac{3}{4}^{\circ}$ W.,
79 lks. dist., mkd. T 9 N R 26 E S 22 B T.

Land, rolling to nearly level.

Soil, gravelly to rocky over sandy loam, 3d rate.

Timber, yellow pine, aspen, fir and spruce; undergrowth,
none.

From the cor. of secs. 23, 24, 25 and 26, hereinbefore
described.

S. $89^{\circ} 38'$ W., on true line bet. secs. 23 and 26.

Asc. 93 ft. over a rolling E. slope, thru timber.

6.70 Old road, bears NW. and SE.

19.90 Slope becomes rocky and steeper, asc. 50 ft.

22.55 Rocky spur, slopes NE.; asc. 38 ft. over a NE. slope.

32.50 Ridge, bears NE. and SW.; desc. slightly.

40.07 The $\frac{1}{4}$ sec. cor., which is a lava stone, 18x14x6 ins.
above ground, mkd. $\frac{1}{4}$ on N. face.

At point for cor.

Set an iron post, 3 ft. long, 1 in. diam., 12 ins. in
the ground to underlying rock, and in a mound of stone
to top, with the original stone set alongside, for $\frac{1}{4}$
sec. cor., with brass cap mkd.

$$\begin{array}{r} \frac{1}{4} \text{ S } 23 \\ \hline \text{S } 26 \\ 1937 \end{array}$$

from which

Original bearing trees:

A yellow pine, 16 ins. diam., bears N. $2\frac{1}{2}^{\circ}$ E., 53
lks. dist., markings overgrown, I remark this tree
 $\frac{1}{4}$ S 23 B T.

A yellow pine, 16 ins. diam., bears East, 58 lks.
dist., markings overgrown.

A new bearing tree:

A yellow pine, 16 ins. diam., bears S. $12\frac{1}{4}^{\circ}$ E.,
167 lks. dist., mkd. $\frac{1}{4}$ S 26 B T.

West, on true line bet. secs. 23 and 26.

13.80 Leave ridge and continue over level land.

22.20 Traveled road, bears NE. and SW.

40.55 The cor. of secs. 22, 23, 26 and 27.

Land, rolling hills to nearly level.

Soil, gravelly and rocky over sandy loam, 3d rate.

Timber, yellow pine; undergrowth, none.

Resurvey of the Subdivisions of T. 9 N., R. 26 E.

Chains

N. 4° 13' W., on true line bet. secs. 22 and 23.

Desc. 30 ft. over a NW. slope, thru timber.

8.10 Draw, 2 chs. wide, course NW.; asc. slightly over a SW. slope.

10.50 Short, rocky spur, slopes W.; desc. 37 ft. over a NW. slope.

16.60 Same draw, course NE.; thence along an E. slope.

23.45 Short spur, slopes NW.; desc. 27 ft. over a NE. slope.

25.80 Same draw, 50 lks. wide, course NW.; asc. slightly over a SW. slope.

27.30 Short spur, slopes W.; thence along a W. slope.

38.50 Ridge, bears NE. and SE.

39.02 Proportional distance:

Set an iron post, 3 ft. long, 1 in. diam., 22 ins. in the ground to underlying rock, and in a mound of stone to top, for $\frac{1}{4}$ sec. cor., with brass cap mkd.

| | | |
|------|---|------|
| | ↑ | |
| S 22 | | S 23 |
| 1937 | | |

from which

A yellow pine, 8 ins. diam., bears N. 57½° E., 47 lks. dist., mkd. $\frac{1}{4}$ S 23 B T.

A yellow pine, 10 ins. diam., bears S. 30½° W., 87 lks. dist., mkd. $\frac{1}{4}$ S 22 B T.

Desc. 94 ft. over a gentle NW. slope, thru timber.

58.00 Slope changes to N., continue descent.

78.04 The cor. of secs. 14, 15, 22 and 23, which is a lava stone, 24x24x16 ins. above ground, in a mound of stone, 3 ft. base, 1 ft. high, mkd. with 3 notches on the S. face, and 2 notches on the E. face.

At point for cor.

Set an iron post, 3 ft. long, 2 ins. diam., 25 ins. in the ground, and in a mound of stone to top, with the original stone set alongside, for cor. of secs. 14, 15, 22 and 23, with brass cap mkd.

| | | |
|------|-----|------|
| | T9N | R26E |
| S 15 | | S 14 |
| S 22 | | S 23 |
| 1937 | | |

from which

Original bearing trees:

A yellow pine stump, 16 ins. diam., bears N. 62° E., 27 lks. dist., mkd. T 9 N R 26 E S 14 B T.

Resurvey of the Subdivisions of T. 9 N., R. 26 E.

Chains

A yellow pine, 10 ins. diam., bears S. $20\frac{1}{2}^{\circ}$ W.,
55 lks. dist., markings overgrown, I remark this
tree T 9 N R 26 E S 22 B T.

No evidence of the original SE. and NW. bearing trees.

New bearing trees:

A yellow pine, 12 ins. diam., bears N. $55\frac{1}{2}^{\circ}$ E.,
58 lks. dist., mkd. T 9 N R 26 E S 14 B T.

A yellow pine, 10 ins. diam., bears S. 50° E.,
48 lks. dist., mkd. T 9 N R 26 E S 23 B T.

A yellow pine, 9 ins. diam., bears N. $80\frac{1}{4}^{\circ}$ W.,
59 lks. dist., mkd. T 9 N R 26 E S 15 B T.

Land, rolling mountainous.

Soil, rocky over sandy loam, 3d rate.

Timber, yellow pine, aspen, fir and spruce; undergrowth,
none.

From the cor. of secs. 13, 14, 23 and 24, hereinbefore
described.

N. $89^{\circ} 46'$ W., on true line bet. secs. 14 and 23.

Asc. 109 ft. over an E. slope, thru timber.

1.30 Old road, bears N. and S.

6.60 Graded road, winding NW. and SE.

10.00 Spur, slopes NW.; desc. 6 ft. over a SW. slope.

11.70 Deep draw, 10 lks. wide, course NE.; asc. 103 ft. over
a NE. slope.

19.90 Thence along a N. slope.

22.80 Head of draw, course NE.; asc. 121 ft. over an E. slope.

28.10 Thence along a N. slope.

31.10 Slope changes to NE., asc. 41 ft.

35.50 Toe of spur, slopes N.; desc. 40 ft. over a NW. slope.

40.41 Set an iron post, 3 ft. long, 1 in. diam., 27 ins. in
the ground, for witness $\frac{1}{4}$ sec. cor., with brass cap mkd.

W C $\frac{1}{4}$ S 14
S 23
1937

40.43 The $\frac{1}{4}$ sec. cor., which is a yellow pine, 8 ins. diam.,
mkd. $\frac{1}{4}$ on N. face, from which

Original bearing trees:

A yellow pine, 8 ins. diam., bears N. $71\frac{3}{4}^{\circ}$ E.,
50 lks. dist., mkd. $\frac{1}{4}$ S B T.

A yellow pine, 12 ins. diam., bears S. $32\frac{1}{2}^{\circ}$ W., 17
lks. dist., mkd. $\frac{1}{4}$ S B T.

Resurvey of the Subdivisions of T. 9 N., R. 26 E.

| Chains | |
|--------|-----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| | S. 89° 32' W., on true line bet. secs. 14 and 23. |
| | Desc. 191 ft. over a W. slope, thru timber. |
| 19.30 | Head of draw, course NW.; asc. 73 ft. over a NE. slope. |
| 26.60 | Thence over rolling land. |
| 30.20 | Spur, slopes N.; desc. 37 ft. over a W. slope. |
| 36.10 | Thence over rolling land. |
| 40.12 | The cor. of secs. 14, 15, 22 and 23. |
| | <p>Land, rolling mountainous. Soil, gravelly and rocky over sandy loam, 3d rate. Timber, yellow pine, aspen, fir and spruce; undergrowth, none.</p> |
| | N. 5° 30' W., on true line bet. secs. 14 and 15. |
| | Desc. 57 ft. over a N. slope, thru timber. |
| 8.20 | Dim road, bears NE. and SW.; enter draw, course NE. |
| 10.80 | Leave draw, course NW.; same dim road follows draw; desc. 37 ft. along a NW. slope. |
| 24.00 | Long ridge-spur, slopes NW.; desc. 39 ft. over a NE. slope. |
| 33.00 | Spur, slopes NW.; desc. 94 ft. over a NE. slope. |
| 36.20 | Blazed trail, bears NW. and SE. |
| 41.43 | The $\frac{1}{4}$ sec. cor., which is a lava stone, 10x8x8 ins., in a mound of stone, 2 ft. base, 1 ft. high, mkd. $\frac{1}{4}$ on E. face. |
| | At point for cor. |
| | Set an iron post, 3 ft. long, $\frac{1}{2}$ in. diam., 28 ins. in the ground, with the original stone set alongside, for $\frac{1}{4}$ sec. cor., with brass cap mkd. |
| | $\begin{array}{c} \frac{1}{4} \\ \text{S } 15 \text{ S } 14 \\ 1937 \end{array}$ |
| | from which |
| | An original bearing tree: |
| | A fir, 24 ins. diam., bears N. 16° E., 19 lks. dist., mkd. $\frac{1}{4}$. I change the markings on this tree to read as follows: $\frac{1}{4}$ S 14 B T. |
| | A new bearing tree: |
| | A fir, 24 ins. diam., bears N. 38° E., 43 lks. dist., mkd. $\frac{1}{4}$ S 14 B T. |
| | N. 0° 30' W., on true line bet. secs. 14 and 15. |

Resurvey of the Subdivisions of T. 9 N., R. 26 E.

Chains

- 2.50 Draw, 30 lks. wide, course N. 70° W.; asc. 77 ft. over a SW. slope.
- 6.60 Long ridge-spur, slopes N. 80° W.; desc. 247 ft. over a NE. slope.
- 11.85 4 strand barbed wire fence, bears NE. and SW.
- 22.00 Slope changes to NW.; desc. 40 ft.
- 34.00 Slope changes to SW.; asc. 5 ft.
- 39.80 The cor. of secs. 10, 11, 14 and 15, which is a lava stone, 18x14x10 ins., set in a mound of stone, 3 ft. base, 1 ft. high, mkd. with 4 notches on the S. face and 2 notches on the E. face.

At point for cor..

Set an iron post, 3 ft. long, 2 ins. diam., 27 ins. in the ground, with the original stone set alongside, for cor. of secs. 10, 11, 14 and 15, with brass cap mkd.

| | |
|-------|------|
| T9N | R26E |
| S 10. | S 11 |
| S 15 | S 14 |
| 1937 | |

from which

A yellow pine, 9 ins. diam., bears N. 73° E., 29 lks. dist., mkd. T 9 N R 26 E S 11 B T.

A yellow pine, 6 ins. diam., bears S. 43° E., 82 lks. dist., mkd. S 14 B T.

A yellow pine, 10 ins. diam., bears S. 12° W., 61 lks. dist., mkd. T 9 N R 26 E S 15 B T.

A yellow pine, 7 ins. diam., bears N. 53° W., 79 lks. dist., mkd. S 10 B T.

Land, rolling mountainous.

Soil, rocky and gravelly over sandy loam, 3d rate.

Timber, yellow pine and scattering aspen, fir and spruce; undergrowth, none.

From the cor. of secs. 11, 12, 13 and 14, hereinbefore described.

N. 89° 55' W., on true line bet. secs. 11 and 14.

Asc. 157 ft. over a SE. slope, thru timber.

- 35.00 Slope becomes steeper, continue ascent.

- 40.47 The $\frac{1}{4}$ sec. cor., which is a lava stone, 10x10x8 ins. above ground, mkd. $\frac{1}{4}$ on bottom.

At point for cor.

Set an iron post, 3 ft. long, 1 in. diam., 23 ins. in the ground to underlying rock, and in a mound of stone to top, with the original stone set alongside, for $\frac{1}{4}$ sec. cor., with brass cap mkd.

Resurvey of the Subdivisions of T. 9 N., R. 26 E.

| Chains | |
|--------|-----------------------------------------------------------------------------------------------------------------------------------------------------|
| | $\frac{1}{4} \frac{S 11}{S 14}$ 1937 |
| | from which |
| | A yellow pine, 10 ins. diam., bears N. 75° W., 6 lks. dist., mkd. $\frac{1}{4}$ S 11 B T. |
| | A yellow pine, 10 ins. diam., bears S. 2° W., 38 lks. dist., mkd. $\frac{1}{4}$ S 14 B T. |
| | N. 89° 53' W., on true line bet. secs. 11 and 14. |
| | Asc. 41 ft. over a SE. slope, thru timber. |
| 3.95 | Ridge, bears N. and S.; continue across same. |
| 11.00 | Leave ridge and desc. 123 ft. over a W. slope. |
| 22.65 | Draw, 30 lks. wide, course NW.; desc. 91 ft. over a NW. slope. |
| 23.36 | 4 strand barbed wire fence, bears N. 30° E. and S. 30° W. |
| 40.24 | The cor. of secs. 10, 11, 14 and 15. |
| | Land, rolling hills. Soil, rocky and gravelly over sandy loam, 3d rate. Timber, yellow pine; undergrowth, none. |
| | N. 0° 45' W., on true line bet. secs. 10 and 11. |
| | Along a gentle W. slope, thru timber. |
| 10.00 | The top of a bald butte in sec. 10, bears N. 15° W., vertical angle = +10 $\frac{1}{2}$ °. |
| 13.00 | Desc. 51 ft. over a NW. slope. |
| 17.25 | Gully wash, 6 ft. wide, 3 ft. deep, course W.; leave timber, bears E. and W.; over rolling hills. |
| 19.70 | 4 strand barbed wire fence, bears E. and W. |
| 21.00 | An old frame house bears W., about 35 chs. dist. |
| 24.40 | Foot of a high, bald butte; asc. 280 ft. over a SE. slope. |
| 40.37 | Proportional distance: Set an iron post, 3 ft. long, 1 in. diam., 30 ins. in the ground, for $\frac{1}{4}$ sec. cor., with brass cap mkd. |
| | $\frac{1}{4} \frac{S 10}{S 11}$ 1937 |
| | from which |
| | A juniper fork, 3 ins. diam., bears N. 69 $\frac{1}{2}$ ° E., 295 lks. dist., mkd. B T. |

Resurvey of the Subdivisions of T. 9 N., R. 26 E.

Chains

Raise a mound of stone, $2\frac{1}{2}$ ft. base, $1\frac{1}{2}$ ft. high, W. of cor.

Asc. 104.ft. over a SE. slope.

45.80 3 strand barbed wire fence, bears N. $86\frac{1}{2}^{\circ}$ W. and S. $86\frac{1}{2}^{\circ}$ E.

48.00 Slope changes to E.

50.80 Long, steep spur, slopes NE.; desc. 431 ft. over a NW. slope.

72.00 Enter scattering timber.

77.00 End of marked descent; desc. 30 ft. over a broken NW. slope.

80.74 The point for the cor. of secs. 2, 3, 10 and 11, as determined from the original bearing tree.

At point for cor.

Set an iron post, 3 ft. long, 2 ins. diam., 27 ins. in the ground, for cor. of secs. 2, 3, 10 and 11, with brass cap mkd.

| | |
|------|------|
| T9N | R26E |
| S 3 | S 2 |
| S 10 | S 11 |
| 1937 | |

from which

An original bearing tree:

A yellow pine, 24 ins. diam., bears N. 64° E., 180 lks. dist., mkd. T 9 N R 26 E S 2 B T.

New bearing trees:

A juniper, 12 ins. diam., bears N. $5\frac{1}{2}^{\circ}$ E., 118 lks. dist., mkd. T 9 N R 26 E S 2 B T.

A juniper, 26 ins. diam., bears S. $78\frac{1}{2}^{\circ}$ E., 580 lks. dist., mkd. T 9 N R 26 E S 11 B T.

No suitable SW. bearing tree within limits.

A juniper, 14 ins. diam., bears N. $1\frac{1}{2}^{\circ}$ W., 124 lks. dist.; mkd. T 9 N R 26 E S 3 B T.

From this point fences extend N. 15° W., and S. 89° W.

From the same point:

The top of a bald butte in sec. 10 bears S. $15\frac{1}{2}^{\circ}$ W., vertical angle = $+19^{\circ}$.

A rock cairn on a high butte in sec. 2, bears N. $31^{\circ} 01'$ E.

The top of a butte in sec. 3, bears N. 34° W., vertical angle = $+2\frac{1}{2}^{\circ}$.

Land, rolling mountainous.

Soil, gravelly and rocky over sandy loam, 3d rate.

Timber, yellow pine on E. 20 chs., and scattering yellow pine and juniper on W. 9 chs.; undergrowth, none.

Resurvey of the Subdivisions of T. 9 N., R. 26 E.

Chains

From the cor. of secs. 1, 2, 11 and 12, hereinbefore described.

N. $89^{\circ} 34'$ W., on true line bet. secs. 2 and 11.

Desc. 12 ft. over a rolling N. slope, thru scattering timber.

9.80 Draw, 20 lks. wide, course N. 10° E.

15.00 Wash, 3 ft. wide, course N. 60° E.; asc. 80 ft. over a SE. slope.

17.90 Wash, 3 ft. wide, course S. 20° E., (same wash as above).

26.40 Desc. 16 ft. over a W. slope.

28.70 Enter wash, 15 ft. wide, course SE. from W.

30.90 Leave wash, course E., from SW.; asc. 125 ft. over a SE. slope.

40.63 The $\frac{1}{4}$ sec. cor., which is a lava stone, 14x12x10 ins. above ground, mkd. $\frac{1}{4}$ on N. face.

At point for cor.

Set an iron post, 3 ft. long, 1 in. diam., 20 ins. in the ground to underlying rock, and in a mound of stone to top, with the original stone set alongside, for $\frac{1}{4}$ sec. cor., with brass cap mkd.

$$\begin{array}{r} \frac{1}{4} \text{ S } 2 \\ \text{S } 11 \\ 1937 \end{array}$$

from which

An original bearing tree:

A yellow pine, 10 ins. diam., bears S. 52° E., 56 lks. dist., markings overgrown, I remark this tree $\frac{1}{4}$ S 11 B T.

New bearing trees:

A juniper, 4 ins. diam., bears S. $88\frac{1}{4}^{\circ}$ E., 113 lks. dist., mkd. $\frac{1}{4}$ S 11 B T.

A juniper, 9 ins. diam., bears N. $31\frac{1}{4}^{\circ}$ W., 212 lks. dist., mkd. $\frac{1}{4}$ S 2 B T.

N. $89^{\circ} 54'$ W., on true line, bet. secs. 2 and 11.

Asc. 57 ft. over a NE. slope.

7.30 Ridge, bears NE. and SW., continue across same.

15.76 Fence, bears N., about 3 chs. dist., thence NW.; and S., about 8 chs. dist., thence SE.

30.30 Leave ridge and desc. 23 ft. over a rolling N. to NW. slope.

35.40 Shallow draw, course N.; asc. 20 ft. over an E. slope.

40.21 The cor. of secs. 2, 3, 10 and 11.

Resurvey of the Subdivisions of T. 9 N., R. 26 E.

Chains

Land, rolling mountainous.
Soil, sandy loam and rocky, 3d rate.
Timber, very scattering juniper and yellow pine; undergrowth, none.

N. 0° 38' E., on true line, bet. secs. 2 and 3.

Desc. 148 ft. over a N. slope, thru very scattering timber.

- 0.75 3 strand barbed wire fence, bears N. 89° E. and S. 89° W.
- 14.10 Grassy draw, 50 lks. wide, course NW.
- 19.36 The cor. of barbed wire fences bears E., 7 lks. dist., from which fences extend W. and S.
- 21.60 Traveled road, bears NE. and SW.
- 22.90 Same draw, course NE.
- 27.90 Same draw, course NW.
- 30.00 Long ridge-spur, slopes NE.; desc. 50 ft. over a NW. slope.
- 40.97 Proportional distance:
Set an iron post, 3 ft. long, 1 in. diam., 26 ins. in the ground, for $\frac{1}{4}$ sec. cor., with brass cap mkd.
- $$\begin{array}{c} \frac{1}{4} \\ | \\ S\ 3 \quad | \quad S\ 2 \\ | \\ 1937 \end{array}$$
- from which
- A yellow pine, 14 ins. diam., bears S. 36 $\frac{1}{2}$ ° W., 556 lks. dist., mkd. $\frac{1}{4}$ S 3 B T.
- Raise a mound of stone, 3 ft. base, 2 ft. high, W. of cor.
- From this point, a natural tank, 20 ft. diam., 2 ft. deep, bears N. 64° W., 4.70 chs. dist., in a wash, course NE.
- Desc. 13 ft. over a NW. slope.
- 43.10 Intersection of draws, course NE., from S. and NW.
- 47.00 Leave draw and asc. 44 ft. over a SE. slope.
- 55.90 Spur, slopes NE.; continue across same.
- 60.90 Leave spur and desc. 30 ft. over a NW. slope.
- 64.50 Grassy draw, 1 ch. wide, course E., from SW.; asc. 8 ft. over a SE. slope.
- 67.80 Short spur, slopes E.; desc. 20 ft. over a NE. slope.
- 70.75 Enter wash, 15 ft. wide, 3 ft. deep, course N. 15° W.

Resurvey of the Subdivisions of T. 9 N., R. 26 E.

Chains

- 71.25 4 strand barbed wire fence, bears NW. and SE.
 72.00 Leave wash and asc. 40 ft. along a W. to SW. slope.
 81.16 4 strand barbed wire fence, bears E. and W.
 81.22 The cor. of secs. 2, 3, 34 and 35, on the N. bdy. of the Tp., described in the field notes of the N. bdy. of T. 9 N., R. 26 E., resurveyed under this group.

Land, rolling hills.

Soil, gravelly and rocky over sandy loam, 3d rate.
 Timber, very scattering yellow pine and juniper;
 undergrowth, none.

From the standard cor. of secs. 33 and 34, on the S. bdy. of the Tp., an iron post, 2 ins. diam., 6 ins. above ground, mkd., set and witnessed as described in the official record.

N. 3° 26' E., on true line bet. secs. 33 and 34.

Desc. 121 ft. over a gentle N. slope, thru timber.

39.83 Proportional distance:

Set an iron post, 3 ft. long, 1 in. diam., 18 ins. in the ground to underlying rock, and in a mound of stone to top, for $\frac{1}{4}$ sec. cor., with brass cap mkd.

$$\begin{array}{c} \frac{1}{4} \\ \text{S } 33 \mid \text{S } 34 \\ 1937 \end{array}$$

from which

An aspen, 8 ins. diam., bears S. 56 $\frac{1}{4}$ ° E., 126 lks. dist., mkd. $\frac{1}{4}$ S 34. B T.

A yellow pine, 30 ins. diam., bears S. 49 $\frac{1}{4}$ ° W., 36 lks. dist., mkd. $\frac{1}{4}$ S 33 B T.

Desc. 238 ft. over a general N. slope.

61.80 Left bank of stream, 3 lks. wide, course NE. from SE.

79.66 The cor. of secs. 27, 28, 33 and 34, which is the midpoint of a mound of earth, 5 ft. base, 1 ft. high.

At point for cor.

Set an iron post, 3 ft. long, 2 ins. diam., 27 ins. in the ground, for cor. of secs. 27, 28, 33 and 34, with brass cap mkd.

$$\begin{array}{c} \text{T9N} \quad \text{R26E} \\ \text{S } 28 \mid \text{S } 27 \\ \text{S } 33 \mid \text{S } 34 \\ 1937 \end{array}$$

from which

Resurvey of the Subdivisions of T. 9 N., R. 26 E.

Chains

Original bearing trees:

A fir, 30 ins. diam., bears N. $31\frac{1}{4}^{\circ}$ E., 56 lks. dist., markings illegible.

A yellow pine, 28 ins. diam., bears S. $47\frac{3}{4}^{\circ}$ E., 70 lks. dist., markings overgrown, I remark this tree, T 9 N R 26 E S 34 B T.

A yellow pine, 30 ins. diam., bears S. 54° W., 111 lks. dist., markings overgrown, I remark this tree, T 9 N R 26 E S 33 B T.

A yellow pine, 20 ins. diam., bears N. $74\frac{1}{2}^{\circ}$ W., 102 lks. dist., markings overgrown, I remark this tree, T 9 N R 26 E S 28 B T.

A new bearing tree:

A fir, 8 ins. diam., bears N. $78\frac{1}{2}^{\circ}$ E., 150 lks. dist., mkd. T 9 N R 26 E S 27 B T.

Land, rolling hills.

Soil, sandy loam and rocky, 3d rate.

Timber, yellow pine, aspen, spruce and fir; undergrowth, none.

From the cor. of secs. 26, 27, 34 and 35, hereinbefore described.

N. $89^{\circ} 50'$ W., on true line bet. secs. 27 and 34.

Desc. 89 ft. over a W. slope, thru timber.

9.90 Thence over rolling land.

38.05 Proportional distance:

Set an iron post, 3 ft. long, 1 in. diam., 24 ins. in the ground, and in a mound of stone to top, for $\frac{1}{4}$ sec. cor., with brass cap mkd.

$$\frac{1}{4} \frac{S 27}{S 34} \\ 1937$$

from which

A yellow pine, 10 ins. diam., bears S. 28° W., 69 lks. dist., mkd. $\frac{1}{4}$ S 34 B T.

A yellow pine, 10 ins. diam., bears N. $37\frac{1}{2}^{\circ}$ W., 108 lks. dist., mkd. $\frac{1}{4}$ S 27 B T.

Desc. 47 ft. over rolling land.

57.60 Traveled road, bears NW. and SE.; in a draw, course NW.

63.40 Draw, 1 ch. wide, course NE.; asc. 41 ft. over an E. slope.

76.10 The cor. of secs. 27, 28, 33 and 34.

Land, rolling hills.

Soil, sandy loam and rocky, 3d rate.

Timber, yellow pine, aspen, spruce and fir; undergrowth, none.

Resurvey of the Subdivisions of T. 9 N., R. 26 E.

Chains

N. 0° 43' W., on true line bet. secs. 27 and 28.

Desc, 158 ft, over rolling land.

22.00 Dim road, bears NW. and SE.

40.07 The point for the $\frac{1}{4}$ sec. cor., as determined from the original bearing trees, and a mound of earth.

At point for cor.

Set an iron post, 3 ft. long, 1 in. diam., 27 ins. in the ground, for $\frac{1}{4}$ sec. cor., with brass cap mkd.
$$\begin{array}{c} \frac{1}{4} \\ \text{S } 28 \mid \text{S } 27 \\ 1937 \end{array}$$

from which

Original bearing trees:

A yellow pine, 24 ins. diam., bears N. 56° E., 115 lks. dist., mkd. $\frac{1}{4}$. I change the markings on this tree to read as follows: $\frac{1}{4}$ S 27 B T.

A yellow pine, 18 ins. diam., bears S. 47° W., 100 lks. dist., mkd. $\frac{1}{4}$. I change the markings on this tree to read as follows: $\frac{1}{4}$ S 28 B T.

N. 0° 07' E., on true line bet. secs. 27 and 28.

Over rolling land, thru timber.

0.60 Traveled road, bears E. and W.

5.00 Leave timber, bears E. and W.

7.00 Draw, 1.50 chs. wide, course NW.

11.50 Small stream, course NW.; enter timber, bears E. and W.

31.60 4 strand barbed wire fence, bears E. and W.; asc. 128 ft. over a SW. slope.

39.65 The cor. of secs. 21, 22, 27 and 28, which is a lava stone, 8x7x4 ins. above ground, mkd. with 2 notches on the S. face, and 3 notches on the E. face.

At point for cor.

Set an iron post, 3 ft. long, 2 ins. diam., 28 ins. in the ground, with the original stone set alongside, for cor. of secs. 21, 22, 27 and 28, with brass cap mkd.

$$\begin{array}{c} \text{T9N} \quad \text{R26E} \\ \text{S } 21 \mid \text{S } 22 \\ \text{S } 28 \mid \text{S } 27 \\ 1937 \end{array}$$

from which

Original bearing trees:

A yellow pine, 30 ins. diam., bears N. 32 $\frac{1}{4}$ ° E., 32 lks. dist., markings overgrown, I remark this tree: T 9 N R 26 E S 22 B T.

Resurvey of the Subdivisions of T. 9 N., R. 26 E.

Chains

A yellow pine, 18 ins. diam., now dead, bears S. 78° E., 40 lks. dist., mkd. T 9 N R 26 E S 27 B T.

A yellow pine, 14 ins. diam., bears S. 69½° W., 49 lks. dist., markings overgrown, I remark this tree, T 9 N R 26 E S 28 B T.

A yellow pine, 28 ins. diam., bears N. 66½° W., 71 lks. dist., markings overgrown, I remark this tree, T 9 N R 26 E S 21 B T.

A new bearing tree:

A yellow pine, 24 ins. diam., bears S. 32¼° E., 130 lks. dist., mkd. T 9 N R 26 E S 27 B T.

Land, rolling hills.

Soil, sandy loam and rocky, 3d rate.

Timber, yellow pine, fir and aspen; undergrowth, none.

From the cor. of secs. 22, 23, 26 and 27, hereinbefore described.

S. 89° 55' W., on true line bet. secs. 22 and 27.

Desc. 35 ft. over a NW. slope, thru timber.

8.40 Grassy draw, 1 ch. wide, course N.; asc. 25 ft. over a NE. slope.

11.80 Short, low spur, slopes NE.; desc. slightly over a NW. slope.

14.30 Head of draw, 2 chs. wide, course N. 30° E.; asc. 115 ft. over a SE. slope.

31.50 4 strand barbed wire fence, bears N. 75° E. and S. 75° W.

40.12 Proportional distance:

Set an iron post, 3 ft. long, 1 in. diam., 28 ins. in the ground, for ¼ sec. cor., with brass cap mkd.

$$\frac{1}{4} \frac{S 22}{S 27}$$

from which

A yellow pine, 10 ins. diam., bears N. 35½° E., 114 lks. dist., mkd. ¼ S 22 B T.

A yellow pine, 10 ins. diam., bears S. 39½° W., 53 lks. dist., mkd. ¼ S 27 B T.

Asc. 120 ft. over a SE. slope, thru timber.

65.00 Thence along a S. slope.

74.60 Desc. 34 ft. over a SW. slope.

80.24 The cor. of secs. 21, 22, 27 and 28.

Land, rolling hills.

Soil, rocky over sandy loam, 3d rate.

Timber, yellow pine and scattering aspen, fir and spruce; undergrowth, none.

Resurvey of the Subdivisions of T. 9 N., R. 26 E.

Chains

N. $4^{\circ} 43'$ W., on true line bet. secs. 21 and 22.

Asc. 280 ft. over a SW. slope, thru timber.

15.10 Spur, slopes W.; desc. 350 ft. over a NW. slope.

39.11 Proportional distance:

Set an iron post, 3 ft. long, 1 in. diam., 26 ins. in the ground, for $\frac{1}{4}$ sec. cor., with brass cap mkd.
$$\begin{array}{c} \frac{1}{4} \\ | \\ \text{S } 21 \text{ | S } 22 \\ | \\ 1937 \end{array}$$

from which

An aspen, 6 ins. diam., bears N. 73° E., 54 lks. dist., mkd. $\frac{1}{4}$ S 22 B T.An aspen, 14 ins. diam., bears S. $81\frac{3}{4}^{\circ}$ W., 66 lks. dist., mkd. $\frac{1}{4}$ S 21 B T.

Desc. slightly over a NW. slope, thru timber.

43.40 Draw, 1 ch. wide, course W.; asc. 160 ft. over a SW. slope.

56.20 Spur, slopes W.; desc. 530 ft. over a N. slope.

78.22 The cor. of secs. 15, 16, 21 and 22, which is a yellow pine, 10 ins. diam.; mkd. with 3 notches on the S. face, other markings obliterated, from which

Original bearing trees:

A yellow pine, 30 ins. diam., dead and fallen, bears N. $24\frac{1}{2}^{\circ}$ E., 45 lks. dist., mkd. T 9 N R 26 E S 15 B T.A yellow pine, 28 ins. diam., bears S. $30\frac{1}{4}^{\circ}$ E., 49 lks. dist., mkd. T 9 N R 26 E S 22 B T.A yellow pine, 10 ins. diam., bears S. 48° W., 24 lks. dist., mkd. T 9 N R 26 E S 21 B T.A yellow pine, 28 ins. diam., bears N. $5\frac{1}{4}^{\circ}$ W., 71 lks. dist., mkd. T 9 N R 26 E S 16 B T.

A new bearing tree:

A yellow pine, 28 ins. diam., bears N. 12° E., 116 lks. dist., mkd. T 9 N R 26 E S 15 B T.

Also set a witness cor. See line bet. secs. 15 and 22. Land, rolling mountainous.

Soil, sandy loam and rocky, 3d rate.

Timber, fir, spruce, aspen and scattering yellow pine; undergrowth, none.

Resurvey of the Subdivisions of T. 9 N., R. 26 E.

Chains

From the cor. of secs. 14, 15, 22, and 23, hereinbefore described.

S. $89^{\circ} 56'$ W., on true line bet. secs. 15 and 22.

Over rolling land, thru timber.

5.00 Desc. 90 ft. over a NW. slope.

12.80 Draw, 1 ch. wide, course NE.; thence over rolling land.

17.20 4 strand barbed wire fence, bears N. and S.

40.32 Set an iron post, 3 ft. long, 1 in. diam., 20 ins. in the ground to underlying rock, and in a mound of stone to top, for witness $\frac{1}{4}$ sec. cor., with brass cap mkd.

| | | | |
|------|---------------|---|----|
| W | $\frac{1}{4}$ | S | 15 |
| C | $\frac{1}{4}$ | S | 22 |
| 1937 | | | |

40.34 The $\frac{1}{4}$ sec. cor., which is a yellow pine, 12 ins. diam., mkd. $\frac{1}{4}$ S on N. face, from which

Original bearing trees:

A yellow pine, 8 ins. diam., bears N. $16\frac{3}{4}^{\circ}$ W., 20 lks. dist.; mkd. $\frac{1}{4}$ S B T.

A yellow pine, 8 ins. diam., dead and fallen, bears S. $52\frac{1}{4}^{\circ}$ E., 26 lks. dist., mkd. $\frac{1}{4}$ S B T.

A new bearing tree:

A yellow pine, 14 ins. diam., bears S. 65° E., 36 lks. dist.; mkd. $\frac{1}{4}$ S 22 B T.

N. $89^{\circ} 53'$ W., on true line bet. secs. 15 and 22.

Desc. 27 ft. over a SW. slope.

5.50 Draw, 4 lks. wide, course NW.; desc. 54 ft. along a N. to NW. slope.

40.56 Set an iron post, 3 ft. long, 2 ins. diam., 18 ins. in the ground to underlying rock, and in a mound of stone to top, for witness cor. of secs. 15, 16, 21 and 22, with brass cap mkd.

| | | | |
|------|---|-----|------|
| | | T9N | R26E |
| W | S | 16 | S |
| C | S | 21 | S |
| | | 15 | 22 |
| 1937 | | | |

40.58 The cor. of secs. 15, 16, 21 and 22.

Land, rolling mountainous.

Soil, sandy loam and rocky, 3d rate.

Timber, fir, spruce, aspen and yellow pine; undergrowth, none.

Resurvey of the Subdivisions of T. 9 N., R. 26 E.

Chains

N. 4° 50' W., on true line bet. secs. 15 and 16.

Desc. 290 ft. over a N. slope, thru timber.

6.60

Traveled road, bears NE. and SW.

40.97

The $\frac{1}{4}$ sec. cor., which is a lava stone, 14x10x8 ins., set in a mound of stone, 3 ft. base, 1 ft. high, mkd. $\frac{1}{4}$ on N. face.

At point for cor.

Set an iron post, 3 ft. long, 1 in. diam., 20 ins. in the ground to underlying rock, and in a mound of stone to top, with the original stone set alongside, for $\frac{1}{4}$ sec. cor., with brass cap mkd.
$$\begin{array}{c} \frac{1}{4} \\ | \\ \text{S } 16 \mid \text{S } 15 \\ | \\ 1937 \end{array}$$

from which

Original bearing trees:

A yellow pine stump, 36 ins. diam., bears S. 87° E., 37 lks. dist., mkd. $\frac{1}{4}$ S B T.A yellow pine, 14 ins. diam., bears S. 47 $\frac{1}{2}$ ° W., 92 lks. dist., markings overgrown, I remark this tree, $\frac{1}{4}$ S 16 B T.

A new bearing tree:

A yellow pine, 30 ins. diam., bears S. 36° E., 60 lks. dist., mkd. $\frac{1}{4}$ S 15 B T.

N. 0° 42' W., on true line bet. secs. 15 and 16.

Over nearly level land, thru timber.

3.00

Desc. 44 ft. over a NW. slope.

8.80

Draw, 1 ch. wide, course NE.; thence over rolling land.

21.90

Stream, 2 lks. wide, course NW.; asc. slightly over a SW. slope.

40.21

The cor. of secs. 9, 10, 15 and 16, which is a lava stone, 20x12x10 ins., set in a mound of stone, 3 ft. base, 2 ft. high, mkd. with 4 notches on the S. face and 3 notches on the E. face.

At point for cor.

Set an iron post, 3 ft. long, 2 ins. diam., 12 ins. in the ground to underlying rock, and in a mound of stone to top, with the original stone set alongside, for cor. of secs. 9, 10, 15 and 16, with brass cap mkd.

$$\begin{array}{c} \text{T9N} \quad \text{R26E} \\ \text{S } 9 \mid \text{S } 10 \\ \text{S } 16 \mid \text{S } 15 \\ | \\ 1937 \end{array}$$

from which

Resurvey of the Subdivisions of T. 9 N., R. 26 E.

Chains

Original bearing trees:

A yellow pine, 30 ins. diam., bears N. 37 1/2° E., 71 lks. dist., mkd. T 9 N R 26 E S 10 B T.

A yellow pine, 14 ins. diam., bears N. 85° E., 29 lks. dist., mkd. T 9 N R 26 E S 15 B T.

A yellow pine, 36 ins. diam., bears S. 37 1/2° W., .84 lks. dist., mkd. T 9 N R 26 E S 16 B T.

A yellow pine, 34 ins. diam., bears N. 85° W., 107 lks. dist., mkd. T 9 N R 26 E S 9 B T.

A new bearing tree:

A yellow pine, .22 ins. diam., bears S. 48 1/2° E., .199 lks. dist., mkd. T 9 N R 26 E S 15 B T.

Land, rolling hills.

Soil, sandy loam and rocky, 3d rate.

Timber, yellow pine; undergrowth, none.

From the cor. of secs. 10, 11, 14 and 15, hereinbefore described.

N. 89° 52' W., on true line bet. secs. 10 and 15.

Desc. 41 ft. over a SW. slope, thru timber.

9.95 Head of wash, 15 ft. wide, 2 ft. deep, course NW.; asc. slightly.

15.00 Asc. 89 ft. over a NE. slope.

22.15 Spur, slopes N.; continue across same.

24.60 Leave spur and desc. 42 ft. over a NW. slope.

28.70 Wash, 6 ft. wide, 1 ft. deep, course NE.; asc. 51 ft. over a NE. slope.

33.40 Ridge, bears NW. and SE., continue across same.

37.40 Leave ridge and desc. slightly over a SW. slope.

40.21 The 1/4 sec. cor., which is a lava stone, 16x16x8 ins. above ground, mkd. 1/4 on N. face.

At point for cor.

Set an iron post, 3 ft. long, 1 in. diam., 27 ins. in the ground, with the original stone set alongside, for 1/4 sec. cor., with brass cap mkd.

1/4 S 10 S 15 1937

from which

Original bearing trees:

A yellow pine, 20 ins. diam., bears N. 12° W., 75 lks. dist., markings overgrown, I remark this tree, 1/4 S 10 B T.

Resurvey of the Subdivisions of T. 9 N., R. 26 E.

| Chains | |
|--------|------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| | <p>A yellow pine, 16 ins. diam., bears S. 8° W., 106 lks. dist., markings overgrown, I remark this tree, $\frac{1}{4}$ S 15 B T.</p> <p>S. 89° 50' W., on true line bet. secs. 10 and 15.</p> <p>Desc. 33 ft. over a SW. slope, thru timber.</p> |
| 0.75 | Old irrigation ditch, running water, 1 lk. wide, 1 in. deep, course NW. |
| 3.60 | Same stream, 5 lks. wide, 3 ins. deep, in ravine, course NW.; asc. 34 ft. over a NE. slope. |
| 20.00 | Long, broad ridge-spur, slopes NW., thence across same. |
| 25.00 | Leave ridge and desc. 52 ft. over a NW. slope. |
| 28.85 | Traveled road, bears NE. to U. S. Highway No. 60, and SW. to Whiting's Mill. |
| 37.85 | Dim road, bears NW. and SE. |
| 40.41 | The cor. of secs. 9, 10, 15 and 16. |
| | <p>Land, rolling hills. Soil, gravelly and rocky over sandy loam, 3d rate. Timber, yellow pine; undergrowth, none.</p> |
| | <p>N. 0° 42' W., on true line bet. secs. 9 and 10.</p> <p>Desc. 90 ft. over rolling land, thru timber.</p> |
| 5.00 | Head of draw, course NW.. |
| 8.70 | Traveled road, bears NW. and SE. |
| 11.00 | Traveled road, bears NE. and SW. |
| 40.55 | <p>The $\frac{1}{4}$ sec. cor., which is a lava stone, 12x10x8 ins. above ground, mkd. $\frac{1}{4}$ on W. face.</p> <p>At point for cor.</p> <p>Set an iron post, 3 ft. long, 1 in. diam., 12 ins. in the ground to underlying rock, and in a mound of stone to top, with the original stone set alongside, for $\frac{1}{4}$ sec. cor., with brass cap mkd.</p> <div style="text-align: center;"> $\frac{1}{4}$ S 9 S 10 1937 </div> <p style="text-align: right;">from which</p> <p>A yellow pine, 6 ins. diam., bears S. 51° E., 59 lks. dist., mkd. $\frac{1}{4}$ S 10 B T.</p> <p>A yellow pine, 6 ins. diam., bears S. 52° W., 109 lks. dist., mkd. $\frac{1}{4}$ S 9 B T.</p> <p>N. 0° 54' W., on true line bet. secs. 9 and 10.</p> <p>Desc. 32 ft. over rolling land, thru timber.</p> |

Resurvey of the Subdivisions of T. 9 N., R. 26 E.

Chains

13.00 Head of cut wash, in draw, course NW.
 17.60 Head of draw, course W.; asc. slightly over a S. slope.
 20.00 Spur, slopes W.; desc. 86 ft. over a N. slope.
 27.50 Slope changes to NE.; continue descent.
 32.40 Leave timber, bears E. and W.; draw, 2 chs. wide, course SE.; over rolling land.

40.63 The cor. of secs. 3, 4, 9 and 10, which is a lava stone, 16x12x10 ins. above ground, mkd. with 5 notches on the S. face and 3 notches on the E. face.

At point for cor.

Set an iron post, 3 ft. long, 2 ins. diam., 18 ins. in the ground to underlying rock, and in a mound of stone to top, with the original stone set alongside, for cor. of secs. 3, 4, 9 and 10, with brass cap mkd.

| | | |
|------|-----|------|
| | T9N | R26E |
| S | 4 | S 3 |
| | | |
| S | 9 | S 10 |
| 1937 | | |

from which

A pine, 4 ins. diam., bears N. 19° E., 94 lks. dist., mkd. B T.

A pine, 4 ins. diam., bears S. 84½° E., 70 lks. dist., mkd. B T.

A pine, 3 ins. diam., bears N. 8½° W., 247 lks. dist., mkd. B T.

No SW. bearing tree within limits.

Land, rolling hills.

Soil, lava rock over sandy loam, 3d rate.

Timber, dense to scattering yellow pine; undergrowth, none.

From the cor. of secs. 2, 3, 10 and 11, hereinbefore described.

N. 89° 43' W., on true line bet. secs. 3 and 10.

Asc. slightly over a NE. slope, thru scattering timber.

5.00 Long spur from a bald butte, slopes N.; desc. 36 ft. over a NW. slope.

11.70 Draw, 30 lks. wide, course N.; asc. 12 ft. over a NE. slope.

16.00 Long spur from same butte, slopes N.; desc. 75 ft. over a NW. slope.

29.70 3 strand barbed wire fence, bears N. 89° E. and S. 89° W.

30.55 Traveled road, bears NE. to U. S. Highway No. 60, and SW. to Whiting's Mill.

Resurvey of the Subdivisions of T. 9 N., R. 26 E.

Chains

40.29

Proportional distance:

Set an iron post, .3 ft. long, 1 in. diam., 29 ins. in the ground, for $\frac{1}{4}$ sec. cor., with brass cap mkd.

$$\frac{1}{4} \frac{S \ 3}{S \ 10} \\ 1937$$

from which

A yellow pine, 4 ins. diam., bears S. $11\frac{3}{4}^{\circ}$ E., 256 lks. dist., mkd. B.T.

Raise a mound of stone, 4 ft. base, 2 ft. high, N. of cor.

From this point:

The cor. of fences bears S. 78° E., 95 lks. dist., from which fences extend N. 89° E., N. $8\frac{1}{2}^{\circ}$ E., and S. $8\frac{1}{2}^{\circ}$ W.

The top of a butte in sec. 3, bears N. $9\frac{1}{2}^{\circ}$ E.

A rock cairn on top of a butte in sec. 2, bears N. $49^{\circ} 50'$ E.

The NE. cor. of the top of a butte in sec. 10, bears S. 49° E.

An old frame cabin, (No. 1), bears S. 20° W.

An old frame cabin, (No. 2), bears S. 26° W.

Wide draw, course NW., 5 chs. dist., thence NE., continue over rolling land.

60.00

Enter scattering timber and asc. 57 ft. over a SE. slope.

67.70

Top of bench, bears NE. and SW., continue across same; from this point old frame cabin No. 1, bears S. 75° E., and old frame cabin No. 2 bears S. $69\frac{1}{2}^{\circ}$ E.

69.62

Barbed wirefence, bears N. and S. 21 lks. dist., thence E., 10 chs. dist., thence S.

80.58

The cor. of secs. 3, 4, 9 and 10.

Land, rolling to nearly level.

Soil, gravelly and rocky over sandy loam, 2nd and 3d rate. Timber, scattering yellow pine and juniper; undergrowth, none.

N. $0^{\circ} 30'$ W., on true line bet. secs. 3 and 4.

Desc. 22 ft. over rolling land.

12.20

Desc. 57 ft. over a NE. slope.

17.12

End of descent, continue over rolling land.

26.82

Traveled road, bears E. and W.

Resurvey of the Subdivisions of T. 9 N., R. 26 E.

Chains

40.03 The $\frac{1}{4}$ sec. cor., which is a lava stone, 12x6x6 ins. above ground, mkd. $\frac{1}{4}$ on W. face.

At point for cor.

Set an iron post, 3 ft. long, 1 in. diam., 27 ins. in the ground, with the original stone set alongside, for $\frac{1}{4}$ sec. cor., with brass cap mkd.

$\frac{1}{4}$
S 4 | S 3
1937

raise a mound of stone, $3\frac{1}{2}$ ft. base, 3 ft. high, W. of cor.

N. $2^{\circ} 46'$ E., on true line bet. secs. 3 and 4.

Over nearly level land.

41.63 The cor. of secs. 3, 4, 33 and 34, on the N. bdy. of the Tp., described in the field notes of the N. bdy. of T. 9 N., R. 26 E., resurveyed under this group.

Land, rolling to nearly level.
Soil, sandy loam and rocky, 3d rate.
Timber, none; undergrowth, none.

From the standard cor. of secs. 32 and 33, on the S. bdy. of the Tp., an iron post, 2 ins. diam., 11 ins. above ground, mkd., set and witnessed as described in the official record.

N. $4^{\circ} 29'$ E., on true line bet. secs. 32 and 33.

Desc. 38 ft. over rolling land.

27.50 Asc. 108 ft. over a S. slope.

32.00 Slope changes to SW., continue ascent.

39.00 Spur, slopes NW.; desc. slightly over a NE. slope.

40.17 Proportional distance:

Set an iron post, 3 ft. long, 1 in. diam., 27 ins. in the ground; for $\frac{1}{4}$ sec. cor., with brass cap mkd.

$\frac{1}{4}$
S 32 | S 33
1937

from which

An aspen, 6 ins. diam., bears S. $89\frac{1}{4}^{\circ}$ E., 81 lks. dist., mkd. $\frac{1}{4}$ S 33 B T.

An aspen, 10 ins. diam., bears N. 66° W., 37 lks. dist., mkd. $\frac{1}{4}$ S 32 B T.

Resurvey of the Subdivisions of T. 9 N., R. 26 E.

Chains

Desc. 348 ft. over a NE. slope, thru timber.

42.50 Slope changes to NW.; continue descent.

47.30 Slope changes to N.; continue descent.

67.00 West fork of Mineral Creek, 5 lks. wide, 6 ins. deep, course NE.; thence over nearly level land.

80.34 The cor. of secs. 28, 29, 32 and 33, which is a lava stone, 12x10x8 ins. above ground, mkd. with 1 notch on the S. face and 4 notches on the E. face.

At point for cor.

Set an iron post, 3 ft. long, 2 ins. diam., 27 ins. in the ground, with the original stone set alongside, for cor. of secs. 28, 29, 32 and 33, with brass cap mkd.

| | |
|------|------|
| T9N | R26E |
| S 29 | S 28 |
| S 32 | S 33 |
| 1937 | |

from which

Original bearing trees:

A yellow pine, 14 ins. diam., dead and fallen, bears N. $17\frac{1}{2}^{\circ}$ E., 87 lks. dist., mkd. T 9 N R 26 E S 28 B T.

No evidence of the original SE. bearing tree.

A yellow pine stump, 15 ins. diam., bears S. $38\frac{1}{4}^{\circ}$ W., 88 lks. dist., mkd. T 9 N R 26 E S 32 B T.

A yellow pine fork, 18 ins. diam., bears N. $48\frac{1}{4}^{\circ}$ W., 85 lks. dist., mkd. T 9 N R 26 E S 29 B T.

New bearing trees:

A yellow pine, 14 ins. diam., bears N. $3\frac{1}{2}^{\circ}$ E., 86 lks. dist., mkd. T 9 N R 26 E S 28 B T.

An aspen, 6 ins. diam., bears S. $56\frac{1}{2}^{\circ}$ E., 55 lks. dist., mkd. T 9 N R 26 E S 33 B T.

A yellow pine, 10 ins. diam., bears S. $13\frac{3}{4}^{\circ}$ W., 51 lks. dist., mkd. T 9 N R 26 E S 32 B T.

Land, rolling hills.

Soil, sandy loam and rocky, 3d rate.

Timber, yellow pine, fir and aspen; undergrowth, none.

From the cor. of secs. 27, 28, 33 and 34, hereinbefore described.

S. $89^{\circ} 54'$ W., on true line bet. secs. 28 and 33.

Desc. 52 ft. over rolling land, thru timber.

39.79 The point for the $\frac{1}{4}$ sec. cor. as determined from the original bearing trees.

Resurvey of the Subdivisions of T. 9 N., R. 26 E.

Chains

At point for cor.

Set an iron post, 3 ft. long, 1 in. diam., 18 ins. in the ground to underlying rock, for $\frac{1}{4}$ sec. cor., with brass cap mkd.

$$\frac{1}{4} \begin{array}{r} S 28 \\ \hline S 33 \\ 1937 \end{array}$$

from which

Original bearing trees:

An aspen, 12 ins. diam., dead and fallen, bears N. 41° E., 53 lks. dist., markings decayed.

A sugar pine, 36 ins. diam., bears S. $41\frac{1}{2}^{\circ}$ W., 35 lks. dist., markings overgrown.

New bearing trees:

A yellow pine, 14 ins. diam., bears N. $29\frac{3}{4}^{\circ}$ E., 126 lks. dist., mkd. $\frac{1}{4}$ S 28 B T.

A yellow pine, 8 ins. diam., bears S. $60\frac{3}{4}^{\circ}$ E., 65 lks. dist., mkd. $\frac{1}{4}$ S 33 B T.

S. $89^{\circ} 05'$ W., on true line bet. secs. 28 and 33.

Over nearly level land, thru timber.

- 1.20 Desc. 63 ft. over a rocky W. slope.
- 7.90 End of descent, thence over rolling land.
- 14.30 Stream, 1 lk. wide, course N.
- 18:70 W. fork of same stream, course NE.
- 31.20 Rocky draw, 50 lks. wide, course NE.; asc. slightly over an E. slope.
- 39.54 The cor. of secs. 28, 29, 32 and 33.

Land, rolling to nearly level.

Soil, sandy loam and rocky, 3d rate.

Timber, yellow pine, fir, spruce and aspen; undergrowth, none.

N. $1^{\circ} 12'$ W., on true line bet. secs. 28 and 29.

Desc. 60 ft. over rolling land.

- 5.70 Old road, bears E. and W.
- 13.80 4 strand barbed wire fence, bears NE. and SW.
- 25.10 Railroad right of way, bears NE. and SW.
- 40.30 The point for the $\frac{1}{4}$ sec. cor., as determined from the original bearing trees.

At point for cor.

Resurvey of the Subdivisions of T. 9 N., R. 26 E.

Chains

Set an iron post, 3 ft. long, 1 in. diam., 24 ins. in the ground to underlying rock, and in a mound of stone to top, for $\frac{1}{4}$ sec. cor., with brass cap mkd.

$$\begin{array}{c} \frac{1}{4} \\ \text{S } 29 \text{ | S } 28 \\ 1937 \end{array}$$

from which

Original bearing trees:

A yellow pine, 20 ins. diam., bears S. $64\frac{1}{2}^{\circ}$ E., 84 lks. dist., mkd: $\frac{1}{4}$ S. I change the markings on this tree to read as follows: $\frac{1}{4}$ S 28 B T:

A yellow pine, 18 ins. diam., bears S. 27° W., 59 lks. dist., mkd. $\frac{1}{4}$ S B T. I change the markings on this tree to read as follows: $\frac{1}{4}$ S 29 B T.

North, on true line bet. secs. 28 and 29.

Desc. 30 ft. over rolling land, thru timber.

13.30 Desc. 120 ft. over a N. slope.

21.10 Railroad right of way, bears E. and W.

25.20 End of marked descent; desc. 38 ft. over rolling land.

39.62 The cor. of secs. 20, 21, 28 and 29, which is a lava stone, 12x8x8 ins. above ground, mkd. with 2 notches on the S. face and 4 notches on the E. face.

At point for cor.

Set an iron post, 3 ft. long, 2 ins. diam., 27 ins. in the ground, with the original stone set alongside, for cor. of secs. 20, 21, 28 and 29, with brass cap mkd.

$$\begin{array}{c} \text{T9N} \quad \text{R26E} \\ \text{S } 20 \text{ | S } 21 \\ \text{S } 29 \text{ | S } 28 \\ 1937 \end{array}$$

from which

Original bearing trees:

A yellow pine, 20 ins. diam., bears S. 68° E., 93 lks. dist., mkd. T 9 N R 26 E S 28 B T.

A yellow pine, 20 ins. diam., bears S. $38\frac{3}{4}^{\circ}$ W., 94 lks. dist., markings overgrown; I remark this tree, T 9 N R 26 E S 29 B T.

New bearing trees:

A yellow pine, 24 ins. diam., bears N. $16\frac{1}{2}^{\circ}$ E., 286 lks. dist., mkd. T 9 N R 26 E S 21 B T.

An aspen, 6 ins. diam., bears N. 83° W., 91 lks. dist., mkd. T 9 N R 26 E S 20 B T.

Land, rolling to nearly level:

Soil, sandy loam and rocky, 3d rate.

Timber, yellow pine and aspen; undergrowth, none.

Resurvey of the Subdivisions of T. 9 N., R. 26 E.

Chains

From the cor. of secs. 21, 22, 27 and 28, hereinbefore described.

S. 89° 32' W., on true line bet. secs. 21 and 28.

Desc. 220 ft. over a SW. slope, thru timber.

24.55 Draw, trace of water, 1 ch. wide, course NW.; asc. 30 ft. over an E. slope.

34.05 Thence over nearly level land.

39.59 The point for the $\frac{1}{4}$ sec. cor., as determined from the original bearing trees.

At point for cor.

Set an iron post, 3 ft. long, 1 in. diam., 18 ins. in the ground to underlying rock, and in a mound of stone to top, for $\frac{1}{4}$ sec. cor., with brass cap mkd.

$$\frac{1}{4} \begin{array}{c} S 21 \\ S 28 \\ 1937 \end{array}$$

from which

Original bearing trees:

A yellow pine, 12 ins. diam., dead and fallen, bears N. 48° W., 52 lks. dist., mkd. $\frac{1}{4}$ S B T.

A yellow pine stump, 14 ins. diam., bears S. 46° E. 38 lks. dist., mkd. $\frac{1}{4}$ S B T.

New bearing trees:

A yellow pine, 8 ins. diam., bears N. 61 $\frac{1}{2}$ ° W., 62 lks. dist., mkd. $\frac{1}{4}$ S 21 B T.

A yellow pine, 12 ins. diam., bears S. 44 $\frac{1}{4}$ ° W., 47 lks. dist., mkd. $\frac{1}{4}$ S 28 B T.

From this point the SE. cor. of the Whiting Sawmill shed, bears S. 25° 10' W., 20.05 chs. dist.

S. 89° 44' W., on true line bet. secs. 21 and 28.

Desc. 81 ft. over rolling land, thru timber.

5.30 Traveled road, bears NE. and SW.

24.50 Mineral creek, 3 lks. wide, course NW.; asc. slightly over a NE. slope.

27.30 Toe of spur, slopes N.; desc. 30 ft. over a SW. slope.

40.41 The cor. of secs. 20, 21, 28 and 29.

Land, rolling hills.

Soil; sandy loam and rocky, 3d rate.

Timber, yellow pine and aspen; undergrowth, none.

Resurvey of the Subdivisions of T. 9 N., R. 26 E.

Chains

N. 0° 19' W., on true line bet. secs. 20 and 21.


Desc. 150 ft. over rolling land, thru timber.

1.70. Mineral Creek, 3 lks. wide, course NW.; continue descent over rolling land.

40.07 The $\frac{1}{4}$ sec. cor., which is a lava stone, 16x14x12 ins. above ground, mkd. $\frac{1}{4}$ on W. face.

At point for cor.

Set an iron post, 3 ft. long, 1 in. diam., 12 ins. in the ground to underlying rock, and in a mound of stone to top, with the original stone set alongside, for $\frac{1}{4}$ sec. cor., with brass cap mkd.



from which

Original bearing trees:

A yellow pine, 26 ins. diam., bears N. 64 $\frac{1}{4}$ ° E., 10 lks. dist., markings overgrown, I remark this tree, $\frac{1}{4}$ S 21 B T.

A yellow pine, 10 ins. diam., bears S. 56 $\frac{3}{4}$ ° W., 20 lks. dist., markings illegible. This tree is dead and fallen.

A new bearing tree:

A yellow pine, 20 ins. diam., bears S. 36° W., 71 lks. dist., mkd. $\frac{1}{4}$ S 20 B T.

N. 8° 15' W., on true line bet. secs. 20 and 21.

Desc. 56 ft. along a W. to NW. slope, thru timber.

8.00 Slope changes to N., continue descent.

11.60 Head of draw, course W., 4 chs. dist. to main draw, thence NW.; desc. 30 ft. over the top of a broad spur, slopes NW.


29.30 Desc. 84 ft. over a rocky NE. slope.

33.90 Draw, 50 lks. wide, course NW.; asc. 12 ft. over a SW. slope.

39.72 The cor. of secs. 16, 17, 20 and 21, which is a lava stone, 14x8x6 ins. above ground, mkd. with 3 notches on the S. face and 4 notches on the E. face.

At point for cor.

Set an iron post, 3 ft. long, 2 ins. diam., 27 ins. in the ground, with the original stone set alongside, for cor. of secs. 16, 17, 20 and 21, with brass cap mkd.



Resurvey of the Subdivisions of T. 9 N., R. 26 E.

Chains

from which

Original bearing trees:

A yellow pine, 20 ins. diam., bears N. $12\frac{1}{2}^{\circ}$ E., 16 lks. dist., markings illegible.

A yellow pine, 16 ins. diam., dead and fallen, bears S. $28\frac{1}{4}^{\circ}$ E., 33 lks. dist., markings illegible.

A yellow pine, 24 ins. diam., bears S. $44\frac{3}{4}^{\circ}$ W., 28 lks. dist., markings illegible.

A yellow pine, 18 ins. diam., bears N. $79\frac{1}{4}^{\circ}$ W., 27 lks. dist., markings overgrowth, I remark this tree, T 9 N R 26 E S 17 B T.

New bearing trees:

A yellow pine, 24 ins. diam., bears N. $54\frac{1}{2}^{\circ}$ E., 46 lks. dist., mkd. T 9 N R 26 E S 16 B T.

A yellow pine, 12 ins. diam., bears S. 22° E., 94 lks. dist., mkd. T 9 N R 26 E S 21 B T.

A yellow pine, 24 ins. diam., bears S. $9\frac{1}{2}^{\circ}$ W., 47 lks. dist., mkd. T 9 N R 26 E S 20 B T.

From this point a lava stone, 18x10x9 ins. above ground, mkd. with 3 notches on the S. face and 4 notches on the E. face, bears N. $82^{\circ} 59'$ E., 5.08 chs. dist., from which

A yellow pine, 30 ins. diam., bears N. $27\frac{1}{4}^{\circ}$ E., 59 lks. dist., mkd. T 9 N R 26 E S 16 B T.

A yellow pine stump, 30 ins. diam., bears S. 57° E., 32 lks. dist., markings illegible.

A yellow pine, 18 ins. diam., now dead, bears S. $19\frac{1}{2}^{\circ}$ W., 62 lks. dist., mkd. T 9 N R 26 E S 20 B T.

A yellow pine, 30 ins. diam., bears N. $59\frac{1}{2}^{\circ}$ W., 14 lks. dist., mkd. T 9 N R 26 E S 17 B T.

As this cor. is not of record, I destroy all evidence of same, together with its' accessories.

Land, rolling hills.

Soil, sandy loam and rocky, 3d rate.

Timber, yellow pine and aspen; undergrowth, none.

From the cor. of secs. 15, 16, 21 and 22, hereinbefore described.

N. $89^{\circ} 10'$ W., on true line bet. secs. 16 and 21.

Desc. 34 ft. over rolling land, thru timber.

11.90 Traveled road, bears S. 60° W. and N. 60° E.

39.87 Proportional distance:

Set an iron post, 3 ft. long, 1 in. diam., 18 ins. in the ground to underlying rock, and in a mound of stone to top, for $\frac{1}{4}$ sec. cor., with brass cap mkd.

Resurvey of the Subdivisions of T. 9 N., R. 26 E.

Chains

$$\frac{1}{4} \begin{array}{c} \text{S } 16 \\ \hline \text{S } 21 \\ 1937 \end{array}$$

from which

A yellow pine fork, 12 ins. diam., bears N. $23\frac{1}{2}^{\circ}$ E.,
19 lks. dist., mkd. $\frac{1}{4}$ S 16 B T.

A yellow pine fork, 14 ins. diam., bears S. $63\frac{3}{4}^{\circ}$ W.,
44 lks. dist., mkd. $\frac{1}{4}$ S 21 B T.

- 43.60 Desc. 51 ft. over a W. slope.
- 47.00 Wash, 10 lks. wide, course N.; asc. 49 ft. over an E. slope.
- 54.60 Long spur, slopes N.; desc. 64 ft. over a W. slope.
- 63.00 Old road, bears N. and S.
- 64.70 Head of draw, course N.; asc. 15 ft. over an E. slope.
- 66.40 End of ascent; thence along a N. slope.
- 75.70 Desc. slightly over a W. slope.
- 79.74 The cor. of secs. 16, 17, 20 and 21:
- Land, rolling hills.
Soil, sandy loam and rocky, 3d rate.
Timber, yellow pine; undergrowth, none.

N. $6^{\circ} 40'$ W., on true line bet. secs. 16 and 17.

Along a gentle W. slope, thru timber.

- 3.00 Desc. 51 ft. over a NW. slope.
- 9.75 Enter draw, 1 ch. wide, course N., from SW.
- 15.45 Leave draw, course NE.; desc. 77 ft. over rolling land.
- 40.62 The $\frac{1}{4}$ sec. cor., which is a lava stone, 14x10x10 ins. above ground, mkd. $\frac{1}{4}$ on W.
- At point for cor.
- Set an iron post, 3 ft. long, 1 in. diam., 24 ins. in the ground to underlying rock, and in a mound of stone to top, with the original stone set alongside, for $\frac{1}{4}$ sec. cor., with brass cap mkd.

$$\frac{1}{4} \begin{array}{c} \text{S } 17 \text{ | } \text{S } 16 \\ \hline 1937 \end{array}$$

from which

An original bearing tree:

A yellow pine, 10 ins. diam., now dead, bears S. 81° E., 6 lks. dist., mkd. $\frac{1}{4}$ S B T.

No trace of the original SW. bearing tree.

Resurvey of the Subdivisions of T. 9 N., R. 26 E.

Chains

New bearing trees:

A yellow pine, 12 ins. diam., bears N. $75\frac{1}{2}^{\circ}$ E.,
22 lks. dist., mkd. $\frac{1}{4}$ S 16 B T.

A yellow pine, 10 ins. diam., bears S. 46° W.,
21 lks. dist., mkd. $\frac{1}{4}$ S 17 B T.

N. $0^{\circ} 34'$ W., on true line bet. secs. 16 and 17.

Desc. 157 ft. over rolling land, thru timber.

36.70 Timber becomes smaller and less dense.

40.40 The cor. of secs. 8, 9, 16 and 17, which is a lava stone,
20x10x8 ins. above ground, mkd. with 4 notches on each
of the S. and E. faces.

At point for cor.

Set an iron post, 3 ft. long, 2 ins. diam., 6 ins. in
the ground to underlying rock, and in a mound of stone
to top, with the original stone set alongside, for cor.
of secs. 8, 9, 16 and 17, with brass cap mkd.

| | |
|------|------|
| T9N | R26E |
| S 8 | S 9 |
| S 17 | S 16 |
| 1937 | |

from which

Original bearing trees:

A yellow pine, 14 ins. diam., bears N. 19° E., 72
lks. dist., markings overgrown, I remark this tree,
T 9 N R 26 E S 9 B T.

A yellow pine, 30 ins. diam., now dead, bears S. 2°
E., 142 lks. dist., markings illegible.

A yellow pine, 24 ins. diam., bears S. 43° W., 45
lks. dist., markings overgrown, I remark this tree,
T 9 N R 26 E S 17 B T.

A yellow pine stump, 26 ins. diam., bears N. 71° W.,
140 lks. dist., mkd. T 9 N R 26 E S 8 B T.

New bearing trees:

A yellow pine, 12 ins. diam., bears S. $7\frac{1}{2}^{\circ}$ E., 228
lks. dist., mkd. T 9 N R 26 E S 16 B T.

A yellow pine, 24 ins. diam., bears N. $63\frac{1}{2}^{\circ}$ W., 197
lks. dist., mkd. T 9 N R 26 E S 8 B T.

Land, rolling hills.

Soil, sandy loam and rocky, 3d rate.

Timber, yellow pine, spruce and fir; undergrowth, none.

Resurvey of the Subdivisions of T. 9 N., R. 26 E.

| Chains | |
|--------|--------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| | From the cor. of secs. 9, 10, 15 and 16, hereinbefore described. |
| | N. 89° 24' W., on true line bet. secs. 9 and 16. |
| | Desc. 67 ft. over a NW. slope, thru timber. |
| 8.40 | Wash, 12 ft. wide, 1 ft. deep, course N.; thence along a N. slope. |
| 31.00 | Leave timber, bears N. and S. |
| 32.20 | Wash, 5 ft. wide, course NE. |
| 40.46 | Proportional distance: Set an iron post, 3 ft. long, 1 in. diam., 27 ins. in the ground, and in a mound of stone to top, for $\frac{1}{4}$ sec. cor., with brass cap mkd. |
| | $\begin{array}{r} S \ 9 \\ \frac{1}{4} \hline S \ 16 \\ 1937 \end{array}$ |
| | from which |
| | A yellow pine, 16 ins. diam., bears N. 17 $\frac{1}{2}$ ° W., 326 lks. dist., mkd. $\frac{1}{4}$ S 9 B T. |
| | A yellow pine, 12 ins. diam., bears S. 6° 37' W., 694 chs. dist., mkd. $\frac{1}{4}$ S 16 B T. |
| | Over nearly level land. |
| 68.00 | Small draw, course N. 45° E. |
| 69.00 | Enter timber, bears N. and S. |
| 80.92 | The cor. of secs. 8, 9, 16 and 17. |
| | Land, rolling to nearly level. Soil, gravelly and rocky over sandy loam, 3d rate. Timber, yellow pine; undergrowth, none. |
| | N. 0° 02' W., on true line bet. secs. 8 and 9. |
| | Desc. 163 ft. over a N. slope, thru timber. |
| 10.80 | Traveled road, bears E. and W. |
| 19.30 | Slope changes to NW.; continue descent. |
| 37.70 | Slope changes to N.; continue descent. |
| 40.49 | The $\frac{1}{4}$ sec. cor., which is a lava stone, 12x10x5 ins. above ground, mkd. $\frac{1}{4}$ on W. face. |
| | At point for cor. |
| | Set an iron post, 3 ft. long, 1 in. diam., 24 ins. in the ground to underlying rock, and in a mound of stone to top, with the original stone set alongside, for $\frac{1}{4}$ sec. cor., with brass cap mkd. |

Resurvey of the Subdivisions of T. 9 N., R. 26 E.

Chains

$$\frac{1}{4}$$

| | | |
|------|--|-----|
| S 8 | | S 9 |
| 1937 | | |

from which

A pine, 5 ins. diam., bears N. 87° E., 117 lks. dist., mkd. $\frac{1}{4}$ S 9 B T.

A pine, 6 ins. diam., bears S. $24\frac{1}{2}^{\circ}$ W., 77 lks. dist., mkd. $\frac{1}{4}$ S 8 B T.

Nigger Spring, bears S. 60° W., 2.10 chs. dist., a spring of good water, 3 ft. diam., drains N. 60° E.

N. $0^{\circ} 40'$ W., on true line bet. secs. 8 and 9.

Desc. 160 ft. over a broken N. slope, thru timber.

0.60 Small stream, from Nigger Spring, course NE.

1.00 Traveled road, bears E. and W.

14.00 Leave timber, bears E. and W.

27.20 Wash, 25 lks. wide, 2 ft. deep, course NW., continue to desc. a broken N. slope.

39.88 The cor. of secs. 4, 5, 8 and 9, which is a lava stone, 14x12x10 ins. above ground, mkd. with 5 notches on the S. face and 4 notches on the E. face.

At point for cor.

Set an iron post, 3 ft. long, 2 ins. diam., 8 ins. in the ground to underlying rock, and in a mound of stone, 4 ft. base, 28 ins. high, with the original stone set alongside, for cor. of secs. 4, 5, 8 and 9, with brass cap mkd.

$$\begin{array}{c} \text{T9N} \quad \text{R26E} \\ \text{S 5} \quad | \quad \text{S 4} \\ \hline \text{S 8} \quad | \quad \text{S 9} \\ \text{1937} \end{array}$$

from which

A yellow pine, 6 ins. diam., bears S. $24\frac{1}{2}^{\circ}$ E., 45 lks. dist., mkd. T 9 N R 26 E S 9 B T.

A yellow pine, 6 ins. diam., bears N. $76\frac{3}{4}^{\circ}$ W., 347 lks. dist., mkd. T 9 N R 26 E S 5 B T.

No other suitable bearing trees within limits.

Land, rolling hills.

Soil, sandy loam and rocky, 3d rate.

Timber, yellow pine and scattering juniper on S. $\frac{1}{4}$; undergrowth, none.

From the cor. of secs. 3, 4, 9 and 10, hereinbefore described.

S. $89^{\circ} 46'$ W., on true line bet. secs. 4 and 9.

Resurvey of the Subdivisions of T. 9 N., R. 26 E.

| Chains | |
|--------|---------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| | Asc. slightly over an E. slope. |
| 10.00 | Spur, slopes N.; desc. 147 ft. over a NW. slope. |
| 26.00 | Cut wash, course NW.; thence over rolling land. |
| 26.60 | Kitchen Spring, a spring of good water, 3 ft. diam., bears North, 6.10 chs. dist., drains N. 60° E. |
| 31.10 | Traveled road, bears N. and S. |
| 31.85 | Draw, 1 ch. wide, course N.; asc. 27 ft. over an E. slope. |
| 36.30 | Old road, bears NE. and SW. |
| 40.15 | The $\frac{1}{4}$ sec. cor., which is a lava stone, 16x10x8 ins., above ground, mkd. $\frac{1}{4}$ on N. face. |
| | At point for cor. |
| | Set an iron post, 3 ft. long, 1 in. diam., 18 ins. in the ground to underlying rock, and in a mound of stone, 3 ft. base, 1 $\frac{1}{2}$ ft. high, with the original stone set alongside, for $\frac{1}{4}$ sec. cor., with brass cap mkd. |
| | $\begin{array}{r} S \quad 4 \\ \frac{1}{4} \quad \hline S \quad 9 \\ 1937 \end{array}$ |
| | N. 89° 36' W., on true line bet. secs. 4 and 9. |
| | Desc. 46 ft. over rolling land. |
| 7.10 | 5 strand barbed wire fence, bears N., and S., 3 chs. dist., thence W. |
| 9.57 | From this point: |
| | The SE. cor. of a frame house, bears N. 26° W., 5.19 chs. dist. |
| | The SW. cor. of a barn, bears N. 7 $\frac{1}{4}$ ° E., 815 chs. dist. |
| | A spring of good water, 4 ft. diam., bears N. 17 $\frac{1}{2}$ ° E., 4.29 chs. dist. |
| 10.20 | Traveled road, bears NW. and SE. |
| 40.18 | The cor. of secs. 4, 5, 8 and 9. |
| | Land, rolling hills. |
| | Soil, sandy loam and rocky, 3d rate. |
| | Timber, none; undergrowth, none. |
| | N. 1° 07' E., on true line bet. secs. 4 and 5. |
| | Desc. 106 ft. over rolling land. |
| 19.00 | Old road, bears W. and SE. |
| 35.46 | Draw, trace of water, course NE. |

Resurvey of the Subdivisions of T. 9 N., R. 26 E.

Chains

- 40.10 Barbed wire fence, bears E. and W., 50 lks. dist., thence S.
- 40.67 Proportional distance:
 Set an iron post, 3 ft. long, 1 in. diam., 12 ins. in the ground to underlying rock, and in a mound of stone, 4 ft. base, 2 ft. high, for $\frac{1}{4}$ sec. cor., with brass cap mkd.
- $\frac{1}{4}$
 S 5 | S 4
 1937
- from which
- A yellow pine, 18 ins. diam., bears S. $11\frac{1}{4}^{\circ}$ E., 414 lks. dist., mkd. $\frac{1}{4}$ S 4 B T.
- No other suitable bearing trees within limits.
- Along bottom of a draw, from SE.
- 50.70 Road, bears NW. and SE.
- 53.80 Leave draw, course NW.; asc. 64 ft. over a SW. slope.
- 61.20 Spur, slopes NW.; desc. 93 ft. over a NW. slope.
- 74.45 Cut wash, course NE.; continue over nearly level land.
- 79.82 Same wash, course NW.
- 80.58 The cor. of secs. 4, 5, 32 and 33, on the N. bdy. of the Tp., described in the field notes of the N. bdy. of T. 9 N., R. 26 E., resurveyed under this group.
- Land; rolling hills.
 Soil, sandy loam and rocky; 3d rate.
 Timber, very scattering yellow pine; undergrowth, none.
-
- From the standard cor. of secs. 31 and 32, on the S. bdy. of the Tp., an iron post, 2 ins. diam., 9 ins. above ground, mkd., set and witnessed as described in the official record.
- N. $3^{\circ} 15'$ W., on true line bet. secs. 31 and 32.
- Asc. 312 ft. over a S. slope, thru timber.
- 0.90 Barbed wire fence, bears N. 60° W., and S. 60° E.
- 14.20 Slope changes to SE., continue ascent.
- 23.10 Slope changes to S., continue ascent.
- 29.10 Ridge; at saddle, bears NE. and W.; desc. 260 ft. over a N. slope.
- 38.66 Proportional distance:
 Set an iron post, 3 ft. long, 1 in. diam., 27 ins. in the ground, for $\frac{1}{4}$ sec. cor., with brass cap mkd.

Resurvey of the Subdivisions of T. 9 N., R. 26 E.

Chains

$$\begin{array}{c} \frac{1}{4} \\ \text{S } 31 \mid \text{S } 32 \\ 1937 \end{array}$$

from which

An aspen, 8 ins. diam., bears N. $77\frac{1}{4}^{\circ}$ E., 36 lks. dist., mkd. $\frac{1}{4}$ S 32 B T.

A fir, 6 ins. diam., bears S. $87\frac{3}{4}^{\circ}$ W., 77 lks. dist., mkd. $\frac{1}{4}$ S 31 B T.

Desc. 390 ft. over a N. slope, thru timber.

68.90 End of marked descent; thence over rolling land.

76.70 Railroad right of way, bears E. and W.

77.32 The point for the cor. of secs. 29, 30, 31 and 32, as determined from the original bearing trees.

At point for cor.

Set an iron post, 3 ft. long, 2 ins. diam., 27 ins. in the ground, for cor. of secs. 29, 30, 31 and 32, with brass cap mkd.

$$\begin{array}{c} \text{T9N} \quad \text{R26E} \\ \text{S } 30 \mid \text{S } 29 \\ \text{S } 31 \mid \text{S } 32 \\ 1937 \end{array}$$

from which

Original bearing trees:

A yellow pine, 28 ins. diam., bears S. $52\frac{1}{4}^{\circ}$ E., 31 lks. dist., mkd. T 9 N R 26 E S 32 B T. This tree is now dead.

A yellow pine, 30 ins. diam., bears S. $40\frac{1}{2}^{\circ}$ W., 41 lks. dist., markings overgrown, I remark this tree, T 9 N R 26 E S 31 B T.

A yellow pine stump, 20 ins. diam., bears N. $14\frac{1}{2}^{\circ}$ W., 30 lks. dist., mkd. T 9 N R 26 E S 30 B T.

No trace of the original NE. bearing tree.

New bearing trees:

An aspen, 5 ins. diam., bears N. $44\frac{3}{4}^{\circ}$ E., 40 lks. dist., mkd. T 9 N R 26 E S 29 B T.

A yellow pine, 14 ins. diam., bears N. 75° W., 51 lks. dist., mkd. T 9 N R 26 E S 30 B T.

A yellow pine, 8 ins. diam., bears S. $28\frac{1}{4}^{\circ}$ E., 87 lks. dist., mkd. T 9 N R 26 E S 32 B T.

Land, rolling mountainous.

Soil, sandy loam and rocky, 2nd rate.

Timber, aspen, yellow pine, spruce and fir; undergrowth, none.

Resurvey of the Subdivisions of T. 9 N., R. 26 E.

| Chains | |
|--------|----------------------------------------------------------------------------------------------------------------------------------------------|
| | From the cor. of secs. 28, 29, 32 and 33, hereinbefore described. |
| | S. 88° 46' W., on true line bet. secs. 29 and 32. |
| | Over rolling land. |
| 6.60 | Traveled road, bears NE. and SW. |
| 9.80 | 4 strand barbed wire fence, bears NE. and SW. |
| 45.83 | Proportional distance: Set an iron post, 3 ft. long, 1 in. diam., 26 ins. in the ground, for $\frac{1}{4}$ sec. cor., with brass cap mkd. |
| | $\frac{1}{4} \frac{S\ 29}{S\ 32}$ 1937 |
| | from which |
| | A yellow pine, 18 ins. diam., bears N. 37 $\frac{1}{2}$ ° E., 33 lks. dist., mkd. $\frac{1}{4}$ S 29 B T. |
| | A yellow pine, 14 ins. diam., bears S. 35° W., 10 lks. dist., mkd. $\frac{1}{4}$ S 32 B T. |
| | Continue over rolling land, thru timber. |
| 60.70 | Traveled road, bears NW. and SE. |
| 91.66 | The cor. of secs. 29, 30, 31 and 32. |
| | Land, rolling. Soil, sandy loam and rocky, 2nd and 3d rate. Timber, yellow pine, aspen and fir; undergrowth, none. |
| | N. 86° 06' W., on true line bet. secs. 30 and 31. |
| | Over rolling land, thru timber. |
| 6.30 | Railroad right of way, bears NE. and SW. |
| 18.10 | 4 strand barbed wire fence, bears N. and S. |
| 25.00 | Leave timber, bears NW. and SE. |
| 37.89 | Proportional distance: Set an iron post, 3 ft. long, 1 in. diam., 26 ins. in the ground, for $\frac{1}{4}$ sec. cor., with brass cap mkd. |
| | $\frac{1}{4} \frac{S\ 30}{S\ 31}$ 1937 |
| | from which |
| | A yellow pine, 14 ins. diam., bears N. 22 $\frac{1}{2}$ ° W., 200 lks. dist., mkd. $\frac{1}{4}$ S 30 B T. |
| | Raise a mound of stone, 3 ft. base, 2 ft. high, N. of cor. |
| | From this point, an old frame house bears S. 70 $\frac{1}{2}$ ° W. |

Resurvey of the Subdivisions of T. 9 N., R. 26 E.

Chains

Over rolling land.

58.50 Silver Creek, dry, 10 lks. wide, course N.

75.96 The cor. of secs. 25, 30, 31 and 36, on the W. bdy. of the Tp., which is an iron post, 3 ins. diam., 10 ins. above ground, mkd., set and witnessed as described in the official record.

From this point, an old frame house bears S. 6° E.

Land, rolling.

Soil, sandy loam and rocky, 3d rate.

Timber, yellow pine and aspen on E. $\frac{1}{2}$ mile; undergrowth, none.

Return to the cor. of secs. 29, 30, 31 and 32.

N. 0° 22' W., on true line bet. secs. 29 and 30.

Over rolling land, thru timber.

6.05 Old road and new railroad right of way, bears N. 70° E., and S. 60° W.

23.90 4 strand barbed wire fence, bears E. and W.

35.00 Asc. 46 ft. over a S. slope.

40.59 The $\frac{1}{4}$ sec. cor., which is a sandstone, 14x10x3 ins. above ground, mkd. $\frac{1}{4}$ on W. face.

At point for cor.

Set an iron post, 3 ft. long, 1 in. diam., 27 ins. in the ground, with the original stone set alongside, for $\frac{1}{4}$ sec. cor., with brass cap mkd.

$\frac{1}{4}$
 S 30 | S 29
 1937

from which

An original bearing tree:

A yellow pine, 18 ins. diam., bears N. 47 $\frac{1}{2}$ ° E., 81 lks. dist., markings overgrown.

No trace of the original SW. bearing tree.

New bearing trees:

A yellow pine, 8 ins. diam., bears N. 55 $\frac{1}{4}$ ° E., 31 lks. dist., mkd. $\frac{1}{4}$ S 29 B T.

A yellow pine, 12 ins. diam., bears S. 13 $\frac{1}{2}$ ° W., 68 lks. dist., mkd. $\frac{1}{4}$ S 30 B T.

From this point the center of Harris Lake, 12 chs. long, 4 chs. wide, lying NW. and SE., bears N. 75° W., 7 chs. dist.; this lake has no definite inlet and no visible outlet.

Resurvey of the Subdivisions of T. 9 N., R. 26 E.

Chains N. $0^{\circ} 33'$ E., on a true line bet. secs. 29 and 30.
Asc. 156 ft. over a S. slope, thru timber.

12.80 Slope changes to SE.; continue ascent.

17.80 Ridge, bears NW. and SE.; desc. 52 ft. over a NE. slope.

21.20 Thence along a broken W. slope.

22.50 4 strand barbed wire fence, bears E. and W.

25.10 Desc. 240 ft. over a N. slope.

34.90 Draw, course NE., continue descent.

39.58 The point for the cor. of secs. 19, 20, 29 and 30, as determined from the original bearing trees.

At point for cor.

Set an iron post, 3 ft. long, .2 ins. diam., 28 ins. in the ground, for cor. of secs. 19, 20, 29 and 30, with brass cap mkd.

| | |
|------|------|
| T9N | R26E |
| S 19 | S 20 |
| S 30 | S 29 |
| 1937 | |

from which

Original bearing trees:

A yellow pine, 30 ins. diam., bears N. $30\frac{1}{2}^{\circ}$ E., 46 lks. dist., mkd. T 9 N R 26 E S 20 B T.

A fir, 24 ins. diam., bears S. 16° E., 52 lks. dist., markings overgrown, I remark this tree, T 9 N R 26 E S 29 B T.

An aspen stump, 8 ins. diam., bears S. 46° W., 41 lks. dist., markings decayed.

A pine, 8 ins. diam., bears N. 25° W., 49 lks. dist., markings overgrown, I remark this tree, T 9 N R 26 E S 19 B T.

A new bearing tree:

A fir, 16 ins. diam., bears S. $66\frac{1}{2}^{\circ}$ W., 42 lks. dist., mkd. T 9 N R 26 E S 30 B T.

Land, rolling mountainous.
Soil, sandy loam and rocky, 2nd rate.
Timber, yellow pine, aspen, fir and spruce; undergrowth, none.

From the cor. of secs. 20, 21, 28 and 29, hereinbefore described.

S. $88^{\circ} 50'$ W., on true line bet. secs. 20 and 29.

Asc. slightly over a NE. slope, thru timber.

2.20 End of ascent, thence over a low spur, slopes SW.

Resurvey of the Subdivisions of T. 9 N., R. 26 E.

| Chains | |
|--------|------------------------------------------------------------------------------------------------------------------------------------|
| 19.20 | Desc. slightly over a W. slope. |
| 21.50 | Draw, course NW.; asc. 125 ft. over an E. slope. |
| 28.95 | Ridge, bears NE. and SW.; desc. 161 ft. over a NW. slope. |
| 45.29 | Proportional distance: |
| | Set an iron post, 3 ft. long, 1 in. diam., 27 ins. in the ground, for $\frac{1}{4}$ sec. cor., with brass cap mkd. |
| | $\frac{1}{4} \frac{S 20}{S 29}$ 1937 |
| | from which |
| | A yellow pine, 10 ins. diam., bears S. $2\frac{3}{4}^{\circ}$ E., 98 lks. dist., mkd. $\frac{1}{4}$ S 29 B T. |
| | A yellow pine, 10 ins. diam., bears N. $54\frac{3}{4}^{\circ}$ W., 48 lks. dist., mkd. $\frac{1}{4}$ S 20 B T. |
| | Over swampy bottom land, thru timber. |
| 47.90 | A seep spring, bears N., 50 lks. dist. |
| 52.40 | Leave swamp and continue over rolling land. |
| 58.40 | Desc. 66 ft. over a rocky SW. slope. |
| 61.80 | Draw; 1 ch. wide, stream 1 lk. wide, course N.; asc. 93 ft. over a NE. slope. |
| 90.58 | The cor. of secs. 19, 20, 29 and 30. |
| | Land, rolling hills. Soil, rocky over sandy loam, 3d rate. Timber, yellow pine, fir, aspen and jack pine; undergrowth, none. |
| | N. $85^{\circ} 44'$ W., on true line bet. secs. 19 and 30. |
| | Asc. 25 ft. over a NE. slope, thru timber. |
| 4.30 | Desc. 35 ft. over a NW. slope. |
| 9.70 | Side hill draw, course N.; asc. 47 ft. over a NE. slope. |
| 12.65 | Desc. 170 ft. over a NW. slope. |
| 37.26 | Proportional distance: |
| | Set an iron post, 3 ft. long, 1 in. diam., 27 ins. in the ground, for $\frac{1}{4}$ sec. cor., with brass cap mkd. |
| | $\frac{1}{4} \frac{S 19}{S 30}$ 1937 |
| | from which |

Resurvey of the Subdivisions of T. 9 N., R. 26 E.

Chains

A yellow pine, 14 ins. diam., bears N. $63\frac{1}{2}^{\circ}$ W.,
49 lks. dist., mkd. $\frac{1}{4}$ S 19 B T.

A yellow pine, 16 ins. diam., bears S. $82\frac{1}{4}^{\circ}$ W.,
18 lks. dist., mkd. $\frac{1}{4}$ S 30 B T.

Desc. 42 ft. over rolling land.

59.00 4 strand barbed wire fence, bears NW. and SE.

62.50 Old road, bears N. and S.

75.38 The cor. of secs. 19, 24, 25 and 30, on the W. bdy. of
the Tp., described in the field notes of the W. bdy. of
T. 9 N., R. 26 E., resurveyed under this group.

Land, rolling hills.

Soil, sandy loam and rocky, 3d rate.

Timber, yellow pine, fir and aspen; undergrowth, none.

From the cor. of secs. 19, 20, 29 and 30.
N. $0^{\circ} 08'$ E., on true line bet. secs. 19 and 20.

Desc. 210 ft. over a N. slope, thru timber.

40.38 The $\frac{1}{4}$ sec. cor., which is a lava stone, 10x10x6 ins.
above ground, mkd. $\frac{1}{4}$ on W. face.

At point for cor.

Set an iron post, 3 ft. long, 1 in. diam., 27 ins. in
the ground, with the original stone set alongside, for
 $\frac{1}{4}$ sec. cor., with brass cap mkd.

$\frac{1}{4}$
S 19 | S 20
1937

from which

Original bearing trees:

A yellow pine stump, 24 ins. diam., bears S. 79° E.,
89 lks. dist., markings destroyed by fire.

A yellow pine, 36 ins. diam., bears S. 75° W., 38
lks. dist., markings illegible, I remark this tree,
 $\frac{1}{4}$ S 19 B T.

A new bearing tree:

A yellow pine, 14 ins. diam., bears S. $39\frac{1}{4}^{\circ}$ E.,
77 lks. dist., mkd. $\frac{1}{4}$ S 20 B T.

N. $0^{\circ} 16'$ W., on true line bet. secs. 19 and 20.

Over nearly level land, thru timber:

10.00 Desc. 50 ft. over a NE. slope.

18.40 Draw, 50 lks. wide, course NW.; asc. slightly over a SW.
slope.

22.20 Short spur, slopes W.; desc. slightly over a NW. slope.

Resurvey of the Subdivisions of T. 9 N., R. 26 E.

Chains

- 23.70 Draw, 30 lks. wide, course SW.; asc. 27 ft. over a SE. slope.
- 26.75 Thence over rolling land.
- 40.42 The cor. of secs. 17, 18, 19 and 20, which is a lava stone, 18x10x10 ins. above ground, mkd. with 5 notches on the E. face and 3 notches on the S. face.

At point for cor.

Set an iron post, 3 ft. long, .2 ins. diam., 26 ins. in the ground, with the original stone set alongside, for cor. of secs. 17, 18, 19 and 20, with brass cap mkd.

| | |
|------|------|
| T9N | R26E |
| S 18 | S 17 |
| S 19 | S 20 |
| 1937 | |

from which

Original bearing trees:

A yellow pine, 24 ins. diam., bears N. 81° E.,
36 lks. dist., mkd. T 9 N R 26 E S 17 B T.

A yellow pine, 14 ins. diam., bears S. 65½° W., 50
lks. dist., mkd. T 9 N R 26 E S 19 B T.

A yellow pine, 20 ins. diam., bears N. 3° W.,
86 lks. dist., mkd. T 9 N R 26 E S 18 B T.

No trace of the original SE. bearing tree.

A new bearing tree:

A yellow pine, 18 ins. diam., bears S. 38½° E.,
41 lks. dist., mkd. T 9 N R 26 E S 20 B T.

Land, rolling hills.

Soil, sandy loam and rocky, 2nd rate.

Timber, yellow pine, fir and spruce; undergrowth, none.

From the cor. of secs. 16, 17, 20 and 21, hereinbefore described.

S. 89° 44' W., on true line bet. secs. 17 and 20.

Desc. 40 ft. over a W. slope, thru timber.

2.10 Draw, course N., asc. 54 ft. over a NE. slope.

6.80 End of ascent, thence over top of spur, slopes N.

16.75 Small draw, course NW.; asc. 71 ft. over a NE. slope.

39.90 Low spur, slopes N. 10° W.; desc. 59 ft. over a W. slope.

42.39 Proportional distance:

Set an iron post, 3 ft. long, 1 in. diam., 27 ins. in the ground, for ¼ sec. cor., with brass cap mkd.

Resurvey of the Subdivisions of T. 9 N., R. 26 E.

Chains

$\frac{1}{4}$ $\frac{S\ 17}{S\ 20}$
 1937

from which

A yellow pine, 16 ins. diam., bears S. 62° W.,
66 lks. dist., mkd. $\frac{1}{4}$ S 20 B T.

A fir, 12 ins. diam., bears N. 16 $\frac{3}{4}$ ° E., 44 lks.
dist., mkd. $\frac{1}{4}$ S 17 B T.

46.20 Stream, 1 lk. wide, course N.; asc. 35 ft. over an E.
slope.

49.00 Rocky spur, slopes N.; desc. 42 ft. over a NW. slope.
5 lks. wide, 4 ins. deep,

53.10 Mineral Creek, course NW.; asc. slightly over a NE. slope.

56.00 Thence desc. 30 ft. over rolling land.

84.78 The cor. of secs. 17, 18, 19 and 20.

Land, rolling hills.
Soil, sandy loam and rocky, 3d rate.
Timber, yellow pine and some aspen and fir; undergrowth,
none.

S. 89° 33' W., on true line bet. secs. 18 and 19.
Over rolling land, thru timber.

5.00 Desc. 100 ft. over a W. to SW. slope.

14.20 Draw, 50 lks. wide, course NW.; asc. 37 ft. over a NE.
slope.

21.80 Spur, slopes NW.; desc. 52 ft. over a W. slope.

40.19 The $\frac{1}{4}$ sec. cor., which is a lava stone, 21x18x14 ins.
above ground, mkd. $\frac{1}{4}$ on N. face.

At point for cor.

Set an iron post, 3 ft. long, 1 in. diam., 24 ins. in
the ground to underlying rock, and in a mound of stone
to top, with the original stone set alongside, for $\frac{1}{4}$
sec. cor., with brass cap mkd.

$\frac{1}{4}$ $\frac{S\ 18}{S\ 19}$
 1937

from which

Original bearing trees:

A yellow pine, 8 ins. diam., bears S. 15° E., 52
lks. dist., mkd. $\frac{1}{4}$ S B T.

A yellow pine, 36 ins. diam., now dead, bears N. 44°
W., 50 lks. dist., markings destroyed by fire.

New bearing trees:

Resurvey of the Subdivisions of T. 9 N., R. 26 E.

Chains

A yellow pine, 8 ins. diam., bears S. $23\frac{1}{2}^{\circ}$ E.,
38 lks. dist., mkd. $\frac{1}{4}$ S 19 B T.

A yellow pine, 10 ins. diam., bears N. $60\frac{1}{4}^{\circ}$ W.,
90 lks. dist., mkd. $\frac{1}{4}$ S 18 B T.

N. $80^{\circ} 18'$ W., on true line bet. secs. 18 and 19.

Desc. 87 ft. over rolling land, thru timber.

15.85 Draw, 1 ch. wide, course NW.

34.97 The cor. of secs. 13, 18, 19 and 24, on the W. bdy. of
the Tp., described in the field notes of the W. bdy. of T.
9 N., R. 26 E., resurveyed under this group.

Land, rolling hills.

Soil, sandy loam and rocky, 3d rate.

Timber, yellow pine; undergrowth, none.

Return to the cor. of secs. 17, 18, 19 and 20.

N. $2^{\circ} 33'$ W., on true line bet. secs. 17 and 18.

Desc. 60 ft. over rolling land, thru timber.

18.40 Desc. 80 ft. over a NW. slope.

23.00 Draw, 1 ch. wide, course NE.; asc. slightly over a SE.
slope.

26.50 Spur, slopes NE., desc. 100 ft. over a NW. slope.

41.90 The $\frac{1}{4}$ sec. cor., which is a lava stone, 14x12x4 ins.,
set in a small mound of stone, mkd. $\frac{1}{4}$ on W. face.

At point for cor.

Set an iron post, 3 ft. long, 1 in. diam., 20 ins. in
the ground to underlying rock, and in a mound of stone
to top, with the original stone set alongside, for
 $\frac{1}{4}$ sec. cor., with brass cap mkd.

$\frac{1}{4}$
S 18 | S 17
1937

from which

An original bearing tree:

A yellow pine, 20 ins. diam., now dead, bears
S. $28\frac{1}{4}^{\circ}$ E., 54 lks. dist., mkd. $\frac{1}{4}$ S B T.

No trace of the original SW. bearing tree.

New bearing trees:

A yellow pine, 20 ins. diam., bears N. $87\frac{1}{4}^{\circ}$ E.,
54 lks. dist., mkd. $\frac{1}{4}$ S 17 B T.

A yellow pine, 10 ins. diam., bears N. $76\frac{1}{4}^{\circ}$ W.,
21 lks. dist., mkd. $\frac{1}{4}$ S 18 B T.

Resurvey of the Subdivisions of T. 9 N., R. 26 E.

Chains

N. 0° 24' E., on true line bet. secs. 17 and 18.

Desc. 140 ft. over a NW. slope, thru timber.

34.20 Stream, 8 lks. wide, 6 ins. deep, course NW.

39.68 The cor. of secs. 7, 8, 17 and 18, which is a lava stone, 12x10x8 ins. above ground, mkd. with 4 notches on the S. face and 5 notches on the E. face.

At point for cor.

Set an iron post, 3 ft. long, 2 ins. diam., 12 ins. in the ground to underlying rock, and in a mound of stone to top, with the original stone set alongside, for cor. of secs. 7, 8, 17 and 18, with brass cap mkd.

| | |
|------------|-------|
| T9N. R26E. | |
| S 7 | S 8 |
| S 18 | S 17. |
| 1937 | |

from which

Original bearing trees:

A yellow pine, 20 ins. diam., bears N. 59½° E., 39 lks. dist., markings overgrown.

A yellow pine, 36 ins. diam., dead and fallen, bears S. 40° W., 58 lks. dist., mkd. T 9 N R 26 E S 18 B T.

A yellow pine stump, 24 ins. diam., bears N. 12½° W., 45 lks. dist., mkd. T 9 N R 26 E S 7 B T.

New bearing trees:

A yellow pine, 18 ins. diam., bears N. 69° E., 74 lks. dist., mkd. T 9 N R 26 E S 8 B T.

A yellow pine, 30 ins. diam., bears S. 42½° E., 175 lks. dist., mkd. T 9 N R 26 E S 17 B T.

No other suitable bearing trees available.

Land, rolling hills.

Soil, sandy loam and rocky, 2nd rate.

Timber, yellow pine and fir; undergrowth, none.

From the cor. of secs. 8, 9, 16 and 17, hereinbefore described.

N. 89° 38' W., on true line bet. secs. 8 and 17.

Over rolling land, thru timber.

40.27 The ¼ sec. cor., which is a lava stone, 14x12x10 ins. above ground, mkd. ¼ on N. face.

At point for cor.

Set an iron post, 3 ft. long, 1 in. diam., 24 ins. in the ground to underlying rock, and in a mound of stone to top, with the original stone set alongside, for ¼ sec. cor., with brass cap mkd.

Resurvey of the Subdivisions of T. 9 N., R. 26 E.

Chains

$$\frac{1}{4} \frac{S \ 8}{S \ 17}$$

1937

from which

Original bearing trees:

A yellow pine, 18 ins. diam., bears N. $54\frac{1}{2}^\circ$ W.,
101 lks. dist., mkd. $\frac{1}{4}$ S B T.

A yellow pine, 26 ins. diam., now dead, bears
S. $70\frac{3}{4}^\circ$ E., 64 lks. dist., mkd. $\frac{1}{4}$ S B T.

New bearing trees:

A yellow pine, 28 ins. diam., bears N. $35\frac{1}{2}^\circ$ E.,
41 lks. dist., mkd. $\frac{1}{4}$ S 8 B T.

A yellow pine, 26 ins. diam., bears S. 39° W.,
89 lks. dist., mkd. $\frac{1}{4}$ S 17 B T.

N. $89^\circ 46'$ W., on true line bet. secs. 8 and 17.

Desc. 30 ft. over a W. slope, thru timber.

7.70 Draw, 50 lks. wide, course N.; asc. slightly over an E.
slope.

10.00 End of ascent, thence over nearly level land.

20.00 Desc. 62 ft. over a rolling W. slope.

41.03 The cor. of secs. 7, 8, 17 and 18.

Land, rolling hills.

Soil, sandy loam and rocky, 3d rate.

Timber, yellow pine and jack pine; undergrowth, none.

N. $89^\circ 25'$ W., on true line bet. secs. 7 and 18.

Over rolling land, thru timber.

4.10 Mineral Creek, 5 lks. wide, course N.

22.90 A spring of good water, bears S., 50 lks. dist.

25.00 Enter swamp, bears N. and S.

35.00 Leave swamp, bears N. and S., continue over rolling land.

40.05 The $\frac{1}{4}$ sec. cor., which is a lava stone, 14x10x6 ins.
above ground, mkd. $\frac{1}{4}$ on N. face.

At point for cor.

Set an iron post, 3 ft. long, 1 in. diam., 18 ins. in
the ground to underlying rock, and in a mound of stone
to top, with the original stone set alongside, for
 $\frac{1}{4}$ sec. cor., with brass cap mkd.

$$\frac{1}{4} \frac{S \ 7}{S \ 18}$$

1937

Resurvey of the Subdivisions of T. 9 N., R. 26 E.

Chains

from which

An original bearing tree:

A yellow pine, 18 ins. diam., bears S. $41\frac{1}{2}^{\circ}$ W.,
126 lks. dist., markings overgrown, I remark this
tree, $\frac{1}{4}$ S 18 B T.

A new bearing tree:

A jack pine, 10 ins. diam., bears N. $40\frac{1}{2}^{\circ}$ E., 174
lks. dist., mkd. $\frac{1}{4}$ S 7 B T.

N. $81^{\circ} 40'$ W., on true line bet. secs. 7 and 18.

Desc. 90 ft. over rolling land, thru timber.

33.03 4 strand barbed wire fence, bears N. and S.

33.14 The cor. of secs. 7, 12, 13 and 18, on the W. bdy. of
the Tp., described in the field notes of the W. bdy.
of T. 9 N., R. 26 E., resurveyed under this group.

Land, rolling hills.

Soil, sandy loam and rocky, 3d rate.

Timber, yellow pine and jack pine; undergrowth, none.

Return to the cor. of secs. 7, 8, 17 and 18.

N. $0^{\circ} 26'$ E., on true line bet. secs. 7 and 8.

Desc. 78 ft. over rolling land, thru timber.

32.60 Desc. 50 ft. over a NE. slope.

37.50 Draw, 1 ch. wide, course winding N., continue along
bottom of same.39.93 Set an iron post, 3 ft. long, 1 in. diam., 27 ins. in
the ground, for witness $\frac{1}{4}$ sec. cor., with brass cap mkd.

W. C

 $\frac{1}{4}$

S. 7 | S 8

1937

39.95 The $\frac{1}{4}$ sec. cor., which is a yellow pine, 16 ins. diam.,
mkd. $\frac{1}{4}$ S on W. face, from which

Original bearing trees:

A yellow pine, 14 ins. diam., bears N. $31\frac{3}{4}^{\circ}$ E., 18
lks. dist., markings overgrown, I remark this tree,
 $\frac{1}{4}$ S 8 B T.

A yellow pine, 30 ins. diam., bears S. $64\frac{1}{2}^{\circ}$ W., 108
lks. dist., markings overgrown, I remark this tree,
 $\frac{1}{4}$ S 7 B T.

N. $0^{\circ} 02'$ E., on true line bet. secs. 7 and 8.

Over rolling land, thru timber.

Resurvey of the Subdivisions of T. 9 N., R. 26 E.

| | | | | | | | | | |
|--------|-------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|-----|------|-----|-----|-----|-----|------|--|
| Chains | | | | | | | | | |
| 1.00 | Draw, 1 ch. wide, course NE. | | | | | | | | |
| 6.00 | Same draw, course NW. | | | | | | | | |
| 20.00 | Desc. 96 ft. over a NW. slope. | | | | | | | | |
| 30.00 | Leave timber, bears E. and W.; continue over rolling land. | | | | | | | | |
| 36.60 | Draw, 1 ch. wide, course NE. | | | | | | | | |
| 40.21 | The cor. of secs. 5, 6, 7 and 8, which is a lava stone, 10x8x8 ins. above ground, mkd. with 5 notches on each of the S. and E. faces. | | | | | | | | |
| | At point for cor. | | | | | | | | |
| | Set an iron post, 3 ft. long, 2 ins. diam., 6 ins. in the ground to underlying rock, and in a mound of stone to top, with the original stone set alongside, for cor. of secs. 5, 6, 7 and 8, with brass cap mkd. | | | | | | | | |
| | <table border="1" style="margin-left: auto; margin-right: auto;"> <tr> <td>T9N</td> <td>R26E</td> </tr> <tr> <td>S 6</td> <td>S 5</td> </tr> <tr> <td>S 7</td> <td>S 8</td> </tr> <tr> <td colspan="2" style="text-align: center;">1937</td> </tr> </table> | T9N | R26E | S 6 | S 5 | S 7 | S 8 | 1937 | |
| T9N | R26E | | | | | | | | |
| S 6 | S 5 | | | | | | | | |
| S 7 | S 8 | | | | | | | | |
| 1937 | | | | | | | | | |
| | from which | | | | | | | | |
| | An original bearing tree: | | | | | | | | |
| | A yellow pine, 18 ins. diam., bears N. 51 $\frac{1}{2}$ ° E., 145 lks. dist., mkd. T 9 N R 26 E S 5 B T. | | | | | | | | |
| | No trace of the other original bearing trees. | | | | | | | | |
| | New bearing trees: | | | | | | | | |
| | A yellow pine, 30 ins. diam., bears S. 66 $\frac{1}{2}$ ° E.; 162 lks. dist., mkd. T 9 N R 26 E S 8 B T. | | | | | | | | |
| | A yellow pine, 28 ins. diam., bears S. 74 $\frac{3}{4}$ ° W.; 159 lks. dist., mkd. T 9 N R 26 E S 7 B T. | | | | | | | | |
| | A yellow pine, 30 ins. diam., bears N. 56 $\frac{1}{2}$ ° W., 208 lks. dist., mkd. T 9 N R 26 E S 6 B T. | | | | | | | | |
| | Land, rolling hills. Soil, sandy loam and rocky, 3d rate. Timber, yellow pine, jack pine, and fir; undergrowth, none. | | | | | | | | |
| | From the cor. of secs. 4, 5, 8 and 9, hereinbefore described. | | | | | | | | |
| | N. 89° 44' W., on true line bet. secs. 5 and 8. | | | | | | | | |
| | Over rolling land. | | | | | | | | |
| 8.20 | Draw, course NE. | | | | | | | | |
| 16.50 | Draw, course N.; asc. 52 ft. over an E. slope. | | | | | | | | |
| 20.10 | 4 strand barbed wire fence, bears N. and S. | | | | | | | | |
| 27.90 | The NE. cor. of a frame house, bears S. 11° 26' W.; end of ascent, continue over rolling land. | | | | | | | | |

Resurvey of the Subdivisions of T. 9 N., R. 26 E.

Chains

- 30.67 The NE. cor. of the same house bears S. 4° 02' W.; continue over rolling land.
- 33.09 Traveled road, bears NW. and SE.
- 40.05 The $\frac{1}{4}$ sec. cor., which is a lava stone, 8x8x5 ins. above ground, mkd. $\frac{1}{4}$ on N. face.

At point for cor.

Set an iron post, 3 ft. long, 1 in. diam., 24 ins. in the ground to underlying rock, and in a mound of stone 2 ft. base, 1 ft. high, with the original stone set alongside, for $\frac{1}{4}$ sec. cor., with brass cap mkd.

$$\frac{1}{4} \begin{array}{r} S \ 5 \\ \hline S \ 8 \\ 1937 \end{array}$$

S. 89° 45' W., on true line bet. secs. 5 and 8.

Over rolling land.

- 2.10 Traveled road, bears NW. and SE.
- 18.30 4 strand barbed wire fence, bears N. and S.
- 27.00 Desc. 45 ft. over a SW. slope.
- 32.80 Cut wash, course NW.; asc. 7 ft. over a NW. slope.
- 40.34 The cor. of secs. 5, 6, 7 and 8.

Land, rolling hills.

Soil, sandy loam and rocky, 3d rate.

Timber, none; undergrowth, none.

N. 89° 46' W., on true line bet. secs. 6 and 7.

Over rolling land.

- 40.14 The $\frac{1}{4}$ sec. cor., which is a lava stone, 10x8x4 ins. above ground, mkd. $\frac{1}{4}$ on N. face.

At point for cor.

Set an iron post, 3 ft. long, 1 in. diam., 8 ins. in the ground to underlying rock, and in a mound of stone, 3 ft. base, 2 $\frac{1}{2}$ ft. high, with the original stone set alongside, for $\frac{1}{4}$ sec. cor., with brass cap mkd.

$$\frac{1}{4} \begin{array}{r} S \ 6 \\ \hline S \ 7 \\ 1937 \end{array}$$

from which

A yellow pine, 4 ins. diam., bears N. 64 $\frac{1}{2}$ ° W., 174 lks. dist., mkd. $\frac{1}{4}$ S 6 B T.

A juniper fork, 3 ins. diam., bears S. 36 $\frac{1}{2}$ ° W., 62 lks. dist., mkd. B T.

Resurvey of the Subdivisions of T. 9 N., R. 26 E.

| Chains | |
|--------|----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| | N. 82° 21' W., on true line bet. secs. 6 and 7. Over rolling land. |
| 10.70 | Ditch, 5 lks. wide, 8 ins. deep, course NW.; enter timber, bears E. and W. |
| 14.40 | Mineral Creek, 5 lks. wide, course NW. |
| 21.25 | Draw, course NW.; asc. 22 ft. over an E. slope. |
| 23.30 | End of ascent; desc. 30 ft. over rolling land. |
| 34.30 | 4 strand barbed wire fence, bears NE. and SW. |
| 35.18 | The cor. of secs. 1, 6, 7 and 12, on the W. bdy. of the Tp., described in the field notes of the W. bdy. of T. 9 N., R. 26 E., resurveyed under this group. Land, rolling hills. Soil, sandy loam and rocky, 3d rate. Timber, scattering oak and jack pine; undergrowth, none. |
| | Return to the cor. of secs. 5, 6, 7 and 8. N. 0° 08' W., on true line bet. secs. 5 and 6. Over rolling land, thru scattering timber: |
| 13.90 | Stream, 4 lks. wide, course NW. |
| 40.32 | The $\frac{1}{4}$ sec. cor., which is a lava stone, 16x12x10 ins. above ground, mkd. $\frac{1}{4}$ on W. face. At point for cor. Set an iron post, 3 ft. long, 1 in. diam., 6 ins. in the ground to underlying rock, and in a mound of stone to top, with the original stone set alongside, for $\frac{1}{4}$ sec. cor., with brass cap mkd. $\begin{array}{c} \frac{1}{4} \\ S\ 6\ \ S\ 5 \\ 1937 \end{array}$ from which A juniper fork, 5 ins. diam., bears S. 69° E., 179 lks. dist., mkd. $\frac{1}{4}$ S 5 B T. A pine; 4 ins. diam., bears S. 40 $\frac{1}{2}$ ° W., 121 lks. dist., mkd. $\frac{1}{4}$ S 6 B T. |
| | N. 0° 42' E., on true line bet. secs. 5 and 6. Desc. 124 ft. over rolling land. |
| 15.06 | 4 strand barbed wire fence, bears NW. and SE. |
| 17.80 | Traveled road, bears NW. and SE. |
| 40.30 | The cor. of secs. 5, 6, 31 and 32, on the N. bdy. of the Tp., described in the field notes of the N. bdy. of T. 9 N., R. 26 E., resurveyed under this group. Land, rolling. Soil, sandy loam and very rocky, 3d and 4th rate. Timber, scattering juniper; undergrowth, none. |

Resurvey of the Subdivisions of T. 9 N., R. 26 E.

Final tests of solar attachments of Buff and Buff solar transits Nos. 23,829 and 18,002, and Young and Sons solar transit No. 8541.

July 7, 1937: In camp in the SE. $\frac{1}{4}$ of sec. 15, T. 9 N., R. 26 E., at 8 a.m., l.m.t., $34^{\circ} 10\frac{1}{2}'$ N., was set off on the lat. arcs; and $22^{\circ} 36'$ N. on the decl. arcs. The line of site of each transit agreed with the meridian established by Polaris observation.

At 4 p.m., l.m.t., $34^{\circ} 10\frac{1}{2}'$ N., was set off on the lat. arcs, and $22^{\circ} 34'$ N. on the decl. arcs. The line of site of each transit agreed with the meridian established by Polaris observation.

General Description.

The soil in most of this township is a loose sandy loam, rocky over nearly the entire township, and especially so in the northern portion. The general elevation of the township is from about 8000 to 9000 ft. above sea level. Most of the township is rolling hills to nearly level, with a few barren buttes in the northern portion, and a few rounded hills in the southern portion, which stand out above the surrounding country. Except for the northernmost portion, the township is covered with timber, mostly yellow pine with some fir, aspen, spruce and juniper. The entire township is within the Fort Apache National Forest.

There are no large streams within the township, but there are several small streams and some springs of good water, making water very accessible throughout the township for live stock purposes.

Cattle grazing is the principal industry, most of the township is covered with a good stand of native grass.

The Whiting Saw Mill lies in sec. 28, and is in operation; much of the timber is of a size suitable for lumber. Temporary railroads are in various stages of construction, to be used for the purpose of hauling the logs to the mill, and the lumber to market.

There are several roads in the township, which make nearly every part of the township accessible by auto during the summer months.

There is no evidence of mineral deposits within the township.

Springerville is the most accessible town and trading point; it is a town of about 600 population, and lies about 30 miles to the east of the township. There is no railroad in Springerville, mail and supplies are brought there from Holbrook, Arizona, by motor bus and truck.

91
67

FIELD ASSISTANTS

| NAMES | CAPACITY |
|----------------------|----------------------|
| Norton B. Stephenson | Principal Assistant. |
| Clark Blevins | Principal Assistant. |
| Ellis W. Murphy | Chainman. |
| Herbert Qualls | Chainman. |
| Bithel L. Sizemore | Flagman. |
| John W. Henry | Flagman. |
| A. C. Terry | Axman. |
| Ray W. Hammack | Axman. |
| William J. Martin | Axman. |
| Paschal Austin | Axman. |
| Wesley R. Farley | Axman. |
| Raymond S. Davis | Moundsman. |
| Edwin Forbes Gutzman | Moundsman. |
| | |
| | |
| | |
| | |
| | |

92
64

BOOK 1180

CERTIFICATE OF ~~UNITED STATES~~ SURVEYOR

We, Roger F. Wilson, F. Wayne Forrest
and Elliott Pearson, HEREBY CERTIFY upon honor that, in
pursuance of special instructions bearing date of the 28th day of January, 1937
received from the district cadastral engineer for Arizona, with assignment
instructions dated June 11 & 21, 1937, I have surveyed We have dependently resurveyed
the subdivisional lines of Township 9 North, Range 26 East

of the Gila & Salt River Meridian, in the State of Arizona, which are
us our
represented in the foregoing field notes as having been executed by me and under my direction; and that said
re survey has been made in strict conformity with said instructions, the Manual of Instructions for the Survey
of the Public Lands of the United States, and in the specific manner described in the foregoing field notes.

Yucca Grove, California
January 3, 1940

Glendale, Calif.
December 13, 1938.

Yreboon, Arizona

December 23, 1939

Roger F. Wilson
Surveyor
F. Wayne Forrest

Public Land Surveyor

Elliott Pearson
Transitman

General Land Office

CERTIFICATE OF APPROVAL

OFFICE OF U.S. SUPERVISOR OF SURVEYS,

Denver, Colorado, 1940.

The foregoing field notes of the survey of dependent resurvey of the subdivisional
lines of Township 9 North, Range 26 East of the Gila and Salt River
Meridian, in the state of Arizona,

executed by Roger F. Wilson, F. Wayne Forrest and Elliott Pearson,
under special instructions dated January 28, 1937, and assignment
instructions dated June 11 and 21, 1937, having been critically examined, and
the necessary corrections made prior to their certification by the engineer, the said field notes, and the ^{re} survey
therein described, are hereby approved.

Wm. A. Johnson

U.S. Supervisor of Surveys.

CERTIFICATE OF TRANSCRIPT

I certify that the foregoing transcript of the field notes of the above-described surveys in
is a true copy of the original field notes on file in the public survey office.

U.S. Supervisor of Surveys.