

125

BOOK 4298

FIELD NOTES

OF THE

Resurvey of a Portion of the East Boundary of

Township 9 South, Range 17 East,

and

Survey and Resurvey of a Portion of the Subdivisional Lines,

Completing the Subdivision of

Township 9 South, Range 18 East,

4298

Of the Gila and Salt River Meridian,

In the State of Arizona

EXECUTED BY

Benjamin J. Kinsey, Cadastral Engineer.

General Land Office

Under special instructions dated October 5, 1938, which provided
for the surveys included under Group No. 224, bearing the approval of the
Commissioner of the General Land Office under date of November 18, 1938
and assignment instructions dated November 28, 1938.

Survey commenced April 20, 1939.

Survey completed May 20, 1939.

126
1A

BOOK 4298

INDEX DIAGRAM.

Township 9 South, Range 18 East.

6	6	60 5	51 4	42 3	34 2	23 1
-	59	58	50	41	34	22
5	61 7	57 8	49 9	41 10	32 11	21 12
-	57	56	48	40	32	20
3	61 13	55 17	47 16	39 15	31 14	20 13
-	54	53	46	38	30	19
2	19	52 20	45 21	37 22	29 23	18 24
-	14	44	44	36	28	17
	30	12 29	43 28 11	35 27 9	27 26	16 25
	31	11 32	10 33	26 8 34	25 24 35	16 15 36

Township 9 South, Range 18 East.

4293

The resurveys and surveys herein described were executed with Buff light mountain transit, Serial No. 18000. The instrument is equipped with full vertical circle and the improved Smith solar attachment, and otherwise conforms to the standard specifications of the General Land Office. It was approved by the district cadastral engineer on November 28, 1938, conditional upon satisfactory field tests. All of the instrumental adjustments were examined before making the field tests hereinafter described.

The directions of the lines were determined by the solar transit method. The measurements were made with a Lallie steel tape, 5 chs. in length, graduated every link for the first 100 lks., and thereafter at intervals of 10 lks. The tape was tested by comparison with a Lufkin standard and found correct. The measurements were made on the slope and the vertical angle of each interval was ascertained with a clinometer in good adjustment. The horizontal equivalents are entered in the field note record.

The data furnished with the special instructions give the geographical position of the SE. cor. of T.9 S., R.18 E., G. and S.R. meridian, Arizona, as follows: latitude $32^{\circ}35'56''$ N., and longitude $110^{\circ}26'54''$ W.

April 19, 1939, in camp near the center of sec. 21, T.9 S., R.18 E., at 5h 58m a.m., l.m.t., observe Polaris at eastern elongation, making four observations, two each with the telescope in direct and reversed positions, and marking the mean point in the line thus determined by a tack set in top of a peg, driven firmly in the ground about 5 chs. N. I then deflect the azimuth of Polaris, $1^{\circ}13'$ to the west of the mean point in the line determined by the observation, and made a meridian mark on a second peg about 5 chs. N. Check the deflection angle by repetition.

At 9h 0m a.m., app.t., set off $32^{\circ}38'$ N., on the lat. arc; $11^{\circ}02'$ N., on the decl. arc; and orient the instrument with the solar; the line of sight agrees with the meridian established by Polaris observation.

At app. noon, with lat. arc unchanged, observe the sun on the meridian; the resultant reading of the declination arc is $11^{\circ}04'$ N., which agrees with the computed declination of the sun.

At 3h 0m p.m., app.t., with lat. arc unchanged; set off $11^{\circ}07'$ N., on the decl. arc; and repeat the test of the solar; the line of sight agrees with the meridian established by Polaris observation.

As all of the solar observations taken during the usual hours of solar work agree within $1'$ of the true meridian, conclude that the instrument is in satisfactory adjustment.

Resurvey of Part of East boundary of T.9 S., R.17 E.

chains

Preliminary to the resurvey, the necessary lines of the original survey are retraced and diligent search is made for all original corners. Identified corners of the original survey are remonumented at their original points. All lost corners are appropriately reestablished based on the record of the original survey. The retracement data are thoroly verified and only true line notes are given herein.

Reestablishment of surveys executed by T.F. White, Deputy Surveyor, in 1877, and resurveyed in part by G.F. Sawyer, Surveyor, in 1924.

The cor. of secs. 19, 24, 25 and 30, T.9 S., R.17 and 18 E., is a stone, 16x14x6 ins., loosely set in a mound of stone, with faint notches on two sides, alongside a very old mesquite stake about 1 1/2 ft. long and 2 ins. square.

At point for cor.

Set an iron post, 3 ft. long, 2 ins. diam., 28 ins. in the ground, with cor. stone deposited at the base, for cor. of secs. 19, 24, 25, and 30, with brass cap mkd.

T9S	
R17E	R18E
S 24	S 19
S 25	S 30

1939

raise a

mound of stone, 3 1/2 ft. base and 1 1/2 ft. high, W. of cor.

Thence

N.2°00'E., on true line bet. secs. 19 and 24.

Over mountainous land, thru scattering timber and undergrowth.

Asc. 56 ft. over SW. slope.

1.30 Spur, slopes SW.; desc. 90 ft. over NW. slope.

9.40 Wash, 10 lks. wide, course SW.; enter washed land.

12.60 Road, bears NE. and SW.; leave washed land, bears NE. and SW.; asc. 234 ft. over SE. slope.

30.80 Spur, slopes W.; desc. 135 ft. over N. slope.

Resurvey of part of East Bdy. of T. 9 S., R. 17 E.

Chains.

39.00 Wash, 10 lks. wide, course W.; asc. 11 ft. over SW. slope.

39.46 Proportional dist.

Set an iron post, 3 ft. long, 1 in. in diam., 14 ins. in the ground to bedrock, with stone 4x4x6 ins., mkd. with a cross (X) deposited at base, and in a mound of stone to top, for $\frac{1}{4}$ sec. cor., with brass cap mkd.

	↑	
S 24		S 19
	↓	
1939		

Asc. 52 ft. over SW. slope.

41.75 Top of ascent; over stony W. slope.

44.65 Spur, slopes W.; desc. 99 ft. over NW. slope.

47.65 Wash, 15 lks. wide, course W.; asc. 99 ft. over steep SW. slope.

49.65 Top of ascent; over rolling W. slope.

51.65 Spur, slopes W.; desc. 117 ft. over NW. slope.

58.05 Wash, 15 lks. wide, course SW.; asc. 118 ft. over SW. slope.

63.25 Top of ascent; continue over level bench.

78.92 The cor. of secs. 13, 18, 19 and 24, which is a granite stone 6x10x6 ins. above ground, marked and witnessed as described in the official record.

At point for cor.

Set an iron post, 3 ft. long, 2 ins. diam., 16 ins. in the ground to bedrock, with original cor. stone deposited at base and in a mound of stone to top, for cor. of secs. 13, 18, 19 and 24, with brass cap mkd.

	T9S		
	R17E		R18E
	S 13		S 18
	S 24		S 19
1939			

Land, rolling mountainous.
Soil, rocky and gypseous, 4th. rate.
Timber, mesquite and paloverde.
Undergrowth, greasewood and cacti.

N. 1° 44' W., on true line, on E. bdy. of sec. 13.

Over hilly land, thru scattering timber and undergrowth.

Desc. 53 ft. over NW. slope.

5.00 Wash, 30 lks. wide, course SW.; asc. 33 ft. over S. slope.

8.00 Continue over rolling land.

4. Resurvey of part of East Bdy. of T. 9 S., R. 17 E.

Chains.

- 27.90 Edge of canyon; desc. 80 ft. over N. slope.
- 32.80 Wash in bottom, 20 lks. wide, course SW.; asc. 36 ft. over SE. slope.
- 36.60 Spur, slopes W.; desc. 100 ft. over vertical bank of canyon.
- 37.00 Wash, 30 lks. wide, course W. Across stony bottom land.
- 39.49 Proportional dist.

Set an iron post, 3 ft. long, 1 in. diam., 20 ins. in the ground to bedrock, and in a mound of stone to top, for $\frac{1}{4}$ sec. cor. of sec. 13 only, with brass cap mkd.

$\frac{1}{4}$ S 13
 1939

from which

A mesquite, 6 ins. diam., bears S. 14° E., 153 lks. dist., marked $\frac{1}{4}$ S 13 B T.

A mesquite, 6 ins. diam., bears S. 37° W., 204 lks. dist., marked $\frac{1}{4}$ S 13 B T.

Asc. 43 ft. over S. slope.

- 42.10 Spur, slopes W.; desc. 26 ft. over broken N. slope.
- 48.00 Wash, 10 lks. wide, course W.; asc. 45 ft. over S. slope.
- 53.60 Spur, slopes W.; over broken W. slope.
- 60.70 Desc. 105 ft. over rough N. slope.
- 78.80 Wash, 10 lks. wide, course SW.; over bottom land.
- 78.98 The cor. of secs. 7, 12, 13 and 18, which is an iron post, 2 ins. diam., firmly set, projecting 13 ins. above ground, marked and witnessed as described in the official record. This cor. now refers to secs. 12 and 13 only.

Alter marks on brass cap to read:

T9S
 R17E | R18E
 S 12 | S 18
 S 13 |
 1924 | 39

Land, hilly and broken.
 Soil, gypseous and rocky, 4th rate.
 Timber, paloverde and mesquite.
 Undergrowth, greasewood and cacti.

Resurvey of part of East Bdy. of T. 9 S., R. 17 E.

Chains.

N. 0° 06' W., on true line, on E. bdy. of sec. 12.

Over hilly land, through scattering timber and undergrowth.

Asc. 15 ft. over S. slope.

13.30 Spur, slopes W.; desc. 96 ft. over N. slope.

17.50 Wash, 10 lks. wide, course W.; asc. 77 ft. over S. slope.

21.00 Spur, slopes SW.; desc. 78 ft. along NW. slope.

30.00 Wash, 20 lks. wide, course SW.; asc. 93 ft. over steep S. slope.

33.30 Point of spur, slopes SW.; desc. 99 ft. over NW. slope.

40.10 Proportional dist.

Set an iron post, 3 ft. long, 1 in. in diam., 28 ins. in the ground, for $\frac{1}{4}$ sec. cor. of sec. 12 only, with brass cap mkd.

$\frac{1}{4}$ S 12

1939

raise a mound

of stone, 3 ft. base, 2 ft. high, W. of cor.

Asc. 285 ft. over S. slope.

62.50 Ridge, bears S. 80° W., and N. 80° E., desc. 100 ft. over NW. slope.

68.20 Wash, 30 lks. wide, course SW.; asc. 46 ft. over SW. slope.

72.00 Spur, slopes SW.; desc. 118 ft. over NW. slope.

80.20 Proportional dist.

Set an iron post, 5 ft. long, 2 ins. in diam., 12 ins. in the ground to bedrock, with a stone 12x8x4 ins., marked with a cross (X) deposited at the base, and in a mound of stone to top, for cor. of secs. 1 and 12 only, with brass cap mkd.

T9S T9S

S 1 | R18E

S12 | S7
R17E

1939

Resurvey of part of East Bdy. of T. 9 S., R. 17 E.

Chains.

Land, hilly and broken.
Soil, stony and gypseous, 4th. rate.
Timber, paloverde and mesquite.
Undergrowth, greasewood and cacti.

N. $0^{\circ} 06'$ W., on true line, on E. bdy. of sec. 1.

Over hilly land, thru scattering timber and undergrowth.

Desc. 65 ft. over NW. slope.

4.80 Wash, 30 lks. wide, course SW.; ascend 54 ft. over SW. slope.

12.00 Spur, slopes SW.; desc. 40 ft. over NW. slope.

23.10 Wash, 20 lks. wide, course SW.; ascend 177 ft. over SW. slope.

32.50 Ridge, bears NE. and SW.; descend 148 ft. over NW. slope.

39.00 Enter washed land.

39.93 Set an iron post, 3 ft. long, 1 in. diam., 18 ins. in the ground to bedrock, and in a mound of stone to top, for witness $\frac{1}{4}$ sec. cor. of secs. 1 and 6, with brass cap mkd.

WC
|
S 1 | S 6
|
1939

from which

A mesquite, 6 ins. diam., bears S. 25° E., 16 lks. dist., marked W C $\frac{1}{4}$ S 6 B T.

A paloverde, 6 ins. diam., bears S. 59° W., 83 lks. dist., marked W C $\frac{1}{4}$ S 1 B T.

From witness $\frac{1}{4}$ sec. cor., the true point for $\frac{1}{4}$ sec. cor. of sec. 1 of R 17 E. bears N. $0^{\circ} 06'$ W., 17 lks. dist., and the true point for $\frac{1}{4}$ sec. cor. of sec. 6 of R. 18 E. bears N. $0^{\circ} 06'$ W., 4.27 chs. dist:

40.10 Proportional point for $\frac{1}{4}$ sec. cor. of sec. 1 only falls in wash, which drains W.

46.20 Leave wash; asc. 50 ft. over cut bank.

47.00 Spur, slopes W.; desc. 79 ft. over N. slope.



Resurvey of part of East Bdy. of T. 9 S., R. 18 E.

Chains.

- 51.70 Wash, 20 lks. wide, course SW.; across washed land.
- 59.00 Leave washed land; asc. 137 ft. over S. slope.
- 74.60 Ridge, bears NE. and SW.; descend 50 ft. over NW. slope.
- 80.20 The cor. of Tps. 8 and 9 S., Rs. 17 and 18 E., which is an iron post; 3 ins. in diam.; firmly set, projecting 14 ins. above ground, marked and witnessed as described in the field notes of the resurvey of the W. bdy. of T 8 S., R. 18 E.

Land, hilly.
 Soil, stony and sandy, 4th rate.
 Timber, mesquite and paloverde.
 Undergrowth, greasewood and cacti.

Resurvey of part of Subdivision of T. 9 S., R. 18 E.

Chains.	
	<p>Reestablishment of surveys executed by J. L. Harris, Deputy Surveyor, in 1879.</p> <p style="text-align: center;">-----</p> <p>From cor. of secs. 3; 4, 33 and 34, on S. bdy. of Tp.; an iron post, 2 ins. in diam., firmly set, projecting 14 ins. above ground, marked and witnessed as described in the field notes of the resurvey of a portion of the S. bdy. of T. 9 S., R. 18 E.</p> <p>N. 0° 08' E., on true line, on E. bdy. of sec. 33.</p> <p>Over hilly land, thru scattering timber and undergrowth.</p> <p>Desc. 132 ft. over NW. slope.</p>
10.30	Wash, 60 lks. wide, course SW.; over rolling W. slope.
22.50	Wash, 30 lks. wide, course W.; asc. 162 ft. over SW. slope.
32.00	Spur, slopes SW.; desc. 136 ft. over NW. slope.
39.50	Proportional dist.
	<p>Set an iron post, 3 ft. long, 1 in. diam., 28 ins. in the ground, for $\frac{1}{4}$ sec. cor. of sec. 33 only, with brass cap mkd.</p> <div style="text-align: center;">  <p>$\frac{1}{4}$ S 33 1939</p> </div> <p style="text-align: right;">raise a mound of stone, 4 ft. base, 2 ft. high, W. of cor.</p>
40.00	<p>Set an iron post, 3 ft. long, 1 in. diam., 28 ins. in the ground, for $\frac{1}{4}$ sec. cor. of sec. 34 only, with brass cap mkd.</p> <div style="text-align: center;">  <p>$\frac{1}{4}$ S 34 1939</p> </div> <p style="text-align: right;">raise a mound of stone, 4 ft. base, 2 ft. high, E. of cor.</p>
40.65	Wash, 20 lks. wide, course SW.; asc. 131 ft. over SW. slope.
47.80	Spur, slopes SW.
53.30	Desc. 108 ft. over NW. slope.
62.70	Wash, 150 lks. wide, course SW.
65.20	Asc. 30 ft. over broken SW. slope.

Resurvey of part of Subdivision of T. 9 S., R. 18 E. 9

Chains.

- 78.60 Low spur, slopes SW.; desc. 15 ft. over NW. slope.
- 79.00 The cor. of secs. 27, 28, 33 and 34, which is an old mound of stone. This cor. now refers to secs. 28 and 33 only.
- At point for cor.
- Set an iron post, 3 ft. long, 2 ins. diam., 18 ins. in the ground to bedrock, with a stone 8x6x4 ins., marked with a cross (X) deposited at the base, and in a mound of stone to top, for cor. of secs. 28 and 33 only, with brass cap mkd.
- | | |
|----------|------|
| T9S R18E | |
| S 28 | S 34 |
| S 33 | |
| 1939 | |
- Land, rolling and hilly.
Soil, stony and gravelly, 3rd. rate.
Timber, paloverde and mesquite.
Undergrowth, greasewood and caeti.
-
- North, on true line, on E. bdy. of sec. 28.
- Over hilly land, thru scattering timber and undergrowth.
- 1.00 80 chs. from the SW. cor. of sec. 34.
- Set an iron post, 3 ft. long, 2 ins. diam., 18 ins. in the ground to bedrock, with stone 10x6x4 ins., mkd. with a cross (X) deposited at the base, and in a mound of stone to top, for cor. of secs. 27 and 34 only, with brass cap mkd.
- | | |
|----------|------|
| T9S R18E | |
| S 28 | S 27 |
| | S 34 |
| 1939 | |
- Desc. 20 ft. over NW. slope.
- 1.50 4 strand barbed wire fence, bears E. and W.; corners about 20 lks. W., thence turns S.
- 5.00 Wash, 20 lks. wide, course W.; asc. 78 ft. over SW. slope.
- 9.60 Ridge, bears E. and W.; desc. 61 ft. over N. slope.
- 14.10 Wash, 20 lks. wide, course SW.; asc. 39 ft. over S. slope.
- 19.20 Spur, slopes W.; desc. 50 ft. over NW. slope.
- 23.40 Wash, 10 lks. wide, course SW.; asc. 99 ft. over SW. slope.
- 37.00 Spur, slopes SW.; desc. 59 ft. over NW. slope.
- 40.00 Record dist.
- Set an iron post, 3 ft. long, 1 in. diam., 27 ins. in the ground, for $\frac{1}{4}$ sec. cor. of sec. 28 only, with brass cap mkd.

Resurvey of part of the Subdivision of T. 9 S., R. 18 E.

Chains.

$$\frac{1}{4} \text{ S } 28$$

1939

raise a mound
of stone, 4 ft. base, 2 ft. high, W. of cor.

Land, hilly.
Soil, stony, 4th rate.
Timber, paloverde and mesquite.
Undergrowth, greasewood and cacti.

From cor. of secs, 28 and 33.

N. 89° 52' W., on true line, bet. secs. 28 and 33.

Over hilly land, thru scattering timber and undergrowth.

Desc. 59 ft. over NW. slope.

3.10 Wash, 20 lks. wide, course SW.; continue descent.

34.50 Wash, 1 ch. wide, course SW.; thence along gentle SW. slope.

40.15 Proportional dist.

Set an iron post, 3 ft. long, 1 in. diam., 22 ins. in the ground to bedrock, with stone 4x4x2 ins., mkd. with a cross (X) deposited at base, and in a mound of stone to top, for $\frac{1}{4}$ sec. cor., with brass cap mkd.

$$\frac{\frac{1}{4} \text{ S } 28}{\text{S } 33}$$

1939

Desc. 183 ft. over gradual SW. slope.

45.30 4 strand barbed wire fence, bears N. 6° W. and S. 6° E.

76.80 Wash, 30 lks. wide, course SW. Continue over level land to sec. cor.

80.30 The cor. of secs. 28, 29, 32 and 33, which is a post, 3 ins. square and 36 ins. long, with scribe marks visible but illegible, set in mound of stone.

At point for cor.

Set an iron post, 3 ft. long, 2 ins. diam., 18 ins. in the ground to bedrock, with stone 4x4x2 ins., marked with a cross (X) deposited at the base and in a mound of stone to top, for cor. of secs. 28, 29, 32 and 33, with brass cap mkd.

T9S	R18E
S29	S28
S32	S33

1939

Resurvey of part of Subdivision of T. 9 S., R. 18 E.

Chains.

Land, rolling hills.
Soil, rocky, 4th rate,
Timber, paloverde and mesquite.
Undergrowth, greasewood and cacti.

North, on true line, bet. secs. 28 and 29.

Over hilly land, thru scattering timber and undergrowth.

2.30 Desc. 53 ft. over NW. slope.

7.00 Wash, 1 ch. wide, course SW. Continue over washed land.

20.00 Leave washed land; asc. 119 ft. over SE. slope.

40.00 Record dist.

Set an iron post, 3 ft. long, 1 in. diam., 18 ins. in the ground to bedrock, with stone 8x5x4 ins., mkd. with a cross (X) deposited at the base and in a mound of stone to top, for $\frac{1}{4}$ sec. cor., with brass cap mkd.

$\frac{1}{4}$
 S 29 | S 28

1939

Land, rolling hills.
Soil, gravelly, 3rd rate.
Timber, paloverde and cacti.
Undergrowth, greasewood and cacti.

From cor. of secs. 28, 29, 32 and 33.

S. 89° 44' W., on true line, bet. secs. 29 and 32.

2.80 Edge of wash; desc. 60 ft. over cut bank.

3.50 Whitlock wash, 40 lks. wide, course SW. Continue over wash bottom.

16.10 Leave wash bottom; asc. 40 ft. over cut bank.

17.00 Top of bank; across rolling land.

21.30 Desc. 74 ft. over NW. slope.

26.00 Wash, 20 lks. wide, course SW.; asc. 111 ft. over SE, slope.

31.40 Spur, slopes SW.; desc. 128 ft. over NW. slope.


39.25 The $\frac{1}{4}$ sec. cor. of secs. 29 and 32, which is a badly rotted wooden stake in old mound of stone.

At point for cor.

Resurvey of part of Subdivision of T. 9 S., R. 18 E.

Chains.

Set an iron post, 3 ft. long, 1 in. diam., 12 ins. in the ground to bedrock, with stone 10x8x3 ins., mkd. with a cross (X) deposited at the base, and in a mound of stone to top, for 1/4 sec. cor. of secs. 29 and 32, with brass cap mkd.



1939

Thence

S. 88° 37' W., on true line, bet. secs. 29 and 32.

Over hilly land, thru scattering timber and undergrowth.

Desc. 44 ft. over NW. slope.

3.55 Wash, 15 lks. wide, course SW. Asc. 27 ft. over SE. slope.


15.75 Spur, slopes SW. Desc. 139 ft. over NW. slope.

37.75 Wash, 15 lks. wide, course SW. Continue over bottom land.

39.55 The cor. of secs. 29, 30, 31 and 32, which is a wooden post, 3 ins. square, 2 ft. long, projecting 1 ft. above ground and mound of stone; scribe marks visible but illegible.

At point for cor.

Set an iron post, 3 ft. long, 2 ins. in diam., 24 ins. in the ground, with old post alongside, for cor. of secs. 29, 30, 31 and 32, with brass cap mkd.



1939

raise a mound of stone, 4 ft. base, 2 ft. high, W. of cor.

Land, rolling.
Soil, stony and gravelly, 3rd. rate.
Timber, paloverde and mesquite.
Undergrowth, greasewood and cacti.

N. 1° 49' W., on true line, bet: secs. 29 and 30.

Over level land, thru scattering timber and undergrowth.

Desc. slightly over NE. slope.

1.00 Enter washed land, drains SW.

10.50 Leave washed land; asc. 65 ft. over SE. slope.

Resurvey of part of Subdivision of T. 9 S., R. 18 E.

Chains.

20.60 Road on ridge, bears NE. and SW.; desc. 60 ft. over W. slope.

27.40 Wash, 20 lks. wide, course SW.; asc. 77 ft. over SE. slope.

32.00 Enter stony mesa, bears NE. and SW.

39.33 Proportional dist.

Set an iron post, 3 ft. long, 1 in. diam., 18 ins. in the ground to bedrock, with stone 6x4x2 ins., mkd. with a cross (X) deposited at the base, and in a mound of stone to top, for $\frac{1}{4}$ sec. cor., with brass cap mkd.

$\frac{1}{4}$
 S 30 | S 29
 1939

52.30 Leave mesa; desc. 96 ft. over N. slope.

57.00 Wash, 40 lks. wide, from NE. to SW.; asc. 83 ft. over S. slope.

64.00 Spur, slopes W.; across level top.

67.00 Desc. 54 ft. over N. slope.

69.00 Wash, 30 lks. wide, course W., from NE.; W. 2.50 chs., thence S. Across bottom land.

74.20 Leave bottom land; asc. 98 ft. over S. slope.

77.00 Asc. over vertical bluff, 35 ft. high, bears E. and W.

77.10 Continue ascent of 39 ft. over S. slope.

78.66 The cor. of secs. 19, 20, 29 and 30, which is a wooden post, 4 ins. square, projecting 12 ins. above a mound of stone. Marks illegible but indications of scribing.

At point for cor.

Set an iron post, 3 ft. long, 2 ins. diam., 8 ins. in the ground to bedrock, with stone 8x6x4 ins., mkd. with a cross (X) deposited at base, and in a mound of stone to top, for cor. of secs. 19, 20, 29 and 30, with brass cap mkd.

T9S R18E
 S 19 | S 20
 S 30 | S 29
 1939

Land, rolling hills.
 Soil, rocky, 4th rate.
 Timber, paleverde and mesquite.
 Undergrowth, greasewood and cacti.

Chains.	
	N. 89° 12' W., bn true line, bet. secs. 19 and 30.
	Over rolling, hilly land, thru scattering timber and undergrowth.
1.90	Desc. 129 ft. over SW. slope.
7.70	Wash, 15 lks. wide, course SW.; asc. 92 ft. over SE. slope.
24.00	Spur, slopes SW.; desc. 99 ft. over SW. slope.
27.20	Wash, 10 lks. wide, course SW.; asc. 48 ft. over E. slope.
28.80	Spur, slopes S.; desc. 42 ft. over W. slope.
29.60	Wash, 10 lks. wide, course SW.; asc. 64 ft. over SE. slope.
33.30	Spur, slopes SW.; desc. 100 ft. over vertical bluff, bears NE. and SW.
37.40	Wash, 50 lks. wide, course SW.; thence across bottom land.
40.75	Proportional dist.
	Set an iron post, 3 ft. long, 1 in. diam., 18 ins. in the ground to bedrock, with stone 8x6x4 ins., mkd. with a cross (X) deposited at the base and in a mound of stone to top, for $\frac{1}{4}$ sec. cor., with brass cap mkd.
	$\frac{1}{4} \frac{S 19}{S 30}$
	1939
	Continue thru dense timber and undergrowth, across washed land.
45.00	Leave bottom land. asc. 54 ft. over E. slope.
46.60	Spur, slopes SW.; over level top.
54.00	Desc. 81 ft. over W. slope.
56.80	Wash, 30 lks. wide, course SW.; asc. 95 ft. over SE. slope.
62.70	Spur, slopes SW.; desc. 95 ft. over SW. slope.
70.00	Spur, slopes SW.; desc. 134 ft. over NW. slope.
75.80	Wash, 30 lks. wide, course SW.; asc. gradually over SE. slope.
77.80	Low spur, slopes S.; desc. 18 ft. over W. slope.
80.94	The cor. of secs. 19, 24, 25 and 30, on the W. Bdy. of Tp.
	Land, rolling hills. Soil, gravelly, 3rd rate. Timber, paloverde and mesquite. Undergrowth, greasewood and cacti.

Completion of Subdivision of T.9 S., R.18 E.

Chains

From cor. of secs. 1, 2, 35 and 36, on S. bdy. of Tp., which is an iron post 2 ins. in diam., firmly set and projecting 12 ins. above ground and with brass cap mkd. and witnessed as described in the official record.

N.0°01'W., bet. secs. 35 and 36.

Over rolling, hilly land, thru scattering timber & undergrowth.

Asc. 31 ft. over SW slope.

12.70 Ridge, bears NE and SW; desc. gradual NW slope.


18.40 Wash, 20 lks. wide, course SW.; asc. 57 ft. over SE slope.

29.00 Ridge, bears NE and SW. Desc. 61 ft. over NW slope.

34.00 Wash, 20 lks. wide, course SW.; asc. 94 ft. over SW slope.

39.00 Spur; slopes SW.; desc. gradual NW slope.

40.00 Set an iron post 3 ft. long, 1 in. in diam., 20 ins. in the ground to bedrock, with stone 8x4x2 ins., mkd. with a cross (X) deposited at the base and in a mound of stone to top for 1/4 sec. cor., with brass cap mkd.



Desc. 35 ft. over NW slope.

45.00 Wash, 20 lks. wide, course SW.; asc. 81 ft. over S. slope.

52.00 Ridge, bears E. and W.; desc. 48 ft. over N. slope.


56.00 Wash, 30 lks. wide, course W.; asc. 95 ft. over SE slope.

62.10 Spur, slopes SW. Desc. 108 ft. over N. slope.

68.70 Wash, 10 lks. wide, course W.; asc. 90 ft. over S. slope.

76.00 Spur, slopes W.; desc. 53 ft. over N. slope.

80.00 Set an iron post 3 ft. long, 2 ins. in diam., 28 ins. in the ground for cor. of secs. 25, 26, 35, and 36, with brass cap marked



1939

Land, rolling hills.

Soil, gravelly, sandy, 3rd. rate.

Timber, paloverde and mesquite. Undergrowth, greasewood and cacti.

East, on a random line, bet. secs. 25 and 36.

40.00 Set temp. $\frac{1}{4}$ sec. cor.

80:04 Intersect E. bdy. of Tp. at 23 lks. S. of cor. of secs. 25, 30, 31, and 36, established by T. Vander Meer, U.S.T. in 1924, which is an iron post 2 ins. in diam., firmly set, marked and witnessed as described in the official record.

Thence,

S.89°50'W., on true line, bet. secs. 25 and 36.

Over rolling land, thru scattering timber and undergrowth.

12.15 Wash, 20 lks. wide, course SW.

19.45 Same wash, course SW from bend to SE.

40.02 Set an iron post .3 ft. long, .1 in. in diam., 20 ins. in the ground to bedrock, with stone 6x4x2 ins., mkd. with a cross (X) deposited at the base and in a mound of stone to top for $\frac{1}{4}$ sec. cor., with brass cap marked

$\frac{1}{4}$ S25

S36
1939

Desc. gradual NW slope.

41.00 Wash, 20 lks. wide, course SW. Asc. 60 ft. over SE slope.

62.00 Ridge, bears NE, and SW.; desc. 109 ft. over NW slope.

76.50 Across bottom land, bears NE and SW.

80.04 The cor. of secs. 25, 26, 35, and 36.

Land, rolling hills.
Soil, stony and sandy loam, 3rd. rate.
Timber, palo verde, and mesquite.
Undergrowth, greasewood and cacti.

N.0°01'W., bet. secs. 25 and 26.

Over rolling land, thru scattering timber & undergrowth.
Asc. 92 ft. over SW slope, to ridge.

.30 Wash, 10 lks. wide, course SW.

7.20 Ridge, bears E. and W.; desc. 111 ft. over N. slope.

13.90 Wash, 10 lks. wide, course W. Asc. 55 ft. over S. slope.

18.30 Spur, slopes W.; desc. 68 ft. over NW slope.

21.20 Wash, 10 lks. wide, course SW. Asc. 65 ft. over broken SW slope.

Completion of Subdivision of T. 9 S., R. 18 E.

17

Chains

40.00 Set an iron post 3 ft. long, 1 in. in diam., 18 ins. in the ground to bedrock, with stone 10x6x2 ins., mkd. with a cross (X) deposited at the base and in a mound of stone to top for $\frac{1}{4}$ sec. cor., with brass cap marked

$$\begin{array}{c} \frac{1}{4} \\ \text{S26} \quad | \quad \text{S25} \\ \hline 1939 \end{array}$$

57.70 Asc. 36 ft. over gradual SW slope.
Ridge, bears NE and SW. Desc. along gradual NW slope.

59.00 Head of wash, course SW.

61.30 Head of wash, course SW.

69.70 Desc. 32 ft. over NW slope.

78.60 Wash, 20 lks. wide, course SW. Asc. 13 ft. over SW slope.

80.00 Set an iron post 3 ft. long, 2 ins. in diam., 14 ins. in the ground to bedrock, with stone 10x6x3 ins., mkd. with a cross (X) deposited at the base and in a mound of stone to top for cor. of secs. 23, 24, 25, and 26, with brass cap mkd.

$$\begin{array}{c} \text{T9SR18E} \\ \hline \text{S23} \quad | \quad \text{S24} \\ \hline \text{S26} \quad | \quad \text{S25} \\ \hline 1939 \end{array}$$

Land, rolling hills.
Soil, stony 4th. rate.
Timber, paloverde and mesquite.
Undergrowth, greasewood and cacti.

N. 89° 50' E., on a random line, bet. secs. 24 and 25.

40.00 Set temp. $\frac{1}{4}$ sec. cor.

80.00 Intersect E. bdy. of Tp., 5 lks. N. of cor. of secs. 19, 24, 25, and 30, which is an iron post 2 ins. in diam., firmly set, projecting 12 ins. above ground, with brass cap marked and witnessed as described in the official record.

Thence,

S. 89° 52' W., on true line, bet. secs. 24 and 25.

Over rolling land, thru scattering timber & undergrowth.


8.20 Wash, 10 lks. wide, course SW.; asc. 29 ft. along SE slope.

21:00 Spur, slopes SW.; desc. 44 ft. over NW slope.

27.20 Wash, 10 lks. wide, course SW. Asc. 30 ft. over SE slope.

Chains

40.00 Set an iron post 3 ft. long, 1 in. in diam., 14 ins. in the ground to bedrock; with stone 6x4x2 ins., mkd. with a cross (X) deposited at the base and in a mound of stone to top for 1/4 sec. cor., with brass cap mkd..



1939

Asc. 61 ft. along SE slope.

69.10 Ridge, bears NE and SW. Desc. 43 ft. over NW slope.

76.70 Wash, 20 lks. wide, course SW. Asc. 26 ft. along SE slope.

80.00 The cor. of secs. 23, 24, 25, and 26.

Land, rolling.
Soil, stony and gravelly 3rd. rate,
Timber, paloverde and mesquite.
Undergrowth, greasewood and cacti.

N.0°01'W., bet. secs..23 and 24.

Over rolling land, thru scattering timber & undergrowth.


5.20 Wash, 10 lks. wide, course SW.

14.50 Wash, 10 lks. wide, course SW.

21.80 Wash, 10 lks. wide, course SW.

25.80 Ridge, bears NE and SW.

40.00 Set an iron post 3 ft. long, 1 in. in diam., 14 ins. in the ground to bedrock, with stone 10x6x2 ins., mkd. with a cross (X) deposited at the base and in a mound of stone to top for 1/4 sec. cor., with brass cap marked



55.40 Wash, 10 lks. wide, course SW. Asc. 131 ft. over SE slope.

66.70 Ridge, bears NE and SW. Desc. 80 ft. over broken SW slope.

80.00 Set an iron post 3 ft. long, 2 ins. in diam., 18 ins. in the ground to bedrock, with stone 10x6x2 ins., mkd. with a cross (X) deposited at the base and in a mound of stone to top for cor. of secs. 13, 14, 23, and 24, with brass cap marked:

Completion of Subdivision of T.9 S., R.18 E.

19

Chains

T9SR18E

S14 | S13

S23 | S24

1939

Land, rolling.
Soil, stony 4th. rate.
Timber, paloverde and mesquite.
Undergrowth, greasewood and cacti.

N.89°52'E., on a random line, bet. secs. 13 and 24.

40.00 Set temp. $\frac{1}{4}$ sec. cor.

80.02 Intersect E. bdy. of Tp. at 7 lks. N. of cor. of secs. 13, 18, 19, and 24, which is an iron post 2 ins. in diam., firmly set, projecting 12 ins. above ground, with brass cap marked and witnessed as described in the official record.

Thence,

S.89°55'W., on true line, bet. secs. 13 and 24.

Over rolling land, thru scattering timber & undergrowth.

Desc. 67 ft. over SW slope.

31.80 Wash, 10 lks. wide, course SW. Asc. gradual SE slope.

40.01 Set an iron post 3 ft. long, 1 in. in diam., 16 ins. in the ground to bedrock, with stone 10x6x4 ins., mkd: with a cross (X) deposited at the base and in a mound of stone to top for $\frac{1}{4}$ sec. cor., with brass cap marked

$\frac{1}{4}$ $\frac{S13}{S24}$

1939

Asc. 35 ft. over SE slope.

48.00 Spur, slopes SW. Desc. 51 ft. over SW slope.

50.00 Wash, 10 lks. wide, course SW. Asc. 40 ft. over E. slope.

54.40 Spur, slopes SW; across level top.

64.00 Spur, edge; desc. 50 ft. over SW slope.

68.30 Wash, 20 lks. wide, course SW.; asc. 73 ft. over SE slope.

74.40 Ridge, bears NE and SW.; desc. 82 ft. over NW slope.

80.02 The cor. of secs. 13, 14, 23, and 24;

Land, rolling hills.
Soil, stony 4th. rate.
Timber, paloverde and mesquite; undergrowth, greasewood and cacti.

Chains

N.0°01'W., on true line, bet. secs. 13 and 14.

Over rolling land, thru scattering timber & undergrowth.


Desc. 39 ft. over NW slope.

6.00 Wash, 10 lks. wide, course SW. Asc. 111 ft. over SW slope.

18.00 Spur, slopes SW. Desc. 78 ft. over gradual NW slope.

32.60 Wash, 10 lks. wide, course SW. Asc. 44 ft. over SW slope.

40.00 Set an iron post 3 ft. long, 1 in. in diam., 8 ins. in the ground to bedrock, with stone 10x6x4 ins., mkd. with a cross (X) deposited at the base and in a mound of stone to top for 1/4 sec. cor., with brass cap marked




Asc. 196 ft. over SW slope.

64.00 Ridge, bears NE and SW. Desc. 73 ft. over NW slope.

72.20 Wash, 10 lks. wide, course SW.; asc. 71 ft. over SW slope.

78.30 Spur, slopes S.70°W.; desc. 15 ft. over NW slope.

80.00 Set an iron post 3 ft. long, 2 ins. in diam., 10 ins. in the ground to bedrock, with stone 10x6x6 ins., mkd. with a cross (X) deposited at the base and in a mound of stone to top for cor. of secs. 11, 12, 13, and 14, with brass cap mkd.



Land, rolling hills.
Soil, stony 3rd. rate.
Timber, paloverde and mesquite.
Undergrowth, greasewood and cacti.

N.89°55'E., on a random line, bet. secs. 12 and 13.

40.00 Set temp. 1/4 sec. cor.

79.82 Intersect N. and S. line 23 lks. S. of cor. of secs. 7, 12, 13, and 18 on E. bdy. of Tp., which is an iron post 2 ins. in diam., firmly set, projecting 14 ins. above ground, with brass cap marked and witnessed as described in the official record.

Thence,

Completion of Subdivision of T.9 S., R.18 E.

21

Chains

S.89°45'W., on true line, bet. secs. 12 and 13.

Over rolling land, thru scattering timber & undergrowth.

Desc. 34 ft. over NW slope.

1.95 Wash, 20 lks. wide, course SW. Asc. 34 ft. over SE slope.

9.00 Spur, slopes SW.; desc. 125 ft. over NW slope.

23.00 Wire fence, bears N. and S. (S. 3 chs. thence SE.)

25.85 Wash, 20 lks. wide, course SW. Asc. 48 ft. over SE slope.

32.40 Spur, slopes SW.; desc. 114 ft. over NW slope.

39.91 Set an iron post 3 ft. long, 1 in. in diam., 10 ins. in the ground to bedrock, with stone 6x4x2 ins., mkd. with a cross (X) deposited at the base, and in a mound of stone to top for $\frac{1}{4}$ sec. cor., with brass cap mkd.
$$\frac{S12}{S13}$$

1939

Desc. 45 ft. over NW slope.

43.50 Wash, 10 lks. wide, course SW. Asc. 85 ft. over SE slope.

56.00 Spur, slopes SW.; desc. 71 ft. over SW slope.

61.20 Wash, 10 lks. wide, course SW. Asc. 52 ft. over SE slope.

67.70 Spur, slopes SW.; desc. 57 ft. over SW slope.

72.60 Wash, 10 lks. wide, course SW.; asc. 23 ft. over SE slope.

77.60 Spur, slopes S.70°W.; desc. 20 ft. over NW slope.

79.82 The cor. of secs. 11, 12, 13, and 14.

Land, rolling hills.

Soil, stony 4th. rate.

Timber, palo verde and mesquite.

Undergrowth, greasewood and cacti.

N.0°01'W., bet. secs. 11 and 12.

Over mountainous land, thru scattering timber and undergrowth.

Desc. 71 ft. over NW slope.

3.40 Wash, 10 lks. wide, course S.60°W.; asc. 105 ft. over SW slope.

8.70 Spur, slopes SW.; desc. 150 ft. over NW slope.

19.80 Wash, 30 lks. wide, course SW. Across bottom land.

Chains

Desc. 27 ft. over SW slope.

- 2.65 Whitlock wash, 15 lks. wide, course NW.; asc. 80 ft. over NE slope.
- 10.65 Rough, broken spur, slopes NW.; desc. 150 ft. over NW slope.
- 17.65 Wash, 20 lks. wide, course NW.; asc. 96 ft. over NE slope.
- 35.15 Spur, slopes N.; desc. 134 ft. over NW slope.
- 39.82 Set an iron post 3 ft. long, 1 in. in diam., 28 ins. in the ground for $\frac{1}{4}$ sec. cor. with brass cap marked

$\frac{1}{4}$ $\frac{S1}{S12}$

1939

Raise a mound of stone 4 ft. base, 2 ft. high, N. of cor.

Desc. 189 ft. over NW slope.

- 53.65 4-strand barb wire fence, bears NW and SE.
- 61.25 Ranch house of John Rhodes, bears North, 12 chs. dist.
- 62.65 Whitlock wash, 70 lks. wide, course SW. Asc. 38 ft. over SE slope.
- 72.00 Thence over rolling land, on slight ascent.
- 79.64 The cor. of secs. 1, 2, 11, and 12.

Land, mountainous and rolling.
Soil, stony 4th. rate.
Timber, paloverde and mesquite.
Undergrowth, greasewood and cacti.

N. 0° 01' W., on a random line, bet. secs. 1 and 2.

- 40.00 Set temp. $\frac{1}{4}$ sec. cor., thru weathering timber and under-

- 75.00 Intersect N. bdy. of Tp. 40 lks. east of cor. of secs. 1, 2, 35, and 36, which is an iron post 2 ins. in diam., firmly set, projecting 14 ins. above ground with brass cap marked and witnessed as described in the official record.

Thence,

S. 0° 18' E., on true line, bet. secs. 1 and 2.


Over mountainous land, thru scattering timber & undergrowth.

Asc. 100 ft. over NW slope.

- 6.30 Ridge, bears NE and SW. Desc. 137 ft. over SE slope.

Chains

- 14.90 Wash, 10 lks. wide, course SW.; asc. 198 ft. over N. slope.
 29.00 Spur, slopes West.; desc. 34 ft. over S. slope.
 33.10 Wash, 10 lks. wide, course west. Asc. 27 ft. over NW. slope.
 35.00 Set an iron post 3 ft. long, 1 in. in diam., above six inch cross cut in bedrock, and in a mound of stone to top for $\frac{1}{4}$ sec. cor., with brass cap marked



Asc. 30 ft. over NW slope.

- 38.00 Spur, slopes SW.; desc. 408 ft. over SE slope.
 70.00 Road, bears E. and SW.
 71.00 Barb wire fence, bears N.70°E. and S.70°W.
 71.50 Wash, 10 lks. wide, course SW.; asc. 33 ft. over NW slope.
 75.00 The cor. of secs. 1, 2, 11, and 12.

Land, mountainous.
 Soil, rocky 4th. rate.
 Timber, paloverde and mesquite.
 Undergrowth, greasewood and cacti.

From cor. of secs. 2, 3, 34, and 35, on S. bdy. of Tp., established by T. Vander Meer, U.S.T., 1924, which is an iron post 2 ins. in diam., firmly set in a mound of stone, projecting 14 ins. above ground, with brass cap marked and witnessed as described in the official record.

N.0°01'W., bet. secs. 34 and 35.

Over hilly land, thru scattering timber & undergrowth.

Asc. 8 ft. over SE.slope.

- 1.50 Top of ridge, bears NE and SW. Over level top.
 4.40 Leave top, desc. 91 ft. over NW slope.
 11.20 Wash, 30 lks. wide, course SW.; asc. 83 ft. over SW slope.
 27.00 Ridge, bears E. and W. Desc. 69 ft. over NW slope.
 32.80 Wash, 20 lks. wide, course SW.; asc. 29 ft. over SW slope.
 40.00 Set an iron post 3 ft. long, 1 in. in diam., 16 ins. in the ground to bedrock, with stone 10x8x3 ins., mkd. with a cross (X) deposited at the base, and in a mound of stone to top for $\frac{1}{4}$ sec. cor., with brass cap mkd.

Chains

- 30.00 Spur, slopes SW. Desc. 54 ft. over W. slope.
 31.70 Wash, 10 lks. wide, course SW.; asc. 55 ft. over SE slope.
 40.02 Set an iron post 3 ft. long, 1 in. in diam., 18 ins. in the ground to bedrock, with stone 6x5x2 ins., mkd. with a cross (X) deposited at the base and in a mound of stone to top for $\frac{1}{4}$ sec. cor., with brass cap mkd.

$\frac{1}{4}$ $\frac{S26}{S35}$

1939

Corner set on ridge, bears NE and SW.

- 41.00 Desc. 51 ft. over **NW** slope.
 45.50 Wash, 20 lks. wide, course SW.; asc. 52 ft. over SE slope.
 56.20 Wash, 10 lks. wide, course SW. Asc. 41 ft. over SE slope.
 61.50 Spur, slopes SW. Desc. 74 ft. over NW slope.
 67.00 Wash, 20 lks. wide, course SW.; asc. 31 ft. over SE slope.
 73.00 Spur, slopes SW.; desc. 64 ft. over NW slope.
 77.60 Wash, 15 lks. wide, course SW.; asc. 21 ft. over SE slope.
 80.04 The cor. of secs. 26, 27, 34, and 35.

Land, mountainous.
 Soil, stony 4th. rate.
 Timber, palo verde and mesquite.
 Undergrowth, greasewood and cacti.

West, on a random line, bet. secs. 27 and 34.

- 40.00 Set temp. $\frac{1}{4}$ sec. cor.
 80.04 Intersect N. and S. line, at cor. of secs. 27 and 34, only.
 Thence,
 East, on true line, bet. secs. 27 and 34.
 Over hilly land, thru scattering timber & undergrowth.
 Asc. 72 ft. over NW slope.
 9.00 Ridge, bears N.80°E. and S.80°W. Desc. gradual SW slope.
 14.60 Spur, slopes SW.; desc. 23 ft. over SE slope.
 24.10 Wash, 150 lks. wide, course SW.; asc. 37 ft. over SW slope.
 26.30 Spur, slopes SW.; desc. 38 ft. over SE slope.
 33.60 Wash, 25 lks. wide, course SW.; asc. 90 ft. over SW slope.
 40.02 Set an iron post 3 ft. long, 1 in. in diam., 27 ins. in

Chains

the ground for $\frac{1}{4}$ sec. cor., with brass cap marked

$\frac{1}{4}$ $\frac{S27}{S34}$

1939

raise a mound
of stone 4 ft. base, .2 ft. high, N. of cor.

Asc. 98 ft. over SW slope.

52.00 Knoll on spur, slopes SW.; desc. 21 ft. over SE slope.

57.50 Wash, 10 lks. wide, course SW.; asc. 79 ft. over NW slope.

74.20 Ridge, bears NE and SW. Desc. 34 ft. over SE slope.

80.04 The cor. of secs. 26, 27, 34, and 35.

Land, rolling hills.

Soil, stony and gravelly 3rd. rate.

Timber, palo verde, and mesquite.

Undergrowth, greasewood, and cacti.

N.0°01'W., bet. secs. 26 and 27.

Over rolling hills, thru scattering timber & undergrowth.

Asc. 59 ft. over broken SE slope.

8.00 Spur, slopes West.; desc. 94 ft. over N. slope.

13.10 Wash, 10 lks. wide, course W.; asc. 49 ft. over S. slope.

16.70 Spur, slopes SW. Desc. 39 ft. over N. slope.

18.90 Wash, 10 lks. wide, course SW.; desc. 49 ft. over S. slope.

23.40 Spur, slopes SW.; desc. 49 ft. over NW slope.

26.60 Wash, 10 lks. wide, course SW.; asc. 46 ft. over SW slope.

30.00 Spur, slopes SW.; desc. 23 ft. over NW slope.

32.80 Wash, 10 lks. wide, course SW.; asc. 46 ft. over SW slope.

36.80 Spur, slopes W.; desc. 32 ft. over NW slope.

40.00 Set an iron post 3 ft. long, 1 in. in diam., 20 ins. in
the ground to bedrock, with stone 6x4x4 ins., mkd. with
a cross (X) deposited at the base and in a mound of
stone to top for $\frac{1}{4}$ sec. cor., with brass cap mkd.

$\frac{1}{4}$
S27 | S26
1939

Desc. 46 ft. over NW slope.

Chains

- 42.60 Wash, 30 lks. wide, course SW.; asc. 32 ft. over broken SW. slope.
- 56.20 Spur, slopes SW.; thence over rolling land.
- 73.20 Wash, 10 lks. wide, course SW.; asc. 20 ft. over SE slope.
- 80.00 Set an iron post 3 ft. long, 2 ins. in diam., 18 ins. in the ground to bedrock, with stone 10x5x2 ins., mkd. with a cross (X) deposited at the base and in a mound of stone to top for cor. of secs. 22, 23, 26, and 27, with brass cap mkd.

T9SR18E
 S22 | S23
 S27 | S26

1939

Land, rolling hills.
 Soil, sandy and gravelly 3rd. rate.
 Timber, palo verde, and mesquite.
 Undergrowth, greasewood, and cacti.

N.89°56'E., on a random line, bet. secs. 23 and 26.

- 40.00 Set temp. 1/4 sec. cor.
- 80.00 Intersect N. and S. line, 3 lks. S. of cor. of secs. 23, 24, 25, and 26.
- Thence,
- S.89°55'W., on true line, bet. secs. 23 and 26.
- Over rolling hills, thru scattering timber & undergrowth.
- Desc. 57 ft. over W. slope.
- 5.80 Wash, 10 lks. wide, course SW.
- 22.00 Spur, slopes SW.;
- 29.00 Ridge, bears NE and SW.; desc. 103 ft. over NW slope.
- 38.50 Wash, 10 lks. wide, course SW.;
- 39.70 Wash, 10 lks. wide, course SE.
- 40.00 Set an iron post 3 ft. long, 1 in. in diam., 14 ins. in the ground to bedrock, with stone 6x6x3 ins., mkd. with a cross (X) deposited at the base and in a mound of stone to top for 1/4 sec. cor., with brass cap mkd.

1/4 S23
 S26

1939

Asc. 46 ft. over SE slope.

- 48.00 Spur, slopes SW.; desc. 176 ft. over W. slope.

Completion of Subdivision of T. 9 S., R. 18 E.

Chains

74.00 Wash, 10 lks. wide, course W.; asc. 13. ft. over SE slope.

80.00 The cor. of secs. 22, 23, 26, and 27.

Land, rolling hills.
Soil, rocky and gravelly 3rd. rate.
Timber, palo verde, and mesquite.
Undergrowth, greasewood, and cacti.

N.0°01'W., bet. secs. 22 and 23.

Over rolling land, thru scattering timber & undergrowth.

Asc. 20 ft. over SE slope.


2.80 Ridge, bears NE and SW.; desc. 86 ft. over NW slope.

11.65 Wash, 30 lks. wide, course W.; asc. 110 ft. over S. slope.

28.00 Spur, slopes SW.; desc. 30 ft. over NW slope.

31.10 Wash, 10 lks. wide, course SW. asc. 100 ft. over SW slope.

40.00 Set an iron post 3 ft. long, 1 in. in diam., 6 ins. in the ground to bedrock, with stone 5x4x2 ins., mkd. with a cross (X) deposited at the base and in a mound of stone to top for 1/4 sec. cor., with brass cap mkd.



Asc. 51 ft. over SW slope.

49.00 Ridge, bears NE and SW, Desc. 105 ft. over NW slope.


57.50 Wash, 10 lks. wide, course SW. Asc. 69 ft. over SW slope.

62.00 Spur, slopes SW. Desc. 85 ft. over NW slope.

71.70 Wash, 10 lks. wide, course SW. Asc. 98 ft. over SW slope.

78.30 Spur, slopes SW.;

80.00 Set an iron post 3 ft. long, 2 ins. in diam., 8 ins. in the ground to bedrock, with a stone 8x6x4 ins., mkd. with a cross (X) deposited at the base, and in a mound of stone to top, for cor. of secs. 14, 15, 22, and 23, with brass cap mkd.



1939.

Land, rolling.
Soil, rocky 3rd. rate.
Timber, palo verde, and mesquite.
Undergrowth, greasewood and sage.

Chains	
	N. 89°55'E., on a random line, bet. secs. 14 and 23.
40.00	Set temp. 1/4 sec. cor.
80.00	Intersect N. and S. line 5 lks. N. of cor. of secs. 13, 14, 23 and 24.
	Thence,
	S. 89°57'W., on true line, bet. secs. 14 and 23.
	Over rolling hills, thru scattering timber & undergrowth.
	Desc. 82 ft. over NW slope.
5.60	Wash, 10 lks. wide, course SW. Asc. 81 ft. over SE slope.
12.40	Ridge, bears NE and SW. Desc. 61 ft. over SW slope.
18.40	Wash, 10 lks. wide, course SW.; asc. 83 ft. over SE slope.
26.00	Spur, slopes SW.; desc. 96 ft. over SW slope.
32.70	Wash, 10 lks. wide, course SW.; asc. 79 ft. over SE slope.
39.90	Spur, slopes SW.
40.00	Set an iron post 3 ft. long, 1 in. in diam., 10 ins. in the ground to bedrock, with stone 10x6x2 ins., mkd. with a cross (X) deposited at the base and in a mound of stone to top for 1/4 sec. cor., with brass cap mkd.
	$\frac{1}{4} \frac{S14}{S23}$
	1939
	Desc. 77 ft. over SW slope.
43.80	Wash, 10 lks. wide, course SW.; asc. 80 ft. over SE slope.
50.40	Ridge, bears NE and SW.; desc. 184 ft. over W. slope.
62.50	Wash, 10 lks. wide, course SW. Asc. 15 ft. over SE slope.
65.00	Spur, slopes SW.; over level top.
72.00	Desc. 36 ft. over SW slope.
74.20	Wash, 10 lks. wide, course SW.; asc. 67 ft. over SE slope.
79.00	Spur, slopes SW. Over level top.
80.00	The cor. of secs. 14, 15, 22, and 23.
	Land, rolling.
	Soil, rocky 4th. rate.
	Timber, paloverde and mesquite.
	Undergrowth, greasewood and cacti.

BOOK 4266

Completion of Subdivision of T.9 S., R.18 E.

Chains

N.0°01'W., bet. secs. 14 and 15.

Over rolling hills, thru scattering timber & undergrowth.


4.00 Wash, 10 lks. wide, course SW.; asc. 98 ft. over SE slope.

17.00 Ridge, bears NE and SW. Desc. 96 ft. over NW slope.

27.70 Wash, 10 lks. wide, course SW.; asc. 110 ft. over SW slope.

32.30 Spur, slopes SW.; desc. 59 ft. over NW slope.

40.00 Set an iron post 3 ft. long, 1 in. in diam., 12 ins. in the ground to bedrock, with stone 6x3x2 ins. mkd. with a cross (X) deposited at the base and in a mound of stone to top for 1/4 sec. cor., with brass cap mkd.



Desc. 46 ft. over NW slope.


47.30 Wash, 20 lks. wide, course SW.; asc. 34 ft. over SW slope.

53.60 Spur, slopes SW.; desc. 58 ft. over NW slope.

61.00 Junction of wash from east and wash from NE, 40 lks. wide, course SW.

73.80 Whitlock wash, 40 lks. wide, course S.10°W. Asc. 81 ft. over SE slope.

80.00 Set an iron post 3 ft. long, 2 ins. in diam., 14 ins. in the ground to bedrock, with stone 10x6x4 ins., mkd. with a cross (X) deposited at the base and in a mound of stone to top for cor. of secs. 10, 11, 14, and 15; with brass cap marked



Land, rolling.
Soil, rocky 4th. rate.
Timber, palo verde, and cacti.
Undergrowth, greasewood and cacti.

Chains	
	N.89°57'E., on a random line, bet. secs. 11 and 14.
40.00	Set temp. $\frac{1}{4}$ sec. cor.
80.00	Intersect N. and S. line, 7 lks. N. of cor. of secs: 11, 12, 13, and 14.
	Thence,
	West; on true line, bet. secs. 11 and 14.
	Over mountainous land, thru scattering timber & undergrowth.
	Desc. 125 ft. over NW slope.
10.50	Wash, 10 lks. wide, course S.70°W. Asc. 11 ft. over SE slope.
13.00	Low spur, slopes S.70°W. desc. 55 ft. over W slope.
21.30	Course SW.; asc. 135 ft. over SW. slope.
36.00	Spur, slopes SW.; desc. 39 ft. over NW slope.
40.00	Set an iron post 3 ft. long, 1 in. in diam., 14 ins. in the ground to bedrock, with stone 10x4x4 ins., mkd. with a cross (X) deposited at the base and in a mound of stone to top for $\frac{1}{4}$ sec. cor., with brass cap mkd.
	$\frac{1}{4}$ $\frac{S11}{S14}$
	June 1939
	Desc. 173 ft. over NW slope.
49.20	Wash, 15 lks. wide, course S.30°W.; asc. 40 ft. over SE slope.
56.70	Spur, slopes S.30°W.; desc. 112 ft. over NW slope.
70.90	Enter Whitlock wash, drains SW; across bottom.
74.80	Center of wash, 40 lks. wide, course SW. Asc. 69 ft. over SE slope.
80.00	The cor. of secs. 10, 11, 14, and 15.
	Land, mountainous. Soil, rocky 4th. rate. Timber, palo verde and mesquite. Undergrowth, greasewood and cacti.
	N.0°01'W., bet. secs. 10 and 11.
	Over mountainous land, thru scattering timber & undergrowth.
	Asc. 135 ft. over SE slope.
7.00	Spur, slopes SW.; desc. 30 ft. over NW slope.
9.00	Wash, 10 lks. wide, course SW.; asc. 89 ft. over SW slope.

Completion of Subdivision of T. 9 S., R. 18 E.

Chains

- 15.40 Road on ridge, bears N.78°E. and S.78°W. Desc. 69 ft. over NW slope.
- 21.90 Wash, 20 lks. wide, course S.80°W. Asc. 91 ft. over SW slope.
- 29.70 Ridge, bears N.80°E. and S.80°W. Desc. 151 ft. over NW slope.
- 37.20 Wash, 20 lks. wide, course S.60°W. Asc. 49 ft. over SW slope.
- 40.00 Set an iron post 3 ft. long, 1 in. in diam., 12 ins. in the ground to bedrock, with stone 10x6x4 ins., mkd. with a cross (X) deposited at the base, and in a mound of stone to top for 4 sec. cor., with brass cap mkd.

- 1/4
- S10 | S11
- 1939
- Asc. 67 ft. over SW slope.
- 44.00 Spur, slopes S.60°W. Desc. 134 ft. over NW slope.
- 48.10 Wash, 10 lks. wide, course S.60°W. Asc. 96 ft. over SW slope.
- 54.00 Spur, slopes SW.; desc. 148 ft. over NW slope.
- 63.50 Wash, 5 lks. wide, course S.70°W.; asc. 115 ft. over SW slope.
- 69.90 Spur, slopes SW.; desc. 114 ft. over N. slope.
- 70.60 4-strand barb.wire fence, bears E. and W.
- 77.00 Wash, 20 lks. wide, course W.; asc. 17 ft. S. slope.
- 80.00 Set an iron post 3 ft. long, 2 ins. in diam., 20 ins. in the ground to bedrock, with stone 10x6x6 ins., mkd. with a cross (X) deposited at the base, and in a mound of stone to top for cor. of secs. 2, 3, 10, and 11, with brass cap mkd.

T9SR18E
 S3 | S2
 S10 | S11.

1939

Land, rolling.
 Soil, rocky 4th. rate.
 Timber, palo verde, and mesquite.
 Undergrowth, greasewood, and cacti.

Completion of Subdivision of T.9 S., R.18 E.

Chains

East, on a random line, bet. secs. 2 and 11.

40.00 Set temp. $\frac{1}{4}$ sec. cor.

80.10 Intersect N. and S. line, 12 lks. S. of cor. of secs. 1, 2, 11, and 12.

Thence,

3.50 S. $89^{\circ}55'$ W., on true line, bet. secs. 2 and 11.
Wash, course SW.
Over hilly land, thru scattering timber & undergrowth.
Asc. 177 ft. over SE slope.

17.20 Wire fence, bears N. 70° E. and S. 70° W.

20.30 Road, bears NE and SW.

23.60 Ridge, bears NE and SW. Desc. 131 ft. over NW slope.

40.05 Set an iron post 3 ft. long, 1 in. in diam., 18 ins. in the ground to bedrock, with stone 10x6x4 ins., mkd. with a cross (X) deposited at the base and in a mound of stone to top for $\frac{1}{4}$ sec. cor. with brass cap mkd.

$\frac{1}{4}$ $\frac{\$2}{\$11}$

1939

Desc. 216 ft. over NW slope.

68.10 Wash, 30 lks. wide, course SW.; over rolling S. slope on slight ascent.

80.10 The cor. of secs. 2, 3, 10 and 11.

Land, hilly.
Soil, rocky 4th. rate.
Timber, paloverde and mesquite.
Undergrowth, greasewood and cacti.

N. $0^{\circ}18'$ W., on a random line, bet. secs. 2 and 3.

40.00 Set temp. $\frac{1}{4}$ sec. cor.

75.26 Intersect N. bdy. of Tp., 5 lks. W. of cor. of secs. 2, 3, 34, and 35, which is an iron post 2 ins. in diam., firmly set, projecting 14 ins. above ground and mound of stone, with brass cap mkd. and witnessed as described in the official record.

Thence,

S. $0^{\circ}16'$ E., on true line, bet. secs. 2 and 3.

Over mountainous land, thru scattering timber & undergrowth.
Asc. gradual NW slope.

Completion of Subdivision of T.9 N., R.18 E.

chains	
3.00	Ridge, bears E. and SW.; desc. 247 ft. on S. slope.
26.15	Wash, 20 lks. wide, course SW.; asc. 33 ft. on NW. slope.
35.26	Set a malpais stone, 14x16x24 ins., 14 ins. in the ground to bedrock, mkd. $\frac{1}{2}$ S 3 on W. face and S 2 on E. face (no iron post available); and raise a mound of stone, 4 ft. base and 2 ft. high, N. of cor. Asc. 111 ft. on NW. slope.
43.45	Ridge, bears NE. and SW.; desc. 155 ft. on S. slope.
55.25	Wash, 10 lks. wide, course SW.; asc. 92 ft. on NW. slope.
67.30	Spur, slopes SW.; desc. 122 ft. on SW. slope.
75.26	The cor. of secs. 2, 3, 10 and 11. Land, mountainous. Soil, rocky, 4th rate. Timber, palo verde and mesquite. Undergrowth, greasewood and cacti.

	From the $\frac{1}{4}$ sec. cor. of sec. 26 only, which is 40.00 chs. from the SE. cor. of sec. 26.
	North, on E. bdy. of sec. 26, counting measurement from said SE. cor.
	Over rolling land, thru scattering timber and undergrowth.
	Desc. gradual NW. slope.
41.00	40.00 chs. from the SW. cor. of sec. 27. Set an iron post, 3 ft. long, 1 in. diam., 27 ins. in the ground, for $\frac{1}{4}$ sec. cor. of sec. 27 only, with brass cap mkd. $\frac{1}{4}$ S27 1939 raise a mound of stone, 4 ft. base and 2 ft. high, W. of cor. Continue descent.
42.90	Wash, 10 lks. wide, course SW.; asc. 34 ft. on SW. slope.
47.60	Spur, slopes SW.; desc. 87 ft. on NW. slope.
53.20	Wash, 10 lks. wide, course SW.; asc. 64 ft. on SW. slope.
56.10	Spur, slopes SW.; desc. 46 ft. on NW. slope.
58.80	Wash, 10 lks. wide, course SW.; asc. 58 ft. on SW. slope.
62.30	Spur, slopes SW.; desc. 54 ft. on broken N. slope.
78.13	Set an iron post, 3 ft. long, 2 ins. diam., 14 ins. in the ground to bedrock, with stone, 10x6x4 ins., mkd. X, deposited at the base, and in a mound of stone to top, for cor. of secs. 21 and 28, only, with brass cap mkd.

chains

T9SR18E

S21	S27
S28	

1939

Thence

N.0°02'W., bet. secs. 21 and 27.

Continue descent on N. slope.

2.87 80.00 chs. from the SW. cor. of sec. 27.

Set an iron post, 3 ft. long, 2 ins. diam., 18 ins. in the ground to bedrock, with stone, 8x6x4 ins., mkd. X, deposited at the base, and in a mound of stone to top, for cor. of secs. 22 and 27, only, with brass cap mkd.

T9SR18E

S21	S22
	S27

1939

Land, rolling hills.

Soil, rocky, 4th rate.

Timber, palo verde and mesquite.

Undergrowth, greasewood and cacti.

East, on a random line bet. secs. 22 and 27.

40.00 Set temp. 1/4 sec. cor.

80.00 Intersect N. and S. line, 16 lks. S. of cor. of secs. 22, 23, 26 and 27.

Thence

S.89°53'W., on true line bet. secs. 22 and 27.

Over rolling hills, thru scattering timber and undergrowth.

Asc. 30 ft. on SE. slope.

2.40 Low spur, slopes SW.; desc. 136 ft. on NW. slope.

30.10 Wash, 20 lks. wide, course SW.; asc. 69 ft. on SE. slope.

34.50 Spur, slopes SW.; desc. 37 ft. on NW. slope.

40.00 Set an iron post, 3 ft. long, 1 in. diam., 18 ins. in the ground to bedrock, with stone, 8x6x2 ins., mkd. X, deposited at the base, and in a mound of stone to top, for 1/4 sec. cor., with brass cap mkd.

1/4 S22
S27

1939

Desc. 15 ft. on NW. slope.

41.00 Wash, 10 lks. wide, course N.; asc. 55 ft. on NE. slope.

Completion of Subdivision of T. 9 S., R. 18 E.

Chains.

- 41.40 4 strand barb wire fence, bears N. and S.
 62.10 Ridge, bears NW. and SE. Desc. 102 ft. over SW. slope.
 67.20 Wash, 30 lks. wide, course NW.; asc. 39 ft. over broken N. slope.
 80.00 The cor. of secs. 22 and 27.

Land, rolling.
 Soil, stony, 4th rate.
 Timber, paloverde and cacti.
 Undergrowth, greasewood and cacti.

N. 0° 02' W., bet. secs. 21 and 22.

Over rolling hills, thru scattering timber and undergrowth.
 Desc. 75 ft. over N. slope.

- 5.70 Wash, 40 lks. wide, course W.; asc. 109 ft. over S. slope.
 11.70 Asc. over vertical bank, 50 ft. high, bears E. and W.
 13.60 Spur, slopes SW.; desc. 99 ft. over NW. slope.
 20.20 Wash, 20 lks. wide, course NW. Over broken W. slope.
 38.40 Desc. 15 ft. over NW. slope.
 38.95 Wash, 10 lks. wide, course W.; asc. 10 ft. over SW. slope.
 40.00 Set an iron post, 3 ft. long, 1 in. diam., 12 ins. in the ground to bedrock, with stone 10x6x4 ins., mkd. with a cross (X) deposited at the base and in a mound of stone to top, for $\frac{1}{4}$ sec. cor., with brass cap mkd.

$\frac{1}{4}$
 S 21 | S 22
 1939

Asc. 233 ft. over SW. slope.

- 54.00 Edge of malpais bluff, bears N. and SW. Continue ascent over same.
 70.50 Rocky point, bears SW. Desc. 103 ft. along W. slope.
 80.00 Set an iron post, 3 ft. long, 2 ins. diam., 20 ins. in the ground to bedrock, with stone 8x4x2 ins., mkd. with a cross (X) deposited at the base and in a mound of stone to top, for cor. of secs. 15, 16, 21 and 22, with brass cap mkd.

T9S | R18E
 S 16 | S 15
 S 21 | S 22
 1939

Completion of Subdivision of T. 9 S., R. 18 E.

Chains.

Land, rolling, broken and hilly.
Soil, rocky, 4th. rate.
Timber, paloverde and mesquite.
Undergrowth, greasewood and cacti.

N. 89° 53' E., on a random line, bet. secs. 15 and 22.

40.00 Set temp. 1/4 sec. cor.

80.02 Intersect N. and S. line, 3 lks. S. of cor. of secs. 14, 15, 22 and 23.

Thence

S. 89° 52' W., on true line, bet. secs. 15 and 22.

Over rolling, rough hills, thru scattering timber and undergrowth.

Desc. 41 ft. over SW. slope.

2.10 Wash, 10 lks. wide, course SW.; asc. 140 ft. over SE. slope.

10.00 Spur, slopes SW.; desc. 104 ft. over SW. slope.

15.80 Wash, 10 lks. wide, course SW.; asc. 28 ft. over SE. slope.


20.40 Spur, slopes SW.; desc. 79 ft. over SW. slope.

25.70 Wash, 10 lks. wide, course SW.; asc. 69 ft. over SE. slope.

31.40 Spur, slopes SW. Desc. 77 ft. over SW. slope.

34.90 Wash, 10 lks. wide, course S.; asc. 63 ft. over E. slope.

40.01 Set an iron post, 3 ft. long, 1 in. in diam., 18 ins. in the ground to bedrock, with stone 8x5x2 ins., marked with a cross (X) deposited at the base and in a mound of stone to top, for 1/4 sec. cor., with brass cap mkd.



1939

Asc. gradual SE. slope.

42.00 Spur, slopes S.; desc. 57 ft. over W. slope.

47.20 Wash, 10 lks. wide, course NW.; asc. 22 ft. over NE. slope.

51.00 Spur, slopes N.; desc. 64 ft. over W. slope.

60.70 Head of canyon, drains N.; asc. 55 ft. over E. slope.

67.00 Spur, slopes NE. Over top.

74.00 Leave top; desc. 202 ft. over W. slope.

80.02 The cor. of secs. 15, 16, 21 and 22.

Land, rough and broken hills.

Completion of Subdivision of T. 9 S., R.18 E.

Chains

Soil, rocky 4th. rate.
Timber, palo verde and mesquite.
Undergrowth, greasewood and cacti.

N.0°02'W., bet. secs. 15 and 16.

Over rolling hills; thru scattering timber & undergrowth.

Desc. 102 ft. over NW slope.

10.50 Whitlock wash, 25 lks. wide, course W.; asc. 225 ft. over SE slope.


22.70 Ridge, with road on same, bears NE and SW. Over level top.

27.60 Desc. 102 ft. over NW slope.

32.80 Wash, 10 lks. wide, course NW.; asc. 43 ft. over SW slope.

36.60 Spur, slopes NW; desc. 20 ft. over NW slope.

40.00 Set an iron post 3 ft. long, 1 in. in diam., 24 ins. in the ground for 1/4 sec. cor., with brass cap mkd.



raise a mound of stone 4 ft. base, 2 ft. high W. of cor.


Desc. 57 ft. over NW slope.

44.80 Wash, 10 lks. wide, course SW.; asc. 229 ft. over SW slope.

69.50 Ridge, bears NE and SW.; desc. 99 ft. over NW slope.

76.10 Wash, 10 lks. wide, course SW.; asc. 41 ft. over SE slope.

80.00 Set an iron post 3 ft. long, 2 ins. in diam., 10 ins. in the ground to bedrock, with stone 10x6x4 ins., mkd. with a cross (X) deposited at the base and in a mound of stone to top for cor. of secs. 9, 10, 15, and 16, with brass cap marked



1939

Land, rolling hills.
Soil, rocky 4th. rate.
Timber, palo verde and mesquite.
Undergrowth, greasewood and cacti.

Chains	
	N. 89° 52' E., on a random line, bet. secs. 10 and 15.
40.00	Set temp. $\frac{1}{4}$ sec. cor.
80.00	Intersect N. and S. line 19 lks. N. of cor. of secs. 10, 11, 14, and 15.
	Thence,
	West, on true line, bet. secs. 10 and 15.
	Asc. 102 ft. over SE slope.
7.90	Spur, slopes SW.; desc. 69 ft. over SW slope.
12.10	Wash, 10 lks. wide, course S. 30° W. Asc. 39 ft. over SE slope.
18.20	Spur, slopes S.; desc. 26 ft. over W. slope.
20.60	Wash, 10 lks. wide, course S.; asc. 32 ft. over E. slope.
25.30	Ridge, bears N. 30° E. and S. 30° W. Road on same bears same. From this point US Geological Survey B.M. No. 3737 bears N. 30° E., 40 lks. dist.
	Desc. 96 ft. over W. slope.
35.60	Wash, 20 lks. wide, course S. 60° W.; asc. 64 ft. over SE slope.
40.00	Set an iron post 3 ft. long, 1 in. in diam., 10 ins. in the ground to bedrock, with stone 6x4x2 ins., mkd. with a cross (X) deposited at the base and in a mound of stone to top for $\frac{1}{4}$ sec. cor., with brass cap mkd.
	$\frac{1}{4} \frac{S10}{S15}$
	1939
	Asc. 11 ft. over SE slope.
43.00	Spur, slopes S. 60° W.; desc. 265 ft. over W slope.
64.10	Wash, 10 lks. wide, course S.; asc. 118 ft. over E. slope.
72.20	Spur, slopes S.; desc. 79 ft. over W. slope.
77.10	Wash, 10 lks. wide, course S. 20° W.; asc. 45 ft. over SE slope.
80.00	The cor. of secs. 9, 10, 15, and 16.
	Land, rolling, rough hills. Soil, rocky 4th. rate. Timber, palo verde and mesquite. Undergrowth, greasewood and cacti.

Completion of Subdivision of T. 9 S., R. 18 E.

Chains

N.0°02'W., bet. secs. 9 and 10.

Over rolling, hilly land, thru scattering timber & undergrowth.

Asc. 86 ft. over SE slope.


8.00 Spur, slopes SW.; desc. 209 ft. over NW slope.

22.50 Wash; 30 lks. wide, course SW.; asc. 99 ft. over SW slope.

32.00 Spur, slopes SW.; desc. 23 ft. over NW slope.

39.80 Wash, 10 lks. wide, course SW. Asc. slightly over SE slope.

40.00 Set an iron post 3 ft. long, 1 in. in diam., 26 ins. in the ground for 1/4 sec. cor., with brass cap marked




raise a mound of stone 4 ft. base, 2 ft. high, W. of cor.

Asc. 173 ft. over broken E. slope.

63.50 Continue over E. slope with little change in elevation.

80.00 Set an iron post 3 ft. long, 2 ins. in diam., 10 ins. in the ground to bedrock, with stone 10x6x4 ins., mkd. with a cross (X) deposited at the base and in a mound of stone to top for cor. of secs. 3, 4, 9, and 10, with brass cap mkd.



Land, rolling hills..
Soil, stony 4th. rate.
Timber, palo verde and mesquite.
Undergrowth, greasewood and cacti.

East, on a random line, bet. secs. 3 and 10.

40.00 Set temp. 1/4 sec. cor.

80.00 Intersect N. and S. line, 6 lks. N. of cor. of secs. 2, 3, 10 and 11.

Thence,

N.89°57'W., on true line, bet. secs. 3 and 10.

Over rolling land; thru scattering timber and undergrowth.

Desc. 71 ft. over SW slope.

42 . Completion of Subdivision of T.9 S., R.18 E.


Chains	
9.70	Wash, 20 lks. wide, course S.20°W. Asc. 63 ft. over SE slope.
12.80	4-strand barb wire fence, bears N. and S.
26.30	Spur, slopes SW.; desc. 110 ft. over SW slope.
38.00	Wash, 20 lks. wide, course S. asc. 34 ft. over SE slope.
40.00	Set an iron post 3 ft. long, 1 in. in diam., 22 ins. in the ground to bedrock, with stone 10x6x4 ins., mkd. with a cross (X) deposited at the base and in a mound of stone to top for ¼ sec. cor., with brass cap mkd.
	$\frac{1}{4} \frac{S3}{S10}$ <p>1939</p>
	Asc. 96 ft. over SE slope.
48.00	Spur, slopes S.; desc. 47 ft. over W. slope.
52.10	Wash, 10 lks. wide, course S.20°W.; asc. 97 ft. over east slope.
57.40	Spur, slopes S.; desc. 161 ft. over W. slope.
65.30	Wash, 10 lks. wide, course south, asc. 82 ft. over E. slope.
71.30	Spur, slopes SW. Desc. 83 ft. over W. slope.
76.00	Wash, 10 lks. wide, course S.10°W.; asc. 77 ft. over SE slope.
80.00	<p>The cor. of secs. 3, 4, 9, and 10.</p> <p>Land, rolling hills. Soil, gravelly and rocky 4th. rate. Timber, palo verde and mesquite. Undergrowth, greasewood and cacti.</p>
	N.0°16'W. on a random line, bet. secs. 3 and 4.
40.00	Set temp. ¼ sec. cor.
75.24	Intersect N. bdy. of Tp. at cor. of secs. 3, 4, 33, and 34, which is an iron post 2 ins. in diam., firmly set, projecting 14 ins. above ground, with brass cap mkd. and witnessed as described in the official record.
	Thence,
	S.0°16'E., on true line, bet. secs. 3 and 4.
	Over rolling, hilly land, thru scattering timber and undergrowth.
	Asc. 194 ft. over NW slope.
9.65	Spur, slopes SW.; desc. 130 ft. over SE slope.
18.45	Wash, 10 lks. wide, course SW.; asc. 93 ft. over NW slope.

Completion of Subdivision of T. 9 S., R. 18 E.

Chains

24.25 Spur, slopes SW.; desc. 115 ft. over SE slope.

35.24 (40.00 chs. in latitude from cor. of secs. 3, 4, 9, and 10)
Set an iron post 3 ft. long, 1 in. in diam., 8 ins. in the ground to bedrock, with stone 10x6x4 ins., mkd. with a cross (X) deposited at the base and in a mound of stone to top for $\frac{1}{4}$ sec. cor., with brass cap marked



Desc. 120 ft. over SE slope.

45.25 Wash, 50 lks. wide, course SW.; asc. 120 ft. over NW slope.

57.25 Ridge, bears NE and SW. Desc. 118 ft. over SE slope.

75.24 The cor. of secs. 3, 4, 9, and 10.


Land, rough and hilly.
Soil, rocky 4th. rate.
Timber, palo verde, and mesquite.
Undergrowth, greasewood and cacti.

From $\frac{1}{4}$ sec. cor. of secs. 28 and 29.
North., bet. secs. 28 and 29, continuing measurement.
Over rolling land, thru scattering timber & undergrowth.
Asc. 65 ft. over SE slope.

55.30 Ridge, bears NE and SW.; desc. 205 ft. over NW slope.

64.60 Wash, 10 lks. wide, course S.70°W.; asc. 203 ft. over SE slope.

77.78 A point East of the cor. of secs. 19, 20, 29, & 30.
Set an iron post 3 ft. long, 2 ins. in diam., 10 ins. in the ground to bedrock, with stone 10x6x4 ins., mkd. with a cross (X) deposited at the base, and in a mound of stone to top for cor. of secs. 20, 21, 28, & 29, with brass cap marked



Land, rolling hills.
Soil, stony 4th. rate.
Timber, palo verde and mesquite.
Undergrowth, greasewood and cacti.

Chains	<p>From the cor. of secs. 21 and 28 only, West, on true line, bet. secs. 21 and 28. Over rolling hills, thru scattering timber & undergrowth. Desc. 199 ft. over NW slope.</p>
38.80	Whitlock wash, 30 lks. wide, course SW. Over washed land.
40.15	(Midpoint) set an iron post 3 ft. long, 1 in. in diam., 20 ins. in the ground to bedrock, with stone 10x6x2 ins., mkd. with a cross (X) deposited at the base and in a mound of stone to top for $\frac{1}{4}$ sec. cor. with brass cap mkd.
	$\frac{1}{4} \frac{S21}{S28}$ 1939
47.00	Leave washed land; asc. 97 ft. over SE slope.
60.60	Ridge, bears NE and SW.; Desc. 104 ft. over SW slope.
69.00	Ravine, course SW.; asc. 40 ft. over SE. slope.
69.70	Spur, slopes SW.; desc. 101 ft. over SW slope.
73.50	Wash, 10 lks. wide, course SW.; asc. 138 ft. over SE slope.
79.00	Spur, slopes SW.; desc. 32 ft. over SW slope.
80.30	The cor. of secs. 20, 21, 28, and 29. Land, rolling hills. Soil, stony 4th. rate. Timber, paloverde and mesquite. Undergrowth, greasewood and cacti.
	<hr/> West, on true line, bet. secs. 20 and 29. Over rolling hills, thru scattering timber and undergrowth. Asc. 16 ft. over SE slope.
12.00	Spur, slopes S.60°W. Desc. 156 ft. over NW slope.
24.60	Wash, 10 lks. wide, course S.60°W.; asc. 29 ft. over broken SE slope.
40.00	Set an iron post 3 ft. long. 1 in. in diam., 10 ins. in the ground to bedrock, with stone 8x4x3 ins., mkd. with a cross (X) deposited at the base and in a mound of stone to top for $\frac{1}{4}$ sec. cor., of section 20 only , with brass cap mkd.
	$\frac{1}{4} \frac{S20}{S21}$ 1939
40.84	(Proportionate point) set an iron post 3 ft. long, 1 in.

Completion of Subdivision of T.9 S., R.18 E.

45

Chains

in diam., 10 ins. in the ground to bedrock, with stone 10x3x2 ins., mkd. with a cross (X) deposited at the base, and in a mound of stone to top, for $\frac{1}{4}$ sec. cor. of sec. 29, only, with brass cap marked

$\frac{1}{4}$ S 29

1939

Continue gradual ascent.


- 50.80 Ridge, bears N.75°E. and S.75°W. Desc. 217 ft. over NW slope.
- 52.70 Road, bears N.75°E., and S.75°W.
- 69.00 Wash, 30 lks. wide, course SW.; asc. 136 ft. over SE slope.
- 81.68 The cor. of secs. 19, 20, 29, and 30.

Land, rolling hills.
Soil, stony 4th. rate.
Timber, palo verde and mesquite.
Undergrowth, greasewood and cacti.

From cor. of secs. 16, 17, 20, and 21, established west of the cor. of secs. 15, 16, 21, and 22, hereinafter described.

S.0°02'E., on a random line, bet. secs. 20 and 21.

- 40.00 Set temp. $\frac{1}{4}$ sec. cor.
- 83.01 Intersect E. and W. line, 22 lks. E. of cor. of secs. 20, 21, 28, and 29.
- Thence,
- N.0°07'E., on true line, bet. secs. 20 and 21.
- Over rolling hilly land, thru scattering timber & undergrowth.
- Asc. 46 ft. over S. slope.
- 4.00 Spur, slopes W.; desc. 68 ft. over NW slope.
- 14.90 Wash, 10 lks. wide, course SW.; asc. 103 ft. over SW slope.
- 20.20 Ridge, bears NE and SW.; across level top.
- 24.30 Road, bears NE and SW.; leave ridge, desc. 34 ft. over N. slope.
- 32.50 Wash, 10 lks. wide, course SW.; asc. 71 ft. over S. slope.
- 38.50 Spur, slopes SW.; desc. 30 ft. over NW. slope.
- 42.30 Wash, 10 lks. wide, course SW.; asc. 5 ft. over SE slope.
- 43.01 (40.00 chs. in lat. from cor. of secs. 16, 17, 20, & 21.)

Chains	
	Set an iron post $\frac{3}{4}$ ft. long, 1 in. in diam., 28 ins. in the ground for $\frac{1}{4}$ sec. cor., with brass cap marked
	
	raise a mound of stone 4 ft. base, 2 ft. high W. of cor.
	Asc. 43 ft. over SE slope.
47.00	Top of ascent; across level land.
52.10	Spur, slopes SW.; desc. 17 ft. over NW slope.
60.10	Wash, 10 lks. wide, course SW.; asc. 22 ft. over SE slope.
65.75	Spur, slopes SW.; from this point, the S. end of earth dam bears S. $78\frac{1}{2}^{\circ}$ E., 17.26 chs. distant.
73.00	Ridge, bears NE and SW.; desc. 75 ft. over N. slope.
77.10	Wash, 10 lks. wide, course S. 70° W.; asc. 50 ft. over SW slope.
83.01	The cor. of secs. 16, 17, 20, and 21. Land, rolling hills. Soil, rocky 4th. rate. Timber, palo verde, and mesquite. Undergrowth, greasewood and cacti.
	#
	East, on a random line, bet. secs. 16 and 21.
40.00	Set temp. $\frac{1}{4}$ sec. cor.
80.00	Intersect N. and S. line at cor. of secs. 15, 16, 21, and 22.
	Thence, West, on true line, bet. secs. 16 and 21. Over rolling hills, thru scattering timber & undergrowth. Desc. 75 ft. over W. slope, into WHITLOCK wash.
4.60	Wash, 30 lks. wide, course S.; asc. 54 ft. over E. slope.
17.60	Road, on ridge, both bear N. 45° E. and S. 45° W. Desc. 57 ft. over SW slope.
22.90	Wash, 10 lks. wide, course SW.; asc. 39 ft. over SE slope.
29.50	Spur, slopes SW.; desc. 76 ft. over SW slope.
34.80	Wash, 20 lks. wide, course S. 80° W.; asc. 27 ft. over SE slope.
37.30	Tip of spur, slopes S.; desc. 12 ft. over SW slope.

Completion of Subdivision of T. 9 S., R. 18 E.

47

Chains

40.00 Set an iron post 3 ft. long, 1 in. in diam., 18 ins. in the ground to bedrock, with stone 10x6x4 ins., mkd. with a cross (X) deposited at the base and in a mound of stone to top for $\frac{1}{4}$ sec. cor., with brass cap marked

$$\frac{S16}{S21}$$

1939

Desc. 29 ft. over SW slope.

44.00 Wash, 10 lks. wide, course SW (from N.). asc. 26 ft. over SE slope.

58.00 Spur, slopes SW.; desc. 93 ft. over W. slope.

69.40 Junction of washes from NE and N., thence SW.; asc. 27 ft. over SE slope.

78.90 Spur, slopes S.; desc. 34 ft. over W. slope.

80.00 Set an iron post 3 ft. long, 2 ins. in diam., 12 ins. in the ground to bedrock, with stone 10x6x4 ins., mkd. with a cross (X) deposited at the base, and in a mound of stone to top for cor. of secs. 16, 17, 20, and 21, with brass cap mkd.

$$\begin{array}{c} T9SR18E \\ S17 | S16 \\ S20 | S21 \end{array}$$

1939.

Land, rolling hills.
Soil, rocky 4th. rate.
Timber, palo verde and mesquite.
Undergrowth, greasewood, and cacti.

N.0°02'W., bet. secs. 16 and 17.

Over rolling hills, & thru scattering timber & undergrowth.

Asc. 29 ft. over SW slope.

4.00 Spur, slopes SW.; desc. 19 ft. over NW slope.

6.70 Wash, 10 lks. wide, course S.20°W.; asc. 82 ft. over SE slope.

13.00 Ridge, bears NE and SW.; across level top.


26.00 Leave level land; desc. 56 ft. over NW slope.

38.50 Wash, 10 lks. wide, course SW.; asc. 17 ft. over SE slope.

40.00 Set an iron post 3 ft. long, 1 in. in diam., 24 ins. in the ground for $\frac{1}{4}$ sec. cor., with brass cap marked.

Completion of Subdivision of T. 9 S., R. 18 E.

Chains



raise a mound
of stone 4 ft. base, 2 ft. high W. of cor.

Desc. 6 ft. over NW slope.

Little Gust James

41.20 Wash, 150 lks. wide, course SW.; across level bottom.

42.70 Foot of bank, 70 ft. high, bears NE and SW. Asc. same.

43.50 Top of bank; spur, slopes SW.; desc. 61 ft. over NW slope.

50.30 Wash, 20 lks. wide, course S.30°W.; asc. 62 ft. over SW slope.


66.40 Spur, slopes SW.; desc. 58 ft. over NW slope.

70.20 Wash, 10 lks. wide, course SW.; asc. 85 ft. over SW slope.

74.00 Spur, slopes SW.; across level bottom.

76.30 Spur, slopes SW.; desc. 41 ft. over NW slope.

80.00 Set an iron post 3 ft. long, 2 ins. in diam., 22 ins. in the ground to bedrock, with stone 10x6x4 ins., mkd. with a cross (X) deposited at the base and in a mound of stone to top for cor. of secs. 8, 9, 16, and 17, with brass cap mkd.



Land, rolling hills.
Soil, rocky 4th. rate.
Timber, palo verde, and mesquite.
Undergrowth, greasewood, and cacti.

East, on a random line, bet. secs. 9 and 16.

40.00 Set temp. 1/4 sec. cor.

80.00 Intersect N. and S. line, 12 lks. N. of cor. of secs. 9, 10, 15, and 16.

Thence,

N.89°55'W., on true line, bet. secs. 9 and 16.

Over rolling hills, thru scattering timber & undergrowth.

Asc. 49 ft. over SE slope.

5.30 Spur, slopes SW.; desc. 84 ft. over W. slope.

10.50 Wash, 10 lks. wide; course S.; asc. 66 ft. over E. slope.


15.00 Spur, slopes S.; desc. 217 ft. over NW slope.

Completion of Subdivision of T.9 S., R.18 E.

Chains	
40.00	Set an iron post $\frac{3}{4}$ ft. long, 1 in. in diam., 28 ins. in the ground for $\frac{1}{4}$ sec. cor., with brass cap mkd.
	$\frac{S9}{\frac{1}{4} S16}$
	1939
	of stone 4 ft. base, 2 ft. high, N. of cor. raise a mound
	Desc. gradually over NW slope.
42.50	Wash, 2 chs. wide, course SW.; asc. 69 ft. over SE slope.
56.50	Spur, slopes SW.; desc. 67 ft. over NW slope.
63.90	Wash, 10 lks. wide, course SW.; asc. 60 ft. over SE slope.
75.00	Spur, slopes SW. Desc. 67 ft. over NW slope.
80.00	The cor. of secs. 8, 9, 16, and 17.
	Land, rolling hills. Soil, rocky 4th. rate. Timber, palo verde and mesquite. Undergrowth, greasewood and mesquite.
	N.0°02'W., bet. secs. 8 and 9.
	Over rolling hills, thru scattering timber & undergrowth.
	Desc. 29 ft. over NW slope.
1.70	Wash, 10 lks. wide, course S.60°W.; asc. 78 ft. over SE slope.
8.00	Spur, slopes SW.; desc. 82 ft. over NW slope.
12.80	Wash, 10 lks. wide, course SW.; asc. 108 ft. over SE slope.
19.60	Spur, slopes SW.; desc. 118 ft. over NW slope.
24.40	Wash, 10 lks. wide, course W.; asc. 70 ft. over S. slope.
28.00	Spur, slopes SW.; desc. 20 ft. over W. slope.
37.80	Gust James Wash, 10 lks. wide, course SW.; asc. 23 ft. over SE slope.
40.00	Set an iron post $\frac{3}{4}$ ft. long, 1 in. in diam., 24 ins. in the ground for $\frac{1}{4}$ sec. cor., with brass cap mkd..
	$\frac{S8}{\frac{1}{4} S9}$
	1939
	of stone 4 ft. base, 2 ft. high, W. of cor. raise a mound

Chains


- Asc. 165 ft. over SE slope.
- 52.50 Spur, slopes SW.; desc. 119 ft. over NW slope.
- 58.30 Wash, 10 lks. wide, course W.; asc. 77 ft. over S. slope.
- 63.00 Spur, slopes SW.; desc. 75 ft. over NW slope.
- 69.20 Wash, 10 lks. wide, course SW.; asc. 142 ft. over SE slope.
- 79.20 Ridge, bears East to SW.; desc. 13 ft. over N. slope.
- 80.00 Set an iron post 3 ft. long, 2 ins. in diam., 10 ins. in the ground to bedrock, with stone 10x4x3 ins., mkd. with a cross(X) deposited at the base and in a mound of stone to top for cor. of secs. 4, 5, 8, and 9, with brass cap marked



Land, rolling hills..
Soil, stony 4th. rate.
Timber, paloverde and mesquite.
Undergrowth, greasewood and cacti.

E.89°55'E., on a random line, bet. secs. 4. and 9.

- 40.00 Set temp. 1/4 sec. cor.
- 79.98 Intersect N. and S. line at corner of secs. 3, 4, 9, and 10.
Thence,
N.89°55'W., on true line, bet. secs. 4 and 9.
Over high rolling hills, thru scattering timber & undergrowth.
Asc. 80 ft. over SE slope.
- 5.00 Ridge, bears NE and SW.; desc. 238 ft. over NW slope.
- 21.80 Big wash, 60 lks. wide, course SW.; asc. 146 ft. over SE slope.
- 33.00 Spur, slopes SW.; desc. 52 ft. over SW slope.
- 36.70 Wash, 10 lks. wide, course SW.; asc. 45 ft. over SE slope.
- 39.99 Set an iron post 3 ft. long, 1 in. in diam., 14 ins. in the ground to bedrock, with stone 8x6x4 ins., mkd. with a cross (X) deposited at the base and in a mound of stone to top for 1/4 sec. cor., with brass cap mkd..



Completion of Subdivision of T. 9 S., R. 18 E. 51

Chains	
	Asc. 47 ft. over SE slope.
44.00	Spur, slopes SW.; desc. 156 ft. over SW slope.
51.70	Wash, 10 lks. wide, course SW.; asc. 57 ft. over SE slope.
56.00	Spur, slopes SW.; desc. 86 ft. over NW slope.
61.50	Wash, 10 lks. wide, course SW.; asc. 51 ft. over SE slope.
75.20	Spur, slopes SW.; desc. 84 ft. over NW slope.
79.98	The cor. of secs. 4, 5, 8, and 9.
	Land, rolling hills. Soil, rocky 4th. rate. Timber, palo verde and mesquite. Undergrowth, greasewood and cacti.
	N.0°16'W., on a random line, bet. secs. 4 and 5.
40.00	Set temp. $\frac{1}{4}$ sec. cor.
75.38	Intersect N. bdy. of Tp., at 3 lks. W. of cor. of secs. 4, 5, 32, and 33, which is an iron post 2 ins. in diam., firmly set, mkd. properly on brass cap, projecting 14 ins. above ground, witnessed as described in the official record.
	Thence,
	S.0°15'E., on true line, bet. secs. 4 and 5.
	Over rolling high hills, thru scattering timber & undergrowth.
	Asc. 263 ft. over NW slope.
32.80	Top of ascent; along nearly level W. slope.
35.38	(40.00 chs. in latitude from cor. of secs. 4, 5, 8, and 9.) Set an iron post 3 ft. long, 1 in. in diam., 24 ins. in the ground for $\frac{1}{4}$ sec. cor., with brass cap marked
	$\frac{1}{4}$ S5 S4 1939
	of stone 4 ft. base, 2 ft. high, W. of cor. raise a mound
	Continue along west slope.
41.50	Ridge, bears N. to SW.; desc. 233 ft. over SE slope.
57.60	Wash, 20 lks. wide; course SW.; asc. 67 ft. over NW slope.
64.00	Spur, slopes SW.; desc. 96 ft. over S. slope.
67.35	Wash, 10 lks. wide, course W.; asc. 118 ft. over N. slope.

Chains

75.38 The cor. of secs. 4, 5, 8, and 9.

Land, rolling hills.
Soil, rocky 3rd. & 4th. rate.
Timber, palo verde, and mesquite.
Undergrowth, greasewood and cacti.

From cor. of secs. 19, 20, 29, and 30.

North, bet. secs. 19 and 20.

Over broken, rolling land, thru scattering timber and undergrowth.

Asc. 13 ft. over SE slope.

1.80 Spur, slopes SW.; desc. 29 ft. over NW slope.

10.00 Wash, 10 lks. wide, course SW.; asc. 70 ft. over S. slope.

16.00 Spur, slopes SW.; desc. 23 ft. over NW slope.

25.20 Wash, 10 lks. wide, course SW.; asc. 57 ft. over SW slope.

30.00 Spur, slopes SW.; desc. 45 ft. over NW slope.

36.20 Wash, 10 lks. wide, course SW.; asc. 41 ft. over SE slope.

40.00 Set an iron post 3 ft. long, 1 in. in diam., 18 ins. in the ground to bedrock, with stone 10x6x4 ins., mkd. with a cross (X) deposited at the base, and in a mound of stone to top for $\frac{1}{4}$ sec. cor. of sec. 19 only, with brass cap mkd.

$\frac{1}{4}$ S 19

1939

Asc. 14 ft. over SE slope.

42.87 Set an iron post 3 ft. long, 1 in. in diam., .24 ins. in the ground for $\frac{1}{4}$ sec. cor. of sec. 20 only, with brass cap mkd..

$\frac{1}{4}$ S20

1939

raise a mound
of stone 4 ft. base, 2 ft. high E. of cor.

45.80 Spur, slopes SW.; desc. 100 ft. over vertical bank.

45.90 Foot of bluff, continue over bottom land.

47.80 Wash, 40 lks. wide, course SW.; continue over bottom.

50.00 Leave bottom; asc. 80 ft. over SE slope.

62.40 Narrow spur, slopes SW.; desc. 64 ft. over NW slope.

65.30 Wash, 20 lks. wide, course S.20°W.; asc. 91 ft. over SW slope.

Chains

72.30 Spur, slopes SW.; desc. 89 ft. over NW. slope.

80.00 A point E. of the cor. of secs. 13, 18, 19 and 24, on W. bdy. of the Tp.

Set an iron post, 3 ft. long, 2 ins. diam., 18 ins. in the ground to bedrock, with a stone 14 x 10 x 7 ins. mkd. with a cross (X) deposited at the base, and in a mound of stone to top, for cor. of secs. 19 and 20 only, with brass cap mkd.

T9S	R18E
S 18	
S 19	S 20
1939	

Land, rolling and broken.
Soil, rocky, 4th rate.
Timber, palo verde and mesquite.
Undergrowth, greasewood and cacti.

From the cor. of secs. 16, 17, 20 and 21.

West, on true line bet. secs. 17 and 20.

Over rolling and broken land, through scattering timber and undergrowth.

Desc. 28 ft. over SW. slope.

1.30 Wash, from N.20°E. to SW.; asc. 100 ft. over E. slope.

12.00 Ridge; bears NE. and SW.; over level mesa.

29.60 Leave mesa; desc. 107 ft. over W. slope.

34.50 Little Gust James Wash, 2 chs. wide, course SW.; asc. 28 ft. over SE. slope.

40.00 Set an iron post, 3 ft. long, 1 in. diam., 28 ins. in the ground for $\frac{1}{4}$ sec. cor., with brass cap mkd.

$\frac{1}{4}$	S 17
	S 20
1939	

of stone, 4 ft. base, 2 ft. high, N. of cor. raise a mound

Asc. 42 ft. over SE. slope.

42.75 Spur, slopes S.; over broken land.

67.00 Desc. 205 ft. over NW. slope.

80.00 Set an iron post, 3 ft. long, 2 ins. diam., 28 ins. in the ground for cor. of secs. 17 and 20 only, with brass cap mkd.

Chains

T 9 S	R 18 E
S 18	S 17
	S 20

1939

Land, rolling and broken.
 Soil, stony, 3d and 4th rate.
 Timber, palo verde and mesquite.
 Undergrowth, greasewood and cacti.

From the cor. of secs. 13, 18, 19 and 24, on the W. bdy. of the Tp.

East, on true line bet. secs. 18 and 19.

Asc. 190 ft. over NW. slope, over rolling and broken land, through scattering timber and undergrowth.

28.90 Ridge, bears NE. and SW.; desc. 57 ft. over E. slope.

39.20 Wash, 15 lks. wide, course S. for 1 ch., then W.; asc. 40 ft. over vertical bank.

39.44 Point for $\frac{1}{4}$ sec. cor. of sec. 19 falls on washed land, impracticable to set cor.

39.96 Point for $\frac{1}{4}$ sec. cor. of sec. 18 falls on washed land, impracticable to set cor.

41.01 Set an iron post, 3 ft. long, 1 in. diam., 14 ins. in the ground to bedrock, with a stone 10 x 6 x 4 ins., mkd. with a cross (X) deposited at the base, and in a mound of stone to top, for witness $\frac{1}{4}$ sec. cor. of sec. 19, and witness $\frac{1}{4}$ sec. cor. of sec. 18, with brass cap mkd.

WC $\frac{1}{4}$	S 18
	S 19

1939

Asc. 179 ft. over NW. slope.

62.90 Spur, slopes SW.; desc. 166 ft. over SE. slope.

71.20 Wash, 15 lks. wide, course S. 20° W.; asc. 108 ft. over NW. slope.

77.91 The cor. of secs. 19 and 20.

Completion of Subdivision of T. 9 S., R.18 E.

Chains

Continue line and measurement, on S. bdy. of sec. 18.

79.96 A point 2.87 chs. S. 0°03' E. of the cor. of secs. 17 and 20.

Set an iron post 3 ft. long, 2 ins. in diam., 20 ins. in the ground to bedrock, with stone 8x4x2 ins., mkd. with a cross (X) deposited at the base and in a mound of stone to top for cor. of sec. 18, only, with brass cap marked

T9SR18E
S18

S20

1939.

Land, rolling and broken, gypsum and malpais formation. Soil, stony and poor gumbo, 4th. rate. Timber, palo verde and mesquite. Undergrowth, greasewood and cacti.

From cor. of secs. 17 and 20, only, hereinbefore described.

N. 0°03' W., on west bdy. of sec. 17.

Over rolling and broken land, thru scattering timber and undergrowth.

Asc. 15 ft. over SW slope.

.50 Spur, slopes W.; desc. 39 ft. over NW slope.

1.70 Wash, 15 lks. wide, course SW.; to junction with wash from North. Asc. 40 ft. over vertical bank of wash.

1.80 Top of bank, bears NE and SW. Asc. 23 ft. over washed W. slope.

10.00 Wash, 10 lks. wide, course SW.; asc. 140 ft. over SE. slope.

19.00 Ridge, bears N^E and SW.; desc. 117 ft. over NW slope.

23.70 Wash, 10 lks. wide, course S. 70° W. Asc. 43 ft. over SE slope.

27.00 Spur, slopes W.; desc. 96 ft. over NW slope.

36.30 Wash, 10 lks. wide, course W.; asc. 77 ft. over S. slope.

40.00 Set an iron post 3 ft. long, 1 in. in diam., 24 ins. in the ground for $\frac{1}{4}$ sec. cor., with brass cap mkd.

$\frac{1}{4}$

S18 | S17

1939.

raise a mound of stone 4 ft. base, 2 ft. high N. of cor.

Chains

Asc. 33 ft. over rolling S. slope.

71.90 Wash, 10 lks. wide, course SW.

80:00 Set an iron post 3 ft. long, 2 ins. in diam., 28 ins. in the ground for cor. of secs. 7, 8, 17, and 18, with brass cap marked

T9SR18E	
S7	S8
S18	S17

1939

of stone 4 ft. base, 2 ft. high W. of cor. raise a mound

Land, rolling and broken.
Soil, stony and sandy 4th. rate.
Timber, palo verde, and mesquite.
Undergrowth, greasewood and mesquite.

East, on a random line, bet. secs. 8 and 17.

40.00 Set temp. 1/4 sec. cor.

79.98 Intersect cor. of secs. 8, 9, 16, and 17.

Thence,

West, on true line, bet. secs. 8 and 17.

Over high, rolling land, thru scattering timber and undergrowth.

Desc. 25 ft. over NW slope.

2.50 Wash, 10 lks. wide, course S.60°W.; asc. 38 ft. over SE slope.

4.00 Spur, slopes SW; desc. 157 ft. over NW slope.

32.60 Wash, 10 lks. wide, course SW.; asc. 82 ft. over SE slope.

35.80 Spur, slopes SW.; desc. 30 ft. over NW slope.

39.99 Set an iron post 3 ft. long, 1 in. in diam., 6 ins. in the ground to bedrock, with stone 10x6x4 ins., mkd. with a cross (X) deposited at the base and in a mound of stone to top for 1/4 sec. cor., with brass cap mkd.

1/4	S8
	S17

1939

Asc. 18 ft. over SE slope.

46.00 Spur, slopes SW.; desc. 168 ft. over W. slope.
Gust James

59.40 Wash, 10 lks. wide, course S.60°W.

Completion of Subdivision of T. 9 S., R. 18 E.

Chains

79.98 The cor. of secs. 7, 8, 17 and 18.

Land, rolling high hills.
Soil, stony 4th. rate.
Timber, palo verde, and mesquite.
Undergrowth, greasewood and cacti.

West, on true line, bet. secs. 7 and 18.


Over rolling land, thru scattering timber & undergrowth.

Desc. 85 ft. over gradual SW slope.

27.90 Wash, 10 lks. wide, course SW.;

38.80 Wash, 40 lks. wide, course SW.

40.00 Set an iron post 3 ft. long, 1 in. in diam., 14 ins. in the ground to bedrock, with stone 10x6x4 ins., mkd. with a cross (X) deposited at the base and in a mound of stone to top for 1/4 sec. cor., with brass cap mkd.



1939

Asc. 51 ft. over broken E. slope.

44.00 Ridge, bears NE and SW. Desc. 159 ft. over NW slope.


60.00 Wash, 20 lks. wide, course SW, from N.85°E. Asc. 55 ft. over E. slope.

73.20 Spur, slopes S.; desc. 20 ft. over W. slope.

75.00 Wash, 10 lks. wide, course SW.; asc. 47 ft. over E. slope.

82.07 Intersect W. bdy. of Tp., 424 lks. N.0°06'W. of cor. of secs. 12 and 13, hereinbefore described.

At point for cor.; set an iron post 3ft. long, 2 ins. in diam., 14 ins. in the ground to bedrock, with stone 10x5x4 ins., mkd. with a cross (X) deposited at the base, and in a mound of stone to top for cor. of secs. 7 and 18, with brass cap mkd. closing



1939

Land, rolling. Soil; rocky 4th. rate. Timber, paloverde, and mesquite. Undergrowth, greasewood and cacti.

From cor. of secs. 7, 8, 17 and 18.

N.0°03'W., bet. secs. 7 and 8.


Over rolling land, thru scattering timber & undergrowth.

Chains

18.00 Wash, 30 lks. wide, course SW.

29.30 Wash, 40 lks. wide, course SW.

40.00 Set an iron post 3 ft. long, 1 in. in diam., 22 ins. in the ground to bedrock, with stone 10x6x4 ins., mkd. with a cross (X) deposited at the base and in a mound of stone to top for $\frac{1}{4}$ sec. cor., with brass cap mkd.




48.70 Wash, 20 lks. wide, course SW.;

51.70 Wash, 5 lks. wide, course S.30°W.

60.50 Begin ascent over S. slope. 194 ft.

80.00 Set an iron post 3 ft. long, 2 ins. in diam., 28 ins. in the ground for cor. of secs. 5, 6, 7, and 8, with brass cap marked



Land, rolling.
Soil, stony 4th. rate.
Timber, palo verde, and mesquite.
Undergrowth, greasewood and cacti.

East, on a random line, bet. secs. 5 and 8.

40.00 Set temp. $\frac{1}{4}$ sec. cor.

80.00 Intersect cor. of secs. 4, 5, 8, and 9.

Thence,

West, on true line, bet. secs. 5 and 8.

Over rolling, high hills, thru scattering timber and undergrowth.

Desc. 178 ft. over NW slope.

14.00 Wash, 40 lks. wide, course SW.; asc. 91 ft. over SE slope.

23.00 Ridge, bears NE and SW.; desc. 96 ft. over NW slope.

28.00 Wash, 10 lks. wide, course SW.; asc. 13 ft. over SE slope.

31.00 Tip of spur, slopes S.; desc. 60 ft. over SW. slope.

37.30 Shallow wash, course S.; asc. 45 ft. over E. slope.

40.00 Set an iron post 3 ft. long, 1 in. in diam., 18 ins. in the ground to bedrock, with stone 8x6x2 ins., mkd. with a

Chains

cross (X) deposited at the base, and in a mound of stone to top for $\frac{1}{4}$ sec. cor., with brass cap mkd.

$\frac{1}{4}$ $\frac{S5}{S8}$

1939

Asc. 47 ft. over E. slope.

42.50 Spur, slopes SW.; desc. 159 ft. over SW slope.

52.10 Wash, 20 lks. wide, course SW.; asc. 64 ft. over SE slope.

59.30 Spur, slopes S.; desc. 103 ft. over west slope.

63.70 Wash, 10 lks. wide, course S. Asc. 43 ft. over E. slope.

68.00 Spur, slopes SW.; Desc. 63 ft. over SW slope.

71.00 Wash, 10 lks. wide, course S.20°W.; asc. 43 ft. over SE slope.

80.00 The cor. of secs. 5, 6, 7, and 8.

Land, rolling.

Soil, stony 4th. rate.

Timber, paloverde and mesquite.

Undergrowth, greasewood and cacti.

West, on true line, bet. secs. 6 and 7.

Over rolling land, thru scattering timber and undergrowth.

2.00 Spur, slopes SW; desc. 201 ft. over broken NW slope.

21.50 Wash, 10 lks. wide, course S.60°W.; asc. 70 ft. over SE slope.

30.50 Spur, slopes S.; desc. 71 ft. over broken SW slope.

36.80 Wash, 10 lks. wide, course S.; asc. 18 ft. over SE slope.

40.00 Set an iron post 3 ft. long, 1 in. in diam., 24 ins. in the ground for $\frac{1}{4}$ sec. cor., with brass cap mkd.

$\frac{1}{4}$ $\frac{S6}{S7}$

1939

raise a mound
of stone 4 ft. base, 2 ft. high N. of cor.

Asc. 57 ft. over SE slope.


45.00 Ridge, bears N.70°E. and S.70°W.; desc. 225 ft. over NW slope.

82.40 Intersect W. bdy. of Tp. at 4.20 chs. N.0°06'W., of cor.

Chains

of secs. 1 and 12, hereinbefore described.

At point for cor., set an iron post 3 ft. long, 2 ins. in diam., 20 ins. in the ground to bedrock, with stone 14x8x2 ins., mkd. with a cross (X) deposited at the base, and in a mound of stone to top for closing cor. of secs. 6 and 7, with brass cap marked



Land, rolling.
Soil, stony 4th. rate.
Timber, palo verde and mesquite.
Undergrowth, greasewood and cacti.

From cor. of secs. 5, 6, 7 and 8.
N.0°15'W., on a random line, bet. secs. 5 and 6.

40.00 Set temp. 1/4 sec. cor.

75.76 Intersect N. bdy. of Tp., 9 lks. E. of cor. of secs. 5, 6, 31 and 32, which is an iron post 2 ins. in diam., firmly set, projecting 14 ins. above ground, with brass cap marked and witnessed as described in the official record.

Thence,

S.0°19'E., on true line, bet. secs. 5 and 6.


Over rolling land, thru scattering timber & undergrowth.

Desc. 229 ft. over SE slope.

18.25 Wash, 10 lks. wide, course SW.; asc. 151 ft. over NW slope.

34.35 Tip of Spur, slopes W.; Desc. 18 ft. over SW slope.

35.76 (40.00 chs. in latitude from cor. of secs. 5, 6, 7, & 8.)
Set an iron post 3 ft. long, 1 in. in diam., 14 ins. in the ground to bedrock, with stone 10x6x4 ins., mkd. with a cross (X) deposited at the base, and in a mound of stone to top for 1/4 sec. cor., with brass cap mkd.



Desc. 38 ft. over SW slope.

37.55 Wash, 10 lks. wide, course NW.; asc. 144 ft. over NW slope.

40.45 Ridge, bears NE and SW.; desc. 130 ft. over SE slope.

Completion of Subdivision of T. 9 S., R. 18 E.

Chains.

- 56.95 Clark Wash, 40 lks. wide, course S. 70° W.; asc. 154 ft. over NW. slope.
- 67.85 Spur, slopes SW.; across level top.
- 72.85 Leave spur top; desc. 57 ft. over SE. slope.
- 75.76 The cor. of secs. 5, 6, 7 and 8.

Land, rolling.
Soil, stony and gravelly, 4th. rate.
Timber, paloverde and mesquite.
Undergrowth, greasewood and cacti.

40.00 chs. in lat. from closing cor. of secs. 7 and 18, and on the W. bdy. of sec. 18.
Set an iron post, 3 ft. long, 1 in. diam., 28 ins. in the ground, for $\frac{1}{4}$ sec. cor. of sec. 18 only, with brass cap mkd.

|
 $\frac{1}{4}$ S 18
1939

raise a mound

of stone, 4 ft. base, 2 ft. high, E. of cor.

From this point, $\frac{1}{4}$ sec. cor. of sec. 13, of R. 17 E., bears S. 1° 44' E., 3.71 chs. dist.

At midpoint on W. bdy. of sec. 7.

Set an iron post, 3 ft. long, 1 in. diam., 28 ins. in the ground, for $\frac{1}{4}$ sec. cor. of sec. 7 only, with brass cap mkd.

|
 $\frac{1}{4}$ S 7
1939

raise a mound

of stone, 2 ft. base, 1 $\frac{1}{2}$ ft. high, E. of cor.

From this point, $\frac{1}{4}$ sec. cor. of sec. 12, of R. 17 E., bears S. 0° 06' E., 4.22 chs. dist.

40.00 chs. from SW. cor. of sec. 6, the true point for $\frac{1}{4}$ sec. cor. on W. bdy. of sec. 6 falls in wash.

Witness $\frac{1}{4}$ sec. cor. of sec. 6 is identical with witness $\frac{1}{4}$ sec. cor. of sec. 1, of R. 17 E., hereinbefore described.

For continued satisfactory adjustment of Buff transit No. 18,000 during the surveys described herein, see preliminary test in field notes of T. 17 S., R. 30 E., surveyed under this group.

GENERAL DESCRIPTION.

LAND: High ridges along the east bdy. of Tp., with elevation ranging from 3500 ft. in sec. 36, to 4300 ft. in sec. 1, slope generally southwesterly, terminating in low gypseous bluffs overlooking the valley of the San Pedro River, where the elevation above sea level in this vicinity is about 2500 ft.

SOIL: A good, black sandy loam, 2nd. rate, is found at the mouths of the larger washes along the western border of the Tp.; elsewhere, and on slopes generally the soil is poor and stony, 4th rate, over an igneous formation.

TIMBER: Along most of the washes, especially the larger, there is a good thick growth of mesquite; on the slopes and table-lands, paloverde grows thick in the washes, and scattering along the slopes.

UNDERGROWTH: Greasewood and cactus predominate, with a good growth of the sahuaro cactus over the entire area surveyed.

WATER: The only living water noted was in sec. 1, developed by John Rhodes.

ROADS: The only worked road enters the surveyed area in sec. 30, and bearing northwesterly, terminates in sec. 1, at the Rhodes ranch.

SETTLEMENT: John Rhodes, in sec. 1, is the only settler living in the township. His improvements consist of houses, corrals, barns, reservoirs and fences.

INDUSTRY: The land is chiefly good for grazing.

MINERAL: No evidence of mineral was found.

187
63

RECORDED

4-680
(Revised May 1934)

UNITED STATES
DEPARTMENT OF THE INTERIOR
GENERAL LAND OFFICE

FIELD ASSISTANTS

NAMES	CAPACITY
Irwin B. Williams	Principal Assistant
Jack Bowker	Chainman
Jack Williams	Flagman
Amos R. Roten	Cornerman
Clifford Cline	Axeman
John G. Coverdale	Axeman

64
BOOK 488
CERTIFICATE OF SURVEYOR

Benjamin J. Kinsey, Associate Cadastral Engineer
I, /General Land Office, HEREBY CERTIFY upon honor that, in

pursuance of special instructions bearing date of the 5th day of October, 1938,

received from the district cadastral engineer for Arizona, with assignment

instructions dated November 28, 1938 I have ~~surveyed~~ resurveyed a portion of the west boundary and a portion of the subdivisional lines, and surveyed a portion of the subdivisional lines, completing the subdivision of Township 9 South, Range 18 East,

Gila and
of the /Salt River Meridian, in the State of Arizona, which are

represented in the foregoing field notes as having been executed by me and under my direction; and that said resurvey and

/survey has been made in strict conformity with said instructions, the Manual of Instructions for the Survey

of the Public Lands of the United States, and in the specific manner described in the foregoing field notes.

Phoenix, Arizona.

February 17, 1944.

Benjamin J. Kinsey
Associate Cadastral Engineer
General Land Office.
(Formerly Cadastral Engineer)

CERTIFICATE OF APPROVAL

OFFICE OF SUPERVISOR OF SURVEYS,

Denver, Colorado, August 12, 1944.

The foregoing field notes of the ~~survey~~ resurvey of a portion of the west boundary and a portion of the subdivisional lines, and survey of a portion of the subdivisional lines, completing the subdivision of Township 9 South, Range 18 East, of the Gila and Salt River Meridian, in the State of Arizona,

executed by Benjamin J. Kinsey, Cadastral Engineer, General Land Office,

under special instructions dated October 5, 1938, and assignment

instructions dated November 28, 1938, having been critically examined, and

the necessary corrections made prior to their certification by the engineer, the said field notes, and the survey

therein described, are hereby approved.

W. H. [Signature]
Supervisor of Surveys.

CERTIFICATE OF TRANSCRIPT

I CERTIFY that the foregoing transcript of the field notes of the above described surveys in

is a true copy of the original field notes on file in the public survey office.

Supervisor of Surveys.