

UNITED STATES
DEPARTMENT OF THE INTERIOR
~~GENERAL LAND OFFICE~~
BUREAU OF LAND MANAGEMENT

BOOK 4348

FIELD NOTES

OF THE

Survey of the Subdivisional Lines of

Township 4 North, Range 9 West,

Of the Gila and Salt River Meridian,

In the State of Arizona

EXECUTED BY

F. Wayne Forrest, Assistant Cadastral Engineer,

~~Bert E. Wakeman, Senior Engineering Aide,~~

and

~~John Roggs, Engineering Aide~~

~~General Land Office~~

Under special instructions dated October 29, 1941, which provided

for the surveys included under Group No. 234, bearing the approval of the

Commissioner of the General Land Office under date of November 7, 1941

and assignment instructions dated Febr. 14 and Apr. 13, 1946

Survey commenced April 5, 1946

Survey completed May 13, 1946

4348

4348

BOOK 4848

INDEX DIAGRAM.

Township		4 N.		Range		9 W.	
44	44	33	25	17	10		
6	43 5	32 4	24 3	16 2	9 1		
43	42	31	23	16	8		
7	41 8	30 9	22 10	15 11	7 12		
40	40	30	22	15	7		
18	39 17	29 16	21 15	14 14	6 13		
38	38	29	21	13	5		
19	37 20	28 21	20 22	13 23	4 24		
36	36	27	20	12	4		
30	35 29	26 28	19 27	12 26	3 25		
35	34	26	18	11	2		
31	33 32	25 33	18 34	10 35	1 36		

T. 4 N., R. 9 W.

Chains.

The subdivisional survey herein described was executed with Buff solar transits Nos. 24,846 and 24,849 and Gurley solar transit No. 371,537. The instruments comply with the standard specifications of the General Land Office and were placed in satisfactory adjustment prior to the beginning of the survey.

The directions of the lines were determined by the solar transit method. The measurements were made with Lufkin steel tapes, 5 chains in length, graduated every link for the first 100 links and the balance at intervals of ten links. The tapes were tested by comparison with a Lufkin standard tape and found correct. The measurements were made on the slope and the vertical angle of each interval was ascertained with a clinometer in good adjustment; the horizontal equivalents are entered in the field note record.

The data furnished with the special instructions gives the geographic position for the SE. cor. of T. 4 N., R. 9 W., as follows: latitude $33^{\circ} 38' 14''$ N., and longitude $113^{\circ} 07' 38''$ W.

April 3, 1946, in camp in the NE. $\frac{1}{4}$ of sec. 30, T. 4 N., R. 9 W., latitude $33^{\circ} 39' 50''$ N., longitude $113^{\circ} 13' 06''$ W., make an hour angle observation on Polaris for azimuth at 6h 29m 00s p.m., l.m.t., making two observations each with the telescope in the direct and the reversed positions, and measuring the horizontal angle from a sharply defined cactus on the horizon. From the reduced azimuth of Polaris, N. $1^{\circ} 10' 54''$ W., and the mean horizontal angle measured, $1^{\circ} 51' 00''$ left, determine the azimuth of the distant cactus to be N. $0^{\circ} 40' 06''$ E.

April 4, 1946, every 30 minutes from 7 to 10:30 a.m. and 1:30 to 5 p.m., make the proper settings on the arcs of the solar attachments and ascertain the resulting orientation of the instruments, when compared with the meridian established by Polaris observation, has a maximum error of less than $1' 30''$.

Repeat the tests of the arcs daily by noon observations and verify the meridional indications at frequent intervals throughout the survey.

The mean magnetic declination for T. 4 N., R. 9 W. is $14^{\circ} 00'$ E.

Subdivision of T. 4 N., R. 9 W.

From the cor. of secs. 1, 2, 35, and 36, on the S. bdy. of the Tp., marked with an iron post, 2 ins. diam., firmly set in a mound of stone 3 ft. base, 2 ft. high to top, marked and witnessed as described in the official record.

N. $0^{\circ} 01'$ W., bet. secs. 35 and 36.

Over broken hills through scattering desert timber and undergrowth; desc. 78 ft. over a NE. slope.

5.70 wash, 10 lks. wide, course N. 80° E.; thence along an E. slope.

Subdivision of T. 4 N., R. 9 W.

Chains.	
36.70	Low spur, slopes N. 70° E.; desc. 50 ft. to $\frac{1}{4}$ sec. cor.
40.00	Point for $\frac{1}{4}$ sec. cor. of secs. 35 and 36. Set an iron post, 3 ft. long, 1 in. diam., 27 ins. in the ground, with brass cap mkd. <div style="text-align: center;"> \dagger S 35 S 36 1946 </div> <p style="text-align: center;">Raise a mound of stone, 3 ft. base, 2 ft. high, W. of cor.</p> <p>Desc. slightly.</p>
42.50	Saddle in spur, sloping N. 70° E.; desc. N. slope
47.90	Enter junction of washes, 5 lks. wide, course N., from S. 20° W. and S. 10° E.; thence along bottom of wash.
53.80	Leave wash, course N. 10° W.
55.70	Same wash, 10 lks. wide, course NE.
58.20	wash, 8 lks. wide, course SW.
76.90	Wash, 10 lks. wide, course E.
80.00	Point for the cor. of secs. 25, 26, 35, and 36. Mark a cross (+) on the sloping W. face of a sandstone boulder, 6 x 4 x 3 ft. For the description of the witness cor. established, see the line bet. secs. 25 and 36. Land, broken desert. Soil, gravelly and rocky, 3rd. rate. Timber, palo verde and ironwood; undergrowth, creosote and rabbit brush, ocotillo, and cactuses.

	From the cor. of secs. 25, 30, 31, and 36, on the E. bdy. of the Tp., marked with an iron post, 2 ins. diam., firmly set in a mound of stone 2 ft. high to top, marked and witnessed as described in the official record. N. 89° 56' W., bet. secs. 25 and 36. Asc. 97 ft. over a NE. slope.
13.60	Low ridge, bears N. 60° W. and S. 60° E.; thence along a S. slope.
16.90	Desc. 97 ft. over a broken SW. slope.
26.70	wash, 20 lks. wide, course S. 80° E.; asc. 30 ft.
40.00	Point for the $\frac{1}{4}$ sec. cor. of secs. 25 and 36. Set an iron post, 3 ft. long, 1 in. diam., 16 ins. in the ground and in a mound of stone 5 ft. base to top, with brass cap mkd.

Subdivision of T. 4 N., R. 9 W.

Chains.

$$\frac{1}{4} \begin{array}{c} \text{S } 25 \\ \text{S } 36 \end{array}$$

1946

Asc. 95 ft. over rolling desert land.

52.70 Low ridge, bears NW. and SE.; desc. 52 ft. over a broken SW. slope.

71.60 Wash, 5 lks. wide, course S. 80° E.; asc. 34 ft.

79.88 Establish a witness cor. of secs. 25, 26, 35, and 36.

Set an iron post, 3 ft. long, 2 ins. diam., 24 ins. in a crevice in the rock and in a mound of stone to top, with brass cap mkd.

$$\begin{array}{c} \text{T4N R9W} \\ \text{WC } \begin{array}{c|c} \text{S } 26 & \text{S } 25 \\ \text{S } 35 & \text{S } 36 \end{array} \end{array}$$

1946

80.00 The cor. of secs. 25, 26, 35, and 36.

Land, rolling and broken desert.

Soil, gravelly and rocky, 3rd. rate.

Timber, palo verde and ironwood; undergrowth, creosote and rabbit brush, ocotillo, and cactuses.

N. 0° 01' W., bet. secs. 25 and 26.

Over broken desert land.

3.50 Wash, 10 lks. wide, course E.

26.00 Wash, 10 lks. wide, course W.

28.80 Wash, 15 lks. wide, course N. 80° W., winding.

40.00 Point for the 4 sec. cor. of secs. 25 and 26.

Set an iron post, 3 ft. long, 1 in. diam., 10 ins. in the ground and in a mound of stone 4 ft. base to top, with brass cap mkd.

$$\begin{array}{c} \frac{1}{4} \\ \text{S } 26 \uparrow \text{S } 25 \\ 1946 \end{array}$$

46.40 Desc. N. slope over rolling land.

63.40 Wash, 20 lks. wide, course W.

69.40 Wash, 10 lks. wide, course S. 60° W.

70.00 Asc. 75 ft. over a S. slope.

80.00 Point for the cor. of secs. 23, 24, 25, and 26.

Set an iron post, 3 ft. long, 2 ins. diam., 10 ins. in the ground and in a mound of stone 5 ft. base to top, with brass cap mkd.

Subdivision of T. 4 N., R. 9 W.

Chains

T4N R9W
S 23 | S 24
S 26 | S 25

1946

Land, rolling and broken desert.
Soil, gravelly and rocky, 3rd. rate.
Timber, palo verde and ironwood; undergrowth, creosote and rabbit brush, ocotillo and cactuses.

From the cor. of secs. 19, 24, 25, and 30 on the E. bdy. of the Tp., marked with an iron post, 2 ins. diam., firmly set in a mound of stone 2 ft. high to top, marked and witnessed as described in the official record.

N. 89° 51' W., bet. secs. 24 and 25.

Desc. 18 ft. over broken desert land.

1.90 Wash, 30 lks. wide, course SW.; asc. 113 ft. over an E. slope.

6.40 Spur, slopes S. 20° E., from NE.; desc. 25 ft.

9.80 Wash, 5 lks. wide, course N.; asc. 110 ft. over an E. slope.

15.00 Ridge, bears S. 20° E. and N. 20° W.; desc. 270 ft. over a W. slope.

39.20 wash, 15 lks. wide, course S.

40.01 Point for the $\frac{1}{4}$ sec. cor. of secs. 24 and 25.

Set an iron post, 3 ft. long, 1 in. diam., 6 ins. in the ground and in a mound of stone 5 ft. base to top, with brass cap mkd.

$\frac{1}{4}$ $\frac{S\ 24}{S\ 25}$
1946

67.40 Spur, slopes S.; desc. 80 ft. over a broken SW. slope.

80.02 The cor. of secs. 23, 24, 25, and 26.

Land, broken desert.
Soil, gravelly and rocky, 3rd. rate.
Timber, palo verde and ironwood; undergrowth, creosote and rabbit brush, ocotillo and cactuses.

N. 0° 01' W., bet. secs. 23 and 24.

7.10 Head of wash, course SW.; asc. 64 ft. over a S. slope.

9.10 Ridge, bears E. and W.; desc. 105 ft. over a N. slope.

14.00 Wash, 5 lks. wide, course NW.

18.00 Wash, 10 lks. wide, course NW.; asc. 50 ft. over a S. slope.

Subdivision of T. 4 N., R. 9 W.

Chains.

26.30 Ridge, bears E. and W.; desc. gradually over a N. slope.

35.50 Wash, 15 lks. wide, course W.

40.00 Point for the $\frac{1}{4}$ sec. cor. of secs. 23 and 24.

Set an iron post, 3 ft. long, 1 in. diam., 18 ins. in the ground and in a mound of stone 3 ft. base to top, with brass cap mkd.

$$\begin{array}{c} \frac{1}{4} \\ S\ 23\ | \ S\ 24 \end{array}$$

1946

54.70 Wash, 60 lks. wide, course W.

77.20 Wash, 10 lks. wide, course SW., winding.

80.00 Point for the cor. of secs. 13, 14, 23, and 24.

Set an iron post, 3 ft. long, 2 ins. diam., 28 ins. in the ground, with brass cap mkd.

$$\begin{array}{c} T4N\ R9W \\ S\ 14\ | \ S13 \\ \hline S\ 23\ | \ S24 \end{array}$$

1946

Raise a mound of stone, 3 ft. base, 2 ft. high, W. of cor.

Land, rolling desert.

Soil, sandy and gravelly, 3 rd. rate.

Timber, palo verde and ironwood; undergrowth, creosote and rabbit brush, ocotillo, and cactuses.

From the cor. of secs. 13, 18, 19, and 24, on the E. bdy. of the Tp., marked with an iron post, 2 ins. diam.; firmly set in a mound of stone 2 ft. high to top, marked and witnessed as described in the official record.

N. 89° 41' W., bet. secs. 13 and 24.

Over rolling desert land.

8.55 Wash, 10 lks. wide, course S.

21.25 Wash, 20 lks. wide, course SW., winding.

30.55 Wash, 20 lks. wide, course SW.

38.85 Wash, 10 lks. wide, course S. 10° E.

40.02 Point for the $\frac{1}{4}$ sec. cor. of secs. 13, and 24.

Set an iron post, 3 ft. long, 1 in. diam., 28 ins. in the ground, with brass cap mkd.

$$\frac{1}{4} \frac{S\ 13}{S\ 24}$$

1946

Raise a mound of stone, 2 ft. base, 2 ft. high, N. of cor.

Subdivision of T. 4 N., R. 9 W.

Chains

53.15 Wash, 20 lks. wide, course SW.

80.04 The cor. of secs. 13, 14, 23, and 24.

Land, rolling desert.

Soil, sandy and gravelly, 3rd. rate.

Timber, palo verde and ironwood; undergrowth, creosote and rabbit brush, ocotillo, and cactuses.

N. 0° 01' W., bet. secs. 13 and 14.

Over broken land thru scattering desert timber.

5.90 wash, 10 lks. wide, course W., winding.

8.80 wash, 10 lks. wide, course SW.

20.50 Wash, 10 lks. wide, course W,

24.20 Wash, 10 lks. wide, course SW.

28.70 Wash, 20 lks. wide, course S. 30° W.

40.00 Point for the $\frac{1}{4}$ sec. cor. of secs. 13 and 14.

Set an iron post, 3 ft. long, 1 in. diam., 18 ins. in the ground and in a mound of stone 3 ft. base to top, with brass cap mkd.

$$\begin{array}{c} \frac{1}{4} \\ \text{S } 14 \mid \text{S } 13 \\ 1946 \end{array}$$

47.40 Wash, 10 lks. wide, course W.

57.50 wash, 5 lks. wide, course SW.

63.20 Wash, 5 lks. wide, course W.

67.60 spur, slopes S. 60° W.; desc. 85 ft. over a N. slope.

73.50 Wash, 20 lks. wide, course S. 60° W.; asc. 60 ft. over a SW. slope.

80.00 Point for the cor. of secs. 11, 12, 13, and 14.

Set an iron post, 3 ft. long, 2 ins. diam., 28 ins. in the ground, with brass cap mkd.

$$\begin{array}{c} \text{T4N} \mid \text{R9W} \\ \text{S } 11 \mid \text{S } 12 \\ \text{S } 14 \mid \text{S } 13 \end{array}$$

1946

Raise a mound of stone, 3 ft. base, 2 ft. high, W. of cor.

Land, rolling and broken hills.

Soil, gravelly and rocky, 3rd. rate.

Timber, paloverde and ironwood; undergrowth, creosote and rabbit brush, ocotillo and cactuses.

Subdivision of T. 4 N., R. 9 W.

Chains.

From the cor. of secs. 7, 12, 13, and 18, on the E. bdy. of the Tp., marked with an iron post, 2 ins. diam., firmly set in a mound of stone 1 ft. high to top, marked and witnessed as described in the official record.

N. 89° 42' W., bet. secs. 12 and 13.

Over broken desert land.

20.95 Wash, 15 lks. wide, course SW.

40.03 Point for the $\frac{1}{4}$ sec. cor. of secs. 12 and 13.

Set an iron post, 3 ft. long, 1 in. diam., 24 ins. in the ground and in a mound of stone 3 ft. base to top, with brass cap mkd.

$$\frac{1}{4} \begin{array}{c} \text{S } 12 \\ \text{S } 13 \\ 1946 \end{array}$$

53.55 Wash, 20 lks. wide, course S. 20° W.; asc. 130 ft.

66.75 Short spur, slopes S.; desc. 83 ft. over a S. slope.

80.06 The cor. of secs. 11, 12, 13, and 14.

Land, broken desert.

Soil, gravelly and rocky, 3 rd. rate.

Timber, palo verde and ironwood; undergrowth, creosote brush, ocotillo, and cactuses.

N. 0° 01' W., bet. secs. 11 and 12.

Asc. 143 ft. over a S. slope.

5.40 Ridge, bears E. and W.; desc. 139 ft. over a N. slope.

16.80 Wash, 5 lks. wide, course W.; thence over rolling land.

30.50 wash, 50 lks. wide, course SW.

40.00 Point for the $\frac{1}{4}$ sec. cor. of secs. 11 and 12.

Set an iron post, 3 ft. long, 1 in. diam., 28 ins. in the ground, with brass cap mkd.

$$\begin{array}{c} \frac{1}{4} \\ \text{S } 11 \mid \text{S } 12 \\ 1946 \end{array}$$

Raise a mound of stone, 3 ft. base, 2 $\frac{1}{2}$ ft. high, W. of cor.

80.00 Point for the cor. of secs. 1, 2, 11, and 12.

Set an iron post, 3 ft. long, 2 ins. diam., 28 ins. in the ground, with brass cap mkd.

$$\begin{array}{c} \text{T4N } \mid \text{R9W} \\ \text{S } 2 \mid \text{S } 1 \\ \text{S } 11 \mid \text{S } 12 \\ 1946 \end{array}$$

Chains.

Raise a mound of stone, 3 ft. base, 2½ ft. high,
W. of cor.

Land, rolling and broken.

Soil, sandy and gravelly, 3rd. rate.

Timber, palo verde and iron wood; undergrowth, creosote
brush, ocotillo, and cactuses.

from the cor. of secs. 1, 6, 7, and 12, on the E. bdy. of
the Tp., marked with an iron post, 2 ins. diam., firmly
set in a mound of stone 1½ ft. high to top, marked and
witnessed as described in the official record.

N. 89° 39' W., bet. secs. 1 and 12.

Desc. 225 ft. over broken desert land.

9.25 Wash, 5 lks. wide, course N. W.; asc. 45 ft. over a NE.
slope.

15.35 Top of ascent; descend 120 ft. over a NW. slope.

27.55 Wash, 60 lks. wide, course SW.; asc. 62 ft. over a NE.
slope.

29.50 Top of ascent; desc. 50 ft. over a SW. slope.

39.55 Wash, 5 lks. wide, course S., winding.

40.03 Point for ¼ sec. cor. of secs. 1 and 12.

Set an iron post, 3 ft. long, 1 in. diam., 28 ins. in the
ground, with a brass cap mkd.

 S 1
 ¼ S 12

1946

Raise a mound of stone, 3 ft. base, 2½ ft. high,
N. of cor.

Asc. 268 ft. over a broken NE. slope.

52.25 Spur, slopes S. 30° E.; desc. 122 ft. over a broken SW.
slope.

61.65 wash, 10 lks. wide, course S. 20° E.; asc. 145 ft. over a
NE. slope.

66.05 Spur, slopes S. 30° E.; desc. 264 ft. over a broken W.
slope.

80.06 The cor. of secs. 1, 2, 11, and 12.

Land, broken hills.

Soil, gravelly and rocky, 3rd. and 4th. rates.

Timber, paloverde and ironwood; undergrowth, creosote
brush, ocotillo, and cactuses.

Subdivision of T. 4 N., R. 9 W.

Chains

N. 0° 01' W., bet. secs. 1 and 2.

Enter broken hills; asc. 178 ft. over a broken W. slope.

11.55 Rocky point on spur, slopes W.; desc. 92 ft. over a NW. slope.

16.40 Head of ravine, drains W.; asc. 90 ft. over SW. slope.

21.00 Rocky point on spur, slopes NW.; desc. 179 ft. over a N. slope.

32.70 Wash, 15 lks. wide, course W.

33.90 Wash, 15 lks. wide., course S. 80° W.; asc. 16 ft.

40.00 Point for the $\frac{1}{4}$ sec. cor. of secs. 1 and 2.

Set an iron post, 3 ft. long, 1 in. diam., 28 ins. in the ground, with brass cap mkd.

$$\begin{array}{c} \frac{1}{4} \\ S\ 2\ | \ S\ 1 \\ 1946 \end{array}$$

Raise a mound of stone, 2 $\frac{1}{2}$ ft. base, 2 ft. high, W. of cor.

40.50 Wash, 5 lks. wide, course S. 10° W.; asc. 211 ft. over a broken S. slope.

66.10 Spur, slopes NW.; desc. 105 ft. over NE. slope.

72.95 Intersect the 1st. stan. par. N.; point for the closing cor. of secs. 1 and 2.

Set an iron post, 3 ft. long, 2 ins. diam., 24 ins. in the ground and in a mound of stone 2 ft. base to top, with brass cap mkd.

$$\begin{array}{c} T5N\ | \ R9W \\ S\ 36 \\ \hline S\ 2\ | \ S\ 1 \\ T4N\ | \ R9W \\ C\ | \ C \\ 1946 \end{array}$$

From this cor. the standard cor. of Ts. 5 N., Rs. 8 and 9 W. bears S. 89° 53' W., 11.72 chs. dist., marked with an iron post, 3 ins. diam., firmly set, marked and witnessed as described in the 1942 resurvey record.

Land, broken hills.

Soil, gravelly and rocky, 3rd. and 4th. rates.

Timber, palo verde and ironwood; undergrowth, creosote brush, sage, ocotillo, and cactuses.

Chains.

Point for the $\frac{1}{4}$ sec. cor. of sec. 1, at midpoint on the N. bdy. of sec. 1.

Set an iron post, 3 ft. long, 1 in. diam., 4 ins. in the ground, over a cross (+) marked on solid rock, and in a mound of stone $4\frac{1}{2}$ ft. base to top, with brass cap mkd.

$\frac{1}{4}$ S 1

1946

From this cor. the standard $\frac{1}{4}$ sec. cor. of sec. 31, T. 5 N., R. 8 W., bears East, 13.12 chs. dist., marked with an iron post, 1 in. diam., firmly set, marked and witnessed as described in the 1916 resurvey record.

From this cor. the standard cor. of Ts. 5 N., Rs. 8 and 9 W., bears West, 28.27 chs. dist.

From the cor. of secs. 2, 3, 34 and 35, on the S. bdy. of the Tp.; witnessed N. $89^{\circ} 58'$ W., 10 lks. dist. by an iron post, 2 ins. diam., firmly set in a mound of stone, 4 ft. base, 2 ft. high to top, marked and witnessed as described in the official record.

N. $0^{\circ} 01'$ W., bet. secs. 34 and 35.

Desc. 48 ft. along rocky W. to NW. slope.

1.90 Rocky ravine, 10 lks. wide, course S. 60° W.; asc. 649 ft. over broken cliffs on a S. slope.

16.00 Spur, slopes SW; asc. 45 ft. over a SW. slope.

19.00 Slope changes to W.

22.30 Desc. 326 ft. over a broken NW. slope.

40.00 Point for the $\frac{1}{4}$ sec. cor. of secs. 34 and 35.

Set an iron post, 3 ft. long, 1 in. diam., 12 ins. in the ground and in a mound of stone 4 ft. base to top, with brass cap mkd.

$\frac{1}{4}$
S 34 | S 35

1946

Desc. 61 ft.

43.40 Wash, 10 lks. wide, course S. 80° W.; asc. 263 ft. over a S. slope.

54.10 Ridge, bears N. 70° W. and S. 60° E.

57.00 Desc. 550 ft. over a N. slope.

79.00 Wash, 15 lks. wide, course N. 20° W.

Subdivision of T. 4 N., R. 9 W.

Chains.
80.00

Point for the cor. of secs. 26, 27, 34, and 35.

Set an iron post, 3 ft. long, 2 ins. diam., 18 ins. in the ground and in a mound of stone 4 ft. base to top, with cap mkd.

T4N R9W	
S 27	S 26
S 34	S 35

1946

Land, rough, mountainous.

Soil, rocky, 3rd. and 4th. rates.

Timber, palo verde and ironwood; undergrowth, creosote brush and cactuses.

From the cor. of secs. 25, 26, 35, and 36.

N. 89° 55' W., bet. secs. 26 and 35.

Asc. 23 ft. over a broken NE. slope over granite boulders.

17.60 Wash, 10 lks. wide, course N.

33.90 Wash, 10 lks. wide, course N.

39.01 Establish a witness $\frac{1}{4}$ sec. cor. of secs. 26 and 35.

Set an iron post, 3 ft. long, 1 in. diam., 28 ins. in the ground, with brass cap mkd.

W C $\frac{1}{4}$	S 26
	S 35

1946

Raise a mound of stone, 3 ft. base, 2 ft. high,
N. of cor.40.01 Point for the $\frac{1}{4}$ sec. cor. of secs. 26 and 35, on the face of a granite ledge on the E. bank of a Wash.

40.20 Wash, 30 lks. wide, course N.; asc. 115 ft. over an E. slope.

48.60 Spur, slopes N.; desc. W. slope 109 ft.

56.10 Wash, 10 lks. wide, course N. 20° W.

64.70 Wash, 15 lks. wide, course N.; asc. 199 ft. over an E. slope.

74.20 Spur, slopes N. 10° W.; desc. 110 ft. over a W. slope.

80.02 The cor. of secs. 26, 27, 34, and 35.

Land, broken hills.

Soil, gravelly and rocky, 3rd. and 4th. rates;

Timber, paloverde and ironwood; undergrowth, creosote brush and cactuses.

Chains.

N. 0° 01' W., bet. secs. 26 and 27.

Over broken land thru scattering desert timber.

1.30 Wash, 10 lks. wide, course NE.

3.50 Desc. 74 ft. along an E. slope.

13.43 Foot of descent; asc. 53 ft. along an E. slope.

20.00 Spur, slopes E., near toe; desc. 113 ft.

25.10 Foot of descent, bears E. and W.; thence over rolling land.

28.30 Wash, 20 lks. wide, course N. 60° W.

37.50 Wash, 20 lks. wide, course N. 80° W.

40.00 Point for the 1/4 sec. cor. of secs. 26 and 27.

Set an iron post, 3 ft. long, 1 in. diam., 28 ins. in the ground, with brass cap mkd.

1/4
S 27 | S 26
1946

Raise a mound of stone, 3 ft. base, 2 ft. high, W. of cor.

58.30 wash, 20 lks. wide, course W.

71.40 Wash, 100 lks. wide, course W.

80.00 Point for the cor. of secs. 22, 23, 26, and 27.

Set an iron post, 3 ft. long, 2 ins. diam., 28 ins. in the ground, with brass cap mkd.

T4N | R9W
S 22 | S 23
S 27 | S 26
1946

Raise a mound of stone, 2 ft. base, 1 1/2 ft. high, W. of cor.

Land, broken and rolling.
Soil, gravelly and rocky, 3rd. rate.
Timber, palo verde and ironwood; undergrowth, creosote brush, ocotillo, and cactuses.

From the cor. of secs. 23, 24, 25, and 26.

N. 89° 53' W., bet. secs. 23 and 26.

2.90 Wash, 10 lks. wide, course SW.

31.60 Wash, 100 lks. wide, course SW.

40.02 Point for the 1/4 sec. cor. of secs. 23 and 26.

Set an iron post, 3 ft. long, 1 in. diam., 28 ins. in the ground, with brass cap mkd.

Subdivision of T. 4 N., R. 9 W.

1946 4848

Chains.

$$\frac{1}{4} \frac{S.23}{S.26}$$
 1946

Raise a mound of stone, 3 ft. base, 2 ft. high,
N. of cor.

45.30 Enter wash, 100 lks. wide, course W. winding, from SE.

66.00 Leave wash, course SW.

80.04 The cor. of secs. 22, 23, 26, and 27.

Land, rolling.

Soil, gravelly, 3rd. rate.

Timber, palo verde and ironwood; undergrowth, creosote
brush and cactuses.-----
N. 0° 01' W., bet. secs. 22 and 23.Over slightly rolling land sloping SW. thru scattering
desert vegetation.

3.80 wash, 20 lks. wide, course SW.

8.00 Wash, 100 lks. wide, 15 ft. deep, course SW.

40.00 Point for $\frac{1}{4}$ sec. cor. of secs. 22 and 23.Set an iron post, 3 ft. long, 1 in. diam., 28 ins. in the
ground, with brass cap mkd.
$$S.22 \frac{1}{4} S.23$$
 1946

Raise a mound of stone, 3 ft. base, 2 ft. high,
W. of cor.

48.90 Wash, 100 lks. wide, 10 ft. deep, course SW.

70.00 Low spur, slopes SW.; thence along W. slope of spur.

80.00 Point for the cor. of secs. 14, 15, 22, and 23.

Set an iron post, 3 ft. long, 2 ins. diam., 10 ins. in the
ground and in a mound of stone 3 ft. base to top, with
brass cap mkd.
$$\begin{array}{c} T4N R9W \\ S.15 | S.14 \\ S.22 | S.23 \end{array}$$

1946

Land, rolling.

Soil, gravelly, 3rd. rate.

Timber, palo verde and ironwood; undergrowth, creosote
brush and cactuses.-----
From the cor. of secs. 13, 14, 23, and 24.

N. 89° 56' W., bet. secs. 14 and 23.

Chains.

Over rolling and rocky land.

- 5.00 Low spur, slopes SW.; thence along SW. slope.
- 18.10 Small wash, near head, course SW.
- 25.00 Low spur, slopes SW.
- 34.60 Wash, 100 lks. wide, 10 ft. deep, course S.
- 40.01 Point for the $\frac{1}{4}$ sec. cor. of secs. 14 and 23.

Set an iron post, 3 ft. long, 1 in. diam., 28 ins. in the ground, with brass cap mkd.

$\frac{1}{4}$ S 14
S 23
1946

Raise a mound of stone, 3 ft. base, 2 $\frac{1}{2}$ ft. high, N. of cor.

- 45.00 Wash, 100 lks. wide, 10 ft. deep, course SW.
- 80.02 The cor. of secs. 14, 15, 22, and 23.

Land, rolling.
Soil, gravelly and rocky, 3 rd. rate.
Timber, palo verde and ironwood; undergrowth, creosote brush and cactuses.

N. 0° 01' W., bet. secs. 14 and 15.

Over rolling land.

- 40.00 Point for the $\frac{1}{4}$ sec. cor. of secs. 14 and 15.

Set an iron post, 3 ft. long, 1 in. diam., 28 ins. in the ground, with brass cap mkd.

$\frac{1}{4}$
S 15 | S 14
1946

Raise a mound of stone, 2 $\frac{1}{2}$ ft. base, 2 ft. high, W. of cor.

- 41.10 wash, 10 lks. wide, course W.
- 59.10 Wash, 20 lks. wide, course SW.
- 80.00 Point for the cor. of secs. 10, 11, 14, and 15.

Set an iron post, 3 ft. long, 2 ins. diam., 18 ins. in the ground and in a mound of stone 3 ft. base to top, with brass cap mkd.

T4N R9W
S 10 | S 11
S 15 | S 14
1946

Land, rolling.
Soil, sandy and gravelly, 3 rd. rate.
Timber, palo verde and ironwood; undergrowth, creosote brush and cactuses.

Subdivision of T. 4 N., R. 9 W.

BOOK 4048

Chains.

From the cor. of secs. 11, 12, 13, and 14.

N. 89° 56' W., bet. secs. 11 and 14.

Asc. 144 ft. over rolling desert land.

15.75 Spur, slopes S.; desc. 152 ft.

32.05 wash, 25 lks. wide, course SW.

38.55 Enter same wash, course W. from SE.


40.02 Point for the $\frac{1}{4}$ sec. cor. of secs. 11 and 14, in same wash course W.

Continue along bottom of wash.

41.45 Leave wash, 25 lks. wide, course S. 60° W.

42.42 Establish a witness $\frac{1}{4}$ sec. cor. of secs. 11 and 14.

Set an iron post, 3 ft. long, 1 in. diam., 28 ins. in the ground, with brass cap mkd.



1946

Raise a mound of stone, 3 ft. base, 2 ft. high, N. of cor.

80.04 The cor. of secs. 10, 11, 14, and 15.

Land, rolling.

Soil, gravelly, 3rd. rate.

Timber, palo verde and ironwood; undergrowth, creosote brush, sage, and cactuses.

N. 0° 01' W., bet. secs. 10 and 11.

Over rolling desert land.

18.70 Wash, 15 lks. wide, 10 ft. deep, course S. 80° W.

30.60 wash, 50 lks. wide, 10 ft. deep, course S. 70° W.; enter broken hills, bear NW. and SE.

40.00 Point for the $\frac{1}{4}$ sec. cor. of secs. 10 and 11.

Set an iron post, 3 ft. long, 1 in. diam., 28 ins. in the ground, with brass cap mkd.



1946

Raise a mound of stone, 2 $\frac{1}{2}$ ft. base, 2 ft. high, W. of cor.

80.00 Point for the cor. of secs. 2, 3, 10, and 11.

Set an iron post, 3 ft. long, 2 ins. diam., 28 ins. in the ground, with brass cap mkd.

BOOK 4348

Subdivision of T. 4 N., R. 9 W;

Chains.

T4N R9W
S 3 | S 2
S 10 | S 11

1946

Raise a mound of stone, 2½ ft. base, 2 ft. high, W. of cor.

Land, rolling.

Soil, sandy and rocky, 3rd. rate.

Timber, palo verde and ironwood; undergrowth, creosote brush, sage, and cactuses.

From the cor. of secs. 1, 2, 11, and 12.

N. 89° 51' W., bet. secs. 2 and 11.

Desc. 90 ft. over a W. slope.

23.10 Wash, 20 lks. wide, course S.; asc. 100 ft. over E. slope.

31.80 Spur, slopes S.; desc. 121 ft. over a W. slope.

40.01 Point for the ¼ sec. cor. of secs. 2 and 11.

Set an iron post, 3 ft. long, 1 in. diam., 12 ins. in the ground and in a mound of stone, 4 ft. base to top, with brass cap mkd.

¼ S 2
S 11
1946

49.00 Wash, 8 lks. wide, course SW.; desc. 36 ft. over a S. slope.

58.30 Same wash, course N. 80° W.

62.20 Same wash, 15 lks. wide, course S. 30° W.; asc. 50 ft.

66.60 Spur, slopes S.; desc. 57 ft. over a W. slope.

80.02 The cor. of secs. 2, 3, 10, and 11.

Land, broken hills.

Soil, rocky, 2nd. and 3rd. rates.

Timber, palo verde and ironwood; undergrowth, creosote brush, sage, cats claw; and cactuses.

N. 0° 01' W., bet. secs. 2 and 3.

Along a broken SW. slope.

3.30 Wash, 20 lks. wide, 18 ft. deep, course SW.

7.70 Wash, 15. lks. wide, 18 ft. deep, course SW.

40.00 Point for the ¼ sec. cor. of secs. 2 and 3.

Set an iron post, 3 ft. long, 1 in. diam., 12 ins. in the ground and in a mound of stone 4 ft. base to top, with brass cap mkd.

Subdivision of T. 4 N., R. 9 W.

BOOK 4648

Chains.

$$\begin{array}{c} \frac{1}{2} \\ S \ 3 \ | \ S \ 2 \\ 1946 \end{array}$$

Asc. 63 ft. over a S. slope.

45.90 Spur, slopes S. 65° W. from NE.

70.35 Establish a witness closing cor. of secs. 2 and 3.

Set an iron post, 3 ft. long, 2 ins. diam., 28 ins. in the ground, with brass cap mkd.

$$\begin{array}{c} W \ C. \\ T5N \ R9W \\ S \ 35 \\ \hline S \ 3 \ | \ S \ 2 \\ T4N \ R9W \\ C \ C \end{array}$$

1946

Raise a mound of stone, 3 ft. base, 2 ft. high, S. of cor.

72.90 Long wash, 60 lks. wide, course SW.

72.95 Intersect the 1st. Stan. Par. N.; point for the closing cor. of secs. 2 and 3, in the same wash, course SW.

From this point the standard cor. of secs. 35 and 36, T. 5 N., R. 9 W., bears S. 89° 53' E., 11.72 chs. dist., marked with an iron post, 2 ins. diam., firmly set, marked and witnessed as described in the 1942 resurvey record.

Land, broken hills.

Soil, rocky, 3rd. rate.

Timber, palo verde and ironwood; undergrowth, creosote brush, sage, cats claw, and castuses.

Point for the $\frac{1}{2}$ sec. cor. of sec. 1 at midpoint on the N. bdy. of sec. 1.

Set an iron post, 3 ft. long, 1 in. diam., 28 ins. in the ground, with brass cap mkd.

$$\frac{1}{2} \ S \ 2$$

1946

Raise a mound of stone, 3 ft. base, 2 ft. high, S. of cor.

From this cor. the standard $\frac{1}{2}$ sec. cor. of sec. 36, T. 5 N., R. 9 W., bears S. 89° 53' E., 11.72 chs. dist., marked with an iron post, 1 in. diam., firmly set, marked and witnessed as described in the 1942 resurvey record.

Chains.

From the cor. of secs. 3, 4, 33, and 34, on the S. bdy. of the Tp., marked with an iron post, 2 ins. diam., firmly set in a mound of stone, 4 ft. base, 2 1/2 ft. high to top, marked and witnessed as described in the official record.


N. 0° 02' W., bet. secs. 33 and 34.

1.00 Wash, 20 lks. wide, course W.; asc. broken S. slope, 332 ft.

16.20 Rocky spur, slopes N. 60° W.; desc. 534 ft. over a N. slope.

39.85 Establish a witness 1/4 sec. cor. of secs. 33 and 34.

Set an iron post, 3 ft. long, 1 in. diam., 18 ins. in the ground and in a mound of stone 3 ft. base to top, with brass cap mkd.



40.00 Point for the 1/4 sec. cor. of secs. 33 and 34,


Mark a cross (+) near the N. end of the top of a granite boulder 8x5x4 ft.

41.10 Wash, 10 lks. wide; course W.; desc. 135 ft.

69.60 Wash, 20 lks. wide, course W.; asc. 85 ft. over a S. slope.

80.00 Point for the cor. of secs. 27, 28, 33, and 34.

Set an iron post, 3 ft. long, 2 ins. diam., 18 ins. in the ground and in a mound of stone 4 ft. base to top, with brass cap mkd.



1946

Land, rough and broken hills.
Soil, gravelly and rocky, 3rd. rate.
Timber, palo verde and ironwood; undergrowth, creosote brush and cactuses.

From the cor. of secs. 26, 27, 34, and 35.

N. 89° 58' W., bet. secs. 27 and 34.

0.35 Wash, 10 lks. wide, course N.; asc. 73 ft.

2.85 Spur, slopes N.; desc. over a W. slope.

39.93 Point for the 1/4 sec. cor. of secs. 27 and 34.

Set an iron post, 3 ft. long, 1 in. diam., 16 ins. in the ground and in a mound of stone 4 ft. base to top, with brass cap mkd.

Subdivision of T. 4 N., R. 9 W.

LOCK 4848

Chains.

$$\frac{1}{4} \begin{array}{c} \text{S } 27 \\ \text{S } 34 \\ 1946 \end{array}$$

- 45.10 Wash, 20 lks. wide, course N.; asc. 232 ft. over an E. slope.
- 56.15 Spur, slopes N. 30° W.; desc. 233 ft. over a W. slope.
- 69.85 Wash, 5 lks. wide, course N.; asc. 70 ft. over an E. slope.
- 77.25 Spur, slopes N.
- 79.86 The cor. of secs. 27, 28, 33, and 34.

Land, rough and mountainous.
 Soil, gravelly and rocky, 3rd. rate.
 Timber, palo verde and ironwood; undergrowth, creosote brush and cactuses.

N. 0° 02' W., bet. secs. 27 and 28.

Asc. 176 ft. over a SW. slope.

- 10.80 Spur, slopes NW.; desc. 313 ft. over a NE. slope.
- 27.60 Wash, 40 lks. wide, course NW.
- 40.00 Point for the $\frac{1}{4}$ sec. cor. of secs. 27 and 28.
 Set an iron post, 3 ft. long, $\frac{1}{2}$ in. diam., 28 ins. in the ground, with brass cap mkd.

$$\begin{array}{c} \frac{1}{4} \\ \text{S } 28 \mid \text{S } 27 \\ 1946 \end{array}$$

Raise a mound of stone, 3 ft. base, 2 ft. high, W. of cor.

- 40.20 Wash, 50 lks. wide, course SW.
- 45.60 An old road, bears E. and W.
- 80.00 Point for the cor. of secs. 21, 22, 27, and 28.
 Set an iron post, 3 ft. long, 2 ins. diam., 28 ins. in the ground, with brass cap mkd.

$$\begin{array}{c} \text{T4N R9W} \\ \text{S } 21 \mid \text{S } 22 \\ \text{S } 28 \mid \text{S } 27 \\ 1946 \end{array}$$

Raise a mound of stone, 3 ft. base, 2 ft. high, W. of cor.

Land, broken hills and nearly level.
 Soil, rocky gravelly and sandy, 2nd. and 3rd. rates.
 Timber, palo verde and ironwood; undergrowth; creosote brush, sage, and cactuses.

Chains.	From the cor. of secs. 22, 23, 26, and 27.
	N. 89° 57' W., bet. secs. 22 and 27
	Over level land.
10.20	Wash, 1 ch. wide, 15 ft. deep, course SW:
26.50	Wash, 20 lks. wide, 10 ft. deep; course SW.
40.00	Point for the $\frac{1}{4}$ sec. cor. of secs. 22 and 27.
	Set an iron post, 3 ft. long, 1 in. diam., 28 ins. in the ground, with brass cap mkd.
	$\frac{1}{4} \begin{array}{l} S 22 \\ S 27 \end{array}$
	1946
	Raise a mound of stone, 3 ft. base, 2 ft. high, N. of cor.
45.00	Wash, 1 ch. wide, 10 ft. deep, course SW.
80.00	The cor. of secs. 21, 22, 27, and 28.
	Land, level, and rolling.
	Soil, sandy and gravelly, 2nd and 3rd. rate.
	Timber, palo verde and ironwood; undergrowth, creosote brush, sage, and cactuses.

	N. 0° 02' W., bet. secs. 21 and 22.
	Over rolling land.
0.50	Wash, 20 lks. wide, course S. 70° W.
40.00	Point for the $\frac{1}{4}$ sec. cor. of secs. 21 and 22.
	Set an iron post, 3 ft. long, 1 in. diam., 28 ins. in the ground, with brass cap mkd.
	$\frac{1}{4} \begin{array}{l} S 21 \\ S 22 \end{array}$
	1946
	Raise a mound of stone, 2 ft. base, 1 $\frac{1}{2}$ ft. high, W. of cor.
57.10	Wash, 40 lks. wide, course SW.
80.00	Point for the cor. of secs. 15, 16, 21, and 22.
	Set an iron post, 3 ft. long, 2 ins. diam., 28 ins. in the ground, with brass cap mkd.
	$\begin{array}{l} T4N R9W \\ S 16 S 15 \\ S 21 S 22 \end{array}$
	1946

Subdivision of T. 4 N., R. 9 W.

Chains.

Raise a mound of stone, $2\frac{1}{2}$ ft. base, 2 ft. high,
W. of cor.

Land, gently rolling.
Soil, sandy and gravelly, 3 rd. rate.
Timber, palo verde and ironwood; undergrowth, creosote
brush, sage and cactuses.

From the cor. of secs. 14, 15, 22, and 23.

N. $89^{\circ} 57'$ W., bet. secs. 15 and 22.

Over rolling land.

40.06 Point for the $\frac{1}{4}$ sec. cor. of secs, 15 and 22.

Set an iron post, 3 ft. long, 1 in. diam., 28 ins. in the
ground, with brass cap mkd.

$\frac{1}{4}$ $\frac{S 15}{S 22}$
1946

Raise a mound of stone, 2 ft. base, $1\frac{1}{2}$ ft. high,
N. of cor.

76.30 Wash, 20 lks. wide, course SW.

80.12 The cor. of secs. 15, 16, 21, and 22.

Land, rolling.
Soil, gravelly and rocky, 3rd. rate.
Timber, palo verde and ironwood; undergrowth, creosote
brush, sage, cats claw, and cactuses.

N. $0^{\circ} 02'$ W., bet. secs. 15 and 16.

Over gently rolling land.

20.60 An old road, bears NE. and SW.

36.70 Wash, 60 lks. wide, 20 ft. deep, course SW.

40.00 Point for the $\frac{1}{4}$ sec. cor. of secs. 15 and 16.

Set an iron post, 3 ft. long, 1 in. diam., 28 ins. in the
ground, with brass cap mkd.

$\frac{1}{4}$
S 16 | S 15
1946

Raise a mound of stone, $2\frac{1}{2}$ ft. base, 2 ft. high,
W. of cor.

59.40 Wash, 20 lks. wide, 15 ft. deep, course SW.

Subdivision of T. 4 N., R. 9 W.

Chains.
80.00 Point for the cor. of secs. 9, 10, 15, and 16.
Set an iron post, 3 ft. long, 2 ins. diam., 18 ins. in the ground and in a mound of stone $3\frac{1}{2}$ ft. base to top, with brass cap mkd.

T4N R9W	
S 9	S 10
S 16	S 15

1946

Land, rolling.
Soil, gravelly and sandy, 3rd. rate.
Timber, palo verde and ironwood; undergrowth, creosote brush, sage, and cactuses.

From the cor. of secs. 10, 11, 14, and 15.
N. 89° 57' W. bet. secs. 10 and 15.
Over rolling desert land.

17.65 Wash, 50 lks. wide, 15 ft. deep, course S. 30° W.

40.07 Point for the $\frac{1}{4}$ sec. cor. of secs. 10 and 15.
Set an iron post, 3 ft. long, 1 in. diam., 28 ins. in the ground, with brass cap mkd.

$\frac{1}{4}$ S 10
S 15

1946

Raise a mound of stone, 3ft. base, 2 ft. high, N. of cor.

40.95 An old road, bears N. and S.

43.75 wash, 50 lks. wide, 20 ft. deep, course S.

62.75 Wash, 25 lks. wide, 12 ft. deep, course SW.

80.14 The cor. of secs. 9, 10, 15, and 16.
Land, rolling.
Soil, gravelly and rocky, 3rd. rate.
Timber, palo verde and ironwood; undergrowth, creosote brush, sage, and cactuses.

N. 0° 02' W., bet. secs. 9 and 10.
Over gently rolling desert land.

14.00 wash, 40 lks. wide, 5 ft. deep, course S. 60° W.

27.50 Center of wash, 150 lks. wide, 2 ft. deep, course SW.

Subdivision of T. 4 N., R. 9 W.

BOOK 4348

Chains.
40.00Point for the $\frac{1}{4}$ sec. cor. of secs. 9 and 10.

Set an iron post, 3 ft. long, 1 in. diam., 28 ins. in the ground, with brass cap mkd.

$$\begin{array}{c} \frac{1}{4} \\ \text{S } 9 \text{ | S } 10 \\ \hline 1946 \end{array}$$

from which

An ironwood, 8 ins. diam., bears S. $89\frac{1}{4}^{\circ}$ E., 122 lks. dist., mkd. $\frac{1}{4}$ S 10 BT.An ironwood, 7 ins. diam., bears N. $0\frac{1}{4}^{\circ}$ W., 90 lks. dist., mkd. $\frac{1}{4}$ S 9 BT.

80.00

Point for the cor. of secs. 3, 4, 9, and 10.

Set an iron post, 3 ft. long, 2 ins. diam., 28 ins. in the ground, with brass cap mkd.

$$\begin{array}{c} \text{T } 4\text{N } \text{R } 9\text{W} \\ \text{S } 4 \text{ | S } 3 \\ \hline \text{S } 9 \text{ | S } 10 \\ \hline 1946 \end{array}$$
Raise a mound of stone, $2\frac{1}{2}$ ft. base, 2 ft. high, W. of cor.

Land, rolling.

Soil, sandy and gravelly, 3 rd. rate.

Timber, palo verde and ironwood; undergrowth, creosote brush, sage, and cactuses.

from the cor. of secs. 2, 3, 10, and 11.N. $89^{\circ} 56'$ W., bet. secs. 3 and 10.

Over rolling desert land.

2.80

Wash, 40 lks. wide, 12 ft. deep, course S.

25.10

Enter broken hills, bears N. and S.

40.04

Point for the $\frac{1}{4}$ sec. cor. of secs. 3 and 10.

Set an iron post, 3 ft. long, 1 in. diam., 28 ins. in the ground, with brass cap mkd.

$$\begin{array}{c} \frac{1}{4} \text{ S } 3 \\ \text{S } 10 \\ \hline 1946 \end{array}$$
Raise a mound of stone, $2\frac{1}{2}$ ft. base, 2 ft. high, N. of cor.

Subdivision of T. 4 N., R. 9 W.

Chains

45.50 wash, 30 lks. wide, 7 ft. deep, course SW.

61.50 Wash, 80 lks. wide, 5 ft. deep, course S. 25° W.

80.08 The cor. of secs. 3, 4, 9, and 10.

Land, rolling.
Soil, gravelly and rocky, 3rd. rate.
Timber, palo verde and ironwood; undergrowth, creosote brush, sage, and cactuses.

N. 0° 02' W., bet. secs. 3 and 4.

Over rolling desert land.

9.60 Dim road, bears W. and E. 10 chs. to end.

12.60 Enter broken hills, bears E. and W.; asc. 110 ft. over a SW. slope.

25.10 spur, slopes W.; desc. 155 ft. over a N. slope.

33.70 Wash, 8 lks. wide, course S. 70° W.

40.00 Point for the 1/4 sec. cor. of secs. 3 and 4, in a wash, 10 lks. wide, course SW.

41.00 Establish a witness 1/4 sec. cor. of secs. 3 and 4.

Set an iron post, 3 ft. long, 1 in. diam., 28 ins. in the ground, with brass cap mkd.



1946


Raise a mound of stone, 2 1/2 ft. base, 2 ft. high, W. of cor.

45.50 Wash, 20 lks. wide, course SW.; enter rolling land, bears NE. and SW.

64.10 wash, 30 lks. wide, 23 ft. deep, course SW.

73.02 Intersect the 1st. Stan. Par. N.; point for the closing cor. of secs. 3 and 4.

Set an iron post, 3 ft. long, 2 ins. diam., 28 ins. in the ground, with brass cap mkd.



1946

Raise a mound of stone, 3 ft. base, 2 ft. high, S. of cor.

From this cor. the standard cor. of secs. 34 and 35, T. 5

Subdivision of T. 4 N., R. 9 W.

BOOK 4848

Chains.

N., R. 9 W., bears S. 89° 53' E., 11.88 chs. dist., marked with an iron post, 2 ins. diam., firmly set, marked and witnessed as described in the 1942 resurvey record.

Land, rolling, and broken hills.
Soil, rocky and sandy, 2nd. and 3rd. rates.
Timber, palo verde and ironwood; undergrowth, creosote brush, sage, cats claw, and cactuses.

Point for the $\frac{1}{4}$ sec. cor. of sec. 3 at midpoint on the N. bdy. of sec. 3.

Set an iron post, 3 ft. long, 1 in. diam., on a ledge and in a mound of stone 6 ft. base to top, with brass cap mkd.

$\frac{1}{4}$ S 3

-----1946-----

From this cor. the standard $\frac{1}{4}$ sec. cor. of sec. 35, T. 5 N., R. 9 W., bears S. 89° 53' E., 11.80 chs. dist., marked with an iron post, 1 in. diam., firmly set, marked and witnessed as described in the 1942 resurvey record.

From the cor. of secs. 4, 5, 32, and 33, on the S. bdy. of the Tp., marked with an iron post, 2 ins. diam., firmly set in a mound of stone 4 ft. base, 3 ft. high to top, marked and witnessed as described in the official record.

N. 0° 02' W., bet. secs. 32 and 33.

Over broken desert land.

- 1.60 wash, 20 lks. wide, course S. 60° W.
- 17.70 Wash, 20 lks. wide, course W., winding.
- 24.00 Foot of hill, bears E. and W.; asc. 205 ft. over a S. Slope.
- 35.30 Top of ascent; top of hill bears NW., 5 chs. dist.; desc. 50 ft. over a NE. slope.
- 40.00 Point for the $\frac{1}{4}$ sec. cor. of secs. 32 and 33.

Set an iron post, 3 ft. long, 1 in. diam., 12 ins. in the ground and in a mound of stone 4 ft. base to top, with brass cap mkd.

S 32 $\frac{1}{4}$ S 33

-----1946-----

Desc. 91 ft. over a NE. slope.

Chains.
49.90

Foot of hill, bears SE. and NW.

80.00

Point for the cor. of secs. 28, 29, 32, and 33.

Set an iron post, 3 ft. long, 2 ins. diam., 28 ins. in the ground, with brass cap mkd.

T4N R9W	
S 29	S 28
S 32	S 33

1946

Raise a mound of stone, 3 ft. base, 2½ ft. high, W. of cor.

Land, rolling and broken.

Soil, gravelly and rocky, 3 rd. rate.

Timber, palo verde and ironwood; undergrowth, creosote brush, sage, and cactuses.

From the cor. of secs. 27, 28, 33, and 34.

N. 89° 59' W., bet. secs. 28 and 33.

Over broken hills, desc. 106 ft. over a W. slope.

18.40

Wash, 10 lks. wide, course NW.; Asc. 243 ft. over a NE. slope.

40.10

Point for the ¼ sec. cor. of secs. 28 and 33.

Set an iron post, 3 ft. long, 1 in. diam., 3 ins. in the ground and in a mound of stone 5 ft. base to top, with brass cap mkd.

¼	S 28
	S 33

1946

Asc. 56 ft. over a NE. slope.

42.10

Spur, slopes N.; desc. 321 ft. over a W. slope.

55.20

Foot of descent; thence over rolling land.

68.00

Wash, 10 lks. wide, course SW.

80.20

The cor. of secs. 28, 29, 32, and 33.

Land, broken hills.

Soil, rocky, 4th. rate.

Timber, palo verde and ironwood; undergrowth, creosote brush, sage, and cactuses.

N. 0° 02' W., bet. secs. 28 and 29.

Subdivision of T. 4 N., R. 9 W.

BOOK 3848

Chains.	
	Over gently rolling land.
33.40	Wash, 50 lks. wide, course S. 80° W.
40.00	Point for the $\frac{1}{4}$ sec. cor. of secs. 28 and 29. Set an iron post, 3 ft. long, 1 in. diam., 28 ins. in the ground, with brass cap mkd. $\begin{array}{c} \frac{1}{4} \\ \uparrow \\ \text{S } 29 \text{ S } 28 \\ \text{1946} \end{array}$ Raise a mound of stone, 3 ft. base, 2 ft. high, W. of cor.
44.00	Wash, 80 lks. wide, course W.
46.00	An old road, bears E. and W.
79.70	Wash, 20 lks. wide, course SW.
80.00	Point for the cor. of secs. 20, 21, 28, and 29, on the right bank of a wash. For the description of the witness cor. established, see the line bet. secs. 21 and 28. Land, gently rolling. Soil, gravelly, 3rd. rate. Timber, palo verde and ironwood; undergrowth, creosote brush, sage, and cactuses.

	From the cor. of secs. 21, 22, 27, and 28. N. 89° 57' W., bet. secs. 21 and 28. Over rolling land.
1.85	Wash, 20 lks. wide, course S. 60° W.
33.15	Wash, 20 lks. wide, course SW.
40.03	Point for the $\frac{1}{4}$ sec. cor. of secs. 21 and 28. Set an iron post, 3 ft. long, 1 in. diam., 28 ins. in the ground, with brass cap mkd. $\begin{array}{c} \frac{1}{4} \text{ S } 21 \\ \text{S } 28 \\ \text{1946} \end{array}$ Raise a mound of stone, 2 ft. base, 1 $\frac{1}{2}$ ft. high, N. of cor.
79.06	Establish a witness cor. of secs. 20, 21, 28, and 29. Set an iron post, 3 ft. long, 2 ins. diam., 28 ins. in the ground, with brass cap mkd.

Subdivision of T. 4 N., R. 9 W.

Chains.

	T4N R9W	
W C	S 20	S 21
	S 29	S 28

1946

Raise a mound of stone, 2 ft. base, 1½ ft. high,
W. of cor.

79.95 Wash, 20 lks. wide, course SW.

80.06 The cor. of secs. 20, 21, 28, and 29.

Land, gently rolling.
Soil, gravelly, 3rd. rate.
Timber, palo verde and ironwood; undergrowth, creosote
brush, sage, and cactuses.

N. 0° 02' W., bet. secs. 20 and 21.

Over gently rolling desert land.

31.10 Enter wash, 15 lks. wide, 4 ft. deep, course SW. from N.;

33.30 Leave bottom of wash, course S. from NE.

40.00 Point for the ¼ sec. cor. of secs. 20 and 21.

Set an iron post, 3 ft. long, 1 in. diam., 14 ins. in the
ground and in a mound of stone 3 ft. base to top, with
brass cap mkd.

	¼	
	S 20	S 21
		1946

From this cor. a butte bears N. 54¼° E.

41.90 An old road, bears SW. and N. 60° E.

43.40 Wash, 50 lks. wide, 2 ft. deep, course SW.

72.20 Wash, 50 lks. wide, 2 ft. deep, course SW.

80.00 Point for the cor. of secs. 16, 17, 20, and 21.

Set an iron post, 3 ft. long, 2 ins. diam., 28 ins. in the
ground, with brass cap mkd.

	T4N R9W	
	S 17	S 16
	S 20	S 21
		1946

Raise a mound of stone, 2½ ft. base, 2 ft. high,
W. of cor.

From this cor. the same butte, bears S. 39¼° E.

Subdivision of T. 4N., R. 9 W.

BOOK 4008

Obs ins.

Land, rolling.
Soil, sandy and gravelly, 2nd. and 3rd. rates.
Timber, palo verde and ironwood; undergrowth, creosote
brush, sage, cats claw, and cactuses.

from the cor. of secs. 15, 16, 21, and 22.

West, bet. secs. 16 and 21.

32.65 An old road, bears NE. and SW.

35.25 wash, 70 lks. wide, 6 ft. deep, course SW.

40.02 Point for the $\frac{1}{4}$ sec. cor. of secs. 16 and 21.

Set an iron post, 3 ft. long, 1 in. diam., 28 ins. in the
ground, with brass cap mkd.

$$\frac{1}{4} \begin{array}{l} S 16 \\ S 21 \\ 1946 \end{array}$$

Raise a mound of stone, 3 ft. base, 2 ft. high,
N. of cor.

60.05 Wash, 60 lks. wide, 3 ft. deep, course S. 30° W.

70.75 Wash, 30 lks. wide, low banks, course SW.

80.04 The cor. of secs. 16, 17, 20, and 21.

Land, gently rolling desert.
Soil, gravelly and rocky, 2nd. and 3rd. rates.
Timber, palo verde and ironwood; undergrowth, creosote
brush, sage, cats claw, and cactuses.

N. 0° 02' W., bet. secs. 16 and 17.

Over nearly level desert land, thru scattering vegetation.

20.00 Wash, 25 lks. wide, low banks, course S. 60° W.

34.50 Wash, 60 lks. wide, low banks, course SW.

40.00 Point for the $\frac{1}{4}$ sec. cor. of secs. 16 and 17.

Set an iron post, 3 ft. long, 1 in. diam., 28 ins. in the
ground, with brass cap mkd.

$$S 17 \begin{array}{l} \frac{1}{4} \\ S 16 \\ 1946 \end{array}$$

Raise a mound of stone, 2 $\frac{1}{2}$ ft. base, 2 ft. high,
W. of cor.

80.00 Point for the cor. of secs. 8, 9, 16, and 17.

Subdivision of T. 4 N., R. 9 W.

Chains.

Set an iron post, 3 ft. long, 2 ins. diam., 28 ins. in the ground, with brass cap, mkd.

T4N	R9W
S 8	S 9
S 17	S 16

1946

Raise a mound of stone, 2 ft. base, 1½ ft. high, W. of cor.

Land, nearly level.

Soil, sandy and gravelly, 2nd and 3rd. rates.

Timber, palo verde and ironwood; undergrowth, creosote brush, sage, cats claw, and cactuses.

From the cor. of secs. 9, 10, 15, and 16.

S. 89° 57' W., bet. secs. 9 and 16.

Over nearly level desert land.

16.65 Center of wash, 150 lks. wide, 2 ft. banks, course SW.

40.02 Point for the ¼ sec. cor. of secs. 9 and 16.

Set an iron post, 3 ft. long, 1 in. diam., 28 ins. in the ground, with brass cap mkd.

¼	S 9
	S 16

1946

from which

An ironwood, 10 ins. diam., bears N. 11¼° E., 91 lks. dist., mkd. ¼ S9 BT.

An ironwood, 8 ins. diam., bears S. 61¼° W., 142 lks. dist., mkd. ¼ S16 BT.

80.04 The cor. of secs. 8, 9, 16, and 17.

Land, nearly level.

Soil, sandy and gravelly, 2nd. and 3rd. rates.

Timber, palo verde and ironwood; undergrowth, creosote brush, sage, cats claw, and cactuses.

N. 0° 02' W., bet. secs. 8 and 9.

Over rolling land.

11.30 wash, 60 lks. wide, 2 ft. deep, course SW.

32.80 An old road, bears NE. and SW.

Subdivision of T. 4 N., R. 9 W.

BOOK 4048

Chains.

38.90

Establish a witness $\frac{1}{4}$ sec. cor. of secs. 8 and 9.

Set an iron post, 3 ft. long, 1 in. diam., 28 ins. in the ground, with brass cap mkd.

$$\begin{array}{c} \text{W C} \\ \uparrow \\ \text{S } 8 \mid \text{S } 9 \\ \text{1946} \end{array}$$
Raise a mound of stone, $2\frac{1}{2}$ ft. base, 2 ft. high, W. of cor.

40.00

Point for the $\frac{1}{4}$ sec. cor. of secs. 8 and 9, on the edge of a wash, course SW.

42.00

Wash, 18 ft. deep, course SW.

48.20

Wash, 25 lks. wide, 27 ft. deep, course S. 35° W.; enter broken hills, bear NE. and SW.

63.30

Same wash, 20 lks. wide, 10 ft. deep, course SE.

80.00

Point for the cor. of secs. 4, 5, 8, and 9.

Set an iron post, 3 ft. long, 2 ins. diam., 28 ins. in the ground, with brass cap mkd.

$$\begin{array}{c} \text{T4N R9W} \\ \text{S } 5 \mid \text{S } 4 \\ \hline \text{S } 8 \mid \text{S } 9 \\ \text{1946} \end{array}$$

1946

Raise a mound of stone, $2\frac{1}{2}$ ft. base, 2 ft. high, W. of cor.

Land, rolling and broken hills.

Soil, sandy and rocky, 2nd. and 3rd. rates.

Timber, palo verde and ironwood; undergrowth, creosote brush, sage, cats claw, and cactuses.

From the cor. of secs. 3, 4, 9, and 10.S. $89^{\circ} 58'$ W., bet. secs. 4 and 9.

Over rolling land.

29.20

An old road, bears NE. and SW.

31.50

wash, 50 lks. wide, course SW.

40.05

Point for the $\frac{1}{4}$ sec. cor. of secs. 4 and 9.

Set an iron post, 3 ft. long, 1 in. diam., 28 ins. in the ground, with brass cap mkd.

$$\begin{array}{c} \frac{1}{4} \text{ S } 4 \\ \text{S } 9 \\ \text{1946} \end{array}$$

Chains.

Raise a mound of stone, 2½ ft. base, 2 ft. high, N. of cor.

Enter broken hills, bear NE. and SW.

69.70 Wash, 10 lks. wide, 10 ft. deep, course S. 20° W.

80.10 the cor. of secs. 4, 5, 8, and 9.

Land, rolling and broken hills.
Soil, gravelly and rocky, 2nd. and 3rd. rates.
Timber, palo verde and ironwood; undergrowth, creosote brush, sage, and cactuses.

N. 0° 02' W., bet. secs. 4 and 5.

Asc. 222 ft. over a broken S. slope.

14.50 Spur, slopes S. 15° E.; desc. 45 ft. along an E. slope.

26.20 Wash, near head, course S. 60° E.; desc. 110 ft. over a SE. slope.

33.40 Spur, slopes E.; thence along a broken E. slope.

40.00 Point for the ¼ sec. cor. of secs. 4 and 5.

Set an iron post, 3 ft. long, 1 in. diam., 28 ins. in the ground, with brass cap mkd.

¼
S 5 | S 4
1946

Raise a mound of stone, 3 ft. base, 2 ft. high, W. of cor.

This cor. is on a spur, slopes N. 60° E.; desc. 175 ft. over a NE. slope.

50.80 Wash, 10 lks. wide, near head, course E.; asc. 167 ft. over a S. slope.

61.80 Spur, slopes S. 80° E.; desc. 75 ft. over a NE. slope.

65.50 wash, near head, course S. 80° E.; asc. 165 ft. over a SE. slope.

73.36 Intersect the 1st. Stan. Par. N.; point for the closing cor. of secs. 4 and 5.

Set an iron post, 3 ft. long, 2 ins. diam., 14 ins. in the ground and in a mound of stone 4 ft. base to top, with brass cap mkd.

T5N R9W
S 33

S 5 | S 4
T4N R9W
C C
1946

Subdivision of T. 4 N., R. 9 W.

Chains.

From this cor. the standard cor. of secs. 33 and 34, T. 5 N., R. 9 W., bears S. 89° 53' E., 11.86 chs. dist., marked with an iron post, 2 ins. diam., firmly set in a mound of stone 4 ft. base to top, marked and witnessed as described in the 1942 resurvey record.

Land; broken hills.

Soil, gravelly and rocky, 3rd. rate.

Timber, palo verde and ironwood; undergrowth, creosote brush, sage, and cactuses.

Point for the $\frac{1}{4}$ sec. cor. of sec. 4 at midpoint on the N. bdy. of sec. 4.

Set an iron post, 3 ft. long, 1 in. diam., 28 ins. in the ground, with brass cap mkd.

$\frac{1}{4}$ S 4

1946

Raise a mound of stone, 3 ft. base, 2 ft. high, S. of cor.

From this cor. the standard $\frac{1}{4}$ sec. cor. of sec. 34, T. 5 N., R. 9 W., bears S. 89° 53' E., 11.87 chs. dist., marked with an iron post, 1 in. diam., firmly set in a mound of stone 4 ft. base to top, marked and witnessed as described in the 1942 resurvey record.

From the cor. of secs. 5, 6, 31, and 32, on the S. bdy. of the Tp., marked with an iron post, 2 ins. diam., firmly set, marked and witnessed as described in the official record.

N. 0° 03' W., bet. secs. 31 and 32.

From this cor. a 4 wire barbed wire fence bears E. and W. wash, 30 lks. wide, course SW.

24.70

40.00

Point for the $\frac{1}{4}$ sec. cor. of secs. 31 and 32.

Set an iron post, 3 ft. long, 1 in. diam., 28 ins. in the ground, with brass cap mkd.

$\frac{1}{4}$
S 31 | S 32

1946

Raise a mound of stone, 2 ft. base, 1½ ft. high, W. of cor.

54.20

An old road, bears N. 20° E. and S. 20° W.

Subdivision of T. 4 N., R. 9 W.

Chains.

70.90 Wash, 15 lks. wide, course S. 60° W.

75.50 Wash, 10 lks. wide, course S. 30° W.

80.00 Point for the cor. of secs. 29, 30, 31, and 32.

Set an iron post, 3 ft. long, 2 ins. diam., 28 ins. in the ground, with brass cap mkd.

T4N	R9W
S 30	S 29
S 31	S 32

1946

Raise a mound of stone, 2 ft. base, 1½ ft. high, W. of cor.

Land, nearly level.

Soil, sandy and gravelly, 2nd. and 3rd. rates.

Timber, palo verde and ironwood; undergrowth, creosote brush, sage, and cactuses.

From the cor. of secs. 28, 29, 32, and 33.

N. 89° 56' W., bet. secs. 29 and 32.

Over nearly level land.

27.60 Wash, 30 lks. wide, course SW.

33.40 Wash, 30 lks. wide, course S. 70° W.

39.94 Point for the ¼ sec. cor. of secs. 29 and 32.

Set an iron post, 3 ft. long, 1 in. diam., 28 ins. in the ground, with brass cap mkd.

¼	S 29
	S 32

1946

Raise a mound of stone, 2 ft. base 1½ ft. high, N. of cor.

48.70 Wash, 80 lks. wide, course S. 10° W.

55.40 An old road, bears NE. and SW.

60.50 Road, bears N. and S.

79.88 The cor. of secs. 29, 30, 31, and 32.

Land, gently rolling.

Soil, sandy and gravelly, 3rd. rate.

Timber, palo verde and ironwood; undergrowth, creosote brush, sage, cats claw, and cactuses.

Subdivision of T. 4 N., R. 9 W.

Chains.

From the cor. of secs. 25, 30, 31, and 36, on the W. bdy. of the Tp., marked with an iron post, 2 ins. diam., firmly set, marked and witnessed as described in the official record.

S. 89° 58' E., bet. secs. 30 and 31.

Over nearly level land.

39.04 Point for the $\frac{1}{4}$ sec. cor. of secs. 30 and 31.

Set an iron post, 3 ft. long, 1 in. diam., 28 ins. in the ground, with brass cap mkd.

$$\frac{1}{4} \begin{array}{c} \text{S } 30 \\ \hline \text{S } 31 \\ 1946 \end{array}$$

Raise a mound of stone, 2 ft. base, $1\frac{1}{2}$ ft. high, N. of cor.

40.35 Wash, 10 lks. wide, course S. 30° W.

50.35 Wash, 30 lks. wide, course S. 20° W.

79.04 The cor. of secs. 29, 30, 31, and 32.

Land, nearly level.

Soil, sandy and rocky, 3rd. rate.

Timber, palo verde and ironwood; undergrowth, creosote brush, sage, and cactuses.

N. 0° 03' W., bet. secs. 29 and 30.

Over nearly level desert thru scattering vegetation.

37.70 Road, bears S. 15° E., and N. 15° W.

40.00 Point for the $\frac{1}{4}$ sec. cor. of secs. 29 and 30.

Set an iron post, 3 ft. long, 1 in. diam., 28 ins. in the ground, with brass cap mkd.

$$\frac{1}{4} \begin{array}{c} \text{S } 30 \mid \text{S } 29 \\ \hline 1946 \end{array}$$

Raise a mound of stone, 3 ft. base, 2 ft. high, W. of cor.

From the cor. a windmill and well bears N. 27° W.

80.00 Point for the cor. of secs. 19, 20, 29, and 30.

Set an iron post, 3 ft. long, 2 ins. diam., 28 ins. in the ground, with brass cap mkd.

$$\begin{array}{c} \text{T4N } 89\text{W} \\ \text{S } 19 \mid \text{S } 20 \\ \hline \text{S } 30 \mid \text{S } 29 \\ 1946 \end{array}$$

Subdivision of T. 4 N., R. 9 W.

Chains.

Raise a mound of stone, 3 ft. base, 2 ft. high,
W. of cor.

From the cor. the same windmill and well bears S. $53\frac{1}{4}^{\circ}$ W.

From the cor. a butte bears S. $71^{\circ} 52'$ E.

Land, nearly level desert.

Soil, gravelly, 2nd. rate.

Timber, palo verde and ironwood; undergrowth, creosote
brush, sage, cats claw, and cactuses.

From the cor. of secs. 20, 21, 28, and 29.

N. $89^{\circ} 58'$ W., bet. secs. 20 and 29.

Over nearly level desert land.

12.30 wash, 20 lks. wide, course SW.

14.90 An old road, bears NE. and SW.

23.80 wash, 50 lks. wide, course S. 20° W.

27.54 Butte, bears S. $26^{\circ} 26'$ W.

39.91 Point for the $\frac{1}{4}$ sec. cor. of secs. 20 and 29.

Set an iron post, 3 ft. long, 1 in. diam., 28 ins. in the
ground, with brass cap mkd.

$\frac{1}{4}$ $\frac{S 20}{S 29}$
1946

Raise a mound of stone, 3 ft. base, 2 ft. high,
N. of cor.

79.82 The cor. of secs. 19, 20, 29, and 30.

Land, nearly level.

Soil, sandy and gravelly, 2nd. and 3rd. rates.

Timber, palo verde and ironwood; undergrowth, creosote
brush, sage, cats claw, and cactuses.

From the cor. of secs. 19, 24, 25, and 30, on the W. bdy.
of the Tp., marked with an iron post, 2 ins. diam.,
firmly set, marked and witnessed as described in the
official record.

N. $89^{\circ} 59'$ E., bet. secs. 19 and 30.

Over nearly level desert land.

8.90 Wash, 20 lks. wide, 3 ft. banks, course S.

31.00 Wash, 25 lks. wide, 5 ft. deep, course SW.

38.98 Point for the $\frac{1}{4}$ sec. cor. of secs. 19 and 30.

Subdivision of T. 4 N., R. 9 W.

BOOK 4000

Chains.

Set an iron post, 3 ft. long, 1 in. diam., 28 ins. in the ground, with brass cap mkd.

$$\frac{1}{4} \begin{array}{c} \text{S 19} \\ \hline \text{S 30} \\ 1946 \end{array}$$

Raise a mound of stone, 2½ ft. base, 2 ft. high, N. of cor.

41.60 Wash, 30 lks. wide, 6 ft. deep, course SW.

53.50 Wash, 25 lks. wide, course SW.

59.60 An old road, bears N. and S.

78.98 The cor. of secs. 19, 20, 29, and 30.

Land, nearly level.

Soil, sandy and gravelly, 2nd. and 3rd. rates.

Timber, palo verde and ironwood; undergrowth, creosote brush, sage, cats claw, and cactuses.

N. 0° 03' W., bet. secs. 19 and 20.

27.10 Wash, 15 lks. wide, 3 ft. deep, course SW.

37.90 Wash, 20 lks. wide, 7 ft. deep, course SW.

40.00 Point for the ¼ sec. cor. of secs. 19 and 20.

Set an iron post, 3 ft. long, 1 in. diam., 28 ins. in the ground, with brass cap mkd.

$$\begin{array}{c} \frac{1}{4} \\ \text{S 19} \mid \text{S 20} \\ 1946 \end{array}$$

Raise a mound of stone, 2½ ft. base, 2 ft. high, W. of cor.

63.50 Wash, 50 lks. wide, 4 ft. deep, course SW.

73.80 Wash, 40 lks. wide, 7 ft. deep, course SW.

80.00 Point for the cor. of secs. 17, 18, 19, and 20.

Set an iron post, 3 ft. long, 2 ins. diam., 28 ins. in the ground, with brass cap mkd.

$$\begin{array}{c} \text{T4N R9W} \\ \text{S 18} \mid \text{S 17} \\ \hline \text{S 19} \mid \text{S 20} \\ 1946 \end{array}$$

1946

Raise a mound of stone, 2½ ft. base, 2 ft. high, W. of cor.

Subdivision of T. 4 N., R. 9 W.

Chains.

Land, nearly level.
Soil, sandy and gravelly, 2nd. and 3rd. rates.
Timber, palo verde and ironwood; undergrowth, creosote brush, sage, cats claw, and cactuses.

From the cor. of secs. 16, 17, 20, and 21.

N. 89° 55' W., bet. secs. 17 and 20.

30.80 Wash, 30 lks. wide, course SW.

39.94 Point for the $\frac{1}{4}$ sec. cor. of secs. 17 and 20.

Set an iron post, 3 ft. long, 1 in. diam., 8 ins. in the ground and in a mound of stone 4 ft. base to top, with brass cap mkd.

$\frac{1}{4}$ $\frac{S\ 17}{S\ 20}$
1946

56.20 Wash, 30 lks. wide, 2 ft. deep, course SW.

71.00 Wash, 40 lks. wide, 5 ft. deep, course SW.

79.88 The cor. of secs. 17, 18, 19, and 20.

Land, nearly level.
Soil, sandy and gravelly, 2nd. and 3rd. rates.
Timber, palo verde and ironwood; undergrowth, creosote brush, sage, cats claw, and cactuses.

From the cor. of secs. 13, 18, 19, and 24, on the W. bdy. of the Tp., marked with an iron post, 2 ins. diam., firmly set, marked and witnessed as described in the official record.

S. 89° 57' E., bet. secs. 18 and 19.

Desc. 13 ft.

0.75 Wash, 40 lks. wide, course S. 20° W.; asc. 193 ft. over a W. slope.

15.25 Spur, slopes SW.; thence along a steep S. slope.

21.15 Short spur, slopes S.; desc. 193 ft. over a broken SE. slope.

38.87 Point for the $\frac{1}{4}$ sec. cor. of secs. 18 and 19.

Set an iron post, 3 ft. long, 1 in. diam., 10 ins. in the ground and in a mound of stone 4 ft. base to top, with brass cap mkd.

$\frac{1}{4}$ $\frac{S\ 18}{S\ 19}$
1946

Subdivision of T. 4 N., R. 9 W.

BOOK 4048

Chains.

- Desc. 50 ft. over a SE. slope.
- 51.45 Wash, 100 lks. wide, 20 ft. deep, course SW.; leave broken hills bearing NE. and SW., enter rolling desert land.
- 67.15 An old road, bears N. and S.
- 78.87 The cor. of secs. 17, 18, 19, and 20.
- Land, broken hills and rolling desert.
Soil, rocky, 3rd. rate.
Timber, palo verde and ironwood; undergrowth, creosote brush, sage, cats claw, and cactuses.
-
- N. 0° 03' W., bet. secs. 17 and 18.
- Over rolling desert land.
- 15.70 An old road, bears E. and W.
- 25.60 Wash, 70 lks. wide, 10 ft. deep, course S. 60° W.; enter low broken hills, bear NE. and SW.
- 39.60 Establish a witness $\frac{1}{4}$ sec. cor. of secs. 17 and 18.
- Set an iron post, 3 ft. long, 1 in. diam., 28 ins. in the ground, with brass cap mkd.

W C
 $\frac{1}{4}$
 S 18 | S 17
 1946

Raise a mound of stone, 3 ft. base, 2 ft. high,
W. of cor.

- 40.00 Point for the $\frac{1}{4}$ sec. cor. of secs. 17 and 18, on a sloping ledge.
- Asc. 37 ft. over a SE. slope.
- 43.60 Spur, slopes SW.; desc. 32 ft.
- 48.00 Foot of descent; thence along a broken SE. slope.
- 64.20 Dim road, bears NE. and SW.
- 67.20 Same road, bears NW. and SW.
- 70.80 Same road in bend, N. 15° W. and SW.
- 80.00 Point for the cor. of secs. 7, 8, 17, and 18.

Set an iron post, 3 ft. long, 2 ins. diam., 18 ins. in the ground and in a mound of stone 3 ft. base to top, with brass cap mkd.

T4N R9W
 S 7 | S 8
 S 18 | S 17

1946

Subdivision of T. 4 N., R. 9 W.

Chains.

Land, rolling and broken hills.
Soil, gravelly and rocky, 3rd. rate.
Timber, palo verde and ironwood; undergrowth, creosote
brush, sage, cats claw, and cactuses.

From the cor. of secs. 8, 9, 16, and 17.

West, bet. secs. 8 and 17.

Over rolling desert land.

13.00 Wash, 60 lks. wide, course SW.

22.30 An old road, bears NE. and SW.

27.30 Wash, 70 lks, wide, 20 ft. deep, course S. 20° W.

39.89 Point for the 1/4 sec. cor. of secs. 8 and 17.

Set an iron post, 3 ft. long, 1 in. diam., 28 ins. in the
ground, with brass cap mkd.

1/4 $\frac{S\ 8}{S\ 17}$
1946

Raise a mound of stone, 3 ft. base, 2 ft. high,
N. of cor.

53.60 Wash, 15 lks. wide, 15 ft. deep, course S.; enter low
broken hills, bear NE. and SW.; asc. 35 ft.

61.00 Spur, slopes S. 20° W.; desc. 45 ft.

79.78 The cor. of secs. 7, 8, 17, and 18.

Land, rolling and broken hills.
Soil, gravelly and rocky, 3rd. rate.
Timber, palo verde and ironwood; undergrowth, creosote
brush, sage, cats claw and cactuses.

From the cor. of secs. 7, 12, 13, and 18, on the W. bdy.
of the Tp., marked with an iron post, 2 ins. diam.,
firmly set in a mound of stone, 1 1/2 ft. high to top,
marked and witnessed as described in the official record.

S. 89° 57' E., bet. secs. 7 and 18.

Desc. 90 ft. over a broken SE. slope.

4.85 Road, bears N. and S.

24.05 Wash, 30 lks. wide, course SW.; asc. 45 ft.

29.85 Spur, slopes SW.; desc. 45 ft. over a SE. slope.

36.25 Establish a witness 1/4 sec. cor. of secs. 7 and 18.

Subdivision of T. 4 N., R. 9 W.

Chains.	
	<p>Set an iron post, 3 ft. long, 1 in. diam., 28 ins. in the ground, with brass cap mkd.</p> $\frac{1}{4} \frac{S 7}{S 18} W C$ <p>1946</p> <p>Raise a mound of stone, 2½ ft. base, 2 ft. high, N. of Cor.</p>
38.25	Wash, 30 lks. wide, 12 ft. deep, course SW.; road in wash, bears SW. and NE.
38.85	Point for the ¼ sec. cor. of secs. 7 and 18, on a precipitous slope.
39.75	Same wash, course N. for 30 lks. then W.
45.05	Same wash, 10 lks. wide, course S. 70° W.
70.45	Dim road, bears NW. and SE.; asc. 30 ft. over a N. slope.
76.05	Spur, slopes SW.; desc. 37 ft. over a SE. slope.
78.85	The cor. of secs. 7, 8, 17, and 18.
	<p>Land, low broken hills. Soil, rocky, 3rd. rate. Timber, palo verde and ironwood; undergrowth, creosote brush, sage, cats claw, and cactuses.</p> <p>-----</p> <p>N. 0° 03' W., bet. secs. 7 and 8. Asc. 75 ft. over a SE. slope.</p>
10.20	Spur, slopes W.; asc. 76 ft. along a broken W. slope.
20.90	Spur, slopes N. 80° W.; a mine shaft, bears S. 53° W., about 5.50 chs. dist.; another mine shaft at end of road, bears S. 70° W., about 5.00 chs. dist.; desc. 117 ft. over a NW. slope.
34.60	Wash, 15 lks. wide, course S. 60° W.; asc. 23 ft.
40.00	Point for the ¼ sec. cor. of secs. 7 and 8.
	<p>Set an iron post, 3 ft. long, 1 in. diam., 12 ins. in the ground and in a mound of stone 3½ ft. base to top, with brass cap mkd.</p> $S 7 \begin{array}{c} \uparrow \\ S 8 \end{array}$ <p>1946</p> <p>Asc. 63 ft. over a S. slope.</p>
48.30	Spur, slopes W. from NE.; desc. 57 ft. over a W. slope.
58.90	Wash, 8 lks. wide, course W.
60.60	Wash, 10 lks. wide, course SW.

42.

BOOK 4848

Subdivision of T. 4 N., R. 9 W.

Chains.							
66.70	Road, bears SW. and NE. to cabin.						
68.60	W. L. Barron's cabin, bears E. 25 lks. dist.						
71.40	Wash, 15 lks. wide, course SW.; asc. 55 ft. over a SE. slope.						
80.00	Point for the cor. of secs. 5, 6, 7, and 8. Set an iron post, 3 ft. long, 2 ins. diam., 14 ins. in the ground and in a mound of stone $3\frac{1}{2}$ ft. base to top, with brass cap mkd.						
	<table style="margin-left: auto; margin-right: auto;"> <tr><td>T4N</td><td>R9W</td></tr> <tr><td>S 6</td><td>S 5</td></tr> <tr><td>S 7</td><td>S 8</td></tr> </table> <p>1946.</p>	T4N	R9W	S 6	S 5	S 7	S 8
T4N	R9W						
S 6	S 5						
S 7	S 8						
	Land, low broken hills. Soil, rocky, 3rd. rate. Timber, palo verde and ironwood; undergrowth, creosote brush, sage, and cactuses.						

	From the cor. of secs. 4, 5, 8, and 9. N. 89° 58' W., bet. secs. 5 and 8. Asc. 44 ft. over a SE. slope.						
2.80	Spur, slopes S.; desc. 70 ft.						
13.50	Wash, 15 lks. wide, course SE. from N.						
29.90	Wash, 15 lks. wide, course SE.; asc. 48 ft. over NE. slope.						
39.91	Point for the $\frac{1}{4}$ sec. cor. of secs. 5 and 8. Set an iron post, 3 ft. long, 1 in. diam., 20 ins. in the ground and in a mound of stone 3 ft. base to top, with brass cap mkd.						
	<table style="margin-left: auto; margin-right: auto;"> <tr><td>$\frac{1}{4}$</td><td>S 5</td></tr> <tr><td></td><td>S 8</td></tr> </table> <p>1946</p>	$\frac{1}{4}$	S 5		S 8		
$\frac{1}{4}$	S 5						
	S 8						
	Asc. 44 ft. over a NE. slope.						
45.60	Ridge, bears N. and S.; desc. 34 ft. along a N. slope.						
58.80	Slope changes to NW.; desc. 148 ft.						
70.30	Wash, 10 lks. wide, course SW. in ravine; asc. 20 ft. over a SE. slope.						
79.82	The cor. of secs. 5, 6, 7, and 8. Land, broken hills. Soil, rocky, 3rd. rate. Timber, palo verde and ironwood; undergrowth, creosote brush, sage, and cactuses.						

Subdivision of T. 4 N., R. 9 W.

BOOK 9046

Chains.

From the cor. of secs. 1, 6, 7, and 12, on the w. bdy of the Tp., marked with an iron post, 2 ins. diam., firmly set in a mound of stone $1\frac{1}{2}$ ft. high to top, marked and witnessed as described in the official record.

S. $89^{\circ} 58'$ E., bet. secs. 6 and 7.

Desc. 16 ft. over an E. slope.

2.40 Wash, 10 lks. wide, in ravine, course S.; asc. 255 ft. over a SW. slope.

25.30 Spur, slopes SW.; desc. 204 ft. over a SE. slope.

38.71 Point for the $\frac{1}{4}$ sec. cor. of secs. 6 and 7.

Set an iron post, 3 ft. long, 1 in. diam., 18 ins. in the ground, and in a mound of stone 3 ft. base to top, with brass cap mkd.

$$\begin{array}{r} \frac{1}{4} \text{ S } 6 \\ \text{S } 7 \\ 1946 \end{array}$$

39.30 Ravine, 5 lks. wide, course S.; asc. 156 ft. over a SW. slope.

54.40 Spur, slopes S.; desc. 152 ft. over a SE. slope.

78.71 The cor. of secs. 5, 6, 7, and 8.

Land, broken hills.

Soil, rocky, 3rd. rate.

Timber, palo verde and ironwood; undergrowth, creosote brush, sage, cats claw, and cactuses.

N. $0^{\circ} 03'$ W., bet. secs. 5 and 6.

Asc. 120 ft. over a broken S. slope.

14.70 Ridge, bears N. 80° W. and E.; desc. 72 ft. over a N. slope.

19.60 Wash, 5 lks. wide, course NW.; thence over broken land.

34.50 Wash, 20 lks. wide, course SW.

40.00 Point for the $\frac{1}{4}$ sec. cor. of secs. 5 and 6.

Set an iron post, 3 ft. long, 1 in. diam., 28 ins. in the ground, with brass cap mkd.

$$\begin{array}{r} \frac{1}{4} \text{ S } 6 \\ \text{S } 5 \\ 1946 \end{array}$$

Raise a mound of stone, 3 ft. base, 2 ft. high, W. of cor.

42.40 Wash, 20 lks. wide, course S. 70° W. from NE.; desc. 85 ft. over a S. slope.

49.90 root of descent; asc. 55 ft. over a S. slope.

Subdivision of T. 4 N., R. 9 W.

Chains.

57.50 Spur, slopes N. 80° W.; desc. 117 ft. over a N. slope.

64.10 Wash, 5 lks. wide, course W.

73.47 Intersect the 1st. Stan. Par. N.; point for the closing cor. of secs. 5 and 6.

Set an iron post, 3 ft. long, 2 ins. diam., 28 ins. in the ground, with brass cap mkd.

T5N R9W	
S 32	

S 6	S 5
T4N R9W	C
C	
1946	

Raise a mound of stone, 3 ft. base, 2 ft. high, S. of cor.

From this cor. the standard cor. of secs. 32 and 33, T. 5 N., R. 9 W., bears S. 89° 53' E., 11.72 chs. dist., marked with an iron post, 2 ins. diam., firmly set in a mound of stone 1½ ft. high to top, marked and witnessed as described in the 1942 resurvey record.

and, broken hills.

Soil, rocky, 3rd. rate.

Timber, palo verde and ironwood; undergrowth, creosote brush, sage, cats claw, and cactuses.

Point for the ¼ sec. cor. of sec. 5 at midpoint on the N. bdy. of sec. 5, in a wash, course S. 80° W.

Establish a witness ¼ sec. cor. of sec. 5, N. 89° 53' W., 70 lks. dist.

Set an iron post, 3 ft. long., 1 in. diam., 18 ins. in the ground and in a mound of stone 3 ft. base to top, with brass cap mkd.

¼ S 5	W C
1946	

From the ¼ sec. cor. the standard ¼ sec. cor. of sec. 33, T. 5 N., R. 9 W., bears S. 89° 53' E., 11.79 chs. dist., marked with an iron post, 1 in. diam., firmly set, marked and witnessed as described in the 1942 resurvey record.

Point for the ¼ sec. cor. of sec. 6 at a point on the N. bdy. 40.00 chs. from the NE. cor. of sec. 6.

Set an iron post, 3 ft. long, 1 in. diam., 6 ins. in the ground and in a mound of stone 4 ft. base to top, with brass cap mkd.

¼ S 6	
1946	

Subdivision of T. 4 N., R. 9 W.

Chains.

From this cor. the standard $\frac{1}{4}$ sec. cor. of sec. 32, T. 5 N., R. 9 W., bears S. $89^{\circ} 53'$ E., 11.72 chs. dist., marked with an iron post, 1 in. diam., firmly set in a mound of stone $1\frac{1}{2}$ ft. high to top, marked and witnessed as described in the 1942 resurvey record.

Final Test of Solar Attachments.

May 13, 1946, in camp in the NE. $\frac{1}{4}$ of sec. 30, T. 4 N., R. 9 W., on the meridian hereinbefore described, at 8 a.m. and 4 p.m., make the proper settings on the arcs of the solar attachments and ascertain that the resulting orientation of the instruments agree with the meridian established by Polaris observation.

General Description.

The area embraced in this survey ranges from broken hills to nearly level desert land, with a general drainage SW. through the middle of the Tp. The soil, is sandy, gravelly, and rocky.

The Tp. is covered with a scattering growth of palo-verde and ironwood timber, with some mesquite along the washes. The undergrowth is cactuses, creosote brush, sage, ocotillo, and cats claw.

There are no patented mineral claims in the area. No present mineral activity is evident but there has been some prospecting in the past. Two mine shafts are located in the SE. $\frac{1}{4}$ of sec. 7.

One cabin in the NW. $\frac{1}{4}$ of sec. 8 constitutes the extent of settlement.

Stock grazing is the principal industry. There is but one source of water in the Tp. a well and windmill in the NE. $\frac{1}{4}$ of sec. 30.

The roads traversing the area are unimproved desert roads infrequently used.

UNITED STATES
DEPARTMENT OF THE INTERIOR
GENERAL LAND OFFICE

FIELD ASSISTANTS

NAMES	CAPACITY
Bert E. Wakeman	Senior Engineering Aid
John Beggs	Engineering Aid
Stephen B. Viggers	Principal Assistant
James C. Bennett	Chairman
Donald C. DePman	Bookkeeper
Benjamin V. Young	Field Assistant
Benjamin P. Cook	" "
Arlene Schreiber	" "

82
48

CERTIFICATE OF SURVEYOR

I, F. Wayne Forrest, HEREBY CERTIFY upon honor that, in
pursuance of special instructions bearing date of the 29th day of October, 1941
received from the district cadastral engineer for Arizona, with assignment
instructions dated February 14 and April 13, 1946, I have surveyed the subdivisioal lines of
Township 4 North, Range 9 West,

of the Gila & Salt River Meridian, in the State of Arizona, which are
represented in the foregoing field notes as having been executed by me and under my direction; and that said
survey has been made in strict conformity with said instructions, the Manual of Instructions for the Survey
of the Public Lands of the United States, and in the specific manner described in the foregoing field notes.

Glendale, California,
June 10, 1946

F. Wayne Forrest
Assistant Cadastral Engineer

CERTIFICATE OF APPROVAL

~~CHIEF~~ **CADASTRAL ENGINEER**
OFFICE OF ~~Supervisor of Surveys~~

Denver, Colorado, June 25, 1947

The foregoing field notes of the survey of the subdivisioal lines of Township 4 North,
Range 9 West of the Gila and Salt River Meridian, in the State of Arizona,

executed by F. Wayne Forrest, Assistant Cadastral Engineer,
under special instructions dated October 29, 1941, and assignment
instructions dated February 14 and April 13, 1946, having been critically examined, and
the necessary corrections made prior to their certification by the engineer, the said field notes, and the survey
therein described, are hereby approved.

[Signature]
~~Supervisor of Surveys~~
Acting Chief Cadastral Engineer.

~~CERTIFICATE OF TRANSCRIPT~~

~~I CERTIFY that the foregoing transcript of the field notes of the above-described surveys in
is a true copy of the original field notes on file in the public survey office.~~

~~Supervisor of Surveys.~~