

UNITED STATES  
DEPARTMENT OF THE INTERIOR  
~~GENERAL LAND OFFICE~~

BUREAU OF LAND MANAGEMENT

BOOK 4354

FIELD NOTES

of the

RESURVEY

of the

Sixth Standard Parallel North, along the South Boundary of T.25 N., R.5 E.,

First Guide Meridian East, along the East Boundary of T.24 N., R.4 E.,

and the

Subdivision of T.24 N., R.5 E.

Of the Gila and Salt River Meridian,

In the State of ARIZONA

EXECUTED BY

Ty White, Associate Cadastral Engineer,

Claude F. Warner, Assistant Cadastral Engineer,

Bert E. Wakeman, Senior Engineering Aid.

Under special instructions dated March 13, 1942, which provided  
for the surveys included under Group No. 239, bearing the approval of the  
Commissioner of the General Land Office under date of March 28, 1942  
and assignment instructions dated June 26, 1944 and June 16, 1945.

Survey commenced September 14, 1944.

Survey completed October 26, 1945.

4354

1A

BOOK 4354

# INDEX DIAGRAM.

Township 24 North, Range 5 East.

	8	6	5	4	3	2
17	90	89	68	56	45	31
16	88 6	88 5	67 4	55 3	42 2	29 1
	86	85	66	54	41	28
14	87 7	84 8	65 9	53 10	39 11	27 12
	82	82	64	52	38	27
13	84 18	80 17	63 16	50 15	37 14	26 13
	79	78	62	50	36	25
11	80 19	77 20	61 21	48 22	35 23	23 24
	75	74	60	47	34	23
10	76 30	73 29	59 28	46 27	33 26	21 25
	71	70	58	45	32	20
9	72 31	69 32	56 33	43 34	31 35	19 36

6-151

TOWNSHIP 24 NORTH, RANGE 5 EAST

36	31	32	33	34	35	36
6	5	4	3	2	1	
7	8	9	10	11	12	
18	17	16	15	14	13	
19	20	21	22	23	24	
30	29	28	27	26	25	
31	32	33	34	35	36	

- Indicates surveys executed by Ty White in 1944
- Indicates surveys executed by Ty White in 1945
- Indicates surveys executed by Claude F. Warner

Date of Survey

North Boundary: September 18 to October 14, 1944  
 West Boundary: October 15 to October 25, 1945 ←  
 Subdivisions: July 3 to September 20, 1945

*Some done  
in June, 1947*

T. 24 N., R. 5 E.

BOOK 4354

The resurveys hereinafter described were executed with Buff solar transits Nos. 16724 and 9984, equipped with Smith solar attachments, constructed in accordance with the standard specifications of the General Land Office. The instruments were in good condition and having been placed in satisfactory adjustment prior to the beginning of the resurvey and tested and found free from appreciable error, were approved by the district cadastral engineer.

The directions of the lines were determined by the solar transit method. The measurements were made with Lufkin steel tapes, 5 chains in length, graduated every link for the first 100 links and the balance at intervals of 10 links. The tapes were tested by comparison with a Lufkin standard steel tape and found correct. The measurements were made on the slope and the vertical angles ascertained with a clinometer in good adjustment; the horizontal equivalents are entered in the field note record.

The geographic position of the southeast corner of the township, as determined from the State map, is as follows: Latitude  $35^{\circ} 25' N.$  and longitude  $111^{\circ} 48' W.$

July 7, 1944, in camp, at Curley Seep Guard Station, in the  $SE\frac{1}{4}$   $SW\frac{1}{4}$ , sec. 21; T. 24 N., R. 5 E., Gila and Salt River Meridian, Arizona, my watch reading correct 105th meridian time, as checked by radio time signals, make an hour angle observation on Polaris, east of the meridian, making four observations, two each with the telescope in direct and reversed positions, reading the horizontal deflection angles from a well defined point on a dead pine tree, approximately 15 chains northwesterly.

To determine the latitude of the station; read the vertical angles to Polaris.

Mean watch time of observation	8h 07m 27s p.m.
Watch fast of l.m.t.	0h 27m 04s

Mean horizontal deflection angle	$1^{\circ} 31' 30''$
Azimuth of Polaris	$0^{\circ} 18' 42''$

Bearing of reference point	N. $1^{\circ} 12' 48''$ W.
----------------------------	----------------------------

Mean observed vertical angle	$34^{\circ} 29' 45''$
Reduced latitude	$35^{\circ} 25' 44'' N.$

July 9, 1944, with Buff solar transit No. 16724 on the meridian above described, every 30 minutes from 8 to 10:30 a.m., and from 1:30 to 4 p.m., make the proper settings on the arcs of the solar attachment and ascertain that the resulting orientation of the instrument when compared with the meridian established by Polaris observation, have a maximum error of less than  $1' 30''$ .

June 28, 1945, at the same station, with Buff solar transits Nos. 16724 and 9984, every 30 minutes from 8 to 10:30 a.m., and from 1:30 to 4 p.m., make the proper settings on the arcs of the solar attachments and ascertain that the resulting orientation of the instruments when compared with the meridian established by Polaris observation, have a maximum error of less than  $1' 30''$ .

We repeat the tests of the arcs daily by noon observations and verify the meridional indications at frequent intervals throughout the survey.

The observed magnetic declination is  $14^{\circ} 45' E.$

## Resurvey of the 6th Stan. Pa. N., S. Bdy. T. 25 N., R. 5 E.

## Chains

Preliminary to the resurvey the lines of the original survey are retraced and diligent search is made for all original corners. Identified corners of the original survey are reestablished in their original positions. All lost corners are reestablished at proportionate positions, based on the record of the original survey. The retrace-ment data are thoroughly verified and only the true line notes are given here.

-----

Reestablishment of the survey executed by A. E. Shoemaker, Deputy Surveyor, in 1883, and resurveyed by F. W. Oury, Deputy Surveyor, in 1894.

-----

Note: For the field notes of the east half mile of the S. bdy. of sec. 36, see the field notes of T. 24 N., R. 6 E., resurveyed under this group.

From the standard  $\frac{1}{4}$  sec. cor. of sec. 36.

S.  $89^{\circ} 54'$  W., along the S. bdy. of sec. 36.

Over rolling land, through scattered timber and heavy undergrowth.

Ascend 11 ft. over a gentle N. slope.

- 0.95 Graded road, bears N.  $10^{\circ}$  W. to Grand Canyon and S.  $10^{\circ}$  E. to Flagstaff.
- 5.20 Low spur, slopes NW.; desc. 39 ft. over a gradual W. slope.
- 15.90 A wire drift fence, bears N.  $21\frac{1}{2}^{\circ}$  W. and S.  $21\frac{1}{2}^{\circ}$  E.
- 21.60 Draw, drains N.  $20^{\circ}$  E.; thence, along a gentle N. slope.
- 40.48 The standard cor. of secs. 35 and 36, as evidenced by a lava stone, 22x10x8 ins., firmly set in a mound of stone, 2 ft. base, 1 ft. high, mkd. SC on N., 5 grooves on W., and 1 groove on E. faces.

Set an iron post, 3 ft. long, 2 ins. diam., 28 ins. in the ground, with the original cor. stone buried alongside, at the standard cor. of secs. 35 and 36, with brass cap mkd.

S C  
T25N | R5E  
S35 | S36

1944

from which

A pine, 4 ins. diam., bears N.  $7\frac{1}{2}^{\circ}$  E., 43 lks. dist., mkd. T 25 N R 5 E S 36 S C B T.

A pine, 4 ins. diam., bears N.  $59\frac{3}{4}^{\circ}$  W., 33 lks. dist., mkd. T 25 N R 5 E S 35 S C B T.

Land, rolling.

Soil, rocky, 2nd and 3rd rates.

Timber, yellow pine, pinon and juniper; undergrowth, 2nd growth timber.

-----

## Resurvey of the 6th Stan. Par. N., S. Bdy. T. 25 N., R. 5 E.

Chains	N. 89° 27' W., along the S. bdy. of sec. 35. Over rolling land, through scattered timber and dense undergrowth. Ascend along a gentle N. slope.
6.15	Old road, bears NW. and SE.
14.00	Foot of ascent; enter mountainous land, bears NW. and SE.; asc. 64 ft. over a NE. slope.
20.80	Short spur, slopes N.; desc. 40 ft. over a NW. slope.
25.00	Enter heavy timber and scattered undergrowth, bears N. and S.
26.90	Draw, 1 chain wide, drains N. 20° E.; asc. 68 ft. over a SE. slope.
40.16	The standard $\frac{1}{4}$ sec. cor., determined from the old bearing tree. Set an iron post, 3 ft. long, 1 in. diam., 28 ins. in the ground, at standard $\frac{1}{4}$ sec. cor., with brass cap mkd.
	S C $\frac{1}{4}$ S 35 1944
	from which Old bearing tree: A pine, 20 ins. diam., bears S. 4° 29' E., 8 lks. dist., mkd. $\frac{1}{4}$ S B T. New bearing trees: A juniper, 4 ins. diam., bears N. 62½° E., 76 lks. dist., mkd. $\frac{1}{4}$ S 35 S C B T. A pine, 28 ins. diam., bears N. 26½° W., 45 lks. dist., mkd. $\frac{1}{4}$ S 35 S C B T. Thence, S. 89° 46' W., along the S. bdy. of sec. 35. Ascend 34 ft. over a SE. slope.
4.20	Spur, slopes N. 30° E.; desc. 12 ft. over a NW. slope.
5.05	Ravine, course N. 30° E.; asc. 116 ft. over an E. slope.
10.90	Spur, slopes NE.; desc. 33 ft. over a NW. slope.
13.30	Steep ravine, course N. 25° E.; asc. 284 ft. over an E. slope.
24.00	Spur, slopes NE. from S. 70° W.; continue ascent of 83 ft. along a steep N. slope.
38.13	The standard cor. of secs. 34 and 35, determined from the old bearing trees. Set an iron post, 3 ft. long, 2 ins. diam., 28 ins. in the ground, at standard cor. of secs. 34 and 35, with brass cap mkd.

Resurvey of the 6th Stan. Par. N., S. Bdy. of T. 25 N., R. 5 E.

Chains

S. C.  
T25N | R5E  
S34 | S35

1944

from which

Old bearing trees:

A pine, 16 ins. diam., bears N. 7° E., 29 lks.  
dist., mkd. T 25 N R 5 E S 34 B T S C

A pine, 18 ins. diam., bears N. 76° E., 38 lks.  
dist., markings overgrown. Mark on overgrowth T 25 N  
R 5 E S 35 S C B T.

New bearing tree:

A pine, 5 ins. diam., bears N. 37½° W., 68 lks.  
dist., mkd. T 25 N R 5 E S 34 S C B T.

Land, E. 14.00 chs. rolling; remainder of mile mountainous.  
Soil, rocky, 3rd rate.  
Timber, yellow pine, pinon and juniper; undergrowth, 2nd  
growth timber.

S. 89° 53' W., along the S. bdy. of sec. 34.

Over mountainous land, through heavy timber and scattered  
undergrowth.

Along a N. slope.

0.40 Spur, slopes N. 20° E.; desc. 40 ft. over a NW. slope.

4.00 Steep ravine, course N. 10° E.; heads 1.50 chs. S.; asc.  
263 ft. over a NE. slope.

16.83 S. end of a saddle in a high spur, slopes N. Forest Service  
Lookout Station on top of Slate Mountain, bears S. 26° W.;  
desc. 237 ft. over a W. slope.

19.76 Lookout Station on Slate Mountain, bears S. 15° 42' W.

26.50 Steep ravine, course NW.; asc. 26 ft. along a steep N.  
slope.

32.10 Steep spur, slopes NW.; desc. 173 ft. over a rocky W.  
slope.

38.08 The standard ¼ sec. cor. as evidenced by a limestone,  
10x8x6 ins., firmly set in a mound of stone, 2 ft. base,  
1 ft. high, mkd. ¼ on N. face.

Set an iron post, 3 ft. long, 1 in. diam., 28 ins. in the  
ground, with the old corner stone buried alongside, at  
standard ¼ sec. cor., with brass cap mkd,

S. C.  
¼ S 34

1944

from which

Old bearing tree:

A pine, 18 ins. diam., bears N. 10½° W., 10 lks.  
dist., mkd. ¼ S B T. Additionally mark on overgrowth  
¼ S 34 S C B T.

## Resurvey of the 6th Stan. Par. N., S. Bdy. of T. 25 N., R. 5 E.

## Chains

## New bearing tree:

A pine, 5 ins. diam., bears N.  $48\frac{1}{2}^{\circ}$  E., 100 lks. dist., mkd.  $\frac{1}{4}$  S 34 S C B T.

Thence,

N.  $89^{\circ} 35'$  W., along the S. bdy. of sec. 34.

Descend 508 ft. over a NW. slope.

39.10 The standard cor. of secs. 33 and 34, determined from old bearing tree.

Set an iron post, 3 ft. long, 2 ins. diam., 28 ins. in the ground, at standard cor. of secs. 33 and 34, with brass cap mkd.

S C	
T25N	R5E
S33	S34

1944

from which

## Old bearing tree:

The original position of a pine, (now dead lying on ground), 18 ins. diam., bears N.  $0^{\circ} 03'$  E., 125 lks. dist., markings are too faint to be read.

## New bearing trees:

A pine, 7 ins. diam., bears N.  $5^{\circ}$  E., 2 lks. dist., mkd. T 25 N R 5 E S 34 S C B T.

A juniper, 6 ins. diam., bears N.  $39\frac{3}{4}^{\circ}$  W., 37 lks. dist., mkd. T 25 N R 5 E S 33 S C B T.

Land, mountainous.

Soil, rocky, 3rd and 4th rates.

Timber, yellow pine, pinon, juniper, fir and spruce; undergrowth, 2nd growth timber and wild currants.

S.  $89^{\circ} 41'$  W., along the S. bdy. of sec. 33.

Over mountainous land, through heavy timber and scattered undergrowth.

Descend 36 ft. over a NW. slope.

3.90 Old road bears N. and S; about 16 chs. S. of this point a road forks from this road to the W. and travels along the N. side of Prong Lake.

4.45 Wash, 20 lks. wide, course N.; foot of descent of Slate Mountain, bears N. and S.; leave timber, enter open grassy land, bears N. and S.; asc. 22 ft. over an E. slope.

15.00 Top of ascent, bears N. and S., thence, over nearly level land.

26.20 A ditch from Prong Lake, 8 lks, wide, 1 ft. deep, flows NE.

40.22 The standard  $\frac{1}{4}$  sec. cor., as evidenced by a lava stone,  $14 \times 8 \times 5$  ins., firmly set in the ground, mkd. S C  $\frac{1}{4}$  on N. face; a mound of stone, 2 ft. base, 1 ft. high, N. of cor.

## Resurvey of the 6th Stan. Par. N., S. Bdy. of T. 25 N., R. 5 E.

## Chains

Set an iron post, 3 ft. long, 1 in. diam., 28 ins. in the ground, with the old corner stone buried alongside, at standard  $\frac{1}{4}$  sec. cor., with brass cap mkd.

S C  
 $\frac{1}{4}$  S33

1944

raise a mound

of stone,  $3\frac{1}{2}$  ft. base, 2 ft. high, N. of corner.

The center of Prong Lake, an earthen reservoir, 3 chs. diam., bears S.  $10^{\circ}$  W., 8.80 chs. dist.; from a point a short distance NE. of the lake, a drift fence extends W. and S.

Thence,

S.  $89^{\circ} 37'$  W., along the S. bdy. of sec. 33.

Over gently rolling land, through scattered timber.

6.20 A ditch, 8 lks. wide,  $1\frac{1}{2}$  ft. deep, flows S.  $20^{\circ}$  E. to Prong Lake.

40.39 The standard cor. of secs. 32 and 33, as evidenced by a malpais stone  $12 \times 8 \times 6$  ins. firmly set in the ground, mkd. 4 notches on E. and 2 notches on W. edges and S C on N. face; a mound of stone, 2 ft. base, 1 ft. high, N. of cor.

Set an iron post, 3 ft. long, 2 ins. diam., 28 ins. in the ground, with the old corner stone buried alongside, at standard corner of secs. 32 and 33, with brass cap mkd.

S C  
T25N | R5E  
S32 | S33

1944

from which

A pinon, 4 ins. diam., bears N.  $70^{\circ}$  E., 116 lks. dist., mkd. T 25 N R 5 E S 33 S C B T.

A pinon, 3 ins. diam., bears N.  $64^{\circ}$  W., 107 lks. dist., mkd. S C B T.

Land, E. 4.45 chs. mountainous; remainder of mile, nearly level.

Soil, rocky, 2nd and 3rd rates.

Timber, yellow pine, juniper and pinon; undergrowth, 2nd growth timber.

S.  $89^{\circ} 41'$  W., along the S. bdy. of sec. 32.

Over rolling land, through scattered timber and undergrowth.

13.10 Wash, 6 lks. wide; course NW.; thence, along a rolling N. slope.

39.80 Wash, 6 lks. wide; course N.  $10^{\circ}$  E.

40.07 The standard  $\frac{1}{4}$  sec. cor., as evidenced by a malpais stone,  $16 \times 12 \times 8$  ins., firmly set in the ground, mkd. S C  $\frac{1}{4}$  on N. face; a mound of stone, 2 ft. base, 1 ft. high, S. of cor.

## Resurvey of the 6th Stan. Par. N., S. Bdy. of T. 25 N., R. 5 E.

## Chains

Set an iron post, 3 ft. long, 1 in. diam., 6 ins. in the ground to solid rock, with the old corner stone buried alongside, and in a mound of stone to top, at standard  $\frac{1}{4}$  sec. cor., with brass cap mkd.

S C  
 $\frac{1}{4}$  S 32

1944

from which

## Old bearing trees:

A pine, 24 ins. diam., bears N.  $58\frac{3}{4}^{\circ}$  E., 67 lks. dist., mkd.  $\frac{1}{4}$  S B T. Additionally mark on overgrowth  $\frac{1}{4}$  S 32 S C B T.

A pine, 26 ins. diam., bears S.  $1\frac{1}{2}^{\circ}$  E., 37 lks. dist., mkd.  $\frac{1}{4}$  S B T.

## New bearing tree:

A pine, 10 ins. diam., bears N.  $24\frac{3}{4}^{\circ}$  W., 109 lks. dist., mkd.  $\frac{1}{4}$  S 32 S C B T.

Thence,

N.  $88^{\circ} 49'$  W., along the S. bdy. of sec. 32.

Along a rolling N. slope.

9.15 A 4 wire drift fence, bears N,  $15^{\circ}$  W. and S.  $15^{\circ}$  E.

14:80 Ravine, course N.; continue along a rolling N. slope.

40.15 The standard cor. of secs. 31 and 32, as evidenced by a malpais stone, 12x10x5 ins., firmly set in the ground, mkd. 5 notches on E. and 1 notch on W. edges; a mound of stone, 2 ft. base, 1 ft. high, S. of cor.

Set an iron post, 3 ft. long, 2 ins. diam., 28 ins. in the ground, with the old cor. stone buried alongside, at standard corner of secs. 31 and 32, with brass cap mkd.

S C  
T25N | R5E  
S31 | S32

1944

from which

## Old bearing tree:

A pine stump, 20 ins. diam., bears S.  $87^{\circ} 22'$  W., 461 lks. dist., mkd. S C B T.

## New bearing trees:

A pine, 3 ins. diam., bears N.  $22^{\circ}$  E., 395 lks. dist., mkd. S C B T.

A pine, 4 ins. diam., bears N.  $26^{\circ}$  W., 367 lks. dist., mkd. S C B T.

Land, rolling.

Soil, rocky, 2nd and 3rd rates.

Timber, yellow pine, juniper and pinon; undergrowth, 2nd growth timber.

Resurvey of the 6th Stan. Par. N., S. Bdy. of T. 25 N., R. 5 E..

Chains

N. 89° 11' W., along the S. bdy. of sec. 31.

Over rolling land, through scattered timber and undergrowth.

Along a rolling N. slope.

4.85 Wash, 5 lks. wide, course NW.

29.00 Slope changes; desc. 28 ft. over a W. slope.

40.26 The standard 1/4 sec. cor., as evidenced by a malpais stone, 14x12x10 ins., firmly set in the ground, mkd. S C 1/4 on N. face; a mound of stone, 2 ft. base, 1 ft. high, S. of cor.

Set an iron post, 3 ft. long, 1 in. diam., 28 ins. in the ground, with the old corner stone buried alongside, at standard 1/4 sec. cor., with brass cap, mkd.

S C  
1/4 S 31

1944

from which

Old bearing tree:

A pinon, 20 ins. diam., bears S. 15° E., 68 lks. dist., mkd. 1/4 S B T.

New bearing trees:

A pinon, 4 ins. diam., bears N. 20 3/4° E., 18 lks. dist., mkd. 1/4 S 31 S C B T.

A pinon, 3 ins. diam., bears N. 70 1/4° W., 82 lks. dist., mkd. 1/4 S 31 S C B T.

Thence,

N. 89° 23' W., along the S. bdy. of sec. 31.

Descend 50 ft. over a SW. slope.

14.40 Foot of descent, bears NW. and SE.; enter wide valley, thence, over nearly level land.

16.60 Old road, bears NW. and SE.

21.10 Wash, 15 lks. wide, 4 ft. deep, course N. 30° W.

40.15 The standard corner of Ts. 25 N., Rs. 4 and 5 E., as evidenced by a juniper post, 4 ins. sq., 2 ft. long, firmly set in the ground, mkd: T 25 N R 4 E S 36 on NW., T 25 N R 5 E S 31 on NE., and S C on S. faces and 6 notches on N., E. and W. edges.

Set an iron post, 3 ft. long, 3 ins. diam., 28 ins. in the ground; with the original wood post buried alongside, at standard corner of Ts. 25 N., Rs: 4 and 5 E., with brass cap mkd.

SC  
T 25 N  
R4E | R5E  
S36 | S31

1944

from which

## Resurvey of the 6th. Stan. Par. N., S. Bdy. of T. 25 N., R. 5 E.

## Chains

A juniper, 4 ins. diam., bears N.24°E., 124 lks. dist., mkd. B.T.

A juniper, 3 ins. diam., bears N.22°W., 193 lks. dist., mkd. B T.

Land, rolling.

Soil, E. 54 chs. rocky, 3rd and 4th rate; remainder of mile, sandy loam, 1st rate.

Timber, juniper, pinon and yellow pine; undergrowth, 2nd growth timber.

-----  
Resurvey of the E. Bdy. of T.24 N., R.4 E.  
-----

Reestablishment of the survey executed by F.W.Oury, Deputy Surveyor, and C.E.Perkins, Compassman and Deputy Surveyor, in 1894; resurveyed by Marvin Caudle, Deputy Surveyor in 1903, who established corners on this line referring to sections in R. 4 E., only. Corners of the original (Oury) survey function as angle points only, and are so remonumented.

-----  
From the cor. of Ts. 23 and 24 N., R. 4 E., evidenced by an iron post, 3 ins. diam., firmly set, mkd. and witnessed as described in the field notes of the E. bdy. of T. 23 N. R. 4 E., resurveyed under this group.

N.0° 12'W., on the E. bdy. of sec. 36,

Over gently rolling land, through heavy growth of timber.

19.95 Road, bears N.70°W. to Stiver's Ranch and SE. to Spring Valley. Continue through scattered timber.

39.94 The  $\frac{1}{4}$  sec. cor. of sec. 36, evidenced by a lava stone, 16x16x16 ins., firmly set, mkd.  $\frac{1}{4}$  on the W. face, with traces of pits N. and S. of cor.

Set an iron post, 3 ft. long, 1 in. diam., 30 ins. in the ground, with the original corner stone buried alongside, at  $\frac{1}{4}$  sec. cor. of sec. 36, with brass cap mkd.

$\frac{1}{4}$  S36 |

1947

raise a mound of stone,  
2 ft. base, 1 $\frac{1}{2}$  ft. high, W. of cor.

From cor., fences extend N., S. and E.

48.42 The original  $\frac{1}{4}$  sec. cor., now an angle point, evidenced by a sandstone 14x8x5 ins., firmly set, mkd.  $\frac{1}{4}$  on the W. face, with traces of pits to the N. and S.

Set an iron post, 3 ft. long, 1 in. diam., 28 ins. in the ground, with original corner stone buried at base, at angle point, with brass cap mkd.

AP

T24N

R4E R5E

S 36 | S 31

1945

from which

A pine, 8 ins. diam., bears N.26 $\frac{3}{4}$ ° E., 252 lks. dist., mkd. T 24 N R 5 E S 31 A P B T.

A pine, 8 ins. diam., bears S.88 $\frac{1}{2}$ ° E., 285 lks. dist., mkd. T 24 N R 5 E S 31 A P B T.

Resurvey of the E. Bdy. of T. 24 N., R. 4 E.

Chains									
	N.0° 48' E., beginning new measurement.								
7.70	Stub road, bears W. to Marlars' residence, from N. and S. roadway about 1 ch. to the E.								
11.04	NE. corner of Marlar's house bears W. about 2.00 chs. dist.								
30.90	Road extends W., from irregular roadway bearing N. and S.								
31.63	The cor. of secs. 25 and 36, evidenced by a sandstone 18x10x8 ins., firmly set, mkd. with 1 notch on the S. and 5 notches on the N. faces, and witnessed by a mound of stone 2 ft. base, 1 ft. high, to the W.								
	Set an iron post, 3 ft. long, 2 ins. diam., 30 ins. in the ground, with the original corner stone buried alongside at cor. of secs. 25 and 36 with brass cap mkd.								
	<table border="0"> <tr> <td>T24N</td> <td>T24N</td> </tr> <tr> <td>S25</td> <td>R5E</td> </tr> <tr> <td>S36</td> <td>S31</td> </tr> <tr> <td>R4E</td> <td></td> </tr> </table>	T24N	T24N	S25	R5E	S36	S31	R4E	
T24N	T24N								
S25	R5E								
S36	S31								
R4E									
	1947								
	from which								
	A pine, 10 ins. diam., bears S.54½° W., 43 lks. dist., mkd. T 24 N R 4 E S 36 B T.								
	A pine, 30 ins. diam., bears N.40½° W., 181 lks. dist., mkd. T 24 N R 4 E S 25 B T.								
	From this corner wire fencing extends irregularly to the W. and N.								
	Land, slightly rolling. Soil, gravelly clay, 3rd rate. Timber, pine and 2nd growth.								
	-----								
	N.0° 22' E., on the E. bdy. of sec. 25.								
	Through cultivated field, along west side of wire fencing, extending to the N.								
8.87	Point for the original cor. of secs. 25, 30, 31 and 36, now an angle point, determined from the resurvey record.								
	Set an iron post, 3 ft. long, 2 ins. diam., 48 ins. in the ground, at angle point, with brass cap mkd.								
	<table border="0"> <tr> <td>AP</td> <td></td> </tr> <tr> <td>T24N</td> <td></td> </tr> <tr> <td>R4E</td> <td>R5E</td> </tr> <tr> <td>S25</td> <td>S31</td> </tr> </table>	AP		T24N		R4E	R5E	S25	S31
AP									
T24N									
R4E	R5E								
S25	S31								
	1945								
	from which								
	The original bearing tree:								
	A pine, 28 ins. diam., bears S.46°W., 190 lks. dist., mkd. T24N R4E S BT. Additionally mark this tree T24N R4E S25 AP BT.								
	New bearing tree:								
	A pine, 6 ins. diam., bears S.59°E., 88 lks. dist., mkd. T24N R5E S31 AP BT.								
	N.0° 19' W., beginning new measurement.								
	Continue through cultivated field.								

Resurvey of the E. Bdy. of T. 24 N., R. 4 E.

Chains

- 31.02 Point for  $\frac{1}{4}$  sec. cor., of sec. 25, determined from the original bearing trees.  
Set an iron post, 3 ft. long, 1 in. diam., 28 ins. in the ground, with brass cap mkd.  
 $\frac{1}{4}$  S 25 |  
1945  
from which  
Original bearing trees:  
A pine, 36 ins. diam., bears N.54°W., 37 lks. dist., mkd.  $\frac{1}{4}$  S 25 BT.  
A pine, 30 ins. diam., bears S.56°W., 45 lks. dist., mkd.  $\frac{1}{4}$  S 25 BT.  
From the corner wire fencing extends N., W. and E.  
N. 0° 42' E., beginning new measurement.
- 6.10 Old road, not in use, bears E. and W.
- 8.93 The original  $\frac{1}{4}$  sec. cor., now an angle point, evidenced by a sandstone 15x14x6 ins., firmly set, mkd.  $\frac{1}{4}$  on the W. face.  
Set an iron post, 3 ft. long, 1 in. diam., 28 ins. in the ground, at angle point, with original corner stone buried alongside, with brass cap mkd.  
  
AP  
T24N  
R4E | R5E  
S 25 | S 30  
1945  
from which  
An original bearing tree:  
A pine, 38 ins. diam., bears S.35°E., 57 lks. dist., markings overgrown. Remark this tree T24N R5E S30 AP BT.  
New bearing tree:  
A pine, 12 ins. diam., bears S.86 $\frac{1}{2}$ °W., 42 lks. dist., mkd. T24N R4E S25 AP BT.  
N.0° 18' W., beginning new measurement.  
Asc. 230 ft. over S. slope, through heavy growth of timber.
- 14.00 Spur, slopes SW. Desc. slightly over W. slope.
- 16.50 Head of gulch, course SW. Asc. 90 ft. over SW. slope.
- 25.00 Spur, slopes SW. Desc. 55 ft. over broken NW. slope.
- 31.03 The cor. of secs. 24 and 25; evidenced by a limestone 18x10x6 ins., firmly set, marked with 2 notches on S. and 4 notches on N. edge.  
Set an iron post, 3 ft. long, 2 ins. diam., 30 ins. in the ground with the original corner stone buried alongside at cor. of secs. 24 and 25, with brass cap mkd.  
  
T24N | T24N  
S24 | R5E  
S25 | S30  
R4E |  
1947  
from which  
An original bearing tree:

Resurvey of the E. Bdy. of T. 24 N., R. 4 E.

Chains	<p>A dead pine, 24 ins. diam., bears N.15½° W., 30 lks. dist., mkd. T24N R4E S24 BT.</p> <p>New bearing trees:</p> <p>A pine, 16 ins. diam., bears S.56°W., 81 lks. dist., mkd. T24N R4E S25 BT.</p> <p>A pine, 30 ins. diam., bears N.81½°W., 70 lks. dist., mkd. T24N R4E S24 BT.</p> <p>Land, slightly rolling and hilly. Soil, rocky, 3rd rate. Timber, pine and 2nd growth.</p> <p>-----</p> <p>N. 0°18'W., on the E. bdy. of sec. 24.</p> <p>Over mountainous land, through heavy timber.</p> <p>Desc. 20 ft. over NW. slope.</p> <p>2.00 Gulch, course SW. Asc. 113 ft.</p> <p>7.36 The original cor. of secs. 19, 24, 25 and 30, now an angle point, evidenced by a sandstone 24x14x4 ins., firmly set, mkd. with 2 notches on the S. and 4 notches on the N. faces.</p> <p>Set an iron post, 3 ft. long, 2 ins. diam., 28 ins. in the ground, at angle point, with original corner stone buried alongside, with brass cap mkd.</p> <div style="text-align: center;"> <p>AP T24N R4E   R5E S24   S30</p> <p>1945 from which</p> </div> <p>An original bearing tree:</p> <p>A pine, 24 ins. diam., bears N.25°W., 40 lks. dist., blaze is overgrown. Remark this tree T24N R4E S24 AP BT.</p> <p>New bearing tree:</p> <p>A pine, 10 ins. diam., bears N.71¼°E. 70 lks. dist., mkd. T24N R5E S30 AP BT.</p> <p>N.0° 07'E., beginning new measurement.</p> <p>Asc. 183 ft. over SW. slope.</p> <p>7.40 Spur, slopes W. Desc. 33 ft. over N. slope.</p> <p>10.30 Head of gulch, course W. Asc. 80 ft. over S. slope.</p> <p>18.90 Road, bears E. and W. Continue over bench land.</p> <p>24.00 Spur, slopes W. Desc. slightly.</p> <p>32.49 The ¼ sec. cor. of sec. 24, evidenced by a sandstone 18x12 x8 ins., firmly set, marked ¼ on W. face.</p> <p>Set an iron post, 3 ft. long, 1 in. diam., 30 ins. in the ground, with the old corner stone buried alongside at ¼ sec. cor. with brass cap mkd.</p> <div style="text-align: center;"> <p>¼   S24  </p> <p>1947 from which</p> </div> <p>Original bearing trees:</p>
--------	--

## Resurvey of the E. Bdy. of T. 24 N., R. 4 E.

4354

## Chains

A pine, 36 ins. diam., bears S.75½° W., 135 lks. dist., marks not uncovered.

A pine, 30 ins. diam., bears N.86½° W., 98 lks. dist., marks not uncovered.

N. 0° 35' W., beginning new measurement.

Desc. 95 ft. over N. slope.

5.20 Gulch, course W. Asc. 35 ft.

6.86 The original ¼ sec. cor., now an angle point, evidenced by a cross + on sandstone, in place, 36x25x10 ins., above ground, and mkd. ¼ on the W. face.

Set a bronze plate, 3½ ins. diam., 3 ins. stem, in drill hole, at angle point, marked on top

AP  
T24N  
R4E R5E  
S24 | S19

1945

from which

A pine; 30 ins. diam.; bears N.70¾° W., 116 lks. dist., mkd. T24N R4E S24 AP BT.

A pine, 8 ins. diam., bears N.46¾° E.; 71 lks. dist., mkd. T24N R5E S19 AP BT.

N.0° 36' E., beginning new measurement.

Asc. 113 ft. over SW. slope.

5.75 Spur, slopes W. Desc. 40 ft. over broken westerly slope.

22.30 Spur, slopes W. Desc. 230 ft. over NW. slope.

33.26 The cor. of secs. 13 and 24, evidenced by a malpais stone 18x12x6 ins., firmly set, marked with 3 notches on S. and 3 notches on N. edge.

Set an iron post, 3 ft. long, 2 ins. diam., 30 ins. in the ground, with the original corner stone buried alongside, with brass cap mkd.

T24N | T24N  
S13 | R5E  
S24 | S19  
R4E

1947

from which

The original bearing trees:

A pine, 10 ins. diam., bears S.54° W., 81 lks. dist., marks overgrown.

A pine, 14 ins. diam., bears N.63½° W., 77 lks. dist., marks overgrown.

New bearing tree:

A pine, 30 ins. diam., bears S.74¾° W., 109 lks. dist., mkd. T24N R4E S24 BT.

Land, mountainous.

Soil, rocky, 3rd rate.

Timber, pine and 2nd growth.

N.0° 36' E., on the E. bdy. of Sec. 13.

Over mountainous land, through heavy timber.

Desc. 140 ft. over NW. slope.

Resurvey of the E. Bdy. of T. 24 N., R. 4 E.

Chains

5.23

The original corner of secs. 13, 18, 19 and 24, now an angle point, evidenced by a sandstone 30x18x10 ins. above ground, firmly set, mkd. with 3 grooves on the S. and N. faces.

Set an iron post, 3 ft. long, 2 ins. diam., 28 ins. in the ground, at angle point, with original corner stone buried alongside, with brass cap mkd.

.AP  
T24N  
R4E .R5E  
S13 | S19

1945 from which

An original bearing tree:

A pine, now dead, 10 ins. diam., bears N.38 $\frac{3}{4}$ ° E., 79 lks. dist., mkd. T24N R5E S19 BT.

New bearing trees:

A pine, 14 ins. diam., bears S.42 $\frac{1}{4}$ ° E., 16 lks. dist., mkd. T24N R5E S19 AP BT.

A pine, 8 ins. diam., bears N.68 $\frac{3}{4}$ ° W., 27 lks. dist., mkd. T24N R5E S13 AP BT.

N.0°47'E., beginning new measurement.

Desc. 170 ft. over NW: slope.

12.00 Wash, 10 lks. wide, in gulch, course N.80°W. Continue over rolling land.

19.40 Wash, 12 lks. wide, course W.

31.60 Wash, 10 lks. wide, course W.

34.87 The  $\frac{1}{4}$  sec. cor. of sec. 13, evidenced by a malpais 24x8x6 ins., firmly set, marked  $\frac{1}{4}$  on W. face.

Set an iron post, 3 ft. long, 1 in. diam., 30 ins. in the ground with the original corner stone buried alongside at  $\frac{1}{4}$  sec. cor. of sec. 13, with brass cap mkd.

$\frac{1}{4}$   
S13 |

1947 from which

The original bearing trees:

Base of a fallen pine, 10 ins. diam., bears S.25°W., 60 lks. dist.

A pine, 30 ins. diam., bears N.30 $\frac{3}{4}$ °W., 197 lks. dist., marks overgrown.

New bearing tree:

A pine, 24 ins. diam., bears S.40 $\frac{3}{4}$ °W., 85 lks. dist., mkd.  $\frac{1}{4}$  S 13 B T.

Continue line and measurement.

38.70 Wash, 15 lks. wide, course W. Asc. 10 ft.

39.93 The original  $\frac{1}{4}$  sec. cor., now an angle point, evidenced by a sandstone 14x10x6 ins., firmly set, mkd.  $\frac{1}{4}$  on the W. face.

Set an iron post, 3 ft. long, 1 in. diam., 28 ins. in the ground, at angle point, with original corner stone buried alongside, with brass cap mkd.

## Resurvey of the E. Bdy. of T. 24 N., R. 4 E. 4354

Chains

AP  
T24N  
R4E R5E  
S 13 | S 18

1945 from which

A pine, 14 ins. diam., bears N.50 $\frac{1}{4}$ °E., 38 lks. dist.,  
mkd. T24N R5E S18 AP BT.

A pine; 14 ins. diam., bears S.46°W., 68 lks. dist.,  
mkd. T24N R4E S13 AP BT.

N.2° 02' W., beginning new measurement.

Asc. 240 ft. over SW. slope.

15.60 Spur, slopes W. Desc. 67 ft. over NW. slope.

21.50 Gulch, course W. Asc. 200 ft. over S. slope.

28.00 Spur, slopes SW. Desc. 60 ft. over broken W. slope.

33.90 Spur, slopes NW. Desc. 30 ft.

34.79 The cor. of secs. 12 and 13, evidenced by a malpais 20x12x  
6 ins., firmly set, marked with 4 notches on S. and 2  
notches on N. edges.

Set an iron post, 3 ft. long, 2 ins. diam., 30 ins. in the  
ground, with the original corner stone buried alongside at  
the corner of secs. 12 and 13, with brass cap mkd.

T24N	T24N
S12	R5E
S13	S 18
R4E	

1947 from which

An original bearing tree:

A pine, 20 ins. diam., bears N.3 $\frac{3}{4}$ °W., 97 lks. dist.  
marks overgrown.

New bearing tree:

A pine, 24 ins. diam., bears S.27°W., 63 lks. dist.,  
mkd. T24N R4E S13 BT.

Land, mountainous.

Soil, gravelly and rocky, 3rd rate.

Timber, pine and 2nd growth.

-----  
N.2° 02' W., on the E. bdy. of sec. 12.

Over mountainous land, through heavy growth of timber.

Desc. 100 ft. over NE. slope.

3.11 The original cor. of secs. 7, 12, 13 and 18, now an angle  
point, evidenced by a sandstone 12x10x6 ins., firmly set,  
marked with 4 grooves on the S. and 2 grooves on the N.  
faces.

Set an iron post, 3 ft. long, 2 ins. diam., 28 ins. in the  
ground, at angle point, with original corner stone buried  
alongside, with brass cap mkd.

AP  
T24N  
R4E R5E  
S12 | S 18

1945 from which

Resurvey of the E. Bdy. of T. 24 N., R. 4 E.

Chains	
	<p>An original bearing tree:</p> <p>A pine, 24 ins. diam., bears N.66<math>\frac{3}{4}</math>°E., 32 lks. dist., marks overgrown. Remark this tree T24N R5E S18 AP BT.</p> <p>New bearing tree:</p> <p>A pine, 8 ins. diam., bears N.74°W., 28 lks. dist., mkd. T24N R4E S12 AP BT.</p> <p>N.2° 34' E., beginning new measurement.</p> <p>Desc. 340 ft. over NE: slope.</p>
22.50	Draw, course W., continue gradual descent 40 ft.
26.20	Wash, 10 lks. wide, course W.
36.83	<p>The <math>\frac{1}{4}</math> sec. cor. of sec. 12, evidenced by a malpais stone 16x12x6 ins., firmly set, marked <math>\frac{1}{4}</math> on W. face.</p> <p>Set an iron post, 3 ft. long, 1 in. diam., 20 ins. in the ground, with the original corner stone buried alongside and in a mound of stone to top, at <math>\frac{1}{4}</math> sec. cor. with brass cap mkd.</p> <p style="text-align: center;"> <math>\frac{1}{4}</math>                        S12                        1947      from which                 </p>
	<p>The original bearing trees:</p> <p>A juniper, 24 ins. diam., bears S.11°W., 47 lks. dist., marks overgrown.</p> <p>A pinyon, 12 ins. diam., bears N.15<math>\frac{3}{4}</math>°W., 148 lks. dist., marks overgrown.</p> <p>North, beginning new measurement.</p>
1.94	<p>The original <math>\frac{1}{4}</math> sec. cor., now an angle point, evidenced by a sandstone 16x14x6 ins., firmly set, mkd. <math>\frac{1}{4}</math> on the W. face.</p> <p>Set an iron post, 3 ft. long, 1 in. diam., 28 ins. in the ground, at angle point, with original corner stone buried alongside, with brass cap mkd.</p> <p style="text-align: center;">                     AP                      T24N                      R4E R5E                      S 12   S 7.                      1945      from which                 </p>
	<p>An original bearing tree:</p> <p>A pinon, 8 ins. diam., bears S.0<math>\frac{1}{4}</math>°W., 57 lks. dist., marks overgrown. Remark this tree T24N R5E S7 AP BT.</p> <p>New bearing tree:</p> <p>A juniper, 16 ins. diam., bears N.77<math>\frac{3}{4}</math>°W., 87 lks. dist. mkd. T24N R4E S12 AP BT.</p> <p>N.0° 21' W., beginning new measurement.</p>
3.10	Small spur, slopes W. Desc. 160 ft. over slightly rolling N. slope.
29.80	Draw, 10 lks. wide, course NW.
38.02	<p>The cor. of secs. 1 and 12, evidenced by a malpais 18x12x6 ins., firmly set, marked with 5 notches on S. and 1 notch on N. face.</p> <p>Set an iron post, 3 ft. long, 1 in. diam., 30 ins. in the</p>

## Resurvey of the E. Bdy. of T. 24 N., R. 4 E. BOOK 4354

Chains

ground, with the original corner stone buried alongside,  
at cor. of secs. 1 and 12 with brass cap mkd.

T24N	T24N
S 1	R5E
S 12	S 7
R4E	

1947

from which

A juniper, 6 ins. diam., bears S.66°W., 175 lks.  
dist., mkd. BT.

A juniper, 8 ins. diam., bears N. 77½°W., 166 lks.  
dist., mkd. T 24 N R 4 W S 1 B T.

Land, mountainous and rolling.

Soil, rocky, 3rd and 4th rate.

Timber, pine, juniper, pinon and 2nd growth.

N.0°21'W., on the E. bdy. of sec. 1.

Over slightly rolling land, through scattered timber.

1.80

The original cor. of secs. 1, 6, 7 and 12, now an angle  
point, evidenced by a sandstone 16x14x8 ins., firmly set,  
mkd. with 5 grooves on the S. and 1 groove on the N.faces.

Set an iron post, 3 ft. long, 2 ins. diam., 28 ins. in the  
ground, at angle point, with original corner stone buried  
alongside, with brass cap mkd.

AP	
T24N	
R4E	R5E
S 1	S 7

1945

from which

An original bearing tree:

A juniper, 14 ins. diam., bears S.73¼°E., 296 lks. dist.,  
marks overgrown. Remark this tree T24N R5E S7 AP BT.

New bearing tree:

A pinon, 10 ins. diam., bears N.25½°W., 317 lks. dist.,  
mkd. T24N R4E S1 AP BT.

N. 0° 30' W., beginning new measurement.

20.50

Low spur, slopes NW. Enter heavy growth of timber, bears  
E. and W. Descend slightly.

30.50

Enter light and very scattered timber, bearing E. and W.  
Desc. 50 ft. over NE. slope.

35.00

Continue over nearly level land.

38.25

Point for ¼ sec. cor. of sec. 1, at proportionate dis-  
tance, based on the 1903 resurvey record.

This point falls in roadway, bearing E. and W., and is  
not a desirable location for the establishment of a  
permanent corner monument.

38.75

Set an iron post, 3 ft. long, 1 in. diam., 28 ins. in the  
ground, for witness ¼ sec. cor. of sec. 1, with brass cap  
mkd.

¼ S 1	
WC	

1945

from which

## Resurvey of the E. Bdy. of T. 24 N., R. 4 E.

## Chains

A pine, 3 ins. diam., bears S.  $38\frac{3}{4}^{\circ}$ W., 328 lks. dist., mkd. BT.

A pine, 3 ins. diam., bears S.  $73\frac{3}{4}^{\circ}$ W., 242 lks. dist., mkd. BT.

39.63 The original  $\frac{1}{4}$  sec. cor., now an angle point, evidenced by a sandstone  $14 \times 12 \times 8$  ins., firmly set, mkd.  $\frac{1}{4}$  on the W. face, and witnessed by a mound of stone  $2\frac{1}{2}$  ft. base,  $1\frac{1}{2}$  ft. high, to the W.

Set an iron post, 3 ft. long, 1 in. diam., 28 ins. in the ground, at angle point, with original corner stone buried alongside, with brass cap mkd.

AP  
T24N  
R4E R5E  
S 1 | S 6

1945 from which

A pine, 3 ins. diam., bears S.  $62\frac{3}{4}^{\circ}$ E., 189 lks. dist., mkd. AP BT.

N.  $0^{\circ} 53'$  W., beginning new measurement.

Over slightly rolling land, through light timber.

38.19 The closing cor. of Ts. 24 N., Rs. 4 and 5 E., evidenced by the original monument, a lava stone  $12 \times 8 \times 5$  ins., above ground, firmly set, mkd. with 6 grooves on the S., E. and W. faces, and witnessed by a mound of stone 2 ft. base, 1 ft. high, to the S.

At the corner,

Set an iron post, 3 ft. long, 3 ins. diam., 28 ins. in the ground, with original corner stone buried at base, with brass cap mkd.

T25N R4E  
S 36  
S 1 | S 6  
R4E R5E

T24N  
CC  
1945

$3\frac{1}{2}$  ft. base,  $2\frac{1}{2}$  ft. high, S. of cor. raise a mound of stone,

From the corner:

The standard cor. of Ts. 25 N., Rs. 4 and 5 E., bears S.  $89^{\circ} 31'$  E., 15.35 chs. dist.

The standard cor. of secs. 35 and 36, T. 25 N., R. 4 E. bears N.  $89^{\circ} 50'$  W., 66.18 chs. dist., evidenced by a sandstone  $6 \times 6 \times 5$  ins. above ground, firmly set, marked with 1 groove on the E. and 5 grooves on the W. faces, and witnessed by a mound of stone 3 ft. base, 1 ft. high to the N. An original bearing tree:

A juniper, 14 ins. diam., bears N.  $20\frac{3}{4}^{\circ}$ W., 249 lks. dist. mkd. SC T25N R4E S35 BT.

Land, slightly rolling and level.

Soil, gravelly and rocky clay, 3rd rate.

Timber, pine, piñon and juniper in south half mile, lightly scattered pine in the N.  $\frac{1}{2}$  mile.

No undergrowth.

-----

## Resurvey of the Subdivision of T. 24 N., R. 5 E.

## Chains

Reestablishment of the survey executed by F. W. Oury, Deputy Surveyor, and C. E. Perkins, Compassman and Deputy Surveyor, in 1894.

From the cor. of secs. 1, 2, 35 and 36 on the S. bdy. of the Tp. as evidenced by an iron post, 2 ins. diam., firmly set, mkd. and witnessed, as described in the field notes of the N. bdy. of T. 23 N., R. 5 E., resurveyed under this group.

N.  $0^{\circ} 58'$  W.; bet. secs. 35 and 36.

Over mountainous land, through heavy timber and dense undergrowth.

Ascend 135 ft. over a SE. slope.

5.40 Slope changes; asc. 22 ft. along an E. slope.

14.40 Top of ridge (main divide), bears E. and W.; descend 58 ft. along a steep E. slope.

22.20 Slope changes; desc. 485 ft. over a NE. slope.

40.44 Proportional distance.

Set an iron post, 3 ft. long, 1 in. diam., 12 ins. in a crevice between two large boulders, and in a mound of stone to top, at  $\frac{1}{4}$  sec. cor., with brass cap mkd.

S35 | S36

1945

from which

A fir, 10 ins. diam., bears S.  $48\frac{1}{2}^{\circ}$  E., 18 lks. dist., mkd.  $\frac{1}{4}$  S 36 B T.

A fir, 5 ins. diam., bears N.  $86^{\circ}$  W., 65 lks. dist., mkd.  $\frac{1}{4}$  S 35 B T.

Desc. 36 ft. over a NE. slope.

Leave heavy timber and undergrowth; enter slide rock, bears NE. and SW.

41.70 Ravine, course NE.; continue descent 110 ft. over a NE. slope.

43.90 Leave rock slide; enter heavy timber and undergrowth, bears NE. and SW.

59.90 Side hill drain, course E.; asc. 40 ft. along an E. slope.

65.30 Spur, slopes E.; desc. 315 ft. over a NE. slope.

79.45 Drain, course N.  $60^{\circ}$  E.; desc. gradually along an E. slope.

80.88 The cor. of secs. 25, 26, 35 and 36, as evidenced by a lava stone, 16x12x10 ins., firmly set in the ground, mkd. 1 groove on E. and 1 groove on S. faces; mound of stone, 3 ft. base, 2 ft. high, W. of cor.


Set an iron post, 3 ft. long, 2 ins. diam., 28 ins. in the ground, with the old corner stone buried alongside, at

BOOK 4354

Resurvey of the Subdivision of T. 24 N., R. 5 E.

Chains

cor. of secs. 25, 26, 35 and 36, with brass cap mkd.



from which

Old bearing trees:

A pine, 30 ins. diam., bears N. 56° E., 29 lks. dist., markings overgrown, not uncovered, mark on overgrowth, T 24 N R 5 E S 25 B T.

A pine, 28 ins. diam., bears S. 30 1/2° E., 104 lks. dist., markings overgrown, not uncovered, mark on overgrowth, T 24 N R 5 E S 36 B T.

A pine, 24 ins. diam., bears S. 8 1/2° W., 48 lks. dist., mkd. T 24 N R 5 E S 35 B T.

A pine, 16 ins. diam., bears N. 49 1/2° W., 83 lks. dist., markings overgrown, not uncovered, mark on overgrowth, T 24 N R 5 E S 26 B T.

Land, mountainous.

Soil, rocky 3rd and 4th rates.

Timber, Fir, pine and aspen; undergrowth, 2nd growth timber, maple, mountain willow and cherry.

From the cor. of secs. 25, 30, 31 and 36 on the E. bdy. of the Tp., as evidenced by an iron post, 2 ins. diam., firmly set, mkd. and witnessed as described in the field notes of the W. bdy. of T. 24 N., R. 6 E., resurveyed under this group.

N. 89° 06' W.; bet. secs. 25 and 36.


Over rolling land, through heavy timber and undergrowth

Along a gentle N. slope.

32.00 Shallow draw, drains N.; continue along a N. slope.

39.80 The 1/4 sec. cor., as evidenced by a lava stone, 16x10x8 ins., firmly set in the ground; mkd. 1/4 on N. face,

Set an iron post, 3 ft. long, 1 in. diam., 27 ins. in the ground, with the old corner stone buried alongside, at 1/4 sec. cor., with brass cap mkd.



1945.

from which

Old bearing trees:

A pine, 16 ins. diam., bears N. 52° E., 27 lks. dist., markings overgrown, not uncovered, mark on overgrowth 1/4 S 25 B T.

A pine, 18 ins. diam., bears S. 24 1/2° E., 31 lks. dist., markings overgrown, not uncovered, mark on overgrowth, 1/4 S 36 B T.

Resurvey of the Subdivision of T. 24 N., R. 5 E.

4354

Chains	
	Center of an earthen reservoir, bears S. 13° 16' E., 25.57 chains dist. (This tie computed from a traverse)
	Thence,
	N. 89° 43' W., bet. secs. 25 and 36.
	Along a gentle N. slope.
3.20	U. S. Forest Service telephone line, (one wire), bears S. and NW. to Slate Mountain Lookout Station.
10.50	Road, bears SE. and NW. to Bull Basin.
11.00	Slope changes; asc. 46 ft. over a NE. slope.
20.30	Low spur, slopes N. 20° E.; thence, along a gentle N. slope.
25.20	Drain, course N.; asc. 45 ft. over a NE. slope.
33.30	Drain, course NE.; asc. 34 ft. over a NE. slope.
36.00	Leave rolling, enter mountainous land, bears SE. and N.; asc. 49 ft. over an E. slope.
39.74	The cor. of secs. 25, 26, 35 and 36.
	Land, rolling. Soil, rocky, 2nd and 3rd rates. Timber, pine; undergrowth, 2nd growth pine.
	-----
	N. 0° 40' W., bet. secs. 25 and 26.
	Over mountainous land, through heavy timber and scattered undergrowth.
	Ascend 30 ft. along an E. slope.
4.50	Spur, slopes NE.; desc. 183 ft. over a N. slope.
14.00	Enter dense 2nd growth pine. bears E. and W.
18.00	Enter rolling land, bears E. and W.; desc. 136 ft. over a gradual N. slope.
39.86	The 1/4 sec. cor., as evidenced by a sandstone, 20x14x6 ins. firmly set in the ground, mkd. 1/4 on W. face.
	Set an iron post, 3 ft. long, 1 in. diam., 28 ins. in the ground, with the old corner stone buried alongside, at 1/4 sec. cor., with brass cap mkd.
	$\begin{array}{c} \frac{1}{4} \\ \text{S } 26 \mid \text{S } 25 \\ \hline 1945 \end{array}$
	from which
	Old bearing trees:
	. A pine, 24 ins. diam., bears N. 45° E., 11 lks. dist., markings overgrown, not uncovered, mark on overgrowth, 1/4 S 25 B T.
	The original position of a pine, 12 ins. diam. (now dead lying on ground), bears N. 26° W., 48 lks. dist., mkd. 1/4 S B T.

4354 Resurvey of the Subdivision of T. 24 N., R. 5 E.

Chains

New bearing tree:

A pine, 11 ins. diam., bears N. 61½° W., 82 lks. dist., mkd. ½ S 26 B T.

A U. S. G. S. bench mark, bears S. 42° 13' E., 19.63 chains dist. (bearing and distance computed from a traverse). This bench mark is evidenced by a brass tablet, 3½ ins. diam., seated in a lava stone in place, 36x30 ins., 8 ins. above ground, mkd.

ELEVATION  
ABOVE SEA  
7843 FEET  
DATUM  
1907  
BM

Thence,

N. 0° 22' E., bet. secs. 25 and 26.

Descend 139 ft. over a gradual N. slope.

10.40 U. S. Forest Service telephone line, bears SE. and NW. to Slate Mountain Lookout Station.

14.65 Road, bears SE. and NW. to Bull Basin.

40.03 The cor. of secs. 23, 24, 25 and 26, as evidenced by a lava stone, 16x14x6 ins., firmly set in the ground, mkd. 2 notches on S. and 1 notch on E. edges.

Set an iron post, 3 ft. long, 2 ins. diam., 28 ins. in the ground, with the old corner stone, buried alongside, at cor. of secs. 23, 24, 25 and 26, with brass cap mkd.

T24N R5E  
S23 | S24  
S26 | S25  
1945

from which

Old bearing trees:

A pine stump, 24 ins. diam., bears S. 49° E., 38 lks. dist., mkd. T 24 N R 5 E S 25 B T.

A pine, 30 ins. diam., bears N. 25½° W., 18 lks. dist., markings overgrown, not uncovered, mark on overgrowth T 24 N R 5 E S 23 B T.

New bearing trees:

A pine, 4 ins. diam., bears N. 15° E., 84 lks. dist., mkd. T 24 N R 5 E S 24 B T.

A pine, 6 ins. diam., bears S. 43½° E., 28 lks. dist., mkd. T 24 N R 5 E S 25 B T.

A pine, 6 ins. diam., bears S. 23½° W., 106 lks. dist., mkd. T 24 N R 5 E S 26 B T.

Land, S. 18.00 chains, mountainous; N. 22.00 chains, rolling.

Soil, rocky, 2nd and 3rd rates.

Timber, pine and fir; undergrowth, 2nd growth timber.

Resurvey of the Subdivision of T. 24 N., R. 5 E.

Chains

From the cor. of secs. 19, 24, 25 and 30, on the E. bdy. of the Tp., as evidenced by an iron post, 3 ft. long, 2 ins. diam., firmly set, mkd. and witnessed as described in the field notes of the W. bdy. of T. 24 N., R. 6 E., resurveyed under this group.

S. 87° 17' W., bet. secs. 24 and 25.

Over rolling land, through heavy timber and dense undergrowth.

Along a gentle N. slope.

22.50 Drain, 10 lks. wide, 5 ft. deep, course N.; asc. 12 ft. over an E. slope.

28.00 Graded road, bears S. 25° E. to Flagstaff and N. 25° W. to Bull Basin.

33.00 Low spur, slopes N. 10° E., Thence, along a gentle N. slope.

39.91 The 1/4 sec. cor., as evidenced by a lava stone, 16x10x6 ins., firmly set in the ground, mkd. 1/4 on N. face. A mound of stone, 2 ft. base, 1 ft. high, W. of cor.

Set an iron post, 3 ft. long, 1 in. diam., 28 ins. in the ground, with the old corner stone buried alongside, at 1/4 sec. cor., with brass cap mkd.

S24  
1/4  
S25  
1945

from which

A pine, 6 ins. diam., bears N. 17° E., 9 lks. dist., mkd. 1/4 S 24 B T.

A pine, 4 ins. diam., bears S. 65 1/4° W., 21 lks. dist., mkd. 1/4 S 25 B T.

Thence,

N. 87° 13' W., bet. secs. 24 and 25.

Along a gentle N. slope.

7.50 Low spur, slopes N.; desc. 96 ft. over a NW. slope.

38.10 Drain, 10 lks. wide, 3 ft. deep, course N.; along a gentle N. slope.

39.60 The cor. of secs. 23, 24, 25 and 26.

Land, rolling.

Soil, rocky, 2nd and 3rd rates.

Timber, pine; undergrowth, 2nd growth pine.

N. 0° 17' E., bet. secs. 23 and 24.

Over rolling land, through heavy timber and scattered undergrowth.

Descend 48 ft. over a gradual N. slope.

10.80 Road, bears E. and W.

Resurvey of the Subdivision of T. 24 N., R. 5 E.

Chains


20.65 Drain, course N. 30° W.; continue gradual descent over a NW. slope.

30.00 Enter dense 2nd growth pine, bears E. and W.

35.20 U. S. Forest Service telephone line and 4 wire drift fence, bears E. and W..

39.92 The 1/4 sec. cor., as evidenced by a lava stone, 18x10x5 ins., firmly set in the ground, mkd. 1/4 on W. face.

Set an iron post, 3 ft. long, 1 in. diam., 28 ins. in the ground, with the old corner stone buried alongside, at 1/4 sec. cor., with brass cap mkd.



from which

Old bearing tree:

A pine stump, 24 ins. diam., bears S. 81° W., 24 lks. dist., mkd. 1/4 S B T.

New bearing trees:

A pine, 5 ins. diam., bears S. 83 1/2° E., 52 lks. dist., mkd. 1/4 S 24 B T.

A pine, 6 ins. diam., bears WEST, 21 lks. dist., mkd. 1/4 S 23 B T.

Thence,


N. 0° 16' E., bet. secs. 23 and 24.

Descend 57 ft. over a gradual N. slope.

38.05 Truck trail, bears SE. and NW.

39.85 The cor. of secs. 13, 14, 23 and 24, as evidenced by a lava stone, 16x10x6 ins., firmly set in the ground, mkd. 3 grooves on S. and 1 groove on E. faces, with a mound of stone, 2 ft. base, 1 ft. high, W. of cor.

Set an iron post, 3 ft. long, 2 ins. diam., 28 ins. in the ground, with the old corner stone buried alongside, at cor. of secs. 13, 14, 23 and 24, with brass cap mkd.



from which

A pine, 6 ins. diam., bears N. 76 1/2° E., 16 lks. dist., mkd. T 24 N R 5 E S 13 B T.

A pine, 6 ins. diam., bears S. 42 3/4° E., 52 lks. dist., mkd. T 24 N R 5 E S 24 B T.

A pine, 5 ins. diam., bears S. 16 3/4° W., 54 lks. dist., mkd. T 24 N R 5 E S 23 B T.

A pine, 5 ins. diam., bears N. 67 1/2° W., 35 lks. dist., mkd. T 24 N R 5 E S 14 B T.

## Resurvey of the Subdivision of T. 24 N., R. 5 E.

4354

Chains	
	Land, rolling. Soil, rocky, 2nd and 3rd rates. Timber, pine; undergrowth, 2nd growth pine.
	-----
	From the cor. of secs. 13, 18, 19 and 24 on the E. bdy. of the Tp., as evidenced by an iron post, 2 ins. diam., firmly set, mkd. and witnessed as described in the field notes of the W. bdy. of T. 24 N., R. 6 E., resurveyed under this group.
	S. 89° 58' W., bet. secs. 13 and 24. Over rolling land, through heavy timber and dense undergrowth.
	Along a gentle N. slope.
15.00	Wash, 8 lks. wide, 4 ft. deep, course NE. from S.; asc. over a gradual NE. slope.
25.00	Low, wide spur, slopes N.
39.98	The $\frac{1}{4}$ sec. cor., as evidenced by a lava stone, 16x10x8 ins. firmly set in the ground, mkd. $\frac{1}{4}$ on N. face, with a mound of stone, 2 ft. base, 1 ft. high, N. of cor. Set an iron post, 3 ft. long, 1 in. diam., 27 ins. in the ground, with the old corner stone buried alongside, at $\frac{1}{4}$ sec. cor., with brass cap mkd.
	S13
	S24
	1945
	from which
	Old bearing trees:
	A pine, 24 ins. diam., (partly dead), bears N. 74 $\frac{1}{2}$ ° W., 52 lks. dist., markings overgrown, not uncovered.
	A pine, 18 ins. diam., (partly dead), bears S. 79° W., 75 lks. dist., markings overgrown, not uncovered.
	New bearing trees:
	A pine, 5 ins. diam., bears N. 23 $\frac{1}{2}$ ° E., 59 lks. dist., mkd. $\frac{1}{4}$ S 13 B T.
	A pine, 5 ins. diam., bears S. 24 $\frac{3}{4}$ ° W., 7 lks. dist., mkd. $\frac{1}{4}$ S 24 B T.
	Thence,
	S. 89° 49' W., bet. secs. 13 and 24.
	Descend gradually along a gentle N. slope.
11.70	Wash, 15 lks. wide, 5 ft. deep, course N. 20° E.
13.20	Wash, 15 lks. wide, course NE.; continue along a gentle N. slope.
40.04	The cor. of secs. 13, 14, 23 and 24. Land, rolling. Soil, rocky, 2nd and 3rd rates. Timber, pine; undergrowth, 2nd growth pine.
	-----

BOOK 4354

Resurvey of the Subdivision of T. 24 N., R. 5 E.

Chains


N. 2° 09' E., bet. secs. 13 and 14.

Over nearly level land, through heavy timber and dense undergrowth.

15.40 Junction of truck trails, which bear NE., SW. and S. 15° W. Leave heavy timber, enter scattered timber, bears E. and W.

39.02 The  $\frac{1}{4}$  sec. cor., as evidenced by a lava stone, 11x6x6 ins., firmly set in the ground, mkd.  $\frac{1}{4}$  on W. face, with a mound of stone, 2 ft. base, 1 ft. high, W. of cor.

Set an iron post, 3 ft. long, 1 in. diam., 27 ins. in the ground, with the old corner stone buried alongside, at  $\frac{1}{4}$  sec. cor., with brass cap mkd.



from which

A pine, 7 ins. diam., bears N. 48° E., 160 lks. dist., mkd.  $\frac{1}{4}$  S 13 B T.

A pine, 5 ins. diam., bears N. 81 $\frac{1}{2}$ ° W., 189 lks. dist., mkd.  $\frac{1}{4}$  S 14 B T.

Thence,


NORTH, bet. secs. 13 and 14.

Over nearly level land, through scattered timber and undergrowth.

22.50 Enter open grassy land, bears E. and W.

40.00 The cor. of secs. 11, 12, 13 and 14, as evidenced by a lava stone, 16x8x4 ins., firmly set in the ground, mkd. 4 grooves on S. and 1 groove on E. faces, with a mound of stone, 2 ft. base, 1 ft. high, W. of cor.

Set an iron post, 3 ft. long, 2 ins. diam., 28 ins. in the ground, with the old corner stone buried alongside, at cor. of secs. 11, 12, 13 and 14, with brass cap mkd.



from which

A pine, 3 ins. diam., bears N. 59° E., 257 lks. dist., mkd B T.

A pine, 3 ins. diam., bears S. 74 $\frac{1}{2}$ ° E., 274 lks. dist., mkd. B T.

A pine, 3 ins. diam., bears S. 63 $\frac{1}{4}$ ° W., 105 lks. dist., mkd. B T.

A pine, 3 ins. diam., bears N. 83 $\frac{1}{4}$ ° W., 156 lks. dist., mkd. B T.

Rebuild mound of stone, 2 ft. base, 1 $\frac{1}{2}$  ft. high, W. of cor.

## Resurvey of the Subdivision of T. 24 N., R. 5 E.

4354

## Chains

Land, nearly level.  
Soil, rocky, 2nd and 3rd rates.  
Timber, pine; undergrowth, 2nd growth pine.

-----  
From the cor. of secs. 7, 12, 13 and 18, on the E. bdy. of the Tp., as evidenced by an iron post, 2 ins. diam., firmly set, mkd. and witnessed as described in the field notes of the W. bdy. of T. 24 N., R. 6 E., resurveyed under this group.

N. 89° 56' W., bet. secs. 12 and 13.

Over nearly level land, through scattered timber.

30.00 Leave level land, enter rolling land, bears N. and S.

40.01 The  $\frac{1}{4}$  sec. cor.; as evidenced by a lava stone, 18x14x12 ins., firmly set in the ground, mkd.  $\frac{1}{4}$  on N. face, with a mound of stone, 2 ft. base, 1 ft. high, N. of cor.

Set an iron post, 3 ft. long, 1 in. diam., 10 ins. in the ground to solid rock, with the old corner stone buried alongside, and in a mound of stone to top, at  $\frac{1}{4}$  sec. cor. with brass cap mkd.

S12

$\frac{1}{4}$   
S13  
1945

from which

Old bearing tree:

A pine, 24 ins. diam., (partly dead), bears S. 84 $\frac{1}{2}$ ° E. 62 lks. dist., markings overgrown, not uncovered.

New bearing trees:

A pine, 10 ins. diam., bears N. 29 $\frac{1}{4}$ ° E., 72 lks. dist., mkd.  $\frac{1}{4}$  S 12 B T.

A pine, 7 ins. diam., bears S. 63° E., 33 lks. dist., mkd.  $\frac{1}{4}$  S 13 B T.

Thence,

S. 88° 18' W., bet. secs. 12 and 13.

5.50 Leave timber, enter open grassy land.

9.00 Enter nearly level land.

38.81 The cor. of secs. 11, 12, 13 and 14.

Land, W. 30 chs. and E. 30 chs. nearly level; remainder of mile rolling.

Soil, rocky, 2nd and 3rd rates.  
Timber, pine; undergrowth, none.

-----  
N. 0° 04' E., bet. secs. 11 and 12.


Over nearly level, open, grassy land.

39.98 The  $\frac{1}{4}$  sec. cor., as evidenced by a lava stone, 16x14x5 ins., firmly set in the ground, mkd.  $\frac{1}{4}$  on W. face.

Resurvey of the Subdivision of T. 24 N., R. 5 E.

Chains

Set an iron post, 3 ft. long; 1 in. diam., 28 ins. in the ground, with the old corner stone buried alongside, at  $\frac{1}{4}$  sec. cor., with brass cap mkd.



raise a mound of stone, 3 ft. base, 2 ft. high, W. of cor.

Thence,

N. 0° 02' W., bet. secs. 11 and 12.


Continue over nearly level land.

15.00 Enter scattered timber, bears E. and W.

18.90 Road, bears W. to Slate Mountain Lookout Station and E. to junction with Flagstaff-Grand Canyon road.

39.97 The cor. of secs. 1, 2, 11 and 12, as evidenced by a malpais stone, 20x16x6 ins., firmly set in the ground, mkd. 5 grooves on S. and 1 groove on E. faces, with a mound of stone, 2 ft. base, 1 ft. high, W. of cor.

Set an iron post, 3 ft. long, 2 ins. diam., 28 ins. in the ground, with the old corner stone buried alongside, at cor. of secs. 1, 2, 11 and 12, with brass cap mkd.



from which

A pine, 3 ins. diam., bears N. 17° E., 116 lks. dist., mkd. B.T.

A pine, 6 ins. diam., bears S. 79½° E., 367 lks. dist., mkd. T 24 N R 5 E S 12 B.T.

A pine, 5 ins. diam., bears S. 53½° W., 542 lks. dist., mkd. T 24 N R 5 E S 11 B.T.

A juniper, 10 ins. diam., bears N. 41¼° W., 119 lks. dist., mkd. T 24 N R 5 E S 2 B.T.

Land, nearly level.

Soil, rocky, 2nd and 3rd rates.

Timber, pine; undergrowth, none.

From the cor. of secs. 1, 6, 7 and 12, on the E. bdy. of the Tp., as evidenced by an iron post, 2 ins. diam., set, mkd. and witnessed as described in the field notes of the W. bdy. of T. 24 N., R. 6 E., resurveyed under this group.

WEST, bet. secs. 1 and 12.

Over rolling, open, grassy land.

Descend gradually along a gentle S. slope.

## Resurvey of the Subdivision of T. 24 N., R. 5 E.

BOOK 4354

Chains	
8.20	A four wire drift fence, bears N. and S.; enter scattered timber and undergrowth, bears N. and S.
20.70	Road, bears N. 60° W. to Slate Mountain Lookout Station and S. 60° E. to junction with the Grand Canyon-Flagstaff road.
25.00	Foot of descent, bears N. and S.; asc. 45 ft. over E. slope.
33.00	Point of a low bench, extends N.; desc. 8 ft. along a gentle N. slope.
37.80	Recross road, bears NE. and SW.
38.50	Draw, drains NE.; asc. gradual SE. slope.
40.04	The $\frac{1}{4}$ sec. cor., as evidenced by a lava stone, 18x8x5 ins. firmly set in the ground, mkd. $\frac{1}{4}$ on N. face, with a mound of stone, 3 ft. base, 1 ft. high, N. of cor.  Set an iron post, 3 ft. long, 1 in. diam., 27 ins. in the ground, with the old corner stone buried alongside, at $\frac{1}{4}$ sec. cor., with brass cap mkd.  <div style="text-align: center;"> <math display="block">\begin{array}{r} S\ 1 \\ \hline \frac{1}{4} \\ S\ 12 \\ 1945 \end{array}</math> </div> from which  A pine, 4 ins. diam., bears N. 2 $\frac{1}{2}$ ° E., 229 lks. dist., mkd. $\frac{1}{4}$ S 1 B T.  A pine, 5 ins. diam., bears S. 16 $\frac{1}{4}$ ° E., 308 lks. dist., mkd. $\frac{1}{4}$ S 12 B T. Thence,  S. 88° 20' W., bet. secs. 1 and 12.  Ascend 28 ft. over an E. slope.
10.00	Top of ascent, bears N. and S.; over nearly level land.
38.81	The cor. of secs. 1, 2, 11 and 12. Land, E. 50.00 chs. rolling; W. 30.00 chs. nearly level. Soil, rocky, 2nd and 3rd rates. Timber, pine; undergrowth, 2nd growth pine. ----- N. 0° 33' W., bet. secs. 1 and 2.  Over rolling, open, grassy land; asc. gradual SE. slope.
1.70	Enter heavy timber and dense undergrowth, bears NE. and W.; top of ascent; desc. 52 ft. over a NW. slope.
11.00	Center of an earthen reservoir, 2 chs. diam., bears W., 6.00 chs. dist.
15.80	Draw, 1.00 ch. wide, drains NE.; thence, along a gentle E. slope.
40.08	The $\frac{1}{4}$ sec. cor., determined from the old bearing trees.  Set an iron post, 3 ft. long, 1 in. diam., 28 ins. in the ground, at $\frac{1}{4}$ sec. cor., with brass cap mkd.  <div style="text-align: center;"> <math display="block">\begin{array}{r} \frac{1}{4} \\ S\ 2\ S\ 1 \\ \hline 1945 \end{array}</math> </div> from which

## Resurvey of the Subdivision of T. 24 N., R. 5 E.

## Chains

## Old bearing trees:

A pine, 40 ins. diam., bears N.  $71^{\circ}$  E., 36 lks.  
dist., mkd.  $\frac{1}{4}$  S B T.

A pine stump, 18 ins. diam., S.  $15\frac{1}{4}^{\circ}$  W., 146 lks.  
dist., mkd.  $\frac{1}{4}$  S B T.

## New bearing trees:

A pine, 4 ins. diam., bears S.  $27^{\circ}$  E., 174 lks.  
dist., mkd.  $\frac{1}{4}$  S 1 B T.

A pine, 4 ins. diam., bears S.  $36\frac{1}{2}^{\circ}$  W., 108 lks,  
dist., mkd.  $\frac{1}{4}$  S 2 B T.

Corner is located in grassy draw, drains SE.

Thence,

N.  $0^{\circ} 17'$  E., bet. secs. 1 and 2.

Ascend gradual SW. slope.

7.50 East end of a low saddle in spur, slopes NE.; descend gradually along a W. slope.

20.15 Wash, 5 lks. wide, course NE.; asc. gradually along E. slope.

21.84 Intersect Sixth Standard Parallel North.

Set an iron post, 3 ft. long, 2 ins. diam., 28 ins. in the ground, at closing corner of secs. 1 and 2, with brass cap mkd.

T25N R5E  
S35  
-----  
S 2 | S 1  
T24N R5E  
C C  
1945

from which

The old bearing trees of the original closing corner:

A pine, 20 ins. diam., bears S.  $64\frac{1}{2}^{\circ}$  E., 63 lks.  
dist., mkd. T 24 N R 5 E S 1 B T. Additionally mark  
on overgrowth T 24 N R 5 E S 1 C C B T.

A pine, 10 ins. diam., bears S.  $78\frac{3}{4}^{\circ}$  W., 38 lks.  
dist., mkd. T 24 N R 5 E S 2 B T. Additionally mark  
on overgrowth T 24 N R 5 E S 2 C C B T.

From the closing corner, the standard  $\frac{1}{4}$  sec. cor., S. bdy.  
sec. 35, T. 25 N., R. 5 E., bears N.  $89^{\circ} 27'$  W., 11.31  
chs. dist.

Continue on blank line in sec. 35.

0.20 The original closing corner of secs. 1 and 2, as evidenced by a sandstone, 14x14x6 ins., firmly set in the ground, mkd. 1 groove on E., 5 grooves on W. and C C on S. faces, with faint evidence of pits on line E., W. and S., 3 ft. dist. Additionally mark this cor. stone W P on S. face. From this witness point,

Old bearing trees:

A pine, 16 ins. diam., bears N.  $8\frac{3}{4}^{\circ}$  E., 48 lks.  
dist., mkd. T 24 N R 5 E C C S 1-2 B T.

A pine, described above, bears S.  $50\frac{1}{4}^{\circ}$  E., 74 lks.  
dist.

## Resurvey of the Subdivision of T. 24 N., R. 5 E.

## Chains

A pine, described above, bears S.  $53\frac{1}{4}^{\circ}$  W., 46 lks. dist.

Land, rolling.

Soil, rocky, 2nd and 3rd rates.

Timber, pine; undergrowth, 2nd growth pine.

-----  
At midpoint on the N. bdy. of sec. 1.

Set an iron post, 3 ft. long, 1 in. diam., 28 ins. in the ground, at  $\frac{1}{4}$  sec. cor. of sec. 1, with brass cap mkd.

-----  
 $\frac{1}{4}$  S 1  
1945

from which

A pine, 4 ins. diam., bears S.  $14\frac{1}{2}^{\circ}$  E., 54 lks. dist., mkd.  $\frac{1}{4}$  S 1 B T.

A pine, 4 ins. diam., bears S.  $53\frac{3}{4}^{\circ}$  W., 55 lks. dist., mkd.  $\frac{1}{4}$  S 1 B T.

From this corner, the standard cor. of secs. 35 and 36, T. 25 N., R. 5 E., bears S.  $89^{\circ} 54'$  W., 11.11 $\sqrt{}$  chs. dist.

-----  
From the cor. of secs. 2, 3, 34 and 35 on the S. bdy of the Tp., as evidenced by an iron post, 2 ins. diam., firmly set, mkd. and witnessed as described in the field notes of the N. bdy. of T. 23 N., R. 5 E., resurveyed under this group.

N.  $2^{\circ} 14'$  W., bet. secs. 34 and 35.

Over mountainous land, through heavy timber and undergrowth.

Descend gradually over a NW. slope.

7.15 Top of a cliff, 50 ft. high, faces N.; desc. 549 ft. over a NW. slope.

20.90 Gulch, near head, course NW.; continue descent.

30.30 Enter dense aspen timber, bears E. and W.

37.60 Slope changes; desc. along a W. slope.

40.19 Proportional distance.

Set an iron post, 3 ft. long, 1 in. diam., 28 ins. in the ground, at  $\frac{1}{4}$  sec. cor., with brass cap mkd.

$\frac{1}{4}$   
S34 | S35  
1945

from which

A pine, 8 ins. diam., bears S.  $50^{\circ}$  E., 52 lks. dist., mkd.  $\frac{1}{4}$  S 35 B T.

A pine, 8 ins. diam., bears S.  $28\frac{1}{2}^{\circ}$  W., 20 lks. dist., mkd.  $\frac{1}{4}$  S 34 B T.

Descend gradual NW. slope.

41.30 Enter open park, bears E. and W.

BOOK 4354

## Resurvey of the Subdivision of T. 24 N., R. 5 E.

Chains  
 42.50 Foot of descent; asc. gradual SW. slope.  
 43.10 Leave open park, bears E. and W.; enter dense aspen timber.  
 47.00 Long spur, slopes NW.; descend 590 ft. over a NE. slope, through dense aspen timber.  
 75.00 Leave aspen timber, bears E. and W.  
 78.92 Trail, bears NW. and SE.  
 79.00 Gulch, near head, course NW.; asc. 26 ft. over a S. slope.  
 80.38 At this point, determined by the method of double proportion.  
 Set an iron post, 3 ft. long, 2 ins. diam., 28 ins. in the ground, at cor. of secs. 26, 27, 34 and 35, with brass cap mkd.

T24N	R5E
S27	S26
S34	S35
1945	

from which

A pine, 8 ins. diam., bears N.  $76\frac{1}{4}^{\circ}$  E., 67 lks. dist., mkd. T 24 N R 5 E S 26 B T.

A pine, 14 ins. diam., bears S.  $86\frac{1}{2}^{\circ}$  E., 55 lks. dist., mkd. T 24 N R 5 E S 35 B T.

A pine, 5 ins. diam., bears S.  $87^{\circ}$  W., 10 lks. dist., mkd. T 24 N R 5 E S 34 B T.

A pine, 14 ins. diam. bears N.  $27\frac{1}{2}^{\circ}$  W., 53 lks. dist., mkd. T 24 N R 5 E S 27 B T.

Land, mountainous.

Soil, rocky, 2nd and 3rd rates.

Timber, aspen, pine and fir; undergrowth, 2nd growth timber:

-----  
 From the cor. of secs. 25, 26, 35 and 36.

S.  $88^{\circ} 50'$  W., bet. secs. 26 and 35.

Over mountainous land, through heavy timber and dense undergrowth.

Ascend 103 ft. over an E. slope.

5.00 Spur, slopes NE.; continue ascent 119 ft. over a NE. slope.

19.30 Spur, slopes N.; desc. 95 ft. over a W. slope.

26.80 Ravine, course N.; asc. 183 ft. over a NE. slope.

40.18 Proportional distance.

Set an iron post, 3 ft. long, 1 in. diam., 28 ins. in the ground, at  $\frac{1}{4}$  sec. cor., with brass cap mkd.

S26
$\frac{1}{4}$
S35
1945

from which

## Resurvey of the Subdivision of T. 24 N., R. 5 E.

Chains	A pine, 6 ins. diam., bears N. 5° W., 27 lks. dist., mkd. $\frac{1}{4}$ S 26 B T.
	A pine, 8 ins. diam., bears S. 71° E., 9 lks. dist., mkd. $\frac{1}{4}$ S 35 B T.
	Ascend 575 ft. over a NE. slope.
63.70	Top of high, long spur, slopes NW.; desc. 49 ft. along a S. slope.
80.36	The cor. of secs. 26, 27, 34 and 35. Land, mountainous. Soil, rocky, 2nd and 3rd rates. Timber, pine and fir; undergrowth, 2nd growth timber.
	N. 0° 05' E., bet. secs. 26 and 27. Over mountainous land, through heavy timber and under- growth. Ascend 30 ft. over a S. slope.
1.65	Short spur, slopes SW.; desc. 231 ft. along a W. slope.
4.92	Dim trail, bears N. 20° W. and S. 20° E.
20.90	Long spur, slopes N. 20° W.; desc. 399 ft. over a NE. slope.
40.16	Proportional distance. Set an iron post, 3 ft. long, 1 in. diam., 28 ins. in the ground, at $\frac{1}{4}$ sec. cor., with brass cap mkd.
	$\frac{1}{4}$ S27   S26 1945 from which
	A fir, 6 ins. diam., bears S. 30 $\frac{3}{4}$ ° E., 26 lks. dist., mkd. $\frac{1}{4}$ S 26 B T.
	A pine, 5 ins. diam., bears S. 32° W., 19 lks. dist., mkd. $\frac{1}{4}$ S 27 B T.
	Descend 517 ft. over a NE. slope.
56.80	Wash, 10 lks. wide, course NW.
60.10	Point of a low spur, slopes NW.
62.50	Recross wash, 10 lks. wide, course NE.
65.30	Point of a low spur, slopes E.; desc. 130 ft. over a NE. slope.
80.32	The cor. of secs. 22, 23, 26 and 27, as evidenced by a sandstone 20x12x6 ins., firmly set in the ground, mkd. with 2 grooves on E. and 2 grooves on S. faces. Set an iron post, 3 ft. long, 2 ins. diam., 28 ins. in the ground, with the old corner stone buried alongside, at cor. of secs. 22, 23, 26 and 27, with brass cap mkd.
	T24N R5E S22   S23 S27   S26 1945 from which
	Old bearing trees: A pine stump 20 ins. diam., 3 ft. high, bears N. 25 $\frac{1}{4}$ ° E., 83 lks. dist., mkd. T24N R 5 E S 23 B T. A pine, 20 ins. diam., bears S. 18 $\frac{1}{4}$ ° E., 48 lks. dist., mkd. T 24 N R 5 E S 26 B T.

## Resurvey of the Subdivision of T. 24 N., R. 5 E.

Chains	New bearing trees:
	A pine, 6 ins. diam., bears N. $19\frac{1}{2}^{\circ}$ E., 35 lks. dist., mkd. T 24 N R 5 E S 23 B T.
	A pine, 8 ins. diam., bears S. $52\frac{1}{4}^{\circ}$ E., 23 lks. dist., mkd. T 24 N R 5 E S 26 B T.
	A pine, 8 ins. diam., bears S. $10\frac{1}{4}^{\circ}$ W., 120 lks. dist., mkd. T 24 N R 5 E S 27 B T.
	A pine, 6 ins. diam., bears N. $62^{\circ}$ W., 63 lks. dist., mkd. T 24 N R 5 E S 22 B T.
	Land, mountainous. Soil, rocky, 2nd and 3rd rates. Timber, pine and fir; undergrowth, 2nd growth timber.
	----- From the cor. of secs. 23, 24, 25 and 26. S. $88^{\circ} 53'$ W., bet. secs. 23 and 26. Over rolling land, through heavy timber and dense undergrowth. Along a gentle N. slope.
12.40	Road, bears N. and S.
17.20	Road, bears SE. and NW. to Bull Basin.
32.10	U.S. Forest Service telephone line, bears NW. and SE.
40.07	The $\frac{1}{4}$ sec. cor., as evidenced by a sandstone $16 \times 10 \times 9$ ins. firmly set in the ground, mkd. $\frac{1}{4}$ on N. face, with a mound of stone, 2 ft. base, 1 ft. high, W. of cor. Set an iron post, 3 ft. long, 1 in. diam., 28 ins. in the ground, with the old corner stone buried alongside, at $\frac{1}{4}$ sec. cor., with brass cap mkd.
	$\begin{array}{r} \frac{1}{4} \text{ S23} \\ \frac{1}{4} \text{ S26} \\ \hline 1945 \end{array}$
	from which
	Old bearing trees: A pine, 34 ins. diam., (now dead), bears N. $86^{\circ}$ W., 83 lks. dist., mkd. $\frac{1}{4}$ S B T.
	New bearing trees: A pine, 6 ins. diam., bears N. $28^{\circ}$ W., 32 lks. dist., mkd. $\frac{1}{4}$ S 23 B T. A pine, 6 ins. diam., bears S. $23\frac{1}{2}^{\circ}$ E., 87 lks. dist., mkd. $\frac{1}{4}$ S 26 B T.
	Thence, S. $89^{\circ} 36'$ W., bet. secs. 23 and 26. Descend along a gentle N. slope.
4.40	Wash, 8 lks. wide, 6 ft. deep, course N.; continue along a gentle N. slope.
14.30	Low spur, slopes N.; descend gradually along a N. slope.
22.78	From this point, Kendrick Spring, bears N. $1^{\circ} 15'$ E., 2.07 chains dist.
23.40	Wash, 8 lks. wide, 4 ft. deep, course N. $10^{\circ}$ E.; asc. 27 ft.
34.80	Drain, 10 lks. wide, 2 ft. deep, course NE.; asc. 46 ft. over an E. slope.
39.97	The cor. of secs. 22, 23, 26 and 27. Land, rolling. Soil, rocky, 2nd and 3rd rates. Timber, pine; undergrowth, 2nd growth pine.

## Resurvey of the Subdivision of T. 24 N., R. 5 E.

BOOK 4354

## Chains

N. 0° 19' W., bet. secs. 22 and 23.

Over rolling land, through heavy timber and dense undergrowth.

Descend 10 ft. along an E. slope.

3.00 Low spur, slopes NE.; desc. 179 ft. over a N. slope.

30.00 Slope changes; desc. 28 ft. over a gradual NW. slope.

33.00 Road; bears E. and W.

35.60 A five wire drift fence, bears E. and N. 70° W.; enter scattered timber and undergrowth.

40.20 The  $\frac{1}{4}$  sec. cor., as evidenced by a lava stone, 12x12x6 ins., firmly set in the ground, mkd.  $\frac{1}{4}$  on W. face, with a mound of stone, 2 ft. base, 1 ft. high, W. of cor.Set an iron post, 3 ft. long, 1 in. diam., 27 ins. in the ground, with the old corner stone buried alongside, at  $\frac{1}{4}$  sec. cor., with brass cap mkd.
$$\begin{array}{c} \frac{1}{4} \\ \text{S22} | \text{S23} \\ 1945 \end{array}$$

from which

Old bearing tree:

A pine, stump, 18 ins. diam., bears S. 36 $\frac{3}{4}$ ° W., 38 lks. dist., mkd.  $\frac{1}{4}$  S B T.

New bearing trees:

A pine, 4 ins. diam., bears S. 23 $\frac{1}{4}$ ° E., 75 lks. dist., mkd.  $\frac{1}{4}$  S 23 B T.A pine, 5 ins. diam., bears N. 81 $\frac{3}{4}$ ° W., 108 lks. dist., mkd.  $\frac{1}{4}$  S 22 B T.

Thence,

N. 1° 05' E., bet. secs. 22 and 23.

Over nearly level land, through scattered timber and undergrowth; the general drainage NW.

20.40 Enter heavy timber and undergrowth, bears NW. and SE.

39.82 The cor. of secs. 14, 15, 22 and 23, as evidenced by a lava stone, 18x16x10 ins., firmly set in the ground, mkd. 3 grooves on S and 2 grooves on E. faces

Set an iron post, 3 ft. long, 2 ins. diam., 28 ins. in the ground, with the old corner stone buried alongside, at cor. of secs. 14, 15, 22 and 23, with brass cap mkd.

$$\begin{array}{c} \text{T24N R5E} \\ \text{S15} | \text{S14} \\ \hline \text{S22} | \text{S23} \\ 1945 \end{array}$$

from which

Old bearing trees:

A pine, 32 ins. diam., (partly dead), bears S. 32 $\frac{3}{4}$ ° E. 200 lks. dist., mkd. T 24 N R 5 E S 23 B T.

## Resurvey of the Subdivision of T. 24 N., R. 5 E.

## Chains

A pine, 36 ins. diam., (partly dead), bears S. 10° W., 265 lks. dist., markings overgrown, not uncovered.

## New bearing trees:

A pine, 5 ins. diam., bears N. 71½° E., 15 lks. dist., mkd. T 24 N R 5 E S 14 B T.

A pine, 5 ins. diam., bears S. 69½° E., 16 lks. dist., mkd. T 24 N R 5 E S 23 B T.

A pine, 7 ins. diam., bears S. 80° W., 32 lks. dist., mkd. T 24 N R 5 E S 22 B T.

A pine, 5 ins. diam., bears N. 30° W., 38 lks. dist., mkd. T 24 N R 5 E S 15 B T.

Land, S. ½ mile, rolling; N. ½ mile nearly level.

Soil, rocky, 2nd and 3rd rates.

Timber, pine; undergrowth, 2nd growth pine.

From the cor. of secs. 13, 14, 23 and 24.

S. 89° 26' W., bet. secs. 14 and 23.

Over rolling land, through heavy timber and dense undergrowth.

Along a gentle N. slope.

3.80 Truck trail, bears N. and S. at junction of another truck trail which bears SE.

21.50 Truck trail, bears NE. and SW.

39.97 The ¼ sec. cor., as evidenced by a lava stone, 16x10x4 ins., firmly set in the ground, mkd. ¼ on N. face, with a mound of stone, 2 ft. base, 1 ft. high, N. of cor.

Set an iron post, 3 ft. long, 1 in. diam., 28 ins. in the ground, with the old corner stone buried alongside, at ¼ sec. cor., with brass cap mkd.

$$\frac{1}{4} \frac{S14}{S23} \\ 1945$$

from which

## Old bearing trees:

The original position of a pine, 34 ins. diam., (now dead, lying on ground), bears N. 10° W., 12 lks. dist., mkd. ¼ S B T.

A pine, 36 ins. diam., (now dead), bears S. 14½° W., 194 lks. dist., markings not uncovered.

## New bearing trees:

A pine, 5 ins. diam., bears N. 44½° W., 26 lks. dist., mkd. ¼ S 14 B T.

A pine, 7 ins. diam., bears S. 9½° E., 22 lks. dist., mkd. ¼ S 23 B T.

Thence,

S. 89° 28' W., bet. secs. 14 and 23.

## Resurvey of the Subdivision of T. 24 N., R. 5 E.

4354

Chains	<p>Descend gradually along a gentle N. slope.</p> <p>13.10 Road, bears N. and S.</p> <p>13.20 U. S. Forest Service telephone line, bears S., and N. to Slate Mountain Lookout Station.</p> <p>32.25 Road, bears N. to Prong Lake and S. to Flagstaff.</p> <p>39.92 The cor. of secs. 14, 15, 22 and 23.</p> <p>Land, rolling. Soil, rocky, 2nd and 3rd rates. Timber, pine; undergrowth, 2nd growth pine.</p> <p>-----</p> <p>N. 0° 24' W., bet. secs. 14 and 15.</p> <p>Over nearly level land, through heavy timber and dense undergrowth.</p> <p>Descend gradually over a NW. slope.</p> <p>32.00 Right bank of a wash, 20 lks. wide, 2 ft. deep, course N. from S. 10° W., thence along bank.</p> <p>35.00 Leave right bank of wash, course N. 30° W. from S.</p> <p>39.79 The <math>\frac{1}{4}</math> sec. cor., as evidenced by a lava stone, 12x10x10 ins., firmly set in the ground, mkd. <math>\frac{1}{4}</math> on W. face.</p> <p>Set an iron post, 3 ft. long, 1 in. diam., 28 ins. in the ground, with the old corner stone buried alongside, at <math>\frac{1}{4}</math> sec. cor., with brass cap mkd.</p> <div style="text-align: center;"> <math>\frac{1}{4}</math>  S15   S14  1945 </div> <p style="text-align: right;">from which</p> <p>Old bearing trees:</p> <p>A pine, 32 ins. diam., (partly dead), bears N. 71<math>\frac{1}{2}</math>° E. 51 lks. dist., mkd. <math>\frac{1}{4}</math> S B T.</p> <p>A pine stump, 28 ins. diam., bears S. 27<math>\frac{1}{4}</math>° W., 32 lks. dist., mkd. <math>\frac{1}{4}</math> S B T.</p> <p>New bearing trees:</p> <p>A pine, 4 ins. diam., bears S. 53<math>\frac{1}{2}</math>° E., 20 lks. dist., mkd. <math>\frac{1}{4}</math> S 14 B T.</p> <p>A pine, 4 ins. diam., bears S. 41° W., 81 lks. dist., mkd. <math>\frac{1}{4}</math> S 15 B T.</p> <p>A U. S. Geological Survey Bench Mark, as evidenced by a brass tablet, 4 ins. diam., seated in a lava stone, 20x24 ins., 8 ins. above ground, mkd.</p> <div style="text-align: center;"> ELEVATION  ABOVE SEA  7387 FEET  DATUM  1907  BM </div> <p style="text-align: right;">bears</p> <p>N. 16° 18' E., 18.28 chains dist. This bench mark is</p>
--------	--

BOOK 4354

## Resurvey of the Subdivision of T. 24 N., R. 5 E.

- Chains located approx. 40 lks. W. of unimproved road.  
Thence,  
N. 0° 44' E., bet. secs. 14 and 15.  
Along a gentle W. slope.
- 7.00 A wash, courses parallel to line at a dist. of 2 chs. to the W.
- 10.00 A road, bearing N. 15° W. and S. 15° E., travels along E. of line, about 8 chs. dist.
- 20.00 Slope changes; desc. gradually over a N. slope.
- 30.00 Road, bears N. 15° W. to Prong Lake and S. 15° E. to Flagstaff.
- 40.04 The cor. of secs. 10, 11, 14 and 15, as evidenced by a lava stone, 24x9x9 ins., firmly set in the ground, mkd. 4 grooves on S. and 2 grooves on E. faces, with a mound of stone 2 ft. base, 1 ft. high, W. of cor.
- Set an iron post, 3 ft. long, 2 ins. diam., 27 ins. in the ground, with the old corner stone buried alongside, at cor. of secs. 10, 11, 14 and 15, with brass cap mkd.
- |      |     |
|------|-----|
| T24N | R5E |
| S10  | S11 |
| S15  | S14 |
| 1945 |     |
- from which
- Old bearing trees:
- A pine, 18 ins. diam., (partly dead), bears N. 26¼° E. 219 lks. dist., mkd. T 24 N R 5 E S 11 B T.
- A pine stump, 16 ins. diam., bears S. 46¼° W., 277 lks. dist., mkd. S 15 B T.
- New bearing trees:
- A pine, 5 ins. diam., bears N. 38¼° E., 53 lks. dist., mkd. T 24 N R 5 E S 11 B T.
- A pine, 5 ins. diam., bears S. 57¼° E., 85 lks. dist., mkd. T 24 N R 5 E S 14 B T.
- A pine, 6 ins. diam., bears S. 32° W., 17 lks. dist., mkd. T 24 N R 5 E S 15 B T.
- A pine, 5 ins. diam., bears N. 26¼° W., 70 lks. dist., mkd. T 24 N R 5 E S 10 B T.
- Land, nearly level.  
Soil, rocky, 2nd and 3rd rates.  
Timber, pine; undergrowth, 2nd growth pine.
- 
- From the cor. of secs. 11, 12, 13 and 14.  
N. 89° 56' W., bet. secs. 11 and 14.  
Over rolling, open, grassy land.  
Descend gradually over a W. slope.
- 40.18 The ¼ sec. cor., as evidenced by a lava stone, 16x8x6 ins. firmly set in the ground, mkd. ¼ on N. face, with a mound of stone, 2 ft. base, 1 ft. high, N. of cor.

## Resurvey of the Subdivision of T. 24 N., R. 5 E.

4354

## Chains

Set an iron post, 3 ft. long, 1 in. diam., 27 ins. in the ground, with the old corner stone buried alongside, at  $\frac{1}{4}$  sec. cor., with brass cap mkd.

S11.  
 $\frac{1}{4}$   
 S14  
 1945

rebuild mound

of stone, 3 ft. base, 2 ft. high, N. of cor.

Thence,

S. 89° 59' W., bet. secs. 11 and 14.

Descend 52 ft. over a gradual NW. slope.

9.30 Enter dense undergrowth, bears N. and S.

9.50 Road, bears N. and S.

9.59 U. S. Forest Service telephone line, bears N. and S.

11.80 Enter heavy timber, bears N. and S.

16.70 Road, bears SE. to Flagstaff and NE. to Slate Mountain Lookout Station.

35.10 Wash, 10 lks. wide, in bottom of a gulch, 2.00 chs. wide, 18 ft. deep, course N.; asc. 18 ft. along a gentle N. slope.

40.79 The cor. of secs. 10, 11, 14 and 15.

Land, rolling.

Soil, rocky, 2nd and 3rd rates.

Timber, pine; undergrowth, 2nd growth pine.

-----  
 N. 0° 03' W., bet. secs. 10 and 11.

Over rolling land, through heavy timber and dense undergrowth.

Descend 76 ft. over a gradual N. slope.

17.25 Wash, 10 lks. wide, course NW.; asc. 29 ft. along a W. slope.

37.70 Low spur, slopes NW.; desc. 17 ft. over a N. slope.

39.87 Wash, 8 lks. wide, course N. 80° W.

39.90 The  $\frac{1}{4}$  sec. cor., as evidenced by a lava stone in place, 34x24 ins., 8 ins. above ground, mkd.  $\frac{1}{4}$  + on top, with a mound of stone, 2 ft. base, 1 ft. high, W. of cor.

Set a brass tablet, 3 $\frac{1}{2}$  ins. diam., 3 in. stem, in the original stone in place, at  $\frac{1}{4}$  sec. cor., with top mkd.

$\frac{1}{4}$   
 S10 | S11  
 1945

from which

BOOK 4354

## Resurvey of the Subdivision of T. 24 N., R. 5 E.

## Chains

## Old bearing trees:

A pine stump, 36 ins. diam., bears S.  $40\frac{1}{2}^{\circ}$  E., 23 lks. dist., mkd.  $\frac{1}{4}$ , other markings overgrown, not uncovered.

A pine, 20 ins. diam., bears S.  $72\frac{1}{2}^{\circ}$  W., 101 lks. dist., markings overgrown, not uncovered. Mark on overgrowth,  $\frac{1}{4}$  S 10 B T.

## New bearing tree:

A pine, 14 ins. diam., bears S.  $63^{\circ}$  E., 97 lks. dist., mkd.  $\frac{1}{4}$  S 11 B T.

Thence,

N.  $2^{\circ} 38'$  W., bet. secs. 10 and 11.

Enter scattered timber; asc. 26 ft. along a gentle W. slope.

- 8.30 Top of ascent; desc gradually along a gentle W. slope.
- 23.30 Enter heavy timber and dense undergrowth, bears E. and W.
- 31.30 Ravine, course S.  $70^{\circ}$  W.; asc. 103 ft. over a SE. slope.
- 32.30 Road, bears S.  $70^{\circ}$  W. and N.  $70^{\circ}$  E.
- 39.21 The cor. of secs. 2, 3, 10 and 11, as evidenced by a sandstone, 16x12x10 ins., firmly set in the ground, mkd. 5 grooves on S. and 2 grooves on E. faces, with a mound of stone 3 ft. base, 1 ft. high, W. of cor.
- Set an iron post, 3 ft. long, 2 ins. diam., 28 ins. in the ground, with the old cor. stone buried alongside, at cor. of secs. 2, 3, 10 and 11, with brass cap mkd.

T24N R5E	
S 3	S 2
S10	S11
1945	

from which

## Old bearing trees:

A juniper, 14 ins. diam., bears N.  $70\frac{1}{2}^{\circ}$  E., 18 lks. dist., mkd. T 24 N R 5 E S 2 B T.

A pinon, 10 ins. diam., bears S.  $10\frac{1}{4}^{\circ}$  W., 19 lks. dist., mkd. T 24 N R 5 E S 11 B T.

A pinon, 5 ins. diam., (now dead), bears S.  $38\frac{3}{4}^{\circ}$  W., 30 lks. dist., mkd. T 24 N R 5 E S 10 B T.

A pinon, 12 ins. diam., bears N.  $69\frac{3}{4}^{\circ}$  W., 39 lks. dist., mkd. T 24 N R 5 E S 3 B T.

## New bearing trees:

A juniper, 10 ins. diam., bears S.  $39\frac{1}{2}^{\circ}$  E., 139 lks. dist., mkd. T 24 N R 5 E S 11 B T.

A juniper, 6 ins. diam., bears S.  $56\frac{3}{4}^{\circ}$  W., 35 lks. dist., mkd. T 24 N R 5 E S 10 B T.

A juniper, 12 ins. diam., bears N.  $48^{\circ}$  W., 33 lks. dist., mkd. T 24 N R 5 E S 3 B T.

## Resurvey of the Subdivision of T. 24 N., R. 5 E.

BOOK 4354

## Chains

Land, rolling.  
Soil, rocky, 2nd and 3rd rates.  
Timber, pine, juniper and pinon; undergrowth, 2nd growth timber.

-----  
From the cor. of secs. 1, 2, 11 and 12.

N. 89° 14' W., bet. secs. 2 and 11.

Over rolling land, through scattered timber.

Descend 25 ft. along a gentle N. slope.

- 8.00 Enter heavy timber and dense undergrowth, bears NW. and SE.
- 14.40 Draw, drains N.; asc. 14 ft. over a NE. slope.
- 18.80 Short spur, slopes N.; desc. 46 ft. along a N. slope.
- 32.60 Draw, 1.00 ch. wide, drains N. 60° E.; truck trail, bears NE. and SW.; asc. gradually over a SE. slope.
- 39.97 The  $\frac{1}{4}$  sec. cor., as evidenced by a lava stone, 16x8x6 ins. firmly set in the ground, mkd.  $\frac{1}{4}$  on N. face, with a mound of stone, 2 ft. base, 1 ft. high, N. of cor.
- Set an iron post, 3 ft. long, 1 in. diam., 27 ins. in the ground, with the old corner stone buried alongside, at  $\frac{1}{4}$  sec. cor., with brass cap mkd.

$$\begin{array}{r} S2 \\ \frac{1}{4} \\ \hline S11 \\ 1945 \end{array}$$

from which

Old bearing trees:

A pine, 28 ins. diam., bears N. 85 $\frac{1}{4}$ ° E., 165 lks. dist., markings overgrown, mark on overgrowth,  $\frac{1}{4}$  S 2 B T.

A pine, 20 ins. diam., bears S. 2 $\frac{1}{4}$ ° E., 80 lks. dist., markings overgrown, mark on overgrowth,  $\frac{1}{4}$  S 11 B T.

Thence,

S. 88° 14' W., bet. secs. 2 and 11.

Ascend gradually over a SE. slope.

- 4.30 A saddle in a low ridge, bears NE. and SW.; road, bears NW. to Slate Mountain Lookout Station and SE. to junction with the Grand Canyon-Flagstaff road; a junction of a road, which runs W. bears N. 20° W. 2.00 chs. dist.; desc. 27 ft. along a N. slope.
- 6.50 U. S. Forest Service telephone line, bears N. and S.
- 12.80 Ravine, course S. 70° W.; continue descent of 39 ft. along a S. slope.
- 12.90 Road, bears N. 70° E. and S. 70° W.
- 27.10 Short ravine, course S.; asc. 10 ft. over an E. slope.

DOCK 4354

## Resurvey of the Subdivision of T. 24 N., R. 5 E.

Chains	
28.60	Point of a spur, from Slate Mountain, slopes S.; desc. 49 ft. over a SW. slope.
38.40	Wash, 25 lks. wide, course S.; asc. 77 ft. over an E. slope.
43.04	The cor. of secs. 2, 3, 10 and 11. Land, rolling. Soil, rocky, 2nd and 3rd rates. Timber, pine, juniper and pinon; undergrowth, 2nd growth timber.
-----	
	N. 5° 10' E., bet. secs. 2 and 3. Over mountainous land, through heavy timber and scattered undergrowth. Descend 13 ft. along an E. slope.
9.20	Ravine, course SE., (heads 5 chs. NW.); asc. 110 ft. over a S. slope.
24.00	Spur, slopes SW.; continue ascent of 14 ft. along a W. slope.
25.70	Sidehill drain, course SW.; asc. 335 ft. over a S. slope.
41.00	Proportional distance. Set an iron post, 3 ft. long, 1 in. diam., 28 ins. in the ground, at $\frac{1}{4}$ sec. cor., with brass cap mkd.
	$\frac{1}{4}$ $S \ 3 \   \ S \ 2$ $1945$
	from which
	A pine, 8 ins. diam., bears S. 75½° E., 58 lks. dist., mkd. $\frac{1}{4}$ S 2 B T.
	A pine, 6 ins. diam., bears N. 29½° W., 13 lks. dist., mkd. $\frac{1}{4}$ S 3 B T.
	Ascend 150 ft. over a SW. slope.
47.60	High spur, slopes W. from Slate Mountain; from this spur another spur slopes N. 10° W.; desc. 215 ft. over a N. slope.
62.89	A point on the 6th Standard Parallel North, determined by proportion. Set an iron post, 3 ft. long, 2 ins. diam., 28 ins. in the ground, at closing corner of secs. 2 and 3, with brass cap mkd.
	$\begin{array}{r} 25N \ R5E \\ S34 \\ \hline S \ 3 \   \ S \ 2 \\ T24N \ R5E \\ C \ C \\ 1945 \end{array}$
	from which

## Resurvey of the Subdivision of T. 24 N., R. 5 E.

BOOK 2854

## Chains

A fir, 5 ins. diam., bears S.  $44\frac{1}{2}^{\circ}$  E., 35 lks.  
dist., mkd. T 24 N R 5 E S 2 C C B T.

A fir, 9 ins. diam., bears S.  $82\frac{3}{4}^{\circ}$  W., 38 lks.  
dist., mkd. T 24 N R 5 E S 3 C C B T.

From the closing corner, the standard  $\frac{1}{4}$  sec. cor. on the  
S. bdy. of sec. 34, T. 25 N., R. 5 E., bears S.  $89^{\circ} 53' W.$   
10.50 chs. dist.

Land, mountainous.

Soil, rocky, 2nd and 3rd rates.

Timber, pine, fir and aspen; undergrowth, 2nd growth  
timber.

-----  
At midpoint on the N. bdy. of sec. 2.

Set an iron post, 3 ft. long, 1 in. diam., 18 ins. in the  
ground to solid rock, and in a mound of stone to top, at  
 $\frac{1}{4}$  sec. cor. of sec. 2, with brass cap mkd.

$\frac{1}{4}$  S 2  
1945

from which

A pine, 8 ins. diam., bears S.  $53\frac{3}{4}^{\circ}$  E., 25 lks.  
dist., mkd.  $\frac{1}{4}$  S 2 B T.

A pine, 5 ins. diam., bears S.  $2\frac{3}{4}^{\circ}$  W., 30 lks.  
dist., mkd.  $\frac{1}{4}$  S 2 B T.

From this corner, the standard cor. of secs. 34 and 35,  
T. 25 N., R. 5 E., bears S.  $89^{\circ} 46' W.$ , 10.93 chs. dist.

-----  
From the cor. of secs. 3, 4, 33 and 34, on the S. bdy. of  
the Tp., as evidenced by an iron post, 2 ins. diam., firmly  
set, mkd. and witnessed as described in the field notes  
of the N. bdy. of T. 23 N., R. 5 E., resurveyed under  
this group.

N.  $7^{\circ} 20' W.$ , bet. secs. 33 and 34.

Over mountainous land, through heavy timber and under-  
growth.

Descend 46 ft. along a W. slope.

- 5.20 Trail, bears NW. and SE.  
6.50 Ridge, bears NW. and SE.; desc. 623 ft. over a NE. slope.  
28.30 Trail, bears NE. and SW.  
43.71 The  $\frac{1}{4}$  sec. cor., as evidenced by a sandstone, 22x12x4 ins.  
firmly set in a mound of stone, 2 ft. base, 1 ft. high.

Set an iron post, 3 ft. long, 1 in. diam., 20 ins. in the  
ground to solid rock, with the old corner stone buried  
alongside, and in a mound of stone to top, at  $\frac{1}{4}$  sec. cor.  
with brass cap mkd.

$\frac{1}{4}$   
S33 | S34  
1945

BOOK 4354

## Resurvey of the Subdivision of T. 24 N., R. 5 E.

Chains

from which

## Old bearing trees:

A fir, 12 ins. diam., bears S.  $11^{\circ}$  E., 47 lks. dist., markings overgrown, not uncovered.

A fir, 20 ins. diam., bears S.  $10\frac{1}{2}^{\circ}$  W., 44 lks. dist., markings overgrown, not uncovered.

## New bearing trees:

A fir, 8 ins. diam., bears S.  $69^{\circ}$  E., 38 lks. dist., mkd.  $\frac{1}{4}$  S 34 B T.

A fir, 5 ins. diam., bears N.  $40\frac{1}{2}^{\circ}$  W., 11 lks. dist., mkd.  $\frac{1}{4}$  S 33 B T.

Thence,

N.  $0^{\circ} 37'$  E., bet. secs. 33 and 34.

Descend 122 ft. over a steep NE. slope.

5.00 Base of steep descent, bears NW. and SE.; desc. 53 ft. over a N. slope.

8.90 Bottom of a wide ravine, course NW.; continue descent of 121 ft. over a NW. slope.

27.20 Low spur, slopes NW.; desc. 53 ft. over a N. slope.

33.50 Ravine, course NW.; asc. 4 ft. over a SW. slope.

34.30 Low spur, slopes NW.; desc. 51 ft. over a N. slope.

39.58 The cor. of secs. 27, 28, 33 and 34; as evidenced by a sandstone, 16x14x12 ins., firmly set in the ground, mkd. 1 groove on S. and 3 grooves on E. faces, with a mound of stone, 2 ft. base,  $1\frac{1}{2}$  ft. high, W. of cor.

Set an iron post, 3 ft. long, 2 ins. diam., 28 ins. in the ground, with the old corner stone buried alongside, at cor. of secs. 27, 28, 33 and 34, with brass cap mkd.

T24N	R5E
S28	S27
S33	S34
1945	

from which

## Old bearing trees:

A pine, 16 ins. diam., bears S.  $42\frac{1}{2}^{\circ}$  E., 37 lks. dist., markings overgrown, mark on overgrowth, T 24 N R 5 E S 34 B T.

A pine, 16 ins. diam., (partly dead), bears S.  $21^{\circ}$  W., 136 lks. dist., mkd. T 24 N R 5 E S 33 B T.

A pine, 24 ins. diam., bears N.  $83^{\circ}$  W., 6 lks. dist., markings overgrown, mark on overgrowth, T 24 N R 5 E S 28 B T.

A pine, 18 ins. diam., N.  $1^{\circ}$  W., 35 lks. dist., markings overgrown, mark on overgrowth, T 24 N R 5 E S 28 B T.

## New bearing trees:

## Resurvey of the Subdivision of T. 24 N., R. 5 E.

BOOK 4354

## Chains

A pine, 5 ins. diam., bears N. 15° E., 82 lks.  
dist., mkd. T 24 N R 5 E S 27 B T.

A pine, 9 ins. diam., bears S. 17° W., 91 lks.  
dist., mkd. T 24 N R 5 E S 33 B T.

Land, mountainous.

Soil, rocky, 2nd and 3rd rates.

Timber, pine, fir and aspen; undergrowth, 2nd growth  
timber.

-----  
From the cor. of secs. 26, 27, 34 and 35,

N. 89° 04' W., bet. secs. 27 and 34.

Over mountainous land, through heavy timber and dense  
undergrowth.

Descend 134 ft. over a NW. slope.

3.70 Ravine, course N. 10° W.; asc. 90 ft. over a NE. slope.

7.00 Blazed trail, bears SE. and NW.

14.00 High ridge, bears N. 20° W. and S. 20° E.; desc. 384 ft.  
over a W. slope.

36.70 Ravine, course NW.; asc. 67 ft. over a NE. slope.

40.16 Proportional distance.

Set an iron post, 3 ft. long, 1 in. diam., 28 ins. in the  
ground at  $\frac{1}{4}$  sec. cor., with brass cap mkd.

$$\begin{array}{r} S\ 27 \\ \hline \frac{1}{4} \\ S\ 34 \\ .1945 \end{array}$$

from which

A fir, 8 ins. diam., bears N. 63 $\frac{3}{4}$ ° E., 16 lks.  
dist., mkd.  $\frac{1}{4}$  S 27 B T.

A fir, 10 ins. diam., bears S. 17° E., 3 lks.  
dist., mkd.  $\frac{1}{4}$  S 34 B T.

Ascend 14 ft. over a NE. slope.

41.80 Spur, slopes N. 20° W.; desc. 208 ft. over a W. slope.

53.20 Ravine, course NW.; asc. 25 ft. over a NE. slope.

58.00 Spur, slopes NW.; desc. 168 ft. over a W. slope.

69.00 Ravine, course NW.; asc. 7 ft. along a N. slope.

71.00 Top of ascent, bears N. and S.; desc. 24 ft. along a N.  
slope.

80.32 The cor. of secs. 27, 28, 33 and 34.

Land, mountainous.

Soil, rocky, 2nd and 3rd rates.

Timber, fir and pine; undergrowth, 2nd growth timber and  
cherry.

-----

BOOK 4354

## Resurvey of the Subdivision of T. 24 N., R. 5 E.

Chains	
	N. 0° 05' E., bet. secs. 27 and 28. Over mountainous land, through heavy timber and dense undergrowth. Descend 233 ft. over a N. slope.
12.25	A wire and rail fence, bears W., and a wire fence bears E., 2.00 chs. dist. to a fence cor., from which fences extend N. and W.; leave dense undergrowth, bears E. and W.
35.00	Enter scattered timber and Bull Basin, bears E. and W.
37.50	A pole fence, bears E. and W.; enter corral.
38.46	A pole fence, bears E. and W..
39.69	The $\frac{1}{4}$ sec. cor., as evidenced by a lava stone, 16x14x14 ins., firmly set in the ground, mkd. $\frac{1}{4}$ on W. face, with a mound of stone, 2 ft. base, 1 ft. high, W. of cor.  Set an iron post, 3 ft. long, 1 in. diam., 28 ins. in the ground, with the old corner stone buried alongside, at $\frac{1}{4}$ sec. cor., with brass cap mkd.  $\begin{array}{c} \frac{1}{4} \\ S28   S27 \\ 1945 \end{array}$ from which  A pine, 36 ins. diam., bears S. 39 $\frac{1}{2}$ ° E., 270 lks. dist., mkd. $\frac{1}{4}$ S 27 B T.  A pine, 24 ins. diam., bears N. 32 $\frac{1}{4}$ ° W., 321 lks. dist., mkd. $\frac{1}{4}$ S 28 B T.  The NE. cor. of a rock house, bears S. 50° 10' W., 8.61 chs. dist.  NW. cor. of a frame house, bears S. 51° 03' W., 9.72 chs. dist.  SE. cor. of a log cabin, bears S. 70° 30' W., 0.85 chs. dist.  A spring, bears S. 58 $\frac{1}{2}$ ° W., 5.70 chs. dist.  The center of dam on the N. side of an earthen reservoir, 2.50 chs. diam., bears N. 84° W., 7.00 chs. dist.  Thence, N. 0° 14' W., bet. secs. 27 and 28. Descend 79 ft. over a gradual N. slope.
0.13	Woven wire fence, bears E. and W.; leave corral.
2.00	Enter marsh land, bears E. and W.
4.50	Leave marsh land, bears NW. and SE.
11.50	A wire fence, bears W., and E., 2.00 chs. dist. to a fence cor., from which fences extend S. and W.
19.50	Road, bears E. and W.; S. end of a dam, on the E. side of an earthen reservoir, 5 chs. diam., bears W. 3.80 chs. dist.

## Resurvey of the Subdivision of T. 24 N., R. 5 E.

## Chains

- 21.50 Leave Bull Basin; enter heavy timber, bears E. and W.
- 27.10 Wash, 10 lks. wide, course NE.; asc. gradually along a gentle E. slope.
- 30.10 Road, bears N. 20° W. and S. 20° E.
- 33.90 Recross road, bears N. 30° E. and S. 30° W.
- 40.01 The cor. of secs. 21, 22, 27 and 28, as evidenced by a lava stone, 18x12x6 ins., firmly set in the ground, mkd. 2 grooves on S. and 3 grooves on E. faces, with a mound of stone, 3 ft. base, 1½ ft. high, W. of cor.
- Set an iron post, 3 ft. long, 2 ins. diam., 28 ins. in the ground, with the old corner stone buried alongside, at cor. of secs. 21, 22, 27 and 28, with brass cap mkd.

T24N	R5E
S21	S22
S28	S27
1945	

from which

## Old bearing trees:

A pine, 14 ins. diam., bears N. 57½° E., 117 lks. dist., markings overgrown, mark on overgrowth, T 24 N R 5 E S 22 B T.

A pine, 20 ins. diam., bears S. 52° E., 66 lks. dist., markings overgrown, mark on overgrowth, T 24 N R 5 E S 27 B T.

A pine, 22 ins. diam., bears S. 28° W., 65 lks. dist., markings overgrown, mark on overgrowth, T 24 N R 5 E S 28 B T.

A pine, 20 ins. diam., bears N. 20½° W., 80 lks. dist., markings overgrown, mark on overgrowth, T 24 N R 5 E S 21 B T.

NE. cor. of Kendrick Peak Lookout Station, bears S. 15° 21' E.

Land, mountainous.

Soil, rocky, 2nd and 3rd rates.

Timber, pine and fir; undergrowth, 2nd growth timber.

-----

From the cor. of secs. 22, 23, 26 and 27.

N. 89° 20' W., bet. secs. 22 and 27.

Over mountainous land, through heavy timber and dense undergrowth.

Ascend 12 ft. over an E. slope.

2.50 Spur, slopes NE.; asc. 16 ft. along a N. slope.

9.80 Wash, 15 lks. wide, 8 ft. deep, course N. 10° E.; asc. 189 ft. over a broken NE. slope.

32.40 Spur, slopes NE.; desc. 94 ft. over a NW. slope.

39.90 The ¼ sec. cor., determined from old bearing trees. The old corner stone, which is a limestone, 11x8x7 ins., mkd.

BOOK

4354

## Resurvey of the Subdivision of T. 24 N., R. 5 E.

## Chains

$\frac{1}{4}$ , found leaning against a tree, approx. 7 lks. N. of true point for cor.

Set an iron post, 3 ft. long, 1 in. diam., 27 ins. in the ground, with the old corner stone buried alongside, at  $\frac{1}{4}$  sec. cor., with brass cap mkd.

S22

 $\frac{1}{4}$ 

S27

1945

from which

## Old bearing trees:

A pine, 7 ins. diam., (partly dead), bears N. 81° W., 9 lks. dist., mkd.  $\frac{1}{4}$  S B T.

A fir, 18 ins. diam., bears S. 17° E., 11 lks. dist., mkd.  $\frac{1}{4}$  S B T. Additionally mark this tree  $\frac{1}{4}$  S 27 B T.

## New bearing tree:

A pine, 5 ins. diam., bears N. 68° W., 54 lks. dist., mkd.  $\frac{1}{4}$  S 22 B T.

Thence,

N. 89° 45' W., bet. secs. 22 and 27.

Descend 31 ft. over a NW. slope.

- 3.00 Head of a ravine, course N.; asc. 111 ft. over an E. slope.
- 9.70 Spur; slopes N. 15° W.; desc. 130 ft. over a SW. slope.
- 27.80 Wash, 8 lks. wide, course N.; thence, along a N. slope.
- 36.00 Wash, 10 lks. wide, course N. 25° E.; asc. 33 ft. over an E. slope.
- 39.65 Road, bears N. to Flagstaff and S. to Bull Basin.
- 40.54 The cor. of secs. 21, 22, 27 and 28.

Land, mountainous.

Soil, rocky, 2nd and 3rd rates.

Timber, pine and fir; undergrowth, 2nd growth timber.

-----

N. 1° 04' E., bet. secs. 21 and 22.

Over rolling land, through heavy timber and scattered undergrowth.

Descend 23 ft. along an E. slope.

- 3.80 Road, bears E. and W.
- 12.60 Slope changes; desc. 73 ft. over a NE. slope.
- 25.00 Enter dense undergrowth; bears E. and W.
- 26.90 Recross road, bears NE. to Flagstaff and SW. to Bull Basin.
- 39.35 The  $\frac{1}{4}$  sec. cor., as evidenced by a lava stone, in place, 50x40 ins., 18 ins. above ground, mkd.  $\frac{1}{4}$  + on top.

## Resurvey of the Subdivision of T. 24 N., R. 5 E.

654

## Chains

Set a brass tablet,  $3\frac{1}{2}$  in. diam., 3 in. stem, in the original stone in place, at  $\frac{1}{4}$  sec. cor., with top mkd.

$$\begin{array}{c} \frac{1}{4} \\ \hline \text{S21} | \text{S22} \\ \hline 1945 \end{array}$$

from which

## Old bearing trees:

A pine, 16 ins. diam., bears S.  $83^{\circ}$  E., 83 lks. dist., markings overgrown. Mark on overgrowth  $\frac{1}{4}$  S 22 B T.

A pine, 12 ins. diam., bears S.  $75^{\circ}$  W., 63 lks. dist., markings overgrown. Mark on overgrowth,  $\frac{1}{4}$  S 21 B T.

Thence,

N.  $0^{\circ} 52'$  E., bet. secs. 21 and 22.

Descend 89 ft. over NE. slope.

39.95 The cor. of secs. 15, 16, 21 and 22, as evidenced by a lava stone, 20x14x6 ins., firmly set in the ground, mkd. 3 grooves on S. and E. faces, with a mound of stone, 2 ft. base, 1 ft. high, W. of cor.

Set an iron post, 3 ft. long, 2 ins. diam., 16 ins. in the ground, to solid rock, with the old corner stone, buried alongside, and in a mound of stone to top, at cor. of secs. 15, 16, 21 and 22, with brass cap mkd.

$$\begin{array}{c} \text{T24N R5E} \\ \hline \text{S16} | \text{S15} \\ \hline \text{S21} | \text{S22} \\ \hline 1945 \end{array}$$

from which

## Old bearing trees:

A pine, 18 ins. diam., (partly dead), bears N.  $26\frac{1}{4}^{\circ}$  E. 30 lks. dist., mkd. T 24 N R 5 E S 15 B T.

A pine, 20 ins. diam., bears S.  $13^{\circ}$  E., 81 lks. dist., mkd. T 24 N R 5 E S 22 B T.

A pine, 24 ins. diam., bears S.  $7\frac{1}{4}^{\circ}$  W., 17 lks. dist., mkd. T 24 N R 5 E S 21 B T.

A pine, 18 ins. diam., (partly dead), bears N.  $84\frac{1}{4}^{\circ}$  W. 88 lks. dist., mkd. T 24 N R 5 E S 16 B T.

## New bearing trees:

A pine, 10 ins. diam., bears N.  $59\frac{1}{4}^{\circ}$  E., 179 lks. dist., mkd. T 24 N R 5 E S 15 B T.

A pine, 16 ins. diam., bears S.  $42\frac{3}{4}^{\circ}$  E., 175 lks. dist., mkd. T 24 N R 5 E S 22 B T.

A pine, 16 ins. diam., bears S.  $50\frac{3}{4}^{\circ}$  W., 136 lks. dist., mkd. T 24 N R 5 E S 21 B T.

A pine, 16 ins. diam., bears N.  $45\frac{1}{2}^{\circ}$  W., 123 lks. dist., mkd. T 24 N R 5 E S 16 B T.

BOOK 4354

## Resurvey of the Subdivision of T. 24 N., R. 5 E.

## Chains

Land, rolling.  
Soil, rocky, 2nd and 3rd rates.  
Timber, pine; undergrowth, 2nd growth pine.

-----  
From the cor. of secs. 14, 15, 22 and 23.

N. 89° 47' W., bet. secs. 15 and 22.

Over rolling land, through heavy timber and dense undergrowth.

Descend gradually along a gentle N. slope.

11.30 Shallow draw, 1.00 ch. wide, drains N.; continue along a gentle N. slope.

16.80 Wash, 20 lks. wide, 5 ft. deep, course N.; asc. gradually along a gentle N. slope.

39.94 The  $\frac{1}{4}$  sec. cor., as evidenced by a lava stone, 18x12x10 ins. firmly set in the ground; mkd.  $\frac{1}{4}$  on N. face.

Set an iron post, 3 ft. long, 1 in. diam., 27 ins. in the ground, with the old corner stone buried alongside, at  $\frac{1}{4}$  sec. cor., with brass cap mkd.

S15

$\frac{1}{4}$ -----  
S22

1945

from which

## Old bearing trees:

A pine stump, 34 ins. diam., bears N. 11 $\frac{3}{4}$ ° W., 54 lks. dist., mkd.  $\frac{1}{4}$  S B T.

A pine, 36 ins. diam., (partly dead), bears S. 63 $\frac{1}{2}$ ° E. 46 lks. dist., mkd.  $\frac{1}{4}$  S B T.

## New bearing trees:

A pine, 10 ins. diam., bears N. 42° E., 84 lks. dist., mkd.  $\frac{1}{4}$  S 15 B T.

A pine, 4 ins. diam., bears S. 7 $\frac{3}{4}$ ° E., 85 lks. dist., mkd.  $\frac{1}{4}$  S 22 B T.

## Thence,

S. 89° 36' W., bet. secs. 15 and 22.

Ascend gradually along a gentle N. slope.

15.00 Slope changes; asc. 128 ft. over a NE. slope.

18.30 A wire drift fence, bears S. 10° E., and N. 45° W.

39.84 The cor. of secs. 15, 16, 21 and 22.

Land, rolling.  
Soil, rocky, 2nd and 3rd rates.  
Timber, pine; undergrowth, 2nd growth pine.

-----  
N. 0° 55' E., bet. secs. 15 and 16.

## Resurvey of the Subdivision of T. 24 N., R. 5 E.

BOOK 4354

Chains	
	Over rolling land, through heavy timber and dense undergrowth.
	Descend 45 ft. over a NE. slope.
3.95	Head of a ravine, course NE.; asc. gradually over a NE. slope.
8.00	Spur, slopes E., 6.00 chs. to toe; desc. 82 ft. along the top of another spur, slopes N.
18.30	Ravine, course NE. for 1.00 ch. to a junction with a ravine, which courses N.; desc. 50 ft. along an E. slope.
31.10	Ravine, course N. 10° W.; along a steep W. slope.
39.94	The $\frac{1}{4}$ sec. cor., as evidenced by a sandstone, 9x9x6 ins. firmly set in the ground, mkd. $\frac{1}{4}$ on W. face, with a mound of stone, 2 ft. base, 10 ins. high, W. of cor.
	Set an iron post, 3 ft. long, 1 in. diam., 28 ins. in the ground, with the old cor. stone buried alongside, at $\frac{1}{4}$ sec. cor., with brass cap mkd.
	$\frac{1}{4}$ S16   S15 1945
	from which
	Old bearing trees:
	A pine, 18 ins. diam., bears N. 31 $\frac{1}{2}$ ° E., 15 lks. dist., markings overgrown. Mark on overgrowth, $\frac{1}{4}$ S 15 B T.
	A pine, 16 ins. diam., bears S. 15 $\frac{1}{4}$ ° E., 24 lks. dist., markings overgrown, not uncovered.
	New bearing tree:
	A pine, 18 ins. diam., bears S. 44 $\frac{3}{4}$ ° W., 79 lks. dist., mkd. $\frac{1}{4}$ S 16 B T.
	Thence,
	N. 1° 35' W., bet. secs. 15 and 16.
	Descend 58 ft. over a NW. slope.
3.30	Recross ravine, course N. 15° E.; asc. 77 ft. along an E. slope.
23.50	Low spur, slopes E.; desc. 18 ft. along an E. slope.
24.54	Slate Mountain Lookout Station, bears N. 31° 13' E.
28.10	Spur, slopes NE.; desc. 57 ft. over a NE. slope.
32.20	Head of a ravine, draining NE.; desc. 21 ft. along an E. slope.
38.50	Spur, slopes N. 15° E.; desc. 6 ft. over a NW. slope.
39.92	The cor. of secs. 9, 10, 15 and 16, as evidenced by a sandstone, 16x8x8 ins., firmly set in the ground, mkd. 4 grooves on S. and 3 grooves on E. faces, with a mound of stone, 2 ft. base, 1 ft. high, W. of cor.
	Set an iron post, 3 ft. long, 2 ins. diam., 16 ins. in the

BOOK 4354

Resurvey of the Subdivision of T. 24 N., R. 5 E.

Chains

ground, to solid rock, with the old corner stone buried alongside, and in a mound of stone to top, at cor. of secs. 9, 10, 15 and 16, with brass cap mkd.

T24N R5E  
 S 9 | S10  
 S16 | S15  
 1945

from which

Old bearing trees:

A pine, 20 ins. diam., (partly dead), bears N.  $36\frac{3}{4}^\circ$  E., 119 lks. dist., markings overgrown, not uncovered.

The original position of a pine, 14 ins. diam., now dead, lying on ground, bears S.  $41\frac{1}{4}^\circ$  E., 62 lks. dist., markings illegible.

A pine, 18 ins. diam., (partly dead), bears S.  $43^\circ$  W. 116 lks. dist., mkd. T 24 N R 5 E S 16 B T.

A pine, 20 ins. diam., bears S.  $89^\circ$  W., 95 lks. dist., markings overgrown, not uncovered.

New bearing trees:

A pine, 10 ins. diam., bears N.  $54\frac{1}{2}^\circ$  E., 51 lks. dist., mkd. T 24 N R 5 E S 10 B T.

A pine, 5 ins. diam., bears S.  $12\frac{1}{4}^\circ$  E., 30 lks. dist., mkd. T 24 N R 5 E S 15 B T.

A pine, 5 ins. diam., bears S.  $41\frac{1}{4}^\circ$  W., 37 lks. dist., mkd. T 24 N R 5 E S 16 B T.

A pine, 12 ins. diam., bears N.  $79\frac{1}{2}^\circ$  W., 20 lks. dist., mkd. T 24 N R 5 E S 9 B T.

Land, rolling.

Soil, rocky, 2nd and 3rd rates.

Timber, pine and juniper; undergrowth, 2nd growth timber.

-----  
 From the cor. of secs. 10, 11, 14 and 15.

S.  $89^\circ 18'$  W., bet. secs. 10 and 15.

Over rolling land, through heavy timber and dense undergrowth.

Descend 40 ft. along a gentle N. slope.

3.70 Road, bears N.  $15^\circ$  W., to Prong Lake and S.  $15^\circ$  E. to Flagstaff.

10.35 Wash, 10 lks. wide, 12 ft. deep, course N.; continue along gentle N. slope.

39.88 The  $\frac{1}{4}$  sec. cor., as evidenced by a lava stone, 12x8x4 ins. firmly set in the ground, mkd.  $\frac{1}{4}$  on N. face, with a mound of stone, 2 ft. base, 1 ft. high, N. of cor.

Set an iron post, 3 ft. long, 1 in. diam., 28 ins. in the ground, with the old corner stone buried alongside, at  $\frac{1}{4}$  sec. cor., with brass cap mkd.

## Resurvey of the Subdivision of T. 24 N., R. 5 E.

4854

Chains

S10

 $\frac{1}{4}$ 

S15

1945

from which

## Old bearing trees:

A juniper, 40 ins. diam., bears N.  $36\frac{1}{2}^{\circ}$  E.,  
155 lks. dist., mkd.  $\frac{1}{4}$  S B T. Additionally mark on  
overgrowth,  $\frac{1}{4}$  S 10 B T.

A pine, 36 ins. diam., (partly dead), bears S.  $35\frac{3}{4}^{\circ}$  W.  
237 lks. dist., markings overgrown, not uncovered.

## New bearing tree:

A pine, 5 ins. diam., bears S.  $7\frac{1}{2}^{\circ}$  W., 22 lks.  
dist., mkd.  $\frac{1}{4}$  S 15 B T.

Thence,

N.  $89^{\circ} 37'$  W., bet. secs. 10 and 15.

Descend 53 ft. along a N. slope.

16.65 Wash, 25 lks. wide, course N.; asc. 62 ft. along a gentle N. slope.

26.50 Spur, slopes N.; desc. 69 ft. over a NW. slope.

29.13 A wire drift fence, bears N. and S.

32.70 Ravine, course N.; asc. 116 ft. over an E. slope.

39.60 Spur, slopes N.  $15^{\circ}$  E.

40.63 The cor. of secs. 9, 10, 15 and 16.

Land, rolling.

Soil, rocky, 2nd and 3rd rates.

Timber, pine; undergrowth, 2nd growth pine.

-----  
N.  $0^{\circ} 03'$  E., bet. secs. 9 and 10.

Over rolling land, through heavy timber and dense undergrowth.

Descend 151 ft. over a NW. slope.

11.00 Ravine, course NE.; asc. 34 ft. over a SE. slope.

15.40 Spur, slopes E.; desc. 86 ft. over a NE. slope.

27.30 Wash, 10 lks. wide, course NW.; desc. 31 ft. along a gentle W. slope.

39.44 The  $\frac{1}{4}$  sec. cor., as evidenced by a red sandstone, 20x14x10 ins., firmly set in the ground, mkd.  $\frac{1}{4}$  on W. face.Set an iron post, 3 ft. long, 1 in. diam., 28 ins. in the ground, with the old corner stone buried alongside, at  $\frac{1}{4}$  sec. cor., with brass cap mkd. $\frac{1}{4}$   
S 9 | S10

1945

from which

## Resurvey of the Subdivision of T. 24 N., R. 5 E.

## Chains

A pine, 6 ins. diam., bears S. 45° E., 37 lks.  
dist., mkd.  $\frac{1}{4}$  S 10 B T.

A pine, 28 ins. diam., bears N. 58° W., 83 lks.  
dist., mkd.  $\frac{1}{4}$  S 9 B T.

Cor. is located under a wire fence, which bears  
S. 18° E. and N. 2½° W.

Thence,

N. 1° 51' W., bet. secs. 9 and 10.

Descend 16 ft. along a gentle W. slope.

12.50 Wash, 15 lks. wide, 3 ft. deep, course N. 80° W.; continue  
along a W. slope.

19.60 Wash, 30 lks. wide, 4 ft. deep, course W.; asc. 39 ft.  
over a gradual SW. slope.

30.00 Leave heavy timber, enter scattered 2nd growth pine, bears  
E. and W.

32.00 Enter nearly level land, bears E. and W.

39.91 The cor. of secs. 3, 4, 9 and 10, as evidenced by a lava  
stone, 16x14x10 ins., firmly set in the ground, mkd. 5  
notches on S. and 3 notches on E. edges, with a mound of  
stone, 3 ft. base, 1 ft. high, W. of cor.

Set an iron post, 3 ft. long, 2 ins. diam., 28 ins. in the  
ground, with the old corner stone buried alongside, at  
cor. of secs. 3, 4, 9 and 10, with brass cap mkd.

T24N	R5E
S4	S3

S9	S10
1945	

from which

A pine, 4 ins. diam., bears N. 40½° E., 158 lks.  
dist., mkd. T 24 N R 5 E S 3 B T.

A pine, 3 ins. diam., bears S. 62° E., 271 lks.  
dist., B T.

A pine, 4 ins. diam., bears S. 76½° W., 290 lks.  
dist., mkd. T 24 N R 5 E S 9 B T.

A pine, 5 ins. diam., bears N. 29¾° W., 453 lks.  
dist., mkd. T 24 N R 5 E S 4 B T.

Land, rolling.

Soil, rocky, 2nd and 3rd rates.

Timber, pine, juniper and pinon; undergrowth, 2nd growth  
timber.

-----  
From the cor. of secs. 2, 3, 10 and 11.

N. 89° 27' W., bet. secs. 3 and 10.

Over rolling land, through heavy timber and dense under-  
growth.

Ascend 98 ft. over a SE. slope.

Resurvey of the Subdivision of T. 24 N., R. 5 E.

BOOK 4354

Chains	
6.50	Spur, slopes S.; desc. 83 ft. over SW. slope.
13.70	Low spur, slopes SW.; desc. 120 ft. over a W. slope.
20.00	Ravine, course N. 70° W.; desc. 69 ft. over a gradual W. slope.
34.20	Road, bears S. 15° E. and N. 15° W.; enter scattered timber and undergrowth, bears N. and S.
39.45	Road, bears S. to Flagstaff and N. to Prong Lake.
40.11	The $\frac{1}{4}$ sec. cor., as evidenced by a lava stone, 16x14x12 ins., firmly set in the ground, mkd. $\frac{1}{4}$ on N. face, with a mound of stone, 2 ft. base, 1 ft. high, N. of cor.  Set an iron post, 3 ft. long, 1 in. diam., 27 ins. in the ground, with the old corner stone buried alongside, at $\frac{1}{4}$ sec. cor., with brass cap mkd.  <div style="text-align: center;"> <math display="block">\begin{array}{r} S\ 3 \\ \hline \frac{1}{4} \\ S\ 10 \\ 1945 \end{array}</math> </div> <div style="text-align: right;">from which</div> <p>A juniper, 4 ins. diam., bears N. 50<math>\frac{1}{2}</math>° W., 134 lks. dist., mkd. <math>\frac{1}{4}</math> S 3 B T.</p> <p>A pine, 4 ins. diam., bears S. 39° E., 185 lks. dist., mkd. <math>\frac{1}{4}</math> S 10 B T.</p> <p>Thence, S. 89° 37' W., bet. secs. 3 and 10. Descend 28 ft. over a gradual W. slope.</p>
9.90	Drainage ditch, 18 lks. wide, 2 ft. deep, course N. 20° W. to Prong Lake.
10.00	Slope changes; descend gradually along a gentle S. slope.
13.30	Truck trail, bears SW. and NE.
39.89	The cor. of secs. 3, 4, 9 and 10.  Land, rolling. Soil, rocky, 2nd and 3rd rates. Timber, pine, juniper and pinon; undergrowth, 2nd growth timber.
-----	
40.96	N. 5° 37' E., bet. secs. 3 and 4. Over nearly level land, through scattered timber and undergrowth. Proportional distance.  Set an iron post, 3 ft. long, 1 in. diam., 28 ins. in the ground, at $\frac{1}{4}$ sec. cor., with brass cap mkd.  <div style="text-align: center;"> <math display="block">\begin{array}{r} \frac{1}{4} \\ S\ 4\   \ S\ 3 \\ 1945 \end{array}</math> </div> <div style="text-align: right;">from which</div>

BOOK 4354

## Resurvey of the Subdivision of T. 24 N., R. 5 E.

## Chains

A juniper, 14 ins. diam., bears N.  $54\frac{1}{2}^{\circ}$  E., 200 lks. dist., mkd.  $\frac{1}{4}$  S 3 B T.

A pine, 5 ins. diam., bears N.  $64\frac{1}{2}^{\circ}$  W., 422 lks. dist., mkd.  $\frac{1}{4}$  S 4 B T.

42.57 Drainage ditch, 9 lks. wide, 1 ft. deep, course NW. to Prong Lake.

49.20 Road, bears E. and NW.

61.18 Drainage ditch, 12 lks. wide,  $1\frac{1}{2}$  ft. deep, course SW. to Prong Lake.

62.78 A point on the 6th Standard Parallel North determined by proportion.

Set an iron post, 3 ft. long, 2 ins. diam., 28 ins. in the ground, at closing corner of secs. 3 and 4, with brass cap mkd.

T25N	R5E
S33	
-----	
S4	S3
T24N	R5E
C C	
1945	

raise a mound

of stone, 3 ft. base, 2 ft. high, S. of cor.

From the closing corner, the standard  $\frac{1}{4}$  sec. cor. on the S. bdy. of sec. 33, T. 25 N., R. 5 E., bears S.  $89^{\circ} 41'$  W. 10.56 chs. dist.

Land, nearly level.

Soil, rocky, 2nd and 3rd rates.

Timber, pine, juniper and pinon; undergrowth, 2nd growth pine.

-----

At midpoint on the N. bdy. of sec. 3.

Set an iron post, 3 ft. long, 1 in. diam., 20 ins. in the ground, to solid rock, and in a mound of stone to top, at  $\frac{1}{4}$  sec. cor. of sec. 3, with brass cap mkd.

-----	
$\frac{1}{4}$ S	3
1945	

from which

A pine, 28 ins. diam., bears S.  $47\frac{1}{2}^{\circ}$  E., 38 lks. dist., mkd.  $\frac{1}{4}$  S 3 B T.

A juniper, 5 ins. diam., bears S.  $29\frac{1}{2}^{\circ}$  W., 35 lks. dist., mkd.  $\frac{1}{4}$  S 3 B T.

From this corner, the standard corner of secs. 33 and 34, T. 25 N., R. 5 E., bears N.  $89^{\circ} 35'$  W., 9.97 chs. dist.

-----

From the cor. of secs. 4, 5, 32 and 33 on the S. bdy. of the Tp., as evidenced by a limestone in place, 4x3 ft., 3 ft. above ground, mkd. and witnessed as described in the field notes of the N. bdy. of T. 23 N., R. 5 E., resurveyed under this group.

Resurvey of the Subdivision of T. 24 N., R. 5 E.,  
4354

## Chains

N. 9° 29' W., bet. secs. 32 and 33.

Over mountainous land, through heavy timber and undergrowth.

Ascend 434 ft. over a steep SW. slope.

8.00 Slope changes; asc. over a S. slope.

19.00 High ridge, bears N. 80° W., and S. 80° E.; desc. 413 ft. over a NE. slope.

38.00 Slope changes; desc. over a NW. slope.

44.91 The  $\frac{1}{4}$  sec. cor., as evidenced by a limestone, 14x14x3 ins. firmly set in the ground, mkd.  $\frac{1}{4}$  on W. face.

Set an iron post, 3 ft. long, 1 in. diam., 28 ins. in the ground, with the old corner stone buried alongside, at  $\frac{1}{4}$  sec. cor., with brass cap mkd.

$\frac{1}{4}$   
S32 | S33  
1945

from which

## Old bearing trees:

An aspen, 10 ins. diam., bears N. 41 $\frac{1}{2}$ ° E., 4 lks. dist., markings overgrown, mark on overgrowth,  $\frac{1}{4}$  S 33 B T.

A fir, 14 ins. diam., bears S. 76 $\frac{1}{2}$ ° W., 31 lks. dist., markings overgrown, mark on overgrowth,  $\frac{1}{4}$  S 32 B T.

Thence,

N. 1° 32' E., bet. secs. 32 and 33.

Descend 333 ft. over a NW. slope.

0.40 Side hill drain, course W.

37.15 Ravine, course SW.; asc. 19 ft. over a SE. slope.

39.24 The cor. of secs. 28, 29, 32 and 33, as evidenced by sandstone, 18x12x5 ins., firmly set in the ground, mkd. 1 groove on S. and 4 grooves on E. faces, with a mound of stone, 3 ft. base, 1 ft. high, W. of cor.

Set an iron post, 3 ft. long, 2 ins. diam., 28 ins. in the ground, with the original corner stone buried alongside, at cor. of secs. 28, 29, 32 and 33, with brass cap mkd.

T24N R5E  
S29 | S28  
-----  
S32 | S33  
1945

from which

## Old bearing trees:

A pine, 12 ins. diam., bears S. 87 $\frac{3}{4}$ ° E., 27 lks. dist., markings overgrown, mark on overgrowth, T 24 N R 5 E S 33 B T.

A pine, 18 ins. diam., bears S. 72 $\frac{1}{4}$ ° W., 47 lks. dist., markings overgrown, mark on overgrowth

BOOK 4354

## Resurvey of the Subdivision of T. 24 N., R. 5 E.

## Chains

T 24 N R 5 E, S 32 B T.

A pine, 18 ins. diam., (now dead), bears N.  $63\frac{1}{2}^{\circ}$  W., 65 lks. dist., mkd. T 24 N R 5 E, other markings overgrown, not uncovered.

## New bearing trees:

A pine, 5 ins. diam., bears N.  $23^{\circ}$  E., 78 lks. dist., mkd. T 24 N R 5 E S 28 B T.

A pine, 12 ins. diam., bears N.  $51\frac{1}{4}^{\circ}$  W., 128 lks. dist., mkd. T 24 N R 5 E S 29 B T.

Land, mountainous.

Soil, rocky, 1st and 2nd rates.

Timber, pine and fir; undergrowth, 2nd growth timber.

-----  
From the cor. of secs. 27, 28, 33 and 34.

S.  $89^{\circ} 39'$  W., bet. secs. 28 and 33.

Over mountainous land, through heavy timber and dense undergrowth.

Descend gradually along a gentle N. slope.

3.80 Slope changes; desc. 24 ft. over a NW. slope.

8.75 Wash, 5 lks. wide, course N.  $10^{\circ}$  W., from SE.; continue descent 117 ft. over a gradual NW. slope.39.84 The  $\frac{1}{4}$  sec. cor., as evidenced by a lava stone, in place, 26x24x12 ins. above ground, mkd.  $\frac{1}{4} +$ , with a mound of stone, 3 ft. base, 1 ft. high, N. of cor.Set a brass tablet,  $3\frac{1}{2}$  ins. diam., 3 in. stem, in the original stone in place, at  $\frac{1}{4}$  sec. cor., mkd. on top.

S28  
-----  
 $\frac{1}{4}$   
S33  
1945

from which

## Old bearing trees:

The original position of a pine, 6 ins. diam., (now dead, lying on ground), bears S.  $30\frac{3}{4}^{\circ}$  E., 18 lks. dist., mkd.  $\frac{1}{4}$  S B T.

A pine, 12 ins. diam., bears S.  $83^{\circ}$  W., 24 lks. dist., markings overgrown, not uncovered.

## New bearing trees:

A pine, 5 ins. diam., bears N.  $54\frac{3}{4}^{\circ}$  E., 146 lks. dist., mkd.  $\frac{1}{4}$  S 28 B T.

A pine, 9 ins. diam., bears S.  $20\frac{1}{4}^{\circ}$  E., 20 lks. dist., mkd.  $\frac{1}{4}$  S 33 B T.

Thence,

S.  $89^{\circ} 17'$  W., bet. secs. 28 and 33.

Descend 14 ft. over a gradual NW. slope.

## Resurvey of the Subdivision of T. 24 N., R. 5 E.

4354

Chains	
3.00	Shallow draw, drains N.; asc. 62 ft. over gradual E. slope.
16.00	Base of steep ascent, bears N. and S.; asc. 125 ft. over a SE. slope.
23.10	Long spur, slopes N.; desc. 115 ft. over a NW. slope.
36.05	Ravine, course SW.; asc. 30 ft. over a SE. slope.
39.92	The cor. of secs. 28, 29, 32 and 33.

Land, mountainous.  
Soil, rocky, 1st and 2nd rates.  
Timber, pine and fir; undergrowth, 2nd growth timber.

-----  
N. 2° 48' W., bet. secs. 28 and 29.

Over mountainous land, through heavy timber and scattered undergrowth.

Ascend 30 ft. over a SE. slope.

5.00	Spur, slopes SW.; thence, along a broken SW. slope.
12.00	Head of a gulch, course W.; asc. 46 ft. over a S. slope.
17.00	Spur; slopes W.; along a broken W. slope.
25.00	Slope changes; asc. 83 ft. over a SW. slope.
33.00	Spur; slopes SW; continue ascent 23 ft. along a W. slope.
39.71	The $\frac{1}{4}$ sec. cor., as evidenced by a sandstone, 12x8x4 ins., firmly set in the ground, mkd. $\frac{1}{4}$ on W. face, with a mound of stone, 2 ft. base, 1 $\frac{1}{2}$ ft. high, W. of cor.

Set an iron post, 3 ft. long; 1 in. diam., 28 ins. in the ground, with the old corner stone buried alongside, at  $\frac{1}{4}$  sec. cor., with brass cap mkd.

$\frac{1}{4}$   
S29 | S28  
1945

from which

Old bearing trees:

A pine, 25 ins. diam., bears S. 18° E., 48 lks. dist., markings overgrown, not uncovered.

A pine, 32 ins. diam., bears N. 75° W., 65 lks. dist., mkd.  $\frac{1}{4}$  S B T.

New bearing trees:

A pine, 14 ins. diam., bears N. 48° E., 55 lks. dist., mkd.  $\frac{1}{4}$  S 28 B T.

A pine, 12 ins. diam., bears N. 20 $\frac{3}{4}$ ° W., 176 lks. dist., mkd.  $\frac{1}{4}$  S 29 B T.

Thence,

N. 1° 15' E., bet. secs. 28 and 29.

Along a W. slope.


BOOK 4354

Resurvey of the Subdivision of T. 24 N., R. 5 E.

Chains

- 13.10 Spur, slopes W.; desc. 146 ft. over a NW. slope.
- 35.80 Road, bears E. to Bull Basin and W. to Pumpkin Center.
- 39.98 The cor. of secs. 20, 21, 28 and 29, as evidenced by a lava stone, 18x18x14 ins., firmly set in the ground, mkd. 2 notches on S. and 4 notches on E. edges.

Set an iron post, 3 ft. long, 2 ins. diam., 28 ins. in the ground, with the old corner stone buried alongside, at cor. of secs. 20, 21, 28 and 29, with brass cap mkd.



from which

Old bearing trees:

A pine, 16 ins. diam., bears N. 42 $\frac{1}{2}$ ° E., 61 lks. dist., markings overgrown, mark on overgrowth, T 24 N R 5 E S 21 B T.

A pine stump, 28 ins. diam., bears S. 37° E., 120 lks. dist., mkd. T 24 N R 5 E S, other markings overgrown.

A pine, 18 ins. diam., bears S. 21 $\frac{3}{4}$ ° W., 59 lks. dist., markings overgrown, mark on overgrowth, T 24 N R 5 E S 29 B T.

A pine, 14 ins. diam., bears N. 6 $\frac{3}{4}$ ° W., 85 lks. dist., markings overgrown, mark on overgrowth, T 24 N R 5 E S 20 B T.

New bearing tree:

A pine, 12 ins. diam., bears S. 15° E., 146 lks. dist., mkd. T 24 N R 5 E S 28 B T.

Land mountainous.

Soil, rocky, 2nd and 3rd rates.

Timber, pine; undergrowth, 2nd growth pine.

-----

From the cor. of secs. 21, 22, 27 and 28.

S. 89° 18' W., bet. secs. 21 and 28.

Over mountainous land, through heavy timber and scattered undergrowth.

Ascend 77 ft. over a NE. slope.

- 17.50 Slope changes; asc. 158 ft. over a NE. slope.
- 25.00 Enter dense undergrowth, bears N. and S.
- 30.00 Low spur, slopes SE.; continue ascent 62 ft. along a S. slope.
- 35.10 Head of a ravine, course SE.; asc. 64 ft. over a SE. slope.
- 41.32 The  $\frac{1}{4}$  sec. cor., as evidenced by a lava stone, 16x10x3 ins., firmly set in the ground, mkd.  $\frac{1}{4}$  on N. face, with a mound of stone, 2 ft. base, 1 ft. high, N. of cor.

## Resurvey of the Subdivision of T. 24 N., R. 5 E.

4654

## Chains

Set an iron post, 3 ft. long, 1 in. diam., 27 ins. in the ground, with the old corner stone buried alongside, at  $\frac{1}{4}$  sec. cor., with brass cap mkd.

S21  
 $\frac{1}{4}$ -----  
S28  
1945

from which

## Old bearing tree:

A pine, 16 ins. diam., (partly dead), bears S.  $26^{\circ}$  W.; 41 lks. dist., markings overgrown, not uncovered.

## New bearing trees:

A pine, 9 ins. diam., bears N.  $3\frac{1}{2}^{\circ}$  E., 80 lks. dist., mkd.  $\frac{1}{4}$  S 21 B T.

A pine, 12 ins. diam., bears S.  $32\frac{3}{4}^{\circ}$  W., 44 lks. dist., mkd.  $\frac{1}{4}$  S 28 B T.

## Thence,

S.  $89^{\circ} 38'$  W., bet. secs. 21 and 28.

Ascend 21 ft. over a SE. slope.

2.00 Spur, slopes S.; desc. 75 ft. over a SW. slope.

9.40 Long spur, slopes NE.; a saddle in same, bears SW., about 15 chs. dist.; desc. 163 ft. over a SW. slope.

27.20 Slope changes; desc. 35 ft. over a W. slope.

35.00 Road, bears N., and S. to a junction with a road, which bears E. and W.

39.57 The cor. of secs. 20, 21, 28 and 29.

Land, mountainous.

Soil, rocky, 2nd and 3rd rates.

Timber, pine; undergrowth, 2nd growth pine.

-----  
N.  $0^{\circ} 18'$  E., bet. secs. 20 and 21.

Over mountainous land, through heavy timber and scattered undergrowth.

38.95 The  $\frac{1}{4}$  sec. cor., as evidenced by a malpais stone, 15x8x4 ins., firmly set in the ground; mkd.  $\frac{1}{4}$  on W. face, with a mound of stone, 2 ft. base, 1 ft. high, W. of cor.

Set an iron post, 3 ft. long, 1 in. diam., 6 ins. in the ground to solid rock, with the old corner stone buried alongside, and in a mound of stone to top, at  $\frac{1}{4}$  sec. cor., with brass cap mkd.

$\frac{1}{4}$   
S20 | S21  
1945

from which

## Old bearing trees:

The original position of a pine, 30 ins. diam., (now

BOOK 4354

## Resurvey of the Subdivision of T. 24 N., R. 5 E.

## Chains

dead, lying on ground), bears S.  $81\frac{1}{2}^{\circ}$  E., 53 lks. dist., markings illegible.

A pine, 24 ins. diam., bears S.  $56^{\circ}$  W., 42 lks. dist. markings overgrown, mark on overgrowth,  $\frac{1}{4}$  S 20 B T.

## New bearing tree:

A pine, 24 ins. diam., bears S.  $51^{\circ}$  E., 96 lks. dist., mkd.  $\frac{1}{4}$  S 21 B T.

## Thence,

N.  $3^{\circ} 06'$  E., bet. secs. 20 and 21.

Ascend 64 ft. over a SW. slope.

27.00 Spur, slopes NW.; desc. 65 ft. over a NE. slope.

39.96 The cor. of secs. 16, 17, 20 and 21, as evidenced by a lava stone, 10x10x8 ins., firmly set in the ground, mkd. 4 grooves on E. and 2 grooves on S. faces.

Set an iron post, 3 ft. long, 2 ins. diam., 28 ins. in the ground, with the old corner stone buried alongside, at cor. of secs. 16, 17, 20 and 21, with brass cap mkd.

T24N	R5E
S17	S16
S20	S21
1945	

from which

## Old bearing trees:

A pine, 20 ins. diam., (now dead), bears N.  $2\frac{3}{4}^{\circ}$  E., 15 lks. dist., mkd. T 24 N R 5 E S 16 B T.

A pine, 24 ins. diam., bears N.  $64\frac{3}{4}^{\circ}$  W., 54 lks. dist., mkd. T 24 N R 5 E S 17 B T.

A pine, 30 ins. diam., bears S.  $60\frac{1}{2}^{\circ}$  W., 136 lks. dist., markings overgrown, mark on overgrowth, T 24 N R 5 E S 20 B T.

A pine, 28 ins. diam., bears S.  $75\frac{1}{4}^{\circ}$  E., 51 lks. dist., markings overgrown, mark on overgrowth, T 24 N R 5 E S 21 B T.

## New bearing tree:

A pine, 8 ins. diam., bears N.  $55\frac{3}{4}^{\circ}$  E., 237 lks. dist., mkd. T 24 N R 5 E S 16 B T.

## Land, mountainous.

Soil, rocky, 2nd and 3rd rates.

Timber, pine; undergrowth, 2nd growth pine.

From the cor. of secs. 15, 16, 21 and 22.

S.  $89^{\circ} 18'$  W., bet. secs. 16 and 21.

Over mountainous land, through heavy timber and scattered undergrowth.

Ascend a gradual E. slope.

## Resurvey of the Subdivision of T. 24 N., R. 5 E.

Chains	
18.00	Top of ascent; desc. 30 ft. over a W. slope.
18.95	Gulch, course N.; asc. 20 ft. over a NE. slope.
23.45	Spur, slopes N.; desc. 19 ft. over a W. slope.
27.65	Wash, 5 lks. wide, course N.; asc. 175 ft. over a NE. slope.
39.95	The $\frac{1}{4}$ sec. cor., as evidenced by a lava stone, 16x16x10 ins., firmly set in a mound of stone, 2 ft. base, 1 ft. high, mkd. $\frac{1}{4}$ on N. face.
	Set an iron post, 3 ft. long, 1 in. diam., 28 ins. in the ground with the old corner stone buried alongside, at $\frac{1}{4}$ sec. cor. with brass cap mkd.
	$\frac{1}{4}$ S16 S21 1945
	from which
	Old bearing trees:
	A pine, 20 ins. diam., bears N. $3\frac{1}{2}^{\circ}$ W., 40 lks. dist., markings overgrown, mark on overgrowth, $\frac{1}{4}$ S 16 B T.
	A pine, 14 ins. diam., bears S. $70\frac{1}{2}^{\circ}$ W., 33 lks. dist., dead and fallen, marked $\frac{1}{4}$ S B T.
	New bearing tree:
	A pine, 16 ins. diam., bears S. $44\frac{1}{2}^{\circ}$ E., 52 lks. dist., mkd. $\frac{1}{4}$ S 21 B T.
	Thence,
	S. $89^{\circ}$ 14' W., bet. secs. 16 and 21.
	Ascend 73 ft. over a NE. slope.
4.75	Spur, slopes NW.; desc. 127 ft. over a SW. slope.
24.65	Foot of descent; asc. 52 ft. over a gradual NE. slope.
39.72	The cor. of secs. 16, 17, 20 and 21.
	Land, mountainous.
	Soil, rocky, 2nd and 3rd rates.
	Timber, pine; undergrowth, 2nd growth pine.
	N. $1^{\circ}$ 50' W., bet. secs. 16 and 17.
	Over mountainous land, through heavy timber and dense undergrowth.
	Ascend 103 ft. over a SW. slope.
13.30	Spur, slopes E.; desc. 518 ft. over a NE. slope.
21.00	Cliff, 40 ft. high, bears E. and W.
33.00	Gulch, course NW.; asc. 50 ft. over a SW. slope.
38.00	Spur, slopes W.; desc. 24 ft. over a NW. slope.
40.58	The $\frac{1}{4}$ sec. cor., as evidenced by a lava stone, 12x10x8 ins. set in a mound of stone, 2 ft. base, 1 ft. high, mkd. $\frac{1}{4}$ on W. face.
	Set an iron post, 3 ft. long, 1 in. diam., 28 ins. in the ground, with the old corner stone buried alongside, at $\frac{1}{4}$ sec. cor., with brass cap mkd.
	$\frac{1}{4}$ S17 S16 1945
	from which

## Resurvey of the Subdivision of T. 24 N., R. 5 E.

Chains	<p>Old bearing trees:</p> <p>A pine, 16 ins. diam., bears N. <math>67\frac{1}{2}^{\circ}</math>E., 30 lks. dist., markings overgrown, mark on overgrowth, <math>\frac{1}{4}</math> S 16 B T.</p> <p>A pine, 12 ins. diam., bears N. <math>23\frac{1}{2}^{\circ}</math>W., 14 lks. dist., mkd. <math>\frac{1}{4}</math> S B T.; additionally mark this tree <math>\frac{1}{4}</math> S 17 B T.</p> <p>Thence,</p> <p>N. <math>1^{\circ}</math> 16' W., bet. secs. 16 and 17.</p> <p>Descend 130 ft. over a NW. slope.</p> <p>8.20 Wash, 20 lks. wide, course NE.; continue descent of 115 ft. along an E. slope.</p> <p>39.61 The cor. of secs. 8, 9, 16 and 17, as evidenced by a sandstone, 16x12x8 ins., firmly set in the ground, marked 4 grooves on S. and 4 grooves on E. faces, with a mound of stone, 2 ft. base, 1 ft. high, W. of cor.</p> <p>Set an iron post, 3 ft. long, 2 ins. diam., 26 ins. in the ground, with the old corner stone buried alongside, and in a mound of stone to top, at cor. of secs. 8, 9, 16 and 17, with brass cap mkd.</p> <p style="text-align: center;">T24N R5E S 8   S 9 S17   S16 1945</p> <p style="text-align: right;">from which</p> <p>Old bearing trees:</p> <p>A pine, 20 ins. diam., bears N. <math>38\frac{1}{2}^{\circ}</math>E., 50 lks. dist., markings overgrown, mark on overgrowth T 24 N R 5 E S 9 B T.</p> <p>A pine, 24 ins. diam., bears S. <math>74\frac{1}{2}^{\circ}</math>E., 120 lks. dist., mkd. T 24 N R 5 E S 16 B T.</p> <p>A pine, 18 ins. diam., bears S. <math>56^{\circ}</math> W., 21 lks. dist., markings overgrown, mark on overgrowth, T 24 N R 5 E S 17 B T.</p> <p>A pine, 28 ins. diam., bears N. <math>66^{\circ}</math> W., 90 lks. dist., markings overgrown, mark on overgrowth, T 24 N R 5 E S 8 B T.</p> <p>Land, mountainous. Soil, rocky, 2nd and 3rd rates. Timber, pine; undergrowth, 2nd growth pine.</p> <p>-----</p> <p>From the cor. of secs. 9, 10, 15 and 16.</p> <p>S. <math>89^{\circ}</math> 37' W., bet. secs. 9 and 16.</p> <p>Over mountainous land, through heavy timber and scattering undergrowth.</p> <p>Descend 107 ft. over a W. slope.</p> <p>8.15 Wash, 10 lks. wide, course N.; asc. 149 ft. over an E. slope.</p> <p>30.00 Spur, slopes N.; desc. 78 ft. along a S. slope.</p> <p>41.43 The <math>\frac{1}{4}</math> sec. cor., as evidenced by a sandstone, 12x10x8 ins. firmly set in the ground, mkd. <math>\frac{1}{4}</math> on N. face, with a mound of stone, 2 ft. base, 1 ft. high, N. of cor.</p> <p>Set an iron post, 3 ft. long, 1 in. diam., 20 ins. in the ground to solid rock, with the original corner stone buried alongside, and in a mound of stone to top, at <math>\frac{1}{4}</math> sec. cor., with brass cap mkd.</p>
--------	---

## Resurvey of the Subdivision of T. 24 N., R. 5 E.

4354

## Chains

$$\frac{1}{4} \frac{S9}{S16}$$
 1945

from which

## Old bearing tree:

A pine, 18 ins. diam., bears N.  $50\frac{3}{4}^{\circ}$  W., 25 lks. dist., markings overgrown, mark on overgrowth,  $\frac{1}{4}$  S 9 B T.

## New bearing tree:

A pine, 5 ins. diam., bears S.  $39^{\circ}$  E., 18 lks. dist., mkd.  $\frac{1}{4}$  S 16 B T.

Thence,

S.  $89^{\circ} 45'$  W., bet. secs. 9 and 16.

Descend 28 ft. over a W. slope.

- 1.60 Gulch, course N.; asc. 120 ft. over an E. slope.  
 10.00 Spur, slopes N.; desc. 209 ft. over a NW. slope.  
 24.70 Wash, 20 lks. wide, course N.; asc. 34 ft. over a gradual E. slope.  
 39.69 The cor. of secs. 8, 9, 16 and 17.

Land, mountainous.

Soil, rocky, 2nd and 3rd rates.

Timber, pine; undergrowth, 2nd growth pine.

-----  
N.  $0^{\circ} 06'$  E., bet. secs. 8 and 9.

Over rolling land, through heavy timber and scattered undergrowth.

Descend 147 ft. over a gradual NE. slope.

- 7.13 From this point, the center of the top of a concrete tank, 8x8x8 ft., at Mudersbach Spring, bears S.  $55^{\circ} 45'$  W., 3.40 chains dist.  
 9.00 Road, bears NE. and SW. to spring  
 23.20 Recross road, bears NW. and SE.  
 33.10 Wash, 5 lks. wide, course NW.  
 39.99 The  $\frac{1}{4}$  sec. cor., as evidenced by a sandstone, 12x10x6 ins. firmly set in the ground, mkd.  $\frac{1}{4}$  on W. face, with a scattered mound of stone, W. of cor.

Set an iron post, 3 ft. long, 1 in. diam., 28 ins. in the ground, with the old corner stone buried alongside, at  $\frac{1}{4}$  sec. cor., with brass cap mkd.

$$\frac{1}{4} \frac{S8}{S9}$$
 1945

from which

## Resurvey of the Subdivision of T. 24 N., R. 5 E.

## Chains

## Old bearing trees:

The original position of a pine, 30 ins. diam., (now dead, lying on the ground), bears N.  $30\frac{3}{4}^{\circ}$  W., 79 lks. dist., mkd.  $\frac{1}{4}$  S B T.

A pine, 32 ins. diam., bears N.  $30^{\circ}$  E., 102 lks. dist., markings overgrown, mark on overgrowth,  $\frac{1}{4}$  S 9 B. T.

## New bearing tree:

A pine, 8 ins. diam., bears N.  $54^{\circ}$  W., 58 lks. dist., mkd.  $\frac{1}{4}$  S 8 B T.

Thence,

NORTH, bet. secs. 8 and 9.

14.00 Recross wash, .5 lks. wide, course NE.

25.00 Enter scattered timber, bears E. and W.

29.50 Wash, 20 lks. wide, course W.; asc. gradual S. slope.

39.99 The cor. of secs. 4, 5, 8 and 9, as evidenced by a lava stone, 12x10x10 ins., firmly set in the ground, mkd. 5 grooves on S. and 4 grooves on E. faces, with a mound of stone,  $2\frac{1}{2}$  ft. base, 1 ft. high, W. of cor.

Set an iron post, 3 ft. long, 2 ins. diam., 28 ins. in the ground, with the old corner stone buried alongside, at cor. of secs. 4, 5, 8 and 9, with brass cap mkd.

T24N R5E	
S5	S4
S8	S9
1945	

from which

A pine, 6 ins. diam., bears N.  $33\frac{3}{4}^{\circ}$  E., 42 lks. dist., mkd. T 24 N R 5 E S 4 B T.

A pine, 5 ins. diam., bears S.  $26^{\circ}$  E., 8 lks. dist., mkd. T 24 N R 5 E S 9 B T.

A pine, 6 ins. diam., bears S.  $33\frac{3}{4}^{\circ}$  W., 116 lks. dist., mkd. T 24 N R 5 E S 8 B T.

A pine, 7 ins. diam., bears N.  $55^{\circ}$  W., 114 lks. dist., mkd. T 24 N R 5 E S 5 B T.

Land, rolling.

Soil, rocky, 2nd and 3rd rates.

Timber, pine; undergrowth, 2nd growth pine.

From the cor. of secs. 3, 4, 9 and 10.

N.  $89^{\circ} 27'$  W., bet. secs. 4 and 9.

Over nearly level land, through scattered timber and undergrowth.

0.07 A six wire drift fence, bears N. and S.

39.98 The  $\frac{1}{4}$  sec. cor., as evidenced by a lava stone, 20x14x12 ins., firmly set in the ground, mkd.  $\frac{1}{4}$  on N. face, with a mound of stone, 3 ft. base, 10 ins. high, N. of cor.

## Resurvey of the Subdivision of T. 24 N., R. 5 E.

4854

Chains

Set an iron post, 3 ft. long, 1 in. diam., 27 ins. in the ground, with the old corner stone buried alongside, at  $\frac{1}{4}$  sec. cor., with brass cap mkd.

$$\begin{array}{r} S4 \\ \frac{1}{4} \text{---} \\ .S9 \\ 1945 \end{array}$$

from which

A pine, 6 ins. diam., bears N.  $71^\circ$  E., 160 lks. dist., mkd.  $\frac{1}{4}$  S 4 B T.

A pine, 4 ins. diam., bears S.  $31\frac{3}{4}^\circ$  E., 69 lks. dist., mkd.  $\frac{1}{4}$  S 9 B T.

Thence,

S.  $89^\circ 33'$  W., bet. secs. 4 and 9.

32.50 Enter heavy timber and dense undergrowth, bears SE. and NW.; enter rolling land, bears SE. and NW.; desc. 28 ft. over a SW. slope.

39.97 The cor. of secs. 4, 5, 8 and 9.

Land, W. 10 chs. rolling; remainder of mile, nearly level. Soil, rocky, 2nd and 3rd rates. Timber, pine; undergrowth, 2nd growth pine.

N.  $1^\circ 01'$  E., bet. secs. 4 and 5.

Over rolling land, through heavy timber and dense undergrowth.

Ascend 22 ft. over a SW. slope.

5.00 Leave heavy timber, bears NW. and SE.

7.50 Enter scattered 2nd growth pine and nearly level land, bears NW. and SE.; asc. gradual SW. slope.

40.10 The  $\frac{1}{4}$  sec. cor., as evidenced by a lava stone, 16x14x4 ins., firmly set in the ground, mkd.  $\frac{1}{4}$  on W. face, with a mound of stone, 2 ft. base, 1 ft. high, W. of cor.

Set an iron post, 3 ft. long, 1 in. diam., 28 ins. in the ground, with the old corner stone buried alongside, at  $\frac{1}{4}$  sec. cor., with brass cap mkd.

$$\begin{array}{r} \frac{1}{4} \\ S5 | S4 \\ 1945 \end{array}$$

from which

A pine, 6 ins. diam., bears S.  $18\frac{1}{4}^\circ$  E., 498 lks. dist., mkd.  $\frac{1}{4}$  S 4 B T.

A pinon, 14 ins. diam., bears S.  $73\frac{1}{4}^\circ$  W., 234 lks. dist., mkd.  $\frac{1}{4}$  S 5 B T.

A U. S. Geological Survey Bench Mark, as evidenced by a brass tablet, 4 ins. diam., seated in a lava stone in place, 36x24x12 ins. above ground, with top mkd.

ELEVATION  
ABOVE SEA  
7001 FEET  
DATUM  
1907

bears

N. 65° 23' W., 19.67 chs. dist.

This Bench Mark is situated about 15 ft. S. of a graded road.

The 1/4 sec. cor. is under a wire fence, which bears N. 80° E. and N. 85 1/4° W.

Thence,

N. 15° 41' E., bet. secs. 4 and 5.

5.70 Graded road, bears E. and W.

10.00 Enter rolling land; top of ascent, bears E. and W.; desc. 34 ft. over a N. slope.

22.73 A point on the 6th Standard Parallel North, determined by proportion.

Set an iron post, 3 ft. long, 2 ins. diam., 16 ins. in the ground to solid rock, and in a mound of stone to top, at closing corner of secs. 4 and 5, with brass cap mkd.

T25N R5E  
S32  
S5 S4  
T24N R5E  
C C  
1945

from which

A pine, 20 ins. diam., bears S. 82 1/2° E., 71 lks. dist., mkd. T 24 N R 5 E S 4 C C B T.

A pine, 22 ins. diam., bears S. 61 1/2° W., 32 lks. dist., mkd. T 24 N R 5 E S 5 C C B T.

From the closing corner, the standard 1/4 sec. cor., on the S. bdy. of sec. 32, T. 25 N., R. 5 E., bears S. 89° 41' W., 11.74 chs. dist.

Land, S. 7.50 chs. and N. 10.00 chs. of mile rolling; remainder of mile, nearly level.  
Soil, rocky, 2nd and 3rd rates.  
Timber, pine and pinon; undergrowth, 2nd growth pine.

-----  
At midpoint on the N. bdy. of sec. 4.

Set an iron post, 3 ft. long, 1 in. diam., 28 ins. in the ground, at 1/4 sec. cor. of sec. 4, with brass cap mkd.

1/4 S4  
1945

from which

A cedar, 3 ins. diam., bears S. 70 1/2° E., 154 lks. dist., mkd. B T.

A pine, 4 ins. diam., bears S. 21 3/4° W., 420 lks. dist., mkd. 1/4 S 4 B T.

## Resurvey of the Subdivision of T. 24 N., R. 5 E.

BOOK 4854

## Chains

From this corner, the standard corner of secs. 32 and 33, T. 25 N., R. 5 E., bears S.  $89^{\circ} 37'$  W., 11.31 chs. dist.

-----

From the cor. of secs. 5, 6, 31 and 32, on the S. bdy. of the Tp., as evidenced by an iron post, 2 ins. diam., firmly set in the ground, mkd. and witnessed as described in the field notes of the N. bdy. of T. 23 N., R. 5 E., resurveyed under this group.

N.  $4^{\circ} 12'$  W., bet. secs. 31 and 32.

Over mountainous land, through heavy timber and undergrowth.

Ascend a gradual SE. slope.

- 5.80 Spur, slopes SW.
- 12.80 Ridge, bears E. and W.
- 20.00 Spur, slopes NE.
- 26.00 Recross spur, slopes NW.; desc. 159 ft. over a NE. slope.
- 32.90 Gulch, course NW.; asc. 137 ft. over a broken SW. slope.
- 39.20 Spur, slopes W.; desc. 47 ft. over a NW. slope.
- 41.41 Proportional distance,  
Set an iron post, 3 ft. long, 1 in. diam., 20 ins. in the ground to solid rock, and in a mound of stone to top, at  $\frac{1}{4}$  sec. cor., with brass cap mkd.

$\frac{1}{4}$   
S31 | S32

1945

from which

A fir, 10 ins. diam., bears N.  $87^{\circ}$  E., 30 lks. dist., mkd.  $\frac{1}{4}$  S 32 B T.

A pine, 20 ins. diam., bears S.  $73^{\circ}$  W., 66 lks. dist., mkd.  $\frac{1}{4}$  S 31 B T.

Descend 182 ft. over a broken NW. slope.

- 51.55 Drain, course W.
- 66.40 Gulch, course NW.
- 67.50 Spur, slopes NW.; desc. 46 ft. over a NE. slope.
- 69.50 Gulch, near head, course NW.; asc. 104 ft. over a S. slope.
- 77.30 Spur, slopes W.; thence, over a broken NW. slope.
- 77.90 Old road, bears E. and W.
- 82.82 The cor. of secs. 29, 30, 31 and 32, as evidenced by a sandstone, 18x14x6 ins., firmly set in the ground, mkd. 1 notch on S. and 5 notches on E. edges.
- Set an iron post, 3 ft. long, 2 ins. diam., 28 ins. in the ground, with the old corner stone buried alongside, at cor. of secs. 29, 30, 31 and 32, with brass cap mkd.

Resurvey of the Subdivision of T. 24 N., R. 5 E.

Chains

T24N R5E  
 S30|S29  
 S31|S32  
 1945

from which

Old bearing trees:

A pine, 24 ins. diam., bears N.  $76\frac{1}{2}^\circ$  E., 62 lks. dist., mkd T 24 N R 5 E S 29 B T.

A pine, 24 ins. diam., (now dead), bears S.  $68^\circ$  E., 117 lks. dist., markings overgrown.

A pine, 10 ins. diam., bears S.  $72^\circ$  W., 112 lks. dist., markings overgrown, mark on overgrowth, T 24 N R 5 E S 31 B T.

A pine, 36 ins. diam., (now dead), bears N.  $30\frac{1}{4}^\circ$  W., 41 lks. dist., markings illegible.

New bearing trees:

A pine, 12 ins. diam., bears S.  $39\frac{1}{2}^\circ$  E., 160 lks. dist., mkd. T 24 N R 5 E S 32 B T.

A pine, 20 ins. diam., bears N.  $67\frac{1}{2}^\circ$  W., 119 lks. dist., mkd. T 24 N R 5 E S 30 B T.

Land, mountainous.

Soil, rocky, 2nd and 3rd rates.

Timber, Pine and fir; undergrowth, 2nd growth timber.

-----  
 From the cor. of secs. 28, 29, 32 and 33.

S.  $89^\circ 31'$  W., bet. secs. 29 and 32.

Over mountainous land, through heavy timber and dense undergrowth.

Ascend gradually over a SE. slope.

1.40 Short spur, slopes S.; desc. 38 ft. over a SW. slope.

4.60 Ravine, course NW.; thence, along a gentle N. slope.

23.30 Low, short spur, slopes N.; desc. 34 ft. over a gradual NW. slope.

35.70 Road, bears N. and S.; foot of ascent, bears N. and S.; asc. 13 ft. over a NE. slope.

39.73 The  $\frac{1}{4}$  sec. cor., as evidenced by a slate rock, 16x10x5 ins., firmly set in the ground, mkd.  $\frac{1}{4}$  on N. face.

Set an iron post, 3 ft. long, 1 in. diam., 27 ins. in the ground, with the old corner stone buried alongside, at  $\frac{1}{4}$  sec. cor., with brass cap mkd.

S29  
 $\frac{1}{4}$   
 S32  
 1945

from which

A pine, 8 ins. diam., bears N.  $51^\circ$  W., 50 lks. dist., mkd.  $\frac{1}{4}$  S 29 B T.

## Resurvey of the Subdivision of T. 24 N., R. 5 E.

BOOK 2354

## Chains

A pine, 8 ins. diam., bears S.  $55\frac{3}{4}^{\circ}$  E., 36 lks. dist., mkd.  $\frac{1}{4}$  S 32 B T.

Thence,

N.  $89^{\circ} 32'$  W., bet. secs. 29 and 32.

Ascend over a gradual NE. slope.

- 2.40 Spur, slopes N.  $20^{\circ}$  W.; desc. 94 ft. over a SW. slope.  
 10.80 Head of a gulch, course SW.; asc. 10 ft. over a SE. slope.  
 15.70 Low, flat spur, slopes SW.; desc. 284 ft. over a SW. slope.  
 31.60 Gulch, course NW.; asc. 51 ft. over a NE. slope.  
 38.50 Spur, slopes NW.  
 39.75 The cor. of secs. 29, 30, 31 and 32.

Land, mountainous.

Soil, rocky, 2nd and 3rd rates.

Timber, pine; undergrowth, 2nd growth pine.

-----  
 S.  $87^{\circ} 10'$  W., bet. secs. 30 and 31.

Over mountainous land, through heavy timber and undergrowth.

Descend 69 ft. along a SW. slope.

- 10.00 Slope changes; continue descent along a broken N. slope.  
 15.00 Spur, slopes N.; desc. 84 ft. over a SW. slope.  
 21.00 Ravine, near head, course NW.; asc. 44 ft. over a NE. slope.  
 27.80 Spur, slopes NW.; desc. 21 ft. along a N. slope.  
 31.04 The  $\frac{1}{4}$  sec. cor., as evidenced by a sandstone, 16x12x8 ins. firmly set in the ground, mkd.  $\frac{1}{4}$  on N. face.

Set an iron post, 3 ft. long, 1 in. diam., 12 ins. in the ground, to bedrock, with the old corner stone buried alongside, and in a mound of stone to top, at  $\frac{1}{4}$  sec. cor., with brass cap mkd.

S30  
 $\frac{1}{4}$ -----  
 S31  
 1945

from which

Old bearing trees:

A pine, 18 ins. diam., bears S.  $58\frac{3}{4}^{\circ}$  E., 65 lks. dist., markings overgrown, mark on overgrowth,  $\frac{1}{4}$  S 31 B T.

A pine, 17 ins. diam., bears S.  $59\frac{3}{4}^{\circ}$  W., 9 lks. dist., markings overgrown.

New bearing tree:

A pine, 20 ins. diam., bears N.  $42\frac{1}{2}^{\circ}$  W., 56 lks. dist., mkd.  $\frac{1}{4}$  S 30 B T.

## Resurvey of the Subdivision of T. 24 N., R. 5 E.

## Chains

Thence,

N.  $74^{\circ} 58'$  W., bet. secs. 30 and 31.

Descend 168 ft. over a W. slope.

19.10 Foot of descent, bears N. and S.; thence, over level land.

23.21 Road, bears N. and S.

24.20 Wire fence, bears N. and S.

28.80 Wire fence, bears about N.  $70^{\circ}$  E. and S.  $70^{\circ}$  W.

31.28 The original closing corner of secs. 30 and 31, determined from the old bearing trees.

Set a sandstone, 14x12x8 ins., 12 ins. below the surface of the ground, mkd. W P on top, from which

Old bearing trees:

A pine, 30 ins. diam., bears N.  $53\frac{1}{2}^{\circ}$  E., 178 lks. dist., mkd. N R 5 E S B T ; remainder of markings illegible; additionally mark this tree W P.A pine, 30 ins. diam., bears N.  $60\frac{1}{4}^{\circ}$  E., 201 lks. dist., mkd. N R 5 E S 30 B T ; remainder of markings illegible ; additionally mark this tree W P.The original position of a pine, 32 ins. diam., (now dead lying on ground), bears N.  $69\frac{1}{2}^{\circ}$  E., 193 lks. dist., markings indiscernible.

Witness point is located in a cultivated field.

32.40 Intersect the W. bdy. of the Tp.

Set an iron post, 3 ft. long, 2 ins. diam., 12 ins. below the surface of the ground, at closing corner of secs. 30 and 31, with brass cap mkd.

T24N	T24N	
	S30	
R4E	S31	CC
S25	R5E	
1945		

from which

A pine, 7 ins. diam., bears N.  $80^{\circ}$  E., 288 lks. dist., mkd. T 24 N R 5 E S 30 C C B T.A pine, 5 ins. diam., bears S.  $73^{\circ}$  E., 260 lks. dist., mkd. T 24 N R 5 E S 31 C C B T.

This closing corner is located in a cultivated field.

From the closing corner, the angle point of secs. 25 and 31, bears S.  $0^{\circ} 19'$  E., 14.91 chains dist.

Land; W. 13 chs., nearly level; remainder of mile mountainous.

Soil, on nearly level land, gravelly, 2nd rate; on mountainous land, rocky, 3rd rate.

Timber, pine; undergrowth, 2nd growth pine.

-----  
At midpoint on the W. bdy. of sec. 31.

## Resurvey of the Subdivision of T. 24 N., R. 5 E.

BOOK 4354

## Chains

Set an iron post, 3 ft. long, 1 in. diam., 28 ins. in the ground, at  $\frac{1}{4}$  sec. cor. of sec. 31, with brass cap mkd.

$$\left| \frac{1}{4} \text{ S31} \right.$$

1945

from which

A pine, 8 ins. diam., bears N.  $55\frac{1}{2}^{\circ}$  E., 115 lks. dist., mkd.  $\frac{1}{4}$  S 31 B T.

A pine, 10 ins. diam., bears S.  $71\frac{3}{4}^{\circ}$  E., 217 lks. dist., mkd.  $\frac{1}{4}$  S 31 B T.

The NE. corner of Marlar's House, bears N.  $89^{\circ} 20'$  W., 2.00 chains dist.

From this corner, the angle point of secs. 31 and 36, bears S.  $0^{\circ} 48'$  W., 11.01 chs. dist.

From the cor. of secs. 29, 30, 31 and 32.

N.  $2^{\circ} 47'$  E., bet. secs. 29 and 30.

Over mountainous land, through heavy timber and dense undergrowth.

Descend 105 ft. over a N. slope.

4.90 Wash, 10 lks. wide, course W.; asc. 85 ft. over a SW. slope.

10.40 Spur, slopes W.; desc. 117 ft. over a NW. slope.

29.00 Gulch, course NW.; asc. 176 ft. over a SW. slope.

39.96 Proportional distance.

Set an iron post, 3 ft. long, 1 in. diam., 28 ins. in the ground, at  $\frac{1}{4}$  sec. cor., with brass cap mkd.

$$\frac{1}{4} \text{ S30 | S29}$$

1945

from which

A pine, 6 ins. diam., bears N.  $65^{\circ}$  E., 30 lks. dist., mkd.  $\frac{1}{4}$  S 29 B T.

A pine, 6 ins. diam., bears N.  $64\frac{3}{4}^{\circ}$  W., 24 lks. dist., mkd.  $\frac{1}{4}$  S 30 B T.

Ascend 413 ft. over a SW. slope.

64.00 Top of a hill on a spur, slopes NW.; desc. 203 ft. over a NE. slope.

76.90 Gulch, course NW.; asc. 20 ft. over a SW. slope.

79.92 At this point, determined by the method of double proportional measurement.

Set an iron post, 3 ft. long, 2 ins. diam., 28 ins. in the ground, at cor. of secs. 19, 20, 29 and 30, with brass cap mkd.

## Resurvey of the Subdivision of T. 24 N., R. 5 E.

Chains

T24N R5E	
S19	S20
S30	S29
1945	

from which

A pine, 30 ins. diam., bears N. 64° E., 20 lks.  
dist., mkd. T 24 N R 5 E S 20 B T.

A pine, 6 ins. diam., bears S. 23½° E., 78 lks.  
dist., mkd. T 24 N R 5 E S 29 B T.

A pine, 15 ins. diam., bears S. 46½° W., 33 lks.  
dist., mkd. T 24 N R 5 E S 30 B T.

A pine, 30 ins. diam., bears N. 9½° W., 67 lks.  
dist., mkd. T 24 N R 5 E S 19 B T.

Land, mountainous.

Soil, rocky, 2nd and 3rd rates.

Timber, pine; undergrowth, 2nd growth pine.

-----  
From the cor. of secs. 20, 21, 28 and 29.

S. 89° 47' W., bet. secs. 20 and 29.

Over rolling land, through heavy timber and scattered undergrowth.

Ascend 54 ft. over a gradual E. slope.

14.40 Spur, slopes N.; desc. 34 ft. over a gradual W. slope.

19.70 Leave timber and undergrowth, bears N. and S.

26.90 Road, bears NW. to Pumpkin Center and SE. to Bull Basin;  
foot of descent, bears N. and S.; asc. 61 ft. over a  
gradual E. slope.

35.00 Enter timber, bears N. and S.

38.70 Spur, slopes S.; descend gradual NW. slope.

39.94 The ¼ sec. cor., as evidenced by a sandstone 14x12x8 ins.,  
firmly set in the ground, marked ¼ on N. face, with a  
mound of stone, 1½ ft. base, 1 ft. high, N. of cor.

Set an iron post, 3 ft. long, 1 in. diam., 28 ins. in the  
ground, with the old corner stone buried alongside, at ¼  
sec. cor., with brass cap mkd.

S20	
¼	-----
S29	
1945	

from which

A pine, 6 ins. diam., bears N. 21¾° W., 61 lks.  
dist., mkd. ¼ S 20 B T.

A pine, 10 ins. diam., bears S. 47° W., 26 lks.  
dist., mkd. ¼ S 29 B T.

Thence,

N. 89° 33' W., bet. secs. 20 and 29.

Descend 112 ft. over a NW. slope.

## Resurvey of the Subdivision of T. 24 N., R. 5 E.

BOOK 4854

Chains	
14.20	Gulch, course SW.; asc. 38 ft. over a SE. slope.
25.20	Spur, slopes SW.; desc. 23 ft. along a S. slope.
30.00	Foot of descent; asc. 15 ft. over a SE. slope.
33.40	Top of ascent, bears N. and S.; desc. 20 ft. over a W. slope.
34.56	The cor. of secs. 19, 20, 29 and 30.  Land, rolling. Soil, rocky, 2nd and 3rd rates. Timber, pine; undergrowth, 2nd growth pine.
-----	
	S. 87° 24' W., bet. secs. 19 and 30.  Over mountainous land, through heavy timber and dense undergrowth.  Descend 30 ft. over a W. slope.
2.00	Gulch, course NW.; asc. 50 ft. over a NE. slope.
5.70	Short spur, slopes N. 20° W.; desc. along a N. slope.
11.50	Spur, slopes NW.; thence, along S. slope of same.
14.60	Rocky point of same spur, slopes SW.; descend 100 ft. over cliffs.
17.00	Wash, in bottom of canyon, course S.; asc. 100 ft. over an E. slope.
20.40	West rim of canyon, bears NW. and SE.; continue ascent of 60 ft. over a SE. slope.
34.64	The $\frac{1}{4}$ sec. cor., as evidenced by a sandstone, 15x12x10 ins., firmly set in the ground, mkd. $\frac{1}{4}$ on N. face, with a mound of stone, 2 ft. base, 1 ft. high, N. of cor.  Set an iron post, 3 ft. long, 1 in. diam., 28 ins. in the ground, with the old corner stone buried alongside, at $\frac{1}{4}$ sec. cor., with brass cap mkd.
	$\begin{array}{r} S19 \\ \hline \frac{1}{4} \\ S30 \\ 1945 \end{array}$
	from which
	Old bearing trees:
	The original position of a pine, 12 ins. diam., (now dead, lying on ground), bears N. 63 $\frac{1}{2}$ ° E., 27 lks. dist., mkd. $\frac{1}{4}$ S B T.
	A pine, 20 ins. diam., bears N. 50 $\frac{1}{2}$ ° W., 44 lks. dist., mkd. $\frac{1}{4}$ S B T. Additionally mark this tree, $\frac{1}{4}$ S 19 B T.
	New bearing tree:
	A pine, 14 ins. diam., bears S. 10 $\frac{1}{2}$ ° E., 39 lks. dist., mkd. $\frac{1}{4}$ S 30 B T.
	Thence,

## Resurvey of the Subdivision of T. 24 N., R. 5 E.

## Chains

N. 89° 25' W., bet. secs. 19 and 30.

Begin descent along top of a spur, slopes W.

31.39 The original closing corner of secs. 19 and 30, as evidenced by a sandstone, 16x12x8 ins., firmly set in the ground, mkd. 2 grooves on S., 4 grooves on N. and 6 grooves on E. faces. Additionally mark this stone W P on W. face, from which

Old bearing trees:

A pine, 24 ins. diam., bears N. 76½° W., 45 lks. dist., markings overgrown, mark on overgrowth, W P.

A pine, 14 ins. diam., (now dead), bears S. 64° E., 84 lks. dist., mkd. T 24 N R 5 E S 30 B T.

31.59 Intersect the W. bdy. of the Tp.

Set an iron post, 3 ft. long, 2 ins. diam., 25 ins. in the ground to bedrock, and in a mound of stone to top, at closing corner of secs. 19 and 30, with brass cap mkd.

T24N	T24N	
	S19	
R4E	S30	CC
S24	R5E	
	1945	

from which

A pine, 10 ins. diam., bears N. 81¼° E., 29 lks. dist., mkd. T 24 N. R 5 E S 19 C C B T.

A pine, 12 ins. diam., bears S. 30° E., 46 lks. dist., mkd. T 24 N R 5 E S 30 C C B T.

From the closing corner, the angle point of secs. 24 and 30, bears S. 0° 07' W., 8.29 chs. dist.

Land, mountainous.

Soil, rocky clay, 4th rate.

Timber, pine, fir and juniper; undergrowth, 2nd growth timber and algerita.

At midpoint on the W. bdy. of sec. 30.

Set an iron post, 3 ft. long, 1 in. diam., 28 ins. in the ground, at ¼ sec. cor. of sec. 30, with brass cap mkd.

¼ S30
-------

1945

from which

A pine, 7 ins. diam., bears N. 70¾° E., 53 lks. dist., mkd. ¼ S 30 B T.

A pine, 4 ins. diam., bears S. 35° E., 41 lks. dist., mkd. ¼ S 30 B T.

From this cor., the angle point of secs. 25 and 30, bears S. 0° 18' E., 10.82 chs. dist.

## Resurvey of the Subdivision of T. 24 N., R. 5 E.

4354

Chains	
	From the cor. of secs. 19, 20, 29 and 30.
	N. 1° 35' W., bet. secs. 19 and 20.
	Over mountainous land, through heavy timber and scattered undergrowth.
	Ascend 75 ft. over a S. slope.
10.20	Road, bears W. for 2 chs., then NW. to Pumpkin Center and NE. to Bull Basin; spur, slopes W. for 5 chs., then NW.; desc. 92 ft. over a NE. slope.
19.30	Gulch, course NW.; asc. 157 ft. over a SW. slope.
35.00	Spur, slopes NW.; desc. a gradual NW. slope.
39.93	Proportional distance.
	Set an iron post, 3 ft. long, 1 in. diam., 28 ins. in the ground, at $\frac{1}{4}$ sec. cor., with brass cap mkd.
	$\begin{array}{c} \frac{1}{4} \\ \hline S19   S20 \\ \hline 1945 \end{array}$
	from which
	A pine, 24 ins. diam., bears S. 45½° E., 46 lks. dist., mkd. $\frac{1}{4}$ S 20 B T.
	A pine, 14 ins. diam., bears S. 53° W., 68 lks. dist., mkd. $\frac{1}{4}$ S 19 B T.
	Descend a gradual NW. slope.
46.80	Gulch, course W.; asc. gradual SW. slope.
50.60	Spur, slopes W.; desc. 60 ft. over a N. slope.
65.20	Wash, 10 lks. wide, course SW.; asc. 175 ft. over a S. slope.
74.00	Spur, slopes W.; desc. 60 ft. over a N. slope.
78.50	Wash, 5 lks. wide, course SW.; asc. 15 ft. over a S. slope.
79.86	The cor. of secs. 17, 18, 19 and 20, as evidenced by an old mound of stone, 2 ft. base, 1 ft. high. No marked stone was found.
	At point for cor. in center of mound of stone.
	Set an iron post, 3 ft. long, 2 ins. diam., 28 ins. in the ground, at cor. of secs. 17, 18, 19 and 20, with brass cap mkd.
	$\begin{array}{c} T24N R5E \\ S18   S17 \\ \hline S19   S20 \\ \hline 1945 \end{array}$
	from which
	Old bearing trees:
	A pine, 30 ins. diam., (now dead), bears N. 87° E., 73 lks. dist., markings overgrown, not uncovered.

## Resurvey of the Subdivision of T. 24 N., R. 5 E.

## Chains

A pine, 12 ins. diam., bears S.  $70^{\frac{3}{4}}^{\circ}$  E., 31 lks. dist., markings overgrown, mark on overgrowth, T 24 N R 5 E S 20 B T.

A pine, 28 ins. diam., bears S.  $28^{\circ}$  W., 32 lks. dist., markings overgrown, mark on overgrowth, T 24 N R 5 E S 19 B T.

A pine, 27 ins. diam., (now dead), bears N.  $29^{\frac{1}{2}}^{\circ}$  W., 44 lks. dist., mkd. T 24 N R 5 E S 18 B T.

## New bearing trees:

A pine, 6 ins. diam., bears N.  $24^{\frac{3}{4}}^{\circ}$  E., 48 lks. dist., mkd. T 24 N R 5 E S 17 B T.

A pine, 5 ins. diam., bears N.  $15^{\frac{3}{4}}^{\circ}$  W., 70 lks. dist., mkd. T 24 N R 5 E S 18 B T.

## Land, mountainous.

Soil, rocky, 2nd and 3rd rates.

Timber, pine; undergrowth, 2nd growth pine.

-----  
From the cor. of secs. 16, 17, 20 and 21.

N.  $88^{\circ} 07'$  W., bet. secs. 17 and 20.

Over mountainous land, through heavy timber and undergrowth.

Ascend 214 ft. over an E. slope.

9.30 Spur, slopes N.; thence, along a S. slope.

14.30 Spur, slopes SW.; desc. 81 ft. over a NW. slope.

34.00 Leave heavy timber, bears N. and S.; thence, through scattered timber.

36.75 Dim road, bears N. and S.

39.28 The  $\frac{1}{4}$  sec. cor., as evidenced by a sandstone, 14x12x6 ins., firmly set in the ground, mkd.  $\frac{1}{4}$  on N. face.

Set an iron post, 3 ft. long, 1 in. diam., 28 ins. in the ground, with the old corner stone buried alongside, at  $\frac{1}{4}$  sec. cor., with brass cap mkd.

S17  
-----  
 $\frac{1}{4}$   
S20  
1945

from which

A pine, 10 ins. diam., bears N.  $18^{\circ}$  W., 399 lks. dist., mkd.  $\frac{1}{4}$  S 17 B T.

A pine, 10 ins. diam., bears S.  $9^{\frac{1}{2}}^{\circ}$  E., 153 lks. dist., mkd.  $\frac{1}{4}$  S 20 B T.

Thence,

N.  $89^{\circ} 57'$  W., bet. secs. 17 and 20.

14.90 Enter heavy timber, bears N. and S.

25.00 Begin descent of 41 ft. over a SW. slope.

39.97 The cor. of secs. 17, 18, 19 and 20.

Resurvey of the Subdivision of T. 24 N., R. 5 E.

4354

Chains


Land, mountainous.  
Soil, rocky, 2nd and 3rd rates.  
Timber, pine; undergrowth, 2nd growth pine.

S. 89° 45' W., bet. secs. 18 and 19.

Over mountainous land, through heavy timber and undergrowth.

- 1.70 Draw, drains SW.; asc. over a gradual SE. slope.
- 13.40 Spur, slopes SW.; desc. 200 ft. over a broken SW. slope.
- 32.40 Ravine, course SW.
- 39.47 The  $\frac{1}{4}$  sec. cor., as evidenced by a lava stone, 8x8x6 ins., firmly set in the ground, mkd.  $\frac{1}{4}$  on N. face.

Set an iron post, 3 ft. long, 1 in. diam., 28 ins. in the ground, with the old corner stone buried alongside, at  $\frac{1}{4}$  sec. cor., with brass cap mkd.



from which

Old bearing tree:

A pine, 30 ins. diam., (partly dead), bears N. 58 $\frac{3}{4}$ ° W., 57 lks. dist., markings overgrown.

New bearing trees:

A pine, 14 ins. diam., bears N. 12° E., 34 lks. dist., mkd.  $\frac{1}{4}$  S 18 B T.

A pine, 8 ins. diam., bears S. 1° E., 31 lks. dist., mkd.  $\frac{1}{4}$  S 19 B T.


Thence,

S. 89° 34' W., bet. secs. 18 and 19.

Descend 24 ft. over a SW. slope.

- 0.03 A line tree, a pine, 6 ins. diam., mkd. 2 hack marks on E. and W. sides.
- 1.85 Recross ravine, course NW.; asc. 21 ft. over a NE. slope.
- 6.50 Spur, slopes NW.; desc. 328 ft. over a SW. slope.
- 22.15 Wash, 20 lks. wide, course N. 80° W.
- 23.90 Intersect W. bdy. of Tp.

Set an iron post, 3 ft. long, 2 ins. diam., 28 ins. in the ground, at closing corner of secs. 18 and 19, with brass cap mkd.



from which

## Resurvey of the Subdivision of T. 24 N., R. 5 E.

## Chains

Old bearing tree:

A pine, 24 ins. diam., bears S. 28° E., 65 lks.  
dist., mkd. T 24 N R 5 E S 19 C C B T.

New bearing tree:

A pine, 18 ins. diam., bears N. 17° E., 70 lks.  
dist., mkd. T 24 N R 5 E S 18 C C B T.

From the closing corner the angle point of secs. 13 and 19, bears S. 0° 47' W., 10.95 chs. dist.

Continue on blank line in sec. 13.

0.16

The original closing corner of secs. 18 and 19, as evidenced by a sandstone, 16x14 ins., 12 ins. above ground, firmly set, mkd. C C on E., 3 grooves on N. and 3 grooves on S. faces, with a mound of stone, 3 ft. base, 2 ft. high, W. of cor. Additionally mark this corner stone W P on top.

From this witness point

Old bearing trees:

A pine, 24 ins. diam., bears N. 22 $\frac{1}{4}$ ° E., 9 lks.  
dist., markings overgrown, mark on overgrowth,  
W P B T.

A pine, 24 ins. diam., bears S. 39 $\frac{1}{2}$ ° E., 74 lks.  
dist., markings described above.

Land, mountainous.

Soil, rocky, 2nd and 3rd rates.

Timber, pine and juniper; undergrowth, 2nd growth pine.

At midpoint on the W. bdy. of sec. 19,

Set an iron post, 3 ft. long, 1 in. diam., 28 ins. in the ground, at  $\frac{1}{4}$  sec. cor. of sec. 19, with brass cap mkd.

|  $\frac{1}{4}$  S 19

1945

from which

A pine, 6 ins. diam., bears N. 66° E., 32 lks.  
dist., mkd.  $\frac{1}{4}$  S 19 B T.

A pine, 4 ins. diam., bears S. 50 $\frac{1}{2}$ ° E., 8 lks.  
dist., mkd.  $\frac{1}{4}$  S 19 B T.

From this corner, the angle point of secs. 19 and 24, bears S. 0° 36' W., 9.19 chs. dist.

From the cor. of secs. 17, 18, 19 and 20.

N. 2° 31' W., bet. secs. 17 and 18.

Over mountainous land, through heavy timber and scattered undergrowth.

Ascend 6 ft. along a W. slope.

3.40

Head of a draw, drains SW.; asc. 23 ft. over a SE. slope.

## Resurvey of the Subdivision of T. 24 N., R. 5 E.

BOOK 4854

Chains	
6.50	Spur, slopes SW.; desc. 46 ft. over a NW. slope.
20.50	Gulch, 10 lks. wide, course SW.; asc. 51 ft. over a SE. slope.
36.00	Spur, slopes SW.; desc. 36 ft. over a NW. slope.
38.29	Proportional distance. Set an iron post, 3 ft. long; 1 in. diam., 28 ins. in the ground, at $\frac{1}{4}$ sec. cor., with brass cap mkd.  <div style="text-align: center;"> <math>\frac{1}{4}</math>  S18   S17  1945  from which  A pine, 16 ins. diam., bears S. <math>78\frac{1}{2}^{\circ}</math> E., 32 lks. dist., mkd. <math>\frac{1}{4}</math> S 17 B T.  A pine, 10 ins. diam., bears N. <math>62\frac{1}{2}^{\circ}</math> W., 15 lks. dist., mkd. <math>\frac{1}{4}</math> S 18 B T.  Descend 77 ft. over a NW. slope. </div>
47.00	Wash, course NE.; asc. 85 ft. over a SE. slope.
55.00	Spur, slopes NE.; desc. 128 ft. over a NW. slope.
68.50	Recross wash, 10 lks. wide, course NW.; asc. 18 ft. over a SW. slope.
76.58	The cor. of secs. 7, 8, 17 and 18, as evidenced by a lava stone, 16x14x12 ins., firmly set in the ground, mkd. 4 grooves on S. and 4 grooves on E. faces, with a mound of stone, 2 ft. base, $1\frac{1}{2}$ ft. high, W. of cor. Set an iron post, 3 ft. long; 2 ins. diam., 28 ins. in the ground, with the old corner stone buried alongside, at cor. of secs. 7, 8, 17 and 18, with brass cap mkd.  <div style="text-align: center;"> T24N R5E.  S7   S8  ---  S18   S17  1945  from which  Old bearing trees:  A pine, 36 ins. diam., (partly dead), bears N. <math>62\frac{1}{2}^{\circ}</math> E., 16 lks. dist., markings illegible.  A pine, 12 ins. diam., bears S. <math>7^{\circ}</math> W., 121 lks. dist., markings overgrown, mark on overgrowth, T 24 N R 5 E S 18 B T.  A pine, 24 ins. diam., bears N. <math>84\frac{3}{4}^{\circ}</math> W., 47 lks. dist., markings overgrown, mark on overgrowth, T 24 N R 5 E S 7 B.T.  New bearing trees:  A pine, 12 ins. diam., bears N. <math>17^{\circ}</math> E., 116 lks. dist., mkd. T 24 N R 5 E S 8 B T.  A pine, 12 ins. diam., bears S. <math>57^{\circ}</math> E., 177 lks. dist., mkd. T 24 N R 5 E S 17 B T. </div>

BOOK 4354

Resurvey of the Subdivision of T. 24 N., R. 5 E.

Chains	<p>Land, mountainous. Soil, rocky, 2nd and 3rd rates. Timber, pine, fir and Juniper; undergrowth, 2nd growth pine.</p>
	<p>-----</p> <p>From the cor. of secs. 8, 9, 16 and 17.</p>
	<p>S. 89° 20' W., bet. secs. 8 and 17.</p>
	<p>Over mountainous land, through heavy timber and scattered undergrowth.</p>
	<p>Ascend 413 ft. over a NE. slope.</p>
38.62	<p>The <math>\frac{1}{4}</math> sec. cor., determined from the old bearing trees. Set an iron post, 3 ft. long, 1 in. diam., 28 ins. in the ground, at <math>\frac{1}{4}</math> sec. cor., with brass cap mkd.</p>
	<p style="text-align: center;">S8 ----- S17 1945</p>
	<p style="text-align: right;">from which</p>
	<p>Old bearing trees:</p>
	<p>A fir, 16 ins. diam., bears N. 87° E., 43 lks. dist., markings overgrown, mark on overgrowth, <math>\frac{1}{4}</math> S. 8 B T.</p>
	<p>A fir, 36 ins. diam., bears S. 87½° W., 52 lks. dist., markings overgrown, mark on overgrowth, <math>\frac{1}{4}</math> S 17 B T.</p>
	<p>Thence,</p>
	<p>S. 87° 12' W., bet. secs. 8 and 17.</p>
	<p>Ascend 377 ft. over a NE. slope.</p>
10.20	<p>Top of a cliff, 75 ft. high, bears N. and S., faces E.</p>
15.60	<p>Spur, slopes NW.; desc. 115 ft. over a broken NW. slope.</p>
41.52	<p>The cor. of secs. 7, 8, 17 and 18.</p>
	<p>Land, mountainous. Soil, rocky, 2nd and 3rd rates. Timber, pine, fir and juniper; undergrowth, 2nd growth pine.</p>
	<p>-----</p> <p>N. 88° 46' W., bet. secs. 7 and 18.</p>
	<p>Over mountainous land, through heavy timber and undergrowth.</p>
	<p>Descend 29 ft. over a W. slope.</p>
6.55	<p>Wash, 20 lks. wide, course NW.; asc. 160 ft. over a SE. slope.</p>
24.80	<p>Spur, slopes NE.; desc. 189 ft. over a NW. slope.</p>
39.84	<p>The <math>\frac{1}{4}</math> sec. cor., as evidenced by a lava stone, 14x10x8 ins., firmly set in the ground, mkd. <math>\frac{1}{4}</math> on N. face, with a mound of stone, 2 ft. base, 1 ft. high, N. of cor.</p>

## Resurvey of the Subdivision of T. 24 N., R. 5 E.

4354

## Chains

Set an iron post, 3 ft. long, 1 in. diam., 28 ins. in the ground, with the old corner stone buried alongside, at  $\frac{1}{4}$  sec. cor., with brass cap mkd.

$$\begin{array}{r} S7 \\ \hline \frac{1}{4} \\ S18 \\ 1945 \end{array}$$

from which

## Old bearing tree:

A pine, 36 ins. diam., bears N.  $75\frac{1}{2}^{\circ}$  E., 60 lks. dist., markings overgrown, mark on overgrowth,  $\frac{1}{4}$  S 7 B T.

## New bearing tree:

A pine, 10 ins. diam., bears S.  $20\frac{1}{2}^{\circ}$  E., 83 lks. dist., mkd.  $\frac{1}{4}$  S 18 B T.

## Thence,

N.  $88^{\circ} 34'$  W., bet. secs. 7 and 18.

Descend 57 ft. over a NW. slope.

3.40 Spur, slopes NW.; desc. 415 ft. over a SW. slope.

19.58 The original closing corner of secs. 7 and 18, as evidenced by a sandstone, 16x14x6 ins., firmly set in the ground, mkd. CC and 6 grooves on E., 4 grooves on S. and 2 grooves on N. faces, with a mound of stone, 2 ft. base, 2 ft. high, W. of cor. Additionally mark corner stone W P on top.

From this witness point

## Old bearing trees:

A pine, 26 ins. diam., bears N.  $41\frac{3}{4}^{\circ}$  E., 73 lks. dist., markings overgrown, mark on overgrowth, T 24 N R 5 E S 7 C C B T.

A pine, 16 ins. diam., bears S.  $2\frac{1}{2}^{\circ}$  E., 42 lks. dist., markings overgrown, mark on overgrowth, T 24 N R 5 E S 18 C C B T.

20.57 Intersect the W. bdy. of the Tp.

Set an iron post, 3 ft. long, 2 ins. diam., 28 ins. in the ground, at closing corner of secs. 7 and 18, with brass cap mkd.

$$\begin{array}{r} T24N \quad T24N \\ | \\ R4E \quad | \quad S7 \quad \text{---} \quad CC \\ | \\ S12 \quad R5E \\ | \\ 1945 \end{array}$$

from which

## Old bearing trees of original closing corner:

A pine, 26 ins. diam., bears N.  $70\frac{1}{2}^{\circ}$  E., 156 lks. dist., markings described above.

A pine, 16 ins. diam., bears S.  $66^{\circ}$  E., 109 lks. dist., markings described above.

From the closing corner, the angle point of secs. 12 and 18, bears S.  $2^{\circ} 34'$  W., 11.47 chs. dist.

BOOK 4354

Resurvey of the Subdivision of T. 24 N., R. 5 E.

Chains

Land, mountainous.  
Soil, rocky, 2nd and 3rd rates.  
Timber, pine, fir and juniper; undergrowth, 2nd growth timber.

-----  
At midpoint on the W. bdy. of sec. 18.

Set an iron post, 3 ft. long, 1 in. diam., 27 ins. in the ground to bedrock, and in a mound of stone to top, at  $\frac{1}{4}$  sec. cor. of sec. 18, with brass cap mkd.

$\frac{1}{4}$  S18

1945

from which

A pinon, 8 ins. diam., bears S.  $84\frac{1}{2}^{\circ}$  E., 33 lks. dist., mkd.  $\frac{1}{4}$  S 18 B T.

A pinon, 10 ins. diam., bears S.  $29\frac{3}{4}^{\circ}$  E., 8 lks. dist., mkd.  $\frac{1}{4}$  S 18 B T.

From this corner, the angle point of secs. 13 and 18, bears S.  $2^{\circ} 02'$  E., 10.19 chs. dist.

-----  
From the cor. of secs. 7, 8, 17 and 18.

N.  $0^{\circ} 08'$  W.; bet. secs. 7 and 8.

Over mountainous land, through heavy timber and undergrowth.

Descend 125 ft. over a NW. slope.

25.85 Begin steep descent of 368 ft. over a NW. slope.

38.00 Gulch, course NE.; asc. 80 ft. over a SE. slope.

41.40 Spur, slopes N.  $80^{\circ}$  E.

41.66 The  $\frac{1}{4}$  sec. cor., as evidenced by a sandstone, 16x12x3 ins. firmly set in the ground, mkd.  $\frac{1}{4}$  on W. face, with a mound of stone, 2 ft. base, 1 ft. high, W. of cor.

Set an iron post, 3 ft. long, 1 in. diam., 28 ins. in the ground, with the old corner stone buried alongside, at  $\frac{1}{4}$  sec. cor., with brass cap mkd.

$\frac{1}{4}$   
S7|S8

1945

from which

Old bearing trees:

A pine, 14 ins. diam., bears N.  $87^{\circ}$  E., 36 lks. dist., mkd.  $\frac{1}{4}$  S B T. Additionally mark  $\frac{1}{4}$  S 8 B T.

A pine, 24 ins. diam., bears S.  $87\frac{1}{2}^{\circ}$  W., 104 lks. dist., mkd.  $\frac{1}{4}$  S B T. Additionally mark  $\frac{1}{4}$  S 7 B T.

Thence,

N.  $0^{\circ} 33'$  W., bet. secs. 7 and 8.

## Resurvey of the Subdivision of T. 24 N., R. 5 E.

BOOK 4854

Chains	Descend 201 ft. over a NW. slope.								
10.00	Foot of steep descent, bears E. and W.; desc. 68 ft. over a gradual N. slope.								
40.26	The cor. of secs. 5, 6, 7 and 8, as evidenced by a lava stone, 14x10x8 ins., firmly set in the ground, mkd. 5 grooves on S. and 5 grooves on E. faces.  Set an iron post, 3 ft. long, 2 ins. diam., 16 ins. in the ground, to bedrock, with the old corner stone buried alongside, and in a mound of stone to top, at cor. of secs. 5, 6, 7 and 8, with brass cap mkd.  <div style="text-align: center;"> <table border="1"> <tr><td>T24N</td><td>R5E</td></tr> <tr><td>S6</td><td>S5</td></tr> <tr><td>S7</td><td>S8</td></tr> <tr><td colspan="2">1945</td></tr> </table> </div>	T24N	R5E	S6	S5	S7	S8	1945	
T24N	R5E								
S6	S5								
S7	S8								
1945									
	from which								
	Old bearing trees:								
	A pine, 28 ins. diam., bears N. 34° E., 73 lks. dist., mkd. T 24 N R 5 E S 5 B T.								
	A pine, 14 ins. diam., (now dead), bears N. 84° E., 33 lks. dist., markings illegible.								
	A pine, 30 ins. diam., bears N. 40½° W., 88 lks. dist., markings overgrown, mark on overgrowth; T 24 N R 5 E S 6 B T.								
	New bearing trees:								
	A pine, 8 ins. diam., bears S. 49¼° E., 21 lks. dist., mkd. T 24 N R 5 E S 8 B T.								
	A juniper, 12 ins. diam., bears S. 41° W., 107 lks. dist., mkd. T 24 N R 5 E S 7 B T.								
	Land, mountainous. Soil, rocky, 2nd and 3rd rates. Timber, pine, fir and juniper; undergrowth, 2nd growth timber.								
	-----								
	From the cor. of secs. 4, 5, 8 and 9. S. 89° 54' W., bet. secs. 5 and 8. Over rolling land, through heavy timber and undergrowth. Descend 31 ft. along a SW. slope.								
11.40	Dim road, bears N. 10° W. and S. 10° E.								
16.90	Foot of descent; thence, across bottom land:								
20.10	Wash, 20 lks. wide, 2 ft. deep, course N. 20° W.								
21.90	Wash, 25 lks. wide, 3 ft. deep, course NORTH; asc. NE. slope.								
24.00	Low spur, slopes N.; desc. gradual W. slope.								
25.50	Drain, course NE.; asc. 97 ft. over a SE. slope.								
37.00	Top of ascent, bears NE. and SW.								

## Resurvey of the Subdivision of T. 24 N., R. 5 E.

Chains

39.85

The  $\frac{1}{4}$  sec. cor., as evidenced by a malpais stone, 14x8x4 ins., firmly set in the ground, mkd.  $\frac{1}{4}$  on N. face.

Set an iron post, 3 ft. long, 1 in. diam., 28 ins. in the ground, with the old corner stone buried alongside, at  $\frac{1}{4}$  sec. cor., with brass cap mkd.

S5

 $\frac{1}{4}$ —  
S8

1945

from which

Old bearing trees:

A pine, 36 ins. diam., bears N.  $52\frac{3}{4}^{\circ}$  W., 217 lks. dist., mkd.  $\frac{1}{4}$  S B T. Additionally mark this tree  $\frac{1}{4}$  S 5 B T.

A pine, 34 ins. diam., bears S.  $67^{\circ}$  W., 32 lks. dist., mkd.  $\frac{1}{4}$  S B T. Additionally mark this tree  $\frac{1}{4}$  S 8 B T.

Thence,

S.  $89^{\circ} 28'$  W., bet. secs. 5 and 8.

Continue over rolling land.

40.96

The cor. of secs. 5, 6, 7 and 8.

Land, rolling.

Soil, clay, gravelly and rocky, 3rd and 4th rates.

Timber, pine, fir and juniper; undergrowth, 2nd growth pine.

S:  $89^{\circ} 19'$  W., bet. secs. 6 and 7.

Over rolling land, through heavy timber and undergrowth.

Descend 40 ft. over a W. slope.

11.10

Gulch near head, course NW.; asc. broken NE. slope.

14.30

Gulch, course N.  $10^{\circ}$  W., 1.00 ch. dist. to a junction with another gulch from the SE.; asc. 47 ft. over a NE. slope.

17.60

Spur, slopes N.  $10^{\circ}$  W.; desc. over a gradual rolling N. slope.

22.60

Leave heavy timber and undergrowth; enter scattered timber, bears NE. and SW.

39.64

The  $\frac{1}{4}$  sec. cor.; as evidenced by a malpais stone 16x10x3 ins., firmly set, mkd.  $\frac{1}{4}$  on N. face.

Set an iron post, 3 ft. long, 1 in. diam., 28 ins. in the ground; with the old corner stone buried alongside, at  $\frac{1}{4}$  sec. cor., with brass cap mkd.

S6

 $\frac{1}{4}$ —  
S7

1945

from which

## Resurvey of the Subdivision of T. 24 N., R. 5 E.

4854

## Chains

Old bearing trees:

A pine, 20 ins. diam., bears N.  $43\frac{3}{4}^{\circ}$  E., 180 lks. dist., mkd.  $\frac{1}{4}$  S B T.

A pinon, 24 ins. diam., bears S.  $20\frac{3}{4}^{\circ}$  E., 46 lks. dist., mkd.  $\frac{1}{4}$  S B T. Additionally mark this tree  $\frac{1}{4}$  S 7 B T.

New bearing tree:

A juniper, 6 ins. diam., bears N.  $60\frac{1}{2}^{\circ}$  E., 197 lks. dist., mkd.  $\frac{1}{4}$  S 6 B T.

Thence,

N.  $83^{\circ}46'$  W., bet. secs. 6 and 7.

Ascend a gradual E. slope.

3.50 Spur, slopes N.; desc. over a gradual NW. slope.

19.52 The original closing corner of secs. 6 and 7, as evidenced by a lava stone, 14x10x7 ins., firmly set in the ground, mkd. CC on E. face and 1 notch on N., and 5 notches on S. edges. Additionally mark this stone W P on top. From this witness point

Old bearing trees:

A juniper, 16 ins. diam., bears S.  $65^{\circ}$  E., 124 lks. dist., mkd. T 24 N R 5 E S 7 B T.

A juniper, 16 ins. diam., bears S.  $36\frac{1}{2}^{\circ}$  E., 120 lks. dist., markings overgrown, mark on over growth, T 24 N R 5 E S 7 C C B T.

19.60 Intersect the W. bdy. of the Tp.

Set an iron post, 3 ft. long; 2 ins. diam., 28 ins. in the ground, at closing corner of secs. 6 and 7, with brass cap mkd.

T24N	T24N	
R4E	S6	CC
S1	S7	
	R5E	
	1945	

.. from which

Old bearing tree of the original closing corner, a juniper, 16 ins. diam., bears S.  $39\frac{1}{4}^{\circ}$  E., 127 lks. dist., markings described above.

A juniper, 16 ins. diam., bears N.  $77^{\circ}$  E., 204 lks. dist., mkd. T 24 N R 5 E S 6 C C B T.

From the closing corner, the angle point of, secs. 1 and 7, bears S.  $0^{\circ}30'$  E., 15.19 chs. dist.

Land, rolling.

Soil, rocky, 2nd and 3rd rates.

Timber, pine, juniper and pinon; undergrowth, 2nd growth timber.

-----  
At midpoint on the W. bdy. of sec. 7.

BOOK 4354

## Resurvey of the Subdivision of T. 24 N., R. 5 E.

## Chains

Set an iron post, 3 ft. long, 1 in. diam., 28 ins. in the ground, at  $\frac{1}{4}$  sec. cor. of sec. 7, with brass cap mkd.

|  $\frac{1}{4}$  S7

1945

from which

A pinon, 20 ins. diam., bears N.  $71\frac{1}{4}^{\circ}$  E., 134 lks. dist., mkd.  $\frac{1}{4}$  S 7 B T.

A pinon, 4 ins. diam., bears S.  $37\frac{3}{4}^{\circ}$  E., 118 lks. dist., mkd.  $\frac{1}{4}$  S 7 B T.

From this corner, the angle point of secs. 7 and 12, bears S.  $0^{\circ} 21' E.$ , 13.87 chs. dist.

At proportional distance on the W. bdy. of sec. 6.

Set an iron post, 3 ft. long, 1 in. diam., 28 ins. in the ground, at  $\frac{1}{4}$  sec. cor., of sec. 6, with brass cap mkd.

|  $\frac{1}{4}$  S6

1945

raise a mound

of stone, 3 ft. base, 2 ft. high, E. of cor.

From this corner the angle point of secs. 1 and 6, bears S.  $0^{\circ} 53' E.$ , 15.26 chs. dist.

From the cor. of secs. 5, 6, 7 and 8.

N.  $11^{\circ} 03' E.$ , bet. secs. 5 and 6.

Over rolling land, through scattered timber and undergrowth.

Descend 85 ft. over a gradual NW. slope.

38.00 Begin steep descent; desc. 50 ft. over a NE. slope.

40.59 The  $\frac{1}{4}$  sec. cor., as evidenced by a sandstone, 18x14x12 ins., firmly set in the ground, mkd.  $\frac{1}{4}$  on W. face.

Set an iron post, 3 ft. long, 1 in. diam., 28 ins. in the ground, with the old corner stone buried alongside, at  $\frac{1}{4}$  sec. cor., with brass cap mkd.

|  $\frac{1}{4}$   
S6 | S5

1945

from which

Old bearing tree:

A pine, 36 ins. diam., bears S.  $34\frac{3}{4}^{\circ}$  E., 76 lks. dist., markings overgrown, not uncovered.

New bearing trees:

A pine, 6 ins. diam., bears S.  $59\frac{1}{4}^{\circ}$  E., 20 lks. dist., mkd.  $\frac{1}{4}$  S 5 B T.

## Resurvey of the Subdivision of T. 24 N., R. 5 E.

BOOK 4854

- Chains
- A pine, 7 ins. diam., bears S.  $35\frac{3}{4}^{\circ}$  W., 43 lks. dist., mkd.  $\frac{1}{4}$  S 6 B T.
- Thence,
- N.  $0^{\circ} 31'$  W., bet. secs. 5 and 6.
- 0.50 Ravine, course N.  $70^{\circ}$  W., from S,  $45^{\circ}$  E.; an earthen reservoir, bears about N.  $70^{\circ}$  W., approx. 23.00 chs. dist.; asc. 67 ft. over a SW. slope.
- 6.40 Spur, slopes W.; desc. 26 ft. over a N. slope.
- 11.20 Draw, near head, drains W.; asc. 40 ft. over a S. slope.
- 20.80 Road, bears E., to Prong Lake and W. to Spring Valley.
- 23.65 Intersect the 6th Standard Parallel North.
- Set an iron post, 3 ft. long, 2 ins. diam., 28 ins. in the ground, at closing corner of secs. 5 and 6, with brass cap mkd.

T25N R5E  
S31

S6	S5
T24N	R5E
C	C

1945

from which

A pinon, 4 ins. diam., bears S.  $55\frac{1}{4}^{\circ}$  E., 144 lks. dist., mkd. T 24 N R 5 E S 5 C C B T.

A pinon, 3 ins. diam., bears S.  $83\frac{3}{4}^{\circ}$  W., 85 lks. dist., mkd. C C B T.

From the closing corner, the standard  $\frac{1}{4}$  sec. cor. on the S. bdy. of sec. 31, T. 25 N., R. 5 E., bears N.  $89^{\circ} 11'$  W., 12.03 chs. dist.

Continue on a blank line in sec. 31.

- 0.44 The original closing corner of secs. 5 and 6, as evidenced by a sandstone, 12x10x8 ins., firmly set in the ground, mkd. C C on S. face, 5 grooves on E. and 1 groove on W. faces, with a mound of stone, 2 ft. base, 1 ft. high, W. of cor. Additionally mark this corner stone W P on top.

Land, heavily rolling.

Soil, gravelly and rocky, 3rd and 4th rates.

Timber, pine, pinon and juniper; undergrowth, 2nd growth pine.

-----

At midpoint on the N. bdy. of sec. 5.

Set an iron post, 3 ft. long, 1 in. diam., 18 ins. in the ground, with a stone mkd. with a cross + deposited at the base, and in a mound of stone to top, at  $\frac{1}{4}$  sec. cor. of sec. 5, with brass cap mkd.

$\frac{1}{4}$  S5  
1945

From this corner, the standard corner of secs. 31 and 32, T. 25 N., R. 5 E., bears N.  $88^{\circ} 49'$  W., 11.83 chs. dist.

-----

BOOK 4354

## Resurvey of the Subdivision of T. 24 N., R. 5 E.

## Chains

At proportional distance on the N. bdy. of sec. 6.

Set an iron post, 3 ft. long, 1 in. diam., 28 ins. in the ground, at  $\frac{1}{4}$  sec. cor. of sec. 6, with brass cap mkd.

$\frac{1}{4}$  S 6  
1945

from which

A cedar, 3 ins. diam., bears S.  $16\frac{3}{4}^{\circ}$  E., 440 lks. dist., mkd. B T.

A cedar, 4 ins. diam., bears S.  $31\frac{1}{2}^{\circ}$  W., 377 lks. dist., mkd.  $\frac{1}{4}$  S 6 B T.

From this corner, the standard corner of Ts. 25 N., Rs. 4 and 5 E., bears N.  $89^{\circ} 23'$  W., 12.78 chs. dist.

For final test of instruments see field notes of the resurvey of T. 25 N., R. 5 E.

## GENERAL DESCRIPTION.

The land herein surveyed is of a rolling mountainous character, lying at a mean elevation of 7500 ft. above sea level. The area supports a fair growth of pine timber, with a sprinkling of juniper and pinon; there is very little undergrowth, although dense thickets of 2nd. growth timber are encountered throughout the township. The soil is of clay or gumbo texture, shallow and rocky and of poor quality. The main drainage is to the north and west, from a dividing ridge extending north into the center of the township.

The country is arid, drainage waters are impounded in earthen reservoirs where physical conditions permit and the need dictates. A house, corrals and spring is noted in Bull Basin, near the  $\frac{1}{4}$  section corner on the east boundary of section 28. No other improvements, with the exception of some irregular range fencing and various local roadways are noted. Kendricks Spring is situated in section 23, near the center of the west half mile between sections 23 and 26, and Muddersbach Spring is noted near the southeast corner of section 8.

The Forest Service maintains a look-out station on the apex of Slate Mountain, in the NW. quarter of section 2, reached by a well graded road from the south.

The highway from Flagstaff to Grand Canyon traverses the extreme northeast portion of section 1.

BOOK 4354

4-680  
(Revised May 1934)

UNITED STATES  
DEPARTMENT OF THE INTERIOR  
~~GENERAL LAND OFFICE~~

BUREAU OF LAND MANAGEMENT

FIELD ASSISTANTS

NAMES	CAPACITY
John Boggs	Truckdriver.
Theodore Cole	Principal Assistant.
George D. Blair	Cornerman.
Sidney G. Tait	Flagman.
Tommy J. Cade	Axman.
Frank L. Harris	Axman.
George C. Hopkins	Axman.
James C. Kennicott	Axman.
George K. Mills, Jr.	Axman.
Richard A. Rogers	Axman.
Henry Whitney	Axman.
Harold R. Muller	Axman.

92  
1954  
CERTIFICATE OF SURVEYOR

Ty White, Associate Cadastral Engineer,  
We, Bert E. Wakeman, Senior Engineering Aid, Claude F. Warner, Assistant Cadastral Engineer, HEREBY CERTIFY upon honor that, in  
pursuance of special instructions bearing date of the 13th day of March, 1942,

received from the district cadastral engineer for Arizona, with assignment  
June 26, 1944  
instructions dated and we have resurveyed the Sixth Standard  
June 16, 1945  
Parallel North, along the South Boundary of T.25 N., R.5 E., the First  
Guide Meridian East, along the East Boundary of T.24 N., R.4 E., and  
the Subdivision of T.24 N., R.5 E.,  
Gila and Salt River  
of the Meridian, in the State of Arizona, which are

represented in the foregoing field notes as having been executed by me and under my direction; and that said  
resurvey has been made in strict conformity with said instructions, the Manual of Instructions for the Survey  
of the Public Lands of the United States, and in the specific manner described in the foregoing field notes.

Phoenix, Arizona, Mar. 17, 1947

Phoenix, Arizona, Mar. 24, 1947

Phoenix, Arizona, Mar. 17, 1947

*Ty White*  
Associate Cadastral Engineer.  
*Bert E. Wakeman*  
Senior Engineering Aid.  
*Claude F. Warner*  
Assistant Cadastral Engineer.

CERTIFICATE OF APPROVAL

Chief Cadastral Engineer  
OFFICE OF SUPERVISOR OF SURVEYS,  
Denver, Colorado

OCT 20 1947

The foregoing field notes of the dependent resurvey of the Sixth Standard Parallel  
North, along the South Boundary of T.25 N., R.5 E., the First Guide  
Meridian East, along the East Boundary of T.24 N., R.4 E., and the  
Subdivision of T.24 N., R.5 E.,

executed by Ty White, Associate Cadastral Engineer; Claude F. Warner, Assistant Cadastral Engineer and Bert E. Wakeman, Senior Engineering Aid, under special instructions dated March 13, 1942, and assignment instructions dated June 26, 1944 and June 16, 1945, having been critically examined, and the necessary corrections made prior to their certification by the engineer, the said field notes, and the survey therein described, are hereby approved.

*Earl G. Harrington*  
Supervisor of Surveys.  
Acting Assistant Chief Cadastral Engineer

CERTIFICATE OF TRANSCRIPT

I CERTIFY that the foregoing transcript of the field notes of the above described surveys in  
is a true copy of the original field notes on file in the public survey office.

Supervisor of Surveys.