

Original

RECEIVED
U. S. LAND OFFICE
Phoenix, Arizona

JUN 16 1952

4-679
(April 1933)

BOOK 4390

4390
74
RECEIVED
JUN 1951
Bureau of Land Management
Cadastral Engineering
Region V,
Albuquerque

FIELD NOTES

of the survey of the

East Boundary, North Boundary and Subdivisional Lines of

Township 5 North, Range 19 West

Of the Gila and Salt River Meridian,

In the State of Arizona.

EXECUTED BY

Ty White and Claude F. Warner, Cadastral Engineers.

Under special instructions dated September 27, 1950, which provided

for the surveys included under Group No. 269, bearing the approval of the
Director, Bureau of Land Management

~~Commissioner of the General Land Office~~ under date of October 25, 1950

and assignment instructions dated November 1, 1950

Survey commenced November 17, 1950

Survey completed December 11, 1950

75

1A

BOOK 4390

INDEX DIAGRAM.

Township 5 North, Range 19 West.

	8	7	7	6	6	5					
6	41	5	33	4	27	3	21	2	14	1	4
	41		40		32		26		20		14
7	40	8	32	9	26	10	19	11	13	12	4
	39		39		31		25		19		13
18	38	17	31	16	25	15	18	14	12	13	3
	38		38		30		24		18		12
19	37	20	30	21	23	22	17	23	11	24	2
	36		36		29		23		17		11
30	35	29	29	28	22	27	16	26	10	25	2
	35		34		28		22		16		9
31	33	32	27	33	21	34	15	35	8	36	1

T. 5 N., R. 19 W.

4890

The survey was made with Buff and Buff light mountain transits Nos. 16724 and 23816. For description of the instruments, determination of meridian and other preliminary data, see the field notes of T. 5 N., R. 20 W., surveyed under this group.

The geographic position of the SE. cor. of T. 5 N., R. 19 W., as determined by data furnished with the special instructions is latitude $33^{\circ} 43' 28''$ N., longitude $114^{\circ} 10' 32''$ W.

November 16, 1950, on the meridian established on Nov. 15, 1950, at half hour intervals from 8:00 a.m. to 4:00 p.m., we make orientation tests of Buff and Buff transits Nos. 16724 and 23816, including a latitude test by noon observation. The tests give a maximum error in orientation of less than $1' 30''$.

The observed magnetic declination is 14° E.

East Boundary of T. 5 N., R. 19 W.

Chains.

The standard cor. of Ts. 5 N., Rs. 18 and 19 W. is monumented with a granite stone $16 \times 10 \times 8$ ins., marked and witnessed as described in the official record.

At the corner point

Set an iron post, 3 ft. long, 3 ins. diam., 28 ins. in the ground, with brass cap mkd.

S C
T5N
R19W R18W
S36 | S31

1950

Bury the original corner stone alongside the iron post.

Thence

North, bet. secs. 31 and 36.

Over rolling land, through scattering timber.

0.90 Wash, 15 lks. wide, course WSW.
13.50 Wash, 30 lks. wide, course W.
31.65 Wash, 30 lks. wide, course W.
36.80 Graded road, bears ENE. and WSW.
40.00 Point for the $\frac{1}{4}$ sec. cor. of secs. 31 and 36.
Set an iron post, 3 ft. long, 1 in. diam., 28 ins. in the ground, with brass cap mkd.

$\frac{1}{4}$
S36 | S31
1950

raise a mound of stone, $2\frac{1}{2}$ ft. base, 2 ft. high, W. of cor.




54.60 Wash, 15 lks. wide, course W.

62.30 Wash, 10 lks. wide, course W.

. East Boundary of T. 5 N., R. 19 W.

Chains. 78.70	Wash, 10 lks. wide, course W.
80.00	Point for the cor. of secs. 25, 30, 31 and 36. Set an iron post, 3 ft. long, 2 ins. diam., 28 ins. in the ground, with brass cap mkd. <div style="text-align: center;"> <p>T5N R19W R18W S25 S30 S36 S31 1950</p> </div>
	raise a mound of stone, 2½ ft. base, 2 ft. high, W. of cor. Land, rolling. Soil, sandy clay and gravelly. Timber, paloverde and ironwood; undergrowth, greasewood, mesquite and cacti.
	North, bet. secs. 25 and 30. Over rolling land, through scattering timber.
36.40	Wash, 60 lks. wide, course WSW.
38.00	Wash, 60 lks. wide, course SW.
40.00	Point for the ¼ sec. cor. of secs. 25 and 30. Set an iron post, 3 ft. long, 1 in. diam., 28 ins. in the ground, with brass cap mkd. <div style="text-align: center;"> <p>↑ S25 S30 1950</p> </div>
	raise a mound of stone, 2½ ft. base, 2 ft. high, W. of cor.
55.20	Wash, 15 lks. wide, course W.
80.00	Point for the cor. of secs. 19, 24, 25 and 30. Set an iron post, 3 ft. long, 2 ins. diam., 28 ins. in the ground, with brass cap mkd. <div style="text-align: center;"> <p>T5N R19W R18W S24 S19 S25 S30 1950</p> </div>
	raise a mound of stone, 2½ ft. base, 2 ft. high, W. of cor. Land, rolling. Soil, gravelly clay and rocky. Timber, paloverde and ironwood; undergrowth, greasewood and cacti.
	North, bet. secs. 19 and 24. Over rolling land, through scattering timber.
2.90	Wash, 100 lks. wide, course SW.

East Boundary of T. 5 N., R. 19 W.


Chains.	
12.70	Wash, 30 lks. wide, course SW.
24.90	Graded road, bears NE. and SW.
40.00	Point for the $\frac{1}{4}$ sec. cor. of secs. 19 and 24. Set an iron post, 3 ft. long, 1 in. diam., 28 ins. in the ground, with brass cap mkd.
	
	raise a mound of stone, 2 $\frac{1}{2}$ ft. base, 2 ft. high, W. of cor.
67.47	Road, bears ENE. and WSW.
77.90	Wash, 10 lks. wide, course W.
80.00	Point for the cor. of secs. 13, 18, 19 and 24. Set an iron post, 3 ft. long, 2 ins. diam., 28 ins. in the ground, with brass cap mkd.
	
	raise a mound of stone, 3 ft. base, 2 $\frac{1}{2}$ ft. high, W. of cor.
	Land, rolling. Soil, gravelly clay and rocky. Timber, paloverde and ironwood; undergrowth, mesquite, greasewood and cacti.
	North, bet. secs. 13 and 18. Over rolling land, through scattering timber.
17.30	Wash, 25 lks. wide, course W.
33.40	Wash, 20 lks. wide, course W.
40.00	Point for the $\frac{1}{4}$ sec. cor. of secs. 13 and 18. Set an iron post, 3 ft. long, 1 in. diam., 28 ins. in the ground, with brass cap mkd.
	
	raise a mound of stone, 2 $\frac{1}{2}$ ft. base, 2 ft. high, W. of cor.
59.50	Wash, 25 lks. wide, course WNW.
62.70	Wash, 60 lks. wide, course W.
70.30	Wash, 40 lks. wide, course WSW.
79.60	Wash, 20 lks. wide, course WSW.

East Boundary of T. 5 N., R. 19 W.

Chains.
80.00

Point for the cor. of secs. 7, 12, 13 and 18.

Set an iron post, 3 ft. long, 2 ins. diam., 16 ins. in the ground, to bedrock and in a mound of stone to top, with brass cap mkd.



Land, rolling.
Soil, sandy clay, and gravelly.
Timber, paloverde and ironwood; undergrowth, greasewood, mesquite and cacti.


North, bet. secs. 7 and 12.

Over rolling land, through scattering timber.

29.00 Wash, 40 lks. wide, course W.

40.00 Point for the $\frac{1}{4}$ sec. cor. of secs. 7 and 12.


Set an iron post, 3 ft. long, 1 in. diam., 28 ins. in the ground, with brass cap mkd.



raise a mound of stone, 2 $\frac{1}{2}$ ft. base, 2 ft. high, W. of cor.
Continue over rolling land.

80.00 Point for the cor. of secs. 1, 6, 7 and 12.

Set an iron post, 3 ft. long, 2 ins. diam., 28 ins. in the ground, with brass cap mkd.



raise a mound of stone, 2 ft. base, 1 $\frac{1}{2}$ ft. high, W. of cor.

Land, rolling.
Soil, sandy and gravelly.
Timber, paloverde and ironwood; undergrowth, greasewood and cacti.

North; bet. secs. 1 and 6.

Over rolling land, through scattering timber.

40.00 Point for the $\frac{1}{4}$ sec. cor. of secs. 1 and 6.

Set an iron post; 3 ft. long, 1 in. diam., 28 ins. in the ground, with brass cap mkd.

East Boundary of T. 5 N., R. 19 W.

Chains.

↑
S1 | S6
1950

dig pits 18x18x12 ins., N. and S. of post, 3 ft. dist.

73.99 Point for the cor. of Ts. 5 and 6 N., Rs. 18 and 19 W.;
due East of the cor. of Ts. 5 and 6 N., Rs. 19 and 20 W.

Set an iron post, 3 ft. long, 3 ins. diam., 28 ins. in the
ground, with brass cap mkd.

T6N
R19W R18W
S36 | S31
S1 | S6
T5N
1950

raise a mound of stone, 2½ ft. base, 2 ft. high, S. of cor.

Land, rolling.

Soil, sandy and gravelly.

Timber, paloverde, ironwood and mesquite; undergrowth,
greasewood and cacti.

North Boundary of T. 5 N., R. 19 W.

From the cor. of Ts. 5 and 6 N., Rs. 18 and 19 W.

West, bet. secs. 1 and 36.

Over rolling land, through scattering timber.

40.00 Point for the ¼ sec. cor. of secs. 1 and 36.

Set an iron post, 3 ft. long, 1 in. diam., 28 ins. in the
ground, with brass cap mkd.

¼ S36
S1
1950

raise a mound of stone, 2½ ft. base, 2 ft. high, N. of cor.

Continue over rolling land.

80.00 Point for the cor. of secs. 1, 2, 35 and 36.

Set an iron post, 3 ft. long, 2 ins. diam., 28 ins. in the
ground, with brass cap mkd.

T6N R19W
S35 | S36
S2 | S1
T5N
1950

dig pits 18x18x12 ins., in each sec., 3 ft. dist.

Land, rolling.

Soil, sandy and gravelly.

Timber, paloverde and ironwood; undergrowth, greasewood.

North Boundary of T. 5 N., R. 19 W.

Chains.

West, bet. secs. 2 and 35.

Over rolling land, through scattering timber.

40.00 Point for the 1/4 sec. cor. of secs. 2 and 35.

Set an iron post, 3 ft. long, 1 in. diam., 28 ins. in the ground, with brass cap mkd.

1/4 S35
S2
1950

dig pits 18x18x12 ins., E. and W. of post, 3 ft. dist.

Continue over rolling land.

80.00 Point for the cor. of secs. 2, 3, 34 and 35.

Set an iron post, 3 ft. long, 2 ins. diam., 28 ins. in the ground, with brass cap mkd.

T6N R19W
S34 | S35
S3 | S2
T5N
1950

dig pits 18x18x12 ins., in each sec., 3 ft. dist.
Land, rolling.

Soil, sandy and gravelly.

Timber, paloverde and ironwood; undergrowth, greasewood and cacti.

West, bet. secs. 3 and 34.

Over rolling land, through scattering timber.

5.83 Power line from Parker Dam, bears N. and S.

6.10 Power line service road, bears N. and S.

40.00 Point for the 1/4 sec. cor. of secs. 3 and 34.

Set an iron post, 3 ft. long, 1 in. diam., 28 ins. in the ground, with brass cap mkd.

1/4 S34
S3
1950

dig pits 18x18x12 ins., E. and W. of post, 3 ft. dist.

45.00 Low sand ridge, bears N. and S.

80.00 Point for the cor. of secs. 3, 4, 33 and 34.

Set an iron post, 3 ft. long, 2 ins. diam., 28 ins. in the ground, with brass cap mkd.

T6N R19W
S33 | S34
S4 | S3
T5N
1950

North Boundary of T. 5 N., R. 19 W.

Chains.

dig pits 18x18x12 ins., in each sec., 3 ft. dist.

Land, rolling.

Soil, sandy.

Timber, paloverde and ironwood; undergrowth, greasewood and cacti.

West, bet. secs. 4 and 33.

Over rolling land, through scattering timber.

40.00 Point for the $\frac{1}{4}$ sec. cor. of secs. 4 and 33.

Set an iron post, 3 ft. long, 1 in. diam., 28 ins. in the ground, with brass cap mkd.

$$\frac{1}{4} \frac{S33}{S4}$$
 1950

dig pits 18x18x12 ins., E. and W. of post, 3 ft. dist.

Continue over rolling land.

80.00 Point for the cor. of secs. 4, 5, 32 and 33.

Set an iron post, 3 ft. long, 2 ins. diam., 28 ins. in the ground, with brass cap mkd.

$$\begin{array}{c} T6N R19W \\ S32 | S33 \\ S5 | S4 \\ T5N \\ 1950 \end{array}$$

dig pits 18x18x12 ins., in each sec., 3 ft. dist.

Land, rolling.

Soil, sandy and gravelly.

Timber, paloverde and ironwood; undergrowth, greasewood and cacti.

West, bet. secs. 5 and 32.

Over rolling land, through scattering timber.

40.00 Point for the $\frac{1}{4}$ sec. cor. of secs. 5 and 32.

Set an iron post, 3 ft. long, 1 in. diam., 28 ins. in the ground, with brass cap mkd.

$$\frac{1}{4} \frac{S32}{S5}$$
 1950

dig pits 18x18x12 ins., E. and W. of post, 3 ft. dist.

Continue over rolling land.

80.00 Point for the cor. of secs. 5, 6, 31 and 32.

Set an iron post, 3 ft. long, 2 ins. diam., 28 ins. in the ground, with brass cap mkd.

North Boundary of T. 5 N., R. 19 W.

Chains.

T6N R19W
S31 | S32
S6 | S5
 T5N
 1950

dig pits 18x18x12 ins., in each sec., 3 ft. dist.

Land, rolling.

Soil, sandy and gravelly.

Timber, paloverde and ironwood; undergrowth, greasewood.

West, bet. secs. 6 and 31:

Over rolling land, through scattering timber.

25.80 Wash, 15 lks. wide, banks 2 ft. high, course SW.

40.00 Point for the $\frac{1}{4}$ sec. cor. of secs. 6 and 31.

Set an iron post, 3 ft. long, 1 in. diam., 28 ins. in the ground, with brass cap mkd.

$\frac{1}{4}$ S31
S6

dig pits 18x18x12 ins., E. and W. of post, 3 ft. dist.

Continue over rolling land and low sand dunes, through scattering timber.

45.40 Road, bears N. and S.

46.27 The cor. of Ts. 5 and 6 N., Rs. 19 and 20 W.

Land, rolling.

Soil, sandy.

Timber, paloverde; undergrowth, greasewood and cacti.

Subdivision of T. 5 N., R. 19 W.

The standard cor. of secs. 35 and 36, on the S. bdy. of Tp. is monumented with a granite stone 14x10x8 ins., mkd. and witnessed as described in the official record.

At the corner point

Set an iron post, 3 ft. long, 2 ins. diam., 28 ins. in the ground, with brass cap mkd.

S C
 T5N R19W
S35 | S36
 1950

Bury the original corner stone alongside the iron post.

Thence

N. 0° 01' W., bet. secs. 35 and 36.

Subdivision of T. 5 N., R. 19 W.

Chains.	Over rolling land, through scattering timber.
26.00	Wash, 50 lks. wide, banks 2 ft. high, course W.
37.40	Wash, 30 lks. wide, banks 2 ft. high, course W.
40.00	Point for the $\frac{1}{4}$ sec. cor. of secs. 35 and 36. Set an iron post, 3 ft. long, 1 in. diam., 18 ins. in the ground, to bedrock and in a mound of stone to top, with brass cap mkd.
	$\begin{array}{c} \frac{1}{4} \\ \hline \text{S35} \text{S36} \\ \hline 1950 \end{array}$
	Bury a granite stone 4x3x2 ins., mkd. X, alongside the iron post.
55.60	Wash, 35 lks. wide, banks 3 ft. high, course W.
63.50	Wash, 40 lks. wide, banks 2 ft. high, course W.
80.00	Point for the cor. of secs. 25, 26, 35 and 36. Set an iron post, 3 ft. long, 2 ins. diam., 26 ins. in the ground, with brass cap mkd.
	$\begin{array}{c} \text{T5N R19W} \\ \hline \text{S26} \text{S25} \\ \hline \text{S35} \text{S36} \\ \hline 1950 \end{array}$
	raise a mound of stone, 3 ft. base, 2 ft. high, W. of cor.
	Land, rolling. Soil, gravelly and rocky. Timber, paloverde, ironwood and mesquite; undergrowth, greasewood and cacti.
	From the cor. of secs. 25, 30, 31 and 36, on the E. bdy. of Tp.
	S. 89° 55' W., bet. secs. 25 and 36.
	Over rolling land, through scattering timber.
3.70	Wash, 30 lks. wide, banks 2 ft. high, course NW.
15.10	Same wash, course SW.
24.75	Wash, 30 lks. wide, banks 2 ft. high, course SW.
40.01	Point for the $\frac{1}{4}$ sec. cor. of secs. 25 and 36. Set an iron post, 3 ft. long, 1 in. diam., 28 ins. in the ground, with brass cap mkd.
	$\begin{array}{c} \frac{1}{4} \text{ S25} \\ \hline \text{S36} \\ \hline 1950 \end{array}$
	raise a mound of stone, 2 ft. base, 1 $\frac{1}{2}$ ft. high, N. of cor.
47.50	Wash, 15 lks. wide, course SW.

Subdivision of T. 5 N., R. 19 W.

Chains.

80.02 The cor. of secs. 25, 26, 35 and 36.

Land, rolling.
Soil, rocky and gravelly.
Timber, paloverde and ironwood; undergrowth, greasewood and cacti.


N. 0° 01' W., bet. secs. 25 and 26.

Over rolling land, through scattering timber.

24.10 Draw, course N. 60° W.

40.00 Point for the $\frac{1}{4}$ sec. cor. of secs. 25 and 26.

Set an iron post, 3 ft. long, 1 in. diam., 18 ins. in the ground, to bedrock and in a mound of stone to top, with brass cap mkd.



Bury a granite stone 5x4x2 ins., mkd. X, alongside the iron post.

40.75 Wash, 20 lks. wide, banks 3 ft. high, course W.

49.00 Wash, 40 lks. wide, banks 2 ft. high, course N. 70° W.


55.50 Wash, 50 lks. wide, banks 2 ft. high, course W.

59.00 Wash, 30 lks. wide, banks 2 ft. high, course S. 60° W.

79.00 Road, bears E. and W.

80.00 Point for the cor. of secs. 23, 24, 25 and 26.

Set an iron post, 3 ft. long, 2 ins. diam., 28 ins. in the ground, with brass cap mkd.



raise a mound of stone, 2½ ft. base, 2 ft. high, W. of cor.

From the cor. a U. S. Geological Survey station bears S. 74° 10' W., 10.78 chs. dist., and is monumented with a brass cap set in a concrete shaft, 6 ins. sq., projecting 12 ins. above ground, mkd.

USGS

N18 1926



Land, rolling.
Soil, gravelly and rocky.
Timber, paloverde, ironwood and cat's claw; undergrowth, greasewood and cacti.

Subdivision of T. 5 N., R. 19 W.

BOOK 4090

Chains.	<p>From the cor. of secs. 19, 24, 25 and 30 on the E. bdy. of Tp.</p> <p>S. 89° 55' W., bet. secs. 24 and 25.</p> <p>Over rolling land, through scattering timber.</p> <p>12.80 Wash, 70 lks. wide, banks 3 ft. high, course S. 60° W.</p> <p>35.00 Wash, 15 lks. wide, course S. 60° W.</p> <p>40.00 Point for the $\frac{1}{4}$ sec. cor. of secs. 24 and 25.</p> <p>Set an iron post, 3 ft. long, 1 in. diam., 28 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center;"> $\begin{array}{r} S24 \\ \frac{1}{4} \hline S25 \\ 1950 \end{array}$ </div> <p>raise a mound of stone, 3 ft. base, 2$\frac{1}{2}$ ft. high, N. of cor.</p> <p>55.00 Road, bears ENE. and WSW.</p> <p>80.00 The cor. of secs. 23, 24, 25 and 26.</p> <p>Land, rolling. Soil, gravelly and rocky. Timber, paloverde, ironwood and cat's claw; undergrowth, greasewood and cacti.</p> <hr/> <p>N. 0° 01' W., bet. secs. 23 and 24.</p> <p>Over rolling land, through scattering timber.</p> <p>2.90 Wash, 20 lks. wide, banks 2 ft. high, course S. 70° W.</p> <p>17.50 Wash, 20 lks. wide, course S. 70° W.</p> <p>38.50 Wash, 10 lks. wide, course SW.</p> <p>40.00 Point for the $\frac{1}{4}$ sec. cor. of secs. 23 and 24.</p> <p>Set an iron post, 3 ft. long, 1 in. diam., 28 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center;"> $\begin{array}{c} \uparrow \\ S23 \mid S24 \\ 1950 \end{array}$ </div> <p>raise a mound of stone, 2$\frac{1}{2}$ ft. base, 2 ft. high, W. of cor.</p> <p>66.10 Road, bears E. and W.</p> <p>76.10 Wash, 20 lks. wide, banks 2 ft. high, course S. 70° W.</p> <p>80.00 Point for the cor. of secs. 13, 14, 23 and 24.</p> <p>Set an iron post, 3 ft. long, 2 ins. diam., 28 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center;"> $\begin{array}{c} T5N R19W \\ S14 \mid S13 \\ S23 \mid S24 \\ 1950 \end{array}$ </div>
---------	---

Subdivision of T. 5 N., R. 19 W.

Chains.

raise a mound of stone, 2½ ft. base, 2 ft. high, W. of cor.
Land, rolling.
Soil, gravelly and rocky.
Timber, paloverde, ironwood and cat's claw; undergrowth, greasewood and cacti.

From the cor. of secs. 13, 18, 19 and 24, on the E. bdy. of Tp.

S. 89° 53' W., bet. secs. 13 and 24.

Over rolling land, through scattering timber.

12.50 Wash, 10 lks. wide, course SW.

40.04 Point for the ¼ sec. cor. of secs. 13 and 24.

Set an iron post, 3 ft. long, 1 in. diam., 28 ins. in the ground, with brass cap mkd.

¼ S13
S24
1950

raise a mound of stone, 2½ ft. base, 2 ft. high, N. of cor.

44.60 Wash, 10 lks. wide, course SW.

80.08 The cor. of secs. 13, 14, 23 and 24.

Land, rolling.
Soil, gravelly and rocky.
Timber, paloverde and ironwood; undergrowth, greasewood and cacti.

N. 0° 01' W., bet. secs. 13 and 14.

Over rolling land, through scattering timber.

30.25 Wash, 20 lks. wide, banks 2 ft. high, course N. 20° W.

31.60 Wash, 15 lks. wide, course W.

34.50 Wash, 70 lks. wide, banks 2 ft. high, course W.

36.50 Wash, 30 lks. wide, banks 2 ft. high, course SW.

40.00 Point for the ¼ sec. cor. of secs. 13 and 14.

Set an iron post, 3 ft. long, 1 in. diam., 28 ins. in the ground, with brass cap mkd.

¼
S14 | S13
1950

raise a mound of stone, 2½ ft. base, 2 ft. high, W. of cor.

47.50 Wash, 40 lks. wide, banks 2 ft. high, course W.

56.00 Wash, 20 lks. wide, banks 2 ft. high, course S. 70° W.

80.00 Point for the cor. of secs. 11, 12, 13 and 14.

Subdivision of T. 5 N., R. 19 W.

4890

Chains.

Set an iron post, 3 ft. long, 2 ins. diam., 28 ins. in the ground, with brass cap mkd.

T5N R19W

S11 | S12

S14 | S13

1950

raise a mound of stone, 2½ ft. base, 2 ft. high, W. of cor.

Land, rolling.

Soil, gravelly and rocky.

Timber, paloverde, ironwood and cat's claw; undergrowth, greasewood and cacti.

From the cor. of secs. 7, 12, 13 and 18, on the E. bdy. of Tp.

S. 89° 50' W., bet. secs. 12 and 13.

Over rolling land, through scattering timber.

3.70 Wash, 30 lks. wide, course S. 60° W.

40.06 Point for the ¼ sec. cor. of secs. 12 and 13.

Set an iron post, 3 ft. long, 1 in. diam., 28 ins. in the ground, with brass cap mkd.

¼ S12

¼ S13

1950

raise a mound of stone, 2½ ft. base, 2 ft. high, N. of cor.

Continue over rolling land.

80.12 The cor. of secs. 11, 12, 13 and 14.

Land, rolling.

Soil, gravelly and rocky.

Timber, paloverde, ironwood and cat's claw; undergrowth, greasewood and cacti.

N. 0° 01' W., bet. secs. 11 and 12.

Over rolling land, through scattering timber.

16.60 Wash, 25 lks. wide, banks 2 ft. high, course W.

40.00 Point for the ¼ sec. cor. of secs. 11 and 12.

Set an iron post, 3 ft. long, 1 in. diam., 28 ins. in the ground, with brass cap mkd.

S11 | S12

1950

raise a mound of stone, 2½ ft. base, 2 ft. high, W. of cor.

80.00 Point for the cor. of secs. 1, 2, 11 and 12.

Subdivision of T. 5 N., R. 19 W.

Chains.

Set an iron post, 3 ft. long, 2 ins. diam., 28 ins. in the ground, with brass cap mkd.

T5N R19W

S2 | S1

S11 | S12

1950

from which

A paloverde, 12 ins. diam., bears N. 34½° E., 316 lks. dist., mkd. T5N R19W S1 BT.

A paloverde, 10 ins. diam., bears N. 45¾° W., 319 lks. dist., mkd. T5N R19W S2 BT.

Dig pits 18x18x12 ins., in each sec., 3 ft. dist.

Land, rolling.

Soil, gravelly and rocky.

Timber, paloverde and ironwood; undergrowth, greasewood and cacti.

From the cor. of secs. 1, 6, 7 and 12, on the E. bdy. of Tp.

S. 89° 49' W., bet. secs. 1 and 12.

Over rolling land, through scattering timber.

40.06 Point for the ¼ sec. cor. of secs. 1 and 12.

Set an iron post, 3 ft. long, 1 in. diam., 28 ins. in the ground, with brass cap mkd.

¼ S1

S12

1950

from which

A paloverde, 10 ins. diam., bears S. 27° E., 345 lks. dist., mkd. ¼ S12 BT.

A paloverde, 10 ins. diam., bears N. 47° W., 299 lks. dist., mkd. ¼ S1 BT.

Continue over rolling land, through scattering timber.

80.12 The cor. of secs. 1, 2, 11 and 12.

Land, rolling.

Soil, gravelly and rocky.

Timber, paloverde and ironwood; undergrowth, greasewood and cacti.

N. 0° 06' E., bet. secs. 1 and 2.

Over rolling land, through scattering timber.

40.00 Point for the ¼ sec. cor. of secs. 1 and 2.

Set an iron post, 3 ft. long, 1 in. diam., 28 ins. in the ground, with brass cap mkd.

Subdivision of T. 5 N., R. 19 W.

ECON 4390

Chains.

$\frac{1}{4}$
 S2 | S1
 1950

raise a mound of stone, $2\frac{1}{2}$ ft. base, 2 ft. high, W. of cor.
Continue over rolling land.

74.26 Intersect N. bdy. of the Tp., at the cor. of secs. 1, 2,
35 and 36.

Land, rolling.
Soil, sandy and gravelly.
Timber, paloverde and ironwood; undergrowth, greasewood
and cacti.

The standard cor. of secs. 34 and 35, on the S. bdy. of
Tp., is monumented with a granite stone 16x10x6 ins.,
mkd. and witnessed as described in the official record.

At the corner point

Set an iron post, 3 ft. long, 2 ins. diam., 28 ins. in the
ground, with brass cap mkd.

S C
 T5N R19W
S34 | S35

1950

Bury the original corner stone alongside the iron post.

Thence

N. $0^{\circ} 01'$ W., bet. secs. 34 and 35.

Over rolling land, through scattering timber.

10.00 Wash, 15 lks. wide, banks 2 ft. high, course W.

17.40 Wash, 50 lks. wide, banks 2 ft. high, course S. 80° W.

40.00 Point for the $\frac{1}{4}$ sec. cor. of secs. 34 and 35.

Set an iron post, 3 ft. long, 1 in. diam., 28 ins. in the
ground, with brass cap mkd.

$\frac{1}{4}$
 S34 | S35
 1950

raise a mound of stone, $2\frac{1}{2}$ ft. base, 2 ft. high, W. of cor.

52.00 Wash, 25 lks. wide, banks 2 ft. high, course W.

54.00 Wash, 35 lks. wide, banks 2 ft. high, course W.

80.00 Point for the cor. of secs. 26, 27, 34 and 35.

Set an iron post, 3 ft. long, 2 ins. diam., 28 ins. in the
ground, with brass cap mkd.

Subdivision of T. 5 N., R. 19 W.

Chains.	<p>T5N R19W <u>S27</u> <u>S26</u> <u>S34</u> <u>S35</u> 1950</p>
	<p>raise a mound of stone, 2 ft. base, 2½ ft. high, W. of cor. Land, rolling. Soil, gravelly and rocky. Timber, paloverde, ironwood and cat's claw; undergrowth, greasewood and cacti.</p>
	<p>From the cor. of secs. 25, 26, 35 and 36. N. 89° 55' W., bet. secs. 26 and 35. Over rolling land, through scattering timber.</p>
39.99	<p>Point for the ¼ sec. cor. of secs. 26 and 35. Set an iron post, 3 ft. long, 1 in. diam., 28 ins. in the ground, with brass cap mkd.</p>
	<p> S26 ¼ ——— S35 1950</p>
	<p>raise a mound of stone, 2½ ft. base, 2 ft. high, N. of cor. Continue over rolling land, through scattering timber.</p>
79.98	<p>The cor. of secs. 26, 27, 34 and 35. Land, rolling. Soil, gravelly and rocky. Timber, paloverde, ironwood and cat's claw; undergrowth, greasewood and cacti.</p>
	<p>N. 0° 01' W., bet. secs. 26 and 27. Over rolling land, through scattering timber.</p>
38.60	<p>Wash, 50 lks. wide, banks 3 ft. high, course W.</p>
40.00	<p>Point for the ¼ sec. cor. of secs. 26 and 27. Set an iron post, 3 ft. long, 1 in. diam., 28 ins. in the ground, with brass cap mkd.</p>
	<p> ¼ S27 S26 1950</p>
	<p>raise a mound of stone, 2½ ft. base, 2 ft. high, W. of cor.</p>
46.90	<p>Wash, 35 lks. wide, banks 3 ft. high, course W.</p>
51.60	<p>Partially improved road, bears E. and W.</p>
69.00	<p>Wash, 20 lks. wide, banks 2 ft. high, course W.</p>
80.00	<p>Point for the cor. of secs. 22, 23, 26 and 27. Set an iron post, 3 ft. long, 2 ins. diam., 28 ins. in the ground, with brass cap mkd.</p>

Subdivision of T. 5 N., R. 19 W.

BOOK 4890

Chains.

T5N R19W
S22|S23
S27|S26
1950

raise a mound of stone, 2½ ft. base, 2 ft. high, W. of cor.

Land, rolling.
Soil, gravelly and rocky.
Timber, paloverde, ironwood and eat's claw; undergrowth, greasewood and cacti.

From the cor. of secs. 23, 24, 25 and 26.

N. 89° 51' W., bet. secs. 23 and 26.

Over rolling land, through scattering timber.

6.70 Wash, 15 lks. wide, banks 2 ft. high, course S. 60° W.

9.80 Same wash, course N. 60° W.

12.00 Same wash, course S. 65° W.

26.50 Wash, 20 lks. wide, banks 2 ft. high, course S. 80° W.

32.00 Same wash noted at 12.00 chs., course N. 60° W.

39.98 Point for the ¼ sec. cor. of secs. 23 and 26.

Set an iron post, 3 ft. long, 1 in. diam., 28 ins. in the ground, with brass cap mkd.

¼ S23
S26
1950

raise a mound of stone, 2½ ft. base, 2 ft. high, N. of cor.

79.96 The cor. of secs. 22, 23, 26 and 27.

Land, rolling.
Soil, gravelly and rocky.
Timber, paloverde and ironwood; undergrowth, greasewood and cacti.

N. 0° 01' W., bet. secs. 22 and 23.

Over rolling land, through scattering timber.

5.00 Unimproved road, bears E. and W.

10.75 Wash, 20 lks. wide, banks 3 ft. high, course N. 80° W.

40.00 Point for the ¼ sec. cor. of secs. 22 and 23.

Set an iron post, 3 ft. long, 1 in. diam., 28 ins. in the ground, with brass cap mkd.

¼
S22|S23
1950

raise a mound of stone, 2½ ft. base, 2 ft. high, W. of cor.

Subdivision of T. 5 N., R. 19 W.

Chains. 48.00 57.00 75.80 80.00	<p>Wash, 30 lks. wide, banks 4 ft. high, course W.</p> <p>Wash, 20 lks. wide, banks 5 ft. high, course W.</p> <p>Wash, 15 lks. wide, banks 3 ft. high, course W.</p> <p>Point for the cor. of secs. 14, 15, 22 and 23.</p> <p>Set an iron post, 3 ft. long, 2 ins. diam., 18 ins. in the ground, to bedrock and in a mound of stone to top, with brass cap mkd.</p> <p style="text-align: center;">T5N R19W S15 S14 S22 S23 1950</p> <p>Bury a granite stone, 4x3x2 ins., mkd. X, alongside the iron post.</p> <p>Land, rolling. Soil, gravelly and rocky. Timber, paloverde and ironwood; undergrowth, greasewood and cacti.</p> <hr/> <p>From the cor. of secs. 13, 14, 23 and 24. N. 89° 51' W., bet. secs. 14 and 23. Over rolling land, through scattering timber.</p> <p>20.30 Wash, 15 lks. wide, banks 2 ft. high, course SW.</p> <p>39.96 Point for the ¼ sec. cor. of secs. 14 and 23.</p> <p>Set an iron post, 3 ft. long, 1 in. diam., 28 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">¼ S14 S23 1950</p> <p>raise a mound of stone, 2½ ft. base, 2 ft. high, N. of cor.</p> <p>64.70 Wash, 20 lks. wide, course S. 60° W.</p> <p>79.92 The cor. of secs. 14, 15, 22 and 23.</p> <p>Land, rolling. Soil, gravelly and rocky. Timber, paloverde, ironwood and cat's claw; undergrowth, greasewood and cacti.</p> <hr/> <p>N. 0° 01' W., bet. secs. 14 and 15. Over rolling land, through scattering timber.</p> <p>15.00 Wash, 20 lks. wide, banks 2 ft. high, course W.</p> <p>25.40 Wash, 40 lks. wide, course SW.</p> <p>40.00 Point for the ¼ sec. cor. of secs. 14 and 15.</p> <p>Set an iron post, 3 ft. long, 1 in. diam., 28 ins. in the ground, with brass cap mkd.</p>
---	---

Subdivision of T. 5 N., R. 19 W.

BOOK 4390

Chains.

$$\begin{array}{c} \frac{1}{4} \\ \uparrow \\ S15 | S14 \\ \downarrow \\ 1950 \end{array}$$

- raise a mound of stone, 2 ft. base, $1\frac{1}{2}$ ft. high, W. of cor.
- 48.50 Wash, 15 lks. wide, banks 4 ft. high, course W.
- 72.50 Wash, 20 lks. wide, banks 2 ft. high, course W.
- 80.00 Point for the cor. of secs. 10, 11, 14 and 15.

Set an iron post, 3 ft. long, 2 ins. diam., 28 ins. in the ground, with brass cap mkd.

$$\begin{array}{c} T5N R19W \\ \hline S10 | S11 \\ \hline S15 | S14 \\ 1950 \end{array}$$

raise a mound of stone, $2\frac{1}{2}$ ft. base, 2 ft. high, W. of cor.

Land, rolling.

Soil, gravelly and rocky.

Timber, paloverde and ironwood; undergrowth, greasewood and cacti.

From the cor. of secs. 11, 12, 13 and 14.

N. $89^{\circ} 48'$ W., bet. secs. 11 and 14.

Over rolling land, through scattering timber.

- 39.96 Point for the $\frac{1}{4}$ sec. cor. of secs. 11 and 14.

Set an iron post, 3 ft. long, 1 in. diam., 28 ins. in the ground, with brass cap mkd.

$$\begin{array}{c} S11 \\ \frac{1}{4} \text{ ---} \\ S14 \\ 1950 \end{array}$$

raise a mound of stone, $2\frac{1}{2}$ ft. base, 2 ft. high, N. of cor.

- 57.00 Wash, 30 lks. wide, course S. 10° W.

- 79.92 The cor. of secs. 10, 11, 14 and 15.

Land, rolling.

Soil, gravelly and rocky.

Timber, paloverde and ironwood; undergrowth, greasewood and cacti.

N. $0^{\circ} 01'$ W., bet. secs. 10 and 11.


Over rolling land, through scattering timber.

- 40.00 Point for the $\frac{1}{4}$ sec. cor. of secs. 10 and 11.

Set an iron post; 3 ft. long, 1 in. diam., 28 ins. in the ground, with brass cap mkd.

Subdivision of T. 5 N., R. 19 W.

Chains.




from which

A paloverde, 8 ins. diam., bears N. $47\frac{1}{2}^\circ$ E., 143 lks. dist., mkd. $\frac{1}{4}$ S11 BT.

A paloverde, 3 ins. diam., bears N. 11° W., 141 lks. dist., mkd. BT.

A U.S. Geological Survey station bears N. $89^\circ 47'$ W., 4.97 chs. dist. and is monumented with a brass tablet, set in a cement form 12 ins. sq., 4 ins. above ground, mkd.


G S
POSA



Continue over rolling land.

80.00 Point for the cor. of secs. 2, 3, 10 and 11.

Set an iron post, 3 ft. long, 2 ins. diam., 28 ins. in the ground, with brass cap mkd.



raise a mound of stone, $2\frac{1}{2}$ ft. base, 2 ft. high, W. of cor.

Land, rolling.

Soil, gravelly and rocky.

Timber, paloverde and ironwood; undergrowth, greasewood and cacti.


From the cor. of secs. 1, 2, 11 and 12.

N. $89^\circ 49'$ W., bet. secs. 2 and 11.

Over rolling land, through scattering timber.

39.95 Point for the $\frac{1}{4}$ sec. cor. of secs. 2 and 11.

Set an iron post, 3 ft. long, 1 in. diam., 28 ins. in the ground, with brass cap mkd.



raise a mound of stone, $2\frac{1}{2}$ ft. base, 2 ft. high, N. of cor.

79.90 The cor. of secs. 2, 3, 10 and 11.

Land, rolling.

Soil, sandy, rocky and gravelly.

Timber, paloverde and ironwood; undergrowth, greasewood and cacti.

Subdivision of T. 5 N., R. 19 W.


Chains.

North, bet. secs. 2 and 3.

Over rolling land, through scattering timber.

40.00 Point for the 1/4 sec. cor. of secs. 2 and 3.

Set an iron post, 3 ft. long, 1 in. diam., 28 ins. in the ground, with brass cap mkd.



dig pits 18x18x12 ins., N. and S. of post, 3 ft. dist.

Continue over rolling land.

74.04 Intersect N. bdy. of Tp., at the cor. of secs. 2, 3, 34 and 35.

Land, rolling.


Soil, sandy and gravelly.

Timber, paloverde and ironwood; undergrowth, greasewood and cacti.

The standard cor. of secs. 33 and 34, on the S. bdy. of Tp. is monumented with a malpais stone 14x12x8 ins., mkd. and witnessed as described in the official record.

At the corner point

Set an iron post, 3 ft. long, 2 ins. diam., 28 ins. in the ground, with brass cap mkd.



Bury the original corner stone alongside the iron post.

Thence

N. 0° 02' W.; bet. secs. 33 and 34.

Over rolling land, through scattering timber.

* 17.90 Wash, 30 lks. wide, course W.

23.80 Wash, 20 lks. wide, course WSW.

37.00 Wash, 12 lks. wide, course SW.

40.00 Point for the 1/4 sec. cor. of secs. 33 and 34.

Set an iron post, 3 ft. long, 1 in. diam., 28 ins. in the ground, with brass cap mkd.



raise a mound of stone, 2 1/2 ft. base, 2 ft. high, W. of cor.

Subdivision of T. 5 N., R. 19 W.


Chains.	
65.70	Wash, 35 lks. wide, course W.
69.70	Wash, 60 lks. wide, course W.
80.00	Point for the cor. of secs. 27, 28, 33 and 34.
	Set an iron post, 3 ft. long, 2 in. diam., 28 ins. in the ground, with brass cap mkd.
	T5N R19W <u>S28 S27</u> S33 S34 1950
	raise a mound of stone, 2½ ft. base, 2 ft. high, W. of cor.
	Land, rolling.
	Soil, gravelly clay.
	Timber, paloverde and ironwood; undergrowth, mesquite, greasewood and cacti.
<hr/>	
	From the cor. of secs. 26, 27, 34 and 35.
	N. 89° 56' W., bet. secs. 27 and 34.
	Over rolling land, through scattering timber.
6.04	Power Line from Parker Dam., bears N. and S.
6.44	Power Line maintenance road, bears N. and S.
40.01	Point for the ¼ sec. cor. of secs. 27 and 34.
	Set an iron post, 3 ft. long, 1 in. diam., 28 ins. in the ground, with brass cap mkd.
	S27 ¼ <u> </u> S34 1950
	raise a mound of stone, 2½ ft. base, 2 ft. high, W. of cor.
	Continue over rolling land, through scattering timber.
80.02	The cor. of secs. 27, 28, 33 and 34.
	Land, rolling.
	Soil, gravelly clay.
	Timber, paloverde and ironwood; undergrowth, greasewood, mesquite and cacti.
<hr/>	
	N. 0° 02' W., bet. secs. 27 and 28.
	Over rolling land, through scattering timber.
2.00	Low spur, slopes W.
8.37	Graded road, bears E. and W.
19.70	Wash, 25 lks. wide, course W.
25.00	Wash, 60 lks. wide, course W.
40.00	Point for the ¼ sec. cor. of secs. 27 and 28.
	Set an iron post, 3 ft. long, 1 in. diam., 28 ins. in the ground, with brass cap mkd.

Subdivision of T. 5 N., R. 19 W.

Chains.	
	$\begin{array}{c} \frac{1}{4} \\ \hline \text{S28} \mid \text{S27} \\ \hline 1950 \end{array}$
	raise a mound of stone, 2½ ft. base, 2 ft. high, W. of cor. Continue over rolling land, through scattering timber.
80.00	Point for the cor. of secs. 21, 22, 27 and 28. Set an iron post, 3 ft. long, 2 ins. diam., 28 ins. in the ground, with brass cap mkd.
	$\begin{array}{c} \text{T5N R19W} \\ \hline \text{S21} \mid \text{S22} \\ \hline \text{S28} \mid \text{S27} \\ \hline 1950 \end{array}$
	raise a mound of stone, 2½ ft. base, 2 ft. high, W. of cor. Land, rolling. Soil, clay and gravelly. Timber, paloverde and ironwood; undergrowth, greasewood, mesquite and cacti.
	From the cor. of secs. 22, 23, 26 and 27. N. 89° 56' W., bet. secs. 22 and 27. Over rolling land, through scattering timber.
6.06	Power Line from Parker Dam, bears N. and S.
6.46	Power Line maintenance road, bears N. and S.
40.03	Point for the ¼ sec. cor. of secs. 22 and 27. Set an iron post, 3 ft. long, 1 in. diam., 28 ins. in the ground, with brass cap mkd.
	$\begin{array}{c} \text{S22} \\ \hline \frac{1}{4} \\ \hline \text{S27} \\ \hline 1950 \end{array}$
57.40	raise a mound of stone, 2½ ft. base, 2 ft. high, N. of cor. Wash, 20 lks. wide, course WNW.
80.06	The cor. of secs. 21, 22, 27 and 28. Land, rolling. Soil, gravelly clay. Timber, paloverde and ironwood; undergrowth, greasewood, mesquite and cacti.
	N. 0° 02' W., bet. secs. 21 and 22. Over rolling land, through scattering timber.
3.50	Wash, 20 lks, wide, course W.
40.00	Point for the ¼ sec. cor. of secs. 21 and 22. Set an iron post, 3 ft. long, 1 in. diam., 28 ins. in the ground, with brass cap mkd.

Subdivision of T. 5 N., R. 19 W.

Chains.



raise a mound of stone, 3 ft. base, 2½ ft. high, W. of cor.

45.50 Unimproved road, bears NE. and SW.


50.00 Wash, 40 lks. wide, course W.

53.80 Wash, 38 lks. wide, course WSW.

62.20 Wash, 30 lks. wide, course SW.

80.00 Point for the cor. of secs. 15, 16, 21 and 22.

Set an iron post, 3 ft. long, 2 ins. diam., 28 ins. in the ground, with brass cap mkd.



raise a mound of stone, 3 ft. base, 2½ ft. high, W. of cor. Land, rolling.

Soil, gravelly clay.

Timber, paloverde and ironwood; undergrowth, greasewood, mesquite and cacti.

From the cor. of secs. 14, 15, 22 and 23.

N. 89° 56' W., bet. secs. 15 and 22.

Over rolling land, through scattering timber.

6.02 Power Line from Parker Dam, bears N. and S.

6.37 Power Line maintenance road, bears N. and S.


20.30 Wash, 20 lks. wide, course WNW.

24.30 Wash, 20 lks. wide, course WSW.

37.39 Unimproved road, bears N. and S.

40.02 Point for the ¼ sec. cor. of secs. 15 and 22.

Set an iron post, 3 ft. long, 1 in. diam., 28 ins. in the ground, with brass cap mkd.



raise a mound of stone, 2½ ft. base, 2 ft. high, N. of cor.

44.15 Wash, 20 lks. wide, course WNW.

60.70 Same wash, course SW.

80.04 The cor. of secs. 15, 16, 21 and 22.

Subdivision of T. 5 N., R. 19 W.

Chains.	<p>Land, rolling. Soil, gravelly clay. Timber, paloverde and ironwood; undergrowth, greasewood, mesquite and cacti.</p> <hr/> <p>N. 0° 02' W., bet. secs. 15 and 16. Over rolling land, through scattering timber.</p> <p>2.47 Road, bears E. and W.</p> <p>17.10 Center of wash, 125 lks. wide, course WSW.</p> <p>31.80 Wash, 30 lks. wide, course W.</p> <p>40.00 Point for the $\frac{1}{4}$ sec. cor. of secs. 15 and 16. Set an iron post, 3 ft. long, 1 in. diam., 28 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center;"> $\frac{1}{4}$ <table style="margin: auto;"> <tr> <td>S16</td> <td> </td> <td>S15</td> </tr> <tr> <td colspan="3">1950</td> </tr> </table> </div> <p>raise a mound of stone, 2½ ft. base, 2 ft. high, W. of cor.</p> <p>68.70 Wash, 15 lks. wide, course SW.</p> <p>73.30 Unimproved road, bears E. and WSW.</p> <p>80.00 Point for the cor. of secs. 9, 10, 15 and 16. Set an iron post, 3 ft. long, 2 ins. diam., 28 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center;"> <table style="margin: auto;"> <tr> <td colspan="2">T5N R19W</td> </tr> <tr> <td>S9</td> <td> S10</td> </tr> <tr> <td>S16</td> <td> S15</td> </tr> <tr> <td colspan="2">1950</td> </tr> </table> </div> <p>raise a mound of stone, 3 ft. base, 2½ ft. high, W. of cor.</p> <p>Land, rolling. Soil, gravelly clay. Timber, paloverde and ironwood; undergrowth, greasewood, mesquite and cacti.</p> <hr/> <p>From the cor. of secs. 10, 11, 14 and 15. N. 89° 56' W., bet. secs. 10 and 15. Over rolling land, through scattering timber.</p> <p>5.94 Power Line, from Parker Dam, bears N. and S.</p> <p>6.31 Power Line maintenance road, bears N. and S.</p> <p>40.01 Point for the $\frac{1}{4}$ sec. cor. of secs. 10 and 15. Set an iron post, 3 ft. long, 1 in. diam., 28 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center;"> $\frac{1}{4}$ <table style="margin: auto;"> <tr> <td>S10</td> </tr> <tr> <td>S15</td> </tr> <tr> <td>1950</td> </tr> </table> </div>	S16		S15	1950			T5N R19W		S9	S10	S16	S15	1950		S10	S15	1950
S16		S15																
1950																		
T5N R19W																		
S9	S10																	
S16	S15																	
1950																		
S10																		
S15																		
1950																		

Subdivision of T. 5 N., R. 19 W.

Chains.

dig pits 18x18x12 ins., E. and W. of post, 3 ft. dist.

74.74 Unimproved road, bears N. and S.

80.02 The cor. of secs. 9, 10, 15 and 16.


Land, rolling.
Soil, sandy and gravelly.
Timber, paloverde and ironwood; undergrowth, greasewood, mesquite and cacti.

N. 0° 02' W., bet. secs. 9 and 10.

Over rolling land, through scattering timber.

40.00 Point for the 1/4 sec. cor. of secs. 9 and 10.

Set an iron post, 3 ft. long, 1 in. diam., 28 ins. in the ground, with brass cap mkd.



from which


A paloverde, 6 ins. diam., bears N. 18 1/2° E., 117 lks. dist., mkd. 1/4 S10 BT.

A paloverde, 8 ins. diam., bears S. 5 1/4° W., 61 lks. dist., mkd. 1/4 S9 BT.

Continue over rolling land.

80.00 Point for the cor. of secs. 3, 4, 9 and 10.

Set an iron post, 3 ft. long, 2 ins. diam., 28 ins. in the ground, with brass cap mkd.



from which

A paloverde, 5 ins. diam., bears S. 69° E., 226 lks. dist., mkd. BT.

A paloverde, 5 ins. diam., bears S. 37° W., 193 lks. dist., mkd. BT.

Dig pits 18x18x12 ins., NE. and NW. of post., 3 ft. dist.

Land, rolling.
Soil, sandy and gravelly.
Timber, paloverde and ironwood; undergrowth, greasewood and cacti.

From the cor. of secs. 2, 3, 10 and 11.

N. 89° 53' W., bet. secs. 3 and 10.

Over rolling land, through scattering timber.

Subdivision of T. 5 N., R. 19 W.

Chains. 5.80 6.20 40.01	<p>Power Line from Parker Dam, bears N. and S.</p> <p>Power Line maintenance road, bears N. and S.</p> <p>Point for the $\frac{1}{4}$ sec. cor. of secs. 3 and 10.</p> <p>Set an iron post, 3 ft. long, 1 in. diam., 28 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center;"> $\begin{array}{r} S3 \\ \frac{1}{4} \text{---} \\ S10 \\ 1950 \end{array}$ </div> <p>raise a mound of stone, 2$\frac{1}{2}$ ft. base, 2 ft. high, N. of cor.</p> <p>Continue over rolling land.</p>
80.02	<p>The cor. of secs. 3, 4, 9 and 10.</p> <p>Land, rolling. Soil, sandy and gravelly. Timber, paloverde and ironwood; undergrowth, greasewood and cacti.</p>
40.00	<p>N. 0° 01' E., bet. secs. 3 and 4.</p> <p>Over rolling land, through scattering timber.</p> <p>Point for the $\frac{1}{4}$ sec. cor. of secs. 3 and 4.</p> <p>Set an iron post, 3 ft. long, 1 in. diam., 28 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center;"> $\begin{array}{c} \frac{1}{4} \\ \\ S4 \quad S3 \\ \\ 1950 \end{array}$ </div> <p>dig pits 18x18x12 ins., N. and S. of post, 3 ft. dist.</p> <p>Continue over rolling land.</p>
46.80	<p>Low sand ridge, bears E. and W.</p>
73.91	<p>Intersect the N. bdy. of Tp. at the cor. of secs. 3, 4, 33 and 34.</p> <p>Land, rolling. Soil, sandy and gravelly. Timber, paloverde and ironwood; undergrowth, greasewood and cacti.</p>
	<p>The standard cor. of secs. 32 and 33, on the S. bdy. of Tp. is monumented with a granite stone 14x12x8 ins., mkd. and witnessed as described in the official record.</p> <p>At the corner point</p> <p>Set an iron post, 3 ft. long, 2 ins. diam., 28 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center;"> $\begin{array}{c} S C \\ T5N R19W \\ \underline{S32 S33} \\ 1950 \end{array}$ </div>

Subdivision of T. 5 N., R. 19 W.

Chains.

Bury the original corner stone alongside the iron post.

Thence

N. 0° 02' W., bet. secs. 32 and 33.

Over rolling land, through scattering timber.


4.00 Wash, 40 lks. wide, course WNW.

13.70 Center of wash, 200 lks. wide, course NW.

27.45 Center of wash, 150 lks. wide, course NW.

40.00 Point for the 1/4 sec. cor. of secs. 32 and 33.

Set an iron post, 3 ft. long, 1 in. diam., 28 ins. in the ground, with brass cap mkd.




raise a mound of stone, 3 ft. base, 2 1/2 ft. high, W. of cor.

47.90 Wash, 15 lks. wide, course NW.

70.37 Graded road, bears ENE. and WSW.

80.00 Point for the cor. of secs. 28, 29, 32 and 33.

Set an iron post, 3 ft. long, 2 ins. diam., 28 ins. in the ground, with brass cap mkd.



raise a mound of stone, 3 ft. base, 2 1/2 ft. high, W. of cor.

Land, rolling.

Soil, gravelly and clay.

Timber, paloverde and ironwood; undergrowth, greasewood and cacti.

From the cor. of secs. 27, 28, 33 and 34.

S. 89° 55' W., bet. secs. 28 and 33.


Over rolling land, through scattering timber.

37.80 Wash, 10 lks. wide, course WNW.

38.11 Graded road, bears NE. and WSW.

39.98 Point for the 1/4 sec. cor. of secs. 28 and 33.

Set an iron post, 3 ft. long, 1 in. diam., 28 ins. in the ground, with brass cap mkd.



raise a mound of stone, 2 1/2 ft. base, 2 ft. high, N. of cor.

Subdivision of T. 5 N., R. 19 W.


BOOK 4890

Chains.	
55.70	Wash, 15 lks. wide, course WSW.
71.80	Wash, 12 lks. wide, course WNW.
78.86	Wash, 10 lks. wide, course NW.
79.96	The cor. of secs. 28, 29, 32 and 33.
	Land, rolling. Soil, gravelly clay. Timber, paloverde and ironwood; undergrowth, greasewood and cacti.
	N. 0° 02' W., bet. secs. 28 and 29.
	Over rolling land, through scattering timber.
3.75	Wash, 10 lks. wide, course NW.
6.90	Wash, 10 lks. wide, course NW.
28.75	Wash, 50 lks. wide, course WNW.
36.00	Wash, 15 lks. wide, course WNW.
40.00	Point for the $\frac{1}{4}$ sec. cor. of secs. 28 and 29.
	Set an iron post, 3 ft. long, 1 in. diam., 28 ins. in the ground, with brass cap mkd.
	$\frac{1}{4}$ S29 S28 1950
	raise a mound of stone, 2 $\frac{1}{2}$ ft. base, 2 ft. high, W. of cor.
52.20	Wash, 30 lks. wide, course WSW.
80.00	Point for the cor. of secs. 20, 21, 28 and 29.
	Set an iron post, 3 ft. long, 2 ins. diam., 28 ins. in the ground, with brass cap mkd.
	T5N R19W S20 S21 S29 S28 1950
	raise a mound of stone, 3 ft. base, 2 $\frac{1}{2}$ ft. high, W. of cor.
	Land, rolling. Soil, clay and gravelly. Timber, paloverde and ironwood; undergrowth, greasewood and cacti.
	From the cor. of secs. 21, 22, 27 and 28.
	N. 89° 59' W., bet. secs. 21 and 28.
	Over rolling land, through scattering timber.
38.00	Wash, 20 lks. wide, course NW.
40.00	Point for the $\frac{1}{4}$ sec. cor. of secs. 21 and 28.

Subdivision of T. 5 N., R. 19 W.

Chains.

Set an iron post, 3 ft. long, 1 in. diam., 28 ins. in the ground, with brass cap mkd.



raise a mound of stone, 2½ ft. base, 2 ft. high, N. of cor.

63.90 Wash, 15 lks. wide, course NW.

80.00 The cor. of secs. 20, 21, 28 and 29.

Land, rolling.
Soil, gravelly.
Timber, paloverde, ironwood and cat's claw; undergrowth, greasewood and cacti.

N. 0° 02' W., bet. secs. 20 and 21.


Over rolling land, through scattering timber.

11.30 Wash, 25 lks. wide, banks 3 ft. high, course W.

26.50 Wash, 50 lks. wide, banks 3 ft. high, course W.

40.00 Point for the ¼ sec. cor. of secs. 20 and 21.

Set an iron post, 3 ft. long, 1 in. diam., 28 ins. in the ground, with brass cap mkd.




raise a mound of stone, 2½ ft. base, 2 ft. high, W. of cor.

Continue over rolling land.

80.00 Point for the cor. of secs. 16, 17, 20 and 21.

Set an iron post, 3 ft. long, 2 ins. diam., 28 ins. in the ground, with brass cap mkd.



raise a mound of stone, 2½ ft. base, 2 ft. high, W. of cor.

Land, rolling.
Soil, gravelly and rocky.
Timber, paloverde and ironwood; undergrowth, greasewood and cacti.

From the cor. of secs. 15, 16, 21 and 22.

West, bet. secs. 16 and 21.

Over rolling land, through scattering timber.

26.50 Wash, 20 lks. wide, course S. 60° W.

Subdivision of T. 5 N., R. 19 W.


Chains.	
28.00	Wash, 50 lks. wide, banks 3 ft. high, course S. 20° W.
39.98	Point for the $\frac{1}{4}$ sec. cor. of secs. 16 and 21. Set an iron post, 3 ft. long, 1 in. diam., 28 ins. in the ground, with brass cap mkd. $\begin{array}{r} S16 \\ \frac{1}{4} \text{ ---} \\ S21 \\ 1950 \end{array}$ raise a mound of stone, 2 $\frac{1}{2}$ ft. base, 2 ft. high, N. of cor. Continue over rolling land.
79.96	The cor. of secs. 16, 17, 20 and 21. Land, rolling. Soil, gravelly and rocky. Timber, paloverde, ironwood and cat's claw; undergrowth, greasewood and cacti.
	N. 0° 02' W., bet. secs. 16 and 17. Over rolling land, through scattering timber.
17.00	Wash, 50 lks. wide, banks 2 ft. high, course W.
40.00	Point for the $\frac{1}{4}$ sec. cor. of secs. 16 and 17. Set an iron post, 3 ft. long, 1 in. diam., 28 ins. in the ground, with brass cap mkd. $\begin{array}{c} \frac{1}{4} \\ S17 \text{ ---} S16 \\ 1950 \end{array}$ raise a mound of stone, 2 $\frac{1}{2}$ ft. base, 2 ft. high, W. of cor. Continue over rolling land.
80.00	Point for the cor. of secs. 8, 9, 16 and 17. Set an iron post, 3 ft. long, 2 ins. diam., 28 ins. in the ground, with brass cap mkd. $\begin{array}{c} T5N R19W \\ S8 \text{ ---} S9 \\ S17 \text{ ---} S16 \\ 1950 \end{array}$ dig pits 18x18x12 ins., in each sec., 3 ft. dist. Land, rolling. Soil, gravelly and rocky. Timber, paloverde, ironwood and cat's claw; undergrowth, greasewood and cacti.
	From the cor. of secs. 9, 10, 15 and 16. S. 89° 58' W., bet. secs. 9 and 16. Over rolling land, through scattering timber.

Subdivision of T. 5 N., R. 19 W.

Chains.
40.02

Point for the $\frac{1}{4}$ sec. cor. of secs. 9 and 16.

Set an iron post, 3 ft. long, 1 in. diam., 28 ins. in the ground, with brass cap mkd.



dig pits 18x18x12 ins., E. and W. of post, 3 ft. dist.

Continue over rolling land.

80.04 The cor. of secs. 8, 9, 16 and 17.

Land, rolling.
Soil, gravelly and rocky.
Timber, paloverde and ironwood; undergrowth, greasewood and cacti.

N. 0° 02' W., bet. secs. 8 and 9.

Over low sandhills.

2.20 Low, sandy ridge, bears NE. and SW.

17.00 Leave sandhills, bearing NE. and SW.; thence over rolling land, through scattering timber.

40.00 Point for the $\frac{1}{4}$ sec. cor. of secs. 8 and 9.

Set an iron post, 3 ft. long, 1 in. diam., 28 ins. in the ground, with brass cap mkd.




dig pits 18x18x12 ins., N. and S. of post, 3 ft. dist.

Continue over rolling land.

80.00 Point for the cor. of secs. 4, 5, 8 and 9.

Set an iron post, 3 ft. long, 2 ins. diam., 28 ins. in the ground, with brass cap mkd.



dig pits 18x18x12 ins., in each sec., 3 ft. dist.

Land, low sandhills and rolling.
Soil, sandy and gravelly.
Timber, very scattering paloverde; undergrowth, greasewood.

From the cor. of secs. 3, 4, 9 and 10.

S. 89° 55' W., bet. secs. 4 and 9.

Over rolling land, through scattering timber.

Subdivision of T. 5 N., R. 19 W.

BOOK 4890

Chains.

40.01 Point for the $\frac{1}{4}$ sec. cor. of secs. 4 and 9.

Set an iron post, 3 ft. long, 1 in. diam., 28 ins. in the ground, with brass cap mkd.

$$\frac{1}{4} \frac{S4}{S9}$$
 1950

dig pits 18x18x12 ins., E. and W. of post, 3 ft. dist.

Continue over rolling land.

80.02 The cor. of secs. 4, 5, 8 and 9.

Land, rolling.

Soil, sandy and gravelly.

Timber, paloverde and ironwood; undergrowth, greasewood and cacti.

North, bet. secs. 4 and 5.

Over rolling land, through scattering timber.

40.00 Point for the $\frac{1}{4}$ sec. cor. of secs. 4 and 5.

Set an iron post, 3 ft. long, 1 in. diam., 28 ins. in the ground, with brass cap mkd.

$$\frac{1}{4}$$

$$S5 | S4$$
 1950

dig pits 18x18x12 ins., N. and S. of post, 3 ft. dist.

Continue over rolling land.

74.00 Intersect the N. bdy. of Tp., at the cor. of secs. 4, 5, 32 and 33.

Land, rolling.

Soil, sandy and gravelly.

Timber, scattering paloverde; undergrowth, greasewood and cacti.

The standard cor. of secs. 31 and 32, on the S. bdy. of Tp., is monumented with a malpais stone 12x6x6 ins., mkd. and witnessed as described in the official record.

At the corner point

Set an iron post, 3 ft. long, 2 ins. diam., 28 ins. in the ground, with brass cap mkd.

$$S C$$

$$T5N R19W$$

$$S31 | S32$$

1950

Bury the original corner stone alongside the iron post.

Thence

Subdivision of T. 5 N., R. 19 W.

Chains.	<p>N. 0° 03' W., bet. secs. 31 and 32.</p> <p>Over rolling land, through scattering timber.</p> <p>3.30 Wash, 15 lks. wide, banks 3 ft. high, course NE.</p> <p>19.40 Same wash, course NW.</p> <p>32.30 Along right bank of same wash, bears N. and S.</p> <p>33.80 Leave right bank of wash, bears NNW. and S.</p> <p>39.25 Point for the witness $\frac{1}{4}$ sec. cor. of secs. 31 and 32.</p> <p>Set an iron post, 3 ft. long, 1 in. diam., 28 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center;"> <p>W C</p> <p>↑</p> <p>S31 S32</p> <p>1950</p> </div> <p>raise a mound of stone, 2½ ft. base, 2 ft. high, W. of cor.</p> <p>39.50 Same wash, course N., from SSW.; along wash bottom.</p> <p>40.00 True point for the $\frac{1}{4}$ sec. cor. of secs. 31 and 32 falls in bottom of wash, course N.</p> <p>Continue along wash.</p> <p>51.70 Graded road, bears E. and W.</p> <p>58.90 Leave wash, course NE. Over rolling land.</p> <p>75.00 Wash, 15 lks. wide, banks 3 ft. high, course NE.</p> <p>80.00 Point for the cor. of secs. 29, 30, 31 and 32.</p> <p>Set an iron post, 3 ft. long, 2 ins. diam., 28 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center;"> <p>T5N R19W</p> <p>S30 S29</p> <p>S31 S32</p> <p>1950</p> </div> <p>raise a mound of stone, 2½ ft. base, 2 ft. high, W. of cor.</p> <p>Land, rolling.</p> <p>Soil, rocky and gravelly.</p> <p>Timber, paloverde, ironwood and cat's claw; undergrowth, greasewood and cacti.</p> <hr/> <p>From the cor. of secs. 28, 29, 32 and 33.</p> <p>N. 89° 54' W., bet. secs. 29 and 32.</p> <p>Over rolling land, through scattering timber.</p> <p>40.06 Point for the $\frac{1}{4}$ sec. cor. of secs. 29 and 32.</p> <p>Set an iron post, 3 ft. long, 1 in. diam., 28 ins. in the ground, with brass cap mkd.</p>
---------	---

Subdivision of T. 5 N., R. 19 W.

Chains.

$$\frac{1}{4} \frac{S29}{S32}$$

1950

from which

A windmill bears S. 35° 39' E., 22.04 chs. dist.

Raise a mound of stone, 2½ ft. base, 2 ft. high, N. of cor.

47.10 Right bank of Tyson Wash, bears NW. and SE. Across various channels of wash, course NW.

79.83 Left bank of Tyson Wash, bears NW. and SE.

80.12 The cor. of secs. 29, 30, 31 and 32.

Land, rolling and wash bottom.
Soil, sandy, gravelly and rocky.
Timber, ironwood, paloverde, cat's claw and mesquite;
undergrowth, greasewood and cacti.

N. 89° 54' W., bet. secs. 30 and 31.

Over rolling land, through scattering timber.

27.20 Graded road, bears N. 20° W. and S. 20° E.

35.50 Unimproved road, bears N. 30° W. and S. 30° E.

40.00 Point for the ¼ sec. cor. of secs. 30 and 31.

Set an iron post, 3 ft. long, 1 in. diam., 28 ins. in the ground, with brass cap mkd.

$$\frac{1}{4} \frac{S30}{S31}$$

1950

raise a mound of stone, 2½ ft. base, 2 ft. high, N. of cor.

46.67 Intersect the W. bdy. of the Tp., at the cor. of secs. 30 and 31.

Land, rolling.
Soil, rocky and gravelly.
Timber, ironwood, paloverde and cat's claw; undergrowth,
greasewood and cacti.

From the cor. of secs. 29, 30, 31 and 32.

N. 0° 03' W., bet. secs. 29 and 30.

Over rolling land, through scattering timber.

0.40 Left bank of Tyson Wash, bears NW. and SE. Across channels of wash, course N. 40° W.


30.00 Right bank of Tyson Wash, bears NW. and SE.

40.00 Point for the ¼ sec. cor. of secs. 29 and 30.

Set an iron post, 3 ft. long, 1 in. diam., 28 ins. in the ground, with brass cap mkd.

Subdivision of T. 5 N., R. 19 W.

Chains.



raise a mound of stone, 2½ ft. base, 2 ft. high, W. of cor.


54.70 Wash, 15 lks. wide, banks 2 ft. high, course SW.

64.70 Wash, 15 lks. wide, banks 2 ft. high, course NW.

74.00 Wash, 30 lks. wide, banks 2 ft. high, course SW.

80.00 Point for the cor. of secs. 19, 20, 29 and 30.

Set an iron post, 3 ft. long, 2 ins. diam., 28 ins. in the ground, with brass cap mkd.



raise a mound of stone, 2½ ft. base, 2 ft. high, W. of cor.

Land, wash bottom and rolling.

Soil, sandy and gravelly.

Timber, ironwood, paloverde, cat's claw and mesquite; undergrowth, greasewood and cacti.


From the cor. of secs. 20, 21, 28 and 29.

N. 89° 54' W., bet. secs. 20 and 29.

Over rolling land, through scattering timber.

40.09 Point for the ¼ sec. cor. of secs. 20 and 29.

Set an iron post, 3 ft. long, 1 in. diam., 28 ins. in the ground, with brass cap mkd.



raise a mound of stone, 2½ ft. base, 2 ft. high, N. of cor.

55.20 Wash, 15 lks. wide, banks 2 ft. high, course NW.

72.50 Wash, 15 lks. wide, banks 2 ft. high, course S. 20° W.

80.18 The cor. of secs. 19, 20, 29 and 30.

Land, rolling.

Soil, rocky and gravelly.

Timber, paloverde, ironwood and cat's claw; undergrowth, greasewood and cacti.

N. 89° 50' W., bet. secs. 19 and 30.

Over rolling land, through scattering timber.

21.10 Wash, 25 lks. wide, course WNW.

24.90 Same wash, course WSW.

Subdivision of T. 5 N., R. 19 W.

Chains. 40.00	<p>Point for the $\frac{1}{4}$ sec. cor. of secs. 19 and 30.</p> <p>Set an iron post, 3 ft. long, 1 in. diam., 28 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center;"> $\frac{1}{4}$ $\frac{S19}{S30}$ 1950 </div> <p>from which</p> <p>A paloverde, 8 ins. diam., bears N. $1\frac{1}{2}^\circ$ W., 245 lks. dist., mkd. $\frac{1}{4}$ S19 BT.</p> <p>A paloverde, 10 ins. diam., bears S. 66° E., 106 lks. dist., mkd. $\frac{1}{4}$ S30 BT.</p>								
43.00	Right bank of Tyson Wash, bears NW. and SE. Over wash bottom.								
46.46	Intersect the W. bdy. of Tp. at the true point for the cor. of secs. 19 and 30. Witness cor. is established 40 lks. S. of true point.								
	<p>Land, rolling and wash bottom.</p> <p>Soil, sandy and gravelly.</p> <p>Timber, ironwood, paloverde, cat's claw and mesquite; undergrowth, greasewood and cacti.</p>								
	<p>From the cor. of secs. 19, 20, 29 and 30.</p> <p>N. $0^\circ 03'$ W., bet. secs. 19 and 20.</p> <p>Over rolling land, through scattering timber.</p>								
9.10	Low gravel bank, bears WNW. and ESE.								
26.90	Wash, 30 lks. wide, banks 3 ft. high, course WSW.								
40.00	<p>Point for the $\frac{1}{4}$ sec. cor. of secs. 19 and 20.</p> <p>Set an iron post, 3 ft. long, 1 in. diam., 28 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center;"> $\frac{1}{4}$ <table style="margin: auto;"> <tr> <td>S19</td> <td> </td> <td>S20</td> </tr> <tr> <td colspan="3" style="text-align: center;">1950</td> </tr> </table> </div> <p>raise a mound of stone, 2 ft. base, $1\frac{1}{2}$ ft. high, W. of cor.</p>	S19		S20	1950				
S19		S20							
1950									
40.35	Wash, 15 lks. wide, banks 2 ft. high, course SW.								
76.80	Wash, 30 lks. wide, banks 3 ft. high, course SSW.								
80.00	<p>Point for the cor. of secs. 17, 18, 19 and 20.</p> <p>Set an iron post, 3 ft. long, 2 ins. diam., 28 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center;"> <table style="margin: auto;"> <tr> <td colspan="2">T5N R19W</td> </tr> <tr> <td>S18</td> <td> S17</td> </tr> <tr> <td>S19</td> <td> S20</td> </tr> <tr> <td colspan="2" style="text-align: center;">1950</td> </tr> </table> </div> <p>dig pits 18x18x12 ins., in each sec., 3 ft. dist.</p>	T5N R19W		S18	S17	S19	S20	1950	
T5N R19W									
S18	S17								
S19	S20								
1950									

Subdivision of T. 5 N., R. 19 W.

Chains.

Land, rolling.
Soil, gravelly and rocky.
Timber, ironwood, paloverde and cat's claw; undergrowth, greasewood and cacti.

From the cor. of secs. 16, 17, 20 and 21.

N. 89° 54' W., bet. secs. 17 and 20.

Over rolling land, through scattering timber.

40.11 Point for the 1/4 sec. cor. of secs. 17 and 20.

Set an iron post, 3 ft. long, 1 in. diam., 28 ins. in the ground, with brass cap mkd.

1/4 S17
S20
1950

raise a mound of stone, 2 1/2 ft. base, 2 ft. high, N. of cor.

78.30 Wash, 30 lks. wide, banks 3 ft. high, course SSW.

80.22 The cor. of secs. 17, 18, 19 and 20.

Land, rolling.
Soil, gravelly and rocky.
Timber, ironwood, paloverde and cat's claw; undergrowth, greasewood and cacti.

N. 89° 53' W., bet. secs. 18 and 19.

Over rolling land, through scattering timber.

3.30 Wash, 30 lks. wide, banks 2 ft. high, course SSW.

24.00 Wash, 15 lks. wide, banks 2 ft. high, course SSW.

40.00 Point for the 1/4 sec. cor. of secs. 18 and 19.

Set an iron post, 3 ft. long, 1 in. diam., 28 ins. in the ground, with brass cap mkd.

1/4 S18
S19
1950

raise a mound of stone, 2 1/2 ft. base, 2 ft. high, N. of cor.

46.36 Intersect the W. bdy. of Tp. at the cor. of secs. 18 and 19.

Land, rolling.
Soil, rocky and gravelly.
Timber, ironwood and paloverde; undergrowth, greasewood and cacti.

From the cor. of secs. 17, 18, 19 and 20.

N. 0° 03' W., bet. secs. 17 and 18.

Over rolling land, through scattering timber.

2.00 Wash, 30 lks. wide, banks 2 ft. high, course SSW.

Subdivision of T. 5 N., R. 19 W.

BOOK 4890

Chains. 40.00	<p>Point for the $\frac{1}{4}$ sec. cor. of secs. 17 and 18.</p> <p>Set an iron post, 3 ft. long, 1 in. diam., 28 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center;"> $\begin{array}{c} \uparrow \\ \text{S18} \mid \text{S17} \\ \hline 1950 \end{array}$ </div> <p>raise a mound of stone, 2$\frac{1}{2}$ ft. base, 2 ft. high, W. of cor.</p>
47.10	Unimproved road, bears E. and W.
80.00	<p>Point for the cor. of secs. 7, 8, 17 and 18.</p> <p>Set an iron post, 3 ft. long, 2 ins. diam., 28 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center;"> $\begin{array}{c} \text{T5N R19W} \\ \hline \text{S7} \mid \text{S8} \\ \hline \text{S18} \mid \text{S17} \\ \hline 1950 \end{array}$ </div> <p>dig pits 18x18x12 ins., in each sec., 3 ft. dist.</p> <p>Land, rolling. Soil, sandy. Timber, paloverde and ironwood; undergrowth, greasewood and cacti.</p>
From the cor. of secs. 8, 9, 16 and 17.	
N. 89° 54' W., bet. secs. 8 and 17.	
Over rolling land, through scattering timber.	
40.08	<p>Point for the $\frac{1}{4}$ sec. cor. of secs. 8 and 17.</p> <p>Set an iron post, 3 ft. long, 1 in. diam., 28 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center;"> $\begin{array}{c} \frac{1}{4} \text{ S8} \\ \hline \text{S17} \\ \hline 1950 \end{array}$ </div> <p>dig pits 18x18x12 ins., E. and W. of post, 3 ft. dist.</p> <p>Continue over rolling land.</p>
80.16	<p>The cor. of secs. 7, 8, 17 and 18.</p> <p>Land, rolling. Soil, sandy. Timber, paloverde; undergrowth, greasewood.</p>
N. 89° 52' W., bet. secs. 7 and 18.	
Over rolling land, through scattering timber.	
40.00	<p>Point for the $\frac{1}{4}$ sec. cor. of secs. 7 and 18.</p> <p>Set an iron post, 3 ft. long, 1 in. diam., 28 ins. in the ground, with brass cap mkd.</p>

Subdivision of T. 5 N., R. 19 W.

Chains.

$\frac{1}{4}$ $\frac{S7}{S18}$

dig pits 18x18x12 ins., E. and W. of post, 3 ft. dist.

Continue over rolling land.

46.29 Intersect W. bdy. of Tp., at the cor. of secs. 7 and 18.

Land, rolling.

Soil, sandy.

Timber, paloverde; undergrowth, greasewood and cacti.

From the cor. of secs. 7, 8, 17 and 18.

N. 0° 03' W., bet. secs. 7 and 8.

Over rolling land.

40.00 Point for the $\frac{1}{4}$ sec. cor. of secs. 7 and 8.

Set an iron post, 3 ft. long, 1 in. diam., 28 ins. in the ground, with brass cap mkd.

$\frac{1}{4}$
S7 | S8
1950

dig pits 18x18x12 ins., N. and S. of post, 3 ft. dist.

Continue over rolling land.

80.00 Point for the cor. of secs. 5, 6, 7 and 8.

Set an iron post, 3 ft. long, 2 ins. diam., 28 ins. in the ground, with brass cap mkd.

T5N R19W
S6 | S5
S7 | S8
1950

dig pits 18x18x12 ins., in each sec., 3 ft. dist.

Land, rolling.

Soil, sandy.

Timber, none; undergrowth, greasewood and cacti.

From the cor. of secs. 4, 5, 8 and 9.

N. 89° 54' W., bet. secs. 5 and 8.

Over rolling land, through scattering timber.

40.08 Point for the $\frac{1}{4}$ sec. cor. of secs. 5 and 8.

Set an iron post, 3 ft. long, 1 in. diam., 28 ins. in the ground, with brass cap mkd.

$\frac{1}{4}$ $\frac{S5}{S8}$
1950

dig pits 18x18x12 ins., E. and W. of post, 3 ft. dist.

Subdivision of T. 5 N., R. 19 W.

Chains.	Continue over rolling land.
80.16	The cor. of secs. 5, 6, 7 and 8. Land, rolling. Soil, sandy. Timber, paloverde; undergrowth, greasewood and cacti.
	N. 89° 49' W., bet. secs. 6 and 7. Over rolling land.
40.00	Point for the $\frac{1}{4}$ sec. cor. of secs. 6 and 7. Set an iron post, 3 ft. long, 1 in. diam., 28 ins. in the ground, with brass cap mkd. $\begin{array}{r} \frac{1}{4} \text{ S6} \\ \hline \text{S7} \\ 1950 \end{array}$ dig pits 18x18x12 ins., E. and W. of post, 3 ft. dist.
44.20	Road, bears N. and S.
46.17	Intersect the W. bdy. of Tp., at the cor. of secs. 6 and 7. Land, rolling. Soil, sandy. Timber, none; undergrowth, greasewood and cacti.
	From the cor. of secs. 5, 6, 7 and 8. N. 0° 07' E., bet. secs. 5 and 6. Over rolling land, through scattering timber.
40.00	Point for the $\frac{1}{4}$ sec. cor. of secs. 5 and 6. Set an iron post, 3 ft. long, 1 in. diam., 28 ins. in the ground, with brass cap mkd. $\begin{array}{c} \frac{1}{4} \\ \hline \text{S6} \text{S5} \\ \hline 1950 \end{array}$ dig pits 18x18x12 ins., N. and S. of post, 3 ft. dist. Continue over rolling land.
73.87	Intersect the N. bdy. of Tp., at the cor. of secs. 5, 6, 31 and 32. Land, rolling. Soil, sandy. Timber, paloverde; undergrowth, greasewood and cacti.
	Test of Solar Orientation. December 16, 1950; At camp in sec. 27, T. 5 N., R. 19 W., at 8h 30m a.m., app.t., make the proper settings on the arcs and orient the instruments with the solars; the line of sight agrees with the meridian established by Polaris observation. At 4h 30m p.m., app.t., make the proper settings on the arcs and repeat the test of the solars, the line of sight agrees with the meridian established by Polaris observation.

General Description.

The topography of T. 5 N., R. 19 W. is nearly level, and rolling. There are numerous washes in the south and central portions of the township which are dry except during periods of heavy rains. The drainage is to the west and northwest. The soil is rocky and gravelly in the south and central portions, and sandy and gravelly in the north portion. The average elevation is 850 ft. above sea level.

The timber is paloverde, ironwood, mesquite and cat's claw, being generally scattering, with a heavier growth along the washes. The undergrowth is greasewood and cacti.

A power transmission line from Parker Dam extends North and South near the East boundaries of secs. 3, 10, 15, 22, 27 and 34. There is a graded road bearing northwesterly and southeasterly through secs. 30, 31 and 32, and a partially improved road leaves this road in sec. 32, and extends ENE. through secs. 33, 28, 27, 26, 25 and 24. The only permanent water in the township is at a well, with a galvanized tank, in the NE $\frac{1}{4}$ of sec. 32.

There is no evidence of mineral activity, and no settlement in the township.

118
43

4-680
(August 1947)

UNITED STATES
DEPARTMENT OF THE INTERIOR
BUREAU OF LAND MANAGEMENT

FIELD ASSISTANTS

NAMES	CAPACITY
Jesse A. Livesay	Cartographic Survey Aid
Robert D. Stevens	" " "
Max Lester	Surveying and Cartographic Aid
Abenicio Crespín	" " " "
Gerald L. Walters	" " " "
Chas. K. Byrne	" " " "
Carl P. Lyons	" " " "
William R. Disney	" " " "
William H. Derendor	" " " "

119
44

BOOK 4890

CERTIFICATE OF CADASTRAL ENGINEER

 I , We, Ty White and Claude F. Warner, HEREBY CERTIFY upon honor that, in
pursuance of special instructions bearing date of the 27th day of September, 1950,
We
I have surveyed the East Boundary, North Boundary and Subdivisional Lines
of Township 5 North, Range 19 West

of the G. & S.R. Meridian, in the State of Arizona, which are
represented in the foregoing field notes as having been executed by ~~me~~ ^{us} and under ~~my~~ ^{our} direction; and that
said survey has been made in strict conformity with said instructions, the Manual of Instructions for the
Survey of the Public Lands of the United States, and in the specific manner described in the foregoing
field notes.

Apache Junction, Arizona
November 24, 1951
Phoenix, Arizona.
June 21, 1951.

Ty White
Cadastral Engineer
Claude F. Warner
Cadastral Engineer

CERTIFICATE OF APPROVAL

BUREAU OF LAND MANAGEMENT,
Washington, D. C., JUN 9 1952, 19

The foregoing field notes of the survey of the East Boundary, North Boundary and
Subdivisional Lines of Township 5 North, Range 19 West of the Gila
and Salt River Meridian, in the State of Arizona

executed by Ty White and Claude F. Warner

having been critically examined and found correct, are hereby approved.

Earl G. Harrington
~~Chief, Branch of Engineering and Construction.~~
Chief, Division of
Cadastral Engineering

CERTIFICATE OF TRANSCRIPT

~~I CERTIFY that the foregoing transcript of the field notes of the above described surveys in~~
~~is a true copy of the original field notes.~~

~~Chief, Branch of Engineering and Construction.~~