

UNITED STATES
DEPARTMENT OF THE INTERIOR
BUREAU OF LAND MANAGEMENT

RECEIVED
BUREAU OF LAND MANAGEMENT
1951 MAY 17 PM 2:48
REGION 7
PHOENIX, ARIZONA

FIELD NOTES

of the

Dependent Resurvey

of

Portions of the North and East Boundaries and Subdivision,

and

Subdivision of Sections 14 and 23

of

Township 11 North, Range 2 East

Of the Gila and Salt River Meridian,

In the State of Arizona

EXECUTED BY

Clarence E. Bilbray, Cadastral Engineer

Under special instructions dated March 9, 1951, which provided
for the surveys included under Group No. 275, approved May 2, 1951
and assignment instructions dated October 3, 1952.

Survey commenced October 9, 1952.

Survey completed November 10, 1952.

4420

4420

1A

BOOK 4420

INDEX DIAGRAM

Township 11 N, Range 2 E

			5	4	3
6	5	4	3	2	1 3
7	8	9	10	11	12 2
18	17	16	15	14 13	8
				12 15 7	2
				16 14 16	13
				11 14 6	1
				10 9	6
19	20	21	22	8 30 5	
				31 28 31	24
				30	
30	29	28	27	26	25
31	32	33	34	35	36

- Subdivision of NE $\frac{1}{4}$ Sec. 14 ----- 17-18
- Subdivision SW $\frac{1}{4}$ NE $\frac{1}{4}$ sec. 14 ----- 18-19
- Subdivision of NW $\frac{1}{4}$ Sec. 14 ----- 19-20
- Subdivision NE $\frac{1}{4}$ NW $\frac{1}{4}$ Sec. 14 ----- 20-21
- Subdivision NW $\frac{1}{4}$ NW $\frac{1}{4}$ Sec. 14 ----- 21
- Subdivision SW $\frac{1}{4}$ NW $\frac{1}{4}$ Sec. 14 ----- 21-22
- Subdivision SE $\frac{1}{4}$ NW $\frac{1}{4}$ Sec. 14 ----- 22-23
- Subdivision of SW $\frac{1}{4}$ Sec. 14 ----- 23-24
- Subdivision NE $\frac{1}{4}$ SW $\frac{1}{4}$ Sec. 14 ----- 25
- Subdivision NW $\frac{1}{4}$ SW $\frac{1}{4}$ Sec. 14 ----- 25-26
- Subdivision SE $\frac{1}{4}$ SW $\frac{1}{4}$ Sec. 14 ----- 26-27
- Subdivision of SE $\frac{1}{4}$ Sec. 14 ----- 27-28
- Subdivision NW $\frac{1}{4}$ SE $\frac{1}{4}$ Sec. 14 ----- 28-29
- Subdivision SW $\frac{1}{4}$ SE $\frac{1}{4}$ Sec. 14 ----- 29
- Subdivision of NE $\frac{1}{4}$ Sec. 23 ----- 32
- Subdivision NW $\frac{1}{4}$ NE $\frac{1}{4}$ Sec. 23 ----- 32-33
- Subdivision of NW $\frac{1}{4}$ Sec. 23 ----- 33-34
- Subdivision NE $\frac{1}{4}$ NW $\frac{1}{4}$ Sec. 23 ----- 34-35
- Subdivision SE $\frac{1}{4}$ NW $\frac{1}{4}$ Sec. 23 ----- 35-36

T. 11 N., R. 2 E.

This survey represents a dependent resurvey of a portion of the boundaries and portion of subdivision, and survey of the subdivisional lines of sections 14 and 23, T. 11 N., R. 2 E., of the Gila and Salt River Meridian, Arizona. The north half of T. 11 N., R. 2 E. was surveyed by C. B. Foster in 1873, as shown on plat approved July 20, 1874. The south half of the township was surveyed by W. H. Richards in 1916, as shown on plat approved May 14, 1920. The west 3 miles of the north boundary was resurveyed and the east 3 miles retraced by H. L. Baldwin in 1918, also shown on plat approved May 14, 1920.

The survey was executed with a light mountain solar transit made by W. and L. E. Gurley, Serial No. 371540, constructed in accordance with the standard instrumental specifications of the Bureau of Land Management. The instrument is equipped with improved telescopic solar attachment, and was in good condition prior to the beginning of the survey, was tested and found free from appreciable error.

The measurements were made with a narrow steel tape, 5 chains in length, graduated to tenths of a link for the first ten links, every link for the remainder of the first 100 links, and at each 10 link interval for the remaining 400 links. The tape was tested by comparison with a standard 1 chain steel tape and found correct. The measurements were made on the slope, and the vertical angle of each interval was ascertained by a clinometer in good adjustment; the horizontal equivalents are entered in the field note record.

The geographic position of the southeast corner of section 13, T. 11 N., Rs. 2 and 3 E., as computed from data given for the southeast corner of the township, as shown on plat approved May 14, 1920, is Latitude $34^{\circ} 19' 25''$ N., Longitude $112^{\circ} 05' 24''$ W.

The directions of all lines were determined by transit method, with azimuth referred to a meridian established by an altitude observation on the sun as follows.

October 12, 1952, at camp near the west 1/16 section corner of section 14, T. 11 N., R. 2 E., in latitude $34^{\circ} 19' 27''$ N., longitude $112^{\circ} 07' 14''$ W. at 8:30 a.m., Mountain Standard Time, I make a series of three altitude observations of the sun for azimuth, each with the telescope in direct and reversed positions, observing opposite limbs of the sun.

Reference: trunk of a tree in a northwesterly direction, horizontal angle measured to the right from reference to the sun.

Mean observed vertical angle -----	$21^{\circ} 46' 30''$
Mean horizontal angle reference to sun -----	$195^{\circ} 21' 00''$
Resulting bearing -----	N. $79^{\circ} 02' 40''$ W.

Dependent Resurvey of a Portion of East Boundary, T. 11 N., R. 2 E.

Reestablishment of the Survey Executed by
C. B. Foster in 1873.

Beginning at the corner of secs. 13, 18, 19, and 24, T. 11 N., Rs. 2 and 3 E., which is monumented with a malpais stone, 18x14x6 ins., set and marked as described in the official record.

At the corner point

Set an iron post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 24 ins. in the ground, with brass cap mkd.

T11N	
R2E	R3E
S13	S18
S24	S19
1952	

Dependent Resurvey of a Portion of East Boundary, T. 11 N., R. 2 E.

Chains	<p>raise a mound of stone, 3 ft. base, 2 ft. high, W. of cor., and bury the old corner stone alongside the iron post.</p> <p>N. 0° 12' E., bet. secs. 13 and 18.</p> <p>Over nearly level land, through scattering undergrowth.</p>
41.11	<p>Point for the $\frac{1}{4}$ sec. cor. of secs. 13 and 18, at proportionate distance, there is no remaining evidence of the original corner.</p> <p>Set an iron post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 12 ins. in the ground to bedrock, and in a mound of stone to top, with brass cap mkd.</p> <div style="text-align: center;"> $\frac{1}{4}$ S13 S18 1952 </div>
57.10	Descend 200 ft. over rocky N. slope.
66.00	Bottom of canyon, course NE.; ascend 80 ft. over rocky SE. slope.
73.45	Top of ascent; thence over rolling land.
79.05	Rim of bluff, 60 ft. high, bears ESE. and WNW.; descend 100 ft. over rocky N. slope.
82.00	Foot of descent, thence over bottom land.
82.10	Enter cultivated field, bears E. and W.
82.22	<p>Point for the corner of secs. 7, 12, 13, and 18, at proportionate distance, there is no remaining evidence of the original corner.</p> <p>Set an iron post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center;"> T11N R2E R3E S12 S 7 ----- S13 S18 1952 </div> <p>Alongside the iron post, set a juniper post, 6 ft. long, .6 ins. diam., 30 ins. in the ground.</p> <p>Land, south-half, nearly level; north-half, hilly and broken. Soil, rocky clay. No timber; undergrowth, scattering juniper and catclaw.</p>
	<p>N. 0° 12' E., bet. secs. 7 and 12.</p> <p>Over level bottom land, through cultivated field.</p>
11.60	Leave field, bears NW. and SE.
13.80	Right bank of Agua Fria Creek, course ESE.
16.60	Left bank of creek.
22.50	Leave bottom land. Ascend 110 ft. over rocky S. slope.
41.11	<p>Point for the $\frac{1}{4}$ sec. cor. of secs. 7 and 12, at proportionate distance, there is no remaining evidence of the original corner.</p> <p>Set an iron post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 6 ins. in the ground to bedrock, and in a mound of stone to top, with brass cap mkd.</p>

Dependent Resurvey of a Portion of East Boundary, T. 11 N., R. 2 E.

Chains

$$\begin{array}{c} \frac{1}{4} \\ \text{S12} \mid \text{S 7} \\ 1952 \end{array}$$

Thence over rolling land.

66.20 Draw, course SE.

82.22 Point for the cor. of secs. 1, 6, 7, and 12, at proportionate distance, there is no remaining evidence of the original corner.

Set an iron post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 6 ins. in the ground to bedrock, and in a mound of stone to top, with brass cap mkd.
$$\begin{array}{c} \text{T11N} \\ \text{R2E} \mid \text{R3E} \\ \text{S 1} \mid \text{S 6} \\ \hline \text{S12} \mid \text{S 7} \\ 1952 \end{array}$$

Land, south of creek, level bottom; north of creek, hilly and rolling.
Soil, rocky, clay and loam.
Timber, cottonwood, along creek; undergrowth, scattering juniper and catclaw.

N. 0° 12' E., bet. secs. 1 and 6.

Over rolling land, through scattering undergrowth.

41.11 Point for the $\frac{1}{4}$ sec. cor. of secs. 1 and 6, at proportionate distance, there is no remaining evidence of the original corner.Set an iron post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 8 ins. in the ground to bedrock, and in a mound of stone to top, with brass cap mkd.
$$\begin{array}{c} \frac{1}{4} \\ \text{S 1} \mid \text{S 6} \\ 1952 \end{array}$$

82.22 The corner of Ts. 11 and 12 N., Rs. 2 and 3 E., which is monumented with an iron post, 3 ins. diam., set, marked and witnessed as described in the official record.

Land, rolling.
Soil, rocky clay.
No timber; undergrowth, juniper, catclaw and cacti.

Dependent Resurvey of a Portion of North Boundary, T. 11 N., R. 2 E.

Reestablishment of the Survey Executed by
C. B. Foster in 1873

From the corner of Ts. 11 and 12 N., Rs. 2 and 3 E.

N. 89° 34' W., bet. secs. 1 and 36.

Over rolling land, through scattering undergrowth.

40.12 Point for the $\frac{1}{4}$ sec. cor. of secs. 1 and 36, at proportionate distance, there is no remaining evidence of the original corner.Set an iron post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 18 ins. in the ground to bedrock, and in a mound of stone to top, with brass cap mkd.

Dependent Resurvey of a Portion of North Boundary, T. 11 N., R. 2 E.

Chains	$\frac{1}{4} \begin{array}{l} S36 \\ S1 \\ 1952 \end{array}$
62.30	A ravine, course S. 10° W.
75.35	Highway fence, bears NE. and SW.
77.10	Center line of Black Canyon Highway, bears NE. and SW.
80.24	Point for the cor. of secs. 1, 2, 35, and 36, at proportionate distance, there is no remaining evidence of the original corner. Set an iron post, 28 ins. long, 2½ ins. diam., 8 ins. in the ground to bedrock, and in a mound of stone to top, with brass cap mkd.
	$\begin{array}{c} T12NR2E \\ S35 S36 \\ \hline S2 S1 \\ T11N \\ 1952 \end{array}$
	Land, rolling. Soil, rocky clay. No timber; undergrowth, scattering juniper, catclaw and cacti.
	N. 89° 34' W., bet. secs. 2 and 35. Over rolling land, through undergrowth.
19.50	Thence over nearly level bottom.
20.25	Left bank of Agua Fria Creek, course S.
23.95	Right bank of creek.
24.75	Enter dense undergrowth.
26.55	Old road, bears NW. and SE.
40.12	Point for the ¼ sec. cor. of secs. 2 and 35, at proportionate distance, there is no remaining evidence of the original corner. Set an iron post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.
	$\frac{1}{4} \begin{array}{l} S35 \\ S2 \\ 1952 \end{array}$
	raise a mound of stone, 3 ft. base, 2 ft. high, N. of cor.
56.40	Old road, bears NW. and SE.
58.40	Wash, 10 lks. wide, 3 ft. deep, drains ESE.
64.75	Leave dense undergrowth; thence over rolling hills.
76.70	Wash, 5 lks. wide, 4 ft. deep, drains SE.
80.24	Point for the cor. of secs. 2, 3, 34, and 35, at proportionate distance, there is no remaining evidence of the original corner. Set an iron post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.

Dependent Resurvey of a Portion of North Boundary, T. 11 N., R. 2 E.

Chains

T12NR2E	
S34	S35
S 3	S 2
T11N	
1952	

raise a mound of stone, 3 ft. base, 2 ft. high, W. of cor.

Land, rolling.

Soil, rocky and gravelly.

No timber; undergrowth, catclaw and mesquite.

N. 89° 34' W., bet. secs. 3 and 34.

Over rolling hills, through scattering undergrowth.

31.40 Draw, course ESE.

40.12 Point for the $\frac{1}{4}$ sec. cor. of secs. 3 and 34, at proportionate distance, there is no remaining evidence of the original corner.

Set an iron post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 24 ins. in the ground, with brass cap mkd.

S 34
$\frac{1}{4}$
S 3
1952

raise a mound of stone, 3 ft. base, 2 ft. high, N. of cor.

79.60 Graded road, bears NE. and SW.

80.24 The corner of secs. 3, 4, 33, and 34, which is monumented with an iron post, 2 ins. diam., set and marked as described in the official record.

Land, rolling.

Soil, rocky clay.

No timber; undergrowth, scattering juniper and catclaw.

Dependent Resurvey, Portion of Subdivision of T. 11 N., R. 2 E.

Reestablishment of the Surveys Executed by
C. B. Foster in 1873 and W. H. Richards in 1916.

Beginning at the $\frac{1}{4}$ sec. cor. of secs. 23 and 24, which is monumented with an iron post, 1 in. diam., set, marked and witnessed as described in the official record.

N. 0° 04' E., bet. secs. 23 and 24.

Over rolling land, through scattering undergrowth.

6.80 Draw, course SE.

19.989 Point for the N $\frac{1}{16}$ sec. cor. of secs. 23 and 24, at proportionate distance.

Set an iron post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 24 ins. in the ground, with brass cap mkd.

N $\frac{1}{16}$	
S23	S24
1952	

Dependent Resurvey, Portion of Subdivision of T. 11 N., R. 2 E.

Chains	raise a mound of stone, 3 ft. base, 2 ft. high, W. of cor.				
29.10	Wash, 10 lks. wide, 3 ft. deep, drains ENE.				
41.756	Intersect the S. bdy. of sec. 13, point for the closing corner of secs. 23 and 24. Set an iron post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 24 ins. in the ground, with brass cap mkd. <div style="text-align: center;"> <table border="1"> <tr><td colspan="2">S. 13</td></tr> <tr><td>S23</td><td>S24</td></tr> </table> <p>T11NR2E CC 1952</p> </div> Deposit a stone, mkd. X at base of iron post. From this corner the 1916 survey monument, an iron post, 2 ins. diam. set and marked as described in the official record, (I add the marks A M) bears N. $0^{\circ} 04'$ E., 0.077 lks. dist. From this same corner the corner of secs. 13 and 14, bears N. $88^{\circ} 44'$ W., 1.83 chs. dist. Land, gently rolling. Soil, sandy clay. No timber; undergrowth, mesquite, catclaw and cacti.	S. 13		S23	S24
S. 13					
S23	S24				
	From the corner of secs. 13, 18, 19, and 24, on the E. bdy. of the Tp. N. $88^{\circ} 48'$ W., on the S. bdy. of sec. 13. Over rolling land.				
40.00	The $\frac{1}{4}$ sec. cor. of sec. 13, which is monumented with a malapais stone, $14 \times 12 \times 4$ ins., firmly set, marked $\frac{1}{4}$ on N. face. At the corner point Set an iron post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 12 ins. in the ground to bedrock, and in a mound of stone to top, with brass cap mkd. <div style="text-align: center;"> <table border="1"> <tr><td>$\frac{1}{4}$ S13</td></tr> </table> <p>1952</p> </div> N. $88^{\circ} 44'$ W., beginning new measurement.	$\frac{1}{4}$ S13			
$\frac{1}{4}$ S13					
8.00	Shallow wash, drains S.				
38.15	The closing corner of secs. 23 and 24.				
39.98	True point for the corner of secs. 13 and 14, at proportionate distance, falls on cattle scale platform, there is no remaining evidence of the original corner. Land, rolling. Soil, rocky clay. No timber; undergrowth, scattering catclaw and cacti.				
	From the true point for corner of secs. 13 and 14. N. $0^{\circ} 04'$ E., bet. secs. 13 and 14.				

Dependent Resurvey, Portion of Subdivision of T. 11 N., R. 2 E.

Chains	Over gently rolling land, through scattering undergrowth.
0.10	Point for the witness corner of secs. 13 and 14. Set an iron post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 24 ins. in the ground, with brass cap mkd. <div style="text-align: center;"> W C T11NR2E S14 S13 ----- S 23 1952 </div> Deposit a stone, mkd. X at base of iron post.
20.475	Point for the S 1/16 sec. cor. of secs. 13 and 14, at proportionate distance. Set an iron post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 15 ins. in the ground to bedrock, and in a mound of stone to top, with brass cap mkd. <div style="text-align: center;"> S 1/16 S14 S13 ----- 1952 </div>
40.95	Point for the $\frac{1}{4}$ sec. cor. of secs. 13 and 14, at proportionate distance, there is no remaining evidence of the original corner. Set an iron post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 6 ins. in the ground to bedrock, and in a mound of stone to top, with brass cap mkd. <div style="text-align: center;"> $\frac{1}{4}$ S14 S13 ----- 1952 </div>
61.425	Point for the N 1/16 sec. cor. of secs. 13 and 14, at proportionate distance. Set an iron post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 6 ins. in the ground to bedrock, and in a mound of stone to top, with brass cap mkd. <div style="text-align: center;"> N 1/16 S14 S13 ----- 1952 </div>
68.50	Shallow wash, drains ESE.
81.90	Point for the corner of secs. 11, 12, 13, and 14, at proportionate distance, there is no remaining evidence of the original corner. Set an iron post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 6 ins. in the ground to bedrock, and in a mound of stone to top, with brass cap mkd. <div style="text-align: center;"> T11NR2E S11 S12 ----- S14 S13 ----- 1952 </div> From this corner the corner of secs. 1, 2, 35, and 36, on the N. bdy. of the Tp., bears N. $0^{\circ} 09'$ E., 163.80 chs. dist.

Dependent Resurvey, Portion of Subdivision of T. 11 N., R. 2 E.

Chains	<p>Land, gently rolling. Soil, rocky clay. No timber; undergrowth, scattering catclaw and cacti.</p>
	<p>From the corner of secs. 7, 12, 13, and 18, on the E. bdy. of the Tp. N. 89° 00' W., bet. secs. 12 and 13.</p>
	<p>Over nearly level land, through scattering undergrowth.</p>
5.30	<p>Ascend 160 ft. along rocky NE. slope.</p>
18.20	<p>Top of bluff, 50 ft. high, bears NW. and SE. Thence over rolling land.</p>
27.00	<p>Descend 90 ft.</p>
31.90	<p>A ravine, course NE.; ascend 80 ft.</p>
37.00	<p>Top of ascent; thence over rolling land.</p>
40.075	<p>Point for the $\frac{1}{4}$ sec. cor. of secs. 12 and 13, at proportionate distance, there is no remaining evidence of the original corner.</p>
	<p>Set an iron post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 6 ins. in the ground to bedrock, and in a mound of stone to top, with brass cap mkd.</p>
	<p style="text-align: center;"> $\begin{array}{r} \cdot \text{ S } 12 \\ \frac{1}{4} \\ \cdot \text{ S } 13 \\ \cdot 1952 \end{array}$ </p>
60.30	<p>A ravine, course S.</p>
80.15	<p>The corner of secs. 11, 12, 13, and 14.</p>
	<p>Land, rolling and broken. Soil, rocky clay. No timber; undergrowth, scattering catclaw and mesquite.</p>
	<p>From the $\frac{1}{4}$ sec. cor. of secs. 22 and 23, which is monumented with an iron post, 1 in. diam., set, marked and witnessed as described in the official record.</p>
	<p>N. 0° 03' E., bet. secs. 22 and 23.</p>
	<p>Over mountainous land, through scattering undergrowth.</p>
1.35	<p>Old road, bears E. and W., descend 25 ft.</p>
5.50	<p>A ravine, course ENE.; ascend 130 ft.</p>
15.00	<p>Top of spur, slopes E.</p>
19.20	<p>A ravine, course E.</p>
20:00	<p>Point for the N $\frac{1}{16}$ sec. cor. of secs. 22 and 23, at proportionate distance.</p>
	<p>Set an iron post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 6 ins. in the ground to bedrock, and in a mound of stone to top, with brass cap mkd.</p>
	<p style="text-align: center;"> $\begin{array}{r} \text{ N } 1/16 \\ \text{ S22 } \mid \text{ S23 } \\ 1952 \end{array}$ </p>

Dependent Resurvey, Portion of Subdivision of T. 11 N., R. 2 E.

Chains	Top of spur, slopes E.; descend 150 ft. over rocky N. slope.
25.70	A ravine, course E.
43.10	Wash, 20 lks. wide, 3 ft. deep, drains E.
43.42	The closing corner of secs. 22 and 23, which is monumented with an iron post, 2 ins. diam., set, marked and witnessed as described in the official record.
	From this corner the corner of secs. 14 and 15, bears N. 88° 44' W., 1.63 chs. dist.
	Land, mountainous. Soil, rocky clay. No timber; undergrowth, scattering juniper, catclaw and mesquite.
	From the corner of secs. 13 and 14.
	N. 88° 44' W., on the S. bdy. of sec. 14.
	Over nearly level land, through scattering undergrowth.
18.21	Point for the E 1/16 sec. cor. of sec. 23, at proportionate distance. Set an iron post, 28 ins. long, 2 $\frac{1}{2}$ ins. diam., 24 ins. in the ground, with brass cap mkd.
	<u>E 1/16 S23</u> 1952
	raise a mound of stone, 3 ft. base, 2 ft. high, S. of cor,
19.99	Point for the E 1/16 sec. cor. of sec. 14, at proportionate distance. Set an iron post, 28 ins. long, 2 $\frac{1}{2}$ ins. diam., 24 ins. in the ground, with brass cap mkd.
	<u>E 1/16 S14</u> 1952
	raise a mound of stone, 3 ft. base, 2 ft. high, N. of cor.
24.988	Point for the E-W-E 1/256 sec. cor. of sec. 14. Set a wooden stake, 2 ft. long, 2 ins. sq., 12 ins. in the ground, marked for lots 61 and 62 of sec. 14.
28.23	Point for the W-E 1/64 sec. cor. of sec. 23. Set a wooden stake, 2 ft. long, 2 ins. sq., 12 ins. in the ground, marked for lot 5 of sec. 23.
29.985	Point for the W-E 1/64 sec. cor. of sec. 14. Set a wooden stake, 2 ft. long, 2 ins. sq., 12 ins. in the ground, marked for lots 60 and 61 of sec. 14.
38.25	Point for the $\frac{1}{4}$ sec. cor. of sec. 23, at proportionate distance, there is no remaining evidence of the original corner. Set an iron post, 28 ins. long, 2 $\frac{1}{2}$ ins. diam., 24 ins. in the ground, with brass cap mkd.

Dependent Resurvey, Portion of Subdivision of T. 11 N., R. 2 E.

Chains

 $\frac{1}{4}$ S 23

1952

raise a mound of stone, 3 ft. base, 2 ft. high, S. of cor.

39.98 Point for the $\frac{1}{4}$ sec. cor. of sec. 14, at proportionate distance, there is no remaining evidence of the original corner.Set an iron post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 24 ins. in the ground, with brass cap mkd. $\frac{1}{4}$ S 14

1952

raise a mound of stone, 3 ft. base, 2 ft. high, N. of cor.

41.699 **Intersect** the E. bdy. of Highway right-of-way, point for the cor. of lots D and 60 of sec. 14, and lots A and 5 of sec. 23.Set an iron post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 24 ins. in the ground, with brass cap mkd.

LOT	LOT
D	60
	S14
<hr/>	
LOT	LOT
A	5
	S23
	1952

48.27 Point for the E-W $1/64$ sec. cor. of sec. 23, not monumented.

48.663 Intersect the W. bdy of Highway right-of-way, point for the cor. of lots D and 58 of sec. 14, and lots A and 9 of sec. 23.

Set an iron post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 24 ins. in the ground, with brass cap mkd.

LOT	LOT
58	D
S14	
<hr/>	
LOT	LOT
9	A
S23	
	1952

Thence over rolling land.

49.975 Point for the E-W $1/64$ sec. cor. of sec. 14,Set a wooden stake, 2 ft. long, 2 ins. sq., 12 ins. in the ground, marked E-W $1/64$ S14.58.29 Point for the W $1/16$ sec. cor. of sec. 23, at proportionate distance.Set an iron post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 15 ins. in the ground, to bedrock, and in a mound of stone to top, with brass cap mkd.W. $1/16$ S23

1952

59.97 Point for the W $1/16$ sec. cor. of sec. 14, at proportionate distance.Set an iron post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 24 ins. in the ground, with brass cap mkd.

Dependent Resurvey, Portion of Subdivision of T. 11 N., R. 2 E.

Chains

W 1/16 S14

1952

raise a mound of stone, 3 ft. base, 2 ft. high, N. of cor.

67.70 Big Bug Creek, 25 lks. wide, 6 ins. deep, course SSE.; ascend 60 ft. over rocky E. slope.

78.33 The closing corner of secs. 22 and 23.

79.96 The corner of secs. 14 and 15, which is monumented with a granite stone, 18x10x10 ins., firmly set, and properly marked.

At the corner point

Set an iron post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 24 ins. in the ground, with brass cap mkd.

T11NR2E

S15 | S14

S22

1952

raise a mound of stone, 3 ft. base, 2 ft. high, N. of cor.

Land, east-half, nearly level; west-half, rolling hills.

Soil, rocky clay.

No timber; undergrowth, scattering catclaw, mesquite and juniper.

North, bet. secs. 14 and 15.

Ascend 20 ft. over rocky S. slope.

3.30 Top of ascent; descend 60 ft. over rocky N. slope.

9.05 Big Bug Creek, 25 lks. wide, 4 ins. deep, course S. 70° E. Thence over rolling land.

20.373 Point for the S 1/16 sec. cor. of secs. 14 and 15, at proportionate distance.

Set an iron post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 18 ins. in the ground to bedrock, and in a mound of stone to top, with brass cap mkd.

S 1/16

S15 | S14

1952


30.559 Point for the N-S 1/64 sec. cor. of secs. 14 and 15.

Set a wooden stake, 2 ft. long, 2 ins. sq., 12 ins. in the ground, marked for lots 38 and 39 of sec. 14.

40.746 Point for the $\frac{1}{4}$ sec. cor. of secs. 14 and 15, at proportionate distance, there is no remaining evidence of the original corner.Set an iron post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 24 ins. in the ground, with brass cap mkd.

Dependent Resurvey, Portion of Subdivision of T. 11 N., R. 2 E.

Chains



raise a mound of stone, 3 ft. base, 2 ft. high, W. of cor.


49.468

Intersect the S. bdy. of proposed Highway right-of-way, true point for the cor. of lots C and 28 of sec. 14, falls in wash, which drains SE.

49.56

Point for the witness cor. of lots C and 28.

Set an iron post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 24 ins. in the ground, with brass cap mkd.



50.932


Point for the S-N $1/64$ sec. cor. of secs. 14 and 15

Set a wooden stake, 2 ft. long, 2 ins. sq., 12 ins. in the ground, marked S-N $1/64$

57.76

Intersect the N. bdy of proposed Highway right-of-way, point for the cor. of lots C and 27 of sec. 14


Set an iron post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 6 ins. in the ground to bedrock, and in a mound of stone to top, with brass cap mkd.



61.119

Point for the N $1/16$ sec. cor. of secs. 14 and 15, at proportionate distance.

Set an iron post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 24 ins. in the ground, with brass cap mkd.



raise a mound of stone, 3 ft. base, 2 ft. high, W. of cor.

65.20

Graded road, bears E, and W.

71.305

Point for the N-N $1/64$ sec. cor. of secs. 14 and 15.

Set a wooden stake, 2 ft. long, 2 ins. sq., 12 ins. in the ground, marked for lots 8 and 9 of sec. 14.

81.492

Point for the cor. of secs. 10, 11, 14, and 15, at proportionate distance, there is no remaining evidence of the original corner.

Set an iron post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 24 ins. in the ground, with brass cap mkd.

Dependent Resurvey, Portion of Subdivision of T. 11 N., R. 2 E.

Chains

T11NR2E	
S10	S11
S15	S14
1952	

raise a mound of stone, 3 ft. base, 2 ft. high, W. of cor.

From this corner the corner of secs. 2, 3, 34, and 35, on the N. bdy. of the Tp., bears N. 0° 03' E., 163.09 chs. dist.

From this same corner the corner of secs. 7 and 18, on the W. bdy. of the Tp., which is monumented with a granite stone, 12x12x3 ins., firmly set, and marked 2 grooves N. and 4 grooves S. faces, bears N. 89° 05' W., 318.93 chs. dist.

At the corner point

Set an iron post, 28 ins. long, 2½ ins. diam., 18 ins. in the ground to bedrock, and in a mound of stone to top, with brass cap mkd.

T11½	T11N
R1E	R2E
S36	S 7
	S18
1952	

Land, rolling hills.

Soil, rocky clay.

No timber; undergrowth, scattering juniper, catclaw and mesquite.

From the corner of secs. 11, 12, 13, and 14.

N. 89° 02' W., bet. secs. 11 and 14.

Over rolling land, through scattering undergrowth.

20.013 Point for the E 1/16 sec. cor. of secs. 11 and 14, at proportionate distance.

Set an iron post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.

E 1/16	S 11
	S 14
1952	

raise a mound of stone, 3 ft. base, 2 ft. high, N. of cor.

27.30 Highway fence, parallel to road.

28.88 Black Canyon Highway, bears N. 11° 33' E. and S. 11° 33' W.

30.38 Highway fence, parallel to road.

40.026 Point for the ¼ sec. cor. of secs. 11 and 14, at proportionate distance, there is no remaining evidence of the original corner.

Set an iron post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.

¼	S 11
	S 14
1952	


Dependent Resurvey, Portion of Subdivision of T. 11 N., R. 2 E.

Chains	raise a mound of stone, 3 ft. base, 2 ft. high, N. of cor.
45.030	Point for the E-E-W $1/256$ sec. cor. of secs. 11 and 14. Set a wooden stake, 2 ft. long, 2 ins. sq., 12 ins. in the ground, marked for lots 1 and 2 of sec. 14.
50.034	Point for the E-W $1/64$ sec. cor. of secs. 11 and 14. Set a wooden stake, 2 ft. long, 2 ins. sq., 12 ins. in the ground, marked for lots 2 and 3 of sec. 14.
55.037	Point for the W-E-W $1/256$ sec. cor. of secs. 11 and 14. Set a wooden stake, 2 ft. long, 2 ins. sq., 12 ins. in the ground, marked for lots 3 and 4 of sec. 14.
60.040	Point for the W $1/16$ sec. cor. of secs. 11 and 14, at proportionate distance. Set an iron post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 24 ins. in the ground, with brass cap mkd. <div style="text-align: center;"> $\begin{array}{r} \text{S } 11 \\ \hline \text{W } 1/16 \\ \hline \text{S } 14 \\ 1952 \end{array}$ </div>
	raise a mound of stone, 3 ft. base, 2 ft. high, N. of cor.
65.043	Point for the E-W-W $1/256$ sec. cor. of secs. 11 and 14. Set a wooden stake, 2 ft. long, 2 ins. sq., 12 ins. in the ground, marked for lots 5 and 6 of sec. 14.
70.046	Point for the W-W $1/64$ sec. cor. of secs. 11 and 14. Set a wooden stake, 2 ft. long, 2 ins. sq., 12 ins. in the ground, marked for lots 6 and 7 of sec. 14.
75.049	Point for the W-W-W $1/256$ sec. cor. of secs. 11 and 14. Set a wooden stake, 2 ft. long, 2 ins. sq., 12 ins. in the ground, marked for lots 7 and 8 of sec. 14.
78.40	Wash, 20 lks. wide, 3 ft. deep, drains ESE.
80.052	The corner of secs. 10, 11, 14, and 15. Land, rolling. Soil, rocky clay. No timber, undergrowth, scattering catclaw, juniper and mesquite.
Subdivision of Section 14, T. 11 N., R. 2 E.	
From the $\frac{1}{4}$ sec. cor. of sec. 14, on the S. bdy. of the section.	
N. $0^{\circ} 02'$ E., on the N. and S. center line of sec. 14.	
Over rolling land.	
5.108	Point for the C-S-S-S $1/256$ sec. cor. of sec. 14. Set a wooden stake, 2 ft. long, 2 ins. sq., 12 ins. in the ground, marked for lots 59 and 60.
8.556	Intersect the E. bdy. of Highway right-of-way, point for the cor. of lots E, D and 59.

Subdivision of Section 14, T. 11 N., R. 2 E.

Chains

Set an iron post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 24 ins. in the ground, with brass cap mkd.



10.216


Point for the C-S-S $1/64$ sec. cor. of sec. 14.

Set a wooden stake, 2 ft. long, 2 ins. sq., 12 ins. in the ground, marked C-S-S $1/64$

20.432

Point for the C-S $1/16$ sec. cor. of sec. 14.

Set an iron post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 24 ins. in the ground, with brass cap mkd.



raise a mound of stone, 3 ft. base, 2 ft. high, W. of cor.

24.90

Black Canyon Highway, bears N. $11^{\circ} 33'$ E. and S. $11^{\circ} 33'$ W.

30.648


Point for the C-N-S $1/64$ sec. cor. of sec. 14.

Set a wooden stake, 2 ft. long, 2 ins. sq., 12 ins. in the ground, marked C-N-S $1/64$.

40.864

Point for the C $1/4$ sec. cor. of sec. 14, at the intersection of the E. and W. center line of sec. 14.

Set an iron post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 24 ins. in the ground, with brass cap mkd.



raise a mound of stone, 3 ft. base, 2 ft. high, W. of cor.

51.079


Point for the C-S-N $1/64$ sec. cor. of sec. 14.

Set a wooden stake, 2 ft. long, 2 ins. sq., 12 ins. in the ground, marked for lots A, B, 19, and 20.

61.294

Point for the C-N $1/16$ sec. cor. of sec. 14.

Set an iron post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 24 ins. in the ground, with brass cap mkd.



raise a mound of stone, 3 ft. base, 2 ft. high, W. of cor.

71.509


Point for the C-N-N $1/64$ sec. cor. of sec. 14.

Subdivision of Section 14, T. 11 N., R. 2 E.

Chains	Set a wooden stake, 2 ft. long, 2 ins. sq., 12 ins. in the ground, marked for lots 1 and 16.
74.50	Wash, 15 lks. wide, 4 ft. deep, drains E.
81.724	The $\frac{1}{4}$ sec. cor. of secs. 11 and 14. Land, rolling. Soil, rocky clay. No timber; undergrowth, scattering catclaw, mesquite and juniper.
	From the $\frac{1}{4}$ sec. cor. of secs. 13 and 14. N. 88° 53' W., on the E. and W. center line of sec. 14. Over rolling land, through scattering undergrowth.
20.02	Point for the C-E $\frac{1}{16}$ sec. cor. of sec. 14. Set an iron post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 24 ins. in the ground, with brass cap mkd. $\begin{array}{c} \text{E } \frac{1}{16} \\ \text{C} \text{-----} \text{C} \\ \text{S } \frac{1}{4} \\ 1952 \end{array}$
	raise a mound of stone, 3 ft. base, 2 ft. high, N. of cor.
30.03	Point for the C-W-E $\frac{1}{64}$ sec. cor. of sec. 14. Set a wooden stake, 2 ft. long, 2 ins. sq., 12 ins. in the ground, marked C-W-E $\frac{1}{64}$.
33.54	Intersect the E. bdy. of Highway right-of-way, point for the cor. of lots A, E, 31, and 32. Set an iron post, 28 ins. long; $2\frac{1}{2}$ ins. diam., 24 ins. in the ground, with brass cap mkd. $\begin{array}{c} \text{LOT} \quad \text{LOT} \\ \text{A} \quad \quad 31 \\ \text{G} \text{-----} \text{C} \\ \text{LOT} \quad \text{LOT} \\ \text{E} \quad \quad 32 \\ \text{S } \frac{1}{4} \\ 1952 \end{array}$
36.57	Black Canyon Highway, bears N. 11° 33' E. and S. 11° 33' W.
40.04	The C $\frac{1}{4}$ sec. cor. of sec. 14.
50.038	Point for the C-E-W $\frac{1}{64}$ sec. cor. of sec. 14. Set a wooden stake, 2 ft. long; 2 ins. sq., 12 ins. in the ground, marked C-E-W $\frac{1}{64}$.
60.036	Point for the C-W $\frac{1}{16}$ sec. cor. of sec. 14. Set an iron post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 24 ins. in the ground, with brass cap mkd. $\begin{array}{c} \text{W } \frac{1}{16} \\ \text{C} \text{-----} \text{C} \\ \text{S } \frac{1}{4} \\ 1952 \end{array}$
	raise a mound of stone, 3 ft. base, 2 ft. high, N. of cor.
61.486	Intersect the N. bdy. of proposed Highway right-of-way, point for the cor. of lots B, C, D.

Subdivision of Section 14, T. 11 N., R. 2 E.

Chains Set an iron post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 24 ins. in the ground, with brass cap mkd.



raise a mound of stone, 3 ft. base, 2 ft. high, N. of cor.


63.15 Graded road, bears NW. and SE.

70.034 Point for the C-W-W $1/64$ sec. cor. of sec. 14.

Set a wooden stake, 2 ft. long, 2 ins. sq., 12 ins. in the ground, marked C-W-W $1/64$.

70.498 Intersect the S. bdy. of proposed Highway right-of-way, point for the cor. of lots C and 37.

Set an iron post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 24 ins. in the ground, with brass cap mkd.



75.033 Point for the C-W-W-W $1/256$ sec. cor. of sec. 14.

Set a wooden stake, 2 ft. long, 2 ins. sq., 12 ins. in the ground, marked for lots 28, 37 and 38.

78.55 Draw, course S.

80.032 The $\frac{1}{4}$ sec. cor. of secs. 14 and 15.

Land, rolling hills.

Soil, rocky clay.

No timber; undergrowth, scattering catclaw, mesquite and juniper.

Subdivision of the NE $\frac{1}{4}$.

From the C-E $1/16$ sec. cor. of sec. 14.

N. $0^{\circ} 03'$ E., on the N. and S. center line of the NE $\frac{1}{4}$ of sec. 14.

3.408 Point for the cor. of lots 30 and 31.

Set a wooden stake, 2 ft. long, 2 ins. sq., 12 ins. in the ground, marked for lots 30 and 31.

6.816 Point for the cor. of lots 29 and 30.

Set a wooden stake, 2 ft. long, 2 ins. sq., 12 ins. in the ground, marked for lots 29 and 30.

10.224 Point for the C-S-NE $1/64$ sec. cor. of sec. 14.

Set a wooden stake, 2 ft. long, 2 ins. sq., 12 ins. in the ground, marked for lots 18 and 29.

15.336 Point for the C-N-S-NE $1/256$ sec. cor. of sec. 14.

Set a wooden stake, 2 ft. long, 2 ins. sq., 12 ins. in the ground, marked for lots 17 and 18.

20.448 Point for the NE $1/16$ sec. cor. of sec. 14, at the intersection of the E. and W. center line of the NE $\frac{1}{4}$ of sec. 14.

Set an iron post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 24 ins. in the ground, with brass cap mkd.

Subdivision of Section 14, T. 11 N., R. 2 E.

Chains

NE 1/16 S14

1952

raise a mound of stone, 3 ft. base, 2 ft. high, W. of cor.

40.904 The E 1/16 sec. cor. of secs. 11 and 14.

From the N 1/16 sec. cor. of secs. 11 and 14.

N. 88° 58' W., on the E. and W. center line of the NE 1/4 of sec. 14.

20.015 The NE 1/16 sec. cor. of sec. 14.

29.436 Intersect the E. bdy. of Highway right-of-way, point for the cor. of lots A and 17.

Set an iron post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.

LOT A	/	LOT 17 S14
1952		

raise a mound of stone, 3 ft. base, 2 ft. high, N. of cor.

30.025 Point for the C-W-NE 1/64 sec. cor. of sec. 14.

Set a wooden stake, 2 ft. long, 2 ins. sq., 12 ins. in the ground, marked C-W-NE 1/64.

32.54 Center line of Black Canyon Highway, bears N. 11° 33' E. and S. 11° 33' W.

35.637 Intersect the W. bdy. of Highway right-of-way, point for the cor. of lots A and 19.

Set an iron post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.

LOT 19 S14	/	LOT A
1952		

raise a mound of stone, 3 ft. base, 2 ft. high, N. of cor.

40.034 The C-N 1/16 sec. cor. of sec. 14.

Subdivision of the SW 1/4 NE 1/4.

From the C-W-E 1/64 sec. cor. of sec. 14.

N. 0° 02' E., on the N. and S. center line of the SW 1/4 NE 1/4 of sec. 14.

10.212 Point for the SW-NE 1/64 sec. cor. of sec. 14, at the intersection of the E. and W. center line of the SW 1/4 NE 1/4 of sec. 14.

Set a wooden stake, 2 ft. long, 2 ins. sq., 12 ins. in the ground, marked SW-NE 1/64.

17.451 Intersect the E. bdy. of Highway right-of-way.

Set an iron post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.

Subdivision of Section 14, T. 11 N., R. 2 E.

Chains

LOT
A / LOT
17
S14
1952

raise a mound of stone, 3 ft. base, 2 ft. high, W. of cor.

20.427 The C-W-NE $1/64$ sec. cor. of sec. 14.

From the C-S-NE $1/64$ sec. cor. of sec. 14.

N. $88^{\circ} 55'$ W., on the E. and W. center line of the SW $\frac{1}{4}$ NE $\frac{1}{4}$ of sec. 14.

10.008 The SW-NE $1/64$ sec. cor. of sec. 14.

11.474 Intersect the E. bdy. of Highway right-of-way, point for the cor. of lots A, 18 and 29.

Set an iron post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 24 ins. in the ground, with brass cap mkd.

LOT
A / LOT
18
LOT
29
S14
1952

raise a mound of stone, 3 ft. base, 2 ft. high, N. of cor.

14.56 Center line of Black Canyon Highway, bears N. $11^{\circ} 33'$ E. and S. $11^{\circ} 33'$ W.

17.653 Intersect the W. bdy. of Highway right-of-way, point for the cor. of lots A and 19.

Set an iron post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 24 ins. in the ground, with brass cap mkd.

LOT
19 / LOT
S14 / A
1952

raise a mound of stone, 3 ft. base, 2 ft. high, N. of cor.

20.02 The C-S-N $1/64$ sec. cor. of sec. 14.

Subdivision of the NW $\frac{1}{4}$.

From the C-W $1/16$ sec. cor. of sec. 14.

N. $0^{\circ} 01'$ E., on the N. and S. center line of the NW $\frac{1}{4}$ of sec. 14.

2.60 Head of a draw, course SE.

10.201 Point for the C-S-NW $1/64$ sec. cor. of sec. 14.

Set a wooden stake, 2 ft. long, 2 ins. sq., 12 ins. in the ground, marked for lots B, 23 and 24.

18.00 Wash, 10 lks. wide, 3 ft. deep, drains E.

20.402 Point for the NW $1/16$ sec. cor. of sec. 14, at the intersection of the E. and W. center line of the NW $\frac{1}{4}$ of sec. 14.

Subdivision of Section 14, T. 11 N., R. 2 E.

Chains	Set an iron post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 24 ins. in the ground, with brass cap mkd.
	NW 1/16 S14
	1952
	raise a mound of stone, 3 ft. base, 2 ft. high, W. of cor.
20.612	Point for the C-N-NW 1/64 sec. cor. of sec. 14. Set a wooden stake, 2 ft. long, 2 ins. sq., 12 ins. in the ground, marked for lots 4, 5, 12, and 13.
33.50	Wash, 15 lks. wide, 4 ft. deep, drains E.
40.823	The W 1/16 sec. cor. of secs. 11 and 14.

	From the C-N 1/16 sec. cor. of sec. 14. N. 88° 58' W., on the E. and W. center line of the NW $\frac{1}{4}$ of sec. 14.
5.00	Point for the C-E-E-NW 1/256 sec. cor. of sec. 14. Set a wooden stake, 2 ft. long, 2 ins. sq., 12 ins. in the ground, marked for lots 15, 16, 20, and 21.
10.00	Point for the C-E-NW 1/64 sec. cor. of sec. 14. Set a wooden stake, 2 ft. long, 2 ins. sq., 12 ins. in the ground, marked for lots 14, 15, 21, and 22.
15.00	Point for the C-W-E-NW 1/256 sec. cor. of sec. 14. Set a wooden stake, 2 ft. long, 2 ins. sq., 12 ins. in the ground, marked for lots 13, 14, 22, and 23.
20.00	The NW 1/16 sec. cor. of sec. 14.
25.004	Point for the C-E-W-NW 1/256 sec. cor. of sec. 14. Set a wooden stake, 2 ft. long, 2 ins. sq., 12 ins. in the ground, marked for lots 11, 12, 24, and 25.
30.008	Point for the C-W-NW 1/64 sec. cor. of sec. 14. Set a wooden stake, 2 ft. long, 2 ins. sq., 12 ins. in the ground, marked for lots 10, 11, 25, and 26.
34.65	Graded road, bears NW. and SE.
35.012	Point for the C-W-W-NW 1/256 sec. cor. of sec. 14. Set a wooden stake, 2 ft. long, 2 ins. sq., 12 ins. in the ground, marked for lots 9, 10, 26, and 27.
40.016	The N 1/16 sec. cor. of secs. 14 and 15.
	Subdivision of the NE $\frac{1}{4}$ NW $\frac{1}{4}$.
	From the C-E-NW 1/64 sec. cor. of sec. 14. N. 0° 01' E., on the N. and S. center line of the NE $\frac{1}{4}$ NW $\frac{1}{4}$ of sec. 14.
3.70	Wash, drains E.
10.213	Point for the NE-NW 1/64 sec. cor. of sec. 14, at the intersection of the E. and W. center line of the NE $\frac{1}{4}$ NW $\frac{1}{4}$ of sec. 14.

Subdivision of Section 14, T. 11 N., R. 2 E.

Chains	Set a wooden stake, 2 ft. long, 2 ins. sq., 12 ins. in the ground, marked for lots 2, 3, 14, and 15.
12.80	Wash, 10 lks. wide, 3 ft. deep, drains S. 80° E.
40.426	The E-W 1/64 sec. cor. of secs 11 and 14.
	From the C-N-N 1/64 sec. cor. of sec. 14.
	N. 89° 00' W., on the E. and W. center line of the NE $\frac{1}{4}$ NW $\frac{1}{4}$ of sec. 14.
1.30	Wash, 10 lks. wide, 2 ft. deep, drains NE.
5.004	Point for the C-E-NE-NW 1/256 sec. cor. of sec. 14.
	Set a wooden stake, 2 ft. long, 2 ins. sq., 12 ins. in the ground, marked for lots 1, 2, 15, and 16.
10.008	The NE-NW 1/64 sec. cor. of sec. 14.
15.012	Point for the C-W-NE-NW 1/256 sec. cor. of sec. 14.
	Set a wooden stake, 2 ft. long, 2 ins. sq., 12 ins. in the ground, marked for lots 3, 4, 13, and 14.
20.016	The C-N-NW 1/64 sec. cor. of sec. 14.
Subdivision of the NW $\frac{1}{4}$ NW $\frac{1}{4}$.	
	From the C-W-NW 1/64 sec. cor. of sec. 14.
	N. 0° 01' E., on the N. and S. center line of the NW $\frac{1}{4}$ NW $\frac{1}{4}$ of sec. 14.
10.195	Point for the NW-NW 1/64 sec. cor. of sec. 14, at the intersection of the E. and W. center line of the NW $\frac{1}{4}$ NW $\frac{1}{4}$ of sec. 14.
	Set a wooden stake, 2 ft. long, 2 ins. sq., 12 ins. in the ground, marked for lots 6, 7, 10, and 11.
17.60	Wash, 10 lks. wide, 2 ft. deep, drains SE.
20.393	The W-W 1/64 sec. cor. of secs. 11 and 14.
	From the C-N-NW 1/64 sec. cor. of sec. 14.
	N. 89° 00' W., on the E. and W. center line of the NW $\frac{1}{4}$ NW $\frac{1}{4}$ of sec. 14.
5.002	Point for the C-E-NW-NW 1/256 sec. cor. of sec. 14.
	Set a wooden stake, 2 ft. long, 2 ins. sq., 12 ins. in the ground, marked for lots 5, 6, 11, and 12.
10.004	The NW-NW 1/64 sec. cor. of sec. 14.
15.004	Point for the C-W-NW-NW 1/256 sec. cor. of sec. 14.
	Set a wooden stake, 2 ft. long, 2 ins. sq., 12 ins. in the ground, marked for lots 7, 8, 9, and 10.
20:004	The N-N 1/64 sec. cor. of secs. 14 and 15.
Subdivision of the SW $\frac{1}{4}$ NW $\frac{1}{4}$.	
	From the C-W-W 1/64 sec. cor. of sec. 14.
	North, on the N. and S. center line of the SW $\frac{1}{4}$ NW $\frac{1}{4}$ of sec. 14.

Subdivision of Section 14, T. 11 N., R. 2 E.

Chains

7.861

Intersect the N. bdy. of proposed Highway right-of-way, on line bet. lots B and C.

Set an iron post, 28 ins. long, $2\frac{1}{2}$ ins. diam., $2\frac{1}{2}$ ins. in the ground, with brass cap mkd.

LOT C LOT B

1952

raise a mound of stone, 3 ft. base, 2 ft. high, W. of cor.

9.70

Graded road, bears NW. and S.

10.20

Point for the SW-NW $1/64$ sec. cor. of sec. 14. at the intersection of the E. and W. center line of the SW $1/4$ NW $1/4$ of sec. 14.

Set a wooden stake, 2 ft. long, 2 ins. sq., 12 ins. in the ground, marked for lots B, 25 and 26.

20.394

The C-W-NW $1/64$ sec. cor. of sec. 14.From the C-S-NW $1/64$ sec. cor. of sec. 14.N. $88^{\circ} 55'$ W., on the E. and W. center line of the SW $1/4$ NW $1/4$ of sec. 14.

5.00

Point for the C-E-SW-NW $1/256$ sec. cor. of sec. 14.

Set a wooden stake, 2 ft. long, 2 ins. sq., 12 ins. in the ground, marked for lots B, 24 and 25.

7.90

Graded road, bears NW. and SE.

10.00

The SW-NW $1/64$ sec. cor. of sec. 14.

12.551

Intersect the N. bdy. of proposed Highway right-of-way, point for the cor. of lots B, C and 26.

Set an iron post, 28 ins. long, $2\frac{1}{2}$ ins. diam., $2\frac{1}{2}$ ins. in the ground, with brass cap mkd.

LOT 26
S14
LOT C LOT B

1952

raise a mound of stone, 3 ft. base, 2 ft. high, N. of cor.

18.40

Draw, course S.

19.998

The S-N $1/64$ sec. cor. of secs. 14 and 15.Subdivision of the SE $1/4$ NW $1/4$.From the C-E-W $1/64$ sec. cor. of sec. 14.N. $0^{\circ} 01'$ E., on the N. and S. center line of the SE $1/4$ NW $1/4$ of sec. 14.

10.205

Point for the SE-NW $1/64$ sec. cor. of sec. 14. at the intersection of the E. and W. center line of the SE $1/4$ NW $1/4$ of sec. 14.

Set a wooden stake, 2 ft. long, 2 ins. sq., 12 ins. in the ground, marked for lots B, 21 and 22.

20.407

The C-E-NW $1/64$ sec. cor. of sec. 14.

Subdivision of Section 14, T. 11 N., R. 2 E.

Chains	
	From the C-S-N $1/64$ sec. cor. of sec. 14. N. $88^{\circ} 55'$ W., on the E. and W. center line of the $SE\frac{1}{4}NW\frac{1}{4}$ of sec. 14.
4.999	Point for the C-E-SE-NW $1/256$ sec. cor. of sec. 14. Set a wooden stake; 2 ft. long, 2 ins. sq., 12 ins. in the ground, marked for lots B, 20 and 21.
9.999	The SE-NW $1/64$ sec. cor. of sec. 14.
14.996	Point for the C-W-SE-NW $1/256$ sec. cor. of sec. 14. Set a wooden stake, 2 ft. long, 2 ins. sq., 12 ins. in the ground, marked for lots B. 22 and 23.
19.993	The C-S-NW $1/64$ sec. cor. of sec. 14.
Subdivision of the $SW\frac{1}{4}$.	
	From the W $1/16$ sec. cor. on the S. bdy. of sec. 14. N. $0^{\circ} 01'$ E., on the N. and S. center line of the $SW\frac{1}{4}$ of sec. 14.
3.401	Point for the cor. of lots 57 and 58. Set a wooden stake, 2 ft. long, 2 ins. sq., 12 ins. in the ground, marked for lots 57 and 58.
6.802	Point for the cor. of lots 56 and 57. Set a wooden stake, 2 ft. long, 2 ins. sq., 12 ins. in the ground, marked for lots 56 and 57.
8.20	Draw, course W.
10.203	Point for the C-S-SW $1/64$ sec. cor. of sec. 14. Set a wooden stake, 2 ft. long, 2 ins. sq., 12 ins. in the ground, marked for lots 55 and 56.
13.604	Point for the cor. of lots 54 and 55. Set a wooden stake, 2 ft. long, 2 ins. sq., 12 ins. in the ground, marked for lots 54 and 55.
17.005	Point for the cor. of lots 53 and 54. Set a wooden stake, 2 ft. long, 2 ins. sq., 12 ins. in the ground, marked for lots 53 and 54.
20.406	Point for the SW $1/16$ sec. cor. of sec. 14, at the intersection of the E. and W. center line of the $SW\frac{1}{4}$ of sec. 14. Set an iron post, 28 ins. long, 2 $\frac{1}{2}$ ins. diam., 24 ins. in the ground, with brass cap mkd.
	SW $1/16$ S14 1952
	raise a mound of stone, 3 ft. base, 2 ft. high, W. of cor.
25.509	Point for the C-S-N-SW $1/256$ sec. cor. of sec. 14. Set a wooden stake, 2 ft. long, 2 ins. sq., 12 ins. in the ground, marked for lots 41, 42, 43, and 44.
30.612	Point for the C-N-SW $1/64$ sec. cor. of sec. 14.


Subdivision of Section 14, T. 11 N., R. 2 E.

Chains

Set a wooden stake, 2 ft. long, 2 ins. sq., 12 ins. in the ground, marked for lots 36, 41, and 43.

30.968 Intersect the S. bdy. of proposed Highway right-of-way, point for the cor. of lots C, D, and 36.

Set an iron post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 24 ins. in the ground, with brass cap mkd.



raise a mound of stone, 3 ft. base, 2 ft. high, W. of cor.

34.43 Graded road, bears NW. and SE.

39.260 Intersect the N. bdy. of proposed Highway right-of-way, point for the cor. of lots C, and D.

Set a wooden stake, 2 ft. long, 2 ins. sq., 12 ins. in the ground, marked for lots C, and D.

40.818 The C-W 1/16 sec. cor. of sec. 14.

From the C-S 1/16 sec. cor. of sec. 14.

N. 88° 48' W., on the E. and W. center line of the SW $\frac{1}{4}$ of sec. 14.

0.65 Center line of Black Canyon Highway, bears N. 11° 33' E. and S. 11° 33' W.


9.85 Road, bears NW. and SE.

9.996 Point for the C-E-SW 1/64 sec. cor. of sec. 14, falls on W. side of road.

Set an iron bolt, 6 ins. long, $\frac{1}{2}$ in. diam., 10 ins. in the ground.

13.112 Intersect the W. bdy. of proposed Highway right-of-way, point for the cor. of lots D, 44, and 53.

Set an iron post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 24 ins. in the ground, with brass cap mkd.



raise a mound of stone, 3 ft. base, 2 ft. high. N. of cor.

19.992 The SW 1/16 sec. cor. of sec. 14.

27.20 Draw, course S.

29.987 Point for the C-W-SW 1/64 sec. cor. of sec. 14.

Set a wooden stake, 2 ft. long, 2 ins. sq., 12 ins. in the ground, marked for lots 40 and 42.

34.984 Point for the C-W-W-SW 1/256 sec. cor. of sec. 14.


Set a wooden stake, 2 ft. long, 2 ins. sq., 12 ins. in the ground, marked for lots 39 and 40.

Subdivision of Section 14, T. 11 N., R. 2 E.

Chains	
37.10	Draw, course S. 10° E.
39.982	The S 1/16 sec. cor. of secs. 14 and 15.
Subdivision of the NE 1/4 SW 1/4.	
	From the C-E-SW 1/64 sec. cor. of sec. 14.
	N. 0° 01' E., on the N. and S. center line of the NE 1/4 SW 1/4 of sec. 14.
10.21	Point for the NE-SW 1/64 sec. cor. of sec. 14, at the intersection of the E. and W. center line of the NE 1/4 SW 1/4 of sec. 14. Set a wooden stake, 2 ft. long, 2 ins. sq., 12 ins. in the ground, marked NE-SW 1/64.
12.60	Shallow wash, drains ESE.
20.422	The C-E-W 1/64 sec. cor. of sec. 14.
From the C-N-S 1/64 sec. cor. of sec. 14.	
	N. 88° 53' W., on the E. and W. center line of the NE 1/4 SW 1/4 of sec. 14.
9.996	The NE-SW 1/64 sec. cor. of sec. 14.
19.683	Intersect the S. bdy. of proposed Highway right-of-way, point for the cor. of lots D, 36 and 43. Set an iron post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.
19.994	raise a mound of stone, 3 ft. base, 2 ft. high, N. of cor. The C-N-SW 1/64 sec. cor. of sec. 14.
Subdivision of the NW 1/4 SW 1/4.	
	From the C-W-SW 1/64 sec. cor. of sec. 14.
	N. 0° 01' E., on the N. and S. center line of the NW 1/4 SW 1/4 of sec. 14.
5.097	Point for the C-S-NW-SW 1/256 sec. cor. of sec. 14. Set a wooden stake, 2 ft. long, 2 ins. sq., 12 ins. in the ground, marked for lots 40, 41 and 42.
10.193	Point for the NW-SW 1/64 sec. cor. of sec. 14, at the intersection of the E. and W. center line of the NW 1/4 SW 1/4 of sec. 14. Set a wooden stake, 2 ft. long, 2 ins. sq., 12 ins. in the ground, marked for lots 36, 37, 40, and 41.
15.292	Point for the C-N-NW-SW 1/256 sec. cor. of sec. 14. Set a wooden stake, 2 ft. long, 2 ins. sq., 12 ins. in the ground, marked for lots 35, 36 and 37.
19.96	Intersect the S. bdy. of proposed Highway right-of-way, point for the cor. of lots C, 35, and 37. Set an iron post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.

Subdivision of Section 14, T. 11 N., R. 2 E.

Chains




- 20.391 raise a mound of stone, 3 ft. base, 2 ft. high, W. of cor. The C-W-W 1/64 sec. cor. of sec. 14.

- 3.80 From the C-N-SW 1/64 sec. cor. of sec. 14.
N. 88° 53' W., on the E. and W. center line of the NW 1/4 SW 1/4 of sec. 14.
Draw, course S.
- 9.997 The NW-SW 1/64 sec. cor. of sec. 14.
- 14.995 Point for the C-W-NW-SW 1/256 sec. cor. of sec. 14.
Set a wooden stake, 2 ft. long, 2 ins. sq., 12 ins. in the ground, marked for lots 37, 38, 39, and 40.
- 19.40 Draw, course S.
- 19.993 The N-S 1/64 sec. cor. of secs. 14 and 15.

Subdivision of the SE 1/4 SW 1/4.

- 10.209 From the E-W 1/64 sec. cor. of sec. 14.
N. 0° 01' E., on the N. and S. center line of the SE 1/4 SW 1/4 of sec. 14.
Point for the SE-SW 1/64 sec. cor. of sec. 14, at the intersection of the E. and W. center line of the SE 1/4 SW 1/4 of sec. 14.
Set a wooden stake, 2 ft. long, 2 ins. sq., 12 ins. in the ground, marked SE-SW 1/64.
- 11.639 Intersect the W. bdy. of Highway right-of-way, point for the cor. of lots D and 55.
Set an iron post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.




- 20.419 raise a mound of stone, 3 ft. base, 2 ft. high, W. of cor. The C-E-SW 1/64 sec. cor. of sec. 14.

- 2.80 From the C-S-S 1/64 sec. cor. of sec. 14.
N. 88° 47' W., on the E. and W. center line of the SE 1/4 SW 1/4 of sec. 14.
Black Canyon Highway, bears N. 11° 33' E. and S. 11° 33' W.
- 9.692 Intersect the W. bdy. of Highway right-of-way, point for the cor. of lots 55, 56, and D.
Set an iron post, 28 ins. long, 2 1/2 ins. diam. 24 ins. in the ground, with brass cap mkd.

Subdivision of Section 14, T. 11 N., R. 2 E.

Chains



raise a mound of stone, 3 ft. base, 2 ft. high, N. of cor.

10.00 The SE-SW 1/64 sec. cor. of sec. 14.

17.70 Draw, course S.

19.998 The C-S-SW 1/64 sec. cor. of sec. 14.

Subdivision of the SE 1/4.

From the E 1/16 sec. cor. of sec. 14, on S. bdy. of the section.

N. 0° 03' E., on the N. and S. center line of the SE 1/4 of sec. 14.

10.226 Point for the C-S-SE 1/64 sec. cor. of sec. 14,

Set a wooden stake, 2 ft. long, 2 ins. sq., 12 ins. in the ground, marked for lots 49 and 62.

16.00 Old road, bears NW. and SE.

20.452 Point for the SE 1/16 sec. cor. of sec. 14, at the intersection of the E. and W. center line of the SE 1/4 of sec. 14.

Set an iron post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.

SE 1/16 S14

1952

raise a mound of stone, 3 ft. base, 2 ft. high, W. of cor.

25.567 Point for the C-S-N-SE 1/256 sec. cor. of sec. 14.

Set a wooden stake, 2 ft. long, 2 ins. sq., 12 ins. in the ground, marked for lots 47 and 48.

30.682 Point for the C-N-SE 1/64 sec. cor. of sec. 14.

Set a wooden stake, 2 ft. long, 2 ins. sq., 12 ins. in the ground, marked for lots 33 and 47.

35.797 Point for the C-N-N-SE 1/256 sec. cor. of sec. 14.

Set a wooden stake, 2 ft. long, 2 ins. sq., 12 ins. in the ground, marked for lots 32 and 33.

40.912 The C-E 1/16 sec. cor. of sec. 14.

From the S 1/16 sec. cor. of secs. 13 and 14.

N. 88° 49' W., on the E. and W. center line of the SE 1/4 of sec. 14.

20.016 The SE 1/16 sec. cor. of sec. 14.

25.02 Point for the C-E-W-SE 1/256 sec. cor. of sec. 14.

Set a wooden stake, 2 ft. long, 2 ins. sq., 12 ins. in the ground, marked for lots 48, 49, and 50.

Subdivision of Section 14, T. 11 N., R. 2 E.

Chains

30.025


Point for the C-W-SE 1/64 sec. cor. of sec. 14.

Set a wooden stake, 2 ft. long, 2 ins. sq., 12 ins. in the ground, marked for lots 46, 48, 50, and 51.

37.644

Intersect the E. bdy. of Highway right-of-way, point for the cor. of lots E, 46, and 51.

Set an iron post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.



raise a mound of stone, 3 ft. base, 2 ft. high, N. of cor.

40.033

The C-S 1/16 sec. cor. of sec. 14.

Subdivision of the NW 1/4 SE 1/4.

From the C-W-SE 1/64 sec. cor. of sec. 14.

N. 0° 02' E., on the N. and S. center line of the NW 1/4 SE 1/4 of sec. 14.

3.80

Wash, drains ESE.

5.112

Point for the C-S-NW-SE 1/256 sec. cor. of sec. 14.

Set a wooden stake, 2 ft. long, 2 ins. sq., 12 ins. in the ground, marked for lots 45, 46, 47, and 48.

10.224

Point for the NW-SE 1/64 sec. cor. of sec. 14, at the intersection of the E. and W. center line of the NW 1/4 SE 1/4 of sec. 14.

Set a wooden stake, 2 ft. long, 2 ins. sq., 12 ins. in the ground, marked for lots 33, 34, 45, and 47.

15.336

Point for the C-N-NW-SE 1/256 sec. cor. of sec. 14,

Set a wooden stake, 2 ft. long, 2 ins. sq., 12 ins. in the ground, marked for lots 33 and 34, on line of lot 32.

20.448

The C-W-E 1/64 sec. cor. of sec. 14.

From the C-N-SE 1/64 sec. cor. of sec. 14.

N. 88° 53' W., on the E. and W. center line of the NW 1/4 SE 1/4 of sec. 14.

8.40

Shallow wash, drains SE.

10.007

The NW-SE 1/64 sec. cor. of sec. 14.

15.58


Intersect the E. bdy of Highway right-of-way, point for the cor. of lots E, 34 and 45.

Set an iron post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.

DEED

Subdivision of Section 14, T. 11 N., R. 2 E.

Chains



Raise a mound of stone, 3 ft. base, 2 ft. high, N. of cor.

18.68 Center line of Black Canyon Highway, bears N. $11^{\circ} 33'$ E. and S. $11^{\circ} 33'$ W.

20.016 The C-N-S $1/64$ sec. cor. of sec. 14.

Subdivision of the SW $1/4$ SE $1/4$.

From the W-E $1/64$ sec. cor. of sec. 14.

N. $0^{\circ} 02'$ E., on the N. and S. center line of the SW $1/4$ SE $1/4$ of sec. 14.

5.111 Point for the C-S-SW-SE $1/256$ sec. cor. of sec. 14.

Set a wooden stake, 2 ft. long, 2 ins. sq., 12 ins. in the ground, marked for lots 59, 60, and 61.

10.222 Point for the SW-SE $1/64$ sec. cor. of sec. 14, at the intersection of the E. and W. center line of the SW $1/4$ SE $1/4$ of sec. 14.

Set a wooden stake, 2 ft. long, 2 ins. sq., 12 ins. in the ground, marked for lots 50, 52, 59, and 61.

15.332 Point for the C-N-SW-SE $1/256$ sec. cor. of sec. 14.

Set a wooden stake, 2 ft. long, 2 ins. sq., 12 ins. in the ground, marked for lots 50, 51, and 52.

20.442 The C-W-SE $1/64$ sec. cor. of sec. 14.

From the C-S-SE $1/64$ sec. cor. of sec. 14.

N. $88^{\circ} 47'$ W., on the E. and W. center line of the SW $1/4$ SE $1/4$ of sec. 14.


5.003 Point for the C-E-SW-SE $1/256$ sec. cor. of sec. 14.

Set a wooden stake, 2 ft. long, 2 ins. sq., 12 ins. in the ground, marked for lots 49, 50, 61, and 62.

10.007 The SW-SE $1/64$ sec. cor. of sec. 14.

19.674 Intersect the E. bdy. of Highway right-of-way, point for the cor. of lots E, 52, and 59.

Set an iron post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 24 ins. in the ground, with brass cap mkd.



raise a mound of stone, 3 ft. base, 2 ft. high, N. of cor.

20.002 The C-S-S $1/64$ sec. cor. of sec. 14.

Subdivision of Section 23, T. 11 N., R. 2 E.

Chains	
	From the $\frac{1}{4}$ sec. cor. of secs. 23 and 26. N. $0^{\circ} 03'$ E., on the N. and S. center line of sec. 23. Over rolling land, through scattering undergrowth.
38.95	Wash, 15 lks. wide, 6 ft. deep, drains E.
40.01	Point for the C $\frac{1}{4}$ sec. cor. of sec. 23, at the intersection of the E. and W. center line of sec. 23. Set an iron post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 24 ins. in the ground, with brass cap mkd. C $\frac{1}{4}$ S23 1952 raise a mound of stone, 3 ft. base, 2 ft. high, W. of cor.
44.50	Big Bug Creek, 20 lks. wide, course E.
45.007	Point for the C-S-S-N $1/256$ sec. cor. of sec. 23. Set a wooden stake, 2 ft. long, 2 ins. sq., 12 ins. in the ground, marked for lots 21 and 22.
50.004	Point for the C-S-N $1/64$ sec. cor. of sec. 23. Set a wooden stake, 2 ft. long, 2 ins. sq., 12 ins. in the ground, marked for lots 19 and 21.
55.001	Point for the C-N-S-N $1/256$ sec. cor. of sec. 23. Set a wooden stake, 2 ft. long, 2 ins. sq., 12 ins. in the ground, marked for lots 18 and 19.
59.998	Point for the C-N $1/16$ sec. cor. of sec. 23. Set an iron post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 24 ins. in the ground, with brass cap mkd. C N $1/16$ S23 C 1952 raise a mound of stone, 3 ft. base, 2 ft. high, W. of cor.
64.995	Point for the C-S-N-N $1/256$ sec. cor. of sec. 23. Set a wooden stake, 2 ft. long, 2 ins. sq., 12 ins. in the ground, marked for lots 14, 15, 16, and 17.
69.992	Point for the C-N-N $1/64$ sec. cor. of sec. 23. Set a wooden stake, 2 ft. long, 2 ins. sq., 12 ins. in the ground, marked for lots 7, 8, 14, and 16.
74.989	Point for the C-N-N-N $1/256$ sec. cor. of sec. 23. Set a wooden stake, 2 ft. long, 2 ins. sq., 12 ins. in the ground, marked for lots 6, 7, and 8.
79.986	Point on line bet. lots 5 and 6, sec. 23.
82.585	The $\frac{1}{4}$ sec. cor. of sec. 23, on S. bdy. of sec. 14.

Subdivision of Section 23, T. 11 N. R. 2 E.

Chains	From the $\frac{1}{4}$ sec. cor. of secs. 23 and 24. N. 89° 54' W., on the E. and W. center line of sec. 23. Over rolling land, through scattering undergrowth.
12.10	Old road, bears NW. and SE.
20.031	Point for the C-E $\frac{1}{16}$ sec. cor. of sec. 23. Set an iron post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 24 ins. in the ground, with brass cap mkd. $C \frac{E \frac{1}{16}}{S \frac{1}{23}} C$ 1952 raise a mound of stone, 3 ft. base, 2 ft. high, N. of cor.
22.05	Big Bug Creek, .20 lks. wide, course SE.
40.062	The C $\frac{1}{4}$ sec. cor. of sec. 23. Thence over rolling and broken land.
50.078	Point for the C-E-W $\frac{1}{64}$ sec. cor. of sec. 23. Set a wooden stake, 2 ft. long, 2 ins. sq., 12 ins. in the ground, marked C-E-W $\frac{1}{64}$
52.159	Intersect the E. bdy. of Highway right-of-way, point for the cor. of lots A and 22. Set an iron post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 24 ins. in the ground, with brass cap mkd. $\begin{array}{c} \text{LOT} \\ \text{A} \end{array} / \begin{array}{c} \text{LOT} \\ 22 \\ S23 \end{array}$ 1952 raise a mound of stone, 3 ft. base, 2 ft. high, N. of cor.
55.249	Black Canyon Highway, bears N. 11° 33' E. and S. 11° 33' W.
58.339	Intersect the W. bdy. of Highway right-of-way, point for the cor. of Lots A and 20. Set an iron post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 24 ins. in the ground, with brass cap mkd. $\begin{array}{c} \text{LOT} \\ 20 \\ S23 \end{array} / \begin{array}{c} \text{Lot} \\ A \end{array}$ 1952 raise a mound of stone, 3 ft. base, 2ft. high, N. of cor.
60.095	Point for the C-W $\frac{1}{16}$ sec. cor. of sec. 23. Set an iron post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 24 ins. in the ground, with brass cap mkd. $C \frac{W \frac{1}{16}}{S \frac{1}{23}} C$ 1952
60.10	Old road, bears NW. and SE.
67.40	Same road, bears NE. and SW.
80.128	The $\frac{1}{4}$ sec. cor. of secs. 22 and 23.

Subdivision of Section 23, T. 11 N., R. 2 E.


Chains	Subdivision of the NE $\frac{1}{4}$.
	From the C-E 1/16 sec. cor. of sec. 23. N. 0° 03' E., on the N. and S. center line of the NE $\frac{1}{4}$ of sec. 23.
14.60	Old road, bears NW. and SE.
19.987	Point for the NE 1/16 sec. cor. of sec. 23, at the intersection of the E. and W. center line of the NE $\frac{1}{4}$ of sec. 23. Set an iron post, 28 ins. long, 2 $\frac{1}{2}$ ins. diam., 24 ins. in the ground, with brass cap mkd.
	NE 1/16 S 23 1952
	raise a mound of stone, 3 ft. base, 2 ft. high, W. of cor.
29.977	Point for the C-N-NE 1/64 sec. cor. of sec. 23. Set a wooden stake, 2 ft. long, 2 ins. sq., 12 ins. in the ground, marked C-N-NE 1/64.
42.176	The E 1/16 sec. cor. of sec. 23, on the S. bdy. of sec. 14. From the N 1/16 sec. cor. of secs. 23 and 24. N. 89° 54' W., on the E. and W. center line of the NE $\frac{1}{4}$ of sec. 23.
20.036	The NE 1/16 sec. cor. of sec. 23.
22.50	Old road, bears NW. and SE.
30.054	Point for the C-W-NE 1/64 sec. cor. of sec. 23. Set a wooden stake, 2 ft. long, 2 ins. sq., 12 ins. in the ground, marked for lot 17.
31.65	Wash, 10 lks. wide, 4 ft. deep, drains S. 10° W.
40.072	The C-N 1/16 sec. cor. of sec. 23.
	Subdivision of the NW $\frac{1}{4}$ NE $\frac{1}{4}$.
	From the C-W-NE 1/64 sec. cor. of sec. 23. N. 0° 03' E., on the N. and S. center line of the NW $\frac{1}{4}$ NE $\frac{1}{4}$ of sec. 23.
4.996	Point for the C-S-NW-NE 1/256 sec. cor. of sec. 23. Set a wooden stake, 2 ft. long, 2 ins. sq., 12 ins. in the ground, marked for lots 16 and 17.
9.993	Point for the NW-NE 1/64 sec. cor. of sec. 23, at the intersection of the E. and W. center line of the NW $\frac{1}{4}$ NE $\frac{1}{4}$ of sec. 23. Set a wooden stake, 2 ft. long, 2 ins. sq., 12 ins. in the ground, marked for lots 7 and 16.
11.60	Road, bears NW. and SE.
14.991	Point for the C-N-NW-NE 1/256 sec. cor. of sec. 23. Set a wooden stake, 2 ft. long, 2 ins. sq., 12 ins. in the ground, marked for lots 6 and 7.
19.989	Point for the cor. of lots 5 and 6

Subdivision of Section 23, T. 11 N. R. 2 E.

Chains	Set a wooden stake, 2 ft. long, 2 ins. sq., 12 ins. in the ground, marked for lots 5 and 6.
22.388	The W-E 1/64 sec. cor. of sec. 23 on the S. bdy. of sec. 14.
	From the C-N-NE 1/64 sec. cor. of sec. 23.
	N. 89° 53' W., on the E. and W. center line of the NW 1/4 NE 1/4 of sec. 23.
10.021	The NW-NE 1/64 sec. cor. of sec. 23.
16.80	Old road, bears N. and S.
20.041	The C-N-N 1/64 sec. cor. of sec. 23.
Subdivision of the NW 1/4.	
	From the C-W 1/16 sec. cor. of sec. 23.
	N. 0° 03' E., on the N. and S. center line of the NW 1/4 of sec. 23.
10.001	Point for the C-S-NW 1/64 sec. cor. of sec. 23.
	Set a wooden stake, 2 ft. long, 2 ins. sq., 12 ins. in the ground, marked C-S-NW 1/64.
20.002	Point for the NW 1/16 sec. cor. of sec. 23, at the intersection of the E. and W. center line of the NW 1/4 of sec. 23.
	Set an iron post, 28 ins. long, 2 1/2 ins. diam., 12 ins. in the ground to bedrock, and in a mound of stone to top, with brass cap mkd.
	NW 1/16 S23 1952
24.00	Big Bug Creek, 20 lks. wide, course SE.
24.997	Point for the C-S-N-NW 1/256 sec. cor. of sec. 23.
	Set a wooden stake, 2 ft. long, 2 ins. sq., 12 ins. in the ground, marked for lots 12 and 13.
29.992	Point for the C-N-NW 1/64 sec. cor. of sec. 23.
	Set a wooden stake, 2 ft. long, 2 ins. sq., 12 ins. in the ground, marked for lots 11 and 12.
34.988	Point for the C-N-N-NW 1/256 sec. cor. of sec. 23.
	Set a wooden stake, 2 ft. long, 2 ins. sq., 12 ins. in the ground, marked for lots 10 and 11.
39.984	Point for the cor. of lots 9 and 10.
	Set a wooden stake, 2 ft. long, 2 ins. sq., 12 ins. in the ground, marked for lots 9 and 10.
42.991	The W 1/16 sec. cor. of sec. 23 on the S. bdy. of sec. 14.
	From the C-N 1/16 sec. cor. of sec. 23.
	N. 89° 52' W., on the E. and W. center line of the NW 1/4 of sec. 23.
8.024	Intersect the E. bdy. of Highway right-of-way, point for the cor. of lots 15 and 18 on line of lot A.
	Set an iron post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.
	1952
	raise a mound of stone, 3 ft. base, 2 ft. high, N. of cor.

Subdivision of Section 23, T. 11 N. R. 2 E.

- Chains
- 10.02 Point for the C-E-NW 1/64 sec. cor. of sec. 23.
Set a wooden stake, 2 ft. long, 2 ins. sq., 12 ins. in the ground, marked C-E-NW 1/64.
- 11.10 Black Canyon Highway, bears N. 11° 33' E. and S. 11° 33' W.
- 14.204 Intersect the W. bdy. of Highway right-of-way, point for the cor. of lots 13 and 20, on line of lot A.
Set an iron post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.




raise a mound of stone, 3 ft. base, 2 ft. high, N. of cor.

- 18.10 Big Bug Creek, 20 lks. wide, course SE.
- 20.04 The NW 1/16 sec. cor. of sec. 23.
- 28.70 Draw, course ENE.
- 40.078 The N 1/16 sec. cor. of secs. 22 and 23.

Subdivision of the NE 1/4 NW 1/4.

- From the C-E-NW 1/64 sec. cor. of sec. 23.
- N. 0° 03' E., on the N. and S. center line of the NE 1/4 NW 1/4 of sec. 23.
- 5.00 Black Canyon Highway, bears N. 11° 33' E. and S. 11° 33' W.
- 9.992 Point for the NE-NW 1/64 sec. cor. of sec. 23, at the intersection of the E. and W. center line of the NE 1/4 NW 1/4 of sec. 23.
Set a wooden stake, 2 ft. long, 2 ins. sq., 12 ins. in the ground, marked NE-NW 1/64.
- 22.79 The E-W 1/64 sec. cor. of sec. 23 on the S. bdy. of sec. 14.
From the C-N-N 1/64 sec. cor. of sec. 23.
N. 89° 53' W., on the E. and W. center line of the NE 1/4 NW 1/4 of sec. 23.
- 5.993 Intersect the E. bdy. of Highway right-of-way, point for the cor. of lots 8 and 14 on line of lot A.
Set an iron post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.



- 7.20 Shallow wash, drains S.
- 9.08 Black Canyon Highway, bears N. 11° 33' E. and S. 11° 33' W.

Subdivision of Section 23, T. 11 N., R. 2 E.

Chains	
10.02	The NE-NW 1/64 sec. cor. of sec. 23.
12.171	Intersect the W. bdy. of Highway right-of-way, point for the cor. of lots 11 and 12, on line of lot A. Set an iron post, 28 ins. long, 2 $\frac{1}{2}$ ins. diam., 24 ins. in the ground, with brass cap mkd. <div style="text-align: center;"> <p>LOT 11 / LOT A LOT 12 / S23 1952</p> </div>
20.04	raise a mound of stone, 3 ft. base, 2 ft. high, N. of cor. The C-N-NW 1/64 sec. cor. of sec. 23.
Subdivision of the SE $\frac{1}{4}$ NW $\frac{1}{4}$.	
	From the C-E-W 1/64 sec. cor. of sec. 23. N. 0° 03' E., on the N. and S. center line of the SE $\frac{1}{4}$ NW $\frac{1}{4}$ of sec. 23.
4.998	Point for the C-S-SE-NW 1/256 sec. cor. of sec. 23. Set a wooden stake, 2 ft. long, 2 ins. sq., 12 ins. in the ground, on line bet. lots 21 and 22, marked C-S-SE-NW 1/256.
9.996	Point for the SE-NW 1/64 sec. cor. of sec. 23, at the intersection of the E. and W. center line of the SE $\frac{1}{4}$ NW $\frac{1}{4}$ of sec. 23. Set a wooden stake, 2 ft. long, 2 ins. sq., 12 ins. in the ground, marked SE-NW 1/64.
10.257	Intersect the E. bdy. of Highway right-of-way. Set an iron post, 28 ins. long, 2 $\frac{1}{2}$ ins. diam., 20 ins. in the ground, with brass cap mkd. <div style="text-align: center;"> <p>LOT 19 / LOT A S23 1952</p> </div>
	raise a mound of stone, 3 ft. base, 2 ft. high, W. of cor.
12.26	Big Bug Creek, 15 lks. wide, course SE.
19.989	The C-E-NW 1/64 sec. cor. of sec. 23. From the C-S-N 1/64 sec. cor. of sec. 23. N. 89° 53' W., on the E. and W. center line of the SE $\frac{1}{4}$ NW $\frac{1}{4}$ of sec. 23.
7.15	Big Bug Creek, 15 lks. wide, course SE.
10.02	The SE-NW 1/64 sec. cor. of sec. 23.
10.06	Intersect the E. bdy. of Highway right-of-way, point for the cor. of lots 19 and 21, on line of lot A. Set an iron post, 28 ins. long, 2 $\frac{1}{2}$ ins. diam., 24 ins. in the ground, with brass cap mkd. <div style="text-align: center;"> <p>LOT 19 / LOT A LOT 21 1952</p> </div>

Subdivision of Section 23, T. 11 N., R. 2 E.

Chains

13.15 Black Canyon Highway, bears N. 11° 33' E. and S. 11° 33' W.

16.24 Intersect the W. bdy. of Highway right-of-way.

Set an iron post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.

LOT / LOT
20 / A
S23 /
1952

1
raise a mound of stone, 3 ft. base, 2 ft. high, N. of cor.

17.40 Draw, course NE.

20.035 The C-S-NW 1/64 sec. cor. of sec. 23.

General Description

The surface of sections 14 and 23 is for the most part rolling hills, the average elevation is approximately 3800 ft. above sea level. The soil is a rocky clay. The general direction of the drainage is to the east and southeast through a number of washes and Big Bug Creek. The newly constructed Black Canyon Highway enters section 23 on the south boundary of the SW 1/4 and leaves section 14 on the north boundary of the NW 1/4 NE 1/4. There is a highway maintenance shop and other buildings located near the center of section 14.

UNITED STATES
DEPARTMENT OF THE INTERIOR
BUREAU OF LAND MANAGEMENT

FIELD ASSISTANTS

NAMES	CAPACITY
Fred R. Chappell	Cartographic Survey Aid
Paul O. Heath	Surveying and Cartographic Aid
O. Charles Harper	" "
Abenecio Crespín	" "
Decederio Baca	" "
Fernando D. Chavez	" "

35

CERTIFICATE OF CADASTRAL ENGINEER

I, Clarence E. Bilbray, HEREBY CERTIFY upon honor that, in pursuance of special instructions bearing date of the 9th day of March, 1951, I have ~~surveyed~~ independently resurveyed portions of the north and east boundaries and subdivision, and surveyed the subdivision of sections 14 and 23 of T. 11 N., R. 2 E.

of the Gila & Salt River Meridian, in the State of Arizona, which are represented in the foregoing field notes as having been executed by me and under my direction; and that said survey has been made in strict conformity with said instructions, the Manual of Instructions for the Survey of the Public Lands of the United States, and in the specific manner described in the foregoing field notes.

Albuquerque, New Mexico
November 3, 1953

Clarence E. Bilbray
Clarence E. Bilbray
Cadastral Engineer

CERTIFICATE OF APPROVAL

BUREAU OF LAND MANAGEMENT,
Washington, D. C., APR 15 1954, 19

The foregoing field notes of the ~~survey of~~ resurvey of portions of the north and east boundaries and subdivision, and survey of subdivision of sections 14 and 23 of T. 11 N., R. 2 E., of the Gila and Salt River Meridian, Arizona

executed by Clarence E. Bilbray having been critically examined and found correct, are hereby approved.

Ronald B. Cement
Assistant Chief, Branch of Engineering and Construction.

~~CERTIFICATE OF TRANSCRIPT~~

~~I CERTIFY that the foregoing transcript of the field notes of the above described surveys in~~
~~is a true copy of the original field notes.~~

~~Chief, Branch of Engineering and Construction.~~