

4440

ORIGINAL

4440

(1) index

4-879  
(September 1948)

UNITED STATES  
DEPARTMENT OF THE INTERIOR  
BUREAU OF LAND MANAGEMENT

BOOK 4440

# FIELD NOTES

Of the Dependent Resurvey of

The West Boundary of Township 6 North, Range 17 West

and

Of the Survey

Of the West and North Boundaries and Subdivisional Lines of

Township 6 North, Range 18 West

Of the Gila and Salt River Meridian,

In the State of Arizona

EXECUTED BY

Ty White, Cadastral Engineer

Under special instructions dated October 9, 1952, which provided  
for the surveys included under Group No. 285, approved October 21, 1952  
and assignment instructions dated November 7, 1952.

Survey commenced December 31, 1952.

Survey completed February 4, 1953.

4440

4440

1A

BOOK 4440

# INDEX DIAGRAM

Township 6 North, Range 18 West

|            |             |             |             |             |               |
|------------|-------------|-------------|-------------|-------------|---------------|
| 16         | 15          | 14          | 13          | 12          | 11            |
| 4 6<br>55  | 55 5<br>55  | 47 4<br>47  | 41 3<br>40  | 33 2<br>33  | 25 1 10<br>24 |
| 3 7<br>53  | 54 8<br>53  | 46 9<br>46  | 39 10<br>39 | 32 11<br>31 | 23 12 9<br>23 |
| 3 18<br>52 | 52 17<br>51 | 45 16<br>45 | 38 15<br>38 | 30 14<br>30 | 22 13 8<br>21 |
| 2 19<br>51 | 51 20<br>50 | 44 21<br>43 | 37 22<br>36 | 29 23<br>28 | 20 24 7<br>19 |
| 2 30<br>49 | 49 29<br>49 | 43 28<br>42 | 36 27<br>35 | 27 26<br>27 | 18 25 6<br>18 |
| 1 31       | 48 32       | 42 33       | 34 34       | 26 35       | 17 36 5       |

## Chains

The west boundary of T. 6 N., R. 17 W. was surveyed by Otis O. Gould, U. S. Transitman, in 1927. The following field notes describe the dependent resurvey of this boundary and the survey of the north and west boundaries and subdivisional lines of T. 6 N., R. 18 W.

The survey was executed with light mountain solar transits made by Buff and Buff, serial No. 16724 and W. and L. E. Gurley, serial No. 461263, constructed in accordance with the standard instrumental specifications of the Bureau of Land Management. The instruments were in good condition and having been placed in satisfactory adjustment prior to the beginning of the survey, were tested and found free from appreciable error.

The direction of the lines were determined by the solar transit method. The measurements were made with Lufkin steel tapes, 5 chains in length, graduated to tenths of a link for the first 10 links, every link for the balance of the first 100 links and the remainder at intervals of 10 links. The tapes were tested by comparison with a standard steel tape and found correct. The measurements were made on the slope and the vertical angle of each interval was ascertained by a clinometer in good adjustment; the horizontal equivalents only are entered in this field note record. Lines connecting previously established corners are run by the random and true method but the random lines are omitted from the field notes.

The data furnished with the special instructions give the geographic position of the southeast corner of the township as latitude  $33^{\circ} 48' 37''$  N. and longitude  $114^{\circ} 04' 32''$  W.

January 23, 1953, at camp in the SE.  $\frac{1}{4}$  of sec. 15, T. 6 N., R. 19 W., G. and S. R. Mer., Ariz., in approximate latitude  $33^{\circ} 51' 18''$  N. and longitude  $114^{\circ} 13' 12''$  W., elevation approximately 870 ft. I make an hour angle observation on Polaris east of the meridian for azimuth and latitude, making four observations, two each with the telescope in direct and reversed positions, observing simultaneously the vertical angle to Polaris and the horizontal angle from the west edge of a needle peak, approximately 40 miles N., east to Polaris. My watch reads correct Mountain Standard Time as checked with radio time signals.

|                                  |                            |
|----------------------------------|----------------------------|
| Mean watch time of observation   | 5h 30m 06s p.m.            |
| Watch fast of l.m.t.             | 0h 36m 54s                 |
| Mean horizontal deflection angle | $4^{\circ} 18' 12''$       |
| Azimuth of Polaris               | $0^{\circ} 13' 36''$       |
| Bearing of reference point       | N. $4^{\circ} 04' 36''$ W. |
| Observed vertical angle          | $34^{\circ} 48' 16''$      |
| Reduced latitude                 | $33^{\circ} 51' 14''$ N.   |

January 24, 1953, every 30m. from 8 to 10:30 a.m. and from 1:30 to 4 p.m. we make the proper settings on the arcs of the solar attachments and ascertain that the resulting orientation of the instruments, when compared with the meridian established by Polaris observation, have a maximum error of less than  $1' 30''$ .

Mean observed magnetic declination is  $14\frac{1}{2}^{\circ}$  E.

## West Boundary of T. 6 N., R. 18 W.

From the cor. of Tps. 5 and 6 N., Rs. 18 and 19 W.

NORTH, bet. secs. 31 and 36.


Over rolling land, through scattering timber and undergrowth.

40.00 Point for the  $\frac{1}{4}$  sec. cor. of secs. 31 and 36.

Set an iron post, 28 ins. long,  $2\frac{1}{2}$  ins. diam., 24 ins. in the ground with brass cap mkd.

West Boundary of T. 6 N., R. 18 W.


Chains



Deposit a broken glass bottle alongside the iron post.

80.00 Point for the cor. of secs. 25, 30, 31 and 36.

Set an iron post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground with brass cap mkd.



Deposit a broken glass bottle alongside the iron post.


Land, rolling.  
Soil, sandy loam.  
Timber, palo verde and ironwood; undergrowth, greasewood.

NORTH, bet. secs. 25 and 30.

Over rolling land, through scattering timber and undergrowth.

40.00 Point for the ¼ sec. cor. of secs. 25 and 30.

Set an iron post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground with brass cap mkd.




Deposit a broken glass bottle alongside the iron post.

70.00 Sand ridge, bears NE. and SW.

80.00 Point for the cor. of secs. 19, 24, 25 and 30.

Set an iron post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground with brass cap mkd.



Deposit a broken glass bottle alongside the iron post.

Land, rolling.  
Soil, sandy.  
Timber, ironwood and palo verde; undergrowth, greasewood.

NORTH, bet. secs. 19 and 24.

Over rolling land, through scattering timber and undergrowth.

40.00 Point for the ¼ sec. cor. of secs. 19 and 24.

## Chains

Set an iron post, 28 ins. long,  $2\frac{1}{2}$  ins. diam., 24 ins. in the ground with brass cap mkd.

$$\begin{array}{c} \frac{1}{4} \\ \text{S 24} \mid \text{S 19} \\ 1953 \end{array}$$

Deposit a broken glass bottle alongside the iron post.

80.00 Point for the cor. of secs. 13, 18, 19 and 24.

Set an iron post, 28 ins. long,  $2\frac{1}{2}$  ins. diam., 24 ins. in the ground with brass cap mkd.

$$\begin{array}{c} \text{T 6 N} \\ \text{R 19 W} \mid \text{R 18 W} \\ \text{S 13} \mid \text{S 18} \\ \hline \text{S 24} \mid \text{S 19} \\ 1953 \end{array}$$

Deposit a broken glass bottle alongside the iron post.

Land, rolling.

Soil, sandy.

Timber, palo verde and ironwood; undergrowth, greasewood.

NORTH, bet. secs. 13 and 18.

Over rolling land, through scattering timber and undergrowth.

40.00 Point for the  $\frac{1}{4}$  sec. cor. of secs. 13 and 18.

Set an iron post, 28 ins. long,  $2\frac{1}{2}$  ins. diam., 24 ins. in the ground with brass cap mkd.

$$\begin{array}{c} \frac{1}{4} \\ \text{S 13} \mid \text{S 18} \\ 1953 \end{array}$$

Deposit a broken glass bottle alongside the iron post.

80.00 Point for the cor. of secs. 7, 12, 13 and 18.

Set an iron post, 28 ins. long,  $2\frac{1}{2}$  ins. diam., 24 ins. in the ground with brass cap mkd.

$$\begin{array}{c} \text{T 6 N} \\ \text{R 19 W} \mid \text{R 18 W} \\ \text{S 12} \mid \text{S 7} \\ \hline \text{S 13} \mid \text{S 18} \\ 1953 \end{array}$$

Deposit a broken glass bottle alongside the iron post.

Land, rolling.

Soil, sandy.

Timber, palo verde and ironwood; undergrowth, greasewood.

NORTH, bet. secs. 7 and 12.

Over rolling land, through scattering timber and undergrowth.

West Boundary of T. 6 N., R. 18 W.

Chains  
40.00Point for the  $\frac{1}{4}$  sec. cor. of secs. 7 and 12.Set an iron post, 28 ins. long,  $2\frac{1}{2}$  ins. diam., 24 ins. in the ground with brass cap mkd.
$$\begin{array}{c} \frac{1}{4} \\ \text{S } 12 \mid \text{S } 7 \\ 1953 \end{array}$$

Deposit a broken glass bottle alongside the iron post.

80.00 Point for the cor. of secs. 1, 6, 7 and 12.

Set an iron post, 28 ins. long,  $2\frac{1}{2}$  ins. diam., 24 ins. in the ground with brass cap mkd.
$$\begin{array}{c} \text{T } 6 \text{ N} \\ \text{R } 19 \text{ W} \mid \text{R } 18 \text{ W} \\ \text{S } 1 \mid \text{S } 6 \\ \hline \text{S } 12 \mid \text{S } 7 \\ 1953 \end{array}$$

Deposit a broken glass bottle alongside the iron post.

Land, rolling.

Soil sandy.

Timber, palo verde and ironwood; undergrowth, greasewood.

NORTH, bet. secs. 1 and 6.

Over rolling land, through scattering timber and undergrowth.

40.00 Point for the  $\frac{1}{4}$  sec. cor. of secs. 1 and 6.Set an iron post, 28 ins. long,  $2\frac{1}{2}$  ins. diam., 24 ins. in the ground with brass cap mkd.
$$\begin{array}{c} \frac{1}{4} \\ \text{S } 1 \mid \text{S } 6 \\ 1953 \end{array}$$

Deposit a broken glass bottle alongside the iron post.

60.00 Point for the N  $\frac{1}{16}$  sec. cor. of secs. 1 and 6.Set an iron post, 28 ins. long,  $2\frac{1}{2}$  ins. diam., 24 ins. in the ground with brass cap mkd.
$$\begin{array}{c} \text{N } 1/16 \\ \text{S } 1 \mid \text{S } 6 \\ 1953 \end{array}$$

Deposit a broken glass bottle alongside the iron post.

80.00 Point for the  $\frac{1}{16}$  sec. cor. of secs. 1 and 6.Set an iron post, 28 ins. long,  $2\frac{1}{2}$  ins. diam., 24 ins. in the ground with brass cap mkd.
$$\begin{array}{c} 1/16 \\ \text{S } 1 \mid \text{S } 6 \\ 80 \\ 1953 \end{array}$$

Deposit a broken glass bottle alongside the iron post.

## West Boundary of T. 6 N., R. 18 W.

Chains  
88.46

Point for the cor. of Tps. 6 and 7 N., Rs. 18 and 19 W.

Set an iron post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground with brass cap mkd.

|        |        |  |
|--------|--------|--|
|        | T 7 N. |  |
| R 19 W | R 18 W |  |
| S 36   | S 31   |  |
| — —    |        |  |
| S 1    | S 6    |  |
|        | T 6 N. |  |
|        | 1953   |  |

Deposit a broken glass bottle alongside the iron post.

Land, rolling.

Soil, sandy.

Timber, palo verde and ironwood; undergrowth, greasewood.

Dependent Resurvey, W. Bdy. T. 6 N., R. 17 W.

Amendment of the survey as executed by Otis O. Gould, U. S. Transitman, in 1927 in which the corners along this line were marked as corners of maximum control. The function of these corners is changed to refer to the sections of T. 6 N., R. 17 W. only and the following alterations are made in the corner monuments.

Beginning the resurvey at the cor. of Tps. 5 and 6 N., R. 17 W., from which the cor. of Tps. 5 and 6 N., R. 18 W., bears S. 0° 02' E., 7.88 chs. dist.

N. 0° 01' W., along the W. bdy. of sec. 31.

Over broken land, through scattering timber and undergrowth.

3.00 State Highway No. 95, bears N. 85° E. and S. 85° W.

4.00 Wash, 40 lks. wide, course N. 40° E.; asc. 48 ft. over SE. slope.

14.30 Spur, slopes N. 70° E.; desc. 40 ft. over NW. slope.

32.17 Point for the ¼ sec. cor. of sec. 36, of R. 18 W.

Set an iron post, 28 ins. long, 2½ ins. diam., 12 ins. in the ground to solid rock and in a mound of stone to top, with brass cap mkd.

|        |  |
|--------|--|
| ¼ S 36 |  |
| 1953   |  |

40.12 The ¼ sec. cor. of secs. 31 and 36, monumented with an iron post, 1 in. diam., firmly set, mkd. and witnessed as described in the official record. Change the markings on the brass cap to read.

|      |        |
|------|--------|
|      | ¼ S 31 |
| 1927 |        |


N. 0° 02' E., beginning new measurement.

5.35 Wash, 30 lks. wide, course N. 60° E.

Dependent Resurvey, W. Bdy. T. 6 N., R. 17 W.


Chains

- 31.05 Wash, 30 lks. wide, course NE.
- 32.05 Point for the cor. of secs, 25 and 36 of R. 18 W.  
Set an iron post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground with brass cap mkd.



Raise a mound of stone, 3 ft. base, 2½ ft. high, W. of cor.

- 39.86 The cor. of secs. 25, 30, 31 and 36, monumented by an iron post, 2 ins. diam., firmly set, mkd. and witnessed as described in the official record. Change the markings on the brass cap to read.




Rebuild mound of stone, 3 ft. base, 2½ ft. high, E. of cor.

Land, broken.  
Soil, rocky and gravelly.  
Timber, palo verde and ironwood; undergrowth, greasewood.

N. 0° 04' E., along the W. bdy. 68 sec. 30.


Over broken land, through scattering timber and undergrowth.

- 9.90 Wash, 50 lks. wide, course NE.
- 10.80 Old road, bears NE. and SW.
- 31.20 Old road, bears SE. and NW.
- 32.19 Point for the ¼ sec. cor. of sec. 25 of R. 18 W.  
Set an iron post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground with brass cap mkd.



Raise a mound of stone, 3 ft. base, 2½ ft. high, W. of cor.

- 39.99 The ¼ sec. cor. of secs, 25 and 30, monumented by an iron post, 1 in. diam., firmly set, mkd. and witnessed as described in the official record. Change the markings on brass cap to read.



Rebuild the mound of stone, 3 ft. base, 2½ ft. high, E. of cor.

N. 0° 03' W., beginning new measurement.

Chains

- 1.40 Spur, slopes E.; desc. 93 ft. over N. slope.
- 11.20 Wash, 30 lks. wide, course NE.
- 29.20 Wash, 40 lks. wide, course NE.
- 32.20 Point for the cor. of secs. 24 and 25 of R. 18 W.
- Set an iron post, 28 ins. long,  $2\frac{1}{2}$  ins. diam., 24 ins. in the ground with brass cap mkd.

|        |        |
|--------|--------|
| T 6 N  | T 6 N  |
| S 24   | R 17 W |
| S 25   | S 30   |
| R 18 W | 1953   |

Raise a mound of stone, 3 ft. base,  $2\frac{1}{2}$  ft. high, W. of cor.

- 40.08 The cor. of secs. 19, 24, 25 and 30, monumented by an iron post, 2 ins. diam., firmly set, mkd. and witnessed as described in the official record. Change the markings on brass cap to read.

|         |       |
|---------|-------|
| T 6 N   | T 6 N |
| R 18 W  | S 19  |
| S 24    | S 30  |
| R 17 W. | 1927  |

Rebuild the mound of stone, 3 ft. base,  $2\frac{1}{2}$  ft. high, E. of cor.

Land, broken.

Soil, rocky.

Timber, ironwood and palo verde ; undergrowth, greasewood.

N.  $0^{\circ} 03'$  E., along the W. bdy. of sec. 19.

Over broken land, through scattering timber and undergrowth.

Ascend 80 ft. over SE. slope.

- 18.80 Spur, slopes N.  $70^{\circ}$  E.; desc. 50 ft. over NW. slope.

- 32.12 Point for the  $\frac{1}{4}$  sec. cor. of sec. 24 of R. 18 W.

Set an iron post, 28 ins. long,  $2\frac{1}{2}$  ins. diam., 24 ins. in the ground with brass cap mkd.

|                    |   |
|--------------------|---|
| $\frac{1}{4}$ S 24 | . |
| 1953               |   |

Raise a mound of stone, 3 ft. base,  $2\frac{1}{2}$  ft. high, W. of cor.

- 39.95 The  $\frac{1}{4}$  sec. cor. of secs. 19 and 24, monumented by an iron post, 1 in. diam., firmly set, mkd. and witnessed as described in the official record. Change the markings on brass cap to read.

|                    |  |
|--------------------|--|
| $\frac{1}{4}$ S 19 |  |
| 1927               |  |

N.  $0^{\circ} 01'$  W., beginning new measurement.

- 2.15 Wash, 20 lks. wide, course NE.

## Dependent Resurvey, W. Bdy. T. 6 N., R. 17 W.

- Chains
- 22.15 Wash, 20 lks. wide, course NE.
- 29.15 Road, bears E. and W.
- 32.17 Point for the cor. of secs. 13 and 24 of R. 18 W.
- Set an iron post, 28 ins. long,  $2\frac{1}{2}$  ins. diam., 24 ins. in the ground with brass cap mkd.
- |        |        |
|--------|--------|
| T 6 N  | T 6 N  |
| S 13   |        |
| <hr/>  |        |
| S 24   | R 17 W |
| R 18 W | S 19   |
| 1953   |        |
- Raise a mound of stone, 3 ft. base,  $2\frac{1}{2}$  ft. high, W. of cor.
- 35.35 Wash, 65 lks. wide, course N.  $40^\circ$  E.
- 38.35 Road, bears SW. to old mine and NE. to Bouse-Quartzsite road.
- 40.32 The cor. of secs. 13, 18, 19 and 24, monumented by an iron post, 2 ins. diam., firmly set, mkd. and witnessed as described in the official record. Change the markings on brass cap to read.
- |        |        |
|--------|--------|
| T 6 N  | T 6 N  |
| S 18   |        |
| R 18 W | <hr/>  |
| S 19   | R 17 W |
| S 13   |        |
| 1927   |        |
- Rebuild the mound of stone, 3 ft. base,  $2\frac{1}{2}$  ft. high, E. of cor.
- Land, broken;  
Soil, rocky.  
Timber, palo verde and ironwood; undergrowth, greasewood.
- 
- N.  $0^\circ 02'$  E., along the W. bdy. of sec. 18.
- Over broken land, through scattering timber and undergrowth.
- 10.85 Wash, 50 lks. wide, course N.  $60^\circ$  E.
- 24.35 Begin ascent of 113 ft. over SE. slope.
- 31.85 Point for the  $\frac{1}{4}$  sec. cor. of sec. 13 of R. 18 W.
- Set an iron post, 28 ins. long,  $2\frac{1}{2}$  ins. diam., 24 ins. in the ground with brass cap mkd.
- |                    |  |
|--------------------|--|
| $\frac{1}{4}$ S 13 |  |
| 1953               |  |
- Raise a mound of stone 3 ft. base,  $2\frac{1}{2}$  ft. high, W. of cor.
- 33.43 Road, bears E. and W.
- 39.69 The  $\frac{1}{4}$  sec. cor. of secs. 13 and 18, monumented by an iron post, 1 in. diam., firmly set, mkd. and witnessed as described in the official record. Change the markings on the brass cap to read.
- |                    |  |
|--------------------|--|
| $\frac{1}{4}$ S 18 |  |
| 1927               |  |

## Dependent Resurvey, W. Bdy. T. 6 N., R. 17 W/

Chains

N. 0° 01' E., beginning new measurement.

13.15 Spur, slopes NE.; desc. 97 ft. over NW. slope.

21.15 Wash, 40 lks. wide, course NE.

32.16 Point for the cor. of secs. 12 and 13 of R. 18 W.

Set an iron post, 28 ins. long, 2 $\frac{1}{2}$  ins. diam., 24 ins. in the ground with brass cap mkd.

|        |        |
|--------|--------|
| T 6 N  | T 6 N  |
| S 12   |        |
| S 13   | R 17 W |
| R 18 W | S 18   |
| 1953   |        |

Raise a mound of stone, 3 ft. base, 2 $\frac{1}{2}$  ft. high, W. of cor.

33.96 Wash, 30 lks. wide, course E.

40.05 The cor. of secs. 7, 12, 13 and 18, monumented by an iron post, 2 ins. diam., firmly set, mkd. and witnessed as described in the official record. Change the markings on the brass cap to read

|        |        |
|--------|--------|
| T 6 N  | T 6 N  |
|        | S 7    |
| R 18 W |        |
| S 12   | S 18   |
|        | R 17 W |
| 1927   |        |

Land, broken.

Soil, gravelly.

Timber, palo verde and ironwood; undergrowth, greasewood.

N. 0° 01' W., along the W. bdy. of sec. 7.

Over broken land, through scattering timber and undergrowth.

1.10 Begin ascent of 33 ft. over S. slope.

8.45 Top of a knoll; desc. 57 ft. over N. slope.

12.30 Wash, 30 lks. wide, course E.; asc. 71 ft. over S. slope.

30.10 Spur, slopes E.; desc. 40 ft. over N. slope.

32.11 Point for the  $\frac{1}{4}$  sec. cor. of sec. 12 of R. 18 W.Set an iron post, 28 ins. long, 2 $\frac{1}{2}$  ins. diam., 12 ins. in the ground to solid rock and in a mound of stone to top, with brass cap mkd.

|                    |
|--------------------|
| $\frac{1}{4}$ S 12 |
| 1953               |

39.91 The  $\frac{1}{4}$  sec. cor. of secs. 7 and 12, monumented by an iron post, 1 in. diam., firmly set, mkd. and witnessed as described in the official record. Change the markings on the brass cap to read.

|                   |
|-------------------|
| $\frac{1}{4}$ S 7 |
| 1927              |

Dependent Resurvey, W. Bdy. T. 6 N., R. 17 W.

|        |  |       |       |      |     |        |  |       |        |        |     |        |  |      |  |
|--------|--|-------|-------|------|-----|--------|--|-------|--------|--------|-----|--------|--|------|--|
| Chains | N. 0° 02' E., beginning new measurement.   |       |       |      |     |        |  |       |        |        |     |        |  |      |  |
| 11.20  | Wash, 50 lks. wide, course NE.   |       |       |      |     |        |  |       |        |        |     |        |  |      |  |
| 20.10  | Wash, 40 lks. wide, course E.  |       |       |      |     |        |  |       |        |        |     |        |  |      |  |
| 27.50  | Old road, bears E. and W.  |       |       |      |     |        |  |       |        |        |     |        |  |      |  |
| 32.20  | Point for the cor. of secs. 1 and 12 of R. 18 W.<br>Set an iron post, 28 ins. long, 2½ ins. diam., 14 ins. in the ground to solid rock and in a mound of stone to top, with brass cap mkd.<br><div style="text-align: center;"> <table style="margin: auto;"> <tr><td>T 6 N</td><td>T 6 N</td></tr> <tr><td>S 1</td><td> </td></tr> <tr><td colspan="2"><hr/></td></tr> <tr><td>S 12</td><td>R 17 W</td></tr> <tr><td>R 18 W</td><td>S 7</td></tr> <tr><td colspan="2">1953</td></tr> </table> </div>  | T 6 N | T 6 N | S 1  |     | <hr/>  |  | S 12  | R 17 W | R 18 W | S 7 | 1953   |  |      |  |
| T 6 N  | T 6 N  |       |       |      |     |        |  |       |        |        |     |        |  |      |  |
| S 1    |  |       |       |      |     |        |  |       |        |        |     |        |  |      |  |
| <hr/>  |  |       |       |      |     |        |  |       |        |        |     |        |  |      |  |
| S 12   | R 17 W   |       |       |      |     |        |  |       |        |        |     |        |  |      |  |
| R 18 W | S 7  |       |       |      |     |        |  |       |        |        |     |        |  |      |  |
| 1953   |  |       |       |      |     |        |  |       |        |        |     |        |  |      |  |
| 38.90  | Wash, 30 lks. wide, course E.  |       |       |      |     |        |  |       |        |        |     |        |  |      |  |
| 40.09  | The cor. of secs. 1, 6, 7 and 12, monumented by an iron post, 2 ins. diam., firmly set, mkd. and witnessed as described in the official record. Change the markings on the brass cap to read.<br><div style="text-align: center;"> <table style="margin: auto;"> <tr><td>T 6 N</td><td>T 6 N</td></tr> <tr><td> </td><td>S 6</td></tr> <tr><td>R 18 W</td><td> </td></tr> <tr><td colspan="2"><hr/></td></tr> <tr><td>S 1</td><td>S 7</td></tr> <tr><td colspan="2">R 17 W</td></tr> <tr><td colspan="2">1927</td></tr> </table> </div> <p>Land, broken.<br/>Soil, gravelly.<br/>Timber, palo verde and ironwood; undergrowth, greasewood.</p> | T 6 N | T 6 N |      | S 6 | R 18 W |  | <hr/> |        | S 1    | S 7 | R 17 W |  | 1927 |  |
| T 6 N  | T 6 N  |       |       |      |     |        |  |       |        |        |     |        |  |      |  |
|        | S 6  |       |       |      |     |        |  |       |        |        |     |        |  |      |  |
| R 18 W |  |       |       |      |     |        |  |       |        |        |     |        |  |      |  |
| <hr/>  |  |       |       |      |     |        |  |       |        |        |     |        |  |      |  |
| S 1    | S 7  |       |       |      |     |        |  |       |        |        |     |        |  |      |  |
| R 17 W |  |       |       |      |     |        |  |       |        |        |     |        |  |      |  |
| 1927   |  |       |       |      |     |        |  |       |        |        |     |        |  |      |  |
|        | N. 0° 01' W., along the W. bdy. of sec. 6.<br>Over mountainous land, through scattering timber and undergrowth.  |       |       |      |     |        |  |       |        |        |     |        |  |      |  |
| 8.10   | Begin ascent of 70 ft. over S. slope.  |       |       |      |     |        |  |       |        |        |     |        |  |      |  |
| 17.80  | Spur, slopes E.; desc. 91 ft. over N. slope.   |       |       |      |     |        |  |       |        |        |     |        |  |      |  |
| 32.11  | Point for the ¼ sec. cor. of sec. 1 of R. 18 W.<br>Set an iron post, 28 ins. long, 2½ ins. diam., 14 ins. in the ground to solid rock and in a mound of stone to top, with brass cap mkd.<br><div style="text-align: center;"> <table style="margin: auto;"> <tr><td>¼ S 1</td><td> </td></tr> <tr><td colspan="2">1953</td></tr> </table> </div>  | ¼ S 1 |       | 1953 |     |        |  |       |        |        |     |        |  |      |  |
| ¼ S 1  |  |       |       |      |     |        |  |       |        |        |     |        |  |      |  |
| 1953   |  |       |       |      |     |        |  |       |        |        |     |        |  |      |  |
| 38.00  | Wash, 40 lks. wide, course E.  |       |       |      |     |        |  |       |        |        |     |        |  |      |  |
| 39.96  | The ¼ sec. cor. of secs. 1 and 6, monumented by an iron post 1 in. diam., firmly set, mkd. and witnessed as described in the official record. Change the markings on the brass cap to read.<br><div style="text-align: center;"> <table style="margin: auto;"> <tr><td> </td><td>¼ S 6</td></tr> <tr><td colspan="2">1927</td></tr> </table> </div>  |       | ¼ S 6 | 1927 |     |        |  |       |        |        |     |        |  |      |  |
|        | ¼ S 6  |       |       |      |     |        |  |       |        |        |     |        |  |      |  |
| 1927   |  |       |       |      |     |        |  |       |        |        |     |        |  |      |  |
|        | N. 0° 02' E., beginning new measurement.   |       |       |      |     |        |  |       |        |        |     |        |  |      |  |
| 3.55   | Old road, bears NE. and NW.  |       |       |      |     |        |  |       |        |        |     |        |  |      |  |

## Chains

12.15 Point for the N 1/16 sec. cor. of sec. 1 of R. 18 W.

Set an iron post, 28 ins. long,  $2\frac{1}{2}$  ins. diam., 24 ins. in the ground with brass cap mkd.

N 1/16 |  
S 1 |  
1953

Raise a mound of stone 3 ft. base,  $2\frac{1}{2}$  ft. high, W. of cor.

24.55 Wash, 50 lks. wide, course E.; asc. 63 ft. over SW. slope.

31.65 Spur, slopes SE.; desc. over NE. slope.

32.15 Point for the 1/16 sec. cor. of sec. 1 of R. 18 W.

Set an iron post, 28 ins. long,  $2\frac{1}{2}$  ins. diam., 6 ins. in the ground to solid rock and in a mound of stone to top with brass cap mkd.

1/16 |  
S 1 |  
80  
1953

40.64 The closing corner of Tps. 6 N., Rs. 17 and 18 W., monumented by an iron post, 3 ins. diam., firmly set, mkd. and witnessed as described in the official record.

Land, mountainous.

Soil, rocky.

Timber, palo verde and ironwood; undergrowth, greasewood.

## North Boundary, T. 6 N., R. 18 W.

From the closing corner of Tps. 6 N., Rs. 17 and 18 W.

WEST, along the N. bdy. of sec. 1.

Over broken land, through scattering timber and undergrowth.

5.00 Begin ascent of 41 ft. over NE. slope.

12.00 Spur, slopes SE.; desc. over SW. slope.

12.98 The cor. of Tps. 7 N., Rs. 17 and 18 W., which is monumented by a malpais stone, 16x12x8 ins. lying in a scattered mound of stone and mkd. as described in the official record.

At the corner point

Set an iron post, 28 ins. long,  $2\frac{1}{2}$  ins. diam., 24 ins. in the ground with brass cap mkd.

T 7 N  
R 18 W | R 17 W  
S 36 | S 31

T 6 N R 18 W S 1  
1953

Raise a mound of stone, 3 ft. base,  $2\frac{1}{2}$  ft. high, N. of cor. and bury the original corner stone alongside the iron post.

|        |  |
|--------|--|
| Chains |  |
| 27.50  | Wash, 20 lks. wide, course SE.; asc. 52 ft. over E. slope.   |
| 36.20  | Top of hill; desc. 29 ft. over W. slope.   |
| 40.00  | Point for the $\frac{1}{4}$ sec. cor. of sec. 1.<br>Set an iron post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 16 ins. in the ground to solid rock and in a mound of stone to top, with brass cap mkd. |
|        | $\frac{1}{4}$ S 1<br><hr/> 1953  |
| 42.50  | Wash, 50 lks. wide, course SE.; asc. 134 ft. over SE. slope.   |
| 52.98  | Point for the $\frac{1}{4}$ sec. cor. of sec. 36 of T. 7 N.<br>Set an iron post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 24 ins. in the ground with brass cap mkd.                                    |
|        | $\frac{1}{4}$ S 36<br><hr/> 1953   |
|        | Raise a mound of stone, 3 ft. base, $2\frac{1}{2}$ ft. high, N. of cor.  |
| 60.52  | Spur, slopes NE.; desc. 136 ft. over NW. slope.  |
| 70.50  | Drain, course N-NE.; asc. 85 ft. over E. slope.  |
| 80.00  | Point for the cor. of secs. 1 and 2.<br>Set an iron post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 8 ins. in the ground to solid rock and in a mound of stone to top, with brass cap mkd.              |
|        | T 7 N R 18 W<br>S 36<br><hr/> S 2   S 1<br>T 6 N   R 18 W<br>1953  |
|        | Land, mountainous.<br>Soil, rocky.<br>Timber, palo verde and ironwood; undergrowth, greasewood.  |
|        | WEST, along the N. bdy. of sec. 2.<br>Over mountainous land, through scattering timber and undergrowth.<br>Continue ascent over E. slope.  |
| 0.80   | Ridge, bears N. and S.; desc. 139 ft. over W. slope.   |
| 6.30   | Wash, 20 lks. wide, course SW.; asc. 91 ft. over E. slope.   |
| 12.98  | Point for the cor. of secs. 35 and 36 of T. 7 N.<br>Set an iron post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 10 ins. in the ground to solid rock and in a mound of stone to top, with brass cap mkd. |
|        | T 7 N R 18 W<br>S 35   S 36<br><hr/> T 6 N R 18 W<br>S 2<br>1953   |

|        |   |
|--------|---|
| Chains |   |
| 20.90  | Spur, slopes S.; desc. 131 ft. over W. slope.   |
| 29.70  | Wash, 50 lks. wide, course S.; asc. 123 ft. over E. slope.  |
| 40.00  | Point for the $\frac{1}{4}$ sec. cor. of sec. 2.<br><br>Set an iron post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 14 ins. in the ground to solid rock and in a mound of stone to top, with brass cap mkd.            |
|        | $\frac{1}{4} \text{ S } 2$ <hr style="width: 50px; margin: auto;"/> 1953  |
| 42.15  | Spur, slopes S. for 5 chs., then SW.; desc. 300 ft. over W. slope.  |
| 52.98  | Point for the $\frac{1}{4}$ sec. cor. of sec. 35 of T. 7 N.<br><br>Set an iron post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 10 ins. in the ground to solid rock and in a mound of stone to top, with brass cap mkd. |
|        | $\frac{1}{4} \text{ S } 35$ <hr style="width: 50px; margin: auto;"/> 1953   |
| 68.80  | Wash, 20 lks. wide, course SW.; leave mountainous land, enter valley, bears NE. and SW.   |
| 80.00  | Point for the cor. of secs. 2 and 3.<br><br>Set an iron post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 24 ins. in the ground with brass cap mkd.  |
|        | $\begin{array}{c} \text{T } 7 \text{ N } \text{ R } 18 \text{ W} \\ \text{S } 35 \\ \hline \text{S } 3 \text{   S } 2 \\ \text{T } 6 \text{ N } \text{ R } 18 \text{ W} \\ 1953 \end{array}$                          |
|        | Deposit a broken glass bottle alongside the iron post.<br><br>Land, mountainous.<br>Soil, rocky.<br>Timber, ironwood and palo verde; undergrowth, greasewood.   |
|        | WEST, along the N. bdy. of sec. 3.<br><br>Over rolling land, through scattering timber.   |
| 12.98  | Point for the cor. of secs. 34 and 35 of T. 7 N.<br><br>Set an iron post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 24 ins. in the ground, with brass cap mkd.   |
|        | $\begin{array}{c} \text{T } 7 \text{ N } \text{ R } 18 \text{ W} \\ \text{S } 34 \text{   S } 35 \\ \hline \text{T } 6 \text{ N } \text{ R } 18 \text{ W} \\ \text{S } 3 \\ 1953 \end{array}$                         |
|        | Deposit a broken glass bottle alongside the iron post.  |
| 21.20  | Wash, 30 lks. wide, course NW.  |

Chains

39.00

Point for the witness,  $\frac{1}{4}$  sec. cor. of sec 3.Set an iron post, 28 in. long,  $2\frac{1}{2}$  ins. diam., 24 ins. in the ground, with brass cap mkd.

W C —————  
 $\frac{1}{4}$  S 3  
 1953

Deposit a broken glass bottle alongside the iron post.

40.00

True point for  $\frac{1}{4}$  sec. cor. of sec. 3 falls in wash, 20 lks. wide, course NW.

52.98

Point for  $\frac{1}{4}$  sec. cor. of sec. 34 of T. 7 N.Set an iron post, 28 in. long,  $2\frac{1}{2}$  ins. diam., 24 ins. in the ground, with brass cap mkd.

$\frac{1}{4}$  S 34  
 —————  
 1953

Deposit a broken glass bottle alongside the iron post.

80.00

Point for the cor. of secs. 3 and 4.

Set an iron post, 28 ins. long,  $2\frac{1}{2}$  ins. diam., 24 ins. in the ground, with brass cap mkd.

T 7 N R 18 W  
 S 34  
 —————  
 S 4 | S 3  
 T 6 N R 18 W  
 1953

Deposit a broken glass bottle alongside the iron post.

Land, rolling.  
 Soil, sandy, gravelly.  
 Timber, greasewood.

WEST, along the N. bdy. of sec. 4.

Over rolling land, through scattering timber.

12.98

Point for the cor. of secs. 33 and 34 of T. 7 N.

Set an iron post, 28 ins. long,  $2\frac{1}{2}$  ins. diam., 24 ins. in the ground, with brass cap mkd.

T 7 N R 18 W  
 S 33 | S 34  
 —————  
 T 6 N R 18 W  
 S 4  
 1953

Deposit a broken glass bottle alongside the iron post.

40.00

Point for the  $\frac{1}{4}$  sec. cor. of sec. 4.Set an iron post, 28 ins. long,  $2\frac{1}{2}$  ins. diam., 24 ins. in the ground, with brass cap mkd.

North Boundary T. 6 N., R. 18 W.

Chains

1/4 S 4

1953

Deposit a broken bottle alongside the iron post.

52.00 Wash, 40 lks. wide, course NW.

52.98 True point for 1/4 sec. cor. of sec. 33 of T. 7 N. falls on W. bank of wash.

53.48 Point for the witness, 1/4 sec. cor. of sec. 33 of T. 7 N.

Set an iron post, 28 ins. long, 2 1/2 ins. diam. 24 ins. in the ground, with brass cap mkd.

1/4 S 33 W C

1953

Deposit a broken bottle alongside the iron post.

80.00 Point for the cor. of secs. 4 and 5.

Set an iron post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.

T 7 N R 18 W  
S 33S 5 | S 4  
T 6 N R 18 W

1953

Deposit a broken bottle alongside of iron post.

Land, rolling.

Soil, sandy, gravelly.

Timber, ironwood, palo verde, and greasewood. undergrowth.

WEST, along the N. bdy. of sec. 5.

Over rolling land, through scattering timber.

12.98 Point for the cor. of secs. 32 and 33 of T. 7 N.

Set an iron post, 28 ins. long, 2 1/2 ins. in diam., 24 ins. in the ground with brass cap mkd.

T 7 N R 18 W  
S 32 | S 33

T 6 N R 18 W

S 5

1953

Deposit a broken bottle alongside the iron post.

40.00 Point for the 1/4 sec. cor. of sec. 5.

Set an iron post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.

North Boundary T. 6 N., R 18 W.

| Chains | entire   |
|--------|--|
|        | <p style="text-align: center;"> <u>1/4 S 5</u><br/>           1953         </p>  |
| 52.98  | <p>Deposit a broken glass bottle alongside the iron post.</p> <p>Point for the 1/4 sec. cor. of sec. 32, T. 7 N.</p>   |
|        | <p>Set an iron post, 28 ins. long; 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p>  |
|        | <p style="text-align: center;"> <u>1/4 S 32</u><br/>           1953         </p>   |
| 80.00  | <p>Deposit a broken glass bottle alongside the iron post.</p> <p>Point for the cor. of secs. 5 and 6.</p>  |
|        | <p>Set an iron post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p>  |
|        | <p style="text-align: center;">           T 7 N R 18 W<br/> <u>S 32</u> </p>   |
|        | <p style="text-align: center;"> <u>S 6   S 5</u><br/> <u>T 6 N R 18 W</u><br/>           1953         </p>   |
|        | <p>Deposit a broken glass bottle alongside the iron post.</p> <p>Land, rolling.<br/>Soil, sandy.<br/>Timber, palo verde, ironwood; and greasewood undergrowth.</p> |
| 12.98  | <p>WEST, along the N. bdy. of sec. 6.</p> <p>Over rolling land through scattering timber.</p> <p>Point for the cor. of secs. 31 and 32 of T. 7 N.</p>              |
|        | <p>Set an iron post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p>  |
|        | <p style="text-align: center;">           T 7 N R 18 W<br/> <u>S 31   S 32</u><br/>           T 6 N R 18 W<br/>           S 6         </p>                         |
|        | <p style="text-align: center;">1953</p>  |
| 40.00  | <p>Deposit a broken glass bottle alongside the iron post.</p> <p>Point for the 1/4 sec. cor. of sec. 6.</p>  |
|        | <p>Set an iron post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p>  |
|        | <p style="text-align: center;"> <u>1/4 S 6</u><br/>           1953         </p>  |
|        | <p>Deposit a broken glass bottle alongside the iron post.</p>  |

## North Boundary of T.6 N., R. 18 W.

Chains

52.98

Point for the  $\frac{1}{4}$  sec. cor. of sec. 31, T. 7 N.Set an iron post, 28 ins. long,  $2\frac{1}{2}$  ins. diam., 24 ins. in the ground, with brass cap mkd. $\frac{1}{4}$  S 31

1953

Deposit a broken glass bottle alongside the iron post.

78.74

The cor. of Tps. 6 and 7 N., Rs. 18 and 19 W.

Land, rolling.

Soil, sandy.

Timber, palo verde and ironwood.

Undergrowth, greasewood.

## Subdivision of T. 6 N., R. 18 W.

Beginning the subdivisional survey at the cor. of secs. 1, 2, 35 and 36, on the S. bdy. of the Tp., which is monumented with an iron post, set, marked and witnessed as described in the official record.

NORTH, bet. secs. 35 and 36.

Over broken spurs.

2.00

Drain, course NE.

13.00

Wash, 30 lks. wide, course NE.

29.70

Drain, course N. 60° E.

36.00

Top of spur, slopes E.

38.00

Wash, 20 lks. wide, course NE.

40.00

Point for the  $\frac{1}{4}$  cor. of secs. 35 and 36.Set an iron post, 28 ins. long,  $2\frac{1}{2}$  ins. diam., 24 ins. in the ground, with brass cap mkd.
$$\begin{array}{c} \frac{1}{4} \\ \text{S } 35 \quad | \quad \text{S } 36 \end{array}$$

1953

raise a mound of stone 2 ft. high, W. of cor.

43.50

Wash, 20 lks. wide, course E.

61.70

Wash, 20 lks. wide, course E.

65.40

Wash, 30 lks. wide, course N. 60° E.

71.00

Top of spur, slopes E.

75.93

Enter drain, course N. from SW.

80.00

True point for cor. of secs. 25, 26, 35 and 36, falls in drain, course NW. from S.

From true point for cor. of secs. 25, 26, 35 and 36, NORTH, 30 lks. dist. to point for the witness, cor. of secs. 25, 26, 35 and 36.

Set an iron post, 28 ins. long,  $2\frac{1}{2}$  ins. diam., 24 ins. in the ground, with brass cap mkd.


Subdivision of T. 6 N., R. 18 W.

| Chains        | <table border="1" style="margin: auto;"> <tr> <td colspan="2">T 6 N R 18 W</td> </tr> <tr> <td>S 26</td> <td>S 25</td> </tr> <tr> <td>S 35</td> <td>S 36</td> </tr> <tr> <td colspan="2">W C</td> </tr> <tr> <td colspan="2">1953</td> </tr> </table>  | T 6 N R 18 W |      | S 26          | S 25  | S 35 | S 36 | W C |      | 1953 |  |
|---------------|--|--------------|------|---------------|-------|------|------|-----|------|------|--|
| T 6 N R 18 W  |  |              |      |               |       |      |      |     |      |      |  |
| S 26          | S 25   |              |      |               |       |      |      |     |      |      |  |
| S 35          | S 36   |              |      |               |       |      |      |     |      |      |  |
| W C           |  |              |      |               |       |      |      |     |      |      |  |
| 1953          |  |              |      |               |       |      |      |     |      |      |  |
|               | <p>raise a mound of stone 2 ft. high, W. of cor.</p> <p>Land, broken spurs.<br/>Soil, rocky.<br/>Timber, palo verde and ironwood.<br/>Undergrowth, greasewood.</p>   |              |      |               |       |      |      |     |      |      |  |
|               | <p>From the cor. of secs. 25 and 36, on the E. bdy. of the Tp. which is monumented with an iron post, marked and witnessed as described in the official record.</p> <p>S. 89° 57' W., bet. secs. 25 and 36.</p> <p>Over broken land, through scattering timber.</p>  |              |      |               |       |      |      |     |      |      |  |
| 2.40          | Wash, 20 lks. wide, course S. 70° E.   |              |      |               |       |      |      |     |      |      |  |
| 13.10         | Wash, 20 lks. wide, course N. 70° E.   |              |      |               |       |      |      |     |      |      |  |
| 16.70         | Old road, bears N. and S.  |              |      |               |       |      |      |     |      |      |  |
| 21.10         | Wash, 60 lks. wide, course NE.   |              |      |               |       |      |      |     |      |      |  |
| 23.00         | Old road, bears N. and S.  |              |      |               |       |      |      |     |      |      |  |
| 27.40         | Wash, 30 lks. wide, course N.  |              |      |               |       |      |      |     |      |      |  |
| 39.95         | Point for the $\frac{1}{4}$ cor. of secs. 25 and 36.   |              |      |               |       |      |      |     |      |      |  |
|               | <p>Set an iron post, 28 ins. long, 2<math>\frac{1}{2}</math> ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <table style="margin-left: auto; margin-right: auto;"> <tr> <td></td> <td style="text-align: center;">S 25</td> </tr> <tr> <td style="text-align: center;"><math>\frac{1}{4}</math></td> <td style="text-align: center;">-----</td> </tr> <tr> <td></td> <td style="text-align: center;">S 36</td> </tr> <tr> <td></td> <td style="text-align: center;">1953</td> </tr> </table> |              | S 25 | $\frac{1}{4}$ | ----- |      | S 36 |     | 1953 |      |  |
|               | S 25   |              |      |               |       |      |      |     |      |      |  |
| $\frac{1}{4}$ | -----  |              |      |               |       |      |      |     |      |      |  |
|               | S 36   |              |      |               |       |      |      |     |      |      |  |
|               | 1953   |              |      |               |       |      |      |     |      |      |  |
|               | <p>raise a mound of stone, 2 ft. high, N. of cor.</p>  |              |      |               |       |      |      |     |      |      |  |
| 44.10         | Wash, 30 lks. wide, course N. 40° E.   |              |      |               |       |      |      |     |      |      |  |
| 65.20         | Wash, 50 lks. wide, course NE.   |              |      |               |       |      |      |     |      |      |  |
| 79.90         | <p>The cor. of secs. 25, 26, 35 and 36.</p> <p>Land, broken.<br/>Soil, gravelly.<br/>Timber, palo verde and ironwood.<br/>Undergrowth, greasewood.</p>   |              |      |               |       |      |      |     |      |      |  |
|               | <p>NORTH, bet. secs. 25 and 26.</p> <p>Over broken spurs, through scattering timber.</p>   |              |      |               |       |      |      |     |      |      |  |
| 0.30          | Witness for cor. of secs. 25, 26, 35 and 36, an iron post, set, mkd., and witnessed as described on this page.   |              |      |               |       |      |      |     |      |      |  |
| 0.80          | Drain, course E.   |              |      |               |       |      |      |     |      |      |  |
| 5.00          | Wash, 20 lks. wide, course N. 60° E.   |              |      |               |       |      |      |     |      |      |  |

Subdivision of T. 6 N., R. 18 W.

Chains

19.90 Wash, 50 lks. wide, course N. 70° E.  
 23.70 Ascend S. slope of spur, 25 ft.  
 28.00 Top of spur, slopes E., descend 23 ft. over N. slope.  
 38.00 Drain, course S. 70° E., ascend 17 ft. over S. slope of spur.  
 40.00 Point for  $\frac{1}{4}$  cor. of secs. 25 and 26. Top of spur.  
 Set an iron post, 28 ins. long, 2 $\frac{1}{2}$  ins. diam., 24 ins. in the ground, with brass cap mkd.



1953

raise a mound of stone, 2 ft. high, W. of cor.

U.S.G.S. triangulation station **PLUMOSA** bears N. 59° 40' 30" W. from  $\frac{1}{4}$  cor. of secs. 25 and 26.

Descend 21 ft. over N. slope.

45.20 Wash, 40 lks. wide, course N. 70° E., Ascend 27 ft. over S. slope.

49.20 Top of spur, slopes E.

56.90 Wash, 30 lks. wide, course N. 70° E.

58.90 Ascend 7 ft. over S. slope.

64.55 Top of spur, slopes E. U.S.G.S. triangulation station <sup>PLUMOSA</sup> ~~PLUMOSA~~ bears S. 89° 12' W. from this point. Descend 57 ft. over N. slope.


68.00 Drain, course NE., Ascend 80 ft. over SE. slope of spur.

76.20 Top of spur, slopes NE., Descend 72 ft. over NW. slope.

80.00 Point for cor. of secs. 23, 24, 25 and 26.

Set an iron post, 28 ins. long, 2 $\frac{1}{2}$  ins. diam., 12 ins. in ground to rock and in mound of stone to top, with brass cap mkd.

T 6 N R 18 W



1953

Land, broken spur.

Soil, rocky.

Timber, ironwood, palo verde, and greasewood undergrowth.

From the cor. of secs. 24 and 25 on the E. bdy. of the Tp. which is monumented with an iron post marked and witnessed as described in the official record.

S. 89° 58' W., bet. secs. 24 and 25.

Over broken land.

Subdivision of T. 6 N., R. 18 W.

|        |   |    |       |
|--------|---|----|-------|
| Chains |   |    | 00.00 |
| 9.96   | Old road, bears NE. and SW. along top of low spur.  |    | 00.00 |
| 26.86  | Wash, 70 lks. wide, course N.   |    | 00.00 |
| 33.96  | Wash, 20 lks. wide, course N. 60° E.  |    | 00.00 |
| 39.98  | Point for the 1/4 cor. of secs. 24 and 25.  |    | 00.00 |
|        | Set an iron post, 28 ins. long, 2 1/2 ins. diam., 2 1/2 ins. in the ground, with brass cap mkd. |    |       |
|        | $\begin{array}{c} S \ 24 \\ \hline \frac{1}{4} \\ \hline S \ 25 \\ 1953 \end{array}$            |    |       |
|        | raise a mound of stone 2 ft. high, N. of cor.   |    |       |
| 45.76  | Same wash, course S. 60° E.   |    | 00.00 |
| 48.16  | Same wash, course N. 60° E.   |    | 00.00 |
| 53.96  | Same wash, course S. 60° E.   |    | 00.00 |
| 55.96  | Same wash, course N. 70° E.   |    | 00.00 |
| 59.96  | Same wash, course S. 70° E.   |    | 00.00 |
| 69.06  | Drain, course NE.   |    | 00.00 |
| 77.66  | Top of spur, slopes NE., descend 83 ft. over NW. slope.   | NW | 00.00 |
| 79.96  | The cor. of secs. 23, 24, 25 and 26.  |    | 00.00 |
|        | Land, broken.<br>Soil, rocky.<br>Timber, ironwood, palo verde; and greasewood undergrowth.      |    |       |
|        | NORTH, bet. secs. 23 and 24.  |    | 00.00 |
|        | Over rough broken spurs; descend 34 ft. over NW. slope.   |    |       |
| 3.00   | Wash, 30 lks. wide, course NE.; ascend 46 ft. over SE. slope.                                   |    | 00.00 |
| 18.00  | Top of spur, slopes NE.; descend 69 ft. over NW. slope.   |    | 00.00 |
| 23.00  | Drain, course NE.; ascend 23 ft. over NE. slope.  |    | 00.00 |
| 25.10  | Top of spur, slopes NE.; descend 29 ft. over NW. slope.   |    | 00.00 |
| 28.00  | Drain, course NE.; ascend 14 ft. over SE. slope.  |    | 00.00 |
| 31.50  | Top of spur, slopes N. 60° E.; descend 66 ft. over N. slope.                                    |    | 00.00 |
| 36.00  | Drain, course N. 60° E.; ascend 171 ft. over S. slope.  |    | 00.00 |
| 40.00  | Point for the 1/4 cor. of secs. 23 and 24.  |    | 00.00 |
|        | Set an iron post, 28 ins. long, 2 1/2 ins. diam., 2 1/2 ins. in the ground, with brass cap mkd. |    |       |
|        | $\begin{array}{c} S \ 23 \\   \\ S \ 24 \\ 1953 \end{array}$                                    |    |       |

## BOOK 4440

Subdivision of T. 6 N., R. 18 W.

raise a mound of stone 2 ft. high W. of cor.

Continue to ascend S. slope of spur.

44.00 Top of spur, slopes E., ascend 23 ft. along E. slope of ridge.

55.00 Ridge turns W., descend 113 ft. over N. slope.

60.40 Wash, 20 lks. wide, course East, ascend 145 ft. over SE. slope.

68.85 Top of spur, slopes NE., descend 69 ft. over NW. slope.

80.00 Point for cor. of secs. 13, 14, 23 and 24.

Set an iron post, 28 ins. long,  $2\frac{1}{2}$  ins. diam., 24 ins. in the ground, with brass cap mkd.

T 6 N R 18 W

|      |      |
|------|------|
| S 14 | S 13 |
|------|------|

|      |      |
|------|------|
| S 23 | S 24 |
|------|------|

1953

raise a mound of stone 2 ft. high, W. of cor.

Land, mountainous.

Soil, rocky.

Timber, palo verde and greasewood.

From the cor. of secs. 13 and 24 on the E. bdy. of the Tp. which is monumented with an iron post marked and witnessed as described in the official record.

N.  $89^{\circ} 56'$  W., bet. secs. 13 and 24.

Over broken land.

10.04 Wash, 40 lks. wide, course S.  $70^{\circ}$  E.

26.74 Wash, 30 lks. wide, course NE.

37.44 Old road, bears NE and SW.

39.97 Point for the  $\frac{1}{4}$  cor. of secs. 13 and 24.

Set an iron post, 28 ins. long,  $2\frac{1}{2}$  ins. diam., 12 ins. in ground to rock, with mound of stone to top, with brass cap mkd.

S 13

$\frac{1}{4}$

S 24

1953

43.56 Old road bears, SE. and NW.

52.44 Wash, 20 lks. wide, course S.  $60^{\circ}$  E., ascend 162 ft. over SE. slope.

68.19 Top of spur, slopes NE., descend 68 ft. over NW. slope of spur.

Subdivision of T. 6 N., R. 18 W.

Chains

79.24 Wash, 20 lks. wide, course NE.

79.94 Point for the cor. of secs. 13, 14, 23 and 24.

Land, broken and mountainous.

Soil, rocky.

Timber, palo verde, ironwood; and greasewood; undergrowth:

NORTH, bet. secs. 13 and 14.

Over broken mountainous land.

Ascend 155 ft. over SE. slope of ridge.


12.20 Top of ridge, bears N. 20° E., and S. 20° W., descend 193 ft. over NW. slope.

19.00 Drain, course NW., ascend 46 ft. over SE. slope of spur.

27.40 Top of spur, slopes SW., descend 166 ft. over NW. slope.

40.00 Point for the 1/4 cor. of secs. 13 and 14.

Set an iron post, 28 ins. long, 2 1/2 ins. diam., 12 ins. in ground to rock and mound with stone to top, with brass cap mkd.



1953

44.90 Drain, course W., ascend 21 ft. over S. slope.

47.80 Top of low spur, slopes W.


62.00 Old road, course SW. and NE.

63.30 Wash, 40 lks. wide, course SW.

76.00 Wash, 20 lks. wide, course S. 30° W.

80.00 Point for cor. of secs. 11, 12, 13 and 14.

Set an iron post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.



1953

raise a mound of stone 2 ft. high, W. of cor.

Land, mountainous.

Soil, rocky.

Timber, ironwood, palo verde; and greasewood. undergrowth.

From the cor. of secs. 12 and 13 on the E. bdy. of the Tp. which is monumented with an iron post marked and witnessed as described in the official record.

N. 89° 54' W., bet. secs. 12 and 13.

Over mountainous land.

| Chains |  |
|--------|--|
| 1.20   | Wash, 20 lks. wide, course N.60° E.  |
| 19.00  | Same wash, course S. 60° E., ascend 165 ft. over SE. slope.  |
| 38.60  | Top of spur, slopes NE.  |
| 40.00  | Point for the $\frac{1}{4}$ cor. of secs. 12 and 13.<br>Set an iron post, 28 ins. long, 2 $\frac{1}{2}$ ins. diam., 10 ins. in ground to rock and mound with stone to top, with brass cap mkd. |
|        | S 12<br>$\frac{1}{4}$ —————<br>S 13<br>1953  |
|        | Descend 51 ft. over SW. slope.   |
| 44.00  | Drain, course NE., ascend 57 ft. over NW. slope.   |
| 48.30  | Top of ridge, bears SE. and W.; descend 64 ft. along S. slope of ridge.  |
| 57.00  | Wash, 20 lks. wide, course SW.; ascend 69 ft. over E. slope.   |
| 62.00  | Follow along S. slope of hill.   |
| 68.70  | Top of ridge, bears N. and S.; descend 92 ft. over W. slope.   |
| 76.80  | Wash, 20 lks. wide, course S. 30° W.   |
| 80.00  | The cor. of secs. 11, 12, 13 and 14.<br>Land, mountainous.<br>Soil, rocky.<br>Timber, palo verde, ironwood; and greasewood. undergrowth.   |
|        | NORTH, bet. secs. 11 and 12.<br>Over mountainous land.<br>Ascend 65 ft. over S. slope of spur.   |
| 4.29   | Top of spur, slopes E.; descend 57 ft. over N. slope.  |
| 6.37   | Top of ridge, bears E. and W.  |
| 11.10  | Wash, 10 lks. wide, course E.; ascend 20 ft. over S. slope.  |
| 16.00  | Top of spur, slopes E.; descend 23 ft. over N. slope.  |
| 23.00  | Drain, course NE.; ascend 46 ft. over SE. slope.   |
| 27.20  | Top of spur, slopes NE.; descend 57 ft. over NW. slope.  |
| 32.40  | Wash, 20 lks. wide, course NE.   |
| 34.70  | Old road, bears NE. and SW.; ascend 33 ft. over S. slope.  |
| 40.00  | Point for the $\frac{1}{4}$ cor. of secs. 11 and 12.<br>Set an iron post, 28 ins. long, 2 $\frac{1}{2}$ ins. diam., 24 ins. in the ground, with brass cap mkd.                                 |

Subdivision of T. 6 N., R. 18 W.

Chains

1/4  
S 11 | S 12

1953

Raise a mound of stone 2 ft. high, W. of cor.

- 41.39 Top of spur, slopes E.; descend 20 ft. over N. slope.
- 46.90 Wash, 15 lks. wide, course E.; ascend 24 ft. over S. slope of spur.
- 48.00 Top of spur, slopes E.; descend 15 ft. over N. slope.
- 52.00 Wash, 20 lks. wide, course S. 60° E.
- 56.00 Ascend 24 ft. over S. slope of spur.
- 60.10 Top of spur, slopes E.; descend 35 ft. over N. slope.
- 74.00 Wash, 20 lks. wide, course, N. 60° E.; ascend 84 ft. over S. slope.
- 78.70 Top of spur, slopes E.; descend 21 ft. over N. slope.
- 79.80 Foot of slope.
- 80.00 Point for cor. of secs. 1, 2, 11 and 12.

Set an iron post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.

T 6 N R 18 W

S 2 | S 1  
S 11 | S 12

1953

raise a mound of stone 2 ft. high, W. of cor.

Land, mountainous.  
Soil, rocky.  
Timber, palo verde; and greasewood. undergrowth.

From the cor. of secs. 1 and 12 on the E. bdy. of the Tp. which is monumented with an iron post marked and witnessed as described in the official record.

N. 89° 53' W., bet. secs. 1 and 12.

Over broken land, through scattering timber.

- 40.00 Point for the 1/4 cor. of secs. 1 and 12.

Set an iron post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.

S 1

1/4  
S 12

1953

raise a mound of stone 2 ft. high, N. of cor.

| Chains |  |
|--------|--|
| 74.70  | Wash, 20 lks. wide, course S. 60° E.   |
| 80.00  | The cor. of secs. 1, 2, 11 and 12.   |
|        | Land, broken.<br>Soil, gravelly.<br>Timber, palo verde, ironwood; and greasewood. undergrowth.   |
|        | N. 02° 02' W., bet. secs. 1 and 2.   |
|        | Over mountainous land.   |
| 1.50   | Drain, course E.; ascend 50 ft. over S. slope of hill.   |
| 4.70   | Top of hill; descend 40 ft. over N. slope.   |
| 8.00   | Ascend 59 ft. over S. slope of spur.   |
| 15.90  | Top of spur, slopes E.; descend 20 ft. over N. slope.  |
| 21.00  | Drain, course E.   |
| 23.00  | Ascend 132 ft. over SE. slope of spur.   |
| 30.80  | Top of spur, slopes NE.; descend 186 ft. over NW. slope.   |
| 39.50  | Wash, 30 lks. wide, course NE.   |
| 40.00  | Point for the $\frac{1}{4}$ cor. of secs 1 and 2.<br>Set an iron post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 24 ins. in the ground, with brass cap mkd.                     |
|        | $\frac{1}{4}$<br>S 2   S 1<br>1953   |
|        | raise a mound of stone 2 ft. high, W. of cor.  |
| 46.10  | Ascend 86 ft. over S. slope of spur.   |
| 51.50  | Top of spur, slopes E.; descend 96 ft. over N. slope.  |
| 60.00  | Point for the N. 1/16 cor. of secs. 1 and 2.<br>Set an iron post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 24 ins. in the ground, with brass cap mkd.                          |
|        | N 1/16<br>S 2   S 1<br>1953  |
|        | raise a mound of stone 2 ft. high, W. of cor.  |
| 61.00  | Wash, 20 lks. wide, course E.; ascend 183 ft. over SE. slope of ridge.   |
| 69.00  | Top of ridge, bears SW. and NE.; continue along W. slope of ridge.   |
| 80.00  | Point for the 1/16 cor. secs. 1 and 2.<br>Set an iron post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 8 ins. in ground to rock and mound with stone to top, with brass cap mkd. |

Subdivision of T. 6 N., R 18 W.

| Chains |  | arced |
|--------|--|-------|
|        | <p>1/16</p> <p>S 2   S 1</p> <p>80</p> <p>1953</p>   |       |
| 85.02  | Top of ridge, bears NW. and SE.; descend NE. slope.  |       |
| 88.36  | <p>The cor. of secs. 1 and 2 on the N. bdy. of Tp. 6 N., R 18 W., which is monumented with an iron post marked and witnessed as described in the official record.</p> <p>Land, mountainous.<br/>Soil, rocky.<br/>Timber, palo verde; and greasewood undergrowth.</p> |       |
|        | <p>From the cor. of secs. 2, 3, 34 and 35, T. 5 and 6 N., R. 18 W. which is monumented with an iron post marked and witnessed as described in the official record.</p> <p>NORTH, bet. secs. 34 and 35.</p> <p>Over mountainous land.</p>                             |       |
| 1.00   | Wash, 20 lks. wide, course W.  |       |
| 14.00  | Ascend 208 ft. over SE. slope of spur.   |       |
| 21.77  | Top of spur, slopes SW.; descend 112 ft. over NW. slope.   |       |
| 36.00  | Wash, 20 lks. wide, course SW.; ascend 207 ft. over SE. slope.   |       |
| 40.00  | Point for the $\frac{1}{4}$ cor. of secs. 34 and 35, falls in small drain, course SE.  |       |
| 40.30  | <p>Point for the witness to <math>\frac{1}{4}</math> cor. of secs. 34 and 35.</p> <p>Set an iron post, 28 ins. long, 2<math>\frac{1}{2}</math> ins. diam., 10 ins. in the ground, and mound with stone to top, with brass cap mkd.</p>                               |       |
|        | <p><math>\frac{1}{4}</math></p> <p>S 34   S 35</p> <p>W C</p> <p>1953</p>  |       |
| 45.60  | Top of spur, slopes SW., descend 224 ft. over NW. slope.   |       |
| 53.50  | Drain, course W., ascend 230 ft. over SE. slope.   |       |
| 61.80  | Top of spur, slopes S. 60° W., descend 317 ft. over NW. slope.   |       |
| 66.50  | Top of spur, slopes NW., descend 313 ft. over NW. slope.   |       |
| 76.00  | Wash, 20 lks. wide, course W.  |       |
| 80.00  | <p>Point for the cor. of secs. 26, 27, 34 and 35.</p> <p>Set an iron post, 28 ins. long, 2<math>\frac{1}{2}</math> ins. diam., 10 ins. in the ground and mound with stone to top, with brass cap mkd.</p>  |       |

Subdivision of T. 6 N., R. 18 W.

Chains

T 6 N R 18 W

S 27 | S 26

S 34 | S 35

1953

Land, mountainous.

Soil, rocky.

Timber, palo verde, ironwood; and greasewood undergrowth.

EAST, on a random line bet. secs. 26 and 35.

39.93 Set temp.  $\frac{1}{4}$  cor.

79.92 Fall 12 lks. N. of cor. of secs. 25, 26, 35 and 36.

Thence.

N.  $89^{\circ} 55'$  W., on true line bet. secs. 26 and 35.

9.92 Top of low spur, slopes N.

11.92 Drain, course N. 250 lks. dist., thence E.; ascend 263 ft. over SE. slope.

24.62 Top of spur, slopes NE.; descend 54 ft. over NW. slope.

31.22 Drain, course N.; ascend 52 ft. over E. slope.

36.17 Top of spur, slopes N.; descend 41 ft. over W. slope.

38.52 Drain, course N. 5.00 ch. dist.; thence E.

39.96 Point for the  $\frac{1}{4}$  cor. of secs. 26 and 35.Set an iron post, 28 ins. long,  $2\frac{1}{2}$  ins. diam., 24 ins. in the ground, with brass cap mkd.

S 26

 $\frac{1}{4}$ 

S 35

1953

Raise a mound of stone 2 ft. high, N. of cor.

Ascend 264 ft. over E. slope.

51.12 Top of ridge, bears N. and S.; thence cross N. slope of rocky peak.

60.40 Top of spur, slopes N.  $10^{\circ}$  W.; descend 559 ft. over SW. slope,76.52 Drain, course N.  $10^{\circ}$  W.

79.92 The cor. of secs. 26, 27, 34 and 35.

Land, mountainous.

Soil, rocky.

Timber, ironwood, palo verde; and greasewood undergrowth.

NORTH, bet. secs. 26 and 27.

Over mountainous land.

.Subdivision of T. 6 N., R. 18 W.

|        |  |
|--------|--|
| Chains |  |
| 2.00   | Drain, course N. 70° W.; ascend 180 ft. over S. slope of spur.   |
| 7.86   | Top of spur, slopes W.; descend 268 ft. over N. Slope.   |
| 29.50  | Wash, 30 lks. wide, course SW.; ascend 95 ft. over S. slope.   |
| 35.50  | Top of spur, slopes W.; descend 91 ft. over N. slope.  |
| 40.00  | Point for the $\frac{1}{4}$ cor. of secs. 26 and 27.<br>Set an iron Post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 24 ins. in the ground, with brass cap mkd.  |
|        | $\frac{1}{4}$<br>S 26   S 25<br>1953<br>raise a mound of stone 2 ft. high, W. of cor.  |
| 44.80  | Wash, 30 lks. wide, course W.  |
| 50.70  | Ascend 20 ft. over S. slope of spur.   |
| 55.10  | Top of spur, slopes W.; descend 50 ft. over N. slope.  |
| 60.50  | Wash, 20 lks. wide, course S. 70° W.   |
| 77.00  | Wash, 20 lks. wide, course S. 70° W.   |
| 80.00  | Point for the cor. of secs. 22, 23, 26 and 27.<br>Set an iron post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 24 ins. in the ground, with brass cap mkd.  |
|        | T. 6 N R 18 W<br>S 22   S 23<br>S 27   S 26<br>1953<br>raise a mound of stone 2 ft. high, W. of cor.<br>Land, mountainous.<br>Soil, rocky.<br>Timber, ironwood, palo verde; and greasewood. undergrowth. |
|        | <b>EAST</b> on a random line bet. secs. 23 and 26.   |
| 40.00  | Set temp. $\frac{1}{4}$ sec. cor.  |
| 79.92  | Fall 14 lks. N. of cor. of secs. 23, 24, 25 and 26<br>Thence<br>N. 89° 54' W., bet. secs. 23 and 26.   |
| 3.92   | Drain, course N. 60° E.; ascend 204 ft. over SE. slope.  |
| 14.72  | Top of ridge, bears N. 40° E. and S. 20° W.; descend 30 ft. over W. slope.   |
| 19.72  | Drain, course N., ascend 241 ft. over E. slope.  |

## BOOK 4440

Subdivision of T. 6 N., R. 18 W.

| Chains |   | emarks |
|--------|---|--------|
| 33.32  | Top of spur, slopes N.; descend 34 ft. over W. slope.   |        |
| 36.12  | Braincourse N.; ascend 54 ft. over E. slope.  |        |
| 39.42  | Top of spur, slopes N.  |        |
| 39.96  | Point for the $\frac{1}{4}$ cor. of secs. 23 and 26.  |        |
|        | Set an iron post, 28 ins. long, 2 $\frac{1}{2}$ ins. diam., 8 ins. in the ground and mound to top with stone, with brass cap mkd. |        |
|        | S 23  |        |
|        | $\frac{1}{4}$   |        |
|        | S 26  |        |
|        | 1953  |        |
|        | Descend 716 ft. over cliffs and W. slope of spur.   |        |
| 79.92  | The cor. of secs. 22, 23, 26 and 27   |        |
|        | Land, mountainous.  |        |
|        | Soil, rocky.  |        |
|        | Timber, palo verde; and greasewood undergrowth.   |        |
|        | NORTH bet. secs. 22 and 23.   |        |
|        | Over rolling land and spurs.  |        |
| 14.00  | Wash, 20 lks. wide, course N. 60° W.  |        |
| 31.20  | Wash, 3 lks. wide, course W.  |        |
| 40.00  | Point for the $\frac{1}{4}$ cor. of secs. 22 and 23.  |        |
|        | Set an iron post, 28 ins. long, 2 $\frac{1}{2}$ ins. diam., 24 ins. in the ground, with brass cap mkd.                            |        |
|        | $\frac{1}{4}$   |        |
|        | S 22   S 23   |        |
|        | 1953  |        |
|        | raise a mound of stone 2 ft. high, W. of cor.   |        |
| 74.00  | Old road, bears NE. and SW.   |        |
| 76.40  | Wash, 50 lks. wide, course SW.  |        |
| 80.00  | Point for the cor. of secs. 14, 15, 22 and 23.  |        |
|        | Set an iron post, 28 ins. long, 2 $\frac{1}{2}$ ins. diam., 24 ins. in the ground with brass cap mkd.                             |        |
|        | T 6 N R 18 W  |        |
|        | S 15   S 14   |        |
|        | S 22   S 23   |        |
|        | 1953  |        |
|        | raise a mound of stone 2 ft. high, W. of cor.   |        |

Subdivision of T. 6 N., R. 18 W.

| Chains | Land, rolling.<br>Soil, gravelly.<br>Timber, ironwood, palo verde; and greasewood undergrowth.              |
|--------|---|
|        | EAST on a random line bet. secs. 14 and 23.   |
| 40.00  | Set temp. $\frac{1}{4}$ cor.  |
| 80.00  | Fall 18 lks. N. of cor. of secs. 13, 14, 23 and 24.   |
|        | Thence  |
|        | N. 89° 52' W., bet. secs. 14 and 23.  |
|        | Over rolling mountainous land; ascend 146 ft. over E. slope.  |
| 6.50   | Top of ridge, bears N. and S.; descend 262 ft. over W. slope.   |
| 18.80  | Wash, 20 lks. wide, course N. 20° W.; ascend 23 ft. over E. slope.  |
| 22.00  | Top of spur, slopes N.; descend 49 ft. over W. slope.   |
| 35.00  | Same wash, course SW.   |
| 40.00  | Point for the $\frac{1}{4}$ cor. of secs. 14 and 23.  |
|        | Set an iron post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 24 ins. in the ground, with brass cap mkd.       |
|        | S 14<br>—<br>S 23<br>1953   |
|        | raise a mound of stone 2 ft. high, N. of cor.   |
| 50.82  | Top of low spur, slopes SW.   |
| 55.00  | Wash, 20 lks. wide, course NW.  |
| 75.00  | Old road, bears NE. and SW.   |
| 76.80  | Wash, 50 lks. wide, course SW.  |
| 80.00  | The cor. of secs. 14, 15, 22 and 23.  |
|        | Land, rolling and mountainous.<br>Soil, rocky,<br>Timber, palo verde, ironwood; and greasewood undergrowth. |
|        | NORTH, bet. secs. 14 and 15.  |
|        | Over mountainous land.  |
| 2.20   | Top of low spur, slopes E.; descend 23 ft. over N. slope.   |
| 5.00   | Drain, course E.; ascend 43 ft. over SE. slope.   |
| 9.80   | Top of spur, slopes SW.; descend 77 ft. over NW. slope.   |
| 19.60  | Wash, 20 lks. wide, course SW.; ascend 134 ft. over SE. slope.  |

- 28.80 Top of spur, slopes SW.; descend 105 ft. over NW. slope.  
 35.80 Drain, course NW.; ascend 15 ft. over SW. slope.  
 39.33 Top of slope; descend 38 ft. over NE. slope.  
 40.00 Point for the  $\frac{1}{4}$  cor. of secs. 14 and 15.  
 Set an iron post, 28 ins. long,  $2\frac{1}{2}$  ins. diam., 24 ins. in the ground, with brass cap mkd.

$\frac{1}{4}$   
 S 15 | S 14  
 1953

raise a mound of stone 2 ft. high W. of corl

- 49.60 Wash, 20 lks. wide, course SW.  
 53.90 Old road, bears E. and W.  
 80.00 Point for the cor. of secs. 10, 11, 14 and 15.  
 Set an iron post, 28 ins. long,  $2\frac{1}{2}$  ins. diam., 24 ins. in the ground, with brass cap mkd.

T 6 N R 18 W  
 S 10 | S 11  
 S 15 | S 14  
 1953

Deposit a broken bottle alongside iron post.

Land, S.  $\frac{1}{2}$  mountainous, N.  $\frac{1}{2}$  rolling.  
 Soil, rocky, gravelly.  
 Timber, palo verde, ironwood and greasewood.

- EAST on a random line bet. secs. 11 and 14.  
 40.00 Set temp.  $\frac{1}{4}$  cor.  
 79.94 Fall 8 lks. N. of cor. of secs. 11, 12, 13 and 14.  
 Thence  
 N.  $89^{\circ} 57'$  W., bet. secs. 11 and 14.  
 Over mountainous land.  
 Ascend 77 ft. over SE. slope.  
 3.84 Top of spur, slopes SW.; descend 36 ft. over NW. slope.  
 7.64 Drain, course SE.; ascend 135 ft. over SE. slope.  
 18.14 Top of spur, slopes SW.; descend 264 ft. over SE. slope.

|   |   |      |      |      |      |
|---|---|------|------|------|------|
| <p>Chains<br/>39.97</p>                                       | <p>Point for the <math>\frac{1}{4}</math> cor. of secs. 11 and 14.</p> <p>Set an iron post, 28 ins. long, <math>2\frac{1}{2}</math> ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center;"> <p>S 11</p> <hr style="width: 50px; margin: 0 auto;"/> <p><math>\frac{1}{4}</math></p> <p>S 14</p> <p>1953.</p> </div> <p>raise a mound of stone 2 ft. high, N. of cor.</p>  |      |      |      |      |
| <p>55.64</p>  | <p>Wash, 20 lks. wide, course SW.</p>   |      |      |      |      |
| <p>64.44</p>  | <p>Old road, bears NE and SW.</p>   |      |      |      |      |
| <p>79.94</p>  | <p>The cor. of secs. 10, 11, 14 and 15.</p> <p>Land, E. <math>\frac{1}{2}</math> mountainous, W. <math>\frac{1}{2}</math> rolling.<br/>Soil, gravelly and rocky.<br/>Timber, ironwood, palo verde; and greasewood. undergrowth.</p>   |      |      |      |      |
| <p>NORTH, bet. secs. 10 and 11.</p> <p>Over rolling land.</p> |   |      |      |      |      |
| <p>12.00</p>  | <p>Wash, 30 lks. wide, course N. 60° W.</p>   |      |      |      |      |
| <p>17.89</p>  | <p>Top of detached spur, slopes E. and W.</p>   |      |      |      |      |
| <p>28.50</p>  | <p>Wash, 20 lks. wide, course W.</p>  |      |      |      |      |
| <p>40.00</p>  | <p>Point for the <math>\frac{1}{4}</math> cor. of secs. 10 and 11.</p> <p>Set an iron post, 28 ins. long, <math>2\frac{1}{2}</math> ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center;"> <p><math>\frac{1}{4}</math></p> <table style="margin: 0 auto;"> <tr> <td style="border-right: 1px solid black; padding: 0 5px;">S 10</td> <td style="padding: 0 5px;">S 11</td> </tr> </table> <p>1953</p> </div> <p>Deposit a broken bottle alongside iron post.</p>  | S 10 | S 11 |      |      |
| S 10  | S 11  |      |      |      |      |
| <p>57.00</p>  | <p>Wash, 30 lks. wide, course NW.</p>   |      |      |      |      |
| <p>60.50</p>  | <p>Wash, 20 lks. wide, course NW.</p>   |      |      |      |      |
| <p>68.29</p>  | <p>Top of spur, slopes W.</p>   |      |      |      |      |
| <p>80.00</p>  | <p>Point for the cor. of secs. 2, 3, 10 and 11.</p> <p>Set an iron post, 28 ins. long, <math>2\frac{1}{2}</math> ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center;"> <p>T 6 N R 18 W</p> <table style="margin: 0 auto;"> <tr> <td style="border-right: 1px solid black; padding: 0 5px;">S 3</td> <td style="padding: 0 5px;">S 2</td> </tr> <tr> <td style="border-right: 1px solid black; padding: 0 5px;">S 10</td> <td style="padding: 0 5px;">S 11</td> </tr> </table> <p>1953</p> </div> <p>Deposit a broken bottle alongside iron post.</p> | S 3  | S 2  | S 10 | S 11 |
| S 3   | S 2   |      |      |      |      |
| S 10  | S 11  |      |      |      |      |

Chains

202410

Land, rolling.  
Soil, rocky.  
Timber, palo verde; and greasewood undergrowth.

EAST, on a random line bet. secs. 2 and 11.

39.00 Set temp.  $\frac{1}{4}$  cor.

79.98 Fall 3 lks. N. of cor. of secs. 1, 2, 11 and 12.

Thence

N. 89° 59' W., bet. secs. 2 and 11.

Over mountainous land.

Ascend 52 ft. over NE. slope.

3.48 Top of spur, slopes S. 60° E.; continue to ascend 54 ft. over SE. slope.

11.95 Top of spur, slopes SE.; descend 29 ft. over SW. slope.

15.28 Drain, course SE.; ascend 133 ft. over E. slope.

23.38 Top of ridge, bears N. and S.; descend 111 ft. over W. slope.

27.98 Drain, course SW.; ascend 85 ft. over SE. slope.

32.58 Top of spur, slopes SW.; descend 175 ft. over NW. slope.

39.99 Point for the  $\frac{1}{4}$  cor. of secs. 2 and 11.

Set an iron post, 28 ins. long, 2 $\frac{1}{2}$  ins. diam., 14 ins. in ground to rock and mound with stone to top, with brass cap mkd.

S 2

$\frac{1}{4}$  ———

S 11

1953

40.48 Drain, course NW.; ascend 76 ft. over NE. slope of spur.

44.83 Top of spur, slopes N.; descend 122 ft. over NW. slope.

51.98 Drain, course NW.; ascend 46 ft. over NW. slope.

57.08 Top of spur, slopes SE.; descend 169 ft. over SW. slope.

71.58 Foot of slope, bears NW. and SE.

79.98 The cor. of secs. 2, 3, 10 and 11.

Land, mountainous.  
Soil, rocky.  
Timber, palo verde; and greasewood undergrowth.

N. 40° 02' W., bet. secs. 2 and 3.

Over rolling land, through scattering timber.

## Subdivision of T. 6 N., R. 18 W.

| Chains |   |
|--------|---|
| 19.70  | Wash, course S. 60° W.  |
| 30.50  | Wash, 20 lks. wide, course S. 50° W.  |
| 40.00  | Point for the $\frac{1}{4}$ cor. of secs. 2 and 3.  |
|        | Set an iron post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 24 ins. in the ground, with brass cap mkd.   |
|        | $\frac{1}{4}$<br>S 3   S 2<br>1953  |
|        | Deposit a broken bottle alongside iron post;  |
| 46.70  | Wash, 50 lks. wide, course N. 70° W.  |
| 60.00  | Point for the N. 1/16 cor. of secs. 2 and 3.  |
|        | Set an iron post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 24 ins. in the ground, with brass cap mkd.   |
|        | N 1/16<br>S 3   S 2<br>1953   |
|        | Deposit a broken bottle alongside iron post.  |
| 71.20  | Wash, 20 lks. wide, course N. 60° W.  |
| 80.00  | Point for the 1/16 cor. of secs. 2 and 3.   |
|        | Set an iron post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 24 ins. in the ground, with brass cap mkd.   |
|        | 1/16<br>S 3   S 2<br>80<br>1953   |
|        | Deposit a broken bottle alongside iron post.  |
| 88.33  | The cor. of secs. 2 and 3 on the N. bdy. of T. 6 N., R. 18 W., which is monumented with an iron post marked and witnessed as described in the official record.  |
|        | Land, rolling.<br>Soil, sandy.<br>Timber, palo verde, ironwood; and greasewood. undergrowth.  |
|        | From the cor. of secs. 3, 4, 33 and 34, T. 5 and 6 N., R. 18 W. which is monumented with an iron post marked and witnessed as described in the official record. |
|        | N. 0° 01' W., bet. secs. 33 and 34.   |
|        | Over rolling land, through scattering timber.   |

Chains

6.80 Wash, 40 lks. wide, course W.

33.50 Wash, 30 lks. wide, course W.

40.00 Point for the 1/4 cor. of secs. 33 and 34.

Set an iron post 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.

S 33 | S 34

1953

Deposit a broken bottle alongside iron post.

60.00 Wash, 20 lks. wide, course N. 60° W.

80.00 Point for the cor. of secs. 27, 28, 33 and 34.

Set an iron post, 28 ins. long, 2 1/2 ins. diam. 24 ins. in the ground, with brass cap mkd.

T 6 N R 18 W

S 28 | S 27

S 33 | S 34

1953

Deposit a broken bottle alongside iron post.

Land, rolling.

Soil, sandy, gravelly.

Timber, palo verde, ironwood, and greasewood. undergrowth.

EAST, on a random line bet. secs. 27 and 34.

40.00 Set temp. 1/4 cor.

80.02 Fall 8 lks. S. of cor. of secs. 26, 27, 34 and 35.

Thence

S. 89° 57' W., bet secs. 27 and 34.

Over rolling land, through scattering timber.

Descend 69 ft. along N. slope of spur.

5.02 Bottom of descent.

40.01 Point for the 1/4 cor. of secs 27 and 34.

Set an iron post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.

S 27

S 34

1953

Subdivision of T. 6 N., R. 18 W.

|        |  |      |  |      |      |  |      |
|--------|--|------|--|------|------|--|------|
| Chains | <p>raise a mound of stone 2 ft. high, N. of cor.</p> <p>80.02 The cor. of secs. 27, 28, 33 and 34.</p> <p>Land, rolling.<br/>Soil, sandy, gravelly.<br/>Timber, palo verde, ironwood; and greasewood. undergrowth.</p>   |      |  |      |      |  |      |
| 40.00  | <p>N. 0° 0' W., bet. secs. 27 and 28.</p> <p>Over rolling land, through scattering timber.</p> <p>Point for the <math>\frac{1}{4}</math> cor. of secs. 27 and 28.</p> <p>Set an iron post, 28 ins. long, <math>2\frac{1}{2}</math> ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;"> <math>\frac{1}{4}</math><br/> <table style="margin-left: auto; margin-right: auto;"> <tr> <td>S 28</td> <td> </td> <td>S 27</td> </tr> </table> <br/>                     1953                 </p> <p>Deposit a broken bottle alongside iron post.</p>  | S 28 |  | S 27 |      |  |      |
| S 28   |  | S 27 |  |      |      |  |      |
| 43.00  | Wash, 30 lks. wide, course N. 60° W.   |      |  |      |      |  |      |
| 65.00  | Wash, 30 lks. wide, course NW.   |      |  |      |      |  |      |
| 71.20  | Wash, 50 lks. wide, course S. 60° W.   |      |  |      |      |  |      |
| 80.00  | <p>Point for the cor. of secs. 21, 22, 27 and 28.</p> <p>Set an iron post, 28 ins. long, <math>2\frac{1}{2}</math> ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">                     T 6; N R 18 W<br/> <table style="margin-left: auto; margin-right: auto;"> <tr> <td>S 21</td> <td> </td> <td>S 22</td> </tr> <tr> <td>S 28</td> <td> </td> <td>S 27</td> </tr> </table> <br/>                     1953                 </p> <p>Deposit a broken bottle alongside iron post.</p> <p>Land, rolling.<br/>Soil, sandy.<br/>Timber, ironwood, palo verde; and greasewood. undergrowth.</p> | S 21 |  | S 22 | S 28 |  | S 27 |
| S 21   |  | S 22 |  |      |      |  |      |
| S 28   |  | S 27 |  |      |      |  |      |
| 40.00  | <p>EAST, on a random line bet. secs. 22 and 27.</p> <p>Set temp. <math>\frac{1}{4}</math> cor.</p>   |      |  |      |      |  |      |
| 80.00  | <p>Fall 11 lks, S. of cor. of secs. 22, 23, 26 and 27.</p> <p>Thence</p> <p>S. 89° 55' W., bet. secs. 22 and 27.</p> <p>Over rolling land, through scattering timber.</p>  |      |  |      |      |  |      |
| 27.80  | Wash, 20 lks. wide, course N. 50° W.   |      |  |      |      |  |      |

## Subdivision of T. 6 N., R. 18 W.

## Chains

40.00 Point for the  $\frac{1}{4}$  cor. of secs. 22 and 27.  
Set an iron post, 28 ins. long,  $2\frac{1}{2}$  ins. diam., 24 ins. in the ground, with brass cap mkd.

S 22

$\frac{1}{4}$

S 27

1953

raise a mound of stone 2 ft. high, W. of cor.

73.60 Wash, 40 lks. wide, course SW.

80.00 The cor. of secs. 21, 22, 27 and 28.

Land, rolling.

Soil, sandy, gravelly.

Timber, palo verde, ironwood; and greasewood. undergrowth.

N.  $0^{\circ} 01'$  W., bet. secs 21 and 22.

Over rolling land and spurs, through scattering timber.

0.50 Old road, bears NE. and SW.

40.00 Point for the  $\frac{1}{4}$  cor. of secs. 21 and 22.

Set an iron post, 28 ins. long,  $2\frac{1}{2}$  ins. diam., 24 ins. in the ground, with brass cap mkd.

$\frac{1}{4}$

S 21 | S 22

1953

45.00 Ascend 36 ft. over S. slope of spur.

52.00 Top of spur, slopes W.; descend 29 ft. over N. slope.

60.00 Wash, 20 lks. wide, course W.

72.60 Wash, 20 lks. wide, course SW.

80.00 Point for the cor. of secs. 15, 16, 21 and 22.

Set an iron post. 28 ins. long,  $2\frac{1}{2}$  ins. diam., 24 ins. in the ground, with brass cap mkd.

T 6 N R 18 W

S 16 | S 15

S 21 | S 22

1953

Deposit a broken bottle alongside iron post.

## BOOK 4440

Subdivision of T. 6 N., R. 18 W.

| Chains |   |
|--------|---|
|        | <p>Land, rolling, spurs.<br/>Soil, gravelly, sandy.<br/>Timber, palo verde, ironwood; and greasewood undergrowth.</p>   |
|        | <p>EAST, on a random line bet. secs 15 and 22.</p>  |
| 40.00  | Set temp $\frac{1}{4}$ cor.   |
| 79.96  | <p>Run 6 lks. S. of cor. of secs. 14, 15, 22 and 23.<br/>Thence<br/>S. <math>89^{\circ} 57'</math> W., bet. secs. 15 and 22<br/>Over rolling land and spurs, through scattering timber.<br/>Ascend 93 ft. over SE. slope.</p> |
| 9.56   | Top of spur, slopes SW.; descend 112 ft. over NW. slope.  |
| 24.96  | Bottom of descent.  |
| 30.96  | Wash, 20 lks. wide, course S. $70^{\circ}$ W.   |
| 38.46  | Wash, 50 lks. wide, course NW.  |
| 39.98  | Point for the $\frac{1}{4}$ cor. of secs. 15 and 22.  |
|        | <p>Set an iron post, 28 ins. long, <math>2\frac{1}{2}</math> ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">S 15.<br/><math>\frac{1}{4}</math> ———<br/>S 22<br/>1953</p>           |
|        | raise a mound of stone 2 ft. high, N. of cor.   |
| 74.96  | Wash, 20 lks. wide, course SW.  |
| 79.96  | The cor. of secs. 15, 16, 21 and 22:  |
|        | <p>Land, <math>\frac{1}{2}</math> rolling, <math>\frac{1}{2}</math> spurs.<br/>Soil, <math>\frac{1}{2}</math> sandy, <math>\frac{1}{2}</math> rocky.<br/>Timber, palo verde, ironwood; and greasewood undergrowth.</p>        |
|        | <p>N. <math>60^{\circ}</math> O. <math>1\frac{1}{2}</math> W., bet 15 secs. 15 and 16.</p>  |
|        | Over rolling land and spurs, through scattering timber,   |
| 36.00  | Wash, 50 lks. wide, course N. $50^{\circ}$ W.   |
| 40.00  | Point for the $\frac{1}{4}$ cor. of secs. 15 and 16.  |
|        | <p>Set an iron post, 28 ins. long, <math>2\frac{1}{2}</math> ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;"><math>\frac{1}{4}</math><br/>S 16   S 15<br/>1953</p>                  |

Chains

Deposit a broken bottle alongside iron post.

Ascend 20 ft. over S. slope of detached spur.

41.50 Top of detached spur, bears E. and W.; descend 29 ft. over N. slope.

80.00 Point for the cor. of secs. 9, 10, 15 and 16.

Set an iron post, 28 ins. long, 2 $\frac{1}{2}$  ins. diam., 2 $\frac{1}{4}$  ins. in the ground, with brass cap mkd.

T 6 N R 18 W

S 9 | S 10

S 16 | S 15

1953

Deposit a broken bottle alongside iron post.

Land, rolling.

Soil, sandy, gravelly.

Timber, palo verde and ironwood.

EAST, on a random line bet. secs. 10 and 15.

40.00 Set temp.  $\frac{1}{4}$  cor.

79.90 Fall 4 lks. S. of cor. of secs. 10, 11, 14 and 15.

Thence

S. 89° 58' W., bet. secs. 10 and 15.

Over rolling land, through scattering timber.

39.95 Point for the  $\frac{1}{4}$  cor. of secs. 10 and 15.Set an iron post, 28 ins. long, 2 $\frac{1}{2}$  ins. diam., 2 $\frac{1}{4}$  ins. in the ground, with brass cap mkd.

S 10

 $\frac{1}{4}$  ———

S 15

1953

Deposit a broken bottle alongside iron post.

79.90 The cor. of secs. 9, 10, 15 and 16.

Land, rolling.

Soil, sandy.

Timber, palo verde; and greasewood undergrowth.

N.0° 01' W., bet. secs. 9 and 10.

Over rolling land, through scattering timber.

## Subdivision of T. 6 N., R. 18 W.

| Chains |   |
|--------|---|
| 40.00  | <p>Point for the <math>\frac{1}{4}</math> cor. secs. 9 and 10.</p> <p>Set an iron post 28 ins. long, <math>2\frac{1}{2}</math> ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;"><math>\frac{1}{4}</math></p> <p style="text-align: center;">S 9   S 10</p> <p style="text-align: center;">1953</p> <p>Deposit a broken bottle alongside iron post.</p>   |
| 52.55  | Wash, 50 lks. wide, course SW.  |
| 79.00  | <p>Point for the witness, cor. of secs. 3, 4, 9 and 10.</p> <p>Set an iron post, 28 ins. long, <math>2\frac{1}{2}</math> ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T 6 N R 18 W</p> <p style="text-align: center;">W C</p> <p style="text-align: center;">S 4   S 3</p> <p style="text-align: center;">S 9   S 10</p> <p style="text-align: center;">1953</p> <p>Deposit a broken bottle alongside iron post.</p> |
| 80.00  | <p>True point for cor. secs. 3, 4, 9 and 10, falls in wash, 60 lks. wide, course N. <math>80^\circ</math> W.</p> <p>Land, rolling.</p> <p>Soil, sandy.</p> <p>Timber, palo verde, ironwood, and greasewood undergrowth.</p>   |
| 40.00  | EAST, on a random line bet. secs. 3 and 10.   |
| 79.94  | <p>Set temp. <math>\frac{1}{4}</math> cor.</p> <p>Intersect cor. of secs. 2, 3, 10 and 11.</p> <p>Thence</p> <p>WEST, bet. secs. 3 and 10.</p> <p>Over rolling land, through scattering timber.</p>   |
| 39.97  | <p>Point for the <math>\frac{1}{4}</math> cor. of secs. 3 and 10.</p> <p>Set an iron post, 28 ins. long, <math>2\frac{1}{2}</math> ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">S 3</p> <p style="text-align: center;"><math>\frac{1}{4}</math> ———</p> <p style="text-align: center;">S 10</p> <p style="text-align: center;">1953</p> <p>Deposit a broken bottle alongside iron post.</p>                          |
| 40.04  | Wash, 15 lks. wide, course SW.  |
| 54.94  | Left bank of wash, bears NE. and S. $30^\circ$ W.   |

## Subdivision of T. 6 N., R. 18 W.

## Chains

67.94 Junction of three washes, course W. from NE., E. and SE., thence along bed of wash.

79.94 True point for the cor. of secs. 3, 4, 9 and 10.

Land, rolling.

Soil, gravelly.

Timber, palo verde, ironwood; and greasewood. undergrowth.

N. 0° 05' W., bet. secs. 3 and 4.

Over rolling land, through scattering timber.

0.30 Right bank of wash.

33.10 Wash, 30 lks. wide, course NW.

40.00 Point for the  $\frac{1}{4}$  cor. of secs. 3 and 4.

Set an iron post, 28 ins. long,  $2\frac{1}{2}$  ins. diam., 24 ins. in the ground, with brass cap mkd.

$\frac{1}{4}$   
S 4 | S 3

1953

Deposit a broken bottle alongside iron post.

55.40 Wash, 40 lks. wide, course NW.

60.00 Point for the N.  $\frac{1}{16}$  cor. of secs. 3 and 4.

Set an iron post, 28 ins. long,  $2\frac{1}{2}$  ins. diam., 24 ins. in the ground, with brass cap mkd.

N  $\frac{1}{16}$   
S 4 | S 3

1953

Deposit a broken bottle alongside iron post.

79.00 Wash, 30 lks. wide, course NW.

80.00 Point for the  $\frac{1}{16}$  cor. secs. 3 and 4.

Set an iron post, 28 ins. long,  $2\frac{1}{2}$  ins. diam., 24 ins. in the ground, with brass cap mkd.

$\frac{1}{16}$   
S 4 | S 3

80  
1953

Deposit a broken bottle alongside iron post.


## Subdivision of T. 6 N., R. 18 W.

| Chains |  |      |      |      |      |
|--------|--|------|------|------|------|
| 88.34  | <p>The cor. of secs. 3 and 4 on the N. bdy. of T. 6 N., R. 18 W., which is monumented with an iron post, marked and witnessed as described in the official record.</p> <p>Land, rolling.<br/>Soil, gravelly.<br/>Timber, palo verde, ironwood; and greasewood undergrowth.</p>   |      |      |      |      |
| 40.00  | <p>From the cor. of secs. 4, 5, 32 and 33, T. 5 and 6 N., R. 18 W. which is monumented with an iron post marked and witnessed as described in the official record.</p> <p>N. 0° 01' W., bet. secs. 32 and 33.</p> <p>Over rolling land, through scattering timber.</p> <p>Point for the <math>\frac{1}{4}</math> cor. of secs. 32 and 33.</p> <p>Set an iron post, 28 ins. long, <math>2\frac{1}{2}</math> ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;"><math>\frac{1}{4}</math></p> <p style="text-align: center;">S 32   S 33</p> <p style="text-align: center;">1953</p> <p>Deposit a broken bottle alongside iron post.</p> |      |      |      |      |
| 80.00  | <p>Point for the cor. of secs. 28, 29, 32 and 33.</p> <p>Set an iron post, 28 ins. long, <math>2\frac{1}{2}</math> ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T 6 N R 18 W</p> <table border="1" style="margin-left: auto; margin-right: auto;"> <tr> <td style="padding: 2px;">S 29</td> <td style="padding: 2px;">S 28</td> </tr> <tr> <td style="padding: 2px;">S 32</td> <td style="padding: 2px;">S 33</td> </tr> </table> <p style="text-align: center;">1953</p> <p>Deposit a broken bottle alongside iron post.</p> <p>Land, rolling.<br/>Soil, sandy.<br/>Timber, palo verde; and greasewood undergrowth.</p>        | S 29 | S 28 | S 32 | S 33 |
| S 29   | S 28   |      |      |      |      |
| S 32   | S 33   |      |      |      |      |
| 40.00  | <p>EAST, on a random line bet. secs. 28 and 33.</p> <p>Set temp. <math>\frac{1}{4}</math> cor.</p>   |      |      |      |      |
| 79.98  | <p>Intersect cor. of secs. 27, 28, 33 and 34.</p> <p>Thence</p> <p>WEST, bet. secs. 28 and 33.</p> <p>Over rolling land, through scattering timber.</p>  |      |      |      |      |

Chains  
39.99

Point for the  $\frac{1}{4}$  cor. of secs. 28 and 33.

Set an iron post, 28 ins. long,  $2\frac{1}{2}$  ins. diam., 24 ins. in the ground, with brass cap mkd.



Deposit a broken bottle alongside iron post.

79.98

The cor. of secs. 28, 29, 32 and 33.

Land, rolling.  
Soil, sandy.  
Timber, palo verde; and greasewood undergrowth.


40.00

N. 0° 01' W., bet. secs. 28 and 29.

Over rolling land, through scattering timber.

Point for the  $\frac{1}{4}$  cor. of secs. 28 and 29.

Set an iron post, 28 ins. long,  $2\frac{1}{2}$  ins. diam., 24 ins. in the ground, with brass cap mkd.




Deposit a broken bottle alongside iron post.

80.00

Point for the cor. of secs. 20, 21, 28 and 29.

Set an iron post, 28 ins. long,  $2\frac{1}{2}$  ins. diam., 24 ins. in the ground, with brass cap mkd.



Deposit a broken bottle alongside iron post.

Land, rolling.  
Soil, sandy.  
Timber, palo verde; and greasewood undergrowth.

40.00

EAST, on a random line bet. secs. 21 and 28.

Set temp.  $\frac{1}{4}$  cor.

79.94

Fall 4 lks. N. of cor. of secs. 21, 22, 27 and 28.

Set temp.  $\frac{1}{4}$  cor.

Subdivision of T. 6 N., R. 18 W.

|        |   |
|--------|---|
| Chains | <p>Thence</p> <p>N. 89° 58' W., bet. secs. 21 and 28.</p> <p>Over rolling land, through scattering timber.</p> <p>39.97 Point for the <math>\frac{1}{4}</math> cor. of secs. 21 and 28.</p> <p>Set an iron post, 28 ins. long, <math>2\frac{1}{2}</math> ins. diam., 24 ins. in the ground, with brass cap mkd.</p> |
|        | $\begin{array}{c} S\ 21 \\ \hline S\ 28 \\ 1953 \end{array}$  |
|        | <p>Deposit a broken bottle alongside iron post.</p>   |
| 62.74  | <p>Wash, 50 lks. wide, course N. 50° W.</p>   |
| 79.94  | <p>The cor. of secs. 20, 21, 28 and 29.</p>   |
|        | <p>Land, rolling.<br/>Soil, sandy, gravelly.<br/>Timber, palo verde, ironwood; and greasewood undergrowth.</p>  |
|        | <p>N. 0° 01' W., bet. secs. 20 and 21.</p>  |
|        | <p>Over rolling land, through scattering timber.</p>  |
| 9.80   | <p>Wash, 50 lks. wide, course N. 60° W.</p>   |
| 40.00  | <p>Point for the <math>\frac{1}{4}</math> cor. of secs. 20 and 21.</p>  |
|        | <p>Set an iron post, 28 ins. long, <math>2\frac{1}{2}</math> ins. diam., 24 ins. in the ground, with brass cap mkd.</p>   |
|        | $\begin{array}{c} \frac{1}{4} \\ S\ 20 \mid S\ 21 \\ 1953 \end{array}$  |
|        | <p>Deposit a broken bottle alongside iron post.</p>   |
| 53.60  | <p>Wash, 30 lks. wide, course W.</p>  |
| 80.00  | <p>Point for the cor. of secs. 16, 17, 20 and 21.</p>   |
|        | <p>Set an iron post, 28 ins. long, <math>2\frac{1}{2}</math> ins. diam., 24 ins. in the ground, with brass cap mkd.</p>   |
|        | <p>T. 6 N. R. 18 W.</p>   |
|        | $\begin{array}{c} S\ 17 \mid S\ 16 \\ \hline S\ 20 \mid S\ 21 \end{array}$  |
|        | <p>1953</p>   |
|        | <p>Deposit a broken bottle alongside iron post.</p>   |
|        | <p>Land, rolling,<br/>Soil, sandy.<br/>Timber, palo verde, ironwood; and greasewood undergrowth.</p>  |

## Subdivision of T. 6 N., R. 18 W.

## Chains

EAST, on a random line bet. secs. 16 and 21.

40.00 Set temp.  $\frac{1}{4}$  cor.

79.98 Fall 5 lks. N, of cor. of secs. 15, 16, 21, and 22.

Thence

N. 89°58' W., bet. secs. 16 and 21,

Over gently rolling land, through scattering timber.

39.99 Point for the  $\frac{1}{4}$  cor. of secs. 16 and 21.Set an iron post, 28 ins. long,  $2\frac{1}{2}$  ins. diam., 24 ins. in the ground, with brass cap mkd.

S 16

 $\frac{1}{4}$ 

S 21

1953

79.98

Deposit a broken bottle alongside iron post.  
The cor. of secs. 16, 17, 20, and 21.

Land, gently rolling.

Soil, sandy.

Timber, palo verde; and greasewood undergrowth.

N. 0°01' W., bet. secs. 16 and 17.

Over rolling land, through scattering timber.

40.00 Point for the  $\frac{1}{4}$  cor. of secs. 16 and 17.Set an iron post, 28 ins. long,  $2\frac{1}{2}$  ins. diam., 24 ins. in the ground, with brass cap mkd. $\frac{1}{4}$ 

S 17 | S 16

1953

Deposit a broken bottle alongside iron post.

45.85 Wash, 50 lks. wide, course W.

65.00 Ascend 32 ft. over S. slope of detached spur.

66.84 Top of spur, slopes E. and W., descend 54 ft. over N. slope.

69.00 Foot of slope, continue over rolling land.

80.00 Point for the cor. of secs. 8, 9, 16, and 17.

Set an iron post, 28 ins. long,  $2\frac{1}{2}$  ins. diam., 24 ins. in the ground, with brass cap mkd.

T 6 N R 18 W

S 8 | S 9

S 17 | S 16

1953

Deposit a broken bottle alongside iron post.

Subdivision of T. 6 N., R. 18 W.

|        |  |
|--------|--|
| Chains | Land, rolling.<br>Soil, sandy, gravelly.<br>Timber, ironwood, palo verde; and greasewood undergrowth.  |
|        | EAST, on a random line bet. secs. 9 and 16.  |
| 40.00  | Set temp. $\frac{1}{4}$ cor.   |
| 79.96  | Fall 4 lks. N. of cor. of secs. 9, 10, 15, and 16.<br><br>Thence<br><br>N. 89°58' W., bet. secs. 9 and 16.<br><br>Over rolling land, through scattering timber.  |
| 39.98  | Point for the $\frac{1}{4}$ cor. of secs. 9 and 16.<br><br>Set an iron post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 24 ins. in the ground, with brass cap mkd.<br><br>S 9<br>$\frac{1}{4}$ ———<br>S 16<br><br>1953 |
| 79.96  | Deposit a broken bottle alongside iron post.<br><br>The cor. of secs. 8, 9, 16 and 17.<br><br>Land, rolling.<br>Soil, sandy, gravelly.<br>Timber, palo verde; and greasewood undergrowth.                            |
|        | N. 0°01' W., bet. secs. 8 and 9.<br><br>Over rolling land, through scattering timber.  |
| 40.00  | Point for the $\frac{1}{4}$ cor. of secs. 8 and 9.<br><br>Set an iron post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 24 ins. in the ground, with brass cap mkd.<br><br>$\frac{1}{4}$<br>S 8   S 9<br><br>1953        |
| 40.90  | Deposit a broken bottle alongside iron post.<br><br>Wash 50 lks. wide, course S. 80° W.  |
| 80.00  | Point for the cor. of secs. 4, 5, 8, and 9.<br><br>Set an iron post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 24 ins. in the ground, with brass cap mkd.<br><br>T 6 N R 18 W.<br>S 5   S 4<br>S 8   S 9<br><br>1953  |
|        | Deposit a broken bottle alongside iron post.   |

## Chains

Deposit a broken bottle alongside iron post.

Land, rolling.

Soil, sandy.

Timber, palo verde; and greasewood undergrowth.

EAST, on a random line, bet. secs. 4 and 9.

40.00 Set temp.  $\frac{1}{4}$  cor.

79.92 Intersect the cor. of secs. 3, 4, 9 and 10.

Thence

WEST, bet. secs. 4 and 9.

Over gently rolling land, along bed of wash.

1.12 Leave left bank of wash, bears N. 70° W and S. 80° E.

39.96 Point for the  $\frac{1}{4}$  cor. of secs. 4 and 9.

Set an iron post, 28 ins. long,  $2\frac{1}{2}$  ins. diam., 24 ins. in the ground, with brass cap mkd.

S 4

$\frac{1}{4}$

S 9

1953

Deposit a broken bottle alongside iron post.

79.92 The cor. of secs. 4, 5, 8 and 9.

Land, gently rolling.

Soil, sandy.

Timber, palo verde; and greasewood undergrowth.

N. 0° 05' W., bet. secs. 4 and 5.

Over rolling land.

40.00 Point for the  $\frac{1}{4}$  cor. of secs. 4 and 5.

Set an iron post, 28 ins. long,  $2\frac{1}{2}$  ins. diam., 24 ins. in the ground, with brass cap mkd.

$\frac{1}{4}$

S 5 | S 4

1953

Deposit a broken bottle alongside iron post.

60.00 Point for the N.  $\frac{1}{16}$  cor. of secs. 4 and 5.

Set an iron post, 28 ins. long,  $2\frac{1}{2}$  ins. diam., 24 ins. in the ground, with brass cap mkd.

Subdivision of T. 6 N., R. 18 W.

| Chains | cont'd  |
|--------|---|
| 80.00  | <p style="text-align: center;">N 1/16</p> <p style="text-align: center;">S 5   S 4</p> <p style="text-align: center;">1953</p> <p>Deposit a broken bottle alongside iron post.</p> <p>Point for the 1/16 cor. of secs 4 and 5.</p> <p>Set an iron post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p>  |
| 88.34  | <p style="text-align: center;">1/16</p> <p style="text-align: center;">S 5   S 4</p> <p style="text-align: center;">80</p> <p style="text-align: center;">1953</p> <p>Deposit a broken bottle alongside iron post.</p> <p>The cor. of secs. 4 and 5 on the N. bdy. of T, 6 N., R. 18 W., which is monumented with an iron post marked and witnessed as described in the official record.</p> <p>Land, gently rolling.<br/>Soil, sandy.<br/>Timber, none.<br/>Undergrowth, greasewood.</p>   |
| 40.00  | <p>From the cor. of secs. 5, 6, 31 and 32, T. 5 and 6 N., R. 18 W. which is monumented with an iron post marked and witnessed as described in the official record.</p> <p>N. 0° 02' W., bet. secs. 31 and 32.</p> <p>Over rolling land, through scattering timber.</p> <p>Point for the 1/4 cor. of secs. 31 and 32.</p> <p>Set an iron post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p>  |
| 80.00  | <p style="text-align: center;">1/4</p> <p style="text-align: center;">S 31   S 32</p> <p style="text-align: center;">1953</p> <p>Deposit a broken bottle alongside iron post.</p> <p>Point for the cor. of secs. 29, 30, 31 and 32.</p> <p>Set an iron post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T 6 N R 18 W</p> <p style="text-align: center;">S 30   S 29</p> <p style="text-align: center;">S 31   S 32</p> <p style="text-align: center;">1953</p> |

|        |   |
|--------|---|
| Chains | <p>Deposit a broken bottle alongside iron post.</p> <p>Land, rolling.<br/>Soil, sandy.<br/>Timber, palo verde, ironwood; and greasewood undergrowth.</p>  |
| 39.99  | <p>From the cor. of secs 28, 29, 32 and 33.</p> <p>WEST, bet. secs. 29 and 32.</p> <p>Over rolling land, through scattering timber.</p> <p>Point for the <math>\frac{1}{4}</math> cor. of secs. 29 and 32.</p> <p>Set an iron post, 28 ins. long, 2<math>\frac{1}{2}</math> ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">S 29<br/><math>\frac{1}{4}</math> ———<br/>S 32<br/>1953</p> <p>Deposit a broken bottle alongside iron post.</p> |
| 79.98  | <p>The cor. of secs. 29, 30, 31 and 32.</p> <p>Land, rolling.<br/>Soil, sandy.<br/>Timber, palo verde; and greasewood undergrowth.</p>  |
| 40.00  | <p>WEST, bet. secs. 30 and 31.</p> <p>Over rolling land, through scattering timber.</p> <p>Point for the <math>\frac{1}{4}</math> cor. of secs. 30 and 31.</p> <p>Set an iron post, 28 ins. long, 2<math>\frac{1}{2}</math> ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">S 30<br/><math>\frac{1}{4}</math> ———<br/>S 31<br/>1953</p> <p>Deposit a broken bottle alongside iron post.</p>   |
| 79.26  | <p>The cor. of secs. 25, 30, 31 and 36 on the W. bdy. of T. 6 N., R 18 W. which is monumented with an iron post marked and witnessed as described in the official record.</p> <p>Land, rolling.<br/>Soil, sandy.<br/>Timber, palo verde, ironwood; and greasewood undergrowth.</p>  |
| 40.00  | <p>N. 0° 02' W., bet. secs. 29 and 30.</p> <p>Over rolling land, through scattering timber.</p> <p>Point for the <math>\frac{1}{4}</math> cor. of secs. 29 and 30.</p>  |

Subdivision of T. 6 N., R. 18 W.

|                            |   |
|----------------------------|---|
| <p>Chains</p> <p>80.00</p> | <p>Set an iron post, 28 ins. long, 2<math>\frac{1}{2}</math> ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;"> <math>\frac{1}{4}</math><br/>             S 30   S 29<br/>             1953         </p> <p>Deposit a broken bottle alongside iron post.</p> <p>Point for the cor. of secs. 19, 20, 29 and 30.</p> <p>Set an iron post, 28 ins. long, 2<math>\frac{1}{2}</math> ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">             T 6 N R 18 W<br/>             S 19   S 20<br/>             S 30   S 29<br/>             1953         </p> <p>Deposit a broken bottle alongside iron post.</p> <p>Land, rolling.<br/>             Soil, sandy.<br/>             Timber, palo verde; and greasewood undergrowth.</p> |
| <p>40.00</p> <p>80.00</p>  | <p>From the cor. of secs. 20, 21, 28 and 29.</p> <p>S. 89° 58' W., bet. secs. 20 and 29.</p> <p>Point for the <math>\frac{1}{4}</math> cor. of secs. 20 and 29.</p> <p>Set an iron post, 28 ins. long, 2<math>\frac{1}{2}</math> ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">             S 20<br/> <math>\frac{1}{4}</math> ———<br/>             S 29<br/>             1953         </p> <p>Deposit a broken bottle alongside iron post.</p> <p>The cor. of secs. 19, 20, 29 and 30.</p> <p>Land, rolling.<br/>             Soil, sandy.<br/>             Timber, palo verde; and greasewood undergrowth.</p>  |
| <p>40.00</p>               | <p>WEST, bet. secs. 19 and 30.</p> <p>Over rolling land, through scattering timber.</p> <p>Point for the <math>\frac{1}{4}</math> cor. of secs. 19 and 30.</p>  |

## Subdivision of T. 6 N., R. 18 W.

Chains

Set an iron post, 28 ins. long,  $2\frac{1}{2}$  ins. diam., 24 ins. in the ground, with brass cap mkd.

S 19

 $\frac{1}{4}$ 

S 30

1953

Deposit a broken bottle alongside iron post.

79.18

The cor. of secs. 19, 24, 25 and 30 on the W. bdy. of T. 6 N., R. 18 W., which is monumented with an iron post marked and witnessed as described in the official record.

Land, rolling.

Soil, sandy.

Timber, palo verde; and greasewood. undergrowth.

N.  $0^{\circ} 02'$  W., bet. secs. 19 and 20.

Over rolling land, through scattering timber.

24.10

Wash, 40 lks. wide, course S.  $60^{\circ}$  W.

40.00

Point for the  $\frac{1}{4}$  cor. of secs. 19 and 20.

Set an iron post, 28 ins. long,  $2\frac{1}{2}$  ins. diam., 24 ins. in the ground, with brass cap mkd.

 $\frac{1}{4}$ 

S 19 | S 20

1953

Deposit a broken bottle alongside iron post.

80.00

Point for the cor. of secs. 17, 18, 19 and 20.

Set an iron post, 28 ins. long,  $2\frac{1}{2}$  ins. diam., 24 ins. in the ground, with brass cap mkd.

T 6 N R 18 W

S 18 | S 17

S 19 | S 20

1953

Deposit a broken bottle alongside iron post.

Land, rolling.

Soil, sandy.

Timber, palo verde; and greasewood. undergrowth.

From the cor. of secs. 16, 17, 20 and 21.

S.  $39^{\circ} 59'$  W., bet. secs. 17 and 20.

Over rolling land, through scattering timber.

Subdivision of T. 6 N., R. 18 W.

| Chains |   |
|--------|---|
| 39.98  | <p>Point for the <math>\frac{1}{4}</math> cor. of secs. 17 and 20.</p> <p>Set an iron post, 28 ins. long, <math>2\frac{1}{2}</math> ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">S 17<br/> <math>\frac{1}{4}</math> ———<br/>                     S 20<br/>                     1953</p> <p>Deposit a broken bottle alongside iron post.</p>  |
| 79.96  | <p>The cor. of secs. 17, 18, 19 and 20.</p> <p>Land, rolling.<br/>                     Soil, sandy.<br/>                     Timber, pale-verde, and greasewood. undergrowth.</p>   |
| 40.00  | <p>N. 89° 59' W., bet. secs. 18 and 19.</p> <p>Over gently rolling land.</p> <p>Point for the <math>\frac{1}{4}</math> cor. of secs. 18 and 19.</p> <p>Set an iron post, 28 ins. long, <math>2\frac{1}{2}</math> ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">S 18<br/> <math>\frac{1}{4}</math> ———<br/>                     S 19<br/>                     1953</p> <p>Deposit a broken bottle alongside iron post.</p>                     |
| 79.14  | <p>The cor. of secs. 13, 18, 19 and 24 on the W. bdy. T. 6 N., R. 18 W. which is monumented with an iron post, marked and witnessed as described in the official record.</p> <p>Land, gently rolling.<br/>                     Soil, sandy.<br/>                     Timber, none.<br/>                     Undergrowth, greasewood.</p>  |
| 40.00  | <p>N. 0° 02' W., bet. secs. 17 and 18.</p> <p>Over gently rolling land, through scattering timber.</p> <p>Point for the <math>\frac{1}{4}</math> cor. of secs. 17 and 18.</p> <p>Set an iron post, 28 ins. long, <math>2\frac{1}{2}</math> ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;"> <math>\frac{1}{4}</math><br/>                     S 18   S 17<br/>                     1953</p> <p>Deposit a broken bottle alongside iron post.</p> |

Chains

60.00

Drain, course W.

80.00

Point for the cor. of secs. 7, 8, 17 and 18.

Set an iron post, 28 ins. long,  $2\frac{1}{2}$  ins. diam., 24 ins. in the ground, with brass cap mkd.

T 6 N R 18 W

S 7 | S 8

S 18 | S 17

1953

Deposit a broken bottle alongside iron post.

Land, gently rolling.

Soil, sandy.

Timber, palo verde.

Undergrowth, greasewood.

From the cor. of secs. 8, 9, 16 and 17.

S.  $89^{\circ} 58'$  W., bet. secs. 8 and 17.

Over gently rolling land.

39.98

Point for the  $\frac{1}{4}$  cor. of secs. 8 and 17.Set an iron post, 28 ins. long,  $2\frac{1}{2}$  ins. diam., 24 ins. in the ground, with brass cap mkd.

S 8

 $\frac{1}{4}$ 

S 17

1953

Deposit a broken bottle alongside iron post.

79.96

The cor. of secs. 7, 8, 17 and 18.

Land, rolling.

Soil, sandy.

Timber, palo verde.

Undergrowth, greasewood.

S.  $89^{\circ} 57'$  W., bet. secs. 7 and 18.

Over gently rolling land.

40.00

Point for the  $\frac{1}{4}$  cor. of secs. 7 and 18.Set an iron post, 28 ins. long,  $2\frac{1}{2}$  ins. diam., 24 ins. in the ground, with brass cap mkd.

S 7

 $\frac{1}{4}$ 

S 18

1953

Subdivision of T. 6 N., R. 18 W.

|                            |   |     |     |     |     |
|----------------------------|---|-----|-----|-----|-----|
| <p>Chains</p> <p>79.04</p> | <p>Deposit a broken bottle alongside iron post.</p> <p>The cor. of secs. 7, 12, 13 and 18 on the W. bdy. T. 6 N., R. 18 W., which is monumented with an iron post, marked and witnessed as described in the official record.</p> <p>Land, rolling.<br/>Soil, sandy.<br/>Timber, none.<br/>Undergrowth, greasewood.</p>  |     |     |     |     |
| <p>40.00</p>               | <p>N. 0° 02' W., bet secs. 7 and 8.</p> <p>Over gently rolling land.</p> <p>Point for the <math>\frac{1}{4}</math> cor. of secs. 7 and 8.</p> <p>Set an iron post, 28 ins. long, <math>2\frac{1}{2}</math> ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center;"> <math>\frac{1}{4}</math><br/> <table border="1" style="margin: auto;"> <tr> <td>S 7</td> <td>S 8</td> </tr> </table> <p>1953</p> </div> <p>Deposit a broken bottle alongside iron post.</p>                             | S 7 | S 8 |     |     |
| S 7                        | S 8   |     |     |     |     |
| <p>80.00</p>               | <p>Point for the cor. of secs. 5, 6, 7 and 8.</p> <p>Set an iron post, 28 ins. long, <math>2\frac{1}{2}</math> ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center;"> <p>T 6 N R 18 W</p> <table border="1" style="margin: auto;"> <tr> <td>S 6</td> <td>S 5</td> </tr> <tr> <td>S 7</td> <td>S 8</td> </tr> </table> <p>1953</p> </div> <p>Deposit a broken bottle alongside iron post.</p> <p>Land, gently rolling.<br/>Soil, sandy.<br/>Timber, none.<br/>Undergrowth, greasewood.</p> | S 6 | S 5 | S 7 | S 8 |
| S 6                        | S 5   |     |     |     |     |
| S 7                        | S 8   |     |     |     |     |
| <p>39.99</p>               | <p>From the cor. of secs. 4, 5, 8 and 9.</p> <p>S. 89° 59' W., bet. secs. 5 and 8.</p> <p>Over gently rolling land.</p> <p>Point for the <math>\frac{1}{4}</math> cor. of secs. 5 and 8.</p> <p>Set an iron post, 28 ins. long, <math>2\frac{1}{2}</math> ins. diam., 24 ins. in the ground, with brass cap mkd.</p>  |     |     |     |     |

## Subdivision of T. 6 N., R. 18 W.

Chains

S 5

 $\frac{1}{4}$  ———

S 8

1953

Deposit a broken bottle alongside iron post.

79.98

The cor. of secs. 5, 6, 7 and 8.

Land, gently rolling.

Soil, sandy.

Timber, none.

Undergrowth, greasewood.

S. 89° 56' W., bet. secs. 6 and 7.

Over gently rolling land.

40.00

Point for the  $\frac{1}{4}$  cor. of secs. 6 and 7.Set an iron post, 28 ins. long,  $2\frac{1}{2}$  ins. diam., 24 ins. in the ground, with brass cap mkd.

S 6

 $\frac{1}{4}$  ———

S 7

1953

Deposit a broken bottle alongside iron post.

79.00

The cor. of secs. 1, 6, 7, and 12 on the W. bdy. T. 6 N., R. 18 W., which is monumented with an iron post, marked and witnessed as described in the official record.

Land, gently rolling.

Soil, sandy.

Timber, none.

Undergrowth, greasewood.

N. 0° 11' W., bet. secs. 5 and 6.

Over gently rolling land.

40.00

Point for the  $\frac{1}{4}$  cor. of secs. 5 and 6.Set an iron post, 28 ins. long,  $2\frac{1}{2}$  ins. diam., 24 ins. in the ground, with brass cap mkd. $\frac{1}{4}$   
S 6 | S 5

1953

Deposit a broken bottle alongside iron post.

60.00

Point for the N. 1/16 cor. of secs. 5 and 6.

Subdivision of T. 6 N., R. 18 W.

Chains

Set an iron post, 28 ins. long,  $2\frac{1}{2}$  ins. diam., 24 ins. in the ground, with brass cap mkd.

N 1/16

s 6 | s 5

1953

Deposit a broken bottle alongside iron post.

80.00

Point for the 1/16 cor. of secs. 5 and 6.

Set an iron post, 28 ins. long,  $2\frac{1}{2}$  ins. diam., 24 ins. in the ground, with brass cap mkd.

1/16

s 6 | s 5

80

1953

Deposit a broken bottle alongside iron post.

88.33

The cor. of secs. 5 and 6 on the N. bdy. of T. 6 N., R. 18 W., which is monumented with an iron post, marked and witnessed as described in the official record.

Land, gently rolling. -  
Soil, sandy.  
Timber, none.  
Undergrowth, greasewood.

#### General Description

The main ridge of the Plomosa Mountains cuts through Township 6 North, Range 18 West, in a north and south direction from section 35 to section 1, and consists of broken ridges and spurs up to 2200 feet elevation. The drainage is divided along this ridge; to the east, drains and dry washes in a generally northeast direction; to the west, drains and dry washes in a westerly direction until they disappear in the western half of the township which is gently rolling sandy country from 1000 feet to 1100 feet elevation. The soil is sandy and rocky and there is a covering of scattering ironwood and palo verde timber with greasewood undergrowth.

There are no buildings or improvements in the township and the only access is via an old road from Bouse that enters the township from the east in section 24, crosses the mountains in sections 13 and 14, and ends in section 22.



58

BOOK 4440

### CERTIFICATE OF CADASTRAL ENGINEER

I, Ty White, HEREBY CERTIFY upon honor that, in  
 pursuance of special instructions bearing date of the 9 th. day of October, 1952,  
 I have ~~surveyed~~ executed a dependent resurvey of the west boundary of  
Township 6 North, Range 17 West, and surveyed the west and north  
boundaries and subdivisional lines of Township 6 North, Range 18 West.

Gila and  
 of the Salt River Meridian, in the State of Arizona, which are  
 represented in the foregoing field notes as having been executed by me and under my direction; and that  
 said survey has been made in strict conformity with said instructions, the Manual of Instructions for the  
 Survey of the Public Lands of the United States, and in the specific manner described in the foregoing  
 field notes.

*Calver City, Calif.  
 January 23, 1954*

*Ty White*  
 Cadastral Engineer

### CERTIFICATE OF APPROVAL

BUREAU OF LAND MANAGEMENT,  
 Washington, D. C., APR 5 1955, 19

The foregoing field notes of the ~~survey of~~ dependent resurvey of the west boundary  
of Township 6 North, Range 17 West, and the survey of the west and north  
boundaries and subdivisional lines of Township 6 North, Range 18 West.

executed by Ty White

having been critically examined and found correct, are hereby approved.

*Earl S. Harrington*  
 Chief, Division of Cadastral Engineering  
 Cadastral Engineering Staff Officer

### CERTIFICATE OF TRANSCRIPT

~~I certify that the foregoing transcript of the field notes of the above described surveys in~~  
~~is a true copy of the original field notes.~~

*Chief, Division of Cadastral Engineering.*