

UNITED STATES  
DEPARTMENT OF THE INTERIOR  
BUREAU OF LAND MANAGEMENT

# FIELD NOTES

of the

Dependent Resurvey of a Portion of Boundaries

and

Portion of Subdivision and Survey of Subdivisional Lines

of

Sections 4, 5, 7, and 8,

Township 15 South, Range 12 East

Of the Gila and Salt River Meridian,

In the State of Arizona

### EXECUTED BY

Clarence E. Bilbray, Cartographer (Cadastral)

Under special instructions dated October 29 and November 19, 1952, which provided for the surveys included under Group No. 286, approved November 18, 1952 and assignment instructions dated December 1, 1952.

Survey commenced March 27, 1953.

Survey completed December 15, 1953.

4451

4451

4451



## T. 15 S., R. 12 E.

## Chains

This is a dependent resurvey of a portion of the boundaries and a portion of the subdivision of T. 15 S., R. 12 E., of the Gila and Salt River Meridian, Arizona, and subdivision of sections 4, 5, 7, and 8 therein. The east boundary of the township was originally surveyed by S. W. Foreman in 1871, and the north  $\frac{1}{4}$  miles of this boundary was resurveyed by J. F. Hesse in 1915. The south 2 miles of the west boundary was originally surveyed by L. D. Chillson in 1888, and the north  $\frac{1}{4}$  miles by G. J. Roskruge in 1886, the south 2 miles of this boundary was resurveyed by C. M. Leedy in 1915, and the north  $\frac{1}{4}$  miles by J. F. Hesse the same year. The north boundary and the north  $\frac{2}{3}$  of the subdivisional lines was surveyed by J. F. Hesse in 1915.

The survey was executed with a light mountain solar transit made by W. & L. E. Gurley, serial number 371540, constructed in accordance with the standard instrumental specifications of the Bureau of Land Management. The instrument was in good condition, and having been placed in satisfactory adjustment prior to the beginning of the survey, was tested and found free from appreciable error.

The measurements were made with a narrow steel tape, 5 chains in length, graduated to tenths of a link for the first 10 links, every link for the following 90 links, and at each 10 link interval for the remaining 400 links. The tape was tested by comparison with a standard 1-chain steel tape and found correct. The measurements were made on the slope, and the vertical angle of each interval ascertained by a clinometer in good adjustment; the horizontal equivalents are entered in the field note record.

The directions of all lines were determined by transit method, with azimuth obtained from U. S. Coast & Geodetic Survey triangulation station "Snyder's Hill", which is located in the NW $\frac{1}{4}$  of sec. 3, T. 15 S., R. 12 E. All bearings were adjusted for differences in longitude between stations.

The geographic position of the southeast corner of section 4, T. 15 S., R. 12 E., as computed through the tie made to triangulation station Snyder's Hill, is:

Latitude 32° 08' 52.1 N.      Longitude 111° 06' 50.1 W.

## Dependent Resurvey, Portion of South Boundary; T. 14 S., R. 12 E.

(Reestablishment of the survey executed by J. F. Hesse in 1915)

From the corner of secs. 33 and 34, T. 14 S., R. 12 E., which is monumented with an iron post, 3 ins. diam., set and marked as described in the official record.

S. 89° 41' W., on the south boundary of section 33.

Over nearly level land, through undergrowth.

2.446	The closing corner of secs. 3 and 4, T. 15 S., R. 12 E., which is monumented with an iron post, 2 ins. diam., set and marked as described in the official record.
19.60	Wash, 10 lks. wide, 1 ft. deep, drains SW.
21.65	Wash, 5 lks. wide, 1 ft. deep, drains WSW.
23.20	Same wash, drains WNW.
26.80	Same wash, drains SW.
40.05	The $\frac{1}{4}$ sec. cor. of sec. 33, which is monumented with an iron post, 1 in. diam., set and marked as described in the official record.

## Dependent Resurvey, Portion of South Boundary, T. 14 S., R. 12 E.

Chains	
	S. 89° 41' W., beginning new measurement.
2.521	Point for the $\frac{1}{4}$ sec. cor. of sec. 4.
5.48	El Paso Natural Gas line, bears N. 50° 20' W. and S. 50° 20' E.
11.20	Wash, 10 lks. wide, 1 ft. deep, drains SW.
18.75	Wash, 10 lks. wide, 1 ft. deep, drains SW.
32.05	Wash, 10 lks. wide, 1 ft. deep, drains SW.
37.50	Wash, 10 lks. wide, 1 ft. deep, drains SW.
40.064	The corner of secs. 32 and 33, which is monumented with an iron post, 3 ins. diam., set and marked as described in the official record.  Land, nearly level. Soil, sandy loam. No timber; undergrowth, greasewood, mesquite and cacti.
	S. 89° 42' W., on the south boundary of section 32.  Over nearly level land, through undergrowth.
2.582	The closing corner of secs. 4 and 5, T. 15 S., R. 12 E.
6.40	Shallow wash, drains WSW.
12.632	Point for the E-E $\frac{1}{64}$ sec. cor. of sec. 5.
22.682	Point for the E $\frac{1}{16}$ sec. cor. of sec. 5.
30.15	Junction of washes, drains WNW.
32.10	Same wash, drains WSW.
32.732	Point for the W-E $\frac{1}{64}$ sec. cor. of sec. 5.
34.65	Same wash, drains WNW.
36.45	Gas pipe line, bears NE. and SW.
40.062	The $\frac{1}{4}$ sec. cor. of sec. 32, which is monumented with an iron post, 1 in. diam., set and marked as described in the official record.  S. 89° 42' W., beginning new measurement.
2.72	Point for the $\frac{1}{4}$ sec. cor. of sec. 5.
5.20	Wash, 5 lks. wide, 1 ft. deep, drains SW.
6.80	Same wash, drains NW.
17.70	Wash, 10 lks. wide, 1 ft. deep, drains WNW.
20.60	Shallow wash, drains WNW.
39.00	Wash, 10 lks. wide, 1 ft. deep, drains NW.
40.021	The corner of secs. 31 and 32, which is monumented with an iron post, 3 ins. diam., set and marked as described in the official record.  Land, nearly level. Soil, sandy loam. No timber; undergrowth, greasewood, mesquite, and cacti.

## Dependent Resurvey, Portion of South Boundary, T. 14 S., R. 12 E.

Chains

S. 89° 42' W., on the south boundary of section 31.

Over nearly level land, through undergrowth.

2.899 The closing corner of secs. 5 and 6, T. 15 S., R. 12 E.

40.019 The  $\frac{1}{4}$  sec. cor. of sec. 31, which is monumented with an iron post, 1 in. diam., set and marked as described in the official record.

Land, nearly level.

Soil, sandy loam.

No timber; undergrowth, greasewood and mesquite.

## Dependent Resurvey, Portion of West Boundary, T. 15 S., R. 12 E.

(Reestablishment of the Survey and Resurvey Executed)  
(by G. J. Roskrige and J. F. Hesse in 1886 and 1915 )

Beginning at the corner of secs. 7, 12, 13, and 18, which is marked by a malpais stone, 8x6x6 ins., firmly set and marked as described in the official record.

At the corner point

Set an iron post, 28 ins. long,  $2\frac{1}{2}$  ins. diam., 24 ins. in the ground, with brass cap mkd.

T15S	
R11E	R12E
S12	S 7
S13	S18
1953	

Bury the old corner stone alongside the iron post.

N. 0° 28' W., on the W. bdy. of sec. 7.

Over nearly level land, through scattering undergrowth.

3.40 Wash, 15 lks. wide, 1 ft. deep, drains NE.

12.90 Telephone line, bears N. 70° E. and S. 70° W.

13.60 Center line of Ajo Highway, bears N. 69° 55' E. and S. 69° 55' W.

30.00 Old road, bears NE. and SW.

40.077 Point for the  $\frac{1}{4}$  sec. cor. of secs. 7 and 12, at proportionate distance; there is no remaining evidence of the original corner.Set an iron post, 28 ins. long,  $2\frac{1}{2}$  ins. diam., 24 ins. in the ground, over a deposit of broken glass, with brass cap mkd.

$\frac{1}{4}$	
S12	S 7
1953	

80.154 Point for the corner of secs. 1, 6, 7, and 12, at proportionate distance; there is no remaining evidence of the original corner.

Set an iron post, 28 ins. long,  $2\frac{1}{2}$  ins. diam., 24 ins. in the ground, over a deposit of broken glass, with brass cap mkd.

## Dependent Resurvey, Portion of West Boundary, T. 15 S., R. 12 E.

Chains

T15S	
R11E	R12E
S 1	S 6
S12	S 7

1953

Land, nearly level.  
Soil, sandy loam.  
No timber; undergrowth, mesquite.

N. 0° 28' W., on W. bdy. of sec. 6.

Over nearly level land, through undergrowth.

6.10 Wash, 10 lks. wide, 1 ft. deep, drains NW.

19.00 Wash, 10 lks. wide, 2 ft. deep, drains WNW.

40.057 The  $\frac{1}{4}$  sec. cor. of secs. 1 and 6, which is monumented with an iron post, 1 in. diam., set and marked as described in the official record.

Land, nearly level.  
Soil, sandy loam.  
No timber, undergrowth, mesquite.

Dependent Resurvey of  $S\frac{1}{2}$  East Boundary of Section 4, T. 15 S., R. 12 E.

From the corner of secs. 3, 4, 9, and 10, which is monumented with an iron post, 2 ins. diam., described in the 1953 resurvey record of section 10.

N. 0° 02' W., bet. secs. 3 and 4.

Over nearly level land, along W. side of road.

9.70 Shallow wash, drains WSW.

10.029 Point for the S-S  $\frac{1}{64}$  sec. cor. of secs. 3 and 4, falls on W. edge of road.

Set an iron post, 28 ins. long,  $2\frac{1}{2}$  ins. diam.,  $\frac{3}{4}$  ins. in the ground, with brass cap mkd.

SS  $\frac{1}{64}$ 

S 4	S 3
-----	-----

1953

from which

An iron post, 28 ins. long,  $2\frac{1}{2}$  ins. diam., set 24 ins. in the ground for a reference monument, bears East, 45 lks. dist., with brass cap mkd. SS  $\frac{1}{64}$  S3 RM 1953 and an arrow pointing to the true corner.

An iron post, 28 ins. long,  $2\frac{1}{2}$  ins. diam., set 24 ins. in the ground for a reference monument, bears West, 45 lks. dist., with brass cap mkd. SS  $\frac{1}{64}$  S4 RM 1953 and an arrow pointing to the true corner.

16.90 Wash; 10 lks. wide, 1 ft. deep, drains W.

20.058 Point for the S  $\frac{1}{16}$  sec. cor. of secs. 3 and 4, falls on W. side of road

Set an iron post, 28 ins. long,  $2\frac{1}{2}$  ins. diam.,  $\frac{3}{4}$  ins. in the ground, with brass cap mkd.

Dependent Resurvey of  $S\frac{1}{2}$  East Boundary of Section 4, T. 15 S., R. 12 E.

Chains

S 1/16

S4 | S3

1953

from which

An iron post, 28 ins. long,  $2\frac{1}{2}$  ins. diam., set 24 ins. in the ground for a reference monument, bears East, 45 lks. dist., with brass cap mkd. S 1/16 S3 RM 1953 and an arrow pointing to the true corner.

An iron post, 28 ins. long,  $2\frac{1}{2}$  ins. diam., set 24 ins. in the ground for a reference monument, bears West, 45 lks. dist., with brass cap mkd. S 1/16 S4 RM 1953 and an arrow pointing to the true corner.

24.35 Wash, 10 lks. wide, 2 ft. deep, drains WSW.

30.087 Point for the N-S 1/64 sec. cor. of secs. 3 and 4, falls on W. side of road.

Set an iron post, 28 ins. long,  $2\frac{1}{2}$  ins. diam., 34 ins. in the ground, with brass cap mkd.

NS 1/64

S 4 | S 3

1953

from which

An iron post, 28 ins. long,  $2\frac{1}{2}$  ins. diam., set 24 ins. in the ground for a reference monument, bears East, 45 lks. dist., with brass cap mkd. NS 1/64 S3 RM 1953 and an arrow pointing to the true corner.

An iron post, 28 ins. long,  $2\frac{1}{2}$  ins. diam., set 24 ins. in the ground for a reference monument, bears West, 45 lks. dist., with brass cap mkd. NS 1/64 S4 RM 1953 and an arrow pointing to the true corner.

34.50 Wash, 10 lks. wide, 1 ft. deep, drains WSW.

40.116 The  $\frac{1}{4}$  sec. cor. of secs. 3 and 4, which is monumented with an iron post, 1 in. diam., described in the 1953 resurvey record of section 3.

Land, nearly level.

Soil, sandy.

No timber; undergrowth, greasewood, mesquite, and cacti.

Dependent Resurvey of a Portion of Subdivision of T. 15 S., R. 12 E.

(Reestablishment of the survey executed by J. F. Hesse in 1915)

From the corner of secs. 8, 9, 16, and 17, which is monumented with an iron post, 2 ins. diam., set and marked as described in the official record.

North, bet. secs. 8 and 9.

Over nearly level land, through undergrowth.

10.40 Wash, 15 lks. wide, 2 ft. deep, drains NW.

13.10 Wash, 10 lks. wide, 1 ft. deep, drains W.

## BOOK 4451

## Dependent Resurvey of a Portion of Subdivision of T. 15 S., R. 12 E.

Chains	
31.70	Wash, 25 lks. wide, 2 ft. deep, drains W.
40.08	The $\frac{1}{4}$ sec. cor. of secs. 8 and 9, which is monumented with an iron post, 1 in. diam., set 8 ins. below surface of an E. and W. road, marked as described in the official record.
	N. 0° 01' W., beginning new measurement.
10.031	Point for the S-N- $\frac{1}{64}$ sec. cor. of secs. 8 and 9.
	Set an iron post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 24 ins. in the ground, with brass cap mkd.
	SN $\frac{1}{64}$ S 8   S 9 1953
12.20	Wash, 15 lks. wide, $1\frac{1}{2}$ ft. deep, drains W.
20.062	Point for the N $\frac{1}{16}$ sec. cor. of secs. 8 and 9.
	Set an iron post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 24 ins. in the ground, with brass cap mkd.
	N $\frac{1}{16}$ S 8   S 9 1953
20.10	Wash. 15 lks. wide. $1\frac{1}{2}$ ft. deep, drains W.
23.80	Wash, 10 lks. wide, 2 ft. deep, drains W.
25.50	Wash, 15 lks. wide, 3 ft. deep, drains W.
28.60	Old road, bears E. and W.
30.093	Point for the N-N $\frac{1}{64}$ sec. cor. of secs. 8 and 9.
	Set an iron post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 24 ins. in the ground, over a deposit of broken glass, with brass cap mkd.
	NN $\frac{1}{64}$ S 8   S 9 1953
35.00	Wash, 20 lks. wide, 3 ft. deep, drains W.
39.20	Wash, 15 lks. wide, 2 ft. deep, drains W.
40.124	The corner of secs. 4, 5, 8, and 9, which is monumented with an iron post, 2 ins. diam., set and marked as described in the official record.
	Land, nearly level, Soil, sandy. No timber; undergrowth, mesquite and sage.
	From the corner of secs. 3, 4, 9, and 10.
	S. 89° 55' W., bet. secs. 4 and 9.
	Over nearly level land, through undergrowth.

## BOOK 4451

## Dependent Resurvey of a Portion of Subdivision of T. 15 S., R. 12 E.

Chains	
2.00	Wash, 10 lks. wide, 1 ft. deep, drains SW.
10.033	Point for the E-E $1/64$ sec. cor. of secs. 4 and 9. Set an iron post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 24 ins. in the ground, over a deposit of broken glass, with brass cap mkd. $\begin{array}{r} \text{EE } 1/64 \\ \hline \text{S } 4 \\ \text{S } 9 \\ 1953 \end{array}$
20.066	Point for the E $1/16$ sec. cor. of secs. 4 and 9. Set an iron post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 24 ins. in the ground, over a deposit of broken glass, with brass cap mkd. $\begin{array}{r} \text{E } 1/16 \\ \hline \text{S } 4 \\ \text{S } 9 \\ 1953 \end{array}$
27.45	Wash, 10 lks. wide, drains SW.
30.099	Point for the W-E $1/64$ sec. cor. of secs. 4 and 9. Set an iron post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 24 ins. in the ground, over a deposit of broken glass, with brass cap mkd. $\begin{array}{r} \text{WE } 1/64 \\ \hline \text{S } 4 \\ \text{S } 9 \\ 1953 \end{array}$
40.132	Point for the $\frac{1}{4}$ sec. cor. of secs. 4 and 9, at proportionate distance; there is no remaining evidence of the original corner. Set an iron post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 24 ins. in the ground, over a deposit of broken glass, with brass cap mkd. $\begin{array}{r} \frac{1}{4} \\ \hline \text{S } 4 \\ \text{S } 9 \\ 1953 \end{array}$
44.95	Wash, 35 lks. wide, 2 ft. deep, drains WSW.
50.165	Point for the E-W $1/64$ sec. cor. of secs. 4 and 9. Set an iron post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 24 ins. in the ground, over a deposit of broken glass, with brass cap mkd. $\begin{array}{r} \text{EW } 1/64 \\ \hline \text{S } 4 \\ \text{S } 9 \\ 1953 \end{array}$
60.198	Point for the W $1/16$ sec. cor. of secs. 4 and 9. Set an iron post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 24 ins. in the ground, over a deposit of broken glass, with brass cap mkd. $\begin{array}{r} \text{W } 1/16 \\ \hline \text{S } 4 \\ \text{S } 9 \\ 1953 \end{array}$
61.00	Wash 5 lks. wide, 1 ft. deep, drains NW.
68.00	Wash, 10 lks. wide, 1 ft. deep, drains NW.
70.231	Point for the W-W $1/64$ sec. cor. of secs. 4 and 9.

## Dependent Resurvey of a Portion of Subdivision of T. 15 S., R. 12 E.

Chains	
	Set an iron post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 24 ins. in the ground, over a deposit of broken glass, with brass cap mkd.
	$\begin{array}{r} \text{S } 4 \\ \text{WW } 1/64 \text{ ---} \\ \text{S } 9 \\ 1953 \end{array}$
77.45	Wash, 10 lks. wide, 2 ft. deep, drains WNW.
80.264	The corner of secs. 4, 5, 8, and 9. Land, nearly level. Soil, sandy loam. No timber; undergrowth, mesquite.
	N. $0^{\circ} 01' W_1$ , bet. secs. 4 and 5. Over nearly level land, through undergrowth.
3.55	Wash, 15 lks. wide, 3 ft. deep, drains WSW.
5.85	Power line, bears NE. and SW.
7.65	Wash, 5 lks. wide, 1 ft. deep, drains WNW.
10.02	Point for the S-S $1/64$ sec. cor. of secs. 4 and 5. Set an iron post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 24 ins. in the ground, over a deposit of broken glass, with brass cap mkd. $\begin{array}{r} \text{SS } 1/64 \\ \text{S } 5 \text{   } \text{S } 4 \\ 1953 \end{array}$
15.15	Wash, 20 lks. wide, 1 ft. deep, drains WNW.
20.04	Point for the S $1/16$ sec. cor. of secs. 4 and 5. Set an iron post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 24 ins. in the ground, over a deposit of broken glass, with brass cap mkd. $\begin{array}{r} \text{S } 1/16 \\ \text{S } 5 \text{   } \text{S } 4 \\ 1953 \end{array}$
22.25	Telephone line, bears N. $57^{\circ} 45' E.$ and S. $57^{\circ} 45' W.$
22.355	Center line of Ajo Highway, bears N. $57^{\circ} 37' E.$ and S. $57^{\circ} 37' W.$ , cor. of lots 21, 22, 52, and 53, set nail from which A wooden stake, 2 ft. long, 2 ins. sq., set 12 ins. in the ground for a reference, bears S. $0^{\circ} 01' E.$ , 100 lks. dist., marked for lots 22 and 53. A wooden stake, 2 ft. long, 2 ins. sq., set 12 ins. in the ground for a reference, bears N. $0^{\circ} 01' W.$ , 100 lks. dist., marked for lots 21 and 52.
30.06	Point for the N-S $1/64$ sec. cor. of secs. 4 and 5. Set an iron post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 24 ins. in the ground, over a deposit of broken glass, with brass cap mkd.

## Dependent Resurvey of a Portion of Subdivision of T. 15 S., R. 12 E.

Chains	
	NS 1/64 S 5   S 4 1953
33.85	Wash, 10 lks. wide, 1 ft. deep, drains WSW.
39.90	Shallow wash, drains W.
40.08	The $\frac{1}{4}$ sec. cor. of secs. 4 and 5, which is monumented with an iron post, 1 in. diam., set and marked as described in the official record.
	-----
	North, beginning new measurement.
6.20	Wash, 15 lks. wide, 1 ft. deep, drains WSW.
9.30	Wash, 10 lks. wide, $1\frac{1}{2}$ ft. deep, drains W.
10.024	Point for the S-N 1/64 sec. cor. of secs. 4 and 5. Set an iron post, 28 ins. long, $2\frac{1}{8}$ ins. diam., 24 ins. in the ground, over a deposit of broken glass, with brass cap mkd.
	SN 1/64 S 5   S 4 1953
15.20	Wash, 15 lks. wide, 2 ft. deep, drains W.
20.048	Point for the N 1/16 sec. cor. of secs. 4 and 5. Set an iron post, 28 ins. long, $2\frac{1}{8}$ ins. diam., 24 ins. in the ground, with brass cap mkd.
	N 1/16 S 5   S 4 1953
	Deposit a stone mkd. X at base of iron post.
24.90	Wash, 10 lks. wide, 1 ft. deep, drains W.
27.50	Wash, 15 lks. wide, 2 ft deep, drains W
30.072	Point for the N-N 1/64 sec. cor. of secs. 4 and 5. long, Set an iron post, 28 ins./ $2\frac{1}{8}$ ins. diam., 24 ins. in the ground, over a deposit of broken glass, with brass cap mkd.
	NN 1/64 S 5   S 4 1953
33.00	Wash, 10 lks. wide, 1 ft. deep, drains W.
39.50	Wash, 10 lks. wide, 1 ft. deep, drains WSW.
40.417	Intersect the S. bdy. of sec. 32, T. 14 S., R. 12 E., at the closing corner of secs. 4 and 5, T. 15 S., R. 12 E., which is monumented with an iron post, 2 ins. diam., set and marked as described in the official record  From this closing corner the corner of secs. 32 and 33, T. 14 S., R. 12 E., bears N. 89° 42' E., 2.582 chs. dist.

## Dependent Resurvey of a Portion of Subdivision of T. 15 S., R. 12 E.

## Chains

Land, nearly level.  
Soil, sandy loam.  
No timber; undergrowth, mesquite and sage.

From the corner of secs. 8, 9, 16, and 17.

S. 89° 52' W., bet. secs. 8 and 17.

Over nearly level land, through undergrowth.

2.20 Wash, 10 lks. wide, 2 ft. deep, drains N.

39.70 Wash, 10 lks. wide, 1 ft. deep, drains N.

40.185 The  $\frac{1}{4}$  sec. cor. of secs. 8 and 17, which is monumented with an iron post, 1 in. diam., set and marked as described in the official record.

S. 89° 52' W., beginning new measurement

19.80 Wash, 10 lks. wide, 1 ft. deep, drains N.

32.30 Old road, bears N. and S.

40.177 The corner of secs. 7, 8, 17, and 18, which is monumented with an iron post, 2 ins. diam., set and marked as described in the official record.

Land, nearly level.  
Soil, sandy loam.  
No timber; undergrowth, mesquite and cacti.

S. 89° 51' W., bet. secs. 7 and 18.

Over nearly level land, through undergrowth.

6.50 Wash, 10 lks. wide, 2 ft. deep, drains N.

10.028 Point for the E-E  $\frac{1}{64}$  sec. cor. of secs. 7 and 18.

Set an iron post, 28 ins. long,  $2\frac{1}{2}$  ins. diam., 24 ins. in the ground, over a deposit of broken glass, with brass cap mkd.

$$\begin{array}{r} \text{EE } \frac{1}{64} \text{---} \frac{\text{S } 7}{\text{S } 18} \\ 1953 \end{array}$$

11.75 Wash, 5 lks. wide, 1 ft. deep, drains N.

17.65 Wash, 10 lks. wide, 2 ft. deep, drains N.

20.056 Point for the E  $\frac{1}{16}$  sec. cor. of secs. 7 and 18.

Set an iron post, 28 ins. long,  $2\frac{1}{2}$  ins. diam., 24 ins. in the ground, over a deposit of broken glass, with brass cap mkd.

$$\begin{array}{r} \text{E } \frac{1}{16} \text{---} \frac{\text{S } 7}{\text{S } 18} \\ 1953 \end{array}$$

30.084 Point for the W-E  $\frac{1}{64}$  sec. cor. of secs. 7 and 18.

Set an iron post, 28 ins. long,  $2\frac{1}{2}$  ins. diam., 24 ins. in the ground, over a deposit of broken glass, with brass cap mkd.

## Dependent Resurvey of a Portion of Subdivision of T. 15 S., R. 12 E.

Chains	
	$\begin{array}{r} \text{S } 7 \\ \text{WE } 1/64 \text{ ---} \\ \text{S } 18 \\ 1953 \end{array}$
40.10	Power line, bears NE. and W. along line.
40.112	The $\frac{1}{4}$ sec. cor. of secs. 7 and 18, which is monumented with an iron post, 1 in. diam., set and marked as described in the official record.
	<hr style="width: 20%; margin: auto;"/>
	S. 89° 51' W., beginning new measurement.
30.10	Wash, 10 lks. wide, 2 ft. deep, drains N.
40.20	Wash, 15 lks. wide, 2 ft. deep, drains N.
42.05	The corner of secs. 7, 12, 13, and 18, on the W. bdy. of the Tp.  Land, nearly level. Soil, sandy loam. No timber; undergrowth, mesquite and cacti.
	From the corner of secs. 7, 8, 17, and 18.  N. 0° 02' W., bet. secs. 7 and 8.  Over nearly level land, through undergrowth.
10.023	Point for the S-S 1/64 sec. cor. of secs. 7 and 8.  Set an iron post, 28 ins. long, 2 $\frac{1}{2}$ ins. diam., 24 ins. in the ground, over a deposit of broken glass, with brass cap mkd.
	$\begin{array}{r} \text{SS } 1/64 \\ \text{S } 7 \text{   } \text{S } 8 \\ 1953 \end{array}$
20.046	Point for the S 1/16 sec. cor. of secs. 7 and 8.  Set an iron post, 28 ins. long, 2 $\frac{1}{2}$ ins. diam., 24 ins. in the ground, over a deposit of broken glass, with brass cap mkd.
	$\begin{array}{r} \text{S } 1/16 \\ \text{S } 7 \text{   } \text{S } 8 \\ 1953 \end{array}$
40.092	Point for the $\frac{1}{4}$ sec. cor. of secs. 7 and 8, at proportionate distance; there is no remaining evidence of the original corner.  Set an iron post, 28 ins. long, 2 $\frac{1}{2}$ ins. diam., 24 ins. in the ground, over a deposit of broken glass, with brass cap mkd.
	$\begin{array}{r} \frac{1}{4} \\ \text{S } 7 \text{   } \text{S } 8 \\ 1953 \end{array}$
42.80	Telephone line, bears N. 70° E. and S. 70° W.
43.526	Center line of Ajo Highway, bears N. 69° 55' E. and S. 69° 55' W. cor. of lots 52 and 53 of sec. 8.
50.115	Point for the S-N 1/64 sec. cor. of secs. 7 and 8.  Set an iron post, 28 ins. long, 2 $\frac{1}{2}$ ins. diam., 24 ins. in the ground

## BOOK 4451

## Dependent Resurvey of a Portion of Subdivision of T. 15 S., R. 12 E.

Chains	
	<p>over a deposit of broken glass, with brass cap mkd.</p> <p style="text-align: center;">SN 1/64 S 7   S 8 1953</p>
60.138	<p>Point for the N 1/16 sec. cor. of secs. 7 and 8.</p> <p>Set an iron post, 28 ins. long, 2½ ins. diam., 2¼ ins. in the ground, over a deposit of broken glass, with brass cap mkd.</p> <p style="text-align: center;">N 1/16 S 7   S 8 1953</p>
67.60	Wash, 10 lks. wide, 2 ft. deep, drains NW.
70.161	<p>Point for the N-N 1/64 sec. cor. of secs. 7 and 8.</p> <p>Set an iron post, 28 ins. long, 2½ ins. diam., 2¼ ins. in the ground, over a deposit of broken glass, with brass cap mkd.</p> <p style="text-align: center;">NN 1/64 S 7   S 8 1953</p>
73.40	Wash, 10 lks. wide, 3 ft. deep, drains W.
79.50	Wash, 10 lks. wide, 3 ft. deep, drains W.
80.184	<p>The corner of secs. 5, 6, 7, and 8, which is monumented with an iron post, 2 ins. diam., set and marked as described in the official record.</p> <p>Land, nearly level. Soil, sandy loam. No timber; undergrowth, mesquite and cacti.</p> <hr/> <p>From the corner of secs. 4, 5, 8, and 9.</p> <p>S. 89° 52' W., bet. secs. 5 and 8.</p> <p>Over nearly level land, through undergrowth.</p>
2.40	Wash, 15 lks. wide, 2 ft. deep, drains WNW.
8.35	Power line, bears NE. and SW.
9.00	Same wash, drains SW.
10.047	<p>Point for the E-E 1/64 sec. cor. of secs. 5 and 8.</p> <p>Set an iron post, 28 ins. long, 2½ ins. diam., 2¼ ins. in the ground, over a deposit of broken glass, with brass cap mkd.</p> <p style="text-align: center;">S 5 EE 1/64   S 8 1953</p>
13.65	Wash, drains WNW.
20.094	<p>Point for the E 1/16 sec. cor. of secs. 5 and 8.</p> <p>Set an iron post, 28 ins. long, 2½ ins. diam., 2¼ ins. in the ground, over a deposit of broken glass, with brass cap mkd.</p>

## Dependent Resurvey of a Portion of Subdivision of T. 15 S., R. 12 E.

Chains	
	$\begin{array}{r} \text{E } 1/16 \text{ } \overline{\text{S } 5} \\ \text{S } 8 \\ 1953 \end{array}$
21.35	Wash, 30 lks. wide, 4 ft. deep, drains NW.
21.95	Wash, 30 lks. wide, 4 ft. deep, drains NW.
30.141	Point for the W-E 1/64 sec. cor. of secs. 5 and 8. Set an iron post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, over a deposit of broken glass, with brass cap mkd.
	$\begin{array}{r} \text{WE } 1/64 \text{ } \overline{\text{S } 5} \\ \text{S } 8 \\ 1953 \end{array}$
33.60	Telephone line, bears N. 57° 45' E. and S. 57° 45' W.
34.956	Center line of Ajo Highway, bears N. 57° 37' E. and S. 57° 37' W., cor. of lots 7, 8, 62, and 64, set nail.  from which  A wooden stake, 2 ft. long, 2 ins. sq., set 12 ins. in the ground for a reference, bears N. 89° 52' E., 100 lks. dist., mkd. WP.  A wooden stake, 2 ft. long, 2 ins. sq., set 12 ins. in the ground for a reference, bears S. 89° 52' W., 100 lks. dist., mkd. WP.
40.188	Point for the ¼ sec. cor. of secs. 5 and 8, at proportionate distance; there is no remaining evidence of the original corner. Set an iron post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.
	$\begin{array}{r} \frac{1}{4} \overline{\text{S } 5} \\ \text{S } 8 \\ 1953 \end{array}$
	Deposit a stone mkd. X at base of iron post.
50.235	Point for the E-W 1/64 sec. cor. of secs. 5 and 8. Set an iron post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, over a deposit of broken glass, with brass cap mkd.
	$\begin{array}{r} \text{EW } 1/64 \text{ } \overline{\text{S } 5} \\ \text{S } 8 \\ 1953 \end{array}$
59.75	Wash, 10 lks. wide, 1 ft. deep, drains NW.
60.282	Point for the W 1/16 sec. cor. of secs. 5 and 8. Set an iron post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.
	$\begin{array}{r} \text{W } 1/16 \text{ } \overline{\text{S } 5} \\ \text{S } 8 \\ 1953 \end{array}$
65.35	Power line, bears NNW. and SSE.
65.50	Wash, 10 lks. wide, 3 ft. deep, drains NW.
67.00	Wash, 10 lks. wide, 4 ft. deep, drains NW.
70.15	Wash, 10 lks. wide, 2 ft. deep, drains NW.

## Dependent Resurvey of a Portion of Subdivision of T. 15 S., R. 12 E.

Chains	
70.329	Point for the W-W 1/64 sec. cor. of secs. 5 and 8.
	Set an iron post, 28 ins. long, 2½ ins. diam., 2¼ ins. in the ground, over a deposit of broken glass, with brass cap mkd.
	$\begin{array}{r} \text{S } 5 \\ \text{WW } 1/64 \text{ ---} \\ \text{S } 8 \\ 1953 \end{array}$
71.80	Wash, 20 lks. wide, 2 ft. deep, drains NW.
78.10	Wash, 25 lks. wide, 4 ft. deep, drains NW.
80.376	The corner of secs. 5, 6, 7, and 8.
	Land, nearly level. Soil, sandy loam. No timber; undergrowth, mesquite and cacti.
	S. 89° 52' W., bet. secs. 6 and 7.
	Over nearly level land, through undergrowth.
1.55	Wash, 25 lks. wide, 2 ft. deep, drains NW.
16.85	Wash, 10 lks. wide, 2 ft. deep, drains NW.
29.45	Wash, 6 lks. wide, 3 ft. deep, drains NW.
40.16	The ¼ sec. cor. of secs. 6 and 7, which is monumented with an iron post, 1 in. diam., set and marked as described in the official record.
	S. 89° 52' W., beginning new measurement.
17.10	Wash, 15 lks. wide, 2 ft. deep, drains N.
33.80	Wash, 10 lks. wide, 3 ft. deep, drains N.
40.00	Wash, 10 lks. wide, 2 ft. deep, drains N.
42.62	The corner of secs. 1, 6, 7, and 12, on the W. bdy. of the Tp.
	Land, nearly level, Soil, sandy loam. No timber; undergrowth, mesquite and cacti.
	From the corner of secs. 5, 6, 7, and 8.
	North, bet. secs. 5 and 6.
	Over nearly level land, through undergrowth.
0.65	Wash, 10 lks. wide, 2 ft. deep, drains W.
6.80	Wash, 10 lks. wide, 2 ft. deep, drains W.
9.60	Wash, 15 lks. wide, 3 ft. deep, drains W.
11.20	Wash, 15 lks. wide, 3 ft. deep, drains W.
26.40	Wash, 15 lks. wide, 3 ft. deep, drains W.
35.40	Wash, 10 lks. wide, 1 ft. deep, drains W.
36.10	Wash, 10 lks. wide, 1 ft. deep, drains W.
40.09	The ¼ sec. cor. of secs. 5 and 6, which is monumented with an iron


## Dependent Resurvey of a Portion of Subdivision of T. 15 S., R. 12 E.

Chains	
	post, 1 in. diam., set and marked as described in the official record.
	N. 0° 02' W., beginning new measurement.
5.00	Wash, 15 lks. wide, 1 ft. deep, drains W.
12.50	Wash, 10 lks. wide, 2 ft. deep, drains W.
16.60	Wash, 10 lks. wide, 2 ft. deep, drains W.
18.30	Wash, 10 lks. wide, 2 ft. deep, drains W.
21.40	Wash, 10 lks. wide, 1 ft. deep, drains W.
23.30	Wash, 10 lks. wide, 1 ft. deep, drains W.
35.20	Wash, 5 lks. wide, 1 ft. deep, drains W.
35.50	Wash, 5 lks. wide, 1 ft. deep, drains W.
39.70	Wash, 5 lks. wide, 1 ft. deep, drains W.
40.22	Intersect the S. bdy. of sec. 31, T. 14 S., R. 12 E., at the closing corner of secs. 5 and 6, T. 15 S., R. 12 E., which is monumented with an iron post, 2 ins. diam., set and marked as described in the official record.
	From this closing corner the corner of secs. 31 and 32, T. 14 S., R. 12 E., bears N. 89° 42' E., 2.899 chs. dist.
	Land, nearly level. Soil, sandy loam. No timber; undergrowth, mesquite and cacti.
Subdivision of Section 4, T. 15 S., R. 12 E.	
	From the $\frac{1}{4}$ sec. cor. of secs. 4 and 9.
	North, on the N. and S. center line of sec. 4.
	Over nearly level land, through undergrowth.
1.55	Wash, 20 lks. wide, 2 ft. deep, drains WSW.
10.027	Point for the C-S-S $\frac{1}{64}$ sec. cor. of sec. 4.
	Set an iron post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 24 ins. in the ground, over a deposit of broken glass, with brass cap mkd.
	$\begin{array}{c} C \\ SS \frac{1}{64} \mid S 4 \\ C \\ 1953 \end{array}$
20.054	Point for the C-S $\frac{1}{16}$ sec. cor. of sec. 4.
	Set an iron post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 24 ins. in the ground, over a deposit of broken glass, with brass cap mkd.
	$\begin{array}{c} C \\ S \frac{1}{16} \mid S 4 \\ C \\ 1953 \end{array}$
23.40	Wash, 6 lks. wide, 1 ft. deep, drains SW.
30.081	Point for the C-N-S $\frac{1}{64}$ sec. cor. of sec. 4.

Subdivision of Section 4, T. 15 S., R. 12 E.


Chains

Set an iron post, 28 ins. long,  $2\frac{1}{2}$  ins. diam., 24 ins. in the ground, over a deposit of broken glass, with brass cap mkd.



40.108 Point for the C  $\frac{1}{4}$  sec. cor. of sec. 4, at the intersection of the E. and W. center line of sec. 4.

Set an iron post, 28 ins. long,  $2\frac{1}{2}$  ins. diam., 24 ins. in the ground, over a deposit of broken glass, with brass cap mkd.



46.70 Telephone line, bears N.  $57^{\circ} 30'$  E. and S.  $57^{\circ} 30'$  W.

47.77 Center line of Ajo Highway, bears N.  $57^{\circ} 37'$  E. and S.  $57^{\circ} 37'$  W.

64.75 Wash, 10 lks. wide, 2 ft. deep, drains W.

68.60 Wash, 10 lks. wide, 1 ft. deep, drains W.

78.20 El Paso Natural Gas line, bears N.  $50^{\circ} 20'$  W. and S.  $50^{\circ} 20'$  E.

80.678 Intersect the S. bdy. of sec. 33, T. 14 S., R. 12 E., point for the  $\frac{1}{4}$  sec. cor. of sec. 4, midway between the closing corners of secs. 3 and 4, and secs. 4 and 5.

Set an iron post, 28 ins. long,  $2\frac{1}{2}$  ins. diam., 24 ins. in the ground, with brass cap mkd.



Deposit a stone mkd. X at base of iron post.

From this corner the  $\frac{1}{4}$  sec. cor. of sec. 33, T. 14 S., R. 12 E., bears N.  $89^{\circ} 41'$  E., 2.521 chs. dist.


From the  $\frac{1}{4}$  sec. cor. of secs. 3 and 4.

S.  $89^{\circ} 54'$  W., on the E. and W. center line of sec. 4.

Over nearly level land, through undergrowth.

10.032 Point for the C-E-E  $\frac{1}{64}$  sec. cor. of sec. 4.

Set an iron post, 28 ins. long,  $2\frac{1}{2}$  ins. diam., 24 ins. in the ground, over a deposit of broken glass, with brass cap mkd.



12.65 Old road, bears NE. and SW.

20.064 Point for the C-E  $\frac{1}{16}$  sec. cor. of sec. 4.

Set an iron post, 28 ins. long,  $2\frac{1}{2}$  ins. diam., 24 ins. in the ground, over a deposit of broken glass, with brass cap mkd.

## Subdivision of Section 4, T. 15 S., R. 12 E.

Chains	
30.096	$\begin{array}{c} \text{E } 1/16 \\ \text{C} \text{-----} \text{C} \\ \text{S } 4 \\ 1953 \end{array}$ <p>Point for the C-W-E 1/64 sec. cor. of sec. 4.</p> <p>Set an iron post, 28 ins. long, 2<math>\frac{1}{2}</math> ins. diam., 24 ins. in the ground, over a deposit of broken glass, with brass cap mkd.</p>
40.128	$\begin{array}{c} \text{WE } 1/64 \\ \text{C} \text{-----} \text{C} \\ \text{S } 4 \\ 1953 \end{array}$ <p>The C <math>\frac{1}{4}</math> sec. cor. of sec. 4.</p>
50.165	<p>Point for the C-E-W 1/64 sec. cor. of sec. 4.</p> <p>Set an iron post, 28 ins. long, 2<math>\frac{1}{2}</math> ins. diam., 24 ins. in the ground, over a deposit of broken glass, with brass cap mkd.</p>
50.60	$\begin{array}{c} \text{EW } 1/64 \\ \text{C} \text{-----} \text{C} \\ \text{S } 4 \\ 1953 \end{array}$ <p>Telephone line, bears N. 57° 30' E. and S. 57° 30' W.</p>
52.234	<p>Center line of Ajo Highway, bears N. 57° 37' E. and S. 57° 37' W., cor. lots 15 and 17, set nail. from which</p> <p>A wooden stake, 2 ft. long, 2 ins. sq., set 12 ins. in the ground for a reference, bears N. 89° 54' E., 150 lks. dist., mkd. WP.</p> <p>A wooden stake, 2 ft. long, 2 ins. sq., set 12 ins. in the ground for a reference, bears S. 89° 54' W., 150 lks. dist., mkd. WP.</p>
60.202	<p>Point for the C-W 1/16 sec. cor. of sec. 4.</p> <p>Set an iron post, 28 ins. long, 2<math>\frac{1}{2}</math> ins. diam., 24 ins. in the ground, over a deposit of broken glass, with brass cap mkd.</p> $\begin{array}{c} \text{W } 1/16 \\ \text{C} \text{-----} \text{C} \\ \text{S } 4 \\ 1953 \end{array}$
70.239	<p>Point for the C-W-W 1/64 sec. cor. of sec. 4.</p> <p>Set an iron post, 28 ins. long, 2<math>\frac{1}{2}</math> ins. diam., 24 ins. in the ground, over a deposit of broken glass, with brass cap mkd.</p> $\begin{array}{c} \text{WW } 1/64 \\ \text{C} \text{-----} \text{C} \\ \text{S } 4 \\ 1953 \end{array}$
80.276	<p>The <math>\frac{1}{4}</math> sec. cor. of secs. 4 and 5.</p> <hr/> <p style="text-align: center;">Subdivision of the SE<math>\frac{1}{4}</math>.</p> <p>From the E 1/16 sec. cor. of secs. 4 and 9.</p> <p>N. 0° 01' W., on the N. and S. center line of the SE<math>\frac{1}{4}</math> of sec. 4.</p> <p>Over nearly level land.</p>
8.25	<p>Wash, 6 lks. wide, 2 ft. deep, drains SSW.</p>

## Subdivision of Section 4, T. 15 S., R. 12 E.

Chains	
10.028	<p>Point for the C-S-SE <math>1/64</math> sec. cor. of sec. 4.</p> <p>Set an iron post, 28 ins. long, <math>2\frac{1}{2}</math> ins. diam., 24 ins. in the ground, over a deposit of broken glass, with brass cap mkd.</p> <p style="text-align: center;">S 4 CSSE <math>1/64</math> 1953</p>
11.50	Wash, 20 lks. wide, 3 ft. deep, drains SSW.
14.15	Wash, 15 lks. wide, 4 ft. deep, drains SSW.
20.056	<p>Point for the SE <math>1/16</math> sec. cor. of sec. 4, at the intersection of the E. and W. center line of the SE <math>1/4</math> of sec. 4.</p> <p>Set an iron post, 28 ins. long, <math>2\frac{1}{2}</math> ins. diam., 24 ins. in the ground, over a deposit of broken glass, with brass cap mkd.</p> <p style="text-align: center;">SE <math>1/16</math> S 4 1953</p>
30.084	<p>Point for the C-N-SE <math>1/64</math> sec. cor. of sec. 4.</p> <p>Set an iron post, 28 ins. long, <math>2\frac{1}{2}</math> ins. diam., 24 ins. in the ground, over a deposit of broken glass, with brass cap mkd.</p> <p style="text-align: center;">S 4 CNSE <math>1/64</math> 1953</p>
31.70	Wash, 8 lks. wide, 1 ft. deep, drains W.
40.112	The C-E $1/16$ sec. cor. of sec. 4.
	<p>From the S <math>1/16</math> sec. cor. of secs. 3 and 4.</p> <p>S. <math>89^{\circ} 54'</math> W., on the E. and W. center line of the SE <math>1/4</math> of sec. 4.</p> <p>Over nearly level land.</p>
8.45	Wash, 10 lks. wide, 2 ft. deep, drains SW.
9.55	Same wash, drains NW.
10.033	<p>Point for the C-E-SE <math>1/64</math> sec. cor. of sec. 4.</p> <p>Set an iron post, 28 ins. long, <math>2\frac{1}{2}</math> ins. diam., 24 ins. in the ground, over a deposit of broken glass, with brass cap mkd.</p> <p style="text-align: center;">S 4 CESE <math>1/64</math> 1953</p>
12.10	Wash, 15 lks. wide, 4 ft. deep, drains SW.
13.80	Wash, 20 lks. wide, 4 ft. deep, drains SW.
20.066	The S-E $1/16$ sec. cor. of sec. 4.
30.099	<p>Point for the C-W-SE <math>1/64</math> sec. cor. of sec. 4.</p> <p>Set an iron post, 28 ins. long, <math>2\frac{1}{2}</math> ins. diam., 24 ins. in the ground, over a deposit of broken glass, with brass cap mkd.</p>

## Subdivision of Section 4, T. 15 S., R. 12 E.

Chains

S 4  
CWSE 1/64

1953

40.132 The C-S 1/16 sec. cor. of sec. 4.

Subdivision of the NE $\frac{1}{4}$ SE $\frac{1}{4}$ .

From the C-E-SE 1/64 sec. cor. of sec. 4.

N. 0° 01' W., on the N. and S. center line of the NE $\frac{1}{4}$ SE $\frac{1}{4}$  of sec. 4.

0.15 Wash, 8 lks. wide, 3 ft. deep, drains SW.

3.65 Wash, 20 lks. wide, 4 ft. deep, drains SW.

10.028 Point for the NE-SE 1/64 sec. cor. of sec. 4, at the intersection of the E. and W. center line of the NE $\frac{1}{4}$ SE $\frac{1}{4}$  of sec. 4.Set an iron post, 28 ins. long, 2 $\frac{1}{2}$  ins. diam., 24 ins. in the ground, over a deposit of broken glass, with brass cap mkd.

S 4

NESE

1/64

1953

15.95 Wash, 8 lks. wide, 2 ft. deep, drains W.

20.056 The C-E-E 1/64 sec. cor. of sec. 4.

From the N-S 1/64 sec. cor. of secs. 3 and 4.

S. 89° 54' W., on the E. and W. center line of the NE $\frac{1}{4}$ SE $\frac{1}{4}$  of sec. 4.

2.70 Wash, 5 lks. wide, 2 ft. deep, drains WSW.

4.20 Wash, 5 lks. wide, 1 ft. deep, drains WSW.

10.032 The NE-SE 1/64 sec. cor. of sec. 4.

20.064 The C-N-SE 1/64 sec. cor. of sec. 4.

Subdivision of the NW $\frac{1}{4}$ SE $\frac{1}{4}$ .

From the C-W-SE 1/64 sec. cor. of sec. 4.

North, on the N. and S. center line of the NW $\frac{1}{4}$ SE $\frac{1}{4}$  of sec. 4.

8.05 Wash, 8 lks. wide, 2 ft. deep, drains W.

10.027 Point for the NW-SE 1/64 sec. cor. of sec. 4, at the intersection of the E. and W. center line of the NW $\frac{1}{4}$ SE $\frac{1}{4}$  of sec. 4.Set an iron post, 28 ins. long, 2 $\frac{1}{2}$  ins. diam., 24 ins. in the ground, over a deposit of broken glass, with brass cap mkd.

S 4

NWSE

1/64

1953

20.054 The C-W-E 1/64 sec. cor. of sec. 4.

From the C-N-SE 1/64 sec. cor. of sec. 4.

## Subdivision of Section 4, T. 15 S., R. 12 E.

Chains	
	S. 89° 54' W., on the E. and W. center line of the NW $\frac{1}{4}$ SE $\frac{1}{4}$ of sec. 4.
3.50	Wash, 6 lks. wide, 2 ft. deep, drains WSW.
6.80	Old road, bears NW. and SE.
10.032	The NW-SE 1/64 sec. cor. of sec. 4.
20.064	The C-N-S 1/64 sec. cor. of sec. 4.

Subdivision of the SW $\frac{1}{4}$ SE $\frac{1}{4}$ .

	From the W-E 1/64 sec. cor. of sec. 4.
	North, on the N. and S. center line of the SW $\frac{1}{4}$ SE $\frac{1}{4}$ of sec. 4.
6.55	Wash, 25 lks. wide, 4 ft. deep, drains SW.
10.027	Point for the SW-SE 1/64 sec. cor. of sec. 4, at the intersection of the E. and W. center line of the SW $\frac{1}{4}$ SE $\frac{1}{4}$ of sec. 4. Set an iron post, 28 ins. long, 2 $\frac{1}{2}$ ins. diam., 24 ins. in the ground, over a deposit of broken glass, with brass cap mkd.
	S 4 SWSE 1/64 1953
20.054	The C-W-SE 1/64 sec. cor. of sec. 4.

---

From the C-S-SE 1/64 sec. cor. of sec. 4.

	S. 89° 54' W., on the E. and W. center line of the SW $\frac{1}{4}$ SE $\frac{1}{4}$ of sec. 4.
5.05	Wash, 15 lks. wide, 4 ft. deep, drains SW.
10.033	The SW-SE 1/64 sec. cor. of sec. 4.
20.066	The C-S-S 1/64 sec. cor. of sec. 4.

Subdivision of the SE $\frac{1}{4}$ SE $\frac{1}{4}$ .

	From the E-E 1/64 sec. cor. of sec. 4.
	N. 0° 01' W., on the N. and S. center line of the SE $\frac{1}{4}$ SE $\frac{1}{4}$ of sec. 4.
1.75	Wash, 6 lks. wide, 1 ft. deep, drains W.
10.028.	Point for the SE-SE 1/64 sec. cor. of sec. 4, at the intersection of the E. and W. center line of the SE $\frac{1}{4}$ SE $\frac{1}{4}$ of sec. 4. Set an iron post, 28 ins. long, 2 $\frac{1}{2}$ ins. diam., 24 ins. in the ground, over a deposit of broken glass, with brass cap mkd.
	S 4 SESE 1/64 1953

19.65 Wash, 6 lks. wide, 2 ft. deep, drains W.

20.056 The C-E-SE 1/64 sec. cor. of sec. 4.

---

From the S-S 1/64 sec. cor. of secs. 3 and 4.

S. 89° 54' W., on the E. and W. center line of the SE $\frac{1}{4}$ SE $\frac{1}{4}$  of sec. 4.

## Subdivision of Section 4, T. 15 S., R. 12 E.

Chains	
10.033	The SE-SE 1/64 sec. cor. of sec. 4.
11.75	Wash, 6 lks. wide, 1 ft. deep, drains SW.
20.066	The C-S-SE 1/64 sec. cor. of sec. 4.
Subdivision of the SW 1/4.	
	From the W 1/16 sec. cor. of secs. 4 and 9.
	North, on the N. and S. center line of the SW 1/4 of sec. 4.
10.024	Point for the C-S-SW 1/64 sec. cor. of sec. 4.  Set an iron post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, over a deposit of broken glass, with brass cap mkd.  S 4 CSSW 1/64 1953
20.048	Point for the SW 1/16 sec. cor. of sec. 4, at the intersection of the E. and W. center line of the SW 1/4 of sec. 4.  Set an iron post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, over a deposit of broken glass, with brass cap mkd.  SW 1/16 S 4 1953
20.25	Power line, bears NE. and SW.
30.073	Point for the C-N-SW 1/64 sec. cor. of sec. 4.  Set an iron post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, over a deposit of broken glass, with brass cap mkd.  S 4 CNSW 1/64 1953
34.00	Telephone line, bears N. 57° 45' E. and S. 57° 45' W.
35.055	Center line of Ajo Highway, bears N. 57° 37' E. and S. 57° 37' W., cor. of lots 16 and 17, set nail.  from which  A wooden stake, 2 ft. long, 2 ins. sq., set 12 ins. in the ground for a reference, bears South, 100 lks. dist., mkd. WP.  A wooden stake, 2 ft. long, 2 ins. sq., set 24 ins. in the ground for a reference, bears North, 100 lks. dist., mkd. WP.
40.098	The C-W 1/16 sec. cor. of sec. 4.  From the C-S 1/16 sec. cor. of sec. 4.  S. 89° 54' W., on the E. and W. center line of the SW 1/4 of sec. 4.
3.30	Wash, 6 lks. wide, 1 ft. deep, drains SW.
10.035	Point for the C-E-SW 1/64 sec. cor. of sec. 4.  Set an iron post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground over a deposit of broken glass, with brass cap mkd.

## Subdivision of Section 4, T. 15 S., R. 12 E.

Chains

S 4  
CESW  
1/64  
1953

20.07 The SW 1/16 sec. cor. of sec. 4.

30.105 Point for the C-W-SW 1/64 sec. cor. of sec. 4.

Set an iron post, 28 ins. long,  $2\frac{1}{2}$  ins. diam., 24 ins. in the ground,  
over a deposit of broken glass, with brass cap mkd.

S 4  
CWSW  
1/64  
1953

40.14 The S 1/16 sec. cor. of secs. 4 and 5.

Subdivision of the NE $\frac{1}{4}$ SW $\frac{1}{4}$ .

From the C-E-SW 1/64 sec. cor. of sec. 4.

North, on the N. and S. center line of the NE $\frac{1}{4}$ SW $\frac{1}{4}$  of sec. 4.10.026 Point for the NE-SW 1/64 sec. cor. of sec. 4, at the intersection of the E. and W. center line of the NE $\frac{1}{4}$ SW $\frac{1}{4}$  of sec. 4.

Set an iron post, 28 ins. long,  $2\frac{1}{2}$  ins. diam., 24 ins. in the ground,  
over a deposit of broken glass, with brass cap mkd.

S 4  
NESW  
1/64  
1953

15.95 Wash, 10 lks. wide, 2 ft. deep, drains W.

18.65 Wash, 10 lks. wide, 2 ft. deep, drains W.

20.052 The C-E-W 1/64 sec. cor. of sec. 4.

From the C-N-S 1/64 sec. cor. of sec. 4.

S. 89° 54' W., on the E. and W. center line of the NE $\frac{1}{4}$ SW $\frac{1}{4}$  of sec. 4.

10.037 The NE-SW 1/64 sec. cor. of sec. 4.

20.074 The C-N-SW 1/64 sec. cor. of sec. 4.

Subdivision of the NW $\frac{1}{4}$ SW $\frac{1}{4}$ .

From the C-W-SW 1/64 sec. cor. of sec. 4.

North, on the N. and S. center line of the NW $\frac{1}{4}$ SW $\frac{1}{4}$  of sec. 4.

7.63 Telephone line, bears N. 57° 45' E. and S. 57° 45' W.

8.657 Center line of Ajo Highway, bears N. 57° 37' E. and S. 57° 37' W.,  
cor. of lots 18, 21, 22, and 23, set nail.

from which

A wooden stake, 2 ft. long, 2 ins. sq., set 12 ins. in the ground  
for a reference, bears South, 100 lks. dist., mkd. WP

A wooden stake, 2 ft. long, 2 ins. sq., set 12 ins. in the ground  
for a reference, bears North, 100 lks. dist., mkd. WP.

## Subdivision of Section 4, T. 15 S., R. 12 E.

Chains 10.023	<p>Point for the NW-SW 1/64 sec. cor. of sec. 4, at the intersection of the E. and W. center line of the NW 1/4 SW 1/4 of sec. 4.</p> <p>Set an iron post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, over a deposit of broken glass, with brass cap mkd.</p> <p style="text-align: center;">S 4 NWSW 1/64 1953</p>
14.80	Wash, 12 lks. wide, 1 ft. deep, drains SW.
16.85	Wash, 5 lks. wide, 1 ft. deep, drains W.
20.046	The C-W-W 1/64 sec. cor. of sec. 4.
	_____
	From the C-N-SW 1/64 sec. cor. of sec. 4.
	S. 89° 54' W., on the E. and W. center line of the NW 1/4 SW 1/4 of sec. 4.
6.30	Telephone line, bears N. 57° 45' E. and S. 57° 45' W.
7.883	Center line of Ajo Highway, bears N. 57° 37' E. and S. 57° 37' W., cor. of lots 18 and 23, set nail:
	from which
	A wooden stake, 2 ft. long, 2 ins. sq., set 12 ins. in the ground for a reference, bears N. 89° 54' E., 150 lks. dist., mkd. WP.
	A wooden stake, 2 ft. long, 2 ins. sq., set 12 ins. in the ground for a reference, bears S. 89° 54' W., 150 lks. dist., mkd. WP.
10.037	The NW-SW 1/64 sec. cor. of sec. 4.
20.074	The N-S 1/64 sec. cor. of secs. 4 and 5.
	Subdivision of the SW 1/4 SW 1/4.
	From the W-W 1/64 sec. cor. of secs. 4 and 9.
	North, on the N. and S. center line of the SW 1/4 SW 1/4 of sec. 4.
1.95	Wash, 10 lks. wide, 2 ft. deep, drains W.
7.85	Wash, 10 lks. wide, 2 ft. deep, drains W.
10.023	Point for the SW-SW 1/64 sec. cor. of sec. 4, at the intersection of the E. and W. center line of the SW 1/4 SW 1/4 of sec. 4.
	Set an iron post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, over a deposit of broken glass, with brass cap mkd.
	S 4 SWSW 1/64 1953
20.046	The C-W-SW 1/64 sec. cor. of sec. 4.
	_____
	From the C-S-SW 1/64 sec. cor. of sec. 4.
	S. 89° 55' W., on the E. and W. center line of the SW 1/4 SW 1/4 of sec. 4.
8.25	Wash, 8 lks. wide, 1 ft. deep, drains SW.

## Subdivision of Section 4, T. 15 S., R. 12 E.

Chains

10.034 The SW-SW  $1/64$  sec. cor. of sec. 4.20.068 The S-S  $1/64$  sec. cor. of secs. 4 and 5.Subdivision of the SE $\frac{1}{4}$ SW $\frac{1}{4}$ .From the E-W  $1/64$  sec. cor. of secs. 4 and 9.North, on the N. and S. center line of the SE $\frac{1}{4}$ SW $\frac{1}{4}$  of sec. 4.

8.55 Wash, 6 lks. wide, 1 ft. deep, drains WSW.

10.026 Point for the SE-SW  $1/64$  sec. cor. of sec. 4, at the intersection of the E. and W. center line of the SE $\frac{1}{4}$ SW $\frac{1}{4}$  of sec. 4.Set an iron post, 28 ins. long,  $2\frac{1}{2}$  ins. diam., 24 ins. in the ground, over a deposit of broken glass, with brass cap mkd.

S 4  
SESW  
1/64  
1953

20.052 The C-E-SW  $1/64$  sec. cor. of sec. 4.From the C-S-S  $1/64$  sec. cor. of sec. 4.S.  $89^{\circ} 55'$  W., on the E. and W. center line of the SE $\frac{1}{4}$ SW $\frac{1}{4}$  of sec. 4.10.034 The SE-SW  $1/64$  sec. cor. of sec. 4.20.068 The C-S-SW  $1/64$  sec. cor. of sec. 4.

## Subdivision of Section 5, T. 15 S., R. 12 E.

From the  $\frac{1}{4}$  sec. cor. of secs. 5 and 8.N.  $0^{\circ} 01'$  W., on the N. and S. center line of sec. 5.

Over nearly level land, through undergrowth.

1.95 Bladed road, bears E. and W.

9.15 Wash, 15 lks. wide, 3 ft. deep, drains WNW.

10.025 Point for the C-S-S  $1/64$  sec. cor. of sec. 5.Set an iron post, 28 ins. long,  $2\frac{1}{2}$  ins. diam., 24 ins. in the ground, over a deposit of broken glass, with brass cap mkd.

C  
SS 1/64 | S 5  
C  
1953

12.05 Wash, 15 lks. wide, 3 ft. deep, drains WNW.

18.35 Wash, 8 lks. wide, 1 ft. deep, drains WNW.

20.05 Point for the C-S  $1/16$  sec. cor. of sec. 5.Set an iron post, 28 ins. long,  $2\frac{1}{2}$  ins. diam., 24 ins. in the ground, over a deposit of broken glass, with brass cap mkd.

## Subdivision of Section 5, T. 15 S., R. 12 E.

Chains	
	$\begin{array}{c} C \\ S \frac{1}{16} \left  S 5 \\ C \\ 1953 \end{array}$
30.075	<p>Point for the C-N-S <math>\frac{1}{64}</math> sec. cor. of sec. 5.</p> <p>Set an iron post, 28 ins. long, <math>2\frac{1}{2}</math> ins. diam., 24 ins. in the ground, over a deposit of broken glass, with brass cap mkd.</p>
	$\begin{array}{c} C \\ NS \frac{1}{64} \left  S 5 \\ C \\ 1953 \end{array}$
40.10	<p>Point for the C <math>\frac{1}{4}</math> sec. cor. of sec. 5, at the intersection of the E. and W. center line of sec. 5.</p> <p>Set an iron post, 28 ins. long, <math>2\frac{1}{2}</math> ins. diam., 24 ins. in the ground, over a deposit of broken glass, with brass cap mkd.</p>
	$\begin{array}{c} C \frac{1}{4} S 5 \\ 1953 \end{array}$
42.10	Wash, 12 lks. wide, 2 ft. deep, drains WNW.
44.75	Wash, 6 lks. wide, 1 ft. deep, drains W.
50.121	<p>Point for the C-S-N <math>\frac{1}{64}</math> sec. cor. of sec. 5.</p> <p>Set an iron post, 28 ins. long, <math>2\frac{1}{2}</math> ins. diam., 24 ins. in the ground, over a deposit of broken glass, with brass cap mkd.</p>
	$\begin{array}{c} C \\ SN \frac{1}{64} \left  S 5 \\ C \\ 1953 \end{array}$
60.142	<p>Point for the C-N <math>\frac{1}{16}</math> sec. cor. of sec. 5.</p> <p>Set an iron post, 28 ins. long, <math>2\frac{1}{2}</math> ins. diam., 24 ins. in the ground, over a deposit of broken glass, with brass cap mkd.</p>
	$\begin{array}{c} C \\ N \frac{1}{16} \left  S 5 \\ C \\ 1953 \end{array}$
66.35	Old road, bears NE. and SW.
69.60	Wash, 6 lks. wide, 1 ft. deep, drains W.
70.163	<p>Point for the C-N-N <math>\frac{1}{64}</math> sec. cor. of sec. 5.</p> <p>Set an iron post, 28 ins. long, <math>2\frac{1}{2}</math> ins. diam., 24 ins. in the ground, over a deposit of broken glass, with brass cap mkd.</p>
	$\begin{array}{c} C \\ NN \frac{1}{64} \left  S 5 \\ C \\ 1953 \end{array}$
77.70	Gas pipe line, bears NE. and SW.

## Subdivision of Section 5, T. 15 S., R. 12 E.

Chains

80.419

Intersect the S. bdy. of sec. 32, T. 14 S., R. 12 E., point for the  $\frac{1}{4}$  sec. cor. of sec. 5, midway between the closing corners of secs. 4 and 5, and secs. 5 and 6.

Set an iron post, 28 ins. long,  $2\frac{1}{2}$  ins. diam., 24 ins. in the ground, over a deposit of broken glass, with brass cap mkd.

S 5  
1953

From this corner the  $\frac{1}{4}$  sec. cor. of sec. 32, T. 14 S., R. 12 E., bears N.  $89^{\circ} 42'$  E., 2.72 chs. dist.

From the  $\frac{1}{4}$  sec. cor. of secs. 4 and 5.

S.  $89^{\circ} 52'$  W., on the E. and W. center line of sec. 5.

Over nearly level land, through undergrowth.

10.049

Point for the C-E-E-  $1/64$  sec. cor. of sec. 5.

Set an iron post, 28 ins. long,  $2\frac{1}{2}$  ins. diam., 24 ins. in the ground, over a deposit of broken glass, with brass cap mkd.

EE  $1/64$   
C ————— C  
S 5  
1953

20.098

Point for the C-E  $1/16$  sec. cor. of sec. 5.

Set an iron post, 28 ins. long,  $2\frac{1}{2}$  ins. diam., 24 ins. in the ground, over a deposit of broken glass, with brass cap mkd.

E  $1/16$   
C ————— C  
S 5  
1953

30.147

Point for the C-W-E  $1/64$  sec. cor. of sec. 5.

Set an iron post, 28 ins. long,  $2\frac{1}{2}$  ins. diam., 24 ins. in the ground, over a deposit of broken glass, with brass cap mkd.

WE  $1/64$   
C ————— C  
S 5  
1953

31.65

Shallow wash, drains WNW.

37.65

Wash, 8 lks. wide, 1 ft. deep, drains WNW.

40.196

The C  $\frac{1}{4}$  sec. cor. of sec. 5.

42.90

Wash, 8 lks. wide, 1 ft. deep, drains WNW.

64.30

Gas pipe line, bears NE. and SW.

65.20

Wash, 8 lks. wide, 2 ft. deep, drains WNW.

80.385

The  $\frac{1}{4}$  sec. cor. of secs. 5 and 6.

Subdivision of the NE  $\frac{1}{4}$ .

From the C-E  $1/16$  sec. cor. of sec. 5.

## Subdivision of Section 5, T. 15 S., R. 12 E.

Chains	
	N. 0° 01' W., on the N. and S. center line of the NE $\frac{1}{4}$ of sec. 5.
7.45	Wash, 10 lks. wide, 3 ft. deep, drains W.
10.025	Point for the C-S-NE $\frac{1}{64}$ sec. cor. of sec. 5.
	Set an iron post, 28 ins. long, 2 $\frac{1}{2}$ ins. diam., 2 $\frac{1}{4}$ ins. in the ground, over a deposit of broken glass, with brass cap mkd.
	S 5 CSNE $\frac{1}{64}$ 1953
14.30	Wash, 10 lks. wide, 2 ft. deep, drains WNW.
20.05	Point for the NE $\frac{1}{16}$ sec. cor. of sec, 5, at the intersection of the E. and W. center line of the NE $\frac{1}{4}$ of sec. 5.
	Set an iron post, 28 ins. long, 2 $\frac{1}{2}$ ins. diam., 2 $\frac{1}{4}$ ins. in the ground, over a deposit of broken glass, with brass cap mkd.
	NE $\frac{1}{16}$ S 5 1953
21.60	Wash, 10 lks. wide, 2 ft. deep, drains WNW.
30.075	Point for the C-N-NE $\frac{1}{64}$ sec. cor. of sec. 5.
	Set an iron post, 28 ins. long, 2 $\frac{1}{2}$ ins. diam., 2 $\frac{1}{4}$ ins. in the ground, over a deposit of broken glass, with brass cap mkd.
	S 5 CNNE $\frac{1}{64}$ 1953
40.378	Intersect the S. bdy. of sec. 32, T. 14 S., R. 12 E., at point for the E $\frac{1}{16}$ sec. cor. of sec. 5, as determined in resurvey of the S. bdy. of sec. 32.
	Set an iron post, 28 ins. long, 2 $\frac{1}{2}$ ins. diam., 2 $\frac{1}{4}$ ins. in the ground, over a deposit of broken glass, with brass cap mkd.
	<u>E <math>\frac{1}{16}</math> S 5</u> 1953
	From the N $\frac{1}{16}$ sec. cor of secs. 4 and 5.
	S. 89° 50' W., on the E. and W. center line of the NE $\frac{1}{4}$ of sec. 5.
3.45	Wash, 6 lks. wide, 1 ft. deep, drains WSW.
9.95	Wash, 5 lks. wide, 1 ft. deep, drains WSW.
10.049	Point for the C-E-NE $\frac{1}{64}$ sec. cor. of sec. 5.
	Set an iron post, 28 ins. long, 2 $\frac{1}{2}$ ins. diam., 2 $\frac{1}{4}$ ins. in the ground, over a deposit of broken glass, with brass cap mkd.
	S 5 CENE $\frac{1}{64}$ 1953
20.098	The NE $\frac{1}{16}$ sec. cor. of sec. 5.

Subdivision of Section 5, T. 15 S., R. 12 E.

- Chains  
30.149 Point for the C-W-NE 1/64 sec. cor. of sec. 5.  
Set an iron post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, over a deposit of broken glass, with brass cap mkd.
- S 5  
CWNE  
1/64  
1953
- 33.20 Wash, 5 lks. wide, 1 ft. deep, drains WINW.
- 40.20 The C-N 1/16 sec. cor. of sec. 5.

Subdivision of the NE 1/4 NE 1/4.

- From the C-E-NE 1/64 sec. cor. of sec. 5.  
N. 0° 01' W., on the N. and S. center line of the NE 1/4 NE 1/4 of sec. 5.
- 3.85 Wash, 8 lks. wide, 1 ft. deep, drains W.
- 8.25 Wash, 7 lks. wide, 2 ft. deep, drains WINW.
- 10.024 Point for the NE-NE 1/64 sec. cor. of sec. 5, at the intersection of the E. and W. center line of the NE 1/4 NE 1/4 of sec. 5.  
Set an iron post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, over a deposit of broken glass, with brass cap mkd.
- S 5  
NENE  
1/64  
1953
- 18.85 Wash, 6 lks. wide, 1 ft. deep, drains W.
- 20.348 Intersect the S. bdy. of sec. 32, T. 14 S., R. 12 E., at point for the E-E 1/64 sec. cor. of sec. 5, as determined in resurvey of the S. bdy. of sec. 32.  
Set an iron post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, over a deposit of broken glass, with brass cap mkd.

EE 1/64 S 5

1953

- From the N-N 1/64 sec. cor. of secs. 4 and 5.  
S. 89° 50' W., on the E. and W. center line of the NE 1/4 NE 1/4 of sec. 5.
- 10.049 The NE-NE 1/64 sec. cor. of sec. 5.
- 20.098 The C-N-NE 1/64 sec. cor. of sec. 5.

Subdivision of the NW 1/4 NE 1/4.

- From the C-W-NE 1/64 sec. cor. of sec. 5.  
N. 0° 01' W., on the N. and S. center line of the NW 1/4 NE 1/4 of sec. 5.
- 3.60 Wash, 10 lks. wide, 2 ft. deep, drains NW.
- 7.60 Wash, 8 lks. wide, 2 ft. deep, drains W.
- 10.024 Point for the NW-NE 1/64 sec. cor. of sec. 5, at the intersection of

## Subdivision of Section 5, T. 15 S., R. 12 E.

Chains	
	<p>the E. and W. center line of the NW<math>\frac{1}{4}</math>NE<math>\frac{1}{4}</math> of sec. 5.</p> <p>Set an iron post, 28 ins. long, 2<math>\frac{1}{2}</math> ins. diam., 24 ins. in the ground, over a deposit of broken glass, with brass cap mkd.</p> <p style="text-align: center;">S 5 NWNE 1/64 1953</p>
17.50	Old road, bears NE. and SW.
20.302	<p>Intersect the S. bdy. of sec. 32, T. 14 S., R. 12 E., at point for the W-E 1/64 sec. cor. of sec. 5, as determined in resurvey of the S. bdy. of sec. 32.</p> <p>Set an iron post, 28 ins. long, 2<math>\frac{1}{2}</math> ins. diam., 24 ins. in the ground, over a deposit of broken glass, with brass cap mkd.</p> <p style="text-align: center;">WE 1/64 S 5 1953</p> <p>From the C-N-NE 1/64 sec. cor. of sec. 5.</p> <p>S. 89° 50' W., on the E. and W. center line of the NW<math>\frac{1}{4}</math>NE<math>\frac{1}{4}</math> of sec. 5.</p>
10.05	The NW-NE 1/64 sec. cor. of sec. 5.
16.60	Old road, bears NE. and SW.
20.10	The C-N-N 1/64 sec. cor. of sec. 5.
Subdivision of the SW $\frac{1}{4}$ NE $\frac{1}{4}$ .	
	<p>From the C-W-E 1/64 sec. cor. of sec. 5.</p> <p>N. 0° 01' W., on the N. and S. center line of the SW<math>\frac{1}{4}</math>NE<math>\frac{1}{4}</math> of sec. 5.</p>
10.024	<p>Point for the SW-NE 1/64 sec. cor. of sec. 5, at the intersection of the E. and W. center line of the SW<math>\frac{1}{4}</math>NE<math>\frac{1}{4}</math> of sec. 5.</p> <p>Set an iron post, 28 ins. long, 2<math>\frac{1}{2}</math> ins. diam., 24 ins. in the ground, over a deposit of broken glass, with brass cap mkd.</p> <p style="text-align: center;">S 5 SWNE 1/64 1953</p>
15.55	Wash, 8 lks. wide, 2 ft. deep, drains W.
18.85	Wash, 7 lks. wide, 2 ft. deep, drains NW.
20.048	The C-W-NE 1/64 sec. cor. of sec. 5.
Subdivision of the SE $\frac{1}{4}$ NE $\frac{1}{4}$ .	
	<p>From the C-S-NE 1/64 sec. cor. of sec. 5.</p> <p>S. 89° 51' W., on the E. and W. center line of the SW<math>\frac{1}{4}</math>NE<math>\frac{1}{4}</math> of sec. 5.</p>
10.05	The SW-NE 1/64 sec. cor. of sec. 5.
20.10	The C-S-N 1/64 sec. cor. of sec. 5.

## BOOK 4451

## Subdivision of Section 5, T. 15 S., R. 12 E.

Chains	From the C-E-E 1/64 sec. cor. of sec. 5. N. 0° 01' W., on the N. and S. center line of the SE 1/4 NE 1/4 of sec. 5.
10.024	Point for the SE-NE 1/64 sec. cor. of sec. 5, at the intersection of the E. and W. center line of the SE 1/4 NE 1/4 of sec. 5. Set an iron post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, over a deposit of broken glass, with brass cap mkd.  S 5 SENE 1/64 1953
11.95	Wash, 8 lks. wide, 2 ft. deep, drains W.
20.048	The C-E-NE 1/64 sec. cor. of sec. 5.  From the S-N 1/64 sec. cor. of secs. 4 and 5. S. 89° 51' W., on the E. and W. center line of the SE 1/4 NE 1/4 of sec. 5.
0.95	Wash, 6 lks. wide, 1 ft. deep, drains WNW.
10.049	The SE-NE 1/64 sec. cor. of sec. 5.
15.20	Wash, 6 lks. wide, 1 ft. deep, drains WSW.
20.098	The C-S-NE 1/64 sec. cor. of sec. 5.
Subdivision of the SE 1/4.	
	From the E 1/16 sec. cor. of secs. 5 and 8. N. 0° 01' W., on the N. and S. center line of the SE 1/4 of sec. 5.
1.95	Wash, 10 lks. wide, 4 ft. deep, drains WNW.
4.20	Wash, 8 lks. wide, 3 ft. deep, drains WNW.
8.65	Telephone line, bears N. 57° 45' E. and S. 57° 45' W.
9.665	Center line of Ajo Highway, bears N. 57° 37' E. and S. 57° 37' W., cor. of lots 56, 63, 65, and 66, set nail.  from which  A wooden stake, 2 ft. long, 2 ins. sq., set 12 ins. in the ground for a reference, bears S. 0° 01' E., 100 lks. dist., mkd. WP.
10.025	Point for the C-S-SE 1/64 sec. cor. of sec. 5: Set an iron post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.  S 5 CSSE 1/64 1953
20.05	Point for the SE 1/16 sec. cor. of sec. 5, at the intersection of the E. and W. center line of the SE 1/4 of sec. 5. Set an iron post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, over a deposit of broken glass, with brass cap mkd.  SE 1/16 S 5 1953

## Subdivision of Section 5, T. 15 S., R. 12 E.

Chains	
30.075	Point for the C-N-SE $1/64$ sec. cor. of sec. 5. Set an iron post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 24 ins. in the ground, over a deposit of broken glass, with brass cap mkd.  S. 5 CNSE $1/64$ 1953
36.70	Wash, 8 lks. wide, 2 ft. deep, drains WNW.
40.10	The C-E $1/16$ sec. cor. of sec. 5.  From the S $1/16$ sec. cor. of secs. 4 and 5. S. $89^{\circ} 52'$ W., on the E. and W. center line of the SE $\frac{1}{4}$ of sec. 5.
2.10	Telephone line, bears N. $57^{\circ} 45'$ E. and S. $57^{\circ} 45'$ W.
3.67	Center line of Ajo Highway, bears N. $57^{\circ} 37'$ E. and S. $57^{\circ} 37'$ W., cor. of lots 52 and 53, set nail.  from which  A wooden stake, 2 ft. long, 2 ins. sq., set 12 ins. in the ground for a reference, bears N. $89^{\circ} 52'$ E., 150 lks. dist., mkd. WP.  A wooden stake, 2 ft. long, 2 ins. sq., set 12 ins. in the ground for a reference, bears S. $89^{\circ} 52'$ W., 150 lks. dist., mkd. WP.
10.093	Point for the C-E-SE $1/64$ sec. cor. of sec. 5. Set an iron post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 24 ins. in the ground, over a deposit of broken glass, with brass cap mkd.  S 5 CESE $1/64$ 1953
20.106	The SE $1/16$ sec. cor. of sec. 5.
30.153	Point for the C-W-SE $1/64$ sec. cor. of sec. 5. Set an iron post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 24 ins. in the ground, over a deposit of broken glass, with brass cap mkd.  S 5. CWSE $1/64$ 1953
33.95	Wash, 5 lks. wide, 1 ft. deep, drains NW.
40.20	The C-S $1/16$ sec. cor. of sec. 5.
	Subdivision of the NE $\frac{1}{4}$ SE $\frac{1}{4}$ .
	From the C-E-SE $1/64$ sec. cor. of sec. 5. N. $0^{\circ} 01'$ W., on the N. and S. center line of the NE $\frac{1}{4}$ SE $\frac{1}{4}$ of sec. 5.
10.025	Point for the NE-SE $1/64$ sec. cor. of sec. 5, at the intersection of the E. and W. center line of the NE $\frac{1}{4}$ SE $\frac{1}{4}$ of sec. 5. Set an iron post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 24 ins. in the ground, over a deposit of broken glass, with brass cap mkd.

## Subdivision of Section 5, T. 15 S., R. 12 E.

Chains

S 5  
NESE  
1/64  
1953

15.15 Wash, 15 lks. wide, 1 ft. deep, drains W.

20.05 The C-E-E 1/64 sec. cor. of sec. 5.

---

From the N-S 1/64 sec. cor. of secs. 4 and 5.

S. 89° 52' W., on the E. and W. center line of the NE $\frac{1}{4}$ SE $\frac{1}{4}$  of sec. 5.

10.05 The NE-SE 1/64 sec. cor. of sec. 5.

11.80 Wash, 6 lks. wide, 1 ft. deep, drains WNW.

16.30 Wash, 5 lks. wide, 1 ft. deep, drains WNW.

20.10 The C-N-SE 1/64 sec. cor. of sec. 5.

Subdivision of the NW $\frac{1}{4}$ SE $\frac{1}{4}$ .

From the C-W-SE 1/64 sec. cor. of sec. 5.

N. 0° 01' W., on the N. and S. center line of the NW $\frac{1}{4}$ SE $\frac{1}{4}$  of sec. 5.

10.024 Point for the NW-SE 1/64 sec. cor. of sec. 5, at the intersection of the E. and W. center line of the NW $\frac{1}{4}$ SE $\frac{1}{4}$  of sec. 5.

Set an iron post, 28 ins. long, 2 $\frac{1}{2}$  ins. diam., 24 ins. in the ground, over a deposit of broken glass, with brass cap mkd.

S 5  
NWSE  
1/64  
1953

20.048 The C-W-E 1/64 sec. cor. of sec. 5.

---

From the C-N-SE 1/64 sec. cor. of sec. 5.

S. 89° 52' W., on the E. and W. center line of the NW $\frac{1}{4}$ SE $\frac{1}{4}$  of sec. 5.

10.046 The NW-SE 1/64 sec. cor. of sec. 5.

20.092 The C-N-S 1/64 sec. cor. of sec. 5.

Subdivision of the SW $\frac{1}{4}$ SE $\frac{1}{4}$ .

From the W-E 1/64 sec. cor. of secs. 5 and 8.

N. 0° 01' W., on the N. and S. center line of the SW $\frac{1}{4}$ SE $\frac{1}{4}$  of sec. 5.

2.30 Telephone line, bears N. 57° 45' E. and S. 57° 45' W.

3.322 Center line of Ajo Highway, bears N. 57° 37' E. and S. 57° 37' W., cor. of lots 62, 63, and 64, set nail.

from which

A wooden stake, 2 ft. long, 2 ins. sq., set 12 ins. in the ground for a reference, bears S. 0° 01' E., 100 lks. dist., mkd. WP.

A wooden stake, 2 ft. long, 2 ins. sq., set 12 ins. in the ground for a reference, bears N. 0° 01' W., 100 lks. dist., mkd. WP.

## Subdivision of Section 5, T. 15 S., R. 12 E.

Chains	
5.55	Wash, 30 lks. wide, 4 ft. deep, drains WNW.
10.026	Point for the SW-SE $1/64$ sec. cor. of sec. 5, at the intersection of the E. and W. center line of the SW-SE $1/4$ of sec. 5.  Set an iron post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 24 ins. in the ground, over a deposit of broken glass, with brass cap mkd.  S 5 SWSE $1/64$ 1953
15.75	Wash, 8 lks. wide, 1 ft. deep, drains WNW.
20.052	The C-W-SE $1/64$ sec. cor. of sec. 5.  From the C-S-SE $1/64$ sec. cor. of sec. 5.  S. $89^{\circ} 52'$ W., on the E. and W. center line of the SW-SE $1/4$ of sec. 5.
10.048	The SW-SE $1/64$ sec. cor. of sec. 5.
16.20	Wash, 25 lks. wide, 5 ft. deep, drains WNW.
17.90	Wash, 8 lks. wide, 1 ft. deep, drains WNW.
20.096	The C-S-S $1/64$ sec. cor. of sec. 5.
Subdivision of the SE-SE $1/4$ .	
	From the E-E $1/64$ sec. cor. of secs. 5 and 8.  N. $0^{\circ} 01'$ W., on the N. and S. center line of the SE-SE $1/4$ of sec. 5.
1.55	Wash, 8 lks. wide, 1 ft. deep, drains W.
8.35	Wash, 6 lks. wide, 1 ft. deep, drains W.
10.025	Point for the SE-SE $1/64$ sec. cor. of sec. 5, at the intersection of the E. and W. center line of the SE-SE $1/4$ of sec. 5.  Set an iron post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 24 ins. in the ground, over a deposit of broken glass, with brass cap mkd.  S 5 SESE $1/64$ 1953
15.00	Telephone line, bears N. $57^{\circ} 45'$ E. and S. $57^{\circ} 45'$ W.
15.70	Center line of Ajo Highway, bears N. $57^{\circ} 37'$ E. and S. $57^{\circ} 37'$ W., cor. of lots 54 and 55, set nail.  from which  A wooden stake, 2 ft. long, 2 ins. sq., set 12 ins. in the ground for a reference, bears S. $0^{\circ} 01'$ E., 100 lks. dist., mkd. WP.  A wooden stake, 2 ft. long, 2 ins. sq., set 12 ins. in the ground for a reference, bears N. $0^{\circ} 01'$ W., 100 lks. dist., mkd. WP.
20.05	The C-E-SE $1/64$ sec. cor. of sec. 5.  From the S-S $1/64$ sec. cor. of secs. 4 and 5.

## Subdivision of Section 5, T. 15 S., R. 12 E.

- Chains
- S. 89° 52' W., on the E. and W. center line of the SE  $\frac{1}{4}$  SE  $\frac{1}{4}$  of sec. 5.
- 10.052 The SE-SE  $\frac{1}{64}$  sec. cor. of sec. 5.
- 17.90 Telephone line, bears N. 57° 45' E. and S. 57° 45' W.
- 19.536 Center line of Ajo Highway, bears N. 57° 37' E. and S. 57° 37' W., cor. of lots 56 and 66, set nail.
- from which
- A wooden stake, 2 ft. long, 2 ins. sq., set 12 ins. in the ground, for a reference, bears N. 89° 52' E., 100 lks. dist., mkd. WP.
- 20.104 The C-S-SE  $\frac{1}{64}$  sec. cor. of sec. 5.

## Subdivision of Section 7, T. 15 S., R. 12 E.

- From the  $\frac{1}{4}$  sec. cor. of secs. 7 and 18.
- N. 0° 04' W., on the N. and S. center line of sec. 7.
- Over nearly level land, through undergrowth.
- 10.024 Point for the C-S-S  $\frac{1}{64}$  sec. cor. of sec. 7.
- Set an iron post, 28 ins. long,  $2\frac{1}{2}$  ins. diam., 24 ins. in the ground, over a deposit of broken glass, with brass cap mkd.
- C  
SS  $\frac{1}{64}$  | S 7  
C  
1953
- 20.048 Point for the C-S  $\frac{1}{16}$  sec. cor. of sec. 7.
- Set an iron post, 28 ins. long,  $2\frac{1}{2}$  ins. diam., 24 ins. in the ground, over a deposit of broken glass, with brass cap mkd.
- C  
S  $\frac{1}{16}$  | S 7  
C  
1953
- 27.50 Wash, 8 lks. wide, 2 ft. deep, drains NW.
- 28.20 Telephone line, bears N. 70° E. and S. 70° W.
- 28.95 Center line of Ajo Highway, bears N. 69° 55' E. and S. 69° 55' W.
- 40.096 Point for the C  $\frac{1}{4}$  sec. cor. of sec. 7, at the intersection of the E. and W. center line of sec. 7.
- Set an iron post, 28 ins. long,  $2\frac{1}{2}$  ins. diam., 24 ins. in the ground, over a deposit of broken glass, with brass cap mkd.
- C  $\frac{1}{4}$  S 7  
1953
- 80.176 The  $\frac{1}{4}$  sec. cor. of secs. 6 and 7, which is monumented with an iron post, 1 in. diam., set and marked as described in the official record.

From the  $\frac{1}{4}$  sec. cor. of secs. 7 and 8.

S. 89° 51' W., on the E. and W. center line of sec. 7.

Sudbuvivison of Section 7, T. 15 S., R. 12 E.

Chains	Over nearly level land, through undergrowth.
7.50	Telephone line, bears N. 70° E. and S. 70° W.
9.45	Center line of Ajo Highway, bears N. 69° 55' E. and S. 69° 55' W.
20.067	Point for the C-E 1/16 sec. cor. of sec. 7. Set an iron post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, over a deposit of broken glass, with brass cap mkd. E 1/16 C-----C S 7 1953
40.134	The C ¼ sec. cor. of sec. 7.
44.95	Wash, 15 lks. wide, 2 ft. deep, drains WNW.
46.75	Wash, 12 lks. wide, 2 ft. deep, drains WNW.
69.85	Wash, 20 lks. wide, 2 ft. deep, drains NW.
82.47	The ¼ sec. cor. of secs. 7 and 12, on the W. bdy. of the Tp. Subdivision of the SE¼. From the E 1/16 sec. cor. of secs. 7 and 18. N. 0° 03' W., on the N. and S. center line of the SE¼ of sec. 7.
1.90	Wash, 12 lks. wide, 3 ft. deep, drains NW.
5.25	Wash, 12 lks. wide, 2 ft. deep, drains NW.
10.023	Point for the C-S-SE 1/64 sec. cor. of sec. 7. Set an iron post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, over a deposit of broken glass, with brass cap mkd. S 7 C S SE 1/64 1953
14.30	Power line, bears NE. and SW.
18.50	Wash, 10 lks. wide, 2 ft. deep, drains NW.
20.046	Point for the SE 1/16 sec. cor. of sec. 7, at the intersection of the E. and W. center line of the SE¼ of sec. 7. Set an iron post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, over a deposit of broken glass, with brass cap mkd. S 7 SE 1/16 1953
35.50	Telephone line, bears N. 70° E. and S. 70° W.
36.23	Center line of Ajo Highway, bears N. 69° 55' E., and S. 69° 55' W.
40.094	The C-E 1/16 sec. cor. of sec. 7. From the S 1/16 sec. cor. of secs. 7 and 8. S. 89° 51' W., on the E. and W. center line of the SE¼ of sec. 7.
10.032	Point for the C-E-SE 1/64 sec. cor. of sec. 7.

Subdivision of Section 7, T. 15 S., R. 12 E.


Chains	Set an iron post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, over a deposit of broken glass, with brass cap mkd. S 7 C-SE 1/64 1953
20.064	The SE 1/16 sec. cor. of sec. 7.
21.15	Wash, 18 lks. wide, 2 ft. deep, drains NW.
30.095	Point for the C-W-SE 1/64 sec. cor. of sec. 7. Set an iron post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, over a deposit of broken glass, with brass cap mkd. S 7 C-W-SE 1/64 1953
52.90	Wash, 12 lks. wide, 2 ft. deep, drains NW.
40.126	The C-S 1/16 sec. cor. of sec. 7.
Subdivision of the SW 1/4 SE 1/4	
7.25	From the W-E 1/64 sec. cor. of secs. 7 and 18. N. 0° 04' W., on the N. and S. center line of the SW 1/4 SE 1/4 of sec. 7. Power Line, bears NE. and SW.
10.023	Point for the SW-SE 1/64 sec. cor. of sec. 7, at the intersection of the E. and W. center line of the SW 1/4 SE 1/4 of sec. 7. Set an iron post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, over a deposit of broken glass, with brass cap mkd. S 7 SW-SE 1/64 1953
15.35	Wash, 20 lks. wide, 2 ft. deep, drains W.
20.046	The C-W-SE 1/64 sec. cor. of sec. 7.
6.15	From the C-S-SE 1/64 sec. cor. of sec. 7. S. 89° 51' W., on the E. and W. center line of the SW 1/4 SE 1/4 of sec. 7. Power line, bears NE. and SW.
6.20	Wash, 20 lks. wide, 3 ft. deep, drains NW.
10.03	The SW-SE 1/64 sec. cor. of sec. 7.
20.06	The C-S-S 1/64 sec. cor. of sec. 7.
Subdivision of the SE 1/4 SE 1/4	
10.023	From the E-E 1/64 sec. cor. of secs. 7 and 18. N. 0° 02' W., on the N. and S. center line of the SE 1/4 SE 1/4 of sec. 7. Point for the SE-SE 1/64 sec. cor. of sec. 7, at the intersection of the E. and W. center line of the SE 1/4 SE 1/4 of sec. 7. Set an iron post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, over a deposit of broken glass, with brass cap mkd.

## Subdivision of Section 7, T. 15 S., R. 12 E.

Chains	
	S 7 SESE 1/64 1953
20.046	The C-E-SE 1/64 sec. cor. of sec. 7. <b>Note: See page 47 for E. and W. center line of SE 1/4 sec. 7.</b>
	Subdivision of Section 8, T. 15 S., R. 12 E.
	From the 1/4 sec. cor. of secs. 8 and 17. N. 0° 01' W., on the N. and S. center line of sec. 8. Over nearly level land.
4.70	Wash, 8 lks. wide, 1 ft. deep, drains NW.
18.20	Wash, 10 lks. wide, 1 ft. deep, drains NW.
38.30	Wash, 10 lks. wide, 1 ft. deep, drains NW.
40.08	Point for the C 1/4 sec. cor. of sec. 8, at the intersection of the E. and W. center line of sec. 8.  Set an iron post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, over a deposit of broken glass, with brass cap mkd.
	C 1/4 S 8  1953
41.20	Wash, 6 lks. wide, 2 ft. deep, drains W.
41.40	Old road, bears E. and W.
49.30	Wash, 20 lks. wide, 3 ft. deep, drains WNW.
50.106	Point for the C-S-N 1/64 sec. cor. of sec. 8.  Set an iron post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, over a deposit of broken glass, with brass cap mkd.
	C SN 1/64   S 8 C 1953
57.40	Power line, bears NE. and SW.
60.132	Point for the C-N 1/16 sec. cor. of sec. 8.  Set an iron post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, over a deposit of broken glass, with brass cap mkd.
	C N 1/16   S 8 C 1953
61.75	Old road, bears WNW. and SSE.
66.45	Wash, 20 lks. wide, 4 ft. deep, drains NNW.
70.158	Point for the C-N-N 1/64 sec. cor. of sec. 8.  Set an iron post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, over a deposit of broken glass, with brass cap mkd.

Subdivision of Section 8, T. 15 S., R. 12 E.

Chains



73.25 Telephone line, bears N. 43° 30' E. and S. 43° 30' W.

74.538 Center line of Ajo Highway, bears N. 42° 33' E. and S. 42° 33' W., cor. of lots 8, 9, and 10, set nail.

from which

A wooden stake, 2 ft. long, 2 ins. sq., set 12 ins. in the ground for a reference, bears S. 0° 01' E., 100 lks. dist., mkd. WP.

A wooden stake, 2 ft. long, 2 ins. sq., set 12 ins. in the ground for a reference, bears N. 0° 01' W., 130 lks. dist., mkd. WP.

80.184 The  $\frac{1}{4}$  sec. cor. of secs. 5 and 8.

From the  $\frac{1}{4}$  sec. cor. of secs. 8 and 9.


S. 89° 53' W., on the E. and W. center line of sec. 8.

Over nearly level land.

4.25 Wash, 7 lks. wide, 1 ft. deep, drains WNW.


10.048 Point for the C-E-E  $\frac{1}{64}$  sec. cor. of sec. 8.

Set an iron post, 28 ins. long,  $2\frac{1}{2}$  ins. diam., 24 ins. in the ground, over a deposit of broken glass, with brass cap mkd.



20.096 Point for the C-E  $\frac{1}{16}$  sec. cor. of sec. 8.


Set an iron post, 28 ins. long,  $2\frac{1}{2}$  ins. diam., 24 ins. in the ground, over a deposit of broken glass, with brass cap mkd.



21.25 Wash, 6 lks. wide, 2 ft. deep, drains NW.

30.114 Point for the C-W-E  $\frac{1}{64}$  sec. cor. of sec. 8.

Set an iron post, 28 ins. long,  $2\frac{1}{2}$  ins. diam., 24 ins. in the ground, over a deposit of broken glass, with brass cap mkd.



40.192 The C  $\frac{1}{4}$  sec. cor. of sec. 8.

42.90 Wash, 10 lks. wide, 3 ft. deep, drains NW.

50.24 Point for the C-E-W  $\frac{1}{64}$  sec. cor. of sec. 8.

Set an iron post, 28 ins. long,  $2\frac{1}{2}$  ins. diam., 24 ins. in the ground, over a deposit of broken glass, with brass cap mkd.

## Subdivision of Section 8, T. 15 S., R. 12 E.

Chains	
	$\begin{array}{c} \text{EW } 1/64 \\ \text{---} \\ \text{C} \quad \text{S } 8 \quad \text{C} \\ 1953 \end{array}$
60.288	<p>Point for the C-W 1/16 sec. cor. of sec. 8.</p> <p>Set an iron post, 28 ins. long, 2½ ins. diam., 2¼ ins. in the ground, over a deposit of broken glass, with brass cap mkd.</p>
	$\begin{array}{c} \text{W } 1/16 \\ \text{---} \\ \text{C} \quad \text{S } 8 \quad \text{C} \\ 1953 \end{array}$
64.40	Power line, bears NE. and SW.
68.45	Wash, 10 lks. wide, 2 ft. deep, drains NW.
70.336	<p>Point for the C-W-W 1/64 sec. cor. of sec. 8.</p> <p>Set an iron post, 28 ins. long, 2½ ins. diam., 2¼ ins. in the ground, over a deposit of broken glass, with brass cap mkd.</p>
	$\begin{array}{c} \text{WW } 1/64 \\ \text{---} \\ \text{C} \quad \text{S } 8 \quad \text{C} \\ 1953 \end{array}$
74.20	Road, bears N. and S.
80.384	The ¼ sec. cor. of secs. 7 and 8.
Subdivision of the NE¼.	
	<p>From the C-E 1/16 sec. cor. of sec. 8.</p> <p>N. 0° 01' W., on the N. and S. center line of the NE¼ of sec. 8.</p>
7.20	Old road, bears E. and W.
10.03	<p>Point for the C-S-NE 1/64 sec. cor. of sec. 8.</p> <p>Set an iron post, 28 ins. long, 2½ ins. diam., 2¼ ins. in the ground, over a deposit of broken glass, with brass cap mkd.</p>
	$\begin{array}{c} \text{S } 8 \\ \text{CSNE} \\ 1/64 \\ 1953 \end{array}$
16.15	Wash, 10 lks. wide, 3 ft. deep, drains W.
20.06	<p>Point for the NE 1/16 sec. cor. of sec. 8, at the intersection of the E. and W. center line of the NE¼ of sec. 8.</p> <p>Set an iron post, 28 ins. long, 2½ ins. diam., 2¼ ins. in the ground, over a deposit of broken glass, with brass cap mkd.</p>
	$\begin{array}{c} \text{NE } 1/16 \text{ S } 8 \\ 1953 \end{array}$
29.35	Wash, 10 lks. wide, 3 ft. deep, drains WNW.
30.088	<p>Point for the C-N-NE 1/64 sec. cor. of sec. 8.</p> <p>Set an iron post, 28 ins. long, 2½ ins. diam., 2¼ ins. in the ground, over a deposit of broken glass, with brass cap mkd.</p>

## Subdivision of Section 8, T. 15 S., R. 12 E.

Chains	
	S 8 CNNE 1/64 1953
31.00	Wash, 10 lks. wide, 3 ft. deep, drains SW.
31.70	Power line, bears NE. and SW.
34.70	Old road, bears NW. and SE.
37.80	Wash, 25 lks. wide, 6 ft. deep, drains WNW.
40.116	The E 1/16 sec. cor. of secs. 5 and 8.
	<hr/> From the N 1/16 sec. cor. of secs. 8 and 9. S. 89° 52' W., on the E, and W. center line of the NE $\frac{1}{4}$ of sec. 8.
10.047	Point for the C-E-NE 1/64 sec. cor. of sec. 8. Set an iron post, 28 ins. long, 2 $\frac{1}{2}$ ins. diam., 24 ins. in the ground, over a deposit of broken glass, with brass cap mkd.
	S 8 CENE 1/64 1953
20.094	The NE 1/16 sec. cor. of sec. 8.
30.142	Point for the C-W-NE 1/64 sec. cor. of sec. 8. Set an iron post, 28 ins. long, 2 $\frac{1}{2}$ ins. diam., 24 ins. in the ground, over a deposit of broken glass, with brass cap mkd.
	S 8 CWNE 1/64 1953
36.40	Power line, bears NE. and SW.
37.90	Wash, 10 lks. wide, 3 ft. deep, drains WNW.
39.10	Old road, bears N. and S.
40.19	The C-N 1/16 sec. cor. of sec. 8.
	Subdivision of the NE $\frac{1}{4}$ -NE $\frac{1}{4}$ . From the C-E-NE 1/64 sec. cor. of sec. 8. N. 0° 01' W., on the N. and S. center line of the NE $\frac{1}{4}$ -NE $\frac{1}{4}$ of sec. 8.
7.20	Wash, 8 lks. wide, 2 ft. deep, drains WNW.
8.30	Wash, 20 lks. wide, 3 ft. deep, drains W.
10.03	Point for the NE-NE 1/64 sec. cor. of sec. 8, at the intersection of the E. and W. center line of the NE $\frac{1}{4}$ -NE $\frac{1}{4}$ of sec. 8. Set an iron post, 28 ins. long, 2 $\frac{1}{2}$ ins. diam., 24 ins. in the ground, over a deposit of broken glass, with brass cap mkd.

## Subdivision of Section 8, T. 15 S., R. 12 E.

Chains

S 8  
NENE  
1/64  
1953

11.55 Old road, bears NE. and SW.

13.95 Wash, 10 lks. wide, 2 ft. deep, drains WSW.

18.65 Wash, 12 lks. wide, 3 ft. deep, drains WSW.

20.06 The E-E 1/64 sec. cor. of secs. 5 and 8.

---

From the N-N 1/64 sec. cor. of secs. 8 and 9.

S. 89° 52' W., on the E. and W. center line of the NE-NE 1/4 of sec. 8.

6.05 Old road, bears WINW. and ESE.

10.047 The NE-NE 1/64 sec. cor. of sec. 8.

12.00 Wash, 6 lks. wide, 1 ft. deep, drains WINW.

18.70 Wash, 5 lks. wide, 1 ft. deep, drains NW.

20.094 The C-N-NE 1/64 sec. cor. of sec. 8.

---

Subdivision of the NW-NE 1/4.

From the C-W-NE 1/64 sec. cor. of sec. 8.

N. 0° 01' W., on the N. and S. center line of the NW-NE 1/4 of sec. 8.

3.70 Wash, 8 lks. wide, 2 ft. deep, drains W.

4.50 Power line, bears NE. and SW.

9.40 Wash, 5 lks. wide, 1 ft. deep, drains WINW.

10.026 Point for the NW-NE 1/64 sec. cor. of sec. 8.

Set an iron post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, over a deposit of broken glass, with brass cap mkd.

S 8  
NWNE  
1/64  
1953

10.90 Wash, 6 lks. wide, 1 ft. deep, drains NW.

20.052 The W-E 1/64 sec. cor. of secs. 5 and 8.

---

From the C-N-NE 1/64 sec. cor. of sec. 8.

S. 89° 52' W., on the E. and W. center line of the NW-NE 1/4 of sec. 8.

1.65 Wash, 5 lks. wide, 1 ft. deep, drains WINW.

10.047 The NW-NE 1/64 sec. cor. of sec. 8.

11.20 Wash, 8 lks. wide, 3 ft. deep, drains WINW.

20.095 The C-N-N 1/64 sec. cor. of sec. 8.

---

Subdivision of the SW-NE 1/4.

## Subdivision of Section 8, T. 15 S., R. 12 E.

Chains	
	From the C-W-E 1/64 sec. cor. of sec. 8.
	N. 0° 01' W., on the N. and S. center line of the SW 1/4 NE 1/4 of sec. 8.
1.00	Old road, bears E. and W.
4.40	Wash, 15 lks. wide, 2 ft. deep, drains NW.
5.30	Wash, 10 lks. wide, 4 ft. deep, drains NW.
6.20	Old road, bears NW. and SE.
10.027	Point for the SW-NE 1/64 sec. cor. of sec. 8, at the intersection of the E. and W. center line of the SW 1/4 NE 1/4 of sec. 8.
	Set an iron post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, over a deposit of broken glass, with brass cap mkd.
	S 8 SWNE 1/64 1953
18.05	Wash, 8 lks. wide, 3 ft. deep, drains W.
20.054	The C-W-NE 1/64 sec. cor. of sec. 8.
	-----
	From the C-S-NE 1/64 sec. cor. of sec. 8.
	S. 89° 53' W., on the E. and W. center line of the SW 1/4 NE 1/4 of sec. 8.
10.048	The SW-NE 1/64 sec. cor. of sec. 8.
15.50	Old road, bears NW. and SE.
20.096	The C-S-N 1/64 sec. cor. of sec. 8.
	-----
	Subdivision of the SE 1/4 NE 1/4.
	From the C-E-E 1/64 sec. cor. of sec. 8.
	N. 0° 01' W., on the N. and S. center line of the SE 1/4 NE 1/4 of sec. 8.
0.30	Old road, bears E. and W.
10.03	Point for the SE-NE 1/64 sec. cor. of sec. 8, at the intersection of the E. and W. center line of the SE 1/4 NE 1/4 of sec. 8.
	Set an iron post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, over a deposit of broken glass, with brass cap mkd.
	S 8 SENE 1/64 1953
14.05	Wash, 8 lks. wide, 2 ft. deep, drains WINW.
20.06	The C-E-NE 1/64 sec. cor. of sec. 8.
	-----
	From the S-N 1/64 sec. cor. of secs. 8 and 9.
	S. 89° 53' W., on the E. and W. center line of the SE 1/4 NE 1/4 of sec. 8.
10.048	The SE-NE 1/64 sec. cor. of sec. 8.
20.096	The C-S-NE 1/64 sec. cor. of sec. 8.

## Subdivision of Section 8, T. 15 S., R. 12 E.

Chains	Subdivision of the NW $\frac{1}{4}$ .
	From the C-W 1/16 sec. cor. of sec. 8.
	N. 0° 02' W., on the N. and S. center line of the NW $\frac{1}{4}$ of sec. 8.
2.00	Old road, bears E. and W.
3.00	Power line, bears NE. and SW.
10.02 $\frac{1}{4}$	Point for the C-S-NW 1/64 sec. cor. of sec. 8. Set an iron post, 28 ins. long, 2 $\frac{1}{2}$ ins. diam., 24 ins. in the ground, over a deposit of broken glass, with brass cap mkd.  S 8 CSNW 1/64 1953
12.43	Telephone line, bears N. 49° 50' E. and S. 52° 25' W.
13.27	Center line of Ajo Highway, bears N. 42° 33' E. and S. 42° 33' W., cor. of lots 46, 47, 48, and 55, set nail:  from which  A wooden stake, 2 ft. long, 2 ins. sq., set 12 ins. in the ground for a reference, bears S. 0° 02' E., 100 lks. dist., mkd. WP.  A wooden stake, 2 ft. long, 2 ins. sq., set 12 ins. in the ground for a reference, bears N. 0° 02' W., 100 lks. dist., mkd. WP.
20.048	Point for the NW 1/16 sec. cor. of sec. 8, at the intersection of the E. and W. center line of the NW $\frac{1}{4}$ of sec. 8. Set an iron post, 28 ins. long, 2 $\frac{1}{2}$ ins. diam., 24 ins. in the ground, over a deposit of broken glass, with brass cap mkd.  NW 1/16 S 8  1953
26.00	Wash, 15 lks. wide, 4 ft. deep, drains NW.
30.073	Point for the C-N-NW 1/64 sec. cor. of sec. 8. Set an iron post, 28 ins. long, 2 $\frac{1}{2}$ ins. diam., 24 ins. in the ground, over a deposit of broken glass, with brass cap mkd.  S 8 CNNW 1/64 1953
31.30	Power line, bears NW. and SE.
35.40	Wash, 25 lks. wide, 4 ft. deep, drains W.
40.098	The W 1/16 sec. cor. of secs. 5 and 8.  From the C-N 1/16 sec. cor. of sec. 8. S. 89° 53' W., on the E. and W. center line of the NW $\frac{1}{4}$ of sec. 8.
5.35	Wash, 10 lks. wide; 1 ft. deep, drains NNW.
10.048	Point for the C-E-NW 1/64 sec. cor. of sec. 8. Set an iron post, 28 ins. long, 2 $\frac{1}{2}$ ins. diam., 24 ins. in the ground, over a deposit of broken glass, with brass cap mkd.

## Subdivision of Section 8, T. 15 S., R. 12 E.

Chains

S 8

CENW

1/64

1953.

11.00 Wash, 20 lks. wide, 5 ft. deep, drains N.

12.00 Telephone line, bears N. 42° 30' E. and S. 42° 30' W.

13.255 Center line of Ajo Highway, bears N. 42° 33' E. and S. 42° 33' W.,  
cor. of lots 23, 25, 45, and 46, set nail.

from which

A wooden stake, 2 ft. long, 2 ins. sq., set 12 ins. in the ground  
for a reference, bears N. 89° 53' E. 100 lks. dist., mkd. WP.A wooden stake, 2 ft. long, 2 ins. sq., set 12 ins. in the ground  
for a reference, bears S. 89° 53' W., 100 lks. dist., mkd. WP.

13.60 Power line, bears NE. and SW.

20.096 The NW 1/16 sec. cor. of sec. 8.

26.45 Wash, 8 lks. wide, 1 ft. deep, drains NNW.

30.144 Point for the C-W-NW 1/64 sec. cor. of sec. 8.

Set an iron post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground,  
over a deposit of broken glass, with brass cap mkd.

S 8

CWNW

1/64

1953

33.40 Wash, 10 lks. wide, 2 ft. deep, drains N.

40.192 The N 1/16 sec. cor. of secs. 7 and 8.

## Subdivision of the NE 1/4 NW 1/4.

From the C-E-NW 1/64 sec. cor. of sec. 8.

N. 0° 01' W., on the N. and S. center line of the NE 1/4 NW 1/4 of sec. 8.

1.20 Wash, 20 lks. wide, 5 ft. deep, drains WINW.

2.20 Telephone line, bears N. 42° 30' E. and S. 42° 30' W.

3.485 Center line of Ajo Highway, bears N. 42° 33' E. and S. 42° 33' W.,  
cor. of lots 23, 24, and 25, set nail.

from which

A wooden stake, 2 ft. long, 2 ins. sq., set 12 ins. in the ground  
for a reference, bears S. 0° 01' E., 100 lks. dist., mkd. WP.A wooden stake, 2 ft. long, 2 ins. sq., set 12 ins. in the ground  
for a reference, bears N. 0° 01' W., 100 lks. dist., mkd. WP.10.025 Point for the NE-NW 1/64 sec. cor. of sec. 8, at the intersection of  
the E. and W. center line of the NE 1/4 NW 1/4 of sec. 8.Set an iron post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground,  
over a deposit of broken glass, with brass cap mkd.

S 8

NENW

1/64

1953

## Subdivision of Section 8, T. 15 S., R. 12 E.

Chains	
13.25	Wash, 20 lks. wide, 5 ft. deep, drains W.
20.05	The E-W 1/64 sec. cor. of secs. 5 and 8.  From the C-N-N 1/64 sec. cor. of sec. 8. S. 89° 53' W., on the E. and W. center line of the NE 1/4 NW 1/4 of sec. 8.
0.45	Wash, 18 lks. wide, 3 ft. deep, drains NW.
2.85	Telephone line, bears N. 42° 30' E. and S. 42° 30' W.
4.029	Center line of Ajo Highway, bears N. 42° 33' E. and S. 42° 33' W., cor. of lots 10, 24, and 26, set nail.  from which  A wooden stake, 2 ft. long, 2 ins. sq., set 12 ins. in the ground for a reference; bears N. 89° 53' E., 100 lks. dist., mkd. WP.  A wooden stake, 2 ft. long, 2 ins. sq., set 12 ins. in the ground for a reference, bears S. 89° 53' W., 100 lks. dist., mkd. WP.
10.047	The NE-NW 1/64 sec. cor. of sec. 8.
19.40	Power line, bears NE. and SW.
20.094	The C-N-NW 1/64 sec. cor. of sec. 8.  Subdivision of the NW 1/4 NW 1/4.  From the C-W-NW 1/64 sec. cor. of sec. 8. N. 0° 02' W., on the N. and S. center line of the NW 1/4 NW 1/4 of sec. 8.
3.40	Wash, 18 lks. wide, 3 ft. deep, drains WNW.
9.60	Wash, 20 lks. wide, 3 ft. deep, drains WNW.
10.024	Point for the NW-NW 1/64 sec. cor. of sec. 8, at the intersection of the E. and W. center line of the NW 1/4 NW 1/4 of sec. 8. Set an iron post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, over a deposit of broken glass, with brass cap mkd.  S 8 NW 1/4 1/64 1953
11.35	Power line, bears NW. and SE.
16.85	Wash, 15 lks. wide, 5 ft. deep, drains WNW.
20.049	The W-W 1/64 sec. cor. of secs. 5 and 8.  From the C-N-NW 1/64 sec. cor. of sec. 8. S. 89° 53' W., on the E. and W. center line of the NW 1/4 NW 1/4 of sec. 8.
10.046	The NW-NW 1/64 sec. cor. of sec. 8.
11.60	Wash, 25 lks. wide, 3 ft. deep, drains NW.
17.80	Wash, 5 lks. wide, 1 ft. deep, drains NW.
20.092	The N-N 1/64 sec. cor. of secs. 7 and 8.

## Subdivision of Section 8, T. 15 S., R. 12 E.

Chains

Subdivision of the SW $\frac{1}{4}$ NW $\frac{1}{4}$ .

From the C-W-W 1/64 sec. cor. of sec. 8.

N. 0° 02' W., on the N. and S. center line of the SW $\frac{1}{4}$ NW $\frac{1}{4}$  of sec. 8.

2.40 Old road, bears E. and W.

6.40 Telephone line, bears N. 65° E. and S. 65° W.

7.17 Center line of Ajo Highway, bears N. 64° 05' E. and S. 68° 10' W.,  
cor. of lots 49, 52, 53, and 54, set nail.

from which

A wooden stake, 2 ft. long, 2 ins. sq., set 12 ins. in the ground  
for a reference, bears S. 0° 02' E., 100 lks. dist., mkd. WP.A wooden stake, 2 ft. long, 2 ins. sq., set 12 ins. in the ground  
for a reference, bears N. 0° 02' W., 100 lks. dist., mkd. WP.10.024 Point for the SW-NW 1/64 sec. cor. of sec. 8, at the intersection of  
the E. and W. center line of the SW $\frac{1}{4}$ NW $\frac{1}{4}$  of sec. 8.Set an iron post, 28 ins. long, 2 $\frac{1}{2}$  ins. diam., 24 ins. in the ground,  
over a deposit of broken glass, with brass cap mkd.

S 8

SWNW

1/64

1953

20.048 The C-W-NW 1/64 sec. cor. of sec. 8.

From the C-S-NW 1/64 sec. cor. of sec. 8.

S. 89° 53' W., on the E. and W. center line of the SW $\frac{1}{4}$ NW $\frac{1}{4}$  of sec. 8.

3.15 Telephone line, bears N. 56° 23' E. and S. 59° 40' W.

4.582 Center line of Ajo Highway, bears N. 56° 23' E. and S. 59° 40' W.,  
cor. of lots 48 and 55, set nail.

from which

A wooden stake, 2 ft. long, 2 ins. sq., set 12 ins. in the ground  
for a reference, bears N. 89° 53' E., 100 lks. dist., mkd. WP.A wooden stake, 2 ft. long, 2 ins. sq., set 12 ins. in the ground  
for a reference, bears S. 89° 53' W., 100 lks. dist., mkd. WP.

7.95 Wash, 8 lks. wide, 1 ft. deep, drains NW.

10.047 The SW-NW 1/64 sec. cor. of sec. 8.

20.095 The S-N 1/64 sec. cor. of secs. 7 and 8.

Subdivision of the SE $\frac{1}{4}$ NW $\frac{1}{4}$ .

From the C-E-W 1/64 sec. cor. of sec. 8.

N. 0° 01' W., on the N. and S. center line of the SE $\frac{1}{4}$ NW $\frac{1}{4}$  of sec. 8.

1.70 Old road, bears E. and W.

10.025 Point for the SE-NW 1/64 sec. cor. of sec. 8, at the intersection of  
the E. and W. center line of the SE $\frac{1}{4}$ NW $\frac{1}{4}$  of sec. 8.

## Subdivision of Section 8, T. 15 S., R. 12 E.

## Chains

Set an iron post, 28 ins. long,  $2\frac{1}{2}$  ins. diam.,  $2\frac{1}{4}$  ins. in the ground, over a deposit of broken glass, with brass cap mkd.

S 8  
SE $\frac{1}{4}$ NW $\frac{1}{4}$   
1/64  
1953

- 10.12 Power line, bears NE. and SW.  
13.83 Power line, bears NW. and SE.  
20.05 The C-E-NW 1/64 sec. cor. of sec. 8.

From the C-S-N 1/64 sec. cor. of sec. 8:

S.  $89^{\circ} 53'$  W., on the E. and W. center line of the SE $\frac{1}{4}$ NW $\frac{1}{4}$  of sec. 8.

- 1.85 Wash, 8 lks. wide, 3 ft. deep, drains NW.  
7.45 Wash, 8 lks. wide, 2 ft. deep, drains NW.  
10.047 The SE-NW 1/64 sec. cor. of sec. 8  
20.094 The C-S-NW 1/64 sec. cor. of sec. 8.

## General Description

The surface of sections 4, 5, 7, and 8 of T. 15 S., R. 12 E., is nearly level. The soil is a sandy loam. There is no timber, undergrowth consists of greasewood, mesquite and cacti. The general drainage is to the west and northwest through a number of shallow washes. The Ajo Highway enters section 4 on the east boundary of the NE $\frac{1}{4}$  and leaves on the west boundary of the SW $\frac{1}{4}$  of section 7. The El Paso Natural Gas line enters section 4 on the east boundary of the NE $\frac{1}{4}$  and leaves the section on the north boundary of the NW $\frac{1}{4}$ .

(From note on page 37):

From the S-S 1/64 sec. corner of secs. 7 and 8.  
S.  $89^{\circ} 51'$  W. on E. and W. center line of the SE $\frac{1}{4}$ SE $\frac{1}{4}$  of sec. 7

- 10.029 The SE-SE 1/64 sec. cor. of sec. 7  
20.058 The C-S-SE 1/64 sec. cor. of sec. 7



49

CERTIFICATE OF CADASTRAL ENGINEER

451

I, Clarence E. Bilbray, HEREBY CERTIFY upon honor that, in 29th. day of October and pursuance of special instructions bearing date of the 19th day of November, 1952,

I have surveyed dependently resurveyed a portion of the boundaries and portion of the subdivision, and surveyed the subdivisional lines of sections 4, 5, 7, and 8, T. 15 S., R. 12 E.

of the Gila & Salt River Meridian, in the State of Arizona, which are represented in the foregoing field notes as having been executed by me and under my direction; and that said survey has been made in strict conformity with said instructions, the Manual of Instructions for the Survey of the Public Lands of the United States, and in the specific manner described in the foregoing field notes.

Albuquerque, New Mexico
March 31, 1953

Signature of Clarence E. Bilbray
Clarence E. Bilbray
Cartographer (Cadastral)

CERTIFICATE OF APPROVAL

BUREAU OF LAND MANAGEMENT,
Washington, D. C., AUG 30 1955, 19

The foregoing field notes of the survey of dependent resurvey of a portion of the boundaries and portion of the subdivision, and survey of the subdivisional lines of sections 4, 5, 7, and 8, T. 15 S., R. 12 E., of the Gila and Salt River Meridian, Arizona.

executed by Clarence E. Bilbray
having been critically examined and found correct, are hereby approved.

Signature of Carl G. Harvinton
Chief, Division of Cadastral Engineering
Cadastral Engineering Staff Officer

CERTIFICATE OF TRANSCRIPT

I certify that the foregoing transcript of the field notes of the above-described surveys in is a true copy of the original field notes.

Chief, Division of Cadastral Engineering