

UNITED STATES
DEPARTMENT OF THE INTERIOR
BUREAU OF LAND MANAGEMENT

Original
FIELD NOTES

of the

Survey of the South Boundary

the North Boundary,

a Portion of the East Boundary,

and a

Portion of the Subdivision

of

Township 35 North, Range 4 West

Of the Gila and Salt River Meridian,

In the State of Arizona

EXECUTED BY

Horace G. Parker - Cartographer-Cadastral

Under special instructions dated August 16, 1954, which provided
for the surveys included under Group No. 294, approved August 20, 1954
and assignment instructions dated October 4, 1954.

Survey commenced November 9, 1954

Survey completed December 1, 1954

4456

4456

4456

(A) 74

BOOK 4456

INDEX DIAGRAM

Township 35 North, Range 4 West

19 6	18 5	17 4	16 3	15 20 2 21	14 13 1
7	8	9	10	11	13 12
18	17	16	15	14	12 13
19	20	21	22	23	11 24 8 11
30	29	28	27	26	10 25 7
31 1	32 2	33 3	34 4	35 5	9 36 7 6

Survey of the South and North Boundaries, a Portion of the East Boundary, and a Portion of the Subdivision of Township 35 North, Range 4 West.

Chains

The following field notes are those of the survey of the South and North Boundaries, a portion of the East Boundary, and a portion of the subdivision of Township 35 North, Range 4 West.

The survey was initiated on the official request by the Arizona State Land Department, Phoenix, Arizona, and the Division of Range Management, requesting the surveys of certain unsurveyed exterior boundaries as a means of assisting them in affixing the boundaries of allotments and the boundary of the Grand Canyon National Monument.

For the description of instruments and method of measurement used, refer to the field notes of the survey of the South, East and North Boundaries and a portion of the subdivisional lines of Township 35 North, Range 5 West, executed during the same period.

Azimuth determinations were made at frequent intervals during the survey. For detailed data pertaining to azimuth determination, refer to the field notes of the survey of the South, East and North Bdys. and a part of the subdivision of T. 35 N., R. 5 W., executed under this same group.

The computed geographic position of the SE. cor. of the Tp., is determined as latitude $36^{\circ} 22' 50''$ N., and longitude $112^{\circ} 40' 25.90''$ W.

The observed magnetic declination is $15^{\circ} 50' E.$

SOUTH BOUNDARY OF T. 35 N., R. 4 W.

From the true point for the corner of Ts. 34 and 35 N., Rs. 4 and 5 W. inaccessible, not monumented; continue by triangulation.


East, along the S. bdy. of sec. 31, T. 35 N., R. 4 W.

Over broken, mountainous land; asc. 500 ft. over SW. slope.

24.30 Top of sandstone rim, 300 ft. high, edge bears NNW. and SSE.

25.28 Point for E. end of triangulation.

Set an iron post, 30 ins. long, $2\frac{1}{2}$ ins. diam., 22 ins. in the ground, with brass cap mkd.



from which

A pinon, 10 ins. diam., bears N. $27^{\circ} 30' E.$, 147 lks. dist., mkd. T 35 N R4W S 31 WP BT.

A juniper, 20 ins. diam., bears S. $13^{\circ} 28' E.$, 140 lks. dist., mkd. T34N R4W S 6 WP BT.

A juniper, 12 ins. diam., bears S. $39^{\circ} 30' W.$, 95 lks. dist., mkd. T34N R4W S 6 WP BT.

A pinon, 16 ins. diam., bears N. $76^{\circ} 32' W.$, 114 lks. dist., mkd. T35N R4W S 31 WP BT.

Continue over mountainous land, through scattering timber.

29.32 Top of spur from ridge, slopes S.; desc. 127 ft. over E. slope.

38.94 Point for the $\frac{1}{4}$ sec. cor. of secs. 6 and 31.

Set an iron post, 30 ins. long, $2\frac{1}{2}$ ins. diam., 22 ins. in the ground, with brass cap mkd.

SOUTH BOUNDARY OF T. 35 N., R. 4 W.

Chains

$\frac{1}{4}$ S 31
S 6
1954

raise a mound of stone, 4 ft. base, $2\frac{1}{2}$ ft. high, N. of corner.

Asc. 40 ft. over steep W. slope.

46.40 Top of ascent; thence over nearly level land, through scattering timber.

55.50 Top of spur, slopes S.

57.72 Point selected for the W. end of triangulation.

Set an iron post, 30 ins. long, $2\frac{1}{2}$ ins. diam., 22 ins. in the ground, with brass cap mkd.

T 35 N R 4 W
S 31 WP
S 6
T 34 N
1954

raise a mound of stone, 4 ft. base, $2\frac{1}{2}$ ft. high, W. of corner.

Continue by triangulation across a series of deep rocky canyons which are inaccessible.

59.50 Top of sandstone rim, 300 ft. high, edge bears N. and S.; desc. 900 ft. over ESE. slope.

78.94 Point for the corner of secs. 5, 6, 31 and 32, inaccessible, not monumented.

Land, rolling and broken mountainous.
Soil, gravelly and rocky clay loam.
Timber, juniper and pinon.
Undergrowth, sagebrush.

East, bet. secs. 5 and 32.

Continue by triangulation over broken, mountainous land; desc. 120 ft. over E. slope.

13.80 Bottom of wash, 1 ch. wide, drains S. Asc. 150 ft. over W. slope.

30.30 Top of ascent, slopes S. Thence over broken land to corner.

40.00 Point for the $\frac{1}{4}$ sec. cor. of secs. 5 and 32, inaccessible, not monumented.

Continue over broken mountainous land.

55.30 Bottom of wash, 2 chs. wide, drains SW.; asc. 500 ft. over W. slope to corner.

80.00 Point for the corner of secs. 4, 5, 32 and 33, inaccessible, not monumented.

Land, broken mountainous.
Soil, gravelly and rocky clay.
Timber, none.
Undergrowth, sagebrush.

BOOK 4486

SOUTH BOUNDARY OF T. 35 N., R. 4 W.

Chains

East, between secs. 4 and 33.

Continue by triangulation over broken mountainous land; asc. 400 ft. over W. slope.

12.50 Top of sandstone rim, 200 ft. high, edge bears NW. and SE.

14.38 Point selected for the triangulation station and witness point on E. end of triangulation. This point is located approximately 2 chs. E. of the top of a sandstone rim on E. edge of canyon; edge bears NW. and SE., near the top of a small spur, sloping S.

Set an iron post, 30 ins. long, $2\frac{1}{2}$ ins. diam., 22 ins. in the ground, with brass cap mkd.

T 35 N R 4 W
S 33
WP —————
S 4
T 34 N
1954

raise a mound of stone, 4 ft. base, $2\frac{1}{2}$ ft. high, W. of corner.

Continue over rolling land, through scattering timber; desc. 29 ft. over SE. slope.

21.63 Wash, 21 lks. wide, $1\frac{1}{2}$ ft. deep, drains SE., asc. 45 ft. over W. slope.

32.55 Wash, 15 lks. wide, 2 ft. deep, drains S.

40.00 Point for the $\frac{1}{4}$ sec. cor. of secs. 4 and 33.

Set an iron post, 30 ins. long, $2\frac{1}{2}$ ins. diam., 10 ins. in the ground to solid rock, and in a mound of stone to top, with brass cap mkd.

$\frac{1}{4}$ S 33
—————
S 4
1954

from which

A juniper, 14 ins. diam., bears N. $65^{\circ} 42'$ E., 195 lks. dist., mkd. $\frac{1}{4}$ S 33 BT.

A pinon, 12 ins. diam., bears S. $9^{\circ} 30'$ E., 237 lks. dist., mkd. $\frac{1}{4}$ S 4 BT.

Continue over gently rolling land, through heavy timber.

42.10 Wash, 20 lks. wide, 3 ft. deep, drains SW.; asc. 17 ft. over W. slope.

50.00 Top of ascent, slopes S.; desc. 12 ft. to corner.

80.00 Point for the cor. of secs. 3, 4, 33 and 34.

Set an iron post, 30 ins. long, $2\frac{1}{2}$ ins. diam., 10 ins. in the ground to solid rock, and in a mound of stone to top, with brass cap mkd.

T 35 N R 4 W
S 33 | S 34
—————
S 4 | S 3
T 34 N
1954

SOUTH BOUNDARY OF T. 35 N., R. 4 W.

Chains

from which

A juniper, 6 ins. diam., bears N. 24° 43' E., 81 lks. dist., mkd.
T35N R4W S 34 BT.

A pinon, 12 ins. diam., bears S. 21° 20' E., 17 lks. dist., mkd.
T34N R4W S 3 BT.

A pinon, 12 ins. diam., bears S. 38° 25' W., 53 lks. dist., mkd.
T34N R4W S 4 BT.

A juniper, 10 ins. diam., bears N. 49° 57' W., 73 lks. dist., mkd.
T35N R4W S 33 BT.

Land, gently rolling.
Soil, sandy and gravelly clay loam.
Timber, juniper and pinon.
Undergrowth, sagebrush and mountain holly.

East, between secs. 3 and 34.

Over gently rolling land, through scattering timber.

13.00 Begin descent; desc. 22 ft. over SE. slope.

20.20 Wash, 15 lks. wide, 3 ft. deep, drains S.

28.30 Wash, 20 lks. wide, 1½ ft. deep, drains SW.; enter heavy timber,
edge bears NE. and SW.; asc. 15 ft. over W. slope.

40.00 Point for the ¼ sec. cor. of secs. 3 and 34:

Set an iron post, 30 ins. long, 2½ ins. diam., 18 ins. in the ground
to solid rock, and in a mound of stone to top, with brass cap mkd.

S 34
—
¼
S 3
1954

from which

A pinon, 24 ins. diam., bears N. 34° 30' E., 49 lks. dist., mkd.
¼ S 34 BT.

A juniper, 12 ins. diam., bears S. 60° 30' E.; 42 lks. dist., mkd.
¼ S 3 BT.

Continue over gently rolling land, through heavy timber.

45.08 Point selected for the triangulation station and witness point on the
W. end of the triangulation. This point is approximately 40 lks. W.
of the top of a sandstone rim approximately 350 feet high, edge bears
NE. and SW.; continue by triangulation across an inaccessible canyon.

Set an iron post, 30 ins. long, 2½ ins. diam., 24 ins. in the ground,
with brass cap mkd.

T. 35 N. R. 4 W
S 34 WP
—
S 3
T 34 N
1954

from which

A juniper, 8 ins. diam., bears N. 32° 00' E., 71 lks. dist., mkd.
T35N R4W S 34 WP BT.

BOOK 4455

SOUTH BOUNDARY OF T. 35 N., R. 4 W.

Chains																			
	A juniper, 12 ins. diam., bears S. 8° 00' E., 50 lks. dist., mkd. T34N R4W S 3 WP BT.																		
	A juniper, 14 ins. diam., bears S. 57° 00' W., 80 lks. dist., mkd. T34N R4W S 3 WP BT.																		
	A juniper, 12 ins. diam., bears N. 23° 00' W., 145 lks. dist., mkd. T35N R4W S 34 WP BT.																		
45.45	Top of sandstone rim, approximately 350 ft. high, edge bears NE. and SW.; desc. 1450 ft. over broken E. slope to corner.																		
80.00	Point for the cor. of secs. 2, 3, 34 and 35, inaccessible, not monumented.																		
	Land, west-half, gently rolling; east-half, broken mountainous. Soil, gravelly and rocky clay loam. Timber, juniper and pinon. Undergrowth, sagebrush.																		
	East, between secs. 2 and 35.																		
	Continue by triangulation, over broken mountainous land; desc. 10 ft. over E. slope.																		
5.50	Bottom of canyon, 2 chs. wide, drains S.; asc. 950 ft. over steep W. slope to corner.																		
40.00	Point for the $\frac{1}{4}$ sec. cor. of secs. 2 and 35, inaccessible, not monumented.																		
	Continue ascent; asc. 500 ft. over steep W. slope and perpendicular sandstone cliff.																		
52.90	Top of sandstone rim, approximately 300 ft. high, edge bears NE. and SW.; continue over rolling land; asc. 54 ft. over W. slope.																		
54.10	Point selected for the witness point on the E. side of canyon. This point is approximately 1 ch. E. of the top of the canyon rim.																		
	Set an iron post, 30 ins. long, $2\frac{1}{2}$ ins. diam., 10 ins. in the ground to solid rock, and in a mound of stone to top, with brass cap mkd.																		
	<table border="0"> <tr><td></td><td>T 35 N</td><td>R 4 W</td></tr> <tr><td></td><td>S 35</td><td></td></tr> <tr><td>WP</td><td>—</td><td></td></tr> <tr><td></td><td>S 2</td><td></td></tr> <tr><td></td><td>T 34 N</td><td></td></tr> <tr><td></td><td>1954</td><td></td></tr> </table>		T 35 N	R 4 W		S 35		WP	—			S 2			T 34 N			1954	
	T 35 N	R 4 W																	
	S 35																		
WP	—																		
	S 2																		
	T 34 N																		
	1954																		
	raise a mound of stone, 4 ft. base, $2\frac{1}{2}$ ft. high, N. of corner.																		
60.00	Top of ascent, slopes S.; desc. 54 ft. over E. slope.																		
67.80	Wash, 13 lks. wide, $1\frac{1}{2}$ ft. deep, drains SW.; asc. 64 ft. over W. slope.																		
80.00	Point for the cor. of secs. 1, 2, 35 and 36.																		
	Set an iron post, 30 ins. long, $2\frac{1}{2}$ ins. diam., 8 ins. in the ground to solid rock, and in a mound of stone to top, with brass cap mkd.																		
	<table border="0"> <tr><td></td><td>T 35 N</td><td>R 4 W</td></tr> <tr><td></td><td>S 35</td><td>S 36</td></tr> <tr><td></td><td>—</td><td>—</td></tr> <tr><td></td><td>S 2</td><td>S 1</td></tr> <tr><td></td><td>T 34 N</td><td></td></tr> <tr><td></td><td>1954</td><td></td></tr> </table>		T 35 N	R 4 W		S 35	S 36		—	—		S 2	S 1		T 34 N			1954	
	T 35 N	R 4 W																	
	S 35	S 36																	
	—	—																	
	S 2	S 1																	
	T 34 N																		
	1954																		

SOUTH BOUNDARY OF T. 35 N., R. 4 W.

Chains

from which

A pinon, 10 ins. diam., bears N. 33° 08' E., 69 lks. dist., mkd. T35N R4W S 36 BT.

A juniper, 14 ins. diam., bears S. 19° 30' E., 270 lks. dist., mkd. T34N R4W S 1 BT.

A juniper, 12 ins. diam., bears S. 50° 48' W., 74 lks. dist., mkd. T34N R4W S 2 BT.

A juniper, 12 ins. diam., bears N. 17° 15' W., 123 lks. dist., mkd. T35N R4W S 35 BT.

Land, western $\frac{1}{2}$, broken mountainous; eastern $\frac{1}{2}$, gently rolling.
Soil, sandy and gravelly clay loam.
Timber, juniper and pinon.
Undergrowth, sagebrush.

East, between secs. 1 and 36.

Over rolling land, through scattering timber; asc. 20 ft. over WSW. slope. Continue by triangulation.

2.83

Point selected for the triangulation station at the E. end of the triangulation. This point is located on nearly level land near the top of a low spur from ridge, sloping SE. Thence by chaining.

10.51

Point selected for the W. end of triangulation and witness point, approximately 60 lks. W. of the top of a sandstone rim approximately 350 ft. high.

Set an iron post, 30 ins. long, 2 $\frac{1}{2}$ ins. diam., 16 ins. in the ground to solid rock, and in a mound of stone to top, with brass cap mkd.

T 35 N R 4 W
S 36
----- WP
S 1
T 34 N
1954

from which

A pinon, 40 ins. diam., bears S. 35° 39' E., 122 lks. dist., mkd. T34N R4W S 1 WP BT.

A pinon, 30 ins. diam., bears N. 74° 00' W., 120 lks. dist., mkd. T35N R4W S 36 WP BT.

No other suitable bearing trees available.

Continue by triangulation over broken mountainous land.

11.11

Top of sandstone rim, approximately 350 ft. high, edge bears ^{NW} and ^{SE} SE.; leave scattering timber, desc. 1450 ft. over broken E. and NE. slope.

40.00

Point for the $\frac{1}{4}$ sec. cor. of secs. 1 and 36, inaccessible, not monumented.

Continue over broken mountainous land; desc. 1050 ft. over broken E. and NE. slope.

80.00

Point for the cor. of Ts. 34 and 35 N., Rs. 3 and 4 W., inaccessible, not monumented.

Land, broken mountainous.
Soil, gravelly and rocky clay.
Timber, juniper and pinon.
Undergrowth, sagebrush.

BOOK 4456

EAST BOUNDARY OF T. 35 N., R. 4 W.

Chains

From the true point for the cor. of Ts. 34 and 35 N., Rs. 3 and 4 W., inaccessible, not monumented.

North, bet. secs. 31 and 36.

Continue by triangulation over broken mountainous land; desc. 200 ft. over N. slope.

13.00 Wash, 1 ch. wide, 5 ft. deep, drains SE.; asc. 750 ft. over sandstone cliffs 50 to 100 ft. high, and over steep S. slope to corner.

40.00 Point for the $\frac{1}{4}$ sec. cor. of secs. 31 and 36, inaccessible, not monumented.

Continue ascent; asc. 875 ft. over steep S. slope.

80.00 Point for the cor. of secs. 25, 30, 31 and 36, inaccessible, not monumented.

Land, broken mountainous.
Soil, gravelly and rocky clay loam.
Timber, none.
Undergrowth, sagebrush.


North, bet. secs. 25 and 30.

Continue by triangulation over broken mountainous land; asc. 200 ft. over perpendicular sandstone cliffs.

2.80 Top of sandstone rim, N. rim of Colorado River canyon, approximately 200 ft. high, edge bears E. and W.

3.43 E. end of triangulation and point selected for the witness corner of secs. 25, 30, 31 and 36 on the true line bet. secs. 25 and 30, on the E. bdy. of the Tp.

Set an iron post, 30 ins. long, $2\frac{1}{2}$ ins. diam., 3 ins. in the ground to solid rock, and in a mound of stone to top, with brass cap mkd.



from which

A juniper, 10 ins. diam., bears N. $49^{\circ} 20'$ E., 41 lks. dist., mkd. T35N R3W S 30 WC BT.

A pinon, 8 ins. diam., bears N. $24^{\circ} 30'$ W., 92 lks. dist., mkd. T35N R4W S 25 WC BT.

No other suitable bearing trees available.

From this cor. the witness point on the W. end of the triangulation which is located on the S. bdy. of sec. 36, T. 35 N., R. 4 W., 10.51 chs. dist. from the cor. of secs. 1, 2, 35 and 36, bears S. $39^{\circ} 47' 30''$ W., 108.584 chs. dist.

Continue over gently rolling land, through scattering timber; asc. 56 ft. over gradual S. slope.

39.00 Road, bears E. and W.

40.00 Point for the $\frac{1}{4}$ sec. cor. of secs. 25 and 30.

EAST BOUNDARY OF T. 35 N., R. 4 W.

Chains

Set an iron post, 30 ins. long, $2\frac{1}{2}$ ins. diam., 24 ins. in the ground, with brass cap mkd.

$\frac{1}{4}$
 S 25 | S 30
 1954

from which

A juniper, 10 ins. diam., bears S. $67^{\circ} 25'$ E., 113 lks. dist., mkd. $\frac{1}{4}$ S 30 BT.

A pinon, 16 ins. diam., bears N. $13^{\circ} 10'$ W., 136 lks. dist., mkd. $\frac{1}{4}$ S 25 BT.

- 44.00 Top of ridge, bears E. and W.; desc. 52 ft. over gradual N. slope.
- 50.00 Leave scattering timber, edge bears E. and W.
- 71.12 Wash, 25 lks. wide, 6 ft. deep, drains NE.; asc. 18 ft. over S. slope.
- 76.10 Top of ascent, slopes E.; desc. 18 ft. to corner.
- 80.00 Point for the corner of secs. 19, 24, 25 and 30.

Set an iron post, 30 ins. long, $2\frac{1}{2}$ ins. diam., 22 ins. in the ground, with brass cap mkd.

T 35 N
 R 4 W | R 3 W
 S 24 | S 19
 S 25 | S 30
 1954

raise a mound of stone, 3 ft. base, $2\frac{1}{2}$ ft. high, W. of cor.

Land, gently rolling.
 Soil, gravelly clay loam.
 Timber, juniper and pinon.
 Undergrowth, sagebrush, buckbrush, and mountain holly.

North, bet. secs. 19 and 24.

Over gently rolling land, through heavy undergrowth.

- 6.23 Point selected for the witness point bet. secs. 19 and 24, on the E. bdy. of the Tp. This point is located on the top of a small low spur sloping ESE., approximately 1 ch. S. of the top of a sandstone rim approximately 300 ft. high. This rim is the W. rim of the Kanab Creek canyon, edge bears WNW and ESE.

Set an iron post, 30 ins. long, $2\frac{1}{2}$ ins. diam., 2 ins. in the ground to solid rock, and in a mound of stone to top, with brass cap mkd.

W P
 S 24 | S 19
 1954

- 7.10 Top of sandstone rim approximately 300 ft. high, edge bears WNW. and ESE. At this point, I discontinue the survey of the E. bdy. of T. 35 N., R. 4 W., as the land lying N. of this point is broken mountainous land with many small canyons having perpendicular cliffs varying from 50 to 200 ft. high, and this area is inaccessible.

BOOK 4456

PORTION OF THE SUBDIVISION OF T. 35 N., R. 4 W.

Chains

Survey of a Portion of the Subdivision of T. 35 N., R. 4 W.

Beginning a portion of the subdivisional survey at the cor. of secs. 1, 2, 35 and 36, on the S. bdy. of the Tp., which is monumented with an iron post, $2\frac{1}{2}$ ins. diam., firmly set, and heretofore described.

N. 0° 01' W., bet. secs. 35 and 36.

Over rolling land, through scattering timber; asc. 48 ft. over S. slope.

11.00 Top of spur from ridge, slopes WNW.; desc. 82 ft. over N. slope.

26.00 Enter heavy timber, edge bears SE. and NW.

40.00 Point for the $\frac{1}{4}$ sec. cor. of secs. 35 and 36.

Set an iron post, 30 ins. long, $2\frac{1}{2}$ ins. diam., 24 ins. in the ground, with brass cap mkd.

$$\begin{array}{c} \frac{1}{4} \\ \text{S } 35 \quad | \quad \text{S } 36 \\ 1954 \end{array}$$

from which

A pinon, 12 ins. diam., bears S. 67° 02' E., 37 lks. dist., mkd. $\frac{1}{4}$ S 36 BT.

A juniper, 10 ins. diam., bears N. 54° 55' W., 34 lks. dist., mkd. $\frac{1}{4}$ S 35 BT.

Continue descent over rolling land, through heavy timber; desc. 81 ft. over N. slope.

45.74 Wash, 15 lks. wide, 2 ft. deep, drains WSW.; asc. 79 ft. over SE. slope.

55.35 Leave heavy timber, edge bears E. and W.; continue through scattering timber.

76.45 Road, bears NE. and SW.

80.00 Point for the cor. of secs. 25, 26, 35 and 36.

Set an iron post, 30 ins. long, $2\frac{1}{2}$ ins. diam., 24 ins. in the ground, with brass cap mkd.

$$\begin{array}{c} \text{T } 35 \text{ N } \quad \text{R } 4 \text{ W} \\ \text{S } 26 \quad | \quad \text{S } 25 \\ \hline \text{S } 35 \quad | \quad \text{S } 36 \\ 1954 \end{array}$$

from which

A pinon, 24 ins. diam., bears N. 13° 08' E., 157 lks. dist., mkd. T35N R4W S 25 BT.

A juniper, 16 ins. diam., bears S. 65° 40' E., 177 lks. dist., mkd. T35N R4W S 36 BT.

A juniper, 24 ins. diam., bears S. 2° 03' W., 346 lks. dist., mkd. T35N R4W S 35 BT.

A juniper, 10 ins. diam., bears N. 61° 50' W., 193 lks. dist., mkd. T35N R4W S 26 BT.

PORTION OF THE SUBDIVISION OF T. 35 N., R. 4 W.

Chains

Land, gently rolling.
Soil, sandy and gravelly clay loam.
Timber, juniper and pinon.
Undergrowth, sagebrush and mountain holly.

N. 0° 01' W., bet. secs. 25 and 26.

Over rolling land through scattering timber; desc. 17 ft. over N. slope.

9.30 Bottom of descent; begin ascent, asc. 16 ft. over gradual SW. slope.


23.60 Top of low spur from ridge, slopes NW., continue over nearly level land.

24.07 Road, bears NW. and SE.

36.30 Wash, 5 lks. wide, 8 ins. deep, drains W.

40.00 Point for the $\frac{1}{4}$ sec. cor. of secs. 25 and 26.

Set an iron post, 30 ins. long, $2\frac{1}{2}$ ins. diam., 22 ins. in the ground, with brass cap mkd.



from which

A juniper, 8 ins. diam., bears N. 41° 45' E., 13 lks. dist., mkd. $\frac{1}{4}$ S 25 BT.

A juniper, 16 ins. diam., bears N. 84° 10' W., 155 lks. dist., mkd. $\frac{1}{4}$ S 26 BT.

Continue over gently rolling land.

50.00 Enter scattering timber.


53.40 Wash, 8 lks. wide, 10 ins. deep, drains W. Enter heavy timber, edge bears E. and W.

59.10 Leave heavy timber, edge bears NE. and SW. Continue through scattering timber.

64.70 Wash, 6 lks. wide, 1 ft. deep, drains SW.

80.00 Point for the cor. of secs. 23, 24, 25 and 26.

Set an iron post, 30 ins. long, $2\frac{1}{2}$ ins. diam., 20 ins. in the ground, with brass cap mkd.



from which

A juniper, 10 ins. diam., bears N. 89° 02' E., 216 lks. dist., mkd. T35N R4W S 24 BT.

A pinon, 10 ins. diam., bears S. 19° 06' E., 127 lks. dist., mkd. T35N R4W S 25 BT.

BOOK 4456

PORTION OF THE SUBDIVISION OF T. 35 N., R. 4 W.

Chains

A juniper, 12 ins. diam., bears S. 22° 45' W., 44 lks. dist., mkd. T35N R4W S 26 BT.

A juniper, 8 ins. diam., bears N. 44° 38' W., 73 lks. dist., mkd. T35N R4W S 23 BT.

Land, gently rolling.
Soil, sandy and gravelly clay loam.
Timber, juniper and pinon.
Undergrowth, sagebrush.

From the cor. of secs. 19, 24, 25 and 30, on the E. bdy. of the Tp., which is monumented with an iron post, 2½ ins. diam., firmly set and heretofore described.

West, bet. secs. 24 and 25.

Over gently rolling land; asc. 97 ft. over E. slope.

18.90 Enter timber, edge bears NW. and SE.

26.60 Top of ascent, slopes SW., continue over nearly level land.

40.00 Point for the ¼ sec. cor. of secs. 24 and 25.

Set an iron post, 30 ins. long, 2½ ins. diam., 22 ins. in the ground, with brass cap mkd.

$$\frac{1}{4} \begin{array}{l} \text{S } 24 \\ \hline \text{S } 25 \\ 1954 \end{array}$$

from which

A juniper, 8 ins. diam., bears N. 74° 25' E., 49 lks. dist., mkd. ¼ S 24 BT.

A juniper, 5 ins. diam.; bears S. 69° 55' W., 53 lks. dist., mkd. ¼ S 25 BT.

42.00 Wash, 10 lks. wide, 1½ ft. deep, drains SW.

71.10 Road, bears NW. and SE.; leave heavy timber, edge bears NW. and SE., continue through scattering timber.

80.00 The cor. of secs. 23, 24, 25 and 26.

Land, east-half, gently rolling; west-half, nearly level.
Soil, sandy and gravelly clay loam.
Timber, juniper and pinon.
Undergrowth, sagebrush.

N. 0° 01' W., bet. secs. 23 and 24.

Over low, rolling land, through scattering timber.

4.40 Road, bears WNW. and ESE.

40.00 Point for the ¼ sec. cor. of secs. 23 and 24.

Set an iron post, 30 ins. long, 2½ ins. diam., 22 ins. in the ground, with brass cap mkd.

$$\frac{1}{4} \begin{array}{l} \text{S } 23 \quad | \quad \text{S } 24 \\ \hline 1954 \end{array}$$

PORTION OF THE SUBDIVISION OF T. 35 N., R. 4 W.

Chains	<p>from which</p> <p>A juniper, 16 ins. diam., bears S. 87° 32' E., 111 lks. dist., mkd. $\frac{1}{4}$ S 24 BT.</p> <p>A juniper, 16 ins. diam., bears S. 83° 45' W., 132 lks. dist., mkd. $\frac{1}{4}$ S 23 BT.</p> <p>Continue over gently rolling land, through scattering timber; desc. 63 ft. over N. slope.</p> <p>42.30 Wash, 20 lks. wide, 4 ft. deep, drains E.</p> <p>55.60 Same wash, 22 lks. wide, 8 ft. deep, drains NW.</p> <p>56.90 Same wash, 22 lks. wide, 8 ft. deep, drains NE.; asc. 28 ft. over E. slope.</p> <p>67.20 Top of ascent, slopes E.; desc. 18 ft. over gradual N. slope.</p> <p>70.94 Wash, 20 lks. wide, 5 ft. deep, drains NE.; asc. 17 ft. over S. slope to corner.</p> <p>75.64 Point selected for the witness corner of secs. 13, 14, 23 and 24, and the S. end of triangulation. This point is located approximately 60 lks. S. of the top of a sandstone rim approximately 300 ft. high, edge bears NW. and SE.</p> <p>Set an iron post, 30 ins. long, 2$\frac{1}{2}$ ins. diam., 12 ins. in the ground to solid rock, and in a mound of stone to top, with brass cap mkd.</p> <div style="text-align: center;"> <p>T 35 N R 4 W</p> <table style="margin: auto;"> <tr> <td></td> <td>WC</td> <td></td> </tr> <tr> <td>S 14</td> <td> </td> <td>S 13</td> </tr> <tr> <td>S 23</td> <td> </td> <td>S 24</td> </tr> </table> <p>1954</p> </div> <p>raise a mound of stone, 4 ft. base, 2$\frac{1}{2}$ ft. high, W. of corner.</p> <p>Continue by triangulation.</p> <p>76.10 Top of sandstone rim approximately 300 ft. high, edge bears NW. and SE.</p> <p>80.00 Point for the cor. of secs. 13, 14, 23 and 24, inaccessible, not monumented.</p> <p>Land, gently rolling. Soil, sandy and gravelly clay loam. Timber, juniper and pinon. Undergrowth, sagebrush.</p>		WC		S 14		S 13	S 23		S 24
	WC									
S 14		S 13								
S 23		S 24								
	<p>N. 0° 01' W., bet. secs. 13 and 14.</p> <p>Over broken mountainous land, continue by triangulation.</p> <p>40.00 Point for the $\frac{1}{4}$ sec. cor. of secs. 13 and 14, inaccessible, not monumented.</p> <p>80.00 Point for the cor. of secs. 11, 12, 13 and 14, inaccessible, not monumented.</p> <p>Land, broken mountainous. Soil, gravelly and rocky clay loam. Timber, none. Undergrowth, sagebrush.</p>									

BOOK 4456

PORTION OF THE SUBDIVISION OF T. 35 N., R. 4 W.

Chains							
	N. 0° 01' W., bet. secs. 11 and 12.						
	Continue by triangulation over broken mountainous land.						
40.00	Point for the $\frac{1}{4}$ sec. cor. of secs. 11 and 12, inaccessible, not monumented.						
80.00	Point for the cor. of secs. 1, 2, 11 and 12, inaccessible, not monumented.						
	Land, broken mountainous. Soil, gravelly and rocky clay loam. Timber, juniper and pinon. Undergrowth, sagebrush.						
	N. 0° 01' W., bet. secs. 1 and 2.						
	Continue by triangulation over broken mountainous land.						
35.40	Top of sandstone rim approximately 300 ft. high, edge bears NE. and SW.						
37.56	Point selected for the triangulation station on the N. end of triangulation.						
	Continue over rolling land through scattering timber.						
40.00	Point for the $\frac{1}{4}$ sec. cor. of secs. 1 and 2.						
	Set an iron post, 30 ins. long, $2\frac{1}{2}$ ins. diam., 22 ins. in the ground, with brass cap mkd.						
	$\frac{1}{4}$ <table style="margin: auto; border-collapse: collapse;"> <tr> <td style="padding: 0 10px;">S 2</td> <td style="border-left: 1px solid black; border-right: 1px solid black; padding: 0 5px;"> </td> <td style="padding: 0 10px;">S 1</td> </tr> <tr> <td colspan="3" style="text-align: center;">1954</td> </tr> </table>	S 2		S 1	1954		
S 2		S 1					
1954							
	from which						
	A juniper, 8 ins. diam., bears N. 70° 50' E., 50 lks. dist., mkd. $\frac{1}{4}$ S 1 BT.						
	A pinon, 12 ins. diam., bears S. 87° 36' W., 78 lks. dist., mkd. $\frac{1}{4}$ S 2 BT.						
	From this corner, the United States Geological Survey triangulation station "Phillips", bears S. 28° 16' W.						
	Continue over rolling land, through scattering timber.						
45.66	Road, bears NE. and SW.; enter heavy timber, edge bears NE. and SW.						
53.10	Wash, 12 lks. wide, 2 ft. deep, drains E.						
64.00	Same wash, 15 lks. wide, $1\frac{1}{2}$ ft. deep, drains NW.						
66.70	Leave heavy timber, edge bears NE. and SW.						
68.80	Wash, 15 lks. wide, 2 ft. deep, drains WNW.; asc. 20 ft. over S. slope.						
79.95	Intersect the N. bdy. of the Tp. at the cor. of secs. 1, 2, 35, and 36.						
	Land, south-half, broken mountainous; north-half, gently rolling. Soil, sandy and gravelly clay loam. Timber, juniper and pinon. Undergrowth, sagebrush.						

NORTH BOUNDARY OF T. 35 N., R. 4 W.

Chains

Beginning the survey of the N. bdy. of T. 35 N., R. 4 W., at the true point for the cor. of Ts. 35 and 36 N., Rs. 3 and 4 W.

At the cor. point.

Set an iron post, 30 ins. long, $2\frac{1}{2}$ ins. diam., 24 ins. in the ground, with brass cap mkd.

T 36 N	
R 4 W	R 3 W
S 36	S 31
S 1	S 6
T 35 N	
1954	

raise a mound of stone, 4 ft. base, $2\frac{1}{2}$ ft. high, S. of corner.

S. $89^{\circ} 58'$ W., bet. secs. 1 and 36, marking and blazing the true line.

Over rolling land; asc. 96 ft. over E. slope.

21.50 Top of ascent, slopes N.; desc. 39 ft. over W. slope.

23.50 Bottom of descent; asc. 29 ft. over E. slope.

28.50 Top of ascent, slopes N.; desc. 23 ft. over W. slope.

32.93 Wash, 20 lks. wide, 5 ft. deep, drains N.; enter scattering timber.

40.00 Point for the $\frac{1}{4}$ sec. cor. of secs. 1 and 36.

Set an iron post, 30 ins. long, $2\frac{1}{2}$ ins. diam., 2 ins. in the ground to solid rock, and in a mound of stone to top, with brass cap mkd.

$\frac{1}{4}$	S 36
	S 1
	1954

from which

A pinon, 12 ins. diam., bears N. $43^{\circ} 08'$ W., 308 lks. dist., mkd. $\frac{1}{4}$ S, 36 BT.

There is no other suitable bearing tree within limits.

raise a mound of stone, 4 ft. base, $2\frac{1}{2}$ ft. high, N. of corner.

Continue over rolling land, through scattering timber; desc. 105 ft. over W. slope.

50.18 Wash, 8 lks. wide, 3 ft. deep, drains NW.

52.27 Wash, 15 lks. wide, 3 ft. deep, drains NE.; asc. 100 ft. over gradual E. slope.

75.00 Top of ascent, slopes N.; desc. 34 ft. over W. slope.

80.00 Point for the cor. of secs. 1, 2, 35 and 36.

Set an iron post, 30 ins. long, $2\frac{1}{2}$ ins. diam., 20 ins. in the ground to solid rock, and in a mound of stone to top, with brass cap mkd.

T 36 N	R 4 W
S 35	S 36
S 2	S 1
T 35 N	
1954	

BOOK 4456

NORTH BOUNDARY OF T. 35 N., R. 4 W.

Chains	<p>from which</p> <p>A juniper, 12 ins. diam., bears N. 40° 12' E., 57 lks. dist., mkd. T36N R4W S 36 BT.</p> <p>A juniper, 8 ins. diam., bears S. 82° 45' E., 215 lks. dist., mkd. T35N R4W S 1 BT.</p> <p>A pinon, 8 ins. diam., bears S. 7° 20' W., 39 lks. dist., mkd. T35N R4W S 2 BT.</p> <p>A juniper, 10 ins. diam., bears N. 42° 26' W., 38 lks. dist., mkd. T36N R4W S 35 BT.</p> <p>Land, gently rolling. Soil, sandy and gravelly clay loam. Timber, juniper and pinon. Undergrowth, sagebrush, buckbrush and mountain holly.</p> <hr/> <p>S. 89° 58' W., bet. secs. 2 and 35.</p> <p>Over rolling land, through scattering timber and heavy undergrowth; desc. 74 ft. over WNW. slope.</p> <p>6.68 Wash, 12 lks. wide, 3 ft. deep, drains NNE.; asc. 85 ft. over SE. slope.</p> <p>18.40 Top of ascent, slopes NE.; desc. 23 ft. over SW. slope.</p> <p>25.80 Wash, 10 lks. wide, 1½ ft. deep, drains NE.; asc. 78 ft. over E. slope.</p> <p>35.00 Top of spur from ridge, slopes NNW.; desc. 34 ft. over gradual W. slope.</p> <p>40.00 Point for the ¼ sec. cor. of secs. 2 and 35.</p> <p>Set an iron post, 30 ins. long, 2½ ins. diam., 8 ins. in the ground to solid rock, and in a mound of stone to top, with brass cap mkd.</p> <div style="text-align: center;"> <table style="margin-left: auto; margin-right: auto;"> <tr><td style="padding: 0 10px;">¼</td><td style="border-bottom: 1px solid black; padding: 0 10px;">S 35</td></tr> <tr><td style="padding: 0 10px;"></td><td style="padding: 0 10px;">S 2</td></tr> <tr><td style="padding: 0 10px;"></td><td style="padding: 0 10px;">1954</td></tr> </table> </div> <p>from which</p> <p>A pinon, 20 ins. diam., bears N. 39° 20' E., 41 lks. dist., mkd. ¼ S 35 BT.</p> <p>A pinon, 10 ins. diam., bears S. 58° 41' E., 63 lks. dist., mkd. ¼ S 2 BT.</p> <p>Continue over low rolling land, through scattering timber and heavy undergrowth.</p> <p>52.60 Road, bears NE. and SW.</p> <p>80.00 Point for the cor. of secs. 2, 3, 34 and 35.</p> <p>Set an iron post, 30 ins. long, 2½ ins. diam., 12 ins. in the ground to solid rock, and in a mound of stone to top, with brass cap mkd.</p> <div style="text-align: center;"> <table style="margin-left: auto; margin-right: auto;"> <tr><td style="padding: 0 10px;">T 36 N</td><td style="padding: 0 10px;">R 4 W</td></tr> <tr><td style="border-right: 1px solid black; padding: 0 5px;">S 34</td><td style="padding: 0 5px;">S 35</td></tr> <tr><td style="border-right: 1px solid black; padding: 0 5px;">S 3</td><td style="padding: 0 5px;">S 2</td></tr> <tr><td colspan="2" style="padding: 0 10px;">T 35 N</td></tr> <tr><td colspan="2" style="padding: 0 10px;">1954</td></tr> </table> </div>	¼	S 35		S 2		1954	T 36 N	R 4 W	S 34	S 35	S 3	S 2	T 35 N		1954	
¼	S 35																
	S 2																
	1954																
T 36 N	R 4 W																
S 34	S 35																
S 3	S 2																
T 35 N																	
1954																	

NORTH BOUNDARY OF T. 35 N., R. 4 W.

Chains

from which

A juniper, 8 ins. diam., bears N. 6° 18' E., 44 lks. dist., mkd. T36N R4W S 35 BT.

A juniper, 12 ins. diam., bears S. 35° 55' E., 25 lks. dist., mkd. T35N R4W S 2 BT.

A juniper, 18 ins. diam., bears S. 51° 08' W., 185 lks. dist., mkd. T35N R4W S 3 BT.

A juniper, 16 ins. diam., bears N. 66° 35' W., 160 lks. dist., mkd. T36N R4W S 34 BT.

Land, low rolling.
Soil, gravelly clay loam.
Timber, juniper and pinon.
Undergrowth, sagebrush, buckbrush and mountain holly.

S. 89° 58' W., bet. secs. 3 and 34.

Over low rolling land, through scattering timber and heavy undergrowth.

7.50 Begin ascent; asc. 16 ft. over E. slope.

12.00 Top of ascent, slopes N.; continue over nearly level land.

30.70 Begin ascent; asc. 15 ft. over E. slope to cor.

40.00 Point for the $\frac{1}{4}$ sec. cor. of secs. 3 and 34.

Set an iron post, 30 ins. long, $2\frac{1}{2}$ ins. diam., 10 ins. in the ground to solid rock, and in a mound of stone to top, with brass cap mkd.

$\frac{1}{4}$ S 34
S 3
1954

from which

A juniper, 14 ins. diam., bears N. 19° 00' E., 120 lks. dist., mkd. $\frac{1}{4}$ S 34 BT.

A juniper, 8 ins. diam., bears S. 30° 06' W., 39 lks. dist., mkd. $\frac{1}{4}$ S 3 BT.

44.00 Leave scattering timber in area where sagebrush has been cleared by railing, edge bears NW. and SE.

49.50 Road, bears NW. and SE.; leave area where sagebrush has been cleared by railing, edge bears NE. and SW.; enter scattering timber.

55.30 Wash, 15 lks. wide, 2 ft. deep, drains S.; enter heavy timber, edge bears NE. and SW.

68.30 Begin descent; desc. 51 ft. over W. slope.

75.47 Wash, 10 lks. wide, $1\frac{1}{2}$ ft. deep, drains SW.

80.00 Point for the cor. of secs. 3, 4, 33 and 34.

Set an iron post, 30 ins. long, $2\frac{1}{2}$ ins. diam., 22 ins. in the ground, with brass cap mkd.

BOOK 4456

NORTH BOUNDARY OF T. 35 N., R. 4 W.

Chains

T 36 N R 4 W
 S 33 | S 34

 S 4 | S 3
 T 35 N
 1954

from which

A piñon, 10 ins. diam., bears N. 7° 45' E., 52 lks. dist., mkd. T36N R4W S 34 BT.

A juniper, 12 ins. diam., bears S. 14° 00' E., 80 lks. dist., mkd. T35N R4W S 3 BT.

A piñon, 10 ins. diam., bears S. 52° 50' W., 54 lks. dist., mkd. T35N R4W S 4 BT.

A juniper, 18 ins. diam., bears N. 67° 12' W., 49 lks. dist., mkd. T36N R4W S 33 BT.

Land, low rolling.
 Soil, gravelly clay loam.
 Timber, juniper and piñon.
 Undergrowth, sagebrush, buckbrush and mountain holly.

S. 89° 58' W., bet. secs. 4 and 33.

Over low rolling land, through heavy timber and undergrowth.

7.20 Leave heavy timber, edge bears NW. and SE.; desc. 17 ft. over W. slope.

14.80 Wash, 6 lks. wide, 1½ ft. deep, drains NW.; enter scattering timber.

40.00 Point for the ¼ sec. cor. of secs. 4 and 33.

Set an iron post, 30 ins. long, 2½ ins. diam., 22 ins. in the ground, with brass cap mkd.

¼ S 33

 S 4
 1954

from which

A juniper, 12 ins. diam., bears N. 16° 00' E., 126 lks. dist., mkd. ¼ S 33 BT.

A juniper, 12 ins. diam., bears S. 50° 33' W., 167 lks. dist., mkd. ¼ S 4 BT.

Continue over low rolling land, through scattering timber and heavy undergrowth.

50.60 Wash, 3 lks. wide, 8 ins. deep, drains NE.

53.03 Road, bears N. and S.

62.20 Enter heavy timber; edge bears NE. and SW.

65.00 Begin ascent; asc. 37 ft. over gradual E. slope.

80.00 Point for the cor. of secs. 4, 5, 32 and 33.

Set an iron post, 30 ins. long, 2½ ins. diam., 22 ins. in the ground, with brass cap mkd.

NORTH BOUNDARY OF T. 35 N., R. 4 W.

Chains

T 36 N R 4 W	
S 32	S 33
S 5	S 4
T 35 N	
1954	

from which

A juniper, 30 ins. diam., bears N. 82° 03' E., 118 lks. dist., mkd. T36N R4W S 33 BT.

A pinon, 10 ins. diam., bears S. 25° 13' E., 336 lks. dist., mkd. T35N R4W S 4 BT.

A pinon, 12 ins. diam., bears S. 25° 15' W., 340 lks. dist., mkd. T35N R4W S 5 BT.

A pinon, 30 ins. diam., bears N. 11° 36' W., 117 lks. dist., mkd. T36N R4W S 32 BT.

Land, low rolling.
Soil, gravelly clay loam.
Timber, juniper and pinon.
Undergrowth, sagebrush and mountain holly.

S. 89° 58' W., bet. secs. 5 and 32.

Over low rolling land, through heavy timber and undergrowth.

9.70 Begin descent; desc. 95 ft. over gradual W. slope.

16.94 Wash, 20 lks. wide, 3 ft. deep, drains N.

25.00 Begin descent; desc. 53 ft. over gradual W. slope.

34.00 Wash, 15 lks. wide, 3 ft. deep, drains N.; asc. 58 ft. over E. slope.

40.00 Point for the 1/4 sec. cor. of secs. 5 and 32.

Set an iron post, 30 ins. long, 2 1/2 ins. diam., 22 ins. in the ground, with brass cap mkd.

1/4	S 32

	S 5
	1954

from which

A pinon, 10 ins. diam., bears N. 14° 00' E., 37 lks. dist., mkd. 1/4 S 32 BT.

A pinon, 8 ins. diam., bears S. 7° 08' W., 38 lks. dist., mkd. 1/4 S 5 BT.

Continue over low rolling land, through heavy timber and undergrowth.

58.60 Begin descent; desc. 101 ft. over gradual W. slope.

79.23 Wash, 8 lks. wide, 1 1/2 ft. deep, drains NW.

80.00 Point for the cor. of secs. 5, 6, 31 and 32.

Set an iron post, 30 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.

BOOK 4456

NORTH BOUNDARY OF T. 35 N., R. 4 W.

Chains

T 36 N R 4 W

S 31 | S 32

S 6 | S 5

T 35 N

1954

from which

A pinon, 12 ins. diam., bears N. $64^{\circ} 32'$ E., 79 lks. dist.,
mkd. T36N R4W S 32 BT.

A pinon, 12 ins. diam., bears S. $24^{\circ} 20'$ E., 58 lks. dist.,
mkd. T35N R4W S 5 BT.

A pinon, 14 ins. diam., bears S. $35^{\circ} 15'$ W., 127 lks. dist.,
mkd. T35N R4W S 6 BT.

A juniper, 10 ins. diam., bears N. $38^{\circ} 17'$ W., 61 lks. dist.,
mkd. T36N R4W S 31 BT.

Land, low rolling.

Soil, gravelly clay loam.

Timber, juniper and pinon.

Undergrowth, sagebrush, buckbrush and mountain holly.

S. $89^{\circ} 58'$ W., bet. secs. 6 and 31.

Over low rolling land, through heavy timber and undergrowth.

13.60 Begin descent; desc. 23 ft. over gradual W. slope.

19.88 Road, bears N. and S.

23.60 Begin ascent; asc. 23 ft. over E. slope.

29.00 Top of ascent, slopes N.; desc. 29 ft. over W. slope.

33.77 Road, bears N. and S.

40.00 Point for the $\frac{1}{4}$ sec. cor. of secs. 6 and 31.

Set an iron post, 30 ins. long, $2\frac{1}{2}$ ins. diam., 6 ins. in the ground
to solid rock, and in a mound of stone to top, with brass cap. mkd.

 $\frac{1}{4}$ S 31

S 6

1954

from which

A juniper, 14 ins. diam., bears N. $39^{\circ} 04'$ E., 220 lks. dist.,
mkd. $\frac{1}{4}$ S 31 BT.

A juniper, 10 ins. diam., bears S. $19^{\circ} 28'$ W., 54 lks. dist.,
mkd. $\frac{1}{4}$ S 6 BT.

Continue over low rolling land, through heavy timber and undergrowth.

47.00 Begin descent; desc. 61 ft. over gradual W. slope to cor.

62.00 Leave heavy timber, edge bears NW. and SE.; enter heavy undergrowth.

78.34 The cor. of Ts. 35 and 36 N., Rs. 4 and 5 W., which is monumented
with an iron post, $2\frac{1}{2}$ ins. diam., firmly set, marked and witnessed as
described in field notes of survey of E. bdy. of T. 35 N., R. 5 W.,
this group.

NORTH BOUNDARY OF T. 35 N., R. 4 W.

Chains

Land, low rolling.
Soil, gravelly clay loam.
Timber, juniper and pinon.
Undergrowth, sagebrush.

Survey of a Portion of the Subdivision of T. 35 N., R. 4 W.

From the cor. of secs. 2, 3, 34 and 35, on the N. bdy. of the Tp., monumented with an iron post, 2½ ins. diam., firmly set and heretofore described.

S. 0° 01' E., bet. secs. 2 and 3.

Over nearly level land, through heavy timber and undergrowth.

8.80 Road, bears NW. and SE.


27.30 Leave heavy timber, edge bears NW. and SE.

31.40 Road, bears NW. and SE.

37.30 Enter area where sagebrush has been railed, edge bears NW. and SE.

40.00 Point for the ¼ sec. cor. of secs. 2 and 3.

Set an iron post, 30 ins. long, 2½ ins. diam., 20 ins. in the ground, with brass cap mkd.



from which

A juniper, 12 ins. diam., bears N. 31° 55' E., 317 lks. dist., mkd. ¼ S 2 BT.

A juniper, 16 ins. diam., bears N. 88° 45' W., 14 lks. dist., mkd. ¼ S 3 BT.


65.60 Continue over nearly level land, through scattering timber.

Road, bears N. 80° E. and W.

68.50 Leave area where sagebrush has been railed, edge bears E. and W.; enter heavy timber.

80.00 Point for the cor. of secs. 2, 3, 10 and 11.

Set an iron post, 30 ins. long, 2½ ins. diam., 22 ins. in the ground, with brass cap mkd.



from which

A juniper, 16 ins. diam., bears N. 79° 40' E., 116 lks. dist., mkd. T35N R4W S 2 BT.

A juniper, 16 ins. diam., bears S. 63° 50' E., 110 lks. dist., mkd. T35N R4W S 11 BT.

A pinon, 18 ins. diam., bears S. 40° 42' W., 420 lks. dist., mkd. T35N R4W S 10 BT.

BOOK 4456

PORTION OF THE SUBDIVISION OF T. 35 N., R. 4 W.

Chains

A juniper, 20 ins. diam., bears N. 59° 51' W., 405 lks. dist.,
mkd. T35N R4W S 3 BT.

Land, nearly level.
Soil, gravelly clay loam.
Timber, juniper and pinon.
Undergrowth, sagebrush.

East, between secs. 2 and 11.

Over gently rolling land, through heavy timber; desc. 83 ft. over
E. slope.

14.49 Road, bears N. and S.

26.20 Leave heavy timber, edge bears NW. and SE.

33.00 Bottom of descent; asc. 40 ft. to cor.

40.00 Point for the $\frac{1}{4}$ sec. cor. of secs. 2 and 11.

Set an iron post, 30 ins. long, $2\frac{1}{2}$ ins. diam., 12 ins. in the ground
to solid rock, and in a mound of stone to top, with brass cap mkd.

$$\frac{1}{4} \begin{array}{l} \text{S } 2 \\ \hline \text{S } 11 \\ 1954 \end{array}$$

from which

A juniper, 12 ins. diam., bears S. 63° 40' W., 126 lks. dist.,
mkd. $\frac{1}{4}$ S 11 BT.

A juniper, 18 ins. diam., bears N. 15° 53' W., 76 lks. dist.,
mkd. $\frac{1}{4}$ S 2 BT.

Continue over nearly level land, through scattering timber.

53.63 Point for the W. end of triangulation and witness point for secs. 2
and 11.

Set an iron post, 30 ins. long, $2\frac{1}{2}$ ins. diam., 10 ins. in the ground
to solid rock, and in a mound of stone to top, with brass cap mkd.

$$\begin{array}{l} \text{T } 35 \text{ N } \text{ R } 4 \text{ W} \\ \hline \text{S } 2 \\ \hline \text{S } 11 \\ 1954 \end{array} \quad \text{WP}$$

from which

A juniper, 12 ins. diam., bears N. 3° 10' E., 60 lks. dist.,
mkd. T35N R4W S 2 WP BT.

A juniper, 18 ins. diam., bears S. 4° 49' E., 49 lks. dist.,
mkd. T35N R4W S 11 WP BT.

A pinon, 20 ins. diam., bears N. 63° 57' W., 197 lks. dist.,
mkd. T35N R4W S 2 WP BT.

No other suitable bearing tree available.

Continue by triangulation over land which is inaccessible.

54.63 Top of sandstone rim approximately 300 ft. high, edge bears NE. and
SW.; continue descent over broken land to corner.

PORTION OF THE SUBDIVISION OF T. 35 N., R. 4 W.

Chains

80.00

Point for the cor. of secs. 1, 2, 11 and 12, inaccessible, not monumented.

Land, gently rolling and broken mountainous.
Soil, gravelly clay loam.
Timber, juniper and pinon.
Undergrowth, sagebrush.

General Description

The general elevation of the township ranges from about 3500 ft. in the southwestern and west central part to 5800 ft. above sea level in the eastern portion of T. 35 N., R. 4 W.

The western and central portion of the township is gently and low rolling land, and the southern and eastern portion is broken mountain land adjacent to the Grand Canyon of the Colorado and Kanab Creek which flows into the Colorado River near the southeast corner of the township. The Robinson Wash drains the central and northern portion of the township.

The soil is mostly sandy and gravelly clay loam. There is a heavy stand of juniper and pinon timber over most of the township, except in the valleys which are covered with a heavy growth of sagebrush except in areas where the sagebrush has been railed in order to improve the stand of native grasses.

There are no settlers living within the township. The predominant interest is in stock grazing, and this township provides good winter range during the late fall and winter months. There is no land under cultivation within the township.

