

UNITED STATES
DEPARTMENT OF THE INTERIOR
BUREAU OF LAND MANAGEMENT

Original

FIELD NOTES

of the

Resurvey of a Portion of the 9th Standard Parallel North

Through Range 4 West,

and the

Survey of the West Boundary

and a Portion of the

Subdivision of

Township 36 North, Range 4 West

Of the Gila and Salt River Meridian,

In the State of Arizona

EXECUTED BY

Horace G. Parker - Cartographer-Cadastral

Under special instructions dated August 16, 1954, which provided
for the surveys included under Group No. 294, approved August 20, 1954
and assignment instructions dated October 4, 1954

Survey commenced December 2, 1954

Survey completed December 21, 1954

4458

4458

4458

BOOK 4458

INDEX DIAGRAM

Township 36 North, Range 4 West

1 1

7 6	5	4	3	15 14 2	13 1
6 7	8	9	10	14 11	12 12
5 18	17	16	15	14	10 18
4 19	20	21	22	23	10 24
3 30	29	28	27	26	10 25
19 2 31	18 17 32	16 33	34	35	9 36

1

ECC. 4458

Resurvey of a Portion of the 9th Stan. Par. N. through R. 4 W., Survey of the West Boundary and a Portion of the Subdivision of T. 36 N., R. 4 W.

Chains

The following field notes are those of the resurvey of a portion of the 9th Standard Parallel North through R. 4 W., the survey of the West Boundary and a portion of the subdivision of Township 36 North, Range 4 West.

The survey was initiated on the official request by the Arizona State Land Department, Phoenix, Arizona, and the Division of Range Management, requesting the surveys of certain unsurveyed exterior boundaries as a means of assisting them in affixing the boundaries of allotments.

For the description of instruments and method of measurement used, refer to the field notes of the survey of the South, East and North Boundaries and a portion of the subdivisional lines of Township 35 North, Range 5 West, executed during the same period.

Azimuth determinations were made at frequent intervals during the survey. For detailed data pertaining to azimuth determination, refer to the field notes of the survey of the South, East and North Boundaries and a portion of the subdivision of T. 35 N., R. 5 W., executed under this same group.

The computed geographic position of the SE. corner of the Tp. is determined as latitude $36^{\circ} 28' 04''$ N., and longitude $112^{\circ} 40' 25.87''$ W.

The observed magnetic declination is $14^{\circ} 45'$ E.

EAST BOUNDARY OF T. 36 N., R. 4 W.

The entire East boundary except the south 7 chains falls in the inaccessible breaks and canyons on the west side of Kanab Creek and was not surveyed.

RESURVEY OF A PORTION OF THE 9TH STAN. PAR. N., THROUGH R. 4 W.

standard

From the $\frac{1}{4}$ sec. cor. of sec. 36, on the S. bdy. of T. 37 N., R. 4 W., monumented with an iron post, 1 in. diam., mkd. and witnessed as described in the returns of the 1914 survey of the 9th Stan. Par. N. through R. 4 W.

West, on the true line, S. bdy. of sec. 36.

Over broken sandstone cliffs.

12.43 Top of sandstone rim, edge bears SE. and NW.; desc. 72 ft. over W. slope.

14.00 Bottom of descent; asc. 46 ft. over E. slope.

18.74 Top of sandstone ledge, bears N. and S.; desc. 52 ft. over W. slope.

39.57 Approximate center of Hack's Canyon, approximately 1 chain wide, course SSE. 3 chs., thence S. 70° E.

40.02 Point for the standard cor. of secs. 35 and 36, T. 37 N., R. 4 W., at proportionate distance; there is no remaining evidence of the original corner. This point falls near the center of Hack's Canyon and is deemed unsafe for the corner.

Land, broken and rocky sandstone cliffs.

Soil, rocky and gravelly clay loam.

Timber, none.

Undergrowth, scattering sagebrush.

From the true point for the standard cor. of secs. 35 and 36, T. 37 N., R. 4 W.

West, along the S. bdy. of sec. 35.

Over broken and rolling land.

1.50 Point selected for the witness corner standard corner of secs. 35 and 36, on W. bank of Hack's Canyon, near bottom of sandstone ledge.

Portion of the 9th Stan. Par. N. Through R. 4 W.

Chains	Set an iron post, 30 ins. long, $2\frac{1}{2}$ ins. diam., 24 ins. in the ground with brass cap mkd.
	$\begin{array}{ccc} T\ 37\ N & R\ 4\ W & \\ \hline S\ 35 & & S\ 36 \\ & & WC \\ & & 1954 \end{array}$
	raise a mound of stone, 4 ft. base, $2\frac{1}{2}$ ft. high, N. of cor.
	Begin ascent; asc. 265 ft. over rocky surface, broken with small draws and spurs projecting N.
40.02	The standard $\frac{1}{4}$ sec. cor. of sec. 35, monumented with an iron post, 1 in. diam., firmly set, mkd. and witnessed as described in the record of the 1914 survey of the 9th Stan. Par. N. through R. 4 W.
	Land, broken sandstone ledges. Soil, rocky and gravelly clay loam. Timber, none. Undergrowth, scattering sagebrush.
WEST BOUNDARY OF T. 36 N., R. 4 W.	
	From the cor. of Ts. 35 and 36 N., Rs. 4 and 5 W., monumented with an iron post, $2\frac{1}{2}$ ins. diam., firmly set, mkd. and witnessed as described in the returns of the survey of the E. bdy. of T. 35 N., R. 5 W.
	North, bet. secs. 31 and 36.
	Over gently rolling land, through heavy undergrowth.
0.30	Road, bears NE. and SW.
20.00	Enter scattering timber.
35.00	Top of low spur from ridge, slopes NE.
40.00	Point for the $\frac{1}{4}$ sec. cor. of secs. 31 and 36.
	Set an iron post, 30 ins. long, $2\frac{1}{2}$ ins. diam., 10 ins. in the ground to solid rock, and in a mound of stone to top, with brass cap mkd.
	$\begin{array}{ccc} & \frac{1}{4} & \\ & \cdot & \\ S\ 36 & & S\ 31 \\ & & 1954 \end{array}$
	from which
	A juniper, 12 ins. diam., bears S. $26^{\circ} 20'$ E., 119 lks. dist., mkd. $\frac{1}{4}$ S 31 BT.
	A juniper, 10 ins. diam., bears S. $53^{\circ} 04'$ W., 24 lks. dist., mkd. $\frac{1}{4}$ S. 36 BT.
	Continue over rolling land, through scattering timber.
45.00	Leave scattering timber.
65.52	Wash, 6 lks. wide, 3 ft. deep, drains NE.
71.70	Wash, 10 lks. wide, $1\frac{1}{2}$ ft. deep, drains E.
72.20	Road, bears E. and W.; begin ascent over gradual S. slope, through scattering timber.

BOOK 4458

West Boundary, T. 36 N., R. 4 W.

Chains

80.00

Point for the cor. of secs. 25, 30, 31 and 36.

Set an iron post 30 ins. long, 2 1/2 ins. diam., 24 ins. in the ground with brass cap mkd.

T 36 N	
R 5 W	R 4 W
S 25	S 30
S 36	S 31
1954	

from which

A juniper, 12 ins. diam., bears N. 34° 45' E., 82 lks. dist., mkd. T36N R4W S 30 BT.

A juniper, 12 ins. diam., bears S. 36° 04' E., 110 lks. dist., mkd. T36N R4W S 31 BT.

A juniper, 10 ins. diam., bears S. 11° 30' W., 163 lks. dist., mkd. T36N R5W S 36 BT.

A juniper, 12 ins. diam., bears N. 31° 55' W., 106 lks. dist., mkd. T36N R5W S 25 BT.

Land, gently rolling.

Soil, sandy and gravelly clay loam.

Timber, scattering juniper and pinon.

Undergrowth, sagebrush and mountain holly.

North, between secs. 25 and 30.

Over gently rolling land, through scattering timber and heavy undergrowth.

15.00

Top of low spur from ridge, slopes W.; enter heavy timber, edge bears E. and W.; desc. 23 ft. over gradual N. slope.

29.00

Wash, 4 lks. wide, 1 1/2 ft. deep, drains NE.; asc. over gradual S. slope.

39.80

Top of spur from ridge, slopes E.

40.00

Point for the 1/4 sec. cor. of secs. 25 and 30.

Set an iron post, 30 ins. long, 2 1/2 ins. diam., 24 ins. in the ground with brass cap mkd.

1/4	
S 25	S 30
1954	

from which

A juniper, 14 ins. diam., bears N. 63° 30' E., 18 lks. dist., mkd. 1/4 S 30 BT.

A juniper, 12 ins. diam., bears N. 43° 00' W., 20 lks. dist., mkd. 1/4 S 25 BT.

Continue over rolling land, through heavy timber; desc. 14 ft. over N. slope.

45.10

Bottom of descent; thence over nearly level land.

50.60

Top of low spur from ridge, slopes E.

West Boundary, T. 36 N., R. 4 W.

Chains

57.90 Begin ascent; asc. 53 ft. over S. slope.

60.20 ^{flat} Top of flat spur, slopes E.

65.80 Begin descent; desc. 25 ft. over N. slope.

71.00 Wire fence, 4 strand barbed wire, bears E. and W.

80.00 Point for the cor. of secs. 19, 24, 25 and 30.

Set an iron post, 30 ins. long, 2½ ins. diam., 8 ins. in the ground to solid rock, and in a mound of stone to top, with brass cap mkd.

T 36 N
R 5 W R 4 W
S 24 | S 19

S 25 | S 30
1954

from which

A pinon, 8 ins. diam., bears N. 44° 50' E., 63 lks. dist., mkd. T36N R4W S 19 BT.

A juniper, 10 ins. diam., bears S. 85° 04' E., 78 lks. dist., mkd. T36N R4W S 30 BT.

A pinon, 8 ins. diam., bears S. 41° 00' W., 64 lks. dist., mkd. T36N R5W S 25 BT.

A pinon, 18 ins. diam., bears N. 64° 05' W., 61 lks. dist., mkd. T36N R5W S 24 BT.

Land, low rolling.
Soil, sandy and gravelly clay loam.
Timber, juniper and pinon.
Undergrowth, sagebrush.

North, between secs. 19 and 24.

Over rolling land, through heavy timber; desc. 66 ft. over N. slope.

10.46 Wash, 10 lks. wide, 2 ft. deep, drains E.; asc. 70 ft. over S. slope.

23.00 Top of ascent, slopes E.; desc. 31 ft. over NNE. slope.

26.20 Bottom of descent; asc. 31 ft. over S. slope.

33.00 Top of low spur, slopes E.; thence over nearly level land to cor.

40.00 Point for the ¼ sec. cor. of secs. 19 and 24.

Set an iron post, 30 ins. long, 2½ ins. diam., 20 ins. in the ground with brass cap mkd.

¼
S 24 | S 19
1954

from which

A juniper, 8 ins. diam., bears N. 34° 09' E., 81 lks. dist., mkd. ¼ S 19 BT.

A juniper, 8 ins. diam., bears S. 21° 06' W., 29 lks. dist., mkd. ¼ S 24 BT.

West Boundary, T. 36 N., R. 4 W.

Chains

Continue over rolling land, through heavy timber; desc. 292 ft. over N. slope.

70.00 Leave heavy timber, edge bears E. and W.; continue through scattering timber.

78.68 Wash, 16 lks. wide, 5 ft. deep, drains E.

79.85 Point for the witness corner of secs. 13, 18, 19 and 24.

Set an iron post, 30 ins. long, $2\frac{1}{2}$ ins. diam., 20 ins. in the ground with brass cap mkd.

T 36 N
R 5 W R 4 W
WC
S 13 | S 18
S 24 | S 19
1954

from which

A juniper, 24 ins. diam., bears N. $34^{\circ} 06'$ E., 177 lks. dist., mkd. T36N R4W S 18 WC BT.

A juniper, 8 ins. diam., bears S. $72^{\circ} 15'$ E., 150 lks. dist., mkd. T36N R4W S 19 WC BT.

A pinon, 12 ins. diam., bears S. $73^{\circ} 43'$ W., 107 lks. dist., mkd. T36N R5W S 24 WC BT.

A juniper, 14 ins. diam., bears N. $26^{\circ} 45'$ W., 179 lks. dist., mkd. T36N R5W S 13 WC BT.

80.00 True point for the cor. of secs. 13, 18, 19 and 24 falls on top of small sandstone ledge, edge bears E. and W.

Land, low rolling.
Soil, sandy and gravelly clay loam.
Timber, juniper and pinon.
Undergrowth, sagebrush and mountain holly.

North, between secs. 13 and 18.

Over rolling land, through scattering timber and heavy undergrowth; asc. 139 ft. over S. slope.

12.30 Enter heavy timber, edge bears NE. and SW.

16.20 Top of low ridge, bears E. and W.; road on top of ridge, bears E. and W.; begin descent, desc. 104 ft. over N. slope.

26.27 Wash, 8 lks. wide, 2 ft. deep, drains NE.

28.34 Wash, 13 lks. wide, 3 ft. deep, drains E.; asc. 108 ft. over S. slope.

40.00 Point for the $\frac{1}{4}$ sec. cor. of secs. 13 and 18.

Set an iron post, 30 ins. long, $2\frac{1}{2}$ ins. diam., 20 ins. in the ground with brass cap mkd.

$\frac{1}{4}$
S 13 | S 18
1954

West Boundary, T. 36 N., R. 4 W.

Chains

from which

A juniper, 8 ins. diam., bears N. 81° 20' E., 45 lks. dist., mkd. $\frac{1}{4}$ S 18 BT.

A pinon, 24 ins. diam., bears S. 40° 55' W., 30 lks. dist., mkd. $\frac{1}{4}$ S 13 BT.

Continue over rolling land, through heavy timber.

49.00 Top of spur from ridge, slopes E.; desc. 17 ft. over N. slope.

54.40 Bottom of descent; begin ascent, asc. 15 ft. over S. slope.

58.00 Top of ascent, slopes E.; thence over nearly level land.


67.00 Begin descent; desc. 236 ft. over N. slope.

76.48 Top of sandstone rim, 75 ft. high, edge bears NW. and E.; leave heavy timber, edge bears NW. and E.

77.93 Top of sandstone rim, 75 ft. high, edge bears E. and W.; begin ascent, asc. 48 ft. over S. slope.

80.00 Point for the cor. of secs. 7, 12, 13 and 18.

Set an iron post, 30 ins. long, 2 $\frac{1}{2}$ ins. diam., 24 ins. in the ground with brass cap mkd:



raise a mound of stone, 4 ft. base, 2 $\frac{1}{2}$ ft. high, W. of corner.

Land, rolling.
Soil, gravelly clay loam.
Timber, juniper and pinon.
Undergrowth, sagebrush and mountain holly.

North, between secs. 7 and 12.

Over heavily rolling land, through scattering timber and heavy undergrowth; asc. 116 ft. over S. slope.

5.40 Top of spur from ridge, slopes E.; continue along E. slope.


7.41 Begin descent; desc. 177 ft. over N. slope.

23.19 Wash, 20 lks. wide, 6 ft. deep, drains E.; asc. 34 ft. over S. slope.

34.35 Top of spur from ridge, slopes ENE.; desc. 86 ft. over N. slope.

40.00 Point for the $\frac{1}{4}$ sec. cor. of secs. 7 and 12.

Set an iron post, 30 ins. long, 2 $\frac{1}{2}$ ins. diam., 10 ins. in the ground to solid rock, and in a mound of stone to top, with brass cap mkd.



West Boundary, T. 36 N., R. 4 W.

Chains

from which.

A pinon, 5 ins. diam., bears S. $28^{\circ} 30'$ E., 23 lks. dist.,
mkd. $\frac{1}{4}$ S 7 BT.

A pinon, 16 ins. diam., bears S. $74^{\circ} 08'$ W., 22 lks. dist.,
mkd. $\frac{1}{4}$ S 12 BT.

Continue descent over heavily rolling land, through scattering
timber; desc. 68 ft. over N. slope.

- 42.10 Top of conglomerate rim, 100 ft. high, bears NW. and SE.
- 49.70 Bottom of descent; begin ascent, asc. 136 ft. over S. slope.
- 59.90 Top of spur from ridge, slopes E.; desc. 42 ft. over N. slope.
- 65.30 Bottom of descent; begin ascent; asc. 69 ft. to cor.
- 79.95 Top of spur from ridge, slopes NE.
- 80.00 Point for the cor. of secs. 1, 6, 7 and 12.
- Set an iron post, 30 ins. long, $2\frac{1}{2}$ ins. diam., 24 ins. in the ground
with brass cap mkd.

T 36 N	
R 5 W R 4 W	
S 1	S 6
S 12	S 7
1954	

from which

A pinon, 16 ins. diam., bears N. $77^{\circ} 10'$ E., 311 lks. dist.,
mkd. T36N R4W S 6 BT.

A juniper, 10 ins. diam., bears S. $18^{\circ} 26'$ W., 130 lks. dist.,
mkd. T36N R5W S 12 BT.

No other suitable bearing trees within limits.

Land, heavily rolling.
Soil, gravelly clay loam.
Timber, scattering juniper and pinon.
Undergrowth, sagebrush.

North, between secs. 1 and 6.

Descend gradual N. slope, through scattering timber.

- 10.52 Top of canyon rim on S. side of Hack's Canyon, edge bears NW. and
SE.

From this point, the line falls along the W. side of an inaccessible
canyon which drains NNE. into Hack's Canyon.

Continue by traverse.

- 40.00 Point for the $\frac{1}{4}$ sec. cor. of secs. 1 and 6, inaccessible, not
monumented.


From this point, a witness point bears W. 11.91 chs. dist.

At the point selected for the witness point, on top of the W. rim
of the canyon.

West Boundary, T. 36 N., R. 4 W.

Chains

Set an iron post, 30 ins. long, $2\frac{1}{2}$ ins. diam., 5 ins. in the ground to solid rock, and in a mound of stone to top, with brass cap mkd.



from which

A juniper, 16 ins. diam., bears S. $61^{\circ} 30'$ E., 41 lks. dist., mkd. $\frac{1}{4}$ S 6 WP BT.

A juniper, 24 ins. diam., bears N. $48^{\circ} 45'$ W., 186 lks. dist., mkd. $\frac{1}{4}$ S 1 WP BT.

Continue over inaccessible broken mountainous land over E. slopes along W. side of canyon.

77.40

Intersect the 9th Standard Parallel North.

Point for the closing cor. of Ts. 36 N., Rs. 4 and 5 W., inaccessible, not monumented.

From the point of intersection, the standard $\frac{1}{4}$ sec. cor. on the S. bdy. sec. 31, T. 37 N., R. 4 W., bears E. 29.55 chs. dist., monumented with an iron post, 1 in. diam., firmly set, marked and witnessed as described in the record of the 1914 survey of the 9th Stan. Par. N., through R. 4 W.


From the same point, the standard cor. of secs. 31 and 36, Ts. 37 N., Rs. 4 and 5 W., bears W. 10.45 chs. dist., monumented with an iron post, 3 ins. diam., firmly set, marked and witnessed as described in the 1914 survey of the 9th Stan. Par. N., through R. 4 W.

From the same point, the witness corner closing corner of secs. 1 and 6, Ts. 36 N., Rs. 4 and 5 W., bears W., 6.95 chs. dist.

North end of traverse.

At the point selected for the witness corner closing corner on top of the rim on the S. side of Hack's Canyon, approximately 1500 ft. above the bottom.

Set an iron post, 30 ins. long, $2\frac{1}{2}$ ins. diam., 5 ins. in the ground to solid rock, and in a mound of stone to top, with brass cap mkd.



raise a mound of stone, 4 ft. base, $2\frac{1}{2}$ ft. high, S. of corner.

From this point, the standard corner of secs. 31 and 36, Ts. 37 N., Rs. 4 and 5 W., bears W., 3.50 chs. dist., monumented with an iron post, 3 ins. diam., firmly set, marked and witnessed as described in the record of the 1914 survey of the 9th Stan. Par. N., through R. 4 W.

From this same point, the standard $\frac{1}{4}$ sec. cor. of sec. 31, bears E., 36.50 chs. dist., monumented with an iron post, 1 in. diam., firmly set, marked and witnessed as described in the record of the 1914 survey of the 9th Stan. Par. N., through R. 4 W.

Continue over inaccessible broken mountainous land over E. slopes along W. side of canyon.

West Boundary, T. 36 N., R. 4 W.

Chains

Land, broken mountainous, inaccessible.
Soil, gravelly and rocky clay loam.
Timber, scattering juniper and pinon.
Undergrowth, sagebrush.

SURVEY OF A PORTION OF THE SUBDIVISION OF T. 36 N., R. 4 W.

Beginning the subdivisional survey at the corner of secs. 1, 2, 35 and 36, on the S. bdy. of the township, monumented with an iron post, $2\frac{1}{2}$ ins. diam., firmly set, marked and witnessed as described in the returns of the survey of the N. bdy. of T. 35 N., R. 4 W.

N. $0^{\circ} 01'$ W., bet. secs. 35 and 36.

Over rolling land, through scattering timber and undergrowth; desc. 29 ft. over N. slope.

5.00 Bottom of descent; continue along W. slope of spur.

18.50 Top of spur from ridge, slopes W.; desc. 98 ft. over N. slope.

25.00 Wash, 35 lks. wide, 7 ft. deep, drains E.; asc. 163 ft. over steep SSE. slope.

40.00 Point for the $\frac{1}{4}$ sec. cor. of secs. 35 and 36.

Set an iron post, 30 ins. long, $2\frac{1}{2}$ ins. diam., 12 ins. in the ground to solid rock, and in a mound of stone to top, with brass cap mkd.

$$\begin{array}{c} \frac{1}{4} \\ \text{S } 35 \quad | \quad \text{S } 36 \\ 1954 \end{array}$$

from which

A pinon, 20 ins. diam., bears S. $37^{\circ} 41'$ E., 13 lks. dist., mkd. $\frac{1}{4}$ S 36 BT.

A juniper, 22 ins. diam., bears S. $36^{\circ} 00'$ W., 80 lks. dist., mkd. $\frac{1}{4}$ S 35 BT.

Continue over rolling land, through scattering timber; desc. 16 ft. over N. slope.

55.00 Top of spur from ridge, slopes E.; continue descent, desc. 105 ft. over N. slope.

78.43 Wash, 20 lks. wide, 5 ft. deep, drains NE.

80.00 Point for the cor. of secs. 25, 26, 35 and 36.

Set an iron post, 30 ins. long, $2\frac{1}{2}$ ins. diam., 24 ins. in the ground with brass cap mkd.

$$\begin{array}{c} \text{T } 36 \text{ N} \quad \text{R } 4 \text{ W} \\ \text{S } 26 \quad | \quad \text{S } 25 \\ \hline \text{S } 35 \quad | \quad \text{S } 36 \\ 1954 \end{array}$$

from which

A juniper, 10 ins. diam., bears N. $71^{\circ} 33'$ E., 368 lks. dist., mkd. T36N R4W S 25 BT.

A juniper, 12 ins. diam., bears S. $56^{\circ} 21'$ E., 180 lks. dist., mkd. T36N R4W S 36 BT.

BOOK 4458

Portion of the Subdivision of T. 36 N., R. 4 W.

Chains	
	<p>A juniper, 6 ins. diam., bears S. 57° 03' W., 235 lks. dist., mkd. T36N R4W S 35 BT.</p> <p>A juniper, 8 ins. diam., bears N. 67° 45' W., 168 lks. dist., mkd. T36N R4W S 26 BT.</p> <p>Land, heavily rolling. Soil, gravelly clay loam. Timber, scattering juniper and pinon. Undergrowth, sagebrush and mountain holly, and buckbrush.</p>
	<p>N. 0° 01' W., bet. secs. 25 and 26.</p> <p>Over rolling land, through scattering timber; asc. 10 ft. over S. slope.</p>
1.10	Top of ascent, slopes E.; desc. 33 ft. over N. slope.
12.77	Wash, 8 lks. wide, 1½ ft. deep, drains E.; asc. 11 ft. over S. slope.
16.26	Top of spur from ridge, slopes NE.; desc. 176 ft. over N. slope.
28.53	Wash, 10 lks. wide, 3 ft. deep, drains NE.
35.20	Point used as the S. point of the triangulation; continue chaining to the canyon rim, thence by triangulation across a series of deep rocky canyons on W. side of Kanab Creek, which are inaccessible.
35.45	Point for the witness ¼ sec. cor. of secs. 25 and 26.
	<p>Set an iron post, 30 ins. long, 2½ ins. diam., 24 ins. in the ground with brass cap mkd.</p> <div style="text-align: center;"> <p>¼ W C S 26 ↑ S 25 1954</p> </div>
40.00	raise a mound of stone, 3 ft. base, 2 ft. high, W. of cor.
80.00	Point for the ¼ sec. cor. of secs. 25 and 26, inaccessible, not monumented. Point for the cor. of secs. 23, 24, 25 and 26, inaccessible, not monumented.
	<p>Land, rolling and broken mountainous. Soil, gravelly clay loam. Timber, juniper and pinon. Undergrowth, sagebrush.</p>
	<p>N. 0° 01' W., bet. secs. 23 and 24.</p> <p>Continue by triangulation.</p>
40.00	Point for the ¼ sec. cor. of secs. 23 and 24, inaccessible, not monumented.
80.00	Point for the cor. of secs. 13, 14, 23 and 24, inaccessible, not monumented.
	<p>Land, broken mountainous. Soil, gravelly and rocky clay loam. Timber, juniper and pinon. Undergrowth, scattering sagebrush.</p>
	<p>N. 0° 01' W., bet. secs. 13 and 14.</p>

BOOK 4458

Portion of the Subdivision of T. 36 N., R. 4 W.

Chains

- 7.40 Top of sandstone rim, approximately 350 ft. high, edge bears NE. and SW.; enter scattering timber and undergrowth.
- 8.14 N. end of triangulation. Point selected for the witness corner of secs. 13, 14, 23 and 24.
- Set an iron post, 30 ins. long, $2\frac{1}{2}$ ins. diam., 8 ins. in the ground to solid rock, and in a mound of stone to top, with brass cap mkd.
- T 36 N R 4 W

S 14	S 13
S 23	S 24

W C


1954
- raise a mound of stone, 4 ft. base, $2\frac{1}{2}$ ft. high W. of corner.
- Continue over rolling land, through scattering timber; desc. 74 ft. over gradual N. slope.
- 21.00 Wash, 12 lks. wide, $1\frac{1}{2}$ ft. deep, drains NW.; asc. 32 ft. over SW. slope.
- 27.20 Top of ascent; desc. 40 ft. over N. slope.
- 31.41 Wash, 8 lks. wide, $1\frac{1}{2}$ ft. deep, drains NW.
- 40.00 Point for the $\frac{1}{4}$ sec. cor. of secs. 13 and 14.
- Set an iron post, 30 ins. long, $2\frac{1}{2}$ ins. diam., 24 ins. in the ground, with brass cap mkd.
- $\frac{1}{4}$

S 14	S 13
------	------

1954
- from which
- A juniper, 12 ins. diam., bears N. $4^{\circ} 49' E.$, 128 lks. dist., mkd. $\frac{1}{4}$ S 13 BT.
- A juniper, 24 ins. diam., bears N. $31^{\circ} 30' W.$, 41 lks. dist., mkd. $\frac{1}{4}$ S 14 BT.
- Continue over rolling land, through scattering timber; desc. 24 ft. over N. slope.
- 44.57 Wash, 15 lks. wide, 3 ft. deep, drains NW.; asc. 68 ft. over SW. slope.
- 58.55 Top of spur from ridge, slopes W. Point used for the S. end of triangulation.
- Continue by chaining; desc. 123 ft. to the witness point located near top of sandstone rim.
- 66.60 Wash, 15 lks. wide, 3 ft. deep, drains NW.
- 68.69 Point selected for the witness point, near top of sandstone rim on S. side of a deep inaccessible canyon.
- Set an iron post, 30 ins. long, $2\frac{1}{2}$ ins. diam., 4 ins. in the ground to solid rock, and in a mound of stone to top, with brass cap mkd.

Portion of the Subdivision of T. 36 N., R. 4 W.

Chains



raise a mound of stone, 4 ft. base, $2\frac{1}{2}$ ft. high, W. of corner.

70.69 Top of sandstone rim, approximately 350 ft. high, edge bears NW. and SE.; continue by triangulation across inaccessible canyon.

80.00 Point for the cor. of secs. 11, 12, 13, and 14, inaccessible, not monumented.

Land, rolling and broken mountainous.
Soil, gravelly clay loam.
Timber, juniper and pinon.
Undergrowth, sagebrush.

N. 0° 01' W., bet. secs. 11 and 12.


Continue by triangulation over broken mountainous land.

39.95 Top of conglomerate rim, approximately 350 ft. high, edge bears NE. and SW.

40.00 Point for the $\frac{1}{4}$ sec. cor. inaccessible, not monumented.

44.99 Point for the witness $\frac{1}{4}$ sec. cor. of secs. 11 and 12 as measured from N. end of triangulation.

Set an iron post, 30 ins. long, $2\frac{1}{2}$ ins. diam., 10 ins. in the ground to solid rock, and in a mound of stone to top, with brass cap mkd.



raise a mound of stone, 4 ft. base, $2\frac{1}{2}$ ft. high, W. of corner.

Continue by triangulation over rolling land, through scattering timber.


47.70 N. end of triangulation on north side of canyon.

61.30 Top of spur from ridge, slopes NE.; desc. 67 ft. over N. slope.

69.80 Wash, 5 lks. wide, $1\frac{1}{2}$ ft. deep, drains NNW. Continue along W. slope.

72.51 Point for the witness corner of secs. 1, 2, 11 and 12.

Set an iron post, 30 ins. long, $2\frac{1}{2}$ ins. diam., 8 ins. in the ground to solid rock, and in a mound of stone to top, with brass cap mkd.



raise a mound of stone, 4 ft. base, $2\frac{1}{2}$ ft. high, W. of corner.

73.08 Point for the S. end of triangulation. Continue by triangulation over broken mountainous land.

Portion of the Subdivision of T. 36 N., R. 4 W.

Chains

73.50 Top of S. rim of Hack's Canyon, conglomerate rock rim, approximately 300 ft. high, edge bears NE. and SW.

80.00 Point for the cor. of secs. 1, 2, 11 and 12, inaccessible, not monumented.

Land, south-half, broken mountainous; north-half, low rolling.
Soil, gravelly clay loam.
Timber, juniper and pinon.
Undergrowth, sagebrush.

N. 0° 01' W., bet. secs. 1 and 2.

Descend over steep N. slope.

40.00 Point for the $\frac{1}{4}$ sec. cor. of secs. 1 and 2.

Set an iron post, 30 ins. long, $2\frac{1}{2}$ ins. diam., 10 ins. in the ground to solid rock, and in a mound of stone to top, with brass cap mkd.

$\frac{1}{4}$
S 2 | S 1
1954

raise a mound of stone, 3 ft. base, $2\frac{1}{2}$ ft. high, W. of corner.

69.63 Point for the witness corner closing corner of secs. 1 and 2.

Set an iron post, 30 ins. long, $2\frac{1}{2}$ ins. diam., 4 ins. in the ground to solid rock, and in a mound of stone to top, with brass cap mkd.

T 37 N R 4 W
S 36
S 2 | S 1
T 36 N | R 4 W
W C
C C
1954

raise a mound of stone, 4 ft. base, $2\frac{1}{2}$ ft. high, S. of corner.

75.00 Enter Hack's Canyon, approximately 2 chs. wide, course ENE.

76.25 Intersect the 9th Standard Parallel North. Point for the closing cor. of secs. 1 and 2, T. 36 N., R. 4 W. This point falls in main channel of Hack's Canyon, course S. 80° E.; and is unsafe for cor.

From the point of intersection, the true point for the standard cor. of secs. 35 and 36, T. 37 N., R. 4 W. bears W.; 9.28 chs. dist., as determined by proportionate distance. There is no remaining evidence of the original corner.

From this same point, the witness standard corner of secs. 35 and 36, T. 37 N., R. 4 W., bears W., 10.78 chs. dist., monumented with an iron post, $2\frac{1}{2}$ ins. diam., firmly set, marked and witnessed as hereinbefore described.

From this same point, the standard $\frac{1}{4}$ sec. cor. of sec. 36, bears E., 30.74 chs. dist., monumented with an iron post, 1 in. diam., firmly set, marked and witnessed as described in the 1914 survey record of the 9th Standard Parallel North.

Land, broken mountainous.
Soil, sandy and gravelly clay loam.
Timber, juniper and pinon; undergrowth, sagebrush.

Portion of the Subdivision of T. 36 N., R. 4 W.

Chains

From the true point for the cor. of secs. 11, 2, 11, and 12.
West, bet. secs. 2 and 11.

By triangulation, over inaccessible mountainous land, desc. 300 ft. over NW. slope.

15.00 Slope changes to N.

40.00 True point for the $\frac{1}{4}$ sec. cor. of secs. 2 and 11 and end of triangulation.

Set an iron post, 30 ins. long, $2\frac{1}{2}$ ins. diam., 6 ins. in the ground to solid rock, and in a mound of stone to top, with brass cap mkd.

S 2
 $\frac{1}{4}$ ———
S 11
1954

raise a mound of stone, 4 ft. base, $2\frac{1}{2}$ ft. high, N. of corner.

60.00 Head of wash, 30 lks. wide, 10 ft. deep, drains NE.

75.40 Top of conglomerate rim, approximately 350 ft. high, edge bears NNE. and SSW. approximately 10 chs., thence ESE.

76.00 Top of spur from ridge, slopes NNE. Continue over nearly level land, through scattering timber.

80.00 Point for the cor. of secs. 2, 3, 10 and 11.

Set an iron post, 30 ins. long; $2\frac{1}{2}$ ins. diam., 20 ins. in the ground, with brass cap mkd.

T 36 N R 4 W
S 3 | S 2
S 10 | S 11
1954

raise a mound of stone, 4 ft. base, $2\frac{1}{2}$ ft. high, W. of corner.

Land, broken mountainous.
Soil, sandy and gravelly clay loam.
Timber, scattering juniper and pinon.
Undergrowth, sagebrush.

N. 0° 01' W., bet. secs. 2 and 3.

Over rolling land, through scattering timber; desc. 133 ft. over N. slope.

8.46 Wash, 15 lks. wide, 4 ft. deep, drains NW.

11.39 Same wash, 15 lks. wide, 3 ft. deep, drains N.; continue descent, desc. 17 ft.

19.65 Leave wash, 15 lks. wide, 4 ft. deep, drains NE.; asc. 22 ft. over S. slope.

27.00 Top of ascent, slopes E.; desc. 13 ft. over NE. slope.

32.11 Wash, 20 lks. wide, 5 ft. deep, drains E.

33.91 Point for the witness $\frac{1}{4}$ sec. cor. of secs. 2 and 3.

Set an iron post, 30 ins. long; $2\frac{1}{2}$ ins. diam., 4 ins. in the ground to solid rock, and in a mound of stone to top, with brass cap mkd.

Portion of the Subdivision of T. 36 N., R. 4 W.

W C

$\frac{1}{4}$

S 3 ↑ S 2

1954

raise a mound of stone, 4 ft. base, $2\frac{1}{2}$ ft. high, W. of corner.

Continue over mountainous land.

34.00 Top of conglomerate rim, 350 ft. high, edge bears NW. and SE.; desc. 850 ft. over abrupt N. slope to corner.

40.00 Point for the $\frac{1}{4}$ sec. cor. of secs. 2 and 3, on steep slope, impractical to set corner.

76.35 Intersect the 9th Standard Parallel North. Point for the closing cor. of secs. 2 and 3, T. 36 N., R. 4 W.

Set an iron post, 30 ins. long, $2\frac{1}{2}$ ins. diam., 24 ins. in the ground, with brass cap mkd.

T 37 N R 4 W

S 35

S 3 | S 2

T 36 N R 4 W

C C

1954

raise a mound of stone, 4 ft. base, $2\frac{1}{2}$ ft. high, S. of corner.

From point of intersection, the standard cor. of secs. 34 and 35, T. 37 N., R. 4 W., bears W., 9.30 chs. dist., monumented with an iron post, 2 ins. diam., firmly set, marked and witnessed as described in the record of the 1914 survey of the 9th Stan. Par. N. through R. 4 W.

From this same point, the standard $\frac{1}{4}$ sec. cor. on the S. bdy. of sec. 35, T. 37 N., R. 4 W., bears E., 30.70 chs. dist., monumented with an iron post, 1 in. diam., firmly set, marked and witnessed as described in the record of the 1914 survey of the 9th Standard Parallel North, through R. 4 W.

Land, south-half, rolling; north-half, rough mountainous.

Soil, sandy and gravelly clay loam.

Timber, juniper and pinon.

Undergrowth, sagebrush.

The point for the $\frac{1}{4}$ sec. cor. of sec. 2, on the N. bdy of the Tp. is at midpoint between the closing cor. of secs. 1 and 2 and the closing cor. of secs. 2 and 3, T. 36 N., R. 4 W.

At the corner point.

Set an iron post, 30 ins. long, $2\frac{1}{2}$ ins. diam., 12 ins. in the ground to solid rock, and in a mound of stone to top, with brass cap mkd.

$\frac{1}{4}$

S 2

1954

raise a mound of stone, 4 ft. base, $2\frac{1}{2}$ ft. high, S. of corner.

From this cor., the standard $\frac{1}{4}$ sec. cor. of sec. 35, T. 37 N., R. 4 W. which is an iron post, 1 in. diam., firmly set in the ground with brass cap marked and witnessed as described in the official record, bears W., 9.30 chs. dist.

Portion of the Subdivision of T. 36 N., R. 4 W.

Chains

From this same point, the true point for the standard corner of secs. 35 and 36, T. 37 N., R. 4 W., which falls in the bottom of Hack's Canyon and is not monumented, bears E., 30.72 chs. dist.

From the corner of secs. 4, 5, 32 and 33, on the S. bdy. of the Tp., monumented with an iron post, 2½ ins. diam., firmly set, marked and witnessed as described in the returns for the survey of the N. bdy. of T. 35 N., R. 4 W.

N. 0° 03' W., bet. secs. 32 and 33.


Over rolling land, through heavy timber.

18.90 Top of spur from ridge, slopes NW.; desc. 35 ft. over NNE. slope.

33.00 Continue descent, desc. 39 ft. over N. slope.

40.00 Point for the ¼ sec. cor. of secs. 32 and 33.

Set an iron post, 30 ins. long, 2½ ins. diam., 20 ins. in the ground, with brass cap mkd.



from which

A pinon, 8 ins. diam., bears N. 6° 15' E., 40 lks. dist., mkd. ¼ S 33 BT.

A juniper, 24 ins. diam., bears S. 69° 42' W., 16 lks. dist., mkd. ¼ S 32 BT.

Continue over rolling land, through heavy timber; desc. 52 ft. over NW. slope..

44.78 Wash, 10 lks. wide, 1½ ft. deep, drains NW.

48.27 Same wash, 25 lks. wide, 4 ft. deep, drains NE.

52.00 Same wash, 20 lks. wide, 6 ft. deep, drains NW.; asc. 46 ft. over S. slope.


62.20 Top of spur from ridge, slopes NW.; desc. 10 ft. over N. slope.

71.60 Wash, 10 lks. wide, 2 ft. deep, drains W.

76.50 Top of low spur from ridge, slopes NW.

80.00 Point for the corner of secs. 28, 29, 32 and 33.

Set an iron post, 30 ins. long, 2½ ins. diam., 20 ins. in the ground, with brass cap mkd.



from which

A juniper, 40 ins. diam., bears N. 47° 40' E., 48 lks. dist., mkd. T36N R4W S 28 BT.

A pinon, 12 ins. diam., bears S. 22° 15' E., 16 lks. dist., mkd. T36N R4W S 33 BT.

A juniper, 14 ins. diam., bears S. 66° 24' W., 8 lks. dist., mkd. T36N R4W S 32 BT.

A juniper, 12 ins. diam., bears N. 22° 26' W., 20 lks. dist., mkd. T36N R4W S 29 BT.

Portion of the Subdivision of T. 36 N., R. 4 W.

Chains

Land, rolling.
Soil, gravelly clay loam.
Timber, juniper and pinon.
Undergrowth, sagebrush, mountain holly and buckbrush.

From the corner of secs. 5, 6, 31 and 32, on the S. bdy. of the Tp., monumented with an iron post, $2\frac{1}{2}$ ins. diam., firmly set, with brass cap marked and witnessed as described in the survey of the N. bdy. of T. 35 N., R. 4 W.

N. $0^{\circ} 03' W.$, bet. secs. 31 and 32.

Over rolling land, through heavy timber; asc. 17 ft. over S. slope.

6.60 Top of ascent; begin descent; desc. 17 ft. over gradual N. slope.

23.17 Wash, 15 lks. wide, 3 ft. deep, drains NE.; continue over nearly level land.

37.07 Road, bears NE. and SW.

40.00 Point for the $\frac{1}{4}$ sec. cor. of secs. 31 and 32.

Set an iron post, 30 ins. long, $2\frac{1}{2}$ ins. diam., 24 ins. in the ground with brass cap mkd.

$$\begin{array}{c} \frac{1}{4} \\ S\ 31 \quad | \quad S\ 32 \end{array}$$

1954

from which

A juniper, 18 ins. diam., bears S. $68^{\circ} 37' E.$, 64 lks. dist., mkd. $\frac{1}{4}$ S 32 BT.

A juniper, 20 ins. diam., bears N. $72^{\circ} 47' W.$, 31 lks. dist., mkd. $\frac{1}{4}$ S 31 BT.

Continue over gently rolling land, through heavy timber.

42.50 Same road, bears NNW. and SSE.^E

45.70 Same road, bears N. $45^{\circ} E.$ and SSW.

57.60 Top of low spur from ridge, slopes NW.; desc. 23 ft. over N. slope.

64.96 Wash, 10 lks. wide, $1\frac{1}{2}$ ft. deep, drains NW.

65.35 Road, bears NW. and SE.

78.97 Top of low spur from ridge, slopes NW.

80.00 Point for the cor. of secs. 29, 30, 31 and 32.

Set an iron post, 30 ins. long, $2\frac{1}{2}$ ins. diam., 18 ins. in the ground to solid rock, and in a mound of stone to top, with brass cap mkd.

$$\begin{array}{c} T\ 36\ N \quad R\ 4\ W \\ S\ 30 \quad | \quad S\ 29 \end{array}$$

$$\begin{array}{c} S\ 31 \quad | \quad S\ 32 \end{array}$$

1954

from which

A pinon, 20 ins. diam., bears N. $25^{\circ} 05' E.$, 25 lks. dist., mkd. T36N R4W S 29 BT.

Portion of the Subdivision of T. 36 N., R. 4 W.

Chains

A pinon, 20 ins. diam., bears S. 32° 57' E., 62 lks. dist., mkd. T36N R4W S 32 BT.

A juniper, 16 ins. diam., bears S. 57° 00' W., 62 lks. dist., mkd. T36N R4W S 31 BT.

A juniper, 10 ins. diam., bears N. 70° 29' W., 157 lks. dist., mkd. T36N R4W S 30 BT.

Land, low and gently rolling.
Soil, gravelly clay loam.
Timber, juniper, and pinon.
Undergrowth, sagebrush.

From the cor. of secs. 28, 29, 32 and 33, monumented with an iron post, 2½ ins. diam., firmly set, marked and witnessed, as hereinbefore described.

S. 89° 58' W., bet. secs. 29 and 32.

Over low rolling land, through heavy timber; desc. 63 ft. over W. slope.

7.82 Wash, 10 lks. wide, 1½ ft. deep, drains WNW.; continue descent, desc. 41 ft. over WSW. slope.

9.61 Same wash, 20 lks. wide, 3 ft. deep, drains SW.

15.09 Same, 30 lks. wide, 5 ft. deep, drains N.; asc. 30 ft. over E. slope.

24.50 Top of ascent, slopes N.; desc. 9 ft. over gradual W. slope.

26.25 Begin ascent, asc. 13 ft. over E. slope.

27.90 Top of ascent, slopes N.; desc. 27 ft. over W. slope.

39.96 Point for the ¼ sec. cor. of secs. 29 and 32.

Set an iron post, 30 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.

¼ S 29
S 32
1954

from which

A pinon, 8 ins. diam., bears S. 7° 10' W., 48 lks. dist., mkd. ¼ S 32 BT.

A pinon, 12 ins. diam., bears N. 6° 03' W., 43 lks. dist., mkd. ¼ S 29 BT.

Continue over nearly level land, through heavy timber.

55.66 Begin descent, desc. 93 ft. over W. slope.

67.74 Wash, 20 lks. wide, 4 ft. deep, drains N. A reservoir located in this wash, bears S., approximately 17 chs. dist.; asc. 128 ft. over E. slope.

79.92 The corner of secs. 29, 30, 31 and 32.

Land, east-half, gently rolling; west-half, rolling.
Soil, sandy and gravelly clay loam.
Timber, juniper and pinon.
Undergrowth, sagebrush.

PLAT 4408

Portion of the Subdivision of T. 36 N., R. 4 W.

Chains	
	S. 89° 57' W., bet. secs. 30 and 31.
	Over gently rolling land, through heavy timber and undergrowth.
7.60	Top of spur from ridge, slopes SW.; desc. 83 ft. over W. slope.
14.80	Wash, 10 lks. wide, 2 ft. deep, drains SW.; asc. 23 ft. over E. slope.
18.18	Top of spur from ridge, slopes SW.; desc. 63 ft. over W. slope.
26.50	Road, bears NW. and SE.
27.49	Wash, 20 lks. wide, 1½ ft. deep, drains N.; asc. 15 ft. over E. slope.
40.00	Point for the ¼ sec. cor. of secs. 30 and 31.
	Set an iron post, 30 ins. long, 2½ ins. diam., 20 ins. in the ground to solid rock, and in a mound of stone to top, with brass cap mkd.
	$\frac{1}{4} \begin{array}{l} \text{S } 30 \\ \text{S } 31 \\ 1954 \end{array}$
	from which
	A juniper, 8 ins. diam., bears N. 16° 30' E., 42 lks. dist., mkd. ¼ S 30 BT.
	A juniper, 10 ins. diam., bears S. 60° 45' W., 54 lks. dist., mkd. ¼ S 31 BT.
	Continue over rolling land, through scattering timber; desc. 34 ft. over W. slope.
45.92	Wash, 20 lks. wide, 2 ft. deep, drains NNW.
47.10	Wash, 20 lks. wide, 2 ft. deep, drains NNE.
57.17	Road, bears NE. and SW.
59.37	Road, bears NE. and SW.
70.00	Begin descent; desc. 23 ft. over W. slope.
78.40	The cor. of secs. 25, 30, 31 and 36.
	Land, gently rolling. Soil, sandy and gravelly clay loam. Timber, juniper and pinon. Undergrowth, sagebrush.

BOOK 4458

T. 36 N., R. 4 W.

GENERAL DESCRIPTION

The general elevation of the township ranges from about 5200 ft. in the west central portion to 5600 ft. in the south central portion and 5700 ft. above sea level in the northeastern portion of T. 36 N., R. 4 W.

The west central and south central portion of the township is low rolling and heavily rolling land. The eastern portion and northern portion of the township is rough mountainous land, bounded on the east by Kanab Creek and on the north by Hack's Canyon.

The soil is mostly sandy and gravelly clay loam. There is a heavy stand of juniper and pinon timber over most of the township, except in small valleys which are covered with a heavy growth of sagebrush.

There are no settlers living within the township, and there is no land under cultivation within the township. There is a stock water dam located in section 32, as this area will normally provide an ample supply of water except during periods of drought. The predominant interest is in stock grazing, and this township provides good winter range during the late fall and winter months.

50
72

BOOK 4458

CERTIFICATE OF CADASTRAL ENGINEER

I, Horace G. Parker, HEREBY CERTIFY upon honor that, in pursuance of special instructions bearing date of the 16th day of August, 1954, I have ~~surveyed~~ resurveyed a portion of the 9th Standard Parallel North through Range 4 West, and surveyed the west boundary and a portion of the subdivision of Township 36 North, Range 4 West

of the G & S R Meridian, in the State of Arizona, which are represented in the foregoing field notes as having been executed by me and under my direction; and that said survey has been made in strict conformity with said instructions, the Manual of Instructions for the Survey of the Public Lands of the United States, and in the specific manner described in the foregoing field notes.

Salt Lake City, Utah
July 27, 1955

Horace G. Parker
Horace G. Parker
Cartographer-Cadastral

CERTIFICATE OF APPROVAL

BUREAU OF LAND MANAGEMENT,
Washington, D. C., OCT 25 1955, 19

The foregoing field notes of the ~~survey of~~ resurvey of the 9th Stan. Par. N. through R. 4 W. and the survey of the west boundary and a portion of the subdivision of Township 36 N., R. 4 W., Gila and Salt River Meridian, Arizona

executed by Horace G. Parker having been critically examined and found correct, are hereby approved.

Earl G. Rowington
Chief, Division of Cadastral Engineering,
Cadastral Engineering Staff Officer

CERTIFICATE OF TRANSCRIPT

~~I CERTIFY that the foregoing transcript of the field notes of the above-described surveys in _____, is a true copy of the original field notes.~~

Chief, Division of Cadastral Engineering