

UNITED STATES
DEPARTMENT OF THE INTERIOR
BUREAU OF LAND MANAGEMENT

Original

FIELD NOTES

of the Survey of

Partial Subdivision

of

Township 37 North, Range 7 West

Of the Gila and Salt River Meridian,

In the State of Arizona

EXECUTED BY

Donald E. Harding-Cadastral Engineer

Under special instructions dated August 16, 1954, which provided
for the surveys included under Group No. 294, approved August 20, 1954
and assignment instructions dated October 4, 1954

Survey commenced November 5, 1954

Survey completed November 5, 1954

4462

4462

4462

BOOK 4462

INDEX DIAGRAM

Township 37 North, Range 7 West

| | | | | | |
|----|----|----|----|-----|-----------|
| 6 | 5 | 4 | 3 | 3 2 | 2 1 |
| | | | | 3 | |
| 7 | 8 | 9 | 10 | 11 | 12 |
| 18 | 17 | 16 | 15 | 14 | 13 |
| 19 | 20 | 21 | 22 | 23 | 24 |
| 30 | 29 | 28 | 27 | 26 | 25 |
| 31 | 32 | 33 | 34 | 35 | 1 1 36 |

Partial Subdivision of T. 37 N., R. 7 W.

Chains

The south boundary was surveyed by T. B. Mathews in 1915. The north and west boundaries were surveyed by J. P. Hester in 1934. The east boundary was surveyed by W. E. Hiester in 1924.

For the test of the instruments and methods used see the notes for T. 40 N., R. 1 W.

The geographic position of the southeast corner of T. 37 N., R. 7 W., is latitude $36^{\circ}33'16''$ N., longitude $113^{\circ}00'00''$ W. The mean magnetic declination is $16^{\circ}00'$ E.

From the cor. of secs. 35 and 36, on the south boundary of the township, properly set and marked as described in the official record.

N. $0^{\circ} 01'$ W., bet. secs. 35 and 36.

Over low, rolling, grassy plains.

15.90 Road, track, bears E. and W.

40.00 Point for the $\frac{1}{4}$ sec. cor. of secs. 35 and 36.

Set an iron post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 18 ins. in the ground, with brass cap mkd.

$\frac{1}{4}$
 S 35 | S 36

1954

Raise a mound of stone, 3 ft. base, $2\frac{1}{2}$ ft. high, W. of cor.

74.00 Wash, 20 lks. wide, 2 ft. deep, course NE.

80.00 Point for the cor. of secs. 25, 26, 35, and 36.

Set an iron post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 8 ins. in the ground, and in a mound of stone to top, with brass cap mkd.

T37NR7W
 S26 | S25
 S35 | S36
 1954

Land, low and rolling.

Soil, sandy loam.

Timber, none.

Undergrowth, very scattered brush and good grass.

From the cor. of secs. 25, 30, 31, and 36, on the east boundary of the township, properly set and marked as described in the official record.

West, bet. secs. 25 and 36.

Desc. over gentle NW. slope.

21.30 Road, track, bears NE. and SW.

Partial Subdivision of T. 37 N., R. 7 W.

| Chains | |
|--|---|
| 31.00 | Wash, 10 lks. wide, 3 ft. deep, course NNE. |
| 40.00 | Point for the $\frac{1}{4}$ sec. cor. of secs. 25 and 36. |
| | Set an iron post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 20 ins. in the ground, with brass cap mkd. |
| | $\frac{1}{4} \frac{S\ 25}{S\ 36}$ 1954 |
| | Raise a mound of stone, $2\frac{1}{2}$ ft. base, 2 ft. high, N. of cor. |
| 59.00 | Road, bears SSE. and NNW. |
| 72.80 | Wash, 20 lks. wide, 3 ft. deep, course NE. |
| 80.00 | The cor. of secs. 25, 26, 35, and 36. |
| | Land, low and rolling. Soil, sandy loam. Timber, none. Undergrowth, very scattered brush and good grass. |
| <hr/> From the cor. of secs. 1, 2, 35, and 36, on the north boundary of the township, properly set and marked as described in the official record. | |
| | S. $0^{\circ} 01'$ E., bet. secs. 1 and 2. |
| | Over grassy plains. |
| 4.80 | Wash, 10 lks. wide, 6 ft. deep, course NNE. |
| 15.40 | Road, track, bears SE. and NW. |
| 40.00 | Point for the $\frac{1}{4}$ sec. cor. of secs. 1 and 2. |
| | Set an iron post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 18 ins. in the ground, with brass cap mkd. |
| | $\frac{1}{4}$ $S\ 2 \quad \quad S\ 1$ 1954 |
| | Raise a mound of stone, 2 ft. base, $1\frac{1}{2}$ ft. high, W. of cor. |
| 80.00 | Point for the cor. of secs. 1, 2, 11 and 12. |
| | Set an iron post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 20 ins. in the ground, with brass cap mkd. |
| | $\begin{array}{c} T37NR7W \\ S2 \quad \quad S1 \\ \hline S11 \quad \quad S12 \\ \hline 1954 \end{array}$ |
| | Raise a mound of stone, 2 ft. base, $1\frac{1}{2}$ ft. high, W. of cor. |
| | Land, flats. Soil, sandy loam. Timber, none. Undergrowth, good grass. |

Partial Subdivision of T. 37 N., R. 7 W.

Chains

From the cor. of secs. 2, 3, 34, and 35, on the north boundary of the township, properly set and marked as described in the official record.

S. 0° 01' E., bet. secs. 2 and 3.

40.00

Point for the $\frac{1}{4}$ sec. cor. of secs. 2 and 3.

Set an iron post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 20 ins. in the ground, with brass cap mkd.

 $\frac{1}{4}$

S 3 | S 2

1954

Deposit sandstone, 4x3x1 ins., marked with an "X" at the base of the post, for witness.

80.00

Point for the cor. of secs. 2, 3, 10, and 11.

Set an iron post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 20 ins. in the ground, with brass cap mkd.

T37NR7W

S 3 | S 2

S10 | S11

1954

Deposit sandstone, 4x4x2 ins., marked with an "X" at the base of the post, for witness.

Land, flats.

Soil, sandy loam.

Timber, none.

Undergrowth, good grass.

From the cor. of secs. 1, 2, 11, and 12.

N. 89° 57' W., bet. secs. 2 and 11.

Over grassy plains.

40.01

Point for the $\frac{1}{4}$ sec. cor. of secs. 2 and 11.

Set an iron post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 20 ins. in the ground, with brass cap mkd.

 $\frac{1}{4}$

S 2

S 11

1954

Deposit sandstone, 5x4x2 ins., marked with an "X" at the base of the post, for witness.

80.02

The cor. of secs. 2, 3, 10, and 11.

Land, flats.

Soil, sandy loam.

Timber, none.

Undergrowth, good grass.

Partial Subdivision of T. 37 N., R. 7 W.

General Description

T. 37 N., R. 7 W., is ideal grazing land. There is very little brush in this township. It has good grass. Water is available from man made tanks. The major portion of the township is almost flat. There is no one living within the boundaries of the township. There is no timber. The land is not suitable for farming due to the small amount of rainfall.

CERTIFICATE OF CADASTRAL ENGINEER

I, Donald E. Harding, HEREBY CERTIFY upon honor that, in pursuance of special instructions bearing date of the 16th day of August, 1954

I have surveyed part of the subdivision of T. 37 N., R. 7 W.

of the G. & S. R. Meridian, in the State of Arizona, which are represented in the foregoing field notes as having been executed by me and under my direction; and that said survey has been made in strict conformity with said instructions, the Manual of Instructions for the Survey of the Public Lands of the United States, and in the specific manner described in the foregoing field notes.

June 6, 1955

Donald E. Harding
 Donald E. Harding
 Cartographer - Cadastral

CERTIFICATE OF APPROVAL

BUREAU OF LAND MANAGEMENT,

Washington, D. C., OCT 25 1955, 19

The foregoing field notes of the survey of part of the subdivision of T. 37 N., R. 7 W.,
G. & S. R. Meridian or Arizona.

executed by Donald E. Harding

having been critically examined and found correct, are hereby approved.

Earl G. Harrington
 Chief, Division of Cadastral Engineering
 Cadastral Engineering Staff Officer

CERTIFICATE OF TRANSCRIPT

I CERTIFY that the foregoing transcript of the field notes of the above-described surveys in _____, is a true copy of the original field notes.

Chief, Division of Cadastral Engineering