

UNITED STATES  
DEPARTMENT OF THE INTERIOR  
BUREAU OF LAND MANAGEMENT

Original

# FIELD NOTES

of the Survey of

North Boundary

and

Partial Subdivision

of

Township 38 North, Range 7 West

Of the Gila and Salt River Meridian,

In the State of Arizona

### EXECUTED BY

Donald E. Harding-Cadastral Engineer

Under special instructions dated August 16, 19 54, which provided  
for the surveys included under Group No. 294, approved August 20, 1954  
and assignment instructions dated October 4, 19 54

Survey commenced November 16, 19 54

Survey completed November 17, 19 54

4484

4484

4484

14

BOOK 4464

# INDEX DIAGRAM

Township 38 North, Range 7 West

5	4	4	3	2	1
6	5	4	3	2	1
7	8	9	10	11	12
18	17	16	15	14	13
19	20	21	22	23	24
30	29	28	27	26	25
31	32	33	34	35	6 7 36

North Boundary of T. 38 N., R. 7 W.

Chains

The south boundary was surveyed by J. P. Hester in 1934. The east boundary was surveyed by Hester and Hunter in 1924. The west boundary was surveyed by B. J. Kinsey in 1937.

For the test of the instruments and methods used see the notes for T. 40 N., R. 1 W.

The geographic position of the southeast corner of T. 38 N., R. 7 W., is latitude 36°38'31" N., longitude 113°00'00" W. The mean magnetic declination is 16.00° E.

Survey of the north boundary of T. 38 N., R. 7 W., and the establishment of the corners for T. 39 N., R. 7 W., at regular intervals west of the corner of Ts. 39 N., Rs. 6 and 7 W.

From the closing cor. of Ts. 38 N., Rs. 6 and 7 W., which is properly set and marked as described in the official record.

N. 89°48' W., on the north boundary of sec. 1.

Over grassy plains, through scattered sagebrush.

3.32 The cor. of Ts. 39 N., Rs. 6 and 7 W., monumented with an iron post, 3 ins. in diam., properly set and marked as described in the official record.

5.20 Small wash, course SW.

40.00 Point for the 1/4 sec. cor. of sec. 1.

Set an iron post, 28 ins. long, 2 1/2 ins. diam., 20 ins. in the ground, with brass cap mkd.

1/4 S 1

1954

Deposit broken glass alongside the iron post, for witness.

43.32 Point for the 1/4 sec. cor. of sec. 36.

Set an iron post, 28 ins. long, 2 1/2 ins. diam., 20 ins. in the ground, with brass cap mkd.

1/4 S 36

1954

Deposit broken glass alongside the iron post, for witness.

80.00 Point for the cor. of secs. 1 and 2.

Set an iron post, 28 ins. long, 2 1/2 ins. diam., 20 ins. in the ground, with brass cap mkd.

T39N  
S36  
S 2 | S 1  
T38NR7W  
1954

Deposit broken glass alongside the iron post, for witness.

## North Boundary of T. 38 N., R. 7 W.

Chains	
	<p>Land, plains. Soil, sandy loam. Timber, none. Undergrowth, sagebrush and good grass.</p>
	<p>N. 89° 48' W., on the north boundary of sec. 2. Over grassy plains, through scattered sagebrush.</p>
3.32	<p>Point for the cor. of secs. 35 and 36. Set an iron post, 28 ins. long, 2½ ins. diam., 20 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T39NR7W S35 S36 — S2 T38N 1954</p> <p>Deposit broken glass alongside the iron post, for witness.</p>
38.60	Road, graded, dirt, bears ESE. and WNW.
40.00	<p>Point for the ¼ sec. cor. of sec. 2. Set an iron post, 28 ins. long, 2½ ins. diam., 20 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">¼ S 2 1954</p> <p>Deposit broken glass alongside the iron post, for witness.</p>
43.32	<p>Point for the ¼ sec. cor. of sec. 35. Set an iron post, 28 ins. long, 2½ ins. diam., 20 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">¼ S 35 1954</p> <p>Deposit broken glass alongside the iron post, for witness.</p>
79.00	Small wash, course N.
80.00	<p>Point for the cor. of secs. 2 and 3. Set an iron post, 28 ins. long, 2½ ins. diam., 20 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T39N S35 — S3 S2 T38NR7W 1954</p> <p>Deposit broken glass alongside the iron post, for witness.</p> <p>Land, plains. Soil, sandy loam. Timber, none. Undergrowth, sagebrush and good grass.</p>

North Boundary of T. 38 N., R. 7 W.

Chains

N. 89° 48' W., on the north boundary of sec. 3.

Over grassy plains, through scattered sagebrush.

3.32 Point for the cor. of secs. 34 and 35.

Set an iron post, 28 ins. long, 2 1/2 ins. diam., 20 ins. in the ground, with brass cap mkd.

T39NR7W  
S34 | S35  
S3  
T38N  
1954

Deposit broken glass alongside the iron post, for witness.

40.00 Point for the 1/4 sec. cor. of sec. 3.

Set an iron post, 28 ins. long, 2 1/2 ins. diam., 20 ins. in the ground, with brass cap mkd.

1/4 S 3  
1954

Deposit broken glass alongside the iron post, for witness.

43.32 Point for the 1/4 sec. cor. of sec. 34.

Set an iron post, 28 ins. long, 2 1/2 ins. diam., 20 ins. in the ground, with brass cap mkd.

1/4 S 34  
1954

Deposit broken glass alongside the iron post, for witness.

80.00 Point for the cor. of secs. 3 and 4.

Set an iron post, 28 ins. long, 2 1/2 ins. diam., 20 ins. in the ground, with brass cap mkd.

T39N  
S34  
S 4 | S 3  
T38NR7W  
1954

Deposit broken glass alongside the iron post, for witness.

Land, plains.  
Soil, sandy loam.  
Timber, none.  
Undergrowth, sagebrush and good grass.

N. 89° 48' W., on the north boundary of sec. 4.

Over grassy plains, through sagebrush.

3.32 Point for the cor. of secs. 33 and 34.

## North Boundary of T. 38 N., R. 7 W.

## Chains

Set an iron post, 28 ins. long,  $2\frac{1}{2}$  ins. diam., 20 ins. in the ground, with brass cap mkd.

T39NR7W  
S33 | S34  
S4  
T38N  
1954

Deposit broken glass alongside the iron post, for witness.

10.00 Wash, 20 lks. wide, 7 ft. deep, course SSW.

15.00 Small wash, course SSW.

40.00 Point for the  $\frac{1}{4}$  sec. cor. of sec. 4.

Set an iron post, 28 ins. long,  $2\frac{1}{2}$  ins. diam., 20 ins. in the ground, with brass cap mkd.

$\frac{1}{4}$  S 4  
1954

Deposit broken glass alongside the iron post, for witness.

43.32 Point for the  $\frac{1}{4}$  sec. cor. of sec. 33.

Set an iron post, 28 ins. long,  $2\frac{1}{2}$  ins. diam., 20 ins. in the ground, with brass cap mkd.

$\frac{1}{4}$  S 33  
1954

Deposit broken glass alongside the iron post, for witness.

53.50 Road, track, bears ENE. and WSW.

80.00 Point for the cor. of secs. 4 and 5.

Set an iron post, 28 ins. long,  $2\frac{1}{2}$  ins. diam., 20 ins. in the ground, with brass cap mkd.

T39N  
S33  
S5 | S4  
T38NR7W  
1954

Deposit broken glass alongside the iron post, for witness.

Land, plains.  
Soil, sandy loam.  
Timber, none.  
Undergrowth, sagebrush and good grass.

3.32 Point for the cor. of secs. 32 and 33.

Set an iron post, 28 ins. long,  $2\frac{1}{2}$  ins. diam., 20 ins. in the ground, with brass cap mkd.

N. 89° 48' W., on the north boundary of sec. 5.

Over grassy plains, through scattered sagebrush.

## North Boundary of T. 38 N., R. 7 W.

## Chains

T39NR7W

S32 | S33

S5

T38N

1954

Deposit broken glass alongside the iron post, for witness.

12.60 Wash, 10 lks. wide, 6 ft. deep, course S.

12.80 Road, track, bears NNE. and SSW.

16.60 Road, track, bears NNE. and SSW.

28.10 Road, graded, dirt, bears N. and S.

40.00 Point for the  $\frac{1}{4}$  sec. cor. of sec. 5.Set an iron post, 28 ins. long,  $2\frac{1}{2}$  ins. diam., 20 ins. in the ground, with brass cap mkd. $\frac{1}{4}$  S 5

1954

Deposit broken glass alongside the iron post, for witness.

43.32 Point for the  $\frac{1}{4}$  sec. cor. of sec. 32.Set an iron post, 28 ins. long,  $2\frac{1}{2}$  ins. diam., 20 ins. in the ground, with brass cap mkd. $\frac{1}{4}$  S 32

1954

Deposit broken glass alongside, the iron post, for witness.

62.10 Road, track, bears SE. and NW.

80.00 Point for the cor. of secs. 5 and 6.

Set an iron post, 28 ins. long,  $2\frac{1}{2}$  ins. diam., 20 ins. in the ground, with brass cap mkd.

T39N

S32S 6 | S 5

T38NR7W

1954

Deposit broken glass alongside the iron post, for witness.

Land, plains.

Soil, sandy loam.

Timber, none.

Undergrowth, sagebrush and good grass.

N. 89° 48' W., on the north boundary of sec. 6.

Over grassy plains, through scattered sagebrush.

## North Boundary of T. 38 N., R. 7 W.

## Chains

- 3.32 Point for the cor. of secs. 31 and 32.  
Set an iron post, 28 ins. long,  $2\frac{1}{2}$  ins. diam., 20 ins. in the ground, with brass cap mkd.
- T39NR7W  
S31|S32  
S6  
T38N  
1954
- Deposit broken glass alongside the iron post, for witness.
- 18.70 Wash, 30 lks. wide, 10 ft. deep, course SW.
- 26.90 Wash, 40 lks. wide, 20 ft. deep, course SE.
- 40.00 Point for the  $\frac{1}{4}$  sec. cor. of sec. 6.  
Set an iron post, 28 ins. long,  $2\frac{1}{2}$  ins. diam., 20 ins. in the ground, with brass cap mkd.
- $\frac{1}{4}$  S 6  
1954
- Deposit broken glass alongside the iron post, for witness.
- 43.32 Point for the  $\frac{1}{4}$  sec. cor. of sec. 31.  
Set an iron post, 28 ins. long,  $2\frac{1}{2}$  ins. diam., 20 ins. in the ground, with brass cap mkd.
- $\frac{1}{4}$  S 31  
1954
- Deposit broken glass alongside the iron post, for witness.
- 53.60 Wash, 20 lks. wide, 5 ft. deep, course NNE.
- 79.54 The cor. of Ts. 38 and 39 N., Rs. 7 and 8 W., monumented with an iron post, properly set and marked as described in the official record.
- Land, plains.  
Soil, sandy loam.  
Timber, none.  
Undergrowth, sagebrush and good grass.

## Partial Subdivision of T. 38 N., R. 7 W.

- From the cor. of secs. 1, 2, 35, and 36, on the south boundary of the township, properly set and marked as described in the official record.
- N. 0° 01' W., bet. secs. 35 and 36.
- Over grassy plains, through scattered sagebrush.
- 4.80 Wash, 50 lks. wide, 8 ft. deep, course NW.

## Partial Subdivision of T. 38 N., R. 7 W.

## Chains

- 12.80 Wash, 20 lks. wide, 6 ft. deep, course W.  
 15.50 Small wash, course W.  
 40.00 Point for the  $\frac{1}{4}$  sec. cor. of secs. 35 and 36.  
 Set an iron post, 28 ins. long,  $2\frac{1}{2}$  ins. diam., 20 ins. in the ground, with brass cap mkd.

 $\frac{1}{4}$ 

35 | S 36

1954

- Deposit a sandstone, 5x4x2 ins., marked with an "X" at the base of the post, for witness.  
 68.90 Wash, 10 lks. wide, 4 ft. deep, course W.  
 78.90 Road, track, bears ESE. and WNW.  
 80.00 Point for the cor. of secs. 25, 26, 35, and 36.

Set an iron post, 28 ins. long,  $2\frac{1}{2}$  ins. diam., 20 ins. in the ground, with brass cap mkd.

T38NR7W

S26 | S25

S35 | S36

1954

Deposit a sandstone, 4x3x1 ins., marked with an "X" at the base of the post, for witness.

Land, plains.  
 Soil, sandy loam.  
 Timber, none.  
 Undergrowth, sagebrush and good grass.

From the cor. of secs. 25, 30, 31, and 32, on the east boundary of the township, set and marked as described in the official record.

S. 89° 56' W., bet. secs. 25 and 36.

Over grassy plains, through scattered sagebrush.

- 40.05 Point for the  $\frac{1}{4}$  sec. cor. of secs. 25 and 36.  
 Set an iron post, 28 ins. long,  $2\frac{1}{2}$  ins. diam., 20 ins. in the ground, with brass cap mkd.

S 25

 $\frac{1}{4}$  ———

S 36

1954

Deposit a sandstone, 5x4x3 ins., mkd. with an "X" at the base of the post, for witness.

- 40.20 Small wash, course NNW.  
 58.50 Road, tract, bears NE. and SW.  
 72.80 Wash, 10 lks. wide, 4 ft. deep, course NW.

Partial Subdivision of T. 38 N., R. 7 W.

Chains

79.50

Road, track, bears ESE. and WNW.

80.10

The cor. of secs. 25, 26, 35, and 36.

Land, plains.

Soil, sandy loam.

Timber, none.

Undergrowth, sagebrush and good grass.

General Description

T. 38 N., R. 7 W., is ideal grazing land. The brush is very scattering. It has good grass. Water is available from man made tanks. The entire township is almost flat. There is no one living within the boundary of the township. Land is not suited for farming due to the small rainfall. No timber within the boundary of this township.



