

4477  
index ✓

UNITED STATES  
DEPARTMENT OF THE INTERIOR  
BUREAU OF LAND MANAGEMENT

Original

FIELD NOTES

of the

Survey of Section 32,

Township 3 North, Range 8 West

Of the Gila and Salt River Meridian,

In the State of Arizona

EXECUTED BY

Paul K. Russell, Cartographic Survey Aid

Under special instructions dated December 13, 1954, which provided  
for the surveys included under Group No. 300, approved December 13, 1954  
and assignment instructions dated December 28, 1954

Survey commenced January 24, 1955

Survey completed January 25, 1955

4477

4477

4477

BOOK 4477

# INDEX DIAGRAM

Township 3 North, Range 8 West

6	5	4	3	2	1
7	8	9	10	11	12
18	17	16	15	14	13
19	20	21	22	23	24
30	29	28	27	26	25
31	2 2 32	1 33	34	35	36

Survey of Section 32, Township 3 North, Range 8 West

Chains

The south boundary of this township was surveyed by J. B. Wright in 1914, the east boundary by R. J. Gill in 1916, and the north and west boundaries by G. F. Sawyer in 1925.

The following field notes are those of a portion of the subdivisional lines of T. 3 N., R. 8 W.

For the test of the instruments and methods used, see the notes for T. 2 S., R. 6 W. of this group.


The geographic position of the SE. corner of this township is latitude  $33^{\circ} 33' 00''$  N., longitude  $113^{\circ} 01' 25''$  W. The mean magnetic declination is  $14^{\circ} 45'$  E.

Beginning at the cor. of secs. 4, 5, 32 and 33, on the south boundary of the township, a 3 in. iron post, set, marked and witnessed as described in the official record.

N.  $0^{\circ} 02'$  W., bet. secs. 32 and 33.

Over rolling hills, through scattering palo verde and cacti.


- 6.50 Rocky wash, course NW.
  - 25.10 Small wash, course W.
  - 30.90 Rocky wash, course SW.
  - 33.20 Rocky wash, course SW.
  - 36.80 Old road, bears NE. and SW.
  - 40.00 Point for the  $\frac{1}{4}$  sec. cor. of secs. 32 and 33.
- Set an iron post, 30 ins. long,  $2\frac{1}{2}$  ins. diam., 24 ins. in the ground, with brass cap mkd.



raise a mound of stone, 3 ft. base, 3 ft. high, W. of corner.

- 47.70 Rocky wash, course SW.
- 49.50 Rocky wash, 70 lks. wide, 4 ft. deep, course SW.
- 60.10 Rocky wash, 50 lks. wide, 3 ft. deep, course SW.
- 61.90 Fence, bears E. and W.
- 68.00 Rocky wash, course SW.
- 80.00 Point for the cor. of secs. 28, 29, 32 and 33.

Set an iron post, 30 ins. long,  $2\frac{1}{2}$  ins. diam., 16 ins. in the ground, and in a mound of stone to top, with brass cap mkd.



Land, rolling.  
Soil, rocky.  
Timber, none; undergrowth, cacti and scattering palo verde.

## BOOK 4477

## Survey of a Portion of the Subdivisional Lines of T. 3 N., R. 8 W.

Chains	From the cor. of secs. 5, 6, 31 and 32, on the south boundary of the township, a 3 in. iron post, set and marked as described in the official record.
	N. 0° 03' W., bet. secs. 31 and 32.
	Over level land, through scattering palo verde and cacti.
15.20	Small wash, course W.
17.60	Rocky wash, course SW.
25.80	Rocky wash, course W.
32.50	Small wash, course W.
40.00	Point for the $\frac{1}{4}$ sec. cor. of secs. 31 and 32.
	Set an iron post, 30 ins. long, $2\frac{1}{2}$ ins. diam., 22 ins. in the ground, with brass cap mkd.
	$\frac{1}{4}$ S31   S32 1955
	raise a mound of stone, 3 ft. base, 3 ft. high, W. of corner.
41.50	Small wash, course SW.
53.90	Small wash, course SW.
60.00	Small wash, course SW.
67.00	Small wash, course SW.
78.70	Small wash, course W.
80.00	Point for the cor. of secs. 29, 30, 31 and 32.
	Set an iron post, 30 ins. long, $2\frac{1}{2}$ ins. diam., 20 ins. in the ground, with brass cap mkd.
	T3NR8W S30   S29 S31   S32 1955
	raise a mound of stone, 3 ft. base, 3 ft. high, W. of corner.
	Land, level.
	Soil, rocky.
	Timber, none; undergrowth, cacti and scattering palo verde.
	From the cor. of secs. 28, 29, 32 and 33, hereinbefore described.
	N. 89° 55' W., bet. secs. 29 and 32.
	Over rolling rocky land, through scattering palo verde and cacti.
6.50	Rocky wash, course S.
10.10	Rocky wash, course S.
16.50	Rocky wash, course S.
27.00	Rocky wash, course S.
31.00	Rocky wash, course S.

## Survey of a Portion of the Subdivisional Lines of T. 3 N., R. 8 W.

## Chains

36.30 Rocky wash, course SE.

40.075 Point for the  $\frac{1}{4}$  sec. cor. of secs. 29 and 32.Set an iron post, 30 ins. long,  $2\frac{1}{2}$  ins. diam., 22 ins. in the ground, with brass cap mkd. $\frac{1}{4}$   $\frac{S29}{S32}$ 

1955

raise a mound of stone, 3 ft. base,  $2\frac{1}{2}$  ft. high, N. of corner.

49.90 Small wash, course S.

52.70 Fence, bears N.  $10^\circ$  W. and S.  $10^\circ$  E.76.30 Wash, course S.  $80^\circ$  W.

80.15 The corner of secs. 29, 30, 31 and 32.

Land, rolling.

Soil, rocky.

Timber, none; undergrowth, cacti and scattering palo verde.

## General Description

Section 32 of this township consists of low rolling land with fairly rocky soil. There is no timber, but some undergrowth and sparse grass. Slight rainfall makes it very poor for grazing.

UNITED STATES  
DEPARTMENT OF THE INTERIOR  
BUREAU OF LAND MANAGEMENT

BOOK 4477

FIELD ASSISTANTS

NAMES	CAPACITY
Kenneth D. Witt	Principal Assistant
Andrew M. Nelson	Cornerman
Jacob J. Cook	Note-keeper
John R. Koger	Chainman
Norman S. Christensen	Flagman
Boyd S. Owens	Axeman

