

UNITED STATES
DEPARTMENT OF THE INTERIOR
BUREAU OF LAND MANAGEMENT

Original

FIELD NOTES

of

the survey

of

the North, East and West, Boundaries

and

the subdivision

of

Township 8 North, Range 18 West.

Of the Gila and Salt River Meridian,

In the State of Arizona

EXECUTED BY

Donald E. Harding-Cadastral Engineer

Under special instructions dated October 9, 1952, which provided
for the surveys included under Group No. 285, approved Oct. 21, 1952
and assignment instructions dated Feb. 2, 1953

Survey commenced Dec. 8, 1953

Survey completed Jan. 28, 1954

4491

4491

BOOK 449L

INDEX DIAGRAM

Township 8 N., Range 18 W.

3		3		2		2		1		1	
	41		40		33		27		22		16
10	6	40	5	32	4	27	3	21	2	15	1 7
	39		39		32		26		21		15
10	7	38	8	31	9	26	10	20	11	15	12 6
	38		38		31		25		20		14
9	18	37	17	30	16	25	15	19	14	14	13 6
	37		36		30		25		19		13
9	19	36	20	30	21	24	22	18	23	13	24 5
	35		35		29		24		18		12
8	30	35	29	29	28	23	27	17	26	12	25 5
	34		34		28		23		17		12
7	31	33	32	28	33	22	34	16	35	11	36 4

Chains

The survey of T. 8 N., R. 18 W., was provided for under special instructions for Group 285, Arizona. The south boundary was surveyed by Ty White and D. E. Harding in 1953. For the test of the instruments and chains see the notes for T. 8 N., R. 17 W. The geographic position of the southeast corner of T. 8 N., R. 18 W. is Latitude $33^{\circ}59'04''$ N. and Longitude $114^{\circ}04'46''$ W. The magnetic declination is $14\frac{1}{2}^{\circ}$ E.

2nd Standard Parallel North, Through R. 18 W.

From the standard township corner of T. 9 N., Rs. 17 and 18 W., West, establishing the Second Standard Parallel North, along the south boundary of sec. 36, T. 9 N., R. 18 W., on a transit line describing the tangent.

Over low rolling sand dunes and ridges.

40.00 Point for the standard $\frac{1}{4}$ sec. cor. of sec. 36, on the parallel.

Set an iron post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 24 ins. in the ground, with brass cap mkd.

S C
 $\frac{1}{4}$ S 36

1954

deposit broken glass alongside the iron post, for witness.

80.00 Point for the standard cor. of secs. 35 and 36, N. 1 lk. from the tangent.

Set an iron post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 24 ins. in the ground, with brass cap mkd.

S C
T 9 N R 18 W
S 35 | S 36

1954

deposit broken glass alongside the iron post, for witness.

Land, low rolling sand dunes and ridges.

Soil, sandy clay.

Timber, none; underbrush, ocotillo and cacti.

West, continuing the tangent on the south boundary of sec. 35, which bears S. $89^{\circ}58.8'$ W.

Over low rolling sand dunes and ridges.

40.00 Point for the standard $\frac{1}{4}$ sec. cor. of sec. 35, N. 2 lks. from the tangent.

Set an iron post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 24 ins. in the ground, with brass cap mkd.

S C
 $\frac{1}{4}$ S 35

1954

deposit broken glass alongside the iron post, for witness.

80.00 Point for the standard cor. of secs. 34 and 35, N. 3 lks. from the tangent.

2nd Standard Parallel North, Through R. 18 W.

Chains

Set an iron post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 24 ins. in the ground, with brass cap mkd.

S C

T 9 N R 18 W

S 34 | S 35

1954

deposit broken glass alongside the iron post, for witness.

Land, low rolling sand dunes and ridges.

Soil, sandy clay.

Timber, none; underbrush, ocotillo and cacti.

West, continuing the tangent on the S. bdy. of sec. 34, which bears S. $89^{\circ}58.2'$ W.

Over low rolling sand dunes and ridges.

40.00

Point for the standard $\frac{1}{4}$ sec. cor. of sec. 34, N. 4 lks. from the tangent.

Set an iron post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 24 ins. in the ground, with brass cap mkd.

S C

 $\frac{1}{4}$ S 34

1954

deposit broken glass alongside the iron post, for witness.

80.00

Point for the standard cor. of secs. 33 and 34, N. 6 lks. from the tangent.

Set an iron post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 24 ins. in the ground, with brass cap mkd.

S C

T 9 N R 18 W

S 33 | S 34

1954

deposit broken glass alongside the iron post, for witness.

Land, low rolling sand dunes and ridges.

Soil, sandy clay.

Timber, none; underbrush, ocotillo and cacti.

West, continuing the tangent on the S. bdy. of sec. 33, which bears S. $89^{\circ}57.7'$ W.

Over low rolling sand dunes and ridges.

40.00

Point for the standard $\frac{1}{4}$ sec. cor. of sec. 33, N. 8 lks. from the tangent.

Set an iron post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 24 ins. in the ground, with brass cap mkd.

S C

 $\frac{1}{4}$ S 33

1954

deposit broken glass alongside the iron post, for witness.

80.00

Point for the standard cor. of secs. 32 and 33, N. 11 lks. from the tangent.

2nd Standard Parallel North, through R. 18 W.

Chains

Set an iron post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.

S C
T 9 N R 18 W
S 32 | S 33

1954

deposit broken glass alongside the iron post, for witness.

Land, low rolling sand dunes and ridges.

Soil, sandy clay.

Timber, none; underbrush, ocotillo and cacti.

West, continuing the tangent on the S. bdy. of sec. 32, which bears S. 89°57.1' W.

Over low rolling sand dunes and ridges.

40.00 Point for the standard ¼ sec. cor. of sec. 32, N. 14 lks. from the tangent.

Set an iron post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.

S C
¼ S 32

1954

depsit broken glass alongside the iron post, for witness.

80.00 Point for the standard cor. of secs. 31 and 32, N. 17 lks. from the tangent.

Set an iron post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.

S C
T 9 N R 18 W
S 31 | S 32

1954

deposit broken glass alongside the iron post, for witness.

Land, low rolling sand dunes and ridges.

Soil, sandy clay.

Timber, none; underbrush, ocotillo and cacti.

West, continuing the tangent on the S. bdy. of sec. 31, which bears S. 89°56.5' W.

Over low rolling sand dunes and ridges.

40.00 Point for the standard ¼ sec. cor. of sec. 31, N. 21 lks. from the tangent.

Set an iron post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.

S C
¼ S 31

1954

deposit broken glass alongside the iron post, for witness.

2nd Standard Parallel North, through R. 18 W.

Chains
80.00

Point for the standard cor. of Ts. 9 N., Rs. 18 and 19 W., N. 25 lks. from the tangent.

Set an iron post, 3 ft. long, 3 ins. diam., 26 ins. in the ground, with brass cap mkd.

S C	
T 9 N	
R 19 W	R 18 W
S 36	S 31

1954

Bury a stone, 2 x 3 x 7 ins., mkd. X, alongside the iron post.

Land, low rolling sand dunes and ridges.

Soil, sandy clay.

Timber, none; underbrush, ocotillo and cacti.

East Boundary of T. 8 N., R. 18 W.

From the cor. of Ts. 7 and 8 N., Rs. 17 and 18 W., set and mkd., as described in the official record.

North, bet. secs. 31 and 36.

Over low rolling sand dunes.

14.00 South bank of Bouse Wash, bears N. 80° W. and S. 80° E.

15.00 Wash, 2 chs. wide, 5 ft. deep, course W.

16.00 North bank of Bouse Wash, bears N. 80° W. and S. 80° E.

25.90 State road No. 72, Bouse to Parker, bears E. and W.

26.17 Power line, bears E. and W.

26.63 Telephone line, bears E. and W.

27.93 A. T. & S. F. Railroad, bears E. and W.

40.00 Point for the $\frac{1}{4}$ sec. cor. of secs. 31 and 36.

Set an iron post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.

$\frac{1}{4}$	
S 36	S 31
1954	

deposit broken glass alongside the iron post, for witness.

80.00 Point for the cor. of secs. 25, 30, 31 and 36.

Set an iron post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.

T 8 N	
R 18 W	R 17 W
S 25	S 30
S 36	S 31

1953

deposit broken glass alongside the iron post, for witness.

Land, low rolling sand dunes.

Soil, sandy clay.

Timber, none; underbrush, ocotillo and cacti.

East Boundary, of T. 8 N., R. 18 W.

Chains North, bet. secs. 25 and 30.
Over low rolling sand dunes.

40.00 Point for the $\frac{1}{4}$ sec. cor. of secs. 25 and 30.
Set an iron post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 24 ins. in the ground, with brass cap mkd.

	$\frac{1}{4}$	
S 25		S 30
1953		

deposit broken glass alongside the iron post, for witness.

80.00 Point for the cor. of secs. 19, 24, 25 and 30.
Set an iron post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 24 ins. in the ground, with brass cap mkd.

T 8 N		
R 18 W	R 17 W	
S 24		S 19
S 25		S 30

1953

deposit broken glass alongside the iron post, for witness.

Land, low rolling sand dunes and ridges.
Soil, sandy clay.
Timber, none; underbrush, ocotillo and cacti.

North, bet. secs. 19 and 24.
Over low rolling sand dunes.

39.50 Wash, 30 lks. wide, 1 ft. deep, course W.

40.00 Point for the $\frac{1}{4}$ sec. cor. of secs. 19 and 24.
Set an iron post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 24 ins. in the ground, with brass cap mkd.

	$\frac{1}{4}$	
S 24		S 19
1953		

deposit broken glass alongside the iron post, for witness.

80.00 Point for the cor. of secs. 13, 18, 19 and 24.
Set an iron post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 24 ins. in the ground, with brass cap mkd.

T 8 N		
R 18 W	R 17 W	
S 13		S 18
S 24		S 19

1953

deposit broken glass alongside the iron post, for witness.

East Boundary of T. 8 N., R. 18 W.

Chains

Land, low rolling sand dunes and ridges.
Soil, sandy clay.
Timber, none; underbrush, ocotillo and cacti.


North, bet. secs. 13 and 18.

Over low rolling sand dunes.

6.90 Wash, 10 lks. wide, 2 ft. deep, course SW.

40.00 Point for the 1/4 sec. cor. of secs. 13 and 18.


Set an iron post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.



deposit broken glass alongside the iron post, for witness.

80.00 Point for the cor. of secs. 7, 12, 13 and 18.

Set an iron post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.



deposit broken glass alongside the iron post, for witness.

Land, low rolling sand dunes.
Soil, sandy clay.
Timber, none; underbrush, ocotillo and cacti.

North, bet. secs. 7 and 12.

Over low rolling sand dunes.

40.00 Point for the 1/4 sec. cor. of secs. 7 and 12.


Set an iron post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.



deposit broken glass alongside the iron post, for witness.

80.00 Point for the cor. of secs. 1, 6, 7 and 12.

Set an iron post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.



East Boundary of T. 8 N., R. 18 W.

Chains

deposit broken glass alongside the iron post, for witness.

Land, low rolling sand dunes.

Soil, sandy clay.

Timber, none; underbrush, ocotillo and cacti.

North, bet. secs. 1 and 6.

Over low rolling sand dunes.

40.00

Point for the $\frac{1}{4}$ sec. cor. of secs. 1 and 6.Set an iron post, 28 ins. long, 2 $\frac{1}{2}$ ins. diam., 24 ins. in the ground, with brass cap mkd.
$$\begin{array}{c} \frac{1}{4} \\ S 1 | S 6 \\ 1953 \end{array}$$

deposit broken glass alongside the iron post, for witness.

69.10

Intersect the Second Standard Parallel North.

Point for the closing cor. of T. 8 N., Rs. 17 and 18 W.

Set an iron post, 28 ins. long, 2 $\frac{1}{2}$ ins. diam., 24 ins. in the ground, with brass cap mkd.
$$\begin{array}{c} T 9 N \quad R 17 W \\ S 31 \\ \hline S 1 \quad | \quad S 6 \\ C C \\ R 18 W \quad | \quad R 17 W \\ T 8 N \\ 1954 \end{array}$$

deposit broken glass alongside the iron post, for witness.

From point of intersection the standard cor. of T. 9 N., Rs. 17 and 18 W., bears W., 1.40 chs. dist.

Land, low rolling sand dunes and ridges.

Soil, sandy clay.

Timber, none; underbrush, ocotillo and cacti.

West Boundary of T. 8 N., R. 18 W.

From the cor. of Ts. 7 and 8 N., Rs. 18 and 19 W., marked and witnessed as described in the official record.

North, bet. secs. 31 and 36.

Over low rolling sand dunes.

29.60


Bouse wash, 2 chs. wide, 4 ft. deep, course S. 70° W.

40.00

Point for the $\frac{1}{4}$ sec. cor. of secs. 31 and 36.Set an iron post, 28 ins. long, 2 $\frac{1}{2}$ ins. diam., 24 ins. in the ground, with brass cap mkd.

West Boundary of T. 8 N., R. 18 W.

Chains



deposit broken glass alongside the iron post, for witness.

43.10 Bouse wash, 1 ch. wide, 4 ft. deep, course S 70° W.

52.10 State road No. 72, Bouse to Parker, bears E. and W.


53.70 Power line, bears E. and W.

62.40 Telephone line, bears E. and W.

63.00 A. T. & S. F. Railroad, bears E. and W.

80.00 Point for the cor. of secs. 25, 30, 31 and 36.

Set an iron post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.



deposit broken glass alongside the iron post, for witness.

Land, low rolling sand dunes.

Soil, sandy clay.


Timber, none; underbrush, ocotillo and cacti.

North, bet. secs. 25 and 30.

Over low rolling sand dunes.

40.00 Point for the ¼ sec. cor. of secs. 25 and 30.


Set an iron post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.



deposit broken glass alongside the iron post, for witness.

80.00 Point for the cor. of secs. 19, 24, 25 and 30.

Set an iron post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.



deposit broken glass alongside the iron post, for witness.

BOOK 4491

West Boundary of T. 8 N., R. 18 W.

Chains	<p>Land, low rolling sand dunes. Soil, sandy clay. Timber, none; underbrush, ocotillo and cacti.</p>								
40.00	<p>North, bet. secs. 19 and 24. Over low rolling sand dunes. Point for the $\frac{1}{4}$ sec. cor. of secs. 19 and 24. Set an iron post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center;"> $\frac{1}{4}$ <table border="1" style="margin: auto;"> <tr><td>S 24</td><td>S 19</td></tr> </table> 1953 </div> <p>deposit broken glass alongside the iron post, for witness.</p>	S 24	S 19						
S 24	S 19								
80.00	<p>Point for the cor. of secs. 13, 18, 19 and 24. Set an iron post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center;"> <table border="1" style="margin: auto;"> <tr><td colspan="2">T 8 N</td></tr> <tr><td>R 19 W</td><td>R 18 W</td></tr> <tr><td>S 13</td><td>S 18</td></tr> <tr><td>S 24</td><td>S 19</td></tr> </table> 1953 </div> <p>deposit broken glass alongside the iron post, for witness.</p>	T 8 N		R 19 W	R 18 W	S 13	S 18	S 24	S 19
T 8 N									
R 19 W	R 18 W								
S 13	S 18								
S 24	S 19								
	<p>Land, low rolling sand dunes. Soil, sandy clay. Timber, none; underbrush, ocotillo and cacti.</p>								
40.00	<p>North, bet. secs. 13 and 18. Over low rolling sand dunes. Point for the $\frac{1}{4}$ sec. cor. of secs. 13 and 18. Set an iron post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center;"> $\frac{1}{4}$ <table border="1" style="margin: auto;"> <tr><td>S 13</td><td>S 18</td></tr> </table> 1953 </div> <p>deposit broken glass alongside the iron post, for witness.</p>	S 13	S 18						
S 13	S 18								
80.00	<p>Point for the cor. of secs. 7, 12, 13 and 18. Set an iron post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center;"> <table border="1" style="margin: auto;"> <tr><td colspan="2">T 8 N</td></tr> <tr><td>R 19 W</td><td>R 18 W</td></tr> <tr><td>S 12</td><td>S 7</td></tr> <tr><td>S 13</td><td>S 18</td></tr> </table> 1953 </div>	T 8 N		R 19 W	R 18 W	S 12	S 7	S 13	S 18
T 8 N									
R 19 W	R 18 W								
S 12	S 7								
S 13	S 18								

West Boundary of T. 8 N., R. 18 W.

Chains	deposit broken glass alongside the iron post, for witness.														
	Land, low rolling sand dunes. Soil, sandy clay. Timber, none; underbrush, ocotillo and cacti.														
	<hr/>														
	North, bet. secs. 7 and 12.														
	Over low rolling sand dunes.														
40.00	Point for the $\frac{1}{4}$ sec. cor. of secs. 7 and 12.														
	Set an iron post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 24 ins. in the														
	ground, with brass cap mkd.														
	$\frac{1}{4}$ <table style="margin: auto;"> <tr> <td style="padding: 0 10px;">S 12</td> <td style="border-left: 1px solid black; border-right: 1px solid black; padding: 0 5px;"> </td> <td style="padding: 0 10px;">S 7</td> </tr> <tr> <td colspan="3" style="text-align: center;">1953</td> </tr> </table>	S 12		S 7	1953										
S 12		S 7													
1953															
	deposit broken glass alongside the iron post, for witness.														
80.00	Point for the cor. of secs. 1, 6, 7 and 12.														
	Set an iron post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 24 ins. in the														
	ground, with brass cap mkd.														
	<table style="margin: auto;"> <tr> <td colspan="2" style="text-align: center;">T 8 N</td> </tr> <tr> <td style="padding: 0 10px;">R 19 W</td> <td style="border-left: 1px solid black; border-right: 1px solid black; padding: 0 5px;"> </td> <td style="padding: 0 10px;">R 18 W</td> </tr> <tr> <td style="padding: 0 10px;">S 1</td> <td style="border-left: 1px solid black; border-right: 1px solid black; padding: 0 5px;"> </td> <td style="padding: 0 10px;">S 6</td> </tr> <tr> <td style="border-top: 1px solid black; padding: 0 10px;">S 12</td> <td style="border-left: 1px solid black; border-right: 1px solid black; border-top: 1px solid black; padding: 0 5px;"> </td> <td style="border-top: 1px solid black; padding: 0 10px;">S 7</td> </tr> <tr> <td colspan="3" style="text-align: center;">1953</td> </tr> </table>	T 8 N		R 19 W		R 18 W	S 1		S 6	S 12		S 7	1953		
T 8 N															
R 19 W		R 18 W													
S 1		S 6													
S 12		S 7													
1953															
	deposit broken glass alongside the iron post, for witness.														
	Land, low rolling sand dunes.														
	Soil, sandy clay.														
	Timber, none; underbrush, ocotillo and cacti.														
	<hr/>														
	North, bet. secs. 1 and 6.														
	Over low rolling sand dunes.														
40.00	Point for the $\frac{1}{4}$ sec. cor. of secs. 1 and 6.														
	Set an iron post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 24 ins. in the														
	ground, with brass cap mkd.														
	$\frac{1}{4}$ <table style="margin: auto;"> <tr> <td style="padding: 0 10px;">S 1</td> <td style="border-left: 1px solid black; border-right: 1px solid black; padding: 0 5px;"> </td> <td style="padding: 0 10px;">S 6</td> </tr> <tr> <td colspan="3" style="text-align: center;">1953</td> </tr> </table>	S 1		S 6	1953										
S 1		S 6													
1953															
	deposit broken glass alongside the iron post, for witness.														
69.56	Intersect the Second Standard Parallel North.														
	Point for the closing cor. of T. 8 N., Rs. 18 and 19 W.														
	Set an iron post, 3 ft. long, 3 ins. diam., 27 ins. in the														
	ground, with brass cap mkd.														

BOOK 40

West Boundary of T. 8 N., R. 18 W.

Chains

T 9 N R 18 W
S 31

S 1 | S 6

C | C

T 8 N

R 19 W R 18 W

1954

deposit broken glass alongside the iron post, for witness.

From point of intersection the standard cor. of T. 9 N., Rs. 18 and 19 W., bears W., 17.41 chs. dist.

Land, low rolling sand dunes.

Soil, sandy clay.

Timber, none; underbrush, ocotillo and cacti.

Subdivision of T. 8 N., R. 18 W.

Beginning the subdivisional survey at the cor. of secs. 1, 2, 35 and 36, on the south boundary of the Tp., marked and witnessed as described in the official record.

N. 0° 01' W., bet. secs. 35 and 36.

Over sand flats, through scattering timber.

22.50 Enter overflow bottom land of Bouse wash, edge, bears E. and W.

31.00 Bouse wash, 2 chs. wide, 4 ft. deep, course W.

39.80 Leave overflow bottom land of Bouse wash edge, bears E. and W.

40.00 Point for the $\frac{1}{4}$ sec. cor. of secs. 35 and 36.

Set an iron post, 28 ins. long, 2 $\frac{1}{2}$ ins. diam., 24 ins. in the ground, with brass cap mkd.

$\frac{1}{4}$
S 35 | S 36
1954

deposit broken glass alongside the iron post, for witness.

43.30 State Highway No. 72, Bouse to Parker, bears E. and W.

44.30 Power line, bears E. and W.

45.15 Telephone line, bears E. and W.

45.75 A. T. & S. F. Railroad, bears E. and W.

80.00 Point for the cor. of secs. 25, 26, 35 and 36.

Set an iron post, 28 ins. long, 2 $\frac{1}{2}$ ins. diam., 24 ins. in the ground, with brass cap mkd.

T 8 N | R 18 W
S 26 | S 25
S 35 | S 36
1954

deposit broken glass alongside the iron post, for witness.

Subdivision of T. 8 N., R. 18 W.

Chains

Land, low rolling sand dunes and ridges.
Soil, sandy clay.
Timber, none; underbrush, ocotillo and cacti.

From the cor. of secs. 25, 30, 31 and 36, on the E. bdy. of the Tp.
N. 89° 59' W., bet. secs. 25 and 36.

Over low rolling sand dunes and ridges.

40.02 Point for the $\frac{1}{4}$ sec. cor. of secs. 25 and 36, at proportionate distance.

Set an iron post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 24 ins. in the ground, with brass cap mkd.

$\frac{1}{4}$ S 25

S 36
1953

deposit broken glass alongside the iron post, for witness.

80.04 The cor. of secs. 25, 26, 35 and 36.

Land, low rolling sand dunes and ridges.
Soil, sandy clay.
Timber, none; underbrush, ocotillo and cacti.

N. 0° 01' W., bet. secs. 25 and 26.

Over low rolling sand dunes.

40.00 Point for the $\frac{1}{4}$ sec. cor. of secs. 25 and 26.

Set an iron post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 24 ins. in the ground, with brass cap mkd.

$\frac{1}{4}$
S 26 | S 25

1954

deposit broken glass alongside the iron post, for witness.

80.00 Point for the cor. of secs. 23, 24, 25 and 26.

Set an iron post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 24 ins. in the ground, with brass cap mkd.

T 8 N. R 18 W
S 23 | S 24

S 26 | S 25

1954

deposit broken glass alongside the iron post, for witness.

Land, low rolling sand dunes and ridges.
Soil, sandy clay.
Timber, none; underbrush, ocotillo and cacti.

From the cor. of secs. 19, 24, 25 and 30, on the E. bdy. of the Tp.
S. 89° 58' W., bet. secs. 24 and 25.

Over low rolling sand dunes.

BOOK 4491

Subdivision of T. 8 N., R. 18 W.

Chains
40.05Point for the $\frac{1}{4}$ sec. cor. of secs. 24 and 25, at proportionate distance.Set an iron post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 24 ins. in the ground, with brass cap mkd.
$$\begin{array}{r} \frac{1}{4} \text{ S } 24 \\ \hline \text{S } 25 \\ 1954 \end{array}$$

deposit broken glass alongside the iron post, for witness.

80.10

The cor. of secs. 23, 24, 25 and 26.

Land, low rolling sand dunes.

Soil, sandy clay.

Timber, none; underbrush, ocotillo and cacti.

N. $0^{\circ} 01'$ W., bet. secs. 23 and 24.

Over low rolling sand dunes.

40.00

Point for the $\frac{1}{4}$ sec. cor. of secs. 23 and 24.
$$\begin{array}{r} \frac{1}{4} \\ \text{S } 23 \quad | \quad \text{S } 24 \\ \hline 1954 \end{array}$$

deposit broken glass alongside the iron post, for witness.

45.00

Leave sand dunes, enter gravel flats, edge, bears E. and W.

80.00

Point for the cor. of secs. 13, 14, 23 and 24.

Set an iron post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 24 ins. in the ground, with brass cap mkd.
$$\begin{array}{r} \text{T } 8 \text{ N} \quad \text{R } 18 \text{ W} \\ \hline \text{S } 14 \quad | \quad \text{S } 13 \\ \hline \text{S } 23 \quad | \quad \text{S } 24 \\ 1954 \end{array}$$

deposit broken glass alongside the iron post, for witness.

Land, low rolling sand dunes.

Soil, sandy clay and gravel.

Timber, none; underbrush, ocotillo and cacti.

From the cor. of secs. 13, 18, 19 and 24, on the E. bdy. of the Tp.

S. $89^{\circ} 57'$ W., bet. secs. 13 and 24.

Over low rolling sand dunes.

10.12

Wash, 15 lks. wide, 2 ft. deep, course SW.

40.01

Point for the $\frac{1}{4}$ sec. cor. of secs. 13 and 24, at proportionate distance.
$$\begin{array}{r} \frac{1}{4} \text{ S } 13 \\ \hline \text{S } 24 \\ 1954 \end{array}$$

Subdivision of T. 8 N., R. 18 W

Chains deposit broken glass alongside the iron post, for witness.

40.40 Top of ridge, bears E. and W.

56.00 Gravel ridge, bears E. and W.

80.02 The cor. of secs. 13, 14, 23 and 24.


Land, low rolling sand dunes.
Soil, sandy clay and gravel.
Timber, none; underbrush, ocotillo and cacti.

N. 0° 01' W., bet. secs. 13 and 14.

Over rolling sand dunes.

40.00 Point for the $\frac{1}{4}$ sec. cor. of secs. 13 and 14.


Set an iron post, 28 ins. long, 2 $\frac{1}{2}$ ins. diam., 24 ins. in the ground, with brass cap mkd.



deposit broken glass alongside the iron post, for witness.

80.00 Point for the cor. of secs. 11, 12, 13 and 14.

Set an iron post, 28 ins. long, 2 $\frac{1}{2}$ ins. diam., 24 ins. in the ground, with brass cap mkd.



deposit broken glass alongside the iron post, for witness.

Land, low rolling sand dunes.
Soil, sandy clay.
Timber, none; underbrush, ocotillo and cacti.


From the cor. of secs. 7, 12, 13 and 18, on the E. bdy. of the Tp.

S. 89° 56' W., bet. secs. 12 and 13.

Over low rolling sand dunes.

40.03 Point for the $\frac{1}{4}$ sec. cor. of secs. 12 and 13, at proportionate distance.

Set an iron post, 28 ins. long, 2 $\frac{1}{2}$ ins. diam., 24 ins. in the ground, with brass cap mkd.



deposit broken glass alongside the iron post, for witness.

80.06 The cor. of secs. 11, 12, 13 and 14.

Land, low rolling sand dunes.
Soil, sandy clay.

BOOK 4491


Subdivision of T. 8 N., R. 18 W.

Chains	Timber, none; underbrush, ocotillo and cacti.
	N. 0° 01' W., bet. secs. 11 and 12.
	Over low rolling sand dunes.
40.00	Point for the $\frac{1}{4}$ sec. cor. of secs. 11 and 12.
	Set an iron post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 24 ins. in the ground, with brass cap mkd.
	$\begin{array}{c} \frac{1}{4} \\ \text{S 11} \mid \text{S 12} \\ 1954 \end{array}$
	deposit broken glass alongside the iron post, for witness.
80.00	Point for the cor. of secs. 1, 2, 11 and 12.
	Set an iron post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 24 ins. in the ground, with brass cap mkd.
	$\begin{array}{cc} \text{T 8 N} & \text{R 18 W} \\ \text{S 2} & \mid \text{S 1} \\ \hline \text{S 11} & \mid \text{S 12} \\ 1954 \end{array}$
	deposit broken glass alongside the iron post, for witness.
	Land, low rolling sand dunes. Soil, sandy clay. Timber, none; underbrush, ocotillo and cacti.
	From the cor. of secs. 1, 6, 7 and 12, on the E. bdy. of the Tp.
	S. 89° 59' W., bet. secs. 1 and 12.
	Over low rolling sand dunes.
40.03	Point for the $\frac{1}{4}$ sec. cor. of secs. 1 and 12, at proportionate distance.
	Set an iron post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 24 ins. in the ground, with brass cap mkd.
	$\begin{array}{c} \text{S 1} \\ \frac{1}{4} \\ \text{S 12} \\ 1954 \end{array}$
	deposit broken glass alongside the iron post, for witness.
80.06	The cor. of secs. 1, 2, 11 and 12.
	Land, low rolling sand dunes. Soil, sandy clay. Timber, none, underbrush, ocotillo and cacti.
	N. 0° 01' W., bet. secs. 1 and 2.
	Over low rolling sand dunes.
40.00	Point for the $\frac{1}{4}$ sec. cor. of secs. 1 and 2.

Subdivision of T. 8 N., R. 18 W.

Chains

Set an iron post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.




deposit broken glass alongside the iron post, for witness.

69.20

Intersect the Second Standard Parallel North.

Point for the closing cor. of secs. 1 and 2.

Set an iron post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.




deposit broken glass alongside the iron post, for witness.

From point of intersection the standard cor. of secs. 35 and 36, T. 9 N., R. 18 W., bears W., 1.36 chs. dist.

Land, low rolling sand dunes.
Soil, sandy clay.
Timber, none; underbrush, ocotillo and cacti.

At a point mid-way between the closing township cor. of secs. 1 and 6, T. 8 N., Rs. 17 and 18 W., and closing cor. of secs. 1 and 2, T. 8 N., R. 18 W., point for the ¼ sec. cor. of sec. 1.

Set an iron post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.



deposit broken glass alongside the iron post, for witness.

From this corner the standard ¼ sec. cor. of sec. 36, previously described, bears W., 1.38 chs. dist.

From the cor. of secs. 2, 3, 34 and 35, on the S. bdy. of the Tp., previously described.

N. 0° 01' W., bet. secs. 34 and 35.

Over low rolling sand dunes.

5.00

Road, bears E. and W.

8.40

Left bank of Bouse wash, course S. 60° W.

31.80

Right bank of Bouse wash, course S. 60° W.

40.00

Point for the ¼ sec. cor. of secs. 34 and 35.

BOOK 4491

Subdivision of T. 8 N., R. 18 W.

Chains Set an iron post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.

¼
S 34 | S 35

1953

deposit broken glass alongside the iron post, for witness.

41.20 State road No. 72, Bouse to Parker, bears E. and W.

42.10 Power line, bears E. and W.

43.00 Telephone line, bears E. and W.

43.60 A. T. & S. F. Railroad, bears E. and W.

80.00 Point for the cor. of secs. 26, 27, 34 and 35.

Set an iron post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.

T 8 N R 18 W
S 27 | S 26

S 34 | S 35

1953

deposit broken glass alongside the iron post, for witness.

Land, low rolling sand dunes.

Soil, sandy clay.

Timber, none; underbrush, ocotillo and cacti.

From the cor. of secs. 25, 26, 35 and 36.

S. 89° 57' W., bet. secs. 26 and 35.

Over low rolling sand dunes.

29.50 Wash, 35 lks, wide, 4 ft. deep, course S.

40.00 Point for the ¼ sec. cor. of secs. 26 and 35, at proportionate distance.

Set an iron post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.

S 26
¼

S 35

1953

deposit broken glass alongside the iron post, for witness.

80.00 The cor. of secs. 26, 27, 34 and 35.

Land, low rolling sand dunes.

Soil, sandy clay.

Timber, none; underbrush, ocotillo and cacti.

N. 0° 01' W., bet. secs. 26 and 27.

Over low rolling sand dunes.

Subdivision of T. 8 N., R. 18 W.

Chains
40.00

Point for the $\frac{1}{4}$ sec. cor. of secs. 26 and 27.

Set an iron post, 28 ins. long, 2 $\frac{1}{2}$ ins. diam., 24 ins. in the ground, with brass cap mkd.




deposit broken glass alongside the iron post, for witness.

80.00

Point for the cor. of secs. 22, 23, 26 and 27.

Set an iron post, 28 ins. long, 2 $\frac{1}{2}$ ins. diam., 24 ins. in the ground, with brass cap mkd.



deposit broken glass alongside the iron post, for witness.

Land, low rolling sand dunes.
Soil, sandy clay.
Timber, none; underbrush, ocotillo and cacti.

From the cor. of secs. 23, 24, 25 and 26.

S. 89° 57' W., bet. secs. 23 and 26.

Over low rolling sand dunes.

22.80

Foot of lava dome.

29.11

Top of lava dome.


34.43

Foot of lava dome.

40.02

Point for the $\frac{1}{4}$ sec. cor. of secs. 23 and 26, at proportionate distance.

Set an iron post, 28 ins. long, 2 $\frac{1}{2}$ ins. diam., 24 ins. in the ground, with brass cap mkd.



deposit broken glass alongside the iron post, for witness.

80.04

The cor. of secs. 22, 23, 26 and 27.

Land, low rolling sand dunes.
Soil, sandy clay.
Timber, none; underbrush, ocotillo and cacti.

N. 0° 01' W., bet. secs. 22 and 23.

Over low rolling sand dunes and ridges.

3.70

Wash, 50 lks. wide, 3 ft. deep, course SSW.


Subdivision of T. 8 N., R. 18 W.

Chains ✓ Point for the $\frac{1}{4}$ sec. cor. of secs. 22 and 23.
 40.00 Set an iron post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 24 ins. in the ground, with brass cap mkd.

$$\begin{array}{c} \frac{1}{4} \\ \text{S 22} \mid \text{S 23} \\ 1953 \end{array}$$

deposit broken glass alongside the iron post, for witness.


80.00 Point for the cor. of secs. 14, 15, 22 and 23.
 Set an iron post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 24 ins. in the ground, with brass cap mkd.



deposit broken glass alongside the iron post, for witness.

Land, low rolling sand dunes.
 Soil, sandy clay.
 Timber, none; underbrush, ocotillo and cacti.


40.02 From the cor. of secs. 13, 14, 23 and 24.
 West, bet. secs. 14 and 23.
 Over low rolling sand dunes.
 Point for the $\frac{1}{4}$ sec. cor. of secs. 14 and 23, at proportionate distance.
 Set an iron post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 24 ins. in the ground, with brass cap mkd.



deposit broken glass alongside the iron post, for witness.

80.04 The cor. of secs. 14, 15, 22 and 23.
 Land, low rolling sand dunes.
 Soil, sandy clay.
 Timber, none; underbrush, ocotillo and cacti.

40.00 N. $0^{\circ} 01'$ W., bet. secs. 14 and 15.
 Over low rolling sand dunes.
 Point for the $\frac{1}{4}$ sec. cor. of secs. 14 and 15.
 Set an iron post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 24 ins. in the ground, with brass cap mkd.



Subdivision of T. 8 N., R. 18 W.

Chains deposit broken glass alongside the iron post, for witness.
 70.19 Wash, 45 lks. wide, 5 ft. deep, course SSW.
 80.00 Point for the cor. of secs. 10, 11, 14 and 15.
 Set an iron post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.

T 8 N	R 18 W
S 10	S 11
S 15	S 14

1953

deposit broken glass alongside the iron post, for witness.

Land, low rolling sand dunes.
 Soil, sandy clay.
 Timber, none; underbrush, ocotillo and cacti.

From the cor. of secs. 11, 12, 13 and 14.

West, bet. secs. 11 and 14.

Over low rolling sand dunes.

10.00 Enter sand flats, bears N. and S.

40.00 Point for the ¼ sec. cor. of secs. 11 and 14, at proportionate distance.

Set an iron post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.

¼	S 11
	S 14

1953

deposit broken glass alongside the iron post, for witness.

59.30 Wash, 40 lks wide, 5 ft. deep, course SSW.

73.00 Foot of gravel and rocky ridge, bears N. and S.

76.00 Top of gravel and rocky ridge, bears N. and S.

80.00 The cor. of secs. 10, 11, 14 and 15.

Land, low rolling sand dunes.
 Soil, sandy clay.
 Timber, none; underbrush, ocotillo and cacti.

N. 0° 01' W., bet. secs. 10 and 11.

Over low rolling sand dunes:

40.00 Point for the ¼ sec. cor. of secs. 10 and 11.

Set an iron post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd:

¼	S 10	S 11
---	------	------

1954

Subdivision of T. 8 N., R. 18 W.

Chains	deposit broken glass alongside the iron post, for witness.								
50.77	Malpais dome, enter sand flats.								
80.00	Point for the cor. of secs. 2, 3, 10 and 11. Set an iron post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd. <table style="margin-left: auto; margin-right: auto;"> <tr> <td>T 8 N</td> <td>R 18 W</td> </tr> <tr> <td>S 3</td> <td>S 2</td> </tr> <tr> <td colspan="2" style="border-top: 1px solid black;"></td> </tr> <tr> <td>S 10</td> <td>S 11</td> </tr> </table> 1954 deposit broken glass alongside the iron post, for witness. Land, low rolling sand dunes. Soil, sandy clay. Timber, none, underbrush, ocotillo and cacti.	T 8 N	R 18 W	S 3	S 2			S 10	S 11
T 8 N	R 18 W								
S 3	S 2								
S 10	S 11								
39.96	From the cor. of secs. 1, 2, 11 and 12. West, bet. secs. 2 and 11. Over low rolling sand dunes. Point for the ¼ sec. cor. of secs. 2 and 11, at proportionate distance. Set an iron post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd. <table style="margin-left: auto; margin-right: auto;"> <tr> <td>¼</td> <td>S 2</td> </tr> <tr> <td colspan="2" style="border-top: 1px solid black;"></td> </tr> <tr> <td>¼</td> <td>S 11</td> </tr> </table> 1954 deposit broken glass alongside the iron post, for witness.	¼	S 2			¼	S 11		
¼	S 2								
¼	S 11								
79.92	The cor. of secs. 2, 3, 10 and 11. Land, low rolling sand dunes. Soil, sandy clay. Timber, none; underbrush, ocotillo and cacti.								
40.00	N. 0° 01' W., bet. secs. 2 and 3. Over low rolling sand dunes. Point for the ¼ sec. cor. of secs. 2 and 3. Set an iron post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd. <table style="margin-left: auto; margin-right: auto;"> <tr> <td>¼</td> <td></td> </tr> <tr> <td>S 3</td> <td>S 2</td> </tr> </table> 1954 deposit broken glass alongside the iron post, for witness.	¼		S 3	S 2				
¼									
S 3	S 2								
69.21	Intersect the Second Standard Parallel North. Point for the closing cor. of secs. 2 and 3, T. 8 N., R. 18 W. Set an iron post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.								

BOOK 4491

Subdivision of T. 8 N., R. 18 W.

Chains

T 9 N R 18 W

S 35

S 3	S 2
-----	-----

C C

T 8 N R 18 W

1954

deposit broken glass alongside the iron post, for witness.

From point of intersection the standard cor. of secs. 34 and 35, T. 9 N., R. 18 W., bears W., 1.42 chs. dist.

Land, low rolling sand dunes.

Soil, sandy clay.

Timber, none; underbrush, ocotillo and cacti.

At a point mid-way between the closing cors. of secs. 1 and 2 and 2 and 3, T. 8 N., R. 18 W., point for the $\frac{1}{4}$ sec. cor. of sec. 2

Set an iron post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 24 ins. in the ground, with brass cap mkd.

$\frac{1}{4}$ S 2

1954

deposit broken glass alongside the iron post, for witness.

From this point the standard $\frac{1}{4}$ sec. cor. of sec. 35, bears W., 1.39 chs. dist.

From the cor. of secs. 3, 4, 33 and 34, on the S. bdy. of the Tp.

N. $0^{\circ} 02'$ W., bet. secs. 33 and 34.

Over low rolling sand dunes.

5.00 Wash, 40 lks. wide, 3 ft. deep, course N. 10° W.

35.00 Left bank of Bouse wash, course W.

35.90 Center of Bouse wash, course W.

36.80 Right bank of Bouse wash, course W.

40.00 Point for the $\frac{1}{4}$ sec. cor. of secs. 33 and 34.

Set an iron post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 24 ins. in the ground, with brass cap mkd.

$\frac{1}{4}$

S 33	S 34
------	------

1954

deposit broken glass alongside the iron post, for witness.

40.70 State road No. 72, Bouse to Parker, bears E. and W.

41.98 Power line, bears E. and W.

45.58 Telephone line, bears E. and W.

46.18 A. T. & S. F. Railroad, bears E. and W.


BOOK 4491

Subdivision of T. 8 N., R. 18 W.

Chains
80.00

Point for the cor. of secs. 27, 28, 33 and 34.

Set an iron post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.



deposit broken glass alongside the iron post, for witness.

Land, low rolling sand dunes.

Soil, sandy clay.

Timber, none; underbrush, ocotillo and cacti.

32.50
39.95

From the cor. of secs. 26, 27, 34 and 35.


S. 89° 57' W., bet. secs. 27 and 34.

Over low rolling sand dunes.

Wash, course S.

Point for the ¼ sec. cor. of secs. 27 and 34, at proportionate distance.

Set an iron post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.



deposit broken glass alongside the iron post, for witness.

79.90

The cor. of secs. 27, 28, 33 and 34.

Land, low rolling sand dunes.

Soil, sandy clay.

Timber, none; underbrush, ocotillo and cacti.


40.00

N. 0° 02' W., bet. secs. 27 and 28.

Over low rolling sand dunes.

Point for the ¼ sec. cor. of secs. 27 and 28.

Set an iron post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.




deposit broken glass alongside the iron post, for witness.

80.00

Point for the cor. of secs. 21, 22, 27 and 28.

Set an iron post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.



Subdivision of T. 8 N., R. 18 W.

Chains	<p>deposit broken glass alongside the iron post, for witness.</p> <p>Land, low rolling sand dunes, Soil, sandy clay. Timber, none; underbrush, ocotillo and cacti.</p>
1.80	<p>From the cor. of secs. 22, 23, 26 and 27.</p> <p>S. 89° 57' W., bet. secs. 22 and 27.</p> <p>Over low rolling sand dunes.</p> <p>Wash, 35 lks. wide, 2 ft. deep, course S.</p>
11.80	<p>Wash, 20 lks. wide, 1 ft. deep, course S.</p>
39.98	<p>Point for the $\frac{1}{4}$ sec. cor. of secs. 22 and 27, at proportionate distance.</p> <p>Set an iron post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center;"> $\begin{array}{c} S\ 22 \\ \frac{1}{4} \\ S\ 27 \\ 1953 \end{array}$ </div> <p>deposit broken glass alongside the iron post, for witness.</p>
79.96	<p>The cor. of secs. 21, 22, 27 and 28.</p> <p>Land, low rolling sand dunes. Soil, sandy clay. Timber, none; underbrush, ocotillo and cacti.</p>
40.00	<p>N. 0° 02' W., bet. secs. 21 and 22.</p> <p>Over low rolling sand dunes.</p> <p>Point for the $\frac{1}{4}$ sec. cor. of secs. 21 and 22.</p> <p>Set an iron post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center;"> $\begin{array}{c} \frac{1}{4} \\ S\ 21 \quad \quad S\ 22 \\ 1953 \end{array}$ </div> <p>deposit broken glass alongside the iron post, for witness.</p>
80.00	<p>Point for the cor. of secs. 15, 16, 21 and 22.</p> <p>Set an iron post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center;"> $\begin{array}{cc} T\ 8\ N & R\ 18\ W \\ S\ 16 & & S\ 15 \\ S\ 21 & & S\ 22 \\ 1953 \end{array}$ </div> <p>deposit broken glass alongside the iron post, for witness.</p> <p>Land, low rolling sand dunes. Soil, sandy clay. Timber, none; underbrush, ocotillo and cacti.</p>

BOOK 4491

Subdivision of T. 8 N., R. 18 W.

Chains	<p>From the cor. of secs. 14, 15, 22 and 23.</p> <p>S. 89° 57' W., bet. secs. 15 and 22.</p> <p>Over low rolling sand dunes.</p>
12.10	Wash, 30 lks. wide, 3 ft. deep, course S.
37.58	Wash, 20 lks. wide, 2 ft. deep, course S.
40.00	<p>Point for the $\frac{1}{4}$ sec. cor. of secs. 15 and 22, at proportionate distance.</p> <p>Set an iron post, 28 ins. long, 2$\frac{1}{2}$ ins. diam., 24 ins. in the ground, with brass cap mkd.</p> $\begin{array}{r} \frac{1}{4} \text{ S } 15 \\ \hline \text{S } 22 \\ 1953 \end{array}$ <p>deposit broken glass alongside the iron post, for witness.</p>
80.00	<p>The cor. of secs. 15, 16, 21 and 22.</p> <p>Land, low rolling sand dunes.</p> <p>Soil, sandy clay.</p> <p>Timber, none; underbrush, ocotillo and cacti.</p>
	<p>N. 0° 02' W., bet. secs. 15 and 16.</p> <p>Over low rolling sand dunes.</p>
40.00	<p>Point for the $\frac{1}{4}$ sec. cor. of secs. 15 and 16.</p> <p>Set an iron post, 28 ins. long, 2$\frac{1}{2}$ ins. diam., 24 ins. in the ground, with brass cap mkd.</p> $\begin{array}{r} \frac{1}{4} \\ \text{S } 16 \quad \quad \text{S } 15 \\ \hline 1953 \end{array}$ <p>deposit broken glass alongside the iron post, for witness.</p>
80.00	<p>Point for the cor. of secs. 9, 10, 15 and 16.</p> <p>Set an iron post, 28 ins. long, 2$\frac{1}{2}$ ins. diam., 24 ins. in the ground, with brass cap mkd.</p> $\begin{array}{r} \text{T } 8 \text{ N} \quad \text{R } 18 \text{ W} \\ \text{S } 9 \quad \quad \text{S } 10 \\ \hline \text{S } 16 \quad \quad \text{S } 15 \\ 1953 \end{array}$ <p>deposit broken glass alongside the iron post, for witness.</p> <p>Land, low rolling sand dunes.</p> <p>Soil, sandy clay.</p> <p>Timber, none; underbrush, ocotillo and cacti.</p>
	<p>From the cor. of secs. 10, 11, 14 and 15.</p> <p>S. 89° 57' W., bet. secs. 10 and 15.</p> <p>Over low rolling sand dunes.</p>

Subdivision of T. 8 N., R. 18 W.

Chains 23.69	Wash, 50 lks. wide, 3 ft. deep, course S.
39.98	Point for the $\frac{1}{4}$ sec. cor. of secs. 10 and 15, at proportionate distance. Set an iron post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 24 ins. in the ground, with brass cap mkd. $\begin{array}{c} \frac{1}{4} \\ \hline S 10 \\ S 15 \\ 1953 \end{array}$ deposit broken glass alongside the iron post, for witness.
50.58	Wash, 25 lks. wide, 3 ft. deep, course S. 10° W.
79.96	The cor. of secs. 9, 10, 15 and 16. Land, low rolling sand dunes. Soil, sandy clay. Timber, none; underbrush, ocotillo and cacti.
40.00	N. 0° 02' W., bet. secs. 9 and 10. Over low rolling sand dunes. Point for the $\frac{1}{4}$ sec. cor. of secs. 9 and 10. Set an iron post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 24 ins. in the ground, with brass cap mkd. $\begin{array}{c} \frac{1}{4} \\ S 9 \quad \quad S 10 \\ 1953 \end{array}$ deposit broken glass alongside the iron post, for witness.
80.00	Point for the cor. of secs. 3, 4, 9 and 10. Set an iron post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 24 ins. in the ground, with brass cap mkd. $\begin{array}{c} T 8 N \quad R 18 W \\ S 4 \quad \quad S 3 \\ \hline S 9 \quad \quad S 10 \\ 1953 \end{array}$ deposit broken glass alongside the iron post, for witness. Land, low rolling sand dunes. Soil, sandy clay. Timber, none; underbrush, ocotillo and cacti.
15.00	From the cor. of secs. 2, 3, 10 and 11. N. 89° 58' W., bet. secs. 3 and 10. Over low rolling sand dunes.
39.96	Leave rolling sand dunes; enter sand flats. Point for the $\frac{1}{4}$ sec. cor. of secs. 3 and 10, at proportionate distance.

Subdivision of T. 8 N., R. 18 W.

Chains. Set an iron post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.

$$\frac{1}{4} \begin{array}{c} S 3 \\ S 10 \end{array}$$

1954

deposit broken glass alongside the iron post, for witness.

79.92 The cor. of secs. 3, 4, 9 and 10.

Land, low rolling sand dunes.

Soil, sandy clay.

Timber, none; underbrush, ocotillo and cacti.

N. 0° 02' W., bet. secs. 3 and 4.

Over low rolling sand dunes.

40.00 Point for the ¼ sec. cor. of secs. 3 and 4.

Set an iron post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.

$$\frac{1}{4} \begin{array}{c} S 4 \quad | \quad S 3 \\ 1954 \end{array}$$

deposit broken glass alongside the iron post, for witness.

69.28 Intersect the Second Standard Parallel North.

Point for the closing cor. of secs. 3 and 4, T. 8 N., R. 18 W.

Set an iron post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.

$$\begin{array}{c} T 9 N \quad R 18 W \\ S 34 \end{array}$$

$$\begin{array}{c} S 4 \quad | \quad S 3 \\ C C \end{array}$$

$$T 8 N \quad R 18 W$$

1954

deposit broken glass alongside the iron post, for witness.

From point of intersection the standard cor. of secs. 33 and 34, T. 9 N., R. 18 W., bears W., 1.50 chs. dist.

Land, low rolling sand dunes:

Soil, sandy clay.

Timber, none; underbrush, ocotillo and cacti.

At a point mid-way between the closing cors. of secs. 2 and 3 and 3 and 4, T. 8 N., R. 18 W., point for the ¼ sec. cor. of sec. 3.

Set an iron post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.

$$\frac{1}{4} S 3$$

1954

Subdivision of T. 8 N., R. 18 W.

Chains

deposit broken glass alongside the iron post, for witness.

From this cor. the standard $\frac{1}{4}$ cor. of sec. 34, T. 9 N., R. 18 W., bears W., 1.48 chs. dist.

From the cor. of secs. 4, 5, 32 and 33, on the S. bdy. of the Tp. N. 0° 02' W., bet. secs. 32 and 33.

Over low rolling sand dunes.

19.01 Left bank of Bouse wash, bears S. 70° W. and N. 70° E.

38.91 Right bank of Bouse wash, bears S. 70° W. and N. 70° E.

40.00 Point for the $\frac{1}{4}$ sec. cor. of secs. 32 and 33.

Set an iron post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 24 ins. in the ground, with brass cap mkd.

$\frac{1}{4}$
S 32 | S 33
1953

deposit broken glass alongside the iron post, for witness.

48.00 State Highway No. 72, Bouse to Parker, bears E. and W.

48.90 Power line, bears E. and W.

51.50 Telephone line, bears E. and W.

52.20 A. T. & S. F. Railroad, bears E. and W.

80.00 Point for the cor. of secs. 28, 29, 32 and 33.

Set an iron post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 24 ins. in the ground, with brass cap mkd.

T 8 N R 18 W
S 29 | S 28
S 32 | S 33
1953

deposit broken glass alongside the iron post, for witness.

Land, low rolling sand dunes.

Soil, sandy clay.

Timber, none; underbrush, ocotillo and cacti.

From the cor. of secs. 27, 28, 33 and 34.

S. 89° 55' W., bet. secs. 28 and 33.

Over low rolling sand dunes.

40.01 Point for the $\frac{1}{4}$ sec. cor. of secs. 28 and 33, at proportionate distance.

Set an iron post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 24 ins. in the ground, with brass cap mkd.

$\frac{1}{4}$ S 28
S 33
1953

BOOK 4491

Subdivision of T. 8 N., R. 18 W.

Chains

deposit broken glass alongside the iron post, for witness.

80.02

The cor. of secs. 28, 29, 32 and 33.

Land, low rolling sand dunes.

Soil, sandy clay.

Timber, none; underbrush, ocotillo and cacti.

N. 0° 02' W., bet. secs. 28 and 29.

Over low rolling sand dunes.

40.00

Point for the $\frac{1}{4}$ sec. cor. of secs. 28 and 29.Set an iron post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 24 ins. in the ground, with brass cap mkd.
$$\begin{array}{c} \frac{1}{4} \\ \text{S } 29 \mid \text{S } 28 \\ 1953 \end{array}$$

deposit broken glass alongside the iron post, for witness.

80.00

Point for the cor. of secs. 20, 21, 28 and 29.

Set an iron post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 24 ins. in the ground, with brass cap mkd.
$$\begin{array}{c} \text{T } 8 \text{ N } \quad \text{R } 18 \text{ W} \\ \text{S } 20 \mid \text{S } 21 \\ \hline \text{S } 29 \mid \text{S } 28 \\ 1953 \end{array}$$

deposit broken glass alongside the iron post, for witness.

Land, low rolling sand dunes.

Soil, sandy clay.

Timber, none; underbrush, ocotillo and cacti.

From the cor. of secs. 21, 22, 27 and 28.

S. 89° 55' W., bet. secs. 21 and 28.

Over low rolling sand dunes.

40.01

Point for the $\frac{1}{4}$ sec. cor. of secs. 21 and 28, at proportionate distance.Set an iron post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 24 ins. in the ground, with brass cap mkd.
$$\begin{array}{c} \text{S } 21 \\ \frac{1}{4} \text{ ---} \\ \text{S } 28 \\ 1953 \end{array}$$

deposit broken glass alongside the iron post, for witness.

80.02

The cor. of secs. 20, 21, 28 and 29.

Land, low rolling sand dunes.

Soil, sandy clay.

Timber, none; underbrush, ocotillo and cacti.

Subdivision of T. 8 N., R. 18 W.

Chains


N. 0° 02' W., bet. secs. 20 and 21.

Over low rolling sand dunes.

40.00

Point for the 1/4 sec. cor. of secs. 20 and 21.

Set an iron post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.




deposit broken glass alongside the iron post, for witness.

80.00

Point for the cor. of secs. 16, 17, 20 and 21.

Set an iron post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.



deposit broken glass alongside the iron post, for witness.

Land, low rolling sand dunes.

Soil, sandy clay.

Timber, none; underbrush, ocotillo and cacti.

From the cor. of secs. 15, 16, 21 and 22.


S. 89° 56' W., bet. secs. 16 and 21.

Over low rolling sand dunes.

40.01

Point for the 1/4 sec. cor. of secs. 16 and 21, at proportionate distance.

Set an iron post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.



deposit broken glass alongside the iron post, for witness.

80.02

The cor. of secs. 16, 17, 21 and 22.

Land, low rolling sand dunes.

Soil, sandy clay.

Timber, none; underbrush, ocotillo and cacti.

N. 0° 02' W., bet. secs. 16 and 17.

Over low rolling sand dunes.

40.00

Point for the 1/4 sec. cor. of secs. 16 and 17.

Set an iron post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.

Subdivision of T. 8 N., R. 18 W.

Chains

$$\frac{1}{4}$$

S 17	S 16
------	------

.1953

deposit broken glass alongside the iron post, for witness.

80.00

Point for the cor. of secs. 8, 9, 16 and 17.

Set an iron post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 24 ins. in the ground, with brass cap mkd.

T 8 N	R 18 W
S 8	S 9
S 17	S 16

1953

deposit broken glass alongside the iron post, for witness.

Land, low rolling sand dunes.

Soil, sandy clay.

Timber, none; underbrush, ocotillo and cacti.

From the cor. of secs. 9, 10, 15 and 16.

S. $89^{\circ} 56'$ W., bet. secs. 9 and 16.

Over low rolling sand dunes.

39.98

Point for the $\frac{1}{4}$ sec. cor. of secs. 9 and 16, at proportionate distance.

Set an iron post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 24 ins. in the ground, with brass cap mkd.

$$\frac{1}{4}$$

S 9
S 16

1953

deposit broken glass alongside the iron post, for witness.

79.96

The cor. of secs. 8, 9, 16 and 17.

Land, low rolling sand dunes.

Soil, sandy clay.

Timber, none; underbrush, ocotillo and cacti.

N. $0^{\circ} 02'$ W., bet. secs. 8 and 9.

Over low rolling sand dunes.

40.00

Point for the $\frac{1}{4}$ sec. cor. of secs. 8 and 9.

Set an iron post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 24 ins. in the ground, with brass cap mkd.

$$\frac{1}{4}$$

S 8	S 9
-----	-----

1953

deposit broken glass alongside the iron post, for witness.

Subdivision of T. 8 N., R. 18 W.

Chains
80.00

Point for the cor. of secs. 4, 5, 8 and 9.

Set an iron post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.

T 8 N R 18 W

S 5 | S 4

S 8 | S 9

1953

deposit broken glass alongside the iron post, for witness.

Land, low rolling sand dunes.

Soil, sandy clay.

Timber, none; underbrush, ocotillo and cacti.

From the cor. of secs. 3, 4, 9 and 10.

S. 89° 56' W., bet. secs. 4 and 9.

Over low rolling sand dunes.

39.98

Point for the ¼ sec. cor. of secs. 4 and 9.

Set an iron post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.

S 4

¼

S 9

1953

deposit broken glass alongside the iron post, for witness.

79.96

The cor. of secs. 4, 5, 8 and 9.

Land, low rolling sand dunes.

Soil, sandy clay.

Timber, none; underbrush, ocotillo and cacti.

N. 0° 02' W., bet. secs. 4 and 5.

Over low rolling sand dunes.

40.00

Point for the ¼ sec. cor. of secs. 4 and 5.

Set an iron post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.

¼

S 5 | S 4

1954

deposit broken glass alongside the iron post, for witness.

69.36

Intersect the Second Standard Parallel North.

Point for the closing cor. of secs. 4 and 5, T. 8 N., R. 18 W.

Set an iron post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.

Subdivision of T. 8 N., R. 18 W.

Chains

T 9 N . R 18 W

S 33

S 5 | S 4

C I C

T 8 N R 18 W

1954

deposit broken glass alongside the iron post, for witness.

From point of intersection the standard cor. of secs. 32 and 33, T. 9 N., R. 18 W., bears W., 1.54 chs. dist.

Land, low rolling sand dunes.

Soil, sandy clay.

Timber, none; underbrush, ocotillo and cacti.

At a point mid-way between the closing cor. of secs. 3 and 4, 4 and 5, T. 8 N., R. 18 W., point for the $\frac{1}{4}$ sec. cor. of sec. 4.

Set an iron post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 24 ins. in the ground, with brass cap mkd.

 $\frac{1}{4}$ S 4

1954

deposit broken glass alongside the iron post, for witness.

From this corner the standard $\frac{1}{4}$ sec. cor. of sec. 33, T. 9 N., R. 18 W., bears W., 1.52 chs. dist.

From the cor. of secs. 5, 6, 31 and 32, Ts. 7 and 8 N., R. 18 W., on the S. bdy. of the Tp.

N. $0^{\circ} 03'$ W., bet. secs. 31 and 32.

Over low rolling sand dunes,

28.09 Left bank of Bouse wash, bears N. 70° W. and S. 70° E.

38.29 Right bank of Bouse wash, bears N. 70° W. and S. 70° E.

40.00 Point for the $\frac{1}{4}$ sec. cor. of secs. 31 and 32.

Set an iron post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 24 ins. in the ground, with brass cap mkd.

$$\frac{1}{4}$$

$$S 31 \quad | \quad S 32$$

1953

deposit broken glass alongside the iron post, for witness.

46.40 State Highway No. 72, Bouse to Parker, bears E. and W.

47.10 Power line, bears E. and W.

57.10 Telephone line, bears E. and W.

57.80 A. T. & S. F. Railroad, bears E. and W.

Subdivision of T. 8 N., R. 18 W.

Chains
80.00

Point for the cor. of secs. 29, 30, 31 and 32.

Set an iron post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.

T 8 N	R 18 W
S 30	S 29
S 31	S 32
1953	

deposit broken glass alongside the iron post, for witness.

Land, low rolling sand dunes.

Soil, sandy clay.

Timber, none; underbrush, ocotillo and cacti.

From the cor. of secs. 28, 29, 32 and 33.

S. 89° 55' W., bet. secs. 29 and 32.

Over low rolling sand dunes.

39.97

Point for the ¼ sec. cor. of secs. 29 and 32, at proportionate distance.

Set an iron post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.

S 29	
¼ ———	
S 32	
1953	

deposit broken glass alongside the iron post, for witness.

79.94

The cor. of secs. 29, 30, 31 and 32.

Land, low rolling sand dunes.

Soil, sandy clay.

Timber, none; underbrush, ocotillo and cacti.

S. 89° 56' W., bet. secs. 30 and 31.

Over low rolling sand dunes.

40.00

Point for the ¼ sec. cor. of secs. 30 and 31.

Set an iron post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.

S 30	
¼ ———	
S 31	
1953	

deposit broken glass alongside the iron post, for witness.

64.50

Intersect the W. bdy. of the Tp. at the cor. of secs. 25, 30, 31 and 36, previously described.

Land, low rolling sand dunes.

Soil, sandy clay.

Timber, none; underbrush, ocotillo and cacti.

Subdivision of T. 8 N., R. 18 W.

Chains


From the cor. of secs. 29, 30, 31 and 32.

N. 0° 03' W., bet. secs. 29 and 30.

Over low rolling sand dunes.

40.00 Point for the 1/4 sec. cor. of secs. 29 and 30.


Set an iron post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.



deposit broken glass alongside the iron post, for witness.

80.00 Point for the cor. of secs. 19, 20, 29 and 30.

Set an iron post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.



deposit broken glass alongside the iron post, for witness.

Land, low rolling sand dunes.

Soil, sandy clay.

Timber, none; underbrush, ocotillo and cacti.


From the cor. of secs. 20, 21, 28 and 29.

S. 89° 55' W., bet. secs. 20 and 29.

Over low rolling sand dunes.

39.95 Point for the 1/4 sec. cor. of secs. 20 and 29, at proportionate distance.

Set an iron post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.



deposit broken glass alongside the iron post, for witness.

79.90 The cor. of secs. 19, 20, 29 and 30.

Land, low rolling sand dunes.

Soil, sandy clay.

Timber, none; underbrush, ocotillo and cacti.

S. 89° 55' W., bet. secs. 19 and 30.

Over low rolling sand dunes.

40.00 Point for the 1/4 sec. cor. of secs. 19 and 30.

Subdivision of T. 8 N., R. 18 W.

Chains

Set an iron post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 24 ins. in the ground, with brass cap mkd.

S 19

$\frac{1}{4}$ ———

S 30

1953

deposit broken glass alongside the iron post, for witness.

64.40

Intersect the W. bdy. of the Tp. at the cor. of secs. 19, 24, 25 and 30, previously described.

Land, low rolling sand dunes.

Soil, sandy clay.

Timber, none; underbrush, ocotillo and cacti.

From the cor. of secs. 19, 20, 29 and 30.

N. $0^{\circ} 03'$ W., bet. secs. 19 and 20.

Over low rolling sand dunes.

40.00

Point for the $\frac{1}{4}$ sec. cor. of secs. 19 and 20.

Set an iron post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 24 ins. in the ground, with brass cap mkd.

$\frac{1}{4}$

S 19 | S 20

1953

deposit broken glass alongside the iron post, for witness.

80.00

Point for the cor. of secs. 17, 18, 19 and 20.

Set an iron post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 24 ins. in the ground, with brass cap mkd.

T 8 N R 18 W

S 18 | S 17

S 19 | S 20

1953

deposit broken glass alongside the iron post, for witness.

Land, low rolling sand dunes.

Soil, sandy clay.

Timber, none; underbrush, ocotillo and cacti.

From the cor. of secs. 16, 17, 20 and 21.

S. $89^{\circ} 57'$ W., bet. secs. 17 and 20.

Over low rolling sand dunes.

39.99

Point for the $\frac{1}{4}$ sec. cor. of secs. 17 and 20, at proportionate distance.

Set an iron post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 24 ins. in the ground, with brass cap mkd.

Subdivision of T. 8 N., R. 18 W.

Chains

$$\begin{array}{r} \text{S } 17 \\ \frac{1}{4} \text{ ---} \\ \text{S } 20 \\ 1953 \end{array}$$

deposit broken glass alongside the iron post, for witness.

79.98 The cor. of secs. 17, 18, 19, and 20.

Land, low rolling sand dunes.
Soil, sandy clay.
Timber, none; underbrush, ocotillo and cacti.

S. 89° 57' W., bet. secs. 18 and 19.

Over low rolling sand dunes.

40.00 Point for the $\frac{1}{4}$ sec. cor. of secs. 18 and 19.

Set an iron post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 24 ins. in the ground, with brass cap mkd.

$$\begin{array}{r} \text{S } 18 \\ \frac{1}{4} \text{ ---} \\ \text{S } 19 \\ 1953 \end{array}$$

deposit broken glass alongside the iron post, for witness.

64.30 Intersect the W. bdy. of the Tp. at the cor. of secs. 13, 18, 19, and 24, previously described.

Land, low rolling sand dunes.
Soil, sandy clay.
Timber, none; underbrush, ocotillo and cacti.

From the cor. of secs. 17, 18, 19, and 20.

N. 0° 03' W., bet. secs. 17 and 18.

Over low rolling sand dunes.

40.00 Point for the $\frac{1}{4}$ sec. cor. of secs. 17 and 18.

Set an iron post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 24 ins. in the ground, with brass cap mkd.

$$\begin{array}{r} \frac{1}{4} \\ \text{S } 18 \text{ | S } 17 \\ 1953 \end{array}$$

deposit broken glass alongside the iron post, for witness.

80.00 Point for the cor. of secs. 7, 8, 17, and 18.

Set an iron post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 24 ins. in the ground, with brass cap mkd.

$$\begin{array}{r} \text{T } 8 \text{ N } \text{ R } 18 \text{ W} \\ \text{S } 7 \text{ | S } 8 \\ \text{---} \\ \text{S } 18 \text{ | S } 17 \\ 1953 \end{array}$$

deposit broken glass alongside the iron post, for witness.

Subdivision of T. 8 N., R. 18 W.

Chains	<p>Land, low rolling sand dunes. Soil, sandy clay. Timber, none; underbrush, ocotillo and cacti.</p>
40.00	<p>From the cor. of secs. 8, 9, 16, and 17. S. 89° 57' W., bet. secs. 8 and 17. Over low rolling sand dunes. Point for the $\frac{1}{4}$ sec. cor. of secs. 8 and 17. Set an iron post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;"> $\frac{1}{4}$ $\frac{S\ 8}{S\ 17}$ 1953 </p> <p>deposit broken glass alongside the iron post, for witness.</p>
80.00	<p>The cor. of secs. 7, 8, 17, and 18. Land, low rolling sand dunes. Soil, sandy clay. Timber, none; underbrush, ocotillo and cacti.</p>
40.00	<p>S. 89° 57' W., bet. secs. 7 and 18. Over low rolling sand dunes. Point for the $\frac{1}{4}$ sec. cor. of secs. 7 and 18. Set an iron post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;"> $\frac{1}{4}$ $\frac{S\ 7}{S\ 18}$ 1953 </p> <p>deposit broken glass alongside the iron post, for witness.</p>
64.21	<p>Intersect the W. bdy. of the Tp. at the cor. of secs. 7, 12, 13, and 18, previously described. Land, low rolling sand dunes. Soil, sandy clay. Timber, none; underbrush, ocotillo and cacti.</p>
40.00	<p>From the cor. of secs. 7, 8, 17, and 18. N. 0° 03' W., bet. secs. 7 and 8. Over low rolling sand dunes. Point for the $\frac{1}{4}$ sec. cor. of secs. 7 and 8. Set an iron post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;"> $\frac{1}{4}$ S 7 S 8 1953 </p>

Subdivision of T. 8 N., R. 18 W.

Chains

deposit broken glass alongside the iron post, for witness.

80.00

Point for the cor. of secs. 5, 6, 7, and 8.

Set an iron post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 24 ins. in the ground, with brass cap mkd.

T 8 N R 18 W

S 6 | S 5

S 7 | S 8

1953

deposit broken glass alongside the iron post, for witness.

Land, low rolling sand dunes.

Soil, sandy clay.

Timber none; underbrush, ocotillo and cacti.

From the cor. of secs. 4, 5, 8, and 9.

S. $89^{\circ} 57'$ W., bet. secs. 5 and 8.

Over low rolling sand dunes.

39.99

Point for the $\frac{1}{4}$ sec. cor. of secs. 5 and 8, at proportionate distance.Set an iron post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 24 ins. in the ground, with brass cap mkd.

S 5

 $\frac{1}{4}$ ———

S 8

1953

deposit broken glass alongside the iron post, for witness.

79.98

The cor. of secs. 5, 6, 7, and 8.

Land, low rolling sand dunes.

Soil, sandy clay.

Timber, none; underbrush, ocotillo and cacti.

S. $89^{\circ} 54'$ W., bet. secs. 6 and 7.

Over low rolling sand dunes.

40.00

Point for the $\frac{1}{4}$ sec. cor. of secs. 6 and 7, ~~at proportionate distance~~Set an iron post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 24 ins. in the ground, with brass cap mkd.

S 6

 $\frac{1}{4}$ ———

S 7

1953

deposit broken glass alongside the iron post, for witness.

64.14

Intersect the W. bdy. of the Tp. at the cor. of secs. 1, 6, 7, and 12, previously described.

Subdivision of T. 8 N., R. 18 W.

Chains

Land, low rolling sand dunes.
Soil, sandy clay.
Timber, none; underbrush, ocotille and cacti.

N. 0° 03' W., bet. secs. 5 and 6.

Over low rolling sand dunes.

40.00

Point for the $\frac{1}{4}$ sec. cor. of secs. 5 and 6.

Set an iron post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 24 ins. in the ground, with brass cap mkd.

$\frac{1}{4}$
S 6 | S 5

1953

deposit broken glass alongside the iron post, for witness.

66.50

Wash, 30 lks. wide, 3 ft. deep, bourse W.

69.44

Intersect the Second Standard Parallel North.

Point for the closing cor. of secs. 5 and 6, T. 8 N., R. 18 W.

Set an iron post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 24 ins. in the ground, with brass cap mkd.

T 9 N R 18 W

S 32

S 6 | S 5

C C

T 8 N R 18 W

1954

deposit broken glass alongside the iron post, for witness.

From point of intersection the standard cor. of secs. 31 and 32, T. 9 N., R. 18 W., bears W., 1.53 chs. dist.

Land, low rolling sand dunes.

Soil, sandy clay.

Timber, none; underbrush, ocotille and cacti.

At a point mid-way between the closing cors. of secs. 4 and 5, and secs. 5 and 6, T. 8 N., R. 18 W., point for the $\frac{1}{4}$ sec. cor. of sec. 5.

Set an iron post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 24 ins. in the ground, with brass cap mkd.

$\frac{1}{4}$ S 5

1954

deposit broken glass alongside the iron post, for witness.

From this cor. the standard $\frac{1}{4}$ sec. cor. of sec. 32, bears W., 1.53 chs. dist.

BOOK 4491

Subdivision of T. 8 N., R. 18 W.

Chains

At a point 40 chs. W. in longitude from the closing cor. of secs. 5 and 6, point for the $\frac{1}{4}$ sec. cor. of sec. 6.

Set an iron post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 24 ins. in the ground, with brass cap mkd.

$\frac{1}{4}$ S 6

1954

deposit broken glass alongside the iron post, for witness.

From this cor. the standard $\frac{1}{4}$ sec. cor. of sec. 31, bears W., 1.53 chs. dist.

General Description

The land and soil found in T. 8 N., R. 18 W., is almost identical for the entire township. Consisting mostly of blow sand, some wash sand and gravel. Some ironwood and paloverde are found along the Bouse Wash, in the extreme south side of the township. The balance of the township is covered with scattering ocotille and cacti, with some greasewood. The lack of water and rainfall prohibits the use of this land to any extent. Occasionally there is sufficient rainfall in the fall or winter to afford good feed for livestock in the spring. The Atchison, Topeka & Santa Fe Railway, and State Highway No. 72 cross the extreme southern portion of this township. There are no other roads, and no one living within the boundaries of this township.

CERTIFICATE OF CADASTRAL ENGINEER

I, Donald E. Harding, HEREBY CERTIFY upon honor that, in pursuance of special instructions bearing date of the 9th. day of Oct., 1952,

I have surveyed the North, East and West Boundaries, and the subdivision of
T. 8 N., R. 18 W.

of the G & S R Meridian, in the State of Arizona, which are represented in the foregoing field notes as having been executed by me and under my direction; and that said survey has been made in strict conformity with said instructions, the Manual of Instructions for the Survey of the Public Lands of the United States, and in the specific manner described in the foregoing field notes.

May 24, 1955

Donald E. Harding
Donald E. Harding-Cadastral Engineer

CERTIFICATE OF APPROVAL

BUREAU OF LAND MANAGEMENT,

Washington, D. C., MAY 2 1956, 19

The foregoing field notes of the survey of the North, East and West Boundaries, and the
subdivision of T. 8 N., R. 18 W. of the Gila and Salt River Meridian, of Arizona.

executed by Donald E. Harding

having been critically examined and found correct, are hereby approved.

Earl G. Harrington
Chief, Division of Cadastral Engineering
Cadastral Engineering Staff Officer

CERTIFICATE OF TRANSCRIPT

I CERTIFY that the foregoing transcript of the field notes of the above-described surveys in T. 8 N.,
R. 18 W., G & S R, Ariz., is a true copy of the original field notes.

Chief, Division of Cadastral Engineering.