

UNITED STATES  
DEPARTMENT OF THE INTERIOR  
BUREAU OF LAND MANAGEMENT

Original

# FIELD NOTES

of the

Independent Resurvey of the Fourth Standard Parallel North

and a

Partial Subdivision

of

Township 17 North, Range 2 East

Of the Gila and Salt River Meridian,

In the State of Arizona

### EXECUTED BY

Leslie H. Godwin, Cartographer (Cadastral)

Phil D. Smith, Cartographic Survey Aid

Under special instructions dated February 15, April 2, 1956, which provided for the surveys included under Group No. 309 and 310, approved February 15, April 2, 1956 and assignment instructions dated February 15, April 2, 1956

Survey commenced March 7, 1956

Survey completed April 13, 1956

2  
18

BOOK 4500

# INDEX DIAGRAM

Township 17 North, Range 2 East

6	5	4	3	2	1					
7	8	9	10	11	12					
18	17	16	15	14	13					
19	20	21	22	23	24					
30	29	28	27	26	25					
		12	11	9	8					
31	32	12	33	10	34	9	35	7	36	6
5	5	4	3	2	1					

16-56770-1

..... Phil D. Smith

..... Leslie H. Godwin

## INDEP. RESURVEY OF THE 4TH STAN. PAR. N., T. 17 N., R. 2 E. (B)

Chains	<p>The west and north boundaries of the township were surveyed by J. B. Girard in 1902 and the east boundary of section 12 was surveyed by J. B. Wright in 1908. The south boundary, Fourth Standard Parallel North, was surveyed by J. B. McLaughlin in 1883. No subdivisional lines have been surveyed within this township.</p> <p>For the test of the instruments and methods used, see the notes for T. 17 N., R. 3 E., this Group.</p> <p>The geographic position for the southeast corner of this township is in latitude <math>34^{\circ} 48' 00''</math> N., and longitude <math>112^{\circ} 05' 39''</math> W., as determined from U.S.G.S. Quadrangle sheets.</p> <p>The magnetic declination of the township is <math>14\frac{1}{2}^{\circ}</math> E., as determined from U.S.G.S. Quadrangle sheets.</p> <hr/> <p>Beginning at the standard corner of Ts. 17 N., Rs. 2 and 3 E., as described in the notes of T. 17 N., R. 3 E., this Group.</p> <p>West, with the Independent Resurvey of the Fourth Standard Parallel North, along the south boundary of section 36, T. 17 N., R. 2 E., on a transit line describing the tangent.</p> <p>Over rolling, grassy land.</p> <p>Descend 50 feet over a general SW. slope, general SE. drainage.</p> <p>1.45 Four strand barb wire fence, bears N. &amp; S.</p> <p>25.15 Wash, 20 links wide, 6 foot deep, course SE., ascend 25 feet over east slope.</p> <p>27.10 Low spur, sloping south, descend 115 feet over general SW. slope.</p> <p>31.20 Road, track, bears N. &amp; S.</p> <p>31.80 Wash, 30 links wide, 20 feet deep, course SE., ascend 160 feet over general east slope.</p> <p>40.00 Point for the standard <math>\frac{1}{4}</math> section corner of section 36.</p> <p>Set an iron post, 30 inches long, <math>2\frac{1}{2}</math> inches diameter, 12 inches in the ground and in a mound of stone, 3 foot base to cap, with brass cap marked.</p> <div style="text-align: center;"> <p>S C</p> <p><math>\frac{1}{4}</math> S 36</p> <hr style="width: 50px; margin: 0 auto;"/> <p>1956</p> </div> <p>Thence ascend 20 feet over a general east slope.</p> <p>41.00 Road, track, bears N. &amp; S.</p> <p>42.60 Spur, sloping SE., descend 10 feet over west slope.</p> <p>47.75 Wash, 10 links wide, 10 foot deep, course SE., ascend 100 feet over SE. slope.</p> <p>61.00 Slope changes to east, thence ascend 300 feet to section corner.</p> <p>80.00 Point for the standard corner of sections 35 and 36, North 1 link from the tangent.</p> <p>Set an iron post, 30 inches long, <math>2\frac{1}{2}</math> inches diameter, 8 inches in the ground and in a mound of stone, 4 foot base to cap, with brass cap marked.</p>
--------	---

INDEP: RESURVEY OF THE 4TH STAN. PAR. N., T. 17 N., R. 2 E.

Chains	<p style="text-align: center;">S C T 17 N R 2 E <u>S 35   S 36</u> 1956</p> <p>Raise a mound of stone, 4 foot base, 3 foot high, north of corner.</p> <p>Land: Rolling. Soil: Rocky. Timber: Scattered Juniper. Undergrowth: Dense bunch-grass, salt grass and cacti.</p>
	<p>West, along the south boundary of section 35, on a transit line describing the tangent, which bears S. 89° 59.4' W.</p>
	<p>Ascend 230 feet over NE. slope.</p>
12.00	<p>Spur, sloping SE., descend 280 feet over general SW. slope.</p>
35.60	<p>Road, track, bears NW. &amp; SE.</p>
39.00	<p>Wash, 20 links wide, 15 foot deep, course SSE.</p>
40.00	<p>Point for the standard <math>\frac{1}{4}</math> section corner of section 35, North 2 links from the tangent.</p>
	<p>Set an iron post, 30 inches long, <math>2\frac{1}{2}</math> inches diameter, 12 inches in the ground and in a mound of stone, 3 foot base to cap, with brass cap marked.</p>
	<p style="text-align: center;">S C <math>\frac{1}{4}</math> <u>S 35</u> 1956</p>
	<p>Raise a mound of stone, 4 foot base, 3 foot high, north of corner.</p>
40.40	<p>Same road, bears N. &amp; S., thence ascend 525 feet over general NE. slope.</p>
63.00	<p>Ridge, bears NW. &amp; SE., descend 180 feet over general SW. slope,</p>
78.00	<p>Wash, 10 links wide, 2 foot deep, course south.</p>
80.00	<p>Point for the standard corner of sections 34 and 35, North 3 links from the tangent.</p>
	<p>Set an iron post, 30 inches long, <math>2\frac{1}{2}</math> inches diameter, 12 inches in the ground and in a mound of stone, 3 foot base to cap, with brass cap marked.</p>
	<p style="text-align: center;">S C T 17 N R 2 E <u>S 34   S 35</u> 1956</p>
	<p>Raise a mound of stone, 3 foot base, 2 foot high, north of corner.</p>
	<p>Land: Rolling, with scattered outcroppings of malpai stone. Soil: Rocky. Timber: None. Undergrowth: Dense bunch-grass, salt grass and cacti.</p>

## INDEP. RESURVEY OF THE 4TH STAN. PAR. N., T. 17 N., R. 2 E.

Chains.	West, along the south boundary of section 34, on a transit line describing the tangent, which bears S. $89^{\circ} 58.8'$ W.  Ascend 55 feet over general NE. slope, general drainage SE.
1.90	Four strand barb wire fence, bears N. and S.
3.20	Flat top spur, sloping SE., descend 105 feet over general SW. slope.
11.50	Dim road, bears NW. and SE.
20.00	Wash, 10 links wide, 2 feet deep, course SE., ascend 40 feet over SE. slope.
23.00	Slope changes to NE., thence ascend 380 feet.
28.00	Bakers Pass bears north, approximately 5 chains.
40.00	Point for the standard $\frac{1}{4}$ section corner of section 34, North 4 links from the tangent.  Set an iron post, 30 inches long, $2\frac{1}{2}$ inches diameter, 6 inches in the ground to bedrock and in a mound of stone, 4 foot base to cap, with brass cap marked
	S C  $\frac{1}{4}$ <u>S 34</u> 1956
	Corner is located on top of ascent on north slope.  General drainage changes to north, thence descend 260 feet over general west slope of mountain.
53.50	Red sandstone ledge, facing west.
55.00	Enter moderate scrub oak brush.
60.00	Foot of mountain, bears NE. and SW., thence over rolling land, descend 20 feet over SSW. slope.
75.00	Wash, 10 links wide, 2 feet deep, course N. $30^{\circ}$ E., ascend 55 feet over gentle east slope.
80.00	Point for the standard corner of sections 33 and 34, North 6 links from tangent.  Set an iron post, 30 ins. long, $2\frac{1}{2}$ inches diameter, over a X cut in solid limestone and in a mound of stone, 4 foot base to cap, with brass cap marked

S C  
  
T 17 N R 2 E  
S 33 | S 34  
1956

Land: Rolling.  
Soil: Rocky.  
Timber: Scattered Juniper, west one-half mile.  
Undergrowth: Dense bunch-grass, moderate scrub oak and cacti.

INDEP. RESURVEY OF THE 4TH STAN. PAR. N., T. 17 N., R. 2 E.

Chains	
	West, along the south boundary of section 33, on a transit line describing the tangent, which bears S. 89° 58.2' W.
	Over rolling land.
	Ascend 55 feet over NE. slope.
8.90	Spur, sloping NNW., descend 150 feet over general SW. slope.
23.50	Wash, 20 links wide, 3 feet deep, course N. 20° W.
24.00	Four strand barb wire fence, bears NE. and SW.
28.50	Same fence, bears NW. and SE.
32.75	Wash, 25 links wide, 4 feet deep, course north, thence ascend 60 feet over NE. slope.
34.55	Road, track, bears N. 20° E. and S. 20° W.
35.00	Horseshoe tank, bears south, 8 chains distant.
40.00	Point for the standard $\frac{1}{4}$ section corner of section 33, North 8 links from tangent.
	Set an iron post, 30 ins. long, $2\frac{1}{2}$ ins. diameter, 6 ins. in the ground to bedrock and in a mound of stone, 4 foot base to cap, with brass cap marked
	S C $\frac{1}{4}$ — S 33 1956
	Thence over rolling land.
46.50	Horseshoe Canyon, 20 links wide, 7 feet deep, course north, ascend 155 feet over general east slope.
66.35	Spur, sloping north, descend 180 feet over general west slope.
80.00	Point for the standard corner of sections 32 and 33, North 11 links from tangent.
	Set an iron post, 30 inches long, $2\frac{1}{2}$ inches diameter, 10 inches in the ground and in a mound of stone, 5 foot base to cap, with brass cap marked
	S C T 17 N R 2 E S 32   S 33 1956
	Land: Rolling.
	Soil: Sandy, rocky.
	Timber: Scattered Juniper.
	Undergrowth: Dense bunch-grass, salt grass, and moderate cacti.
	West, along the south boundary of section 32, on a transit line describing the tangent, which bears S. 89° 57.6' W.
	Over rolling land.
.50	Wash, 10 links wide, 2 feet deep, course north, ascend 130 feet over east slope.

## INDEP. RESURVEY OF THE 4TH STAN. PAR. N., T. 17 N., R. 2 E.

Chains	
17.60	Spur, sloping south, descend 115 feet over general west slope.
27.90	Draw, draining north, ascend 45 feet over east slope.
36.40	Spur, sloping north, descend 10 feet over west slope.
39.00	Draw, draining N. 20° E.
40.00	Point for the standard $\frac{1}{4}$ section corner of section 32, North 14 links from the tangent.  Set an iron post, 30 inches long, $2\frac{1}{2}$ inches diameter, over an X cut in solid limestone and in a mound of stone, 4 foot base to cap, with brass cap marked.  $\begin{array}{c} S C \\ \frac{1}{4} S 32 \\ \hline 1956 \end{array}$ Thence ascend 140 feet over rolling east slope.
50.00	Spur, sloping north, descend 190 feet over rolling west slope.
75.00	Wash, 15 links wide, 3 foot deep, course NW., ascend 40 feet over general NE. slope.
80.00	Point for the standard corner of sections 31 and 32, North 18 links from the tangent.  Set an iron post, 30 inches long, $2\frac{1}{2}$ inches diameter, 6 inches in the ground to bedrock and in mound of stone, 4 foot base to cap, with brass cap marked.  $\begin{array}{c} S C \\ T 17 N R 2 E \\ S 31   S 32 \\ \hline 1956 \end{array}$ Land: Rolling. Soil: Sandy, rocky. Timber: Moderate Juniper. Undergrowth: Dense bunch-grass, gramma grass, bitter brush, moderate mountain mahogany and cacti.
	West, along the south boundary of section 31, on a transit line describing the tangent, which bears S. 89° 57.0' W.  Over rolling land, general NW. drainage.
.50	Spur, sloping NW., descend 70 feet over general SW. slope.
4.50	Wash, 20 links wide, 12 foot deep, course north, ascend 150 feet over ENE. slope.
20.00	Spur, sloping north, descend 200 feet over general west slope.
32.75	Road, graded, bears NW. & SE.
40.00	Point for the standard $\frac{1}{4}$ section corner of section 31, North 21 links from the tangent.  Set an iron post, 30 inches long, $2\frac{1}{2}$ inches diameter, 10 inches in the ground and in a mound of stone, 3 foot base to cap, with brass cap marked.

INDEP. RESURVEY OF THE 4TH STAN. PAR. N., T. 17 N., R. 2 E.

Chains

S C  
 $\frac{1}{4}$  S 31  
 1956

41.00 Road, track, bears N. and SW.

42.00 Wash, 10 links wide, 2 foot deep, course NW., thence over rolling land.

86.80 Point for the standard corner of T. 17 N., R. 2 E., North 25 links from the tangent.

Set an iron post, 30 inches long, 2 $\frac{1}{2}$  inches diameter, 6 inches in the ground to bedrock and in a mound of stone, 5 foot base to cap, with brass cap marked.

S C  
 T 17 N  
 R 2 E  
 S 31  
 1956

From the above point, the standard corner of Ts. 17 N., Rs. 1 and 2 E., bears North, 2.03 chains distant, which is monumented with a limestone, 18"x10"x8" marked with 6 notches on the east and west faces and S C on the north face, as the corner now becomes the corner of T. 17 N., R. 1 E., only, 1 remonument.

Set an iron post, 30 inches long, 2 $\frac{1}{2}$  inches diameter, 8 inches in the ground and in mound of stone, 4 foot base to cap, with brass cap marked.

S C  
 T 17 N  
 R 1 E  
 S 36  
 1956

Deposit original corner stone alongside of iron post.

Land: Rolling.  
 Soil: Sandy, rocky.  
 Timber: Scattered Juniper.  
 Undergrowth: Dense bunch-grass, some gramma and cacti.

Partial Subdivision of T. 17 N., R. 2 E.

From the standard corner of Ts. 17 N., Rs. 2 and 3 E.

North, between sections 31 and 36, Rs. 2 and 3 E.

Over high rolling land.

Ascend 80 feet over rocky, general SW. slope.

10.00 Flat top spur, sloping NE., descend 60 feet over rocky, general north slope.

15.60 Four strand barb wire fence, bears NE., & SW. approximately 3 chains thence south.

29.30 Wash, 30 links wide, 3 foot deep, course ENE., ascend 130 feet over south slope.

## Partial Subdivision of T. 17 N., R. 2 E.

Chains  
40.00Point for the  $\frac{1}{4}$  section corner of sections 31 and 36.Set an iron post, 30 inches long,  $2\frac{1}{2}$  inches diameter, 6 inches in the ground to bedrock and in a mound of stone, 4 foot base to cap, with brass cap marked.
$$\begin{array}{c} \frac{1}{4} \\ \text{S } 36 \text{ | S } 31 \\ 1956 \end{array}$$

Thence over rolling land, general east slope.

44.20

Four strand barb wire fence, bears E. and W.

55.60

Leave rolling land, descend 160 feet over NW. slope.

60.40

Wash, 30 links wide, 3 foot deep, course NE.

66.80

Wash, 30 links wide, 6 foot deep, course SE., ascend 45 feet over general south slope.

70.00

Slope changes to SW.

71.40

Draw, draining SSW., ascend 160 feet over SW. slope.

80.00

Point for the corner of sections 25, 30, 31 and 36.

Set an iron post, 30 inches long,  $2\frac{1}{2}$  inches diameter, 10 inches in the ground and in a mound of stone, 4 foot base to cap, with brass cap marked.
$$\begin{array}{c} \text{T } 17 \text{ N} \\ \text{R } 2 \text{ E} \text{ | R } 3 \text{ E} \\ \text{S } 25 \text{ | S } 30 \\ \hline \text{S } 36 \text{ | S } 31 \\ 1956 \end{array}$$

Land: Rolling.

Soil: Rocky.

Timber: None.

Undergrowth: Moderate to dense bunch-grass and cacti.

From the standard corner of sections 35 and 36.

N.  $0^{\circ} 01'$  W., between sections 35 and 36.

Over rolling land, general SE. drainage.

Descend 360 feet over NE. slope.

20.20

Wash, 15 links wide, 10 foot deep, course SE., ascend 140 feet over SW. slope.

29.45

Spur, sloping SE., descend 45 feet over NE. slope.

33.40

Wash, 30 links wide, 4 foot deep, course SE., ascend 80 feet over SW. slope.

40.00

Point for the  $\frac{1}{4}$  section corner of sections 35 and 36.Set an iron post, 30 inches long,  $2\frac{1}{2}$  inches diameter, 6 inches in the ground to bedrock and in a mound of stone, 3 foot base to cap, with brass cap marked.

Partial Subdivision of T. 17 N., R. 2 E.

Chains	<div style="text-align: center;"> <math>\frac{1}{4}</math>  <table style="margin: auto; border-collapse: collapse;"> <tr> <td style="border-right: 1px solid black; padding: 0 5px;">S 35</td> <td style="padding: 0 5px;">S 36</td> </tr> <tr> <td colspan="2" style="text-align: center; padding: 5px 0;">1956</td> </tr> </table> </div> <p>Thence over rolling land, general SW. slope.</p> <p>53.95 Four strand barb wire fence, bears E. and W.</p> <p>63.00 Ridge, bears NW. and SE., ascend 380 feet over general east slope.</p> <p>80.00 Point for the corner of sections 25, 26, 35 and 36.</p> <p>Set an iron post, 30 inches long, <math>2\frac{1}{2}</math> inches diameter, 6 inches in the ground to bedrock and in a mound of stone, 4 foot base to cap, with brass cap marked.</p> <div style="text-align: center; margin-top: 20px;"> <table style="margin: auto; border-collapse: collapse;"> <tr> <td colspan="2" style="padding: 5px 0;">T 17 N R 2 E</td> </tr> <tr> <td style="border-right: 1px solid black; padding: 0 5px;">S 26</td> <td style="padding: 0 5px;">S 25</td> </tr> <tr> <td style="border-right: 1px solid black; padding: 0 5px;">S 35</td> <td style="padding: 0 5px;">S 36</td> </tr> <tr> <td colspan="2" style="text-align: center; padding: 5px 0;">1956</td> </tr> </table> </div> <p>Corner is located 2 chains below spur top.</p> <p>Land: High rolling and broken.          Soil: Rocky.          Timber: None.          Undergrowth: Dense bunch-grass and moderate cacti.</p> <hr/> <p>From the corner of sections 25, 30, 31 and 36, on the east boundary of the township.</p> <p>N. 89° 56' W., between sections 25 and 36.</p> <p>Over rolling to broken land, general drainage SE.</p> <p>Descend 95 feet over SW. slope.</p> <p>12.80 Wash, 25 links wide, 4 foot deep, course SE., ascend 145 feet over NE. slope.</p> <p>17.30 Flat top spur, sloping SE., descend 60 feet over SW. slope.</p> <p>24.90 Wash, 20 links wide, 6 foot deep, course SE., ascend 200 feet over rolling ESE. slope.</p> <p>40.00 Point for the <math>\frac{1}{4}</math> section corner of sections 25 and 36.</p> <p>Set an iron post, 30 inches long, <math>2\frac{1}{2}</math> inches diameter, 4 inches in the ground to bedrock and in a mound of stone, 4 foot base to cap, with brass cap marked.</p> <div style="text-align: center; margin-top: 20px;"> <table style="margin: auto; border-collapse: collapse;"> <tr> <td style="padding: 0 5px;"><math>\frac{1}{4}</math></td> <td style="border-top: 1px solid black; border-right: 1px solid black; padding: 0 5px;">S 25</td> </tr> <tr> <td style="padding: 0 5px;"></td> <td style="border-right: 1px solid black; padding: 0 5px;">S 36</td> </tr> <tr> <td colspan="2" style="text-align: center; padding: 5px 0;">1956</td> </tr> </table> </div> <p>Thence ascend 170 feet across south slope.</p> <p>51.00 Rock ledge, facing south, on point of low spur, sloping south, thence across bench.</p> <p>57.70 Wash, 10 links wide, 10 foot deep, course SE., thence ascend 365 feet over general east slope.</p>	S 35	S 36	1956		T 17 N R 2 E		S 26	S 25	S 35	S 36	1956		$\frac{1}{4}$	S 25		S 36	1956	
S 35	S 36																		
1956																			
T 17 N R 2 E																			
S 26	S 25																		
S 35	S 36																		
1956																			
$\frac{1}{4}$	S 25																		
	S 36																		
1956																			

## Partial Subdivision of T. 17 N., R. 2 E.

Chains  
80.00

The corner of sections 25, 26, 35 and 36.

Land: Rolling to broken.

Soil: Rocky.

Timber: None.

Undergrowth: Dense bunch-grass, scattered cacti.

From the standard corner of sections 34 and 35.

N. 0° 01' W., between sections 34 and 35.

Ascend 200 feet over steep, rocky, south slope.

3.50

Four strand barb wire fence, bears NE. &amp; SW.

9.00

Top of ascent on ridge, bears N. &amp; SE., thence along east edge of ridge.

40.00

Point for the  $\frac{1}{4}$  section corner of sections 34 and 35.Set an iron post, 30 inches long,  $2\frac{1}{2}$  inches diameter, 6 inches in the ground to bedrock and in a mound of stone, 4 foot base to cap, with brass cap marked.
$$\begin{array}{c} \frac{1}{4} \\ \text{S } 34 \mid \text{S } 35 \\ 1956 \end{array}$$

44.00

Top of ridge, bears NE. and S., descend 255 feet over NNW. slope.

59.50

Four strand barb wire fence, bears NW. &amp; SE.

68.00

Stock trail, bears NW. &amp; SE.

73.50

Spur of ridge, sloping NW., thence descend 70 feet over ENE. slope.

80.00

Point for the corner of sections 26, 27, 34 and 35.

Set an iron post, 30 inches long,  $2\frac{1}{2}$  inches diameter, 4 inches in the ground to bedrock and in a mound of stone, 4 foot base to cap, with brass cap marked.
$$\begin{array}{c} \text{T } 17 \text{ N } \text{R } 2 \text{ E} \\ \text{S } 27 \mid \text{S } 26 \\ \hline \text{S } 34 \mid \text{S } 35 \\ 1956 \end{array}$$

Land: Rolling.

Soil: Rocky.

Timber: None.

Undergrowth: Dense bunch-grass, cacti, moderate oak brush.

From the corner of sections 25, 26, 35 and 36.

N. 89° 59' W., between sections 26 and 35.

Over rolling and broken land.

Ascend 20 feet over SE. slope.

5.25

Spur, sloping NE., descend 125 feet across north slope.

Partial Subdivision of T. 17 N., R. 2 E.

Chains 40.01	<p>Point for the <math>\frac{1}{4}</math> section corner of sections 26 and 35.</p> <p>Set an iron post, 30 inches long, <math>2\frac{1}{2}</math> inches diameter, 6 inches in the ground to bedrock and in a mound of stone, 4 foot base to cap, with brass cap marked.</p> <div style="text-align: center;"> <math>\frac{1}{4}</math> <table style="margin-left: auto; margin-right: auto;"> <tr><td style="border-bottom: 1px solid black;">S 26</td></tr> <tr><td>S 35</td></tr> <tr><td>1956</td></tr> </table> </div> <p>Slope changes to NW., descend 65 feet.</p>	S 26	S 35	1956	
S 26					
S 35					
1956					
44.00	Wash, 10 links wide, 10 foot deep, course NE., ascend 150 feet over NE. slope.				
60.00	Spur, sloping north, descend 50 feet over general west slope.				
65.40	Wash, 10 links wide, 10 foot deep, course north, ascend 145 feet over ENE. slope.				
75.80	Spur, sloping NE., descend 20 feet over general NW. slope.				
80.02	<p>The corner of sections 26, 27, 34 and 35.</p> <p>Land: Rolling and broken. Soil: Rocky. Timber: Scattered Juniper, some Pinion. Undergrowth: Dense bunch-grass, bear grass, moderate cacti.</p>				
	<p>From the standard corner of sections 33 and 34.</p> <p>N. 0° 02' W., between sections 33 and 34.</p> <p>Over rolling land, general north slope.</p> <p>Descend 150 feet over general north slope.</p>				
25.00	Wash, 10 links wide, 3 foot deep, course NE., ascend 45 feet over SSW. slope.				
34.80	Knoll, descend 70 feet over general north slope.				
40.00	<p>Point for the <math>\frac{1}{4}</math> section corner of sections 33 and 34.</p> <p>Set an iron post, 30 inches long, <math>2\frac{1}{2}</math> inches diameter, 12 inches in the ground and in a mound of stone, 3 foot base to cap, with brass cap marked.</p> <div style="text-align: center;"> <math>\frac{1}{4}</math> <table style="margin-left: auto; margin-right: auto;"> <tr><td>S 33</td><td style="border-left: 1px solid black; border-right: 1px solid black;">S 34</td></tr> <tr><td colspan="2">1956</td></tr> </table> </div> <p>Thence descend 45 feet over NNW. slope.</p>	S 33	S 34	1956	
S 33	S 34				
1956					
45.65	Wash, 10 links wide, 4 foot deep, course NE., continue to descend 60 feet over NW. slope.				
60.30	Wash, 10 links wide, 6 foot deep, course NE., ascend 20 feet over SE. slope.				
76.85	Spur, sloping NE., descend 10 feet over NW. slope.				
80.00	Point for the corner of sections 27, 28, 33 and 34.				

## Partial Subdivision of T. 17 N., R. 2 E.

Chains Set an iron post, 30 inches long,  $2\frac{1}{2}$  inches diameter, 10 inches in the ground and in a mound of stone, 3 foot base to cap, with brass cap marked.

T 17 N R 2 E  
 S 28 | S 27  
 S 33 | S 34  
 1956

Land: Rolling.

Soil: Dandy loam, some decomposed limestone.

Timber: Scattered Juniper.

Undergrowth: Dense bunch-grass, gramma grass, moderate cacti..

From the corner of sections 26, 27, 34 and 35.

N.  $89^{\circ} 55'$  W., between sections 27 and 34.

Over rolling land, general west slope.

Descend 95 feet over general west slope.

10.75 Five strand barb wire fence, bears N. & S.

16.55 Five strand barb wire fence, bears N. & S.

25.75 Wash, 20 links wide, 6 foot deep, course north, Cathen Dam bears south, 2 chains.

40.00 Point for the  $\frac{1}{4}$  section corner of sections 27 and 34.

Set an iron post, 30 inches long,  $2\frac{1}{2}$  inches diameter, 8 inches in the ground and in a mound of stone, 3 foot base to cap, with brass cap marked.

$\frac{1}{4}$  S 27  
 S 34  
 1956

Thence descend 25 feet over west slope.

50.40 Wash, 20 links wide, 6 foot deep, course north, ascend 45 feet over east slope.

55.70 Spur, sloping north, descend 90 feet over WNW. slope.

62.00 Wash, 20 links wide, 6 foot deep, course NE., ascend 155 feet over SE. slope with scattered outcroppings of red sandstone.

80.00 The corner of sections 27, 28, 33 and 34.

Land: Rolling, with some scattered outcroppings of red sandstone.


Soil: Sandy loam, some decomposed sandstone.

Timber: Scattered Juniper.


Undergrowth: Dense bunch-grass, gramma grass, moderate cacti.

Partial Subdivision of T. 17 N., R. 2 E.

Chains From the standard corner of sections 32 and 33.  
 N. 0° 02' W., between sections 32 and 33.  
 Over rolling land, general NW. drainage.  
 Ascend 70 feet over gradual, general south slope.  
 22.85 Spur, sloping NW., descend 120 feet over NE. slope.  
 34.40 Wash, 10 links wide, 3 foot deep, course NW., ascend 25 feet over SW. slope.  
 40.00 Point for the  $\frac{1}{4}$  section corner of sections 32 and 33.  
 Set an iron post, 30 inches long,  $2\frac{1}{2}$  inches diameter, 6 inches in the ground to bedrock and in a mound of stone, 3 foot base to cap, with brass cap marked.



Thence ascend 30 feet over SW. slope.  
 44.50 Spur, sloping NW., descend 155 feet over NE. slope.  
 53.75 Road, graded, bears E. & W.  
 58.30 Wash, 10 links wide, 5 foot deep, course NW., ascend 120 feet over SW. slope.  
 72.35 Spur, sloping WNW., descend 90 feet over NNE. slope.  
 80.00 Point for the corner of sections 28, 29, 32 and 33.  
 Set an iron post, 30 inches long,  $2\frac{1}{2}$  inches diameter, 10 inches in the ground and in a mound of stone, 4 foot base to cap, with brass cap marked.



Land: Rolling.  
 Soil: Sandy loam, some decomposed limestone.  
 Timber: Moderate to scattered Juniper.  
 Undergrowth: Dense bunch-grass, gramma grass, moderate oak brush and cacti.

From the corner of sections 27, 28, 33 and 34.  
 N. 89° 57' W., between sections 28 and 33.  
 Over rolling land, general drainage NW.  
 Ascend 85 feet over general east slope.  
 5.30 Spur, sloping north, descend 65 feet over west slope.  
 11.55 Wash, 10 links wide, 6 foot deep, course north, ascend 50 feet over east slope.

Partial Subdivision of T. 17 N., R. 2 E.

Chains

- 16.55 Spur, sloping north, descend 190 feet over west slope.
- 26.20 Wash, 10 links wide, 5 foot deep, course north, ascend 65 feet over east slope.
- 35.20 Spur, sloping north, descend 15 feet over west slope.
- 38.80 Wash, 10 links wide, 4 foot deep, course north.
- 39.99 Point for the  $\frac{1}{4}$  section corner of sections 28 and 33.  
 Set an iron post, 30 inches long,  $2\frac{1}{2}$  inches diameter, 6 inches in the ground to bedrock and in a mound of stone, 4 foot base to cap, with brass cap marked.  

$\frac{1}{4}$   $\frac{S\ 28}{S\ 33}$   
 1956

 Thence ascend 55 feet over east slope.
- 45.00 Spur, sloping north, descend 145 feet over west slope.
- 56.70 Wash, 30 links wide, 3 foot deep, course north, ascend 185 feet over east slope.
- 62.00 Road, graded, bears N. & S.
- 74.40 Spur, sloping north, descend 75 feet over west slope.
- 79.98 The corner of sections 28, 29, 32 and 33.

Land: Rolling.  
 Soil: Sandy loam, some decomposed limestone.  
 Timber: Moderate Juniper.  
 Undergrowth: Dense bunch-grass, gramma grass, moderate cacti and oak brush.

General Description

The land contained in the partial subdivision of Township 17 North, Range 2 East, is principally rolling land. The general drainage in sections 35 and 36 is to the southeast, with the general drainage in sections 33 and 34 being to the north. There is good grazing throughout the major portion of the land, with a moderate amount of timber in sections 33 and 34. The general elevation ranges from a low of 4300 in the southeast corner of section 36 to a high of 5400 in the S.  $\frac{1}{2}$  mile between sections 34 and 35. There are numerous roads within the township, with these roads running, generally, north and south. There is no water or wells within the portion surveyed.

19

4-680  
(Feb., 1950)

UNITED STATES  
DEPARTMENT OF THE INTERIOR  
BUREAU OF LAND MANAGEMENT

FIELD ASSISTANTS

NAMES	CAPACITY
Alburn D. Griffin	Notekeeper
Deon J. Allen	Notekeeper
Paul G. Bauer	Chainman
Freddy H. Jones	Chainman
Charley Avants	Flagman
Robert R. Mitchell	Flagman
John J. Trammel	Truck driver
Andrew M. Nelson	Truck driver

18  
15

CERTIFICATE OF CADASTRAL ENGINEER

We  
I, Leslie H. Godwin and Phil D. Smith, HEREBY CERTIFY upon honor that, in  
pursuance of special instructions bearing date of the 15 and 2 day of ~~February~~ and April, 1956  
We  
I have surveyed the Independent Resurvey of the Fourth Standard Parallel North, and a  
Partial Subdivision of Township 17 North, Range 2 East.

of the Gila & Salt River Meridian, in the State of Arizona, which are  
represented in the foregoing field notes as having been executed by me and under my direction; and that  
said survey has been made in strict conformity with said instructions, the Manual of Instructions for the  
Survey of the Public Lands of the United States, and in the specific manner described in the foregoing  
field notes.

Salt Lake City, Utah  
Salt Lake City, Utah

Leslie H. Godwin  
Phil D. Smith

CERTIFICATE OF APPROVAL

BUREAU OF LAND MANAGEMENT,  
Washington, D. C., AUG 14 1956, 19

The foregoing field notes of the survey of the Independent Resurvey of the Fourth Standard  
Parallel North, and a Partial Subdivision of Township 17 North, Range 2 East.

executed by Leslie H. Godwin and Phil D. Smith  
having been critically examined and found correct, are hereby approved.

Earl S. Harrington  
Cadastral Engineering Staff Officer.

CERTIFICATE OF TRANSCRIPT

I CERTIFY that the foregoing transcript of the field notes of the above-described surveys in  
, is a true copy of the original field notes.

Cadastral Engineering Staff Officer.