

UNITED STATES
DEPARTMENT OF THE INTERIOR
BUREAU OF LAND MANAGEMENT

Original

FIELD NOTES

of the

Dependent Resurvey

of the

North, South, East, and West Boundaries

of

Township 8 South, Range 26 East

Of the Gila and Salt River Meridian,

In the State of Arizona

EXECUTED BY

Donald E. Harding, Cadastral Surveyor

Under special instructions dated January 13, 1956, which provided
for the surveys included under Group No. 299, approved January 13, 1956
and assignment instructions dated February 6, 1957.

Survey commenced February 28, 1957.

Survey completed March 15, 1957.

538
4538

4538

BOOK 4538

INDEX DIAGRAM

Township 8 South, Range 26 East

19 14 6	19 5	18 4	17 3	16 2	15 1 5
13 7	8	9	10	11	12 4
13 18	17	16	15	14	13 3
12 19	20	21	22	23	24 3
11 30	29	28	27	26	25 2
10 31 9	32 8	33 7	34 6	35 6	36 1 5

Township 8 South, Range 26 East

Chains

The four boundaries of this township were surveyed by T. F. White in 1874. The south boundary was resurveyed by Philip Contzen in 1904 in connection with the survey of T. 9 S., R. 26 E. The subdivisional lines were surveyed by T. F. White in 1874-1875.

The following field notes are those of the dependent resurvey of the north, south, east, and west boundaries of T. 8 S., R. 26 E. Resurvey of this township was requested by the BLM Range Manager in Charge, Arizona Grazing District No. 4, in a memorandum dated December 5, 1955.

The survey was executed with a W. and L. E. Gurley solar transit, serial number 541332, constructed in accordance with the standard instrumental specifications of the Bureau of Land Management. The instrument was in good condition and was placed in proper adjustment prior to the beginning of the survey.

The azimuth of all lines was established by control from triangulation station "Jones" which was established by the U.S.S.E.S. in 1935 and later occupied by the U. S. Coast and Geodetic Survey. The azimuth of the lines was checked from time to time throughout the survey by the direct solar method. The measurements were made with a Chicago steel tape, 8 chains in length, graduated every 1/10 link for the first 10 links, every link for the next 90 links, and every 10 links for the balance. The tape was tested by comparison with a standard tape and found correct. Measurements were made on the slope and the vertical angle of each interval was ascertained by a clinometer in good adjustment. The horizontal equivalents only are entered in this field note record.

The geographic position of the SE. corner of the township is, latitude $32^{\circ} 41' 10.328''$ N., longitude $109^{\circ} 37' 48.567''$ W. The mean magnetic declination is 13° East.

Dependent Resurvey of the East Boundary of T. 8 S., R. 26 E.

Reestablishment of the Survey Executed by T. F. White in 1874.
Note: No evidence was found of the original corners established in the survey of this line.

From the cor. of Ts. 8 and 9 S., Rs. 26 and 27 E., monumented with an iron post, set, mkd. and witnessed as described in the field notes of T. 8 S., R. 27 E.

N. $0^{\circ} 04'$ W., bet. secs. 31 and 36.

Over nearly level land, through dense undergrowth.

39.78

Point for the $\frac{1}{4}$ sec. cor. of secs. 31 and 36, at proportionate distance.

Set an iron post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 24 ins. in the ground, with brass cap mkd.

T8S
R26E R27E
 $\frac{1}{4}$
S36|S31
1957

Deposit broken glass at the base of the post for witness.

Dependent Resurvey of the East Boundary of T. 8 S., R. 26 E.

Chains

40.85

Small wash, drains NE.

79.56

Point for the cor. of secs. 25, 30, 31 and 36, at proportionate distance.

Set an iron post, 28 ins. long, 2½ ins. diam., 22 ins. in the ground, with brass cap mkd.

T8S
R26E | S27E
S25 | S30
S36 | S31
1957

Deposit broken glass at the base of the post for witness.

Land, level.

Soil, sandy loam.

Timber, none.

Undergrowth, dense greasewood, scattered mesquite, cacti, and sparse grass.

N. 0° 04' W., bet. secs. 25 and 30.

Over level land, through scattered undergrowth.

21.20

Small wash, drains N. 10° W.

39.78

Point for the ¼ sec. cor. of secs. 25 and 30, at proportionate distance.

Set an iron post, 28 ins. long, 2½ ins. diam., 22 ins. in the ground, with brass cap mkd.

T8S
R26E R27E
¼
S25 | S30
1957

Deposit broken glass at the base of the post for witness.

79.56

Point for the cor. of secs. 19, 24, 25 and 30, at proportionate distance.

Set an iron post, 28 ins. long, 2½ ins. diam., 22 ins. in the ground, with brass cap mkd.

T8S
R26E | R27E
S24 | S19
S25 | S30
1957

Deposit broken glass at the base of the post for witness.

Land, level.

Soil, sandy loam.

Timber, none.

Undergrowth, scattered greasewood, mesquite, cacti, and grass.

Dependent Resurvey of the East Boundary of T. 8 S., R. 26 E.

Chains

N. 0° 04' W., bet. secs. 19 and 24.

Over level land, through scattered undergrowth.

17.40 Low flat ridge, bears NE. and SW.

39.78 Point for the $\frac{1}{4}$ sec. cor. of secs. 19 and 24, at proportionate distance.Set an iron post, 28 ins. long, 2 $\frac{1}{2}$ ins. diam., 22 ins. in the ground, with brass cap mkd.T8S
R26E R27E $\frac{1}{4}$
S24|S19
1957

Deposit broken glass at the base of the post for witness.

45.40 Small wash, drains NW.

79.56 Point for the cor. of secs. 13, 18, 19 and 24, at proportionate distance.

Set an iron post, 28 ins. long, 2 $\frac{1}{2}$ ins. diam., 22 ins. in the ground, with brass cap mkd.T8S
R26E R27ES13|S18
S24|S19
1957

Deposit broken glass at the base of the post for witness.

Land, level.

Soil, sandy loam.

Timber, none.

Undergrowth, scattered greasewood, mesquite, cacti, and grass.

N. 0° 04' W., bet. secs. 13 and 18.

Over nearly level land, through scattered undergrowth.

3.80 Small wash, drains NW.

19.00 Corner of fences bearing N., S., and E., bears E., 1 lk. dist.

39.78 Point for the $\frac{1}{4}$ sec. cor. of secs. 13 and 18, at proportionate distance.Set an iron post, 28 ins. long, 2 $\frac{1}{2}$ ins. diam., 22 ins. in the ground, with brass cap mkd.T8S
R26E R27E $\frac{1}{4}$
S13|S18
1957

Deposit broken glass at the base of the post for witness.

Dependent Resurvey of the East Boundary of T. 8 S., R. 26 E.

Chains											
47.60	Small wash, drains NW.										
79.56	Point for the cor. of secs. 7, 12, 13 and 18, at proportionate distance. Set an iron post, 28 ins. long, 2½ ins. diam., 22 ins. in the ground, with brass cap mkd.										
	<table style="margin-left: auto; margin-right: auto;"> <tr><td colspan="2">T8S</td></tr> <tr><td>R26E</td><td>R27E</td></tr> <tr><td>S12</td><td>S 7</td></tr> <tr><td>S13</td><td>S18</td></tr> <tr><td colspan="2">1957</td></tr> </table>	T8S		R26E	R27E	S12	S 7	S13	S18	1957	
T8S											
R26E	R27E										
S12	S 7										
S13	S18										
1957											
	Deposit broken glass at the base of the post for witness.										
	From this corner, U.S.S.E.S. triangulation station "Jones" bears N. 52° 14' 10" E., 29.61 chs. dist. Geographic position of station "Jones" is latitude 32° 44' 51.150" N., longitude 109° 37' 30.477" W.										
	Land, level. Soil, sandy loam. Timber, none. Undergrowth, scattered greasewood, mesquite, cacti, and grass.										
39.78	N. 0° 04' W., bet. secs. 7 and 12. Over nearly level land, through scattered undergrowth. Point for the ¼ sec. cor. of secs. 7 and 12, at proportionate distance. Set an iron post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.										
	<table style="margin-left: auto; margin-right: auto;"> <tr><td colspan="2">T8S</td></tr> <tr><td>R26E</td><td>R27E</td></tr> <tr><td colspan="2">¼</td></tr> <tr><td>S12</td><td>S 7</td></tr> <tr><td colspan="2">1957</td></tr> </table>	T8S		R26E	R27E	¼		S12	S 7	1957	
T8S											
R26E	R27E										
¼											
S12	S 7										
1957											
	Deposit broken glass at the base of the post for witness.										
67.83	Corner of fences bearing N., S., and E.										
79.56	Point for the cor. of secs. 1, 6, 7 and 12, at proportionate distance. Set an iron post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.										
	<table style="margin-left: auto; margin-right: auto;"> <tr><td colspan="2">T8S</td></tr> <tr><td>R26E</td><td>R27E</td></tr> <tr><td>S 1</td><td>S 6</td></tr> <tr><td>S12</td><td>S 7</td></tr> <tr><td colspan="2">1957</td></tr> </table>	T8S		R26E	R27E	S 1	S 6	S12	S 7	1957	
T8S											
R26E	R27E										
S 1	S 6										
S12	S 7										
1957											
	Deposit broken glass at the base of the post for witness.										
	Land, level. Soil, sandy loam. Timber, none. Undergrowth, scattered greasewood, mesquite, cacti, and grass.										

Dependent Resurvey of the East Boundary of T. 8 S., R. 26 E.

Chains

N. 0° 04' W., bet. secs. 1 and 6.

Over nearly level land, through scattered undergrowth.

.80 Corner of fences bearing W. and S.

39.78 Point for the $\frac{1}{4}$ sec. cor. of secs. 1 and 6, at proportionate distance.Set an iron post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 22 ins. in the ground, with brass cap mkd.

T8S
R26E R27E
 $\frac{1}{4}$
S 1 | S 6
1957

Deposit broken glass at the base of the post for witness.

79.56 The cor. of Ts. 7 and 8 S., Rs. 26 and 27 E., monumented with an iron post, set, mkd. and witnessed as described in the field notes of T. 7 S., R. 27 E.

Land, level.

Soil, sandy loam.

Timber, none.

Undergrowth, scattered greasewood, mesquite, cacti and grass.

Dependent Resurvey of the South Boundary of T. 8 S., R. 26 E.

Reestablishment of the resurvey executed by Philip Contzen in 1904. From the cor. of Ts. 8 and 9 S., Rs. 26 and 27 E., monumented with an iron post, set, mkd. and witnessed as described in the field notes of T. 8 S., R. 27 E.

S. 89° 39' W., on the S. bdy. of sec. 36.

Over nearly level land, through scattered undergrowth.

39.73 Point for the $\frac{1}{4}$ sec. cor. of sec. 36, at proportionate distance; there is no remaining evidence of the original corner.Set an iron post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 22 ins. in the ground, with brass cap mkd.

T8S R26E
 $\frac{1}{4}$ S36

1957

Deposit broken glass at the base of the post for witness.

42.50 Wash, 15 lks. wide, 1 ft. deep, drains WSW.

79.37 The cor. of secs. 35 and 36, monumented with a partially rotted stake, firmly set in the ground.

At the corner point

Set an iron post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 22 ins. in the ground, with brass cap mkd.

Dependent Resurvey of the South Boundary of T. 8 S., R. 26 E.

Chains

T8S R26E

S35|S36

1957

Deposit broken glass at the base of the post for witness.

Land, level.

Soil, sandy loam.

Timber, none.

Undergrowth, scattered mesquite, tesota, greasewood, cacti, and sparse grass.

S. 89° 28' W., on the S. bdy. of sec. 35.

Over nearly level land, through scattered undergrowth.

39.96 Point for the $\frac{1}{4}$ sec. cor. of sec. 35, at proportionate position; there is no remaining evidence of the original corner.Set an iron post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 24 ins. in the ground, with brass cap mkd.

T8S R26E

 $\frac{1}{4}$ S35.

1957

Deposit broken glass at the base of the post for witness.

S. 89° 54' W., beginning new measurement.

7.10 Wash, 10 lks. wide, 1 ft. deep, drains N.

27.80 Wash, 30 lks. wide, 1 ft. deep, drains NNW.

34.40 Wash, 75 lks. wide, 2 ft. deep, drains NNW.

39.91 The cor. of secs. 34 and 35, monumented with a rotted stake in a mound of stone.

At the cornerpoint

Set an iron post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 22 ins. in the ground, with brass cap mkd.

T8S R26E

S34|S35

1957

Raise a small mound of stone, N. of cor.

Land, level.

Soil, sandy loam.

Timber, none.

Undergrowth, scattered mesquite, tesota, greasewood, cacti, and sparse grass.

S. 89° 57' W., on the S. bdy. of sec. 34.

Dependent Resurvey of the South Boundary of T. 8 S., R. 26 E.

Chains

Over nearly level land, through scattered undergrowth.

15.20 Wash, 75 lks. wide, 1 ft. deep, drains NNE.

21.30 Corner of fence bearing W. and S.

39.75 The $\frac{1}{2}$ sec. cor. of sec. 34, monumented with a partially rotted stake, firmly set in the ground.

At the corner point

Set an iron post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 20 ins. in the ground, with brass cap mkd.

T8S R26E

$\frac{1}{2}$ S34

1957

Deposit broken glass at the base of the post for witness.

N. $89^{\circ} 54'$ W., beginning new measurement.

6.10 Wash, 30 lks. wide, 2 ft. deep, drains N.

40.05 Point for the cor. of secs. 33 and 34, at proportionate position; there is no remaining evidence of the original corner.

Set an iron post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 23 ins. in the ground, with brass cap mkd.

T8S R26E

S33|S34

1957

Deposit broken glass at the base of the post for witness.

Land, level.

Soil, sandy loam.

Timber, none.

Undergrowth, scattered mesquite, tesota, greasewood, cacti, and sparse grass.

S. $89^{\circ} 58'$ W., on the S. bdy. of sec. 33.

Over nearly level land, through scattered undergrowth.

.30 Road, track, bears N. and S.

8.00 Earthen dam, bears N., 7 chs. dist.

39.65 Fence, bears N., 20 lks., thence E.; and S., 40 lks., thence W.

39.86 Point for the $\frac{1}{2}$ sec. cor. of sec. 33, at proportionate distance; there is no remaining evidence of the original corner.

Set an iron post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 26 ins. in the ground, with brass cap mkd.

Dependent Resurvey of the South Boundary of T. 8 S., R. 26 E.

Chains	
	<p>T8S R26E $\frac{1}{4}$ S33 <hr/> 1957</p>
	<p>Raise a mound of stone, 2½ ft. base, 2 ft. high, N. of cor. Corner is located on edge of curve in graded road bearing W. and N. Thence along center of graded road, with farming land N. of roadway.</p>
57.70	Well, with electric irrigation pump, on S. edge of dirt tank, bears N., 1 chain dist.
66.50	Old school building, bears N., 1 chain dist.
79.65	The cor. of secs. 32 and 33 as identified by the interested land owners as being the position accepted and used for the last several years.
	At the corner point
	Set a 12 inch spike in road bed.
	At a point 57 lks. North
	Set an iron post, 28 ins. long, 2½ ins. diam., 16 ins. in the ground, with brass cap mkd.
	<p>T8S R26E S32 S33 ↓ R M 1957</p>
	At a point 57 lks. South
	Set an iron post, 28 ins. long, 2½ ins. diam., 22 ins. in the ground, with brass cap mkd.
	<p>R M ↑ 1957</p>
	<p>Land, level. Soil, sandy loam. Timber, none. Undergrowth, scattered mesquite, greasewood, tesota, cacti, and sparse grass.</p>
	S. 89° 52' W., along the S. bdy. of sec. 32.
	Over level land; continue along center of graded road.
35.60	Farmhouse, bears N., 1 chain dist.
38.00	Highway right-of-way fence, bears N. and S.
38.60	U. S. Highway No. 666, bears N. and S.

Dependent Resurvey of the South Boundary of T. 8 S., R. 26 E.

Chains	
39.30	Highway right-of-way fence, bears N. and S.
39.45	Point for the $\frac{1}{4}$ sec. cor. of sec. 32, at proportionate distance; there is no remaining evidence of the original corner. Set an iron post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 26 ins. in the ground, with brass cap mkd. T8S R26E <u>$\frac{1}{4}$ S32</u> 1957 Raise a mound of stone, $2\frac{1}{2}$ ft. base, 2 ft. high, N. of cor.
44.80	Wash, 20 lks. wide, 5 ft. deep, drains N.
54.00	Road, track, bears NE. and SW.
54.50	Enter overflow bottom of Cienega Wash.
59.20	Power line, bears N. and S.
60.40	Main channel of Cienega Wash, 30 lks. wide, 2 ft. deep, drains N.
71.20	Fence, bears N. and S.
79.34	Point for the cor. of secs. 31 and 32, at proportionate distance; there is no remaining evidence of the original corner. Set an iron post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 24 ins. in the ground, with brass cap mkd. T8S R26E <u>S31 S32</u> 1957 Bury charcoal at the base of the post for witness. Land, level. Soil, sandy loam. Timber, none. Undergrowth, tesota and mesquite along banks of Cienega Wash.
	S. $89^{\circ} 52'$ W., along the S. bdy. of sec. 31. Over level farm land.
4.10	Fence, bears N. and S.
29.80	Leave farm land, bears NE. and SW.
30.40	Road, bladed, bears NE. and SW.; asc. 165 ft. over rocky SE. slope.
39.78	The $\frac{1}{4}$ sec. cor. of sec. 31, monumented with a sandstone 24x12x10 ins., properly mkd. as described in the official record. At the corner point Set an iron post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 8 ins. in the ground, and in a mound of stone, 4 ft. base to top, with brass cap mkd.

Dependent Resurvey of the South Boundary of T. 8 S., R. 26 E.

Chains

T8S R26E
¼ S31

1957

Place original corner stone alongside of post in the mound of stone.

S. 89° 47' W., beginning new measurement.

Asc. 105 ft. over rocky SE. slope.

3.80 E. edge of bench, bears NE. and SW.; asc. 90 ft. over E. slope, through dense undergrowth.

38.92 The cor. of Ts. 8 S., Rs. 25 and 26 E., monumented with a sandstone, 20x6x6 ins., properly mkd. as described in the official record.

At the corner point

Set an iron post, 28 ins. long, 2½ ins. diam., 15 ins. in the ground, and in a mound of stone, 3 ft. base to top, with brass cap mkd.

T8S
R25E | R26E
S36 | S31

1957

Place the original corner stone alongside the iron post in the mound of stone, and raise a mound of stone, 4 ft. base, 3 ft. high, N. of cor.

Land, level in east half, high rocky bench in west half.
Soil, sandy loam in east half, rocky clay in west half.
Timber, none.
Undergrowth, heavy greasewood in west half only.

Dependent Resurvey of the West Boundary of T. 8 S., R. 26 E.

Reestablishment of the Survey executed by T. F. White in 1874.
N. 0° 01' W., bet. secs. 31 and 36.

Desc. 70 ft. over NE. slope, through dense undergrowth.

13.60 Telephone line, single wire, bears NE. and SW.

16.10 Wash, 10 lks. wide, 6 ft. deep, drains NE.

37.00 Desc. 60 ft. over NW. slope.

39.97 Point for the ¼ sec. cor. of secs. 31 and 36, at proportionate distance; there is no remaining evidence of the original corner.

Set an iron post, 3 ft. long, 1 in. diam., 26 ins. in the ground, with brass cap mkd.

T8S
R25E R26E
¼
S36 | S31
1957

Dependent Resurvey of the West Boundary of T. 8 S., R. 26 E.

Chains

Raise a mound of stone, 4 ft. base, 3 ft. high, W. of cor.

From this corner, a dirt reservoir bears W., 1.50 chs. dist.

51.00 Small wash, drains NE.

62.40 Enter dense mesquite undergrowth, bears NE. and SW.

65.80 Wash, 25 lks. wide, 2 ft. deep, drains NE.

71.00 Small wash, drains NE.

75.10 Small wash, drains NE.

79.94 Point for the cor. of secs. 25, 30, 31 and 36, at proportionate distance; there is no remaining evidence of the original corner.

Set an iron post, 28 ins. long, 2½ ins. diam., 6 ins. in the ground, and in a mound of stone, 4 ft. base to top, with brass cap mkd.

T8S	
R25E	R26E
S25	S30
S36	S31
1957	

Land, rocky benches.

Soil, rocky clay.

Timber, none.

Undergrowth, dense greasewood, mesquite, cacti, and sparse grass.

N. 0° 01' W., bet. secs. 25 and 30.

Desc. 70 ft. over rocky bench, through dense undergrowth.

1.80 Wash, 25 lks. wide, 1 ft. deep, drains NNE.

3.50 Wash, 20 lks. wide, 1 ft. deep, drains NE.

15.80 Wash, 30 lks. wide, 1 ft. deep, drains NE.

39.97 Point for the ¼ sec. cor. of secs. 25 and 30, at proportionate distance; there is no remaining evidence of the original corner.

Set an iron post, 28 ins. long, 2½ ins. diam., 20 ins. in the ground, and in a mound of stone to top, with brass cap mkd.

T8S	
R25E	R26E
¼	S30
S25	S31
1957	

Raise a mound of stone, 3 ft. base, 2½ ft. high, W. of cor.

42.60 Fence, bears S. 70° E. and N. 70° W.

44.75 Road, track, bears N. 70° W. and S. 70° E.

46.80 Wash, 40 lks. wide, 2 ft. deep, drains NE.

Dependent Resurvey of the West Boundary of T, 8 S., R. 26 E.

Chains

- 56.40 Paved road, bears NE. and SW., Safford, Arizona to Graham Mountain.
- 57.10 Telephone line, single wire, bears NE. and SW.
- 63.80 Wash, 20 lks. wide, 6 ft. deep, drains NE.
- 79.94 Point for the cor. of secs. 19, 24, 25 and 30, at proportionate distance; there is no remaining evidence of the original corner.
Set an iron post, 28 ins. long, 2½ ins. diam., 15 ins. in the ground, and in a mound of stone to top, with brass cap mkd.

T8S	
R25E	R26E
S24	S19
S25	S30
1957	

Raise a mound of stone, 3½ ft. base, 2½ ft. high, W. of cor.

Land, rocky benches.

Soil, rocky clay.

Timber, none.

Undergrowth, dense greasewood, mesquite, cacti, and sparse grass.

N. 0° 01' W., bet. secs. 19 and 24.

Desc. over gentle NE. slope, through dense undergrowth.

- .90 Wash, 40 lks. wide, 2 ft. deep, drains E.

9.00 Leave dense mesquite; enter dense greasewood.

- 39.97 Point for the ¼ sec. cor. of secs. 19 and 24, at proportionate distance; there is no remaining evidence of the original corner.

Set an iron post, 28 ins. long, 2½ ins. diam., 15 ins. in the ground, and in a mound of stone to top, with brass cap mkd.

T8S	
R25E	R26E
¼	
S24	S19
1957	

Raise a mound of stone, 3½ ft. base, 2½ ft. high, W. of cor.

- 54.60 Wash, 20 lks. wide, 1 ft. deep, drains N. 70° E.

- 79.94 The cor. of secs. 13, 18, 19 and 24, monumented with a weathered sandstone, firmly set in a mound of stone.

At the corner point

Set an iron post, 28 ins. long, 2½ ins. diam., 16 ins. in the ground, and in a mound of stone to top, with brass cap mkd.

T8S	
R25E	R26E
S13	S18
S24	S19
1957	

Raise a mound of stone, 4 ft. base, 3 ft. high, W. of cor.

Dependent Resurvey of the West Boundary of T. 8 S., R. 26 E.

Chains

Land, rocky benches.
Soil, sandy to rocky clay.
Timber, none.
Undergrowth, dense greasewood, mesquite, cacti, and sparse grass.

N. 0° 13' W., bet. secs. 13 and 18.

Desc. general NE. slope through dense undergrowth.

8.00 Wash, 20 lks. wide, 6 ft. deep, drains NE.

28.90 Power line, bears NW. and SE.

39.93 The $\frac{1}{4}$ sec. cor. of secs. 13 and 18, monumented with a weathered stone in a mound of stone.

At the corner point

Set an iron post, 28 ins. long, 2 $\frac{1}{2}$ ins. diam., 12 ins. in the ground, and in a mound of stone to top, with brass cap mkd.

T8S
R25E R26E
 $\frac{1}{4}$
S13|S18
1957

Raise a mound of stone, 3 $\frac{1}{2}$ ft. base, 2 $\frac{1}{2}$ ft. high, W. of cor.

N. 0° 02' E., beginning new measurement.

26.20 Wash, 20 lks. wide, 1 ft. deep, drains NE.

34.90 Irrigation ditch, 7 ft. wide, 2 ft. deep, flows E. from W.

36.30 Wash, 15 lks. wide, 2 ft. deep, drains NE.

39.90 Point for the cor. of secs. 7, 12, 13 and 18, at proportionate distance; there is no remaining evidence of the original corner.

Set an iron post, 28 ins. long, 2 $\frac{1}{2}$ ins. diam., 22 ins. in the ground, with brass cap mkd.

T8S
R25E R26E
S12|S 7
S13|S18
1957

Raise a mound of stone, 3 ft. base, 2 ft. high, W. of cor.

Land, rocky benches.
Soil, rocky clay.
Timber, none.
Undergrowth, dense greasewood, mesquite, cacti, and sparse grass.

N. 0° 02' E., bet. secs. 7 and 12.

Over level land, through dense undergrowth.

Dependent Resurvey of the West Boundary of T, 8 S., R. 26 E.

Chains

2.00 Small dirt tank, bears E., 1 chain dist.

5.50 Small irrigation ditch, bears NW. and SE., water flows SE.

7.30 Fence, bears NW. and SE.

14.60 Wash, 1 ch. wide, 4 ft. deep, drains NE.

19.70 Fence, bears E. and W.; leave undergrowth, enter farm land.

39.90 Point for the $\frac{1}{4}$ sec. cor. of secs. 7 and 12, at proportionate distance; there is no remaining evidence of the original corner.

Set an iron post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 26 ins. in the ground, with brass cap mkd.

T8S
R25E R26E
 $\frac{1}{4}$
S12 | S 7
1957

Place two large stones W. of the cor.

Corner falls on S. edge of dead end lane bearing ENE.

59.80 Fence, bears E. and W.

71.20 Fence, bears E. and W.

79.80 The cor. of secs. 1, 6, 7 and 12, which point is being used by the land owners concerned as the true point and position of the original corner.

At the corner point

Set an iron post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 26 ins. in the ground, with brass cap mkd.

T8S
R25E | R26E
S 1 | S 6
S12 | S 7
1957

Set a stone, 20x14x7 ins., 10 ins. in the ground along the E. side of the post for witness.

From this corner, an artesian well bears NNE., 30 lks. dist.

Corner is on the E. edge of a track road.

Land, level.
Soil, sandy clay.
Timber, none.
Undergrowth, dense mesquite, greasewood, and grass in south half; north half, none.

N. 0° 03' W., bet. secs. 1 and 6.

Over level farm land.

Dependent Resurvey of the West Boundary of T. 8 S., R. 26 E.

Chains

- 12.75 Road, bears E. and W.; leave farm land; asc. 30 ft. over SE. slope of bench.
- 19.80 Fence, bears E. and W. Earthen pond, bears E., 4 chs. dist.
- 20.10 Road, track, bears E. and W.
- 21.80 Old road, bears NE. and SW.
- 34.80 Fence, bears N. 30° E. and S. 30° W.
- 39.50 Point for the $\frac{1}{4}$ sec. cor. of secs. 1 and 6, at proportionate distance; there is no remaining evidence of the original corner.
- Set an iron post, 28 ins. long, 2½ ins. diam., 10 ins. in the ground, and in a mound of stone, 4 ft. base to top, with brass cap mkd.
- T8S
R25E R26E
¼
S 1 | S 6
1957
- 48.70 Wash, 20 lks. wide, 6 ins. deep, drains NE.
- 59.40 N. rim of bench, bears NE. and SW.; desc. 30 ft. over NW. slope.
- 67.10 Wash, 20 lks. wide, 6 ins. deep, drains NE.
- 79.00 The cor. of Ts. 7 and 8 S., Rs. 25 and 26 E., monumented with a rotted stake in a mound of stone, set by an old fence post.
- At the corner point
- Set an iron post, 28 ins. long, 2½ ins. diam., 20 ins. in the ground, with brass cap mkd.
- T7S
R25E | R26E
S36 | S31
S 1 | S 6
T8S
1957
- Raise a mound of stone, 3½ ft. base, 2½ ft. high, W. of cor.
- Land, rolling.
Soil, rocky clay.
Timber, none.
Undergrowth, scattered mesquite, greasewood, cacti, and grass.

Dependent Resurvey of the North Boundary of T. 8 S., R. 26 E.

Reestablishment of the Survey executed by T. F. White in 1874. From the cor. of Ts. 7 and 8 S., Rs. 26 and 27 E., monumented with an iron post, set, mkd. and witnessed as described in the field notes of T. 7 S., R. 27 E.

S. 89° 52' W., bet. secs. 1 and 36.

Dependent Resurvey of the North Boundary of T. 8 S., R. 26 E.

Chains

Over level land, through scattered undergrowth.

39.71

Point for the $\frac{1}{4}$ sec. cor. of secs. 1 and 36, at proportionate distance; there is no remaining evidence of the original corner.

Set an iron post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 22 ins. in the ground, with brass cap mkd.

T7S R26E
 $\frac{1}{4}$ $\frac{S36}{S1}$
T8S
1957

Deposit broken glass at the base of the post for witness.

79.42

Point for the cor. of secs. 1, 2, 35 and 36, at proportionate distance; there is no remaining evidence of the original corner.

Set an iron post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 24 ins. in the ground, with brass cap mkd.

T7S R26E
 $\frac{S35}{S2}$ $\frac{S36}{S1}$
T8S
1957

Deposit broken glass at the base of the post for witness.

Land, level.

Soil, rocky clay.

Timber, none.

Undergrowth, medium greasewood, cacti, and grass.

S. $89^{\circ} 52'$ W., bet. secs. 2 and 35.

Over level land, through medium undergrowth.

9.00

Road, track, bears N. and S.

39.71

Point for the $\frac{1}{4}$ sec. cor. of secs. 2 and 35, at proportionate distance; there is no remaining evidence of the original corner.

Set an iron post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 23 ins. in the ground, with brass cap mkd.

T7S R26E
 $\frac{1}{4}$ $\frac{S35}{S2}$
T8S
1957

Deposit broken glass at the base of the post for witness.

79.42

Point for the cor. of secs. 2, 3, 34 and 35, at proportionate distance; there is no remaining evidence of the original corner.

Set an iron post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 22 ins. in the ground, with brass cap mkd.

Dependent Resurvey of the North Boundary of T. 8 S., R. 26 E.

Chains

T7S R26E
 S34|S35
 S 3|S 2
 T8S
 1957

Deposit broken glass at the base of the post for witness.

Land, level.

Soil, rocky clay.

Timber, none.

Undergrowth, medium greasewood, cacti, and grass.

S. 89° 52' W., bet. secs. 3 and 34.

Over level land, through medium undergrowth.

- 5.90 Road, track, bears N. and S.
 18.60 Fence, bears N. and S.
 33.50 Small wash, drains S.
 39.71 The $\frac{1}{4}$ sec. cor. of secs. 3 and 34, monumented with a rotted cedar stake in a small mound of stone.

At the corner point

Set an iron post, 28 ins. long, 2 $\frac{1}{2}$ ins. diam., 23 ins. in the ground, with brass cap mkd.

T7S R26E
 $\frac{1}{4}$ $\frac{S34}{S 3}$
 T8S
 1957

Deposit broken glass at the base of the post for witness, and raise a small mound of stone, N. of cor.

S. 89° 47' W., beginning new measurement.

Over rolling land, through scattered undergrowth.

- 25.10 Wash, 15 lks. wide, 6 ft. deep, drains S. 25° W.
 28.40 Low narrow bench, bears NE. and SW.
 36.20 Wash, 70 lks. wide, 2 ft. deep, drains N.
 39.90 Point for the cor. of secs. 3, 4, 33 and 34, at proportionate distance; there is no remaining evidence of the original corner.
 Set an iron post, 28 ins. long, 2 $\frac{1}{2}$ ins. diam., 22 ins. in the ground, with brass cap mkd.

T7S R26E
 S33|S34
 S 4|S 3
 T8S
 1957

Dependent Resurvey of the North Boundary of T. 8 S., R. 26 E.

Chains

Deposit broken glass at the base of the post for witness.

Land, rolling.
Soil, rocky clay.
Timber, none.
Undergrowth, medium greasewood, cacti, and grass.

S. 89° 47' W., bet. secs. 4 and 33.

Over rolling land, through scattered undergrowth.

15.50 Wash, 30 lks. wide, 2 ft. deep, drains NE.

16.20 Fence, bears NE. and SW.; enter farm land.

39.90 Point for the 1/4 sec. cor. of secs. 4 and 33, at proportionate distance; there is no remaining evidence of the original corner.

Set an iron post, 28 ins. long, 2 1/2 ins. diam., 22 ins. in the ground, with brass cap mkd.

T7S R26E
S33
1/4 S 4
T8S
1957

Deposit broken glass at the base of the post for witness.

40.20 Fence, bears N. and S.

60.15 Irrigation ditch, flows N.

63.50 Earthen pond, bears S., 1 chain dist.

79.50 Road, graded, bears N., S., and W.

79.80 The cor. of secs. 4, 5, 32 and 33, reestablished from a concrete monument established as witness by a local surveyor.

At the corner point

Set an iron post, 28 ins. long, 2 1/2 ins. diam., 22 ins. in the ground, with brass cap mkd.

T7S R26E
S32 | S33
S 5 | S 4
T8S
1957

Deposit broken glass at the base of the post for witness.

from which

A concrete monument, bears S. 78° 32' E., 68 lks. dist., mkd.

1950
SC
44' 6" W
9' N

Land, level.
Soil, sandy loam.
Timber, none.
Undergrowth, east 16 chains scattered greasewood and mesquite, west portion none.

Dependent Resurvey of the North Boundary of T. 8 S., R. 26 E.

Chains

S. 89° 55' W., bet. secs. 5 and 32.

Along N. edge of graded road.

24.40 Wash, 20 lks. wide, 4 ft. deep, drains N.

39.90 Point for the $\frac{1}{4}$ sec. cor. of secs. 5 and 32, at proportionate distance; there is no remaining evidence of the original corner.Set an iron post, 28 ins. long, 2 $\frac{1}{2}$ ins. diam., 20 ins. in the ground, with brass cap mkd.

T7S R26E

 $\frac{1}{4} \frac{S32}{S5}$

T8S

1957

Deposit broken glass at the base of the post for witness.

Continue along N. edge of road.

78.90 Reference Monument on line.

79.80 Point for the cor. of secs. 5, 6, 31 and 32, at proportionate distance; there is no remaining evidence of the original corner.

At the corner point

Drive a 10 inch spike in asphalt pavement.

From this corner point, N. 89° 55' E., 90 lks. dist.,

Set an iron post, 28 ins. long, 2 $\frac{1}{2}$ ins. diam., 20 ins. in the ground, with brass cap mkd.

T7S R26E

R $\frac{S32}{S5}$
M

T8S

1957

From the same corner point, S. 89° 55' W., 90 lks. dist.,

Set an iron post, 28 ins. long, 2 $\frac{1}{2}$ ins. diam., 20 ins. in the ground, with brass cap mkd.

T7S R26E

 $\frac{S31}{S6}$ → R
M

T8S

1957

Land, level farm land.

Soil, sandy loam.

Timber, none.

Undergrowth, none.

S. 89° 55' W., bet. secs. 6 and 31.

Over farm land.

Dependent Resurvey of the North Boundary of T. 8 S., R. 26 E.

Chains

.20 U. S. Highway No. 666, bears N. 20° W. and S. 5° E.

.90 Reference Monument on line. Fence, parallel to highway.

17.00 Leave farm land; asc. over rolling rocky land.

26.40 Dim road, bears N. 25° W. and S. 25° E.

39.90 The ¼ sec. cor. of secs. 6 and 31, monumented with a granite stone, 12x6x4 ins., properly mkd. as described in the official record.

At the corner point

Set an iron post, 28 ins. long, 2½ ins. diam., 10 ins. in the ground, and in a mound of stone, 4½ ft. base to top, with brass cap mkd.

T7S R26E
¼ $\frac{S31}{S 6}$
T8S
1957

Deposit original corner alongside the iron post.

N. 89° 55' W., beginning new measurement.

Over rolling land, through scattered undergrowth.

6.80 Old road, bears N. 10° E. and SW.

10.20 Fence, bears N. 10° E. and S. 10° W.

16.70 Enter dense growth of tamarack.

18.00 Leave tamarack; enter greasewood. Earthen pond, bears N., 4 chs. dist.

24.50 Grass bottom draw, drains NE.

38.45 The cor. of Ts. 7 and 8 S., Rs. 25 and 26 E.

Land, east half farm land, west half rolling.
Soil, east half sandy loam, west half rocky clay.
Timber, none.
Undergrowth, east half none, west half tamarack and greasewood.

General Description

The southeast portion of this township is gravel benches and low ridges covered with greasewood, mesquite, cacti, and grass. The south four miles of the west boundary lie on a rocky bench or the foothills of Graham Mountain. A portion of the northwest corner and the southwest corner mainly along Cienega Wash is good farming land, with water being provided for by low volume artesian wells increased with electric pumps. U. S. Highway No. 666 bisects the western half of the township from north to south. There are numerous farm houses scattered within the boundaries. The part of the township that is not farmed is used for limited grazing.

CERTIFICATE OF CADASTRAL ENGINEER

I, Donald E. Harding, HEREBY CERTIFY upon honor that, in
pursuance of special instructions bearing date of the 13th day of January, 1956,
I have ~~surveyed~~ independently resurveyed the north, south, east, and west boundaries
of T. 8 S., R. 26 E.

of the Gila & Salt River Meridian, in the State of Arizona, which are
represented in the foregoing field notes as having been executed by me and under my direction; and that
said survey has been made in strict conformity with said instructions, the Manual of Instructions for the
Survey of the Public Lands of the United States, and in the specific manner described in the foregoing
field notes.

Salt Lake City, Utah
July 2, 1957

Donald E. Harding
Donald E. Harding
Cadastral Surveyor

CERTIFICATE OF APPROVAL

BUREAU OF LAND MANAGEMENT,
Washington, D. C., DEC 26 1957, 19

The foregoing field notes of the ~~survey of~~ independent resurvey of the north, south, east,
and west boundaries of T. 8 S., R. 26 E., Gila & Salt River Meridian, Arizona

executed by Donald E. Harding
having been critically examined and found correct, are hereby approved.

Earl G. Harrington
Cadastral Engineering Staff Officer.

CERTIFICATE OF TRANSCRIPT

I CERTIFY that the foregoing transcript of the field notes of the above-described surveys in
is a true copy of the original field notes.

Cadastral Engineering Staff Officer.