

UNITED STATES
DEPARTMENT OF THE INTERIOR
BUREAU OF LAND MANAGEMENT

Original

FIELD NOTES

of the

North, South, and West Boundaries

and a

Portion of the East Boundary

and a

Portion of the Subdivision

of

Township 17 North, Range 5 East

Of the Gila and Salt River Meridian,

In the State of Arizona

EXECUTED BY

Leslie H. Godwin, Cadastral Surveyor

Donald E. Harding, Cadastral Surveyor, Chief of Party

Under special instructions dated August 2, 1956, which provided
for the surveys included under Group No. 312, approved August 2, 1956
and assignment instructions dated August 20, 1956

Survey commenced September 10, 1956

Survey completed December 13, 1956

BOOK 4556

INDEX DIAGRAM

Township 17 North, Range 5 East
33 32 31 29 28 27

25	6 96 95	5 79 94	4 67 78	3 55 66	2 41 54	1 9
24	7 93 92	8 77 91	9 65 76	10 52 64	11 51	12
22	18 90	17 75	16 63	15 50	14 41	13 7
21	89	88	74	62	49	40
21	19 86 85	20 72 84	21 61 72	22 47 60	23 39 46	24 5 38
19	30 83 82	29 71 81	28 59 70	27 45 57	26 37 44	25 4 36
18	31 80	32 68	33 56	34 42	35 34	36 3
	17	16	14	13	12	10-56770-1

Dependent Resurvey, T. 17 N., R. 5 E.

Chains

T. 17 N., R. 5 E., of the Gila and Salt River Meridian, Arizona, is located within the Coconino National Forest. The south boundary of the township (Fourth Standard Parallel North) was surveyed by J. B. McLaughlin in 1883, retraced by J. C. Smith in 1885 and R. C. Powers in 1886, and dependently resurveyed by Girard and Latimer in 1902. The south boundary of sec. 36 was retraced by W. O. Secor in 1904 as represented on the plat approved May 27, 1904. The south boundary of sec. 31 was dependently resurveyed by W. H. Richards, Jr. in 1916, as shown on the plat of T. 16 N., R. 4 E., approved May 14, 1920. Only the standard quarter section corner required reestablishment, and was monumented with an iron post.

The east boundary was originally surveyed by J. C. Smith in 1885, as represented on the plat approved June 24, 1889, and terminated with a witness corner for the corner of Ts. 17 and 18 N., Rs. 5 and 6 E., portions of this line were dependently resurveyed by W. O. Secor, in 1902-1904 as represented on the plat of T. 17 N., R. 6 E., approved May 27, 1904, at which time the above mentioned witness corner was destroyed and the true corner monumented. The east boundary of sec. 12 was dependently resurveyed by E. H. Kimmell in 1949, as represented on the plat of Exchange Survey No. 678, accepted October 16, 1950.

The west boundary was surveyed by J. C. Smith in 1885 as represented on the plat approved June 24, 1889.

The north boundary was originally surveyed by J. C. Smith in 1885, which survey was superceded by the independent resurvey executed by W. O. Secor in 1902 as represented on the supplemental plat of T. 17 N., R. 5 E., approved August 29, 1905, closing corners for the north were established along the Secor line by E. O. Dietrich in 1905, thereby making a double set of section corners along the entire boundary. The township corners are of maximum control.

The greater portion of the subdivisional lines of the township were surveyed by R. C. Powers in 1886, as represented on the plat approved June 24, 1889. The subdivision was completed and portions of the previously surveyed lines were dependently resurveyed or retraced by W. O. Secor in 1902 and 1904 as represented on the plat approved May 27, 1904. The boundaries of sec. 12, and the north half mile between secs. 13 and 14 were dependently resurveyed by E. H. Kimmell in 1949, as represented on the plat of Exchange Survey No. 678, accepted October 16, 1950. The following field notes are those of the dependent resurvey, or reestablishment of the north, east, west, and south boundaries, and subdivisional lines of the township, with the exception of the four boundaries of sec. 12 and the north half mile between secs. 13 and 14, which were resurveyed in 1949.

The resurvey of this township had been requested at various times by the forest service, the latest request was dated January 3, 1956. Several private engineers and surveyors had made reestablishments of corners, and property line conflicts had arisen between privately owned, and national forest lands. Litigation had been initiated in a number of cases by property owners.

The identified evidence found in restoring the true point of 80% of the original corners consisted of marked stones and mounds of stones, the true position of some was verified by original bearing trees. In some instances the trees were dead and fallen over, but the markings were still legible. The true point for several of the original corners was established by bearing trees alone

Dependent Resurvey, T. 17 N., R. 5 E.

Chains

where no marked rock or mound of stone was in evidence. In four instances, where the original corner was not recovered and two conflicting corners established by private surveyors were present, the land owners were consulted and to prevent litigation from arising, the corner position they agreed to accept was used.

Two locations were accepted as perpetuations of the original corner locations that had been preserved and recognized, but there was no testimony or definite record as to their origin; the locations were adopted after being verified by the direct evidence. The remainder of the corner positions were lost.

Before restoring the corners, the lines of the original survey were retraced, and diligent search made for any evidence of the original corners, bearing trees, and other calls of the original field note record. When duly identified the corner positions were remonumented and, where necessary, new bearing trees marked.

The rules of proportionate measurement were applied in order to ascertain the position of lost corners, after completing the necessary retracements to connect with the identified corner locations, but not until exhausting every reasonable possibility of finding direct evidence for the control of each particular corner. The true lines, thus adjusted to the identified original evidence, were then duly run and marked through the timber. In order to simplify the record, the true line notes only are supplied herewith, which refer to the completed resurvey.

The resurvey was executed with mountain solar transits made by W. E. Gurley, serial number 541332, Buff and Buff, serial number 44439, and Keuffel and Esser, serial number 98796, all constructed in accordance with the standard instrumental specifications of the Bureau of Land Management. The instruments were in good condition and were placed in satisfactory adjustment prior to the beginning of the survey.

The direction of all lines were determined with the solar transit, and the measurements made with standard steel tapes, 5 and 8 chains in length, graduated every link for the first 100 links, and thereafter at intervals of 10 links. The tapes were tested by comparison with a standard tape and found correct. The measurements were made on the slope, and the vertical angle of each interval was ascertained by a clinometer in good adjustment; the horizontal equivalents only are entered in this field note record. The lengths of all lines were determined by chaining where possible; otherwise by traverse or triangulation. The details of such traverses or triangulation have been thoroughly verified and in order to simplify the record, the diagrams and reductions are omitted from these field notes. True line topographic distances were taken from aerial photographs where necessary.

The direction of the lines of survey were determined generally by sustained angulation carried forward from numerous altitude observations on the sun taken at the beginning and throughout the course of the resurvey, and further verified through use of the solar attachment, which was kept in adjustment, as ascertained by tests on a camp meridian, established by Polaris observation at eastern elongation. The following is the initial altitude observation on the sun.

September 11, 1956, at the corner of secs. 25, 30, 31, 36 on the West boundary of the township, in Latitude $34^{\circ} 49' 05''$ N. and Longitude $111^{\circ} 52' 54''$ W., I make a series of three altitude observations of the sun for azimuth, each with the telescope in direct and reversed positions and reading the horizontal angle, from the line of sight to a prominent rock outcrop on the skyline about 8 miles distant, NE. to the sun:

Dependent Resurvey, T. 17 N., R. 5 E.

Chains

Mean observed vertical angle	22° 44'
Refraction in Zenith distance X coefficient for elevation and temperature	- 01' 48"
Parallax	+ 08"
	<u>01' 56"</u>
True vertical angle	h= 22° 42' 04"
Declination of the sun	4° 24' 40"
Reduced bearing of the sun at the mean period of the observation	N. 79° 04' 05" E.
Observed horizontal angle from the sun to the line of sight of the rock outcrop on the skyline	78° 56'

By reduction of observation, using the equation:

$$\cos A = \frac{\sin \phi}{\cos \phi \cos h} - \tan \phi \tan h$$

The true bearing of the rock outcrop on skyline is N 0° 08' 05" W
determined to be: S E

Dependent Resurvey of a Portion of the East Bdy., T. 17 N., R. 5 E.

Reestablishment of the Survey Executed by
J. C. Smith in 1885 and the Partial Depend-
ent Resurvey by W. O. Secor in 1902-1904.

The standard cor. of T. 17 N., Rs. 5 and 6 E., is determined by finding the marked rock and mound of stone, as reestablished by Girard and Latimer in 1902, while dependently resurveying the Fourth Standard Parallel through R. 5 E.; a sandstone rock, 12 x 4 x 30 ins., marked with 6 notches on N, E. and W. sides and SC marked on N. face. Mound of stone, 1½ ft. high, 2 ft. base, N. of marked rock. Point for cor. falls on steep S. sandstone slope of high mountain.

At the cor. point

Set an iron post, 30 ins. long, 2½ ins. diam., over a cross (X) on solid sandstone, and in a mound of stone, 4 ft. base to top, with brass cap marked

SC
T17N
R5E | R6E
S36 | S31
1956

Place original cor. stone in mound of stone.

N. 6° 54' W., bet. secs. 31 and 36, marking and blazing the true line.

Over rough mountainous land, through thinly scattered timber; asc. 100 ft. over steep S. slope.

3.00 Ridge, bears E. and W.; thence by triangulation and traverse. True line runs along precipitous, broken, inaccessible general W. slope.

16.00 End of traverse and triangulation;

Ridge, bears E. and W.; desc. 500 ft. over broken, general WNW. slope.

BOOK 4556

Dependent Resurvey, E. Bdy., T. 17 N., R. 5 E.

Chains

- 38.25 Point for the $\frac{1}{4}$ sec. cor. of secs. 31 and 36, at proportionate dist.; there is no remaining evidence of the original cor.
- Set an iron post, 30 ins. long, $2\frac{1}{2}$ ins. diam., 10 ins. in the ground, and in a mound of stone, 4 ft. base to top, with brass cap marked
- T17N
R5E R6E
 $\frac{1}{4}$
S36|S31
1956
- from which
- A pinon, 6 ins. diam., bears N. 16° E., 19 lks. dist., marked $\frac{1}{4}$ S31 BT.
- A pinon, 10 ins. diam., bears S. $26^\circ 30'$ W., 15 lks. dist., marked $\frac{1}{4}$ S36 BT.
- Continue descent. Desc. 400 ft. over general N. slope.
- 66.00 Road, bladed, bears E. and W.
- 70.00 Wash, 10 lks. wide, 3 ft. deep, drains N. 80° W.
- 76.58 The cor. of secs. 25, 30, 31, and 36, which is monumented with a sandstone, 18 x 10 x 5 ins., marked with 1 notch on S. and 5 notches on N. edges, with mound of stone, 3 ft. base on W. side.
- At the cor. point
- Set an iron post, 30 ins. long, $2\frac{1}{2}$ ins. diam., 16 ins. in the ground, and in a mound of stone, 3 ft. base to top, with brass cap marked
- T17N
R5E R6E
S25|S30
S36|S31
1956
- Place original cor. stone monument in mound of stone.
- Land, high, mountainous.
Soil, broken sandstone, sandy and sandy loam.
Timber, cedar and pinon; undergrowth, manzanita, live oak, sparse grass, thinly scattered cacti.
-
- N. $1^\circ 14'$ E., bet. secs. 25 and 30.
- Over high rolling land, through scattered timber.
- Descend 40 ft. over broken general N. slope.
- .80 Wash, 15 lks. wide, 2 ft. deep, drains NW.
- 5.40 Crest of small ridge, bears NW. and SE.
- 11.00 Wash, 25 lks. wide, 2 ft. deep, drains W.; asc. 80 ft. over nearly vertical S. slope.
- 14.00 Rim, bears S. 80° E. and N. 75° W.; continue ascent. Asc. 150 ft. over steep S. slope.

Dependent Resurvey, E. Bdy., T. 17 N., R. 5 E.

Chains

- 25.70 Ridge, bears S. 70° E. and N. 70° W.; desc. 70 ft. over N. slope.
- 41.05 The $\frac{1}{4}$ sec. cor. of secs. 25 and 30, which is monumented with a limestone, 5 x 10 x 20 ins., marked with $\frac{1}{4}$ on W. face, in a mound of stone, from which an original bearing tree
- A cedar limb, 8 ins. diam., bears S. 70° 30' E., 21 lks. dist., marked $\frac{1}{4}$ S30 BT.
- At the cor. point
- Set an iron post, 30 ins. long, 2 $\frac{1}{2}$ ins. diam., 8 ins. in ground and in a mound of stone, 2 $\frac{1}{2}$ ft. base to top, with brass cap marked
- T17N
R5E R6E
 $\frac{1}{4}$
S25 | S30
1956
- Place original cor. stone monument in mound of stone.
- from which
- A pinon, 8 ins. diam., bears N. 61° 30' W., 77 lks. dist., marked $\frac{1}{4}$ S25 BT.
-
- N. 1° 14' E., beginning new measurement.
- Desc. 40 ft. over rolling NE. slope.
- 7.20 Road, bladed, bears S. 40° E. and NW.
- 7.50 Wash, 25 lks. wide, 2 ft. deep, drains NW.; asc. 80 ft. over broken S. slope.
- 20.30 Wash, 30 lks. wide, 1 $\frac{1}{2}$ ft. deep, drains SW.
- 25.30 Road, bladed, bears E. and W.
- 25.70 Small wash, 10 lks. wide, 1 ft. deep, drains S. 15° E.
- 37.50 Fork of road, bears SE. and W. and NW.; ridge, bears N. 65° W. and S. 65° E.
- 40.04 The cor. of secs. 19, 24, 25, and 30, which is monumented with a mound of stone, from which original bearing trees
- A pinon, 8 ins. diam., bears N. 59° E., 87 lks. dist., marked T17N R6E S19 BT.
- A cedar, 14 ins. diam., bears N. 21° 30' W., 104 lks. dist., marked T17N R5E S24 BT.
- At the cor. point
- Set an iron post, 30 ins. long, 2 $\frac{1}{2}$ ins. diam., 6 ins. in ground, and in a mound of stone, 4 ft. base to top, with brass cap marked

T17N
R5E R6E
S24 | S19
S25 | S30
1956

Dependent Resurvey, E. Bdy., T. 17 N., R. 5 E.

Chains

Place original corner stone in mound of stone.

from which

A pinon, 6 ins. diam., bears S. 21° E., 15 lks. dist.,
marked T17N R6E S30 BT.A pinon, 8 ins. diam., bears S. 84° W., 71 lks. dist.,
marked T17N R5E S25 BT.

Land, rolling and broken.

Soil, sand and sandy loam, loose sandstone.

Timber, cedar and pinon; undergrowth, manzanita, live oak, bitter
brush, sparse grass, thinly scattered cacti.

N. 2° 30' E., bet. secs. 19 and 24.

Over rolling, broken land, through medium heavy timber.

Desc. 100 ft. over N. slope.

9.50 Small wash, 10 lks. wide, 1 ft. deep, drains N. 10° E., on
curve from SE.; continue descent along wash.10.20 Same wash, drains N. 10° W.; continue descent; desc. 110 ft. over
rolling general NW. slope.

17.10 Wash, 10 lks. wide, 1 ft. deep, drains W.

18.00 Road, bladed, bears E. and W.

27.00 Fork of bladed road, bears S. 80° E. and N. 80° W. and N.

27.90 Power line, bears N. 70° W. by S. 70° E.

40.14 The $\frac{1}{4}$ sec. cor. of secs. 19 and 24, which is monumented by a sand-
stone, 10 x 8 x 20 ins., in a mound of stone, with $\frac{1}{4}$ on W. face.

from which the original bearing tree

A cedar, 10 ins. diam., bears N. 89° 30' E., 43 lks. dist.,
marked $\frac{1}{4}$ S19 BT.

At the corner point

Set an iron post, 30 ins. long, 2 $\frac{1}{2}$ ins. diam., over X on solid
rock, and in a mound of stone, 3 $\frac{1}{2}$ ft. base to top, with brass cap
marked

T17N
R5E R6E
 $\frac{1}{4}$
S24 | S19
1956

Place original corner stone in mound of stone.

from which

A pinon, 8 ins. diam., bears S. 14° 45' W., 59 lks. dist.,
marked $\frac{1}{4}$ S24 BT.

Dependent Resurvey, E. Bdy., T. 17 N., R. 5 E.

Chains

N. 2° 32' E., beginning new measurement.

Desc. over NE. slope.

2.00 Wash, 20 lks. wide, 1 ft. deep, drains W. on curve from SE.; asc. 70 ft. over steep S. slope of knoll.

6.20 Top of knoll, thence desc. 125 ft. over nearly vertical wall of bluff, bearing E. and W.

9.00 Oak Creek, 50 lks. wide, 2 ft. deep, drains W. on curve from N. 80° E.; asc. 210 ft. over rolling S. slope.

12.70 Fence, bears N. 70° E. and S. 70° W.

16.60 Road, bladed and power line, bear. NE. and SW.

18.80 Fence, bears N. 15° W. and S. 15° E.

20.80 Fence, bears E. and W.

40.61 The cor. of secs. 13, 18, 19, and 24, which is monumented with a sandstone, 8 x 12 x 17 ins., in a mound of stone, marked with 3 notches on N. side and 3 notches on S. side.

from which the original bearing trees,

A cedar, 12 ins. diam., bears N. 55° 30' E., 43 lks. dist., marked T17N R6E S18 BT.

A cedar, 15 ins. diam., bears S. 1° 00' E., 63 links dist., marked T17N R6E S19 BT.

A cedar, 18 ins. diam., bears S. 32° 00' W., 93 lks. dist., marked T17N R5E S24 BT.

A cedar, 12 ins. diam., bears N. 44° 30' W., 27 lks. dist., marked T17N R5E S13 BT.

At the corner point

Set an iron post, 30 ins. long, 2½ ins. diam., 6 ins. in ground and in a mound of stone, 3 ft. base to top, with brass cap marked

T17N	
R5E	R6E
S13	S18
S24	S19
1956	

Place original corner stone in mound of stone.

Land, high rolling.

Soil, broken sandstone, sandy loam.

Timber, medium heavy cedar and pinon; undergrowth, live oaks, manzanita, palo verde, grass and cacti.

N. 1° 44' E., bet. secs. 13 and 18.

Over moderately rough, broken land, through medium heavy timber and underbrush.

Dependent Resurvey, E. Bdy., T. 17 N., R. 5 E.

Chains	
	Asc. 20 ft. over rough and broken SE. slope of spur.
4.00	Spur, slopes NE.; desc. 20 ft. over N. slope.
10.00	Wash, 10 lks. wide, 1 ft. deep, drains E.; asc. 210 ft. over broken general SE. slope.
13.50	Spur, slopes E.
17.50	Wash, 10 lks. wide, 1 ft. deep, drains S. 75° E.
21.50	Spur, slopes S. 80° E.
22.50	Wash, 10 lks. wide, 1 ft. deep, drains SE.
29.70	Spur, slopes S. 80° E.
31.90	Draw, drains S. 80° E.
35.20	Spur, slopes S. 85° E.
37.00	Draw, drains S. 85° E.
38.00	Spur, slopes S. 85° E.
38.57	The $\frac{1}{4}$ sec. cor. of secs. 13 and 18, which is monumented by a sandstone rock, 16 x 14 x 12 ins., in a mound of stone, marked $\frac{1}{4}$ on E. face.
	At the corner point
	Set an iron post, 30 ins. long, $2\frac{1}{2}$ ins. diam., 12 ins. in ground, and in a mound of stone, 3 ft. base to top, with brass cap marked
	T17N R5E R6E $\frac{1}{4}$ S13 S18 1956
	Bury original corner stone alongside iron post.
	from which
	A pinon, 6 ins. diam., bears S. 47° E., 18 lks. dist., marked $\frac{1}{4}$ S18 BT.
	A pinon, 6 ins. diam., bears S. 87° W., 27 lks. dist., marked $\frac{1}{4}$ S13 BT.
	<hr/>
	N. 1° 18' E., beginning new measurement.
	Desc. 40 ft. over steep N. slope.
3.50	Deep gulch, drains S. 85° E.; asc. 220 ft. over steep broken ESE. slope.
7.40	Spur, slopes S. 85° E.
10.70	Deep gulch, drains S. 85° E., about 7 chains, thence SE.
14.00	W. side of large red sandstone knob in middle of saddle that bears S. 50° E. and N. 50° W.; thence descend 220 ft. over general W. slope.

Dependent Resurvey, E. Bdy., T. 17 N., R. 5 E.

Chains	
39.19	<p>The cor. of secs. 7, 12, 13, and 18, which is monumented with an iron post, previously set, marked, and witnessed as described in the official record of Exchange Survey No. 678, accepted October 16, 1950.</p> <p>Land, mountainous, reasonably steep slopes. Soil, rocky, sand and sandy loam. Timber, medium heavy cedar and pinon and yew; undergrowth, manzanita, live oak, bitter brush, dog bush, palo verde, sparse grass, and scattered cacti.</p>
	<p>From the cor. of secs. 1, 6, 7, and 12, an iron post, previously set, marked, and witnessed as described in the official record of Exchange Survey No. 678, accepted October 16, 1950.</p> <p>N. 0° 58' E., bet. secs. 1 and 6.</p> <p>Over rolling, broken land, through medium heavy timber and underbrush.</p> <p>Asc. 200 ft. over broken general S. 75° W. slope.</p> <p>10.50 Wash, 10 lks. wide, 1 ft. deep, drains SW.</p> <p>24.30 Power line, bears E. and W.</p> <p>29.00 Draw, drains S. 80° W.</p> <p>30.50 Power line, bears E. and W.</p> <p>32.50 Head of draw that drains SW.</p> <p>39.00 Spur, slopes SW.</p> <p>39.81 The $\frac{1}{4}$ sec. cor. of secs. 1 and 6, which is monumented with a weathered sandstone rock, 4 x 12 x 20 ins., in mound of stone from which the original bearing tree</p> <p style="padding-left: 40px;">A pinon, 8 ins. diam., bears N. 29° E., 43 lks. dist., marked S6 BT.</p> <p>At the corner point</p> <p>Set an iron post, 30 ins. long, 2½ ins. diam., 3 ins. in ground to bedrock, and in a mound of stone, 3 ft. base to top, with brass cap marked</p> <div style="text-align: center;"> <p>T17N R5E R6E $\frac{1}{4}$ S1 S6 1956</p> </div> <p>from which</p> <p style="padding-left: 40px;">A pinon, 6 ins. diam., bears N. 56° W., 49 lks. dist., marked $\frac{1}{4}$ S1 BT.</p> <hr style="width: 20%; margin: 20px auto;"/> <p>N. 0° 20' E., beginning new measurement.</p> <p>Des. 130 ft. over general NW. slope.</p>

Dependent Resurvey, E. Bdy., T. 17 N., R. 5 E.

Chains

16.10 Wash, 10 lks. wide, 1 ft. deep, drains S. 80° W.; thence over rolling SW. slope.

20.60 Main wash, 25 lks. wide, 3 ft. deep, drains S. 60° W., 2 water holes downstream, about 1½ and 3½ chains.; asc. 50 ft. along E. slope of spur that slopes S.

31.30 Wash, 10 lks. wide, 5 ft. deep, drains S. 70° E.; asc. 230 ft. over steep S. slope to cor.

38.42 The cor. of T_s. 17 and 18 N., Rs. 5 and 6 E., which falls on narrow ledge of nearly vertical sandstone butte and is monumented with a sandstone rock, 8 x 6 x 15 ins., in mound of stone, marked with 6 notches on N., S., E., and W. edges.

from which

A pinon, 12 ins. diam., bears S. 30° W., 1.69 chs. dist., marked T17N R5E S1 BT.

At the corner point

Set a brass tablet, 3¼ ins. diam., 3½ in. stem, in cement, flush with sandstone ledge marked:

T18N	
R5E	R6E
S36	S31
S1	S6
T17N	
1956	

from which

A pinon, 12 ins. diam., bears S. 5° E., 1.64 chs. dist., marked T17N R6E S6 BT.

Raise a mound of stone, 2 ft. high, 3 ft. base, with original corner stone in mound, W. of cor.

Land, south half rolling; north half broken and mountainous. Soil, broken sandstone and sandy loam. Timber, medium dense yew near washes and scattered pinon, yew, and cedar elsewhere.

Dependent Resurvey of the South Boundary, (Fourth Standard Parallel North) T. 17 N., R. 5 E., Gila & Salt River Meridian, Arizona

Reestablishment of the Dependent Resurvey Executed by Girand and Latimer in 1902 and the Dependent Resurvey of the South Boundary of Section 31, by W. H. Richards, Jr. in 1916.

From the standard township corner of T_s 17 N., Rs. 5 and 6 E., heretofore described.

S. 85° 17' W., along the south boundary of sec. 36, marking and blazing the true line.

Over steep mountainous, broken land, along general S. slope, through scattered timber and undergrowth.

Dependent Resurvey, S. Bdy. T. 17 N., R. 5 E.

Chains

- 11.70 Top of vertical wall of sandstone butte, bears N. 20° W. and S. 20° E.; desc. abruptly 180 ft. to bottom.
- 11.81 Proportionate distance for the closing cor. of secs. 11 and 12, T. 16 N., R. 5 E., there is no remaining evidence of the original cor. Cor. not reestablished.
- Desc. 460 ft. over steep W. slope to $\frac{1}{4}$ sec. cor.
- 41.55 The standard $\frac{1}{4}$ sec. cor. of sec. 36, which is monumented with a sandstone, 36 X 12 X 6 ins., mkd. SC $\frac{1}{4}$ on N. face, in a mound of stone, from which,
- A cedar, 12 ins. diam., bears N. 33° E., 46 lks. dist., mkd. SC $\frac{1}{4}$ S36 BT.
- At the cor. point
- Set an iron post, 30 ins. long, 2 $\frac{1}{2}$ ins. diam., 10 ins. in the ground, and in a mound of stone, 4 ft. base to top, with brass cap marked
- SC
T17N R5E
 $\frac{1}{4}$ S36
1956
- Bury original cor. stone alongside the iron post.
-
- S. 89° 25' W., beginning new measurement.
- Desc. 100 ft. over gradual W. slope.
- 2.00 Wash, 10 lks. wide, 1 ft. deep, drains S. 40° W.
- 8.40 Enter clearing, leave scattered timber., bears N. and S.
- 13.50 Leave clearing, enter heavy timber, bears N. and S.
- 25.30 Leave heavy timber, enter clearing, bears N. and S.
- 40.26 The standard cor. of secs. 35 and 36, which is monumented with a sandstone, 30 X 16 X 6 ins., in a mound of stone, with 5 notches on W. and 1 notch on E., with SC marked on N. face.
- At the cor. point
- Set an iron post, 30 ins. long, 2 $\frac{1}{2}$ ins. diam., 6 ins. in the ground and in a mound of stone, 3 ft. base to top, with brass cap marked
- T17N R5E
S C
S35|S36
1956
- Cor. falls 10 lks. NE. of power line pole on N. side of dim road, bearing E. and W. Power line bears N.
- No bearing trees within limits.
- Land, east half, steep and mountainous; west half gradual slope. Timber, cedar and pinon; undergrowth, palo verde, catclaw, oak, Spanish dagger, scattered cactus, and grass. Soil, rocky and sandy loam.

Dependent Resurvey, S. Bdy., T. 17 N., R. 5 E.

Chains

N. 89° 57' W., along the S. bdy. of sec. 35.

Over nearly level land, through thinly scattered timber and underbrush.

- 1.60 Power line, bears N. 65° E. and S. 65° W.
- 7.50 Wash, 1 ch. wide, 10 ft. deep, drains N. 60° W.
- 10.00 Old road, bears N. and S.
- 10.53 The closing cor. of secs. 10 and 11, T. 16 N., R. 5 E., which is monumented with a sandstone, 24 X 12 X 4 ins., set, marked, and witnessed as described in the official record.
- Cor. point falls on fence line bearing N. and S.
- 13.00 Road, Little Park, gravel, bears SE. and NW.; power line bears, N. 10° W. and S. 10° E.
- 16.60 Wash, 6 lks. wide, 1 ft. deep, drains N. 20° E.
- 23.30 Wash, 10 lks. wide, 3 ft. deep, drains N.
- 35.50 Wash, 20 lks. wide, 2 ft. deep, drains N. 10° E.
- 39.15 Corral fence, bears N. and S.
- 39.93 Point for the standard $\frac{1}{4}$ sec. cor. of sec. 35 at proportionate distance; original cor. stone, a sandstone 20 X 16 X 4 ins., marked SC $\frac{1}{4}$, found lying loose on ground, but true position was not able to be determined.
- At the cor. point
- Set an iron post, 30 ins. long, 2 $\frac{1}{2}$ ins. diam., 32 ins. in ground, brass cap, 2 ins. under surface of ground, marked
- S C
T17N R5E
 $\frac{1}{4}$ S35
1956
- Bury original cor. stone alongside the iron post.
- From which
- A brass tablet, 3 $\frac{1}{2}$ ins. diam., 3 $\frac{1}{2}$ ins. stem, set in cement, flush with ground at base of cement, corral fence post, bears S. 89° 57' E., 77 lks. dist., with cap marked
- R M
S C
T17N R5E
 $\frac{1}{4}$ S35
← 1956
- Corner point falls in horse corral of Verde Valley School.
- Thence across corral and through S. end of school grounds of Verde Valley School, along gentle N. slope.
- 41.20 Horse sheds.
- 45.20 Outdoor basketball court.
- 55.20 Fence, bears N. and S.; asc. 220 ft. over steep N. 75° E. slope through scattered timber and undergrowth.

Dependent Resurvey, S. Bdy., T. 17 N., R. 5 E.

Chains	
56.30	Enter very dense brush.
68.30	Leave dense brush.
74.50	Top of sandstone ridge, bearing N. 20° W. and S. 20° E., near S. edge of sandstone knob and 1 chain N. of vertical wall of butte, about 50 ft. high. Desc. 140 ft. over steep S. 70° W. slope to cor. point.
79.86	The standard cor. of secs. 34 and 35, which is monumented with a sandstone, 20 x 30 x 5 ins., with 4 notches on W. and 2 notches on E. and SC on N. face, set in a mound of stone. from which A pinon, 8 ins. diam., bears N. 70° W., 45 lks., marked T17N R5E SC S34 BT. A pinon, 8 ins. diam., bears N. 29° E., 23 lks., marked T17N R5E SC S35 BT. At the cor. point Set an iron post, 30 ins. long, 2½ ins. diam., 6 ins. in ground and in a mound of stone, 3 ft. base to top, with brass cap marked T17N R5E S C S34 S35 T16N R5E 1956 Place original cor. stone alongside the iron post. Land, east 2/3 gently sloping; west 1/3 rough, mountainous. Soil, east 1/2 sandy loam, west 1/2 broken sandstone and sandy loam. Timber, scattered pinon and cedar; undergrowth, palo verde, live oak, catclaw, sparse grass, and scattered cactus.
	S. 89° 57' W., along the S. bdy. of sec. 34. Over mountainous land, through scattered timber and undergrowth. Continue descent. Desc. 250 ft. over steep broken S. 75° W. slope.
10.39	The closing cor. for secs. 9 and 10, T. 16 N., R. 5 E., which is monumented with a sandstone, 24 x 14 x 6 ins., set, marked, and witnessed as described in the official record.
22.80	Wash, 75 lks. wide, 4 ft. deep, drains N. 20° W.; continue descent. Descend 30 ft. over rolling general N. slope, through medium heavy timber.
39.50	Wash, 50 lks. wide, 3 ft. deep, drains N.
40.32	The standard ¼ sec. cor. of sec. 34, which is monumented with a sandstone, 28 x 12 x 4 ins., marked SC¼ on N. face and set in a mound of stone.

Dependent Resurvey, S. Bdy., R. 17 N., R. 5 E.

Chains

from which

A pinon, 12 ins. diam., bears N. 49° W., 127 lks. dist.,
marked SC $\frac{1}{4}$ S34 BT.

At the cor. point

Set an iron post, 30 ins. long, 2½ ins. diam., 4 ins. in ground
to bedrock, and in a mound of stone, 3 ft. base to top, with
brass cap marked

S C
T17N R5E
 $\frac{1}{4}$ S34
T16N R5E
1956

Place original cor. stone alongside the iron post.

S. 88° 27' W., beginning new measurement.

Continue along rolling gradual N. slope.

10.00 Wash, 60 lks. wide, 3 ft. deep, drains N. 10° W.; asc. 275 ft.
over rough, broken, general E. slope, with cliffs and ledges.

28.70 Ridge, bears N. 50° E. and S. 50° W.; desc. 150 ft. over steep
broken W. slope to cor. point.

39.47 The standard cor. of secs. 33 and 34, which is monumented with a
sandstone, 30 x 20 x 4 ins., 3 notches on E. and 3 notches on W.
edges, SC on N. face, set in a mound of stone.

from which

A pinon, 8 ins. diam., bears N. 33° E., 70 lks. dist.,
marked T17N R5E S34 BT.

At the cor. point

Set an iron post, 30 ins. long, 2½ ins. diam., 10 ins. in ground,
and in a mound of stone, 3 ft. base to top, with brass cap marked

S C
T17N R5E
S33 | S34
1956

Bury original cor. stone alongside the iron post.

from which

A cedar, 18 ins. diam., bears N. 35° 30' W., 195 lks.
dist., marked T17N R5E SC S33 BT

Land, rough, mountainous.

Soil, broken sandstone and sandy loam.

Timber, heavy cedar and pinon; undergrowth, palo verde, live oak,
Spanish dagger, and century plant.

N. 89° 33' W., along the S. bdy. of sec. 33.

L. C. C. 4586

Dependent Resurvey, S. Bdy., R. 17 N., R. 5 E.

Chains	
	Over mountainous land, through medium heavy timber and undergrowth. Asc. 75 ft. over broken, general E. slope.
10.47	The closing cor. for secs. 8 and 9, T. 16 N., R. 5 E., which is monumented with a sandstone, 20 x 10 x 4 ins., set, marked, and witnessed as described in the official record.
20.10	Spur, slopes N.; desc. 90 ft. over W. slope.
25.10	Wash, 10 lks. wide, 1 ft. deep, drains N. 25° W.; asc. 55 ft. over E. slope.
30.10	Spur, slopes N. 10° W.; desc. 40 ft. over W. slope.
34.30	Bottom of slope; asc. 60 ft. over E. slope to cor.
39.88	The standard $\frac{1}{4}$ sec. cor. of sec. 33, which is monumented with a sandstone, 28 x 12 x 4 ins., marked SC $\frac{1}{4}$ on N. face, set in a mound of stone. from which A cedar, 15 ins. diam., bears N. 33° W., 94 lks. dist., marked SC $\frac{1}{4}$ S33 BT. At the cor. point Set an iron post, 30 ins. long, 2 $\frac{1}{2}$ ins. diam., 10 ins. in ground, and in a mound of stone, 4 ft. base to top, with brass cap marked S C T17N R5E <u>$\frac{1}{4}$ S33</u> T16N R5E 1956 Bury original cor. stone alongside the iron post. <hr/> S. 89° 28' W., beginning new measurement. Continue ascent; asc. 320 ft. over E. slope.
14.80	S. edge of prominent flat topped peak, desc. 550 ft. over steep broken, general S. 80° W. slope.
38.90	Wash, 50 lks. wide, 6 ft. deep, drains NW.
39.00	The standard cor. of secs. 32 and 33, which is monumented with a malpais stone, 28 x 14 x 5 ins., marked with 2 notches on W. and 4 notches on E. and SC on N. face. from which A cedar, 15 ins. diam., bears N. 46° E., 50 lks. dist., marked T17N R5E SC S33 BT. A cedar, 10 ins. diam., bears N. 87° W., 26 lks. dist., marked T17N R5E SC S32 BT. At the cor. point.

Dependent Resurvey, S. Bdy., R. 17 N., R. 5 E.

Chains	Set an iron post, 30 ins. long, 2½ ins. diam., over X on solid rock, and in a mound of stone, 3 ft. base to top, with brass cap marked
	<p style="text-align: center;">S C T17N R5E <u>S32 S33</u> 1956</p>
	<p>Place original cor. stone alongside the iron post.</p> <p>Point for cor. falls on W. edge of wash on top of vertical sandstone bank, 6 ft. high.</p> <p>Land, rough, mountainous. Soil, broken sandstone and sandy loam. Timber, cedar and pinon; undergrowth, palo verde, sparse grass, live oak, and scattered cacti.</p>
	<p>N. 89° 25' W., along the S. bdy. of sec. 32</p>
	<p>Over mountainous land, through scattered timber and undergrowth.</p>
	<p>Asc. 525 ft. over steep, broken general N. 80° E. slope.</p>
4.00	<p>Wash, 60 lks. wide, 10 ft. deep, drains N. 80° E.</p>
7.70	<p>Wash, 25 lks. wide, 5 ft. deep, drains NE.</p>
12.37	<p>The closing cor. of secs. 7 and 8, T. 16 N., R. 5 E., which is monumented with a sandstone, 10 x 12 x 36 ins., set, marked and witnessed as described in the official record.</p>
29.00	<p>Top of E. slope, top of mountain, bears S. about 2½ chains, thence desc. 55 ft. along general N. slope. Enter medium dense timber and palo verde.</p>
34.20	<p>Slope changes, desc. 85 ft. over W. slope.</p>
40.22	<p>The standard ¼ sec. cor. of sec. 32, which is monumented with a malpais stone, 8 x 10 x 18 ins., marked ¼ SC on N. face, set in a mound of stone.</p>
	<p>from which</p>
	<p style="padding-left: 40px;">A cedar, 18 ins. diam., bears N. 40° W., 65 lks dist., marked ¼ S32 BT.</p>
	<p>At the cor. point</p>
	<p>Set an iron post, 30 ins. long, 2½ ins. diam., 6 ins. in ground, and in a mound of stone, 3 ft. base to top, with brass cap marked</p>
	<p style="text-align: center;">T17N R5E SC <u>¼ S32</u> 1956</p>
	<p>Bury the original cor. stone alongside the iron post.</p>
	<p>N. 89° 57' W., beginning new measurement.</p>
	<p>Continue descent; desc. 165 ft. along general N. slope.</p>

Dependent Resurvey, S. Bdy., T. 17 N., R. 5 E.

Chains	
3.40	Timber, changes from medium dense to scattered.
13.00	Slope, changes to NW.; desc. 200 ft. over NW. slope.
32.20	Slope, changes to S.
39.00	Slope, changes to W.; desc. 35 ft. over W. slope.
39.98	The standard sec. cor. of secs. 31 and 32, which is monumented with a sandstone, 15 x 12 x 6 ins. lying loose in scattered mound of stone, with 1 notch on one side, and 5 notches on the opposite side, and SC on one face.
	At the cor. point.
	Set an iron post, 30 ins. long, 2½ ins. diam., 15 ins. in ground, and in a mound of stone, 3 ft. base to top, with brass cap marked
	S C T17N R5E <u>S31 S32</u> 1956
	Bury original cor. stone alongside the iron post.
	from which
	A cedar, 8 ins. diam., bears N. 80° W., 15 lks. dist., marked T17N R5E SC S31 BT.
	Land, steep, mountainous. Soil, malpais rocks, broken sandstone, and sandy loam. Timber, heavy to scattering pinon and cedar; undergrowth, live oak palo verde, sparse grass, Spanish dagger, and scattered cacti.
	S. 89° 40' W., along the S. bdy. of sec. 31.
	Over mountainous land, through scattered timber and undergrowth.
	Desc. 50 ft. over W. slope.
3.70	Oak Creek, 50 lks. wide, 1 ft. deep, drains S. 20° W.; asc. 220 ft. over general E. slope.
11.24	The closing cor. of secs. 7 and 12, Ts. 16 N., Rs. 4 and 5 E., a sandstone, 14 x 12 x 6 ins., set, marked, and witnessed as described in the official record.
22.00	Spur, slopes S.; desc. 60 ft. over general SW. slope.
25.50	Asc. 40 ft. over E. slope.
27.50	Desc. over sandstone ledge, 40 ft. high, bearing N. 55° W. and S. 55° E.
39.65	The standard ¼ sec. cor. of sec. 31, which is monumented with a 1 in. iron post, set, marked, and witnessed as described in the official record.
	S. 89° 40' W., beginning new measurement.
	Desc. 50 ft. over SW. slope.

BOOK 4556

Dependent Resurvey, S. Bdy., T. 17 N., R. 5 E.

Chains											
2.50	Oak Creek, 50 lks. wide, 1 ft. deep, drains N. 75° W.; thence through bottom of creek and across plowed field.										
15.00	House, bears S., about 5 chs. dist.										
21.50	End of plowed field; fence bears N. and S.;										
23.30	Oak Creek, 50 lks. wide, 1 ft deep, drains S.; asc. 370 ft. over S. 80° E. slope.										
29.60	Road, bladed, bears N. and S.										
39.11	The standard cor. of Ts. 17 N., Rs. 4 and 5 E., which is monumented with a malpais stone, 30 x 16 x 10 ins., marked with 6 notches on N.E. and W. edges, set in a mound of stone. At the cor. point. Set an iron post, 2½ ins. diam., 30 ins. long, 16 ins. in ground, and in a mound of stone, 3 ft. base to top, with brass cap marked <table style="margin-left: auto; margin-right: auto; border-collapse: collapse;"> <tr><td style="padding: 0 5px;">S</td><td style="padding: 0 5px;">C</td></tr> <tr><td style="padding: 0 5px;">T17N</td><td></td></tr> <tr><td style="padding: 0 5px;">R4E</td><td style="padding: 0 5px;">R5E</td></tr> <tr><td style="padding: 0 5px;">S36</td><td style="padding: 0 5px;">S31</td></tr> <tr><td colspan="2" style="text-align: center; padding: 0 5px;">1956</td></tr> </table> Bury original cor. stone alongside the iron post. Cor. point falls on S. 80° E. slope of malpais mountain, about three chains from top. Land, mountainous. Soil, rocky and sandy loam. Timber, cedar and pinon, sycamore in creek bottom; undergrowth, palo verde, sparse grass, scattered cacti.	S	C	T17N		R4E	R5E	S36	S31	1956	
S	C										
T17N											
R4E	R5E										
S36	S31										
1956											

Dependent Resurvey of the W. Bdy., T. 17 N., R. 5 E.

Reestablishment of the Survey
Executed by J. C. Smith in 1885.

	From the cor. of Ts. 17 N., Rs. 4 and 5 E., a 2½ in. iron post, heretofore described N. 0° 02' W., bet. secs. 31 and 36, marking and blazing the true line.
	Over mountainous land, through scattered timber and underbrush.
	Asc. 35 ft. over SE. slope.
3.20	Slope changes; desc. 30 ft. over E. slope.
7.00	Slope changes, desc. 180 ft. over NE. slope.
15.40	Road, bladed, bears NW. and SE.
18.50	Wash, 10 lks. wide, 1 ft. deep, drains E.; asc. 35 ft. along general E. slope.
24.60	Top of ascent; desc. 70 ft. along general E. slope.
29.64	Wash, 12 lks. wide, 6 ft. deep, drains E.; asc. 25 ft. over rolling E. slope.

Dependent Resurvey, W. Bdy., T. 17 N., R. 5 E.

Chains

- 36.29 Wash, 10 lks. wide, 2 ft. deep, drains SE.; asc. 50 ft. over S. slope.
- 39.80 The $\frac{1}{4}$ sec. cor. of secs. 31 and 36, which is monumented with a malpais stone, 24 x 10 x 8 ins., marked $\frac{1}{4}$ on W. face, set in a mound of stone.
- from which
- A cedar, 12 ins. diam., bears S. 86° E., 35 lks. dist., marked $\frac{1}{4}$ S31 BT.
- At the cor. point
- Set an iron post, 30 ins. long, 2 $\frac{1}{2}$ ins. diam., 10 ins. in ground and in a mound of stone, 2 ft. base to top, with brass cap marked
- | |
|---------------|
| T17N |
| R4E R5E |
| $\frac{1}{4}$ |
| S36 S31 |
| 1956 |
- Bury original cor. stone alongside the iron post.
- Raise a mound of stone to W., 3 ft. base, 2 ft. high.
-
- North, beginning new measurement.
- Continue ascent.
- Asc. 65 ft. over S. slope.
- 3.30 Spur, sloping SW.; thence desc. 45 ft. along broken, general W. slope.
- 8.60 Wash, 10 lks. wide, 2 ft. deep, drains S. 80° W.
- 21.20 Wash, 5 lks. wide, 1 ft. deep, drains SW.; asc. 225 ft. over general SW. slope.
- 40.13 The cor. of secs. 25, 30, 31 and 36, which is monumented with a malpais stone, 10 x 10 x 8 ins., 1 notch on S., 5 notches on N., set in a mound of stone.
- At the cor. point
- Set an iron post, 30 ins. long, 2 $\frac{1}{2}$ ins. diam., 8 ins. in ground, and in a mound of stone, 3 $\frac{1}{2}$ ft. base to top, with brass cap marked
- | |
|-----------|
| T17N |
| R4E R5E |
| S25 S30 |
| S36 S31 |
| 1956 |
- Bury original cor. stone alongside the iron post.
- Land, mountainous.
- Soil, rocky.
- Timber, scattering cedar and pinon.
- Undergrowth, palo verde, grass, scattered cacti.
-
- North, bet. secs. 25 and 30.

Dependent Resurvey, W. Bdy., T. 17 N., R. 5 E.

Chains

- Over low mountains, through scattered timber and underbrush.
Continue ascent; asc. 20 ft. over S. slope.
- 2.00 Ridge, bears NW. and SE.; desc. 105 ft. along N. 80° E. slope.
- 25.50 Bottom of slope, thence along nearly level land, over sparse grass, no trees.
- 35.50 Enter scattered cedar and palo verde.
- 37.70 Desc. 10 ft. over N. slope.
- 40.07 The $\frac{1}{4}$ sec. cor. of secs. 25 and 30, which is monumented with a limestone, 16 x 10 x 8 ins., marked $\frac{1}{4}$ on W. face, set in a mound of stone.
- At the cor. point
- Set an iron post, 30 ins. long, 2 $\frac{1}{2}$ ins. diam., 18 ins. in ground, and in a mound of stone, 3 ft. base to top, with brass cap marked
- T17N
R4E R5E
 $\frac{1}{4}$
S25|S30
1956
- Bury original cor. stone alongside the iron post.
- from which
- A pinon, 8 ins. diam., bears S. 45° 30' W., 37 lks. dist., marked $\frac{1}{4}$ S25 BT.
- A cedar, 4 ins. diam., bears S. 82° E., 56 lks. dist., marked BT only.
-
- N. 0° 01' E., beginning new measurement.
- Continue descent; desc. 140 ft. over N. slope.
- 11.60 Wash, 8 lks. wide, 3 ft. deep, drains S. 60° E.
- 12.30 Asc. 85 ft. over general S. slope.
- 13.60 Old road, abandoned, bears N. 50° W. and S. 50° E.
- 28.30 Top of slope; thence asc. 25 ft. across rolling hills to cor. point.
- 34.30 Wash, 5 lks. wide, 2 ft. deep, drains SE.
- 40.07 The cor. of secs. 19, 24, 25, and 30, which is monumented with a malpais stone, 18 x 6 x 4 ins., 4 notches on N. side, 2 notches on S. side, set in a mound of stone.
- from which
- A cedar, 10 ins. diam., bears S. 45° E., 80 lks. dist., marked T17N R5E S30 BT.
- At the cor. point

BOOK 4536

Dependent Resurvey, W. Bdy., T. 17 N., R. 5 E.

Chains

Set an iron post, 30 ins. long, 2½ ins. diam., 20 ins. in ground, and in a mound of stone, 3 ft. base to top, with brass cap marked

T17N
R4E | R5E
S24 | S19
S25 | S30
1956

Bury original cor. stone alongside the iron post.

Land, rolling hills.

Soil, rocky and gravelly.

Timber, scattered cedar and pinon; undergrowth, palo verde, grass, and cacti.

N. 0° 08' W., bet. secs. 19 and 24.

Over rolling hills, through scattered timber and undergrowth.

Asc. 40 ft. over S. slope.

3.50 Top of hill, bears NE. and SW.; thence desc. 185 ft. over general N. slope into Dry Creek Canyon.

18.90 Bottom of steep slope, thence asc. across open flat W. of Dry Creek.

23.90 Wash, 50 lks. wide, 3 ft. deep, drains E. into Dry Creek; asc. 80 ft. over broken general S. 60° E. slope, to cor. point.

32.20 Highway U.S. 89A bears E. and W., about 10 chains; thence SW.

36.50 Wash, 12 lks. wide, 2 ft. deep, drains SE.

39.91 The ¼ sec. cor. of secs. 19 and 24, which is monumented with a sandstone, 12 x 18 x 8 ins., marked ¼ on W. face, set in a mound of stone.

from which

A cedar, 18 ins. diam., bears S. 80° 30' W., 71 lks. dist., marked ¼ S24 BT.

A cedar, 8 ins. diam., bears S. 59° 30' E., 105 lks. dist., marked ¼ S19 BT.

At the cor. point

Set an iron post, 30 ins. long, 2½ ins. diam., 8 ins. in ground and in a mound of stone, 3 ft. base to top, with brass cap marked

T17N
R4E | R5E
¼
S24 | S19
1956

Bury original cor. stone alongside the iron post.

N. 0° 02' W., beginning new measurement.

Over rolling hills, through scattered timber and underbrush.

Asc. 140 ft. across a series of washes and spurs, over a general, broken, SE. slope, to cor. point.

Dependent Resurvey, W. Bdy., T. 17 N., R. 5 E.

Chains						
3.70	Wash, 15 lks. wide, 3½ ft. deep, drains SE.					
16.30	Spur, slopes SE.					
21.10	Wash, 10 lks. wide, 4 ft. deep, drains SE.					
27.10	Wash, 14 lks. wide, 5 ft. deep, drains SE.					
34.10	Spur, slopes SE.					
40.24	<p>The cor. of secs. 13, 18, 19, and 24, which is monumented with a limestone, 22 x 14 x 14 ins., with three notches on S. and three notches on N. edges, set in a mound of stone.</p> <p>from which</p> <p>A cedar, 30 ins. diam., bears S. 9° 30' E., 56 lks. dist., marked T17N R5E S19 BT.</p> <p>A cedar, 24 ins. diam., bears S. 42° 45' W., 112 lks. dist., marked T17N R4E S24 BT.</p> <p>A cedar, 10 ins. diam., bears N. 55° 15' E., 114 lks. dist., marked T17N R5E S18 BT.</p> <p>At the cor. point.</p> <p>Set an iron post, 30 ins. long, 2½ ins. diam., 18 ins. in ground, and in a mound of stone, 3 ft. base to top, with brass cap marked</p> <table style="margin-left: auto; margin-right: auto;"> <tbody> <tr><td>T17N</td></tr> <tr><td>R4E R5E</td></tr> <tr><td>S13 S18</td></tr> <tr><td>S24 S19</td></tr> <tr><td>1956</td></tr> </tbody> </table> <p>Bury original cornerstone alongside the iron post.</p> <p>from which</p> <p>A cedar, 14 ins. diam., bears N. 79° W., 1.43 lks. dist., marked T17N R4E S13 BT.</p> <p>Land, broken, rolling hills. Soil, rocky with some sandy loam. Timber, scattered cedar and pinon; undergrowth, palo verde, scrub oak, Spanish dagger, and grass.</p>	T17N	R4E R5E	S13 S18	S24 S19	1956
T17N						
R4E R5E						
S13 S18						
S24 S19						
1956						
	N. 0° 02' W., bet. secs. 13 and 18.					
	Over hilly land, through medium dense timber and undergrowth.					
2.20	Top of hill, bears NW. and SE.					
16.80	Desc. 125 ft. over N. slope.					
28.40	Wash, 15 lks. wide, 3 ft. deep, drains SE.; power line bears E. and W.					
30.60	Asc. 35 ft. over S. slope.					
33.70	Top of knoll; desc. 45 ft. over N. slope.					

Dependent Resurvey, W. Bdy., T. 17 N., R. 5 E.

Chains

- 39.60 Wash, 8 lks. wide, 4 ft. deep, drains S. 60° E.
- 40.10 The ¼ sec. cor. of secs. 13 and 18, which is monumented with a limestone, 12 x 12 x 24 ins., set in a mound of stone.

from which

A cedar, 12 ins. diam., bears N. 81° 30' W., 25 lks. dist., marked ¼ S13 BT.

A cedar, 14 ins. diam., bears S. 86° E., 1.17 lks. dist., marked ¼ S18 BT.

At the corner point

Set an iron post, 30 ins. long, 2½ ins. diam., 18 ins. in ground, and in a mound of stone, 3 ft. base to top, with brass cap marked

T17N
R4E R5E
¼
S13|S18
1956

Bury original cor. stone alongside the iron post.

N. 0° 02' W., beginning new measurement.
- 2.40 Along broken S. 60° E. slope.
- 8.40 Wash, 60 lks. wide, 4 ft. deep, drains SE.; thence along W. slope.
- 19.17 Same wash, 50 lks. wide, 4 ft. deep, drains S. 20° W.

Ascend 120 ft. over broken S. slope.
- 21.00 Spur, slopes E.
- 22.26 Wash, 25 lks. wide, 4 ft. deep, drains SE.
- 31.60 Top of hill, bears NW. and SE.; desc. 110 ft. over N. slope.
- 37.60 Wash, 50 lks. wide, 3 ft. deep, drains SE.; asc. 30 ft. over S. slope.
- 39.82 The cor. of secs. 7, 12, 13, and 18, which is monumented with a X on top of large sandstone, 4 x 6 x 4 ft., with 2 notches N. of cross and 4 notches S. of cross.

from which

A cedar, 12 ins. diam., bears E. 24 lks. dist., marked T17N R5E S7 BT.

A cedar, 12 ins. diam., bears N. 2° W., 94 lks. dist., marked T17N R4E S12 BT.

At the corner point

Set a brass tablet, 3½ ins. diam., 3½ in. stem in cement, with top, flush with surface of sandstone, marked

T17N
R4E R5E
S12 S7
S13 S18
1956

Dependent Resurvey, W. Bdy., T. 17 N., R. 5 E.

Chains	
	<p>Raise a mound of stone, 18 ins. high, 2½ ft. base, W. of cor. point.</p> <p>Land, broken and hilly. Soil, rocky, gravelly and sandy. Timber, medium heavy cedar and pinon; undergrowth, palo verde, Spanish dagger, grass, and thinly scattered cacti.</p>
	<p>North, bet. secs. 7 and 12.</p> <p>Over broken, hilly land, through scattered timber.</p> <p>Continue ascent; asc. 95 ft. over S. slope.</p> <p>Asc. 95 ft. over S. slope.</p>
10.20	Top of hill, thence desc. 65 ft. across rolling hills and broken slopes.
33.30	Wash, 8 lks. wide, 1 ft. deep, drains SW.; asc. 25 ft. over general S. slope.
40.08	<p>The ¼ sec. cor. of secs. 7 and 12, which is monumented with a sandstone, 18 x 10 x 10 ins., marked ¼ on W. face, set in a mound' of stone.</p> <p>from which</p> <p style="padding-left: 40px;">A cedar, 18 ins. diam., bears S. 72° 30' E., 67 lks. dist., marked ¼ S7 BT.</p> <p style="padding-left: 40px;">A nearly dead cedar, 12 ins. diam., bears N. 87° 30' W., 87 lks. dist., marked ¼ S12 BT.</p> <p>At the corner point</p> <p>Set an iron post, 30 ins. long, 2½ ins. diam., 4 ins. in ground, and in a mound of stone, 3 ft. base to top, with brass cap marked</p> <div style="text-align: center;"> <p>T17N R4E R5E ¼ S12 S7 1956</p> </div> <p>Bury original corner stone alongside the iron post.</p> <p>from which</p> <p style="padding-left: 40px;">A cedar, 6 ins. diam., bears S. 85° W., 22 lks. dist., marked ¼ S12 BT.</p>
	<p>N. 0° 02' W., beginning new measurement.</p> <p>Asc. 10 ft. over SW. slope.</p>
7.30	Top of hill, bears NE. and SW.; desc. 35 ft. over N. 70° W. slope.
15.10	Wash, 50 lks. wide, 10 ft. deep, drains SW.; thence over rolling E. slope.
21.00	Wash, 15 lks. wide, 2 ft. deep, drains into main wash, about 4 chains SE.; asc. 100 ft. across rolling hills to cor. point.
30.40	Spur, slopes S. 70° E.

Dependent Resurvey, W. Bdy., T. 17 N., R. 5 E.

Chains

40.14

The cor. of secs. 1, 6, 7, and 12, which is monumented with a limestone, 24 x 20 x 15 ins., set in a mound of stone.

from which

A cedar, 12 ins. diam., bears N. 33° 30' E., 89 lks. dist., marked T17N R5E S6 BT.

A cedar, 10 ins. diam., bears S. 40° E., 28 lks. dist., marked T17N R5E S7 BT.

A cedar, 10 ins. diam., bears S. 19° W., 125 lks. dist., marked T17N R4E S12 BT.

A cedar, 14 ins. diam., bears S. 36° 45' W., 38 lks. dist., marked T17N R4E S1 BT.

At the corner point

Set an iron post, 30 ins. long, 2½ ins. diam., 6 ins. in ground, and in a mound of stone, 3 ft. base to top, with brass cap marked

T17N	
R4E	R5E
S1	S6
S12	S7
1956	

Bury original corner stone alongside iron post.

Land, hilly.

Soil, rocky, sandy and gravelly.

Timber, cedar and pinons.

Undergrowth, live oak, Spanish dagger, palo verde, catclaws, grass, and sparse cacti.

N. 0° 02' W., bet. secs. 1 and 6.

Over broken hills, through medium dense timber.

Desc. 35 ft. over broken northerly slope.

11.00

Wash, 7 lks. wide, 18 ins. deep, drains into main wash, 75 lks. E.; thence along gently rolling E. slope.

20.80

Wash, 30 lks. wide, 18 ins. deep, drains SE.

24.60

Road, bladed, bears E. and W.

35.80

Wash, 120 lks. wide, 3 ft. deep, drains SE.; thence along S. 70° W. slope.

40.18

The ¼ sec. cor. of secs. 1 and 6, which is monumented with a sandstone, 10 x 12 x 6 ins., marked with ¼ on W. face, set in a mound of stone.

from which

A cedar, 18 ins. diam., bears S. 68° 30' W., 38 lks. dist., marked ¼ S1 BT.

A cedar, 18 ins. diam., bears S. 57° 30' E., 132 lks. dist., marked ¼ S6 BT.

At the corner point

Dependent Resurvey, W. Bdy., T. 17 N., R. 5 E.

Chains

Set an iron post, 30 ins. long, 2½ ins. diam., 4 ins. in ground, and in a mound of stone, 3 ft. base to top, with brass cap marked

T17N
R4E R5E
¼
S1|S6
1956

Bury original corner stone alongside iron post.

North, beginning new measurement.

- 6.90 Wash, 6 lks. wide, 1 ft. deep, drains SW.; thence across gentle rolling land.
- 22.80 Road, graded, bears E. and W.
- 25.80 Wash, 65 lks. wide, 4 ft. deep, drains SW.
- 40.03 The cor. of Ts. 17 and 18 N., Rs. 4 and 5 E., which is monumented with a sandstone, 24 x 18 x 14 ins., marked with 6 notches on N,E., W. and S. sides, set in a mound of stone.

from which

A cedar, 18 ins. diam., bears N. 69° 30' W., 80 lks. dist., marked T18N ~~R4E~~ S36 BT.

At the corner point

Set an iron post, 30 ins. long, 2½ ins. diam., 12 ins. in ground, and in a mound of stone, 3 ft. base to top, with brass cap marked

T18N
R4E | R5E
S36 | S31
S1 | S6
T17N
1956

Bury original corner stone alongside iron post.

from which

A cedar, 12 ins. diam., bears N. 28° E., 28 lks. dist., marked T18N R5E S31 BT.

A cedar, 18 ins. diam., bears S. 21° 30' W., 126 lks. dist., marked T17N R4E S1 BT.

A cedar, 20 ins. diam., bears S. 26° 15' E., 172 lks. marked T17N R5E S6 BT.

Land, rolling hills.

Soil, rocky, sandy, and sandy loam.

Timber, medium heavy cedar and pinon; undergrowth, live oak, palo verde, catclaws, Spanish dagger, sparse grass and thinly scattered cacti.

Dependent Resurvey, N. Bdy., T. 17 N., R. 5 E.

Chains

Reestablishment of the Independent Resurvey
Executed by W. O. Secor in 1902.

The N. bdy. of sec. 2 and the E. $\frac{1}{2}$ mile of the N. bdy. of sec. 1 are determined by traverse and triangulation. True line distances and items of topography are taken from aerial photographs.

From the cor. of Ts. 17 and 18 N., Rs. 5 and 6 E., which is a $3\frac{1}{4}$ in. brass tablet, set in concrete, heretofore described.

N. $89^{\circ} 20'$ W., along the N. bdy. of sec. 1

Over precipitous inaccessible mountainous land, through scattered timber.

Along nearly vertical S. wall of butte.

3.00 Desc. 250 ft. over broken SW. slope.

8.50 Bottom of slope at head of draw, draining SE.; thence asc. 200 ft. over steep SE. slope.

12.30 Slope changes; asc. 75 ft. over N. 30° E. slope.

18.00 Narrow, sharp top of mountain, bears NW. and SE.; desc. 600 ft. over precipitous S. 75° W. slope.

37.50 Wash, 50 lks. wide, 4 ft. deep, drains S. 20° E.; 6 natural water tanks in sandstone at bottom of wash, each about 5 ft. in diam., 4 upstream, 1, 30, 40, and 50 lks. dist., 2 downstream, 10 and 30 lks. dist. Begin ascent of E. slope.

40.11 The $\frac{1}{4}$ sec. cor. of sec. 1, as monumented by a sandstone, 18 X 12 X 16 ins., marked $\frac{1}{4}$ on N. face.

from which

A cedar, 12 ins. diam., bears S. 53° E., 69 lks. dist., marked $\frac{1}{4}$ S 1 BT.

A yew, 7 ins. diam., bears S. 32° W., 107 lks. dist., marked $\frac{1}{4}$ S1 BT.

At the corner point

Set an iron post, 30 ins. long, $2\frac{1}{2}$ ins. diam., 3 ins. to bedrock, and in a mound of stone, 3 ft. base to top, with brass cap marked

T18N R5E

$\frac{1}{4}$ S1

T17N

1956

Place original corner stone alongside iron post.

N. $89^{\circ} 48'$ W., beginning new measurement.

Continue ascent; asc. 630 ft. over E. slope.

.10 Road, bladed, bears N. 10° E. and S.

5.90 Wash, 10 lks. wide, 4 ft. deep, drains S. 70° E.

40.28 The witness cor. of secs. 1 and 2, which is monumented with a sandstone, 24 X 8 X 10 ins., marked with WC on top, mound of

Dependent Resurvey, N. Bdy., T. 17 N., R. 5 E.

Chains

stone 3 ft. base, 2 ft. high to W.

from which

A yew, 8 ins. diam., bears S. 70° E., 70 lks. dist.,
marked WC T17N R5E S1 BT.

At the corner point

Set an iron post, 30 ins. long, 2½ ins. diam., over X on solid
rock, and in a mound of stone, 4 ft. base to top, with brass cap
marked

T18N R5E

WC	S2	S1
	T17N	
	1956	

Set original corner stone alongside iron post.

40.42 True point for the cor. of secs. 1 and 2, falls on inaccessible
face of cliff that bears N. 10° W. and S. 10° E.

Land, precipitous and mountainous.
Soil, solid sandstone and sandy loam,
Timber, heavy cedar, yew and pinon; undergrowth, live oak, manzanita,
grass, thinly scattered cacti.

N, 89° 36' W., along the N. bdy. of sec. 2.

Over precipitous mountains, through heavy timber; asc. 500 ft. over
cliff facing N. 80° E.

3.50 End of hogsback that slopes from top of mountain about 8 chs. SW.;
thence asc. 100 ft. along precipitous, broken N. slope.

18.00 Spur, slopes N.; thence desc. 650 ft. over steep broken NW. slope.

31.00 Wash, drains NW.

37.70 Wash, 10 lks. wide, 6 ft. deep, drains N. 10° E.; asc. 50 ft.
over E. slope.

40.24 Point for the ¼ sec. cor. of sec. 2, at proportionate dist.; there
is no remaining evidence of the original cor.

Set an iron post, 30 ins. long, 2½ ins. diam., 4 ins. in ground to
bedrock, and in a mound of stone, 3 ft. base to top, with brass cap
marked

T18N R5E

¼ S 2
T17N
1956

from which

A yew, 15 ins. diam., bears S. 75° E., 8 lks. dist.,
marked ¼ S2 BT.

Continue ascent; asc. 400 ft. over broken, rocky E. slope.

63.70 Top of peak, bears N. 10° W. and S. 10° E.; desc. 400 ft. over
broken N. 70° W. slope.

69.60 Slope change; asc. 200 ft. over NE. slope.

75.30 Spur, slopes W.

Dependent Resurvey, N. Bdy., T. 17 N., R. 5 E.

Chains 80.48	<p>True point for the cor. of secs. 2 and 3, falls on a high inaccessible spur.</p> <p>Witness cor. of secs. 2 and 3, bears N. 89° 42' W., 9.35 chs. dist.</p> <p>Land, precipitous and mountainous. Soil, solid sandstone, rocky and sandy loam. Timber, cedar, yew, and pinon; undergrowth, live oak, manzanita, and thinly scattered cacti.</p>
	<p>N. 89° 42' W., along the N. bdy. of sec. 3.</p> <p>Over mountainous land, through heavy timber.</p> <p>Desc. 200 ft. over ledges on broken W. slope.</p>
8.50	Top of cliff facing W.; desc. 200 ft.
9.35	<p>The witness cor. of secs. 2 and 3, which is monumented with a sandstone, 10 x 17 x 20 ins., marked 4 notches on W. and 2 notches on E. faces, WC on E. face, set in a mound of stone.</p> <p>from which</p> <p style="padding-left: 40px;">A cedar limb, 8 ins. diam., bears S. 9° W., 52 lks. dist., marked WC T17N R5E S3 BT.</p> <p>At the corner point</p> <p>Set an iron post, 30 ins. long, 2½ ins. diam., 8 ins. in ground, and in a mound of stone, 3 ft. base to top, with brass cap marked</p> <div style="text-align: center;"> <p>T18N R5E</p> <hr style="width: 100px; margin: 0 auto;"/> <p>S3 S2 WC</p> <p>T17N</p> <p>1956</p> </div> <p>Bury original corner stone alongside iron post.</p> <p>from which</p> <p style="padding-left: 40px;">A pinon, 4 ins. diam., bears S. 65° E., 11 lks. dist., marked T17N R5E S2 BT WC.</p> <p>Desc. 250 ft. over W. slope.</p>
12.10	Top of ledge, about 30 ft. high, faces S. 80° W.
19.40	Draw, drains N. 40° W.
20.30	Road, graded, bears N. and S.
40.90	<p>The ¼ sec. cor. of sec. 3, which is monumented with a sandstone, 10 x 3 x 30 ins., marked ¼ on N. face.</p> <p>from which</p> <p style="padding-left: 40px;">A cedar, 10 ins. diam., bears S. 66° E., 57 lks. dist., marked ¼ S3 BT.</p> <p>At the corner point</p> <p>Set an iron post, 30 ins. long, 2½ ins. diam., 8 ins. in ground, and in a mound of stone, 3 ft. base to top, with brass cap marked</p>

Dependent Resurvey, N. Bdy., T. 17 N., R. 5 E.

Chains

T18N R5E

 $\frac{1}{4}$ S 3

T17N R5E

1956

Bury original corner stone alongside iron post.

from which

A cedar, 8 ins. diam., bears S. 40° W., 33 lks. dist.,
marked $\frac{1}{4}$ S3 BT.

N. 89° 42' W., beginning new measurement.

Continue descent; desc. 100 ft. over broken general N. 80° W. slope.

6.60 Road, bears N. and S.

10.70 Wash, 20 lks. wide, 1 ft. deep, drains N. 85° W.

13.40 Wash, 15 lks. wide, 2 ft. deep, drains N. 80° W.

26.00 Asc. 140 ft. over N. 80° E. slope.

30.70 Wash, 30 lks. wide, 2½ ft. deep, drains N. 15° W.

38.84 The closing cor. for T. 18 N., R. 5 E., secs. 33 and 34, a sandstone, properly set, marked, and witnessed as described in the official record.

40.28 The cor. of secs. 3 and 4, which is monumented with a sandstone, 16 x 6 x 30 ins., marked with 3 notches on E. and W. edges, set in a mound of stone.

from which

A cedar, 16 ins. diam., bears S. 65° W., 65 lks. dist.,
marked T17N R5E S4 BT.

At the corner point

Set an iron post, 30 ins. long, 2½ ins. diam., 10 ins. in ground, and in a mound of stone, 3 ft. base to top, with brass cap marked

T18N R5E

 $\frac{S4}{S3}$

T17N R5E

1956

Bury original corner stone alongside iron post.

from which

A cedar, 6 ins. diam., bears S. 54° E., 76 lks. dist.,
marked T17N R5E S3 BT.

Land; foothills, medium slopes.

Soil, broken sandstone and sandy loam.

Timber, cedar and pinon; undergrowth, manzanita, oak, grass, palo verde, and thinly scattered cacti.

Dependent Resurvey, N. Bdy., T. 17 N., R. 5 E.

Chains

N. 89° 48' W., along the N. bdy. of sec. 4.

Over rolling hilly land, through medium heavy timber.

1.40 Northern end of low mountain that bears N. 10° W. and S. 10° E.; desc. 250 ft. over broken, general N. 75° W. slope.

14.00 Wash, 8 lks. wide, 1 ft. deep, drains NW.

22.30 Thence along south side of Dry Creek.

40.49 The $\frac{1}{4}$ sec. cor. of sec. 4, which is monumented with a sandstone, 30 x 10 x 3 ins., marked $\frac{1}{4}$ on N. face, set in a mound of stone.

from which

A cedar, 26 ins. diam., bears S. 22° E., 75 lks. dist., marked $\frac{1}{4}$ S4 BT.

At the corner point

Set an iron post, 30 ins. long, 2 $\frac{1}{2}$ ins. diam., 22 ins. in ground, with brass cap marked

T18N R5E

 $\frac{1}{4}$ S 4
T17NR5E
1956

Raise a mound of stone, 3 ft. base, 2 ft. high, N. of cor.

Corner point falls about 60 lks. S. of Dry Creek.

N. 89° 47' W., beginning new measurement.

2.10 Dry Creek, 120 lks. wide, 2 ft. deep, drains S. 10° W.; thence asc. 125 ft. over broken general S. 80° E. slope.

7.60 Wash, 40 lks. wide, 2 ft. deep, drains S. 30° E.

20.00 Hill, slopes N. 10° W.; desc. 60 ft. over W. slope.

28.60 Wash, 30 lks. wide, 3 $\frac{1}{2}$ ft. deep, drains S.; asc. 30 ft. over broken E. slope.

34.60 Power line, bears S. 60° E. and N. 60° W.

38.92 The closing corner of T. 18 N., R. 5 E., secs. 32 and 33, a sandstone, 24 x 12 x 6 ins., marked with 2 notches on W., 4 notches on E. edge. Cornerstone in deteriorated condition. Replace with an iron post, 30 ins. long, 2 $\frac{1}{2}$ ins. diam., set 6 ins. in ground and in a mound of stone, 4 ft. base to top, with brass cap marked
CC
T18N R5E
S32|S33
1956

40.28 Bury original corner stone alongside the iron post. The cor. of secs. 4 and 5, which is monumented with a sandstone, 12 x 16 x 10 ins., marked with 2 notches on W. and 4 notches on E. edges, lying on top of ground.

from which

Dependent Resurvey, N. Bdy., T. 17 N., R. 5 E.

Chains

A cedar, 16 ins. diam., bears S. 23° 30' E., 78 lks. dist., marked T17N R5E S4 BT.

At the corner point

Set an iron post, 30 ins. long, 2½ ins. diam., 6 ins. in ground, and in a mound of stone, 4 ft. base to top, with brass cap marked

T18N R5E

S5	S4
T17N R5E	
1956	

Bury original corner stone alongside the iron post.

from which

A cedar, 10 ins. diam., bears S. 77° 30' W., 105 lks. dist., marked T17N R5E S5 BT.

Land, rolling, hilly.

Soil, broken sandstone, and sandy loam.

Timber, cedar, pinon, and in bottom of Dry Creek a few yew;

Undergrowth, palo verde, manzanita, oak, grass, and cacti.

S. 89° 43' W., along the N. bdy. of sec. 5.

Over broken, hilly land, through medium heavy timber.

Ascend 480 ft. over general N. 70° E. slope.

38.40

The ¼ sec. cor. of sec. 5, which is monumented with a sandstone 16 x 8 x 5 ins., marked with ¼ on N. face, set 10 ins. in ground, 25 lks. E. of base of vertical wall of Doe Mountain.

from which

A dead cedar, 15 ins. diam., bears S. 70° E., 60 lks. dist., marked ¼ S5 BT.

At the corner point

Set an iron post, 30 ins. long, 2½ ins. diam., 6 ins. in ground, and in a mound of stone, 4 ft. base to top, with brass cap marked

¼	S 5
T17N R5E	
1956	

Bury original corner stone alongside iron post.

from which

A pinon, 7 ins. diam., bears S. 20° W., 6 lks. dist., marked ¼ S5 BT.

N. 89° 44' W., beginning new measurement.

.25

Base of vertical wall of Doe Mountain, bears N. 30° W. and S. 30° E. Asc. 200 ft. to top.

Dependent Resurvey, N. Bdy., T. 17 N., R. 5 E.

Chains

- 1.00 Top of wall, thence over nearly level top of Doe Mountain, through medium dense timber and brush.
- 26.00 Top of vertical wall, bears S. 50° W. and N. 50° E.; desc. abruptly 170 ft.
- 27.50 Base of wall, thence desc. 190 ft. over steep NW. slope.
- 39.74 The cor. of secs. 5 and 6, which is monumented with a sandstone, 24 x 8 x 2 ins., marked with 5 notches on E. and 1 notch on W. edges, set 12 ins. in ground.
- from which
- A pinon, 8 ins. diam., bears S. 87° W., 81 lks. dist., marked T17N R5E S6 BT
- At the corner point
- Set an iron post, 30 ins. long, 2½ ins. diam., 6 ins. in ground, and in a mound of stone, 3 ft. base to top, with brass cap marked
- T18N R5E

S6 | S5

T17N R5E

1956
- Bury original cornerstone alongside iron post.
- from which
- A cedar, 18 ins. diam., bears S. 27° E., 165 lks. dist., marked T17N R5E S5 BT.
- Land, mountainous.
Soil, broken sandstone and sand.
Timber, cedar and pinon; undergrowth, oak, catclaw, palo verde, Spanish dagger, sparse grass, and cacti.
-
- N. 89° 45' W., along the N. bdy. of sec. 6.
- Continue descent over NW. slope of Doe Mountain, through medium heavy timber.
- Desc. 220 ft.
- 1.52 The closing cor. for secs. 31 and 32, T. 18 N., R. 5 E., a sandstone, 24 x 14 x 3 ins., set, marked, and witnessed as described in the official record.
- 8.00 Enter clearing.
- 25.90 Wash, 20 lks. wide, 3 ft. deep, drains S. 10° W.; thence continue over low, rolling land.
- 34.00 Enter scattered timber.
- 39.90 The ¼ sec. cor. of sec. 6, which is monumented with a sandstone, 24 x 14 x 3 ins., marked ¼ on N. face, set in a mound of stone.
- At the corner point
- Set an iron post, 30 ins. long, 2½ ins. diam., 18 ins. in ground, and in a mound of stone, 3 ft. base to top, with brass cap marked

Dependent Resurvey, N. Bdy., T. 17 N., R. 5 E.

Chains

T18N R5E

 $\frac{1}{4}$ S 6

T17N

1956

from which

A cedar, 4 ins. diam., bears S. 60° E., 176 lks. dist., marked $\frac{1}{4}$ S6 BT.

N. 89° 50' W., beginning new measurement.

4.50 Road, graded, bears NE. and SW.

40.10 The Township cor. of Ts. 17 and 18 N., Rs. 4 and 5 E.

Land, east 1/3 steep; west 2/3 low, rolling.

Soil, broken sandstone, sand.

Timber, cedar and pinon; undergrowth, catclaw, oak, palo verde, grass, and cacti.

Dependent Resurvey of a Portion of the Subdivisional Lines
T. 17 N., R. 5 E.

Reestablishment of the survey executed by
R. C. Powers in 1886 and W. O. Secor in
1902 and 1904 and the Dependent Resurvey
by W. O. Secor in 1902 and 1904.

From the standard cor. of secs. 35 and 36, on the S. bdy of the township.

N. 0° 23' W., between secs. 35 and 36, marking and blazing the true line.

Along grassy gentle W. slope through scattered timber.

2.90 Wash, 30 lks. wide, 4 ft. deep, drains W.

26.50 Wash, 45 lks. wide, 3 ft. deep, drains W.

34.20 Wash, 70 lks. wide, 4 ft. deep, drains S. 80° W.; asc. 50 ft. over general S. 80° W. slope.

40.30 The $\frac{1}{4}$ sec. cor. of secs. 35 and 36, which is monumented with a mound of stone. This position has long been recognized as the original cor. by local landowners and its position is verified by topography from the original notes. It is accepted as the best existing evidence of the position of the original cor.

At the corner point

Set an iron post, 30 ins. long, 2 $\frac{1}{2}$ ins. diam., 8 ins. in the ground, and in a mound of stone 3 ft. base to top, with brass cap marked

Dependent Resurvey of a Portion of the Subdivision, T. 17 N., R. 5 E.

Chains

T17N R5E

 $\frac{1}{4}$

S35|S36

1956

from which

A pinon, 8 ins. diam., bears N. 83° W., 83 lks. dist.,
marked $\frac{1}{4}$ S35 BT.

A pinon, 8 ins. diam., bears S. 19° E., 79 lks. dist.,
marked $\frac{1}{4}$ S36 BT.

N. 0° 04' W., beginning new measurement.

Continue ascent; asc. 330 ft. over broken S. 80° W. slope.

29.00 Wash, 10 lks. wide, 3 ft. deep, drains SW.

29.50 Foot of sandstone spur, with vertical wall about 150 ft. high,
bears S. 80° W. and N. 80° E.

30.00 Top of wall.

34.20 Spur, projects S. 80° W. from Cathedral Rock. Cathedral Rock
bears N. 80° E., about 12 chains dist.

34.80 Desc. abruptly 160 ft. over nearly vertical N. 20° W. slope.

39.37 The cor. of secs. 25, 26, 35, and 36, which is monumented with a
sandstone, 24 x 30 x 6 ins. with 1 notch on S. and 1 notch on E.
edges, set in a mound of stone.

from which

A cedar, 30 ins. diam., bears N. 37° W., 67 lks. dist.,
marked T17N R5E S26 BT.

At the corner point

Set an iron post, 30 ins. long, 2½ ins. diam., over X on solid
sandstone, and in a mound of stone, 3 ft. base to top, with brass
cap marked

T17N R5E

S26|S25

S35|S36

1956

Set original corner stone alongside iron post.

from which

A pinon, 6 ins. diam., bears N. 70° E., 54 lks. dist.,
marked T17N R5E S25 BT.

The corner point is at the head of a prominent wash that drains
S. 80° W., on the W. side of Cathedral Rock.

Land, south half almost level; north half rough, mountainous.
Soil, broken sandstone and sandy loam.

Timber, south half sparse to scattered cedar and pinon; north half
medium heavy cedar and pinon.

Undergrowth, grass, palo verde, Spanish dagger, catclaw, oak, and
cacti.

Dependent Resurvey of a Portion of the Subdivision, T. 17 N., R. 5 E.

Chains

From the cor. of secs. 25, 30, 31, and 36, on the east boundary of the township.

S. 89° 38' W., bet. secs. 25 and 36.

Over broken land, through heavy timber.

5.40 Wash, 30 lks. wide, 5 ft. deep, drains N. 10° W.

13.60 Fence, bears N. and S.

16.20 Wash, 50 lks. wide, 3½ ft. deep, drains N. 25° W.; asc. 105 ft. over broken E. slope.

27.80 Wash, 25 lks. wide, 3 ft. deep, drains N.

37.23 The ¼ sec. cor. of secs. 25 and 36, which is monumented with a cross and ¼ chiseled on sandstone ledge, with a mound of stone, 3 ft. base, 2 ft. high, N. of cor. point.

from which

A dead pinon, 12 ins. diam., bears S. 87° E., 10 lks. marked ¼ S36 BT.

At the corner point

Set an iron post, 14 ins. long, 1 in. diam., 5 ins. in solid sandstone, in cement, in drilled hole, with brass cap marked

T17N R5E
 ¼ $\frac{S\ 25}{S\ 36}$
 1956

Raise a mound of stone, 2½ ft. base, 2½ ft. high, N. of cor.

from which

A yew, 12 ins. diam., bears N. 26° 30' E., 65 lks. dist., marked ¼ S25 BT.

A yew, 12 ins. diam., bears South, 163 lks. dist., marked ¼ S36 BT.

Corner point falls on sandstone ledge on steep E. slope of Cathedral Rock.

N. 89° 56' W., beginning new measurement.

Continue ascent; asc. 250 ft. over steep E. slope.

13.00 Bottom of center butte of three buttes comprising Cathedral Rock; asc. 200 ft. over nearly vertical E. face of butte.

18.00 Top of butte; thence desc. 400 ft. along precipitous N. face of south butte and desc. over cliffs and ledges on W. face to corner point.

35.67 The cor. of secs. 25, 26, 35, and 36.

Land, broken, precipitous.

Soil, broken sandstone and sandy loam.

Timber, cedar, pinon and yew.

Undergrowth, grass, oak, manzanita, palo verde, and cacti.

Dependent Resurvey of a Portion of the Subdivision, T. 17 N., R. 5 E.

Chains	N. 0° 53' E., bet. secs. 25 and 26. Over rough, precipitous spurs and bluffs, through scattered timber. Asc. 88 ft. over precipitous S. slope.
2.80	Hogsback slopes W.; desc. 80 ft. over N. slope.
10.50	Wash, 10 lks. wide, 3 ft. deep, drains N. 80° W.; asc. 160 ft. over S. slope.
19.50	Spur, projects N. 80° W., about 3 chs. to sheer cliff; desc. 55 ft. over N. slope.
22.80	Top of red sandstone cliff facing N. on short spur that projects N. 85° W.; desc. 75 ft.
27.60	Top of nearly vertical bluff that bears N. 70° E. and S. 70° W.; desc. 230 ft. to bottom; thence along nearly level stream valley of Oak Creek.
41.04	The $\frac{1}{4}$ sec. cor. of secs. 25 and 26, which is monumented with a concrete block, 4x4x24 ins., set 12 ins. in ground. This point was established by a private surveyor, and affected property owners have agreed to accept it as the corner point. There is no remaining evidence of the original corner. At the corner point Set an iron post, 30 ins. long, $2\frac{1}{2}$ ins. diam. against concrete block, established by private surveyor, in a cement mound, 3 ft. base to top, with brass cap marked T17N R5E $\frac{1}{4}$ S26 S25 1956 From which A sycamore, 15 ins. diam., bears N. 85° E. 72 lks. dist., marked $\frac{1}{4}$ S25 BT. A sycamore, 15 ins. diam., bears S. 75° W., 110 lks. dist., marked $\frac{1}{4}$ S26 BT.
	N. 3° 27' W., beginning new measurement
	Continue over nearly level land, through dense timber in Oak Creek stream valley, about 3 chs. E. of Oak Creek.
8.00	Oak Creek, 50 lks. wide, $1\frac{1}{2}$ ft. deep, drains S. 70° W.
26.40	Leave dense timber.
27.20	Fence, bears N. 75° E. and S. 75° W.; thence across grassy field.
37.00	Fence, bears N. 75° E. and S. 75° W., begin ascent.
37.40	Road, graded, bears N. 45° E. and S. 45° W.; asc. abruptly 100 ft. over very steep S. slope.
40.13	The point accepted for the position of the corner of secs. 23, 24, 25, and 26, identical with a point established by Charles Dryden, Registered Professional Engineer, for the State of Arizona, conforms to a proportionate position based on the record measurement east and west as surveyed by R. C. Power in 1886 and is at record distance north of the foot of a slope which is an identifiable item of topography. This point is accepted as the best available evidence of the position of the original corner and is harmoniously related to adjacent identified lot corners and in agreement with the nearest topographic call of the original survey, the foot of a slope south of the

Dependent Resurvey of a Portion of the Subdivision, T. 17 N., R. 5 E.

Chains

corner. All of the original land owners in secs. 24, 25, and 26 affected by the corner position have accepted this point for the corner and have had or expressed their intentions to have all their land surveyed and subdivided, deeds changed, and easements granted to conform to this corner position.

At the corner point

Set a brass tablet, $\frac{3}{4}$ ins. diam., $\frac{3}{2}$ ins. stem in cement, in crack of solid rock outcrop, against a 1 in. pipe established by private surveyor, brass tablet marked

T17 N R5E	
S23	S24
S26	S25
1956	

from which

A pinon, 5 ins. diam., bears S. 43° W., 51 lks. dist., marked T17N R5E S26 BT.

A pinon, 10 ins. diam., bears N. 53° W., 117 lks. dist., marked T17N R5E S23 BT.

Land, south half precipitous and mountainous; north half mostly in Oak Creek stream bed.

Soil, broken sandstone, gravelly, sandy loam.

Timber, south half cedar and pinon; north half sycamore, hackberry, ash, cedar, and pinon.

Undergrowth, grass.

From the corner of secs. 19, 24, 25, and 30, on the E. bdy. of the Tp.

S. $89^{\circ} 56'$ W., bet. secs. 24 and 25

Over mountainous land, through scattered timber; asc. 125 ft. over broken N. 20° E. slope.

- 2.00 Road, bladed, bears N. 25° E. and S. 15° W.
- 3.70 Wash, 20 lks. wide, 3 ft. deep, drains S.
- 8.90 Same road, bladed, bears SE. and NW.
- 10.05 South edge of same road.
- 17.90 Road, bladed, bears N. 15° E. and S. 15° W.
- 18.20 Ridge, bears N. 20° E. and S. 20° W.; desc. 260 ft. over steep rolling, general N. 30° W. slope.
- 31.20 Power line, bears N. 25° E. and S. 25° W.
- 37.20 Edge of vertical wall of bluff that bears N. 30° E. and S. 30° W.; desc. abruptly, 150 ft. to corner point.
- 38.23 Point for the $\frac{1}{4}$ sec. cor. of secs. 24 and 25, at proportionate dist.; there is no remaining evidence of the original corner.

Set an iron post, 30 ins. long, $2\frac{1}{2}$ ins. in diam., 12 ins. in ground, and in a mound of stone, 3 ft. base to top, with brass cap marked

T17N R5E	
$\frac{1}{4}$	S 24
	S 25
1956	

Dependent Resurvey of a Portion of the Subdivision, T. 17 N., R. 5 E.

Chains	
	<p>from which</p> <p>A hackberry, 8 ins. diam., bears N. 70° E., 5 lks. dist., marked $\frac{1}{4}$ S24 BT</p> <p>A cedar, 5 ins. diam., bears S. 47° W., 22 lks. dist., marked $\frac{1}{4}$ S25 BT</p>
40.00	Oak Creek, 40 lks. wide, 2 ft. deep, flows SW.; thence over nearly level land, along N. side of Oak Creek, through heavy timber.
63.20	Fence, bears N. and S.; leave creek bottom and timber; thence across cultivated field.
70.00	Fence, bears N. 20° E. and S. 20° W.; begin ascent.
70.20	Road, graded, bears N. 20° E. and S. 20° W.; asc. 70 ft. over steep general SE. slope.
76.46	The corner of secs. 23, 24, 25, and 26.
	<p>Land, mountainous.</p> <p>Soil, broken sandstone, gravelly and sandy loam.</p> <p>Timber, cedar, pinon, sycamore, and hackberry.</p> <p>Undergrowth, grass, oak brush, manzanita, and cacti.</p>
	N. 2° 59' E., bet. secs. 23 and 24.
	Over mountainous land, through scattered timber.
	Asc. abruptly 50 ft. over cliff facing S.; thence asc. 65 ft. over steep S. slope.
3.90	Spur slopes S. 60° E.; desc. 50 ft. over broken general NE. slope.
11.80	Wash, 25 lks. wide, 2 ft. deep, drains S. 20° E.
20.00	Wash, 10 lks. wide, 1 ft. deep, drains SE.; asc. 40 ft. along E. slope.
30.00	Main wash, at bottom of small canyon, 15 lks. wide, 1½ ft. deep, drains S. 5° E.; asc. 100 ft. along E. edge of wash, over S. 80° W. slope to corner point.
39.99	Point for the $\frac{1}{4}$ sec. cor. of secs. 23 and 24, at proportionate distance; there is no remaining evidence of the original corner.
	Set an iron post, 30 ins. long, 7 ins. in ground, and in a mound of stone, 3 ft. base to top, with brass cap marked
	<p>T17N R5E</p> <p>$\frac{1}{4}$</p> <p>S23 S24</p> <p>1956</p>
	from which
	A pinon, 7 ins. diam., bears N. 19° E., 35 lks. dist., marked $\frac{1}{4}$ S24 BT.
	A pinon, 10 ins. diam., bears S. 89° W., 90 lks. dist., marked $\frac{1}{4}$ S23 BT
	Continue ascent; asc. 400 ft. over broken S. 80° W. slope.
70.00	Draw, drains S. 60° W.

Dependent Resurvey of a Portion of the Subdivision, T. 17 N., R. 5 E.

Chains

79.98

The cor. of secs. 13, 14, 23, and 24, which is monumented with a malpais stone, 15 X 20 X 10 ins., marked with 3 notches on S., 1 notch on E. edges, set in a mound of stone.

At the corner point

Set an iron post, 30 ins. long, 2½ ins. diam., 10 ins. in ground, and in a mound of stone, 3½ ft. base to top, with brass cap marked

T17N R5E
S14 | S13
 S23 | S24
 1956

Bury the original corner stone alongside the iron post.

from which

A cedar, 10 ins. diam., bears N. 35° E., 203 lks. dist., marked T17N R5E S13 BT.

A cedar, 6 ins. diam., bears S. 43° E., 120 lks. dist., marked T17N R5E S24 BT.

A cedar, 8 ins. diam., bears S. 24° W., 162 lks. dist., marked T17N R5E S23 BT.

A cedar, 8 ins. diam., bears N. 80° W., 41 lks. dist., marked T17N R5E S14 BT.

Land, mountainous.

Soil, rocky, sandy.

Timber, cedar and pinon.

Undergrowth, palo verde, grass, and cacti.

From the cor. of secs. 13, 18, 19, and 24, on the E. bdy. of the township.

S. 89° 32' W., bet. secs. 13 and 24.

Over mountainous land, through scattered timber.

Asc. 380 ft. over broken S. 30° E. slope to ¼ sec. cor.

28.00

Wash, 20 lks. wide, 3 ft. deep, drains S.

34.00

Bottom of vertical wall, about 70 ft. high, bears N. 10° E., S. 50° W.

35.60

The ¼ sec. cor. of secs. 13 and 24, which is monumented with a malpais stone, 22 X 12 X 6 ins., marked ¼ on N. face.

from which

A dead cedar tree, 15 ins. diam., bears S. 80° E., 20 lks. dist., marked ¼ S24 BT.

At the corner point

Set an iron post, 30 ins. long, 2½ ins. diam., 6 ins. in ground, and in a mound of stone, 4 ft. base to top, with brass cap marked

T17N R5E
¼ S13
 S24
 1956

Dependent Resurvey of a Portion of the Subdivision, T. 17 N., R. 5 E.

Chains	
	<p>Bury original corner stone alongside the iron post.</p> <p>from which</p> <p>A cedar, 14 ins. diam., bears S. 88° W., 31 lks. dist., marked $\frac{1}{4}$ S24 BT.</p> <hr/> <p>S. 89° 06' W., beginning new measurement.</p> <p>Continue ascent; asc. 90 ft. over SE. slope.</p>
6.00	Top of slope, thence over gentle general SE. slope of nearly flat topped mountain.
10.50	Sedona landing field strip, bears N. 20° E. and S. 20° W.
40.20	The cor. of secs. 13, 14, 23, and 24.
	<p>Land, east $\frac{2}{3}$ mountainous; west $\frac{1}{3}$ nearly level. Soil, rocky and sandy. Timber, cedar and pinon. Undergrowth, palo verde, oak brush, grass, and cacti.</p>
	<p>N. 0° 25' W., bet. secs. 13 and 14.</p> <p>Over gentle SE. slope of mountain top, through scattered timber.</p>
12.50	Top of slope; desc. 375 ft. over NW. slope to $\frac{1}{4}$ sec. cor.
40.60	The $\frac{1}{4}$ sec. cor. of secs. 13 and 14, which is monumented with a 1 inch iron post, set, marked, and witnessed as described in the official record of Exchange Survey No. 678, accepted October 16, 1950.
	<p>From the cor. of secs. 1, 2, 11, and 12, a 2 inch iron post, set, marked, and witnessed as described in the official record of Exchange Survey No. 678.</p> <p>N.0°17' W., bet. secs. 1 and 2.</p> <p>Over steep mountainous land, through scattered timber.</p> <p>Asc. 145 ft. along SW. slope.</p>
10.60	Spur, slopes N. 80° W.; desc. 100 ft. over steep N. slope.
14.50	Power line, bears N. 80° E. and S. 80° W.
20.50	Wash, 8 lks. wide, 1 ft. deep, drains S. 80° W.; asc. 90 ft. over S. slope.
33.00	Small ridge, bears SE. and NW.; desc. 15 ft. along NE. slope.
40.00	Wash, 3 lks. wide, 6 ins. deep, drains SE.
40.43	The $\frac{1}{4}$ sec. cor. of secs. 1 and 2, which is monumented with a sandstone, 30 x 8 x 6 ins., marked $\frac{1}{4}$ on W. face, set in a mound of stone.
	from which

Dependent Resurvey of a Portion of the Subdivision, T. 17 N., R. 5 E.

Chains	
	<p>A cedar, 12 ins. diam., bears N. 63° W., 45 lks. dist., marked $\frac{1}{4}$ S2 BT.</p> <p>A cedar, 10 ins. diam., bears N. 84° E., 66 lks. dist., marked $\frac{1}{4}$ S1 BT.</p> <p>At the corner point</p> <p>Set an iron post, 30 ins. long, $2\frac{1}{2}$ ins. diam., 6 ins. in ground to bedrock, and in a mound of stone, 4 ft. base to top, with brass cap marked</p> <p style="text-align: center;">T17N R5E $\frac{1}{4}$ S2 S1 1956</p> <p>Bury original corner stone alongside the iron post.</p> <hr/> <p>N. 1° 18' E., beginning new measurement.</p> <p>Asc. 1000 ft. over broken and precipitous slopes, to top of ridge.</p> <p>Begin ascent over general S. slope.</p> <p>9.00 Spur, slopes S. 80° W.; thence continue ascent along steep S. 80° W. slope.</p> <p>20.00 Mouth of cave, 20 ft. high, at base of vertical mountain wall that bears NW. and SE., about 300 ft. high.</p> <p>24.00 High ridge, bears NW. and SE.; desc. 600 ft. over precipitous broken general NE. slope to corner point.</p> <p>38.70 Point for the cor. of secs. 1 and 2, on the N. bdy. of the township, falls on inaccessible face of mountain wall. The witness corner for secs. 1 and 2 bears S. 89° 48' E., 14 lks. dist.</p> <p>Land, mountainous. Soil, rocky and sandy. Timber, cedar and pinon. Undergrowth, palo verde, grass, and cacti.</p> <hr/> <p>From the standard cor. of secs. 34 and 35, on the S. bdy. of the township.</p> <p>N. 1° 30' E., bet. secs. 34 and 35.</p> <p>Over mountainous land, through scattered timber.</p> <p>Asc. 110 ft. along S. 70° W. slope.</p> <p>4.90 Spur, slopes S. 70° W.; desc. 320 ft. over broken land with a general N. slope.</p> <p>24.70 Power line, bears NW. and SE.</p> <p>32.00 Foot of isolated hill; asc. 30 ft. over S. slope.</p> <p>35.00 Top of hill; desc. 30 ft. over N. slope.</p> <p>41.90 The $\frac{1}{4}$ sec. cor. of secs. 34 and 35, which is monumented with a sandstone, 18 x 20 x 5 ins., lying loose in a mound of stone, marked $\frac{1}{4}$.</p>

Dependent Resurvey of a Portion of the Subdivision, T. 17 N., R. 5 E.

Chains

At the corner point

Set an iron post, 30 ins. long, 2½ ins. diam., 10 ins. in ground, and in a mound of stone, 4 ft. base to top, with brass cap marked

T17N R5E

¼

S34|S35

1956

Bury original corner stone alongside iron post.

from which

A cedar, 10 ins. diam., bears S. 62° E., 48 lks. dist., marked ¼ s35 BT.

A limb of cedar, 30 ins. diam., bears S. 63° W., 34 lks. dist., marked ¼ S34 BT.

N. 0° 07' E., beginning new measurement.

Continue descent; desc. 80 ft. over N. slope.

- 4.20 Road, bladed, bears S. 85° E. and N. 85° W.
- 11.80 Wash, 30 lks. wide, 1 ft. deep, drains N. 80° E.
- 13.80 Power line, bears N. 70° W. and S. 70° E.
- 19.30 Wash, 70 lks. wide, 1 ft. deep, drains N. 80° W.; thence asc. 50 ft. over rolling W. slope, to corner point.
- 23.80 Telephone line, bears NE. and SW.
- 27.80 Wash, 30 lks. wide, 1 ft. deep, drains NW. 40 lks.; thence SW.
- 29.80 Telephone line, bears N. 75° W. and S. 75° E.
- 38.00 Private road, with locked gate, bears N. 70° W. and S. 70° E.; thence along fence bearing N.
- 40.04 The cor. of secs. 26, 27, 34, and 35, which is monumented with a sandstone, 12 x 10 x 6 ins., set in a mound of stone.

from which

A pinon, 16 ins. diam., bears S. 50° E., 15 lks. dist., marked T17N R5E S35 BT.

At the corner point

Set an iron post, 30 ins. long, 2½ ins. diam., 6 ins. in ground and in a mound of stone, 3 ft. base to top, with brass cap marked

T17N R5E

S27|S26

S34|S35

1956

from which

Dependent Resurvey of a Portion of the Subdivision, T. 17 N., R. 5 E.

Chains	
	<p>A pinon, 8 ins. diam., bears S. 78° W., 102 lks. dist., marked T17N R5E S34 BT.</p> <p>A cedar, 4 ins. diam., bears N. 25° W., 30 lks. dist., marked T17N R5E S27 BT.</p> <p>A pinon, 5 ins. diam., bears N. 30° E., 42 lks. dist., marked T17N R5E S26 BT.</p> <p>Land, mountainous. Soil, rocky and sandy. Timber, cedar and pinon. Undergrowth, palo verde, grass, and cacti.</p>
	<p>From the cor. of secs. 25, 26, 35, and 36.</p> <p>Over mountainous land, through medium heavy timber. N. 88° 17' W., bet. secs. 26 and 35. Desc. 230 ft. over W. slope.</p> <p>20.40 Wash, 75 lks. wide, 15 ft. deep, drains N. 5° E.; asc. 310 ft. over steep broken E. slope.</p> <p>34.15 Top of mountain, bears N. 5° E. and S. 5° W.; desc. 90 ft. over W. slope, to corner point.</p> <p>39.22 Point for the $\frac{1}{4}$ sec. cor. of secs. 26 and 35, at proportionate distance; there is no remaining evidence of the original corner.</p> <p>Set an iron post, 30 ins. long, 2$\frac{1}{2}$ ins. diam., over X on solid sandstone, and in a mound of stone, 3 ft. base to top, with brass cap marked</p>
	$\begin{array}{r} \text{T17N R5E} \\ \frac{1}{4} \frac{\text{S26}}{\text{S35}} \\ 1956 \end{array}$
	<p>from which</p> <p>A pinon, 6 ins. diam., bears N. 48° W., 219 lks. dist., marked $\frac{1}{4}$ S26 BT.</p> <p>A pinon, 4 ins. diam., bears S. 87° 30' W., 88 lks. dist., marked $\frac{1}{4}$ S35 BT.</p>
	<p>Continue descent; desc. 320 ft. over broken W. slope.</p>
62.00	<p>Road, graded, bears NE. and SW.</p>
72.00	<p>Bottom of slope; thence asc. 20 ft. over broken S. 80° E. slope.</p>
78.44	<p>The cor. of secs. 26, 27, 34, and 35.</p>
	<p>Land, mountainous. Soil, broken sandstone and sandy loam. Timber, cedar and pinon. Undergrowth, palo verde, oak, grass, and cacti.</p>

Dependent Resurvey of a Portion of the Subdivision, T. 17 N., R. 5 E.

Chains

N. 0° 04' E., bet. secs. 26 and 27.

Over mountainous land, through scattered timber.

Asc. 90 ft. over S. slope.

9.20 Slope changes to W.

15.00 Top of ascent, on W. slope of small isolated mountain; desc. 120 ft. over N. 10° W. slope, through heavy oak brush.

19.00 Ditch, with running water, flows S. 50° W.

21.00 Bottom of slope; thence across Oak Creek stream bed, through heavy timber.

23.00 Oak Creek, 40 lks. wide, 1 ft. deep, flows S. 80° W.

30.70 Spring, flows S. 60° W.

31.50 Fence, bears E. and W.

33.10 Fence, bears E. and W.

33.80 Ditch, with running water, flows S. 50° E.

35.60 Ditch, with running water, flows S. 80° W.

35.60 Fence, bears S. 80° W. and N. 80° E.

38.30 Fence, bears E. and W.; thence through yard of private dwelling.

39.83 Point for the $\frac{1}{4}$ sec. cor. of secs. 26 and 27, at proportionate distance; there is no remaining evidence of the original corner. Point falls in driveway that bears E. and W.Set a brass tablet, $3\frac{1}{4}$ ins. diam., $3\frac{1}{2}$ in. stem, in a concrete form 6 ins. diam., 12 ins. long, and set 14 ins. in ground, with top marked

T17N R5E

 $\frac{1}{4}$
 S27|S26
 1956

from which

A cedar, 12 ins. diam., bears S. 25° W., 148 lks. dist., marked $\frac{1}{4}$ S27 BT.

SW. corner of porch on house owned by Fred E. Schuerman, bears N. 63° 30' E., 86.4 lks. dist.

Thence along 1 ch. W. of house and across cultivated field.

46.20 N. end of field, power line, bears N. 3° E.; asc. 30 ft. over rolling broken general S. 80° E. slope, through medium heavy timber.

54.49 Road, graded, bears NE. and SW.

55.70 Small wash, drains E.

59.20 Small wash, drains E.

60.30 Small wash, drains E.

72.70 Small wash, drains S. 80° E.

Dependent Resurvey of a Portion of the Subdivision, T. 17 N., R. 5 E.

Chains

78.40

Fence, bears N. 60° E. and S. 60° W.

79.66

The cor. of secs. 22, 23, 26 and 27, is determined from the remains of an original bearing tree.

A juniper stump, 12 ins. diam., bears S. 3° E., 120 lks. dist., markings apparent but not readable.

A pinon, 11 ins. diam., bears S. 26° E., 108 lks. dist., marked S XXVI.

At the corner point

Bury an iron post, 30 ins. long, 2½ ins. diam., 2 ins. under ground with brass cap marked

T17N	R5E
S22	S23
S27	S26
1956	

Raise a mound of stone, 3 ft. base, 2 ft. high, W. of corner point.

Corner falls on W. side of graded road.

from which

A cedar, 10 ins. diam., bears S. 35° W., 98 lks. dist., marked T17N R5E S27 BT.

A pinon, 10 ins. diam., bears N. 59° W., 137 lks. dist., marked T17N R5E S22 BT.

A brass tablet, 3½ ins. diam., 3½ in. stem, set in cement, in supporting structure of cattle guard, for reference monument, bears S. 68° E., 18 lks. dist., with cap marked

T17N	R5E
S22	S23
S27	S26
RM	

1956

Land, broken, semi-mountainous.

Soil, broken sandstone, sandy loam.

Timber, cedar, pinon, and in stream bottom sycamore, ash, and hackberry.

Undergrowth, palo verde, oak, grass, manzanita, and cacti.

From the cor. of secs. 23, 24, 25 and 26.

N. 89° 27' W., bet. secs. 23 and 26.

Over broken, semi-mountainous land, through scattered timber.

Asc. 60 ft. along broken S. slope.

3.30

Wash, 30 lks. wide, 4 ft. deep, drains SW.

8.30

Road, bladed, bears S. 30° E. and N. 30° W.

9.50

Road, bladed, line crosses on "U" curve.

Dependent Resurvey of a Portion of the Subdivision, T. 17 N., R. 5 E.

Chains	
12.50	Spur, slopes S.; desc. 175 ft. over general S. 80° W. slope.
20.30	Road, graded, bears S. 65° E. and N. 65° W.
37.00	Same road, bears N. 20° E. and S. 20° W.
38.30	The $\frac{1}{4}$ sec. cor. of secs. 23 and 26, which is monumented with a 1 in. iron pipe, 18 ins. long, set 12 ins. in ground. This point was established by a private surveyor, and all affected property owners have agreed to accept it. It is accepted as the best available evidence of the position of the original corner.
	At the corner point
	Set an iron post, 30 ins. long, $2\frac{1}{2}$ ins. diam., 20 ins. in ground, alongside original 1 in. iron pipe, with brass cap marked
	T17N R5E $\frac{1}{4}$ $\frac{S23}{S26}$ 1956
	Raise a mound of stone, 3 ft. base, $2\frac{1}{2}$ ft. high, N. of corner.
	from which
	A pinon, 20 ins. diam., bears S. 56° W., 29 lks. dist., marked $\frac{1}{4}$ S26 BT.
	A cedar, 8 ins. diam., bears N. 60° W., 49 lks. dist., marked $\frac{1}{4}$ S23 BT.
	N. 89° 26' W., beginning new measurement.
	Desc. 15 ft. over gradual N. 80° W. slope.
9.60	Wash, 1 ch. wide, 3 ft. deep, drains S. 50° E.; asc. 20 ft. along broken general S. slope.
30.50	Wash, 60 lks. wide, 3 ft. deep, drains S. 15° E.
33.30	Road, graded, bears generally E. and W.
38.00	Road, graded, bears NW. and SE.
38.33	The cor. of secs. 22, 23, 26, and 27.
	Land, east half, semi-mountainous; west half gently rolling. Soil, broken sandstone and sandy loam. Timber, cedar and pinon. Undergrowth, palo verde, oak, manzanita, grass, and cacti.
	N. 0° 03' E., bet. secs. 22 and 23.
	Over rolling, broken land, through scattered timber.
.30	Road, graded, bears NW. and SE.
7.00	Wash, 10 lks. wide, 1 ft. deep, drains S. 55° E.; asc. 90 ft. over broken slopes, general SE. drainage.
13.00	Wash, 5 lks. wide, 1 ft. deep, drains S. 80° E.
20.00	Spur, slopes S. 80° E.

Dependent Resurvey of a Portion of the Subdivision, T. 17 N., R. 5 E.

Chains
 24.20 Road, primitive, bears N. 60° W. and S. 60° E.
 28.50 Desc. 90 ft. over N. 10° E. slope.
 35.50 Wash, 12 lks. wide, 2 ft. deep, drains S. 80° E.; asc. 30 ft. over broken general S. slope.
 39.40 The ¼ sec. cor. of secs. 22 and 23, is determined from an original bearing tree.

A cedar, 12 ins. diam., bears S. 20° W., 28 lks. dist., marked ¼ S BT.

At the corner point

Set an iron post, 30 ins. long, 2½ ins. diam., 6 ins. in ground, and in a mound of stone, 4 ft. base to top, with brass cap marked

T17N R5E
 ¼
 S22|S23
 1956

from which

A cedar, 12 ins. diam., bears S. 20° E., 25 lks. dist., marked ¼ S23 BT.

N. 1° 02' E., beginning new measurement.

Continue ascent; asc. 40 ft. over S. slope.

8.00 Foot of steep broken S. 20° W. slope, with limestone outcroppings; asc. 170 ft.

12.50 Road, old, bears S. 80° E. and N. 80° W.

17.80 Saddle, in spur that slopes SE.; desc. 15 ft. over NE. slope.

20.85 Same road, bears SE. and NW.

24.00 Wash, flows S. 50° E.; asc. 90 ft. over S. 10° W. slope.

28.00 Slope changes; asc. 50 ft. along general W. slope.

39.80 The cor. of secs. 14, 15, 22, and 23, which is monumented with a sandstone, 12 x 10 x 6 ins., marked with 3 notches on S. and 2 notches on E. edges, set in a mound of stone.

At the corner point

Set an iron post, 30 ins. long, 2½ ins. diam., 6 ins. in ground, and in a mound of stone, 3 ft. base to top, with brass cap marked

T17N R5E
 S15|S14
 S22|S23
 1956

Set original corner stone alongside the iron post.

Dependent Resurvey of a Portion of the Subdivision, T. 17 N., R. 5 E.

Chains

from which

A cedar, 10 ins. diam., bears S. 41° W., 26 lks. dist.,
marked T17N R5E S22 BT.

A pinon, 8 ins. diam., bears N. 35° E., 46 lks. dist.,
marked T17N R5E S14 BT.

A cedar, 6 ins. diam., bears S. 5° E., 32 lks. dist.,
marked T17N R5E S23 BT.

A cedar, 8 ins. diam., bears N. 26° W., 93 lks. dist.,
marked T17N R5E S15 BT.

Land, rolling, broken, semi-mountainous.

Soil, rocky, sandy.

Timber, cedar and pinon.

Undergrowth, palo verde, oak brush, sparse grass, and cacti.

From the cor. of secs. 13, 14, 23, and 24.

S. 89° 23' W., bet. secs. 14 and 23.

Over mountainous land, through scattered timber.

Desc. 460 ft. over general S. 80° W. slope.

32.80 Wash, 50 lks. wide, 4 ft. deep, drains S. 10° E.; asc. 15 ft. over
E. slope.

40.62 The $\frac{1}{4}$ sec. cor. of secs. 14 and 23, which is monumented with a
sandstone, 15 x 8 x 3 ins., marked $\frac{1}{4}$ on N. face, set in a mound
of stone.

from which

A cedar, 18 ins. diam., bears N. 62° E., 95 lks. dist.,
marked $\frac{1}{4}$ S BT.

At the corner point

Set an iron post, 30 ins. long, 2 $\frac{1}{2}$ ins. diam., 10 ins. in ground,
and in a mound of stone, 4 ft. base to top, with brass cap marked

$$\begin{array}{r} \text{T17N R5E} \\ \frac{1}{4} \frac{\text{S14}}{\text{S23}} \\ 1956 \end{array}$$

Bury original corner stone alongside the iron post.

from which

A cedar, 10 ins. diam., bears S. 76° E., 84 lks. dist.,
marked $\frac{1}{4}$ S23 BT.

N. 89° 32' W., beginning new measurement.

Continue ascent; asc. 200 ft. over broken general N. 80° E. slope.

Dependent Resurvey of a Portion of the Subdivision, T. 17 N., R. 5 E.

Chains	
1.70	Wash, 15 lks. wide, 1½ ft. deep, drains N. 20° E.
11.90	Wash, 30 lks. wide, 2 ft. deep, drains S. 40° E.
17.20	Wash, 10 lks. wide, 1 ft. deep, drains N. 25° E.
35.10	Wash, 25 lks. wide, 2½ ft. deep, drains NE.
37.70	Spur, slopes SE.; desc. 5 ft. over W. slope.
39.53	The cor. of secs. 14, 15, 22, and 23.
	Land, mountainous. Soil, rocky and sandy. Timber, cedar and pinon. Undergrowth, oak, palo verde, sparse grass, and cacti.
	N. 0° 21' W., bet. secs. 14 and 15. Over hilly land, through medium heavy timber. Gradually asc. along W. slope.
2.40	Desc. 40 ft. over N. slope.
13.00	Wash, 25 lks. wide, 1½ ft. deep, drains N. 20° E.; continue descent, desc. 75 ft. along broken general N. 80° E. slope.
26.20	Leave medium heavy timber, enter widely scattered timber.
35.70	Wash, 15 lks. wide, 4 ft. deep, drains N. 15° E.
37.50	Wash, 25 lks. wide, 7 ft. deep, drains N. 15° E.; asc. 10 ft. over S. slope.
40.04	The ¼ sec. cor. of secs. 14 and 15, which is monumented with a sandstone, 10 x 6 x 14 ins., marked ¼ on W. face, set on fence line running N. and W.
	At the corner point Set an iron post, 30 ins. long, 2½ ins. diam., 10 ins. in ground, and in a mound of stone, 3 ft. base to top, with brass cap marked T17N R5E ¼ S15 S14 1956
	Bury original corner stone alongside the iron post. from which A cedar, 8 ins. diam., bears S. 49° E., 33 lks. dist., marked ¼ S14 BT. A pinon, 8 ins. diam., bears N. 85° W., 24 lks. dist., marked ¼ S15 BT. SE. cor. of shed, in corral, bears NW. 1 ch. dist.
	N. 0° 22' E., beginning new measurement.

Dependent Resurvey of a Portion of the Subdivision, T. 17 N., R. 5 E.

Chains	Continue ascent; asc. 10 ft. over S. slope.								
3.00	Top of hill; desc. 40 ft. over N. slope.								
15.50	Enter open flat, covered with small erosion ditches draining easterly.								
24.30	Main wash, 1 ch. wide, 12 ft. deep, drains S. 30° E.; asc. 35 ft. over S. slope.								
24.70	Leave open flat, enter scattered timber.								
31.70	Fence, bears E. and W.								
35.10	Top of small knoll, enter clearing; desc. 5 ft. over N. slope.								
39.60	Fence, right-of-way for U. S. Highway 89A, bears S. 35° W. and N. 35° E.								
39.85	The cor. of secs. 10, 11, 14, and 15, 50 lks. S. of U. S. Highway 89A that bears E. and W., which is monumented with a 1 in. iron pipe, 36 ins. long, set 24 ins. in ground. This position is harmoniously related to existing original corners, has long been recognized as the corner by local land owners, and is accepted as the best existing evidence of the original corner.								
	At the corner point								
	Set an iron post, 30 ins. long, 2½ ins. diam., 22 ins. in the ground, with brass cap marked								
	<table style="margin-left: auto; margin-right: auto;"> <tbody> <tr> <td colspan="2">T17N R5E</td> </tr> <tr> <td style="border-right: 1px solid black; border-bottom: 1px solid black;">S10</td> <td style="border-bottom: 1px solid black;">S11</td> </tr> <tr> <td style="border-right: 1px solid black;">S15</td> <td>S14</td> </tr> <tr> <td colspan="2" style="text-align: center;">1956</td> </tr> </tbody> </table>	T17N R5E		S10	S11	S15	S14	1956	
T17N R5E									
S10	S11								
S15	S14								
1956									
	Raise a mound of stone, 2 ft. high, 4 ft. base, W. of cor.								
	Land, hilly and broken.								
	Soil, sandy loam and gravelly.								
	Timber, cedar and pinon.								
	Undergrowth, oak, palo verde, grass, and cacti.								
	From the cor. of secs. 11, 12, 13, and 14, a 2 in. iron pipe, set, marked, and witnessed as described in the official record.								
	N. 89° 39' W., bet. secs. 11 and 14.								
	Over low rolling land, through scattered timber, across private property.								
	Desc. 30 ft. over W. slope.								
22.60	Wash, 50 lks. wide, 7 ft. deep, drains S., about 2½ chs. into main wash.								
26.70	Main wash, 1 ch. wide, 6 ft. deep, drains SE.; asc. 30 ft. over E. slope.								
29.00	Thence over gently rolling land.								
39.94	The ¼ sec. cor. of secs. 11 and 14, which is monumented with a 1 in. iron pipe, 36 ins. long, set 15 ins. in ground. This position is harmoniously related to existing original corners, has long been recognized as the cor. by land owners and is accepted as the best existing evidence of the original corner.								

Dependent Resurvey of a Portion of the Subdivision, T. 17 N., R. 5 E.

Chains

At the corner point

Set an iron post, 30 ins. long, $2\frac{1}{2}$ ins. diam., 8 ins. in ground to bedrock, and in a mound of stone, 2 ft. base to top, with brass cap marked

T17N R5E
 $\frac{1}{4}$ $\frac{S11}{S14}$
 1956

from which

A cedar, 10 ins. diam., bears S. 74° W., 33 lks. dist., marked $\frac{1}{4}$ S14 BT.

A cedar, 12 ins. diam., bears N. 81° E., 34 lks. dist., marked $\frac{1}{4}$ S11 BT.

N. $89^\circ 39'$ W.; beginning new measurement.

33.50 Road, dirt, bears N. about 1.50 chs. to U. S. Highway 89A and S. 20° E.

34.40 Wash, 20 lks. wide, 4 ft. deep, drains S. 20° W.

39.97 The cor. of secs. 10, 11, 14, and 15.

Land, west half nearly level; east half low rolling.
 Soil, sandy and sandy loam, some sandstone outcrops.
 Timber, thinly scattered cedar.
 Undergrowth, oak, grass, and cacti.

N. $0^\circ 42'$ W., bet. secs. 10 and 11.

Over nearly level land, across grassy clearing.

1.00 U. S. Highway 89A, bears N. 75° E. and SW.

2.00 Fence, highway right-of-way, runs parallel to highway.

2.90 House, bears W., 10 lks. dist.

10.00 Enter scattered timber.

13.00 Wash, 20 lks. wide, 4 ft. deep, drains S. 40° E.; asc. 80 ft. over broken general S. 20° W. slope.

15.20 Fence, bears N. 25° E. and S. 25° W.

28.60 Wash, 60 lks. wide, $4\frac{1}{2}$ ft. deep, drains S. 5° W.

33.00 Same wash, 40 lks. wide, 5 ft. deep, drains S. 5° E.

39.14 The $\frac{1}{4}$ sec. cor. of secs. 10 and 11, which is monumented with a sandstone, 15 x 6 x 3 ins., marked $\frac{1}{4}$ on W. face, set in a mound of stone.

from which

A cedar, 6 ins. diam., bears N. 55° W., 29 lks. dist., marked $\frac{1}{4}$ S BT.

Dependent Resurvey of a Portion of the Subdivision, T. 17 N., R. 5 E.

Chains

A cedar, 8 ins. diam., bears N. 30° E., 46 lks. dist.,
marked $\frac{1}{2}$ S BT.

At the corner point

Set an iron post, 30 ins. long, 2½ ins. diam., 4 ins. in ground,
and in a mound of stone, 3 ft. base to top, with brass cap marked

T17N R5E
 $\frac{1}{2}$
S10|S11
1956

Bury original corner stone alongside the iron post.

N. 0° 36' W., beginning new measurement.

Continue ascent; asc. 50 ft. over broken land, through medium
heavy timber.

- 12.50 Power line, bears N. 40° E. and S. 40° W.
17.20 Power line, bears N. 35° E. and S. 35° W.
23.40 Wash, 30 lks. wide, 2 ft. deep, drains S. 15° E.; asc. 90 ft. over
SW. slope.
33.00 Slope changes; asc. 200 ft. along broken W. slope.
38.95 The cor. of secs. 2, 3, 10, and 11, which is monumented with a
sandstone, 26 x 12 x 4 ins., marked with 5 notches on S. and 2
notches on E. edges, set in a mound of stone.

from which

A pinon, 5 ins. diam., bears N. 9° E., 39 lks. dist.,
marked T17N R5E S2 BT.

A cedar, 20 ins. diam., bears S. 77° E., 77 lks. dist.,
marked T17N R5E S11 BT.

At the corner point

Set an iron post, 30 ins. long, 2½ ins. diam., 14 ins. in ground,
and in a mound of stone, 4 ft. base to top, with brass cap marked

T17N R5E
S3|S2
S10|S11
1956

Bury original corner stone alongside the iron post.

from which

A pinon, 6 ins. diam., bears N. 87° W., 48 lks. dist.,
marked T17N R5 E S3 BT.

A cedar, 6 ins. diam., bears S. 88° W., 48 lks. dist.,
marked T17N R5E S10 BT.

Land, south half nearly level; north half broken, semi-mountainous.
Soil, broken sandstone, sandy, and sandy loam.
Timber, cedar and pinon.
Undergrowth, oak, manzanita, palo verde, grass, and cacti.

Dependent Resurvey of a Portion of the Subdivision, T. 17 N., R. 5 E.

Chains

From the cor. of secs. 1, 2, 11, and 12, a 2 inch iron post, set, marked, and witnessed as described in the official record.

S. 89° 52' W., bet. secs. 2 and 11.

Over semi-mountainous land, through scattered timber.

Desc. 45 ft. over broken W. slope of isolated mountain.

8.30 Wash, 30 lks. wide, 1 ft. deep, drains S.; asc. 25 ft. out of wash, thence along gentle S. slope.

10.00 Road, old, bears N. and S.

39.20 Small wash, drains S.

40.41 The $\frac{1}{4}$ sec. cor. of secs. 2 and 11, which is monumented with a sandstone, 16 x 10 x 5 ins., marked $\frac{1}{4}$ on N. face, set in a mound of stone.

from which

A fallen cedar, 15 ins. diam., bears N. 74° 30' W., 2.28 chs. dist., marked S2 BT.

A dead cedar, 22 ins. diam., bears S. 63° 30' W., 2.36 chs. dist., marked $\frac{1}{4}$ S11 BT.

At the corner point

Set an iron post, 30 ins. long, 2 $\frac{1}{2}$ ins. diam., 8 ins. in ground and in a mound of stone, 4 ft. base to top, with brass cap marked

T17N R5E
 $\frac{1}{4}$ $\frac{S\ 2}{S11}$
 1956

Bury original corner stone alongside the iron post.

S. 89° 46' W., beginning new measurement.

Asc. 100 ft. over broken moderate E. slope.

.10 Fence, bears N. and S.

3.30 Power line, bears N. 60° E. and S. 60° W.

7.60 Wash, 10 lks. wide, 1 ft. deep, drains S.

14.20 Wash, 10 lks. wide, 1 ft. deep, drains SE. on curve from N.

26.00 Base of very steep rocky E. slope of isolated sandstone mountain; asc. 300 ft.

34.90 E. rim of narrow bench, bears N. and S.

36.20 Crest of narrow bench, bears N. and S. Sandstone pinnacle, about 70 ft. high, bears N. about 4 chs.; desc. 135 ft. over steep W. slope.

40.31 The cor. of secs. 2, 3, 10, and 11.

Dependent Resurvey of a Portion of the Subdivision, T. 17 N., R. 5 E.

Chains

Land, middle portion gently sloping; east and west 1/3 mountainous.
Soil, rocky, broken sandstone, and sandy.
Timber, cedar and pinon.
Undergrowth, oak, palo verde, grass, and cacti.

N. 0° 40' E., bet. secs. 2 and 3.

Over mountainous land, through scattered timber.

Asc. 135 ft. over SW. face of nearly vertical cliff.

3.00 Top of cliff, thence asc. 40 ft. along W. slope.

7.50 Sandstone pinnacle, bears E. about 2 chs.

8.60 Begin descent; desc. 200 ft. over N. 20° W. slope.

21.30 Wash, at bottom of valley, 15 lks. wide, 10 ft. deep, drains W.

26.50 Base of steep south slope; asc. 185 ft.

30.57 Point selected for the witness $\frac{1}{4}$ sec. cor. of secs. 2 and 3 falls at base of sandstone wall, 500 ft. high, that bears N. 85° W. and S. 85° E.

Set an iron post, 30 ins. long, $2\frac{1}{2}$ ins. diam., over X on solid sandstone, and in a mound of stone, 4 ft. base to top, with brass cap marked

T17N R5E
W C
 $\frac{1}{4}$
S3↑S2
1956

from which

A pinon, 5 ins. diam., bears S. 30° E., 42 lks. dist., marked WC $\frac{1}{4}$ S2 BT.

A cedar, 10 ins. diam., bears S. 85° W., 89 lks. dist., marked WC $\frac{1}{4}$ S3 BT.

Thence by traverse; true line runs across precipitous and inaccessible mountain; asc. 500 ft.

35.00 Top of nearly vertical wall; thence asc. 50 ft. over steep S. slope.

40.52 Point for the $\frac{1}{4}$ sec. cor. of secs. 2 and 3, at proportionate distance. Point falls where monument cannot be perpetuated.

Continue ascent; asc. 50 ft. over steep S. slope.

42.00 Spur, slopes S. 80° W.; thence desc. about 200 ft. along precipitous broken N. 70° W. slope.

53.00 Wash, drains N. 70° W.

56.00 Spur, slopes N. 70° W.

63.00 Wash, drains N. 70° W.

Dependent Resurvey of a Portion of the Subdivision, T. 17 N., R. 5 E.

Chains	
66.00	Spur, slopes N. 70° W.
70.00	Wash, drains N. 70° W.
79.50	Spur, slopes N. 70° W.
80.14	<p>Point for the cor. of secs. 2 and 3, falls at an inaccessible position. Witness corner for secs. 2 and 3 bears N. 89° 42' W., 9.35 chs. dist.</p> <p>Land, precipitous and mountainous. Soil, broken sandstone and sand. Timber, cedar, pinon and yew. Undergrowth, oak, palo verde, manzanita, and cacti.</p>
From the standard cor. of secs. 33 and 34, on the S. bdy. of the township.	
N. 4° 46' E., bet. secs. 33 and 34.	
Over mountainous land, through medium heavy timber, along broken gradual W. slope.	
2.50	Wash, 25 lks. wide, 1½ ft. deep, drains NW.
5.00	Wash, 10 lks. wide, 3 ft. deep, drains W.
6.50	Desc. 200 ft. over broken general N. slope.
9.00	Wash, 35 lks. wide, 3 ft. deep, drains W.
17.00	Wash, 90 lks. wide, 10 ft. deep, drains NW.
22.50	Wash, 50 lks. wide, 6 ft. deep, drains NW.
27.00	Fence, bears E. and W.
28.00	Ditch, with running water, flows NW.
36.40	Road, bladed, bears E. and W.; thence through Oak Creek stream bed, through heavy timber.
38.60	Oak Creek, 90 lks. wide, 1½ ft. deep, flows N. 70° W.
40.78	<p>The ¼ sec. cor. of secs. 33 and 34, which is monumented with an iron pipe, 30 ins. long, 1 in. diam., set 20 ins. in ground. This position is harmoniously related to existing original corners and is accepted as the best existing evidence of the position of the original corner.</p>
At the corner point	
Set an iron post, 30 ins. long, 2½ ins. diam., 10 ins. in ground, and in a cemented mound of stone, 4 ft. base to top, with brass cap marked	
<p style="text-align: center;">T17N R5E ¼ S33 S34 1956</p>	
from which	
A sycamore, 18 ins. diam., bears N. 71° 30' E., 76 lks. dist., marked ¼ S34 BT.	
A sycamore, 6 ins. diam., bears N. 18° W., 92 lks. dist., marked ¼ S33 BT.	

Dependent Resurvey of a Portion of the Subdivision, T. 17 N., R. 5 E.

Chains

N. 4° 46' E., beginning new measurement.

Continue along, through Oak Creek stream bed.

- 11.00 Road, bladed, bears N. 15° W. and S. 15° E.
- 15.00 Leave Oak Creek stream bed, thence through scattered timber.
- 15.50 Road, graded, bears N. 85° W. and S. 85° E.; asc. 60 ft. over rolling broken general W. slope.
- 36.50 Head of wash, 20 lks. wide, 3 ft. deep, drains N. 80° W.
- 41.07 The cor. of secs. 27, 28, 33, and 34, which is monumented with a sandstone, 36 x 20 x 6 ins., marked with 3 notches on E., 1 notch on S. edges, set in a mound of stone.

from which

A pinon, 6 ins. diam., bears N. 85° W., 30 lks. dist., marked T17N R5E S28 BT.

A pinon, 8 ins. diam., bears N. 26° E., 25 lks. dist., marked T17N R5E S27 BT.

A cedar, 14 ins. diam., bears S. 75° W., 20 lks. dist., marked T17N R5E S33 BT.

At the corner point

Set an iron post, 30 ins. long, 2½ ins. diam., 6 ins. in ground, and in a mound of stone, 3 ft. base to top, with brass cap marked

T17N	R5E
S28	S27
S33	S34
1956	

Bury original corner stone alongside the iron post.

from which

A cedar, 6 ins. diam., bears S. 52° E., 45 lks. dist., marked T17N R5E S34 BT.

Land, hilly, semi-mountainous.

Soil, broken sandstone, sandy.

Timber, cedar, pinon, sycamore near Oak Creek.

Undergrowth, palo verde, oak, manzanita, and cacti.

From the cor. of secs. 26, 27, 34, and 35

S. 89° 00' W., bet. secs. 27 and 34

Over semi-mountainous land, through scattered timber.

Desc. 20 ft. over general SW. slope.

- 1.50 Road, bladed, bears NW. and SE.
- 3.30 Edge of sandstone bluff, bears S. 70° E. and N. 70° W.; desc. 35 ft. to bottom; thence desc. 20 ft. over gentle SW. slope.

Dependent Resurvey of a Portion of the Subdivision, T. 17 N., R. 5 E.

Chains

- 9.00 Fence, bears NE. and SW.
- 10.00 Enter Oak Creek stream bed.
- 15.00 Oak Creek, 50 lks. wide, flows S. 15° E.
- 17.80 Foot of sandstone bluff, bears N. 60° W. and S. 60° E.; asc. 70 ft. abruptly, thence asc. 50 ft. over general S. slope.
- 25.40 Fence, bears N. and S.
- 26.00 Slope changes, desc. 100 ft. over W. slope.
- 37.02 Point for the $\frac{1}{4}$ sec. cor. of secs. 27 and 34, at proportionate distance; there is no remaining evidence of the original corner. Point falls in center of private dirt road, that bears N. 30° W. and S. 30° E.
- Set a brass tablet, $\frac{3}{4}$ ins. diam., $\frac{3}{2}$ ins. stem, in a 1 in. iron pipe, 30 ins. long, 18 ins. in the ground, in a mound of stone to top, with top mkd.
- T17N R5E
 $\frac{1}{4}$ $\frac{S27}{S34}$
 1956
- from which
- A cedar, 12 ins. diam., bears N. 27° E., 2.18 chs. dist., mkd $\frac{1}{4}$ S 27 B T.
- A cedar, 8 ins. diam., bears S 79° W., 1.40 chs. dist., mkd $\frac{1}{4}$ S 34 B T.
- Continue descent; desc. 20 ft. over S. 80° W. slope, through medium heavy timber.
- 40.68 Edge of bluff, bears N. 60° W. and S. 60° E.; desc. abruptly 25 ft. to bottom.
- 41.50 Oak Creek, 50 lks. wide, $1\frac{1}{2}$ ft. deep, flows NW.; thence across Oak Creek stream bed through medium dense timber.
- 47.00 Leave stream bed; asc. 20 ft. over gentle NE. slope.
- 47.50 Fence, bears N. 50° W. and S. 50° E.
- 50.50 Road, bears N. and S.
- 53.00 Desc. 30 ft. over gentle W. slope.
- 57.00 Oak Creek, 1 ch. wide, $1\frac{1}{2}$ ft. deep, drains S.; asc. 105 ft. over nearly vertical wall of bluff that bears NE. and S.
- 59.00 Top of bluff, thence asc. 50 ft. over E. slope.
- 65.00 Ridge, bears N. and S.; desc. 120 ft. over broken general SW. slope.
- 65.50 Road, graded, bears N. and S.
- 71.50 Wash, 10 lks. wide, 3 ft. deep, drains S. 60° W.
- 74.03 The cor. of secs. 27, 28, 33, and 34.
- Land, hilly, with bluffs along Oak Creek.
 Soil, broken sandstone, sand, gravelly in stream bed.
 Timber, cedar, pinon, and sycamore.
 Undergrowth, oak, manzanita, palo verde, grass and cacti.

Dependent Resurvey of a Portion of the Subdivision, T. 17 N., R. 5 E.

Chains	
	N. 0° 09' E., bet. secs. 27 and 28. Over broken hilly land, through scattered timber. Asc. 90 ft. over S. slope.
8.00	Top of slope; desc. 50 ft. over N. slope.
11.90	Wash, 40 lks. wide, 6 ft. deep, drains W.
19.40	Road, graded, bears E. and W.; asc. 70 ft. over general S. slope.
40.09	The $\frac{1}{4}$ sec. cor. of secs. 27 and 28, which is monumented with a mound of stone. from which A cedar, 30 ins. diam., bears S. 60° W., 14 lks. dist., marked $\frac{1}{4}$ S BT. At the corner point Set an iron post, 30 ins. long, 2 $\frac{1}{2}$ ins. diam., 6 ins. in ground, and in a mound of stone, 3 ft. base to top, with brass cap marked T17N R5E $\frac{1}{4}$ S28 S27 1956 from which A pinon, 8 ins. diam., bears S. 41° 30' E., 55 lks. dist., marked $\frac{1}{4}$ S27 BT.
	N. 0° 09' W., beginning new measurement. Continue ascent; asc. 8 ft. over S. slope.
3.10	Top of slope; desc. 30 ft. over N. slope.
8.80	Wash, 1 ch. wide, 25 ft. deep, drains NE.
12.80	Bottom of vertical sandstone cliff, bears N. 80° W. and S. 80° E.; asc. abruptly 180 ft. to top; thence asc. 220 ft. along W. slope of small canyon that drains S. 10° W.
29.00	Wash at bottom of canyon, 80 lks. wide, 7 ft. deep, drains S. 10° W.; asc. 110 ft. along S. 80° E. slope.
39.34	The cor. of secs. 21, 22, 27, and 28, is determined from an original bearing tree, point for the corner falls among loose rocks on surface of ground, and from which the original bearing tree A cedar, 14 ins. diam., bears NE. 98 lks. dist., marked T17N R5E S22 BT. At the corner point Set an iron post, 30 ins. long, 2 $\frac{1}{2}$ ins. diam., 6 ins. in ground, and in a mound of stone, 3 ft. base to top, with brass cap marked

Dependent Resurvey of a Portion of the Subdivision, T. 17 N., R. 5 E.

Chains

T17N R5E	
S21	S22
S28	S27
1956	

No other bearing trees within limits.

Land, south half hilly; north half mountainous.

Soil, south half broken sandstone and sand; north half malpais rocks and **sandy** loam.

Timber, cedar and pinon.

Undergrowth, palo verde, Spanish dagger, grass and cacti.

From the cor. of secs. 22, 23, 26, and 27.

S. 87° 20' W., bet. secs. 22 and 27, over mountainous land, through scattered timber.

Asc. 140 ft. along steep general N. slope.

22.00 Slope changes; desc. 65 ft. over broken general NW. slope.

23.00 Wash, 20 lks. wide, 1 ft. deep, drains N.

33.00 Wash, 25 lks. wide, 1 ft. deep, drains N. 10° E.; asc. 40 ft. over E. slope.

39.36 The $\frac{1}{4}$ sec. cor. of secs. 22 and 27, is determined from the original bearing trees.

A cedar, 24 ins. diam., bears N. 85° W., 50 lks. dist., marked $\frac{1}{4}$ S22 BT.

A pinon, 12 ins. diam., bears East, 133 lks. dist., marked $\frac{1}{4}$ S27 BT.

At the corner point

Set an iron post, 30 ins. long, 2½ ins. diam., 10 ins. in ground, and in a mound of stone, 5 ft. base to top, with brass cap marked

T17N R5E	
$\frac{1}{4}$ S22	
S27	
1956	

N. 89° 39' W., beginning new measurement.

Continue ascent; asc. 420 ft. over general N. 85° E. slope.

25.00 Ridge, bears N. and S.; desc. 80 ft. over W. slope.

31.00 Wash, 15 lks. wide, 1 ft. deep, drains S.; asc. 20 ft. over E. slope.

34.86 The cor. of secs. 21, 22, 27, and 28.

Land, mountainous.

Soil, broken sandstone, malpais rocks, and sand.

Timber, cedar and pinon.

Undergrowth, palo verde, oak, cacti, and grass.

Dependent Resurvey of a Portion of the Subdivision, T. 17 N., R. 5 E.

Chains	N. 1° 10' E., bet. secs. 21 and 22.
	Asc. 105 ft. over S. slope.
7.00	Slope changes; asc. 125 ft. along E. slope.
35.50	Slope changes; desc. 115 ft. over NE. slope to corner point.
39.71	Point for the $\frac{1}{4}$ sec. cor. of secs. 21 and 22, at proportionate distance; there is no remaining evidence of the original corner.
	Set an iron post, 30 ins. long, 2 $\frac{1}{2}$ ins. diam., 3 ins. in ground to bedrock, and in a mound of stone, 3 ft. base to top, with brass cap marked
	T17N R5E $\frac{1}{4}$ S21 S22 1956
	from which
	A pinon, 5 ins. diam., bears S. 74° E., 105 lks. dist., marked $\frac{1}{4}$ S22 BT.
	A cedar, 4 ins. diam., bears N. 61° 15' W., 61 lks. dist., marked $\frac{1}{4}$ S21 BT.
	Continue descent; desc. 250 ft. along broken general E. slope.
46.40	Wash, 15 lks. wide, 1 ft. deep, drains N. 80° E.
59.20	Wash, 1 ch. wide, 5 ft. deep, drains SE.
79.42	The cor. of secs. 15, 16, 21 and 22, which is monumented with a mound of stone.
	from which
	A cedar, 14 ins. diam., bears S. 60° E., 24 lks. dist., marked T17N R5E S22 BT.
	At the corner point
	Set an iron post, 30 ins. long, 2 $\frac{1}{2}$ ins. diam., 8 ins. in ground, and in a mound of stone, 3 $\frac{1}{2}$ ft. base to top, with brass cap marked
	T17N R5E <u>S16 S15</u> S21 S22 1956
	from which
	A pinon, 12 ins. diam., bears S. 30° W., 179 lks. dist., marked T17N R5E S21 BT.
	A pinon, 12 ins. diam., bears N. 31° E., 153 lks. dist., marked T17N R5E S15 BT.
	A cedar, 6 ins. diam., bears N. 51° W., 72 lks. dist., marked T17N R5E S16 BT.
	Land, mountainous.
	Soil, malpais rocks, broken sandstone, and sand.
	Timber, cedar and pinon.
	Undergrowth, oak, palo verde, manzanita, cacti, and grass.

Dependent Resurvey of a Portion of the Subdivision, T. 17 N., R. 5 E.

Chains	<p>From the cor. of secs. 14, 15, 22, and 23.</p> <p>S. 89° 01' W., bet. secs. 15 and 22.</p> <p>Over mountainous land, through scattered timber.</p> <p>Desc. 40 ft. over W. slope.</p> <p>2.50 Road, old, bears N. 15° W. and S. 15° E.</p> <p>12.00 Wash, 1 ch. wide, 5 ft. deep, drains S.; asc. 130 ft. over E. slope.</p> <p>26.90 Spur, slopes S.; thence desc. 50 ft. along broken general S. slope.</p> <p>30.00 Wash, 15 lks. wide, 4 ft. deep, drains S. 20° W.</p> <p>32.00 Spur, slopes S.</p> <p>36.40 Wash, 35 lks. wide, 2½ ft. deep, drains S.</p> <p>36.68 The ¼ sec. cor. of secs. 15 and 22, which is monumented with a sandstone, 14 x 10 x 6 ins., marked ¼ on N. face, and set in a mound of stone.</p> <p>At the corner point</p> <p>Set a brass tablet, 3¼ ins. diam., 3½ in. stem, in cement, in drilled hole, with top flush with solid sandstone, mkd.</p> <div style="text-align: center;"> <p>T17N R5E</p> <p>¼ $\frac{S\ 15}{S\ 22}$</p> <p>1956</p> </div> <p>Raise a mound of stone, 2½ ft. base, 2½ ft. high, N. of cor.</p> <p>from which</p> <p style="padding-left: 40px;">A cedar, 24 ins. diam., bears S. 46° W., 91 lks. dist., marked ¼ S22 BT.</p> <p style="padding-left: 40px;">A pinon, 12 ins. diam., bears N. 46° W., 155 lks. dist., marked ¼ S15 BT.</p> <hr style="width: 20%; margin: 10px auto;"/> <p>S. 89° 01' W., beginning new measurement.</p> <p>Asc. 25 ft. over E. slope.</p> <p>4.50 Spur, slopes S.; thence desc. 90 ft. along rolling, broken, general S. slope.</p> <p>9.10 Wash, 75 lks. wide, 4 ft. deep, drains S. 20° W.</p> <p>13.40 Spur, slopes S. 10° E.</p> <p>19.80 Wash, 60 lks. wide, 3 ft. deep, drains SW.</p> <p>23.10 Spur, slopes S.</p> <p>27.60 Wash, 30 lks. wide, 2 ft. deep, drains SE.; asc. 60 ft. over easterly slope.</p> <p>33.70 Road, graded, bears N. 35° W. and S. 35° E.</p> <p>36.72 The cor. of secs. 15, 16, 21 and 22.</p> <p>Land, broken.</p> <p>Soil, broken sandstone, and sand.</p> <p>Timber, cedar and pinon.</p> <p>Undergrowth, oak, palo verde, sparse grass, and cacti.</p>
--------	---

Dependent Resurvey of a Portion of the Subdivision, T. 17 N., R. 5 E.

Chains	
	N. 6° 51' W., bet. secs. 15 and 16. Over rolling land, through medium heavy timber. Desc. 30 ft. across broken hills with general NW. drainage to $\frac{1}{4}$ sec. cor.
15.50	Fence, highway right-of-way, bears S. 50° W. and N. 50° E.
16.50	U. S. Highway 89A, bears S. 50° W. and N. 50° E.
17.50	Fence, highway right-of-way, bears S. 50° W. and N. 50° E.
23.00	Road, bladed, bears NW. to garbage dump, about 20 chs. dist., and S. 20° E. to U. S. Highway 89A.
41.30	The $\frac{1}{4}$ sec. cor. of secs. 15 and 16, which is monumented with a sandstone, 6 x 12 x 3 ins., marked with $\frac{1}{4}$ on W. face, set in a mound of stone. from which A cedar, 20 ins. diam., bears S. 36° W., 95 lks. dist., marked $\frac{1}{4}$ S16 BT. At the corner point Set an iron post, 30 ins. long, 2 $\frac{1}{2}$ ins. diam., 10 ins. in ground, and in a mound of stone, 3 $\frac{1}{2}$ ft. base to top, with brass cap marked T17N R5 E $\frac{1}{4}$ S16 S15 1956 Bury original corner stone alongside the iron post. from which A pinon, 8 ins. diam., bears S. 22° E., 46 lks. dist., marked $\frac{1}{4}$ S15 BT.
	<hr/>
	N. 2° 21' W., beginning new measurement.
7.00	Wash, 30 lks. wide, 1 ft. deep, drains N. 60° W.
23.00	Fence, bears N. 25° W. and S. 25° E.
33.00	Wash, 50 lks. wide, 4 $\frac{1}{2}$ ft. deep, drains W.
38.00	Wash, drains W.
39.94	The cor. of secs. 9, 10, 15, and 16, which is monumented with a sandstone, 10 x 10 x 12 ins., marked with 4 notches on S. and 3 notches on E. edges, set in a mound of stone. from which A cedar, 14 ins. diam., bears N. 37° W., 50 lks. dist., marked T17N R5E S9 BT. A cedar, 8 ins. diam., bears N. 80° E., 72 lks. dist., marked T17N R5E S10 BT. At the corner point

Dependent Resurvey of a Portion of the Subdivision, T. 17 N., R. 5 E.

Chains

Set an iron post, 30 ins. long, $2\frac{1}{2}$ ins. diam., 10 ins. in ground, and in a mound of stone, $3\frac{1}{2}$ ft. base to top, with brass cap marked

T17N R5E	
S9	S10
S16	S15
1956	

Bury original corner stone, alongside the iron post.

from which

A pinon, 6 ins. diam., bears S. 25° E., 26 lks. dist., marked T17N R5E S15 BT.

A cedar, 18 ins. diam., bears S. 84° W., 80 lks. dist., marked T17N R5E S16 BT.

Land, broken and hilly.

Soil, broken sandstone and sand.

Timber, cedar and pinon.

Undergrowth, oak, palo verde, manzanita, sparse grass and cacti.

From the cor. of secs. 10, 11, 14, and 15.

N. $89^{\circ} 40'$ W., bet. secs. 10 and 15.

Over broken, hilly land, through scattered timber.

3.20 U. S. Highway 89A, bears N. 80° E. and S. 80° W.

7.50 Fence, right-of-way, bears N. 80° E. and S. 80° W.

12.40 Wash, 20 lks. wide, 3 ft. deep, drains S.

12.60 Road, graded, bears N. and S.; asc. 35 ft. along N. slope.

39.90 The $\frac{1}{4}$ sec. cor. of secs. 10 and 15, which is monumented with a sandstone, 28 x 8 x 4 ins., marked with $\frac{1}{4}$ on N. face, set alongside a fence, which bears E. and W.

At the corner point

Set an iron post, 30 ins. long, $2\frac{1}{2}$ ins. diam., 4 ins. in ground, and in a mound of stone, 4 ft. base to top, with brass cap marked

T17N R5E	
$\frac{1}{4}$	S10
$\frac{1}{4}$	S15
1956	

Bury original corner stone alongside the iron post.

from which

A cedar, 6 ins. diam., bears N. 62° W., 65 lks. dist., marked $\frac{1}{4}$ S10 BT.

A pinon, 4 ins. diam., bears S. 65° W., 62 lks. dist., marked $\frac{1}{4}$ S15 BT.

Dependent Resurvey of a Portion of the Subdivision, T. 17 N., R. 5 E.

Chains

S. 89° 32' W., beginning new measurement.

Desc. 45 ft. along N. slope.

5.30 Fence, bears E. and W.

17.00 Enter clearing, slope changes; desc. 30 ft. over gentle W. slope.

18.80 Wash, 45 lks. wide, 6 ft. deep, drains S. 60° W.

20.00 Leave clearing.

24.90 Fence, bears S. 10° W. and N. 10° E.

28.00 Enter clearing.

32.00 Leave clearing.

40.06 The cor. of secs. 9, 10, 15, and 16.

Land, hilly.

Soil, broken sandstone and sand.

Timber, cedar and pinon.

Undergrowth, oak, palo verde, sparse grass, and cacti.

N. 1° 25' W., bet. secs. 9 and 10.

Over hilly, broken land, through scattered timber.

Asc. 75 ft. over broken southerly slope.

3.30 Wash, 65 lks. wide, 2 ft. deep, drains S. 20° W.

17.10 Wash, 25 lks. wide, 4 ft. deep, drains S. 5° W.

27.00 Power line, bears N. 60° E. and S. 60° W.

38.88 The $\frac{1}{4}$ sec. cor. of secs. 9 and 10, which is monumented with a sandstone, 10 x 8 x 2 ins., marked $\frac{1}{4}$ on W. face, set in a mound of stone.

At the corner point

Set an iron post, 30 ins. long, 2 $\frac{1}{2}$ ins. diam., 14 ins. in ground, and in a mound of stone, 3 ft. base to top, with brass cap marked

T17N R5E

$\frac{1}{4}$

S9 | S10

1956

Bury original corner stone alongside the iron post.

from which

A cedar, 8 ins. diam., bears S. 89° 30' W., 31 lks. dist., marked $\frac{1}{4}$ S9 BT.

A cedar, 10 ins. diam., bears SE., 68 lks. dist., marked $\frac{1}{4}$ S10 BT.

BOOK 4553

Dependent Resurvey of a Portion of the Subdivision, T. 17 N., R. 5 E.

Chains									
	<p>N. 1° 22' W., beginning new measurement.</p> <p>Continue ascent; asc. 60 ft. over S. slope.</p>								
5.00	Fence, bears E. and W.								
11.60	Spur, slopes E.; house bears E. about 70 lks. dist.; desc. 75 ft. along E. slope.								
24.00	Road, bladed, bears NW. and SE.								
38.95	<p>The cor. of secs. 3, 4, 9, and 10, which is monumented with a sandstone, 15 x 8 x 6 ins., marked with 5 notches on S., 1 notch on E. edges, set in a mound of stone.</p> <p>from which</p> <p style="padding-left: 40px;">A cedar, 14 ins. diam., bears N. 11° W., 52 lks. dist., marked T17N R5E S4 BT.</p> <p>At the corner point</p> <p>Set an iron post, 30 ins. long, 2½ ins. diam., 20 ins. in ground, and in a mound of stone, 4 ft. base to top, with brass cap marked</p> <div style="text-align: center; margin: 10px 0;"> <table border="1" style="border-collapse: collapse; margin: auto;"> <tr> <td colspan="2" style="padding: 2px;">T17N R5E</td> </tr> <tr> <td style="padding: 2px; text-align: center;">S4</td> <td style="padding: 2px; text-align: center;">S3</td> </tr> <tr> <td style="padding: 2px; text-align: center;">S9</td> <td style="padding: 2px; text-align: center;">S10</td> </tr> <tr> <td colspan="2" style="padding: 2px;">1956</td> </tr> </table> </div> <p>Bury original corner stone alongside the iron post.</p> <p>from which</p> <p style="padding-left: 40px;">A cedar, 12 ins. diam., bears N. 70° E., 118 lks. dist., marked T17N R5E S3 BT.</p> <p style="padding-left: 40px;">A cedar, 20 ins. diam., bears S. 57° 30' E., 80 lks. dist., marked T17N R5E S10 BT.</p> <p style="padding-left: 40px;">A cedar, 36 ins. diam., bears S. 81° W., 30 lks. dist., marked T17N R5E S9 BT.</p> <p>Land, broken and hilly. Soil, broken sandstone and sand. Timber, cedar and pinon. Undergrowth, oak, palo verde, sparse grass, and cacti.</p>	T17N R5E		S4	S3	S9	S10	1956	
T17N R5E									
S4	S3								
S9	S10								
1956									
	<p>From the cor. of secs. 2, 3, 10, and 11.</p> <p>West, bet. secs. 3 and 10.</p> <p>Over mountainous land, through medium heavy timber.</p> <p>Desc. 130 ft. over steep W. slope of mountain.</p>								
5.30	Fence, bears S. 25° W. and N. 25° E.								
10.00	Bottom of steep W. mountain slope; thence desc. 130 ft. over moderate W. slope.								
19.70	Wash, 40 lks. wide, 3 ft. deep, drains SW.								

Dependent Resurvey of a Portion of the Subdivision, T. 17 N., R. 5 E.

Chains	
29.20	Power line, bears N. 10° E. and S. 10° W.
32.70	Road, private, dirt, bears N. 25° E. and S. 25° W.
35.40	Road, graded, bears N. 10° E. and S. 10° W.
40.43	The $\frac{1}{4}$ sec. cor. of secs. 3 and 10, which is monumented with a mound of stone.
	from which
	A cedar, 16 ins. diam., bears S. 6° E., 38 lks. dist., marked $\frac{1}{4}$ S10 BT.
	At the corner point
	Set an iron post, 30 ins. long, 2 $\frac{1}{2}$ ins. diam., 8 ins. in ground, and in a mound of stone, 3 ft. base, to top, with brass cap marked
	$\begin{array}{r} \text{T17N R5E} \\ \text{S } 3 \\ \hline \frac{1}{4} \text{ S10} \\ 1956 \end{array}$
	from which
	A pinon, 4 ins. diam., bears N. 46° E., 14 lks. dist., marked $\frac{1}{4}$ S3 BT.

	S. 89° 16' W., beginning new measurement.
	Continue descent; desc. 125 ft. over broken general W. slope.
4.30	Wash, 10 lks. wide, 1 ft. deep, drains S. 70° W.
16.00	Same wash, 40 lks. wide, 2 $\frac{1}{2}$ ft. deep, drains N. 85° W.
29.10	Wash, 25 lks. wide, 1 $\frac{1}{2}$ ft. deep, drains S. 20° W.
37.10	Wash, 20 lks. wide, 4 ft. deep, drains N. 10° W.
40.47	The cor. of secs. 3, 4, 9 and 10.
	Land, east $\frac{1}{4}$ mountainous; west $\frac{3}{4}$ moderate, broken slopes, general W. drainage.
	Soil, broken sandstone and sand.
	Timber, cedar and pinon.
	Undergrowth, oak, palo verde, sparse grass and cacti.
	N. 0° 26' E., bet. secs. 3 and 4.
	Over semi-mountainous land, through medium heavy timber.
2.10	Wash, 30 lks. wide, 2 $\frac{1}{2}$ ft. deep, drains W.; asc. 35 ft. over S. slope.
5.00	Top of hill, bears E. and W.; desc. 30 ft. over N. slope.
8.80	Wash, 20 lks. wide, 3 ft. deep, drains S. 70° W.; asc. 85 ft. over S. slope.
21.60	Ridge, bears N. 80° E. and S. 80° W.; desc. 90 ft. over N. slope.
31.80	Wash, 40 lks. wide, 2 ft. deep, drains S. 60° W.; asc. 75 ft. over SE. slope.

Dependent Resurvey of a Portion of the Subdivision, T. 17 N., R. 5 E.

Chains	
40.73	<p>The $\frac{1}{4}$ sec. cor. of secs. 3 and 4, which is monumented with a sandstone, 6 x 8 x 15 ins., with $\frac{1}{4}$ marked on W. face, set W. of a mound of stone.</p> <p>from which</p> <p style="padding-left: 40px;">A cedar, 8 ins. diam., bears N. 82° E., 51 lks. dist., marked $\frac{1}{4}$ S BT.</p> <p>At the corner point</p> <p>Set an iron post, 30 ins. long, 2$\frac{1}{2}$ ins. diam., 8 ins. in ground, and in a mound of stone, 3 ft. base to top, with brass cap marked</p> <p style="text-align: center;">T17N R5E $\frac{1}{4}$ S4 S3 1956</p> <p>Bury original corner stone alongside the iron post.</p> <p>from which</p> <p style="padding-left: 40px;">A pinon, 10 ins. diam., bears N. 31° W., 53 lks. dist., marked $\frac{1}{4}$ S4 BT.</p>
22.00	<p>N. 0° 29' E., beginning new measurement.</p> <p>Continue ascent; asc. 195 ft. along E. slope.</p> <p>Top of slope; thence desc. 30 ft. along gradual N. slope, near E. edge of nearly flat-topped mountain.</p>
40.25	<p>The cor. of secs. 3 and 4, on the N. bdy. of the township.</p> <p>Land, semi-mountainous. Soil, broken sandstone, rocks and sand. Timber, cedar and pinon. Undergrowth, palo verde, oak, sparse grass, and cacti.</p>
.35	<p>From the standard corner of secs. 32 and 33, on the S. bdy. of the township.</p> <p>N. 1° 56' E., bet. secs. 32 and 33.</p> <p>Over mountainous land, through scattered timber.</p> <p>Desc. abruptly, 15 ft.</p>
10.50	<p>Wash, 50 lks. wide, 15 ft. deep, drains NW.; asc. 110 ft. along broken S. 80° W. slope.</p> <p>Slope changes; desc. 150 ft. over N. 10° W. slope.</p>
19.00	<p>Enter Oak Creek, stream bed,</p>
21.00	<p>Oak Creek, 130 lks. wide, 2 ft. deep, drains SW.; asc. 140 ft. over S. slope.</p>
27.90	<p>Top of bluff; desc. 40 ft. along N. 70° E. slope.</p>
37.50	<p>Road, bladed, bears NW. and SE.</p>

Dependent Resurvey of a Portion of the Subdivision, T. 17 N., R. 5 E.

Chains

39.18

The $\frac{1}{4}$ sec. cor. of secs. 32 and 33, which is monumented with a sandstone, 12 x 10 x 4 ins., marked $\frac{1}{4}$ on W. face, set in a mound of stone.

At the corner point

Set an iron post, 30 ins. long, $2\frac{1}{2}$ ins. diam., 18 ins. in ground, and in a mound of stone, 3 ft. base to top, with brass cap marked

T17N R5E

$\frac{1}{4}$

S32|S33

1956

Bury original corner stone, alongside the iron post.

from which

A cedar, 30 ins. diam., bears S. 53° E., 51 lks. dist., marked $\frac{1}{4}$ S33 BT.

A cedar, 20 ins. diam., bears NW., 43 lks. dist., marked $\frac{1}{4}$ S32 BT.

N. $0^{\circ} 27'$ W., beginning new measurement.

Asc. 100 ft. over broken slopes and low hills.

4.00

Wash, 50 lks. wide, 3 ft. deep, drains SE.

10.10

Road, bladed, bears E. and W.

16.50

Same road, bears E. and W.

20.10

Power line, bears NE. and SW.

23.80

Power line, bears NE. and SW.

32.40

Road, graded, bears NE. and SW.

39.44

The cor. of secs. 28, 29, 32, and 33, which is monumented with a sandstone, 24 x 10 x 4 ins., marked with 4 notches on E., 1 notch on S. edges, set in a mound of stone.

from which

A cedar, 40 ins. diam., bears SW., 57 lks. dist., marked T17N R5E S32 BT

At the corner point

Set an iron post, 30 ins. long, $2\frac{1}{2}$ ins. diam., 14 ins. in ground, and in a mound of stone, 3 ft. base to top, with brass cap marked

T17N R5E

S29|S28

S32|S33

1956

Bury original corner stone alongside the iron post.

Dependent Resurvey of a Portion of the Subdivision, T. 17 N., R. 5 E.

Chains	
	<p>from which</p> <p>A pinon, 10 ins. diam., bears N. 85° W., 150 lks. dist., marked T17N R5E S29 BT.</p> <p>Land, high and rolling. Soil, broken sandstone and sand. Timber, cedar and pinon. Underbrush, palo verde, oak, sparse grass, and cacti.</p>
	<p>From the cor. of secs. 27, 28, 33, and 34.</p> <p>S. 88° 05' W., bet. secs. 28 and 33.</p> <p>Across rolling hills, scattered washes; general S. drainage, through scattered timber.</p> <p>Desc. 60 ft.</p>
5.00	Wash, 10 lks. wide, 2 ft. deep, drains SW.
17.00	Alongside Oak Creek, which bears S. about 3 chains and flows W.
19.00	Wash, 20 lks. wide, 1 ft. deep, drains S.
21.00	Road, bladed, bears SE. and W.
22.50	Same road, bears NW. and E.
22.70	Power line bears NW. and SE.
25.00	Oak Creek, which bears S. about 3 chs., changes course to SW.
35.00	S. side of road, which bears S. 60° W. and N. 60° E.
37.40	Wash, 15 lks. wide, 1 ft. deep, drains S.
42.28	Point for the $\frac{1}{4}$ sec. cor. of secs. 28 and 33, at proportionate distance; there is no remaining evidence of the original corner.
	<p>Set an iron post, 30 ins. long, 2½ ins. diam., 10 ins. in ground, and in a mound of stone, 3½ ft. base to top, with brass cap marked</p> <div style="text-align: center;"> <p>T17N R5E</p> <p>$\frac{1}{4}$ $\frac{S28}{S33}$</p> <p>1956</p> </div>
	<p>from which</p> <p>A pinon, 14 ins. diam., bears N. 83° W., 110 lks. dist., marked $\frac{1}{4}$ S28 BT.</p> <p>A cedar, 15 ins. diam., bears S. 18° 30' W., 109 lks. dist., marked $\frac{1}{4}$ S33 BT.</p> <p>Asc. 90 ft. across scattered washes and spurs, along S. slope.</p>
56.00	Spur, slopes S. 60° E.
60.50	Wash, 10 lks. wide, 3 ft. deep, drains S.
66.00	Spur, slopes S.
71.00	Wash, 30 lks. wide, 5 ft. deep, drains S.

Dependent Resurvey of a Portion of the Subdivision, T. 17 N., R. 5 E.

Chains 84.56	<p>The cor. of secs. 28, 29, 32 and 33.</p> <p>Land, high and rolling. Soil, broken sandstone and sand. Timber, cedar and pinon. Undergrowth, palo verde, oak, sparse grass, and cacti.</p>
15.00	<p>N. 6° 05' E., bet. secs. 28 and 29.</p> <p>Over mountainous land, through scattered timber.</p> <p>Asc. 250 ft. over steep, general SW. slope.</p> <p>Top of SW. edge of ridge that extends N. 15° E.; thence descend 150 ft. along general W. slope.</p>
40.28	<p>Point for the $\frac{1}{4}$ sec. cor. of secs. 28 and 29, at proportionate distance; there is no remaining evidence of the original corner.</p> <p>Set an iron post, 30 ins. long, 2½ ins. diam., 4 ins. in ground to bedrock and in a mound of stone, 4 ft. base to top, with brass cap marked</p> <p style="text-align: center;">T17N R5E $\frac{1}{4}$ S29 S28 1956</p> <p>from which</p> <p style="padding-left: 40px;">A cedar, 6 ins. diam., bears N. 12° E., 23 lks. dist., marked $\frac{1}{4}$ S28 BT.</p> <p>Continue descent; desc. 70 ft. along westerly slope.</p>
45.00	<p>Slope changes; asc. 150 ft. over SW. slope.</p>
52.00	<p>Top of nearly flat-topped ridge, that extends N. 15° E.; thence along W. side of ridge.</p>
72.00	<p>Top of NW. slope; desc. 50 ft.</p>
80.56	<p>The cor. of secs. 20, 21, 28 and 29, which is monumented with a sandstone, 16 x 8 x 12 ins., marked with 4 notches on E., 2 notches on W. edges.</p> <p>from which</p> <p style="padding-left: 40px;">A cedar, 12 ins. diam., bears N. 30° W., 80 lks. dist., marked T17N R5E S20 BT.</p> <p>At the corner point</p> <p>Set an iron post, 30 ins. long, 2½ ins. diam., 10 ins. in ground and in a mound of stone, 4 ft. base to top, with brass cap marked</p> <p style="text-align: center;">T17N R5E S20 S21 S29 S28 1956</p> <p>Bury original cornerstone alongside the iron post.</p> <p>Land, mountainous. Soil, broken sandstone and malpais, gravelly and sand.</p>

Dependent Resurvey of a Portion of the Subdivision, T. 17 N., R. 5 E.

Chains

Timber, cedar and pinon.
Underbrush, palo verde, Spanish dagger, sparse grass, oak, and cacti.

From the corner of secs. 21, 22, 27 and 28.

S. 88° 34' W., bet. secs. 21 and 28.

Over mountainous land, through scattered timber.

Asc. 150 ft. over E. slope of small canyon.

9.00 Top of slope; thence desc. 150 ft. over moderate W. slope of mountain top.

35.90 Top of east side of canyon; desc. 90 ft. over steep W. slope.

38.04 The $\frac{1}{4}$ sec. cor. of secs. 21 and 28, which is monumented with a malpais stone in place, 8 x 8 x 40 ins., marked $\frac{1}{4}$ on N. face.

At the corner point

Set an iron post, 30 ins. long, 2 $\frac{1}{2}$ ins. diam., over X on original corner stone and in a mound of stone, 5 ft. base to top, with brass cap marked

	T17N R5E
	S21
$\frac{1}{4}$	S28
	1956

from which

A cedar, 8 ins. diam., bears S. 18° W., 58 lks. dist., marked $\frac{1}{4}$ S28 BT.

A cedar, 6 ins. diam., bears N. 18° 30' W., 133 lks. dist., marked $\frac{1}{4}$ S21 BT.

S. 88° 18' W., beginning new measurement.

Continue descent of steep W. slope; desc. 100 ft.

4.00 Wash, at bottom of canyon, 80 lks. wide, 5 ft. deep, drains S.; asc. 260 ft. over steep E. slope.

17.00 Top of slope; thence desc. 90 ft. over moderate W. slope of mountain top.

31.00 Top of steep W. slope; desc. 130 ft. to sec. cor.

38.03 The cor. of secs. 20, 21, 28 and 29.

Land, mountainous.
Soil, malpais rocks, broken sandstone, gravel, and sand.
Timber, cedar and pinon.
Undergrowth, palo verde, Spanish dagger, grass, and cacti.

N. 0° 59' W., bet. secs. 20 and 21.

Dependent Resurvey of a Portion of the Subdivision, T. 17 N., R. 5 E.

Chains	
	Over mountainous land, through scattered timber.
	Desc. 100 ft. over NW. slope.
20.00	Wash, 10 lks. wide, 1 ft. deep, drains W.; asc. 40 ft. along general W. slope.
40.74	Point for the $\frac{1}{4}$ sec. cor. of secs. 20 and 21, at proportionate distance; there is no remaining evidence of the original corner.
	Set an iron post, 30 ins. long, $2\frac{1}{2}$ ins. diam., 4 ins. in ground to bedrock and in a mound of stone, 4 ft. base to top, with brass cap marked
	T17N R5E $\frac{1}{4}$ S20 S21 1956
	from which
	A pinon, 14 ins. diam., bears S. 4° E., 96lks. dist., marked $\frac{1}{4}$ S21 BT.
42.00	Base of nearly vertical sandstone wall, bears N. 70° W. and S. 70° E.; asc. abruptly 80 ft.
45.00	Spur, projects W., about 1 ch. to sheer cliff; desc. 60 ft. over very steep NW. slope.
50.00	Wash, 10 lks. wide, 1 ft. deep, drains W.; asc. 90 ft. over steep SW. slope.
61.00	Spur, slopes N. 80° W.; desc. 100 ft. over steep N. 30° W. slope.
74.00	Right-of-way fence, bears S. 70° W. and N. 70° E.
75.00	U. S. Highway 89A, bears S. 70° W. and N. 70° E.
76.00	Right-of-way fence, bears S. 70° W. and N. 70° E.
77.00	Spur, slopes W.; desc. 40 ft. over N. slope.
79.60	Wash, 10 lks. wide, 1 ft. deep, drains W.; asc. 20 ft. over S. slope.
81.49	The cor. of secs. 16, 17, 20, and 21, which is monumented with a sandstone, 12 x 8 x 6 ins., marked with 4 notches on E. and 3 notches on S. edges, set in a mound of stone.
	from which
	A cedar, 8 ins. diam., bears S. $55^{\circ} 30'$ E., 20 lks. dist., marked T17N R5E S21 BT.
	A cedar, 9 ins. diam., bears N. 2° W., 78 lks. dist., marked T17N R5E S17 BT.
	A cedar, 12 ins. diam., bears N. 36° E., 68 lks. dist., marked T17N R5E S16 BT.
	At the corner point

Dependent Resurvey of a Portion of the Subdivision, T. 17 N., R. 5 E.

Chains

Set an iron post, 30 ins. long, $2\frac{1}{2}$ ins. diam., 18 ins. in ground, and in a mound of stone, 3 ft. base to top, with brass cap marked

T17N R5E	
S17	S16
S20	S21
1956	

Bury original corner stone alongside the iron post.

Land, mountainous.

Soil, broken sandstone, malpais rocks and sand.

Timber, cedar and pinon.

Undergrowth, palo verde, oak, cacti, and grass.

From the cor. of secs. 15, 16, 21, and 22.

N. $89^{\circ} 51'$ W., bet. secs. 16 and 21.

Along gentle N. slope, through medium heavy timber.

15.70 Fence, bears S. 20° W. and N. 20° E.

18.50 Fence, bears S. and N.

21.80 Asc. 12 ft. over E. slope.

26.70 Desc. 30 ft. over W. slope.

31.00 Fence highway right-of-way, bears N. 70° E. and S. 70° W.

32.50 U. S. Highway 89A, bears N. 70° E. and S. 70° W.

34.00 Fence, highway right-of-way, bears N. 70° E. and S. 70° W.; asc. 16 ft. over E. slope.

39.90 The $\frac{1}{4}$ sec. cor. of secs. 16 and 21, which is monumented with a mound of stone.

from which

A cedar, 27 ins. diam., bears N. 35° E., 18 lks. dist., marked $\frac{1}{4}$ S BT

At the corner point

Set an iron post, 30 ins. long, $2\frac{1}{2}$ ins. diam., over X on solid sandstone and in a mound of stone, $3\frac{1}{2}$ ft. base to top, with brass cap marked

T17N R5E	
$\frac{1}{4}$	S16
	S21
1956	

from which

A pinon, 8 ins. diam., bears S. 38° E., 56 lks. dist., marked $\frac{1}{4}$ S21 BT.

N. $89^{\circ} 58'$ W., beginning new measurement.

Desc. 230 ft. along broken general S. 20° W. slope.

Dependent Resurvey of a Portion of the Subdivision, T. 17 N., R. 5 E.

Chains	
39.08	<p>The cor. of secs. 16, 17, 20, and 21.</p> <p>Land, east half gentle slopes; west half semi-mountainous. Soil, broken sandstone and sand. Timber, cedar and pinon. Undergrowth, palo verde, grass, and cacti.</p>
	<p>N. 5° 35' W., bet. secs. 16 and 17.</p> <p>Over mountainous land, through scattered timber.</p> <p>Asc. 85 ft. over S. slope.</p>
8.00	Spur, slopes N. 30° W.; desc. 80 ft. over N. slope.
14.00	Wash, 50 lks. wide, 4 ft. deep, drains N. 60° W.; asc. 80 ft. over S. slope.
22.00	Slope changes; asc. 60 ft. over SE. slope.
31.00	Top of slope; desc. 220 ft. over steep N. 15° E. slope into Dry Creek canyon.
36.00	Dry Creek, drains N. 80° W.; asc. 200 ft. over steep S. 10° W. slope.
39.96	<p>Point for the $\frac{1}{4}$ sec. cor. of secs. 16 and 17, at proportionate distance; there is no remaining evidence of the original corner.</p> <p>Set an iron post, 30 ins. long, 2$\frac{1}{2}$ ins. diam., over X on solid sandstone, and in a mound of stone, 4 ft. base to top, with brass cap marked</p>
	<p>T17N R5E $\frac{1}{4}$ S17 S16 1956</p>
	from which
	<p>A pinon, 11 ins. diam., bears N. 60° W., 54 lks. dist., marked $\frac{1}{4}$ S17 BT.</p>
	<p>A pinon, 5 ins. diam., bears S. 89° 59' E., 17 lks. dist., marked $\frac{1}{4}$ S16 BT.</p>
	Continue ascent; asc. 30 ft. over S. 10° W. slope.
42.00	Spur, slopes S. 80° E.; desc. 150 ft. along general E. slope.
59.00	Wash, 20 lks. wide, 1 ft. deep, drains E. into Dry Creek, about 5 chains dist.; asc. 125 ft. over broken S. slope.
79.93	<p>The cor. of secs. 8, 9, 16, and 17, which is monumented with a sandstone, 24 x 10 x 4 ins., marked with 4 notches on S. and 4 notches on E. edges, set in a mound of stone.</p>
	from which
	<p>A cedar, 8 ins. diam., bears S. 80° W., 35 lks. dist., marked T17N R5E S17 BT.</p>

Dependent Resurvey of a Portion of the Subdivision, T. 17 N., R. 5 E.

Chains

A pinon, 8 ins. diam., bears N. 52° 30' W., 149 lks. dist., marked T17N R5E S8 BT.

A pinon, 12 ins. diam., bears N. 79° E., 119 lks. dist., marked T17N R5E S9 BT.

At the corner point

Set an iron post, 30 ins. long, 2½ ins. diam., 6 ins. in ground, and in a mound of stone, 3½ ft. base to top, with brass cap marked

T17N R5E	
S8	S9
S17	S16
1956	

Bury original corner stone alongside the iron post.

from which

A pinon, 8 ins. diam., bears S. 29° E., 56 lks. dist., marked T17N R5E S16 BT.

Land, mountainous.

Soil, rocky, gravelly, and sandy.

Timber, cedar, and pinon.

Undergrowth, palo verde, cat claw, Spanish dagger, cacti, and grass.

From the cor. of secs. 9, 10, 15, and 16.

S. 89° 25' W., bet. secs. 9 and 16.

Over semi-mountainous land, through medium heavy timber.

Desc. 25 ft. over moderate W. slope.

6.80 Wash, 75 lks. wide, 6 ft. deep, drains S.; asc. 110 ft. over E. slope.

29.80 Spur, slopes N. 85° E.; thence asc. 25 ft. over top of spur.

32.20 Top of mountain extends N. 80° W.; desc. 50 ft. over general SW. slope.

39.62 The ¼ sec. cor. of secs. 9 and 16, which is monumented with a sandstone, 20 x 8 x 4 ins., marked ¼ on N. face, set in a mound of stone.

At the corner point

Set an iron post, 30 ins. long, 2½ ins. diam., 6 ins. in ground, and in a mound of stone, 3½ ft. base to top, with brass cap marked

T17N R5E	
¼	S9
	S16
1956	

Bury original corner stone alongside the iron post.

from which

A pinon, 16 ins. diam., bears N. 38° E., 86 lks. dist., marked ¼ S9 BT.

Dependent Resurvey of a Portion of the Subdivision, T. 17 N., R. 5 E.

Chains	
	<p>A pinon, 6 ins. diam., bears S. 26° 30' W., 30 lks. dist., marked $\frac{1}{4}$ S16 BT.</p> <hr/> <p>S. 88° 42' W., beginning new measurement.</p> <p>Continue descent; desc. 145 ft. over broken S. 80° W. slope.</p>
13.00	Wash, 60 lks. wide, 2 ft. deep, drains N. 20° W.
17.00	Same wash, drains S. 35° W.
20.50	Same wash, drains NW.
29.00	Dry Creek, 125 lks. wide, 3 ft. deep, drains S.; asc. 100 ft. over E. slope.
40.56	The cor. of secs. 8, 9, 16, and 17.
	<p>Land, semi-mountainous. Soil, rocky and sandy. Timber, cedar, pinon and some yew near Dry Creek. Undergrowth, palo verde, catclaw, oak, Spanish dagger, century plants, grass, and cacti.</p>
	<p>N. 1° 27' W., bet. secs. 8 and 9.</p> <p>Over semi-mountainous land, through scattered timber.</p> <p>Asc. 35 ft. over S. slope.</p>
3.30	Power line, on top of hill, bears NE. and SW.; desc. 90 ft. over N. slope.
12.10	Wash, drains S. 80° E.; asc. 100 ft. over broken hilly land; general SE. drainage.
17.40	Wash, 15 lks. wide, 2 ft. deep, drains S. 20° E.
31.00	Top of hill, bears N. 30° W. and S. 30° E.
33.00	Wash, 25 lks. wide, 3 ft. deep, drains SE.
39.65	Point for the $\frac{1}{4}$ sec. cor. of secs. 8 and 9 at proportionate distance; there is no remaining evidence of the original corner.
	<p>Set an iron post, 30 ins. long, 4 ins. in ground to bedrock, and in a mound of stone, 4 ft. base to top, with brass cap marked</p> <p style="text-align: center;">T17N R5E $\frac{1}{4}$ S8 S9 1956</p> <p>from which</p> <p>A pinon, 12 ins. diam., bears S. 65° E., 58 lks. dist., marked $\frac{1}{4}$ S9 BT.</p> <p>A pinon, 8 ins. diam., bears N. 63° W., 22 lks. dist., marked $\frac{1}{4}$ S8 BT.</p> <p>Continue ascent; asc. 40 ft. over S. slope.</p>

Dependent Resurvey of a Portion of the Subdivision, T. 17 N., R. 5 E.

Chains	<p>47.00 Top of hill; desc. 90 ft. over broken land; general drainage east.</p> <p>54.00 Fence, bears N. 60° E. and S. 60° W.</p> <p>73.00 Wash, 30 lks. wide, 3 ft. deep, drains S. 80° E.</p> <p>76.00 Spur, slopes S. 70° E.</p> <p>79.30 The cor. of secs. 4, 5, 8, and 9, which is monumented with a sandstone, 20 x 10 x 10 ins., marked with 5 notches on S., 4 notches on E. edges, set 15 ins. in ground.</p> <p>from which</p> <p style="padding-left: 40px;">A cedar, 12 ins. diam., bears S. 9° W., 77 lks. dist., marked T17N R5E S8 BT.</p> <p style="padding-left: 40px;">A cedar, 12 ins. diam., bears S. 56° E., 110 lks. dist., marked T17N R5E S9 BT.</p> <p style="padding-left: 40px;">A cedar, 10 ins. diam., bears N. 27° W., 225 lks. dist., marked T17N R5E S5 BT.</p> <p>At the corner point</p> <p>Set an iron post, 30 ins. long, 2½ ins. diam., 2 ins. in ground, and in a mound of stone, 6 ft. base to top, with brass cap marked</p> <div style="text-align: center;"> <table border="0"> <tr> <td colspan="2">T17N R5E</td> </tr> <tr> <td style="border-right: 1px solid black; padding-right: 5px;">S5</td> <td style="padding-left: 5px;">S4</td> </tr> <tr> <td style="border-right: 1px solid black; padding-right: 5px;">S8</td> <td style="padding-left: 5px;">S9</td> </tr> <tr> <td colspan="2">1956</td> </tr> </table> </div> <p>Bury original corner stone alongside the iron post.</p> <p>Corner falls on S. side of wash, that drains S. 80° E.</p> <p>Land, broken and hilly. Soil, rocky and sandy. Timber, cedar and pinon. Undergrowth, palo verde, catclaw, Spanish dagger, grass, and cacti.</p>	T17N R5E		S5	S4	S8	S9	1956	
T17N R5E									
S5	S4								
S8	S9								
1956									
.70	<p>From the cor. of secs. 3, 4, 9, and 10.</p> <p>West, bet. secs. 4 and 9.</p> <p>Over semi-mountainous land, through medium heavy timber.</p> <p>Asc. 100 ft. along, rolling broken N. slope.</p> <p>Wash, 15 lks. wide, 4 ft. deep, drains N. 15° W.</p>								
19.40	<p>Wash, 40 lks. wide, 2 ft. deep, drains N. 10° E.</p>								
25.00	<p>Spur, slopes N.; desc. 120 ft. over W. slope.</p>								
40.07	<p>The ¼ sec. cor. of secs. 4 and 9, which is monumented with a sandstone, 17 x 6 x 4 ins., marked ¼ on N. face, set in a mound of stone.</p> <p>from which</p>								

Dependent Resurvey of a Portion of the Subdivision, T. 17 N., R. 5 E.

Chains

A cedar, 6 ins. diam., bears NW., 59 lks. dist.,
marked $\frac{1}{4}$ S4 BT.

A cedar, 6 ins. diam., bears S. 16° W., 8 lks. dist.,
marked $\frac{1}{4}$ S9 BT.

At the corner point

Set an iron post, 30 ins. long, 2½ ins. diam., 10 ins. in ground,
and in a mound of stone, 3 ft. base to top, with brass cap marked

T17N R5E
 $\frac{1}{4}$ $\frac{S4}{S9}$
1956

Bury original corner stone alongside the iron post.

N. 89° 50' W., beginning new measurement.

Continue descent; desc. 120 ft. along N. slope.

- 15.00 Dry Creek, 1 ch. wide, 4 ft. deep, drains S.; asc. 100 ft. over steep
wall of bluff, facing N. 85° E.
- 19.00 Top of bluff; thence asc. 30 ft. over E. slope.
- 20.70 Spur, slopes S.; thence desc. 10 ft. over broken, hilly land to sec.
cor.
- 24.70 Wash, 40 lks. wide, 3 ft. deep, drains S. 30° E.
- 31.90 Wash, 15 lks. wide, 1 ft. deep, drains S. 30° E.
- 34.70 Fence, bears N. and S.
- 40.10 The cor. of secs. 4, 5, 8 and 9.

Land, hilly and broken.
Soil, broken sandstone and sand.
Timber, cedar, pinon, and a few yew near Dry Creek.
Undergrowth, palo verde, oak, manzanita, cacti, and grass.

N. 0° 03' E., bet. secs. 4 and 5.

Over broken, hilly land, through medium heavy timber.

- .10 Wash, drains S. 80° E.; asc. 85 ft. over S. slope.
- 5.40 Spur, slopes S. 60° E.; thence asc. 20 ft. along rolling broken
general E. slope.
- 9.00 Fence, bears N. 60° W. and S. 60° E.
- 20.10 Wash, 10 lks. wide, 2 ft. deep, drains E.
- 28.00 Desc. 80 ft. over N. slope.
- 38.51 Wash, 30 lks. wide, 3 ft. deep, drains NE.; asc. 20 ft. over S.
slope.

Dependent Resurvey of a Portion of the Subdivision, T. 17 N., R. 5 E.

Chains	
40.65	<p>Point for the $\frac{1}{4}$ sec. cor. of secs. 4 and 5, at proportionate distance; there is no remaining evidence of the original cor.</p> <p>Set an iron post, 30 ins. long, $2\frac{1}{2}$ ins. diam., 10 ins. in ground, and in a mound of stone, 4 ft. base to top, with brass cap marked</p>
	<p>T17N R5E</p> <p>$\frac{1}{4}$</p> <p>S5 S4</p> <p>1956</p>
	<p>from which</p> <p>A pinon, 12 ins. diam., bears S. 1° W., 65 lks. dist., marked $\frac{1}{4}$ S5 BT.</p> <p>A pinon, 10 ins. diam., bears S. 85° E., 12 lks. dist., marked $\frac{1}{4}$ S4 BT.</p>
	<p>N. $0^{\circ} 06'$ E., beginning new measurement.</p>
	<p>Continue ascent; asc. 25 ft. over S. slope.</p>
2.60	<p>Spur, slopes S. 60° E.; desc. 40 ft. over N. slope.</p>
6.00	<p>Wash, 1 ch. wide, $1\frac{1}{2}$ ft. deep; drains E.; asc. 65 ft. over hilly broken land; general SE. drainage.</p>
40.47	<p>The cor. of secs. 4 and 5, on the N. boundary of the township.</p> <p>Land, hilly and broken. Soil, broken sandstone, sand, and sandy loam. Timber, cedar and pinon. Undergrowth, palo verde, manzanita, oak, cacti, and grass.</p>
	<p>From the standard cor. of secs. 31 and 32, on the S. bdy. of the township.</p>
	<p>N. $6^{\circ} 27'$ E., bet. secs. 31 and 32.</p>
	<p>Over mountainous land, through scattered timber.</p>
	<p>Desc. 60 ft. over NW. slope.</p>
4.00	<p>Enter Oak Creek stream valley.</p>
9.00	<p>Oak Creek, 150 lks. wide, 1 ft. deep, drains S. 20° W.</p>
23.00	<p>Leave Oak Creek stream valley; asc. 125 ft. over S. 80° E. slope, to point for the $\frac{1}{4}$ sec. cor.</p>
39.36	<p>Point for the $\frac{1}{4}$ sec. cor. of secs. 31 and 32, at proportionate distance; there is no remaining evidence of the original cor.</p> <p>Set an iron post, 30 ins. long, $2\frac{1}{2}$ ins. diam., 3 ins. in ground, and in a mound of stone, 3 ft. base to top, with brass cap marked</p>

Dependent Resurvey of a Portion of the Subdivision, T. 17 N., R. 5 E.

Chains

T17N R5E

 $\frac{1}{4}$

S31|S32

1956

from which

A cedar, 10 ins. diam., bears N. 61° E., 34 lks. dist., marked $\frac{1}{4}$ S32 BT.

A pinon, 6 ins. diam., bears S. 21° 30' W., 30 lks. dist., marked $\frac{1}{4}$ S31 BT.

Continue ascent; asc. 200 ft. along broken E. slope.

43.00 Wash, 8 lks. wide, 1 ft. deep, drains S. 60° E.

47.00 Head of wash that drains S. 60° E.

71.20 Saddle on ridge that bears SW. and NE.; desc. 80 ft. along W. slope to sec. cor.

78.72 The cor. of secs. 29, 30, 31, and 32, which is monumented with a granite stone, 12 X 12 X 8 ins., marked with 1 notch on S. and 5 notches on E. edges, set in a mound of stone.

from which

A cedar, 15 ins. diam., bears S. 62° 30' W., 29 lks. dist., marked T17N R5E S31 BT.

A cedar, 8 ins. diam., bears N. 27° W., 21 lks. dist., original marks partially grown over.

At the corner point

Set an iron post, 30 ins. long, 2½ ins. diam., 10 ins. in ground, and in a mound of stone, 3 ft. base to top, with brass cap marked

T17N R5E

S30|S29

S31|S32

1956

Bury original corner stone alongside the iron post.

from which

A pinon, 10 ins. diam., bears N. 82° 15' E., 95 lks. dist., marked T17N R5E S29 BT.

A pinon, 10 ins. diam., bears S. 15° E., 9½ lks. dist., marked T17N R5E S32 BT.

Land, mountainous.

Soil, rocky, gravelly, and sandy.

Timber, cedar, pinon, sycamore near Oak Creek.

Undergrowth, oak, cat claws, Spanish dagger, palo verde, grass, and cacti.

From the cor. of secs. 28, 29, 32, and 33.

N. 89° 52' W., bet. secs. 29 and 32.

BOOK 4556

Dependent Resurvey of a Portion of the Subdivision, T. 17 N., R. 5 E.

Chains	
	Over mountainous land, through scattered timber.
	Desc. 100 ft. over SW. slope.
7.30	Road, graded, bears NW. and SE.
9.60	Power line, bears NW. and SE.
12.50	Wash, 18 lks. wide, 3 ft. deep, drains SE.; asc. 220 ft. over E. slope.
15.90	Old road, bears NW. and SE.
26.00	Top of mountain, bears N. and S.; desc. 100 ft. over W. slope.
36.23	Point for the $\frac{1}{4}$ sec. cor. of secs. 29 and 32, at proportionate distance; there is no remaining evidence of the original corner.
	Set an iron post, 30 ins. long, $2\frac{1}{2}$ ins. diam., 10 ins. in ground, and in a mound of stone, 6 ft. base to top, with brass cap marked
	T17N R5E $\frac{1}{4}$ <u>S29</u> S32 1956
	from which
	A cedar, 24 ins. diam., bears S. 1° W., 20 lks. dist., marked $\frac{1}{4}$ S32 BT.
	A pinon, 5 ins. diam., bears North, 72 lks. dist., marked $\frac{1}{4}$ S29 BT.
	Continue descent; desc. 180 ft. over W. slope.
44.90	Wash, 60 lks. wide, $2\frac{1}{2}$ ft. deep, drains SW.; asc. 70 ft. over E. slope.
53.00	Slope changes; desc. 25 ft. along S. slope.
58.70	Wash, 80 lks. wide, 5 ft. deep, drains SE.; asc. 100 ft. over E. slope.
66.60	Top of mountain, bears N. and S.; desc. 45 ft. over W. slope.
72.46	The cor. of secs. 29, 30, 31, and 32.
	Land, mountainous. Soil, rocky and sandy. Timber, cedar and pinon. Undergrowth, oak, palo verde, catclaw, Spanish dagger, cacti, and grass.
	N. $89^{\circ} 18'$ W., bet. secs. 30 and 31.
	Over mountainous land, through scattered timber.
	Desc. 80 ft. over W. slope.
17.80	Old road, bears N. and S.
20.20	Wash, 50 lks. wide, 2 ft. deep, drains SE.; asc. 20 ft. over E. slope.
24.60	Slope changes; asc. 20 ft. along broken S. slope.

Dependent Resurvey of a Portion of the Subdivision, T. 17 N., R. 5 E.

Chains	
34.40	Wash, 9 lks. wide, 1½ ft. deep, drains S.
37.00	Desc. 80 ft. over SW. slope.
43.88	Point for the ¼ sec. cor. of secs. 30 and 31, at proportionate distance; there is no remaining evidence of the original corner. Set an iron post, 30 ins. long, 2½ ins. diam., 6 ins. in ground, and in a mound of stone, 3 ft. base to top, with brass cap marked <div style="text-align: center;"> T17N R5E ¼ $\frac{S30}{S31}$ 1956 </div> from which A pinon, 6 ins. diam., bears S. 47° E., 50 lks. dist., marked ¼ S31 BT. A pinon, 8 ins. diam., bears N. 35° 30' W., 33 lks. dist., marked ¼ S30 BT. Continue descent; desc. 30 ft. over SW. slope.
46.90	Dry Creek, 2 chs. wide, 3 ft. deep, drains SE.; asc. 280 ft. over broken general SE. slope.
58.20	Wash, 30 lks. wide, 2 ft. deep, drains S.
72.20	Spur, slopes N. 70° E.; asc. 130 ft. along top of spur.
87.76	The cor. of secs. 25, 30, 31, and 36, on the W. bdy. of the township. Land, mountainous. Soil, rocky, sandy, and gravelly. Timber, cedar, pinon, some yew near Dry Creek. Undergrowth, oak, palo verde, catclaws, Spanish dagger, cacti, and grass.
	From the cor. of secs. 29, 30, 31, and 32. N. 0° 58' W., bet. secs. 29 and 30. Over mountainous land, through scattered timber. Desc. 20 ft. along broken N. 80° W. slope.
2.90	Wash, 5 lks. wide, 1 ft. deep, drains W.
9.80	Wash, 10 lks. wide, 1 ft. deep, drains W.
14.30	Wash, 30 lks. wide, 3 ft. deep, drains S. 60° W.; asc. 80 ft. along E. slope.
28.30	Old road, bears NE. and SW.
36.00	Desc. 30 ft. over general N. slope.
39.62	The ¼ sec. cor. of secs. 29 and 30, which is monumented with a sandstone, 10 x 8 x 6 ins., marked ¼ on W. face, set in a mound of stone. At the corner point.

Dependent Resurvey of a Portion of the Subdivision, T. 17 N., R. 5 E.

Chains

Set an iron post, 30 ins. long, 2½ ins. diam., 8 ins. in ground, and in a mound of stone, 3 ft. base to top, with brass cap marked

T17N R5E

$$\begin{array}{c} \frac{1}{4} \\ \hline \text{S30} | \text{S29} \\ \hline 1956 \end{array}$$

Bury original corner stone alongside the iron post.

from which

A cedar, 10 ins. diam., bears N. 81° W., 73 lks. dist., marked ¼ S30 BT.

A pinon, 10 ins. diam., bears N. 89° E., 88 lks. dist., marked ¼ S29 BT.

N. 0° 58' W., beginning new measurement.

Asc. 140 ft. over broken general SW. slope.

10.00 Wash, 18 lks. wide, 3 ft. deep, drains SW.

17.30 Top of knoll on small ridge that bears SW. and NE.; desc. 100 ft. over N. 15° W. slope.

24.80 Bottom of slope; thence through eroded, nearly level land.

25.80 Wash, 10 lks. wide, 4 ft. deep, drains NW.

30.20 Wash, 12 lks. wide, 4 ft. deep, drains W.

34.60 Fence, bears S. 70° W. and N. 70° E.

35.80 Old road, bears S. 15° E. and N. 15° W.

39.82 The cor. of secs. 19, 20, 29, and 30, which is monumented with a sandstone, 15 x 6 x 8 ins., 2 notches on S. and 5 notches on E. edges.

At the corner point

Set an iron post, 30 ins. long, 2½ ins. diam., 12 ins. in ground, and in a mound of stone, 3 ft. base to top, with brass cap marked

$$\begin{array}{c} \text{T17N R5E} \\ \hline \text{S19} | \text{S20} \\ \hline \text{S30} | \text{S29} \\ \hline 1956 \end{array}$$

Land, broken and hilly.

Soil, sand.

Timber, cedar and pinon.

Undergrowth, oak, catclaw, palo verde, Spanish dagger, cacti, and grass.

From the cor. of secs. 20, 21, 28, and 29.

S. 89° 42' W., bet. secs. 20 and 29.

Over mountainous land, through scattered timber.

Dependent Resurvey of a Portion of the Subdivision, T. 17 N., R. 5 E.

Chains	
	Desc. 280 ft. over broken N. 80° W. slope.
16.80	Wash, 15 lks. wide, 2 ft. deep, drains NW.
22.00	Wash, 30 lks. wide, 3 ft. deep, drains SW.
39.43	Road, graded, bears NW. and SE.
41.00	Wash, 50 lks. wide, 2 ft. deep, drains S.
42.54	The $\frac{1}{4}$ sec. cor. of secs. 20 and 29, which is monumented with a sandstone, 30 x 8 x 4 ins., marked $\frac{1}{4}$ on N. face, set in a mound of stone.
	from which
	A cedar, 18 ins. diam., bears S. 3° E., 54 lks. dist., original markings partially grown over.
	A cedar, 24 ins. diam., bears N. 5° W., 23 lks. dist., original markings partially grown over.
	At the corner point
	Set an iron post, 30 ins. long, $2\frac{1}{2}$ ins. diam., 12 ins. in ground, and in a mound of stone, 3 ft. base to top, with brass cap marked
	$\begin{array}{r} \text{T17N R5E} \\ \frac{1}{4} \frac{\text{S20}}{\text{S29}} \\ 1956 \end{array}$
	Bury original corner stone alongside the iron post.

	S. 89° 53' W., beginning new measurement.
	Asc. 145 ft. over S. 80° E. slope.
4.40	Road, graded, bears NE. and SW.
20.10	Sandstone spur, slopes SW.; desc. 65 ft. over N. 80° W. slope.
25.00	Asc. 15 ft. over NE. slope.
27.50	Small spur, slopes NW.; desc. 120 ft. over W. slope.
34.40	Power line, bears N. 10° W. and S. 10° E.
39.69	The cor. of secs. 19, 20, 29, and 30.
	Land, semi-mountainous. Soil, broken sandstone and sand. Timber, cedar and pinon. Undergrowth, palo verde, catclaw, oak, Spanish dagger, cacti, and grass.
	N. 88° 50' W., bet. secs. 19 and 30.
	Over semi-mountainous land, through scattered timber.
	Desc. 70 ft. over rolling general SW. slope.
21.00	Wash, 15 lks. wide, 3 ft. deep, drains S. 20° W.

Dependent Resurvey of a Portion of the Subdivision, T. 17 N., R. 5 E.

Chains	
23.10	Asc. 50 ft. over E. slope.
27.10	Spur, slopes N. 20° E.; desc. 150 ft. over N. 70° W. slope.
37.00	Dry Creek, 150 lks. wide, 6 ft. deep, drains SW.
41.00	Dry Creek 150 lks. wide, 6 ft. deep, drains NW.; asc. 70 ft. over steep N. 70° E. slope of bluff.
43.28	Point for the $\frac{1}{4}$ sec. cor. of secs. 19 and 30, at proportionate distance; there is no remaining evidence of the original corner.
	Set an iron post, 30 ins. long, 2½ ins. diam., 10 ins. deep, in crack in solid rock, on small ledge, and in a mound of stone, 3 ft. base to top, with brass cap marked
	$\begin{array}{r} \text{T17N R5E} \\ \frac{1}{4} \frac{\text{S19}}{\text{S30}} \\ 1956 \end{array}$
	Raise a mound of stone, 3½ ft. base, 3 ft. high, N. of cor.
	from which
	A pinon, 8 ins. diam., bears S. 10° E., 43 lks. dist., marked $\frac{1}{4}$ S30 BT.
	A pinon, 12 ins. diam., bears N. 65° W., 174 lks. dist., marked $\frac{1}{4}$ S19 BT.
	Continue ascent, asc. 20 ft. over N. 70° E. slope.
45.00	Top of bluff, bears N. 15° W. and S. 15° E.; desc. 110 ft. over steep W. slope.
52.80	Dry Creek, 150 lks. wide, 6 ft. deep, drains S.; asc. 150 ft. over N. 80° E. slope.
60.00	Top of bluff, bears N. & SE.; desc. 20 ft. over W. slope.
61.60	Bottom of W. slope; asc. 60 ft. over E. slope.
66.00	Top of slope; thence asc. 30 ft. over high, broken land to sec. cor.
86.55	The cor. of secs. 19, 24, 25, and 30, on the W. bdy. of the township.
	Land, mountainous. Soil, rocky, sandy, and sandy loam. Timber, cedar, and pinon. Undergrowth, palo verde, oak, catclaw, Spanish dagger, cacti, and grass.
	From the cor. of secs. 19, 20, 29, and 30.
	N. 0° 41' E., bet. secs. 19 and 20.
	Over hilly land, through scattered timber.
8.70	Wash, 7 lks. wide, 1½ ft. deep, drains SW.
14.70	Wash, 12 lks. wide, 2½ ft. deep, drains W.

Dependent Resurvey of a Portion of the Subdivision, T. 17 N., R. 5 E.

Chains	
16.80	Wash, 20 lks. wide, 4 ft. deep, drains SW.
21.00	Wash, 10 lks. wide, 3½ ft. deep, drains W.
29.00	Wash, 25 lks. wide, 4 ft. deep, drains SW.
40.10	The ¼ sec. cor. of secs. 19 and 20, which is monumented with a granite rock, 26 x 10 x 4 ins., marked ¼ on W. face, set in a mound of stone.
	At the corner point
	Set an iron post, 30 ins. long, 2½ ins. diam., 10 ins. in ground, and in a mound of stone, 3 ft. base to top, with brass cap marked
	<p style="text-align: center;">T17N R5E ¼ S19 S20 1956</p>
	Bury original corner stone alongside the iron post. from which
	A cedar, 8 ins. diam., bears N. 78° W., 59 lks. dist., marked ¼ S19 BT.
	A cedar, 24 ins. diam., bears S. 77° E., 158 lks. dist., marked ¼ S20 BT.
	N. 0° 41' E., beginning new measurement.
13.10	Wash, 10 lks. wide, 6 ft. deep, drains SW.
13.70	Wash, 17 lks. wide, 5 ft. deep, drains SW.
15.50	Right-of-way fence, bears NE. and SW.
17.30	U.S. Highway 89A, bears NE. and SW.
19.00	Right-of-way fence, bears NE. and SW.
20.30	Wash, 6 lks. wide, 1½ ft. deep, drains SW.; asc. 65 ft. over S. slope.
37.40	Top of hill, bears E. and W.; desc. 40 ft. over N. slope.
40.40	The cor. of secs. 17, 18, 19, and 20, which is monumented with a granite rock, 14 x 10 x 8 ins., 3 notches on S., 5 notches on E. edges, set in a mound of stone.
	from which
	A cedar, 8 ins. diam., bears S. 54° 30' W., 192 lks. dist., marked T17N R5E S19 BT.
	At the corner point
	Set an iron post, 30 ins. long, 2½ ins. diam., 10 ins. in ground, and in a mound of stone, 3 ft. base to top, with brass cap marked

BOOK 4555

Dependent Resurvey of a Portion of the Subdivision, T. 17 N., R. 5 E.

Chains

T17N R5E	
S18	S17
S19	S20
1956	

Bury original corner stone alongside the iron post.

from which

A cedar, 8 ins. diam., bears N. 64° W., 109 lks. dist.,
marked T17N R5E S18 BT.

A cedar, 12 ins. diam., bears N. 37° E., 189 lks. dist.,
marked T17N R5E S17 BT.

A cedar, 8 ins. diam., bears S. 18° 30' E., 133 lks.
dist., marked T17N R5E S20 BT.

Land, hilly.

Soil, rocky and sandy.

Timber, cedar and pinon.

Undergrowth, oak, catclaw, palo verde, Spanish dagger, cacti,
and grass.

From the cor. of secs. 16, 17, 20, and 21.

S. 89° 09' W., bet. secs. 17 and 20.

Over semi-mountainous land, through scattered timber.

Desc. 70 ft. along broken general SW. slope.

2.30 Wash, 10 lks. wide, 1 ft. deep, drains N. 70° W.

5.00 Same wash, drains SW.

5.30 Same wash, drains N. 70° W.

10.20 Same wash, drains S. 5° W.

18.60 Dry Creek, 1 ch. wide, 2½ ft. deep, drains S. 5° E.; asc. 40 ft.
over E. slope.

24.40 Top of hill, bears N. and S.; desc. 70 ft. over NW. slope.

33.00 Dry Creek, 150 lks. wide, 3 ft. deep, drains N. 5° W.; begin ascent
of gentle E. slope.39.81 The ¼ sec. cor. of secs. 17 and 20, which is monumented with a
mound of stone.

At the corner point

Set an iron post, 30 ins. long, 2½ ins. diam., 20 ins. in ground,
and in a mound of stone, 3 ft. base to top, with brass cap marked

T17N R5E	
¼	S17
	S20
1956	

Raise a mound of stone, 2½ ft. base, 2½ ft. high N. of cor.

from which

Dependent Resurvey of a Portion of the Subdivision, T. 17 N., R. 5 E.

Chains

A pinon, 6 ins. diam., bears S. 8° 30' E., 98 lks. dist.,
marked $\frac{1}{4}$ S20 BT.

A pinon, 6 ins. diam., bears N. 82° 30' W., 58 lks. dist.,
marked $\frac{1}{4}$ S17 BT.

S. 89° 03' W., beginning new measurement.

Asc. 20 ft. over E. slope.

5.20 Thence across nearly level land.

9.40 Fence, bears N. 20° E. and S. 20° W.; desc. 40 ft. over W. slope.

15.50 Enter nearly level clearing.

24.00 Leave clearing; asc. 80 ft. over steep E. slope.

28.90 Top of bluff, bears NW. and SE.; desc. 65 ft. over N. slope.

39.92 The cor. of secs. 17, 18, 19 and 20.

Land, hilly.

Soil, rocky and sandy.

Timber, cedar and pinon.

Undergrowth, palo verde, catclaw, Spanish dagger, cacti, and grass.

N. 89° 10' W., bet. secs. 18 and 19.

Over broken hilly land, through scattered timber.

Desc. 50 ft. over W. slope.

6.80 Fence, bears NE. and SW.

8.20 Dry Creek, 120 lks. wide, 2 ft. deep, drains WSW.; thence along N. side of Dry Creek.

13.00 House, bears South, about $3\frac{1}{2}$ chs. dist.

17.00 House, bears South, about $2\frac{1}{2}$ chs. dist.

17.60 Dry Creek, 100 lks. wide, 2 ft. deep, drains WNW.; thence along S. side of Dry Creek.

24.00 Dry Creek, 120 lks. wide, 4 ft. deep, drains SW.; asc. 25 ft. along broken S. slope.

32.30 Wash, 8 lks. wide, 2 ft. deep, drains S.

39.20 Wash, 6 lks. wide, 1 ft. deep, drains S.

35.90 Enter nearly level clearing.

43.75 Point for the $\frac{1}{4}$ sec. cor. of secs. 18 and 19, at proportionate distance; there is no remaining evidence of the original corner.

Set an iron post, 30 ins. long, $2\frac{1}{2}$ ins. diam., 10 ins. in ground, and in a mound of stone, 3 ft. base to top, with brass cap marked

T17N R5E
 $\frac{1}{4}$ $\frac{S18}{S19}$
1956

Dependent Resurvey of a Portion of the Subdivision, T. 17 N., R. 5 E.

Chains	from which
	<p>A pinon, 8 ins. diam., bears SW., 162 lks. dist., marked $\frac{1}{4}$ S19 BT.</p> <p>A pinon, 8 ins. diam., bears N. 51° 15' W., 135 lks. dist., marked $\frac{1}{4}$ S18 BT.</p>
48.30	Asc. 20 ft. over E. slope.
55.00	Top of slope; desc. 50 ft. over W. slope.
64.00	Wash, 8 lks. wide, 2 ft. deep, drains S.
67.00	Wash, 150 lks. wide, 10 ft. deep, drains SE.; asc. 140 ft. over NE. slope.
87.51	The cor. of secs. 13, 18, 19 and 24, on the W. bdy. of the township.
	<p>Land, east half, broken, hilly; west half semi-mountainous. Soil, sand and sandy loam. Timber, cedar and pinon. Undergrowth, catclaw, palo verde, Spanish dagger, oak, cacti, and grass.</p>
	<p>From the cor. of secs. 17, 18, 19 and 20.</p> <p>N. 5° 22' W., bet. secs. 17 and 18.</p> <p>Over hilly land, through scattered timber.</p> <p>Desc: 35 ft. over NW. slope.</p>
18.00	Dry Creek, 3 chs. wide, 2½ ft. deep, drains SW.; asc. 145 ft. over S. slope.
25.60	Sandstone pinnacle, bears E. about 2 chs.; continue ascent along SW. slope; asc. 125 ft.
39.90	Point for the $\frac{1}{4}$ sec. cor. of secs. 17 and 18, at proportionate distance; there is no remaining evidence of the original corner.
	<p>Set an iron post, 30 ins. long, 2½ ins. diam., 2 ins. in ground, and in a mound of stone, 3 ft. base to top, with brass cap marked</p> <p style="text-align: center;">T17N R5E $\frac{1}{4}$ S18 S17 1956</p>
	from which
	<p>A pinon, 6 ins. diam., bears N. 87° 15' E., 52 lks. dist., marked T17N R5E $\frac{1}{4}$ S17 BT.</p> <p>A pinon, 5 ins. diam., bears N. 52° 15' W., 28 lks. dist., marked T17N R5E $\frac{1}{4}$ S18 BT.</p>
	Continue ascent; asc. 50 ft. over S. slope.
47.00	Ridge, bears E. and W.; desc. 90 ft. over N. slope.
53.50	Wash, 10 lks. wide, 1½ ft. deep, drains W.; asc. 25 ft. over general S. slope.

Dependent Resurvey of a Portion of the Subdivision, T. 17 N., R. 5 E.

Chains

56.00 Power line, bears NE. and SW.

79.81 The cor. of secs. 7, 8, 17, and 18, which is monumented with a sandstone, 12 x 10 x 6 ins., marked with 4 notches on S. and 5 notches on E. edges, set in a mound of stone.

from which

A cedar, 16 ins. diam., bears SW., 49 lks. dist., marked T17N R5E S18 BT.

A dead pinon, bears N. 35° W., 81 lks. dist., marked T17N R5E S7 BT.

A cedar, 25 ins. diam., bears N. 75° E., 153 lks. dist., marked T17N R5E S8 BT.

At the corner point

Set an iron post, 30 ins. long, 2½ ins. diam., 12 ins. in ground, and in a mound of stone, 3 ft. base to top, with brass cap marked

T17N R5E	
S7	S8
S18	S17
1956	

Bury original corner stone alongside the iron post.

from which

A pinon, 6 ins. diam., bears S. 55° 30' E., 190 lks. dist., marked T17N R5E S17 BT.

Land, semi-mountainous.

Soil, broken sandstone and sand.

Timber, cedar and pinon.

Undergrowth, palo verde, catclaw, oak, Spanish dagger, manzanita, cacti, and grass.

From the corner of secs. 8, 9, 16, and 17.

S. 88° 44' W., bet. secs. 8 and 17.

Over high rolling land, through heavy timber.

Asc. 20 ft. over rolling broken land, with general S. 70° E. drainage.

1.40 Fence, 80 lks. N. of line, bears E. and W.

3.30 Power line, bears S. 30° W. and N. 30° E.

14.30 Wash, 10 lks wide, 1 ft. deep, drains S. 10° E.

21.50 Fence, bears SW. and NE.

21.85 Spur, projects S. 15° E.

30.50 Spur, slopes S.

39.71 The ¼ sec. cor. of secs. 8 and 17, which is monumented with a sandstone, 10 x 6 x 2 ins., marked ¼ on one face, lying loose on ground, adjacent to remains of a mound of stone.

Dependent Resurvey of a Portion of the Subdivision, T. 17 N., R. 5 E.

Chains

At the corner point

Set an iron post, 30 ins. long, 2½ ins. diam., 18 ins. in ground, and in a mound of stone, 3 ft. base to top, with brass cap marked

$$\begin{array}{r} \text{T17N R5E} \\ \frac{1}{4} \frac{\text{S } 8}{\text{S17}} \\ 1956 \end{array}$$

Bury original corner stone alongside iron post.

from which

A cedar, 10 ins. diam., bears N. 40° E., 141 lks. dist., marked ¼ S8 BT.

S. 89° 08' W., beginning new measurement.

Asc. 50 ft. over E. slope.

- 5.30 Top of hill, slopes N.; thence descend 100 ft. over rolling broken land to sec. cor.
- 14.40 Top of hill, bears N. and S.
- 27.30 Wash, 6 lks. wide, 3 ft. deep, drains N. 80° W.
- 33.40 Top of hill, bears N. 10° W. and S. 10° E.
- 39.78 The cor. of secs. 7, 8, 17, and 18.

Land, high rolling.

Soil, broken sandstone and sand.

Timber, cedar and pinon.

Undergrowth, palo verde, catclaw, Spanish dagger, cacti, and grass.

S. 88° 47' W., bet. secs. 7 and 18.

Over rolling land, through scattered timber.

- 12.50 Wash, 6 lks. wide, 3 ft. deep, drains S. 10° W.

- 40.02 The ¼ sec. cor. of secs. 7 and 8, which is monumented with a sandstone, 8 x 6 x 3 ins., marked ¼ on one face, lying loose on ground, adjacent to remains of a mound of stone.

At the corner point.

Set an iron post, 30 ins. long, 2½ ins. diam., 20 ins. in ground, and in a mound of stone, 3 ft. base to top, with brass cap marked

$$\begin{array}{r} \text{T17N R5E} \\ \frac{1}{4} \frac{\text{S7}}{\text{S18}} \\ 1956 \end{array}$$

Bury original corner stone alongside the iron post.

Dependent Resurvey of a Portion of the Subdivision, T. 17 N., R. 5 E

Chains

from which

A cedar, 8 ins. diam., bears S. 10° E., 50 lks. dist.,
marked $\frac{1}{4}$ S BT.

N. 86° 15' W., beginning new measurement.

Asc. 45 ft. over E. slope.

12.60 Top of slope; desc. 170 ft. over W. slope.

33.00 Wash, 1 ch. wide, 10 ft. deep, drains S.; asc. 75 ft. along general S. slope.

40.10 The cor. of secs. 7, 12, 13, and 18, on the West bdy. of the township.

Land, east half rolling; west half semi-mountainous.

Soil, rocky, gravelly and sandy.

Timber, cedar and pinon.

Undergrowth, palo verde, Spanish dagger, cacti, and grass.

From the cor. of secs. 7, 8, 17, and 18.

N. 0° 39' W., bet. secs. 7 and 8.

Over rolling land, through scattered timber.

25.70 Road, bears N. 60° W. and S. 60° E.; wash, 6 lks. wide, 3 ft. deep, drains SW.

28.60 Enter level clearing.

40.18 Point for the $\frac{1}{4}$ sec. cor. of secs. 7 and 8, at proportionate distance; there is no remaining evidence of the original corner.

Set an iron post, 30 ins. long, 2½ ins. diam., 10 ins. in ground, and in a mound of stone, 3 ft. base to top, with brass cap marked

T17N R5E

$\frac{1}{4}$

S7|S8

1956

60.00 Wash, 40 lks. wide, 5 ft. deep, drains SW.; leave clearing; asc. 80 ft. over S. slope, through scattered timber.

74.00 Top of slope; desc. 30 ft. over N. slope.

80.36 The cor. of secs. 5, 6, 7, and 8, which is monumented with a sandstone, 20 x 10 x 8 ins., marked with 5 notches on S, 5 notches on E. edges, set 10 ins. in ground.

from which

A juniper, 14 ins. diam., bears S. 10° W., 180 lks. dist.,
marked T17N R5E S7 BT.

A cedar, 12 ins. diam., bears N. 30° W., 176 lks. dist.,
marked T17N R5E S6 BT.

Dependent Resurvey of a Portion of the Subdivision, T. 17 N., R. 5 E.

Chains

At the corner point

Set an iron post, 30 ins. long, 2½ ins. diam., 20 ins. in ground, and in a mound of stone, 3 ft. base to top, with brass cap marked

T17N R5E	
S6	S5
S7	S8
1956	

Bury original corner stone alongside the iron post.

Land, rolling.

Soil, broken sandstone and sand.

Timber, cedar, pinon, a few juniper.

Undergrowth, palo verde, oak, catclaw, Spanish dagger, cactus, and grass.

From the cor. of secs. 4, 5, 8, and 9.

S. 89° 50' W., bet. secs. 5 and 8.

Over high, broken land, through medium heavy timber.

Asc. 270 ft. over broken general S. 70° E. slope.

18.50 Wash, 10 lks. wide, 2 ft. deep, drains S. 70° E.

39.95 The ¼ sec. cor. of secs. 5 and 8, which is monumented with a sandstone, 14 x 8 x 6 ins., marked ¼ on N. face, set 10 ins. in ground.

from which

A cedar, 12 ins. diam., bears S. 7° E., 54 lks. dist., marked ¼ S8 BT.

At the corner point

Set an iron post, 30 ins. long, 2½ ins. diam., 12 ins. in ground, and in a mound of stone, 3½ ft. base to top, with brass cap marked

T17N R5E	
¼ S5	
S8	
1956	

Bury original cornerstone alongside the iron post.

from which

A cedar, 18 ins. diam., bears N. 27° 30' E., 48 lks. dist., marked ¼ S5 BT.

S. 89° 36' W., beginning new measurement.

Asc. 420 ft. over very steep E. slope.

9.00 Top of sandstone ridge, called Cock's Comb, bears N. and S.; desc. 400 ft. over very steep W. slope.

20.00 Bottom of steep slope; continue descent; desc. 200 ft. over W. slope.

Dependent Resurvey of a Portion of the Subdivision, T. 17 N., R. 5 E.

Chains	
36.50	Wash, 15 lks. wide, 6 ft. deep, drains NW.
38.55	<p>The cor. of secs. 5, 6, 7 and 8.</p> <p>Land, middle 1/3 steep and mountainous; east 1/3 and west 1/3 moderate broken slopes.</p> <p>Soil, broken sandstone and sand.</p> <p>Undergrowth, oak, palo verde, cacti, and grass.</p>
	<p>N. 88° 49' W., bet. secs. 6 and 7.</p>
	<p>Over hilly land, through medium heavy timber.</p>
	<p>Desc. 65 ft. along N. slope of hill.</p>
30.00	<p>Wash, 50 lks. wide, 1 ft. deep, drains SW.; asc. 35 ft. over general E. slope.</p>
35.80	<p>Road, bladed, bears N. and S.</p>
40.34	<p>Point for the ¼ sec. cor. of secs. 6 and 7, at proportionate distance; there is no remaining evidence of the original corner.</p> <p>Set an iron post, 30 ins. long, 2½ ins. diam., on bedrock, and in a mound of stone, 4 ft. base to top, with brass cap marked</p>
	<p style="text-align: center;">T17N R5E ¼ $\frac{S6}{S7}$.1956</p>
	<p>from which</p>
	<p>A cedar limb, 10 ins. diam., bears N. 35° 30' E., 54 lks. dist., marked ¼ S6 BT.</p>
	<p>A cedar, 15 ins. diam., bears S. 40° E., 71 lks. dist., marked ¼ S7 BT.</p>
	<p>N. 88° 52' W., beginning new measurement.</p>
	<p>Desc. 100 ft. over broken hilly land.</p>
16.00	<p>Road, bladed, bears NW. and SE.</p>
18.00	<p>Wash, 10 lks. wide, 1½ ft. deep, drains SW.</p>
24.70	<p>Wash, 1 ch. wide, 2½ ft. deep, drains S.; asc. 60 ft. over E. slope.</p>
38.83	<p>The cor. of secs. 1, 6, 7 and 12, on the W. bdy. of the township.</p> <p>Land, hilly and broken.</p> <p>Soil, rocky and sandy.</p> <p>Timber, cedar and pinon.</p> <p>Undergrowth, oak, palo verde, catclaw, Spanish dagger, cacti, and grass.</p>

Dependent Resurvey of a Portion of the Subdivision, T. 17 N., R. 5 E.

Chains

From the cor. of secs. 5, 6, 7 and 8.

N. $0^{\circ} 20'$ W., bet. secs. 5 and 6.

Over nearly level land, through scattered timber.

8.60 Wash, 15 lks. wide, 7 ft. deep, drains W.

30.00 Wash, 6 lks. wide, 3 ft. deep, drains SW.

40.08 The $\frac{1}{2}$ sec. cor. of secs. 5 and 6, which is monumented with a sandstone, 18 x 12 x 5 ins., marked $\frac{1}{2}$ on W. face.

from which

A cedar, 24 ins. diam., bears N. 60° E., 185 lks. dist., marked $\frac{1}{2}$ S5 BT.

At the corner point

Set an iron post, 30 ins. long, $2\frac{1}{2}$ ins. diam., 20 ins. in ground, and in a mound of stone, 3 ft. base to top, with brass cap marked

T17N R5E

$\frac{1}{2}$

S6 | S5

1956

Bury original corner stone, alongside the iron post.

from which

A cedar, 4 ins. diam., bears NW., 105 lks. dist., marked $\frac{1}{2}$ S6 BT.

Cor. No. 1 of H.E.S. No. 626, which is monumented with a sandstone, 10 x 10 x 6 ins., above ground, marked and witnessed as described in the official record, bears N. $87^{\circ} 04'$ E., 11.40 chs. dist.

N. $1^{\circ} 10'$ E., beginning new measurement.

Asc. 90 ft. over S. slope.

12.00 Spur, slopes W.; continue ascent; asc. 150 ft. along W. slope.

25.00 Thence by traverse; true line runs along inaccessible, nearly vertical wall on W. side of Doe Mountain.

29.00 Top of ascent (determined from aerial photographs); desc. 100 ft. over N. 80° W. slope to sec. cor.

34.00 End of traverse.

41.48 The cor. of secs. 5 and 6 on the N. bdy. of the township.

Land, south half, nearly level; north half mountainous.

Soil, broken sandstone and sand.

Timber, cedar and pinon.

Undergrowth, oak, catclaw, palo verde, Spanish dagger, cacti, and grass.

BOOK 537

T. 17 N., R. 5 E.

Chains

General Description

The land within T. 17 N., R. 5 E., is principally high rolling and mountainous, with many sandstone pinnacles and buttes in evidence. The drainage throughout the township is toward Oak Creek, which enters the township on the E. bdy. of sec. 24 and flows through the township in a SW. direction, leaving on the S. bdy. of sec. 31. Dry Creek drains from the N. bdy. of sec. 4 to the S. bdy. of sec. 31, where it enters Oak Creek. It carries the drainage of most of the western half of the township.

The elevation ranges from 3800 ft. to 6350 ft. The average elevation being about 4400 ft.

The soil is principally sand, with numerous sandstone outcrops, and in some areas malpais rocks. A small amount of limestone is present near the western edge.

A growth of cedar and pinon covers the major portion of the township, varying from scattered to heavy in distribution. Yew trees are in evidence in the NE. part of the township and also along the edges of Dry Creek. Sycamore is in abundance along the major portion of the Oak Creek stream bed. Underbrush of scrub oak, palo verde, manzanita, catclaw, Spanish dagger, cacti, sparse native grass, and other growth is fairly evenly distributed.

About 1/5 of the land in T. 17 N., R. 5 E., is privately owned and there is a considerable demand for the land. A small amount of it is under cultivation and the largest portion has been utilized for housing development and has been subdivided into lots. Several ranches are located within the township and several private businesses are located along U. S. Highway 89A. Verde Valley School, a private institution, is located in sec. 35. There is very little evidence of any mining activity.

There are several roads. U. S. Highway 89A is the only hard surfaced road, but graded and dirt roads are fairly evenly distributed and make a good portion of the township accessible to vehicles.

Oak Creek carries a good stream of water throughout the year and this, together with private wells, accounts for all the water present.

The average of several readings, taken throughout the course of the survey, gives an average value of 14° 45' E., for the magnetic declination.

4-680
(Feb., 1950)

UNITED STATES
DEPARTMENT OF THE INTERIOR
BUREAU OF LAND MANAGEMENT

FIELD ASSISTANTS

NAMES	CAPACITY
Leroy McCulley	Notes, Rear chain
Archie Allen	Notes, Rear chain
Buel Johnson	Front chain
Clyde Hance	Flagman
Milton Clark	Axeman, Flagman
Clifton Harding	Truckdriver, Cornerman
Paul Bauer	Truckdriver, Cornerman
Max Ricketts	Axeman
Wayne DeLang	Axeman

CERTIFICATE OF CADASTRAL ENGINEER

I, Leslie H. Godwin, HEREBY CERTIFY upon honor that, in pursuance of special instructions bearing date of the 2nd day of August, 1956, I have ~~surveyed~~ independently resurveyed the North, South, and West boundaries, and a portion of the East boundary, and a portion of the subdivision of Township 17 North, Range 5 East

of the G. and S.R. Meridian, in the State of Arizona, which are represented in the foregoing field notes as having been executed by me and under my direction; and that said survey has been made in strict conformity with said instructions, the Manual of Instructions for the Survey of the Public Lands of the United States, and in the specific manner described in the foregoing field notes.

Salt Lake City, Utah
April 8, 1957

Leslie H. Godwin
Leslie H. Godwin
Cadastral Surveyor

CERTIFICATE OF APPROVAL

BUREAU OF LAND MANAGEMENT,
Washington, D. C., 19

The foregoing field notes of the survey of _____
_____ executed by _____
_____ having been critically examined and found correct, are hereby approved.

Cadastral Engineering Staff Officer.

CERTIFICATE OF TRANSCRIPT

I CERTIFY that the foregoing transcript of the field notes of the above-described surveys in _____, is a true copy of the original field notes.

Cadastral Engineering Staff Officer.


100 2071 551

CERTIFICATE OF CADASTRAL ENGINEER

I, Donald E. Harding, HEREBY CERTIFY upon honor that, in pursuance of special instructions bearing date of the 2nd day of August, 1956, I have ~~surveyed~~ supervised the dependent resurvey of the North, South, and West boundaries, and a portion of the East boundary, and a portion of the subdivision of Township 17 North, Range 5 East

of the G. and S. R. Meridian, in the State of Arizona, which are under my supervision represented in the foregoing field notes as having been executed ~~by me and under my direction~~; and that said survey has been made in strict conformity with said instructions, the Manual of Instructions for the Survey of the Public Lands of the United States, and in the specific manner described in the foregoing field notes.

Salt Lake City, Utah
April 8, 1957


Donald E. Harding
Cadastral Surveyor

CERTIFICATE OF APPROVAL

BUREAU OF LAND MANAGEMENT,
Washington, D. C., MAR 2 1959, 19

The foregoing field notes of the ~~survey of~~ dependent resurvey of the North, South, and West boundaries, and a portion of the East boundary, and a portion of the subdivision of Township 17 North, Range 5 East, of the Gila and Salt River Meridian, in the State of Arizona,

executed by Leslie H. Godwin, under the supervision of Donald E. Harding having been critically examined and found correct, are hereby approved.


Acting Cadastral Engineering Staff Officer.

CERTIFICATE OF TRANSCRIPT

I CERTIFY that the foregoing transcript of the field notes of the above-described surveys in _____, is a true copy of the original field notes.

Cadastral Engineering Staff Officer.