

UNITED STATES
DEPARTMENT OF THE INTERIOR
BUREAU OF LAND MANAGEMENT
ORIGINAL

FIELD NOTES

OF THE SURVEY

OF

A PORTION OF THE SUBDIVISION,

TOWNSHIP 40 NORTH, RANGE 9 EAST

AND

A PORTION OF THE PAGE TOWNSITE BOUNDARY

Of the Gila and Salt River Meridian,

In the State of Arizona

EXECUTED BY

Robert C. Yundt - Cadastral Surveyor (Chief of Party

Boyd S. Owens - Cadastral Surveyor

Under special instructions dated January 22, 1959, which provided
for the surveys included under Group No. 333, approved January 22, 1959
and assignment instructions dated January 28, 1959

Survey commenced March 12, 1959

Survey completed June 5, 1959

BOOK 4562

INDEX DIAGRAM

Township 40 North, Range 9 East

| | | | | | | | | | |
|----|----|----|---|----|---|----|----|----|---|
| | 10 | | 9 | | | | | | |
| | 10 | 8 | 9 | 5 | 4 | 3 | 3 | 2 | 1 |
| | 7 | | 7 | | 5 | | | | |
| 7 | 6 | 8 | 4 | 9 | 3 | 10 | 11 | 12 | |
| 1 | | 2 | | 2 | | | | | |
| 18 | | 17 | | 16 | | 15 | 14 | 13 | |
| 19 | | 20 | | 21 | | 22 | 23 | 24 | |
| 30 | | 29 | | 28 | | 27 | 26 | 25 | |
| 31 | | 32 | | 33 | | 34 | 35 | 36 | |

Township 40 North, Range 9 East

Chains

The west boundary of T. 40 N., R. 9 E. was concurrently surveyed as the east boundary of T. 40 N., R. 8 E., and the north boundary (Tenth Standard Parallel North) as the south boundary of T. 41 N., R. 9 E.

The following field notes are those of the survey of secs. 4, 5, 6, 7, 8 and 9 in T. 40 N., R. 9 E. The survey was made at the request of the U. S. Bureau of Reclamation in order to define the limits of the Federal Reservation surrounding the Glen Canyon Dam.

The survey was executed with a W. and L. E. Gurley solar transit number 541332, property of the Bureau of Land Management and constructed in accordance with their standard specifications. The horizontal plate of the instrument is equipped with two double verniers graduated to thirty seconds of arc. It has a full vertical circle, with one double vernier graduated to single minutes. Since the solar attachment was not used on this assignment, no description of it will be given here. The instrument was in good condition, and prior to the beginning of the field work it was tested and found free from error. It was tested frequently during the progress of the survey work in order to insure its continued accuracy.

The measurements were made with Chicago steel ribbon tapes, 8 chains in length. These tapes are graduated every link for the first chain and thereafter at intervals of 10 links. The tapes were tested by comparison with a standard steel tape, one chain in length, and found to be correct. The measurements were made on the slope and the vertical angle of each interval determined by the use of clinometers, or the transit on the steeper slopes, and the slope distances properly reduced to horizontal equivalents, which are used in these notes.

The geographic position of the cor. of secs. 9, 10, 15 and 16, determined from ties made to U. S. Coast and Geodetic survey stations Manson and Antelope is as follows: Latitude $36^{\circ} 52' 27.7''$ N. and longitude $111^{\circ} 25' 27.7''$ W. The mean magnetic declination was found to be 15° E.

Portion of the Subdivision, T. 40 N., R. 9 E.

Beginning at the cor. of secs. 7, 12, 13 and 18 on the W. bdy. of the township, monumented by a brass tablet, firmly set in solid surface rock, and conforming to the record of the survey of T. 40 N., R. 8 E.

East, bet. secs. 7 and 18.

Over rolling land, through medium dense undergrowth.

38.02 Point for the $\frac{1}{4}$ sec. cor. of secs. 7 and 18.

Set an iron post, 30 ins. long, $2\frac{1}{2}$ ins. diam., 8 ins. in the ground to solid rock, and in a mound of stone, with brass cap mkd.

T40N R9E
 $\frac{1}{4}$ $\frac{S 7}{S18}$
1959

Deposit broken glass at base of iron post.

60.90 Wash, 1 ch. wide, 3 ft. deep, drains N. 20° W.

78.02 Point for the cor. of secs. 7, 8, 17 and 18.

Set an iron post, 30 ins. long, $2\frac{1}{2}$ ins. diam., 20 ins. in the ground to solid rock, and in a mound of stone, with brass cap mkd.

Portion of the Subdivision, T. 40 N., R. 9 E.

Chains

T40N R9E
 S 7 | S 8
 S18 | S17
 1959

Deposit broken glass at base of iron post.

Land, rolling desert.

Soil, sandy clay and deep sand.

Timber, none; undergrowth, sagebrush, bitter brush, cactus, weeds and grass.

East, bet. secs. 8 and 17.

Over rolling land, through medium dense undergrowth.

40.00 Point for the $\frac{1}{4}$ sec. cor. of secs. 8 and 17.

Set an iron post, 30 ins. long, $2\frac{1}{2}$ ins. diam., 20 ins. in the ground to solid rock, and in a mound of stone, with brass cap mkd.

T40N R9E
 $\frac{1}{4}$ S 8
 S17
 1959

Deposit broken glass at base of iron post.

80.00 Point for the cor. of secs. 8, 9, 16 and 17.

Set an iron post, 30 ins. long, $2\frac{1}{2}$ ins. diam., 22 ins. in the ground to solid rock, and in a mound of stone, with brass cap mkd.

T40N R9E
 S 8 | S 9
 S17 | S16
 1959

Deposit broken glass at base of iron post.

Land, rolling hills with exposed sandstone bedrock and low ledges. Soil, sand and barren sandstone.

Timber, none; undergrowth, sagebrush, bitter brush, cactus, weeds and grass.

East, bet. secs. 9 and 16.

Over rolling hills, through medium dense undergrowth.

24.60 Graded gravel road, locally called the Copper Mine Road, bears SW. and N.

40.00 Point for the $\frac{1}{4}$ sec. cor. of secs. 9 and 16.

Set an iron post, 30 ins. long, $2\frac{1}{2}$ ins. diam., 22 ins. in the ground to solid rock, and in a mound of stone, with brass cap mkd.

T40N R9E
 $\frac{1}{4}$ S 9
 S16
 1959

Deposit broken glass at base of iron post.

53.65 Shallow wash, drains N. 30° E.

Portion of the Subdivision, T. 40 N., R. 9 E.

Chains

80.00

Point for the cor. of secs. 9, 10, 15 and 16.

Set an iron post, 30 ins. long, 2½ ins. diam., 26 ins. in the ground, with brass cap mkd.

T40N R9E
 S 9 | S10
 S16 | S15
 1959.

Raise a mound of stone W. of iron post.

Land, rolling hills.

Soil, rocky sand, exposed sandstone bedrock and low sandstone ledges.

Timber, few scattered juniper.

Undergrowth, sagebrush, bitter brush, cactus, weeds and grass.

From the cor. of secs. 9, 10, 15 and 16.

N. 0° 02' W., bet. secs. 9 and 10.

Over rolling land, through medium dense undergrowth.

40.00

Point for the ¼ sec. cor. of secs. 9 and 10.

Set an iron post, 30 ins. long, 2½ ins. diam., 22 ins. in the ground to solid rock, and in a mound of stone, with brass cap mkd.

T40N R9E
 ¼
 S 9 | S10
 1959

Deposit broken glass at base of iron post.

76.70

Shallow wash, drains NE.

80.00

Point for the cor. of secs. 3, 4, 9 and 10, on barren rock.

Set an iron post, 15 ins. long, 1 in. diam., 10 ins. in a hole drilled in solid rock, with brass cap mkd.

T40N R9E
 S 4 | S 3
 S 9 | S10
 1959

Raise a mound of stone W. of iron post.

Land, rolling desert.

Soil, rocky sand, exposed sandstone bedrock and low sandstone ledges.

Timber, none; undergrowth, sagebrush, bitter brush, cactus, weeds and grass.

N. 0° 02' W., bet. secs. 3 and 4.

Over rolling land, through medium dense undergrowth.

40.00

Point for the ¼ sec. cor. of secs. 3 and 4.

Set an iron post, 15 ins. long, 1 in. diam., 10 ins. in a hole drilled in solid rock, with brass cap mkd.

Portion of the Subdivision, T. 40 N., R. 9 E.

Chains

T40N R9E

$$\begin{array}{r} \frac{1}{2} \\ S\ 4\ | S\ 3 \\ 1959 \end{array}$$

Raise a mound of stone W. of iron post.

79.91 Intersect the 10th Standard Parallel North at a point 17.96 chs. W. of the standard cor. of secs. 33 and 34, mkd. by an iron post, 2½ ins. diam., firmly set in the ground and conforming to the record of the survey of T. 41 N., R. 9 E.

At the point of intersection, at the closing cor. of secs. 3 and 4.

Set an iron post, 30 ins. long, 2½ ins. diam., 22 ins. in the ground to solid rock, and in a mound of stone, with brass cap mkd.

T41N R9E

$$\begin{array}{r} S33 \\ S\ 4\ | S\ 3 \\ T40N\ R9E \\ C\ C \\ 1959 \end{array}$$

Raise a mound of stone S. of iron post.

Land, rolling desert.

Soil, rocky sand.

Timber, none; undergrowth, sagebrush, bitter brush, cactus, weeds and grass.

From the cor. of secs. 8, 9, 16 and 17.

N. 0° 03' W., bet. secs. 8 and 9.

Over rolling land, through medium dense undergrowth.

40.00 Point for the ¼ sec. cor. of secs. 8 and 9.

Set an iron post, 30 ins. long, 2½ ins. diam., 22 ins. in the ground to solid rock, and in a mound of stone, with brass cap mkd.

T40N R9E

$$\begin{array}{r} \frac{1}{2} \\ S\ 8\ | S\ 9 \\ 1959 \end{array}$$

Raise a mound of stone W. of iron post.

68.70 Top of low conical hill.

79.60 Unimproved road, bears SW. to city dump and NE. to Copper Mine Road.

80.00 Point for the cor. of secs. 4, 5, 8 and 9.

Set an iron post, 30 ins. long, 2½ ins. diam., 22 ins. in the ground to solid rock, and in a mound of stone, with brass cap mkd.

T40N R9E

$$\begin{array}{r} S\ 5\ | S\ 4 \\ S\ 8\ | S\ 9 \\ 1959 \end{array}$$

Raise a mound of stone W. of iron post.

Portion of the Subdivision, T. 40 N., R. 9 E.

Chains

Land, rolling desert.
Soil, rocky sand, exposed sandstone bedrock and low sandstone ledges.
Timber, few widely scattered juniper.
Undergrowth, sagebrush, bitter brush, cactus, weeds and grass.

From the cor. of secs. 3, 4, 9 and 10.

West, bet. secs. 4 and 9.

Over rolling land, through medium dense undergrowth.

40.01 Point for the $\frac{1}{4}$ sec. cor. of secs. 4 and 9.

Set an iron post, 30 ins. long, $2\frac{1}{2}$ ins. diam., 8 ins. in the ground to solid rock, and in a mound of stone, with brass cap mkd.

T40N R9E

$$\frac{1}{4} \frac{S \ 4}{S \ 9}$$

1959

Deposit broken glass at base of iron post.

75.35 Graded gravel road, bears NW. and SE., Copper Mine Road.

79.10 Unimproved road, bears SW. to city dump and NE. to Copper Mine Road.

80.02 The cor. of secs. 4, 5, 8 and 9.

Land, rolling hills.

Soil, rocky sand, exposed sandstone bedrock, and low sandstone ledges.
Timber, widely scattered juniper.
Undergrowth, sagebrush, bitter brush, cactus, weeds and grass.

N. $0^{\circ} 03'$ W., bet. secs. 4 and 5.

Over rolling land, through medium dense undergrowth.

12.10 Graded gravel road, Copper Mine Road, bears NW. and SE.

37.40 Unimproved road, bears E. to Gun Club and W. to Copper Mine Road.

40.00 Point for the $\frac{1}{4}$ sec. cor. of secs. 4 and 5, and the SE. cor. of the Page Townsite.

Set an iron post, 30 ins. long, $2\frac{1}{2}$ ins. diam., 22 ins. in the ground to solid rock, and in a mound of stone, with brass cap mkd.

T40N R9E

$$P \ TS \ \frac{1}{4}$$

$$S \ 5 \ | \ S \ 4$$

1959

Deposit broken glass at base of iron post

from which

The SW. cor. of the Page Gun Club building bears S. $55^{\circ} 31'$ E., 8.02 chs.

Continue along E. bdy. of the Page Townsite.

40.15 Power line, bears S. $49^{\circ} 30'$ E. to Page Gun Club and N. $49^{\circ} 30'$ W. to Page, Arizona.

Portion of the Subdivision, T. 40 N., R. 9 E

Chains

79.96

Intersect the 10th Standard Parallel North at a point 18.01 chs. W. of the standard cor. of secs. 32 and 33, mkd. by an iron post, 2½ ins. diam., firmly set in the ground and conforming to the record of the survey of T. 41 N., R. 9 E.

At the point of intersection, at the closing cor. of secs. 4 and 5, and on the bdy. of the Page Townsite

Set an iron post, 30 ins. long, 2½ ins. diam., 22 ins. in the ground, and in a mound of stone, with brass cap mkd.

P TS
T41N R9E
S32
S 5 | S 4
T40N R9E
C C
1959

Deposit broken glass at base of iron post.

Land, rolling hills.

Soil, rocky sand, exposed sandstone bedrock, and sandstone ledges.

Timber, few scattered juniper.

Undergrowth, sagebrush, bitter brush, cactus, weeds and grass.

At midpoint on the N. bdy. of sec. 4 and at a point 17.985 chs. W. of the standard ¼ sec. cor. of sec. 33, mkd. by an iron post, 2½ ins. diam., conforming to the record of the survey of T. 41 N., R. 9 E. Point for the ¼ sec. cor. of sec. 4.

Set an iron post, 30 ins. long, 2½ ins. diam., 26 ins. in the ground, with brass cap mkd.

¼ S 4
T40N R9E
1959

Raise a mound of stone S. of iron post.

From the cor. of secs. 7, 8, 17 and 18.

N. 0° 03' W., bet. secs. 7 and 8.

Over rolling land, through medium dense undergrowth.

40.00

Point for the ¼ sec. cor. of secs. 7 and 8.

Set an iron post, 30 ins. long, 2½ ins. diam., 14 ins. in the ground to solid rock, and in a mound of stone, with brass cap mkd.

T40N R9E
¼
S 7 | S 8
1959

Deposit broken glass at base of iron post.

80.00

Point for the cor. of secs. 5, 6, 7 and 8.

Set an iron post, 30 ins. long, 2½ ins. diam., 25 ins. in the ground, with brass cap mkd.

T40N R9E
S 6 | S 5
S 7 | S 8
1959

Portion of the Subdivision, T. 40 N., R. 9 E.

Chains

Raise a mound of stone W. of the iron post.

Land, rolling hills.

Soil, rocky sand, exposed sandstone bedrock, and low sandstone ledges.

Timber, few scattered juniper.

Undergrowth, sagebrush, bitter brush, cactus, weeds and grass.

From the cor. of secs. 4, 5, 8 and 9.

N. 89° 59' W., bet. secs. 5 and 8.

Over rolling land, through medium dense undergrowth.

40.01 Point for the $\frac{1}{4}$ sec. cor. of secs. 5 and 8.

Set an iron post, 30 ins. long, $2\frac{1}{2}$ ins. diam., 24 ins. in the ground, with brass cap mkd.

T40N R9E
 $\frac{1}{4}$ $\frac{S 5}{S 8}$
1959

Deposit broken glass at base of iron post, and raise a mound of stone to the S.

80.02 The cor. of secs. 5, 6, 7 and 8.

Land, rolling desert.

Soil, rocky sand, exposed sandstone bedrock, and low sandstone ledges.

Timber, few scattered juniper.

Undergrowth, sagebrush, bitter brush, cactus, weeds and grass.

West, bet. secs. 6 and 7.

Over rolling land, through medium dense undergrowth.

32.90 Wash, 1 ch. wide, 3 ft. deep, drains N. 20° W.

40.00 Point for the $\frac{1}{4}$ sec. cor. of secs. 6 and 7.

Set an iron post, 30 ins. long, $2\frac{1}{2}$ ins. diam., 24 ins. in the ground, with brass cap mkd.

T40N R9E
 $\frac{1}{4}$ $\frac{S 6}{S 7}$
1959

Deposit broken glass at base of iron post.

46.00 Shallow wash, drains N. 30° E.

73.00 Shallow wash, drains N.

77.90 The cor. of secs. 1, 6, 7 and 12 on the W. bdy., mkd. by an iron post, $2\frac{1}{2}$ ins. diam., firmly set in the ground, and conforming to the record of the survey of T. 40 N., R. 8 E.

Land, rolling desert.

Soil, rocky sand, exposed sandstone bedrock, and low sandstone ledges.

Timber, few scattered juniper.

Undergrowth, sagebrush, bitter brush, cactus, weeds and grass.

Portion of the Subdivision, T. 40 N., R. 9 E.

Chains

From the cor. of secs. 5, 6, 7 and 8.

N. 0° 03' W., bet. secs. 5 and 6.

Over rolling land, through medium dense undergrowth.

40.00 Point for the ¼ sec. cor. of secs. 5 and 6, on the S. bdy. of the Page Townsite

Set an iron post, 30 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.

P TS
T40N R9E
¼
S 6 | S 5
1959

Deposit broken glass at base of iron post.

80.00 Intersect the 10th Standard Parallel North at a point 17.97 chs. W. of the standard cor. of secs. 31 and 32, mkd. by an iron post, 2½ ins. diam., conforming to the record of the survey of T. 41 N., R. 9 E

At the point of intersection, at the closing cor. of secs. 5 and 6.

Set an iron post, 30 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.

T41N R9E
S31
S 6 | S 5
T40N R9E
C C
1959

Deposit broken glass at base of iron post.

Land, rolling desert.

Soil, rocky sand, exposed sandstone bedrock and low sandstone ledges. Timber, few scattered juniper.

Undergrowth, sagebrush, bitter brush, cactus, weeds and grass.

At midpoint on the N. bdy. of sec. 5, and at a point 17.99 chs. W. of the standard ¼ sec. cor. of sec. 32, mkd. by an iron post, 2½ ins. diam., firmly set in the ground and conforming to the record of the survey of T. 41 N., R. 9 E.

Point for the ¼ sec. cor. of sec. 5.

Set an iron post, 30 ins. long, 2½ ins. diam., 24 ins. in the ground, and in a mound of stone, with brass cap mkd.

¼ S 5
T40N R9E
1959

Deposit broken glass at base of iron post.

Portion of the Subdivision, T. 40 N., R. 8 E.

Chains

At a point 40.00 chs. W. of the closing cor. of secs. 5 and 6, and at a point 17.97 chs. W. of the standard $\frac{1}{4}$ sec. cor. of sec. 31, T. 41 N., R. 9 E., mkd. by an iron post, $2\frac{1}{2}$ ins. diam., firmly set in the ground and conforming to the record of the survey of that township.

Point for the $\frac{1}{4}$ sec. cor. of sec. 6.

Set an iron post, 30 ins. long, $2\frac{1}{2}$ ins. diam., 22 ins. in the ground to solid rock, and in a mound of stone, with brass cap mkd.

$\frac{1}{4}$ S 6
T40N R9E
1959

Deposit broken glass at base of iron post.

Subdivision of Sec. 5

From the $\frac{1}{4}$ sec. cor. of secs. 5 and 8.

N. $0^{\circ} 03'$ W., along the N-S. center line of sec. 5.

Over rolling land, through medium dense undergrowth.

39.99 Intersect the E-W. center line of sec. 5, and the S. bdy. of Page City Townsite.

Point for the center $\frac{1}{4}$ sec. cor. of sec. 5.

Set an iron post, 30 ins. long, $2\frac{1}{2}$ ins. diam., 26 ins. in the ground, with brass cap mkd.

P TS
T40N R9E
C $\frac{1}{4}$
+
S 5
1959

Deposit broken glass at base of iron post, and raise a mound of stone to the N.

63.10 Graded gravel road, Copper Mine Road, bears NW. and SE.

79.97 The $\frac{1}{4}$ sec. cor. of sec. 5, on the N. bdy. of the township.

Land, rolling desert.

Soil, Rocky sand, exposed sandstone bedrock, and low sandstone ledges. Timber, none; undergrowth, sagebrush, bitter brush, cactus, weeds and grass.

From the $\frac{1}{4}$ sec. cor. of secs. 4 and 5, and the SE. cor. of the Page Townsite.

N. $89^{\circ} 59'$ W., along the E-W. center line of sec. 5, along the S. bdy. of the Page City Townsite.

Over rolling land, through medium dense undergrowth.

11.20 Graded gravel road, Copper Mine Road, bears NW. and SE.

39.99 The center $\frac{1}{4}$ sec. cor. of sec. 5.

79.98 The $\frac{1}{4}$ sec. cor. of secs. 5 and 6.

Portion of the Subdivision, T. 40 N., R. 9 E.

Chains

Land, rolling desert.
Soil, rocky sand, exposed sandstone bedrock, and low sandstone ledges.
Timber, none; undergrowth, sagebrush, bitter brush, cactus, weeds and grass.

Subdivision of Sec. 6

From the $\frac{1}{4}$ sec. cor. of secs. 6 and 7.

N. $0^{\circ} 03' W.$, along the N-S. center line of sec. 6.

Over rolling land, through medium dense undergrowth.

9.90 Shallow wash, drains N. $30^{\circ} E.$

15.30 Wash, drains N. $60^{\circ} W.$

40.00 Intersect the E-W. center line of sec. 5, and the S. bdy. of the Page Township.

Point for the center $\frac{1}{4}$ sec. cor.

Set an iron post, 30 ins. long, $2\frac{1}{2}$ ins. diam., 24 ins. in the ground, with brass cap mkd.

P TS
T40N R9E
C $\frac{1}{4}$
+
S 6
1959

Raise a mound of stone W. of iron post.

80.00 The $\frac{1}{4}$ sec. cor. of sec. 6 on the N. bdy. of the township.

Land, rolling desert.
Soil, rocky sand, exposed sandstone bedrock, and low sandstone ledges.
Timber, none; undergrowth, sagebrush, bitter brush, cactus, weeds and grass.

From the cor. of secs. 5 and 6.

West, along the E-W. center line of sec. 6, and the S. bdy. of the Page Township.

Over rolling land, through medium dense undergrowth.

39.99 The center $\frac{1}{4}$ sec. cor. of sec. 6.

63.10 Wash, 30 lks. wide, 4 ft. deep, drains NW.

77.83 The $\frac{1}{4}$ sec. cor. of secs. 1 and 6 on the W. bdy. of the township, mkd. by an iron post, $2\frac{1}{2}$ ins. diam., firmly set in the ground and in a mound of stone and conforming to the record of the survey of T. 40 N., R. 8 E.

Land, rolling desert.
Soil, rocky sand, exposed sandstone bedrock and low sandstone ledges.
Timber, none; undergrowth, sagebrush, bitter brush, cactus, weeds and grass.

Township 40 North, Range 9 East

Chains

GENERAL DESCRIPTION

The land in T. 40 N., R. 9 E. covered by this survey is located in the desert area immediately south of Manson Mesa. The surface is largely a rolling sand, with considerable exposed sandstone bedrock and low sandstone islands. The soil is a loose rocky sand.

The vegetation consists mainly of scrub sagebrush, with lesser amounts of bitter brush, cactus, weeds and grass. There are a few scattered scrub juniper in the area. There is no living water.

All of the surveyed land is in the Glen Canyon Reservation and the northern halves of secs. 5 and 6 are in the Page Townsite. The Page Gun Club building is located in the northwest quarter of the northwest quarter of sec. 9. Along the old Copper Mine Road there are many Indian hogans.

CERTIFICATE OF CADASTRAL ENGINEER

I, Boyd S. Owens, HEREBY CERTIFY upon honor that, in pursuance of special instructions bearing date of the 22nd day of January, 1959, I have surveyed a portion of the subdivision of Township 40 North, Range 9 East, and a portion of the Page Townsite boundary

of the Gila & Salt River Meridian, in the State of Arizona, which are represented in the foregoing field notes as having been executed by me and under my direction; and that said survey has been made in strict conformity with said instructions, the Manual of Instructions for the Survey of the Public Lands of the United States, and in the specific manner described in the foregoing field notes.

July 17, 1959
Salt Lake City, Utah

Boyd S. Owens
Boyd S. Owens, Cadastral Surveyor

CERTIFICATE OF APPROVAL

BUREAU OF LAND MANAGEMENT,
Washington, D. C., 19

The foregoing field notes of the survey of _____
executed by _____
having been critically examined and found correct, are hereby approved.

Cadastral Engineering Staff Officer.

CERTIFICATE OF TRANSCRIPT

I CERTIFY that the foregoing transcript of the field notes of the above-described surveys in _____, is a true copy of the original field notes.

Cadastral Engineering Staff Officer.

CERTIFICATE OF CADASTRAL ENGINEER

I, Robert C. Yundt, HEREBY CERTIFY upon honor that, in pursuance of special instructions bearing date of the 22nd day of January, 1959, I have surveyed supervised the survey of a portion of the subdivision, Township 40 North, Range 9 East, and a portion of the Page Townsite boundary

of the Gila & Salt River Meridian, in the State of Arizona, which are represented in the foregoing field notes as having been executed by me and under my direction; and that said survey has been made in strict conformity with said instructions, the Manual of Instructions for the Survey of the Public Lands of the United States, and in the specific manner described in the foregoing field notes.

July 17, 1959
Salt Lake City, Utah

Robert C. Yundt
Robert C. Yundt, Cadastral Surveyor

CERTIFICATE OF APPROVAL

BUREAU OF LAND MANAGEMENT,
Washington, D. C., SEP 14 1959, 19

The foregoing field notes of the survey of a portion of the subdivision, Township 40 North, Range 9 East, and a portion of the Page Townsite boundary, Gila and Salt River Meridian, Arizona

executed by Boyd S. Owens, under the supervision of Robert C. Yundt having been critically examined and found correct, are hereby approved.

James B. Clement
Acting Cadastral Engineering Staff Officer.

CERTIFICATE OF TRANSCRIPT

I CERTIFY that the foregoing transcript of the field notes of the above-described surveys in is a true copy of the original field notes.

Cadastral Engineering Staff Officer