

UNITED STATES
DEPARTMENT OF THE INTERIOR
BUREAU OF LAND MANAGEMENT

ORIGINAL

FIELD NOTES

OF THE

DEPENDENT RESURVEY

OF A

PORTION OF THE EAST BOUNDARY,

A PORTION OF THE WEST BOUNDARY

AND A

PORTION OF THE SUBDIVISION

OF

TOWNSHIP 1 SOUTH, RANGE 3 WEST

Of the GILA AND SALT RIVER *Meridian,*

In the State of ARIZONA

EXECUTED BY

DONALD E. HARDING, CADASTRAL SURVEYOR

Under special instructions dated December 26, 1957..., *which provided*
for the surveys included under Group No. 322, *approved* December 26, 1957
and assignment instructions dated January 20, 1958.....

Survey commenced February 10, 19 58.....

Survey completed March 10, 19 58.....

BOOK 4574

INDEX DIAGRAM

Township 1 South, Range 3 West

	6	5	4	3	2	1	
	7	8	9	10	11	12	
	41	41	32	26	19	12	
5	18	40 17	32 16	25 15	18 14	11 13	2
	40	39	31	24	17	10	
5	19	38 20	30 21	23 22	16 23	9 24	2
	37	36	29	22	16	9	
4	30	35 29	28 28	21 27	14 26	8 25	1
	34	34	27	21	14	7	
3	31	33 32	26 33	20 34	13 35	6 36	

Township 1 South, Range 3 West

Chains

The following field notes are those of a dependent resurvey of a portion of the east boundary, a portion of the west boundary and a portion of the subdivision of T. 1 S., R. 3 W., Gila and Salt River Meridian, Arizona.

The request for this resurvey was made by the Range Manager, Arizona Grazing Districts 2 and 3 in memorandum dated December 6, 1955, to facilitate range management and land classification.

The four boundaries and the subdivisional lines of this township were surveyed by R. C. Powers in 1882-83, represented on the plat approved February 21, 1883. The east half mile of the south boundary was resurveyed by W. H. Thorn in 1916 and the west $5\frac{1}{2}$ miles was resurveyed by K. L. Siebecker in 1931, as represented on the plat of T. 2 S., R. 3 W. approved June 14, 1932. The original corners were made to refer to the north only. The east boundary was resurveyed by K. L. Siebecker in 1931, as represented on the plat of T. 1 S., R. 2 W. approved June 14, 1932.

The northern portion of this township is almost entirely patented and there has been no request for a resurvey of this area.

The survey was executed with a W. and L. E. Gurley solar transit, serial No. 541332, constructed in accordance with the standard instrumental specifications of the Bureau of Land Management. The instrument was in good condition and placed in proper adjustment prior to beginning the survey. Measurements were made with a Lallie steel tape 5 chains in length, graduated every one-tenth of a link for the first link, every link for the next 99 links and every 10 links thereafter. The tape was tested by comparison with a standard steel tape and found to be correct.

The measurements were made on the slope and the vertical angle of each interval was ascertained by a clinometer in good adjustment. The horizontal equivalents only are entered in this field note record. The azimuth of the lines was determined by sustained angulation from U. S. Coast and Geodetic Survey triangulation stations "Buckeye" and "Mica," which are located within the boundaries of this township.

The geographic position of the southeast corner of the township is in latitude $33^{\circ} 17' 25.435''$ N. and longitude $112^{\circ} 30' 13.283''$ W.

The mean magnetic declination is $14^{\circ} 30'$ E.

Dependent Resurvey Portion of East Boundary, T. 1 S., R. 3 W.

Reestablishment of a portion of the resurvey executed by K. L. Siebecker in 1931.

From the $\frac{1}{4}$ sec. cor. of secs. 25 and 30, on the E. bdy. of the Tp., which is monumented with a 1 in. iron post, set, mkd. and witnessed as described in the official record.

N. $0^{\circ} 17'$ E., bet. secs. 25 and 30.

Desc. over gentle NE. slope, through scattered undergrowth.

40.01 Point for the cor. of secs. 19, 24, 25 and 30, which falls in the center of a large wash.

Dependent Resurvey Portion of the East Boundary, T. 1 S., R. 3 W.

Chains	
	<p>This point is proportionate measurement in latitude and a continuation of the center line of a road from the N. for longitude. As it was unsafe to set an iron post at this corner point, a witness corner was set N. 0° 03' W., 2 chs. dist.</p>
	<p>From the true point for the cor. of secs. 19, 24, 25 and 30. N. 0° 03' W., bet. secs. 19 and 24.</p>
	<p>Over rolling land, through scattered undergrowth.</p>
	<p>Asc. out of wash.</p>
2.00	<p>Point selected for the witness cor. of secs. 19, 24, 25 and 30.</p>
	<p>Set an iron post, 28 ins. long, 2½ ins. diam., 22 ins. in the ground, with brass cap mkd.</p>
	<p style="text-align: center;"> T1S R3W R2W S24 S19 S25 S30 W C 1958 </p>
	<p>Raise a mound of stone, 3 ft. base, 2 ft. high, W. of cor.</p>
3.00	<p>Enter road, bearing N. and ESE.; thence along center line of road.</p>
40.00	<p>Point for the ¼ sec. cor. of secs. 19 and 24. The original iron post was found lying loose on the ground. Reset the 1 in. iron post, 27 ins. in the ground, with brass cap mkd.</p>
	<p style="text-align: center;"> T1S R3W R2W ¼ S24 S19 1958 </p>
	<p>Raise a mound of stone 3 ft. base, 2 ft. high, W. of cor.</p>
	<p>Cont. along center of road.</p>
80.00	<p>The cor. of secs. 13, 18, 19 and 24, which is monumented with a 2 ins. iron post, set, mkd. and witnessed as described in the official record.</p>
	<p>Land, nearly level. Soil, sandy and gravelly. Timber, none. Undergrowth, scattered greasewood.</p>
	<p>N. 0° 51' W., bet. secs. 13 and 18.</p>
	<p>Down the center line of graded road.</p>
39.87	<p>Point for the ¼ sec. cor. of secs. 13 and 18, which was found to be monumented with a steel pin, 2 ft. long, 1 in. diam., buried 4 ins. below the surface of the road. As there was no safe place to establish reference monuments, the cor. monumentation was left as found.</p>
79.74	<p>Point for the cor. of secs. 7, 12, 13 and 18. As the iron post was found lying loose on the ground, the cor. point was reestablished from some of the original bearing trees.</p>

Dependent Resurvey Portion of East Boundary, T. 1 S., R. 3 W.

Chains

from which

Original bearing tree, a mesquite 40 ins. diam., bears N. $9\frac{3}{4}^{\circ}$ E.,
341 lks. dist., mkd. T1S R2W S7 BT.

Original bearing tree, a mesquite 10 ins. diam., bears S. $72\frac{1}{4}^{\circ}$ E.,
297 lks. dist., mkd. T1S R2W S18 BT.

At the cor. point,

Set the original iron post with its cap, 6 ins. below the surface of
the road.

Land, level.

Timber, none.

Soil, sandy loam.

Undergrowth, none.

Dependent Resurvey Portion of West Boundary, T. 1 S., R. 3 W.

Reestablishment of the survey executed by R. C. Powers in 1882.
From the cor. of Tps. 1 S., Rs. 3 and 4 W., monumented by an iron
post, 3 ins. diam., as described in the official record.

N. $0^{\circ} 05'$ E., bet. secs. 31 and 36.

Over rolling land, through scattered undergrowth.

- 7.10 Wash, 10 lks. wide, 2 ft. deep, drains N. 80° W.
- 15.20 Wash, 10 lks. wide, 2 ft. deep, drains NW.
- 27.30 Road, bears N. 10° W. and S. 10° E.
- 27.50 Wash, 20 lks. wide, 1 ft. deep, drains N. 20° W.
- 39.92 Point for the $\frac{1}{4}$ sec. cor. of secs. 31 and 36, at proportionate dist.;
No remaining evidence of the original cor.
- Set an iron post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 16 ins. in the ground
and in a mound of stone to top, with brass cap mkd.

T1S
R4W R3W

$\frac{1}{4}$
S36 | S31
1958

49.80 Power line, 80 lks. E. of line, bears S. and N. 10° E.

54.80 Small wash, drains NW.

76.30 Wash, 1 ch. wide, 2 ft. deep, drains N. 10° E.

79.84 The cor. of secs. 25, 30, 31 and 36, which is monumented with a
granite stone, 12x6x3 ins., dimly mkd. and firmly set in a mound of
stone.

At the cor. point

Set an iron post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 22 ins. in the ground,
with brass cap mkd.

Dependent Resurvey Portion of the West Boundary, T. 1 S., R. 3 W.

Chains	T1S R4W R3W S25 S30 S36 S31 1958
	Bury the original cor. alongside the iron post.
	Raise a mound of stone, 3 ft. base, 2 ft. high, W. of the cor.
	Land, rolling. Soil, sandy and rocky. Timber, none. Undergrowth, scattered palo verde, mesquite, greasewood, cacti and sparse grass.
	N. 0° 10' W., bet. secs. 25 and 30.
	Over rolling land, through scattered undergrowth.
9.00	Enter wash, 1 ch. wide, 2 ft. deep, drains N. from S. 10° E.
14.00	Leave wash, drains N. 30° E.
24.80	Road, bears N. 10° E. and S. 10° W.
34.20	Same wash, 1 ch. wide, 3 ft. deep, drains NW.
40.00	Point for the $\frac{1}{4}$ sec. cor. of secs. 25 and 30, at proportionate dist.; no remaining evidence of the original cor.
	Set an iron post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 22 ins. in the ground, with brass cap mkd.
	T1S R4W R3W $\frac{1}{4}$ S25 S30 1958
	Raise a mound of stone, 3 ft. base, 2 ft. high, W. of cor.
54.80	Same wash, 1 ch. wide, 3 ft. deep, drains N. 10° E.
61.50	Same wash, drains NW.
80.00	The cor. of secs. 19, 24, 25 and 30, which is monumented with an iron pin set in the center of an old mound of stone.
	At the cor. point
	Set an iron post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 22 ins. in the ground, with brass cap mkd.
	T1S R4W R3W S24 S19 S25 S30 1958
	Bury the iron pin alongside the iron post.
	Raise a mound of stone, 3 ft. base, 2 ft. high, W. of cor.
	Land, rolling. Soil, rocky and gravelly. Timber, none. Undergrowth, scattered palo verde, mesquite, greasewood, cacti and sparse grass.

Dependent Resurvey Portion of West Boundary, T. 1 S., R. 3 W.

Chains	N. 0° 10' E., bet. secs. 19 and 24. Over rolling land, through scattered undergrowth.
17.80	Road, bears NE. and SW.
39.97	The $\frac{1}{4}$ sec. cor. of secs. 19 and 24, which was monumented with a granite stone, 24x10x10, dimly mkd., firmly set in a mound of stone. At the cor. point Set an iron post, 28 ins. long, 2 $\frac{1}{2}$ ins. diam., 22 ins. in the ground, with brass cap mkd. <div style="text-align: center;">T1S R4W R3W $\frac{1}{4}$ S24 S19 1958</div> Bury the original cornerstone alongside the iron post. Raise a mound of stone, 3 ft. base, 2 ft. high, W. of cor.
	<hr/>
	N. 0° 09' E., beginning new measurement.
28.00	Fence, bears E. and W.
39.73	The cor. of secs. 13, 18, 19 and 24, which is monumented with an iron pin firmly set in an old mound of stone. At the cor. point Set an iron post, 28 ins. long, 2 $\frac{1}{2}$ ins. diam., 22 ins. in the ground, with brass cap mkd. <div style="text-align: center;">T1S R4W R3W S13 S18 S24 S19 1958</div> Bury the iron pin alongside the iron post. Raise a mound of stone, 3 ft. base, 2 ft. high, W. of cor. Land, nearly level. Soil, sandy and gravelly. Timber, none. Undergrowth, scattered greasewood, palo verde, mesquite, cacti and sparse grass.
	<hr/>
	N. 0° 13' E., bet. secs. 13 and 18. Over level bottom land, through medium dense undergrowth.
5.50	Wash, 30 lks. wide, 2 ft. deep, drains W.
10.60	Wash, 50 lks. wide, 1 ft. deep, drains W.
16.00	Wash, 20 lks. wide, 3 ft. deep, drains W.
21.20	Wash, 30 lks. wide, 1 ft. deep, drains W.
37.20	Gila River, 70 lks. wide, 4 ft. deep, drains W.
40.00	The $\frac{1}{4}$ sec. cor. of secs. 13 and 18, which is monumented with an iron pin, firmly set in a mound of small stones.

Dependent Resurvey Portion of the West Boundary, T. 1 S., R. 3 W.

Chains

At the cor. point

Set an iron post, 28 ins. long, 2½ ins. diam., 22 ins. in the ground, with brass cap mkd.

T1S
R4W R3W
½
S13 | S18
1958

Bury the iron pin alongside the iron post.

Raise a mound of stone, 2 ft. base, 1½ ft. high, W. of cor.

20.00

to, 20 chs. long, 3 ft. deep, bearing N. 80°

20.00

N. 0° 07' E., beginning new measurement.

30.70

Wash, 30 lks. wide, 3 ft. deep, drains S. 80° W.

40.00

Point for cor. secs. 7, 12, 13 and 18, which is monumented with an iron pin firmly set in a mound of small stone.

At the cor. point,

Set an iron post, 28 ins. long, 2½ ins. diam., 22 ins. in the ground, with brass cap mkd.

T1S
R4W R3W
S12 | S 7
S13 | S18
1958

Bury the iron pin alongside the iron post.

Raise a mound of stone, 2½ ft. base, 2 ft. high, W. of cor.

Land, level.

Soil, sandy loam.

Timber, none.

Undergrowth, medium dense salt cedar, willow, palo verde, mesquite and sparse grass.

Dependent Resurvey, Portion of Subdivision, T. 1 S., R. 3 W.

Reestablishment of the survey executed by R. C. Powers in 1883.

From the cor. of secs. 35 and 36, on the S. bdy. of the Tp., which is monumented with a 2 ins. iron post, set, mkd. and witnessed as described in the official record.

N. 0° 28' W., bet. secs. 35 and 36.

Over mountainous land, through scattered undergrowth.

Asc. 63 ft. over S. slope.

16.80

Toe of slope on mountain, bears N. 70° E. and S. 60° W.; asc. 480 ft. over S. slope.

33.20

Slope changes to SW.; asc. 85 ft.

38.00

Spur, projects SW.; desc. 55 ft. over W. slope.

39.82

Point for the ¼ sec. cor. of secs. 35 and 36, at proportionate dist.; no remaining evidence of the original cor.

Dependent Resurvey, Portion of Subdivision, T. 1 S., R. 3 W.

Chains

Set an iron post, 28 ins. long, 2½ ins. diam., 6 ins. in the ground, and in a mound of stone, 4½ ft. base to top, with brass cap mkd.

T1S R3W

S35|S36

1958

From the above cor. U. S. C. and G. S. triangulation station "Mica" bears N. 65° 26' E., 4.86 chs. dist. and is in latitude 33° 17' 52.789" N. and longitude 112° 31' 11.839" W.

Desc. 130 ft. over W. slope.

- 43.00 Spur, slopes W.; desc. 440 ft. over rocky N. slope.
- 64.60 Foot of mountain, bears E. and S. 70° W.; desc. general N. slope.
- 78.10 Wash, 30 lks. wide, 10 ft. deep, drains NE.
- 79.64 The cor. of secs. 25, 26, 35 and 36, which is monumented with a granite stone 17x12x8 ins., mkd. 1 notch on E. and 1 notch on S.

At the cor. point

Set an iron post, 28 ins. long, 2½ ins. diam., 14 ins. in the ground and in a mound of stone to top, with brass cap mkd.

T1S R3W

S26|S25

S35|S36

1958

Place the original cornerstone alongside the iron post.

Land, mountainous.

Soil, sandy and rocky.

Timber, none.

Undergrowth, scattered palo verde, mesquite, cacti and sparse grass.

From the cor. of secs. 25, 30, 31 and 36, on the E. bdy. of the Tp., which is monumented with a 2 ins. iron post, set, mkd. and witnessed as described in the official record.

S. 89° 45' W., bet. secs. 25 and 36.

Over rolling land, through scattered undergrowth.

- 24.30 Track road, bears NNE. and S.
- 25.00 Wash, 40 lks. wide, 2 ft. deep, drains NNE.
- 30.70 Wash, 30 lks. wide, 1 ft. deep, drains NNE.
- 35.20 Wash, 20 lks. wide, 1 ft. deep, drains NNE.
- 40.18 Point for the ¼ sec. cor. of secs. 25 and 36, at proportionate dist.; there is no remaining evidence of the original cor.

Set an iron post, 28 ins. long, 2½ ins. diam., 6 ins. in the ground and in a mound of stone, 3½ ft. base to top, with brass cap mkd.

Dependent Resurvey of a Portion of Subdivision, T. 1 S., R. 3 W.

Chains	
	T1S R3W $\frac{1}{4}$ S25 S36 1958
47.00	Wash, 40 lks. wide, 2 ft. deep, drains NNE.
53.50	Wash, 30 lks. wide, 1 ft. deep, drains NNE.
59.30	Wash, 20 lks. wide, 1 ft. deep, drains NNE.
64.30	Wash, 30 lks. wide, 1 ft. deep, drains N.
69.10	Wash, 40 lks. wide, 2 ft. deep, drains N.
72.70	Wash, 10 lks. wide, 1 ft. deep, drains NNE.
76.40	Wash, 30 lks. wide, 2 ft. deep, drains NNE.
79.50	Wash, 40 lks. wide, 2 ft. deep, drains NNE.
80.36	The cor. of secs. 25, 26, 35 and 36. Land, rolling. Soil, rocky and gravelly. Timber, none. Undergrowth, scattered greasewood, palo verde, mesquite, cacti and sparse grass.
	N. 0° 09' W., bet. secs. 25 and 26. Over rolling land, through scattered undergrowth.
40.24	Point for the $\frac{1}{4}$ sec. cor. of secs. 25 and 26, at proportionate dist.; no remaining evidence of the original cor. Set an iron post, 28 ins. long, 2½ ins. diam., 22 ins. in the ground, with brass cap mkd.
	T1S R3W $\frac{1}{4}$ S26 S25 1958
	Raise a mound of stone, 3 ft. base, 2½ ft. high, W. of cor.
70.30	Wash, 20 lks. wide, 3 ft. deep, drains N. 10° E.
80.10	Track road, bears N. 20° E. and S. 20° W.
80.48	Point for the cor. of secs. 23, 24, 25 and 26, at proportionate dist.; no remaining evidence of the original cor. Set an iron post, 28 ins. long, 2½ ins. diam., 22 ins. in the ground, with brass cap mkd.
	T1S R3W S23 S24 S26 S25 1958

Dependent Resurvey, Portion of the Subdivision, T. 1 S., R. 3 W.

Chains

Raise a mound of stone, 3 ft. base, 2 ft. high, W. of cor.

Land, nearly level.

Soil, sandy and gravelly.

Timber, none.

Undergrowth, scattered mesquite, palo verde, greasewood, cacti and sparse grass.

From the true point for the cor. of secs. 19, 24, 25 and 30, on the E. bdy. of the Tp., whose witness cor. bears N. 0° 03' W., 2.00 chs. dist. and is monumented with a 2½ ins. iron post.

N. 89° 55' W., bet. secs. 24 and 25.

Over slightly rolling land, through scattered undergrowth.

3.00 Wash, drains NNW.

7.50 Track road, bears N. and S.

8.50 Wash, 10 lks. wide, 1 ft. deep, drains N.

11.40 Wash, 20 lks. wide, 2 ft. deep, drains NNE.

31.00 Wash, 30 lks. wide, 2 ft. deep, drains NNE.

40.40 Point for the ¼ sec. cor. of secs. 24 and 25, at proportionate dist.; no remaining evidence of the original cor.

Set an iron post, 28 ins. long, 2½ ins. diam., 22 ins. in the ground, with brass cap mkd.

T1S R3W .

¼ S24
S25
1958

Raise a mound of stone, 3 ft. base, 2 ft. high, N. of cor.

44.20 Wash, 20 lks. wide, 2 ft. deep, drains NNE.

68.50 Track road, bears NNE. and SSW.

71.60 Track road, bears N. and S.

79.00 Wash, 40 lks. wide, 2 ft. deep, drains NNE.

80.60 Track road, bears NNE. and SSW.

80.80 The cor. of secs. 23, 24, 25 and 26.

Land, nearly level.

Soil, sandy and gravelly.

Timber, none.

Undergrowth, scattered mesquite, palo verde, greasewood, cacti and sparse grass.

N. 0° 05' E., bet. secs. 23 and 24.

Over rolling land, through scattered undergrowth.

11.70 Wash, 60 lks. wide, 2 ft. deep, drains N. 30° E.

Dependent Resurvey, Portion of Subdivision, T. 1 S., R. 3 W.

Chains	
21.10	Low spur, slopes N. 30° E.
25.60	Wash, 10 lks. wide, 1 ft. deep, drains N. 30° E.
30.60	Low spur, slopes NE.
32.00	Wash, 20 lks. wide, 2 ft. deep, drains N. 20° E.
40.24	The $\frac{1}{4}$ sec. cor. of secs. 23 and 24, which is monumented with a granite stone, 12x10x7 ins., mkd. $\frac{1}{4}$ on W. face, firmly set in a mound of stone.
	At the cor. point
	Set an iron post, 28 ins. long, 2 $\frac{1}{2}$ ins. diam., 6 ins. in the ground and in a mound of stone, 3 $\frac{1}{2}$ ft. base to top, with brass cap mkd.
	T1S R3W $\frac{1}{4}$ S23 S24 1958
	Bury the original cornerstone alongside the iron post.

	N. 0° 10' E., beginning new measurement.
5.00	Low spur, slopes NE.
26.50	Track road, bears N. 30° W. and S. 30° E.
30.90	Fence, bears N. and W.
39.93	The cor. of secs. 13, 14, 23 and 24, as determined by the center line of a fence line N. and an old fence line E. and W.
	At the cor. point
	Set an iron post, 28 ins. long, 2 $\frac{1}{2}$ ins. diam., 22 ins. in the ground, with brass cap mkd.
	T1S R3W S14 S13 S23 S24 1958
	Raise a mound of stone, 3 ft. base, 2 ft. high, W. of cor.
	Land, nearly level.
	Soil, sandy and gravelly.
	Timber, none.
	Undergrowth, scattered mesquite, palo verde, greasewood, cacti and sparse grass.
	From the cor. of secs. 13, 18, 19 and 24, on the E. bdy. of the Tp., which is monumented with a 2 ins. iron post, set, mkd. and witnessed, as described in the official record.
	N. 89° 46' W., bet. secs. 13 and 24.
14.80	Wash, 20 lks. wide, 2 ft. deep, drains NNW.

Dependent Resurvey, Portion of Subdivision, T. 1 S., R. 3 W.

Chains

33.50

Wash, 3 chs. wide, 3 ft. deep, drains NNW.

40.35

The $\frac{1}{4}$ sec. cor. of secs. 13 and 24, as determined by the remains of an old fence bearing N. and W.

At the cor. point

Set an iron post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 22 ins. in the ground, with brass cap mkd.

T1S R3W

 $\frac{1}{4}$ S13

S24

1958

Raise a small mound of stone N. of cor.

N. $89^{\circ} 46'$ W., beginning new measurement.

Over level land, along S. side of fence line.

40.16

The cor. of secs. 13, 14, 23 and 24.

Land, nearly level.

Soil, sandy and gravelly.

Timber, none.

Undergrowth, scattered mesquite, palo verde, greasewood, cacti and sparse grass.

N. $0^{\circ} 54'$ E., bet. secs. 13 and 14.

Along center of fenced lane, over level ground.

40.26

Point for the $\frac{1}{4}$ sec. cor. of secs. 13 and 14, as determined by the intersection of fenced lanes, N., S., E. and W.

At the cor. point

Set a wooden stub, 2 ins. x 2 ins. x 1 ft. long, 2 ins. below the surface of the ground.

from which

An iron post, 28 ins. long, $2\frac{1}{2}$ ins. diam., set 22 ins. in the ground for reference monument, bears N. 51° E., 54 lks. dist., with brass cap mkd.

T1S R3W

RM $\frac{1}{4}$

S13

1958

With an arrow pointing to the true cor.

An iron post, 28 ins. long, $2\frac{1}{2}$ ins. diam., set 22 ins. in the ground for reference monument, bears S. 51° W., 54 lks. dist., with brass cap mkd.

T1S R3W

 $\frac{1}{4}$ RM

S14

1958

with an arrow pointing to the true cor.

Dependent Resurvey, Portion of Subdivision, T. 1 S., R. 3 W.

Chains

N. 0° 54' E., beginning new measurement.

19.90 End of lane; fence, bears E. and W.; thence across cultivated land.

39.84 The cor. of secs. 11, 12, 13 and 14, as determined by the remains of an old fence E. and W. and the center line of an old lane N. and S., which has been abandoned.

At the cor. point

Set an iron post, 28 ins. long, 2½ ins. diam., 22 ins. in the ground, with brass cap mkd.

T1S R3W

S11 | S12

S14 | S13

1958

Deposit broken glass at the base of the post for witness.

Place a sandstone 2½x2x1½ ft. W. of the cor. for witness.

Land, nearly level.

Soil, sandy loam.

Timber, none.

Undergrowth, none.

From the cor. of secs. 7, 12, 13 and 18, on the E. bdy. of the Tp., which is monumented with a 2 ins. iron post, set, mkd. and witnessed as hereinbefore described.

N. 89° 32' W., bet. secs. 12 and 13.

Along center line of graded road.

6.50 Wash, drains N.

35.10 Intersection of roads bearing N. and S. and E.; enter scattered brush.

38.68 The ¼ sec. cor. of secs. 12 and 13, as determined by an old fence cor. with fences bearing W. and S. This is accepted as the best available evidence of the position of the original ¼ sec. cor.

At the cor. point

Set an iron post, 28 ins. long, 2½ ins. diam., 22 ins. in the ground, with brass cap mkd.

T1S R3W

¼ S12

S13

1958

Raise a mound of stone, 3 ft. base, 2½ ft. high, N. of cor.

N. 89° 32' W., beginning new measurement.

Along old fence line bearing E. and W., with cultivated land on the S. and dense brush on the N.

Dependent Resurvey Portion of Subdivision, T. 1 S., R. 3 W.

Chains	
26.20	Fence cor., bears S. and E.
31.20	Wash, 1 ch. wide, 3 ft. deep, drains N. 20° W.
33.00	Fence, bears S. from E. and W. fence just N. of line.
39.10	Fence, bears S. from same E. and W. fence.
39.41	The cor. of secs. 11, 12, 13 and 14. Land, nearly level. Soil, sandy loam. Timber, none. Undergrowth, none E. $\frac{1}{2}$, dense salt cedar, mesquite and willows on N. side of the line on W. $\frac{1}{2}$.
	From the cor. of secs. 34 and 35, on the S. bdy. of the Tp., which is monumented with a 2 ins. iron post, set, mkd. and witnessed as described in the official record. N. 0° 46' W., bet. secs. 34 and 35. Over rolling land, through scattered undergrowth.
1.10	Wash, 20 lks. wide, 4 ft. deep, drains W.
19.00	Wash, 40 lks. wide, 2 ft. deep, drains N. 30° E.
24.40	Road, bears N. 20° E. and S. 20° W.
40.55	Point for the $\frac{1}{4}$ sec. cor. of secs. 34 and 35, at proportionate dist.; no remaining evidence of the original cor. Set an iron post, 28 ins. long, 2 $\frac{1}{2}$ ins. diam., 22 ins. in the ground, with brass cap mkd. T1S R3W S34 S35 1958
	Raise a mound of stone 3 ft. base, 2 $\frac{1}{2}$ ft. high, W. of cor. Over gently rolling E. slope.
81.10	The cor. of secs. 26, 27, 34 and 35, which is monumented with a small mound of stone. At the cor. point Set an iron post, 28 ins. long, 2 $\frac{1}{2}$ ins. diam., 22 ins. in the ground, with brass cap mkd. T1S R3W S27 S26 S34 S35 1958
	Raise a mound of stone, 3 ft. base, 2 $\frac{1}{2}$ ft. high, W. of cor. Land, rolling. Soil, third rate, gravelly and rocky. Timber, none. Undergrowth, medium greasewood, palo verde, mesquite, cactus, sparse grass.

Dependent Resurvey Portion of Subdivision, T. 1 S., R. 3 W.

Chains	
	From the cor. of 25, 26, 35 and 36. S. 89° 55' W., bet. secs. 26 and 35. Over rolling land, through scattered undergrowth.
3.30	Wash, 30 lks. wide, 2 ft. deep, drains N.
5.80	Wash, 20 lks. wide, 1 ft. deep, drains N.
7.00	Wash, 20 lks. wide, 1 ft. deep, drains N.
11.60	Wash, 30 lks. wide, 1½ ft. deep, drains NNE.
18.60	Wash, 20 lks. wide, 1 ft. deep, drains NNE.
21.20	Wash, 20 lks. wide, 1 ft. deep, drains NNE.
26.90	Wash, 20 lks. wide, 1 ft. deep, drains NNE.
28.40	Wash, 30 lks. wide, 1 ft. deep, drains NNE.
34.10	Wash, 10 lks. wide, 1 ft. deep, drains NNE.
40.46	The ¼ sec. cor. of secs. 26 and 35, which is monumented with a wooden stub set in a small mound of small stones; pits visible E. and W. At the cor. point Set an iron post, 28 ins. long, 2½ ins. diam., 18 ins. in the ground, with brass cap mkd. T1S R3W ¼ $\frac{S26}{S35}$ 1958 Raise a small mound of small stones N. of the iron post. <hr/> N. 87° 57' W., beginning new measurement.
4.80	Wash, 40 lks. wide, 1½ ft. deep, drains NE.
11.80	Road, track, bears NE. and SSW.
40.32	The cor. of secs. 26, 27, 34 and 35. Land, rolling. Soil, gravelly and rocky. Timber, none. Undergrowth, medium greasewood, palo verde, mesquite, cactus and sparse grass.
	N. 0° 55' W., bet. secs. 26 and 27. Asc. over slight S. slope.
7.10	Wash, 20 lks. wide, 1 ft. deep, drains E.
16.30	Wash, 30 lks. wide, 6 ft. deep, drains N. 70° E.
29.00	Track road, bears E. and W.

Dependent Resurvey Portion of Subdivision, T. 1 S., R. 3 W.

Chains

- 33.40 Wash, 30 lks. wide, 2 ft. deep, drains N. 70° E.
- 39.49 The $\frac{1}{4}$ sec. cor. of secs. 26 and 27, which is monumented with a granite stone, 36x30x18 ins., mkd. $\frac{1}{4}$ on W. face.
- At the cor. point
- Set an iron post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 6 ins. in the ground to bedrock, and in a mound of stone, 4 ft. base to top, with brass cap mkd.
- T1S R3W
 $\frac{1}{4}$
 S27 | S26
 1958
- Bury the original cornerstone in a mound alongside the iron post.
-
- N. 0° 13' E., beginning new measurement.
- Asc. 100 ft. over SE. slope.
- 8.30 Spur, slopes E.; desc. 80 ft. over N. slope.
- 12.20 Wash, 30 lks. wide, 10 ft. deep, drains S. 80° E.; asc. 105 ft. over S. slope.
- 20.20 Spur, slopes E.; desc. 105 ft. over N. slope.
- 24.20 Wash, 30 lks. wide, 5 ft. deep, drains N. 60° E. about 2 chs., thence E.; asc. 40 ft. over S. slope.
- 27.90 Spur, slopes N. 70° E.; desc. 30 ft. over N. slope.
- 32.40 Wash, 10 lks. wide, 3 ft. deep, drains N. 60° E.
- 33.00 Wash, 20 lks. wide, 10 ft. deep, drains E.; asc. 40 ft. over S. slope.
- 38.30 Spur, slopes E.
- 38.56 The cor. of secs. 22, 23, 26 and 27, which is monumented with a granite stone 22x10x8 ins., mkd. with 2 notches on the E. and 2 notches on the S.
- At the cor. point
- Set an iron post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 6 ins. in the ground to solid rock, and in a mound of stone, 4 ft. base to top, with brass cap mkd.
- T1S R3W
 S22 | S23
 S27 | S26
 1958
- Place the original cornerstone in a mound alongside the iron post.
- Land, hilly.
 Soil, gravelly and rocky.
 Timber, none.
 Undergrowth, scattered greasewood, palo verde, mesquite, cactus and sparse grass.

Dependent Resurvey Portion of Subdivision, T. 1 S., R. 3 W.

Chains	
	From the cor. of secs. 23, 24, 25 and 26.
	S. 89° 15' W., bet. secs. 23 and 26.
	Over rolling land, through scattered undergrowth.
5.10	Wash, 20 lks. wide, 2 ft. deep, drains N.
34.50	Wash, drains NNE.
38.40	Wash, 20 lks. wide, 2 ft. deep, drains ENE.
40.38	Wash, 40 lks. wide, 2 ft. deep, drains SE.
40.44	Point for the $\frac{1}{4}$ sec. cor. of secs. 23 and 26, at proportionate dist.; no remaining evidence of the original cor.
	Set an iron post, 28 ins. long, 2 $\frac{1}{2}$ ins. diam., 22 ins. in the ground, with brass cap mkd.
	T1S R3W $\frac{1}{4}$ S23 S26 1958
	Raise a mound of stone N. of cor., 2 $\frac{1}{2}$ ft. base, 2 ft. high.
41.10	Wash, 40 lks. wide, 2 ft. deep, drains NE.
50.70	Wash, 40 lks. wide, 2 ft. deep, drains NE.; asc. 100 ft. over SE. slope.
69.10	Spur, slopes S.; desc. 50 ft. over W. slope.
77.20	Wash, 40 lks. wide, 3 ft. deep, drains SE.
80.88	The cor. of secs. 22, 23, 26 and 27.
	Land, rolling.
	Soil, sandy and gravelly.
	Timber, none.
	Undergrowth, mesquite, creosote bush, cactus and sparse grass.
	N. 0° 31' E., bet. secs. 22 and 23.
	Over hilly land, through scattered undergrowth.
2.10	Wash, 20 lks. wide, 10 ft. deep, drains S. 20° E.; asc. 140 ft. over S. slope.
11.20	Spur, bears E.; desc. 110 ft. over N. slope.
19.60	Wash, 10 lks. wide, 5 ft. deep, drains N. 10° E.
26.60	Wash, 20 lks. wide, 10 ft. deep, drains N. 70° W.; asc. 120 ft. over S. slope.
32.00	Spur, slopes S. 70° W.; asc. 20 ft.
34.20	Spur, slopes N. 70° W.; desc. 120 ft. over NW. slope.
40.05	The $\frac{1}{4}$ sec. cor. of secs. 22 and 23, which is monumented with a granite stone 20x10x8 ins. mkd. $\frac{1}{4}$ on W. face, firmly set in a mound of stone.

Dependent Resurvey Portion of Subdivision, T. 1 S., R. 3 W.

Chains

At the cor. point

Set an iron post, 28 ins. long, 2½ ins. diam., 6 ins. in the ground, to solid rock, and in a mound of stone, 4 ft. base to top, with brass cap mkd.

T1S R3W

S22|S23

1958

Place the original cornerstone alongside the iron post in a mound.

N. 1° 58' E., beginning new measurement.

Desc. 70 ft. over N. slope.

12.60 Wash, 40 lks. wide, 15 ft. deep, drains NE.

15.16 Asc. 35 ft. over SE. slope.

15.60 Spur, slopes NE.; desc. over gradual N. slope.

25.30 Wash, 10 lks. wide, 2 ft. deep, drains N. 60° E.

32.00 Low ridge, bears E. and W.; desc. 30 ft. over N. slope.

41.57 The cor. of secs. 14, 15, 22 and 23, which is monumented with a granite stone, 16x12x10 ins., mkd. with 3 notches on the S. and 2 notches on the E., firmly set in a mound of stone.

At the cor. point

Set an iron post, 28 ins. long, 2½ ins. diam., 20 ins. in the ground, with brass cap mkd.

T1S R3W

S15|S14

S22|S23

1958

Bury the original cornerstone alongside the iron post and raise a mound of stone, 3 ft. base, 2½ ft. high, W. of cor.

Land, rolling.

Soil, sandy and gravelly.

Timber, none.

Undergrowth, mesquite, creosote bush, cactus and sparse grass,

From the cor. of secs. 13, 14, 23 and 24.

N. 89° 45' W., bet. secs. 14 and 23.

Over rolling land, through scattered undergrowth.

0.40 Fence, bears N. and S.

3.00 Power line, bears S. to house and E. to cor.

20.00 Fence, bears N. and S.

Dependent Resurvey Portion of Subdivision, T. 1 S., R. 3 W.

Chains	
21.80	Fence, bears ESE. and WNW.
24.70	Wash, 40 lks. wide, 2 ft. deep, drains NW.
34.00	Wash, 30 lks. wide, 2 ft. deep, drains NNE.
39.67	Point for the $\frac{1}{4}$ sec. cor. of secs. 14 and 23, at proportionate dist.; no remaining evidence of the original cor. Set an iron post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 22 ins. in the ground, with brass cap mkd. T1S R3W $\frac{1}{4}$ $\frac{S14}{S23}$ 1958 Raise a mound of stone, $2\frac{1}{2}$ ft. base, 2 ft. high, N. of cor. Asc. over gradual E. slope.
45.30	Wash, 20 lks. wide, 1 ft. deep, drains NNE.
51.00	Wash, 30 lks. wide, 2 ft. deep, drains NNE.
60.70	Wash, 10 lks. wide, 2 ft. deep, drains NNW.
63.40	Wash, 30 lks. wide, 2 ft. deep; drains ENE.
71.70	Top of low ascent, spur, slopes NE.; desc. general NW. slope.
77.70	Wash, 20 lks. wide, 2 ft. deep, drains N.
79.34	The cor. of secs. 14, 15, 22 and 23. Land, rolling. Soil, sandy and gravelly. Timber, none. Undergrowth, mesquite, greasewood, cat claw, cactus.
	N. $0^{\circ} 43'$ E., bet. secs. 14 and 15. Desc. 40 ft. over N. slope, through scattered undergrowth.
14.00	Wash, 20 lks. wide, 2 ft. deep, drains WNW.
14.60	Road, bears E. and W.
20.80	Same wash, 30 lks. wide, 2 ft. deep, drains NE.; asc. 70 ft. over SE. slope.
26.30	Spur, slopes E.; desc. 75 ft. over N. slope.
32.70	Road, bears ENE. and WSW.
33.50	Road, bears E. and W.; wash, 20 lks. wide, 1 ft. deep, drains NNW.
35.60	Fence, bears E. and W.
40.04	The $\frac{1}{4}$ sec. cor. of secs. 14 and 15, which is determined from center line of a lane to the E. and midpoint between an old fence N. and an old fence S. At the cor. point

Dependent Resurvey Portion of Subdivision, T. 1 S., R. 3 W.

Chains

Set an iron post, 28 ins. long, 2½ ins. diam., 22 ins. in the ground, with brass cap mkd.

T1S R3W

¼

S15|S14

1958

Set a wooden post, 6 ft. long, 6 ins. diam., 1 lk. W. of cor. for witness.

N. 0° 04' W, beginning new measurement.

Over nearly level land, through dense brush.

16.00 Gila River, 80 lks. wide, 4 ft. deep, course N. 70° W. about 10 chs., thence S. 80° W.

39.73 Point for the cor. of secs. 10, 11, 14 and 15, which position in latitude is controlled by evidence of an old fence E. and W. and position in longitude by proportionate dist.

Set an iron post, 28 ins. long, 2½ ins. diam., 22 ins. in the ground, with brass cap mkd.

T1S R3W

S10|S11

S15|S14

1958

Set a cedar post, 6 ft. long, 6 ins. diam., 1 lk N. of cor. for witness.

Land, level to rolling.

Soil, third rate S. ½, sandy loam N. ½.

Timber, none.

Undergrowth, mesquite, salt cedar, greasewood, cacti and sparse grass.

From the cor. of secs. 11, 12, 13 and 14.

N. 89° 59' W., bet. secs. 11 and 14.

Over nearly level land, through dense undergrowth.

40.06 Point for the ¼ sec. cor. of secs. 11 and 14, at proportionate dist.; no remaining evidence of the original cor.

Set an iron post, 28 ins. long, 2½ ins. diam., 22 ins. in the ground, with brass cap mkd.

T1S R3W

¼ S11

S14

1958

Raise a mound of stone, 2 ft. base, 1½ ft. high, N. of cor.

47.20 Gila River, 1 ch. wide, 4 ft. deep, drains S. 30° W.

80.12 The cor. of secs. 10, 11, 14 and 15.

Land, nearly level.

Soil, second rate sandy clay.

Timber, none.

Undergrowth, dense salt cedar, mesquite, willows and sparse grass.

Dependent Resurvey Portion of Subdivision, T. 1 S., R. 3 W.

Chains	
	<p>From the cor. of secs. 33 and 34, which is monumented with a 2 ins. iron post, set, mkd. and witnessed as described in the official record.</p> <p>N. 0° 46' W., bet. secs. 33 and 34.</p> <p>Asc. 170 ft. over S. slope, through scattered ocotillo, palo verde, cacti and sparse grass.</p>
15.60	Rocky ridge, bears N. 70° E. and S. 70° W.; desc. 250 ft. over NW. slope.
26.70	Wash, 10 lks. wide, 2 ft. deep, drains W.; asc. 240 ft. over rocky S. slope.
33.70	Spur, slopes W.; desc. 210 ft. over NW. slope.
41.95	<p>The $\frac{1}{4}$ sec. cor. of secs. 33 and 34, which is monumented with a granite stone, 20 x 12 x 8 ins., mkd. $\frac{1}{4}$ on W. face, and firmly set in a mound of stone.</p> <p>At the cor. point,</p> <p>Set an iron post, 28 ins. long, 2$\frac{1}{2}$ ins. diam., 6 ins. in the ground to bedrock, and in a mound of stone 3$\frac{1}{2}$ ft. base to top, with brass cap mkd.</p> <p style="text-align: center;">T1S R3W S33 S34 1958</p> <p>Bury the original cornerstone in the mound of stone alongside the iron post.</p> <p>Desc. 210 ft. over NW. slope.</p> <p>N. 0° 26' E., beginning new measurement.</p> <p>Desc. 150 ft. over NW. slope.</p>
6.90	Wash, 20 lks. wide, 6 ft. deep, drains W.; asc. 20 ft. over S. slope.
9.40	Spur, slopes N. 60° W.; desc. 85 ft. over N. slope.
20.50	Wash, 20 lks. wide, 10 ft. deep, drains NNW.; desc. 40 ft. over broken N. slope.
30.40	Wash, 20 lks. wide, 5 ft. deep, drains NE.
38.92	<p>The cor. of secs. 27, 28, 33 and 34, which is monumented with an old mound of small stones.</p> <p>At the cor. point</p> <p>Set an iron post, 28 ins. long, 2$\frac{1}{2}$ ins. diam., 10 ins. in the ground and in a mound of stone, 3 ft. base to top, with brass cap mkd.</p> <p style="text-align: center;">T1S R3W S28 S27 S33 S34 1958</p> <p>Land, rolling. Soil, third rate sandy and gravelly. Timber, none. Undergrowth, scattered mesquite, greasewood, palo verde, ocotillo and cacti.</p>

Dependent Resurvey Portion of Subdivision, T. 1 S., R. 3 W.

Chains	
	From the cor. of secs. 26, 27, 34 and 35.
	S. 89° 50' W., bet. secs. 27 and 34.
	Asc. 60 ft. over gentle E. slope, through scattered undergrowth.
10.40	Begin steep ascent; asc. 190 ft. over broken E. slope.
17.10	Spur, slopes N. 60° E.; desc. 70 ft. over NW. slope.
32.90	Wash, 10 lks. wide, 3 ft. deep, drains N.
39.68	Point for the $\frac{1}{4}$ sec. cor. of secs. 27 and 34, at proportionate dist.; no remaining evidence of the original cor.
	Set an iron post, 28 ins. long, 2 $\frac{1}{2}$ ins. diam., 6 ins. in the ground to bedrock, and in a mound of stone, 4 ft. base to top, with brass cap mkd.
	T1S R3W
	$\frac{1}{4}$ S27
	S34
	1958
	Asc. 85 ft. over NE. slope.
42.50	Fence, bears N. and S.
49.00	Spur, slopes N. 70° W.; desc. 145 ft. over W. slope.
55.90	Wash, 10 lks. wide, 2 ft. deep, drains N. 70° W.
65.10	Wash, 10 lks. wide, 2 ft. deep, drains N. 80° W.
71.60	Enter wash, course W.
74.60	Leave wash, 10 lks. wide, 1 ft. deep, drains N.
79.36	The cor. of secs. 27, 28, 33 and 34.
	Land, rolling.
	Soil, third rate sandy and gravelly.
	Timber, none.
	Undergrowth, scattered mesquite, greasewood, palo verde, ocotillo and cacti.
	N. 0° 20' W., bet. secs. 27 and 28.
	Over slightly rolling land, through scattered undergrowth.
1.00	Wash, 50 lks. wide, 2 ft. deep, drains N. 60° E.
3.30	Low ridge, bears E. and W.
24.40	Wash, 60 lks. wide, 10 ft. deep, drains westerly.
33.00	Wash, drains SW. from NE.
35.70	Same wash, 20 lks. wide, 10 ft. deep, drains S. 20° E. from N. 20° E.
39.99	Point for the $\frac{1}{4}$ sec. cor. of secs. 27 and 28, at proportionate dist.; no remaining evidence of the original cor.

Dependent Resurvey Portion of Subdivision, T. 1 S., R. 3 W.

Chains

Set an iron post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 22 ins. in the ground, with brass cap mkd.

T1S R3W

 $\frac{1}{4}$

S28 | S27

1958

Raise a mound of stone, $2\frac{1}{2}$ ft. base, 2 ft. high, W. of cor.

41.70 Wash, 10 lks. wide, 3 ft. deep, drains S. 10° E.

46.30 Same wash, drains SW.; asc. 375 ft. over S. slope.

62.90 Spur, slopes SE.;

67.90 Ridge, bears E. and W.; desc. 230 ft. over rocky N. slope.

79.98 Point for the cor. of secs. 21, 22, 27 and 28, at proportionate dist.; no remaining evidence of the original cor.

Set an iron post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 14 ins. in the ground to bedrock, and in a mound of stone $2\frac{1}{2}$ ft. base to top, with brass cap mkd.

T1S R3W

S21 | S22

S28 | S27

1958

Land, mountainous.

Soil, third rate sandy and gravelly.

Timber, none.

Undergrowth, scattered greasewood, palo verde, cacti, mesquite and very sparse grass.

From the cor. of secs. 22, 23, 26 and 27.

N. $88^{\circ} 49'$ W., bet. secs. 22 and 27.

Asc. 145 ft. over SE. slope, through scattered undergrowth.

18.00 Spur, slopes S.; desc. 130 ft. over NW. slope.

28.40 Wash, 50 lks. wide, 3 ft. deep, drains NNE.; asc. 110 ft. over SE. slope.

33.60 Spur, slopes N.

39.71 Point for the $\frac{1}{4}$ sec. cor. of secs. 22 and 27, at proportionate dist.; no remaining evidence of the original cor.

Set an iron post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 6 ins. in the ground to solid rock, and in a mound of stone, $3\frac{1}{2}$ ft. base to top, with brass cap mkd.

T1S R3W

 $\frac{1}{4}$

S22 | S27

1958

Desc. 100 ft. over broken N. slope.

Dependent Resurvey Portion of Subdivision, T. 1 S., R. 3 W.

Chains	
65.50	Fence, bears N. and S.
68.30	Wash, 40 lks. wide, 3 ft. deep, drains NE.; asc. 105 ft. over broken NE. slope.
79.42	The cor. of secs. 21, 22, 27 and 28. Land, mountainous. Soil, third rate sandy and gravelly. Timber, none. Undergrowth, scattered greasewood, palo verde, cacti, mesquite and very sparse grass.
	N. 0° 30' E., bet. secs. 21 and 22. Desc. 190 ft. over broken N. slope, through scattered undergrowth.
17.20	Wash, 20 lks. wide, 4 ft. deep, drains N. 60° W.
22.70	Wash, 30 lks. wide, 10 ft. deep, drains W.; asc. 90 ft. over S. slope.
26.80	Spur, slopes N. 70° W.; desc. 75 ft. over N. slope.
30.60	Wash, 10 lks. wide, 2 ft. deep, drains N. 30° W.; asc. 30 ft. over W. slope.
34.80	Spur, slopes N. 10° W.; desc. 95 ft. over broken N. slope.
39.99	Point for the $\frac{1}{4}$ sec. cor. of secs. 21 and 22, at proportionate dist.; no remaining evidence of the original cor. Set an iron post, 28 ins. long, 2 $\frac{1}{2}$ ins. diam., 10 ins. in the ground to solid rock, and in a mound of stone, 3 ft. base to top, with brass cap mkd. T1S R3W $\frac{1}{4}$ S21 S22 1958
	Over rolling land.
41.70	Wash, 20 lks. wide, 4 ft. deep, drains N. 30° W.
48.50	Wash, 50 lks. wide, 10 ft. deep, drains N. 30° W.
54.40	Wash, 10 lks. wide, 3 ft. deep, drains N. 30° W.
58.20	Low spur, slopes N. 30° W.
64.30	Wash, 20 lks. wide, 4 ft. deep, drains N. 60° W.; asc. 100 ft. over SW. slope.
73.20	Spur, slopes NW.; desc. 80 ft. over NW. slope.
79.98	The cor. of secs. 15, 16, 21 and 22, which is monumented with a sandstone, 18x12x8 ins., mkd. with 3 notches on the S. and 3 notches on the E., firmly set in a mound of stone. At the cor. point

Dependent Resurvey Portion of Subdivision, T. 1 S., R. 3 W.

Chains

Set an iron post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 22 ins. in the ground, with brass cap mkd.

T1S R3W

S16 | S15

S21 | S22

1958

Raise a mound of stone, 3 ft. base, 2 ft. high, W. of cor.; bury the original cornerstone alongside the iron post.

Land, mountainous.

Soil, third rate sandy and gravelly.

Timber, none.

Undergrowth, scattered greasewood, palo verde, cacti, mesquite and very sparse grass.

From the cor. of secs. 14, 15, 22 and 23.

N. $89^{\circ} 48'$ W., bet. secs. 15 and 22.

Over rolling N. slope, through scattered undergrowth.

1.30 Wash, 5 lks. wide, 3 ft. deep, drains N.

9.10 Wash, 5 lks. wide, 3 ft. deep, drains NE.

14.20 Low spur, slopes N.

24.20 Wash, 30 lks. wide, 10 ft. deep, drains N.

25.50 Road, bears N. and S.

27.50 Wash, 10 lks. wide, 1 ft. deep, drains N. 20° E.

29.90 Low spur, slopes N. 30° E.

39.40 Wash, 40 lks. wide, 3 ft. deep, drains N. 70° E.

40.03 The $\frac{1}{4}$ sec. cor. of secs. 15 and 22, which is monumented with a sandstone, 14x10x8 ins., mkd. $\frac{1}{4}$ and firmly set in a mound of stone.

At the cor. point

Set an iron post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 16 ins. in the ground to solid rock, and in a mound of stone, 3 ft. base to top, with brass cap mkd.

T1S R3W

 $\frac{1}{4}$ S15

S22

1958

Bury the original cornerstone alongside the iron post.

N. $89^{\circ} 57'$ W., beginning new measurement.

Asc. 60 ft. over SE. slope.

Dependent Resurvey Portion of Subdivision, T. 1 S., R. 3 W.°

Chains	
9.90	Spur, slopes N. 70° E.; asc. 110 ft. along N. slope.
18.70	Top of ridge bearing N. 80° W. and S. 80° E.; desc. 45 ft. over S. slope.
26.20	Slope changes; desc. 120 ft. over W. slope.
30.00	Wash, 10 lks. wide, 3 ft. deep, drains N.; asc. 20 ft. over NE. slope.
31.60	Spur, slopes N. 30° W.; desc. 30 ft. over NW. slope.
35.70	Wash, 5 lks. wide, 2 ft. deep, drains N. 30° W.; asc. 60 ft. over NE. slope.
40.41	The cor. of secs. 15, 16, 21 and 22. Land, mountainous. Soil, third rate sandy and gravelly. Timber, none. Undergrowth, scattered, greasewood, palo verde, cacti, mesquite and very sparse grass.
	N. 0° 30' E., bet. secs. 15 and 16. Over rolling country, through scattered undergrowth. Desc. 70 ft. over general N. slope.
7.50	Wash, drains NE. from S. 30° E.
13.20	Low spur, slopes NE.; desc. 70 ft. over general N. slope.
39.92	Point for the $\frac{1}{4}$ sec. cor. of secs. 15 and 16, at proportionate dist.; no remaining evidence of the original cor. Set an iron post, 28 ins. long, 2 $\frac{1}{2}$ ins. diam., 22 ins. in the ground, with brass cap mkd. T1S R3W $\frac{1}{4}$ S16 S15 1958
	Raise a mound of stone, 3 ft. base, 2 ft. high, W. of cor.
40.90	Clay bank, 10 ft. high, bears No. 80° E. and S. 80° W.; thence over river bottom through dense brush.
56.70	Gila River, 1 ch. wide, 3 ft. deep, flows N. 80° W. about 5 chs., thence S. 80° W.
79.84	Point for the cor. of secs. 9, 10, 15 and 16, which position is determined for position in latitude by an old road bearing E. and W. and proportioned distance for longitude. Set an iron post, 28 ins. long, 2 $\frac{1}{2}$ ins. diam., 22 ins. in the ground, with brass cap mkd. T1S R3W S 9 S10 S16 S15 1958

Dependent Resurvey Portion of Subdivision, T. 1 S., R. 3 W.

Chains

Raise a mound of stone, 3 ft. base, 2 ft. high, W. of cor.

Land, rolling to level.

Soil, S. $\frac{1}{2}$ third rate, N. $\frac{1}{2}$ second rate

Timber, none.

Undergrowth, S. $\frac{1}{2}$ scattered ocotillo, greasewood and sparse grass;N. $\frac{1}{2}$ dense salt cedar, mesquite, tamarick and very sparse grass.

From the cor. of secs. 10, 11, 14 and 15.

N. 89° 58' W., bet. secs. 10 and 15.

Over nearly level bottom land, through scattered undergrowth.

40.07

Point for the $\frac{1}{4}$ sec. cor. of secs. 10 and 15, at proportionate dist.;
no remaining evidence of the original cor.Set an iron post, 28 ins. long, 2 $\frac{1}{2}$ ins. diam., 22 ins. in the ground,
with brass cap mkd.

T1S R3W

 $\frac{1}{4}$ S10

S15

1958

Set a cedar post, 5 ins. diam., 6 ft. long, 2 ft. in the ground, 1 lk.
N. of the cor.

80.14

The cor. of secs. 9, 10, 15 and 16.

Land, nearly level.

Soil, second class sandy loam.

Timber, none.

Undergrowth, dense salt cedar, mesquite, willows and sparse grass.

From the cor. of secs. 32 and 33, which is monumented with a 2 ins.
iron post, set, mkd. and witnessed as described in the official record.

N. 0° 11' W., bet. secs. 32 and 33.

Asc. 60 ft. over rocky SW. slope, through dense scattered undergrowth.

3.20

Rocky point, slopes W.; desc. 310 ft. over NW. slope.

18.60

Wash, 1 ch. wide, 20 ft. deep, drains W.; asc. 230 ft. over S. slope.

32.00

Spur, slopes W.; desc. 20 ft. over NW. slope.

34.30

Wash, 10 lks. wide, 4 ft. deep, drains W.; asc. 40 ft. over S. slope.

36.00

Spur, slopes N. 60° W.; desc. 120 ft. over rocky N. slope.

40.16

Point for the $\frac{1}{4}$ sec. cor. of secs. 32 and 33, at proportionate dist.;
no remaining evidence of the original cor.Set an iron post, 28 ins. long, 2 $\frac{1}{2}$ ins. diam., 8 ins. in the ground
to bedrock, and in a mound of stone, 3 $\frac{1}{2}$ ft. base to top, with brass
cap mkd.

T1S R3W

 $\frac{1}{4}$

S32 | S33

1958

Dependent Resurvey Portion of Subdivision, T. 1 S., R. 3 W.

Chains	
	Desc. 100 ft. over NW. slope.
42.90	Wash, 10 lks. wide, 3 ft. deep, drains NW.
49.40	Wash, 30 lks. wide, 10 ft. deep, drains NW.
51.90	Wash, 20 lks. wide, 6 ft. deep, drains N. 70° W.; asc. 40 ft. over S. slope.
55.20	Spur, slopes N. 80° W.; desc. 55 ft. over N. slope.
59.20	Wash, 10 lks. wide, 3 ft. deep, drains NW.
71.00	Wash, 20 lks. wide, 4 ft. deep, drains N. 70° W.
78.00	Wash, 10 lks. wide, 5 ft. deep, drains W.
80.32	Point for the cor. of secs. 28, 29, 32 and 33, at proportionate dist.; no remaining evidence of the original cor. Set an iron post, 28 ins. long, 2½ ins. diam., 16 ins. in the ground to solid rock, and in a mound of stone, 3 ft. base to top, with brass cap mkd. <div style="text-align: center;"> T1S R3W S29 S28 S32 S33 1958 </div>
	Land, mountainous. Soil, third rate sandy and gravelly. Timber, none. Undergrowth, scattered greasewood, ocotillo, cacti, mesquite, palo verde and sparse grass.
	From the cor. of secs. 27, 28, 33 and 34. S. 89° 41' W., bet. secs. 28 and 33. Over mountainous land, through scattered undergrowth.
.60	Wash, 40 lks. wide, 10 ft. deep, drains NE.; asc. 135 ft. over SE. slope.
13.50	Ridge, bears N. 70° E. and SW.
14.50	Spur, slopes N. 10° W.; desc. 140 ft. over W. slope.
23.30	Wash, 10 lks. wide, 2 ft. deep, drains N. 60° W.
40.17	Point for the ¼ sec. cor. of secs. 28 and 33, at proportionate dist.; no remaining evidence of the original cor. Set an iron post, 28 ins. long, 2½ ins. diam., 22 ins. in the ground with brass cap mkd. <div style="text-align: center;"> T1S R3W ¼ S28 S33 1958 </div>
	Raise a mound of stone 3 ft. base, 2 ft. high, N. of cor.

Dependent Resurvey Portion of Subdivision, T. 1 S., R. 3 W.

Chains	
	Over broken N. slope.
40.90	Wash, 10 lks. wide, 2 ft. deep, drains N.
48.60	Wash, 20 lks. wide, 4 ft. deep, drains N.
52.00	Low spur, slopes N. 10° E.
56.50	Wash, 10 lks. wide, 2 ft. deep, drains N. 70° W.
67.30	Wash, 40 lks. wide, 10 ft. deep, drains N. 70° W.
80.34	The cor. of secs. 28, 29, 32 and 33.
	Land, mountainous. Soil, third rate sandy and gravelly. Timber, none. Undergrowth, scattered greasewood, ocotillo, cacti, mesquite, palo verde and sparse grass.
	N. 0° 14' E., bet. secs. 28 and 29.
	Over medium high rolling land, through scattered undergrowth.
4.70	Spur, slopes N. 70° W.
11.10	Wash, 50 lks. wide, 15 ft. deep, drains NW.
18.30	Road, bears N. 70° W. and S. 70° E.
19.60	Wash, 20 lks. wide, 3 ft. deep, drains N. 70° W.
26.50	Spur, slopes N. 80° W.;
30.90	Road, bears E. and W.
32.40	Wash, 40 lks. wide, 3 ft. deep, drains NW.
40.16	Point for the $\frac{1}{4}$ sec. cor. of secs. 28 and 29, at proportionate dist.; no remaining evidence of the original cor. Set an iron post, 28 ins. long, 2½ ins. diam., 4 ins. in the ground to bedrock, and in a mound of stone, 4 ft. base to top, with brass cap mkd.
	T1S R3W $\frac{1}{4}$ S29 S28 1958
41.10	Wash, 20 lks. wide, 5 ft. deep, drains S.
43.80	Spur, slopes SW.
49.90	Wash, 10 lks. wide, 2 ft. deep, drains S. 10° W.
51.80	Spur, slopes W.
56.60	Wash, 10 lks. wide, 4 ft. deep, drains W.
56.90	Ridge, bears NW. and SE.
68.00	Wash, 20 lks. wide, 6 ft. deep, drains W.

Dependent Resurvey Portion of Subdivision, T. 1 S., R. 3 W.

Chains	
69.80	Wash, 40 lks. wide, 15 ft. deep, drains N. 60° W.
73.70	Spur, slopes N. 60° W.
80.32	Point for the cor. of secs. 20, 21, 28 and 29, at proportionate dist.; no remaining evidence of the original cor. Set an iron post, 28 ins. long, 2½ ins. diam., 22 ins. in the ground, with brass cap mkd. <div style="text-align: center;"> T1S R3W S20 S21 S29 S28 1958 </div>
	Raise a mound of stone, 3 ft. base, 2 ft. high, W. of cor. Land, high and rolling. Soil, third rate sandy and gravelly. Timber, none. Undergrowth, scattered ocotillo, cat claw, greasewood, palo verde.
	From the cor. of secs. 21, 22, 27 and 28. S. 89° 57' W., bet. secs. 21 and 28. Over high rolling land, through scattered undergrowth.
.50	Wash, 30 lks. wide, 2½ ft. deep, drains N.
12.00	Wash, 30 lks. wide, 2 ft. deep, drains N.; asc. 40 ft. over E. slope.
23.10	Spur, slopes N.; desc. 120 ft. over NW. slope.
28.00	Wash, 30 lks. wide, 2 ft. deep, drains NNW.; asc. 140 ft. over SE. slope.
34.30	Spur, slopes N.; desc. 85 ft. over W. slope.
39.71	Point for the ¼ sec. cor. of secs. 21 and 28, at proportionate dist.; no remaining evidence of the original cor. Set an iron post, 28 ins. long, 2½ ins. diam., 4 ins. in the ground to bedrock, and in a mound of stone, 5 ft. base to top, with brass cap mkd. <div style="text-align: center;"> T1S R3W ¼ S21 S28 1958 </div>
	Desc. 130 ft. over W. slope.
48.60	Wash, 20 lks. wide, 1 ft. deep, drains NW.
51.80	Wash, 50 lks. wide, 2 ft. deep, drains NNW.; asc. 85 ft. over E. slope.
59.50	Ridge, bears N. and S.; desc. 160 ft. over WNW. slope.
76.10	Wash, 20 lks. wide, 1 ft. deep, drains WNW.

Dependent Resurvey Portion of Subdivision, T. 1 S., R. 3 W.

Chains 79.42	<p>The cor. of secs. 20, 21, 28 and 29.</p> <p>Land, high and rolling. Soil, third rate sandy and gravelly. Timber, none. Undergrowth, scattered ocotillo, cat claw, greasewood and palo verde.</p>
	<p>N. 0° 24' W., bet. secs. 20 and 21.</p> <p>Over rolling land, through scattered undergrowth.</p>
2.20	Wash, 30 lks. wide, 4 ft. deep, drains N. 60° W.
5.60	Spur, slopes NW.
13.00	Wash, 20 lks. wide, 3 ft. deep, drains N. 80° W. about 2 chs., thence N. 30° W.
36.10	Wash, 20 lks. wide, 2 ft. deep, drains NW.
40.16	<p>The $\frac{1}{4}$ sec. cor. of secs. 20 and 21, which is monumented with a granite stone, 20x16x12 ins., mkd. $\frac{1}{4}$ on W. face, firmly set in a mound of stone.</p> <p>At the cor. point</p> <p>Set an iron post, 28 ins. long, 2$\frac{1}{2}$ ins. diam., 22 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T1S R3W $\frac{1}{4}$ S20 S21 1958</p> <p>Raise a mound of stone, 3 ft. base, 2 ft. high, W. of cor.; bury the original cornerstone alongside the iron post.</p>
	<p>N. 0° 22' E., beginning new measurement.</p>
2.50	Wash, 10 lks. wide, 2 ft. deep, drains N. 70° W.
6.70	Road, bears N. 70° W. and S. 70° E.
21.60	Road, bears SE. and W.
40.09	<p>The cor. of secs. 16, 17, 20 and 21, which is monumented with a granite stone, 16x12x5 ins., dimly mkd. and firmly set in a mound of stone.</p> <p>At the cor. point</p> <p>Set an iron post, 28 ins. long, 2$\frac{1}{2}$ ins. diam., 22 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T1S R3W S17 S16 S20 S21 1958</p> <p>Raise a mound of stone, 3 ft. base, 2 ft. high, W. of cor.; bury the original cornerstone alongside the iron post.</p>

Dependent Resurvey Portion of Subdivision, T. 1 S., R. 3 W.

Chains	
	<p>Land, rolling. Soil, third rate sandy and gravelly. Timber, none. Undergrowth, scattered ocotillo, mesquite, palo verde, cacti and sparse grass.</p>
	<p>From the cor. of secs. 15, 16, 21 and 22. N. 89° 47' W., bet. secs. 16 and 21. Over rolling land, through scattered undergrowth. Asc. 30 ft. over NE. slope.</p>
3.80	Ridge, bears S. 70° E. and N. 70° W., thence along S. slope.
12.80	Slope changes; desc. 110 ft. over SW. slope.
20.00	Wash, 40 lks. wide, 10 ft. deep, drains NW.
25.70	Road, bears NW. and SE.
36.60	Wash, 10 lks. wide, 2 ft. deep, drains N. 60° W.
37.30	Wash, 50 lks. wide, 10 ft. deep, drains N. 30° W.
40.09	Point for the $\frac{1}{4}$ sec. cor. of secs. 16 and 21; at proportionate dist.; no remaining evidence of the original cor. Set an iron post, 28 ins. long, 2 $\frac{1}{2}$ ins. diam., 22 ins. in the ground, with brass cap mkd.
	<p>T1S R3W $\frac{1}{4}$ $\frac{S16}{S21}$ 1958</p>
	Raise a mound of stone, 3 ft. base, 2 ft. high, N. of cor.
	From above cor. point U.S.C.&G.S. triangulation station "Buckeye" bears S. 7° 28' W., 36.45 chs. dist. Said station is in latitude 33° 19' 39.127" N. and longitude 112° 33' 54.676" W.
41.40	Low spur, slopes N. 30° W.
46.70	Wash, 10 lks. wide, 6 ft. deep, drains N. 1 ch, thence NW.
53.90	Wash, 30 lks. wide, 10 ft. deep, drains N. 20° W.
55.60	Low spur, slopes N.
59.10	Wash, 20 lks. wide, 10 ft. deep, drains N. 30° E.
64.60	Spur, slopes N. 20° E.
69.40	Road, bears N. and S.
72.70	Wash, 50 lks. wide, 10 ft. deep, drains N. 20° E.
80.18	The cor. of 16, 17, 20 and 21. Land, rolling. Soil, third rate sandy and gravelly. Timber, none. Undergrowth, scattered ocotillo, mesquite, palo verde, cacti and sparse grass.

Dependent Resurvey Portion of Subdivision, T. 1 S., R. 3 W.

Chains	
	N. 0° 27' E., bet. secs. 16 and 17.
	Over nearly level land, through scattered undergrowth.
10.00	Clay bank, 40 ft. high, bears E. and W.; cont. over nearly level land through dense brush and river bottom.
40.09	Point for the $\frac{1}{4}$ sec. cor. of secs. 16 and 17, at proportionate dist.; no remaining evidence of the original cor.
	Set an iron post, 28 ins. long, 2 $\frac{1}{2}$ ins. diam., 22 ins. in the ground, with brass cap mkd.
	<p style="text-align: center;">T1S R3W $\frac{1}{4}$ S17 S16 1958</p>
	Set a cedar post, 4 ins. diam., 5 ft. long, 2 ft. in ground, 1 lk. W. of cor. for witness.
	Cont. over river bottom land, through dense brush.
60.40	Gila River, 80 lks. wide, 3 ft. deep, drains W.
80.18	The cor. of secs. 8, 9, 16 and 17, which is monumented with a deteriorated stake, in a mound of stone, with pits visible in the SE. and SW. cors.
	At the cor. point
	Set an iron post, 28 ins. long, 2 $\frac{1}{2}$ ins. diam., 22 ins. in the ground with brass cap mkd.
	<p style="text-align: center;">T1S R3W S8 S9 S17 S16 1958</p>
	Deposit a sandstone 4x3x2 ins., mkd. with a cross (X) at the base of the post for witness.
	Land, nearly level.
	Soil, second rate sandy loam, mixed with clay.
	Timber, none.
	Undergrowth, dense salt cedar, willows, scattered mesquite, and sparse grass.
	From the cor. of secs. 9, 10, 15 and 16.
	N. 89° 30' W., bet. secs. 9 and 16.
	Over nearly level bottom land; through scattered undergrowth.
10.20	Fence, bears N. and S., thence along S. side of track road.
40.11	Point for the $\frac{1}{4}$ sec. cor. of secs. 9 and 16, at proportionate dist.; no remaining evidence of the original cor.
	Set an iron post, 28 ins. long, 2 $\frac{1}{2}$ ins. diam., 22 ins. in the ground, with brass cap mkd.

Dependent Resurvey Portion of Subdivision, T. 1 S., R. 3 W.

Chains

T1S R3W

 $\frac{1}{4}$ $\frac{S 9}{S16}$

1958

Raise a mound of stone, 3 ft. base, 2 ft. high, N. of cor. for witness.

80.00

Road, bears N. and S.

80.22

The cor. of secs. 8, 9, 16 and 17.

Land, nearly level.

Soil, second rate sandy clay.

Timber, none.

Undergrowth, scattered salt cedar, mesquite, willows and sparse grass.

From the cor. of secs. 31 and 32, which is monumented with a 2 ins. iron post, set, mkd. and witnessed as described in the official record.

N. 0° 20' W., bet. secs. 31 and 32.

Over rolling land, through scattered undergrowth.

3.10

Wash, 10 lks. wide, 2 ft. deep, drains W.

13.50

Wash, 20 lks. wide, 2 ft. deep, drains N. 30° W.

18.50

Wash, 10 lks. wide, 3 ft. deep, drains NW.

28.10

Wash, 20 lks. wide, 3 ft. deep, drains S. 70° W.

39.81

Point for the $\frac{1}{4}$ sec. cor. of secs. 31 and 32, at proportionate dist.; no remaining evidence of the original cor.

Set an iron post, 28 ins. long, 2½ ins. diam., 22 ins. in the ground, with brass cap mkd.

T1S R3W

 $\frac{1}{4}$ $\frac{S31|S32}{S16}$

1958

Raise a mound of stone, 3 ft. base, 2 ft. high, W. of cor. for witness.

46.40

Wash, 20 lks. wide, 4 ft. deep, drains N. 70° W.

74.90

Wash, 40 lks. wide, 6 ft. deep, drains N. 70° W.

79.62

The cor. of secs. 29, 30, 31 and 32, which is monumented with a sandstone, 22x11x8 ins., dimly mkd. and firmly set in a mound of stone.

At the cor. point

Set an iron post, 28 ins. long, 2½ ins. diam., 22 ins. in the ground, with brass cap mkd.

T1S R3W

 $\frac{S30|S29}{S31|S32}$

1958

Dependent Resurvey Portion of Subdivision, T. 1 S., R. 3 W.

Chains	
	<p>Raise a mound of stone, 3 ft. base, 2 ft. high, W. of cor.; bury the original cornerstone alongside the iron post.</p> <p>Land, rolling. Soil, third rate sandy and gravelly. Timber, none. Undergrowth, scattered ocotillo, palo verde, mesquite, greasewood and sparse grass.</p>
	<p>From the cor. of secs. 28, 29, 32 and 33. S. 89° 34' W., bet. secs. 29 and 32. Over rollingland, through scattered undergrowth.</p>
33.60	<p>Road, bears NE. and SW. about 5 chs., thence S.</p>
40.17	<p>Point for the $\frac{1}{4}$ sec. cor. of secs. 29 and 32, at proportionate dist.; no remaining evidence of the original cor.</p> <p>Set an iron post, 28 ins. long, 2½ ins. diam., 22 ins. in the ground, with brass cap mkd.</p>
	<p style="text-align: center;">T1S R3W $\frac{1}{4}$ S29 S32 1958</p>
	<p>Raise a mound of stone, 2½ ft. high, 2 ft. high, N. of cor. for witness.</p>
42.60	<p>Wash, 40 lks. wide, 10 ft. deep, drains N.</p>
51.70	<p>Wash, 10 lks. wide, 4 ft. deep, drains N.; asc. 80 ft. over SE. slope.</p>
62.20	<p>Ridge, bears NE. and SW.; desc. 80 ft. over NW. slope.</p>
77.60	<p>Spur, slopes N. 70° W.; desc. 10 ft. to cor.</p>
80.34	<p>The cor. of secs. 29, 30, 31 and 32.</p> <p>Land, rolling. Soil, third rate sandy and gravelly. Timber, none. Undergrowth, scattered ocotillo, palo verde, mesquite, greasewood and sparse grass.</p>
16.10	<p>N. 89° 34' W., bet. secs. 30 and 31. Wash, 10 lks. wide, 2 ft. deep, drains N.</p>
20.40	<p>Wash, 30 lks. wide, 3 ft. deep, drains N. 10° E.</p>
40.86	<p>Point for the $\frac{1}{4}$ sec. cor. of secs. 30 and 31, at proportionate dist.; no remaining evidence of the original cor.</p> <p>Set an iron post, 28 ins. long, 2½ ins. diam., 22 ins. in the ground, with brass cap mkd.</p>

Dependent Resurvey Portion of Subdivision, T. 1 S., R. 3 W.

Chains

T1S R3W

S30

S31

1958

Raise a mound of stone, 3 ft. base, 2 ft. high, N. of cor.

43.30 Road, bears N. 20° W. and S. 20° E.

59.25 Wash, drains NW.

68.20 Wash, 5 lks. wide, 1 ft. deep, drains N.

74.10 Road, bears S. 10° W. and N. 10° E.

74.30 Telephone line, bears S. 10° W. and N. 10° E.

78.20 Wash, 1 ch. wide, 2 ft. deep, drains N.

79.50 The cor. of secs. 25, 30, 31 and 36, which is monumented with a 2½ ins. iron post, hereinbefore described.

Land, rolling.

Soil, third rate sandy and gravelly.

Timber, none.

Undergrowth, scattered ocotillo, palo verde, mesquite, greasewood and sparse grass.

From the cor. of secs, 29, 30, 31 and 32.

N. 0° 23' E., bet. secs. 29 and 30.

Asc. over rolling S. slope.

14.40 Gulch, 1 ch. wide, 30 ft. deep, drains W.

21.30 Wash, 10 lks. wide, 3 ft. deep, drains SW.

35.10 Low ridge, bears S. 80° E. and NW.; desc. over rolling N. slope.

40.46 The ¼ sec. cor. of secs. 29 and 30, which is monumented with a sandstone, 14x12x10 ins., mkd. ¼ on W. face and firmly set in a mound of stone.

At the cor. point

Set an iron post, 28 ins. long, 2½ ins. diam., 2 ins. in the ground to bedrock, and in a mound of stone, 4 ft. base to top, with brass cap mkd.

T1S R3W

S30

S29

1958

Bury the original cor. in the mound alongside the iron post.

From above cor. point cor. No. 3 of Jabon mining claim, Mineral Survey No. 4133, bears N. 8° 51' W., 8.93 chs. dist.

N. 0° 04' W., beginning new measurement.

1.60 Wash, 10 lks. wide, 5 ft. deep, drains NW.

3.10 Same wash, drains NE.

Dependent Resurvey Portion of Subdivision, T. 1 S., R. 3 W.

Chains 18.50	Low ridge, bears N. 30° W. and SSE.; desc. along N. slope.
40.50	The cor. of secs. 19, 20, 29 and 30, which is monumented with a granite stone, 18x12x8 ins., mkd. with 5 notches on E. face and 2 notches on the S. At the cor. point Set an iron post, 28 ins. long, 2½ ins. diam., 6 ins. in the ground to bedrock, and in a mound of stone, 4 ft. base to top, with brass cap mkd. T1S R3W S19 S20 S30 S29 1958 Bury the original cornerstone in the mound alongside the iron post. From above cor. point Cor. No. 1 of the Jabon mining claim, Mineral Survey No. 4133, bears S. 3° 18' E., 7.57 chs. dist. Land, rolling. Soil, third rate sandy and gravelly. Timber, none. Undergrowth, scattered ocotillo, palo verde, mesquite, greasewood and sparse grass.
13.60	From the cor. of secs. 20, 21, 28 and 29. West of betw. secs. 20 and 29. Over rolling land, through scattered undergrowth. Wash, 30 lks. wide, 2 ft. deep, drains WNW.
15.60	Road, bears NNE. and SSE.
21.80	Wash, 30 lks. wide, 2 ft. deep, drains NNE.
22.90	Road, bears N. and S.
27.20	Wash, 30 lks. wide, 2 ft. deep, drains NNE.
38.40	Wash, 20 lks. wide, 2 ft. deep, drains N.
39.68	The ¼ sec. cor. of secs. 20 and 29, which is monumented with a granite stone, 20x10x4 ins., mkd. ¼ on N. face, firmly set in a mound of stone. At the cor. point Set an iron post, 28 ins. long, 2½ ins. diam., 16 ins. in the ground and in a mound of stone to top, with brass cap mkd. T1S R3W S20 ¼ S29 1958 Bury the original cornerstone in the mound alongside the iron post.

Dependent Resurvey of Portion of Subdivision, T. 1 S., R. 3 W.

Chains	
	S. 89° 59' W., beginning new measurement.
	Asc. 65 ft. over SE. slope of spur.
3.50	Spur, slopes SSE.; desc. 120 ft. over WSW. slope.
14.30	Road, bears NNW. and SSE.
16.00	Wash, 40 lks. wide, 2 ft. deep, drains NNW.
25.30	Wash, 20 lks. wide, 2 ft. deep, drains WNW.
33.20	Wash, 20 lks. wide, 2 ft. deep, drains NNW.
40.20	Wash, 30 lks. wide, 2 ft. deep, drains NNW.
40.70	The cor. of secs. 19, 20, 29 and 30.
	Land, rolling.
	Soil, third rate sandy and gravelly.
	Timber, none.
	Undergrowth, scattered ocotillo, palo verde, mesquite, greasewood and sparse grass.
	S. 89° 47' W., bet. secs. 19 and 30.
	Over rolling land, through scattered undergrowth.
2.40	Wash, 10 lks. wide, 2 ft. deep, drains NNE.; asc. 60 ft. over E. slope.
8.20	Spur, slopes NNE.; desc. 40 ft. over NW. slope.
11.00	Wash, 10 lks. wide, 2 ft. deep, drains NNW.
29.40	Wash, 20 lks. wide, 2 ft. deep, drains NW.
41.04	Point for the $\frac{1}{4}$ sec. cor. of secs. 19 and 30, at proportionate dist.; no remaining evidence of the original cor.
	Set an iron post, 28 ins. long, 2 $\frac{1}{2}$ ins. diam., 22 ins. in the ground, with brass cap mkd.
	T1S R3W
	$\frac{1}{4}$ <u>S19</u>
	<u>S30</u>
	1958
	Raise a mound of stone, 3 ft. base, 2 ft. high, N. of cor.
43.00	Wash, 20 lks. wide, 1 ft. deep, drains N.
45.50	Wash, 10 lks. wide, 1 ft. deep, drains N.
56.10	Wash, 20 lks. wide, 1 ft. deep, drains N.
63.20	Road, bears NNE. and SSW.
64.40	Wash, 40 lks. wide, 1 ft. deep, drains NNE.
72.40	Wash, 20 lks. wide, 1 ft. deep, drains N.
79.20	Road, bears N. and S.

Dependent Resurvey Portion of Subdivision, T. 1 S., R. 3 W.

Chains	
79.40	Power line, bears N. and SSE.
79.83	The cor. of secs. 19, 24, 25 and 30, which is monumented with a 2½ ins. iron post, hereinbefore described. Land, rolling. Soil, third rate sandy and gravelly. Timber, none. Undergrowth, scattered ocotillo, palo verde, mesquite, greasewood, and sparse grass.
	From the cor. of secs. 19, 20, 29 and 30. N. 0° 32' E., bet. secs. 19 and 20. Over rolling land, through scattered undergrowth.
3.10	Wash, 30 lks. wide, 2 ft. deep, drains N. 30° W.
8.70	Low spur, slopes N. 30° W.
11.40	Wash, 20 lks. wide, 1 ft. deep, drains NW.
21.60	Low spur, slopes NW.
29.10	Wash, 20 lks. wide, 5 ft. deep, drains N. 30° W.
33.90	Spur, slopes N. 30° W.
40.62	The ¼ sec. cor. of secs. 19 and 20, which is monumented with a sandstone, 26x12x12 ins., mkd. ¼ on W. face, firmly set. At the cor. point. Set an iron post, 28 ins. long, 2½ ins. diam., 2 ins. in the ground to solid rock, and in a mound of stone, 4 ft. base to top, with brass cap mkd. T1S R3W S19 S20 1958. Place the original cor. alongside the iron post in a mound of stone. N. 0° 28' E., beginning new measurement.
11.30	Wash, 20 lks. wide, 2 ft. deep, drains NW.
18.90	Fence, bears W. and E. 80 lks. to fence N. and S.
26.90	Wash, 20 lks. wide, 1 ft. deep, drains NW.
34.60	Road, bears N. 30° E. and S. 30° W.
35.40	Fence, bears N. 30° E. and S. 30° W.
39.90	The cor. of secs. 17, 18, 19 and 20, which is monumented with a granite stone, 16x10x8 ins. dimly mkd. and firmly set in the ground. At the cor. point

Dependent Resurvey Portion of Subdivision, T. 1 S., R. 3 W.

Chains

Set an iron post, 28, ins. long, 2½ ins. diam., 22 ins. in the ground, with brass cap mkd.

TLS R3W

S18 | S17

S19 | S20

1958

Raise a mound of stone, 3 ft. base, 2 ft. high, W. of cor.; bury the original cornerstone alongside the iron post.

Land, rolling.

Soil, third rate sandy and gravelly.

Timber, none.

Undergrowth, scattered ocotillo, palo verde, mesquite, greasewood and sparse grass.

From the cor. of secs. 16, 17, 20 and 21.

N. 89° 32' W., bet. secs. 17 and 20.

Over rolling land, through scattered undergrowth.

1.80 Low spur, slopes N.

2.70 Wash, 10 lks. wide, 5 ft. deep, drains N. 10° E.

11.90 Wash, 20 lks. wide, 10 ft. deep, drains N. 20° E.

17.50 Wash, 20 lks. wide, 10 ft. deep, drains N. 20° E.

28.70 Road, bears NW. and SE.

39.79 The ¼ sec. cor. of secs. 17 and 20, which is monumented with a granite stone, 20x10x8 ins., mkd. ¼ on N. face, firmly set.

At the cor. point

Set an iron post, 28 ins. long, 2½ ins. diam., 22 ins. in the ground, with brass cap mkd.

TLS R3W

¼ S17

S20

1958

Raise a mound of stone, 3 ft. base, 2 ft. high, N. of cor.; bury the original cornerstone alongside the iron post.

N. 89° 58' W., beginning new measurement.

4.00 Wash, 30 ft. wide, 2 ft. deep, drains NW.

17.20 Low spur, slopes NW.

23.70 Wash, 10 lks. wide, 3 ft. deep, drains NW.

31.40 Wash, 60 lks. wide, 4 ft. deep, drains N. 20° E.

32.50 Road, bears N. 10° E. about 3 chs. then joins with road from W.

36.20 Wash, 80 lks. wide, 4 ft. deep, drains N. 30° W.

39.00 Road, bears S. 30° W. and N. 80° E.

Dependent Resurvey Portion of Subdivision, T. 1 S., R. 3 W.

Chains	
39.85	<p>The cor. of secs. 17, 18, 19 and 20.</p> <p>Land, rolling. Soil, third rate sandy and gravelly. Timber, none. Undergrowth, scattered ocotillo, palo verde, mesquite, greasewood and sparse grass.</p>
11.30	<p>S. 89° 11' W., bet. secs. 18 and 19.</p> <p>Over nearly level land, through scattered undergrowth.</p> <p>Flood dike, bears N. 30° E. and S. 30° W.</p>
11.90	<p>Drainage ditch, drains N. 30° E.</p>
41.24	<p>Point for the $\frac{1}{4}$ sec. cor. of secs. 18 and 19, at proportionate dist.; no remaining evidence of the original cor.</p> <p>Set an iron post, 28 ins. long, 2$\frac{1}{2}$ ins. diam., 22 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T1S R3W $\frac{1}{4}$ S18 S19 1958</p>
77.40	<p>Deposit broken glass at the base of the post for witness.</p> <p>Set a cedar post, 6 ins. diam., 6 ft. long, 2 ft. in the ground, 1 lk. N. of the cor.</p> <p>Enter medium willows and salt cedar bearing NE. and SW.</p>
79.60	<p>Power line, bears N. and S.</p>
80.21	<p>The cor. of secs. 13, 18, 19 and 24, which is monumented with a 2$\frac{1}{2}$ ins. iron post hereinbefore described.</p> <p>Land, nearly level. Soil, second rate sandy clay. Timber, none. Undergrowth, some salt cedar, willows, greasewood and sparse grass.</p>
39.84	<p>From the cor. of secs. 17, 18, 19 and 20.</p> <p>N. 0° 01' W., bet. secs. 17 and 18.</p> <p>Over nearly level river bottom, through medium dense undergrowth.</p> <p>Point for the $\frac{1}{4}$ sec. cor. of secs. 17 and 18, at proportionate dist.; no remaining evidence of the original cor.</p> <p>Set an iron post, 28 ins. long, 2$\frac{1}{2}$ ins. diam., 22 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T1S R3W $\frac{1}{4}$ S18 S17 1958</p> <p>Set a cedar post, 5 ins. diam., 7 ft. long, 2 ft. in the ground, 1 lk. N. of iron post for witness.</p>

Dependent Resurvey Portion of Subdivision, T. 1 S., R. 3 W.

Chains

- 60.30 Gila River, 80 lks. wide, 2 ft. deep, course S. 60° W.
- 79.68 The cor. of secs. 7, 8, 17 and 18, which position is determined by the center line of a graded road N. and S. and an old fence cor. W. and an old fence cor. E.
- At the cor. point
- Bury an oak stub, 10 ins. long, 1 in. square, flush with the ground; from which
- An iron post, 28 ins. long, 2½ ins. diam., set 22 ins. in the ground for reference monument, bears N. 61° 56' W., 41 lks. dist. with brass cap mkd. T1S R3W S7 RM 1958, with an arrow pointing towards the true cor.
- An iron post, 28 ins. long, 2½ ins. diam., set 22 ins. in the ground for reference monument, bears S. 61° 56' E., 41 lks. dist. with brass cap mkd. T1S R3W S17 RM 1958, with an arrow pointing to the true cor.
- Land, nearly level.
Soil, second rate sandy clay.
Timber, none.
Undergrowth, medium dense willows, salt cedar, scattered mesquite and sparse grass.
-
- From the cor. of secs. 8, 9, 16 and 17.
S. 89° 53' W., bet. secs. 8 and 17.
- Over nearly level land, through scattered undergrowth.
- 30.30 Irrigation ditch, flows NW. for 5 chs., thence W.
- 40.11 Point for the ¼ sec. cor. of secs. 8 and 17, at proportionate dist.; no remaining evidence of the original cor.
- Set an iron post, 28 ins. long, 2½ ins. diam., 22 ins. in the ground, with brass cap mkd.
- T1S R3W
¼ S 8
S17
1958
- Raise a mound of stone, 3 ft. base, 2 ft. high, N. of cor.
- 79.80 Power line, bears N. and S.
- 80.22 The cor. of secs. 7, 8, 17 and 18.
- Land, nearly level.
Soil, second rate sandy clay.
Timber, none.
Undergrowth, medium dense willows, salt cedar, scattered mesquite and sparse grass.
-
- S. 89° 19' W., bet. secs. 7 and 18.
- Over nearly level land, through medium dense undergrowth.

Dependent Resurvey Portion of the Subdivision, T. 1 S., R. 3 W.

Chains
41.21

Point for the 1/4 sec. cor. of secs. 7 and 18, at proportionate dist.; no remaining evidence of the original cor.

Set an iron post, 28 ins. long, 2 1/2 ins. diam., 22 ins. in the ground, with brass cap mkd.

T1S R3W
1/4 S 7
S18
1958

Set a cedar post, 6 ft. long, 6 ins. diam., 2 ft. in the ground, 1 lk. N. of cor.

79.40

Power line, bears N. and S.

79.98

The cor. of secs. 7, 12, 13 and 18, which is monumented with a 2 1/2 ins. iron post, hereinbefore described.

Land, nearly level.

Soil, second rate sandy clay.

Timber, none.

Undergrowth, medium dense willows, salt cedar, scattered mesquite and sparse grass.

General Description

Most of the south half of this township is low to medium high rocky foothills, covered for the most part with greasewood, ocotillo, palo verde, cacti and sparse grass.

The Gila River cuts through the township from east to west with overflow bottom of approximately one mile in width, covered mostly with dense salt cedar, willows, scattered mesquite and sparse grass.

There is some fair farming land in sections 13, 14 and 15. The north portion not resurveyed of this township is mostly good farming land and the city of Buckeye is located in section 5.

4-680
(Feb., 1960)

UNITED STATES
DEPARTMENT OF THE INTERIOR
BUREAU OF LAND MANAGEMENT

FIELD ASSISTANTS

NAMES	CAPACITY
Boyd Owens	Instrumentman
Donald A. Cannon	Notekeeper
Landon A. Kittel	Chainman
James Jepson	Truck Driver
Ted Griffin	Flagman
Richard N. Brand	Axeman

CERTIFICATE OF CADASTRAL ENGINEER

I, Donald E. Harding, HEREBY CERTIFY upon honor that, in pursuance of special instructions bearing date of the 26th day of December, 1957, I have ~~surveyed~~ independently resurveyed a portion of the east boundary, a portion of the west boundary and a portion of the subdivision of T. 1 S., R. 3 W.

of the Gila & Salt River Meridian, in the State of Arizona, which are represented in the foregoing field notes as having been executed by me and under my direction; and that said survey has been made in strict conformity with said instructions, the Manual of Instructions for the Survey of the Public Lands of the United States, and in the specific manner described in the foregoing field notes.

Salt Lake City, Utah
December 24, 1958

Donald E. Harding
Donald E. Harding
Cadastral Surveyor

CERTIFICATE OF APPROVAL

BUREAU OF LAND MANAGEMENT,
Washington, D. C., 1958

The foregoing field notes of the ~~survey of~~ dependent resurvey of a portion of the east boundary, a portion of the west boundary and a portion of the subdivision of T. 1 S., R. 3 W., Gila and Salt River Meridian, Arizona

executed by Donald E. Harding, Cadastral Surveyor
having been critically examined and found correct, are hereby approved.

James O. Clement
Cadastral Engineering Staff Officer.

CERTIFICATE OF TRANSCRIPT

I CERTIFY that the foregoing transcript of the field notes of the above-described surveys in T. 1 S., R. 3 W., G. & S., R. Mer., is a true copy of the original field notes.

Cadastral Engineering Staff Officer.