

UNITED STATES
DEPARTMENT OF THE INTERIOR
BUREAU OF LAND MANAGEMENT

FIELD NOTES

OF

REMONUMENTED

CADASTRAL SURVEY CORNERS

TOWNSHIP 7 SOUTH, RANGE 24 EAST

IN

COOPERATION WITH

U. S. FOREST SERVICE

Of the *Gila & Salt River Meridian,*

In the State of *Arizona*

EXECUTED BY

Lester S. Mann, Office Cadastral Engineer

*Under special instructions dated March 4, 1960, which provided
for the surveys included under Group No. 350, approved March 11, 1960
and assignment instructions dated March 11, 1960*

Survey commenced May 8, 1960

Survey completed May 9, 1960

1A

EOCK 4596

INDEX DIAGRAM

Township 7 South, Range 24 East

6	5	4	3	2	1
7	8	9	10	11	12
13	14	15	16	17	18
19	20	21	22	23	24
25	26	27	28	29	30
31	2	2		2 2	1
32	33	34	35	36	37

Township 7 South, Range 24 East, Arizona

16

Chains

The following field notes are those of remonumented cadastral survey corner monuments by agreement with the U. S. Forest Service. The detailed cooperative agreement was approved by the Director, Bureau of Land Management, by memorandum (5.04b) dated October 16, 1958. The approval of the Special Instructions on March 11, 1960, gave authority to proceed with the remonumentation in accordance with the Director's Order No. 54 dated April 21, 1954.

The $\frac{1}{4}$ cor. of secs. 25 and 36 is monumented with a granite stone, 20 x 12 x 6 ins., firmly set with a mound of stone to N., mkd. $\frac{1}{4}$ on N. face.

At the cor. point

Set an iron post, 30 ins. long, $2\frac{1}{2}$ ins. diam., 18 ins. in the ground, collar of stone to top, brass cap mkd.

T7S R24E

$\frac{1}{4}$ S25

S36

1960

Bury the original cornerstone alongside the iron post.

NOTE: This corner is to be used as control for the National Forest boundary.

The $\frac{1}{4}$ cor. of secs. 35 and 36 is monumented with a granite boulder, 60 x 30 x 12 ins. of it above ground, mound of stone to the W., mkd. "X" and $\frac{1}{4}$ on NW face.

This boulder is too large to move.

The cor. of secs. 23, 24, 25 and 26 is monumented with a granite stone 24 x 12 x 6 ins., firmly set with a mound of stone to the NW, mkd. with 1 notch on the NE and 2 notches on the SE edges.

from which

A dead sycamore, 14 ins. diam., bears S. $48\frac{1}{2}^{\circ}$ W., 69 lks. dist., mkd. with a blaze but with no marks visible.

At the cor. point

Set an iron post, 30 ins. long, $2\frac{1}{2}$ ins. diam., 24 ins. in the ground, collar of stone, brass cap mkd.

T7S R24E

S23 | S24

S26 | S25

1960

Bury the original cornerstone alongside the iron post. The iron post is 29 lks. E. and 45 lks. S. of Ash Creek which is 10 lks. wide, 6 ins. deep, course N. 25° E.

NOTE: This corner is to be used as control for the National Forest boundary.

Chains

The $\frac{1}{4}$ cor. of secs. 26 and 35 is monumented with a granite stone, 18 x 12 x 12 ins., firmly set with a mound of stone to NW, mkd. with $\frac{1}{4}$ on N. face.

At the cor. point

Set an iron post, 30 ins. long, $2\frac{1}{2}$ ins. diam., 16 ins. in the ground, collar of stone to top, brass cap mkd.

T7S R24E

$\frac{1}{4}$ S26

$\frac{1}{4}$ S35

1960

Bury the original cornerstone alongside the iron post. The iron post is on a steep and rocky E. slope.

The cor. of secs. 26, 27, 34 and 35 is monumented with a granite stone, 24 x 8 x 8 ins., firmly set with mound of stone to S., mkd. with 2 notches on the E. and 1 notch on the S. edges.

At the cor. point

Set an iron post, 30 ins. long, $2\frac{1}{2}$ ins. diam., 18 ins. in the ground, collar of stone to top, brass cap mkd.

T7S R24E

S27 | S26

S34 | S35

1960

Bury the original cornerstone alongside the iron post. Iron post is in a small flat near a drain, course NW.

The cor. of secs. 28, 29, 32 and 33 is monumented with a granite stone, 24 x 12 x 10 ins., firmly set with mound of stone to NW, mkd. with 4 notches on the E. and 1 notch on the S. edges.

At the cor. point

Set an iron post, 30 ins. long, $2\frac{1}{2}$ ins. diam., 16 ins. in the ground, collar of stone to top, brass cap mkd.

T7S R24E

S29 | S28

S32 | S33

1960

Bury the original cornerstone alongside the iron post. Iron post is on a high mesa sloping gently to the N.

The cor. of secs. 29, 30, 31 and 32 is monumented with a dark granite stone, 24 x 12 x 8 ins., firmly set with a recently built mound of stone to the SW, mkd. with 5 notches on the E. and 1 notch on the S. edges.

At the cor. point

Set an iron post 30 ins. long, $2\frac{1}{2}$ ins. diam., 24 ins. in the ground, collar of stone, brass cap mkd.

Chains

T7S R24E
S30 | S29
S31 | S32
1960

Bury the original cornerstone alongside the iron post. The iron post is on a steep N. slope.

CERTIFICATE OF CADASTRAL ENGINEER

I, Lester S. Mann, HEREBY CERTIFY upon honor that, in pursuance of special instructions bearing date of the 4th day of March, 1960, I have surveyed and remonumented the cadastral survey corners in T. 7 S., R. 24 E. in cooperation with the U. S. Forest Service.

of the G&SR Meridian, in the State of Arizona, which are represented in the foregoing field notes as having been executed by me and under my direction; and that said survey has been made in strict conformity with said instructions, the Manual of Instructions for the Survey of the Public Lands of the United States, and in the specific manner described in the foregoing field notes.

Phoenix, Arizona
June 21, 1960

Lester S. Mann
Lester S. Mann
Office Cadastral Engineer

CERTIFICATE OF APPROVAL

BUREAU OF LAND MANAGEMENT,
Washington, D. C., SEP 5 1961, 19

The foregoing field notes of the survey of remonumented cadastral survey corners in Township 7 South, Range 24 East, Gila and Salt River Meridian, Arizona

executed by Lester S. Mann, Office Cadastral Engineer
having been critically examined and found correct, are hereby approved.

E. E. Huntington
Chief, Division of Engineering

CERTIFICATE OF TRANSCRIPT

I CERTIFY that the foregoing transcript of the field notes of the above-described surveys in is a true copy of the original field notes.

Cadastral Engineering Staff Officer