

(1)

UNITED STATES
DEPARTMENT OF THE INTERIOR
BUREAU OF LAND MANAGEMENT

FIELD NOTES

OF

REMONUMENTED

CADASTRAL SURVEY CORNERS

TOWNSHIP 8 SOUTH, RANGE 25 EAST

IN

COOPERATION WITH

U. S. FOREST SERVICE

Of the Gila & Salt River Meridian,

In the State of Arizona

EXECUTED BY

Lester S. Mann, Office Cadastral Engineer

Under special instructions dated March 4, 1960, which provided
for the surveys included under Group No. 350, approved March 11, 1960
and assignment instructions dated March 11, 1960

Survey commenced May 4, 1960

Survey completed May 7, 1960

11A

BOOK 4599

INDEX DIAGRAM

Township 8 South, Range 25 East

5						
5	6	5	4	3	2	1
4	4	4				
	7	3	8	9	10	11
		3		2		
	18	17	16	2	15	14
				2		
	19	20	21	3	22	23
				2		
	30	29	28	27	1	26
					1	
	31	32	33	34	35	36
					1	1

Chains

The following field notes are those of remonumented cadastral survey corner monuments by agreement with the U. S. Forest Service. The detailed cooperative agreement was approved by the Director, Bureau of Land Management, by memorandum (5,04b) dated October 16, 1958. The approval of the Special Instructions on March 11, 1960, gave authority to proceed with the remonumentation in accordance with the Director's Order No. 54 dated April 21, 1954.

The $\frac{1}{4}$ cor. of sec. 36 on the S. bdy. of the Tp. is monumented with a granite stone, 18 x 10 x 6 ins., firmly set, mkd. $\frac{1}{4}$ on N. face, with small mound of stone to N.

At the cor. point

Set an iron post, 30 ins. long, $2\frac{1}{2}$ ins. diam., 14 ins. in the ground, collar of stone to top, brass cap mkd.

T8S R25E

$\frac{1}{4}$ S36

1960

Bury the original cornerstone alongside the iron post. Iron post is on a ridge bearing N. and S.

The cor. of secs. 34 and 35 on the S. bdy. of the Tp. is monumented with a granite boulder in place, 80 x 48 x 30 ins. of it above ground, mkd. with an "X" and 2 notches on the E. and 4 notches on the W. sides.

This boulder is too large to move.

No B.T.'s available.

The cor. of secs. 26, 27, 34 and 35 is monumented with a quartzite stone, 20 x 8 x 6 ins., loosely set in a scattered mound of stone, mkd. with 2 notches on the E. and 1 notch on the S. edges.

At the cor. point

Set an iron post, 30 ins. long, $2\frac{1}{2}$ ins. diam., 22 ins. in the ground, brass cap mkd.

T8S R25E

S27 | S26

S34 | S35

1960

Bury the original cornerstone alongside the iron post. The iron post is 6 lks. N. and 4 lks. E. of a fence corner from which fences bear N.-E.-W.

The $\frac{1}{4}$ cor. of secs. 26 and 27 is monumented with a pyramid-shaped granite stone, 10-in. base and 18 ins. long, firmly set with a large mound of stone to west, mkd. $\frac{1}{4}$ on W. face.

At the cor. point

Set an iron post, 30 ins. long, $2\frac{1}{2}$ ins. diam., 22 ins. in the ground, brass cap mkd.

T8S R25E

$\frac{1}{4}$ S27 | S26

1960

Chains

Bury the original cornerstone alongside the iron post. The iron post is on the break of a N. slope, 30 ft. high.

The $\frac{1}{4}$ cor. of secs. 22 and 27 is monumented with a granite stone, 22 x 12 x 12 ins., firmly set with a mound of stone to the N., mkd. $\frac{1}{4}$ on the N. face.

At the cor. point

Set an iron post, 30 ins. long, 2 $\frac{1}{2}$ ins. diam., 20 ins. in the ground, brass cap mkd.

T8S R25E

$\frac{1}{4}$ S22

S27

1960

Bury the original cornerstone alongside the iron post. The iron post is on a NW slope and 1 lk. N. and 2 lks. E. of a fence corner from which fences bear N.-S. and E.

The cor. of secs. 9, 10, 15 and 16 is monumented with a granite stone, 24 x 12 x 6 ins., firmly set, mkd. with 3 notches on the E. and 4 notches on the S. edges.

At the cor. point

Set an iron post, 30 ins. long, 2 $\frac{1}{2}$ ins. diam., 16 ins. in the ground, collar of stone to top, brass cap mkd.

T8S R25E

S 9 | S10

S16 | S15

1960

from which

A mesquite, 6 ins. diam., bears N. 72 $\frac{1}{2}$ ° E., 82 lks. dist., mkd. BT.

Bury the original cornerstone alongside the iron post. The iron post is in a rocky area on the S. side of a small drain, course E.

The $\frac{1}{4}$ cor. of secs. 15 and 16 is monumented with a granite stone, 20 x 10 x 4 ins., set 8 ins. in the ground with mound of stone to W., mkd. $\frac{1}{4}$ on W. face.

At the cor. point

Set an iron post, 30 ins. long, 2 $\frac{1}{2}$ ins. diam., 16 ins. in the ground, collar of stone to top, brass cap mkd.

T8S R25E

$\frac{1}{4}$ S16 | S15

1960

Bury the original cornerstone alongside the iron post. The iron post is on a gentle E. slope.

Chains

The cor. of secs. 15, 16, 21 and 22 is monumented with a granite stone, 24 x 12 x 6 ins., firmly set with mound of stone to W., mkd. with 3 notches on the E. and S. faces.

At the cor. point

Set an iron post, 30 ins. long, 2½ ins. diam., 16 ins. in the ground, collar of stone to top, brass cap mkd.

T8S R25E
 S16|S15
 S21|S22
 1960

Bury the original cornerstone alongside the iron post. The iron post is on a N. slope.

The ¼ cor. of secs. 8 and 17 is monumented with a granite stone, 24 x 12 x 4 ins., firmly set with a mound of stone to N., mkd. ¼ on N. face.

At the cor. point

Set an iron post, 30 ins. long, 2½ ins. diam., 16 ins. in the ground, collar of stone to top, brass cap mkd.

T8S R25E
 ¼ S 8
 S17
 1960

Bury the original stone corner alongside the iron post. The iron post is 60 lks. N. of an E. and W. fence on a gentle N. slope.

The cor. of secs. 7, 8, 17 and 18 is monumented with a granite stone 36 x 12 x 3 ins., firmly set with a mound of stone to SE., mkd. with 5 notches on the E. and 4 notches on the S. edges.

At the cor. point

Set an iron post, 30 ins. long, 2½ ins. diam., 22 ins. in the ground, collar of stone, brass cap mkd.

T8S R25E
 S 7|S 8
 S18|S17
 1960

Bury the original cornerstone alongside the iron post. The iron post is 42 lks. E. of a N. and S. fence on a high spur sloping sharply to the NE.

The ¼ cor. of secs. 7 and 8 is monumented with a granite stone in place, 36 x 36 x 18 ins. of it above ground, mound of stone on W., mkd. "X" on top and ¼ on W. face.

This stone was too large to move. It is 29 lks. E. of a N. and S. fence.

Chains

The cor. of secs. 5, 6, 7 and 8 is monumented with a granite stone, 24 x 8 x 8 ins., firmly set with a mound of stone to NE, mkd. with 5 notches on the E. and S. edges.

At the cor. point

Set an iron post, 30 ins. long, 2½ ins. diam., 16 ins. in the ground, collar of stone to top, brass cap mkd.

T8S	R25E
S 6	S 5
S 7	S 8
1960	

from which

A mesquite, 6 ins. diam., bears N. 78° E., 77 lks. dist., mkd. BT.

A mesquite, 4 ins. diam., bears N. 11° W., 147 lks. dist., mkd. BT.

Bury the original cornerstone alongside the iron post.

The ¼ cor. of secs. 6 and 7 is monumented with a granite stone, 18 x 6 x 4 ins., firmly set with a mound of stone to N., mkd. ¼ on N. face.

At the cor. point

Set an iron post, 30 ins. long, 2½ ins. diam., 12 ins. in ground, collar of stone to top, brass cap mkd.

T8S	R25E
S 6	
S 7	
1960	

Bury the original cornerstone alongside iron post. Iron post is on a high mesa sloping N.

The cor. of secs. 1, 6, 7 and 12 on the W. bdy. of the Tp. is monumented with a granite stone 20 x 10 x 5 ins., firmly set with a mound of stone to W., mkd. with 5 notches on the S. and 1 notch on the N. edges.

At the cor. point

Set an iron post, 30 ins. long, 2½ ins. diam., 16 ins. in the ground, collar of stone to top, brass cap mkd.

T8S	
R24E	R25E
S 12	S 6
	S 7
1960	

Bury the original stone corner alongside the iron post. The iron post is on a high mesa sloping N.

NOTE: This cor. was mkd. for secs. 6 and 7 only since the protraction diagram for unsurveyed T. 8 S., R. 24 E. shows the cor. for secs. 1 and 12 will be a closing corner.

Chains

The $\frac{1}{4}$ cor. of secs. 1 and 6 is monumented with a granite stone, 24 x 16 x 4 ins., firmly set with a mound of stone to W., mkd. $\frac{1}{4}$ on W. face.

At the cor. point

Set an iron post, 30 ins. long, $2\frac{1}{2}$ ins. diam., 16 ins. in the ground, collar of stone to top, brass cap mkd.

T8S
R24E R25E
| $\frac{1}{4}$
S6
1960

Bury the original stone corner alongside the iron post. The iron post is $3\frac{1}{2}$ lks. E. of a N. and S. fence and on a NW slope.

NOTE: This cor. was marked for sec. 6 only since the protraction diagram for unsurveyed T. 8 S., R. 24 E. shows uncommon corner along this line.

The cor. of Tps. 7 and 8 S., Rs. 24 and 25 E. is monumented with a granite stone, 20 x 8 x 6 ins., firmly set with small mound of stone to SW., mkd. with 6 notches on the N., S., E. and W. edges.

At the cor. point

Set an iron post, 30 ins. long, $2\frac{1}{2}$ ins. diam., 18 ins. in the ground, collar of stone to top, brass cap mkd.

T7S
R24E R25E
S36 | S31
S 1 | S 6
T8S
1960

Bury the original stone corner alongside the iron post. The iron post is 6 lks. N. and $3\frac{1}{2}$ lks. E. of a fence corner from which fences bear N., S. and W., and is on the S. side of a small side-hill drain, course NW.

1

CERTIFICATE OF CADASTRAL ENGINEER

I, Lester S. Mann, HEREBY CERTIFY upon honor that, in pursuance of special instructions bearing date of the 4th day of March, 1960, I have surveyed and remonumented the cadastral survey corners in T. 8 S., R. 25 E., in cooperation with the U. S. Forest Service

of the G&SR Meridian, in the State of Arizona, which are represented in the foregoing field notes as having been executed by me and under my direction; and that said survey has been made in strict conformity with said instructions, the Manual of Instructions for the Survey of the Public Lands of the United States, and in the specific manner described in the foregoing field notes.

Phoenix, Arizona
June 21, 1960

Lester S. Mann
Lester S. Mann
Office Cadastral Engineer

CERTIFICATE OF APPROVAL

BUREAU OF LAND MANAGEMENT,
Washington, D. C., SEP 5 1961

The foregoing field notes of the survey of remonumented cadastral survey corners in Township 8 South, Range 25 East, Gila and Salt River Meridian, Arizona,

executed by Lester S. Mann, Office Cadastral Engineer
having been critically examined and found correct, are hereby approved.

Chief, Division of Engineering
Cadastral Engineering Staff Officer

CERTIFICATE OF TRANSCRIPT

I CERTIFY that the foregoing transcript of the field notes of the above-described surveys in
is a true copy of the original field notes.

Cadastral Engineering Staff Officer