

UNITED STATES
DEPARTMENT OF THE INTERIOR
BUREAU OF LAND MANAGEMENT

FIELD NOTES

OF

REMONUMENTED

CADASTRAL SURVEY CORNERS

TOWNSHIP 9 SOUTH, RANGE 23 EAST

IN

COOPERATION WITH

U. S. FOREST SERVICE

Of the Gila & Salt River Meridian,

In the State of Arizona

EXECUTED BY

Lester S. Mann, Office Cadastral Engineer

Under special instructions dated March 4, 1960, which provided
for the surveys included under Group No. 350, approved March 11, 1960
and assignment instructions dated March 11, 1960

Survey commenced May 19, 1960

Survey completed May 19, 1960

1A

BOOK 4601

INDEX DIAGRAM

Township 9 South, Range 23 East

6	5	4	3	2	1
7	8	9	10	11	12
13	2	2	15	14	13
18	17	2	16	15	14
19	20	21	22	23	24
25	26	27	28	29	30
31	32	33	34	35	36

Township 9 South, Range 23 East

18

Chains

The following field notes are those of remonumented cadastral survey corner monuments by agreement with the U.S. Forest Service. The detailed cooperative agreement was approved by the Director, Bureau of Land Management, by memorandum (5.04b) dated October 16, 1958. The approval of the Special Instructions on March 11, 1960, gave authority to proceed with the remonumentation in accordance with the Director's Order No. 54 dated April 21, 1954.

The corner of secs. 4, 5, 32 and 33 on the N. bdy. of the Tp. is monumented with a granite stone, 24 x 16 x 12 ins., marked with 4 notches on the E. face and 2 notches on the W. face, firmly set in a scattered mound of stone.

from which

A dead oak, 12 ins. diam., bears N. 62° E., 102 lks. dist. mkd. with open blaze and faint scribe marks.

A fallen oak, 10 ins. diam., bears S. 52° E., 39 lks. dist., mkd. with open blaze and faint scribe marks.

A white oak, 16 ins. diam., bears N. 25° W., 52 lks. dist., mkd. with a grown-over blaze.

No evidence found of S.W. tree.

At the cor. point

Set an iron post, 30 ins. long, 2½ ins. diam., 24 ins. in the ground, brass cap mkd.

T8S	R23E
S32	S33
S 5	S 4
T9S	
1960	

from which

A white oak, 8 ins. diam., bears N. 76° E., 134 lks. dist., mkd. BT.

A white oak, 5 ins. diam., bears S. 41° W., 61 lks. dist., mkd. BT.

A white oak, 16 ins. diam., bears N. 25° E., 52 lks. dist., mkd. BT. (Orig. B.T.)

Bury the original cornerstone alongside the iron post.

The iron post is 5 lks. S. and 3 lks. W. of a fence corner from which fences bear S. and W. and is on a S.W. slope.

The corner of secs. 5, 6, 31 and 32 on the N. bdy. of the Tp.

Found a granite stone in place, 24 x 12 x 12 ins. of it above ground, in a scattered mound of stone, very faint marks on E. and W. faces.

from which

A white oak, 14 ins. diam., bears S. 4° E., 54 lks. dist. mkd. with an open blaze. (Record S. 4° E., 45 lks.)

Chains

A white oak, 16 ins. diam., bears S. 54° W., 110 lks. dist., mkd. with an open blaze. (Record same.)

There is no evidence of the N.W. or S.E. BT's.

The stone is 5 lks. S. of an E.-W. fence, about 1.30 chs. E. of a draw, course E., and on a steep S.W. slope.

The evidence here was considered insufficient and no iron post was set.

The cor. of secs. 7, 8, 17 and 18 is monumented with a granite stone, 12 x 11 x 7 ins., firmly set, marked with 5 notches on the E. edge and 4 notches on the S. edge.

At the cor. point

Set an iron post, 30 ins. long, 2 1/2 ins. diam., 18 ins. in the ground, collar of stone, brass cap mkd.

T9S R23E
S 7 | S 8
S18 | S17
1960

Bury the original cornerstone alongside the iron post. Iron post is on a steep E. slope and the topography given in the original field notes to the E. appears to check.

The 1/4 sec. cor. of secs. 9 and 16 is monumented with an iron pipe, 3 ins. diam., 3 ft. long. Found the original granite stone, 24 x 14 x 8 ins., mkd. 1/4, lying loose on ground beside pipe. Mr. Ed Moyer, a local rancher, claims he drove the iron pipe in the place where the original stone stood when it became loose.

At the cor. point

Set an iron post, 30 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, collar of stone, brass cap mkd.

T9S R23E
1/4 S9
S16
1960

Bury the original cornerstone alongside the iron post. The iron post is 2 1/2 lks. S. of an E.-W. fence in flat land and 30 lks. W. of a small drain, course S. 30° W.

The 1/4 sec. cor. of secs. 16 and 17.

Found a granite stone in place, 16 x 14 x 14 ins. of it above ground, mkd. 1/4 on S. face.

Did not set an iron post as the corner needs verification by survey.

Stone is about 1.00 ch. S. of a dirt road bearing E. and W. and in flat mesquite land.

CERTIFICATE OF CADASTRAL ENGINEER

I, Lester S. Mann, HEREBY CERTIFY upon honor that, in
pursuance of special instructions bearing date of the 4th day of March, 1960,
I have ~~surveyed~~ remonumented the cadastral survey corners in T. 9 S., R. 23 E. in
cooperation with the U. S. Forest Service

of the G&SR Meridian, in the State of Arizona, which are
represented in the foregoing field notes as having been executed by me and under my direction; and that
said survey has been made in strict conformity with said instructions, the Manual of Instructions for the
Survey of the Public Lands of the United States, and in the specific manner described in the foregoing
field notes.

Phoenix, Arizona
June 21, 1960

Lester S. Mann
Lester S. Mann
Office Cadastral Engineer

CERTIFICATE OF APPROVAL

BUREAU OF LAND MANAGEMENT,
SEP 5 1961
Washington, D. C., _____, 19____

The foregoing field notes of the ~~survey of~~ remonumented cadastral survey corners in
Township 9 South, Range 23 East, Gila and Salt River Meridian, Arizona,

executed by Lester S. Mann, Office Cadastral Engineer
having been critically examined and found correct, are hereby approved.

E. E. Remington
Cadastral Engineering Staff Officer,
Chief, Division of Engineering

~~CERTIFICATE OF TRANSCRIPT~~

~~I CERTIFY that the foregoing transcript of the field notes of the above-described surveys in _____
_____, is a true copy of the original field notes.~~

~~_____
Cadastral Engineering Staff Officer.~~