

UNITED STATES
DEPARTMENT OF THE INTERIOR
BUREAU OF LAND MANAGEMENT

ORIGINAL

FIELD NOTES

OF THE

DEPENDENT RESURVEY

OF

THE FIRST STANDARD PARALLEL SOUTH

IN RANGE 29 EAST

AND A PORTION OF THE WEST BOUNDARY

AND ALL OF THE EAST BOUNDARY

AND

COMPLETION OF THE SURVEY OF THE SUBDIVISION

OF

TOWNSHIP 6 SOUTH, RANGE 29 EAST

Of the Gila and Salt River Meridian,

In the State of Arizona

EXECUTED BY

Phil D. Smith, Cadastral Surveyor - in 1957

Vern E. Lane, Cadastral Surveyor (Chief of Party) - in 1960

Eldon W. Sibley, Cartographic Survey Aid - in 1960

Boyd S. Owens, Cadastral Surveyor - in 1960

Under special instructions dated November 16, 1954, which provided
and supplemental special instructions dated January 13 1956 November 16, 1954
for the surveys included under Group No. 299, approved January 13, 1956

and assignment instructions dated November 1 1957
January 13, 1960

Survey commenced February 15, 1957

Survey completed February 9, 1960

1A

BOOK 4617

INDEX DIAGRAM

Township 6 South, Range 29 East

6	12 •	11 •	10 •	8 •	7 •	6 •	4
5	46 •	45 •	34 •	33 •	10	28 •	19 •
	44 •	32 •	9	18 •	26 •	17 •	3
	43 •	43 •	16	27 •	24 •	17 •	3
	42 •	17	15	25 •	24 •	16 •	2
	41 •	40 •	32 •	21	23 •	23 •	2
	40 •	30 •	28	22 •	22 •	15 •	2
	38 •	38 •	31 •	23 •	22 •	14 •	2
	37 •	29 •	28	27 •	20 •	13 •	2
	36 •	35 •	29 •	21 •	20 •	13 •	2
	35 •	28 •	28	21 •	19 •	13 •	2
	35 •	28 •	28	21 •	19 •	13 •	2

GPO 866119

Phil D. Smith

Eldon W. Sibley and Boyd S. Owens

Township 6 South, Range 29 East

Chains

The north boundary (First Standard Parallel South) of the township was surveyed by Philip Contzen in 1895, portions of this line were resurveyed by W. B. Kimmell in 1914, as represented on the plat of T. 5 S., R. 29 E., approved June 19, 1915. A portion of the east boundary was surveyed by D. Drummond in 1891, as represented on the plat approved September 29, 1891. The south five miles of the east boundary were surveyed by H. G. Parker in 1955. The south boundary was surveyed by C. E. Hunter in 1933, as represented on the plat approved February 27, 1934. The south boundary was again surveyed by H. G. Parker in 1955, who established new corner monuments for T. 6 S., R. 29 E., and remarked the original corner monuments to function for T. 7 S., R. 29 E. The west boundary was independently resurveyed, and the third meridional line and sections 2, 3 and 16 were surveyed by H. G. Parker in 1955, as represented on the plats of T. 6 S., Rs. 28 and 29 E.

The following field notes are those of the dependent resurvey of a portion of the west boundary and all of the north boundary (First Standard Parallel South) and the east boundary, and the completion of all unsurveyed subdivisional lines in T. 6 S., R. 29 E., which were requested by the State Supervisor of Arizona to facilitate range management.

This survey was executed with W. & L. E. Gurley Solar transits, serial Nos. 541329, 560147, 560149, and Buff and Buff light mountain solar transit, serial No. 23831, all transits being constructed in accordance with the standard instrumental specifications of the Bureau of Land Management. The instruments were in good condition prior to the beginning of the survey and were maintained in proper adjustment thereafter throughout the progress of the survey.

Lines connecting previously established corners were run by the random and true method, but for simplification of the record, the random lines are omitted from these field notes.

Measurements herein contained were made with a narrow steel tape, 8 chains in length, graduated every one-tenth link for the first link, every link for the next 99 links, and thereafter at intervals of every 10 links. The tape was tested by comparison with a 1 chain standard steel tape and found to be correct. Measurements were made on the slope, with the vertical angle of each interval ascertained by two clinometers in good adjustment; the field notes show the horizontal equivalents only. All lines of this survey were run by direct method where the lines were accessible; lines inaccessible were run by traverse or triangulation methods. The details of such traverses or triangulations have been thoroughly checked and verified, and in order to simplify the record the diagrams and reductions are omitted from these field notes.

The directions of the lines of this survey were determined generally by sustained angulation carried forward from the following hour angle observations on Polaris for meridian, supplemented by other numerous stellar and solar observations for azimuth taken throughout the progress of the survey.

The geographic position for the southeast corner of the township is latitude $32^{\circ} 51' 39.0''$ N. and longitude $109^{\circ} 19' 14.4''$ W. as determined by traverse from U.S.C. & G.S. triangulation station "Guthrie," situated in section 30, T. 6 S., R. 30 E.

February 10, 1957 at the closing corner of T. 6 S., Rs. 28 and 29 E., at latitude $32^{\circ} 56' 47''$ N. and longitude $109^{\circ} 25' 29''$ W., I make an hour angle observation on Polaris, with the following results:

Mean watch time of observation, p.m. -----	5h 56.8m
Hour angle of Polaris -----	1h 26.3m
True azimuth -----	W. $0^{\circ} 24.7m$
Horizontal angle -----	$89^{\circ} 27.3m$
True bearing of reference line -----	S. $89^{\circ} 52.0m$ W.

Township 6 South, Range 29 East

Chains

The magnetic declination was read at a number of stations throughout the survey and the average of these readings was found to be $12\frac{1}{2}^{\circ}$ E.

Dependent Resurvey of the East Boundary of T. 6 S., R. 29 E.

Reestablishment of surveys executed by H. Parker in 1955. The topography as given in the record is substantially correct and is omitted from these field notes.

Beginning at the cor. of T. 6 S., Rs. 29 and 30 E., which is mkd. by an iron post, 3 ins. diam., conforming to the record of the 1955 survey.

N. $0^{\circ} 09' W.$, bet. secs. 31 and 36.

Over mountainous land.

40.20 The $\frac{1}{4}$ sec. cor. of secs. 31 and 36, on iron post, $2\frac{1}{2}$ ins. diam., conforming to the record.

N. $0^{\circ} 11' E.$, beginning new measurement.

39.96 The cor. of secs. 25, 30, 31 and 36, an iron post, $2\frac{1}{2}$ ins. diam., conforming to the record.

From this cor., U.S.G.S. triangulation station "Guthrie" bears N. $26^{\circ} 20' E.$, 72.60 chs. dist. Its geographic position is Latitude $32^{\circ} 53' 13.836'' N.$, Longitude $109^{\circ} 18' 49.468'' W.$

Land, mountainous.

Soil, gravelly and rocky.

Timber, scattering juniper.

Undergrowth, ocotillo, catclaw and cacti.

N. $0^{\circ} 06' W.$, bet. secs. 25 and 30.

Over mountainous land.

40.20 The $\frac{1}{4}$ sec. cor. of secs. 25 and 30, an iron post, $2\frac{1}{2}$ ins. diam., conforming to the record.

N. $0^{\circ} 11' E.$, beginning new measurement.

40.05 The cor. of secs. 19, 24, 25 and 30, an iron post, $2\frac{1}{2}$ ins. diam., conforming to the record.

Land, mountainous.

Soil, gravelly and rocky.

Timber, scattering juniper and oak,

Undergrowth, ocotillo, catclaw, sagebrush and cacti.

N. $0^{\circ} 02' W.$, bet. secs. 19 and 24.

Over mountainous land.

Dependent Resurvey, E. Bdy., T. 6-S., R. 29-E.

Chains

- 39.81 Point for the $\frac{1}{4}$ sec. cor. of secs. 19 and 24 falls in wash, course NW.; there is no remaining evidence of the position of the original cor.
- 40.01 Point selected for the witness $\frac{1}{4}$ sec. cor. of secs. 19 and 24.
Set an iron post, 30 ins. long, $2\frac{1}{2}$ ins. diam., 10 ins. in the ground and in a mound of stone, 4 ft. base, to top of post with brass cap mkd.
- T6S
R29E R3E
S24 | S19
W-C
1960
- 79.61 The cor. of secs. 13, 18, 19 and 24, an iron post, $2\frac{1}{2}$ ins. diam., conforming to the record.
Land, mountainous.
Soil, gravelly and rocky.
Timber, scattering juniper.
Undergrowth, ocotillo, catclaw, sagebrush and cacti.
-
- N. $0^{\circ} 11' W.$, bet. secs. 13 and 18.
Over mountainous land.
- 40.17 The $\frac{1}{4}$ sec. cor. of secs. 13 and 18, an iron post, $2\frac{1}{2}$ ins. diam., conforming to the record.
N. $0^{\circ} 05' E.$, beginning new measurement.
- 40.54 The cor. of secs. 7, 12, 13 and 18, an iron post, $2\frac{1}{2}$ ins. diam., conforming to the record.
Land, mountainous.
Soil, gravelly and rocky.
Timber, scattering juniper.
Undergrowth, ocotillo, catclaw, sagebrush and cacti.
-
- N. $0^{\circ} 09' W.$, bet. secs. 7 and 12.
Over mountainous land.
- 40.40 The $\frac{1}{4}$ sec. cor. of secs. 7 and 12, an iron post, $2\frac{1}{2}$ ins. diam., conforming to the record.
N. $0^{\circ} 02' W.$, beginning new measurement.
- 39.90 The cor. of secs. 1, 6, 7 and 12, mkd. by an iron post, $2\frac{1}{2}$ ins. diam., conforming to the record.
Land, mountainous.
Soil, gravelly and rocky.
Timber, scattering juniper.
Undergrowth, ocotillo, catclaw, cacti, sagebrush and spanish dagger.

Dependent Resurvey, E. Bdy., T. 6 S., R. 29 E.

Chains

Reestablishment of the survey executed by D. Drummond in 1891.

From the cor. of secs. 1, 6, 7 and 12, T. 6 S., Rs. 29 and 30 E., monumented by an iron post, 2½ ins. diam., 24 ins. above ground, and in a large mound of stone, firmly set, mkd. and witnessed as described in the official record.

N. 0° 03' W., bet. secs. 1 and 6.

Over spur top, rolling NW. slope.

10.00 Small short spur, sloping NE.; desc. 250 ft. over a rocky NW. slope.

20.00 Wash, 20 lks. wide, 2 ft. deep, drains N. 10° E.; asc. 115 ft. over a rocky SE. slope.

37.20 S. edge of spur, from S. 10° W., thence over rocky spur top.

40.00 The original ¼ sec. cor. of secs. 1 and 6, monumented by a malpais stone 10x8x6 ins. above ground, and in a small mound of stone, firmly set, mkd. and witnessed as described in the official record.

At the cor. point

Set an iron post, 30 ins. long, 2½ ins. diam., 10 ins. in the ground, and in a mound of stone, 4 ft. base, to top, with brass cap mkd.

T6S

R29E R30E

¼

S 1 | S 6

1957

Deposit the original cor. monument alongside the iron post.

N. 0° 03' W., beginning new measurement.

Desc. 115 ft. over rocky NW. slope.

11.20 Wash, 40 lks. wide, 4 ft. deep, drains N. 30° E., approximately 5 chs., thence N.; asc. 70 ft. over broken SE. slope.

16.65 N. edge of spur, sloping N. 10° E.; desc. 90 ft. over rocky NW. slope.

31.00 Point for the standard closing cor. of Tps. 5 and 6 S., R. 29 E., hereinafter described.

Thence along the W. bdy. of sec. 6, T. 6 S., R. 30 E., along rolling E. slope.

38.80 The original closing cor. of T. 6 S., Rs. 29 and 30 E., being the NW. cor. of T. 6 S., R. 30 E., monumented by a malpais stone 18x12x4 ins., and in a large mound of stone, set, mkd. and witnessed as described in the official record.

At the cor. point

Set an iron post, 30 ins. long, 2½ ins. diam., 10 ins. in the ground, and in a mound of stone, 5 ft. base to top, with brass cap mkd.

Dependent Resurvey, E. Bdy., T. 6 S., R. 29 E.

Chains

T5S R29E
S36
S 6
T6S
R30E
1957

Deposit original cor. monument alongside the iron post.

Land, mountainous
Soil, rocky, sand, some sandy clay.
Timber, very scattered scrub juniper.
Undergrowth, scattered cat claw, cacti, moderate native grasses.

Dependent Resurvey of a Portion of the West Boundary of T. 6 S., R. 29 E.

Reestablishment of the survey executed by H. Parker in 1955.
Beginning at the ¼ sec. cor. of sec. 12 on the E. bdy. of T. 6 S., R. 28 E., which is monumented with an iron post, 2½ ins. diam., conforming to the record.

North, on the E. bdy. of sec. 12, T. 6 S., R. 28 E.
Over mountainous land; asc. 30 ft.

5.90 Fence, 4 strand barbed wire fence, bears E. and W.

6.665 The ¼ sec. cor. of sec. 7, T. 6 S., R. 29 E., an iron post, 2½ ins. diam., hereinafter described.

8.00 Top of ascent, bears NW. and SE.; desc. NE. slope.

11.28 The witness point on the E. bdy. of sec. 12, an iron post, 2½ ins. diam., conforming to the record.

11.50 Rim of canyon, bears NW. and SE.; desc. 800 ft. abruptly over precipitous ledgy slope facing N. to river.

22.00 Gulch, drains steeply to N, 30° W.; cont. descent over a NW. slope.

35.00 Left bank of the Gila River, a cut bank, 3 ft. high, bears N. 20° E. and SW., thence across the Gila River, flowing SW.

39.20 Right bank of the Gila River, a cut bank, 4 ft. high, bears N. 20° E. and SW. Enter mesquite and willow thicket.

40.00 Point for the cor. of secs. 1 and 12, T. 6 S., R. 28 E.

Set an iron post, 2½ ins. diam., 20 ins. in the ground and in a mound of stone, 4 ft. base, to top of post with brass cap mkd.

T6S
R28E R29E
S 1
S12
1960

Land, rough and mountainous.
Soil, gravelly and rocky and sandy silt in river bottom.
Timber, scattering juniper and mesquite and willow thickets in river bottom.
Undergrowth, ocotillo, catclaw, cacti, sagebrush and spanish dagger.

Dependent Resurvey, Portion of W. Bdy., T. 6 S., R. 29 E.

Chains	
	North, on the E. bdy. of sec. 1, T. 6 S., R. 28 E. Over sandy mesquite and willow covered river bottom.
6.60	The closing cor. of secs. 6 and 7, T. 6 S., R. 29 E., an iron post, 2½ ins. diam., hereinafter described.
11.00	Right bank of the Gila River, a gently sloping gravel bank, bears S. 20° E. and N. 60° W.; thence over the Gila River, flowing S. 20° E.
14.00	Left bank of the Gila River, a cut bank, 3 ft. high, bears S. 30° E. and N. 70° W.; enter mesquite and willow thickets.
16.00	Leave bottom land, bears N. 30° W. and S. 30° E.; asc. along a W. slope.
28.50	Spur, slopes NW.; desc. over N. slope.
36.27	Point selected for the witness cor. of sec. 1, T. 6 S., R. 28 E. Set an iron post, 2½ ins. diam., 12 ins. in the ground and in a mound of stone, 4 ft. base, to top of post, with brass cap mkd. T6S R28E R29E ½ W.C S 1↑ 1960
36.35	The witness cor. of sec. 6, T. 6 S., R. 29 E., an iron post, 2½ ins. diam., hereinafter described.
40.00	True point for the ¼ sec. cor. of sec. 1, T. 6 S., R. 28 E. falls in overflow bottom of the Gila River; there is no remaining evidence of the monument established in the 1955 survey.
43.00	Left bank of the Gila River, bears N. 30° E. and S. 30° W.; thence across the Gila River, flowing S. 30° W.
47.00	Right bank of the Gila River, bears N. 30° E. and S. 30° W.; asc. 400 ft. along a SE. slope.
71.50	Spur, slopes S. 60° E.; desc. 120 ft. over a NE. slope.
78.59	The closing cor. of T. 6 S., R. 28 and 29 E., an iron post, conforming to the record.
	Land, rough and mountainous. Soil, gravelly and rocky and sandy silt in river bottom. Timber, thickets of willows, tamarisk, and mesquite in river bottom.

Dependent Resurvey of the First
Standard Parallel South in Range 29 East

Reestablishment of surveys executed by Philip Contzen in 1895 and W. B. Kimmell in 1914.

Beginning at the closing cor. of Tps. 5 and 6 S., R. 29 E., which is an iron post, 3 ins. diam., conforming to the record of the 1914 survey.

S. 89° 54' W., on the S. bdy of sec. 36.

Over rolling land.

Dependent Resurvey, of the First Standard Parallel South in R. 29 E.

Chains	
4.40	Old State Highway No. 666, a graded gravel road, bears NE. and SW.; desc. 60 ft.
6.13	The standard $\frac{1}{4}$ sec. cor. of sec. 36, an iron post, 1 in. diam., conforming to the record of the 1914 survey.
	N. 89° 58' W., beginning new measurement.
	Desc. a NW. slope.
6.40	Wash, 20 lks. wide, 3 ft. deep, course NE.; asc. 80 ft.
13.70	Bladed road, bears NE. and SW.
16.40	Spur, slopes NE.; desc. NW. slope.
23.70	Wash, 30 lks. wide, 1 ft. deep, course N. 20° E.; asc. E. slope.
33.20	Point for the $\frac{1}{4}$ sec. cor. of sec. 1, T. 6 S., R. 29 E.
	Set an iron post, 30 ins. long, 2 $\frac{1}{2}$ ins. diam., 10 ins. in the ground and in a mound of stone, 4 ft. base, to top of post, with brass cap mkd.
	$\frac{1}{4}$ S 1 T6S R29E 1960
	Cont. ascent over E. slope.
39.94	The standard cor. of secs. 35 and 36, an iron post, 3 ins. diam., conforming to the record.
	Cor. is located under N. and S. fence.
	Land, rolling hills.
	Soil, gravelly light clay and rocky.
	Timber, none.
	Undergrowth, cacti, mesquite, catclaw, scrub cedar.
	S. 89° 59' W., on the S. bdy. of sec. 35.
	Over rolling hills.
3.10	Spur, slopes N.; desc. 160 ft. over NW. slope.
17.90	Wash, 10 lks. wide, 2 ft. deep, course NW.; asc. NE. slope.
24.40	Spur, slopes N., 3 chs. to end; desc. NW. slope.
27.10	Wash, 10 lks. wide, 2 ft. deep, course N.; asc. NE. slope.
33.26	The closing cor. of secs. 1 and 2, T. 6 S., R. 24 E., an iron post, 2 $\frac{1}{2}$ ins. diam., conforming to the record of the 1955 survey.
33.30	Spur, slopes N.; desc. 100 ft. over N. slope.
39.99	The standard $\frac{1}{4}$ sec. cor. of sec. 35, an iron post, 1 in. diam., conforming to the record of the 1914 survey.

Dependent Resurvey, First Standard Parallel South to R. 29 East, T. 6 S.

Chains	
	West, beginning new measurement.
	Desc. 30 ft.
0.90	Wash, 30 lks. wide, 1 ft. deep, course N.; asc. 120 ft. over E. slope.
9.40	Fence, bears N. 10° E. and S. 10° W.
9.70	Spur, slopes N. 20° E.; desc. W. slope.
17.10	Wash, 10 lks. wide, 2 ft. deep, course N.; asc. NE. slope.
24.00	Spur, slopes N.; desc. NW. slope.
27.50	Wash, 10 lks. wide, 2 ft. deep, course N. 10° E.; asc. E. slope.
31.30	Spur, slopes N. 20° E.; desc. 120 ft. to wash.
33.85	The $\frac{1}{4}$ sec. cor. of sec. 2, T. 6 S., R. 29 E., an iron post, 2 $\frac{1}{2}$ ins. diam., conforming to the record of the 1955 survey.
	Cont. descent over W. slope.
39.70	Wash, 60 lks. wide, 2 ft. deep, course N. 10° E.
40.05	True point for the standard cor. of secs. 34 and 35, falls in wash where the cor. could not be monumented.
	Land, rolling hills. Soil, gravelly light clay and rocky. Timber, thinly scattered scrub juniper. Undergrowth, cacti, mesquite and catclaw.
	N. 89° 58' W., on the S. bdy. of sec. 34.
	Over rolling hills; asc. E. slope:
1.00	The original witness standard cor. of secs. 34 and 35, mkd. by the original monument, a malpais stone, 12x10x8 ins., above ground, firmly set and plainly mkd.
	At the point for the cor.
	Set an iron post, 2 $\frac{1}{2}$ ins. diam., 10 ins. in the ground and supported in a mound of stone, 3 ft. base, to top of post, with brass cap mkd.
	T5S R29E
	WSC
	<u>S34 S35</u>
	1960
	1957
	Deposit the original monument alongside the iron post.
	Asc. E. slope.
3.40	Low spur; slopes N.; desc. W. slope.
5.20	Wash, 20 lks. wide, 2 ft. deep, course N. 20° E.; asc. 160 ft. over E. slope.
22.00	Slope changes to a NE. slope.
33.36	The closing cor. of secs. 2 and 3, T. 6 S., R. 29 E., an iron post, 2 $\frac{1}{2}$ ins. diam., conforming to the record of the 1955 survey.

Dependent Resurvey of the First Standard Parallel South in R. 29 E.

Chains	
39.93	<p>The standard $\frac{1}{4}$ sec. cor. of sec. 34, mkd. by the original monument, a malpais stone, 14x8x4 ins., firmly set and plainly mkd., and witnessed by a small mound of stone to the N.</p>
	<p>At the point for the cor.</p>
	<p>Set an iron post, 30 ins. long, 2$\frac{1}{2}$ ins. diam., 6 ins. in the ground to solid rock and in a mound of stone, 3 ft. base, to top of post with brass cap mkd.</p>
	<p>T5S R29E</p>
	<p>S C</p>
	<p>$\frac{1}{4}$ S34</p>
	<p>1960</p>
	<p>1957</p>
	<p>Deposit the original cor. alongside the iron post.</p>
	<p>West, beginning new measurement.</p>
	<p>Asc. 120 ft. over NE. slope.</p>
	<p>Ridge, bears N. 60° E. and S. 20° W.; desc. W. slope.</p>
	<p>The witness standard cor. of secs. 33 & 34, mkd. by the orig. monument, a malpais stone, 12x7x6 ins. firmly set and plainly mkd. with a small mound of stone to N.</p>
	<p>At the point for the witness cor.</p>
	<p>Set an iron post, 30 ins. long, 2$\frac{1}{2}$ ins. diam., 10 ins. in the ground to solid rock and in a mound of stone, 3 ft. base, to top of post, with brass cap mkd.</p>
	<p>T5S R29E</p>
	<p>WSC</p>
	<p>S33 S34</p>
	<p>1960</p>
	<p>1957</p>
	<p>Deposit the original cor. alongside the iron post.</p>
	<p>The witness $\frac{1}{4}$ sec. cor. of sec. 3, mkd. by an iron post, 2$\frac{1}{2}$ ins. diam., set, mkd. and witnessed as described in the official record.</p>
	<p>Desc. 200 ft. over steep rocky W. slope.</p>
	<p>True point for $\frac{1}{4}$ sec. cor. of sec. 3.</p>
	<p>Wash, 30 lks. wide, 3 ft. deep, course N.; asc. NE. slope.</p>
	<p>Spur, slopes N.; desc. over steep W. slope.</p>
	<p>True point for the standard cor. of secs. 33 and 34, falls on steep W. slope where the cor. cannot be monumented.</p>
	<p>Land, rolling hills in E., broken in W. 15 chs.</p>
	<p>Soil, gravelly light clay and rocky.</p>
	<p>Timber, thinly scattered juniper and mesquite.</p>
	<p>Undergrowth, cacti and catclaw.</p>

Dependent Resurvey of the First Standard Parallel South in R. 29 E.

Chains	
	S. 89° 58' W., on the S. bdy. of sec. 33. Over broken land; desc. steep rocky W. slope.
7.50	Wash, 2 chs. wide, 2 ft. deep, course NE.; asc. 480 ft. over steep rocky E. slope.
27.10	Top of ascent, bears NE. and SW.; thence over rolling land.
33.36	The closing cor. of secs. 3 and 4, T. 6 S., R. 29 E., an iron post, 2½ ins. diam., conforming to the record of the 1955 survey.
39.10	Telephone line, bears N. 70° E. and S. 70° W.
39.54	The standard ¼ sec. cor. of sec. 33, mkd. by the original monument, a malpais stone 16x8x4 ins., firmly set and plainly mkd. and witnessed by a small mound of stone to the N. At the point for the cor. Set an iron post, 30 ins. long, 2½ ins. diam., 10 ins. in the ground and in a mound of stone, 4 ft. base, to top of post, with brass cap mkd. T5S R29E S.C. ¼ S33 1960 1957 Deposit the original cor. alongside the iron post. West, beginning new measurement. Over rolling land.
6.00	Spur, slopes N.; desc. 120 ft. over NW. slope.
15.20	Wash, 10 lks. wide, 3 ft. deep, course NE.; asc. 110 ft. over E. slope.
24.60	Spur, slopes N.; desc. 80 ft. over W. slope.
33.93	The ¼ sec. cor. of sec. 4, an iron post, 2½ ins. diam., hereinafter described. Desc. 120 ft. over a W. slope.
37.00	Wash, 20 lks. wide, 2 ft. deep, course N. on curve to W.
37.58	Point selected for the witness standard cor. of secs. 32 and 33. Set an iron post, 30 ins. long, 2½ ins. diam., 4 ins. in the ground to solid rock and in a mound of stone, 4 ft. base, to top of post with brass cap mkd. T5S R29E S.C. W. S32 S33 CROSS 4 1960 1957
38.50	Minor spur, slopes N. 50- E., 1 ch. to end.
39.85	Point for standard cor. of secs. 32 and 33 at proportionate dist.; there is no remaining evidence of the position of the original cor. This point falls on steep N. slope where cor. cannot be monumented.

Dependent Resurvey of the First Standard Parallel South in R. 29 E.

Chains	
	<p>Land, broken. Soil, gravelly light clay and rocky. Timber, thinly scattered scrub juniper and mesquite. Undergrowth, cacti, catclaw and grass.</p>
	<p>West, on the S. bdy. of sec. 32.</p>
	<p>Over broken land; asc. 80 ft.</p>
7.20	<p>Spur, slopes N.; desc. W. slope.</p>
10.40	<p>Wash, 20 lks. wide, 2 ft. deep, course N. 70° E.; asc. 220 ft. over SE. slope.</p>
24.90	<p>Ridge, bears N. 20° E. and S. 20° W.; desc. 60 ft. over NW. slope.</p>
34.19	<p>The closing cor. of secs. 4 and 5, T. 6 S., R. 29 E., an iron post, 2½ ins. diam., hereinafter described.</p>
39.00	<p>Wash, drains N. 20° E.</p>
39.85	<p>Point for the standard ¼ sec. cor. of sec. 32 at proportionate dist.; there is no remaining evidence of the position of the original cor.</p> <p>Set an iron post, 30 ins. long, 2½ ins. diam., 4 ins. in the ground to bedrock and in a mound of stone, 4 ft. base, to top of post, with brass cap mkd.</p> <p style="text-align: center;">T5S R29E S C <u>¼ S32</u></p> <p style="text-align: center;">1960 1957</p>
	<p>Asc. 100 ft. over SE. slope.</p>
53.50	<p>Ridge, bears N. and S.; desc. 160 ft. over a W. slope.</p>
70.30	<p>Wash, 20 lks. wide, 2 ft. deep, course N.; asc. 40 ft. over an E. slope.</p>
74.18	<p>The ¼ sec. cor. of sec. 5, T. 5 S., R. 29 E., an iron post, 2½ ins. diam., hereinafter described.; asc. 40 ft. over E. slope.</p>
79.70	<p>Point for the standard cor. of secs. 31 and 32, at proportionate dist.; there is no remaining evidence of the position of the original cor.</p> <p>Set an iron post, 30 ins. long, 2½ ins. diam., 16 ins. in the ground and in a mound of stone, 3 ft. base, to top of post with brass cap mkd.</p> <p style="text-align: center;">T5S R29E S C <u>S31 S32</u></p> <p style="text-align: center;">1960 1957</p>
	<p>Land, broken. Soil, gravelly light clay and rocky. Timber, thinly scattered scrub juniper and mesquite. Undergrowth, cacti, catclaw and grass.</p>

Dependent Re-survey of the First Standard Parallel South in R. 29 E.

Chains	
	West, on the S. bdy. of sec. 31.
	Over broken land.
5.00	Top of ascent, bears N. and S.; desc. 140 ft. over NW. slope.
17.80	Wash, 10 lks. wide, 1 ft. deep, course N.; asc. 100 ft. over E. slope.
31.00	Top of ascent, bears N. and S.; desc. W. slope.
34.47	The closing cor. of secs. 5 and 6, an iron post, 2½ ins. diam., hereinafter described.
	Desc. 40 ft. over W. slope.
39.85	The standard ¼ sec. cor. of sec. 31, mkd. by the original monument, a malpais stone, 25x18x12 ins.; firmly set and plainly mkd.
	At the point for the cor.
	Set an iron post, 30 ins. long, 2½ ins. diam., 15 ins. in the ground and in a mound of stone, 3 ft. base; to top of post with brass cap mkd.
	T5S R29E S C ¼ S31
	1960 1957
	N. 89° 52' W., beginning new measurement.
	Desc. over W. slope.
3.40	Rim, facing SW., bears NW. and SE.; desc. over precipitous ledges into canyon.
20.00	Gulch, 600 ft. below rim, drains steeply to the NW.; thence along a very steep N. slope.
25.00	Spur, slopes NW.; desc. 400 ft. over NW. slope to the standard Tp. cor.
34.62	The ¼ sec. cor. of sec. 3, T. 6 S., R. 29 E., an iron post, 2½ ins. diam., hereinafter described.
40.42	The standard cor. of T. 5 S., Rs. 28 and 29 E., an iron post, 3 ins. diam., conforming to the record. This iron post is in bad condition and is therefore remonumented.
	At the point for the cor.
	Set an iron post, 30 ins. long, 2½ ins. diam., 10 ins. in the ground and in a mound of stone, 3 ft. base, to top of post with brass cap mkd.
	T5S R28E R29E S36 S31
	1960 1957

Dependent Resurvey of the First Standard Parallel South in R. 29 E.

Chains	<p>From this cor., the $\frac{1}{2}$ sec. cor. of secs. 31 and 36 bears N. $1^{\circ} 00'$ W., 40.00 chs. dist., an iron post, 1 in. diam., conforming to the record of the 1914 survey.</p> <p>Land, rough and broken. Soil, gravelly light clay and rocky. Timber, thinly scattered scrub juniper. Undergrowth, cacti, catalaw and mesquite.</p> <hr/> <p style="text-align: center;">Survey of the Subdivision of T. 6 S., R. 29 E.</p> <hr/> <p>From the cor. of secs. 35 and 36 on the S. bdy. of the Tp., monumented by an iron post, $2\frac{1}{2}$ ins. diam., 10 ins. above ground, and in a small mound of stone, firmly set, mkd. and witnessed as described in the official record.</p> <p>N. $0^{\circ} 01'$ W., bet. secs. 35 and 36;</p> <p>Over rocky mountainous land, through scattered cacti and bunch grass.</p> <p>Asc. 185 ft. over a general S. slope.</p> <p>2.80 Four strand barbed wire fence, bears N. 40° E. and S. 40° W.</p> <p>5.40 Spur, sloping S. 25° W.; desc. 370 ft. over sharp NW. slope.</p> <p>26.90 Wash, 3 chs. wide, 2 ft. deep, drains S. 30° W.; asc. 300 ft. over a SE. slope.</p> <p>40.00 Point for the $\frac{1}{2}$ sec. cor. of secs. 35 and 36.</p> <p>Set an iron post, 30 ins. long, $2\frac{1}{2}$ ins. diam., 10 ins. in the ground, and in a mound of stone, 3 ft. base to top, with brass cap mkd.</p> <p style="text-align: center;">T6S R29E $\frac{1}{2}$ S35 S36 1957</p> <p>Asc. 735 ft. over a general S. slope to sec. cor.</p> <p>48.50 Wash, 2 chs. wide, 2 ft. deep, drains S. 20° W.</p> <p>80.00 Point for the cor. of secs. 25, 26, 35 and 36.</p> <p>Set an iron post, 30 ins. long, $2\frac{1}{2}$ ins. diam., 8 ins. in the ground, and in a mound of stone, 2 ft. base to top, with brass cap mkd.</p> <p style="text-align: center;">T6S R29E S26 S25 S35 S36 1957</p> <p>Land, mountainous. Soil, rocky. Timber, none. Undergrowth, moderate bunch grass and cacti.</p> <hr/> <p>From the cor. of secs. 25, 30, 31 and 36 on the E. bdy. of the Tp., monumented by an iron post, $2\frac{1}{2}$ ins. diam., 10 ins. above ground, firmly set, mkd. and witnessed as described in the official record.</p> <p>N. $89^{\circ} 57'$ W., bet. secs. 25 and 36.</p>
--------	---

Survey, Subdivision, T. 6 S., R. 29 E.

Chains

- Over rough mountainous land, general drainage to the SE.
Desc. 420 ft. over a general SW. slope.
- 14.30 Wash, 30 lks. wide, 2 ft. deep, drains S. 30° W., dim rut road in bottom of wash; asc. 360 ft. over a rocky NE. slope.
- 39.84 Point for the $\frac{1}{4}$ sec. cor. of secs. 25 and 36.
Set an iron post, 30 ins. long, 2½ ins. diam., 10 ins. in the ground, and in a mound of stone, 2 ft. base to top, with brass cap mkd.
T6S R29E
 $\frac{1}{4}$ S25
S36
1957
Asc. 230 ft. over a general rocky NE. slope.
- 51.20 Spur, sloping S. 5° W.; desc. 465 ft. over a rocky general W. slope.
- 69.00 Wash, 20 lks. wide, 2 ft. deep, drains S.; asc. 255 ft. over an E. slope.
- 79.67 The cor. of secs. 25, 26, 35 and 36.
Land, mountainous.
Soil, rocky.
Timber, very scattered juniper.
Undergrowth, scattered cacti and native grasses.
-
- N. 0° 01' W., bet. secs. 25 and 26.
Over rocky mountainous land.
Asc. 75 ft. along SE. slope.
- 7.00 High point of ascent; thence desc. 200 ft. along NE. slope.
- 40.00 Point for the $\frac{1}{4}$ sec. cor. of secs. 25 and 26.
Set an iron post, 30 ins. long, 2½ ins. diam., 8 ins. in the ground, and in a mound of stone, 2 ft. base to top, with brass cap mkd.
T6S R29E
 $\frac{1}{4}$ S26 | S25
1957
Asc. 250 ft. along a SE. slope.
- 56.00 Dividing ridge, bears E. and W.; desc. 245 ft. over a rocky N. slope.
- 56.10 Four strand barbed wire fence, bears E. and W.
- 75.00 Wash, 20 lks. wide, 1 ft. deep, drains W., approximately 6 chs. to main wash; thence S. 30° W. to an earth tank; asc. 15 ft. over a S. slope.
- 80.00 Point for the cor. of secs. 23, 24, 25 and 26.
Set an iron post, 30 ins. long, 2½ ins. diam., 10 ins. in the ground, and in a mound of stone, 3 ft. base, to top, with brass cap mkd.

Survey, Subdivision, T. 6 S., R. 29 E.

Chains

T6S R29E

S23 | S24

S26 | S25

1957

Land, mountainous.
Soil, sandy and rocky.
Timber, very scattered scrub juniper.
Undergrowth, some native grasses.

From the cor. of secs. 19, 24, 25 and 30 on the E. bdy. of the Tp., monumented by an iron post, 2½ ins. diam., 15 ins. above ground, and in a mound of stone, firmly set, mkd. and witnessed as described in the official record.

S, 89° 40' W., bet. secs. 24 and 25.

Over rocky mountainous land.

Asc. 150 ft. along a SE. slope.

- 11.50 High point of ascent; desc. 280 ft. over a rocky NW. slope.
- 12.80 Four strand barbed wire fence, bears N. 20° W. and S. 20° W.
- 26.55 Head of deep draw, draining S. 40° W.; asc. 25 ft. over a SE. slope.
- 38.05 Four strand barbed wire fence, bears N. 60° E. and S. 60° W.
- 39.78 Point for the ¼ sec. cor. of secs. 24 and 25.

Set an iron post, 30 ins. long, 2½ ins. diam., 8 ins. in the ground, and in a mound of stone, 3 ft. base to top, with brass cap mkd.

T6S R29E

¼ S24

S25

1957

- 40.90 Dividing ridge, bears N. 60° E. and S. 60° W.; desc. 510 ft. over a rocky NW. slope to sec. cor.
- 63.65 Wash, 20 lks. wide, 3 ft. deep, drains W.
- 79.55 The cor. of secs. 23, 24, 25 and 26.

Land, mountainous.
Soil, rocky.
Timber, scattered scrub juniper, some pinon.
Undergrowth, scattered cacti, moderate native grasses.

N. 0° 01' W., bet. secs. 23 and 24.

Over high rolling mountainous land.

- 1.00 Spur, sloping E.;
- 6.60 Wash, 20 lks. wide, 2 ft. deep, drains S. 30° W., approximately 20 chs. to earth tank. Asc. 350 ft. over SW. slope.
- 24.55 Dividing ridge, bears N. 50° E. and S. 50° W.; desc. 70 ft. over W. slope of spur,
- 40.00 Point for the ¼ sec. cor. of secs. 23 and 24.

Survey, Subdivision, T. 6 S., R. 29 E.

Chains

Set an iron post, 30 ins. long, $2\frac{1}{2}$ ins. diam., 12 ins. in the ground, and in a mound of stone, 3 ft. base to top, with brass cap mkd.

T6S R29E

$\frac{1}{4}$
S23|S24
1957

Cor. is located on high point of ascent.

Asc. 125 ft. over W. slope of spur.

54.75 Spur, sloping N. 40° W.; desc. 560 ft. over a rocky general NE. slope to sec. cor.

80.00 Point for the cor. of secs. 13, 14, 23 and 24.

Set an iron post, 30 ins. long, $2\frac{1}{2}$ ins. diam., 8 ins. in the ground, and in a mound of stone, 4 ft. base to top, with brass cap mkd.

T6S R29E

S14|S13
S23|S24
1957

From this cor., a bench mark, monumented by a 2 in. brass cap set in concrete, 10 ins. above ground, bears N. $17^\circ 06'$ W., 14.05 chs. dist. mkd. L 40, 1934.

Land, mountainous:

Soil, rocky.

Timber, none.

Undergrowth, scattered cacti and bunch grass.

From the cor. of secs. 13, 18, 19 and 24 on the E. bdy. of the Tp., monumented by an iron post, $2\frac{1}{2}$ ins. diam., 12 ins. above ground, and in a mound of stone, firmly set, mkd. and witnessed as described in the official record.

From this cor., a bench mark, monumented by a 3 in. brass cap set in solid stone, on N. edge of small wash, draining S. 40° W., bears N. $24^\circ 08'$ W., 9.17 chs. dist.

N. $89^\circ 43'$ W., bet. secs. 13 and 24.

Over mountainous land.

Desc. 180 ft. over a rocky general W. slope.

10.50 Base of descent, bears N. and SW.

10.60 Old State highway No. 666, bears N. and S. 40° W.

22.50 Wash, 40 lks. wide, 3 ft. deep, drains N. 20° E.; asc. 120 ft. over a rocky SE. slope.

39.81 Point for the $\frac{1}{4}$ sec. cor. of secs. 13 and 24.

Set an iron post, 30 ins. long, $2\frac{1}{2}$ ins. diam., 8 ins. in the ground, and in a mound of stone, 3 ft. base to top, with brass cap mkd.

T6S R29E

$\frac{1}{4}$ S13
S24
1957

Asc. 350 ft. over a SE. slope.

Survey, Subdivision, T. 6 S., R. 29 E.

Chains	
50.35	Wash, 30 lks. wide, 3 ft. deep, drains S. 30° W., approximately 20 chs. to earth tank.
51.45	Wash, 30 lks. wide, 3 ft. deep, drains N. 50° E., approximately 4 chs. to above wash.
58.05	Old State Highway No. 666, bears N. 50° W. and S. 30° E.
79.62	The cor. of secs. 13, 14, 23 and 24.
	<p>Land, mountainous. Soil, rocky. Timber, scattered scrub juniper. Undergrowth, moderate cacti and bunch grass.</p>
	<p>N. 0° 01' W., bet. secs. 13 and 14. Over mountainous land. Desc. 190 ft. over a general N. slope.</p>
10.70	Wash, drains E.; asc. 105 ft. over a rocky S. slope.
10.80	Old State Highway No. 666, bears E. and W.
24.60	Spur, sloping S. 65° E.; desc. 345 ft. over a general NE. slope.
40.00	Point for the $\frac{1}{4}$ sec. cor. of secs. 13 and 14.
	<p>Set an iron post, 30 ins. long, 2½ ins. diam., 8 ins. in the ground, and in a mound of stone, 3 ft. base to top, with brass cap mkd.</p> <p style="text-align: center;">T6S R29E $\frac{1}{4}$ S14 S13 1957</p> <p>Desc. 60 ft. over a N. slope.</p>
42.40	Wash, 20 lks. wide, 2 ft. deep, drains N. 70° W.; asc. 125 ft. over a rocky general SE. slope.
52.00	Spur, sloping N. 30° W.; desc. 395 ft. along a general NE. slope.
80.00	Point for the cor. of secs. 11, 12, 13 and 14.
	<p>Set an iron post, 30 ins. long, 2½ ins. diam., 10 ins. in the ground, and in a mound of stone, 3 ft. base to top, with brass cap mkd.</p> <p style="text-align: center;">T6S R29E S11 S12 S14 S13 1957</p> <p>Land, mountainous. Soil, rocky. Timber, scattered scrub juniper. Undergrowth, scattered cacti, moderate native grasses.</p>
	<p>From the cor. of secs. 7, 12, 13 and 18, an iron post, 2½ ins. diam., conforming to the record.</p> <p>S. 89° 58' W., bet. secs. 12 and 13. Over mountainous land; asc. 40 ft. over NE. slope.</p>

Survey, Subdivision, T. 6 S., R. 29 E.

Chains	
11.10	Spur, slopes NW.; desc. 180 ft. over W. slope.
20.50	Wash in bottom of ravine, 60 lks. wide, 3 ft. deep, drains N. 30° W.; asc. 100 ft. over NE. slope.
31.30	Spur, slopes N. 30° W.
33.20	Old State Highway No. 666, a graded gravel road, bears N. 50° W. and S. 20° E.; desc. 120 ft. over W. slope to wash.
39.79	Point for the $\frac{1}{4}$ sec. cor. of secs. 12 and 13. Set an iron post, 30 ins. long, 2½ ins. diam., 10 ins. in the ground and in a mound of stone, 3 ft. base, to top of post with brass cap mkd.
	T6S R29E $\frac{1}{4}$ S12 S13 1960 1956
40.40	Wash, 1 ch. wide, 3 ft. deep, course NW.; asc. 40 ft. along N. slope.
47.30	Spur, slopes NW.; desc. 100 ft. over W. slope.
63.60	Wash, 1 ch. wide, 2 ft. deep, drains N. 20° W.; asc. 200 ft. over NE. slope.
79.57	The cor. of secs. 11, 12, 13 and 14. Land, mountainous. Soil; light clay and rocky; Timber; thinly scattered scrub juniper. Undergrowth, moderate cacti, catclaw and grass.
	N. 0° 01' E., bet. secs. 11 and 12. Over mountainous land; desc. 90 ft. over NE. slope.
7.80	Base of NE. slope, thence along a W. slope.
20.60	Slope changes to N. slope; desc. 200 ft.
40.02	Point for the $\frac{1}{4}$ sec. cor. of secs. 11 and 12. Set an iron post, 30 ins. long, 2½ ins. diam., 16 ins. in the ground and in a mound of stone, 3 ft. base, to top of post with brass cap mkd.
	T6S R29E $\frac{1}{4}$ S11 S12 1960 1956
	Desc. 100 ft. over N. slope to wash.
40.34	Fence, bears N. 60° E. and S. 60° W.
50.90	Wash, 1 ch. wide, 4 ft. deep, course N. 60° W.; asc. 140 ft. over W. slope.
58.10	Top of ascent; desc. 60 ft. over gentle N. slope.
80.04	The cor. of secs. 1, 2, 11 and 12, mkd. by an iron post, 2½ ins. diam. conforming to the record.

Survey, Subdivision, T. 6 S., R. 29 E.

Chains	
	<p>Land, mountainous. Soil, light clay and rocky. Timber, none. Undergrowth, moderate cacti, catclaw and grass.</p>
	<p>From the cor. of secs. 1, 6, 7 and 12 on the E. bdy. of the Tp. mkd. by an iron post, 2½ ins. diam., conforming to the record.</p> <p>S. 89° 48' W., bet. secs. 1 and 12.</p> <p>Over broken land; desc. 120 ft. over W. slope.</p>
9.80	Wash, drains N. 20° W.; thence along N. slope.
20.00	Spur, slopes N.; desc. 120 ft. over NW. slope.
31.00	Wash, in bottom of ravine, course N. 10° E.; asc. 90 ft.
39.26	Point for the ¼ sec. cor. of secs. 1 and 12.
	<p>Set an iron post, 30 ins. long, 2½ ins. diam., 15 ins. in the ground and in a mound of stone, 3 ft. base to top of post with brass cap mkd.</p> <p style="text-align: center;">T6S R29E ¼ S 1 S12 1960 1956</p>
	Asc. 40 ft. over rolling land.
44.00	The cor. of fences bearing N. 70° W. and S.
47.40	Old State Highway No. 666, a graded gravel road, bears N. 20° E. and S. 20° W.
50.30	Fence, bears N. and S.
60.70	Small wash, drains N. about 8 chs. to a stock water reservoir.
79.26	The cor. of secs. 1, 2, 11 and 12.
	<p>Land, rolling and broken. Soil, light clay and rocky. Timber, none. Undergrowth, moderate cacti, catclaw and grass.</p>
	<p>From the true point for the cor. of secs. 34 and 35 on the S. bdy. of the Tp. which is witnessed W. 2.00 chs. by an iron post, set, mkd. and witnessed as described in the official record.</p> <p>N. 0° 01' W., bet. secs. 34 and 35.</p> <p>Over broken mountainous land.</p> <p>Desc. 35 ft. over NE. slope of spur.</p>
7.75	Wash, 15 lks. wide, 1 ft. deep, drains S. 30° W.; asc. 130 ft. over a rocky SE. slope.
23.00	High point of ascent on SW. slope of spur, sloping S. 30° W.; desc. 135 ft. over a rocky NW. slope.

Survey, Subdivision, T. 6 S., R. 29 E.

Chains

- 37.20 Wash, 30 lks. wide, 2 ft. deep, drains S. 70° W.; approximately 8 chs. to earth tank; asc. 30 ft. over a rocky general SE. slope.
- 40.00 Point for the $\frac{1}{4}$ sec. cor. of secs. 34 and 35.
- Set an iron post, 30 ins. long, $2\frac{1}{2}$ ins. diam., 8 ins. in the ground, and in a mound of stone, 3 ft. base to top, with brass cap mkd.
- T6S R29E
 $\frac{1}{4}$
S34 | S35
1957
- Asc. 590 ft. over SE. slope.
- 73.10 Four strand barbed wire fence, bears N. 40° E. and S. 40° W.
- 80.00 Point for the cor. of secs. 26, 27, 34 and 35.
- Set an iron post, 30 ins. long, $2\frac{1}{2}$ ins. diam., 10 ins. in the ground, and in a mound of stone, 3 ft. base to top, with brass cap mkd.
- T6S R29E
S27 | S26
S34 | S35
1957
- Land, mountainous.
Soil, rocky.
Timber, scattered juniper and pinon.
Undergrowth, scattered cacti, soap weed and some bunch grass.
-
- From the cor. of secs. 25, 26, 35 and 36.
- S. 89° 53' W., bet. secs. 26 and 35.
- Over mountainous land.
- Asc. 265 ft. over SE. slope of rocky spur.
- 9.15 Spur, sloping S.; desc. 350 ft. over a rocky W. slope.
- 15.40 Wash, 20 lks. wide, 3 ft. deep, drains S. 10° E.; asc. 340 ft. over an E. slope.
- 21.80 Spur, sloping S.; desc. 165 ft. over a rocky W. slope.
- 34.50 Slope changes to NW.
- 40.08 Point for the $\frac{1}{4}$ sec. cor. of secs. 26 and 35.
- Set an iron post, 30 ins. long, $2\frac{1}{2}$ ins. diam., 18 ins. in the ground, and in a mound of stone, 2 ft. base to top, with brass cap mkd.
- T6S R29E
 $\frac{1}{4}$
S26
S35
1957
- Cor. is located on spur sloping S. 10° W.
- Desc. 300 ft. over a general NW. slope.
- 55.10 Draw, drains S. 20° W.; asc. 90 ft. over a general E. slope.

Survey, Subdivision, T. 6 S., R. 29 E.

Chains	
69.85	Four strand barbed wire fence, bears N. 30° E. and S. 30° W. on spur, sloping SW.; desc. 55 ft. over a rocky NW. slope.
80.15	The cor. of secs. 26, 27, 34 and 35. Land, mountainous. Soil, rocky. Timber, scattered juniper. Undergrowth, moderate cacti and greasewood.
	S. 89° 58' W., bet. secs. 27 and 34. Over mountainous land; asc. 40 ft.
8.00	Top of ascent on point of spur from N. 35° E.; desc. 250 ft. over a rocky NW. slope.
9.00	Wash, 10 lks. wide, 2 ft. deep, drains N. 40° W.
29.25	Wash, 30 lks. wide, 3 ft. deep, drains N. 45° W.; asc. 140 ft. over a rocky NE. slope.
38.00	Spur, sloping N. 40° W.
39.79	Point for the $\frac{1}{4}$ sec. cor. of secs. 27 and 34. Set an iron post, 30 ins. long, 2½ ins. diam., 4 ins. in the ground to bedrock, and in a mound of stone, 4 ft. base to top, with brass cap mkd.
	T6S R29E $\frac{1}{4}$ S27 S34 1957
	Thence over rolling land; desc. 50 ft. over SW. slope.
42.10	Wash, 20 lks. wide, 2 ft. deep, drains N. approximately 8 chs. into main wash, thence N. 45° W.; asc. 95 ft. over a rocky general NE. slope.
50.60	Spur, sloping N. 20° W., thence over broken land.
60.05	Wash, 15 lks. wide, 2 ft. deep, drains N. 30° W.
74.10	Four strand barbed wire fence, bears N. and S.
79.57	The cor. of secs. 27, 28, 33 and 34, monumented by an iron post, 2½ ins. diam., 15 ins. above ground, and in a mound of stone, firmly set, mkd. and witnessed as described in the official record. Land, mountainous. Soil, rocky. Timber, scattered juniper. Undergrowth, scattered cacti and bunch grass, some soap weed.
	From the cor. of secs. 26, 27, 34 and 35. N. 0° 01' W., bet. secs. 26 and 27. Over mountainous land. Asc. 135 ft. over a rocky SE. slope.

BOOK 4617

Survey, Subdivision, T. 6 S., R. 29 E.

Chains	
7.70	Dividing ridge, bears N. 50° E. and S. 50° W.; desc. 70 ft. over a rocky NW. slope.
14.15	Wash, 30 lks. wide, 2 ft. deep, drains N. 50° W.
17.75	Four strand barbed wire fence, bears N. 50° W. and S. 50° E.; asc. 245 ft. over a rocky S. slope.
28.00	Spur, sloping W.; desc. 340 ft. over a rocky N. slope.
40.00	<p>Point for the $\frac{1}{4}$ sec. cor. of secs. 26 and 27.</p> <p>Set an iron post, 30 ins. long, 2½ ins. diam., 15 ins. in the ground, and in a mound of stone, 3 ft. base to top, with brass cap mkd.</p> <p style="text-align: center;">T6S R29E S27 S26 1957</p>
41.50	Small wash, drains W.; asc. 530 ft. over a rocky S. slope.
43.00	Rut road to stockmen's tank, bears N. 60° E. and S. 60° W.
69.15	Spur, sloping W.; desc. 50 ft. over a rocky NE. slope.
76.45	Spur, sloping N. 30° W.
80.00	<p>Point for the cor. of secs. 22, 23, 26 and 27.</p> <p>Set an iron post, 30 ins. long, 2½ ins. diam., 16 ins. in the ground, and in a mound of stone, 3 ft. base to top, with brass cap mkd.</p> <p style="text-align: center;">T6S R29E S22 S23 S27 S26 1957</p>
	<p>Land, mountainous.</p> <p>Soil, rocky.</p> <p>Timber, very scattered scrub juniper, some pinon.</p> <p>Undergrowth, moderate cacti, some bunch grass.</p>
	<p>From the cor. of secs. 23, 24, 25 and 26.</p> <p>S. 89° 51' W., bet. secs. 23 and 26.</p> <p>Over mountainous land:</p>
	Desc. 210 ft. over a rocky W. slope.
7.50	Wash, 40 lks. wide, 3 ft. deep, drains S.
9.00	Thence asc. 90 ft. over a rocky general SE. slope.
40.07	<p>Point for the $\frac{1}{4}$ sec. cor. of secs. 23 and 26.</p> <p>Set an iron post, 30 ins. long, 2½ ins. diam., 12 ins. in the ground, and in a mound of stone, 3 ft. base to top, with brass cap mkd.</p>

Survey, Subdivision, T. 6 S., R. 29 E.

Chains	
	<p style="text-align: center;">T6S R29E $\frac{1}{4}$ $\frac{S23}{S26}$ 1957</p> <p>Asc. 100 ft. over SE. slope.</p>
64.75	Dividing ridge, bears N. 50° E. and S. 50° W.; desc. 105 ft. over a rocky NW. slope.
80.13	The cor. of secs. 22, 23, 26 and 27.
	<p>Land, mountainous. Soil, rocky. Timber, scattered juniper and pinon. Undergrowth, scattered cacti, moderate native grasses.</p>
	<p>S. 89° 58' W., bet. secs. 22 and 27.</p> <p>Over mountainous land.</p>
0.15	Wash, 10 lks. wide, 1 ft. deep, drains N. 35° W.; asc. 20 ft. over rocky NE. slope.
4.90	Spur, sloping N. 10° W.; desc. 285 ft. over rocky W. slope.
38.10	Old State Highway No. 666, bears N. 60° E. and S. 60° W.; desc. 75 ft. over W. slope.
39.88	Point for the $\frac{1}{4}$ sec. cor. of secs. 22 and 27.
	Set an iron post, 30 ins. long, 2½ ins. diam., 20 ins. in the ground, and in a mound of stone, 3 ft. base to top, with brass cap mkd.
	<p style="text-align: center;">T6S R29E $\frac{1}{4}$ $\frac{S22}{S27}$ 1957</p>
	Desc. 350 ft. over rocky W. slope.
43.60	Rut road, bears N. 20° W. and S. 10° E.
62.00	Wash, 30 lks. wide, 2 ft. deep, drains N. 10° W.; asc. 105 ft. over a rocky E. slope.
70.70	Spur, sloping N.; desc. 100 ft. over a rocky W. slope.
79.75	The cor. of secs. 21, 22, 27 and 28, monumented by an iron post, 2½ ins. diam., 10 ins. above ground, and in a mound of stone, firmly set, mkd. and witnessed as described in the official record.
	<p>Land, mountainous. Soil, rocky. Timber, very scattered scrub juniper, some pinon. Undergrowth, scattered cacti, some greasewood, moderate native grasses.</p>
	<p>From the cor. of secs. 22, 23, 26 and 27.</p> <p>N. 0° 01' W., bet. secs. 22 and 23.</p> <p>Over mountainous land.</p> <p>Desc. 255 ft. over a rocky NE. slope.</p>

Survey, Subdivision, T. 6 S., R. 29 E.

<p>Chains</p> <p>11.10</p> <p>16.00</p> <p>19.50</p> <p>30.20</p> <p>33.00</p> <p>40.00</p> <p>44.65</p> <p>61.50</p> <p>77.70</p> <p>80.00</p> <p>17.15</p> <p>34.40</p> <p>40.06</p>	<p>Wash, 10 lks. wide, 2 ft. deep, drains N. 50° W.</p> <p>Thence asc. 45 ft. over rocky SW. slope.</p> <p>Spur, sloping N. 50° W.; desc. NE. slope.</p> <p>Old State Highway No. 666, bears N. 30° E. and S. 30° W.</p> <p>Same road, bears N. 30° W. and S. 30° E.</p> <p>Point for the ¼ sec. cor. of secs. 22 and 23.</p> <p>Set an iron post, 30 ins. long, 2½ ins. diam., 10 ins. in the ground, and in a mound of stone, 2 ft. base to top, with brass cap mkd.</p> <p style="text-align: center;">T6S R29E ¼ S22 S23 1957</p> <p>Cont. over broken land.</p> <p>Old State Highway No. 666, bears N. 70° E. and S. 70° W.; desc. 475 ft. over broken NW. slope.</p> <p>Wash, 20 lks. wide, 1 ft. deep, drains N. 70° W.; asc. 375 ft. over rocky SE. slope.</p> <p>Dividing ridge, bears E. and W.; desc. 35 ft. over a rocky broken N. slope.</p> <p>Point for the cor. of secs. 14, 15, 22 and 23.</p> <p>Set an iron post, 30 ins. long, 2½ ins. diam., 10 ins. in the ground, and in a mound of stone, 2 ft. base to top, with brass cap mkd.</p> <p style="text-align: center;">T6S R29E S15 S14 S22 S23 1957</p> <p>Land, mountainous. Soil, rocky. Timber, scattered scrub juniper, some pinon. Undergrowth, scattered cacti, greasewood, some soap weed, moderate native grasses.</p> <hr/> <p>From the cor. of secs. 13, 14, 23 and 24.</p> <p>S. 89° 53' W., bet. secs. 14 and 23.</p> <p>Over mountainous land.</p> <p>Asc. 115 ft. over a broken NE. slope.</p> <p>Spur, sloping N. 25° W.; desc. 175 ft. over a rocky SW. slope.</p> <p>Old State Highway No. 666, bears N. 60° E. and S. 60° W.</p> <p>Point for the ¼ sec. cor. of secs. 14 and 23.</p> <p>Set an iron post, 30 ins. long, 2½ ins. diam., 20 ins. in the ground, and in a mound of stone, 2 ft. base to top, with brass cap mkd.</p>
--	--

Survey, Subdivision, T. 6 S., R. 29 E.

Chains	
	<p style="text-align: center;">T6S R29E $\frac{1}{4}$ S14 S23 1957</p>
	Desc. 185 ft. over broken SW. slope.
56.65	Wash, 10 lks. wide, 2 ft. deep, drains N. 30° W.; asc. 170 ft. over a broken NE. slope.
80.11	The cor. of secs. 14, 15, 22 and 23. Land, mountainous. Soil, rocky. Timber, very scattered scrub juniper, some pinon. Undergrowth, scattered cacti, moderate native grasses.
	S. 89° 59' W., bet. secs. 15 and 22. Over mountainous land. Asc. 40 ft. over NE. slope.
6.85	Spur, sloping N. 50° W.; desc. 80 ft. over rocky W. slope.
39.93	Point for the $\frac{1}{4}$ sec. cor. of secs. 15 and 22. Set an iron post, 30 ins. long, 2½ ins. diam., 6 ins. in the ground to bedrock, and in a mound of stone, 4 ft. base to top, with brass cap mkd.
	<p style="text-align: center;">T6S R29E $\frac{1}{4}$ S15 S22 1957</p>
	Desc. 370 ft. over a SW. slope to sec. cor.
63.95	Wash, 40 lks. wide, 3 ft. deep, drains N. 30° W.
70.20	Spur, sloping N. 10° W.
74.30	Wash, 50 lks. wide, 3 ft. deep, drains N., with rut road through wash channel.
79.86	The cor. of secs. 15, 16, 21 and 22, monumented by an iron post, 2½ ins. diam., 15 ins. above ground, and in a mound of stone, firmly set, mkd. and witnessed as described in the official record. Land, mountainous. Soil, rocky. Timber, scattered scrub juniper, some pinon. Undergrowth, scattered cacti, moderate native grasses.
	From the cor. of secs. 14, 15, 22 and 23. N. 0° 01' W., bet. secs. 14 and 15. Over mountainous land. Desc. 315 ft. over a broken N. slope.
15.05	Wash, 30 lks. wide, 3 ft. deep, drains W.; asc. 190 ft. over a rocky S. slope.

Survey, Subdivision, T. 6 S., R. 29 E.

Chains	
26.15	Spur, sloping N. 40° W.; desc. 45 ft. over a rocky NE. slope.
27.05	Four strand barbed wire fence, bears E. and W.
36.40	Wash, 15 lks. wide, 3 ft. deep, drains N. 40° W.; asc. 45 ft. over a rocky SW. slope.
40.00	Point for the 1/2 sec. cor. of secs. 14 and 15. Set an iron post, 30 ins. long, 2 1/2 ins. diam., 8 ins. in the ground, and in a mound of stone, 3 ft. base to top, with brass cap mkd.
	T6S R29E 1/2 S15 S14 1957
	Along steep hillside, facing W.
66.00	Wash, drains steeply to W.
76.00	Spur, slopes NW.; desc. 110 ft. over NE. slope.
80.00	Point for the cor. of secs. 10, 11, 14 and 15. Set an iron post, 2 1/2 ins. diam., 10 ins. in the ground and in a mound of stone, 3 ft. base, to top of post with brass cap mkd.
	T6S R29E S10 S11 S15 S14 1960 1956
	Land, broken. Soil, light clay and rocky. Timber, none. Undergrowth, moderate cacti, catclaw and grass.
	From the cor. of secs. 11, 12, 13 and 14. S. 89° 46' W., bet. secs. 11 and 14.
	Over mountainous land; asc. 280 ft. over NE. slope.
19.60	Spur, slopes NW.; desc. 400 ft. over W. slope.
40.08	The point for 1/2 sec. cor. of secs. 11 and 14 falls in a wash, course N. 20° W., where the cor. cannot be monumented.
40.38	Point selected for the witness cor. of secs. 11 and 14. Set an iron post, 30 ins. long, 2 1/2 ins. diam., 6 ins. in the ground to solid rock and supported in a mound of stone, 4 ft. base, to top of post with brass cap mkd.
	T6S R29E 1/2 S11 W S14 C 1960 1956

Survey, Subdivision, T. 6 S., R. 29 E.

Chains	
	Asc. 440 ft. over NE. slope.
58.70	Spur, projects NW.; desc. 200 ft. over SW. slope.
69.10	Rocky drain in bottom of ravine, course NW.; asc. 200 ft. over NE. slope.
80.16	The cor. of secs. 10, 11, 14 and 15.
	Land, mountainous. Soil, light clay and rocky. Timber, thinly scattered scrub juniper. Undergrowth, moderate cacti, catclaw and grass.
	N. 89° 48' W., bet. secs. 10 and 15.
	Over mountainous land; asc. 20 ft.
2.50	Spur, slopes NW.; desc. 120 ft. over W. slope.
8.70	Wash, drains N. 30° W.; asc. 100 ft.
18.10	Spur, slopes N.; desc. 200 ft. over W. slope.
26.80	Wash, drains N.; asc. 140 ft. over E. slope.
36.70	Spur, slopes N. 20° W.
39.98	Point for the $\frac{1}{2}$ sec. cor. of secs. 10 and 15.
	Set an iron post, 30 ins. long, 2 $\frac{1}{2}$ ins. diam., 4 ins. in the ground to solid rock and supported in a mound of stone, 4 ft. base, to top of post with brass cap mkd.
	T6S R29E S10 $\frac{1}{2}$ S15 1960 1957
	Desc. 180 ft. over SW. slope.
49.90	Wash, drains N. 60° W.; asc. 60 ft.
58.80	Spur, slopes N. 30° W.; desc. 140 ft.
66.10	Wash, drains N. 20° W.; asc. 140 ft.
75.30	Spur, slopes N.; thence over rolling top of spur.
79.97	The cor. of secs. 9, 10, 15 and 16, mkd. by an iron post, 2 $\frac{1}{2}$ ins. diam., conforming to the record.
	Land, mountainous. Soil, light clay and rocky. Timber, none. Undergrowth, moderate cacti, catclaw and grass.

Survey, Subdivision, T. 6 S., R. 29 E.

Chains

From the cor. of secs. 10, 11, 14 and 15.

N. 0° 05' E., bet. secs. 10 and 11.

Over broken land; desc. 280 ft. over steep NE. slope.

11.30 Wash in bottom of ravine, drains NW.; asc. 160 ft. over SW. slope.

18.80 Slope changes to W. slope.

30.60 Desc. 240 ft. over N. slope.

40.17 Point for the $\frac{1}{4}$ sec. cor. of secs. 10 and 11.

Set an iron post, 30 ins. long, 2½ ins. diam., 16 ins. in the ground and in a mound of stone, 3 ft. base, to top of post with brass cap mkd.

T6S R29E

$\frac{1}{4}$

S10 | S11

1960

1957

Desc. 20 ft.

41.30 Wash, drains NW.; desc. 160 ft.

53.90 Wash, drains NE.; asc. 40 ft.

63.00 Top of ascent; desc. 80 ft. over N. slope.

80.35 The cor. of secs. 2, 3, 10 and 11, an iron post, 2½ ins. diam., conforming to the record.

Land, broken.

Soil, light clay and rocky.

Timber, none.

Undergrowth, moderate cacti, catclaw and grass.

From the cor. of secs. 32 and 33 on the S. bdy. of the Tp., monumented by an iron post, 2½ ins. diam., 10 ins. above ground, and in a mound of stone, firmly set, mkd. and witnessed as described in the official record.

N. 0° 02' W., bet. secs. 32 and 33.

Over rolling land.

Desc. 5 ft. over a gentle N. slope.

6.00 Wash, 10 lks. wide, 2 ft. deep, drains W.; asc. 350 ft. over a rocky S. slope.

10.00 Wash, 10 lks. wide, 2 ft. deep, drains S. 20° W.

13.40 Wash, 10 lks. wide, 1 ft. deep, drains S. 15° W., slope changes to SW.

31.50 Rut road, bears E. and W.

40.00 Point for the $\frac{1}{4}$ sec. cor. of secs. 32 and 33.

Survey, Subdivision, T. 6 S., R. 29 E.

Chains

Set an iron post, 30 ins. long, 2½ ins. diam., 8 ins. in the ground, and in a mound of stone, 4 ft. base to top, with brass cap mkd.

T6S R29E

¼
S32|S33

1957

Cor. is located on a rocky ridge, bears E. and W.

Desc. 225 ft. over a rocky N. slope.

52.00 Wash; 15 lks. wide; 2 ft. deep, drains W.; asc. 475 ft. over a rocky S. slope.

53.40 Four strand barbed wire fence, bears E. and W.

54.60 Rut road, bears N. 70° W. and S. 80° E.

60.00 Rut road, bears N. 65° W. and S. 30° E.

71.15 Single pole, single cross-bar, four wire telephone line, bears N. 45° E. and S. 45° W.

76.30 Old State Highway No. 666, bears N. 70° E. and W.

80.00 Point for the cor. of secs. 28, 29, 32 and 33.

Set an iron post, 30 ins. long, 2½ ins. diam., 10 ins. in the ground, and in a mound of stone, 4 ft. base to top, with brass cap mkd.

T6S. R29E

S29|S28

S32|S33

1957

Land, rolling.

Soil, rocky.

Timber, none

Undergrowth, moderate cacti, catclaw, sage and native grasses.

From the cor. of secs. 27, 28, 33 and 34 on the third meridional line, monumented by an iron post, 2½ ins. diam., 10 ins. above ground, and in a mound of stone, firmly set, mkd. and witnessed as described in the official record.

S. 89° 51' W., bet. secs. 28 and 33.

Over mountainous land.

Desc. 375 ft. over a rocky NW. slope.

18.00 Rim, 50 ft. high, facing NW., with yellow rock formation, extending around point of spur; cont. to desc. 310 ft. over NW. slope.

37.00 Wash, 10 lks. wide, 2 ft. deep, drains S. 15° W.; asc. 20 ft. over a rocky SE. slope.

39.90 Point for the ¼ sec. cor. of secs. 28 and 33.

Set an iron post, 30 ins. long, 2½ ins. diam., 10 ins. in the ground, and in a mound of stone, 3 ft. base to top, with brass cap mkd.

Survey, Subdivision, T. 6 S., R. 29 E.

Chains	
	<p style="text-align: right;">T6S R29E $\frac{1}{2}$ S28 S33 1957</p>
	Asc. 30 ft. over SE. slope.
45.00	Spur, sloping S. 10° E.; desc. 80 ft. over a rocky NW. slope.
49.00	Wash, 10 lks. wide, 2 ft. deep, drains S. 10° E.; asc. 50 ft. over rocky E. slope.
53.00	Spur, sloping S.; desc. 50 ft. over a rocky W. slope.
60.00	Wash, 10 lks. wide, 1 ft. deep, drains S.; asc. 250 ft. over a rocky SE. slope.
70.00	Single pole, single cross-bar, four wire telephone line, bears N. 35° E. and S. 35° W.
70.40	Old State Highway No. 666, bears N. and S. 60° W.
79.80	The cor. of secs. 28, 29, 32 and 33.
	<p>Land, mountainous. Soil, rocky. Timber, very scattered scrub juniper. Undergrowth, moderate cacti, sage and native grasses, some catclaw.</p>
	<p>From the cor. of secs. 28, 29, 32 and 33. N. 0° 02' W., bet. secs. 28 and 29. Over mountainous land. Asc. 205 ft. over a rocky S. slope.</p>
8.50	Spur, sloping W.; desc. 385 ft. over a rocky NE. slope.
39.00	Wash, 20 lks. wide, 2 ft. deep, drains N. 40° W.; asc. 10 ft. over rocky W. slope of spur.
40.00	Point for the $\frac{1}{2}$ sec. cor. of secs. 28 and 29. Set an iron post, 30 ins. long, 2½ ins. diam., 12 ins. in the ground, and in a mound of stone, 4 ft. base to top, with brass cap mkd.
	<p style="text-align: right;">T6S R29E $\frac{1}{2}$ S29 S28 1957</p>
	Asc. 95 ft. along W. slope of spur.
40.15	Rut road, bears N. 50° W. and S. 65° E.
56.00	Top of ascent on W. slope of spur, from S. 35° E.; desc. 80 ft. over rocky NE. slope.
65.30	Wash, 10 lks. wide, 2 ft. deep, drains W.; asc. 190 ft. over rocky S. slope.
77.70	Spur, sloping N. 40° W.; desc. 15 ft. over a rocky NE. slope.
80.00	Point for the cor. of secs. 20, 21, 28 and 29. Set an iron post, 30 ins. long, 2½ ins. diam., 8 ins. in the ground, and in a mound of stone, 3 ft. base to top, with brass cap mkd.

Survey, Subdivision, T. 6 S., R. 29 E.

Chains

T6S R29E

S21 | S20

S29 | S28

1957

Land, mountainous.
Soil, rocky.
Timber, none.
Undergrowth, moderate cacti, sage, native grasses, some catclaw.

From the cor. of secs. 21, 22, 27 and 28 on the third meridional line, monumented by an iron post, 2½ ins. diam., 15 ins. above ground, and in a mound of stone, firmly set, mkd. and witnessed as described in the official record.

N. 89° 59' W., bet. secs. 21 and 28.

Over mountainous land.

Desc. 345 ft. over a rocky W. slope to the ¼ sec. cor.

5.50 Wash, 10 lks. wide, 2 ft. deep, drains N. 30° W.

11.75 Spur, sloping N.

16.25 Wash, 15 lks. wide, 3 ft. deep, drains N. 35° E., approximately 5 chs. thence N.

24.75 Spur, sloping N.

39.30 Single pole, single cross-bar, four wire telephone line, bears N. 10° W. and S. 10° E.

39.86 Point for the ¼ sec. cor. of secs. 21 and 28.

Set an iron post, 30 ins. long, 2½ ins. diam., 10 ins. in the ground, and in a mound of stone, 3 ft. base to top, with brass cap mkd.

T6S R29E

S21

¼ S28

1957

Desc. 20 ft. over W. slope.

41.80 Wash, 20 lks. wide, 2 ft. deep, drains N.; asc. 250 ft. over a rocky E. slope.

48.65 Spur, sloping N.; desc. 310 ft. over a rocky W. slope.

63.50 Wash, 10 lks. wide, 3 ft. deep, drains N. 40° W.; asc. 60 ft. over rocky NE. slope.

65.90 Four strand barbed wire fence, with steel posts, bears N. 15° W. and S. 15° E.

74.20 Spur, sloping N. 35° W.; desc. 35 ft. over a rocky SW slope.

77.00 Wash, 10 lks. wide, 2 ft. deep, drains N. 30° W.

79.72 The cor. of secs. 20, 21, 28 and 29.

Land, mountainous.
Soil, rocky.
Timber, very scattered scrub juniper, some pinon.
Undergrowth, moderate cacti, sage, catclaw and native grasses.

Survey, Subdivision, T₆S., R₂₉E.

Chains	
	N. 0° 11' W., bet. secs. 20 and 21.
	Over rocky broken land; desc. 240 ft. over N. slope.
10.10	Wash, drains N. 70° W.; asc. 130 along SW. slope.
20.20	Spur, slopes W.; desc. 60 ft. over NW. slope.
25.60	Wash, 10 lks. wide, 2 ft. deep, drains W.; asc. 280 ft. over steep SW. slope.
40.08	Point for the $\frac{1}{4}$ sec. cor. of secs. 20 and 21.
	Set an iron post, 30 ins. long, $2\frac{1}{2}$ ins. diam., 8 ins. in the ground to solid rock and supported in a mound of stone, 4 ft. base, to top of post with brass cap mkd.
	T6S R29E $\frac{1}{4}$ S20 S21 1960 1957
	Asc. 80 ft.
43.90	Ridge, bears N. 20° W. and SE.; desc. N. slope.
44.30	Four strand barbed wire fence, bears NW. and SE.; desc. 200 ft. over N. slope.
65.90	Drain, course NE.; thence along rocky E. slope.
80.15	The cor. of secs. 16, 17, 20 and 21, mkd. by an iron post, $2\frac{1}{2}$ ins. diam., set, mkd. and witnessed as described in the official record.
	Land, broken.
	Soil, shallow light clay and rocky.
	Timber, none.
	Undergrowth, moderate casti, catclaw and grass.
	From the cor. of secs. 8, 9, 16 and 17, an iron post, $2\frac{1}{2}$ ins. diam., conforming to the record.
	N. 0° 02' W., bet. secs. 8 and 9.
	Over gently rolling bench land.
17.90	A small stock water reservoir, bears W., about 2.50 chs. dist.
30.00	Wash, draining from reservoir, 10 lks. wide, 1 ft. deep, course N. 30° E.
30.91	Four strand barbed wire fence, bears E. and W.
40.00	Point for the $\frac{1}{4}$ sec. cor. of secs. 8 and 9.
	Set an iron post, 30 ins. long, $2\frac{1}{2}$ ins. diam., 10 ins. in the ground to solid rock and in a mound of stone, 4 ft. base, to top of post with brass cap mkd.

Survey, Subdivision, T. 6 S., R. 29 E.

Chains

T6S R29E

1/4
S 8 | S 9
1960

1957

Cont. over gently rolling land.

80.00 Point for the cor. of secs. 4, 5, 8 and 9.
Set an iron post, 30 ins. long, 2 1/2 ins. diam., 8 ins. in the ground to solid rock and supported in a mound of stone, 3 1/2 ft. base, to top of post with brass cap mkd.

T6S R29E

S 5 | S 4
S 8 | S 9
1960

1957

Land, gently rolling bench land.
Soil, light clay and rocky.
Timber, none.
Undergrowth, moderate cacti, catclaw and grass.

From the cor. of secs. 3, 4, 9 and 10, an iron post, 2 1/2 ins. diam., conforming to the record.

S. 89° 58' W., bet. secs. 4 and 9.

Over broken land; desc. 280 ft. over W. slope.

12.10 Wash, 40 lks. wide, 2 ft. deep, course N.; asc. 360 ft. over E. slope.

27.10 Top of ascent, bears N. 20° E. and S.; desc. 100 ft. over W. slope.

36.60 Wash, 10 lks. wide, 1 ft. deep, course N.; asc. E. slope.

40.04 Point for the 1/4 sec. cor. of secs. 4 and 9.

Set an iron post, 30 ins. long, 2 1/2 ins. diam., 10 ins. in the ground to solid rock and in a mound of stone, 5 1/2 ft. base, to top of post with brass cap mkd.

T6S R29E

1/4 S 4
S 9
1960

1957

Asc. 60 ft. over E. slope to top of ridge.

46.60 Telephone line, bears N. and S.

47.20 Ridge, bears N. 10° E. and S.; desc. 160 ft. over W. slope to wash.

51.80 Trail road, bears N. and S.; cont. descent.

63.10 Wash, 30 lks. wide, 1 ft. deep, course N.; asc. 210 ft. over E. slope.

80.08 The cor. of secs. 4, 5, 8 and 9.

Land, broken.
Soil, light clay and rocky.
Timber, none.
Undergrowth, moderate cacti, catclaw and grass.

Survey, Subdivision, T. 6 S., R. 29 E.

Chains

N. 0° 02' W., bet. secs. 4 and 5.

Over rolling land; desc. 220 ft. over N. slope.

25.00 Wash, 20 lks. wide, 2 ft. deep, course E.; asc. 160 ft. over S. slope.

40.00 Point for the 1/2 sec. cor. of secs. 4 and 5.

Set an iron post, 30 ins. long, 2 1/2 ins. diam., 8 ins. in the ground and supported in a mound of stone, 4 ft. base, to top of post with brass cap mkd.

T6S R29E
S 5 | S 4
1960
1957

Asc. 10 ft.

43.40 Top of ascent on knoll; desc. 160 ft. over NW. slope.

71.46 Intersect the First Standard Parallel South on the S. bdy. of sec. 32 in R. 29 E. at the point for the closing cor. of secs. 4 and 5.

Set an iron post, 30 ins. long, 2 1/2 ins. diam., 4 ins. in the ground to solid rock and supported in a mound of stone, 4 ft. base, to top of post with brass cap mkd.

T5S R29E
S 32
S 5 | S 4
C C
T6S R29E
1960
1957

From this closing cor., the standard 1/2 sec. cor. of sec. 32, bears W., 5.66 chs. dist.; an iron post, 2 1/2 ins. diam., heretofore described.

Land, rolling.
Soil, light clay and rocky.
Timber, none.
Undergrowth, moderate cacti, catclaw and grass.

The point for the 1/2 sec. cor. of sec. 4 on the N. bdy. of the Tp. is at midpoint bet. the closing cor. of secs. 3 and 4 and the closing cor. of secs. 4 and 5.

At the cor. point.

Set an iron post, 30 ins. long, 2 1/2 ins. diam., 8 ins. in the ground, and in a mound of stone, 3 1/2 ft. base to top, with brass cap mkd.

S 4
T6S R29E
1960
1957

From this point, the standard cor. of secs. 32 and 33 bears W., 5.92 chs. dist.

Survey, Subdivision, T. 6 S., R. 29 E.

Chains

From the cor. of secs. 31 and 32 on the S. bdy. of the Tp., monumented by an iron post, 2½ ins. diam., 15 ins. above ground, and in a mound of stone, firmly set, mkd. and witnessed as described in the official record.

N. 0° 03' W., bet. secs. 31 and 32.

Over rolling land.

Asc. 50 ft. over rocky S. slope.

8.85 Old State Highway No. 666, bears N. 30° E. and S. 30° W.

9.00 Rise, bears E. and W.; desc. 15 ft. over a rocky N. slope.

16.30 Rut road, bears E. and W.

18.60 Rut road, bears E. and W.

34.50 Rut road, bears N. 30° W. and S. 30° E.

40.00 Point for the ½ sec. cor. of secs. 31 and 32.

Set an iron post, 30 ins. long, 2½ ins. diam., 10 ins. in the ground, and in a mound of stone, 2 ft. base to top, with brass cap mkd.

T6S R29E

S31|S32

1957

46.00 Leave rolling land, bears E. and W.; asc. 610 ft. over rocky S. slope.

60.35 Four strand barbed wire fence, bears E. and W.

74.55 Spur, sloping N. 30° W.; desc. 80 ft. over rocky NE. slope.

80.00 Point for the cor. of secs. 29, 30, 31 and 32.

Set an iron post, 30 ins. long, 2½ ins. diam., 10 ins. in the ground, and in a mound of stone, 4 ft. base to top, with brass cap mkd.

T6S R29E

S30|S29

S31|S32

1957

Land, rolling, on S. 46.00 chs.

Soil, rocky.

Timber, none.

Undergrowth, scattered sage, cacti, moderate native grasses.

From the cor. of secs. 28, 29, 32 and 33.

S. 89° 55' W., bet. secs. 29 and 32.

Over broken mountainous land.

Desc. 215 ft. over a rocky SW. slope.

13.20 Old State Highway No. 666, bears N. 15° W. and S. 55° E.

18.40 Small wash, drains S. 25° E.

23.00 Old State Highway No. 666, bears N. 20° E. and S. 15° W.

24.00 Open mine and dump truck loading rack.

Survey, Subdivision, T. 6 S., R. 29 E.

Chains	
40.07	Point for the $\frac{1}{4}$ sec. cor. of secs. 29 and 32.
	Set an iron post, 30 ins. long, $2\frac{1}{2}$ ins. diam., 6 ins. in the ground, and in a mound of stone, 4 ft. base to top, with brass cap mkd.
	<p style="text-align: right;">T6S R29E $\frac{1}{4}$ S29 S32 1957</p>
	Desc. 110 ft. over broken SW. slope.
41.50	Rut road, bears N. 10° W. and S. 15° E.
45.30	Wash, 15 lks. wide, 2 ft. deep, drains N. 15° W., a stockmen's tank bears S. 10° E., approximately 3 chs. dist.; asc. 400 ft. over a rocky NE. slope.
80.14	<p>The cor. of secs. 29, 30, 31 and 32.</p> <p>Land, mountainous. Soil, rocky. Timber, very scattered scrub juniper. Undergrowth, scattered cacti, sage, catclaw, moderate native grasses.</p>
	West, bet. secs. 30 and 31.
	Over rolling land.
	Asc. 110 ft. over rocky NE. slope.
6.60	Spur, sloping N. 15° W.; desc. 255 ft. over a rocky SW. slope.
40.00	Point for the $\frac{1}{4}$ sec. cor. of secs. 30 and 31.
	Set an iron post, 30 ins. long, $2\frac{1}{2}$ ins. diam., 10 ins. in the ground, and in a mound of stone, 4 ft. base to top, with brass cap mkd.
	<p style="text-align: right;">T6S R29E $\frac{1}{4}$ S30 S31 1957</p>
40.20	Wash, 10 lks. wide, 2 ft. deep, drains S. 5° E.; asc. 30 ft. over rocky SE. slope.
48.70	Spur, sloping S. 10° W.; desc. 495 ft. over rocky NW. slope.
50.70	Wash, 10 lks. wide, 3 ft. deep, drains S. 60° W.
73.70	Same wash, draining N. 35° W. from S. 50° E.; asc. 45 ft. over rocky NE. slope.
84.83	Intersect the W. bdy. of the Tp.
	Point for the closing cor. of secs. 30 and 31.
	Set an iron post, 30 ins. long, $2\frac{1}{2}$ ins. diam., 12 ins. in the ground, and in a mound of stone, 4 ft. base to top, with brass cap mkd.
	<p style="text-align: right;">T6S T6S R28E R29E S25 S30 C S31 C 1957</p>

BOOK 4617

Survey, Subdivision, T. 6 S., R. 29 E.

Chains

From this point, the cor. of secs. 25 and 36, T. 6 S., R. 28 E., bears S., 6.60 chs. dist.

Land, rolling.
Soil, rocky.
Timber, very scattered scrub juniper.
Undergrowth, moderate cacti, catclaw and native grasses.

The point for the 1/4 sec. cor. of sec. 31 on the W. bdy. of the Tp. is at midpoint bet. the closing cor. of secs. 30 and 31 and the original closing cor. established for the cor. of Tps. 6 and 7 S., R. 29 E.

At the cor. point.

Set an iron post, 30 ins. long, 2 1/2 ins. diam., 10 ins. in the ground, and in a mound of stone, 4 ft. base to top, with brass cap mkd.

T6S
R29E
1/4
S31

1957

From this point, the 1/4 sec. cor. of sec. 36, T. 6 S., R. 28 E., bears S., 6.70 chs. dist. an iron post, 2 1/2 ins. diam. as described in the official record.

From the cor. of secs. 29, 30, 31 and 32.

N. 0° 03' W., bet. secs. 29 and 30.

Over mountainous land.

Desc. 490 ft. over rocky NE. slope.

27.40 Wash, 10 lks. wide, 2 ft. deep, drains N. 70° E.; asc. 70 ft. over rocky, general S. slope.

40.00 Point for the 1/4 sec. cor. of secs. 29 and 30.

Set an iron post, 30 ins. long, 2 1/2 ins. diam., 8 ins. in the ground, and in a mound of stone, 4 ft. base to top, with brass cap mkd.

T6S R29E
1/4
S30 | S29
1957

Asc. 190 ft. over S. slope.

41.90 Rut road, bears N. 50° W. and S. 50° E.

44.00 Wash, 20 lks. wide, 2 ft. deep, drains N. 75° W., general slope changes to SW.

62.40 Wash, 10 lks. wide, 3 ft. deep, drains S. 40° W.

80.00 Point for the cor. of secs. 19, 20, 29 and 30.

Set an iron post, 30 ins. long, 2 1/2 ins. diam., 8 ins. in the ground, and in a mound of stone, 3 ft. base to top, with brass cap mkd.

BOOK 4617

Survey, Subdivision, T. 6 S., R. 29 E.

Chains	
	<p style="text-align: center;">T6S R29E S19 S20 S30 S29 1957</p> <p>Land, mountainous. Soil, rocky. Timber, very scattered scrub juniper and pinon. Undergrowth, scattered cacti, sage, catclaw and moderate native grasses.</p>
	<p>From the cor. of secs. 20, 21, 28 and 29.</p> <p>S. 89° 52' W., bet. secs. 20 and 29.</p> <p>Over broken mountainous land.</p> <p>Asc. 30 ft. over a rocky NE. slope.</p>
4.25	Spur, sloping N. 40° W.; desc. 305 ft. over a rocky SW. slope.
21.20	Wash, 20 lks. wide, 2 ft. deep, drains N. 30° W.; asc. 195 ft. over rocky NE. slope.
32.90	Spur, sloping N. from S. 10° W.; desc. 115 ft. over rocky NW. slope.
40.20	Point for the ¼ sec. cor. of secs. 20 and 29.
	<p>Set an iron post, 30 ins. long, 2½ ins. diam., 10 ins. in the ground and in a mound of stone, 4 ft. base to top, with brass cap mkd.</p> <p style="text-align: center;">T6S R29E ¼ S20 ¼ S29 1957</p>
	Desc. 190 ft. over rocky NW. slope.
56.00	Wash, 10 lks. wide, 2 ft. deep, drains W.; cont. to desc. 10 ft. through wash channel.
59.30	Junction of washes, 20 lks. wide, 3 ft. deep, drains N. 35° W. from E. and S. 35° E.; asc. 140 ft. over rocky NE. slope.
78.65	Spur, sloping N. 35° W.; desc. 40 ft. over rocky SW. slope.
80.39	The cor. of secs. 19, 20, 29 and 30.
	<p>Land, mountainous. Soil, rocky. Timber, very scattered scrub juniper, some pinon. Undergrowth, scattered sage, cacti, moderate native grasses.</p>
	<p>West, bet. secs. 19 and 30.</p> <p>Over mountainous land.</p> <p>Desc. 105 ft. over rocky SW. slope.</p>
6.00	Rut road, bears N. 10° E. and S. 10° W.
15.40	Wash, 10 lks. wide, 1 ft. deep, drains S. 15° W.; asc. 20 ft. over short SE. slope.
17.00	Spur, sloping S. 10° W.; desc. 230 ft. over rocky NW. slope.

BOOK 4617

Survey, Subdivision, T. 6 S., R. 29 E.

Chains	
36.00	Wash, 50 lks. wide, 3 ft. deep, drains N. 5° W.; asc. 25 ft. over rocky NE. slope.
40.00	Point for the $\frac{1}{4}$ sec. cor. of secs. 19 and 30. Set an iron post, 30 ins. long, $2\frac{1}{2}$ ins. diam., 10 ins. in the ground, and in a mound of stone, 4 ft. base to top, with brass cap mkd. T6S R29E $\frac{1}{4}$ S19 S30 1960 1957 Cor. is located on a small rise, bears N. and S. Desc. 55 ft. over rocky, general W. slope.
43.50	Same wash, draining S. 40° W. from N. 50° E.
45.50	Same wash, draining N. approximately 2 chs., thence W. from S. 10° E.; asc. 25 ft. over rolling land, general N. slope.
75.50	Wash, $1\frac{1}{2}$ chs. wide, 3 ft. deep, drains N. 70° W.
84.51	Intersect the W. bdy. of the Tp. Point for the closing cor. of secs. 19 and 30. Set an iron post, 30 ins. long, $2\frac{1}{2}$ ins. diam., 8 ins. in the ground, and in a mound of stone, 4 ft. base to top, with brass cap mkd. T6S T6S R28E R29E S24 S19 C S30 C 1960 1957 From this point, the cor. of secs. 24 and 25, T. 6 S., R. 28 E., bears S. 6.58 chs. dist. Land, mountainous. Soil, rocky. Timber, very scattered scrub juniper, some pinon. Undergrowth, scattered sage, cacti, catclaw, moderate native grasses.
	The point for the $\frac{1}{4}$ sec. cor. of sec. 30 on the W. bdy. of the Tp. is at midpoint bet. the closing cor. of secs. 19 and 30 and the closing cor. of secs. 30 and 31. At the cor. point. Set an iron post, 30 ins. long, $2\frac{1}{2}$ ins. diam., 12 ins. in the ground, to bedrock, and in a mound of stone, 4 ft. base to top, with brass cap mkd. T6S R29E $\frac{1}{4}$ S30 1957 From this point, the $\frac{1}{4}$ sec. cor. of sec. 25, T. 6 S., R. 28 E., bears S., 6.59 chs. dist. an iron post, $2\frac{1}{2}$ ins. diam., as described in the official record.

Survey, Subdivision, T. 6 S., R. 29 E.

Chains	
	From the cor. of secs. 19, 20, 29 and 30.
	N. 0° 03' W., bet. secs. 19 and 20.
	Over rolling mountainous land.
	Asc. 35 ft. over a rocky SW. slope.
3.20	Top of ascent on spur, sloping N. 35° W.; desc. 210 ft. over rocky NE. slope.
27.20	Wash, 50 lks. wide, 2 ft. deep, drains N. 30° W.; asc. 115 ft. over rocky SW. slope.
35.00	Slope changes to S.
40.00	Point for the $\frac{1}{4}$ sec. cor. of secs. 19 and 20.
	Set an iron post, 30 ins. long, 2½ ins. diam., 10 ins. in the ground, and in a mound of stone, 4 ft. base to top, with brass cap mkd.
	T6S R29E
	$\frac{1}{4}$
	S19 S20
	1957
	Asc. 45 ft. over rocky S. slope.
48.00	Spur, sloping N. 75° W.; desc. 60 ft. over rocky, general NE. slope.
54.20	Wash, 10 lks. wide, 2 ft. deep, drains N. 80° W.; asc. 45 ft. over rocky SW. slope.
61.70	Spur, sloping W.; desc. 230 ft. over rocky N. slope.
74.50	Wash, 1 ch. wide, 3 ft. deep, drains S. 80° W.; asc. 60 ft. over rocky S. slope.
80.00	Point for the cor. of secs. 17, 18, 19 and 20.
	Set an iron post, 30 ins. long, 2½ ins. diam., 10 ins. in the ground, and in a mound of stone, 4 ft. base to top, with brass cap mkd.
	T6S R29E
	S18 S17
	S19 S20
	1960
	1957
	Land, mountainous.
	Soil, rocky.
	Timber, very scattered scrub juniper.
	Undergrowth, scattered sage, catclaw, cacti, moderate native grasses.
	From the cor. of secs. 16, 17, 20 and 21, an iron post, 2½ ins. diam., conforming to the record.
	West, bet. 17 and 20.
	Over rocky broken land; asc. along steep N. slope.
18.00	Top of ascent on hillside, slopes NE.; thence desc. over W. slope.
21.10	Four strand barbed wire fence; bears N. 10° W. and S. 10° E.; desc. 240 ft. over SW. slope.
40.00	Point for the $\frac{1}{4}$ sec. cor. of secs. 17 and 20.

Survey, Subdivision, T. 6 S., R. 29 E.

Chains	
	<p>Set an iron post, 30 ins. long, 2½ ins. diam., 3 ins. in the ground and supported in a mound of stone, 4 ft. base, to top of post, with brass cap mkd.</p> <p style="text-align: center;">T6S R29E $\frac{1}{4}$ S17 S20 1960 1957</p>
	<p>Desc. 320 ft. over rocky SW. slope.</p>
67.40	<p>Wash, 40 lks. wide, 2 ft. deep, course S. 80° W. from S. 70° E.; asc. 80 ft. along S. slope.</p>
80.00	<p>The cor. of secs. 17, 18, 19 and 20.</p> <p>Land, rough and broken. Soil, light clay and rocky. Timber, none. Undergrowth, moderate cacti, catclaw and grass.</p>
	<p>West, bet. secs. 18 and 19.</p> <p>Over rolling mountainous land.</p>
19.40	<p>Junction of washes, 15 lks. wide, from N. 20° E. and S. 50° E. draining S. 20° W.; see topographic sheet Duncan 2 NW. Arizona.</p>
24.80	<p>Spur, sloping S. 25° W.</p>
40.00	<p>Point for the $\frac{1}{4}$ sec. cor. of secs. 18 and 19.</p> <p>Set an iron post, 30 ins. long, 2½ ins. diam., 8 ins. in the ground, and in a mound of stone, 4½ ft. base to top, with brass cap mkd.</p> <p style="text-align: center;">T6S R29E $\frac{1}{4}$ S18 S19 1957</p>
	<p>Cor. is located on spur sloping S. 20° W.</p> <p>Desc. 220 ft. over a rough, broken mountainous land, general NW. slope.</p>
48.80	<p>Small wash, draining S.</p>
55.30	<p>Spur, sloping S. 20° W.</p>
68.80	<p>Wash, 1 ch. wide, 2 ft. deep, drains S. 15° W.</p>
82.96	<p>Point selected for the witness closing cor. of secs. 18 and 19.</p> <p>Set an iron post, 30 ins. long, 2½ ins. diam., 10 ins. in the ground, and in a mound of stone, 4 ft. base to top, with brass cap mkd.</p> <p style="text-align: center;">T6S T6S R28E R29E S13 S18 WCC S19 1957</p>
84.36	<p>Intersect the W. bdy. of the Tp.</p>

Survey, Subdivision, T. 6 S., R. 29 E.

Chains

True point for the closing cor. of secs. 18 and 19 falls in wash, $1\frac{1}{2}$ chs. wide, 4 ft. deep, draining N. 25° W., where it is impractical to set the monument.

From this point, the true point for the cor. of secs. 13 and 24, T. 6 S., R. 28 E., bears S. $6^{\circ} 72'$ chs. dist. and is witnessed S. 3.21 chs. dist. by an iron post as described in the official record.

Land, mountainous.

Soil, rocky.

Timber, scattered scrub juniper and pinon.

Undergrowth, moderate cacti, catclaw, native grasses and some sage.

The point for the $\frac{1}{4}$ sec. cor. of sec. 19 on the W. bdy. of the Tp. is at midpoint bet. the closing cor. of secs. 18 and 19 and the closing cor. of secs. 19 and 30.

At the cor. point

Set an iron post, 30 ins. long, $2\frac{1}{2}$ ins. diam., 8 ins. in the ground, and in a mound of stone, 4 ft. base to top, with brass cap mkd.

T6S

T6S R29E

$\frac{1}{4}$

S19

1960

1957

From this point, the $\frac{1}{4}$ sec. cor. of sec. 24, T. 6 S., R. 28 E., bears S., 6.65 chs. dist. an iron post, $2\frac{1}{2}$ ins. diam., as described in the official record.

From the cor. of secs. 17, 18, 19 and 20,

N. $0^{\circ} 03'$ W., bet. secs. 17 and 18.

Over rough, broken mountainous land.

Asc. 240 ft. over broken S. slope.

10.55 Spur, sloping W.; desc. 290 ft. over broken, rocky N. slope.

22.75 Four strand barbed wire fence, with steel posts, bears E. and W.

25.00 Slope changes to NW.

40.00 Point for the $\frac{1}{4}$ sec. cor. of secs. 17 and 18.

Set an iron post, 30 ins. long, $2\frac{1}{2}$ ins. diam., 10 ins. in the ground, and in a mound of stone, 5 ft. base to top, with brass cap mkd.

T6S R29E

$\frac{1}{4}$

S18 S17

1957

40.30 Junction of washes, 20 lks. wide, 3 ft. deep, draining W. from N. 30° E. and N. 80° E.; asc. 330 ft. over a general rocky S. slope.

65.00 Spur, sloping S. 80° W.; desc. 205 ft. over rocky NW. slope.

70.00 Head of wash, 10 lks. wide, 2 ft. deep, drains N. 75° W.

80.00 Point for the cor. of secs. 7, 8, 17 and 18.

Set an iron post, 30 ins. long, $2\frac{1}{2}$ ins. diam., 20 ins. in the ground, and in a mound of stone, 2 ft. base to top, with brass cap mkd.

Survey, Subdivision, T. 6 S., R. 29 E.

Chains

T6S R29E

S 7 | S 8

S18 | S17

1957

Land, mountainous.
Soil, rocky.
Timber, scattered scrub juniper and pinon.
Undergrowth, scattered sage, cacti, moderate native grasses.

From the cor. of secs. 8, 9, 16 and 17, an iron post, 2½ ins. diam., conforming to the record.

N. 89° 59' W., bet. secs. 8 and 17.
Over broken land; asc. slight E. slope.

6.40 Top of low ridge, bears NW. and S.; desc. 180 ft. over W. slope.

27.20 Junction of washes draining from S. 70° E. and S., course N.; asc. 240 ft. over E. slope.

40.01 Point for the ¼ sec. cor. of secs. 8 and 17.

Set an iron post, 30 ins. long, 2½ ins. diam., 8 ins. in the ground to solid rock and supported in a mound of stone, 3½ ft. base, to top of post with brass cap mkd.

T6S R29E

S 8

S17

1960

1957

41.40 Top of ascent, bears N. and S.; desc. 360 ft. over NW. slope.

63.00 Wash, 20 lks. wide, 2 ft. deep, drains N.; asc. 150 ft. over NE. slope.

73.10 Top of ascent, bears N. and S.; desc. 100 ft. over NW. slope.

80.02 The cor. of secs. 7, 8, 17 and 18.

Land, broken.
Soil, light clay and rocky.
Timber, none.
Undergrowth, moderate cacti, catclaw and grass.

From the cor. of secs. 7, 8, 17 and 18.

West, bet. secs. 7 and 18.

Over broken land; desc. 160 ft. along the N. side of wash, draining W.

15.00 Wash, 10 lks. wide, 2 ft. deep, course NW.; thence along N. slope.

40.00 Point for the ¼ sec. cor. of secs. 7 and 18.

Set an iron post, 30 ins. long, 2½ ins. diam., 14 ins. in the ground, with brass cap mkd.

Survey, Subdivision, T. 6 S., R. 29 E.

Chains

T6S R29E
S 7
1/2 S18
1960
1957

Cont. along N. slope.

46.60 Spur, slopes N. 60° W.; desc. 200 ft. over NW slope.

65.00 Wash, 10 lks. wide, 2 ft. deep, drains NW; desc. 160 ft. over NW slope.

84.19 Intersect the E. bdy. of sec. 12, T. 6 S., R. 28 E., at the point for the closing cor. of secs. 7 and 18.

Set an iron post, 30 ins. long, 2 1/2 ins. diam., 8 ins. in the ground to solid rock and in a mound of stone, 4 ft. base, to top of post with brass cap mkd.

T6S
R28E R29E
S12 | S 7 C
S18.0
1960
1957

From this closing cor., the cor. of secs. 12 and 13, T. 6 S., R. 28 E., bears S., 6.73 chs. dist., an iron post, 2 1/2 ins. diam., conforming to the record.

Land, broken.
Soil, light clay and rocky.
Timber, none.
Undergrowth, moderate cacti, catclaw and grass.

The point for the 1/2 sec. cor. of sec. 18 on the W. bdy. of the Tp. is at midpoint bet. the closing cor. of secs. 7 and 18 and the closing cor. of secs. 18 and 19.

At the cor. point.

Set an iron post, 30 ins. long, 2 1/2 ins. diam., 8 ins. in the ground, and in a mound of stone, 3 1/2 ft. base to top, with brass cap mkd.

T6S
R29E
1/2
S18
1957

From this point, the 1/2 sec. cor. of sec. 13, T. 6 S., R. 28 E., bears S. 6.72 chs. dist. an iron post, 2 1/2 ins. diam., conforming to the record.

From the cor. of secs. 7, 8, 17 and 18.

N. 0° 03' W., bet. secs. 7 and 8.

Over broken land; asc. 150 ft.

6.70 Top of ascent on hillside, sloping W.; desc. 200 ft. over N. slope.

20.30 Wash, 20 lks. wide, 2 ft. deep, course N. 70° W.

22.90 Small spur, slopes W., 1 ch. to end.

Survey, Subdivision, T. 6 S., R. 29 E.

Chains	
24.40	Wash, 10 lks. wide, 1 ft. deep, course SW.; asc. 200 ft. along the bottom of a small drain.
40.00	Point for the $\frac{1}{2}$ sec. cor. of secs. 7 and 8.
	Set an iron post, 30 ins. long, $2\frac{1}{2}$ ins. diam., 4 ins. in the ground and in a mound of stone, $3\frac{1}{2}$ ft. base, to top, with brass cap mkd.
	<p style="text-align: center;">T6S R29E $\frac{1}{2}$ S 7 S 8 1960 1957</p>
42.90	Four strand barbed wire fence, bears E. and W.; slope changes to SW.; asc. 140 ft.
61.70	Spur, slopes NW.; desc. 120 ft. over N. slope.
70.40	Wash, 10 lks. wide, 1 ft. deep, course NW.; thence along W. slope.
80.00	Point for the cor. of secs. 5, 6, 7 and 8.
	Set an iron post, 30 ins. long, $2\frac{1}{2}$ ins. diam., 10 ins. in the ground and in a mound of stone, $3\frac{1}{2}$ ft. base, to top of post, with brass cap mkd.
	<p style="text-align: center;">T6S R29E S 6 S 5 S 7 S 8 1960 1957</p>
	<p>Land, broken. Soil, light clay and rocky. Timber, none. Undergrowth, moderate cacti, catclaw and grass.</p>
	From the cor. of secs. 4, 5, 8 and 9.
	N. $89^{\circ} 57' W.$, bet. secs. 5 and 8.
	Over rolling land.
17.90	Small wash, drains N.
40.00	Point for the $\frac{1}{2}$ sec. cor. of secs. 5 and 8.
	Set an iron post, 30 ins. long, $2\frac{1}{2}$ ins. diam., 12 ins. in the ground and in a mound of stone, $3\frac{1}{2}$ ft. base, to top of post with brass cap mkd.
	<p style="text-align: center;">T6S R29E S 5 $\frac{1}{2}$ S 8 1960 1957</p>
	Asc. over rolling E. slope.
60.80	Ridge, bears N. $20^{\circ} E.$ and S. $20^{\circ} W.$; desc. 200 ft. over N. slope.
79.99	The cor. of secs. 5, 6, 7 and 8.
	From this cor., a triangulation station "Gila Box", bears N. $59^{\circ} 09' E.$, 25.90 chs. dist., a brass tablet seated in solid rock established by the U. S. Soil Erosion Service, its geographic position is

Survey, Subdivision, T. 6 S., R. 29 E.

Chains

Latitude 32° 56' 08.818" N., Longitude 109° 24' 06.631" W.

Land, rolling.

Soil, light clay and rocky.

Timber, none.

Undergrowth, moderate cacti, catclaw and grass.

West, bet. secs. 6 and 7.

Over broken land; desc. 80 ft. over W. slope.

4.80 Wash, 10 lks. wide, 1 ft. deep, course NW.; thence along irregular N. slope.

24.10 Spur, slopes N. 70° W.; desc. 150 ft. over W. slope.

40.00 Point for the 1/2 sec. cor. of secs. 6 and 7.

Set an iron post, 30 ins. long, 2 1/2 ins. diam., 10 ins. in the ground and in a mound of stone, 3 1/2 ft. base, to top of post with brass cap mkd.

T6S R29E

1/2 S 6
S 7

1960

1957

Desc. 310 ft. over ledgy W. slope.

61.40 Top of canyon wall, facing W., bears N. and S. 20° E.; desc. 740 ft. abruptly over high ledge and talus slope.

81.00 Left bank of the Gila River, bears N. 10° W. and S. 10° W., thence over river, flowing S. 10° E.

82.50 Right bank of the Gila River, bears N. and S. 10° E., enter sandy bottom land covered with mesquite and willows.

84.07 Intersect the E. bdy. of sec. 1 at the point for the closing cor. of secs. 6 and 7.

Set an iron post, 30 ins. long, 2 1/2 ins. diam., 20 ins. in the sand and in a mound of stone, 3 1/2 ft. base, to top, with brass cap mkd.

T6S
R28E R29E

S 1 | S 6 C
S 7 C

1960

1957

From this closing cor. the cor. of secs. 1 and 12, T. 6 S., R. 28 E., bears S., 6.60 chs. dist., an iron post, 2 1/2 ins. diam., hereinbefore described.

Land, rough and broken.

Soil, light clay and sandy river bottom.

Timber, mesquite and willows in river bottom.

Undergrowth, moderate cacti, catclaw and grass.

Survey, Subdivision, T. 6 S., R. 29 E.

Chains

The point for the $\frac{1}{4}$ sec. cor. of sec. 7 on the W. bdy. of the Tp. is at midpoint bet. the closing cor. of secs. 6 and 7 and the closing cor. of secs. 7 and 18.

At the cor. point

Set an iron post, 30 ins. long, $2\frac{1}{2}$ ins. diam., 10 ins. in the ground to bedrock, and in a mound of stone, 4 ft. base to top, with brass cap mkd.

T6S

R29E

$\frac{1}{4}$

S77

1957

From this point, the $\frac{1}{4}$ sec. cor. of sec. 12, T. 6 S., R. 28 E., bears S., 6.665 chs. dist. an iron post, $2\frac{1}{2}$ ins. diam., conforming to the record.

The point for the W. $\frac{1}{4}$ sec. cor. of sec. 6 is 40.00 chs. N. of the closing cor. of secs. 6 and 7. This point falls in the overflow bottom on the SE. side of the Gila River where it is impractical to set the monument.

Point selected for the witness cor. point bears S., 10.25 chs. dist.

Set an iron post, 30 ins. long, $2\frac{1}{2}$ ins. diam., 10 ins. in the ground, and in a mound of stone, 4 ft. base to top, with brass cap mkd.

T6S

R28E R29E

W C

$\frac{1}{4}$

S 6

1960

1957

From the true point for the above cor., the true point for the $\frac{1}{4}$ sec. cor. of sec. 1, T. 6 S., R. 28 E., bears S., 6.60 chs. dist.

From the cor. of secs. 5, 6, 7 and 8.
N. 0° 03' W., bet. secs. 5 and 6.

Over rolling land, draining W.

- 4.50 Spur, slopes W.; desc. 120 ft.
- 12.40 Wash, 20 lks. wide, 2 ft. deep, course W.; asc. 100 ft.
- 17.90 Spur, slopes W.; desc. 70 ft.
- 25.60 Wash, 10 lks. wide, 2 ft. deep, course W.; asc. 120 ft.
- 35.00 Top of ascent, bears NW. and SE.; desc. slight N. slope.
- 40.00 Point for the $\frac{1}{4}$ sec. cor. of secs. 5 and 6.
Set an iron post, 30 ins. long, $2\frac{1}{2}$ ins. diam., 10 ins. in the ground, $3\frac{1}{2}$ ft. base, to top of post with brass cap mkd.

Survey, Subdivision, T. 6 S., R. 29 E.

Chains

T6S R29E

1/2 S 5
1960
1957

71.65 Desc. 120 ft. over N. slope, intersect the First Standard Parallel South, on the S. bdy. of sec. 31 in T. 5 S., R. 29 E. at the pt. for the closing cor. of secs. 5 and 6.

Set an iron post, 30 ins. long, 2 1/2 ins. long, 2 ins. in the ground to solid rock and in a mound of stone, 4 ft. base, to top of post with brass cap mkd.

T5S R29E

831
S 6 | S 5
C C

T6S R29E
1960

1957

From this closing cor., the standard 1/2 sec. cor. of sec. 31, bears W., 5.38 chs. dist., an iron post, 2 1/2 ins. diam., heretofore described.

Land, rolling.
Soil, light clay and rocky.

Timber, none.
Undergrowth, moderate cacti, catclaw and grass.

The point for the 1/2 sec. cor. of sec. 5 on the N. bdy. of the Tp. is at midpoint bet. the closing cor. of secs. 4 and 5 and the closing cor. of secs. 5 and 6.

At the cor. point

Set an iron post, 30 ins. long, 2 1/2 ins. diam., 8 ins. in the ground, and in a mound of stone, 6 ft. base to top, with brass cap mkd.

1/2 S 5
T6S R29E
1960
1957

From this point, the standard cor. of secs. 31 and 32, T. 5 S., R. 29 E., bears W., 5.52 chs. dist.

The point for the 1/2 sec. cor. of sec. 6 on the N. bdy. of the Tp. is S. 89° 49' W., 40.00 chs. from the closing cor. of secs. 5 and 6.

At the cor. point

Set an iron post, 30 ins. long, 2 1/2 ins. diam., 12 ins. in the ground, and in a mound of stone, 4 ft. base to top, with brass cap mkd.

1/2 S 6
T6S R29E
1960

From this point, the standard cor. of T. 5 S., Rs. 28 and 29 E., bears N. 89° 52' W., 5.80 chs. dist.

Township 6 South, Range 29 East

Chains

The land within T. 6 S., R. 29 E. is principally mountainous, with the general elevation ranging from approximately 4100 feet to 5500 feet above sea level. The soil is very shallow, being gravelly and rocky. The entire township is covered with rock.

There is a ranch in the approximate center of section 33, goat ranches in sections 12 and 30 and a gravel pit in the southwest portion of section 28. There is stock grazing throughout the township, with stock reservoirs and/or earth tanks developed in sections 1, 5, 9, 10, 12, 15, 24, 26, 28, 29, 30 and 34. The area for grazing is rough and rocky, with rainfall sufficient only for a moderate growth of native grasses. There is no cultivated land within the township.

There are numerous rut roads throughout the township. These roads are in very poor condition, affording a limited amount of travel. There is one main road through the township, the old State Highway No. 666. This road enters the township in the southeast corner of section 31 and traverses through the township, leaving it in the northeast corner of section 1. A telephone line enters the township in the southwest corner of section 32 and traverses through the central portion of the township, leaving it in the northeast corner of section 4.

The Gila River enters the township in the northwest corner of section 6, flowing south along and near the west boundary of section 6, leaving the township in the northwest corner of section 7.

There is a scattered to moderate growth of sage, catclaw, greasewood, soap weed and cacti throughout the township, with a scattered growth of timber along the spur tops and ridges.

4-680
(Feb., 1950)

UNITED STATES
DEPARTMENT OF THE INTERIOR
BUREAU OF LAND MANAGEMENT

FIELD ASSISTANTS

NAMES	CAPACITY
Alburn D. Griffin	Principal Assistant
Deon J. Allen	Note Keeper
Lacel E. Bland	Front Chainman
Darwin P. Russell	Flagman
Ray D. Neilson	Cornerman

CERTIFICATE OF CADASTRAL ENGINEER

I, Phil D. Smith, HEREBY CERTIFY upon honor that, in
pursuance of special instructions bearing date of the 16th November 1954
13th day of January, 1956,

I have ~~surveyed~~ independently resurveyed a portion of the east boundary, and surveyed
a portion of the subdivision of Township 6 South, Range 29 East

of the Gila and Salt River Meridian, in the State of Arizona; which are
represented in the foregoing field notes as having been executed by me and under my direction; and that
said survey has been made in strict conformity with said instructions, the Manual of Instructions for the
Survey of the Public Lands of the United States, and in the specific manner described in the foregoing
field notes.

Salt Lake City, Utah

March 16, 1960

Phil D. Smith
Phil D. Smith, Cadastral Surveyor.

CERTIFICATE OF APPROVAL

BUREAU OF LAND MANAGEMENT,

Washington, D. C., _____, 19____

The foregoing field notes of the ~~survey of~~ independent resurvey of a portion of the east
boundary, and survey of a portion of the subdivision of T. 6 S., R. 29 E.

executed by Phil D. Smith

having been critically examined and found correct, are hereby approved.

Cadastral Engineering Staff Officer.

CERTIFICATE OF TRANSCRIPT

~~I CERTIFY that the foregoing transcript of the field notes of the above described surveys in~~
~~_____ is a true copy of the original field notes.~~

Cadastral Engineering Staff Officer.

53

4-680
(Feb., 1950)

UNITED STATES
DEPARTMENT OF THE INTERIOR
BUREAU OF LAND MANAGEMENT

FIELD ASSISTANTS

NAMES	CAPACITY
William Savage	Transitman
Neil Forsyth	Chainman
R. Gordon Shurtz	Chainman
Jerry L. Thomas	Flagman
Parley Pratt	Cornerman
Glen B. Hatch	Transitman
LaVern Griffin	Chainman
Gary T. Oviatt	Chainman
Dan Coleman	Flagman
Leonard Murphy	Cornerman

CERTIFICATE OF CADASTRAL ENGINEER

I, Vern E. Lane, HEREBY CERTIFY upon honor that, in
16th November 1954
pursuance of special instructions bearing date of the 13th day of January, 1956,

I have ~~surveyed~~ supervised the dependent resurvey of the First Standard Parallel South
in R. 29 E., a portion of the west boundary, portion of the east boundary; and
completion of the survey of the subdivision of T. 6 S., R. 29 E.

of the Gila & Salt River Meridian, in the State of Arizona, which are
under my supervision
represented in the foregoing field notes as having been executed ~~by me and under my direction~~, and that
said survey has been made in strict conformity with said instructions, the Manual of Instructions for the
Survey of the Public Lands of the United States, and in the specific manner described in the foregoing
field notes.

Salt Lake City, Utah
March 15, 1960


Vern E. Lane - Cadastral Surveyor

CERTIFICATE OF APPROVAL

BUREAU OF LAND MANAGEMENT,
Washington, D. C., FEB 1 1962, 1960

The foregoing field notes of the ~~survey of~~ dependent resurvey of the First Standard
Parallel South in R. 29 E., a portion of the west boundary, portion of the east
boundary; and completion of the survey of the subdivision of T. 6 S., R. 29 E.,

Gila & Salt River Meridian, Arizona
executed by Eldon W. Sibley and Boyd S. Owens, Cartographic Survey Aids, under the
supervision of Vern E. Lane, Cadastral Surveyor.
having been critically examined and found correct, are hereby approved.


Chief, Division of Engineering

CERTIFICATE OF TRANSCRIPT

~~I CERTIFY that the foregoing transcript of the field notes of the above-described surveys in~~
_____, is a true copy of the original field notes.

Cadastral Engineering Staff Officer.