

UNITED STATES
DEPARTMENT OF THE INTERIOR
BUREAU OF LAND MANAGEMENT

FIELD NOTES

OF

THE SURVEY OF THE SUBDIVISION

OF

TOWNSHIP 41 NORTH, RANGE 7 EAST

Of the Gila and Salt River Meridian,

In the State of Arizona

EXECUTED BY

Glen D. Hatch Cadastral Surveyor

Fred R. Chappell Cadastral Surveyor

Craig P. Sylvester Cadastral Surveyor and Chief of Field Parties.

Under special instructions dated July 3, 1961, which provided
for the surveys included under Group No. 362, approved July 3, 1961
and assignment instructions dated August 21, 1961

Survey commenced October 19, 1961

Survey completed November 7, 1961

1A

BOOK 4644

INDEX DIAGRAM

Township 41 North, Range 7 East

6	34 5	24 4	17 3	12 2	7 1
34	33	24	17	12	6
7	32 8	23 9	16 10	11 11	6 12
32	31	22	16	11	5
18	31 17	22 16	15 15	10 14	5 13
30	29	21	15	10	4
19	29 20	21 21	14 22	9 23	4 24
28	27	20	14	9	3
30	26 29	19 28	13 27	8 26	3 25
26	25	19		8	2
31	25 32	18 33	O.D.Gould 1927 34	35	1 36

Chains

The South Boundary (the 10th Standard Parallel North) was surveyed by W. E. Hiester in 1927. The East Boundary was surveyed by B. J. Kinsey in 1937. The West Boundary was surveyed by D. E. Harding in 1957. The North Boundary was surveyed concurrently and shows in the field notes of the survey of the South Boundary of T.42 N., R.7 E. A portion of the subdivision (sec. 34) was surveyed by O. D. Gould in 1927.

The following field notes are those of a completion survey of the subdivision of Township 41 North, Range 7 East.

The survey was executed with W. & L. E. Gurley Solar Transits Nos. 580518 and 541327 constructed in accordance with the standard instrumental specifications of the Bureau of Land Management. The instruments were in good condition prior to the beginning of the survey and were maintained in proper adjustment throughout the progress of this survey.

Corners on east-west lines were set on the true latitudinal curve. Lines connecting previously established corners were run by random and true method, but for simplification of the record the random lines are omitted from the field notes.

Measurements herein contained were made with a narrow steel tape, 8 chains in length, graduated every link for the first 100 links and thereafter at intervals of 10 links. The tape was tested by comparison with a one chain standard steel tape and found to be correct. Measurements were made on the slope with the vertical angle of each interval ascertained by a clinometer in good adjustment; horizontal equivalents alone are entered in the field notes. All lines of this survey were run by direct method where the lines were accessible; lines inaccessible were run by traverse or triangulation methods. Distances to topography on lines run by traverse or triangulation are approximate as scaled from U.S.G.S. topographic sheets. The details of such traverses or triangulations have been thoroughly checked and verified, and in order to simplify the record the diagrams and reductions are omitted from these field notes.

The direction of the lines of this survey were determined by reference to true meridians established on line by altitude observations on the sun. The lines were carried forward by sustained angulation being supplemented by other numerous altitude observations on the sun taken throughout the progress of the survey.

The geographic position for the southeast corner of the township is at latitude $36^{\circ}54'12.39''$ N. and longitude $111^{\circ}34'58.5''$ W. as adjusted from traverses to the closing corner of Township 40 North, Ranges 7 and 8 East.

The magnetic declination was read at a number of stations throughout the township and the average of these readings was found to be $15^{\circ}00'$ East.

Subdivision of T.41 N., R.7 E.

Beginning at the standard cor. of secs. 35 and 36 on the south boundary of the township.

N. $0^{\circ}01'$ W., bet. secs. 35 and 36.

Over broken and rocky desert land, across mostly barren sandstone; asc. 40 ft. over SE. slope.

4.40 Small spur, slopes E.; desc. 35 ft. along rocky E. slope.

10.30 Slope changes; desc. 200 ft. over irregular N. slope.

Chains	
31.10	Wash, 2 ft. deep, 20 lks. wide, drains E.; asc. 40 ft. over irregular S. slope.
36.70	Small spur, slopes E.; desc. 60 ft. over NE. slope.
40.00	Point for the $\frac{1}{4}$ sec. cor. of secs. 35 and 36. Set an iron post, 30 ins. long, $2\frac{1}{2}$ ins. diam., 6 ins. in the ground, and in a mound of stone to top, with brass cap mkd.
	T41N R7E $\frac{1}{4}$ S35 S36 1961
	Desc. 10 ft. over irregular sandstone formation.
55.60	Top of rim, bears W. and SE.; desc. 235 ft. over rocky and broken NW. slope.
76.60	Small wash, drains E.; asc. sandy S. slope.
80.00	Point for the cor. of secs. 25, 26, 35 and 36. Set an iron post, 30 ins. long, $2\frac{1}{2}$ ins. diam., on solid sandstone, over an X, and in a mound of stone to top, with brass cap mkd.
	T41N R7E S26 S25 S35 S36 1961
	Land, broken. Soil, sand and exposed sandstone. Timber, none.
	From the cor. of secs. 25, 30, 31 and 36 on the E. bdy., monumented by an iron post, 2 ins. diam., set, mkd. and witnessed as described in the official record.
	N. 89°58'W., bet. secs. 25 and 36.
	Over broken desert land, asc. 40 ft. along irregular S. slope, across sand and barren sandstone.
18.40	Wash, 2 ft. deep, 30 lks. wide, drains SE.; asc. 320 ft. over steep and broken NE. slope.
39.97	Point for the $\frac{1}{4}$ sec. cor. of secs. 25 and 36. Set an iron post, 30 ins. long, $2\frac{1}{2}$ ins. diam., on solid rock, over an X, and in a mound of stone to top, with brass cap mkd.
	T41N R7E $\frac{1}{4}$ S25 S36 1961
	Asc. 30 ft. over NE. slope.
41.20	Top of ascent on spur sloping S.; desc. 80 ft. over rocky and irregular NW. slope.
75.00	Wash, 2 ft. deep, 20 lks. wide, drains E. from SW.; asc. 10 ft. over sandy S. slope.

Chains	
79.94	<p>The cor. of secs. 25, 26, 35 and 36.</p> <p>Land, broken. Soil, sand, and exposed sandstone. Timber, none.</p>
6.00	<p>N.0°01'W., bet. secs. 25 and 26.</p> <p>Over broken desert land, through scattered scrub timber, asc. 90 ft. over S. slope on top of spur.</p> <p>Top of spur which slopes S.; asc. 80 ft. over irregular S. slope on top of ridge.</p>
39.70	<p>Top of low rim, bears SW. and NE., thence over irregular sandstone formation on top of ridge.</p>
40.00	<p>Point for the $\frac{1}{4}$ sec. cor. of secs. 25 and 26.</p> <p>Set an iron post, 30 ins. long, $2\frac{1}{2}$ ins. diam., on solid sandstone, over an X, and in a mound of stone to top, with brass cap mkd.</p> <p style="text-align: center;">T41N R7E $\frac{1}{4}$ S26 S25 1961</p>
57.10	<p>Continue over irregular formation on top of ridge.</p> <p>Crest of steep descent, bears W. and curves NE.; desc. 300 ft. over steep and rocky N. slope.</p>
80.00	<p>Point for the cor. of secs. 23, 24, 25 and 26.</p> <p>Set an iron post, 30 ins. long, $2\frac{1}{2}$ ins. diam., on solid rock, over an X, and in a mound of stone to top, with brass cap mkd.</p> <p style="text-align: center;">T41N R7E S23 S24 S26 S25 1961</p>
16.00	<p>Land, broken. Soil, sand and exposed sandstone. Timber, very scattered scrub juniper and pinon.</p> <p>From the cor. of secs. 19, 24, 25 and 30 on the E. bdy., monumented by an iron post, 2 ins. diam., set, mkd. and witnessed as described in the official record.</p> <p>S. 89°57'W., bet. secs. 24 and 25.</p> <p>Over sandy desert land; asc. 35 ft. over NE. slope.</p> <p>Base of steeper ascent; asc. 145 ft. over rocky NE. slope.</p>
40.01	<p>Point for the $\frac{1}{4}$ sec. cor. of secs. 24 and 25.</p> <p>Set an iron post, 30 ins. long, $2\frac{1}{2}$ ins. diam., 12 ins. in the ground, and in a mound of stone, $3\frac{1}{2}$ ft. base, to top, with brass cap mkd.</p> <p style="text-align: center;">T41N R7E $\frac{1}{4}$ S24 S25 1961</p>

Chains	
	Asc. 20 ft. over NE. slope.
43.90	Spur, slopes N.; desc. 20 ft. over NW. slope.
53.00	Small draw, drains NW.; asc. 110 ft. along irregular S. slope.
79.00	Small spur, slopes N.; desc. 10 ft. along S. slope.
80.02	The cor. of secs. 23, 24, 25 and 26.
	Land, broken. Soil, sand and exposed sandstone. Timber, none.
	N.0°01'W., bet. secs. 23 and 24.
	Over broken desert land; desc. 90 ft. over rocky N. slope.
7.60	Wash, 3 ft. deep, 20 lks. wide, drains E., asc. 100 ft. over sandy SE. slope.
40.00	Point for the $\frac{1}{4}$ sec. cor. of secs. 23 and 24.
	Set an iron post, 30 ins. long, $2\frac{1}{2}$ ins. diam., 22 ins. in the ground, with brass cap mkd. <div style="text-align: center;"> T41N R7E $\frac{1}{4}$ S23 S24 1961 </div> No accessories available.
	Asc. 80 ft. over SE. slope.
49.90	Spur, slopes E.; desc. 150 ft. over irregular NE. slope.
80.00	Point for the cor. of secs. 13, 14, 23 and 24.
	Set an iron post, 30 ins. long, $2\frac{1}{2}$ ins. diam., 22 ins. in the ground, with brass cap mkd. <div style="text-align: center;"> T41N R7E S14 S13 S23 S24 1961 </div> No accessories available.
	Land, broken.
	Soil, sand and exposed sandstone.
	Timber, none; black brush, and undergrowth.
	From the cor. of secs. 13, 18, 19 and 24 on the E. bdy., monumented by an iron post, 2 ins. diam., set, mkd. and witnessed as described in the official record.
	S.89°58'W., bet. secs. 13 and 24.
	Over rolling sandy desert land; asc. 50 ft. over gentle E. slope.
39.98	Point for the $\frac{1}{4}$ sec. cor. of secs. 13 and 24.
	Set an iron post, 30 ins. long, $2\frac{1}{2}$ ins. diam., 22 ins. in the ground, with brass cap mkd.

Chains	
	<p style="text-align: center;">T41N R7E S13 $\frac{1}{4}$ S24 1961</p> <p>No accessories available.</p> <p>Continue over rolling sandy land.</p>
41.60	Top of sandy rise, bears N. and S.; desc. 50 ft. over SW. slope.
59.30	Wash, 3 ft. deep, 40 lks. wide; drains SE., asc. 60 ft. over SE. slope.
79.96	The cor. of secs. 13, 14; 23 and 24.
	<p>Land, rolling. Soil, sand. Timber, none; black brush and bunch grass undergrowth.</p> <hr/> <p>N.0°01'W., bet. secs. 13 and 14.</p> <p>Over rolling sandy desert land; desc. 10 ft. over gentle NE. slope.</p>
7.70	Wash, 2 ft. deep, 20 lks. wide, drains SE.; asc. 70 ft. over SE. slope.
33.80	Low sandy spur, slopes E., thence along sandy E. slope.
40.00	Point for the $\frac{1}{4}$ sec. cor. of secs. 13 and 14.
	Set an iron post, 30 ins. long, $2\frac{1}{2}$ ins. diam., 24 ins. in the ground, with brass cap mkd.
	<p style="text-align: center;">T41N R7E $\frac{1}{4}$ S14 S13 1961</p> <p>No accessories available.</p> <p>Continue along gentle E. slope.</p>
80.00	Point for the cor. of secs. 11, 12, 13 and 14.
	Set an iron post, 30 ins. long, $2\frac{1}{2}$ ins. diam., 24 ins. in the ground, with brass cap mkd.
	<p style="text-align: center;">T41N R7E S11 S12 S14 S13 1961</p> <p>No accessories available.</p> <p>Land, rolling. Soil, sand. Timber, none; black brush and bunch grass undergrowth.</p> <hr/> <p>From the cor. of secs. 7, 12, 13 and 18 on the E. bdy., monumented by an iron post, 2 ins. diam., set, mkd. and witnessed as described in the official record.</p> <p>S.89°57'W., bet. secs. 12 and 13.</p> <p>Over rolling sandy desert land, along gentle S. slope.</p>

Chains 40.00	<p>Point for the $\frac{1}{4}$ sec. cor. of secs. 12 and 13.</p> <p>Set an iron post, 30 ins. long, $2\frac{1}{2}$ ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T41N R7E $\frac{1}{4}$ <u>S12</u> S13 1961</p>
	<p>No accessories available.</p> <p>Continue along gentle S. slope.</p>
41.20	Trail road, bears N.15°W. and S.15°E., continue along S. slope.
45.50	Small wash, drains SE.; asc. 40 ft. over gentle E. slope.
80.00	The cor. of secs. 11, 12, 13 and 14.
	<p>Land, rolling. Soil, sand. Timber, none; black brush and bunch grass undergrowth.</p>
	<p>N.0°01'W., bet. secs. 11 and 12.</p> <p>Over sandy desert land; desc. 10 ft. along gentle E. slope.</p>
29.80	Small wash, drains SE.; asc. 10 ft. over gentle S. slope.
40.00	Point for the $\frac{1}{4}$ sec. cor. of secs. 11 and 12.
	<p>Set an iron post, 30 ins. long, $2\frac{1}{2}$ ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T41N R7E $\frac{1}{4}$ <u>S11</u> S12 1961</p>
	<p>No accessories available.</p> <p>Asc. 90 ft. over gentle S. slope.</p>
80.00	Point for the cor. of secs. 1, 2, 11 and 12.
	<p>Set an iron post, 30 ins. long, $2\frac{1}{2}$ ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T41N R7E <u>S2</u> S1 S11 S12 1961</p>
	<p>No accessories available.</p> <p>Land, rolling. Soil, sand. Timber, none; black brush and bunch grass undergrowth.</p>
	<p>From the cor. of secs. 1, 6, 7 and 12 on the E. bdy., monumented by an iron post, 2 ins. diam., set, mkd. and witnessed as described in the official record.</p>
	S.89°58' W., bet. secs. 1 and 12.
	Over sandy desert land, asc. 25 ft. along gentle N. slope.

Chains	
28.60	Unimproved road, bears N.50°E. and S.50°W.
28.80	Power line, parallel road.
40.04	Point for the $\frac{1}{4}$ sec. cor. of secs. 1 and 12. Set an iron post, 30 ins. long, $2\frac{1}{2}$ ins. diam., 24 ins. in the ground, with brass cap mkd.
	T41N R7E S1 $\frac{1}{4}$ S12 1961
	No accessories available.
	Continue along S. slope.
50.40	Small stock pond enclosed in barbed wire fence, also wash which drains NE.; asc. 120 ft. over sandy E. slope with barren sandstone outcrops.
63.70	Barbed wire fence, bears N.20°E. and S.20°W.; asc. 50 ft. over E. slope.
67.20	Crest steep ascent, bears E. and W., asc. 5 ft. over gentle E. slope.
68.40	Trail road, bears N. and S., irregular.
80.08	The cor. of secs. 1, 2, 11 and 12. Land, rolling and broken. Soil, sand and some exposed sandstone. Timber, none; black brush and bunch grass undergrowth.
	N.0°06'E., bet. secs. 1 and 2.
	Over rolling sandy desert land; asc. 70 ft. over gentle S. slope.
40.00	Point for the $\frac{1}{4}$ sec. cor. of secs. 1 and 2. Set an iron post, 30 ins. long, $2\frac{1}{2}$ ins. diam., 24 ins. in the ground, with brass cap mkd.
	T41N R7E $\frac{1}{4}$ S2 S1 1961
	No accessories available.
	Asc. 55 ft. over gentle S. slope.
70.80	Top of ascent, bears NW. and SE., desc. 100 ft. over sand and exposed sandstone.
79.98	The cor. of secs. 1, 2, 35 and 36 on the N. bdy., monumented by an iron post, 1 in diam., set, mkd. and witnessed as described in the field notes of the survey of the S. bdy. of T.42 N., R.7 E. Land, rolling and broken. Soil, sand and exposed sandstone. Timber, none; black brush and bunch grass undergrowth.

Chains

From the cor. of secs. 25, 26, 35 and 36.

N.89°57'W., bet. secs. 26 and 35.

Over broken land, across irregular sandstone formation asc. 100 ft. over NE. slope.

14.00 Spur, slopes SE.; desc. 90 ft. over SW. slope.

17.50 Small draw, drains SE.; asc. 160 ft. over NE. slope.

29.50 Spur, slopes SE.; desc. 90 ft. over SW. slope.

32.60 Small draw, drains SE., asc. 30 ft. over NE. slope in draw.

33.86 Point selected for the witness $\frac{1}{4}$ sec. cor. of secs. 26 and 35.

Drilled an iron post, 18 ins. long, 1 in. diam., 8 ins. in solid sandstone, with brass cap mkd.

T41N R7E
W S26
 $\frac{1}{4}$ C S35
1961

Asc. about 400 ft. over irregular and inaccessible sandstone ledges facing generally NE. By traverse.

40.00 Point for the $\frac{1}{4}$ sec. cor. of secs. 26 and 35, falls on inaccessible ledges and cannot be monumented.

68.50 Top of ascent on E. rim of Paria Canyon, bears NW. and SE., desc. about 400 ft. over irregular sandstone formation and ledges facing SW., by triangulation and traverse.

80.00 The true point for the cor. of secs. 26, 27, 34 and 35.

From the true point the witness cor. bears S.0°01'E. 42 lks. dist., monumented by an iron post, 2 ins. diam., set, mkd. and witnessed as described in the official records of the 1927 survey by Otis D. Gould.

Land, broken.
Soil, sand and exposed sandstone.
Timber, none.

N.0°01'W., bet. secs. 26 and 27.

Over broken land of E. breaks of Paria Canyon, asc. about 500 ft. over ledges facing SW.

6.90 E. rim Paria Canyon, bears NW. and SE.; desc. 320 ft. over N. slope. Across barren and irregular sandstone formation.

39.00 Small wash, drains E.; asc. broken SE. slope.

40.00 Point for the $\frac{1}{4}$ sec. cor. of secs. 26 and 27.

Drilled an iron post, 18 ins. long, 1 in. diam., 8 ins. in solid sandstone, with brass cap mkd.

T41N R7E
 $\frac{1}{4}$
S27 | S26
1961

Chains
 Asc. 20 ft. over SE. slope.
 42.30 Small spur, slopes E.; asc. 40 ft. along broken E. slope.
 54.90 Spur, slopes E.; desc. 80 ft. over NE. slope.
 64.70 Wash, drains E.; asc. 35 ft. over S. slope.
 66.30 Sandy rise; slopes SE.; desc. 30 ft. over sandy NE. slope.
 80.00 Point for the cor. of secs. 22, 23, 26 and 27.
 Set an iron post, 30 ins. long, $2\frac{1}{2}$ ins. diam., 24 ins. in the ground, with brass cap mkd.

T41N R7E
 S22|S23
 S27|S26
 1961

No accessories available.

Land, broken.
 Soil, sand and exposed sandstone.
 Timber, very scattered scrub juniper.

From the cor. of secs. 23, 24, 25 and 26.

S.89°57'W., bet. secs. 23 and 26.

Over broken desert land; asc. 130 ft. over NE. slope.

24.30 Spur, slopes NW.; desc. 50 ft. over SW. slope.
 27.60 Wash, 3 ft. deep, 20 lks. wide, drains NW.; asc. 40 ft. along S. slope.
 36.10 Small spur, slopes N.; desc. 10 ft. over W. slope.
 39.15 Point selected for the witness $\frac{1}{4}$ sec. cor. of secs. 23 and 26.
 Set an iron post, 30 ins. long, $2\frac{1}{2}$ ins. diam., on solid rock, over an X, and in a mound of stone to top, with brass cap mkd.

T41N R7E
 $\frac{1}{4}W \leftarrow S23$
 $\frac{1}{4}C \leftarrow S26$
 1961

Desc. W. slope.

40.00 Point for the $\frac{1}{4}$ sec. cor. of secs. 23 and 26, falls on small ledge facing W. and cannot be perpetuated.
 40.55 Small draw, drains N.; asc. 340 ft. over NE. slope, across sand and exposed sandstone.
 80.00 The cor. of secs. 22, 23, 26 and 27.

Land, broken.
 Soil, sand and exposed sandstone.
 Timber, none.

N.0°01'W., bet. secs. 22 and 23.

Over broken desert land, desc. 55 ft. over NE. slope.

Chains

- 22.20 Wash, 3 ft. deep, 50 lks. wide, drains E.; asc. 10 ft. along E. slope.
- 28.80 Small wash, drains E.; asc. 165 ft. over broken S. slope.
- 35.30 Top of ascent, bears E. and W.; desc. 30 ft. over gentle NE. slope, on top of spur.
- 40.00 Point for the $\frac{1}{4}$ sec. cor. of secs. 22 and 23.

Set an iron post, 30 ins. long, $2\frac{1}{2}$ ins. diam., on solid rock, over an X, and in a mound of stone to top, with brass cap mkd.

T41N R7E

$\frac{1}{4}$
S22 | S23
1961

Desc. 35 ft. over NE. slope on top of spur.

- 60.60 Top of steep descent, bears NW. and SE.; desc. 160 ft. over NE. slope.
- 80.00 Point for the cor. of secs. 14, 15, 22 and 23.

Set an iron post, 30 ins. long, $2\frac{1}{2}$ ins. diam., 24 ins. in the ground, with brass cap mkd.

T41N R7E

S15 | S14
S22 | S23
1961

Land, broken.

Soil, sand and exposed sandstone.

Timber, none; black brush and bunch grass undergrowth.

From the cor. of secs. 13, 14, 23 and 24.

N.89°55'W., bet. secs. 14 and 23.

Over broken desert land, asc. 295 ft. over NE. slope, across sand and exposed patches of sandstone.

- 40.04 Point for the $\frac{1}{4}$ sec. cor. of secs. 14 and 23.

Set an iron post, 30 ins. long, $2\frac{1}{2}$ ins. diam., 22 ins. in the ground, and in a collar of stone, with brass cap mkd.

T41N R7E

$\frac{1}{4}$ $\frac{S14}{S23}$
1961

Asc. 295 ft. over NE. slope.

- 80.08 The cor. of secs. 14, 15, 22 and 23.

Land, broken.

Soil, sand and exposed sandstone.

Timber, none; black brush and bunch grass undergrowth.

N.0°01'W., bet. secs. 14 and 15.

Over broken desert land, desc. 165 ft. over NE. slope.

- 25.60 Wash, 2 ft. deep, 20 lks. wide, drains N.80°E.; desc. 65 ft. along E. slope. Enter sandy rolling desert land.

Chains	
40.00	<p>Point for the $\frac{1}{4}$ sec. cor. of secs. 14 and 15.</p> <p>Set an iron post, 30 ins. long, $2\frac{1}{2}$ ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T41N R7E $\frac{1}{4}$ S15 S14 1961</p> <p>No accessories available.</p> <p>Continue along gentle E. slope.</p>
66.50	Small wash, drains NE., continue along gentle E. slope.
80.00	<p>Point for the cor. of secs. 10, 11, 14 and 15.</p> <p>Set an iron post, 30 ins. long, $2\frac{1}{2}$ ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T41N R7E S10 S11 S15 S14 1961</p> <p>No accessories available.</p> <p>Land, broken S. portion, rolling N. portion. Soil, sand and exposed sandstone. Timber, none; black brush and bunch grass undergrowth.</p> <hr/> <p>From the cor. of secs. 11, 12, 13 and 14. N.89°59'W., bet. secs. 11 and 14. Over sandy rolling desert land; asc. 60 ft. over gentle E. slope.</p>
40.01	<p>Point for the $\frac{1}{4}$ sec. cor. of secs. 11 and 14.</p> <p>Set an iron post, 30 ins. long, $2\frac{1}{2}$ ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T41N R7E $\frac{1}{4}$ S11 S14 1961</p> <p>No accessories available.</p> <p>Asc. 60 ft. over gentle E. slope.</p>
70.10	Small wash, drains NE.; asc. 20 ft. over gentle E. slope.
80.02	<p>The cor. of secs. 10, 11, 14 and 15.</p> <p>Land, rolling. Soil, sand. Timber, none; black brush and bunch grass undergrowth.</p> <hr/> <p>N.0°01'W., bet. secs. 10 and 11. Over rolling sandy desert land, along gentle E. slope.</p>
40.00	Point for the $\frac{1}{4}$ sec. cor. of secs. 10 and 11.

Chains	Set an iron post, 30 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.
	$\begin{array}{r} T41N R7E \\ \frac{1}{4} \\ S10 S11 \\ 1961 \end{array}$
	No accessories available.
	Continue along gentle E. slope.
43.20	Small wash, drains E., continue along gentle E. slope.
80.00	Point for the cor. of secs. 2, 3, 10 and 11.
	Set an iron post, 30 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.
	$\begin{array}{r} T41N R7E \\ S 3 S 2 \\ S10 S11 \\ 1961 \end{array}$
	No accessories available.
	Land, rolling. Soil, sand. Timber, none; black brush and bunch grass undergrowth.
	From the cor. of secs. 1, 2, 11 and 12.
	West, bet. secs. 2 and 11.
	Over sandy desert land; desc. 40 ft. along gentle S. slope.
37.90	Trail road, bears N. 15°W. and E. irregular.
40.01	Point for the ¼ sec. cor. of secs. 2 and 11.
	Set an iron post, 30 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.
	$\begin{array}{r} T41N R7E \\ \frac{1}{4} \quad S 2 \\ \quad \quad S11 \\ 1961 \end{array}$
	No accessories available.
	Desc. 25 ft. along gentle S. slope.
54.90	Wash, 2 ft. deep, 30 lks. wide, drains SE.; asc. 30 ft. over gentle E. slope.
80.02	The cor. of secs. 2, 3, 10 and 11.
	Land, rolling. Soil, sand. Timber, none; black brush and bunch grass undergrowth.
	N.0°05'E., bet. secs. 2 and 3.
	Over rolling sandy desert land; asc. 25 ft. along gentle E. slope.
13.30	Barbed wire fence, bears E. and W.

Chains

40.00

Point for the $\frac{1}{4}$ sec. cor. of secs. 2 and 3.Set an iron post, 30 ins. long, $2\frac{1}{2}$ ins. diam., 24 ins. in the ground, with brass cap mkd.

T41N R7E

 $\frac{1}{4}$
S3|S2

1961

No accessories available.

Continue along gentle E. slope.

44.50

Small wash, drains SE.; asc. 70 ft. over gentle S. slope.

80.06

The cor. of secs. 2, 3, 34 and 35, on the N. bdy., monumented by an iron post, $2\frac{1}{2}$ ins. diam., set, mkd. and witnessed as described in the field notes of the survey of the S. bdy. of T.42 N., R.7 E.

Land, rolling.

Soil, sand.

Timber, none; black brush and bunch grass undergrowth.

From the cor. of secs. 27, 28, 33 and 34 monumented by an iron post, 2 ins. diam., set, mkd. and witnessed as described in the official record of the 1927 survey.

N.0°02'W., bet. secs. 27 and 28.

Over broken land of E. breaks of Paria Canyon; asc. 35 ft. over SW. slope.

4.40

Small spur, slopes W.; desc. 40 ft. over NW. slope.

10.50

Ravine, drains W.; asc. 300 ft. over steep SW. slope.

20.90

Spur, slopes W.; desc. 200 ft. over NW. slope.

27.50

Draw, drains W.; asc. 160 ft. over S. slope.

32.00

Point selected for the witness $\frac{1}{4}$ sec. cor. of secs. 27 and 28.Set an iron post, 30 ins. long, $2\frac{1}{2}$ ins. diam., 10 ins. in the ground, and in a mound of stone to top, with brass cap mkd.

T41N R7E

 $\frac{1}{4}$
W C
S28↑S27

1961

Witness cor. falls on top of small spur sloping W.

Asc. 1600 ft. over ledges facing SW. on E. wall of Paria Canyon. By triangulation with topography scaled from U.S.G.S. sheets.

40.00

Point for the $\frac{1}{4}$ sec. cor. of 27 and 28 falls on E. wall of Paria Canyon and cannot be monumented.

62.40

Crest of E. rim of Paria Canyon, bears NW. and SE.; desc. 200 ft. over irregular N. slope.

80.00

Point for the cor. of secs. 21, 22, 27 and 28.

Set an iron post, 30 ins. long, $2\frac{1}{2}$ ins. diam., 10 ins. in the ground, and in a mound of stone to top, with brass cap mkd.

Chains

T41N R7E
 S21 | S22
 S28 | S27
 1961

Land, broken.
 Soil, sand and exposed sandstone.
 Timber, very scattered scrub juniper and pinion.

From the cor. of secs. 22, 23, 26 and 27.

S.89°53'W., bet. secs. 22 and 27.

Over broken desert land, asc. 100 ft. over E. slope, by triangulation with topography scaled from U.S.G.S. sheets.

13.00 Base steep ascent, bears N. and S.; asc. 240 ft. over steep and ledgy E. slope.

24.20 Top of ascent on butte about 2 chs. diam.; desc. 85 ft. over NW. slope.

39.93 Point for the $\frac{1}{4}$ sec. cor. of secs. 22 and 27.

Set an iron post, 30 ins. long, $2\frac{1}{2}$ ins. diam., 6 ins. in the ground, and in a mound of stone to top, with brass cap mkd.

T41N R7E
 $\frac{1}{4}$ S22
 S27
 1961

Corner falls on spur which slopes N.

Desc. 130 ft. over irregular W. slope.

53.50 Ravine, drains N.10°E.; asc. 110 ft. over NE. slope.

79.86 The cor. of secs. 21, 22, 27 and 28.

Land, broken.
 Soil, sand and exposed sandstone.
 Timber, scrub juniper and pinion.

N.0°02'W., bet. secs. 21 and 22.

Over broken desert land; desc. 75 ft. over sandy NE. slope.

29.10 Wash, 3 ft. deep, 20 lks. wide, drains N.80°E.; asc. 45 ft. over sandy SE. slope.

40.00 Point for the $\frac{1}{4}$ sec. cor. of secs. 21 and 22.

Set an iron post, 30 ins. long, $2\frac{1}{2}$ ins. diam., 24 ins. in the ground, with brass cap mkd.

T41N R7E
 $\frac{1}{4}$ S21 | S22
 1961

No accessories available.

Asc. 30 ft. over SE. slope.

58.50 Spur, slopes E.; desc. 150 ft. over N. slope.

Chains

- 75.10 Wash, 3 ft. deep; 20 lks wide, drains NE.; asc. 35 ft. over S. slope.
- 79.72 Point selected for the witness cor. of secs. 15, 16, 21 and 22.
Set an iron post, 30 ins. long, $2\frac{1}{2}$ ins. diam., 8 ins. in the ground, and in a mound of stone to top, with brass cap mkd.
- T41N R7E
W C
S16 | S15
S21 | S22
1961
- 80.00 Point for the cor. of secs. 16, 15, 21 and 22.
Falls on small ledge facing S. and cannot be perpetuated.
Land, broken.
Soil, sand and exposed sandstone.
Timber, very scattered scrub juniper and pinon.
-
- From the cor. of secs. 14, 15, 22 and 23.
S. $89^{\circ}54'W.$, bet. secs. 15 and 22.
Over broken desert land; asc. 90 ft. over NE. slope.
- 12.00 Small draw, drains NE.; asc. 105 ft. over NE. slope.
- 39.90 Point for the $\frac{1}{4}$ sec. cor. of secs. 15 and 22.
Set an iron post, 30 ins. long, $2\frac{1}{2}$ ins. diam., 12 ins. in the ground, and in a mound of stone to top, with brass cap mkd.
- T41N R7E
 $\frac{1}{4}$ S15
S22
1961
- Asc. 100 ft. over NE. slope.
- 65.60 Spur, slopes N.; desc. 30 ft. over W. slope.
- 71.50 Wash, 2 ft. deep, 20 lks. wide, drains NE.; asc. 65 ft. along S. slope.
- 79.80 The true point for the cor. of secs. 15, 16, 21 and 22.
Land, broken.
Soil, sand and exposed sandstone.
Timber, scattered scrub pinon and juniper.
-
- N. $0^{\circ}02'W.$, bet. secs. 15 and 16.
Over broken desert land; asc. 65 ft. over S. slope.
- 2.20 Top of rise, bears W. and NE.; desc 280 ft. over rocky N. slope of rise.
- 35.00 Wash, 5 ft. deep, 50 lks. wide, drains N. $80^{\circ}E.$, also small sandy draw; asc. 85 ft. over SE. slope.
- 38.00 Low sandy spur, slopes E.; desc. 15 ft. along gentle E. slope over rolling sandy land.
- 40.00 Point for the $\frac{1}{4}$ sec. cor. of secs. 15 and 16.

Chains	
	<p>Set an iron post, 30 ins. long, $2\frac{1}{2}$ ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T41N R7E $\frac{1}{4}$ S16 S15 1961</p>
	No accessories available.
	Desc. 40 ft. along gentle E. slope.
57.60	Small wash, drains E.; desc. 20 ft. along gentle E. slope.
80.00	Point for the cor. of secs. 9, 10, 15 and 16.
	<p>Set an iron post, 30 ins. long, $2\frac{1}{2}$ ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T41N R7E S9 S10 <u> </u> S16 S15 1961</p>
	No accessories available.
	<p>Land, broken S. portion, rolling N. portion. Soil, sand and exposed sandstone. Timber, none; black brush and bunch grass undergrowth.</p>
	<p>From the cor. of secs. 10, 11, 14 and 15.</p> <p>S.89°56'W., bet. secs. 10 and 15.</p> <p>Over rolling sandy desert land; asc. 80 ft. over gentle E. slope.</p>
39.91	Point for the $\frac{1}{4}$ sec. cor. of secs. 10 and 15.
	<p>Set an iron post, 30 ins. long, $2\frac{1}{2}$ ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T41N R7E $\frac{1}{4}$ S10 <u> </u> S15 1961</p>
	No accessories available.
	Asc. 60 ft. over gentle E. slope.
79.82	The cor. of secs. 9, 10, 15 and 16.
	<p>Land, rolling. Soil, sand. Timber, none; black brush and bunch grass undergrowth.</p>
	N.0°02'W., bet. secs. 9 and 10.
	Over rolling sandy land, along gentle E. slope.
7.00	Small wash, drains E.
25.90	Small wash, drains E.
40.00	Point for the $\frac{1}{4}$ sec. cor. of secs. 9 and 10.

Chains

Set an iron post, 30 ins. long, $2\frac{1}{2}$ ins. diam., 24 ins. in the ground, with brass cap mkd.

T41N R7E
 $\frac{1}{4}$
 S9 | S10
 1961

No accessories available.

Continue along gentle E. slope.

46.50 Wash, 2 ft. deep, 20 lks. wide, drains E.

68.00 Wash, 2 ft. deep, 20 lks. wide, drains E.

71.78 Barbed wire fence, bears N.75°E. and S.75°W.

80.00 Point for the cor. of secs. 3, 4, 9 and 10.

Set an iron post, 30 ins. long, $2\frac{1}{2}$ ins. diam., 24 ins. in the ground, with brass cap mkd.

T41N R7E
 S4 | S3
 S9 | S10
 1961

No accessories available.

Land, rolling.

Soil, sand.

Timber, none; black brush and bunch grass undergrowth.

From the cor. of secs. 2, 3, 10 and 11.

S.89°57'W., bet. secs. 3 and 10.

Over sandy rolling desert land; asc. 85 ft. over gentle E. slope.

39.90 Point for the $\frac{1}{4}$ sec. cor. of secs. 3 and 10.

Set an iron post, 30 ins. long, $2\frac{1}{2}$ ins. diam., 24 ins. in the ground, with brass cap mkd.

T41N R7E
 $\frac{1}{4}$ S3
 S10
 1961

No accessories available.

Asc. 80 ft. over gentle E. slope.

49.43 Barbed wire fence, bears N.75°E. and S.75°W.

79.80 The cor. of secs. 3, 4, 9 and 10.

Land, rolling.

Soil, sand.

Timber, none; black brush and bunch grass undergrowth.

N.0°04'W., bet. secs. 3 and 4.

Over sandy rolling desert land, desc. 20 ft. along gentle E. slope.

36.50 Small wash, drains E.

Chains

40.00

Point for the $\frac{1}{4}$ sec. cor. of secs. 3 and 4.

Set an iron post, 30 ins. long, $2\frac{1}{2}$ ins. diam., 24 ins. in the ground, with brass cap mkd.

T41N R7E

 $\frac{1}{4}$

S4 | S3

1961

No accessories available.

Continue along gentle E. slope.

80.10

The cor. of secs. 3, 4, 33 and 34 on the N. bdy., marked by an iron post, $2\frac{1}{2}$ ins. diam., set, mkd., and witnessed as described in the field notes of the survey of the S. bdy. of T.42 N., R.7E.

Land, rolling.

Soil, sand.

Timber, none; black brush and bunch grass undergrowth.

From the true point for the standard cor. of secs. 32 and 33 on the S. bdy.

From the true point the witness standard cor. of secs. 32 and 33 bears East, 4.21 chs. dist., monumented by an iron post, 2 ins. diam., set, mkd. and witnessed as described in the official record.

N. $0^{\circ}03'W.$, bet. secs. 32 and 33.

Over broken W. breaks of Paria Canyon; desc. about 350 ft. over ledges facing E., by triangulation with topography scaled from U.S.G.S. sheets.

18.00

Base of ledges in Paria Canyon, bears S. and curves NW.; desc. 300 ft. along W. slope of sandy spur.

40.00

Point for the $\frac{1}{4}$ sec. cor. of secs. 32 and 33.

Set an iron post, 30 ins. long, $2\frac{1}{2}$ ins. diam., 24 ins. in the ground, with brass cap mkd.

T41N R7E

 $\frac{1}{4}$

S32 | S33

1961

No accessories available.

Desc. 45 ft. along E. slope of sandy spur.

50.00

Top of spur, slopes $N.10^{\circ}W.$; desc. 270 ft. over NE. slope of sandy spur, in bottom of Paria Canyon.

80.00

Point for the cor. of secs. 28, 29, 32 and 33.

Set an iron post, 30 ins. long, $2\frac{1}{2}$ ins. diam., 24 ins. in the ground, with brass cap mkd.

T41N R7E

S29 | S28

S32 | S33

1961

No accessories available.

Chains

Land, broken.
Soil, sand and exposed sandstone.
Timber, none; very little vegetation.

From the cor. of secs. 27, 28, 33 and 34, monumented by an iron post, 2 ins. diam., set, mkd. and witnessed as described in the official record.

West, bet. secs. 28 and 33.

Over broken land in bottom of Paria Canyon; desc. 235 ft. over W. slope.

12.70 Center Paria River, drains S.20°E. from NW., small stream of water 6 ins. deep, 10 lks. wide, asc. 250 ft. over sandy NE. slope.

39.98 Point for the $\frac{1}{4}$ sec. cor. of secs. 28 and 33.

Set an iron post, 30 ins. long, $2\frac{1}{2}$ ins. diam. 24 ins. in the ground, with brass cap mkd.

T41N R7E
 $\frac{1}{4}$ $\frac{S28}{S33}$
1961

No accessories available.

Asc. 240 ft. over rolling sandy NE. slope.

79.96 The cor. of secs. 28, 29, 32 and 33.

Land, rolling.
Soil, sand and exposed sandstone.
Timber, none; sparse vegetation.

N.0°03'W., bet. secs. 28 and 29.

Over broken sand hills in bottom of Paria Canyon; desc. 40 ft. over NE. slope.

4.50 Top of sandy spur, slopes N. 20°E.; desc. 160 ft. over NW. slope into sandy draw.

8.60 Wash in bottom of draw, drains NE.; asc. 80 ft. over SE. slope.

12.70 Sandy spur, slopes E.; desc. 250 ft. over NE. slope.

38.50 Right bank Paria River Channel, bears NW. and SE., thence across channel.

40.00 Point for the $\frac{1}{4}$ sec. cor. of secs. 28 and 29, falls in river channel and cannot be monumented.

41.70 Center of small stream of water, 8 ins. deep, 30 lks. wide, course SE.

42.00 Left bank same river, bears NW. and SE.; asc. 10 ft. over SW. slope.

42.50 Point selected for the witness $\frac{1}{4}$ sec. cor. of secs. 28 and 29.

Set an iron post, 30 ins. long, $2\frac{1}{2}$ ins. diam., 24 ins. in the ground, and in a collar of stone, with brass cap mkd.

Chains

T41N R7E

$$\frac{1}{4}$$
 S29 ↓ S28

 W C
 1961

Asc. 250 ft. over SW. slope.

56.20 Spur, slopes W.; desc. 80 ft. along broken W. slope.

68.20 Wash in bottom of draw, drains S.30°W. from irregular N.; asc. 40 ft. up broken bottom of draw.

76.40 Leave bottom of draw which forks NW. and NE.; asc. 100 ft. along E. slope of spur which slopes S.

80.00 True point for the cor. of secs. 20, 21, 28 and 29, falls on ledges facing E. and cannot be perpetuated. The witness cor. bears N.89°53'W., 0.54 chs. dist.

Land, broken.

Soil, sand and exposed sandstone.

Timber, none; very little vegetation.

From the cor. of secs. 21, 22, 27 and 28.

West, bet. secs. 21 and 28.

Over broken desert land, across barren sandstone; asc. 125 ft. over NE. slope.

12.20 Spur, slopes NE.; desc. 20 ft. over NW. slope.

16.40 Small draw, drains N.30°E.; asc. 160 ft. over broken E. slope.

31.57 Point selected for the witness $\frac{1}{4}$ sec. cor. of secs. 21 and 28.Set an iron post, 30 ins. long, $2\frac{1}{2}$ ins. diam., on solid sandstone, over an X, and in a mound of stone to top, with brass cap mkd.

T41N R7E

$$\frac{1}{4}$$
 ← W S21
 C S28

1961

Continue over broken land.

31.70 E. rim Paria Canyon, bears N. and curves SE.; desc. 1000 ft. over ledges facing W., by triangulation with topography scaled from U.S.G.S. sheets.

39.95 True point for the $\frac{1}{4}$ sec. cor. of secs. 21 and 28 falls on inaccessible ledges of canyon and cannot be monumented.

49.00 Ravine, drains SW.; desc. 800 ft. over ledges facing SW.

78.50 Wash, drains S.; asc. 30 ft. over E. slope of small spur.

79.90 The true point for the cor. of secs. 20, 21, 28 and 29. The witness cor. bears N.89°53'W., 0.54 chs. dist.

Land, broken.

Soil, sand and exposed sandstone.

Timber, scattered scrub juniper and pinon on higher elevations; very little undergrowth.

Chains

N.0°03'W., bet. secs. 20 and 21.

Over broken and inaccessible ledges of E. breaks of Paria Canyon; asc. 2000 ft. over ledges facing SW.

40.00 Point for the $\frac{1}{4}$ sec. cor. of secs. 20 and 21, falls on inaccessible ledges facing SW. and cannot be monumented.

41.50 Crest of E. rim of Paria Canyon, bears NW. and SE.; asc. SW. slope.

41.59 Point selected for the witness $\frac{1}{4}$ sec. cor. of secs. 20 and 21.

Set an iron post, 30 ins. long, $2\frac{1}{2}$ ins. diam., on solid sandstone, over an X, and in a mound of stone to top, with brass cap mkd.

T41N R7E

$\frac{1}{4}$
S20 | S21

W C

1961

Asc. 30 ft. over SW. slope.

48.30 Top of ascent, bears NW. and E.; desc. 145 ft. over broken N. slope.

76.40 Draw, drains SE.; asc. 35 ft. over S. slope.

80.00 Point for the cor. of secs. 16, 17, 20 and 21.

Set an iron post, 30 ins. long, $2\frac{1}{2}$ ins. diam., on solid rock, over an X, and in a mound of stone to top, with brass cap mkd.

T41N R7E

S17 | S16

S20 | S21

1961

Land, broken.

Soil, sand and exposed sandstone.

Timber, scattered scrub pinon and juniper.

From the true point for the cor. of secs. 15, 16, 21 and 22. The witness cor. bears S.0°02'E., 0.28 chs. dist.

West, bet. secs. 16 and 21.

Over broken desert land; asc. 240 ft. over rocky E. slope.

36.00 Base steep ascent, bears N. and S.; asc. 120 ft. over rocky E. slope.

39.98 Point for the $\frac{1}{4}$ sec. cor. of secs. 16 and 21.

Set an iron post, 30 ins. long, $2\frac{1}{2}$ ins. diam., 4 ins. in the ground, to bedrock, and in a mound of stone to top, with brass cap mkd.

T41N R7E

$\frac{1}{4}$ S16

S21

1961

Asc. 100 ft. over E. slope.

50.20 Spur, slopes NE.; desc. 50 ft. over NW. slope.

58.00 Wash, 2 ft. deep, 20 lks. wide, drains NE.; asc. 170 ft. over E. slope.

72.30 Slope changes, desc. 20 ft. along S. slope of spur.

Chains	
79.96	The cor. of secs. 16, 17, 20 and 21. Land, broken desert. Soil, sand and exposed sandstone. Timber, scattered scrub juniper and pinon.
	N.0°03'W., bet. secs. 16 and 17. Over broken land, across mostly barren sandstone, asc. 30 ft. over S. slope.
5.20	Spur, slopes E.; desc. 70 ft. over N. slope.
15.50	Draw, drains E.; asc. 60 ft. over SE. slope.
26.00	Spur, slopes E.; desc. 100 ft. over NE. slope.
34.20	Draw, drains E.; asc. 60 ft. over SE. slope.
40.00	Point for the $\frac{1}{4}$ sec. cor. of secs. 16 and 17. Set an iron post, 30 ins. long, $2\frac{1}{2}$ ins. diam., 6 ins. in the ground, and in a mound of stone to top, with brass cap mkd.
	T41N R7E $\frac{1}{4}$ S17 S16 1961
	Asc. 30 ft. over SE. slope.
41.90	Top of small broken bench; desc. 40 ft. along E. slope.
72.50	Small spur, slopes N.80°E.; desc. 60 ft. over NE. slope.
78.00	Small wash, drains N.45°E.; asc. 20 ft. over SE. slope.
80.00	Point for the cor. of secs. 8, 9, 16 and 17. Set an iron post, 30 ins. long, $2\frac{1}{2}$ ins. diam., 10 ins. in the ground, and in a mound of stone to top, with brass cap mkd.
	T41N R7E S8 S9 S17 S16 1961
	Land, broken. Soil, sand and exposed sandstone. Timber, scattered scrub juniper and pinon.
	From the cor. of secs. 9, 10, 15 and 16. West, bet. secs. 9 and 16. Over rolling sandy desert land, draining NE., asc. 70 ft. over gentle E. slope.
25.00	Head of wash, also base of steep ascent, bears N. and S. irregular; asc. 200 ft. over broken and ledgy NE. slope.
40.00	Point for the $\frac{1}{4}$ sec. cor. of secs. 9 and 16. Set an iron post, 30 ins. long, $2\frac{1}{2}$ ins. diam., on solid rock, over an X, and in a mound of stone to top, with brass cap mkd.

Chains

T41N R7E

$$\frac{1}{4} \frac{S9}{S16}$$
 1961

Slope changes; asc. 200 ft. over broken and ledgy E. slope.

50.50 Ledgy spur, slopes NE.; asc. 250 ft. over broken NE. slope.

78.50 Wash, drains NE.; asc. 15 ft. over SE. slope.

80.00 The cor. of secs. 8, 9, 16 and 17.

Land, broken and ledgy W. portion, rolling sandy E. portion.
Soil, sand and sandstone W. portion, sand E. portion.
Timber, scattered scrub juniper on W. portion, no timber on E. portion.

N.0°03'W., bet. secs. 8 and 9.

Over broken desert land, asc. 10 ft. over SE. slope.

8.00 Rise, bears E. and W.; desc. 50 ft. over gentle NE. slope.

31.90 Slope changes; desc. 80 ft. over N. slope into draw.

40.00 Point for the $\frac{1}{4}$ sec. cor. of secs. 8 and 9, falls on low sandstone ledge facing N. and cannot be perpetuated. Chisled an X, 8 ins. high, at true point.40.05 Point selected for the witness $\frac{1}{4}$ sec. cor. of secs. 8 and 9.Set an iron post, 30 ins. long, $2\frac{1}{2}$ ins. diam., on solid rock, over an X, and in a mound of stone to top, with brass cap mkd.

T41N R7E

$$\frac{1}{4} \frac{S8 \downarrow S9}{WC}$$
 1961

Cor. falls on S. rim of draw, which bears E. and curves NW.; desc. 160 ft. over N. slope.

45.10 Bottom of draw, drains E.; asc. 120 ft. over ledgy S. slope.

53.00 N. rim same draw, bears E. and curves SW.; asc. 60 ft. over sandy SE. slope.

59.20 Sandy spur, slopes NE.; desc. 50 ft. over N. slope.

66.90 Wash, 4 ft. deep, 30 lks. wide, drains E.; desc. 20 ft. along E. slope.

80.00 Point for the cor. of secs. 4, 5, 8 and 9.

Set an iron post, 30 ins. long, $2\frac{1}{2}$ ins. diam., 15 ins. in the ground, and in a mound of stone to top, with brass cap mkd.

T41N R7E

$$\frac{S5 \downarrow S4}{S8 \downarrow S9}$$
 1961

Land, broken.
Soil, sand and exposed sandstone.
Timber, scattered scrub juniper and pinon.

Chains	
	From the cor. of secs. 3, 4, 9 and 10.
	West, bet. secs. 4 and 9.
	Over sandy rolling desert land, draining E.; asc. 95 ft. over gentle E. slope.
39.97	Point for the $\frac{1}{4}$ sec. cor. of secs. 4 and 9.
	Set an iron post, 30 ins. long, $2\frac{1}{2}$ ins. diam., 24 ins. in the ground, with brass cap mkd;
	<p style="text-align: center;">T41N R7E $\frac{1}{4}$ $\frac{S4}{S9}$ 1961</p>
	No accessories available.
	Cor. falls about 1 ch. S. of wash; asc. 80 ft. over sandy E. slope of small spur.
48.90	Spur; slopes N.; desc. 60 ft. over NW. slope.
58.80	Head of wash which drains N. 45° E., also base of steep ascent which bears SW. and NE.; asc. 350 ft. over steep SE. slope and ledges facing SE.
65.10	Rim, bears N. and S. irregular; also top of sandstone knob, about 30 ft. high, 20 ft. diam.; asc. 110 ft. over E. slope of broken bench.
79.94	The cor. of secs. 4, 5, 8 and 9.
	Land, broken W. portion, rolling E. portion. Soil, sand and exposed sandstone W. portion, sand E. portion. Timber, scattered juniper and pinon W. portion.
	N. $0^{\circ}07'W.$, bet. secs. 4 and 5.
	Over broken desert land, desc. 20 ft. along E. slope.
4.60	Wash, 3 ft. deep, 30 lks. wide, drains E.; desc. 15 ft. along E. slope.
16.20	Wash, 2 ft. deep, 30 lks. wide; drains E.; desc. 60 ft. along E. slope.
33.10	Slope changes, desc. 120 ft. into head of small draw.
39.50	Point selected for the witness $\frac{1}{4}$ sec. cor. of secs. 4 and 5.
	Set an iron post, 30 ins. long, $2\frac{1}{2}$ ins. diam., 12 ins. in the ground, and in a mound of stone to top; with brass cap mkd.
	<p style="text-align: center;">T41 R7E $\frac{1}{4}$ W C S5 \uparrow S4 1961</p>
40.00	Point for the $\frac{1}{4}$ sec. cor. of secs. 4 and 5, falls in wash, 4 ft. deep, 40 lks. wide, and drains E. Cor. cannot be perpetuated. Asc. 80 ft. along broken E. slope.
56.80	Spur, slopes E.; desc. 100 ft. over broken NE. slope.

Chains

70.00 Head of deep draw, drains E.; asc. 40 ft. along broken E. slope.

80.13 The cor. of secs. 4, 5, 32 and 33 on the N. bdy., marked by an iron post, $2\frac{1}{2}$ ins. diam., set, mkd. and witnessed as described in the field notes of the concurrent survey of the S. bdy. of T.42 N., R.7 E.

Land, broken.

Soil, sand and exposed sandstone.

Timber, scattered juniper and pinon.

From the standard cor. of secs. 31 and 32 on the S. bdy., monumented by an iron post, 2 ins. diam., set, mkd. and witnessed as described in the official record.

N.0°03'W. bet. secs. 31 and 32.

Over rolling gravelly land, on top of Paria Plateau; desc. 100 ft. over gentle NE. slope.

40.00 Point for the $\frac{1}{4}$ sec. cor. of secs. 31 and 32.

Set an iron post, 30 ins. long, $2\frac{1}{2}$ ins. diam., 24 ins. in the ground, with brass cap mkd.

T41N R7E

$\frac{1}{4}$
S31|S32
1961

Desc. 40 ft. over gentle NE. slope of Paria Plateau.

56.80 W. rim of Paria Canyon, bears NW. and SE.; desc. about 1080 ft. over ledges facing NE. and steep NE. slope, by triangulation with topography scaled from U.S.G.S. sheets.

80.00 Point for the cor. of secs. 29, 30, 31 and 32.

Set an iron post, 30 ins. long, $2\frac{1}{2}$ ins. diam., 8 ins. in the ground, and in a mound of stone to top, with brass cap mkd.

T41N R7E

S30|S29
S31|S32
1961

Cor. falls on top of rocky spur, 3 chs. from base of nearly sheer ledges.

Land, rolling S. portion, broken N. portion.

Soil, gravelly S. portion, sand and exposed sandstone N. portion.

Timber, moderate growth of scrub pinion and juniper on the S. portion.

From the cor. of secs. 28, 29, 32 and 33.

N. 89°52'W., bet. secs. 29 and 32.

Over broken sandy land of W. breaks in Paria Canyon; asc. 20 ft. over NE. slope.

4.50 Sandy spur, slopes N.; desc. 90 ft. over sandy NW. slope.

10.20 Wash, drains NE.; asc. 250 ft. over sandy NE. slope.

37.50 Sandy spur, slopes N.; desc. 20 ft. over NW. slope.

Chains 40.01	<p>Point for the $\frac{1}{4}$ sec. cor. of secs. 29 and 32.</p> <p>Set an iron post, 30 ins. long, $2\frac{1}{2}$ ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T41N R7E $\frac{1}{4}$ $\frac{S29}{S32}$ 1961</p> <p>No accessories available.</p> <p>Desc. 40 ft. over sandy NW. slope.</p>
44.80	Wash, 3 ft. deep, 10 lks. wide, drains NE.; asc. 80 ft. over sandy E. slope.
48.00	Sandy spur, slopes N.20°E.; desc. 80 ft. over sandy W. slope.
52.50	Wash, drains N.20°E.; asc. 1000 ft. over steep rocky E. slope.
80.02	<p>The cor. of secs. 29, 30, 31 and 32.</p> <p>Land, broken. Soil, sand and exposed sandstone. Timber, none.</p>
	<p>S. 89°59'W., bet. secs. 30 and 31.</p> <p>Over broken land of W. breaks of Paria Canyon; asc. about 50 ft. over E. slope, by triangulation with topography scaled from U.S.G.S. sheets.</p>
3.00	Base of nearly sheer ledges, bears NW. and SE. irregularly; asc. about 1000 ft. over ledges facing NE.
10.90	Crest same ledges, bears NW. and SE.; asc. 60 ft. over rolling land of Paria Plateau, through medium growth scrub timber. End of triangulation.
40.00	<p>Point for the $\frac{1}{4}$ sec. cor. of secs. 30 and 31.</p> <p>Set an iron post, 30 ins. long, $2\frac{1}{2}$ ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T41N R7E $\frac{1}{4}$ $\frac{S30}{S31}$ 1961</p> <p>No accessories available.</p> <p>Asc. 120 ft. over gentle NE. slope.</p>
67.70	Rise, bears NE. and SW.; desc. 65 ft. over NW. slope.
79.50	<p>The cor. of secs. 25, 30, 31 and 36, on the W. bdy., monumented by an iron post, 2 ins. diam., set, mkd. and witnessed as described in the official record.</p> <p>Land, broken E. portion, rolling W. portion. Soil, sand and exposed sandstone. Timber, medium growth scrub juniper and pinon on W. portion.</p>
	<p>From the cor. of secs. 29, 30, 31 and 32.</p> <p>N.0°03'W. bet. secs. 29 and 30.</p>

Chains	Over broken land of W. breaks of Paria Canyon; desc. 160 ft. over steep and ledgy NE. slope.
4.80	Rocky wash, .6 ft. deep, 30 lks. wide, drains N.70°E.; desc. 780 ft. over steep and ledgy NE. slope.
36.80	Deep rocky wash, 5 ft. deep, 20 lks. wide, drains NE.; desc. 20 ft. over sandy NE. slope.
40.00	Point for the $\frac{1}{4}$ sec. cor. of secs. 29 and 30. Set an iron post, 30 ins. long, $2\frac{1}{2}$ ins. diam., 24 ins. in the ground and in a collar of stone, with brass cap mkd. T41N R7E $\frac{1}{4}$ S30 S29 1961 Desc. 180 ft. over sandy NE. slope.
64.50	Wash, 3 ft. deep, 20 lks. wide, drains NE.; desc. 100 ft. over sandy NE. slope.
80.00	Set an iron post, 30 ins. long, $2\frac{1}{2}$ ins. diam., 15 ins. in the ground and in a mound of stone to top, with brass cap mkd. T41N R7E S19 S20 S30 S29 1961 Land, broken. Soil, sand and exposed sandstone. Timber, none.
	From the true point for the cor. of secs. 20, 21, 28 and 29. N.89°53'W. bet. secs. 20 and 29. Over broken land of E. breaks of Paria Canyon; asc. 20 ft. over E. slope of spur.
0.54	Point selected for the witness cor. of secs. 20, 21, 28 and 29. Set an iron post, 30 ins. long, $2\frac{1}{2}$ ins. diam., 8 ins. in the ground, and in a mound of stone to top, with brass cap mkd. T41N R7E S20 S21 W S29 S28 C 1961 Witness cor. falls on top of spur which slopes S. Desc. 80 ft. over W. slope of spur, by triangulation, topography scaled from U.S.G.S. sheets.
5.00	Wash, drains SE.; asc. 220 ft. over NE. slope. End of triangulation.
15.80	Spur, slopes SE.; desc. 40 ft. along S. slope on top of spur.
24.90	Top of abrupt descent, bears NW. and SE.; desc 320 ft. over SW slope of mostly barren sandstone.
37.20	E. bank of Paria River, bears NW. and SE.; thence across river.
39.50	Center same river, water about 1 ft. deep, 20 lks. wide, course S.15°W.

Chains	
40.04	Point for the $\frac{1}{4}$ sec. cor. of secs. 20 and 29 falls below high water mark and cannot be perpetuated.
40.10	W. bank same river, bears NW. and SE.; asc. NE. slope.
41.64	Point selected for the witness $\frac{1}{4}$ sec. cor. of secs. 20 and 29, Set an iron post, 30 ins. long, $2\frac{1}{2}$ ins. diam., 12 ins. in the ground and in a mound of stone to top, with brass cap mkd.
	T41N R7E $\frac{1}{4}$ $\frac{S20}{S29}$ $\frac{W}{C}$ 1961
	Asc. 40 ft. over canyon bottom.
47.00	Base of steep ascent, bears NW. and SE.; asc. 260 ft. over NE. slope.
68.00	Crest steep ascent, bears NE. and SE.; asc. 40 ft. over sandy SE. slope of spur.
80.08	The cor. of secs. 19, 20, 29 and 30. Land, broken. Soil, sand and exposed sandstone. Timber, none.
	S.89°51'W., bet. secs. 19 and 30. Over broken land of W. breaks of Paria Canyon; asc. 20 ft. over SE. slope, by triangulation with topography scaled from U.S.G.S. sheets.
2.50	Spur, slopes NE.; desc. 20 ft. over W. slope.
4.50	Wash, drains NE.; asc. about 2160 ft. over steep E. slope and ledges facing E.
40.00	Point for the $\frac{1}{4}$ sec. cor. of secs. 19 and 30, falls on inaccessible ledges and cannot be monumented.
45.80	W. rim of Paria Canyon, bears NW. and SE.; thence over rolling land of Paria Plateau.
45.87	Point selected for the witness $\frac{1}{4}$ sec. cor. of secs. 19 and 30. Set an iron post, 30 ins. long $2\frac{1}{2}$ ins. diam., on solid sandstone, over an X, and in a mound of stone to top, with brass cap mkd.
	T41N R7E $\frac{1}{4}$ $\frac{S19}{S30}$ $\frac{W}{C}$ 1961
	Asc. 130 ft. over gentle E. slope on Paria Plateau.
76.30	Rise, bears N. and S.; desc. 35 ft. over SW. slope.
79.39	The cor. of secs. 19, 24, 25 and 30 on the W. bdy., marked by an iron post, $2\frac{1}{2}$ ins. diam., set, mkd. and witnessed as described in the official record of the 1956 survey. Land, broken and rolling. Soil, sand and exposed sandstone. Timber, scattered juniper and pinon on higher plateau.

Chains

From the cor. of secs. 19, 20, 29 and 30.

N.0°03'W., bet. secs. 19 and 20.

Over broken land of W. breaks of Paria Canyon; desc. 40 ft. over NE. slope.

- 7.50 Sandy wash, 2 ft. deep, 20 lks. wide, drains NE.; desc. 40 ft. along E. slope.
- 20.10 Wash, 2 ft. deep, 30 lks. wide, drains N.80°E.; asc. 50 ft. over SE. slope.
- 29.40 Spur, slopes E.; desc. 80 ft. over series of broken sandstone spurs and washes draining E.
- 40.00 Point for the $\frac{1}{4}$ sec. cor. of secs. 19 and 20 falls in wash draining E. and cannot be perpetuated.
- 40.30 Point selected for the witness $\frac{1}{4}$ sec. cor. of secs. 19 and 20.

Set an iron post, 30 ins. long, $2\frac{1}{2}$ ins. diam., 18 ins. in the ground and in a collar of stone, with brass cap mkd.

T41N R7E
 $\frac{1}{4}$
 S19 | S20
 W C
 1961

Asc. 20 ft. along broken E. slope.

- 51.10 Small spur, slopes NE.; desc. 140 ft. over NE. slope.
- 66.30 Paria River, 1 ch. wide, water 1 ft. deep, 10 lks. wide, drains SE.; asc. 340 ft. over ledgy SW. slope, by triangulation.
- 80.00 Point for the cor. of secs. 17, 18, 19 and 20.

Set an iron post, 30 ins. long, $2\frac{1}{2}$ ins. diam., on solid sandstone, over an X and in a mound of stone to top, with brass cap mkd.

T41N R7E
 S18 | S17
 S19 | S20
 1961

Land, broken.
 Soil, sand and exposed sandstone.
 Timber, none.

From the cor. of secs. 16, 17, 20 and 21.

N.89°53'W. bet. secs. 17 and 20.

Over rolling desert land on top of mesa; asc. 75 ft. over gentle SE. slope.

- 16.04 Point selected for the witness point for the $\frac{1}{4}$ sec. cor. of secs. 17 and 20.

Set an iron post, 16 ins. long, 1 in. diam., drilled 8 ins. in solid sandstone, with brass cap mkd.

T41N R7E
 W S17
 $\frac{1}{4}$ ← P S20
 1961

Chains	
16.10	E. rim Paria Canyon, bears NW. and SE.; desc. about 1800 ft. over broken and inaccessible ledges facing SW. by triangulation.
40.00	Point for the $\frac{1}{4}$ sec. cor. of secs. 17 and 20, falls on inaccessible ledges and cannot be monumented.
80.00	The cor. of secs. 17, 18, 19 and 20.
	Land, broken W. portion, rolling on mesa. Soil, sand and exposed sandstone. Timber, none on W. portion, scattered juniper and pinon on mesa top.
	S.89°59'W., bet. secs. 18 and 19.
	Over broken land of E. breaks of Paria Canyon; desc. 280 ft. over irregular SW. slope.
12.00	E. bank Paria River, bears NW. and SE.
14.00	Center Paria River, drains SE., water about 6 ins. deep, 15 lks. wide.
16.00	W. bank same river, bears SE. and NW.; asc. 150 ft. over NE. slope.
32.30	Spur, slopes N.; desc. 90 ft. along irregular N. slope.
40.00	Point for the $\frac{1}{4}$ sec. cor. of secs. 18 and 19.
	Set an iron post, 30 ins. long, $2\frac{1}{2}$ ins. diam., 8 ins. in the ground, and in a mound of stone to top, with brass cap mkd.
	T41N R7E. $\frac{1}{4}$ $\frac{S18}{S19}$ 1961
	Desc. 20 ft. along irregular N. slope.
61.70	Paria River, drains NE.; asc. 100 ft. over SE. slope.
68.00	Spur, slopes SE.; desc. 50 ft. over SW. slope.
72.50	Wash, 2 ft. deep, 10 lks. wide, drains S.; asc. 70 ft. over rocky SE. slope.
79.29	Point for the cor. of secs. 13, 18, 19 and 24, on W. bdy., at prop. dist. bet. the cor. of secs. 19, 24, 25 and 30, and the $\frac{1}{4}$ sec. cor. of secs. 13 and 18 on the W. bdy. This cor. was not monumented during the 1957 survey of the W. bdy.
	Set an iron post, 30 ins. long, $2\frac{1}{2}$ ins. diam., 20 ins. in the ground and in a mound of stone to top, with brass cap mkd.
	T41N R6E R7E $\frac{S13}{S24} \frac{S18}{S19}$ 1961
	From this cor. the $\frac{1}{4}$ sec. cor. of secs. 13 and 18, bears North, 40.00 chs. dist., monumented by an iron post, $2\frac{1}{2}$ ins. diam., set, mkd. and witnessed as described in the official record.
	The cor. of secs. 19, 24, 25 and 30 on the W. bdy., bears South, 80.00 chs. dist., monumented by an iron post, $2\frac{1}{2}$ ins. diam., set, mkd. and witnessed as described in the official record.

Chains

Land, broken.
Soil, sand and exposed sandstone.
Timber, none.

From the cor. of secs. 17, 18, 19 and 20.

N.0°03'W., bet. secs. 17 and 18.

Over broken land of E. breaks of Paria Canyon; asc. about 1200 ft. over steep SW. slope and ledges facing SW. by triangulation.

40.00 Point for the $\frac{1}{4}$ sec. cor. of secs. 17 and 18, falls on sheer ledges facing SW. and cannot be monumented.

44.60 Point selected for the witness $\frac{1}{4}$ sec. cor. of secs. 17 and 18.

Drilled an iron post, 18 ins. long, 1 in. diam., 8 ins. in solid sandstone, with brass cap mkd.

T41N R7E
 $\frac{1}{4}$
 S18 | S17
 W C
 1961

Witness cor. falls on small sandstone spur sloping W.; desc. about 400 ft. over ledgy NW. slope.

48.80 Ravine, drains SW.; asc. about 250 ft. over ledgy S. slope.

55.00 Spur, slopes E.; desc. about 50 ft. along broken E. slope.

67.00 Same ravine, drains SE.; asc. about 280 ft. over SW. slope.

80.00 Point for the cor. of secs. 7, 8, 17 and 18.

Drilled an iron post, 18 ins. long, 1 in. diam., 8 ins. in solid sandstone, and in a collar of stone, with brass cap mkd.

T41N R7E
 S7 | S8
 S18 | S17
 1961

Cor. falls on sandstone rib about 5 ft. high, which bears E. and W.; about 180 ft. below canyon rim.

Land, broken.
Soil, sand and exposed sandstone.
Timber, none.

From the cor. of secs. 8, 9, 16 and 17.

N.89°51'W., bet. secs. 8 and 17.

Over rolling land on top of Cedar Mountain; asc. 110 ft. over gentle E. slope.

29.70 Top of ascent on mountain, bears N. and S.; desc. 35 ft. over gentle W. slope.

39.96 Point for the $\frac{1}{4}$ sec. cor. of secs. 8 and 17.

Set an iron post, 30 ins. in diam., 24 ins. in the ground, with brass cap mkd.

Chains	<p style="text-align: center;">T41N R7E $\frac{1}{4}$ $\frac{S8}{S17}$ 1961</p>
	<p>No accessories available.</p> <p>Desc. 75 ft. over gentle W. slope.</p>
56.60	Top of steep descent, bears N. and S.; desc. 200 ft. over rocky W. slope.
61.00	Base of steep descent, bears N. and S.; desc. 90 ft. over W. slope.
76.60	E. rim of Paria Canyon, bears NW. and SE. irregularly; desc. 120 ft. over steep SW. slope.
79.92	<p>The cor. of secs. 7, 8, 17 and 18.</p> <p>Land, rolling and broken. Soil, sand and exposed sandstone. Timber, scattered scrub juniper and pinon.</p>
	<p>S. 89°56'W., bet. secs. 7 and 18.</p> <p>Over broken land of E. breaks of Paria Canyon; desc. about 200 ft. over broken and irregular SW. slope, by triangulation with topography scaled from U.S.G.S. sheets.</p>
20.00	Ravine, drains SE.; asc. about 800 ft. over ledges facing E.
40.00	Point for the $\frac{1}{4}$ sec. cor. of secs. 7 and 18, falls on inaccessible ledges and cannot be monumented.
43.90	<p>Point selected for the witness $\frac{1}{4}$ sec. cor. of secs. 7 and 18.</p> <p>Set an iron post, 30 ins. long, 2$\frac{1}{2}$ ins. diam., on solid sandstone, over an X, and in a mound of stone to top, with brass cap mkd.</p>
	<p style="text-align: center;">T41N R7E $\frac{1}{4}$ $\frac{W S7}{C S18}$ 1961</p>
	<p>Witness cor. falls on top of sheer ledges.</p> <p>Asc. 210 ft. over ledgy E. slope.</p>
51.30	W. rim of Paria Canyon, bears N. and S.; desc. 20 ft. over gentle W. slope on top of Cedar Mountain.
79.12	<p>The cor. of secs. 7, 12, 13 and 18 on the W. bdy., monumented by iron post, 2$\frac{1}{2}$ ins. diam., set, mkd. and witnessed as described in official record.</p> <p>Land, broken in canyon, rolling on mountain top. Soil, sand and exposed sandstone. Timber, scattered scrub juniper on mountain top.</p>
	<p>From the cor. of secs. 7, 8, 17 and 18.</p> <p>N. 0°03'W., bet. secs. 7 and 8.</p> <p>Over broken land of E. breaks of Paria Canyon; asc. 180 ft. over ledgy SW. slope.</p>
6.20	E. rim Paria Canyon, bears NW. and SE.; asc. 45 ft. over SW. slope

Chains	
	on top of Cedar Mountain.
25.00	Wash, 2 ft. deep, 15 lks. wide, drains S.80°W.; asc. 30 ft. along SW. slope.
34.10	Wash, 3 ft. deep, 20 lks. wide, drains S.80°W.; asc. 30 ft. over S. slope.
40.00	Point for the $\frac{1}{4}$ sec. cor. of secs. 7 and 8. Set an iron post, 30 ins. long, $2\frac{1}{2}$ ins. diam., 6 ins. in the ground, and in a mound of stone to top, with brass cap mkd. T41N R7E $\frac{1}{4}$ S7 S8 1961 Cor. falls at base of steep ascent; asc. 140 ft. over rocky S. slope.
49.60	Top of steep ascent, bears E. and W.; asc. 60 ft. over rolling top of Cedar Mountain.
80.00	Point for the cor. of secs. 5, 6, 7 and 8. Set an iron post, 30 ins. long, $2\frac{1}{2}$ ins. diam., 24 ins. in the ground, with brass cap mkd. T41N R7E S6 S5 S7 S8 1961 No accessories available. Land, broken and rolling mountain top. Soil, sand and exposed sandstone. Timber, scattered juniper and pinon. Undergrowth, black brush and bunch grass on mountain.
	From the cor. of secs. 4, 5, 8 and 9. N.89°50'W. bet. secs. 5 and 8. Over broken desert land on top of Cedar Mountain; asc. 30 ft. over E. slope.
8.10	Small wash, drains N.80°E.; asc. 280 ft. over E. slope.
33.00	Base of steep ascent, bears N. and S.; asc. 170 ft. over ledgy E. slope.
36.80	Top of ascent, bears N. 10°E. and curves SW.; thence over level top of small point which extends S. about 4 chs.
39.95	Point for the $\frac{1}{4}$ sec. cor. of secs. 5 and 8. Set an iron post, 30 ins. long, $2\frac{1}{2}$ ins. diam., 6 ins. in the ground, and in a mound of stone to top, with brass cap mkd. T41N R7E $\frac{1}{4}$ S5 S8 1961 Continue over top of point.

Chains	
41.00	Top of rim, bears N. and curves SE.; desc. 50 ft. over ledgy W. slope.
42.10	Base of same ledgy rim, bears N. and curves SE.; desc. 70 ft. over rolling sandy W. slope.
57.90	Exposed sandstone rib of rock, about 3 ft. high, 4 ft. wide, bears N. and S.; desc. 75 ft. over gentle W. slope.
79.90	<p>The cor. of secs. 5, 6; 7 and 8:</p> <p>Land, broken and rolling. Soil, sand and exposed sandstone. Timber, very scattered juniper and pinon.</p>
	<p>S. 89°55'W., bet. secs. 6 and 7.</p> <p>Over rolling sandy desert land on top of Cedar Mountain; desc. 120 ft. over gentle W. slope.</p>
26.00	Enter low broken and exposed sandstone ledges; desc. 60 ft. along S. slope.
36.00	Wash, 4 ft. deep, 40 lks. wide, drains S.; asc. 40 ft. over sandy SE. slope.
40.00	<p>Point for the $\frac{1}{4}$ sec. cor. of secs. 6 and 7.</p> <p>Set an iron post, 30 ins. long $2\frac{1}{2}$ ins. diam., 15 ins. in the ground and in a mound of stone to top, with brass cap mkd.</p> <p style="text-align: center;">T41N R7E $\frac{1}{4}$ $\frac{S6}{S7}$ 1961</p>
79.06	<p>Asc. 215 ft. over sandy SE. slope.</p> <p>The cor. of secs. 1, 6, 7 and 12, monumented by an iron post, 1 ins. diam., set, mkd. and witnessed as described in the official record of the 1957 survey of the W. bdy.</p> <p>Land, rolling. Soil, sand and exposed sandstone. Timber, very scattered juniper and pinon.</p>
40.00	<p>From the cor. of secs. 5, 6, 7 and 8.</p> <p>N. 0°13'W., bet. secs. 5 and 6.</p> <p>Over rolling desert land on top of Cedar Mountain; desc. 15 ft. over gentle N. slope.</p> <p>Point for the $\frac{1}{4}$ sec. cor. of secs. 5 and 6.</p> <p>Set an iron post, 30 ins. long, $2\frac{1}{2}$ ins. diam., 10 ins. in the ground, and in a mound of stone to top, with brass cap mkd.</p> <p style="text-align: center;">T41N R7E $\frac{1}{4}$ S6 S5 1961</p> <p>Asc. 100 ft. over gentle S. slope.</p>
79.83	The cor. of secs. 5, 6, 31 and 32 on the N. bdy., marked by an iron

Chains

post, $2\frac{1}{2}$ ins. diam., set, mkd. and witnessed as described in the field notes of the survey of the S. bdy. of T. 42 N., R. 7 E.

Land, rolling.

Soil, sand.

Timber, very scattered juniper and pinon.

GENERAL DESCRIPTION

Township 41 North, Range 7 East consists of desert land, and is located about 12 miles west of Glen Canyon Dam. The Northeast portion of the township consists mainly of rolling sand, the Southeast portion of the township consists mostly of broken barren sandstone of Paria Canyon.

The only permanent water noted during the survey was the Paria River, which enters the township on the West boundary of Section 19, drains irregularly Southeast and leaves the township on the South boundary of Section 34. The river flow appeared to be about normal at time of survey

The vegetation consists of black brush and scattered bunch grass, with scattered juniper and pinon on the higher elevations.

The elevation varies from about 5850 feet above sea level on Cedar Mountain, to about 3200 feet along the Paria River.

There are a few trail roads in the North portion of the township, which lead to small stock ponds. Most of the rolling land in the township can be traveled by four-wheel drive vehicle.

Chains

UNITED STATES
DEPARTMENT OF THE INTERIOR
BUREAU OF LAND MANAGEMENT

FIELD ASSISTANTS

NAMES	CAPACITY
Morris E. Blackburn	Notekeeper
Ferrel D. Reynolds	Chainman
Charles C. Brindley	Cornerman
Gary W. Rutledge	Notekeeper
Wallace R. Ott	Chainman
Daniel R. Bauer	Cornerman

