

UNITED STATES  
DEPARTMENT OF THE INTERIOR  
BUREAU OF LAND MANAGEMENT

# FIELD NOTES

of the

SURVEY

of the

North, East and West Boundaries

and the

Subdivisional Lines

of

Township 3 South, Range 13 West

*Of the* Gila and Salt River *Meridian,*

*In the State of* Arizona

## EXECUTED BY

Horace G. Parker

Cadastral Surveyor

*Under special instructions dated* July 30, 19 59, *which provided*  
*for the surveys included under Group No.* 339, *approved* August 7, 1959  
*and assignment instructions dated* February 17, 19 60.

*Survey commenced* March 14, 19 60

*Survey completed* April 3, 19 61

11A

COOK 4653

# INDEX DIAGRAM

Township 3 South, Range 13 West

4	<sup>9</sup> (49) 6 48 47	<sup>8</sup> (49) 5 39 47	<sup>7</sup> (39) 4 32 38	<sup>7</sup> (33) 3 25 31	<sup>6</sup> (26) 2 19 25	<sup>5</sup> (20) 1 13 18
4	<sup>7</sup> 46 46	<sup>8</sup> 38 45	<sup>9</sup> 31 37	<sup>10</sup> 24 30	<sup>11</sup> 18 24	<sup>12</sup> 12 17
3	<sup>18</sup> 45 44	<sup>17</sup> 37 44	<sup>16</sup> 30 36	<sup>15</sup> 23 29	<sup>14</sup> 17 23	<sup>13</sup> 11 16
2	<sup>19</sup> 43 42	<sup>20</sup> 35 42	<sup>21</sup> 29 35	<sup>22</sup> 22 28	<sup>23</sup> 16 22	<sup>24</sup> 11 15
2	<sup>30</sup> 41 41	<sup>29</sup> 34 40	<sup>28</sup> 27 34	<sup>27</sup> 21 27	<sup>26</sup> 15 20	<sup>25</sup> 10 14
1	<sup>31</sup> 40	<sup>32</sup> 33	<sup>33</sup> 26	<sup>34</sup> 20	<sup>35</sup> 14	<sup>36</sup> 9

16-56770-1

## Township 3 South, Range 13 West, Arizona

1. B

## Chains

The south boundary was surveyed in 1913 by W. K. Kierulf.

The following notes are those of the survey of the north, east and west boundaries and the subdivisional lines of Township 3 South, Range 13 West, Gila and Salt River Meridian, Arizona.

This survey was executed in accordance with the specifications as set forth in the Manual of Surveying Instructions, 1947, and the Special Instructions, dated July 30, 1959.

True bearing and horizontal distances for the surveyed lines are given in these notes. All corners were monumented with standard iron posts, 30 inches long, 2½ inches in diameter, flanged at the bases with brass caps riveted to the tops.

The geographic position of the southeast corner of the township is: 33°06'56" N. latitude and 113°32'48" W. longitude. The magnetic declination was found to be 15° East.

---

Survey of the West Boundary of Township 3 South, Range 13 West

---

From the cor. of Ts. 3 and 4 S., Rs. 13 and 14 W.; monumented with an iron post, 3 ins. diam., firmly set, mkd. and witnessed as described in the official record.

North, bet. secs. 31 and 36.

Over gently rolling land, through scattered timber and undergrowth.

8.00 Wash, 15 lks. wide, 4 ft. deep, drains E.

29.00 Wash, 10 lks. wide, 4 ft. deep, drains E., asc. over rocky, SE. slope.

40.00 Point for the ¼ sec. cor. of secs. 31 and 36.

Set the iron post 15 ins. in the ground, to solid rock, and in a mound of stone to top, with brass cap mkd.

T 3 S  
R14W ¼ R13W  
S 36 | S 31  
1960

Raise a mound of stone, 5 ft. base, 2½ ft. high, W. of corner.

44.80 Top of rimrock of mesa, bears W. and S. 70° E., 50 lks. dist., thence NW.

45.30 Top of rimrock of mesa, bears NW. and SE.; desc. over steep, rocky NE. slope.

55.00 Bottom of steep slope, bears NW. and SE.; continue over nearly level land.

58.90 Wash, 20 lks. wide, 3 ft. deep, drains S. 20° E.

71.00 Begin ascent; over steep SE. slope.

74.50 Top of spur, slopes S. 70° E.; desc. over NE. slope.

80.00 Point for the cor. of secs. 25, 30, 31, and 36.

Chains

Set the iron post 8 ins. in the ground, to solid rock, and in a mound of stone to top, with brass cap mkd.

T 3 S	
R14W	R13W
S 25	S 30
S 36	S 31
1960	

Raise a mound of stone, 4 ft. base, 2½ ft. high, W. of corner.

Land, southern portion, nearly level; northern portion, heavily rolling.

Soil, gravel, sandy clay and loam.

Timber, palo verde; undergrowth, cactus, yucca, and greasewood.

North, bet. secs. 25 and 30.

Over gently rolling land, through scattered timber and undergrowth.

18.30 Wash, 100 lks. wide, 3 ft. deep, drains S. 20° E.

40.00 Point for the ¼ sec. cor. of secs. 25 and 30.

Set the iron post 20 ins. in the ground, and in a collar of stone to top, with brass cap mkd.

T 3 S	
R14W	¼ R13W
S 25	S 30
1960	

Raise a mound of stone, 4 ft. base, 3 ft. high, W. of corner.

Continue over nearly level land.

70.00 Wash, 10 lks. wide, 2 ft. deep, drains S. 70° E.; asc. over SE. slope.

79.00 Descend over NE. slope.

80.00 Point for the cor. of secs. 19, 24, 25 and 30.

Set the iron post 20 ins. in the ground, and in a collar of stone to top, with brass cap mkd.

T 3 S	
R14W	R13W
S 24	S 19
S 25	S 30
1960	

Raise a mound of stone, 4 ft. base, 3 ft. high, W. of corner.

Land; southern half, gently rolling; northern half, nearly level. Soil, gravel, sandy clay and loam.

Timber, palo verde; undergrowth, cactus, yucca, and greasewood.

North, bet. secs. 19 and 24.

Over gently rolling land, through scattered timber and undergrowth.

2.50 Wash, 15 lks. wide, 2 ft. deep, drains S. 70° E.

## Chains

25.60 Trail road, bears N. 20° W. and S. 20° E.

28.00 Wash, 50 lks. wide, 4 ft. deep, drains SE.

40.00 Point for the  $\frac{1}{4}$  sec. cor. of secs. 19 and 24.

Set the iron post 18 ins. in the ground to solid rock, and in a mound of stone to top, with brass cap mkd.

T 3 S  
R14W  $\frac{1}{4}$  R13W

S 24 | S 19  
1960

48.20 Leave gently rolling land; begin ascent over heavily rolling land.

70.00 Top of spur, slopes S. 70° E.; desc. over NE. slope.

80.00 Point for the cor. of secs. 13, 18, 19 and 24.

Set the iron post 12 ins. in the ground to solid rock, and in a mound of stone to top, with brass cap mkd.

T 3 S  
R14W R13W

S 13 | S 18  
S 24 | S 19  
1960

Land, southern half, gently rolling; northern half, heavily rolling  
Soil, gravel, sandy clay and loam.  
Timber, palo verde; undergrowth, cactus and greasewood.

North, bet. secs. 13 and 18.

Over rolling land, through scattered timber and undergrowth; desc. over NE. slope.

9.00 Wash, 30 lks. wide, 6 ft. deep, drains S. 80° E.; asc. over steep, rocky S. slope.

20.80 Top of spur, slopes S. 70° E.; desc. over NE. slope.

35.80 Wash, 10 lks. wide, 5 ft. deep, drains NE.; continue over gently rolling land.

40.00 Point for the  $\frac{1}{4}$  sec. cor. of secs. 13 and 18.

Set the iron post 14 ins. in the ground to solid rock, and in a mound of stone to top, with brass cap mkd.

T 3 S  
R14W  $\frac{1}{4}$  R13W

S 13 | S 18  
1960

66.90 Top of ascent, slopes ESE.; desc. over gradual NNE. slope.

74.00 Wash, 12 lks. wide, 3 ft. deep, drains E.

80.00 Point for the cor. of secs. 7, 12, 13, and 18.

Set the iron post 24 ins. in the ground, with brass cap mkd.

## Chains

T 3 S  
R14W R13W  
S 12 | S 7  

---

S 13 | S 18  
1960

Raise a mound of stone, 3 ft. base, 2 ft. high, W. of corner.

Land, southern half, heavily rolling; northern half, gently rolling.  
Soil, gravel, sandy clay and loam.  
Timber, palo verde; undergrowth, cactus, yucca and greasewood.

North, bet. secs. 7 and 12.

Over gently rolling desert land, through scattered timber and undergrowth.

- 8.10 Wash, 17 lks. wide, 2 ft. deep, drains NNE.
- 17.80 Wash, 12 lks. wide, 2 ft. deep, drains E.; continue over nearly level land.
- 23.40 Wash, 15 lks. wide, 3 ft. deep, drains SE.
- 29.80 Wash, 150 lks. wide, 4 ft. deep, drains E.
- 40.00 Point for the  $\frac{1}{4}$  sec. cor. of secs. 7 and 12.

Set the iron post 24 ins. in the ground, with brass cap mkd.

T 3 S  
R14W  $\frac{1}{4}$  R13W  
S 12 | S 7  
1960

Raise a mound of stone, 3 $\frac{1}{2}$  ft. base, 2 ft. high, W. of corner.

Continue over nearly level land, through scattered timber and undergrowth.

- 42.50 Wash, 20 lks. wide, 2 ft. deep, drains E.
- 76.40 Wash, 20 lks. wide, 3 ft. deep, drains E.
- 80.00 Point for the cor. of secs. 1, 6, 7 and 12.

Set the iron post 24 ins. in the ground, with brass cap mkd.

T 3 S  
R14W R13W  
S 1 | S 6  

---

S 12 | S 7  
1960

Raise a mound of stone, 3 ft. base, 2 ft. high, W. of corner.

Land: southern half, gently rolling; northern half, nearly level.  
Soil, gravel, sandy clay and loam.  
Timber, palo verde; undergrowth, cactus, yucca and greasewood.

North, bet. secs. 1 and 6.

## Chains

- Over slightly rolling land, through scattered timber and undergrowth.
- .75 Wash, 10 lks. wide, 2 ft. deep, drains S. 80° E.
- 9.10 Wash, 30 lks. wide, 5 ft. deep, drains S. 75° E.
- 31.40 Wash, 15 lks. wide, 1½ ft. deep, drains S. 80° E.
- 40.00 Point for the ¼ sec. cor. of secs. 1 and 6.

Set the iron post 24 ins. in the ground, with brass cap mkd.

T 3 S  
R14W ¼ R13W  
S 1 | S 6  
1960

Raise a mound of stone, 3 ft. base, 2½ ft. high, W. of corner.

- 50.40 Wash, 4 lks. wide, 6 ins. deep, drains S. 60° E.
- 59.40 Road, partially graded, bears N. 85° W. and S. 85° E.
- 64.20 Wash, 40 lks. wide, 5½ ft. deep, drains E.
- 74.30 Wash, 15 lks. wide, 2½ ft. deep, drains S. 75° E.
- 77.30 Wash, 8 lks. wide, 1½ ft. deep, drains S. 15° E.
- 80.00 Point for the cor. of Ts. 2 and 3 S., Rs. 13 and 14 W.

Set the iron post 24 ins. in the ground, with brass cap mkd.

T 2 S  
R 14 W R 13 W  
S 36 | S 31  
S 1 | S 6  
T 3 S  
1960

Raise a mound of stone, 4 ft. base, 2½ ft. high, S. of corner.

Land, slightly rolling.  
Soil, gravel, sandy clay and loam.  
Timber, palo verde and ironwood; undergrowth, cactus, yucca and greasewood.

---

Survey of the South Boundary of Township 2 South, Range 13 West

---

From the cor. of Ts. 2 S., Rs. 12 and 13 West, monumented with an iron post 3 ins. diam., firmly set, mkd., and witnessed as described in the official record.

S. 89°58' W., on true line, along the S. bdy. of sec. 36.

Over nearly level land, through scattered timber and undergrowth.

- 7.20 Wash, 100 lks. wide, 4 ft. deep, drains S. 55° E.
- 23.10 Wash, 15 lks. wide, 2 ft. deep, drains S. 75° E.
- 40.00 Point for the ¼ sec. cor. of sec. 36.

## Chains

Set the iron post 24 ins. in the ground, with brass cap mkd.

T2S R13W

$\frac{1}{4}$  S 36

T3S R13W

1960

Raise a mound of stone, 3 ft. base, 2 ft. high, N. of corner.

73.20 Wash, 6 lks. wide, 2 ft. deep, drains S. 50° E.

80.00 Point for the cor. of secs. 35 and 36.

Set the iron post 24 ins. in the ground, with brass cap mkd.

T2S R13W

S 35 | S 36

S 1

T3S R13W

1960

Raise a mound of stone, 3 ft. base, 2½ ft. high, N. of corner.

Land, nearly level.

Soil, gravel, sandy clay and loam.

Timber, palo verde and ironwood; undergrowth, cactus, yucca and greasewood.

S. 89°58' W., along the S. bdy. of sec. 35.

Over nearly level land, through scattered timber and undergrowth.

6.50 Wash, 8 lks. wide, 1 ft. deep, drains SE.

14.45 Road, partially graded, bears N. 10° E., and S. 10° W.

19.30 Wash, 10 lks. wide, 1 ft. deep, drains S. 75° E.

40.00 Point for the  $\frac{1}{4}$  sec. cor. of sec. 35.

Set the iron post 24 ins. in the ground, with brass cap mkd.

T2S R13W

$\frac{1}{4}$  S 35

T3S R13W

Raise a mound of stone, 3 ft. base, 2 ft. high, N. of corner.

58.30 Wash, 10 lks. wide, 1 ft. deep, drains S. 50° E.

66.10 Wash, 8 lks. wide, 6 ins. deep, drains S. 75° E.

78.80 Wash, 4 lks. wide, 1 ft. deep, drains SSE.

80.00 Point for the cor. of secs. 34 and 35.

Set the iron post 24 ins. in the ground, with brass cap mkd.

T2S R13W

S 34 | S 35

S 2

T3S R13W

1960

## Chains

Land, nearly level.  
Soil, gravel, sandy clay and loam.  
Timber, palo verde and ironwood; undergrowth, cactus, yucca and greasewood.

S. 89°58' W., along the S. bdy. of sec. 34.

Over nearly level land, through scattered timber and undergrowth.

22.80 Wash, 30 lks. wide, 2½ ft. deep, drains SSE.

40.00 Point for the ¼ sec. cor. of sec. 34.

Set the iron post 24 ins. in the ground, with brass cap mkd.

T2S R13W  
¼ S 34  
T3S R13W  
1960

Raise a mound of stone, 3½ ft. base, 2 ft. high, N. of corner.

41.10 Old road, bears N. 15° W., and S. 15° E.

54.50 Wash, 8 lks. wide, 6 ins. deep, drains S. 60° E.

62.90 Wash, 12 lks. wide, 8 ins. deep, drains SE.

76.50 Wash, 10 lks. wide, 2 ft. deep, drains S. 50° E.

80.00 Point for the cor. of secs. 33 and 34.

Set the iron post 24 ins. in the ground, with brass cap mkd.

T2S R13W  
S 33 | S 34  
S 3  
T3S R13W  
1960

Raise a mound of stone, 3½ ft. base, 2 ft. high, N. of corner.

Land, nearly level.  
Soil, gravel, sandy clay and loam.  
Timber, palo verde and ironwood; undergrowth, cactus, yucca, and greasewood.

S. 89°58' W., along the S. bdy. of sec. 33.

Over nearly level land, through scattered timber and undergrowth.

10.50 Wash, 40 lks. wide, 3 ft. deep, drains SE.

23.10 Wash, 6 lks. wide, 4 ins. deep, drains SE.

31.00 Wash, 8 lks. wide, 6 ins. deep, drains S. 40° E.

39.98 ; Old road, bears N. and S.

40.00 Point for the ¼ sec. cor. of sec. 33.

Set the iron post 10 ins. in the ground to solid rock, and in a mound of stone to top, with brass cap mkd.

Chains	
	T2S R13W <u>    ½ S 33</u> T3S R13W 1960
42.00	Wash, 8 lks. wide, 6 ins. deep, drains S. 30° E.
54.55	Wash, 5 lks. wide, 1 ft. deep, drains S.
62.60	Wash, 8 lks. wide, 2 ft. deep, drains S. 30° E.
66.90	Wash, 30 lks. wide, 2 ft. deep, drains S.
69.55	Wash, 20 lks. wide, 3 ft. deep, drains S. 20° E.
80.00	Point for the cor. of secs. 32 and 33.
	Set the iron post 24 ins. in the ground, with brass cap mkd.
	T2S R13W <u>  S 32   S33</u> S 4 T3S R13W 1960
	Raise a mound of stone, 3½ ft. base, 2 ft. high, N. of corner.
	Land, nearly level.
	Soil, gravel, sandy clay and loam.
	Timber, palo verde and ironwood; undergrowth, cactus, yucca and greasewood.
	S. 89°58' W., along the S. bdy. of sec. 32.
	Over nearly level land, through scattered timber and undergrowth.
.65	Wash, 10 lks. wide, 3 ft. deep, drains SE.
13.60	Wash, 6 lks. wide, 6 ins. deep, drains S. 55° E.
25.00	Wash, 8 lks. wide, 6 ins. deep, drains S. 40° E.
34.80	Wash, 50 lks. wide, 4 ft. deep, drains SSE.
40.00	Point for the ¼ sec. cor. of sec. 32.
	Set the iron post 10 ins. in the ground, to solid rock, and in a mound of stone to top, with brass cap mkd.
	T2S R13W <u>    ½ S 32</u> T3S R13W 1960
45.80	Wash, 30 lks. wide, 2 ft. deep, drains SE.
53.60	Wash, 25 lks. wide, 3½ ft. deep, drains S. 15° E.
80.00	Point for the cor. of secs. 31 and 32.
	Set the iron post 24 ins. in the ground, with brass cap mkd.

## Chains

T2S R13W  
 S 31 | S 32  
 S 5  
 T3S R13W  
 1960

Raise a mound of stone,  $3\frac{1}{2}$  ft. base,  $2\frac{1}{2}$  ft. high, N. of corner.

Land, nearly level.

Soil, gravel, sandy clay and loam.

Timber, palo verde and ironwood; undergrowth, cactus, yucca and greasewood.

S.  $89^{\circ}58'$  W., along the S. bdy. of sec. 31.

Over nearly level land, through scattered timber and undergrowth.

.90 Old road, bears N.  $70^{\circ}$  W. and S.  $70^{\circ}$  E.

10.70 Wash, 25 lks. wide, 4 ft. deep, drains S.  $65^{\circ}$  E.

40.00 Point for the  $\frac{1}{4}$  sec. cor. of sec. 31.

Set the iron post 24 ins. in the ground, with brass cap mkd.

T2S R13W  
 $\frac{1}{4}$  S 31  
 T3S R13W  
 1960

Raise a mound of stone, 3 ft. base, 2 ft. high, N. of corner.

45.40 Wash, 15 lks. wide, 3 ft. deep, drains SE.

80.00 Point for the  $\frac{1}{16}$ th sec. cor. of sec. 31.

Set the iron post 24 ins. in the ground, with brass cap mkd.

T2S R13W  
 $\frac{1}{16}$  S 31 80  
 T3S R13W  
 1960

Raise a mound of stone, 3 ft. base, 2 ft. high, N. of corner.

98.50 Wash, 30 lks. wide,  $2\frac{1}{2}$  ft. deep, drains SE.

103.89 The cor. of Ts. 2 and 3 S., Rs. 13 and 14 W.

Land, nearly level.

Soil, gravel, sandy clay and loam.

Timber, palo verde and ironwood; undergrowth, cactus, yucca and greasewood.

Survey of the East Boundary of Township 3 South, Range 13 W.

From the cor. of Ts. 3 and 4 S., Rs. 12 and 13 W., monumented with an iron post 3 ins. diam., firmly set, mkd. and witnessed as described in the official record.

## Chains

North, bet. secs. 31 and 36.

Over nearly level land, through timber and undergrowth.

- 3.30 Wash, 30 lks. wide, 3 ft. deep, drains S. 30° E.  
 11.20 Wash, 40 lks. wide, 2 ft. deep, drains SE.  
 20.80 Wash, 20 lks. wide, 3 ft. deep, drains S. 20° E.  
 38.90 Wash, 75 lks. wide, 4 ft. deep, drains SE.  
 40.00 Point for the  $\frac{1}{4}$  sec. cor. of secs. 31 and 36.

Set the iron post 24 ins. in the ground, with brass cap mkd.

T 3 S  
 R13W  $\frac{1}{4}$  R12W  
 S 36 | S 31  
 1960

Raise a mound of stone, 3 $\frac{1}{2}$  ft. base, 2 $\frac{1}{2}$  ft. high, W. of corner.

- 80.00 Point for the cor. of secs. 25, 30, 31 and 36.

Set the iron post 24 ins. in the ground, with brass cap mkd.

T 3 S  
 R13W R12W  
 S 25 | S 30  
 S 36 | S 31  
 1960

Raise a mound of stone, 4 ft. base, 2 $\frac{1}{2}$  ft. high, W. of corner.

Land, nearly level.

Soil, gravel, sandy clay and loam.

Timber, palo verde and ironwood; undergrowth, cactus, yucca, and greasewood.

North, bet. secs. 25 and 30.

Over nearly level land, through scattered timber and undergrowth.

- 40.00 Point for the  $\frac{1}{4}$  sec. cor. of secs. 25 and 30.

Set the iron post 24 ins. in the ground, with brass cap mkd.

T 3 S  
 R13W  $\frac{1}{4}$  R12W  
 S 25 | S 30  
 1960

Raise a mound of stone, 3 $\frac{1}{2}$  ft. base, 2 $\frac{1}{2}$  ft. high, W. of corner.

- 64.50 Wash, 30 lks. wide, 2 ft. deep, drains S. 15° W.

- 78.40 Wash, 10 lks. wide, 2 $\frac{1}{2}$  ft. deep, drains SW.

- 80.00 Point for the cor. of secs. 19, 24, 25 and 30.

Chains

Set the iron post 24 ins. in the ground, with brass cap mkd.

T 3 S  
R13W R12W  
S 24 | S 19  
S 25 | S 30  
1960

Raise a mound of stone, 4 ft. base, 2½ ft. high, W. of corner.

Land, nearly level.  
Soil, gravel, sandy clay and loam.  
Timber, palo verde and ironwood; undergrowth, cactus, yucca and greasewood.

North, bet. secs. 19 and 24.

Over nearly level land, through scattered timber and undergrowth.

- 8.10 Wash, 30 lks. wide, 2 ft. deep, drains S. 20° E.
- 17.20 Same wash, 30 lks. wide, 3 ft. deep, drains S. 20° W.
- 26.30 Same wash, 30 lks. wide, 3 ft. deep, drains S. 20° E.
- 40.00 Point for the ¼ sec. cor. of secs. 19 and 24.

Set the iron post 24 ins. in the ground, with brass cap mkd.

T 3 S  
R13W ¼ R12W  
S24 | S19  
1960

Raise a mound of stone, 3½ ft. base, 2½ ft. high, W. of corner.

- 40.75 Old road, bears N. 30° W., and S. 30° E.
- 70.26 A brass tablet, 3 ins. diam., firmly set in concrete, U. S. Coast and Geodetic Survey azimuth mark MALLEY, bears East, 141 lks. distant.
- 79.80 Wash, 3 lks. wide, 1 ft. deep, drains SE.
- 80.00 Point for the cor. of secs. 13, 18, 19 and 24.

Set the iron post 24 ins. in the ground, with brass cap mkd.

T 3 S  
R13W R12W  
S 13 | S 18  
S 24 | S 19  
1960

Raise a mound of stone, 4 ft. base, 2½ ft. high, W. of corner.

Land, nearly level.  
Soil, gravel, sandy clay and loam.  
Timber, palo verde and ironwood; undergrowth, cactus, yucca, and greasewood.

North, bet. secs. 13 and 18.

Over slightly rolling land, through scattered timber and undergrowth.

## Chains

18.60 Wash, 10 lks. wide, 2 ft. deep, drains SE.

38.60 Wash, 15 lks. wide, 5 ins. deep, drains S. 75° E.

40.00 Point for the  $\frac{1}{4}$  sec. cor. of secs. 13 and 18.

Set the iron post 24 ins. in the ground, with brass cap mkd.

T 3 S  
R13W  $\frac{1}{4}$  R12W  
S 13 | S 18  
1960

Raise a mound of stone, 3 ft. base, 2 $\frac{1}{2}$  ft. high, W. of corner.

55.70 Wash, 5 lks. wide, 2 ft. deep, drains S. 50° E.

69.50 Wash, 7 lks. wide, 2 ft. deep, drains S. 80° E.

74.80 Wash, 10 lks. wide, 1 ft. deep, drains S. 60° E.

80.00 Point for the cor. of secs. 7, 12, 13, and 18.

Set the iron post 24 ins. in the ground, with brass cap mkd.

T 3 S  
R13W R12W  
S 12 | S 7  
S 13 | S 18  
1960

Raise a mound of stone, 3 $\frac{1}{2}$  ft. base, 2 ft. high, W. of corner.

Land, slightly rolling.

Soil, gravel, sandy clay and loam.

Timber, palo verde and ironwood; undergrowth, cactus, yucca, and greasewood.

North, bet. secs. 7 and 12.

Over nearly level land, through scattered timber and undergrowth.

10.20 Wash, 20 lks. wide, 3 ft. deep, drains S. 85° E.

29.30 Wash, 10 lks. wide, 2 ft. deep, drains S. 70° E.

40.00 Point for the  $\frac{1}{4}$  sec. cor. of secs. 7 and 12.

Set the iron post 24 ins. in the ground, with brass cap mkd.

T 3 S  
R13W  $\frac{1}{4}$  R12W  
S 12 | S 7  
1960

Raise a mound of stone, 3 $\frac{1}{2}$  ft. base, 2 $\frac{1}{2}$  ft. high, W. of corner.

40.50 Wash, 8 lks. wide, 6 ins. deep, drains S. 60° E.

46.20 Wash, 30 lks. wide, 3 $\frac{1}{2}$  ft. deep, drains S. 65° E.

75.10 Wash, 12 lks. wide, 6 ins. deep, drains S. 30° E.

## Chains

80.00 Point for the cor. of secs. 1, 6, 7 and 12.  
Set the iron poast 24 ins. in the ground, with brass cap mkd.

T 3 S  
R13W R12W  
S 1 | S 6  
S12 | S 7  
1960

Raise a mound of stone, 3 ft. base, 2 ft. high, W. of corner.

Land, nearly level.  
Soil, gravel, sandy clay and loam.  
Timber, palo verde and ironwood; undergrowth, cactus, yucca, and greasewood.

North, bet. secs. 1 and 6.

Over nearly level land, through scattered timber and undergrowth.

11.20 Wash, 15 lks. wide, 3 ft. deep, drains S. 65° E.

36.20 Wash, 6 lks. wide, 6 ins. deep, drains S. 60° E.

40.00 Point for the  $\frac{1}{4}$  sec. cor. of secs. 1 and 6.

Set the iron post 24 ins. in the ground, with brass cap mkd.

T 3 S  
R13W  $\frac{1}{4}$  R12W  
S 1 | S 6  
1960

Raise a mound of stone, 3 $\frac{1}{2}$  ft. base, 2 $\frac{1}{2}$  ft. high, W. of corner.

49.00 Wash, 20 lks. wide, 2 ft. deep, drains S. 65° E.

52.40 Wash, 40 lks. wide, 3 ft. deep, drains S. 60° E.

67.80 Wash, 7 lks. wide, 2 ft. deep, drains S. 55° E.

80.32 Intersect S. bdy. of sec. 36, T. 2 S., R. 13 W.

Point for the closing cor. of Ts. 3 S., Rs. 12 and 13 W.

Set the iron post 24 ins. in the ground, with brass cap mkd.

T2S R13W  
S 36  
S 1 | S 6  
C | C  
R13W R12W  
T3S  
1960

Raise a mound of stone, 4 ft. base, 2 $\frac{1}{2}$  ft. high, S. of corner.

From this cor., the cor. of Ts. 2 S., Rs. 12 and 13 W., monumented with an iron post 3 ins. diam., firmly set, mkd. and witnessed as described in the official record, bears N. 89°58' E., 25.06 chs. distant.

14

Chains

Land, nearly level.  
Soil, gravel, sandy clay and loam.  
Timber, palo verde and ironwood; undergrowth, cactus, yucca, and greasewood.

Survey of the Subdivisions of T. 3 S., R. 13 W.

From the cor. of secs. 1, 2, 35 and 36, on the S. bdy. of the township, monumented with an iron post 3 ins. diam., set, mkd., and witnessed as described in the official record.

N. 0°01' W., bet. secs. 35 and 36.

Over gently rolling land, through scattered timber and undergrowth.

40.00 Point for the 1/4 sec. cor. of secs. 35 and 36.

Set the iron post 24 ins. in the ground, with brass cap mkd.

T3S R13W  
1/4  
S 35 | S 36  
1961

Raise a mound of stone, 3 ft. base, 2 1/2 ft. high, W. of corner.

80.00 Point for the cor. of secs. 25, 26, 35 and 36.

Set the iron post 24 ins. in the ground, with brass cap mkd.

T3S R13W  
S 26 | S 25  
S 35 | S 36  
1961

Raise a mound of stone, 3 ft. base, 2 1/2 ft. high, W. of corner.

Land, gently rolling.  
Soil, gravel, sandy clay and loam.  
Timber, palo verde; undergrowth, cactus and greasewood.

From the cor. of secs. 25, 30, 31 and 36, on the E. bdy. of the township.

West, bet. secs. 25 and 36.

Over gently rolling land, through scattered timber and undergrowth.

9.00 Wash, 40 lks. wide, 4 ft. deep, drains S.

10.00 Wash, 30 lks. wide, 3 ft. deep, drains S.

17.70 Wash, 100 lks. wide, 3 ft. deep, drains S.

27.60 Wash, 40 lks. wide, 2 ft. deep, drains S.

40.04 Point for the 1/4 sec. cor. of secs. 25 and 36.

Set the iron post 24 ins. in the ground, with brass cap mkd.

T3S R13W  
1/4 S 25  
S 36  
1961

## Survey of the Subdivisions of T. 3 S., R. 13 W.

## Chains

Raise a mound of stone, 3 ft. base, 2½ ft. high, N. of corner.

43.60 Wash, 10 lks. wide, 2 ft. deep, drains S.

65.00 Wash, 10 lks. wide, 2 ft. deep, drains S.

76.10 Wash, 10 lks. wide, 2 ft. deep, drains S.

80.08 The cor. of sections 25, 26, 35 and 36.

Land, gently rolling.

Soil, gravel, sandy clay and loam.

Timber, palo verde; undergrowth, cactus and greasewood.

N. 0°01' W., bet. secs. 25 and 26.

Over gently rolling land, through scattered timber and undergrowth.

40.00 Point for the ¼ sec. cor. of secs. 25 and 26.

Set the iron post 24 ins. in the ground, with brass cap mkd.

T3S ¼ R13W

S 26 | S 25

1961

Raise a mound of stone 3 ft. base, 2½ ft. high, W. of corner.

80.00 Point for the cor. of secs. 23, 24, 25 and 26.

Set the iron post 24 ins. in the ground, with brass cap mkd.

T3S R13W

S 23 | S 24

S 26 | S 25

1961

Raise a mound of stone, 3 ft. base, 2½ ft. high, W. of corner.

Land, gently rolling.

Soil, gravel, sandy clay and loam.

Timber, palo verde; undergrowth, cactus and greasewood.

From the cor. of secs. 19, 24, 25 and 30, on the E. bdy. of the township.

West, bet. secs. 24 and 25.

Over gently rolling land, through scattered timber and undergrowth.

11.40 Wash, 20 lks. wide, 2 ft. deep, drains S.

16.60 Wash, 30 lks. wide, 4 ft. deep, drains S. 20° E.

19.30 Wash, 40 lks. wide, 3 ft. deep, drains S. 20° E.

40.04 Point for the ¼ sec. cor. of secs. 24 and 25.

Set the iron post 20 ins. in the ground and in a mound of stone to top, with brass cap mkd.

T3S R13W

¼ S 24

S 25

1961

16

## Survey of the Subdivisions of T. 3 S., R. 13 W.

16.

Chains	
	Raise a mound of stone, 3 ft. base, 2½ ft. high, N. of corner.
80.08	The cor. of secs. 23, 24, 25 and 26.  Land, gently rolling. Soil, gravel, sandy clay and loam. Timber, palo verde; undergrowth, cactus and greasewood.
40.00	N. 0°01' W., bet. secs. 23 and 24.  Over gently rolling land, through scattered timber and undergrowth.  Point for the ¼ sec. cor. of secs. 23 and 24.  Set the iron post 24 ins. in the ground, with brass cap mkd.  <div style="text-align: center;">           T3S, R13W            S 23   S 24            1961         </div>
80.00	Raise a mound of stone, 3 ft. base, 2½ ft. high, W. of corner.  Point for the cor. of secs. 13, 14, 23 and 24.  Set the iron post 24 ins. in the ground, with brass cap mkd.  <div style="text-align: center;">           T3S R13W            S 14   S 13            S 23   S 24            1961         </div> Raise a mound of stone, 3 ft. base, 2½ ft. high, W. of corner.  Land, gently rolling. Soil, gravel, sandy clay and loam. Timber, palo verde; undergrowth, cactus and greasewood.
9.50	From the cor. of secs. 13, 18, 19 and 24, on the E. bdy. of the township.
10.00	N. 89°57' W., bet. secs. 13 and 24.
20.10	Over gently rolling land, through scattered timber and undergrowth.
24.30	Trail road, bears S. 30° E. and N. 30° W.
30.90	Trail road, bears N. and S.
40.04	Wash, 1.50 chs. wide, 3 ft. deep, drains S.
30.90	Wash, 10 lks. wide, 2 ft. deep, drains S. 30° E.
40.04	Wash, 30 lks. wide, 4 ft. deep, drains S. 30° E.
40.04	Point for the ¼ sec. cor. of secs. 13 and 24.  Set the iron post 24 ins. in the ground, with brass cap mkd.  <div style="text-align: center;">           T3S R13W            ¼ S 13            S 24            1961         </div>
	Raise a mound of stone, 3 ft. base, 2½ ft. high, N. of corner.

Chains	
43.60	Wash, 30 lks. wide, 2 ft. deep, drains S. 20° E.
56.00	Wash, 50 lks. wide, 3 ft. deep, drains S. 20° E.
66.40	Wash, 30 lks. wide, 2 ft. deep, drains S.
80.08	The cor. of secs. 13, 14, 23 and 24.
	Land, gently rolling. Soil, gravel, sandy clay and loam. Timber, palo verde; undergrowth, cactus and greasewood.
	N. 0°01' W., bet. secs. 13 and 14.
	Over gently rolling land, through scattered timber and undergrowth.
13.70	Wash, 10 lks. wide, 1 ft. deep, drains E.
39.00	Wash, 1.50 chs. wide, 4 ft. deep, drains SE.
40.00	Point for the $\frac{1}{4}$ sec. cor. of secs. 13 and 14.
	Set the iron post 24 ins. in the ground, with brass cap mkd.
	T3S R13W $\frac{1}{4}$ S 14   S 13 1961
	Raise a mound of stone, 3 ft. base, 2 $\frac{1}{2}$ ft. high, W. of corner.
54.90	Wash, 10 lks. wide, 3 ft. deep, drains SE.
63.70	Wash, 10 lks. wide, 1 ft. deep, drains E.
67.70	Wash, 30 lks. wide, 2 ft. deep, drains E.
77.00	Wash, 20 lks. wide, 2 ft. deep, drains E.
80.00	Point for the cor. of secs. 11, 12, 13 and 14.
	Set the iron post 24 ins. in the ground, with brass cap mkd.
	T3S R13W S 11   S 12 S 14   S 13 1961
	Raise a mound of stone, 3 ft. base, 2 $\frac{1}{2}$ ft. high, W. of corner.
	Land, gently rolling. Soil, gravel, sandy clay and loam. Timber, palo verde; undergrowth, cactus and greasewood.
	From the cor. of secs. 7, 12, 13 and 18, on E. bdy. of the township.
	N. 89°54' W., bet. secs. 12 and 13.
	Over gently rolling land, through scattered timber and undergrowth.
40.02	Point for the $\frac{1}{4}$ sec. cor. of secs. 12 and 13.
	Set the iron post 24 ins. in the ground, with brass cap mkd.

18

2001 4003

Survey of the Subdivisions of T. 3 S., R. 13 W.

Chains	
	T3S R13W $\frac{1}{4}$ $\frac{S\ 12}{S\ 13}$ 1961
	Raise a mound of stone, 3 ft. base, 2½ ft. high, N of corner.
57.40	Trail road, bears S. 20° E. and N. 20° W.
63.80	Wash, 10 lks. wide, 2 ft. deep, drains S. 20° E.
80.04	The cor. of secs. 11, 12, 13, and 14.
	Land, gently rolling. Soil, gravel, sandy clay and loam. Timber, palo verde; undergrowth, cactus and greasewood.
	N. 0°01 W., bet. secs. 11 and 12. Over gently rolling land, through scattered timber and undergrowth.
17.80	Wash, 10 lks. wide, 2 ft. deep, drains E.
27.00	Trail road, bears E. and W.
38.70	Wash, 10 lks. wide, 1 ft. deep, drains E.
40.00	Point for the ¼ sec. cor. of secs. 11 and 12.
	Set the iron post 24 ins. in the ground, with brass cap mkd.
	T3S, R13W $S\ 11\ \frac{1}{2}\ S\ 12$ 1961
	Raise a mound of stone, 3 ft. base, 2 ft. high, W. of corner.
61.00	Wash, 10 lks. wide, 2 ft. deep, drains E.
73.90	Wash, 10 lks. wide; 2 ft. deep, drains E.
80.00	Point for the cor. of secs. 1, 2, 11 and 12.
	Set the iron post 24 ins. in the ground, with brass cap mkd.
	T3S R13W $S\ 2\ \frac{1}{2}\ S\ 1$ $S\ 11\ \frac{1}{2}\ S\ 12$ 1961
	Land, gently rolling. Soil, gravel, sandy clay and loam. Timber, palo verde; undergrowth, cactus and greasewood.
	From the cor. of secs. 1, 6, 7 and 12, on the E. bdy. of the township.
	N. 89°54' W., bet. secs. 1 and 12.
	Over gently rolling land, through scattered timber and undergrowth.
25.50	Wash, 10 lks. wide, .3 ft. deep, drains S. 20° E.
40.02	Point for the ¼ sec. cor. of secs. 1 and 12.

## Chains

Set the iron post 24 ins. in the ground, with brass cap mkd.

$$\begin{array}{r} \text{T3S R13W} \\ \text{S } 1 \\ \hline \frac{1}{2} \text{ S } 12 \\ 1962 \end{array}$$

Raise a mound of stone, 3 ft. base, 2 ft. high, N. of corner.

42.90 Wash, 50 lks. wide, 4 ft. deep, drains S. 10° E.

80.04 The cor. of secs. 1, 2, 11 and 12.

Land, gently rolling.

Soil, gravel, sandy clay and loam.

Timber, palo verde; undergrowth, cactus and greasewood.

N. 0°01' W., bet. secs. 1 and 2.

Over gently rolling land, through scattered timber and undergrowth.

20.30 Wash, 40 lks. wide, 4 ft. deep, drains S. 70° E.

40.00 Point for the  $\frac{1}{2}$  sec. cor. of secs. 1 and 2.

Set the iron post 24 ins. in the ground, with brass cap mkd.

$$\begin{array}{r} \text{T3S R13W} \\ \frac{1}{2} \\ \text{S } 2 \text{ | S } 1 \\ 1961 \end{array}$$

Raise a mound of stone, 3 ft. base, 2 ft. high, W. of corner.

45.10 Trail road, bears N. 30° E., and S. 30° W.

53.40 Wash, 10 lks. wide, 4 ft. deep, drains S. 60° E.

80.12 Intersect the S. bdy. of sec. 35, T. 2 S., R. 13 W.

Point for the closing corner of secs. 1 and 2.

Set the iron post 24 ins. in the ground, with brass cap mkd.

$$\begin{array}{r} \text{T2S R13W} \\ \text{S } 35 \\ \hline \text{S } 2 \text{ | S } 1 \\ \text{C } | \text{ C} \\ \text{T3S R13W} \\ 1961 \end{array}$$

Raise a mound of stone, 3 ft. base, 2½ ft. high, S. of corner.

From this cor. the  $\frac{1}{2}$  sec. cor. on the S. bdy. of sec. 35, T. 2 S., R. 13 W., bears S. 89°58' W., 14.94 chs. distant.

Land, gently rolling.

Soil, sandy clay and loam.

Timber, palo verde; undergrowth, cactus and greasewood.

The point for the N.  $\frac{1}{2}$  sec. cor. of sec. 1 is at midpoint and on the N. bdy. of the township.

At the corner point

## Chains

Set the iron post 24 ins. in the ground, with brass cap mkd.

T2S R13W

$\frac{1}{4}$  S 1

T3S R13W

1961

Raise a mound of stone, 3 ft. base,  $2\frac{1}{2}$  ft. high, S. of corner.

From this cor., the cor. of secs. 35 and 36 on the S. bdy. of T. 2 S., R. 13 W., bears S.  $89^{\circ}58'$  W., 14.94 chs. distant.

From the cor. of secs. 2, 3, 34 and 35, on the S. bdy. of the township, monumented with an iron post 3 ins. diam., set, mkd., and witnessed as described in the official record.

N.  $0^{\circ}01'$  W., bet. secs. 34 and 35.

Over gently rolling land, through scattered timber and undergrowth.

2.90 Wash, 40 lks. wide, 3 ft. deep, drains S.  $20^{\circ}$  E.

29.00 Wash, 10 lks. wide, 2 ft. deep, drains SW.

40.00 Point for the  $\frac{1}{4}$  sec. cor. of secs. 34 and 35.

Set the iron post 24 ins. in the ground, with brass cap mkd.

T3S R13W

$\frac{1}{4}$

S 34 | S 35

1961

Raise a mound of stone, 3 ft. base,  $2\frac{1}{2}$  ft. high, W. of corner.

70.40 Wash, 30 lks. wide, 2 ft. deep, drains SW.

80.00 Point for the cor. of secs. 26, 27, 34 and 35.

Set the iron post 24 ins. in the ground, with brass cap mkd.

T3S R13W

S 27 | S 26

S 34 | S 35

1961

Raise a mound of stone, 3 ft. base,  $2\frac{1}{2}$  ft. high, W. of corner.

Land, gently rolling.

Soil, gravel, sandy clay and loam.

Timber, palo verde; undergrowth, cactus and greasewood.

From the cor. of secs. 25, 26, 35 and 36.

S.  $89^{\circ}58'$  W., bet. secs. 26 and 35.

Over gently rolling land, through scattered timber and undergrowth.

40.00 Point for the  $\frac{1}{4}$  sec. cor. of secs. 26 and 35.

Set the iron post 24 ins. in the ground, with brass cap mkd.

## Chains

T3S R13W  
 $\frac{1}{4}$   $\frac{S\ 26}{S\ 35}$   
 1961

Raise a mound of stone, 3 ft. base, 2½ ft. high, N. of corner.

- 48.90 Wash, 10 lks. wide, 2 ft. deep, drains S.  
 60.50 Wash, 20 lks. wide, 2 ft. deep, drains S.  
 71.60 Wash, 20 lks. wide, 2 ft. deep, drains SW.  
 77.20 Wash, 50 lks. wide, 2 ft. deep, drains S.  
 80.00 The cor. of secs. 26, 27, 34 and 35.

Land, gently rolling.  
 Soil, gravel, sandy clay and loam.  
 Timber, palo verde; undergrowth, cactus and greasewood.

N. 0°01' W., bet. secs. 26 and 27.

Over gently rolling land, through scattered timber and undergrowth..

- 5.70 Wash, 30 lks. wide, 3 ft. deep, drains SE.  
 11.10 Wash, 30 lks. wide, 3 ft. deep, drains SE.  
 29.40 Wash, 20 lks. wide, 2 ft. deep, drains E.  
 40.00 Point for the  $\frac{1}{4}$  sec. cor. of secs. 26 and 27.

Set the iron post 10 ins. in the ground to bedrock, and in a mound of stone to top, with brass cap mkd.

T3S R13W  
 $\frac{1}{4}$   
 S 27 | S 26  
 1961

- 46.10 Spur, slopes SE.  
 62.50 Wash, 20 lks. wide, 4 ft. deep, drains E.  
 66.30 Wash, 10 lks. wide, 2 ft. deep, drains E.  
 73.20 Wash, 20 lks. wide, 2 ft. deep, drains SE.  
 80.00 Point for the cor. of secs. 22, 23, 26 and 27.

Set the iron post 18 ins. in the ground to bedrock, and in a mound of stone to top, with brass cap mkd.

T3S R13W  
 S 22 | S 23  
 S 27 | S 26  
 1961

Raise a mound of stone, 3 ft. base, 2½ ft. high, W. of corner.

Land, rolling.  
 Soil, gravel, sandy clay and loam.  
 Timber, palo verde; undergrowth, cactus and greasewood.

Chains	
	From the cor. of secs. 23, 24, 25 and 26.
	S. 89°57' W., bet. secs. 23 and 26.
	Over gently rolling land, through scattered timber and undergrowth.
35.70	Wash, 10 lks. wide, 1 ft. deep, course S.
39.99	Point for the $\frac{1}{4}$ sec. cor. of secs. 23 and 26.
	Set the iron post 24 ins. in the ground, with brass cap mkd.
	$\begin{array}{r} \text{T3S R13W} \\ \frac{1}{4} \text{ S } 23 \\ \hline \text{S } 26 \\ 1961 \end{array}$
	Raise a mound of stone, 3 ft. base, 2 $\frac{1}{2}$ ft. high, N. of corner.
46.00	Wash, 10 lks. wide, drains S.
51.00	Wash, 10 lks. wide, 1 ft. deep, drains S.
59.80	Wash, 30 lks. wide, 2 ft. deep, drains S.
69.60	Wash, 20 lks. wide, 4 ft. deep, drains S.
79.98	The cor. of secs. 22, 23, 26 and 27.
	Land, gently rolling.
	Soil, gravel, sandy clay and loam.
	Timber, palo verde; undergrowth, cactus and greasewood.
	N. 0°01' W., bet. secs. 22 and 23.
	Over rolling and broken land, through scattered timber and undergrowth.
32.61	Spur, projects E.
40.00	Point for the $\frac{1}{4}$ sec. cor. of secs. 22 and 23.
	Set the iron post 24 ins. in the ground, with brass cap mkd.
	$\begin{array}{r} \text{T3S R13W} \\ \frac{1}{4} \\ \text{S } 22   \text{S } 23 \\ 1961 \end{array}$
	from which
	U.S. Coast and Geodetic Survey Triangulation Station "MALLEY" bears S. 26°54' W., 10.66 chs. distant.
	Raise a mound of stone, 3 ft. base, 2 $\frac{1}{2}$ ft. high, W. of corner.
	Thence begin desc. over NE. slope.
51.92	Draw, drains E.; asc. over SE. slope.
69.66	Point of spur, slopes E.
80.00	Point for the cor. of secs. 14, 15, 22 and 23.

## Survey of the Subdivisions of T. 3 S., R. 13 W.

23.

## Chains

Set the iron post 24 ins. in the ground, with brass cap mkd.

$$\begin{array}{r} \text{T3S R13W} \\ \text{S 15 | S 14} \\ \hline \text{S 22 | S 23} \\ \text{1961} \end{array}$$

Raise a mound of stone, 3 ft. base, 2½ ft. high, W. of corner.

Land, broken.

Soil, gravel, sandy clay and loam.

Timber, none; undergrowth, cactus and greasewood.

From the cor. of secs. 13, 14, 23 and 24.

S. 89°54' W., bet. secs. 14 and 23.

Over rolling and broken land, through scattered timber and undergrowth.

23.47 Point of spur, slopes SE.; desc. 105 ft. to the ¼ sec. corner.

40.02 Point for the ¼ sec. cor. of secs. 14 and 23.

Set the iron post 6 ins. in the ground to bedrock and in a mound of stone to top, with brass cap mkd.

$$\begin{array}{r} \text{T3S R13W} \\ \frac{1}{4} \frac{\text{S 14}}{\text{S 23}} \\ \text{1961} \end{array}$$

44.88 Wash, 30 lks. wide, 4 ft. deep, drains SE.; thence asc. to sec. corner.

80.04 The cor. of secs. 14, 15, 22 and 23.

Land, rolling and broken.

Soil, gravel, sandy clay and loam.

Timber, palo verde; undergrowth, cactus and greasewood.

N. 0°01' W., bet. secs. 14 and 15.

Over rolling land, through scattered timber and undergrowth.

8.00 Wash, 10 lks. wide, 1 ft. deep, drains to SE.

30.05 Small draw, drains to E.

40.00 Point for the ¼ sec. cor. of secs. 14 and 15.

Set the iron post 6 ins. in the ground to bedrock, and in a mound of stone to top, with brass cap mkd.

$$\begin{array}{r} \text{T3S R13W} \\ \frac{1}{4} \\ \text{S 15 | S 14} \\ \text{1961} \end{array}$$

Raise a mound of stone, 3 ft. base, 2½ ft. high, W. of corner.

56.41 Draw, drains W.; ascend gradually.

73.72 Draw, drains W.

80.00 Point for the cor. of secs. 10, 11, 14 and 15.

## Chains

Set the iron post 24 ins. in the ground, with brass cap mkd.

T3S R13W  
 S 10 | S 11  
 S 15 | S 14  
 1961

Raise a mound of stone, 3 ft. base, 2½ ft. high, W. of corner.

Land, rolling mesa top.

Soil, gravel, sandy clay and loam.

Timber, palo verde; undergrowth, cactus and greasewood.

From the cor. of secs. 11, 12, 13 and 14.

S. 89°47' W., bet. secs. 11 and 14.

Over gently rolling land, through scattered timber and undergrowth.

20.50 Wash, 150 lks. wide, 5 ft. deep, drains S. 30° E.

40.00 Point for the ¼ sec. cor. of secs. 11 and 14.

Set the iron post 24 ins. in the ground, with brass cap mkd.

T3S R13W  
 S 11  
 ¼ ———  
 S 14  
 1961

Raise a mound of stone, 3 ft. base, 2½ ft. high, N. of corner.

60.00 Begin gentle ascent over rocky E. slope.

69.20 Top of ascent; thence along S. slope.

80.00 The cor. of secs. 10, 11, 14 and 15.

Land, rolling mesa top.

Soil, gravel, sandy clay and loam.

Timber, palo verde; undergrowth, cactus and greasewood.

N. 0°01' W., bet. secs. 10 and 11.

Over gently rolling land, through scattered timber and undergrowth.

7.78 Desc. 136 ft. over N. slope.

24.98 Wash, 1.50 chs. wide, 3 ft. deep, drains E.

36.20 Road, bears E. and W.

40.00 Point for the ¼ sec. cor. of secs. 10 and 11.

Set the iron post 24 ins. in the ground, with brass cap mkd.

T3S R13W  
 ¼  
 S 11 | S 10  
 1961

Raise a mound of stone, 3 ft. base, 2½ ft. high, W. of corner.

## Survey of the Subdivisions of T. 3 S., R. 13 W.

## Chains

46.00 Wash, 30 lks. wide, 2 ft. deep, drains SE.

57.90 Road, bears NW. and SE.

67.20 Wash, 50 lks. wide, 4 ft. deep, drains SE.

73.00 Road, bears E. and W.

73.90 Wash, 20 lks. wide, 2 ft. deep, drains E.

80.00 Point for the cor. of secs. 2, 3, 10 and 11.

Set the iron post 24 ins. in the ground, with brass cap mkd.

T3S R13W	
S 3	S 2
S 10	S 11
1961	

Raise a mound of stone, 3 ft. base, 2½ ft. high, W. of corner.

Land, gently rolling.

Soil, gravel, sandy clay and loam.

Timber, scattered palo verde; undergrowth, cactus and greasewood.

From the cor. of secs. 1, 2, 11 and 12.

S. 89°44' W., bet. secs. 2 and 11.

Over gently rolling land, through scattered timber and undergrowth.

17.90 Trail road, bears N. 30° E. and S. 30° W.

39.93 Point for the ¼ cor. of secs. 2 and 11.

Set the iron post 24 ins. in the ground, with brass cap mkd.

T3S R13W	
¼	S 2
	S 11
1961	

46.90 Trail road, bears N. 75° W. and S. 75° E.

62.00 Wash, 10 lks. wide, 2 ft. deep, drains S.

79.86 The cor. of secs. 2, 3, 10 and 11.

Land, gently rolling.

Soil, gravel, sandy clay and loam.

Timber, palo verde; undergrowth, cactus and greasewood.

N. 0°01' W., bet. secs. 2 and 3.

Over gently rolling land, through scattered timber and undergrowth.

17.50 Wash, 20 lks. wide, 3 ft. deep, drains N. 30° W.

25.50 Trail road, bears N. 70° W. and S. 70° E.

40.00 Point for the ¼ cor. of secs. 2 and 3.

Set the iron post 20 ins. in the ground, with brass cap mkd.

Survey of the Subdivisions of T. 3 S., R. 13 W.

Chains	
	<p style="text-align: center;">T3S R13W  <math>\frac{1}{2}</math>                      S 3   S 2                      1961</p> <p>Raise a mound of stone, 3 ft. base, 2½ ft. high, W. of corner.</p>
57.10	Wash, 70 lks. wide, 2 ft. deep, drains E.
80.43	Intersect the S. bdy. of sec. 34, T. 2 S., R. 13 W.
	Point for the closing corner of secs. 2 and 3.
	Set the iron post 24 ins. in the ground, with brass cap mkd.
	<p style="text-align: center;">T2S R13W                      S 34  <hr/>                     S 3   S 2                      C C                      T3S R13W                      1961</p> <p>Raise a mound of stone, 4 ft. base, 2½ ft. high, S. of corner.</p> <p>From this cor. the <math>\frac{1}{4}</math> sec. cor. on the S. bdy. of sec. 34, T. 2 S., R. 13 W., bears S. 89°58' W., 15.10 chs. distant.</p> <p>Land, gently rolling.                      Soil, gravel, sandy clay and loam.                      Timber, palo verde; undergrowth, cactus and greasewood.</p>
	<p>The point for the N. <math>\frac{1}{4}</math> sec. cor. of sec. 2 is at midpoint and on the N. bdy. of the township.</p> <p>At the corner point</p> <p>Set the iron post 24 ins. in the ground, with brass cap mkd.</p>
	<p style="text-align: center;">T2S R13W  <hr/> <math>\frac{1}{4}</math> S 2                      T3S R13W                      1961</p> <p>Raise a mound of stone, 3 ft. base, 2½ ft. high, S. of corner.</p> <p>From this cor. the cor. of secs. 34 and 35 on the S. bdy. of T. 2 S., R. 13 W., bears S. 89°58' W., 15.02 chs. distant.</p>
	<p>From the cor. of secs. 3, 4, 33 and 34, on the S. bdy. of the township, monumented with an iron post, 3 ins. in diam., set, mkd., and witnessed as described in the official record.</p> <p>N. 0°02' W., bet. secs. 33 and 34.</p> <p>Over gently rolling land, through scattered timber and undergrowth.</p>
1.00	Spur, slopes E.
4.50	Wash, 10 lks. wide, 1 ft. deep, drains E.
39.50	Wash, 10 lks. wide, 1 ft. deep, drains E.
40.00	Point for the $\frac{1}{4}$ cor. of secs. 33 and 34.

## Survey of the Subdivisions of T. 3 S., R. 13 W.

27.

## Chains

Set the iron post 24 ins. in the ground, with brass cap mkd.

T3S R13W  
 $\frac{1}{2}$   
 S 33 | S 34  
 1961

Raise a mound of stone, 3 ft. base,  $2\frac{1}{2}$  ft. high, W. of corner.

42.30 Wash, 20 lks. wide, 2 ft. deep, drains E.

64.50 Wash, 20 lks. wide, 2 ft. deep, drains E.

70.25 Wash, 30 lks. wide, 2 ft. deep, drains E.

80.00 Point for the cor. of secs. 27, 28, 33 and 34.

Set the iron post 24 ins. in the ground, with brass cap mkd.

T3S R13W  
 S 28 | S 27  
 S 33 | S 34  
 1961

Raise a mound of stone, 3 ft. base,  $2\frac{1}{2}$  ft. high, W. of corner.

Land, gently rolling.

Soil, gravel, sandy clay and loam.

Timber, palo verde; undergrowth, catclaw, greasewood.

From the cor. of secs. 26, 27, 34 and 35.

S.  $89^{\circ}58'$  W., bet. secs. 27 and 34.

Over gently rolling hills, through scattered timber and undergrowth.

7.30 Wash, 10 lks. wide, 2 ft. deep, drains S.

20.80 Spur, slopes N.

29.10 Wash, 10 lks. wide, 3 ft. deep, drains S.

32.40 Wash, 20 lks. wide, 3 ft. deep, drains SE.

40.02 Point for the  $\frac{1}{2}$  sec. cor. of secs. 27 and 34.

Set the iron post 24 ins. in the ground, with brass cap mkd.

T3S R13W  
 $\frac{1}{2}$  S 27  
 S 34  
 1961

Raise a mound of stone, 3 ft. base,  $2\frac{1}{2}$  ft. high, N. of corner.

62.80 Wash, 30 lks. wide, 3 ft. deep, drains SE.

80.04 The cor. of secs. 27, 28, 33 and 34.

Land, gently rolling hills.

Soil, gravel, sandy clay and loam.

Timber, palo verde; undergrowth, greasewood and cactus.

N.  $0^{\circ}02'$  W., bet. secs. 27 and 28.

Over nearly level land, through scattered timber and undergrowth.

Chains	
14.60	Wash, 20 lks. wide, 3 ft. deep, drains E.
40.00	Point for the $\frac{1}{4}$ sec. cor. of secs. 27 and 28. Set the iron post 24 ins. in the ground, with brass cap mkd.
	T3S R13W $\frac{1}{4}$ S 28   S 27 1961
	Raise a mound of stone, 3 ft. base, $2\frac{1}{2}$ ft. high, W. of corner.
	Asc. 95 ft. over S. slope.
47.20	Spur, slopes E.; desc. 106 ft. over N. slope.
57.45	Spur, slopes E.
80.00	Point for the cor. of secs. 21, 22, 27 and 28.
	Set the iron post 6 ins. in the ground to bedrock, mound of stone to top, with brass cap mkd.
	T3S R13W S 21   S 22 <hr/> S 28   S 27 1961
	Land, nearly level. Soil, gravel, sandy clay and loam. Timber, palo verde; undergrowth, cactus and greasewood.
	From the cor. of secs. 22, 23, 26 and 27.
	S. $89^{\circ} 55'$ W., bet. secs. 22 and 27.
	Over rolling hills, through scattered timber and undergrowth.
19.80	Wash, 20 lks. wide, 2 ft. deep, drains S.; ascend.
33.10	Spur, slopes E.; begin gradual descent.
40.12	Point for the $\frac{1}{4}$ sec. cor. of secs. 22 and 27.
	Set the iron post 6 ins. in the ground to bedrock and in a mound of stone to top, with brass cap mkd.
	T3S R13W $\frac{1}{4}$ S 22 <hr/> S 27 1961
41.70	Wash, 10 lks. wide, 2 ft. deep, drains S.
63.95	Spur, slopes S.
67.74	Wash, 10 lks. wide, 2 ft. deep, drains S.
80.24	The cor. of secs. 21, 22, 27 and 28.

## Survey of the Subdivision of T. 3 S., R. 13 W.

29.

## Chains

Land, gently rolling.  
Soil, gravel, sandy clay and loam.  
Timber, palo verde; undergrowth, cactus and greasewood.

N. 0°02' W., bet. secs. 21 and 22.

Over rolling and broken land, through scattered timber and undergrowth.

2.27 Spur, slopes W.; cont. asc. W. slope.

21.00 Spur, slopes E.; desc. over N. slope.

40.00 Point for the  $\frac{1}{4}$  sec. cor. of secs. 21 and 22.

Set the iron post 8 ins. in the ground to bedrock and in a mound of stone to top, with brass cap mkd.

T3S R13W

$\frac{1}{4}$

S21|S22

1961

59.00 Base of hill, begin ascending.

80.00 Point for the cor. of secs. 15, 16, 21 and 22.

Set the iron post 12 ins. in the ground to bedrock and in a mound of stone to top, with brass cap mkd.

T3S R13W

S 16|S 15

S 21|S 22

1961

Land, rolling.

Soil, gravel, sandy clay and loam.

Timber, palo verde; undergrowth, cactus and greasewood.

From the cor. of secs. 14, 15, 22 and 23.

S. 89°58' W., bet. secs. 15 and 22.

Over gently rolling mesa top, through scattering timber and undergrowth.

40.10 Point for the  $\frac{1}{4}$  sec. cor. of secs. 15 and 22.

Set the iron post 6 ins. in the ground to bedrock and in a mound of stone to top, with brass cap mkd.

T3S R13W

$\frac{1}{4}$  S 15

S 22

1961

Descend.

63.80 Wash, 40 lks. wide, 2 ft. deep, drains W.

66.20 Wash, 40 lks. wide, 2 ft. deep, drains SW.

72.10 Wash, 20 lks. wide, 2 ft. deep, drains NW.

Survey of the Subdivisions of T. 3 S., R. 13 W.

Chains	
78.50	Spur, slopes NW.; asc. over NE. slope.
80.20	The cor. of secs. 15, 16, 21 and 22.
	Land, rolling. Soil, gravel, sandy clay and loam. Timber, palo verde; undergrowth, cactus and greasewood.
	N. 0°02 W., bet. secs. 15 and 16.
	Over gently rolling land, through scattered timber and undergrowth.
1.30	Descend.
6.50	Wash, 30 lks. wide, 3 ft. deep, drains NW.; asc. SW. slope.
26.60	Spur, slopes NW.; desc. over NW. slope.
40.00	Point for the ¼ sec. cor. of secs. 15 and 16.
	Set the iron post 18 ins. in the ground to hard rock and in a mound of stone to top, with brass cap mkd.
	<p style="text-align: center;">T3S R13W ¼ S16 S15 1961</p> <p style="text-align: center;">Raise a mound of stone, 5 ft. base, 2½ ft. high, W. of corner.</p>
63.60	Saddle of spur, bears E. and W.
78.85	Wash, 20 lks. wide, 2 ft. deep, drains W.
80.00	Point for the cor. of secs. 9, 10, 15 and 16.
	Set the iron post 24 ins. in the ground, with brass cap mkd.
	<p style="text-align: center;">T3S R13W S 9 S 10 S 16 S 15 1961</p> <p style="text-align: center;">Raise a mound of stone, 3 ft. base, 2½ ft. high, W. of corner.</p>
	Land, rolling. Soil, gravel, sandy clay and loam. Timber, palo verde; undergrowth, cactus and greasewood.
	From the cor. of secs. 10, 11, 14 and 15.
	S. 89°58' W., bet. secs. 10 and 15.
	Over rolling and broken land sloping to W.; through scattered timber and undergrowth.
2.50	Begin desc. W. slope.
30.86	End desc.; thence over nearly level valley.
40.10	Point for the ¼ sec. cor. of secs. 10 and 15.
	Set the iron post 24 ins. in the ground, with brass cap mkd.

## Survey of the Subdivisions of T. 3 S., R. 13 W.

Chains

T3S R13W  
 $\frac{1}{4}$   $\frac{S 10}{S 15}$   
 1961

Raise a mound of stone, 3 ft. base,  $2\frac{1}{2}$  ft. high, N. of corner.

47.90 Wash, 30 lks. wide, 4 ft. deep, drains NE.

80.20 The cor. of secs. 9, 10, 15 and 16.

Land, rolling in E.  $\frac{1}{2}$ ; nearly level in W.  $\frac{1}{2}$ .

Soil, gravel, sandy clay and loam.

Timber, palo verde; undergrowth, catclaw and greasewood.

N.  $0^{\circ}02'$  W., bet. secs. 9 and 10.

Over nearly level land, through scattered timber and undergrowth.

2.90 Wash, 40 lks. wide, 3 ft. deep, drains E.

8.80 Trail road, bears E. and W.

12.25 Spur, slopes SE.

38.20 Wash, 1 chain wide, 4 ft. deep, drains E.

40.00 Point for the  $\frac{1}{4}$  sec. cor. of secs. 9 and 10.

Set the iron post 24 ins. in the ground, with brass cap mkd.

T3S R13W  
 $\frac{1}{4}$   
 S 9 | S 10  
 1961

Raise a mound of stone, 3 ft. base,  $2\frac{1}{2}$  ft. high, W. of corner.

44.00 Wash, 40 lks. wide, 4 ft. deep, drains E.

50.40 Wash, 20 lks. wide, 2 ft. deep, drains SE.

58.60 Wash, 40 lks. wide, 2 ft. deep, drains SE.

63.20 Track road, bears E. and W.

80.00 Point for the cor. of secs. 3, 4, 9 and 10.

Set the iron post 24 ins. in the ground, with brass cap mkd.

T3S R13W  
 S 4 | S 3  
 S 9 | S 10  
 1961

Raise a mound of stone,  $3\frac{1}{2}$  ft. base,  $2\frac{1}{2}$  ft. high, W. of corner.

Land, nearly level.

Soil, gravel, sandy clay and loam.

Timber, palo verde; undergrowth, catclaw and cactus.

From the cor. of secs. 2, 3, 10 and 11.

N.  $89^{\circ}58'$  W., bet. secs. 3 and 10.

Survey of the Subdivisions of T. 3 S., R. 13 W.

Chains	
	Over nearly level land, through scattered timber and undergrowth.
14.30	Wash, 50 lks. wide, 3 ft. deep, drains SE.
21.90	Wash, 1 chain wide, 3 ft. deep, drains SE.
40.09	Point for the $\frac{1}{4}$ sec. cor. of secs. 3 and 10. Set the iron post 24 ins. in the ground, with brass cap mkd.  <div style="text-align: center;">                     T3S R13W  <math>\frac{1}{4}</math> <math>\frac{S \ 3}{S \ 10}</math>                      1961                 </div> Raise a mound of stone, 3 ft. base, $2\frac{1}{2}$ ft. high, N. of corner.
41.40	Trail road, bears NW. and SE.
49.10	Trail road, bears N. $75^\circ$ W., and S. $75^\circ$ E.
72.60	Wash, 30 lks. wide, 2 ft. deep, drains SE.
80.18	The cor. of secs. 3, 4, 9 and 10.  Land, nearly level. Soil, gravel, sandy clay and loam. Timber, palo verde; undergrowth, cactus and greasewood.
	N. $0^\circ 02'$ W., bet. secs. 3 and 4.  Over gently rolling land, through scattered timber and undergrowth.
1.80	Wash, 20 lks. wide, 3 ft. deep, drains E.
5.80	Road, bears N. $70^\circ$ W., and S. $70^\circ$ E.
36.90	Wash, 20 lks. wide, 3 ft. deep, drains E.
40.00	Point for the $\frac{1}{4}$ sec. cor. of secs. 3 and 4. Set the iron post 24 ins. in the ground, with brass cap mkd.  <div style="text-align: center;">                     T3S R13W  <math>\frac{1}{4}</math>                      S 4   S 3                      1961                 </div> Raise a mound of stone, 3 ft. base, $2\frac{1}{2}$ ft. high, W. of corner.
48.00	Wash, 250 lks. wide, 2 ft. deep, drains E.
73.00	Track road, bears NW. and SE.
80.40	Intersect the S. bdy. of sec. 33, T. 2 S., R. 13 W.  Point for the closing corner of secs. 3 and 4.  Set the iron post 24 ins. in the ground, with brass cap mkd.  <div style="text-align: center;">                     T2S R13W                      S33  <hr/>                     T3S   R13W                      S 4   S 3                      C C                      1961                 </div>

## Survey of the Subdivisions of T. 3 S., R. 13 W.

## Chains

Raise a mound of stone, 3 ft. base, 2½ ft. high, S. of corner.

From this cor., the ¼ sec. cor. on the S. bdy. of sec. 33,  
T. 2 S., R. 13 W., bears S. 89°58' W., 15 chs. distant.

Land, gently rolling.

Soil, gravel, sandy clay and loam.

Timber, palo verde; undergrowth, cactus and greasewood.

The point for the N. ¼ sec. cor. of sec. 3 is at midpoint and on  
the bdy. of the township.

At the corner point

Set the iron post 24 ins. in the ground, with brass cap mkd.

T2S R13W

¼ S 3

T3S R13W

1961

Raise a mound of stone, 4 ft. base, 2½ ft. high, S. of corner.

From this cor., the cor. of secs. 33 and 34 on the S. bdy.  
of T. 2 S., R. 13 W., bears S. 89°58' W., 15.05 chs. distant.

From the cor. of secs. 4, 5, 32 and 33, on the S. bdy. of the  
township, monumented with an iron post 3 ins. diam., set, mkd.,  
and witnessed as described in the official record.

N. 0°02' W., bet. secs. 32 and 33.

Over gently rolling land, through scattered timber and undergrowth.

1.80 Road, bladed, bears E. and W.

2.80 Wash, 10 lks. wide, 1 ft. deep, drains W.

5.00 Spur, slopes W.

22.90 Road, bladed, bears NW. and SE.

40.00 Point for the ¼ sec. cor. of secs. 32 and 33.

Set the iron post 24 ins. in the ground, with brass cap mkd.

T3S R13W

¼

S32|S33

1961

Raise a mound of stone, 3 ft. base, 2½ ft. high, W. of corner.

65.50 Low spur, slopes W.

72.70 Low spur, slopes E.

80.00 Point for the cor. of secs. 28, 29, 32 and 33.

Set the iron post 24 ins. in the ground, with brass cap mkd.

T3S R13W

S29|S28

S32|S33

1961

Chains	
	<p>Raise a mound of stone, 3 ft. base, 2½ ft. high, W. of corner.</p> <p>Land, gently rolling. Soil, gravel, sandy clay and loam. Timber, palo verde; undergrowth, cactus and greasewood.</p>
	<p>From the cor. of secs. 27, 28, 33 and 34.</p> <p>S. 89°59' W., bet. secs. 28 and 33.</p> <p>Over gently rolling land, through scattered timber and undergrowth.</p>
7.20	Wash, 10 lks. wide, 2 ft. deep, drains S.
10.20	Wash, 10 lks. wide, 2 ft. deep, drains S.
40.01	Point for the ¼ sec. cor. of secs. 28 and 33.
	Set the iron post 24 ins. in the ground, with brass cap mkd.
	<p>T3S R13W                  S 28            ¼ ———                  S 33            1961</p>
	<p>Raise a mound of stone, 3 ft. base, 2½ ft. high, N. of corner.</p>
55.00	Wash, 50 lks. wide, 3 ft. deep, drains S.
65.00	Low spur, slopes N.
67.50	Wash, 30 lks. wide, 3 ft. deep, drains E.
77.50	Wash, 10 lks. wide, 2 ft. deep, drains S.
80.02	The cor. of secs. 28, 29, 32 and 33.
	<p>Land, gently rolling. Soil, gravel, sandy clay and loam. Timber, palo verde; undergrowth, cactus.</p>
	<p>N. 0°02' W., bet. secs. 28 and 29.</p> <p>Over gently rolling land, through scattered timber and undergrowth.</p>
6.04	Low spur, slopes E.
10.25	Wash, 10 lks. wide, 2 ft. deep, drains N. 70° E.
12.80	Low spur, slopes E.
21.80	Wash, 30 lks. wide, 2 ft. deep, drains SE.
40.00	Point for the ¼ sec. cor. of secs. 28 and 29.
	Set the iron post 10 ins. in the ground to bedrock, and in a mound of stone to top, with brass cap mkd.
	<p>T3S R13W                  ¼            S29   S28            1961</p>
50.30	Wash, 1 chain wide, 3 ft. deep, drains S. 60° E.

## Chains

72.20 Wash, 30 lks. wide, 2 ft. deep, drains S. 60° W.; begin ascent.

80.00 Point for the cor. of secs. 20, 21, 28 and 29.

Set the iron post 4 ins. in the ground to bedrock and in a mound of stone to top, with brass cap mkd.

T3S R13W	
S20	S21
S29	S28
1961	

Land, gently rolling.

Soil, gravel, sandy clay and loam.

Timber, palo verde; undergrowth, catclaw and cactus.

---

From the cor. of secs. 21, 22, 27 and 28.

West, bet. secs. 21 and 28.

Over rolling and broken land, through scattered timber and undergrowth.

9.80 Wash, 15 lks. wide, 3 ft. deep, drains S.

18.00 Low spur, slopes S.

31.30 Wash, 40 lks. wide, 3 feet deep, drains S.

39.97 Point for the  $\frac{1}{4}$  sec. cor. of secs. 21 and 28.

Set the iron post 6 ins. in the ground to bed rock and in a mound of stone to top, with brass cap mkd.

T3S R13W	
$\frac{1}{4}$	S 21
	S 28
1961	

47.50 Wash, 10 lks. wide, 2 ft. deep, drains S.; asc. SE. slope.

58.50 End ascent; low, very rocky hill top.

62.60 W. edge of hill, begin descent.

71.50 Wash, 30 lks. wide, 3 ft. deep, drains S.

79.94 The cor. of secs. 20, 21, 28 and 29.

Land, rolling and broken.

Soil, gravel, sandy clay and loam.

Timber, palo verde; undergrowth, cactus and greasewood.

---

N. 0°02' W., bet. secs. 20 and 21.

Over rolling and broken land, through scattered timber and undergrowth.

Ascend.

11.84 Spur, slopes W.; descend.

24.55 Wash, 20 lks. wide, drains E.; begin ascending.

## Survey of the Subdivisions of T. 3 S., R. 13 W.

Chains	
40.00	<p>Point for the <math>\frac{1}{4}</math> sec. cor. of secs. 20 and 21.</p> <p>Set the iron post 8 ins. in the ground to bedrock and in a mound of stone to top, with brass cap mkd.</p> <p style="text-align: center;">T3S R13W <math>\frac{1}{4}</math> S20 S21 1961</p> <p>Raise a mound of stone, 3 ft. base, 2 ft. high, W. of corner.</p>
42.35	Spur, slopes E.; desc. over NE. slope.
59.81	Wash, 15 lks. wide, 2 ft. deep, drains E.
80.00	<p>Point for the cor. of secs. 16, 17, 20 and 21.</p> <p>Set the iron post 12 ins. in the ground to bedrock and in a mound of stone to top, with brass cap mkd.</p> <p style="text-align: center;">T3S R13W S17 S16 S20 S21 1961</p> <p>Land, rolling and broken. Soil, gravel, sandy clay and loam. Timber, palo verde; undergrowth, catclaw and cactus.</p>
	From the cor. of secs. 15, 16, 21 and 22.
	S. 89°54' W., bet. secs. 16 and 21.
	Over rolling and broken land, through scattered timber and undergrowth.
12.10	Begin asc. over W. slope.
30.10	Spur, slopes N.
39.99	<p>Point for the <math>\frac{1}{4}</math> sec. cor. of secs. 16 and 21.</p> <p>Set the iron post 12 ins. in the ground to bedrock and in a mound of stone to top, with brass cap mkd.</p> <p style="text-align: center;">T3S R13W <math>\frac{1}{4}</math> S 16 S 21 1961</p> <p>Raise a mound of stone, 3<math>\frac{1}{2}</math> ft. base, 2<math>\frac{1}{2}</math> ft. high, N. of corner</p>
44.30	Spur, slopes N. 15° W.; desc. over W. slope.
64.00	End desc.; enter nearly level land.
79.98	<p>The cor. of secs. 16, 17, 20 and 21.</p> <p>Land, rolling. Soil, gravel, sandy clay and loam. Timber, palo verde; undergrowth, cactus and greasewood.</p>

## Survey of the Subdivisions of T. 3 S., R. 13 W.

37.

## Chains

N. 0°02' W., bet. secs. 16 and 17.

Over gently rolling land, through scattered timber and undergrowth.

4.90 Wash, 150 lks. wide, 6 ft. deep, drains SE.

7.90 Wash, 75 lks. wide, 3 ft. deep, drains S.

25.90 Wash, 60 lks. wide, 6 ft. deep, drains E.

37.90 Wash, 30 lks. wide, 3 ft. deep, drains N. 80° E.

39.00 Road, bladed, bears N. 65° E., and S. 65° W.

40.00 Point for the  $\frac{1}{4}$  sec. cor. of secs. 16 and 17.

Set the iron post 18 ins. in the ground to bedrock and in a mound of stone to top, with brass cap mkd.

T3S R13W

 $\frac{1}{4}$ 

S17|S16

1961

Raise a mound of stone, 3 ft. base, 2 ft. high, W. of corner.

52.00 Road, unimproved, bears NE. and SW.

80.00 Point for the cor. of secs. 8, 9, 16 and 17.

Set the iron post 24 ins. in the ground, with brass cap mkd.

T3S R13W

S 8|S 9

S17|S16

1961

Raise a mound of stone, 3 ft. base, 2 ft. high, W. of corner.

Land, gently rolling.

Soil, gravel, sandy clay and loam.

Timber, palo verde; undergrowth, cactus and greasewood.

From the cor. of secs. 9, 10, 15 and 16.

S. 89°55' W., bet. secs. 9 and 16.

Over nearly level land, through scattered timber and undergrowth.

4.50 Wash, 40 lks. wide, 5 ft. deep, drains NE.

19.20 Road, bladed, bears N. 60° E., and S. 60° W.

39.95 Point for the  $\frac{1}{4}$  sec. cor. of secs. 9 and 16.

Set the iron post 25 ins. in the ground, with brass cap mkd.

T3S R13W

 $\frac{1}{4}$  S 9

S 16

1961

Raise a mound of stone, 4 ft. base, 3 ft. high, N. of corner.

## Survey of the Subdivisions of T. 3 S., R. 13 W.

Chains	
79.90	<p>The corner of secs. 8, 9, 16 and 17.</p> <p>Land, nearly level. Soil, gravel, sandy clay and loam. Timber, palo verde; undergrowth, catclaw and cactus.</p>
13.80	<p>N. 0°02' W., bet. secs. 8 and 9.</p> <p>Over nearly level land, through scattered timber and undergrowth.</p>
18.10	Wash, 30 lks. wide, 3 ft. deep, drains E.
40.00	<p>Wash, 1 chain wide, 2 ft. deep, drains E.</p> <p>Point for the <math>\frac{1}{4}</math> sec. cor. of secs. 8 and 9.</p> <p>Set the iron post 24 ins. in the ground, with brass cap mkd.</p>
47.90	<p style="text-align: center;">T3S R13W <math>\frac{1}{4}</math> S 8   S 9 1961</p> <p>Raise a mound of stone, 3 ft. base, 2 ft. high, W. of corner.</p> <p>Road, unimproved, bears N. 20° E. and S. 20° W.</p>
73.00	Wash, 30 lks. wide, 3 ft. deep, drains E.
75.80	Road, unimproved, bears E. and W.
80.00	<p>Point for the cor. of secs. 4, 5, 8 and 9.</p> <p>Set the iron post 10 ins. in the ground to bedrock and in a mound of stone to top, with brass cap mkd.</p> <p style="text-align: center;">T3S R13W S 5   S 4 S 8   S 9 1961</p> <p>Land, nearly level. Soil, gravel, sandy clay and loam. Timber, palo verde; undergrowth, cactus and greasewood.</p>
26.50	<p>From the cor. of secs. 3, 4, 9 and 10.</p> <p>N. 89°54' W., bet. secs. 4 and 9.</p> <p>Over nearly level land, through scattered timber and undergrowth.</p>
39.20	Wash, 10 lks. wide, 4 ft. deep, drains SE.
39.98	<p>Wash, 20 lks. wide, 3 ft. deep, drains SE.</p> <p>Point for the <math>\frac{1}{4}</math> sec. cor. of secs. 4 and 9.</p> <p>Set the iron post 24 ins. in the ground, with brass cap mkd.</p>
	<p style="text-align: center;">T3S R13W S 4 <math>\frac{1}{4}</math> ——— S 9 1961</p>

## Survey of the Subdivisions of T. 3 S., R. 13 W.

## Chains

- Raise a mound of stone, 3 ft. base,  $2\frac{1}{2}$  ft. high, N. of corner.
- 79.96 The cor. of secs. 4, 5, 8 and 9.
- Land, nearly level.  
Soil, gravel, sandy clay and loam.  
Timber, palo verde; undergrowth, cactus and greasewood.
- 
- N.  $0^{\circ}02'$  W., bet. secs. 4 and 5.
- Over nearly level land, through scattered timber and undergrowth.
- 19.50 Road, unimproved, bears S.  $80^{\circ}$  E., and N.  $80^{\circ}$  W.
- 21.00 Wash, 15 lks. wide, 2 ft. deep, drains E.
- 25.20 Wash, 50 lks. wide, 2 ft. deep, drains E.
- 40.00 Point for the  $\frac{1}{4}$  sec. cor. of secs. 4 and 5.
- Set the iron post 14 ins. in the ground to bedrock and in a mound of stone to top, with brass cap mkd.
- T3S R13W  
 $\frac{1}{4}$   
S 5 | S 4  
1961
- Raise a mound of stone, 3 ft. base,  $2\frac{1}{2}$  ft. high, W. of corner.
- 66.40 Wash, 60 lks. wide, 3 ft. deep, drains S.  $60^{\circ}$  E.
- 71.90 Wash, 40 lks. wide, 3 ft. deep, drains E.
- 80.36 Intersect the S. bdy. of sec. 32, T. 2 S., R. 13 W.
- Point for the closing cor. of secs. 4 and 5.
- Set the iron post 24 ins. in the ground, with brass cap mkd.
- T2S R13W  
S32  

---

S 5 | S 4  
T3S | R13W  
C C  
1961
- Raise a mound of stone, 4 ft. base,  $2\frac{1}{2}$  ft. high, S. of the corner.
- From this cor., the  $\frac{1}{4}$  sec. cor. on the S. bdy. of Sec. 32, T. 2 S., R. 13 W., bears S.  $89^{\circ}58'$  W., 15.00 chs. distant.
- Land, nearly level.  
Soil, gravel, sandy clay and loam.  
Timber, palo verde; undergrowth, cactus and greasewood.
- 
- The point for the N.  $\frac{1}{4}$  sec. cor. of sec. 4 is at midpoint and on the bdy. of the township.
- At the corner point
- Set the iron post 24 ins. in the ground, with brass cap mkd.

## Survey of the Subdivisions of T. 3 S., R. 13 W.

40.

Chains	<p style="text-align: center;">T2S R13W</p> <hr style="width: 20%; margin: auto;"/> <p style="text-align: center;">½ S 4 T3S R13W 1961</p> <p>Raise a mound of stone, 4 ft. base, 2½ ft. high, S. of corner.</p> <p>From this cor. the cor. of secs. 32 and 33 on the S. bdy. of T. 2 S., R. 13 W., bears S. 89°58' W., 15.00 chs. distant.</p>
	<p>From the cor. of secs. 5, 6, 31 and 32, on the S. bdy. of the township, monumented with an iron post, 3 ins. diam., set, mkd., and witnessed as described in the official record.</p> <p>N. 0°03' W., bet. secs. 31 and 32.</p> <p>Over rolling land, through scattered timber and undergrowth.</p> <p>2.00 Spur, slopes W.; desc. over rolling N. slope.</p> <p>15.45 Wash, 20 lks. wide, 2 ft. deep, drains N. 15° E.</p> <p>22.90 Wash, 20 lks. wide, 2 ft. deep, drains NE.</p> <p>24.20 Road, unimproved, bears E. and W.</p> <p>27.00 Wash, 15 lks. wide, 3 ft. deep, drains S. 75° E.</p> <p>40.00 Point for the ½ sec. cor. of secs. 31 and 32.</p> <p>Set the iron post 18 ins. in the ground to bedrock and in a mound of stone to top, with brass cap mkd.</p>
80.00	<p style="text-align: center;">T3S R13W</p> <p style="text-align: center;">½</p> <p style="text-align: center;">S31 S32 1961</p> <p>Raise a mound of stone, 3 ft. base, 2½ ft. high, W. of corner.</p> <p>Point for the cor. of secs. 29, 30, 31 and 32.</p> <p>Set the iron post 20 ins. in the ground to bedrock and in a mound of stone to top, with brass cap mkd.</p>
	<p style="text-align: center;">T3S R13W</p> <p style="text-align: center;">S30 S29</p> <hr style="width: 20%; margin: auto;"/> <p style="text-align: center;">S31 S32 1961</p> <p>Raise a mound of stone, 3½ ft. base, 2 ft. high, W. of corner.</p> <p>Land, nearly level..</p> <p>Soil, gravel, sandy clay and loam.</p> <p>Timber, palo verde; undergrowth, cactus and greasewood.</p>
	<p>From the cor. of secs. 28, 29, 32 and 33.</p> <p>N. 89°56' W., bet. secs. 29 and 32.</p> <p>Over rolling and broken land, through scattered timber and undergrowth.</p>

## Chains

- 19.30 Spur, slopes N.; desc. SE. slope.
- 37.10 Wash, 40 lks. wide, 3 ft. deep, drains S.
- 39.95 Point for the  $\frac{1}{4}$  sec. cor. of secs. 29 and 32.  
Set the iron post 24 ins. in the ground, with brass cap mkd.
- T3S R13W  
 $\frac{1}{4}$   $\frac{S\ 29}{S\ 32}$   
1961
- Raise a mound of stone,  $3\frac{1}{2}$  ft. base,  $2\frac{1}{2}$  ft. high, N. of corner.
- 49.10 Road, unimproved, bears SE. and NW.
- 59.90 Wash, 40 lks. wide, 4 ft. deep, drains N.  $80^\circ$  E.
- 70.50 Wash, 40 lks. wide, 4 ft. deep, drains S.  $80^\circ$  E.
- 79.90 The cor. of secs. 29, 30, 31 and 32.
- Land, rolling and broken.  
Soil, gravel, sandy clay and loam.  
Timber, palo verde; undergrowth, catclaw and cactus.
- 
- West, bet. secs. 30 and 31.  
Over gently rolling land, through scattered timber and undergrowth.
- 40.00 Point for the  $\frac{1}{4}$  sec. cor. of secs. 30 and 31.  
Set the iron post 24 ins. in the ground, with brass cap mkd.
- T3S R13W  
 $\frac{1}{4}$   $\frac{S\ 30}{S\ 31}$   
1961
- Raise a mound of stone, 3 ft. base,  $2\frac{1}{2}$  ft. high, N. of corner.
- 71.50 Spur, slopes N.
- 79.64 The cor. of secs. 25, 30, 31 and 36 on the W. bdy. of the township.
- Land, rolling and broken.  
Soil, gravel, sandy clay and loam.  
Timber, palo verde; undergrowth, cactus.
- 
- From the cor. of secs. 29, 30, 31 and 32.  
N.  $0^\circ 03'$  W., bet. secs. 29 and 30.  
Over rolling land, through scattered timber and undergrowth.
- 6.80 Wash, 1 chain wide, 4 ft. deep, drains E.
- 24.62 Road, unimproved, bears N.  $30^\circ$  W., and S.  $30^\circ$  E.
- 25.67 Wash, 40 lks. wide, 3 ft. deep, drains SE.
- 33.55 Wash, 40 lks. wide, 3 ft. deep, drains SE.
- 40.00 Point for the  $\frac{1}{4}$  sec. cor. of secs. 29 and 30.  
Set the iron post 18 ins. in the ground to bedrock and in a mound of stone to top, with brass cap mkd.
- T3S R13W  
 $\frac{1}{4}$   
S30|S29  
1961

Survey of the Subdivisions of T. 3 S., R. 13 W.

<p>Chains</p> <p>63.50</p> <p>80.00</p>	<p>Ascend over SW. slope.</p> <p>Ridge, bears E. and W.; desc. over rolling N. slope.</p> <p>Point for the cor. of secs. 19, 20, 29 and 30.</p> <p>Set the iron post 6 ins. in the ground to bedrock and in a mound of stone to top, with brass cap mkd.</p> <div style="text-align: center;"> <table border="0"> <tr><td colspan="2">T3S R13W</td></tr> <tr><td>S19</td><td>S20</td></tr> <tr><td>S30</td><td>S29</td></tr> <tr><td colspan="2">1961</td></tr> </table> </div> <p>Land, rolling and broken. Soil, gravel, sandy clay and loam. Timber, palo verde; undergrowth, cactus and greasewood.</p> <hr/> <p>From the cor. of secs. 20, 21, 28 and 29. N. 89°57' W., bet. secs. 20 and 29. Over rolling land, through scattered timber and undergrowth.</p> <p>13.20 Spur, slopes S.</p> <p>28.00 Wash, 20 lks. wide, 2 ft. deep, drains S.</p> <p>39.99 Point for the ¼ sec. cor. of secs. 20 and 29.</p> <p>Set the iron post 10 ins. in the ground to bedrock and in a mound of stone to top, with brass cap mkd.</p> <div style="text-align: center;"> <table border="0"> <tr><td colspan="2">T3S R13W</td></tr> <tr><td>¼</td><td>S 20</td></tr> <tr><td></td><td>S 29</td></tr> <tr><td colspan="2">1961</td></tr> </table> </div> <p>Raise a mound of stone, 3½ ft. base, 2½ ft. high, N. of corner.</p> <p>40.60 Wash, 40 lks. wide, 3 ft. deep, drains SE.</p> <p>48.90 Wash, 30 lks. wide, 3 ft. deep, drains N.; asc. SE. slope.</p> <p>61.80 Spur, slopes N.; descend.</p> <p>69.60 Wash, 20 lks. wide, 3 ft. deep, drains N.; thence asc. gradually over N. slope.</p> <p>79.98 The cor. of secs. 19, 20, 29 and 30.</p> <p>Land, rolling. Soil, gravel, sandy clay and loam. Timber, palo verde; undergrowth, cactus and catclaw.</p> <hr/> <p>N. 89°55' W., bet. secs. 19 and 30.</p> <p>Over rolling and broken land, through scattered timber and undergrowth.</p> <p>6.90 Base of spur, bears N. and S.; asc. over broken E. slope.</p> <p>14.75 Spur, slopes N.; descend.</p>	T3S R13W		S19	S20	S30	S29	1961		T3S R13W		¼	S 20		S 29	1961	
T3S R13W																	
S19	S20																
S30	S29																
1961																	
T3S R13W																	
¼	S 20																
	S 29																
1961																	

## Survey of the Subdivisions of T. 3 S., R. 13 W.

Chains	
26.35	Wash, 30 lks. wide, 2 ft. deep, drains S.
36.75	Wash, 20 lks. wide, 3 ft. deep, drains S.
40.00	Point for the $\frac{1}{4}$ sec. cor. of secs. 19 and 30.
	Set the iron post 10 ins. in the ground to bedrock and in a mound of stone to top, with brass cap mkd.
	T3S R13W $\frac{1}{4}$ $\frac{S 19}{S 30}$
48.90	Wash, 15 lks. wide, 2 ft. deep, drains SE.
56.25	Wash, 40 lks. wide, 3 ft. deep, drains S.
64.55	Wash, 30 lks. wide, 3 ft. deep, drains S.
79.65	The cor. of secs. 19, 24, 25 and 30 on the W. bdy. of the township.
	Land, rolling and broken. Soil, gravel, sandy clay and loam. Timber, palo verde; undergrowth, cactus.
	From the cor. of secs. 19, 20, 29 and 30.
	N. $0^{\circ}03'$ W., bet. secs. 19 and 20.
	Over rolling land, through scattered timber and undergrowth.
13.80	Wash, 40 lks. wide, 3 ft. deep, drains S. $80^{\circ}$ E.
19.30	Spur, slopes E.
27.20	Spur, slopes E.; desc. over N. slope.
40.00	Point for the $\frac{1}{4}$ sec. cor. of secs. 19 and 20.
	Set the iron post 24 ins. in the ground, with brass cap mkd.
	T3S R13W $\frac{1}{4}$ S19   S20 1961
	Raise a mound of stone, $3\frac{1}{2}$ ft. base, $2\frac{1}{2}$ ft. high, W. of corner.
	Ascend over rolling S. slope.
66.85	Ridge, bears E. and W.; desc. over N. slope.
80.00	Point for the cor. of secs. 17, 18, 19 and 20.
	Set the iron post 24 ins. in the ground, with brass cap mkd.
	T3S R13W S18   S17 S19   S20 1961
	Raise a mound of stone, 3 ft. base, $2\frac{1}{2}$ ft. high, W. of corner.

44

Survey of the Subdivisions of T. 3 S., R. 13 W.

Chains	
	<p>Land, rolling and broken. Soil, gravel, sandy clay and loam. Timber, palo verde; undergrowth, catclaw and cactus.</p>
	<p>From the cor. of secs. 16, 17, 20 and 21. N. 89°57' W., bet. secs. 17 and 20. Over gently rolling hills, through scattered timber and undergrowth.</p>
7.00	Wash, 40 lks. wide, 2 ft. deep, drains NE.
20.20	Wash, 40 lks. wide, 4 ft. deep, drains NE.
24.00	Low spur, slopes S.
36.00	Low spur, slopes S.
40.01	Point for the ¼ sec. cor. of secs. 17 and 20.  Set the iron post 8 ins. in the ground to bedrock and in a mound of stone to top, with brass cap mkd.
	<p>T3S R13W S 17 ¼ ——— S 20 1961</p>
41.40	Low spur, slopes N.; gradually descend.
47.90	Wash, 20 lks. wide, 3 ft. deep, drains N.
59.66	Road, unimproved, bears S. 10° E., and N. 10° W.
74.70	Wash, 20 lks. wide, 2 ft. deep, drains N.
80.02	The cor. of secs. 17, 18, 19 and 20.  Land, gently rolling. Soil, gravel, sandy clay and loam. Timber, palo verde; undergrowth, cactus and greasewood.
	<p>S. 89°59' W., bet. secs. 18 and 19. Over nearly level land, through scattered timber and undergrowth.</p>
32.50	Wash, 10 lks. wide, 2 ft. deep, drains N.
40.00	Point for the ¼ sec. cor. of secs. 18 and 19.  Set the iron post 8 ins. in the ground to bedrock and in a mound of stone to top, with brass cap mkd.
	<p>T3S R13W S 18 ¼ ——— S 19 1961</p>
41.20	Wash, 30 lks. wide, 2 ft. deep, drains S.
49.88	Low spur, slopes N.
75.84	Wash, 40 lks. wide, 4 ft. deep, drains SE.

## Chains

79.54

The cor. of secs. 13, 18, 19 and 24 on the W. bdy. of the township.

Land, gently rolling.

Soil, gravel, sandy clay and loam.

Timber, palo verde; undergrowth, cactus and catclaw.

---

From the cor. of secs. 17, 18, 19 and 20.

N. 0°03' W., bet. secs. 17 and 18.

Over rolling land, through scattered timber and undergrowth.

8.80

Road, unimproved, bears N. 80° W., and S. 80° E.

9.40

Wash, 30 lks. wide, 3 ft. deep, drains E.

18.75

Low spur, slopes E.

36.02

Wash, 30 lks. wide, 4 ft. deep, drains SE.

40.00

Point for the  $\frac{1}{2}$  sec. cor. of secs. 17 and 18.

Set the iron post 18 ins. in the ground to bedrock and in a mound of stone to top, with brass cap mkd.

T3S R13W

$\frac{1}{2}$

S18 | S17

1961

53.75

Wash, 20 lks. wide, 2 ft. deep, drains E.

62.70

Road, unimproved, bears E. and W.

80.00

Point for the cor. of secs. 7, 8, 17 and 18.

Set the iron post 18 ins. in the ground to bed rock and in a mound of stone to top, with brass cap mkd.

T3S R13W

S 7 | S 8

S18 | S17

1961

Raise a mound of stone, 3 ft. base, 2 ft. high, W. of corner.

Land, rolling.

Soil, gravel, sandy clay and loam.

Timber, palo verde; undergrowth, cactus.

---

From the cor. of secs. 8, 9, 16 and 17.

S. 89°59' W., bet. secs. 8 and 17.

Over nearly level land, through scattered timber and undergrowth.

11.40

Road, unimproved, bears N. and S.

39.99

Point for the  $\frac{1}{2}$  sec. cor. of secs. 8 and 17.

Set the iron post 25 ins. in the ground, with brass cap mkd.

Survey of the Subdivisions of T. 3 S., R. 13 W.

Chains	
	T3S R13W $\frac{1}{4} \frac{S 8}{S 17}$ 1961
	Raise a mound of stone, 3 ft. base, 2½ ft. high, N. of corner.
40.50	Road, unimproved, bears NW. and SE.
48.00	Base of spur; asc. NE. slope.
55.98	Top of spur, slopes NE.; descend.
60.40	Wash, 30 lks. wide, 4 ft. deep, drains NE.
64.80	Road, unimproved, bears NE. and SW.
76.60	Wash, 20 lks. wide, 10 ft. deep, drains N.
79.98	The cor. of secs. 7, 8, 17 and 18.
	Land, nearly level and rolling. Soil, gravel, sandy clay and loam. Timber, palo verde; undergrowth, cactus and catclaw.
<hr/>	
	N. 89°59' W., bet. secs. 7 and 18.
	Over gently rolling land, through scattered timber and undergrowth.
4.10	Wash, 20 lks. wide, 12 ft. deep, drains N.
17.00	Wash, 50 lks. wide, 12 ft. deep, drains N. 20° E.
24.90	Wash, 30 lks. wide, 10 ft. deep, drains N. 20° E.
37.90	Wash, 30 lks. wide, 12 ft. deep, drains N.
40.00	Point for the ¼ sec. cor. of secs. 7 and 18.
	Set the iron post 14 ins. in the ground to bedrock and in a mound of stone to top, with brass cap mkd.
	T3S R13W $\frac{1}{4} \frac{S 7}{S 18}$ 1961
	Raise a mound of stone, 4 ft. base, 2½ ft. high, N. of corner.
44.90	Wash, 50 lks. wide, 6 ft. deep, drains N.
68.20	Wash, 10 lks. wide, 4 ft. deep, drains N.
79.35	The cor. of secs. 7, 12, 13 and 18 on the W. bdy. of the township.
	Land, gently rolling. Soil, gravel, sandy clay and loam. Timber, palo verde; undergrowth, cactus and greasewood.
<hr/>	
	From the cor. of secs. 7, 8, 17 and 18.
	N. 0°03' W., bet. secs. 7 and 8.
	Over nearly level land, through scattered timber and undergrowth.

## Chains

4.70	Wash, 1 chain wide, 6 ft. deep, drains E.
29.30	Wash, 15 lks. wide, 2 ft. deep, drains NE.
40.00	Point for the $\frac{1}{4}$ sec. cor. of secs. 7 and 8. Set the iron post 24 ins. in the ground, with brass cap mkd.  T3S R13W $\frac{1}{4}$ S 7   S 8 1961  Raise a mound of stone, 3 ft. base, $2\frac{1}{2}$ ft. high, W. of corner.
80.00	Point for the cor. of secs. 5, 6, 7 and 8. Set the iron post 24 ins. in the ground, with brass cap mkd.  T3S R13W S 6   S 5 <hr/> S 7   S 8 1961  Raise a mound of stone, 3 ft. base, $2\frac{1}{2}$ ft. high, W. of corner.  Land, nearly level. Soil, gravel, sandy clay and loam. Timber, palo verde; undergrowth, cactus and catclaw.
	From the cor. of secs. 4, 5, 8 and 9. S. $89^{\circ}55'$ W., bet. secs. 5 and 8. Over nearly level land, through scattered timber and undergrowth.
21.30	Road, unimproved, bears SW. and NE.
39.20	Wash, 30 lks. wide, 3 ft. deep, drains SE.
39.95	Point for the $\frac{1}{4}$ sec. cor. of secs. 5 and 8. Set the iron post 24 ins. in the ground, with brass cap mkd.  T3S R13W $\frac{1}{4}$ S 5 S 8 1961  Raise a mound of stone, 3 ft. base, $2\frac{1}{2}$ ft. high, N. of corner.
79.90	The cor. of secs. 5, 6, 7 and 8.  Land, gently rolling. Soil, gravel, sandy clay and loam. Timber, palo verde; undergrowth, cactus and catclaw.
	N. $89^{\circ}53'$ W., bet. secs. 6 and 7. Over nearly level land, through scattered timber and undergrowth.
40.00	Point for the $\frac{1}{4}$ sec. cor. of secs. 6 and 7. Set the iron post 8 ins. in the ground to bedrock and in a mound of stone to top, with brass cap mkd.

Survey of the Subdivisions of T. 3 S., R. 13 W.

Chains

T3S R13W  
 $\frac{1}{4}$   $\frac{S 6}{S 7}$   
 1961

43.50 Wash, 10 lks. wide, 2 ft. deep, drains NE.

48.50 Wash, 10 lks. wide, 3 ft. deep, drains SE.

79.26 The cor. of secs. 1, 6, 7 and 12 on the W. bdy. of the township.

Land, nearly level.  
 Soil, gravel, sandy clay and loam.  
 Timber, palo verde; undergrowth, cactus and greasewood.

From the cor. of secs. 5, 6, 7 and 8.

N. 0°03' W., bet. secs. 5 and 6.

Over nearly level land, through scattered timber and undergrowth.

11.60 Wash, 10 lks. wide, 2 ft. deep, drains E.

21.40 Road, unimproved, bears NW. and S. 70° E.

39.90 Road, unimproved, bears NW. and SE.

40.00 Point for the  $\frac{1}{4}$  sec. cor. of secs. 5 and 6.

Set the iron post 24 ins. in the ground, with brass cap mkd.

T3S R13W  
 $\frac{1}{4}$   
 S 6 | S 5  
 1961

Raise a mound of stone, 3 ft. base, 2½ ft. high, W. of corner.

44.30 Wash, 20 lks. wide, 2 ft. deep, drains E.

56.00 Wash, 50 lks. wide, 2 ft. deep, drains E.

68.40 Wash, 30 lks. wide, 4 ft. deep, drains E.

80.29 Intersect the S. bdy. of sec. 31, T. 2 S., R. 13 W.

Point for the closing corner of secs. 5 and 6.

Set the iron post 24 ins. in the ground, with brass cap mkd.

T2S R13W  
 S 31  
 $\frac{S 6 | S 5}{C | C}$   
 T3S R13W  
 1961

Raise a mound of stone, 4 ft. base, 2½ ft. high, S. of corner.

From this cor., the  $\frac{1}{4}$  sec. cor. of sec. 31, on the S. bdy. of Township 2 S., R. 13 W., bears S. 89°58' W., 15.00 chains distant.

From this same cor., the cor. of secs. 31 and 32, T. 2 S., R. 13 W., bears N. 89°58' E., 25.00 chains distant.

## Chains

Land, nearly level.  
Soil, gravel, sandy clay and loam.  
Timber, palo verde; undergrowth, cactus.

The point for the N.  $\frac{1}{4}$  sec. cor. of sec. 5 is at midpoint and on the bdy. of the township.

At the corner point

Set the iron post 24 ins. in the ground, with brass cap mkd.

T2S R13W

$\frac{1}{4}$  S 5

T3S R13W

1961

Raise a mound of stone,  $3\frac{1}{2}$  ft. base,  $2\frac{1}{2}$  ft. high, S. of corner.

From this cor. the cor. of secs. 31 and 32 on the S. bdy. of T. 2 S., R. 13 W., bears S.  $89^{\circ}58'$  W., 15.00 chs. distant.

The point for the N.  $\frac{1}{4}$  sec. cor. of sec. 6 is 40.00 chs. in westing from the closing cor. of secs. 5 and 6, and on N. bdy. of Tp.

At the corner point

Set the iron post 24 ins. in the ground, with brass cap mkd.

T2S R13W

$\frac{1}{4}$  S 6

T3S R13W

1961

Raise a mound of stone, 4 ft. base,  $2\frac{1}{2}$  ft. high, S. of corner.

From this cor. the 1/16 cor of sec. 31, T. 2 S., R. 13 W., on the N. bdy. of the township bears S.  $89^{\circ}58'$  W., 15 chs. distant.

#### General Description

The land in the south portion of the township varies from nearly level to gently rolling, the central portion is heavily rolling mountainous, and the northern portion is gently rolling to nearly level on the northern boundary, which is adjacent to the Palomas Plains.

The soil is gravel, sandy clay and loam covered with loose stones. There are no springs or running water, or developments, or settlers, or cultivated land, in the township.

There is a scattered growth of timber (non-commercial), and undergrowth of desert vegetation over the township. There are no graded roads within the township and most travel in the area requires 4-wheel drive vehicles.



CERTIFICATE OF CADASTRAL ENGINEER

I, Horace G. Parker, HEREBY CERTIFY upon honor that, in pursuance of special instructions bearing date of the 30th day of July, 1959, I have surveyed the South Boundary of T. 2 S., R. 13 W.; the East and West Boundaries and the Subdivisional Lines of T. 3 S., R. 13 W.

of the Gila & Salt River Meridian, in the State of Arizona, which are represented in the foregoing field notes as having been executed by me and under my direction; and that said survey has been made in strict conformity with said instructions, the Manual of Instructions for the Survey of the Public Lands of the United States, and in the specific manner described in the foregoing field notes.

April 3, 1961  
~~February 28, 1961~~

Horace G. Parker  
Horace G. Parker  
Cadastral Surveyor

CERTIFICATE OF APPROVAL

BUREAU OF LAND MANAGEMENT,  
Washington, D. C., MAR 13 1963, 19

The foregoing field notes of the survey of the South Boundary of T. 2 S., R. 13 W.; the East and West Boundaries and the Subdivisional Lines of T. 3 S.; R. 13 W., Gila and Salt River Meridian, Arizona

executed by Horace G. Parker, Cadastral Surveyor, having been critically examined and found correct, are hereby approved.

[Signature]  
Cadastral Engineering Staff Officer,  
Chief, Division of Engineering

CERTIFICATE OF TRANSCRIPT

~~I CERTIFY that the foregoing transcript of the field notes of the above-described surveys in \_\_\_\_\_, is a true copy of the original field notes.~~

~~Cadastral Engineering Staff Officer.~~