

BOOK 4687
UNITED STATES
DEPARTMENT OF THE INTERIOR
BUREAU OF LAND MANAGEMENT

FIELD NOTES

SUBDIVISION

Section 11

Township 13 North, Range 2 West

Of the Gila and Salt River Meridian,

In the State of Arizona

EXECUTED BY

Leonard W. Murphy, Cadastral Surveyor

Under special instructions dated June 25, 19 62, which provided for the surveys included under Group Number 381, approved June 26, 1962, and assignment instructions dated June 26, 19 62.

Survey commenced July 16, 19 62

Survey completed July 18, 19 62

1A

BOOK 4680
INDEX DIAGRAM

Township 13 North, Range 2 West,

6	5	4	3	2	1
7	8	9	10	1 11 2	12
18	17	16	15	14	13
19	20	21	22	23	24
30	29	28	27	26	25
31	32	33	34	35	36

UNITED STATES
DEPARTMENT OF THE INTERIOR
BUREAU OF LAND MANAGEMENT

FIELD NOTE PAPER

1B

CHAINS

Section 11, T. 13 N., R. 2 W., Arizona

The boundaries of section 11, T. 13 N., R. 2 W., Gila and Salt River Meridian, Arizona, were surveyed in 1871 by O. H. Case and dependently resurveyed in 1930 by B. J. Kinsey.

The following field notes are those of the survey of the center lines of section 11, T. 13 N., R. 2 W., Gila and Salt River Meridian, Arizona.

The survey was executed in accordance with the specifications as set forth in the Manual of Surveying Instructions, 1947, and the Special Instructions dated June 25, 1962.

Only the true line bearings and horizontal distances for the surveyed lines are given in these notes.

The geographic position of the southeast corner of the section is: Latitude 34°30'45" North and Longitude 112°25'42" West.

The magnetic declination was found to be: 14½° East.

Subdivision, Section 11, T. 13 N., R. 2 W., Arizona

From the ¼ sec. cor. of secs. 11 and 14, monumented by and iron post, 1 inch diam., projecting 8 ins. above the ground, set, mkd., and witnessed as described in the official record.

N. 10°04' W., on the N. and S. center line of sec. 11.

Over rolling land, through sparse timber and dense undergrowth; desc. gentle N. slope.

3.80 Wash, 15 lks. wide, 2 ft. deep, drains W.; asc. S. slope.

11.60 Spur, projects W.

21.70 Spur, projects generally W.; desc. NW. slope.

41.16 Point for the center ¼ cor. of sec. 11.

Set an iron post 30 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.

T13NR2W

C ¼

S 11

1962

from which

A red cedar, 14 ins. diam., bears S. 25°40' E., 35 lks. dist., mkd. C ¼ S11 BT

A red cedar, 14 ins. diam., bears N. 44°30' W., 27 lks. dist., mkd. C ¼ S11 BT

CHAINS	
	The corner is set on a NW. slope.
47.86	Powerline, bears N. 30 W., and S. 30 E.
53.65	Road, graded, bears NW. and SE.
57.10	Small wash, drains NW.
61.20	Point for the Center North 1/16 cor. of sec. 11.
	Set an iron post 30 ins. long, 2½ ins. diam., 12 ins. in the ground to bedrock and in a mound of stone to top, with brass cap mkd.
	C - N 1/16 S 11 1962
	from which
	An oak tree, 10 ins. diam., bears N. 19°40' E., 120 lks. dist., mkd. S 11 C N 1/16 BT
	A pine tree, 8 ins. diam., bears N. 74°40' W., 25 lks. dist., mkd. S 11 C N 1/16 BT
	Corner set on slight NE. slope.
61.60	Wash, 25 lks. wide, 4 ft. deep, drains to NW.
62.30	Road, unimproved, bears approx. N. 80° W. for 1.00 chain then irregularly N.; enter dense pine trees and sparse undergrowth.
75.65	Small wash, drains N. 10°W.
78.40	Road, unimproved, bears irregularly E. and W.; enter dense brush.
79.90	Crest of small spur, projects SW.
81.24	The ¼ sec. cor. of secs. 2 and 11, monumented by an iron post 1 inch diam., set, mkd. and witnessed as described in the official record.
	Land, rolling. Soil, rocky. Timber, yellow pine, red cedar. Undergrowth, oak brush, manzanita and mahogany.
	From the ¼ sec. cor. of secs. 11 and 12, monumented by an iron post 1 inch diam., set, mkd. and witnessed as described in the official record. The cor. post is set in a wire fence which marks the Prescott National Forest Boundary line.
	S. 89°33' W., on the E. and W. centerline of sec. 11.
	Over rolling land, through dense undergrowth; desc. over W. slope.
7.80	Ravine, 15 lks. wide, drains to NW.; asc. E. slope.
16.00	Ridge, slopes to N.
17.20	Desc. over W. slope of ridge.
19.37	Point for the center east 1/16 cor. of sec. 11.

UNITED STATES
DEPARTMENT OF THE INTERIOR
BUREAU OF LAND MANAGEMENT

FIELD NOTE PAPER

3.

CHAINS

Subdivision, Sec. 11, T. 13 N., R. 2 W., Arizona

Set an iron post 30 ins. long, 2½ ins. diam., 10 ins. in the ground to bedrock and in a mound of stone, 3½ ft. base, to top, with brass cap mkd.

C - E 1/16
S 11
1962

Corner set on steep W. slope of ridge.

- 35.50 Slope changes to more gentle descent.
- 38.74 The center ¼ cor. of sec. 11.
- 47.54 Small wash, drains N. 10° W.
- 50.14 Small wash, drains irregularly NW.
- 52.64 Road, bladed and gravelled, bears approx. S. 20° W. and N. 20° E.
- 54.86 Point for the center west 1/16 cor. of sec. 11.
- Set an iron post, 30 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.

C - W
1/16
S 11
1962

- 57.30 Wash, 20 lks. wide, 2 ft. deep, drains NE.; asc. rocky SE. slope.
- 59.64 Fence, bears NW. and SE.
- 66.50 Fence, bears NE. and SW.
- 70.98 The ¼ sec. cor. of secs. 10 and 11, monumented by an iron post 1 inch diam., set, mkd. and witnessed as described in the official record.

Land, rolling.
Soil, rocky.
Timber, pine and scrub oak.
Undergrowth, oak brush, manzanita.

General Description

Section 11, Township 13 North, Range 2 West, Arizona, is located 2 miles south of Prescott, Arizona, and just east of the Senator Highway, which is paved beyond this area.

The southwest quarter of the section is patented land and has been intensely developed into home sites, most of which are now occupied. The rest of section 11 is easily accessible by many bladed roads which follow the numerous small canyons.

The entire section is covered with large yellow pines except for the ridge tops, which are covered with dense manzanita and oak brush.

CERTIFICATE OF SURVEY

I, Leonard W. Murphy, Cadastral Surveyor, HEREBY CERTIFY upon honor that, in pursuance of special instructions bearing date of the 25 day of June, 19 62, I have surveyed the subdivisions of section 11, Township 13 North, Range 2 West,

of the Gila and Salt River Meridian, in the State of Arizona, which are represented in the foregoing field notes as having been executed by me and under my direction; and that said survey has been made in strict conformity with said special instructions, the Manual of Instructions for the Survey of the Public Lands of the United States, and in specific manner described in the foregoing field notes.

July 24, 1962
(Date)

Leonard W. Murphy
(Cadastral Surveyor)

(Date)

(Cadastral Surveyor)

CERTIFICATE OF APPROVAL

Bureau of Land Management

The foregoing field notes of the survey of the subdivisions of section 11, Township 13 North, Range 2 West, Gila and Salt River Meridian, Arizona,

executed by Leonard W. Murphy, Cadastral Surveyor, having been critically examined and found correct, are hereby approved.

Washington, D.C.

DEC 27 1963

(Date)

Clark I. Gumm
Acting (Chief, Division of Engineering)

CERTIFICATE OF TRANSCRIPT

I CERTIFY That the foregoing transcript of the field notes of the above-described surveys in _____ is a true copy of the original field notes.

(Date)

(Chief, Division of Engineering)