

BOOK 4095

Form 4-679
(January 1963)

UNITED STATES
DEPARTMENT OF THE INTERIOR
BUREAU OF LAND MANAGEMENT

FIELD NOTES

INDEPENDENT RESURVEY

_____ of a _____

_____ Portion _____

_____ of the _____

_____ First Standard Parallel North _____

_____ SURVEY _____

_____ of _____

_____ Sections 29, 30, 31 and 32 _____

_____ Township 5 North, Range 7 East _____

Of the _____ Gila and Salt River _____ Meridian,

In the State of _____ Arizona _____.

EXECUTED BY

_____ Leonard W. Murphy, Cadastral Surveyor _____

Under special instructions dated _____ October 22 _____, 19 62 _____, which provided for the surveys

included under Group Number _____ 385 _____, approved _____ October 23, 1962 _____,

and assignment instructions dated _____ November 29 _____, 19 62 _____.

Survey commenced _____ January 25 _____, 19 63 _____

Survey completed _____ February 1 _____, 19 63 _____

Doc 4605
INDEX DIAGRAM

Township 5 North, Range 7 East,

6	5	4	3	2	1
7	8	9	10	11	12
18	17	16	15	14	13
19	20	21	22	23	24
9	9				
30 8	29 4	28	27	26	25
7	6				
31 5	32 3	33	34	35	36
1	2				

UNITED STATES
DEPARTMENT OF THE INTERIOR
BUREAU OF LAND MANAGEMENT

FIELD NOTE PAPER

16

CHAINS

Township 5 North, Range 7 East, G&SRM, Arizona

The south boundary, the First Standard Parallel North, was surveyed in 1867 by W. H. Pierce and the east $2\frac{1}{2}$ miles were resurveyed in 1878 by W. A. Hancock. Homestead Entry Survey No. 512 was surveyed in 1917 by R.P.A. Johnson, Forest Service. The west boundary is concurrently being surveyed under Group No. 383, Arizona.

These notes are those of an independent resurvey of a portion of the south boundary and a survey of sections 29, 30, 31 and 32, Township 5 North, Range 7 East.

Only the true line bearings and horizontal distances for the surveyed lines are given in these notes. Unless described, each corner was monumented with a standard iron post 30 inches long, $2\frac{1}{2}$ inches in diameter, flanged at the base and with a brass cap riveted to the top.

The survey was executed in accordance with the specifications as set forth in the Manual of Surveying Instructions, 1947, and the Special Instructions dated October 22, 1962.

The direction of all lines were determined by sustained angulation from ties made to the U.S. Coast and Geodetic Triangulation Station MOOREN located in the NE $\frac{1}{2}$ of section 31, and substantiated by direct observations on the sun for azimuth.

The geographic position of the southwest corner of section 31 is: Latitude $33^{\circ}43'37.45''$ North, and Longitude $111^{\circ}40'55.44''$ West as determined by computation from Coast and Geodetic Survey Triangulation Station MOOREN.

The magnetic declination was found to be: $14\frac{1}{2}^{\circ}$ E.

First Stan. Par. N., T. 5 N., R. 7 E.

Independent Resurvey of a Portion of the
First Standard Parallel North

Beginning at the standard corner of Ts. 5 N., Rs. 6 and 7 E., which is monumented with an iron post 3 ins. in diameter, firmly set, properly marked, and witnessed as described in the official record.

East on the S. bdy. of sec. 31, T. 5 N., R. 7 E.

Over gently rolling land, through scattered timber.

3.00 Road, unimproved, bears S. 45° E. and N. 45° W.

19.80 Wash, 40 lks. wide, drains N. 40° E.

40.00 Point for the standard $\frac{1}{4}$ cor. of sec. 31.

Set the post 24 inches in the ground, cap mkd.

2

CHAINS

SC
T5N R7E
 $\frac{1}{4}$ S31

1963

Raise a mound of stone, 3 ft. base, 2 ft. high, N. of iron post. No evidence of the original was found.

- 43.10 Wash, 10 lks. wide, drains N. 80° E.
- 49.80 Road, graded, bears N. and S.; from gauging station to Ft. McDowell.
- 55.40 Same wash described above, drains S. 80° E.
- 66.50 Cross same wash again, drains N. 80° E.
- 78.50 Small wash, 20 lks. wide, drains N. 60° E.
- 80.00 Point for the standard cor. of secs. 31 and 32.
- Set the iron post 24 ins. in the ground, cap mkd.

SC
T5N R7E
S31|S32

1963

Raise a mound of stone, 3 ft. base, 2 ft. high, N. of iron post. No evidence of the original cor. was found.

Land, gently rolling.
Soil, sandy and stony.
Timber, palo verde, mesquite and ironwood.
Undergrowth, greasewood and catclaw.

-
- East, on the S. bdy. of sec. 32.
- Over nearly level land, through scattered timber.
- 2.70 Road, graded, bears N. and S.
- 13.80 Road, bladed only, bears N. 45° E. and S. 45° W.
- 40.00 Point for the standard $\frac{1}{4}$ cor. of sec. 32.
- Set the iron post 24 ins. in the ground, cap mkd.

SC
T5N R7E
 $\frac{1}{4}$ S32

1963

Raise a mound of stone, 3 ft. base, 2 ft. high, N. of post. No evidence of the original cor. was found.

- 42.90 Road, unimproved, bears N. and S.
- 47.60 Fence, barbed wire, bears N. and S.
- 47.70 Point selected for the witness cor. for the meander cor. of sec. 32.
- Set the post 24 ins. in the ground, cap mkd.

T5N
R7E
S32 / WC

S 5
1963

UNITED STATES
DEPARTMENT OF THE INTERIOR
BUREAU OF LAND MANAGEMENT

FIELD NOTE PAPER

CHAINS	
	Desc. steep bank, approximately 30 ft. high.
49.70	Right bank of the Verde River, bearing N. 10°50' W., and S. 7°36' E.; on steep bank where a monument cannot be maintained.
54.00	Left bank of the Verde River, bearing N. 8°31' W. and S. 9°49' E.
	Point for the meander cor. of sec. 32.
	Set the post 24 ins. in the ground, cap mkd.
	<div style="text-align: center;"> T5N R7E MC <u>S32</u> <u>S 5</u> 1963 </div>
	Bank approximately 7 ft. high; thence over level, sandy bottom land.
63.80	Leave river bottom land; asc. W. slope.
75.00	Wash, 40 lks. wide, 3 ft. deep, drains S. 15° W. for 2 chs., then W.; asc. gentle W. slope.
80.00	Point for the standard cor. of secs. 32 and 33.
	Set the post 24 ins. in the ground, cap mkd.
	<div style="text-align: center;"> SC T5N R7E <u>S32</u> <u>S33</u> 1963 </div>
	Raise a mound of stone, 3½ ft. base, 3 ft. high, N. of post; falls on gentle W. slope. No evidence of the original cor. was found.
	Land, nearly level W. ½ mile; gently rolling E. ½.
	Soil, sandy and stony.
	Timber, palo verde, mesquite and cottonwood along river bank.
	Undergrowth, salt cedar along river bank.
	Portion of the Subdivisional Lines, T. 5 N., R. 7 E.
	From the standard cor. of secs. 32 and 33, on the S. bdy. of the township.
	N. 0°02' W., bet. secs. 32 and 33.
	Over rolling hills, through scattered timber and undergrowth.
4.20	Wash, 40 lks. wide, 3 ft. deep, drains S. 15° W.; asc. S. slope.
14.40	Ridge, bears E. and W.; desc. N. slope.
17.90	Wash, 60 lks. wide, 3 ft. deep, drains S. 80° W.; asc. S. slope.

CHAINS		
26.50	Spur, slopes W.; desc. N. slope.	
33.20	Wash, 40 lks. wide, 5 ft. deep, drains W.	
37.45	Low spur, slopes S. 45° W.; desc. NW. slope.	
40.00	Point for the ½ sec. cor. of secs. 32 and 33.	
	Set the post 8 ins. in the ground to bedrock, mound with stone to top, cap mkd.	
	T5N R7E ½ S32 S33 1963	
	Cor. falls on gentle NW. slope.	
40.20	Asc. S. slope.	
45.90	Ridge, bears N. 80° E. and S. 80° W.; desc. E. slope.	
63.50	Wash, 30 lks. wide, 3 ft. deep, drains S. 85° W.; asc. S. slope.	
75.70	Ridge, bears N. 45° E. and S. 45° W.; desc. NW. slope.	
80.00	Point for the cor. of secs. 28, 29, 32 and 33.	
	Set the post 18 ins. in the ground to bedrock, mound with stone to top, cap mkd.	
	T5N R7E S29 S28 S32 S33 1963	
	Raise a mound of stone, 3 ft. base, 2½ ft. high, W. of post; cor. falls on NW. slope.	
	Land, rolling. Soil, weathered sandstone. Timber, palo verde and mesquite. Undergrowth, cactus and catclaw.	
	N. 0°02' W., bet. secs. 28 and 29.	
	Over rolling hills, through scattered timber and undergrowth.	
	Desc. NW. slope.	
13.30	Wash, 40 lks. wide, 5 ft. deep, drains S. 80° W.; asc. S. slope.	
23.00	Road, unimproved, bears E. and W.	
31.60	Desc. steep NW. slope.	
34.60	S. bank of wash, bears E. and W.	
38.10	N. bank of the wash; asc. gentle S. slope.	
40.00	Point for the ½ sec. cor. of secs. 28 and 29.	
	Set the post 24 ins. in the ground, cap mkd.	
	T5N R7E ½ S29 S28 1963	

UNITED STATES
DEPARTMENT OF THE INTERIOR
BUREAU OF LAND MANAGEMENT

FIELD NOTE PAPER

CHAINS									
	Portion, Subdivisions, T. 5N., R. 7E., Arizona								
	Raise a mound of stone, 3½ ft. base, 2 ft. high, W. of post; cor. falls on gentle S. Slope.								
46.80	Ridge top, bears E. and W.; desc. NW. slope.								
59.30	Center of wash area, 8 chs. wide, drains S. 75° W.								
63.40	Asc. SE. slope.								
78.30	Mesa top; thence over mesa.								
80.00	Point for the cor. of secs. 20, 21, 28 and 29.								
	Set the post 18 ins. in the ground to bedrock, mound with stone to top, cap mkd.								
	<table style="margin-left: auto; margin-right: auto;"> <tr> <td colspan="2">T5N R7E</td> </tr> <tr> <td style="border-right: 1px solid black;">S20</td> <td>S21</td> </tr> <tr> <td style="border-right: 1px solid black;">S29</td> <td>S28</td> </tr> <tr> <td colspan="2" style="text-align: center;">1963</td> </tr> </table>	T5N R7E		S20	S21	S29	S28	1963	
T5N R7E									
S20	S21								
S29	S28								
1963									
	Raise a mound of stone, 3½ ft. base, 2½ ft. high, W. of post.								
	Land, rolling Soil, sandstone gravel. Timber, mesquite and palo verde. Undergrowth, catclaw, cactus and sage.								
	From the standard cor. of secs. 31 and 32 on the S. bdy. of the township.								
	N. 0°03' W., bet. secs. 31 and 32.								
	Over nearly level land, through medium dense timber.								
3.90	Wash, 30 lks. wide, 2 ft. deep, drains N. 80° E.								
7.80	Road, graded, bears generally N. and S.								
11.50	Same road, bears N. and S.								
15.00	Wash, 30 lks. wide, 2 ft. deep, drains N. 80° E.								
16.70	Cross same road, bears N. and S.								
25.40	Fence, barbed wire, bears N. 5° W. and S. 5° E.								
29.33	Intersect line 1 - 2 of HES. No. 512 at a point from which Cor. No. 1 bears S. 4° 54' E., 5.64 chs. dist.								
40.00	Point for the ¼ cor. of secs. 31 and 32								
	Set the post 24 ins. in the ground, cap mkd.								
	<table style="margin-left: auto; margin-right: auto;"> <tr> <td colspan="2">T5N R7E</td> </tr> <tr> <td colspan="2" style="text-align: center;">¼</td> </tr> <tr> <td style="border-right: 1px solid black;">S31</td> <td>S32</td> </tr> <tr> <td colspan="2" style="text-align: center;">1963</td> </tr> </table>	T5N R7E		¼		S31	S32	1963	
T5N R7E									
¼									
S31	S32								
1963									
	from which								
	Cor.No.1 of Homestead Entry No. 512 bears S. 1°43' E., 16.30 chs. dist., monumented with a granite stone, 20 x 6 x 3 ins., marked with a cross (x) HES 512 on NE. face, firmly set and witnessed as described in the official record.								

CHAINS

54.90 Wash, 40 lks. wide, 1 ft. deep, drains S. 80° E.

63.50 Fence, barbed wire, bears E. and W.

63.80 Fence, Barbed wire, bears E. and W.

77.80 Graded road, bears W. and E. to ranch house.

80.00 Point for the cor. of secs. 29, 30, 31 and 32.

Set the post 24 ins. in the ground, cap mkd.

T5N R7E	
S30	S29
S31	S32
1963	

from which

A mesquite, 10 ins. in diam., bears S. 76° W., 53 lks. dist., mkd. S 31 BT.

A mesquite, 10 ins. in diam., bears N. 68° W., 31 lks. dist., mkd. S 30 BT.

U.S. Coast and Geodetic Survey triangulation station MOOREN bears S. 74°53' W., 17.13 chs. dist.

Cor. No. 2 of Homestead Entry No. 512 bears N. 47°03' W., 6.38 chs. dist., monumented with a lava stone, 20 x 10 x 10 ins., firmly set, and mkd. with a cross (x) 2 HES 512 on SE. face. Bearing trees as described in the official record.

Land, nearly level.

Soil, sandy and gravelly clay loam.

Timber, mesquite and palo verde.

Undergrowth, catclaw, black brush and cactus.

From the cor. of secs. 28, 29, 32 and 33.

S. 89°59' W., bet. secs. 29 and 32.

Over rolling land, through scattered timber and undergrowth.

Desc. gentle NW. slope.

17.50 Wash, 40 lks. wide, 2 ft. deep, drains S. 15° W.; thence along SW. slope.

25.90 Fence, barbed wire, bears N. and S.; thence over nearly level land, through dense timber and undergrowth.

40.01 Point for the $\frac{1}{4}$ sec. cor. of secs. 29 and 32.

Set the post 24 ins. in the ground, cap mkd.

T5N R7E	
$\frac{1}{4}$ S	29
	S 32
1963	

Raise a mound of stone $3\frac{1}{2}$ ft. base, 2 ft. high, N. of post.


42.15 Unimproved road, bears N. 45° E. and S. 45° W.

49.50 Left bank of the Verde River, 6 ft. high, bears N. 37°19' W. and S. 17°12' E.

BOOK 4695
UNITED STATES
DEPARTMENT OF THE INTERIOR
BUREAU OF LAND MANAGEMENT

FIELD NOTE PAPER

CHAINS	
	Portion, Subdivisions, T. 5 N., R. 7 E., Arizona
	Point for the meander cor. of secs. 29 and 32. Set the post 24 ins. in the ground, cap mkd.
	T5N R7E S29 MC \ S32 1963
52.40	Right bank of the Verde River bearing N. 33°28' W. and S. 19°47' E.
	Point for the meander cor. of secs. 29 and 32. Set the post 20 ins. in the ground, cap. mkd.
	T5N R7E S29 \ MC S32 1963
55.74	Intersect line 3 - 4 of H. E. S. No. 512 at a point from which cor. No. 3 bears N. 17°35' W. 9.15 chs. dist.
80.02	The cor. of secs. 29, 30, 31 and 32.. Land, rolling E. ½ mile; nearly level W. ½ mile. Soil, sandy. Timber, mesquite and palo verde. Undergrowth, salt cedar along river bank, and cactus.
	West, bet. secs. 30 and 31. Over nearly level land, through medium dense timber.
4.30	Intersect line 1 - 2 of H. E. S. No. 512 at a point from which cor. No. 2 bears N. 4°54' W., 4.36 chs. dist.
5.60	Fence, barbed wire, bears N. and S.
7.70	Earthen dike, bears N. 20° E. and S. 20° W.
16.30	Graded road, bears N. and S.
30.40	Graded road, Fort McDowell to U.S.G.S. gaging station, bears N. and S.
40.01	Point for the ¼ cor. of secs. 30 and 31. Set the iron post 24 ins. in the ground, cap. mkd.
	T5N R7E ¼ S30 S31 1963
	Raise a mound of stone, 3 ft. base, 2 ft. high, N. of post.
49.50	Graded road, leads to Pinnacle Peak, bears N. 80° W. and S. 80° E.
68.50	Same road, bears S. 75° W. and N. 75° E.
80.02	The cor. of secs. 25, 30, 31 and 36, on the W. bdy. of the township, described in the field notes of T. 5 N., R. 6 E.

CHAINS	
	<p>Land, nearly level. Soil, sandy and gravelly clay loam. Timber, palo verde and mesquite. Undergrowth, cactus, chaparral and ocotillo.</p> <hr/> <p>From the cor. of secs. 29, 30, 31 and 32. N. 0°03' W., bet. secs. 29 and 30. Over nearly level land, through dense undergrowth.</p>
4.30	Fence, barbed wire, bears E. and W.
5.13	Intersect line 2-3 of H.E.S. No. 512 at a point from which Cor. No. 2 bears S. 80°30' W., 4.73 chs. dist.
5.20	Wash, 30 lks. wide, 3 ft. deep, drains E.
22.30	Wash, 40 lks. wide, 6 ft. deep, drains E.
40.00	Point for the ¼ cor. of secs. 29 and 30. Set the iron post 24 ins. in the ground, cap mkd. <div style="text-align: center;"> T5N R7E ¼ S30 S29 1963 </div>
47.40	<p>Raise a mound of stone, 3½ ft. base, 2 ft. high, W. of iron post.</p> <p>Right bank of the Verde River, bears N. 76°27' W. and S. 59°52' E. Point for the meander cor. of secs. 29 and 30. Set the post 24 ins. in the ground, cap. mkd. <div style="text-align: center;"> MC  </div> </p>
49.90	<p>Left bank of the Verde River, bears N. 70°44' W. and S. 51°50' E. Point for the meander cor. of secs. 29 and 30. Set the post 22 ins. in the ground, cap mkd. <div style="text-align: center;"> T5N R7E S30 S29 MC 1963 </div> </p>
80.00	<p>Point for the cor. of secs. 19, 20, 29 and 30. Set the post 24 ins. in the ground, cap mkd. <div style="text-align: center;"> T5N R7E S19 S20 S30 S29 1963 </div> <p>from which A mesquite, 10 ins. diam., bears N. 15° E., 105 lks. dist., mkd. S 20 BT. A cottonwood, 24 ins. diam., bears S. 36° W. 73 lks. dist., mkd. T5N R7E S30 BT.</p> </p>


UNITED STATES
DEPARTMENT OF THE INTERIOR
BUREAU OF LAND MANAGEMENT

FIELD NOTE PAPER

CHAINS	
	Portion, Subdivisions, T. 5 N., R. 7 E., Arizona
	<p>Land, nearly level. Soil, sandy and stony. Timber, mesquite and cottonwood. Undergrowth, salt cedar and creosote bush.</p>
	<p>From the cor. of secs. 20, 21, 28 and 29.</p> <p>S. 89°59' W., bet. secs. 20 and 29.</p> <p>Over rolling hills, through scattered timber.</p>
9.25	Spur, slopes SW.; desc. NW. slope.
11.25	Wash, 30 lks. wide, 3 ft. deep, drains S. 45° W.; asc. SE. slope.
21.10	Crest of low spur, slopes SW.; desc. W. slope.
31.50	End desc.; over nearly level land, through dense undergrowth.
40.01	Point for the ¼ cor. of secs. 20 and 29.
	Set the post 24 ins. in the ground, cap mkd.
	<p>T5N R7E ¼ $\frac{S\ 20}{S\ 29}$ 1963</p>
80.02	The cor. of secs. 19, 20, 29 and 30.
	<p>Land, nearly level W. ½ mile. Soil, sandy and stony. Timber, palo verde, mesquite and cottonwood. Undergrowth, cactus, catclaw and salt cedar.</p>
	<p>West, bet. secs. 19 and 30.</p> <p>Over nearly level land.</p>
40.00	Point for the ¼ sec. cor. of secs. 19 and 30.
	Set the post 24 ins. in the ground, cap mkd.
	<p>T5N R7E ¼ $\frac{S\ 19}{S\ 30}$ 1963</p>
	Raise a mound of stone, 3½ ft. base, 2 ft. high, N. of post.
40.20	Left bank of the Verde River, bears N. and S. 24°54' E.
	Point for the meander cor. of secs. 19 and 30.
	Set the post 24 ins. in the ground with cap mkd.

CHAINS

T5N R7E



1963


42.30

The right bank of the Verde River, bearing N. and S. 35°46' E.; on steep bank where a monument cannot be maintained.

43.40

Point selected for the witness meander cor. of secs. 19 and 30.

Set the post 24 ins. in the ground, cap mkd.



Cor. set on high bank in dense undergrowth; asc. E. slope.

46.70

Small spur, slopes NE.; over series of erosion cuts.

57.50

Wash, 60 lks. wide, drains N. 80° E.

71.30

Graded road, Fort McDowell to U.S.G.S. gaging station, bears N. 35° W. and S. 35° E.

80.00

The cor. of secs. 19, 24, 25 and 30, on the W. bdy. of the township, described in field notes of T. 5 N., R. 6 E.

Land, nearly level.
Soil, sandy and gravelly clay loam.
Timber, palo verde and mesquite.
Undergrowth, cactus, chaparral and ocotillo.

Meanders of the Left Bank of the Verde River in Sections 29, 30 and 32, T. 5 N., R. 7 E.

From the meander cor. of secs. 19 and 30, along a well defined bank, 4 to 6 ft. high, through dense salt cedar.

Thence downstream with the meanders of the left bank of the Verde River in sec. 30.

S. 24°54' E., 6.38 chs.

S. 51°40' E., 4.94 chs.

S. 53°28' E., 6.00 chs.

S. 51°08' E., 19.45 chs.

S. 60°18' E., 3.54 chs.

S. 70°44' E., 11.24 chs. The meander cor. of secs. 29 and 30.

Land, nearly level.
Soil, silt and sandy clay.
Timber, none; undergrowth, salt cedar.

UNITED STATES
DEPARTMENT OF THE INTERIOR
BUREAU OF LAND MANAGEMENT

FIELD NOTE PAPER

11.

CHAINS

Meanders, Left Bank, Verde River,
T. 5 N., R. 7 E., Arizona

Thence in sec. 29

S. 51°50' E., 15.00 chs.

S. 32°30' E., 9.16 chs.

S. 32°04' E., 10.22 chs.

S. 16°28' E., 5.96 chs.

S. 11°30' E., 13.49 chs.

S. 37°19' E., 6.65 chs. The M.C. of secs. 29 and 32.

Land, nearly level.

Soil, silt and sandy clay.

Timber, cottonwood.

Undergrowth, salt cedar.

Thence in sec. 32

Continue through dense undergrowth, bank 4 ft. high.

S. 17°12' E., 11.20 chs.

S. 37°45' E., 10.06 chs.

S. 54°53' E., 13.34 chs.

S. 55°52' E., 7.47 chs.

S. 24°30' E., 3.26 chs.

S. 8°04' W., 21.93 chs..

S. 11°22' W., 14.76 chs.

S. 8°31' E., 10.45 chs. The meander cor. of secs. 5
and 32 on the S. bdy. of the township.

Land, level bottom.

Soil, sandy loam.

Timber, cottonwood.

Undergrowth, salt cedar.

Meanders, Right Bank, Verde River,
T. 5 N., R. 7 E., ArizonaFrom the true point for the meander cor. of secs. 19
and 30, along a well defined bank, through dense salt
cedar.Thence downstream with the meanders of the Verde River
in sec. 30.

S. 35°46' E., 12.25 chs.

S. 49°38' E., 10.68 chs.

S. 50°28' E., 10.43 chs.

12

CHAINS

S. 54°15' E., 11.77 chs.

S. 76°47' E., 9.68 chs., the meander cor. of secs. 29 and 30.

Land, nearly level.
Soil, silt and sandy clay.
Timber, cottonwood.
Undergrowth, salt cedar.

Thence in sec. 29.

S. 59°52" E., 8.30 chs.

S. 33°47' E., 11.45 chs.

S. 36°35' E., 5.90 chs.

S. 18°21' E., 5.71 chs.

S. 9°47' E., 9.24 chs.

S. 11°37' E., 5.46 chs.

S. 33°28' E., 11.00 chs., the meander cor. of secs. 29 and 32.

Land, nearly level.
Soil, silt and sandy clay.
Timber, cottonwood.
Undergrowth, salt cedar.

Thence in sec. 32.

S. 19°47' E., 11.12 chs.

S. 37°25' E., 9.78 chs.

S. 33°37' E., 2.74 chs.

S. 47°11' E., 5.59 chs.

S. 64°40' E., 7.18 chs.

S. 35°21' E., 12.86 chs.

S. 7°00' W., 11.60 chs.

S. 15°58' W., 25.21 chs.

S. 10°50' E., 6.49 chs. the meander cor. of secs. 5 and 32 on the S. bdy. of the township.

Land, level bottom.
Soil, sandy loam.
Timber, cottonwood.
Undergrowth, salt cedar.

General Description

The area covered by these field notes lies adjacent to the Verde River 7 miles from Fort McDowell. The portion west of the river is nearly level and the portion east of the river is rough and stony. The soil of the bottom land along the Verde River is an alluvial silt and loam. There are both cottonwood and tamarisk along the river bank.

UNITED STATES
DEPARTMENT OF THE INTERIOR
BUREAU OF LAND MANAGEMENT

FIELD NOTE PAPER

CHAINS

Township 5 North, Range 7 East, G&SRM, Arizona

The Verde River crosses through sections 29, 30 and 32; it is a meanderable stream, under surveying rules, but there is no navigation on the river.

There are numerous jeep roads in this portion of the township but only one road maintained by grader, which is the Fort McDowell-Gaging Station Road.

Homestead Entry No. 512 lies principally in section 32. It is the only settlement and at present there are no other important improvements. There is no commercial timber and the land is being used for grazing only.

CHAINS

CERTIFICATE OF SURVEY

I, Leonard W. Murphy, HEREBY CERTIFY upon honor that,
in pursuance of special instructions bearing date of the 22nd day of October, 1962,
I have independently resurveyed a portion of the First Standard
Parallel North and surveyed sections 29, 30, 31 and 32, Township 5 North,
Range 7 East

of the Gila and Salt River Meridian, in the State of Arizona, which
are represented in the foregoing field notes as having been executed by me and under my direction;
and that said survey has been made in strict conformity with said special instructions, the Manual
of Instructions for the Survey of the Public Lands of the United States, and in specific manner
described in the foregoing field notes.

February 22, 1963
(Date)

Leonard W. Murphy
(Cadastral Surveyor)
Leonard W. Murphy

(Date)

(Cadastral Surveyor)

CERTIFICATE OF APPROVAL
Bureau of Land Management

The foregoing field notes of the independent resurvey of a portion of the
First Standard Parallel North and surveyed sections 29, 30, 31 and 32,
Township 5 North, Range 7 East, Gila and Salt River Meridian, Arizona,

executed by Leonard W. Murphy

having been critically examined and found correct, are hereby approved.

Washington, D. C.

APR 7 1964
(Date)

E. E. Remington
(Chief, Division of Engineering)

CERTIFICATE OF TRANSCRIPT

I CERTIFY That the foregoing transcript of the field notes of the above-described surveys in
is a true copy of the original field notes.

(Date)

(Chief, Division of Engineering)